

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250266833

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Veskovic; Dragan

---

## LOAD CONTROL DEVICE HAVING A CAPACITIVE TOUCH SURFACE

---

### Abstract

A control device configured for use in a load control system to control one or more electrical loads external to the control device may include an antenna and an actuation member having a front surface defining a touch sensitive surface configured to detect a touch actuation along at least a portion of the front surface. The control device may include a main printed circuit board (PCB) comprising a control circuit, an antenna PCB connected to the main PCB, a tactile switch(es), a controllably conductive device, and a drive circuit operatively coupled to a control input of the controllably conductive device for rendering the controllably conductive device conductive or non-conductive to control the amount of power delivered to the electrical load. The antenna may extend substantially perpendicular from the main PCB through an opening in the yoke and into a cavity defined by the actuation member and the yoke.

---

**Inventors:** Veskovic; Dragan (Allentown, PA)

**Applicant:** Lutron Technology Company LLC (Coopersburg, PA)

**Family ID:** 1000008578261

**Assignee:** Lutron Technology Company LLC (Coopersburg, PA)

**Appl. No.:** 19/199997

**Filed:** May 06, 2025

### Related U.S. Application Data

parent US continuation 18374793 20230929 parent-grant-document US 12301226 child US 19199997

parent US continuation 17508103 20211022 parent-grant-document US 11817856 child US 18374793

us-provisional-application US 63104321 20201022

---

## Publication Classification

**Int. Cl.:** **H03K17/96** (20060101); **H01H3/02** (20060101); **H01H23/14** (20060101); **H05B39/08** (20060101)

**U.S. Cl.:**

**CPC** **H03K17/962** (20130101); **H01H3/02** (20130101); **H01H23/145** (20130101); **H05B39/085** (20130101); H01H2003/0293 (20130101); H01H2215/00 (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This is a continuation of Non-Provisional U.S. patent application Ser. No. 18/374,793, filed Sep. 29, 2023, which is a continuation of Non-Provisional U.S. patent application Ser. No. 17/508, 103, filed Oct. 22, 2021, which claims the benefit of Provisional U.S. Patent Application No. 63/104,321, filed Oct. 22, 2020, the disclosure of which is incorporated herein by reference in its entirety.

### BACKGROUND

[0002] A load control system may include one or more electrical loads that a user may wish to control via a single load control device. These electrical loads may include, for example, lighting loads, HVAC units, motorized window treatment or projection screens, humidity control units, audio systems or amplifiers, Internet of Things (IoT) devices, and/or the like. The electrical loads may have advanced features. For example, a lighting load may be controlled to emit light of varying intensities and/or colors in response to a user command. The amount of power delivered to the electrical loads may be adjusted to an absolute level or by a relative amount. Multiple electrical loads may be manipulated such that one or more presets or scenes (e.g., combinations of particular lighting conditions, temperature settings, speaker volume, and/or the like) may be created, and a user may desire the ability to browse through the presets or scenes, and activate one that fits a particular occasion. With a traditional load control device such as a mechanical toggle switch, a user will not be able to perform any of the aforementioned functions, let alone performing multiple of them through one device.

[0003] The insufficiencies of traditional load control devices arise at least in part from the actuation mechanism utilized in those devices. More specifically, traditional load control devices are typically only capable of responding to simple user actions such as moving a lever or pushing a button. As such, the number and/or types of control that may be applied through a load control device is limited. To meet the demand of advanced electrical loads, there is a need to employ alternative user interface technologies such as those capable of detecting human gestures and translating the gestures into control data (e.g., control signals) for controlling the electrical loads. These technologies may expand the capacity of a load control device, while at the same time enhancing its usability and aesthetic appeal, for example.

[0004] A traditional load control device may also lack the capacity to provide visual feedback to a user about the operation of the load control device and/or the electrical loads controlled by the load control devices. Such capacity is an important aspect of user experience in an advanced load control system where a user may be able to manipulate multiple operating parameters of an electrical load or to control multiple electrical loads via a single control device. Provision of feedback in those environments can keep the user informed about the state and/or mode of the control device and electrical loads, and may help the user navigate through the various functionalities of the control device.

## SUMMARY

[0005] As described herein, a control device configured for use in a load control system to control one or more electrical loads external to the control device may comprise an antenna and an actuation member having a front surface defining a touch sensitive surface (e.g., capacitive touch surface) configured to detect a touch actuation (e.g., a point actuation) along at least a portion of the front surface. The control device may include a main printed circuit board (PCB) comprising a control circuit, an antenna PCB connected to the main PCB, a tactile switch(es), a controllably conductive device, and a drive circuit operatively coupled to a control input of the controllably conductive device for rendering the controllably conductive device conductive or non-conductive to control the amount of power delivered to the electrical load. The main PCB may include a counterpoise. The antenna PCB may include an antenna mounted thereto. The antenna may be a monopole antenna. The antenna may extend substantially perpendicular from the main PCB. The main PCB may include a wireless communication circuit that is coupled to the antenna for transmitting and/or receiving wireless messages that include a command for controlling one or more electrical loads. The control device may determine the command based on a user input on the actuation member.

[0006] The control device may include a yoke that is configured to attach the control device to a wallbox. The yoke may be a metal yoke. The control device may define a cavity between the actuation member and the yoke. The yoke may define an opening that is configured to receive the antenna PCB. The opening may include a first portion that is configured to receive the antenna PCB and a second portion that is configured to enable electrical connection of a capacitive touch PCB to the main PCB. The antenna may extend from a location proximate to the main PCB through the opening in the yoke and into the cavity. For example, a portion of the antenna may be located within the cavity. The antenna PCB may include one or more fingers. The main PCB may include one or more slots that are configured to receive the fingers. The antenna PCB may define one or more slots proximate to the antenna. The slots may extend from a first surface of the antenna PCB to a second surface of the antenna PCB. The antenna may be attached to the first surface of the antenna PCB.

[0007] The antenna may include a horizontal trace that extends from a front side of the yoke to a rear side of the yoke. The antenna may further include a vertical trace connected to the horizontal trace. The vertical trace may include the portion of the antenna located within the cavity. The vertical trace of the monopole antenna may define a first width and the horizontal trace of the antenna may define a second width. The first width may be greater than the second width. The antenna PCB may include a plurality of fingers that are configured to connect the antenna PCB to the main PCB. The antenna is electrically connected to the wireless communication circuit via one of the plurality of fingers. The antenna PCB may include pads on one or more of the plurality of fingers that are configured to attach the antenna PCB to the main PCB. The main PCB may include a plurality of slots configured to receive the plurality of fingers. The antenna PCB may include one or more slots proximate to the antenna. The slots may be configured to reduce an amount of board material proximate to the antenna. A first slot of the one or more slots may be located proximate to the vertical trace of the antenna and a second slot of the one or more slots may be located proximate to the horizontal trace of the antenna. The antenna may be located substantially at a midpoint between the capacitive touch printed circuit board and a bidirectional semiconductor switch of the control device. The antenna may be located outside of a capacitive touch area defined by the capacitive touch printed circuit board.

[0008] The control device may also include a capacitive touch PCB affixed to the actuation member. The capacitive touch PCB may comprise a touch sensitive circuit comprising one or more receiving capacitive touch pads located on the capacitive touch PCB, behind the actuation member, and arranged in a linear array and adjacent to the capacitive touch surface. The capacitive touch PCB may include a ground plane on a back side of the capacitive touch PCB. The actuation

member may be configured to pivot about a pivot axis to actuate the tactile switch on the main PCB in response to actuations of the actuation member, such that the capacitive touch surface and the capacitive touch PCB are configured to move with the actuation member in response to actuations of the actuation member. The actuation member may additionally be configured to substantially maintain its position (e.g., not pivot about the pivot axis) in response to a user input applied over the pivot axis so that the tactile switch is not actuated by the user input. In response to such a user input, the control device may enter a programming mode to allow a user to configure or adjust the operating characteristics of the control device. The control device may also be configured to perform a specific operation (e.g., switch from an intensity control mode to a color control mode) in response to the user input.

[0009] A control device may include an actuation member, a main printed circuit board, and/or a capacitive touch printed circuit board affixed to the actuation member. The actuation member has a front surface that may define a touch sensitive surface (e.g. capacitive touch surface) that is configured to detect a touch actuation along at least a portion of the touch sensitive surface (e.g., a portion above a light bar of the control device). The main printed circuit board may include a first control circuit, a tactile switch, a controllably conductive device, and/or a drive circuit. The drive circuit is operatively coupled to a control input of the controllably conductive device for rendering the controllably conductive device conductive or non-conductive to control the amount of power delivered to the electrical load. The actuation member may be configured to pivot about a pivot axis to actuate the tactile switch on the main printed circuit board in response to tactile actuations of the actuation member. The antenna may be located proximate to the pivot axis.

[0010] The capacitive touch printed circuit board may include one or more receiving touch sensitive pads, such as capacitive touch pads, located on the capacitive touch printed circuit board. The touch sensitive pads may be located behind the actuation member and/or may be arranged in a linear array adjacent to the touch sensitive surface. The capacitive touch printed circuit board may also include a second control circuit configured to receive inputs from the capacitive touch pads and provide an output signal to the first control circuit in response to the inputs received from the capacitive touch pads. The capacitive touch printed circuit board may be configured to move with the actuation member in response to tactile actuations of the actuation member. The first control circuit may be configured to control an amount of power delivered to the electrical load in response to a position of a touch actuation along the length of the touch sensitive surface indicated by the output signal from the second control circuit.

[0011] The second control circuit may be configured to compare a measured voltage provided via a capacitive touch pad to a voltage threshold and generate an output signal that indicates when the measured voltage exceeds the voltage threshold. The second control circuit may be configured to use different voltage thresholds for different capacitive touch pads. For example, the receiving capacitive touch pads may be separated from the capacitive touch surface by varying distances, and the different voltage thresholds may be used based on the distance between the capacitive touch pad and the capacitive touch surface.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0012] FIG. 1 depicts an example load control system that includes one or more example control devices.

[0013] FIG. 2 is a perspective view of an example control device that may be deployed as a dimmer switch and/or a remote control device of the load control system illustrated in FIG. 1.

[0014] FIG. 3 is a front view of the control device of FIG. 2.

[0015] FIG. 4 is a partially exploded view of the control device of FIG. 2.

[0016] FIG. 5 is a cross-sectional view of the control device of FIG. 2 taken through the center of the control device (e.g., through the line shown in FIG. 3).

[0017] FIG. 6 is a side cross-sectional view of the control device of FIG. 2 taken through a center of an antenna printed circuit board (e.g., through the line shown in FIG. 3).

[0018] FIG. 7 is a perspective view of a base portion of the control device of FIG. 2.

[0019] FIG. 8 is a front view of the base portion of the control device of FIG. 2.

[0020] FIG. 9 is a front view of the control device of FIG. 2 with an actuator removed.

[0021] FIG. 10 is a side view of an example antenna printed circuit board.

[0022] FIG. 11 shows a simplified block diagram of an example control device (e.g., dimmer switch) that may be implemented as the control device illustrated in FIG. 2.

#### DETAILED DESCRIPTION

[0023] FIG. 1 is a simplified block diagram of an example load control system. As shown, the load control system is configured as a lighting control system **100** for control of one or more lighting loads, such as a lighting load **102** that is installed in a ceiling-mounted downlight fixture **103** and a controllable lighting load **104** that is installed in a table lamp **105**. The lighting loads **102**, **104** shown in FIG. 1 may include light sources of different types (e.g., incandescent lamps, fluorescent lamps, and/or LED light sources). The lighting loads may have advanced features. For example, the lighting loads may be controlled to emit light of varying intensities and/or colors in response to a user command. The amount of power delivered to the lighting loads may be adjusted to an absolute level or by a relative amount. The lighting control system **100** may be configured to control one or more of the lighting loads (e.g., and/or other electrical loads) according to one or more configurable presets or scenes. These presets or scenes may correspond to, for example, predefined light intensities and/or colors, predefined entertainment settings such as music selection and/or volume settings, predefined window treatment settings such as positions of shades, predefined environmental settings such as HVAC settings, or any combination thereof. The presets or scenes may correspond to one or more specific electrical loads (e.g., bedside lamps, ceiling lights, etc.) and/or one or more specific locations (e.g., a room, an entire house, etc.).

[0024] The lighting load **102** may be an example of a lighting load that is wired into a power control and/or delivery path of the lighting control system **100**. As such, the lighting load **102** may be controllable by a wall-mounted control device such as a dimmer switch. The lighting load **104** may be an example of a lighting load that is equipped with integral load control circuitry and/or wireless communication capabilities such that the lighting load may be controlled via a wireless control mechanism (e.g., by a remote control device).

[0025] The lighting control system **100** may include one or more control devices for controlling the lighting loads **102**, **104** (e.g., controlling an amount of power delivered to the lighting loads). The lighting loads **102**, **104** may be controlled substantially in unison, or be controlled individually. For example, the lighting loads may be zoned so that the lighting load **102** may be controlled by a first control device, while the lighting load **104** may be controlled by a second control device. The control devices may be configured to turn the lighting loads **102**, **104** on and off. The control devices may be configured to control the magnitude of a load current conducted through the lighting loads (e.g., so as to control an intensity level of the lighting loads **102**, **104** between a low-end intensity level LLE and a high-end intensity level LHE). The control devices may be configured to control an amount of power delivered to the lighting loads to an absolute level (e.g., to a maximum allowable amount), or by a relative amount (e.g., an increase of 10% from a current level). The control devices may be configured to control a color of the lighting load **102**, **104** (e.g., by controlling a color temperature of the lighting loads or by applying full color control over the lighting loads).

[0026] The lighting loads **102**, **104** may be smart lamps capable of sending and/or receiving wireless communications. The dimmer switch **110** may include a control circuit. The control circuit may be configured to be responsive to a user input and generate control instructions (e.g., a wired

and/or wireless control signal) for controlling the lighting loads **102**, **104** based on the user input. The control instructions may include commands and/or other information (e.g., such as identification information) for controlling the lighting loads **102**, **104**. The dimmer switch **110** may be configured to transmit messages via the RF signals **108** for controlling the lighting loads **102**, **104**. The dimmer switch **110** may include a wireless communication circuit that is configured to send/receive wireless signals such as the RF signals **108**. For example, the dimmer switch **110** may be configured to transmit messages to lighting devices (e.g., the lighting loads **102**, **104**) that are within a wireless communication range of the dimmer switch **110** via the RF signals **108**.

[0027] The control devices may be configured to activate a preset associated with the lighting load **102**, **104**. A preset may be associated with one or more predetermined settings of the lighting loads, such as an intensity level of the lighting loads and/or a color of the lighting loads. The presets may be configured via the control device and/or via an external device (e.g., a mobile device) by way of the wireless communication circuit of the control device. The control devices may be configured to activate control of a zone. A zone may correspond to one or more electrical loads that are configured to be controlled by the control devices. A zone may be associated with a specific location (e.g., a living room) or multiple locations (e.g., an entire house with multiple rooms and hallways). The control devices may be configured to switch between different operational modes. An operational mode may be associated with controlling different types of electrical loads or different operational aspects of one or more electrical loads. Examples of operational modes may include a lighting control mode for controlling one or more lighting loads (e.g., which in turn may include a color control mode and an intensity control mode), an entertainment system control mode (e.g., for controlling music selection and/or the volume of an audio system), an HVAC system control mode, a winter treatment device control mode (e.g., for controlling one or more shades), and/or the like.

[0028] One or more characteristics of the control device and/or the lighting load **102**, **104** described herein may be customized via an advanced programming mode (APM). Such characteristics may include, for example, an intensity level associated with a preset, a fade-on/fade-off time, enablement/disablement of visual indicators, a low-end trim (e.g., a minimum intensity level to which the lighting load **102**, **104** may be set by the control device), a high-end trim (e.g., a maximum intensity level to which the lighting load **102**, **104** may be set by the control device), and/or the like. Examples of an advanced programming mode for a wall-mounted load control device can be found in U.S. Pat. No. 7,190,125, issued Mar. 13, 2007, entitled PROGRAMMABLE WALLBOX DIMMER, the entire disclosure of which is hereby incorporated by reference. The control device may be manipulated to enter the advanced programming mode in various ways. For instance, the control device may be moved into the advanced programming mode via a press-and-hold or a double-tap applied to a front area of the control device. Ways to activate the advanced programming mode for a control device will be described in greater detail below.

[0029] The control device described herein may be, for example, a dimmer switch **110**, a retrofit remote control device **112**, a wall-mounted remote control device **114**, a tabletop remote control device **116**, and/or a handheld remote control device **118**, as shown in FIG. 1. The dimmer switch **110** may be configured to be mounted to a standard electrical wallbox (e.g., via a yoke) and be coupled in series electrical connection between an alternating-current (AC) power source **105** and a lighting load that is wired into the control path of the dimmer switch **110** (e.g., such as the lighting load **102**). The dimmer switch **110** may receive an AC mains line voltage VAC from the AC power source **105**, and may generate a control signal for controlling the lighting load **102**. The control signal may be generated via various phase-control techniques (e.g., a forward phase-control dimming technique or a reverse phase-control dimming technique). The dimmer switch **110** may be configured to receive wireless signals (e.g., from a remote control device) representative of commands to control the lighting load **102**, and generate respective control signals for executing the commands. Examples of wall-mounted dimmer switches are described in greater detail in

commonly-assigned U.S. Pat. No. 7,242,150, issued Jul. 10, 2007, entitled DIMMER HAVING A POWER SUPPLY MONITORING CIRCUIT; U.S. Pat. No. 7,546,473, issued Jun. 9, 2009, entitled DIMMER HAVING A MICROPROCESSOR-CONTROLLED POWER SUPPLY; and U.S. Pat. No. 8,664,881, issued Mar. 4, 2014, entitled TWO-WIRE DIMMER SWITCH FOR LOW-POWER LOADS, the entire disclosures of which are hereby incorporated by reference.

[0030] The retrofit remote control device **112** may be configured to be mounted to a mechanical switch (e.g., a toggle switch **122**) that may be pre-existing in the lighting control system **100**. Such a retrofit solution may provide energy savings and/or advanced control features, for example without requiring significant electrical re-wiring and/or without requiring the replacement of existing mechanical switches. As an example, a consumer may replace an existing lamp with the controllable lighting load **104**, switch a toggle switch **122** that is coupled to the lighting load **104** to the on position, install (e.g., mount) the remote control device **112** onto the toggle switch **122**, and associate the remote control device **112** with the lighting source **104**. The retrofit remoted control **112** may then be used to perform advanced functions that the toggle switch **122** may be incapable of performing (e.g., such as dimming the intensity level of the light output, changing the color of the light output, providing feedback to a user, etc.). As shown, the toggle switch **122** is coupled (e.g., via a series electrical connection) between the AC power source **105** and an electrical receptacle **120** into which the lighting load **104** may be plugged (e.g., as shown in FIG. 1). Alternative, the toggle switch **122** may be coupled between the AC power source **105** and one or more of the lighting loads **102**, **104**, without the electrical receptacle **120**.

[0031] The wall-mounted remote control device **114** may be configured to be mounted to a standard electrical wallbox and be electrically connected to the AC power source **105** for receiving power. The wall-mounted remote control device **114** may be configured to receive a user input and may generate and transmit a control signal (e.g., control data such as a digital message) for controlling the lighting loads **102**, **104** in response to the user input. The tabletop remote control device **116** may be configured to be placed on a surface (e.g., an end table or nightstand), and may be powered by a direct-current (DC) power source (e.g., a battery or an external DC power supply plugged into an electrical outlet). The tabletop remote control device **116** may be configured to receive a user input, and may generate and transmit a signal (e.g., a digital message) for controlling the lighting loads **102**, **104** in response to the user input. The handheld remote control device **118** may be sized to fit into a user's hand, and may be powered by a direct-current (DC) power source (e.g., a battery or an external DC power supply plugged into an electrical outlet). The handheld remote control device **118** may be configured to receive a user input, and may generate and transmit a signal (e.g., a digital message) for controlling the lighting loads **102**, **104** in response to the user input. Examples of battery-powered remote controls are described in greater detail in commonly assigned U.S. Pat. No. 8,330,638, issued Dec. 11, 2012, entitled "Wireless Battery Powered Remote Control Having Multiple Mounting Means," and U.S. Pat. No. 7,573,208, issued Aug. 11, 2009, entitled "Method Of Programming A Lighting Preset From A Radio-Frequency Remote Control," the entire disclosures of which are hereby incorporated by reference.

[0032] It should be appreciated that, although a lighting control system with two lighting loads is provided as an example above, a load control system as described herein may include more or fewer lighting loads, other types of lighting loads, and/or other types of electrical loads that may be configured to be controlled by the one or more control devices. For example, the load control system may include one or more of: a dimming ballast for driving a gas-discharge lamp; an LED driver for driving an LED light source; a dimming circuit for controlling the intensity level of a lighting load; a screw-in luminaire including a dimmer circuit and an incandescent or halogen lamp; a screw-in luminaire including a ballast and a compact fluorescent lamp; a screw-in luminaire including an LED driver and an LED light source; an electronic switch, controllable circuit breaker, or other switching device for turning an appliance on and off; a plug-in control device, controllable electrical receptacle, or controllable power strip for controlling one or more

plug-in loads; a motor control unit for controlling a motor load, such as a ceiling fan or an exhaust fan; a drive unit for controlling a motorized window treatment or a projection screen; one or more motorized interior and/or exterior shutters; a thermostat for a heating and/or cooling system; a temperature control device for controlling a setpoint temperature of a heating, ventilation, and air-conditioning (HVAC) system; an air conditioner; a compressor; an electric baseboard heater controller; a controllable damper; a variable air volume controller; a fresh air intake controller; a ventilation controller; one or more hydraulic valves for use in radiators and radiant heating system; a humidity control unit; a humidifier; a dehumidifier; a water heater; a boiler controller; a pool pump; a refrigerator; a freezer; a television and/or computer monitor; a video camera; an audio system or amplifier; an elevator; a power supply; a generator; an electric charger, such as an electric vehicle charger; an alternative energy controller; and/or the like.

[0033] FIGS. 2-9 depict an example control device **200** that may be deployed as the dimmer switch **110** and/or the retrofit remote control device **112** in the lighting control system **100**. FIG. 2 is a perspective view and FIG. 3 is a front view of the example control device **200**. The control device **200** may comprise a user interface **202** and a faceplate **204**. The control device **200** may be configured to control the amount of power delivered to a lighting load (e.g., turn the lighting load on or off, or adjust the intensity level of the lighting load by transmitting a message for controlling the lighting load via a communication circuit (e.g., a wireless signal via a wireless communication circuit), and/or by controlling the lighting load via an internal load control circuit (e.g., a controllably conductive device of the control device **200**)). When the control device **200** is a wall-mounted dimmer switch, the control device **200** may comprise a rear enclosure **230** for housing load control circuitry of the control device **200**. For example the rear enclosure **230** may enclose a portion (e.g., one or more components) of the control device **200**. The control device **200** may be configured to be mounted to an electrical wallbox (e.g., a metal wallbox).

[0034] The user interface **202** of the control device **200** may include an actuation member **210** that is configured to be mounted to a bezel **212** (e.g., a base portion). The actuation member **210** may comprise a front surface **214** including an upper portion **216** and a lower portion **218**. The user interface **202** may include a light bar **220** extending along the length of the front surface **214** of the actuation member **210**. The light bar **220** may be configured to be illuminated by one or more light sources (e.g., one or more LEDs) to visibly display information. The actuation member **210** may be configured to pivot about a pivot axis **222** (e.g., a central axis) in response to a tactile actuation (e.g., a tactile input) of the upper portion **216** and the lower portion **218**. The control device **200** may be configured to control a lighting load of the lighting control system **100** to turn the lighting load on in response to a tactile actuation of the upper portion **216**, and to turn the lighting load off in response to a tactile actuation (e.g., a tactile input) of the lower portion **218** (or vice versa). For example, the control device **200** may be configured to turn the lighting load on to a previous intensity level (e.g., before the lighting load was previously turned off) or to a preset intensity level (e.g., a predetermined or locked preset intensity level) in response to a tactile actuation of the upper portion **216** of the actuation member **210**. The control device **200** may include one or more tactile switches that are actuated in response to the tactile actuations of the upper and/or lower portions **216**, **218** of the actuation member **210**.

[0035] The control device **200** may be configured to control a lighting load of the lighting control system **100** in response to a touch actuation of the actuation member **210**. For example, the actuation member **210** may also receive user inputs that do not cause the actuation member to pivot (e.g., about the pivot axis **222**). At least a portion of the front surface **214** of the actuation member **210** may be configured as a touch sensitive surface (e.g., a capacitive touch surface) that is configured to receive (e.g., detect) inputs (e.g., touch actuations/inputs), such as point actuations or gestures, from a user of the control device **200**. The touch sensitive surface of the actuation member **210** may be located adjacent to and/or overlap with the light bar **220**. The actuation member **210** may substantially maintain its position (e.g., with respect to the bezel **212**) in response



to these inputs and, depending on the positions of the inputs, the control device may enter different operating modes and/or carry out different control functions in response. For example, during a normal operating mode of the control device **200**, the front surface **214** of the actuation member **210** may be actuated along the light bar **220** (e.g., along the touch sensitive surface) to adjust the amount of power delivered to, and thus the intensity level of, the lighting load according to the position of the actuation. For instance, the control device **200** may control the magnitude of a load current conducted through the lighting load based on the position of a touch actuation (e.g., a touch input) along the touch sensitive surface of the actuation member **210** to control an intensity level of the lighting load between a low-end intensity level LLE and a high-end intensity level LHE. The control device **200** may control an amount of power delivered to the lighting load to an absolute level (e.g., to a maximum allowable amount) or by a relative amount (e.g., an increase of 10% from a current level) based on the position of a touch actuation along the touch sensitive surface of the actuation member **210**. Examples of control devices having capacitive touch surfaces are described in greater detail in commonly-assigned U.S. Pat. No. 10,109,181, issued Oct. 23, 2018, entitled GESTURE-BASED CONTROL DEVICE FOR CONTROLLING AN ELECTRICAL LOAD, and U.S. Patent Publication No. 2020/0382120, published Dec. 3, 2020, entitled LOAD CONTROL DEVICE HAVING A CAPACITIVE TOUCH SURFACE, the entire disclosure of which are hereby incorporated by reference. Although described primarily in context of a capacitive touch surface, it should be appreciated that the control device **200** is not so limited, and in some examples, at least a portion of the front surface **214** of the actuation member **210** may be configured as a different type of touch sensitive surface, such as a resistive touch surface, an inductive touch surface, a surface acoustic wave (SAW) touch surface, an infrared touch surface, acoustic pulse touch surface, or the like.

[0036] The control device **200** may control the magnitude of a load current conducted through the lighting load based on a single discrete input along the touch sensitive surface and/or based on a plurality of consecutive inputs along the touch sensitive surface. For example, the user may tap their finger at a position along the touch sensitive surface, and in response, the control device **200** may turn the lighting load on to an intensity level based on the position. As an example, if the lighting load is off, the control device **200** may turn the lighting load on to an intensity level based on the position of a touch actuation along the touch sensitive surface of the actuation member **210**. While the lighting load is on, the user may move (e.g., slide) their finger along the touch sensitive surface, and in response, the control device **200** may adjust (e.g., continuously control) the magnitude of the load current conducted through the lighting load based on the positions of a plurality of inputs along the touch sensitive surface.

[0037] Further, in a color control mode, the control device **200** may control a color of the lighting load based on the position of a touch actuation along the touch sensitive surface of the actuation member **210** (e.g., by controlling a color temperature of the lighting load or by applying full color control over the lighting load). For example, the light bar **220** may be configured to illuminate a spectrum of colors through the length of the light bar **220** (e.g., across the full visible color spectrum, a subset of the visual color spectrum, and/or the light spectrum associated with the color temperatures of a black body radiator). Accordingly, the control device **200** may control the color of the lighting load based on the position of a touch actuation along the touch sensitive surface, and in turn, the corresponding color of that position on the light bar **220**.

[0038] The control device **200** may be configured to prioritize user inputs that cause the actuation member **210** to pivot over user inputs that do not cause the actuation member **210** to pivot, or vice versa. For example, when the lighting load is off and a user moves a finger close to the upper portion **216** of the actuation member **210** causing the control device **200** to detect a touch actuation via the touch sensitive surface (e.g., along the light bar **220**), the control device **200** may temporarily delay responding to the touch actuations received via the touch sensitive surface to see if a user is attempting to actuate the upper portion **216** of the actuation member **210** to turn on the

lighting load. Accordingly, the control device **200** may avoid turning on the lighting load to an intensity level based on the position of the actuation on the light bar **220** (e.g., in response to the touch sensitive surface) if the user's finger happens to sweep past the light bar **220** while actuating the upper portion **216** of the actuation member **210** or if the user's finger actuates the upper portion **216** of the actuation member **210** too close to the light bar **220**. In addition, when the lighting load is on and a user moves a finger close to the lower portion **218** of the actuation member **210** causing the control device **200** to detect a touch actuation via the touch sensitive surface, the control device **200** may temporarily ignore the touch actuations received via the touch sensitive surface after the actuation of the lower portion **218**. Accordingly, the control device **200** may avoid turning on the lighting load again if the user's finger happens to sweep past the light bar **220** while moving away from the lower portion **218** of the actuation member **210**.

[0039] The control device **200** may, for example, be configured to prioritize inputs received in response to actuation of the actuation member **210** over the inputs received via the touch sensitive surface by ignoring inputs received via the touch sensitive surface when a tactile actuation of the actuation member **210** is received within a blanking period (e.g., a first blanking period or an after-touch blanking period) after an initial detection of a touch actuation received via the touch sensitive surface. For example, the blanking period may be approximately **200** milliseconds. The blanking period may occur after (e.g., in response to) a touch actuation (e.g., the initial detection of a touch actuation). That is, the control device **200** may ignore touch actuations received via the touch sensitive surface when a touch actuation of the actuation member **210** is received within the blanking period (e.g., a touch actuation that begins during the blanking period). For instance, in some examples, the control device **200** may start the blanking period (e.g., a timer) in response to receiving a touch actuation via the touch sensitive surface, and ignore touch actuations received via the touch sensitive surface during the blanking period if the control device **200** receives a touch actuation of the actuation member **210** during the blanking period (e.g., a touch actuation begins during the blanking period). As such, the control device **200** may prioritize user inputs that cause the actuation member **210** to pivot over user inputs that do not cause the actuation member **210** to pivot during the blanking period.

[0040] Further, even if a blanking period is implemented, the control device **200** may be configured to respond to a quick “tap” along the touch sensitive surface. For instance, the control device **200** may be configured to determine that a touch actuation is at a position on the touch sensitive surface for an amount of time that is shorter than the blanking period without the actuation member **210** being actuated (e.g., a touch actuation starts and finishes before the end of the blanking period) and, in response, turn the lighting load on to an intensity level associated with the position in response to the touch actuation. Accordingly, the control device **200** may both implement the blanking period to avoid unintentional touch actuations along the touch sensitive surface and still respond quickly to intentional touch actuations along the touch sensitive surface.

[0041] The control device **200** may be configured to turn the lighting load on in response to a touch actuation received via the touch sensitive surface even when implementing the blanking period. For example, the control device **200** may be configured to receive a touch actuation via the touch sensitive surface at a position for an amount of time that is greater than the blanking period without the tactile switch being actuated (e.g., a touch actuation begins during the blanking period and ends after the blanking period) and, in response, turn the lighting load on to an intensity level associated with the position in response to the touch actuation. Further, the control device **200** may adjust the length of a blanking period, for example, through a user input (e.g., a touch actuation and/or a tactile actuation) received while in the advanced programming mode. For instance, in some examples, the blanking period may be configured to be greater than one second (e.g., multiple seconds). In such examples, the control device **200** may respond to a press-and-hold touch actuation along the light bar **220** by turning the lighting load on to an intensity level associated with the position of the press-and-hold actuation.

[0042] The control device **200** may be configured to temporarily ignore inputs received via the touch sensitive surface after a tactile actuation of the actuation member **210** that causes the lighting load to turn on or off. The control device **200** may be configured in this manner to, for example, avoid mistakenly turning the lighting load back on and/or adjusting the power delivered to (e.g., the intensity level of) the lighting load after a tactile actuation of the actuation member **210**. For example, the control device **200** may be configured to ignore inputs received via the touch sensitive surface during a blanking period (e.g., a second blanking period or after-tactile period) after detecting a tactile actuation of the actuation member to turn the lighting load on or off. For instance, in some examples, the control device **200** may start the blanking period in response to turning on or off the lighting load and, during the blanking period, ignore inputs received via the touch sensitive surface during the blanking period. As such, through the use of the blanking period, the control device **200** may be able avoid unintentional touch actuations along the touch sensitive surface after a tactile actuation of the actuation member **210**. In sum, the control device **200** may be configured with one or more blanking periods, such as a first blanking period that is used to avoid unintentional touch actuations after an initial detection of a touch actuation received via the touch sensitive surface and prior to tactile actuations of the actuation member **210** (e.g., a blanking period that occurs after (e.g., in response to) a touch actuation), and/or a second blanking period that is used to avoid unintentional touch actuations after tactile actuations of the actuation member **210** (e.g., a blanking period that occurs after (e.g., in response to) a tactile actuation).

[0043] FIG. **4** is an exploded view of the control device **200**. The control device **200** may include the actuation member **210**, the bezel **212**, an enclosure ring **280**, a capacitive touch PCB **240**, and a rear enclosure **230**. FIG. **5** is a top cross-sectional view of the control device **200** taken through the line shown in FIG. **3**. FIG. **6** is a right side cross-sectional view of the control device **200** taken through the line shown in FIG. **3**. FIG. **7** is a perspective view of the control device **200** with the bezel **212**, the actuation member **210**, and the capacitive touch PCB **240** removed. FIG. **8** is a front view of the control device **200** with the bezel **212**, the actuation member **210**, and the capacitive touch PCB **240** removed. FIG. **9** is a front view of the control device **200** with the actuation member **210** removed. As noted herein, the enclosure ring **280** and the rear enclosure **230** may together house the load control circuitry of the control device **200**. Although illustrated with the enclosure portion **280** and/or the rear enclosure **230**, in some examples, such as when the control device **200** is a wireless, remote control device, the enclosure ring **280** and/or the rear enclosure **230** may be omitted. In such examples, the control device **200** may connect to a base that is affixed to the toggle or paddle actuator of a standard light switch.

[0044] The control device **200** may comprise a yoke **232** that may be configured to mount the control device **200** to an electrical wallbox (e.g., when the control device **200** is a wall-mounted dimmer switch). The yoke **232** may be connected to the rear enclosure **230**, such that a main printed circuit board (PCB) **260** of the control device **200** is located between the enclosure ring **280** and the rear enclosure **230**. The yoke **232** may be a metal yoke and may be configured as a heat sink for the control device **200**. For example, the yoke **232** may include metal. As shown in FIG. **5**, the control device **200** may comprise a diffuser **234** including a protruding portion **235** that extends through an elongated opening in the actuation member **210** to form the light bar **220**. The control device **200** may also comprise a light pipe **236** that may be configured to conduct light from one or more light sources **238** located inside of the rear enclosure **230** to the light bar **220**. For example, the light sources **238** may comprise one or more light-emitting diodes (LEDs) mounted to the main PCB **260**.

[0045] The main PCB **260** may be located within the rear enclosure **230**. For example, the main PCB **260** may be attached to the rear enclosure **230** or the enclosure ring **280**. The main PCB **260** may have mounted thereto the load control circuitry used to control power delivered to an electrical load. For example, the main PCB **260** may have mounted thereto any combination of a control circuit (e.g., a primary control circuit), memory, a drive circuit, one or more controllably

conductive devices, a zero-crossing detector, a power supply, etc. (e.g., as shown in FIG. 11). For example, the controllably conductive devices of the control device **200** may include a bidirectional semiconductor switch **268**. The bidirectional semiconductor switch **268** may comprise a triac, a field-effect transistor (FET) in a rectifier bridge, two FETs in anti-series connection, one or more silicon-controlled rectifiers (SCRs), or one or more insulated-gate bipolar junction transistors (IGBTs). The control circuit of the main PCB **260** may be configured to render the bidirectional semiconductor switch **268** conductive or non-conductive, for example, to control the amount of power delivered to the electrical load. As shown in FIG. 5, the bidirectional semiconductor switch **268** may be mechanically connected to the yoke **232**, for example, via one or more rivets (not shown) received through one or more opening **269** in the yoke **232** (e.g., shown in FIG. 7). The bidirectional semiconductor switch **268** may be thermally coupled to the yoke **232**, for example, to dissipate heat generated by the bidirectional semiconductor switch **268**.

[0046] The control device **200** may also include mechanical switches, such as first and second tactile switches **264**, **265**, that may be mounted to the main PCB **260**. The first and second tactile switches **264**, **265** may be actuated in response to actuations (e.g., tactile actuations) of the upper portion **216** and the lower portion **218** of the actuation member **210**, respectively (e.g., to control turning the load on and off). In some examples, the control device **200** may be configured to control a lighting load of the lighting control system **100** to turn the load on in response to an actuation of the first tactile switch **264** and to turn the load off in response to an actuation of the second tactile switch **265**.

[0047] The control device **200** may also comprise a touch sensitive printed circuit board, such as a capacitive touch printed circuit board (PCB) **240**. The capacitive touch PCB **240** may be located behind (e.g., along the rear surface of) the user interface **202** (e.g., the actuation member **210**) for detecting actuations of the front surface **214** of the actuation member **210**. The capacitive touch PCB **240** may be planar. The capacitive touch PCB **240** may include one or more pads located adjacent to (e.g., but not immediately behind) the light bar **220** for detecting touch actuations of the light bar **220** (e.g., and/or touch actuations of the front surface **214** of the actuation member **210** adjacent to the light bar **220**). In some examples, the capacitive touch PCB **240** is not located immediately behind the light bar **220** since the light pipe **236** may extend from the light sources **238** in the enclosure **230** to the light bar **220**. Further, the capacitive touch PCB **240** may be mounted or affixed to the actuation member **210**, for example, such that movement of the actuation member **210** causes movement of the capacitive touch PCB **240**. That is, the capacitive touch PCB **240** creates the touch sensitive surface on the front side of actuation member **210**, and as such, the touch surface also moves with tactile actuations of the actuation member **210**.

[0048] The capacitive touch PCB **240** may include a capacitive touch controller and one or more receiving capacitive touch pads **244** for detecting the touch actuations on or adjacent to the light bar **220**. The receiving capacitive touch pads **244** may be arranged in a linear array that extends from the top to the bottom of the capacitive touch PCB **240** (e.g., below the area **249**). The capacitive touch PCB **240** (e.g., the capacitive touch controller) may be configured to detect the position of the touch actuation along the length of the light bar **220** in response to touch actuations received from the one or more receiving capacitive touch pads **244** and to control the electrical loads according to the determined position. For example, the capacitive touch PCB **240** (e.g., the capacitive touch controller) may provide an output signal to the main PCB **260**, and the main PCB **260** may control the electrical load(s) based on the determined position (e.g., by controlling a drive circuit of the control device **200**, by sending a message, such as a digital message, to the electrical load and/or to a system controller, etc.). The capacitive touch PCB **240** may be electrically connected to the main PCB **260** via a cable **246** (e.g., a ribbon cable) connected to a first connector **248** on the main PCB **260** and a second connector **249** on the capacitive touch PCB **240** (e.g., as shown in FIG. 5).

[0049] The capacitive touch pads **244** may include one or more electrodes. For example, as shown

in FIGS. 4 and 5, the diffuser **234** may be located between actuation member **210** and the capacitive touch pads **244** on the capacitive touch PCB **240**, such there may not be any air between the actuation member **210** and the capacitive touch pads **244** to improve the sensitivity of the capacitive touch controller. The capacitive touch PCB **240** may receive power from a power supply of the main PCB **260** to power the components of the capacitive touch PCB **240**.

[0050] The actuation member **210** may include pivot arms **252** that enable the actuation member **210** to pivot about the pivot axis **222** in response to respective tactile actuation of the upper portion **216** and the lower portion **218**. As described herein, the capacitive touch PCB **240** may be mounted to the actuation member **210**. Accordingly, the capacitive touch PCB **240** may move (e.g. pivot) when the actuation member **210** pivots in response to a tactile actuation of the upper or lower portion **216**, **218**. The pivot arms **250** may define the pivot axis **222** of the actuation member **210**. The PCB **240** may create the touch sensitive surface on the front surface **214** of the actuation member **210**, and as such, the touch sensitive surface may also move with tactile actuations of the actuation member **210**. In examples, the capacitive touch PCB **240** may be a solid PCB (e.g., PCB with a solid substrate). In examples, the capacitive touch PCB **240** may be a flexible PCB (e.g., PCB with a flexible substrate) to enable further movement or bend of the capacitive touch PCB **240** in response to tactile actuations of the actuation member **210**.

[0051] The tactile actuation of the actuation member **210** may cause one of the first and second tactile switches **264**, **265** of the main PCB **260** to be actuated. For example, when the upper portion **216** of the actuation member **210** is actuated, the diffuser **234** may be moved toward the main PCB **260**. The diffuser **234** may contact a rubber membrane **250** (e.g., rubber membrane extension **256**) which may deflect inward (e.g., toward the main PCB **260**) to actuate the first tactile switch **264** of the main PCB **260**. Similarly, when the lower portion **218** of the actuation member **210** is actuated, the diffuser **234** may be moved toward the main PCB **260**. The diffuser **234** may contact the rubber membrane **250** (e.g., rubber membrane extension **258**), which may deflect inward (e.g., toward the main PCB **260**) to actuate the second tactile switch **265** of the main PCB **260**. Accordingly, the capacitive touch PCB **240** may be affixed to the actuation member **210**, and the actuation member **210**, when actuated, may pivot to actuate a tactile switch on a separate main PCB **260** of the control device **200**. As such, tactile actuations of the actuation member **210** may cause movement of the capacitive touch PCB **240** (e.g., and the diffuser **234**).

[0052] Further, it should also be appreciated that the diffuser **234** may be configured to perform multiple functions. For example, the diffuser **234** may be configured to diffuse light emitted from light sources **238** located inside the enclosure **230** to the light bar **220** located on the front surface **214** of the actuation member **210**, and may also be configured to cause the actuation of one or more of the tactile switches **264**, **265** located on the main PCB **260**. Stated differently, the diffuser **234** may be configured to transfer movement of the actuation member **210** to the tactile switches **264**, **265**, for example, via the capacitive touch PCB **240** and/or the rubber membrane **250**.

[0053] In alternate examples, the capacitive touch PCB **240** may include tactile switches on the back of the capacitive touch PCB **240**. In such embodiments, the tactile switches of the capacitive touch PCB **240** would be actuated in response to tactile actuations of the upper portion **216** and the lower portion **218** of the actuation member **210**. That is, tactile actuations of the actuation member **210** would cause the upper portion **216** or the lower portion **218** to move into the tactile switches of the capacitive touch PCB **240**, for example, to actuate the tactile switches.

[0054] The capacitive touch PCB **240** may comprise a plurality of (e.g., five) receiving capacitive touch pads **244** (e.g., capacitive touch regions A-E) as shown in FIG. 9. The receiving capacitive touch pads **244** may each be triangular in shape and may be arranged in a linear array that extends from the top to the bottom of the capacitive touch PCB **240** (e.g., on the right side of the capacitive touch PCB **240**). For example, the capacitive touch region A and the capacitive touch region E of the receiving capacitive touch pads **244** may be electrically coupled together.

[0055] Although described as a capacitive touch PCB **240**, in some examples, the control device

**200** may include any PCB, such as the main PCB **260**, at the position where the capacitive touch PCB **240** is illustrated in FIGS. **4** and **9**. In such examples, the PCB may be located behind (along the rear surface of) the actuation member **210**. This PCB may include any combination of circuitry, such as any combination of the circuitry described with reference to the capacitive touch PCB **240**, the main PCB **260**, a communication circuit (e.g., a wireless communication circuit), and/or a sensing circuit (e.g., a proximity sensing circuit, an ambient light sensing circuit, etc.). As such, the PCB may both move in response to actuations of the actuation member **210** and perform the functions enabled by the relevant circuitry (e.g., control internal or external light sources based on feedback from an ambient light sensor and/or a proximity sensor, wirelessly transmit control signals to external electrical loads, etc.).

[0056] The control device **200** may be configured to transmit and receive wireless messages, e.g., radio-frequency (RF) signals. The control device **200** may include an antenna **275** and a communication circuit (e.g., such as antenna **324** and wireless communication circuit **322** shown in FIG. **11**). The wireless communication circuit may comprise an RF transceiver coupled to the antenna **275** for transmitting and/or receiving RF signals. In addition, the wireless communication circuit may comprise an RF transmitter for transmitting RF signals, an RF receiver for receiving RF signals. The control device **200** may include an antenna PCB **270**. FIG. **10** is a side view of the antenna PCB **270**. The antenna PCB **270** may define a first surface **271** and a second surface **273**. The antenna PCB **270** may include the antenna **275**. The antenna **275** may be a monopole antenna that is configured to operate at **2.4 GHz**. The antenna **275** may be configured to transmit and/or receive the wireless signals (e.g., the RF signals). The antenna **275** may be located on the second surface **273** of the antenna PCB **270**. The wireless communication circuit may be coupled to the antenna **275** for transmitting and/or receiving messages that include command(s) for controlling one or more electrical loads via the RF signals. The wireless communication circuit may determine the one or more commands for controlling the one or more electrical loads based on the inputs from the capacitive touch PCB **240**. The control device **200** may control the bidirectional semiconductor switch **268** to control the amount of power delivered to the electrical load in response to a command received via the wireless communication circuit. The control device **200** may determine a command to transmit via the wireless communication circuit based on user input on the actuation member **210**.

[0057] The antenna PCB **270** may be configured to be received by (e.g., connected to) the main PCB **260**. When the antenna PCB **270** is connected to the main PCB **260**, the first surface **271** may be facing the light pipe **236** and the second surface **273** may be facing away from the light pipe **236**. The antenna PCB **270** may include a plurality of fingers **272A**, **272B**, **272C** that are configured to connect the antenna PCB **270** to the main PCB **260**. For example, one or more of the fingers **272A**, **272B**, **272C** may include conductors (e.g., gold-plated conductors) that are configured to contact corresponding contacts on the main PCB **260**. The main PCB **260** may define openings **262A**, **262B**, **262C** that are configured to receive the fingers **272A**, **272B**, **272C**. The fingers **272A**, **272B**, **272C** may be soldered into the openings **262A**, **262B**, **262C** to provide mechanical and electrical connection between the antenna PCB **270** and the main PCB **260**. In addition, when the fingers **272A**, **272B**, **272C** are received by the openings **262A**, **262B**, **262C**, frictional forces may retain the connection between the antenna PCB **270** and the main PCB **260**. The antenna **275** of the antenna PCB **270** may be electrically connected to the wireless communication circuit on the main PCB **260** via the middle finger **272B**. The additional outside fingers **272A**, **272C** may provide additional mechanical support for the antenna PCB **270**. The finger **272C** may be wider than fingers **272A**, **272B**, for example, as shown in FIGS. **6** and **10**. It should be appreciated that the fingers **272A**, **272B**, **272C** are not limited to the geometry shown in FIGS. **6** and **10**. Rather, the fingers **272A**, **272B**, **272C** may define any respective width(s). Additionally or alternatively, the antenna PCB **270** may include more or less fingers than the three fingers **272A**, **272B**, **272C** shown in FIGS. **6** and **10**.

[0058] The antenna PCB **270** may be configured such that a portion of the antenna **275** protrudes through an opening **242** defined by the yoke **232**. For example, the antenna **275** may extend from a location proximate to the main PCB **260** through the opening **242**. The opening **242** may define a first portion **242A** that is configured to receive a portion of the antenna PCB **270** and a second portion **242B** that is configured to receive the cable **246** connected between the capacitive touch PCB **240** and the main PCB **260**. For example, the second portion **242B** may be configured to enable electrical connection of the capacitive PCB **240** to the main PCB **260**. The first portion **242A** may be longer than the second portion **242B**, for example, to receive the antenna PCB **270**. The first portion **242A** may define a length **L1** and the second portion **242B** may define a length **L2**. The length **L1** may be greater than the length **L2**. It should be appreciated that the opening **242** may define different geometry than shown in FIG. **8**. For example, the length **L1** and the length **L2** may be equal such that the opening **242** is rectangular. In examples, the length **L2** may be greater than the length **L1** such that the first portion **242A** is longer than the second portion **242B**.

[0059] The portion of the antenna **275** that protrudes through the opening **242** may be located within a cavity **271** defined by the actuation member **210**, the bezel **212**, and the yoke **232**. For example, the antenna **275** may extend from the location proximate to the main PCB **260** through the opening **242** in the yoke **232** and into the cavity **271**. A horizontal trace **275B** of the antenna **275** may extend from the location proximate to the main PCB **260** through the opening **242** in the yoke **232** and into the cavity **271**. The horizontal trace **275B** may be connected to a vertical trace **275A** of the antenna **275**. The vertical trace **275A** may be located within the cavity **271** (e.g., entirely within the cavity **271**) when the antenna PCB **270** is attached to the main PCB **260**.

[0060] When the control device **200** is mounted in a metal wallbox, the yoke **232** and the metal wallbox may form a shielded volume around the electrical circuitry on the main PCB **260** (e.g., including the wireless communication circuit). Locating the portion of the antenna **275** within the cavity **271** may allow the vertical trace **275A** to be positioned in front of the yoke **232** (e.g., between the yoke **232** and the actuation member **210**), for example, to allow electrical fields to be generated by and/or received by the antenna **275** and to help avoid interference with metal portions of the control device **200** (e.g., the yoke **232** and/or a metal faceplate). The material (e.g., substrate) of the antenna PCB **270** proximate to the antenna **275** may introduce loss and decrease performance of the antenna **275**. The antenna PCB **270** may define slot(s) **274**, **276** proximate to the antenna **275**. The slot(s) **274**, **276** may be located within the cavity **271** when the antenna PCB **270** is attached to the main PCB **260**. The slot(s) **274**, **276** may be configured to reduce an amount of board material proximate to the antenna **275** such that the performance of the antenna **275** is improved. The slot(s) **274**, **276** may extend through the antenna PCB **270**. For example, the slot(s) **274**, **276** may extend from the first surface **261** of the antenna PCB **270** to the second surface **263** of the antenna PCB **270**.

[0061] The antenna PCB **270** may be located proximate to a vertical midpoint of the control device **200**, for example, so that the antenna **275** is located proximate to the pivot axis **222** of the actuation member **210**. For example, at least a portion of the antenna **275** may be aligned with the pivot axis **222**. When the antenna **275** is located proximate to the pivot axis **222**, interference with the yoke **232** and/or other metal surfaces may be reduced (e.g., minimized). The antenna **275** may be located as far as possible from the capacitive touch PCB **240** and bidirectional semiconductor switch **268**. For example, the antenna PCB **270** may be located substantially at a midpoint between the capacitive touch PCB **240** and the bidirectional semiconductor switch **268**, for example, to avoid interference. The antenna PCB **270** may be located outside of a capacitive touch area, for example, defined by the capacitive touch regions A-E shown in FIG. **9**.

[0062] The main PCB **260** may include one or more ground planes. For example, the main PCB **260** may include a ground plane **266** that is located on the main PCB **260** (e.g., a front side of the main PCB **260**). The antenna **275** may extend perpendicularly from the main PCB **260** (e.g., the ground plane **266**). For example, the ground plane **266** may be configured as a counterpoise for the

antenna **275**. The counterpoise for the antenna **275** may be located on the main PCB **260**. The ground plane **266** may be located within the control device **200** (e.g., inside of the yoke **232**, the enclosure ring **280**, and the rear enclosure **230**), such that the counterpoise for the antenna **275** may be located on an opposite side of the yoke **232** than the vertical trace **275A** of the antenna **275** (e.g., the counterpoise may be submerged in the wallbox in which the control device **200** is installed). The second portion **242A** of the opening **242** in the yoke **232** may be located over the ground place **266**. The second portion **242A** of the opening **242** may allow electrical fields to be generated by and/or received by the antenna **275**.

[0063] The antenna **275** may be a bent pole antenna. For example, the antenna **275** may include a horizontal trace **275B** and a vertical trace **275A**. The antenna PCB **270** and the vertical trace **275A** may be configured such that the antenna **275** is as close to vertical midpoint of the control device **200** (e.g., which may be defined by the pivot axis **222**) as possible (e.g., without causing interference with the actuation member **210** and/or the capacitive touch PCB **240**). The horizontal trace **275B** may extend from the finger **272B** to the vertical trace **275A**. The finger **272B** may be configured to connect the antenna **275** to the wireless communication circuit on the main PCB **260**. The vertical trace **275A** may have a width **L3** and the horizontal trace **275B** may have a width **L4**. The width **L3** may be greater than the width **L4**. The width **L3** of the vertical trace **275A** may be sized to maximize the amount of the antenna **275** in front of the yoke **232**, for example, as shown in FIGS. **6** and **7**. Maximizing the amount of the antenna **275** in front of the yoke **232** may mitigate interference and increase bandwidth capabilities of the antenna **275**. The antenna PCB **270** may comprise pads **278** that are configured to attach (e.g., mount) the antenna PCB **270** to the main PCB **260**. For example, the pads **278** may be located on fingers **272A**, **272C**. It should be appreciated that the vertical trace **275A** and the horizontal trace **275B** of the antenna **275** are not limited to the geometry shown in FIG. **10**. In examples, the width **L4** of the horizontal trace **275B** may be reduced and the width **L3** of the vertical trace **275A** may be increased. It should also be appreciated that although the figures show the antenna **275** on the second surface **273**, the antenna **275** may be on the first surface **271** of the antenna PCB **270**.

[0064] FIG. **11** is a simplified block diagram of an example control device **300** (e.g., a dimmer switch) that may be deployed as, for example, the dimmer switch **110** of the lighting control system **100** shown in FIG. **1** and/or the control device **200** shown in FIGS. **2-9**. The control device **300** may include a hot terminal **H** that may be adapted to be coupled to an AC power source **302**. The control device **300** may include a dimmed hot terminal **DH** that may be adapted to be coupled to an electrical load, such as a lighting load **304**. The control device **300** may include a controllably conductive device **310** coupled in series electrical connection between the AC power source **302** and the lighting load **304**. The controllably conductive device **310** may control the power delivered to the lighting load. The controllably conductive device **310** may include a suitable type of bidirectional semiconductor switch (e.g., such as the bidirectional semiconductor switch **268** shown in FIG. **9**), such as, for example, a triac, a field-effect transistor (FET) in a rectifier bridge, two FETs in anti-series connection, or one or more insulated-gate bipolar junction transistors (IGBTs). An air-gap switch **329** may be coupled in series with the controllably conductive device **310**. The air-gap switch **329** may be opened and closed in response to actuations of an air-gap actuator (e.g., not shown). When the air-gap switch **329** is closed, the controllably conductive device **310** is operable to conduct current to the load. When the air-gap switch **329** is open, the lighting load **304** is disconnected from the AC power source **302**.

[0065] The control device **300** may include a dimmer control circuit **314**. The dimmer control circuit **314** may include one or more of a processor (e.g., a microprocessor), a microcontroller, a programmable logic device (PLD), a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), or any suitable controller or processing device. The dimmer control circuit **314** may be operatively coupled to a control input of the controllably conductive device **310**, for example, via a gate drive circuit **312**. The dimmer control circuit **314** may be used



for rendering the controllably conductive device **310** conductive or non-conductive, for example, to control the amount of power delivered to the lighting load **304**. The dimmer control circuit **314** may receive a control signal representative of the zero-crossing points of the AC mains line voltage of the AC power source **302** from a zero-crossing detector **316**. The dimmer control circuit **314** may be operable to render the controllably conductive device **310** conductive and/or non-conductive at predetermined times relative to the zero-crossing points of the AC waveform using a phase-control dimming technique. The dimmer control circuit **314** may be configured to control the magnitude of a load current conducted through the lighting load(s) so as to control an intensity level of the lighting load **304** across a dimming range between a low-end intensity level  $L_{sub.LE}$  and a high-end intensity level  $L_{sub.HE}$ . For example, the dimmer control circuit **314** may be configured to control the intensity level of the lighting load **304** to a number  $N_{sub.INT}$  (e.g., **255**) of intensity levels between the low-end intensity level  $L_{sub.LE}$  and the high-end intensity level  $L_{sub.HE}$ .

[0066] The control device **300** may include a memory **318**. The memory **318** may be communicatively coupled to the dimmer control circuit **314** for the storage and/or retrieval of, for example, operational settings, such as, lighting presets and associated preset light intensities. The memory **318** may be implemented as an external integrated circuit (IC) or as an internal circuit of the dimmer control circuit **314**. The control device **300** may include a power supply **320**. The power supply **320** may generate a direct-current (DC) supply voltage  $V_{sub.CC}$  for powering the dimmer control circuit **314** and the other low-voltage circuitry of the control device **300**. The power supply **320** may be coupled in parallel with the controllably conductive device **310**. The power supply **320** may be operable to conduct a charging current through the lighting load **304** to generate the DC supply voltage  $V_{sub.CC}$ .

[0067] The dimmer control circuit **314** may be responsive to user inputs received from actuators **330** and/or a touch sensitive device **350**. It should be appreciated that in examples where the control device is a dual-dimmer, the control device may include two touch sensitive devices **350** or a single touch sensitive device that is responsive to two sets of capacitive touch elements, such as capacitive touch pads. The dimmer control circuit **314** may control the controllably conductive device **310** to adjust the intensity level of the lighting load **304** in response to the user inputs (e.g., tactile actuations and/or touch actuations) received via the actuators **330** and/or the touch sensitive device **350**. The dimmer control circuit **314** may receive respective actuator signals from the actuators **330** in response to tactile actuations of the actuators **330** (e.g., in response to movements of the actuators **330**). For example, the actuators **330** may be actuated in response to tactile actuations of an upper portion and/or a lower portion of the actuation member of the control device.

[0068] The touch sensitive device **350** may be configured to detect touch actuations (e.g., point actuations and/or gestures, where, for example, the gestures may be effectuated with or without physical contacts with the touch sensitive device **350**), and provide respective one or more output signals  $V_{sub.OUT}$  to the dimmer control circuit **314** indicating the touch actuations (e.g., indicating a position of one or more touch actuations). The touch sensitive device **350** may detect a touch actuation of the front surface along the light bar and cause the dimmer control circuit **314** to adjust the amount of power delivered to the lighting load **304** accordingly. The dimmer control circuit **314** may be configured to translate the actuator signals received from the actuators **330** and/or the output signals  $V_{sub.OUT}$  received from the touch sensitive device **350** into control data (e.g., one or more control signals). The control circuit **314** may use the control data to drive a drive circuit **312** to control a controllably conductive device **310** to adjust the amount of power delivered to the lighting load **304** and/or cause the control data to be transmitted to the lighting load **304** or a central controller of the load control system.

[0069] The touch sensitive device **350** may include a capacitive touch circuit **352** and a user interface control circuit **354** (e.g., which may be an example of the capacitive touch controller). The capacitive touch circuit **352** that comprises one more capacitive touch elements. For example,

the capacitive touch circuit **352** may comprise one or more capacitive touch pads, such as the receiving capacitive touch pads **244** mounted to the capacitive touch PCB **240** of the control device **200**. In addition, the capacitive touch circuit **352** may comprise one or more capacitive transmission traces **245**. The capacitive touch circuit **352** may provide one or more capacitive receive signals V.sub.RX-A-V.sub.RX-E from the capacitive touch pads of the capacitive touch circuit **352** (e.g., from regions A-E of the receiving capacitive touch pads **244** mounted to the capacitive touch PCB **240** of the control device **200**), where each capacitive receive signal V.sub.RX-A-V.sub.RX-E indicates the capacitance of a capacitive touch pad.

[0070] The user interface control circuit **354** may include one or more of a processor (e.g., a microprocessor), a microcontroller, a programmable logic device (PLD), a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), or any suitable controller or processing device. The user interface control circuit **354** may include a memory and/or may use the memory **318**. The user interface control circuit **354** may be configured to determine or detect a change in the capacitances of the capacitive touch pads of the capacitive touch circuit **352** (e.g., due to a user's finger actuating the front surface **214** of the actuation member **210**), and generate the output signal V.sub.OUT in accordance with the change in capacitance of the capacitive touch pads. The output signal V.sub.OUT may indicate a position of a touch actuation along the front surface of the actuation member (e.g., over the light bar **220**). As noted above, the user interface control circuit **354** may receive one or more capacitive receive signals V.sub.RX-A-V.sub.RX-E from the capacitive touch pads of the capacitive touch circuit **352** (e.g., from regions A-E of the receiving capacitive touch pads **244** mounted to the capacitive touch PCB **240** of the control device **200**), where each capacitive receive signal V.sub.RX-A-V.sub.RX-E indicates the capacitance of a capacitive touch pad.

[0071] The user interface control circuit **354** may be configured to determine the position of the touch actuation along the front surface of the actuation member (e.g., along the light bar **220**) in response to the receive signals V.sub.RX-A-V.sub.RX-E generated by the receiving capacitive touch pads. In response, the user interface control circuit **354** may generate and provide the output signal V.sub.OUT to the dimmer control circuit **314**. For example, the user interface control circuit **354** may be configured to charge capacitances of the capacitive touch pads of the capacitive touch circuit **352**. For example, although not illustrated, the capacitive touch pads of the capacitive touch circuit **352** may be coupled to user interface control circuit **354** via a capacitive transmitting circuit (not shown) and/or a capacitive receiving circuit (not shown). The user interface control circuit **354** may be configured to control the capacitive transmitting circuit to charge capacitances of the capacitive touch pads (e.g., the capacitive touch pads **244**) of the capacitive touch circuit **352**. For example, the capacitive transmitting circuit may be configured to control a capacitive transmitting signal V.sub.TX to pull the transmission traces (e.g., the transmission traces **245**) of the capacitive touch circuit **352** up towards the supply voltage V.sub.CC to charge the capacitances of the capacitive touch pads.

[0072] The user interface control circuit **354** may step through each of the capacitive touch pads of the capacitive touch circuit **352** and process the capacitive receive signals V.sub.RX-A-V.sub.RX-E to detect a change in the capacitance of the respective capacitive touch pad. For example, the user interface control circuit **354** may periodically charge the capacitance of each of the capacitive touch pads of the capacitive touch circuit **352** and then discharge the capacitance of the respective touch pad into a capacitor (not shown) of the user interface control circuit **354** (e.g., which may have a much larger capacitance than the capacitance of each of the capacitive touch pads of the capacitive touch circuit **352**). The user interface control circuit **354** may be configured to compare the voltage across the capacitor of the touch sensitive device **350** to a voltage threshold V.sub.TH and generate an output signal V.sub.OUT, which may indicate when the voltage across the capacitor of the touch sensitive device **350** exceeds the voltage threshold V.sub.TH. For example, the user interface control circuit **354** may charge and discharge the capacitance of each capacitive touch pad a

predetermined number of time (e.g., 500 times) during a sensing interval (e.g., 500  $\mu$ sec) before moving on the next capacitive touch pad of the capacitive touch circuit **352**. The user interface control circuit **354** may be configured to compare a measured voltage provided via one or more of the capacitive touch pads to a voltage threshold. The user interface control circuit **354** may generate an output signal that indicates when the measured voltage exceeds the voltage threshold. The user interface control circuit **354** may be configured to use different voltage thresholds for different capacitive touch pads. For example, the capacitive touch pads may be separated from the touch sensitive surface by varying distances and the different voltage thresholds used may be based on the distance(s) between the capacitive touch pads and the touch sensitive surface.

[0073] The user interface control circuit **354** may be configured to determine a count  $N_{\text{sub.CAP}}$  that indicates how many times the capacitance of the respective capacitive touch pad was charged and discharged before the voltage across the capacitor of the touch sensitive device **350** exceeds the voltage threshold  $V_{\text{sub.TH}}$ . The count  $N_{\text{sub.CAP}}$  may indicate the present capacitance of the respective capacitive touch pad of the capacitive touch circuit **352**. The count  $N_{\text{sub.CAP}}$  for each of the capacitive touch pads of the capacitive touch circuit **352** may represent a sample of the present capacitance of the respective touch pad during the preceding sensing interval. The user interface control circuit **354** may be configured to process the count  $N_{\text{sub.CAP}}$  to determine the present capacitance of the respective touch pad of the capacitive touch circuit **352** using a respective baseline count  $N_{\text{sub.BL}}$  for each of the capacitive touch pads of the capacitive touch circuit **352**. The baseline count  $N_{\text{sub.BL}}$  may indicate an idle capacitance of each of the capacitive touch pads when the front surface of the actuation member (e.g., the light bar) is not being actuated. The user interface control circuit **354** may be configured to determine the respective baseline counts  $N_{\text{sub.BL}}$  for each of the capacitive touch pads of the capacitive touch circuit **352** when the front surface of the actuation member is not being actuated. For example, the baseline count  $N_{\text{sub.BL}}$  may be a long-term average of the count  $N_{\text{sub.CAP}}$  determined by the user interface control circuit **354** from the capacitive receive signals  $V_{\text{sub.RX-A}}$ - $V_{\text{sub.RX-E}}$ .

[0074] After stepping through each of the capacitive touch pads of the capacitive touch circuit **352** (e.g., after a round of capacitive sensing of the capacitive touch pads), the user interface control circuit **354** may process the determined counts  $N_{\text{sub.CAP}}$  for each of the respective capacitive touch pads of the capacitive touch circuit **352** to detect a touch actuation. The user interface control circuit **354** may be configured to determine a change  $\Delta_{\text{sub.CAP}}$  in the count (e.g., which may indicate the capacitance of each of the capacitive touch pad of the capacitive touch circuit **352**) by determining the difference between the respective baseline count  $N_{\text{sub.BL}}$  from the present count  $N_{\text{sub.CAP}}$  of the respective capacitive touch pad, e.g.,  $\Delta_{\text{sub.CAP}} = |N_{\text{sub.CAP}} - N_{\text{sub.BL}}|$ . The user interface control circuit **354** may be configured to determine that capacitive sensitive surface (e.g., the light bar) is being actuated when at least one of the changes  $\Delta_{\text{sub.CAP}}$  in count exceeds a capacitance-change threshold  $TH_{\text{sub.CAP}}$ , which may represent a 0.5% to 1% change in the capacitance, for example.

[0075] The user interface control circuit **354** may be configured to determine a number  $N_{\text{sub.TOUCH-IN}}$  of times (e.g., a number of consecutive rounds of capacitive sensing) that the change  $\Delta_{\text{sub.CAP}}$  in count for one of the capacitive touch pads exceeds the capacitance-change threshold  $TH_{\text{sub.CAP}}$ . The user interface control circuit **354** may be configured to enter an active touch mode when the number  $N_{\text{sub.TOUCH-IN}}$  exceeds a touch-in threshold  $TH_{\text{sub.TOUCH-IN}}$  (e.g., such as two, three, four, five, six, seven, or eight). For example, the user interface control circuit **354** may detect a touch actuation when the number  $N_{\text{sub.TOUCH-IN}}$  exceeds a touch-in threshold  $TH_{\text{sub.TOUCH-IN}}$ . When in the active touch mode, the user interface control circuit **354** may be configured to determine a number  $N_{\text{sub.TOUCH-OUT}}$  of times (e.g., a number of consecutive rounds of capacitive sensing) that the change  $\Delta_{\text{sub.CAP}}$  in count for one of the capacitive touch pads does not exceed the capacitance-change threshold  $TH_{\text{sub.CAP}}$ . The user interface control circuit **354** may be configured to exit the active touch mode when the number

N.sub.TOUCH-OUT exceeds a touch-out threshold TH.sub.TOUCH-OUT.

[0076] While in the active touch mode, the user interface control circuit **354** may be configured to determine the position of the touch actuation along the touch sensitive surface (e.g., the light bar) in response to ratios of the changes  $\Delta$ .sub.CAP in the count for each of the capacitive touch pads of the capacitive touch circuit **352** (e.g., in response to the receive signals V.sub.RX-A-V.sub.RX-E generated by the receiving capacitive touch pads). For example, the ratio of the change  $\Delta$ .sub.CAP in the count for region B to the change  $\Delta$ .sub.CAP in the count for region C of the receiving capacitive touch pads **244** of the control device **200** may indicate a position of a touch actuation along the light bar **220** between the regions B and C.

[0077] The user interface control circuit **354** may provide an output signal V.sub.OUT to the dimmer control circuit **314** in response to detecting a touch actuation along the touch sensitive surface of the control device **300** (e.g., in response to detecting a touch actuation along the light bar **220**). The output signal V.sub.OUT may indicate a position of the touch along the front surface of the actuation member. The dimmer control circuit **314** may be configured to translate the output signal V.sub.OUT into control data (e.g., one or more control signals) for controlling one or more electrical loads. For example, the dimmer control circuit **314** may use the control data to drive a drive circuit **312** to control a controllably conductive device **310** to adjust the amount of power delivered to the lighting load **304** and/or may cause the control data to be transmitted to the lighting load **304**, another load control device, and/or a system controller of the load control system via a communication circuit **322**.

[0078] The user interface control circuit **354** may generate a touch actuation signal V.sub.ACT that may indicate that a touch is present along the touch sensitive surface of the actuation member of the control device. The user interface control circuit **354** may provide the touch actuation signal V.sub.ACT to the dimmer control circuit **314**. For example, the user interface control circuit **354** may drive the touch actuation signal V.sub.ACT high upon detecting a touch actuation along the touch sensitive surface to indicate that the control device is operating in active touch mode, and otherwise drive the touch activation signal V.sub.ACT low.

[0079] Although described with reference to the user interface control circuit **354**, it should be appreciated that in some examples the control device **300** may include a single control circuit, such as the dimmer control circuit **314**, and the processing performed by the user interface control circuit **354** may be performed by the dimmer control circuit **314**.

[0080] The control device **300** may comprise the wireless communication circuit **322**. The wireless communication circuit **322** may include for example, a radio-frequency (RF) transceiver coupled to an antenna **324** (e.g., the antenna **275**) for transmitting and/or receiving RF signals. The wireless communication circuit **322** may also include an RF transmitter for transmitting RF signals, an RF receiver for receiving RF signals, or an infrared (IR) transmitter and/or receiver for transmitting and/or receiving IR signals. The wireless communication circuit **322** may be configured to transmit a control signal that includes the control data (e.g., a digital message) generated by the dimmer control circuit **314** to the lighting load **304**. For example, the wireless communication circuit **322** may be coupled to an antenna (e.g., such as antenna **275** shown in FIGS. **6**, **7**, and **10**) for transmitting one or more messages to one or more lighting loads (e.g., lighting load **304**). As described herein, the control data may be generated in response to a user input (e.g., a point actuation or a gesture) to adjust one or more operational aspects of the lighting load **304**. The control data may include a command and/or identification information (e.g., such as a unique identifier) associated with the control device **300**. In addition to or in lieu of transmitting the control signal to the lighting load **304**, the wireless communication circuit **322** may be controlled to transmit the control signal to a central controller of the lighting control system.

[0081] The dimmer control circuit **314** may be configured to illuminate visual indicators **360** (e.g., LEDs) to provide feedback of a status of the lighting load **304**, in response to receiving indications of actuations of capacitive touch pads, to indicate a status of the control device **300**, and/or to assist

with a control operation (e.g., to provide a color gradient for controlling the color of the lighting load **304**, to present backlit virtual buttons for preset, zone, or operational mode selection, etc.). The visual indicators **360** may be configured to illuminate a light bar (e.g., the light bar **220**) and/or to serve as indicators of various conditions. As one example, touch sensitive device **350** may be used to allow a user to control dimming of a lighting load, with visual indicators **360**, through illumination of light bar **220**, showing the degree of dimming (e.g., increased illumination of the light bar to show increased intensity of the load).

## Claims

1. A control device configured to control one or more electrical loads, the control device comprising: an actuation member having a front surface defining a touch sensitive surface configured to receive a touch actuation along at least a portion of the touch sensitive surface; a metal yoke that is configured to attach the control device to a wallbox, the metal yoke defining an opening, wherein the control device defines a cavity between the actuation member and the metal yoke; a main printed circuit board having a control circuit and a wireless communication circuit mounted thereto, the main printed circuit board located on an opposite side of the metal yoke than the actuation member; a capacitive touch printed circuit board having one or more receiving capacitive touch pads mounted to the capacitive touch printed circuit board, behind the actuation member, wherein the control circuit of the main printed circuit board is responsive to the capacitive touch printed circuit board to detect the touch actuation along at least the portion of the touch sensitive surface; and an antenna printed circuit board electrically connected to the main printed circuit board, the antenna printed circuit board having an antenna mounted thereto, the antenna extending substantially perpendicular from the main printed circuit board and through the opening in the metal yoke such that a portion of the antenna is located within the cavity, wherein the wireless communication circuit is coupled to the antenna for receiving messages that include one or more commands for controlling the one or more electrical loads.
2. The control device of claim 1, wherein the antenna comprises a monopole antenna.
3. The control device of claim 2, wherein the monopole antenna comprises; a horizontal trace that extends from a front side of the metal yoke to a rear side of the metal yoke, and a vertical trace connected to the horizontal trace, the vertical trace comprising the portion of the monopole antenna located within the cavity.
4. The control device of claim 3, wherein the vertical trace of the monopole antenna defines a first width and the horizontal trace of the monopole antenna defines a second width, and wherein the first width is greater than the second width.
5. The control device of claim 4, wherein the antenna printed circuit board comprises a plurality of fingers that are configured to connect the antenna printed circuit board to the main printed circuit board.
6. The control device of claim 4, wherein the antenna printed circuit board comprises pads on one or more of the plurality of fingers that are configured to attach the antenna printed circuit board to the main printed circuit board.
7. The control device of claim 6, wherein the main printed circuit board comprises a plurality of slots configured to receive the plurality of fingers.
8. The control device of claim 4, wherein the antenna printed circuit board comprises one or more slots proximate to the monopole antenna, the one or more slots configured to reduce an amount of board material proximate to the monopole antenna.
9. The control device of claim 8, wherein a first slot of the one or more slots is located proximate to the vertical trace of the monopole antenna and a second slot of the one or more slots is located proximate to the horizontal trace of the monopole antenna.
10. The control device of claim 2, wherein the monopole antenna extends from a location

proximate to the main printed circuit board through the opening in the metal yoke and into the cavity.

**11.** The control device of claim 10, wherein the monopole antenna is located substantially at a midpoint between the capacitive touch printed circuit board and a bidirectional semiconductor switch of the control device.

**12.** The control device of claim 11, wherein the monopole antenna is located outside of a capacitive touch area defined by the capacitive touch printed circuit board.

**13.** The control device of claim 1, wherein the capacitive touch printed circuit board is affixed to the actuation member such that the capacitive touch printed circuit board is configured to move with the actuation member in response to tactile actuations of the actuation member.

**14.** The control device of claim 13, wherein the actuation member is configured to pivot about a pivot axis.

**15.** The control device of claim 14, wherein the actuation member is configured to actuate a tactile switch mounted to the main printed circuit board in response to tactile actuations of the actuation member.

**16.** A control device configured to control one or more electrical loads, the control device comprising: an actuation member having a front surface defining a touch sensitive surface configured to receive a touch actuation along at least a portion of the touch sensitive surface; a metal yoke that is configured to attach the control device to a wallbox, the metal yoke defining an opening, wherein the control device defines a cavity between the actuation member and the metal yoke; a main printed circuit board having a control circuit and a wireless communication circuit mounted thereto, the main printed circuit board located on an opposite side of the metal yoke than the actuation member; a capacitive touch printed circuit board having one or more receiving capacitive touch pads mounted to the capacitive touch printed circuit board, behind the actuation member, wherein the control circuit of the main printed circuit board is responsive to the capacitive touch printed circuit board to detect the touch actuation along at least the portion of the touch sensitive surface; and an antenna printed circuit board electrically connected to the main printed circuit board, the antenna printed circuit board having an antenna mounted thereto, the antenna extending substantially perpendicular from the main printed circuit board and through the opening in the metal yoke such that a portion of the antenna is located within the cavity, wherein the wireless communication circuit is coupled to the antenna for receiving messages that include one or more commands for controlling the one or more electrical loads, and wherein a controllably conductive device and a drive circuit are mounted to the main printed circuit board, the drive circuit operatively coupled to a control input of the controllably conductive device for rendering the controllably conductive device conductive or non-conductive to control an amount of power delivered to the one or more electrical loads.

**17.** The control device of claim 16, wherein a tactile switch is mounted to the main printed circuit board.

**18.** The control device of claim 17, wherein the tactile switch is configured to be actuated in response to the actuation member pivoting.

**19.** The control device of claim 17, wherein the control device is configured to turn the one or more electrical loads on or off in response to actuation of the tactile switch.

**20.** The control device of claim 16, wherein the capacitive touch printed circuit board is affixed to the actuation member such that the capacitive touch printed circuit board is configured to move with the actuation member in response to tactile actuations of the actuation member.

---