



US012391183B2

(12) **United States Patent**
Blank et al.

(10) **Patent No.:** **US 12,391,183 B2**

(45) **Date of Patent:** ***Aug. 19, 2025**

(54) **VEHICULAR VIDEO CAMERA DISPLAY SYSTEM**

(71) Applicant: **Magna Mirrors of America, Inc.**,
Holland, MI (US)

(72) Inventors: **Rodney K. Blank**, Zeeland, MI (US);
Mark L. Larson, Grand Haven, MI (US);
Niall R. Lynam, Holland, MI (US)

(73) Assignee: **Magna Mirrors of America, Inc.**,
Holland, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/794,058**

(22) Filed: **Aug. 5, 2024**

(65) **Prior Publication Data**

US 2024/0391385 A1 Nov. 28, 2024

Related U.S. Application Data

(63) Continuation of application No. 18/502,129, filed on Nov. 6, 2023, now Pat. No. 12,054,098, which is a
(Continued)

(51) **Int. Cl.**
H04N 5/262 (2006.01)
B60R 1/12 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B60R 1/12** (2013.01); **G02B 27/01**
(2013.01); **G02F 1/1533** (2013.01); **G02F 1/157** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC B60R 1/12; B60R 2001/1215; B60R 2001/1253; G02B 2027/0118;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,166,303 A 7/1939 Hodney et al.

2,414,223 A 1/1947 De Virgilis

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2001064481 A2 9/2001


Primary Examiner — Md N Haque

(74) *Attorney, Agent, or Firm* — HONIGMAN LLP

(57) **ABSTRACT**

A vehicular video camera display system includes an interior rearview mirror assembly having a mirror head accommodating an electrochromic reflective element, with a video display device disposed in the mirror head behind the electrochromic reflective element. With the interior rearview mirror assembly disposed at the in-cabin side of a windshield of a vehicle, a video display screen of the video display device is operable to display video images that are viewable through the electrochromic reflective element by a driver of the vehicle. Image data captured by a rearward-viewing video camera is communicated via a cable as a digital signal from the rearward-viewing video camera to control circuitry. The video display device displays video images that are derived, at least in part, from image data communicated from the rearward-viewing video camera to the control circuitry. The control circuitry controls display at the video display device of the video images.

49 Claims, 31 Drawing Sheets



Related U.S. Application Data

continuation of application No. 18/167,930, filed on Feb. 13, 2023, now Pat. No. 11,807,164, which is a continuation of application No. 17/303,404, filed on May 28, 2021, now Pat. No. 11,577,652, which is a continuation of application No. 16/812,864, filed on Mar. 9, 2020, now Pat. No. 11,021,107, which is a continuation of application No. 15/344,865, filed on Nov. 7, 2016, now Pat. No. 10,583,782, which is a continuation of application No. 12/578,732, filed on Oct. 14, 2009, now Pat. No. 9,487,144.

- (60) Provisional application No. 61/219,214, filed on Jun. 22, 2009, provisional application No. 61/187,069, filed on Jun. 15, 2009, provisional application No. 61/117,301, filed on Nov. 24, 2008, provisional application No. 61/105,903, filed on Oct. 16, 2008.

(51) **Int. Cl.**

G02B 27/01 (2006.01)
G02F 1/153 (2006.01)
G02F 1/157 (2006.01)
H04N 23/63 (2023.01)
H10K 59/50 (2023.01)
H10K 59/65 (2023.01)
G02B 5/00 (2006.01)

(52) **U.S. Cl.**

CPC **H04N 23/63** (2023.01); **H10K 59/50**
 (2023.02); **H10K 59/65** (2023.02); **B60R**
2001/1215 (2013.01); **B60R 2001/1253**
 (2013.01); **G02B 5/003** (2013.01); **G02B**
2027/0118 (2013.01); **G02B 2027/0138**
 (2013.01); **G02B 2027/014** (2013.01)

(58) **Field of Classification Search**

CPC **G02B 2027/0138**; **G02B 2027/014**; **G02B**
27/01; **G02B 5/003**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,004,473 A 10/1961 Athur et al.
 3,075,430 A 1/1963 Woodward et al.
 3,141,393 A 7/1964 Platt
 3,152,216 A 10/1964 Woodward
 3,185,020 A 5/1965 Thelen
 3,280,701 A 10/1966 Donnelly et al.
 3,432,225 A 3/1969 Rock
 3,451,741 A 6/1969 Manos
 3,453,038 A 7/1969 Kissa et al.
 3,467,465 A 9/1969 Noord
 3,521,941 A 7/1970 Deb et al.
 3,543,018 A 11/1970 Barcus et al.
 3,557,265 A 1/1971 Chisholm et al.
 3,565,985 A 2/1971 Schrenk et al.
 3,628,851 A 12/1971 Robertson
 3,676,668 A 7/1972 Collins et al.
 3,689,695 A 9/1972 Rosenfield et al.
 3,711,176 A 1/1973 Alfrey, Jr. et al.
 3,781,090 A 12/1973 Sumita
 3,806,229 A 4/1974 Schoot et al.
 3,807,832 A 4/1974 Castellion
 3,821,590 A 6/1974 Kosman et al.
 3,860,847 A 1/1975 Carley
 3,870,404 A 3/1975 Wilson et al.
 3,876,287 A 4/1975 Sprokel
 3,978,190 A 8/1976 Kurz, Jr. et al.
 3,985,424 A 10/1976 Steinacher
 4,006,546 A 2/1977 Anderson et al.
 4,035,681 A 7/1977 Savage, Jr.

4,052,712 A 10/1977 Ohama et al.
 4,075,468 A 2/1978 Marcus
 4,088,400 A 5/1978 Assouline et al.
 4,093,364 A 6/1978 Miller
 4,109,235 A 8/1978 Bouthors
 4,139,234 A 2/1979 Morgan
 4,171,875 A 10/1979 Taylor et al.
 4,174,152 A 11/1979 Giglia et al.
 4,211,955 A 7/1980 Ray
 4,214,266 A 7/1980 Myers
 4,221,955 A 9/1980 Joslyn
 4,228,490 A 10/1980 Thillays
 4,247,870 A 1/1981 Gabel et al.
 4,257,703 A 3/1981 Goodrich
 4,277,804 A 7/1981 Robison
 4,281,899 A 8/1981 Oskam
 4,288,814 A 9/1981 Talley et al.
 4,306,768 A 12/1981 Egging
 4,310,851 A 1/1982 Pierrat
 4,331,382 A 5/1982 Graff
 4,338,000 A 7/1982 Kamimori et al.
 4,377,613 A 3/1983 Gordon
 4,398,805 A 8/1983 Cole
 4,419,386 A 12/1983 Gordon
 4,420,238 A 12/1983 Felix
 4,425,717 A 1/1984 Marcus
 4,435,042 A 3/1984 Wood et al.
 4,435,048 A 3/1984 Kamimori et al.
 4,436,371 A 3/1984 Wood et al.
 4,443,057 A 4/1984 Bauer et al.
 4,446,171 A 5/1984 Thomas
 4,465,339 A 8/1984 Baucke et al.
 4,473,695 A 9/1984 Wrighton et al.
 4,490,227 A 12/1984 Bitter
 4,499,451 A 2/1985 Suzuki et al.
 4,524,941 A 6/1985 Wood et al.
 4,546,551 A 10/1985 Franks
 4,561,625 A 12/1985 Weaver
 4,580,196 A 4/1986 Task
 4,581,827 A 4/1986 Higashi
 4,588,267 A 5/1986 Pastore
 4,603,946 A 8/1986 Kato et al.
 4,626,850 A 12/1986 Chey
 4,630,109 A 12/1986 Barton
 4,630,904 A 12/1986 Pastore
 4,638,287 A 1/1987 Umebayashi et al.
 4,646,210 A 2/1987 Skogler et al.
 4,652,090 A 3/1987 Uchikawa et al.
 4,665,430 A 5/1987 Hiroyasu
 4,671,619 A 6/1987 Kamimori et al.
 4,692,798 A 9/1987 Seko et al.
 4,694,295 A 9/1987 Miller et al.
 4,702,566 A 10/1987 Tukude
 4,712,879 A 12/1987 Lynam et al.
 4,713,685 A 12/1987 Nishimura et al.
 4,729,076 A 3/1988 Masami et al.
 4,731,669 A 3/1988 Hayashi et al.
 4,733,335 A 3/1988 Serizawa et al.
 4,733,336 A 3/1988 Skogler et al.
 4,740,838 A 4/1988 Mase et al.
 4,761,061 A 8/1988 Nishiyama et al.
 4,780,752 A 10/1988 Angerstein et al.
 4,781,436 A 11/1988 Ambruster
 4,789,904 A 12/1988 Peterson
 4,793,690 A 12/1988 Gahan et al.
 4,793,695 A 12/1988 Wada et al.
 4,799,768 A 1/1989 Gahan
 4,807,096 A 2/1989 Skogler et al.
 4,825,232 A 4/1989 Howdle
 4,826,289 A 5/1989 Vandenbrink et al.
 4,847,772 A 7/1989 Michalopoulos et al.
 4,855,161 A 8/1989 Moser et al.
 4,859,867 A 8/1989 Larson et al.
 4,862,594 A 9/1989 Schierbeek et al.
 4,871,917 A 10/1989 O'Farrell et al.
 4,872,051 A 10/1989 Dye
 4,882,565 A 11/1989 Gallmeyer
 4,883,349 A 11/1989 Mittelhauser
 4,886,960 A 12/1989 Molyneux et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

4,892,345	A	1/1990	Rachael, III	5,285,060	A	2/1994	Larson et al.
4,902,108	A	2/1990	Byker	5,289,321	A	2/1994	Secor
4,910,591	A	3/1990	Petrossian et al.	5,296,924	A	3/1994	de Saint Blancard et al.
4,916,374	A	4/1990	Schierbeek et al.	5,303,205	A	4/1994	Gauthier et al.
4,926,170	A	5/1990	Beggs et al.	5,304,980	A	4/1994	Maekawa
4,930,742	A	6/1990	Schofield et al.	5,305,012	A	4/1994	Faris
4,935,665	A	6/1990	Murata	5,307,136	A	4/1994	Saneyoshi
4,936,533	A	6/1990	Adams et al.	5,313,335	A	5/1994	Gray et al.
4,937,796	A	6/1990	Tendler	5,325,096	A	6/1994	Pakett
4,937,945	A	7/1990	Schofield et al.	5,325,386	A	6/1994	Jewell et al.
4,943,796	A	7/1990	Lee	5,327,288	A	7/1994	Wellington
4,948,242	A	8/1990	Desmond et al.	5,330,149	A	7/1994	Haan et al.
4,953,305	A	9/1990	Van Lente et al.	5,331,312	A	7/1994	Kudoh
4,956,591	A	9/1990	Schierbeek et al.	5,331,358	A	7/1994	Schurle et al.
4,959,247	A	9/1990	Moser et al.	5,339,075	A	8/1994	Abst et al.
4,959,865	A	9/1990	Stettiner et al.	5,339,529	A	8/1994	Lindberg
4,970,653	A	11/1990	Kenue	5,341,437	A	8/1994	Nakayama
4,973,844	A	11/1990	O'Farrell et al.	D351,370	S	10/1994	Lawlor et al.
4,987,357	A	1/1991	Masaki	5,355,118	A	10/1994	Fukuhara
4,996,083	A	2/1991	Moser et al.	5,355,284	A	10/1994	Roberts
5,001,558	A	3/1991	Burley et al.	5,361,190	A	11/1994	Roberts et al.
5,005,213	A	4/1991	Hanson et al.	5,371,659	A	12/1994	Pastrick et al.
5,006,971	A	4/1991	Jenkins	5,373,482	A	12/1994	Gauthier
5,014,167	A	5/1991	Roberts	5,386,285	A	1/1995	Asayama
5,016,996	A	5/1991	Ueno	5,406,395	A	4/1995	Wilson et al.
5,027,200	A	6/1991	Petrossian et al.	5,406,414	A	4/1995	O'Farrell et al.
5,038,255	A	8/1991	Nishihashi et al.	5,408,357	A	4/1995	Beukema
5,056,899	A	10/1991	Warszawski	5,410,346	A	4/1995	Saneyoshi et al.
5,058,851	A	10/1991	Lawlor et al.	5,414,461	A	5/1995	Kishi et al.
5,066,108	A	11/1991	McDonald	5,416,313	A	5/1995	Larson et al.
5,066,112	A	11/1991	Lynam et al.	5,416,478	A	5/1995	Morinaga
5,073,012	A	12/1991	Lynam	5,418,610	A	5/1995	Fischer
5,076,673	A	12/1991	Lynam et al.	5,422,756	A	6/1995	Weber
5,076,674	A	12/1991	Lynam	5,424,726	A	6/1995	Beymer
5,096,287	A	3/1992	Kakinami et al.	5,424,865	A	6/1995	Lynam
5,100,095	A	3/1992	Haan et al.	5,424,952	A	6/1995	Asayama
5,105,127	A	4/1992	Lavaud et al.	5,430,431	A	7/1995	Nelson
5,115,346	A	5/1992	Lynam	5,432,496	A	7/1995	Lin
5,117,346	A	5/1992	Gard	5,439,305	A	8/1995	Santo
5,121,200	A	6/1992	Choi	5,444,478	A	8/1995	Lelong et al.
5,128,799	A	7/1992	Byker	5,446,576	A	8/1995	Lynam et al.
5,131,154	A	7/1992	Schierbeek et al.	5,455,716	A	10/1995	Suman et al.
5,135,298	A	8/1992	Feltman	5,461,361	A	10/1995	Moore
5,136,483	A	8/1992	Schoniger et al.	5,469,298	A	11/1995	Suman et al.
5,140,455	A	8/1992	Varaprasad et al.	5,475,366	A	12/1995	Van Lente et al.
5,142,407	A	8/1992	Varaprasad et al.	5,475,494	A	12/1995	Nishida et al.
5,151,816	A	9/1992	Varaprasad et al.	5,481,409	A	1/1996	Roberts
5,151,824	A	9/1992	O'Farrell	5,483,453	A	1/1996	Uemura et al.
5,160,200	A	11/1992	Cheselske	5,485,161	A	1/1996	Vaughn
5,160,201	A	11/1992	Wrobel	5,485,378	A	1/1996	Franke et al.
5,173,881	A	12/1992	Sindle	5,487,522	A	1/1996	Hook
5,178,448	A	1/1993	Adams et al.	5,488,496	A	1/1996	Pine
5,179,471	A	1/1993	Caskey et al.	5,497,305	A	3/1996	Pastrick et al.
5,184,956	A	2/1993	Langlais et al.	5,497,306	A	3/1996	Pastrick
5,189,537	A	2/1993	O'Farrell	5,500,760	A	3/1996	Varaprasad et al.
5,193,029	A	3/1993	Schofield et al.	5,510,983	A	4/1996	Lino
5,197,562	A	3/1993	Kakinami et al.	5,515,448	A	5/1996	Nishitani
5,207,492	A	5/1993	Roberts	5,519,621	A	5/1996	Wortham
5,214,408	A	5/1993	Asayama	5,521,760	A	5/1996	De Young et al.
5,217,794	A	6/1993	Schrenk	5,523,811	A	6/1996	Wada et al.
5,223,814	A	6/1993	Suman	5,525,264	A	6/1996	Cronin et al.
5,223,844	A	6/1993	Mansell et al.	5,528,474	A	6/1996	Roney et al.
5,229,975	A	7/1993	Truesdell et al.	5,529,138	A	6/1996	Shaw et al.
5,230,400	A	7/1993	Kakinami et al.	5,530,240	A	6/1996	Larson et al.
5,233,461	A	8/1993	Dorman et al.	5,530,420	A	6/1996	Tsuchiya et al.
5,235,316	A	8/1993	Qualizza	5,530,421	A	6/1996	Marshall et al.
5,239,405	A	8/1993	Varaprasad et al.	5,535,056	A	7/1996	Caskey et al.
5,239,406	A	8/1993	Lynam	5,535,144	A	7/1996	Kise
5,243,417	A	9/1993	Pollard	5,539,397	A	7/1996	Asanuma et al.
5,245,422	A	9/1993	Borcherts et al.	5,541,590	A	7/1996	Nishio
5,252,354	A	10/1993	Cronin et al.	5,550,677	A	8/1996	Schofield et al.
5,253,109	A	10/1993	O'Farrell et al.	5,566,224	A	10/1996	ul Azam et al.
5,255,442	A	10/1993	Schierbeek et al.	5,567,360	A	10/1996	Varaprasad et al.
5,277,986	A	1/1994	Cronin et al.	5,568,316	A	10/1996	Schrenk et al.
5,280,555	A	1/1994	Ainsburg	5,570,127	A	10/1996	Schmidt
				5,572,354	A	11/1996	Desmond et al.
				5,574,443	A	11/1996	Hsieh
				5,576,687	A	11/1996	Blank et al.
				5,576,854	A	11/1996	Schmidt et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,576,975 A	11/1996	Sasaki et al.	5,798,688 A	8/1998	Schofield
5,587,236 A	12/1996	Agrawal et al.	5,802,727 A	9/1998	Blank et al.
5,602,542 A	2/1997	Widmann	5,803,579 A	9/1998	Turnbull et al.
5,608,550 A	3/1997	Epstein et al.	5,805,367 A	9/1998	Kanazawa
5,610,756 A	3/1997	Lynam et al.	5,806,879 A	9/1998	Hamada et al.
5,611,966 A	3/1997	Varaprasad et al.	5,806,965 A	9/1998	Deese
5,615,023 A	3/1997	Yang	5,808,197 A	9/1998	Dao
5,615,857 A	4/1997	Hook	5,808,566 A	9/1998	Behr et al.
5,617,085 A	4/1997	Tsutsumi et al.	5,808,589 A	9/1998	Ferguson
5,626,800 A	5/1997	Williams et al.	5,808,713 A	9/1998	Broer et al.
5,631,089 A	5/1997	Center, Jr. et al.	5,808,777 A	9/1998	Lynam et al.
5,631,638 A	5/1997	Kaspar et al.	5,808,778 A	9/1998	Bauer et al.
5,631,639 A	5/1997	Hibino et al.	5,812,321 A	9/1998	Schierbeek et al.
5,632,092 A	5/1997	Blank et al.	5,813,745 A	9/1998	Fant, Jr. et al.
5,632,551 A	5/1997	Roney et al.	5,818,625 A	10/1998	Forgette et al.
5,634,709 A	6/1997	Iwama	5,820,097 A	10/1998	Spooner
5,642,238 A	6/1997	Sala	5,820,245 A	10/1998	Desmond et al.
5,644,851 A	7/1997	Blank et al.	5,823,654 A	10/1998	Pastrick et al.
5,646,614 A	7/1997	Abersfelder et al.	5,825,527 A	10/1998	Forgette et al.
5,649,756 A	7/1997	Adams et al.	5,837,994 A	11/1998	Stam et al.
5,649,758 A	7/1997	Dion	5,844,505 A	12/1998	Van Ryzin
5,650,765 A	7/1997	Park	5,848,373 A	12/1998	DeLorme et al.
5,661,455 A	8/1997	Van Lente et al.	5,850,176 A	12/1998	Kinoshita et al.
5,662,375 A	9/1997	Adams et al.	5,863,116 A	1/1999	Pastrick et al.
5,666,157 A	9/1997	Aviv	5,867,801 A	2/1999	Denny
5,668,663 A	9/1997	Varaprasad et al.	5,871,275 A	2/1999	O'Farrell et al.
5,668,675 A	9/1997	Fredricks	5,877,707 A	3/1999	Kowalick
5,669,698 A	9/1997	Veldman et al.	5,877,897 A	3/1999	Schofield et al.
5,669,699 A	9/1997	Pastrick et al.	5,878,353 A	3/1999	ul Azam et al.
5,669,704 A	9/1997	Pastrick	5,878,370 A	3/1999	Olson
5,669,705 A	9/1997	Pastrick et al.	5,879,074 A	3/1999	Pastrick
5,670,935 A	9/1997	Schofield et al.	5,883,605 A	3/1999	Knapp
5,671,996 A	9/1997	Bos et al.	5,883,739 A	3/1999	Ashihara et al.
5,673,994 A	10/1997	Fant, Jr. et al.	5,888,431 A	3/1999	Tonar et al.
5,673,999 A	10/1997	Koenck	5,899,551 A	5/1999	Neijzen et al.
5,680,123 A	10/1997	Lee	5,899,956 A	5/1999	Chan
5,680,245 A	10/1997	Lynam	5,904,729 A	5/1999	Ruzicka
5,686,975 A	11/1997	Lipton	5,910,854 A	6/1999	Varaprasad et al.
5,689,241 A	11/1997	Clarke, Sr. et al.	5,914,815 A	6/1999	Bos
5,691,848 A	11/1997	Van Lente et al.	5,917,664 A	6/1999	O'Neill et al.
5,692,819 A	12/1997	Mitsutake et al.	5,918,180 A	6/1999	Dimino
5,699,044 A	12/1997	Van Lente et al.	5,923,027 A	7/1999	Stam et al.
5,708,410 A	1/1998	Blank et al.	5,923,457 A	7/1999	Byker et al.
5,708,415 A	1/1998	Van Lente et al.	5,924,212 A	7/1999	Domanski
5,708,857 A	1/1998	Ishibashi	5,928,572 A	7/1999	Tonar et al.
5,715,093 A	2/1998	Schierbeek et al.	5,929,786 A	7/1999	Schofield et al.
5,724,187 A	3/1998	Varaprasad et al.	5,938,321 A	8/1999	Bos et al.
5,724,316 A	3/1998	Brunts	5,938,721 A	8/1999	Dussell et al.
5,729,194 A	3/1998	Spears et al.	5,940,011 A	8/1999	Agravante et al.
5,737,226 A	4/1998	Olson et al.	5,940,120 A	8/1999	Frankhouse et al.
5,741,966 A	4/1998	Handfield et al.	5,940,201 A	8/1999	Ash et al.
5,745,050 A	4/1998	Nakagawa	5,942,895 A	8/1999	Popovic et al.
5,745,266 A	4/1998	Smith	5,949,331 A	9/1999	Schofield et al.
5,748,287 A	5/1998	Takahashi et al.	5,956,079 A	9/1999	Ridgley
5,751,211 A	5/1998	Shirai et al.	5,956,181 A	9/1999	Lin
5,751,246 A	5/1998	Hertel	5,959,367 A	9/1999	O'Farrell et al.
5,751,390 A	5/1998	Crawford et al.	5,959,555 A	9/1999	Furuta
5,751,489 A	5/1998	Caskey et al.	5,959,577 A	9/1999	Fan et al.
5,754,099 A	5/1998	Nishimura et al.	5,963,247 A	10/1999	Banitt
5,760,828 A	6/1998	Cortes	5,965,247 A	10/1999	Jonza et al.
5,760,931 A	6/1998	Saburi et al.	5,971,552 A	10/1999	O'Farrell et al.
5,760,962 A	6/1998	Schofield et al.	5,973,760 A	10/1999	Dehmlow
5,761,094 A	6/1998	Olson et al.	5,975,715 A	11/1999	Bauder
5,762,823 A	6/1998	Hikmet	5,984,482 A	11/1999	Rumsey et al.
5,767,793 A	6/1998	Agravante et al.	5,986,730 A	11/1999	Hansen et al.
5,775,762 A	7/1998	Vitito	5,990,469 A	11/1999	Bechtel et al.
5,786,772 A	7/1998	Schofield et al.	5,998,617 A	12/1999	Srinivasa et al.
5,788,357 A	8/1998	Muth et al.	5,998,929 A	12/1999	Bechtel et al.
5,790,973 A	8/1998	Blaker et al.	6,000,823 A	12/1999	Desmond et al.
5,793,308 A	8/1998	Rosinski et al.	6,001,486 A	12/1999	Varaprasad et al.
5,793,420 A	8/1998	Schmidt	6,002,511 A	12/1999	Varaprasad et al.
5,796,094 A	8/1998	Schofield et al.	6,002,544 A	12/1999	Yatsu
5,796,176 A	8/1998	Kramer et al.	6,007,222 A	12/1999	Thau
5,798,057 A	8/1998	Hikmet	6,008,486 A	12/1999	Stam et al.
5,798,575 A	8/1998	O'Farrell et al.	6,008,871 A	12/1999	Okumura
			6,009,359 A	12/1999	El-Hakim et al.
			6,016,035 A	1/2000	Eberspacher et al.
			6,016,215 A	1/2000	Byker
			6,019,411 A	2/2000	Carter et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,019,475	A	2/2000	Lynam et al.	6,173,501	B1	1/2001	Blank et al.
6,021,371	A	2/2000	Fultz	6,175,164	B1	1/2001	O'Farrell et al.
6,023,229	A	2/2000	Bugno et al.	6,175,300	B1	1/2001	Kendrick
6,025,872	A	2/2000	Ozaki et al.	6,176,602	B1	1/2001	Pastrick et al.
6,037,689	A	3/2000	Bingle et al.	6,178,034	B1	1/2001	Allemand et al.
6,042,253	A	3/2000	Fant, Jr. et al.	6,178,377	B1	1/2001	Ishihara et al.
6,045,243	A	4/2000	Muth et al.	6,182,006	B1	1/2001	Meek
6,045,643	A	4/2000	Byker et al.	6,183,119	B1	2/2001	Desmond et al.
6,046,766	A	4/2000	Sakata	6,184,679	B1	2/2001	Popovic et al.
6,046,837	A	4/2000	Yamamoto	6,184,781	B1	2/2001	Ramakesavan
6,049,171	A	4/2000	Stam et al.	6,185,492	B1	2/2001	Kagawa et al.
6,060,989	A	5/2000	Gehlot	6,185,501	B1	2/2001	Smith et al.
6,061,002	A	5/2000	Weber et al.	6,188,505	B1	2/2001	Lompfrey et al.
6,064,508	A	5/2000	Forgette et al.	6,191,704	B1	2/2001	Takenaga et al.
6,065,840	A	5/2000	Caskey et al.	6,196,688	B1	3/2001	Caskey et al.
6,067,111	A	5/2000	Hahn et al.	6,198,409	B1	3/2001	Schofield et al.
6,067,500	A	5/2000	Morimoto et al.	6,199,014	B1	3/2001	Walker et al.
6,072,391	A	6/2000	Suzuki et al.	6,200,010	B1	3/2001	Anders
6,074,777	A	6/2000	Reimers et al.	6,201,642	B1	3/2001	Bos
6,078,355	A	6/2000	Zengel	6,210,008	B1	4/2001	Hoekstra et al.
6,078,865	A	6/2000	Koyanagi	6,210,012	B1	4/2001	Broer
6,082,881	A	7/2000	Hicks	6,212,470	B1	4/2001	Seymour et al.
6,084,700	A	7/2000	Knapp et al.	6,217,181	B1	4/2001	Lynam et al.
6,086,131	A	7/2000	Bingle et al.	6,218,934	B1	4/2001	Regan
6,086,229	A	7/2000	Pastrick	6,222,447	B1	4/2001	Schofield et al.
6,087,012	A	7/2000	Varaprasad et al.	6,222,460	B1	4/2001	DeLine et al.
6,087,953	A	7/2000	DeLine et al.	6,227,689	B1	5/2001	Miller
6,094,618	A	7/2000	Harada	6,232,937	B1	5/2001	Jacobsen et al.
6,097,023	A	8/2000	Schofield et al.	6,239,851	B1	5/2001	Hatazawa et al.
6,097,316	A	8/2000	Liaw et al.	6,239,898	B1	5/2001	Byker et al.
6,099,131	A	8/2000	Fletcher et al.	6,243,003	B1	6/2001	DeLine et al.
6,099,155	A	8/2000	Pastrick et al.	6,245,262	B1	6/2001	Varaprasad et al.
6,102,559	A	8/2000	Nold et al.	6,249,214	B1	6/2001	Kashiwazaki
6,104,552	A	8/2000	Thau et al.	6,250,148	B1	6/2001	Lynam
6,106,121	A	8/2000	Buckley et al.	6,250,766	B1	6/2001	Strumolo et al.
6,111,498	A	8/2000	Jobes, I et al.	6,250,783	B1	6/2001	Stidham et al.
6,111,683	A	8/2000	Cammenga et al.	6,255,639	B1	7/2001	Stam et al.
6,111,684	A	8/2000	Forgette et al.	6,257,746	B1	7/2001	Todd et al.
6,111,685	A	8/2000	Tench et al.	6,259,412	B1	7/2001	Duroux
6,111,696	A	8/2000	Allen et al.	6,259,475	B1	7/2001	Ramachandran et al.
6,115,651	A	9/2000	Cruz	6,265,968	B1	7/2001	Betzitza et al.
6,116,743	A	9/2000	Hoek	6,268,803	B1	7/2001	Gunderson et al.
6,122,597	A	9/2000	Saneyoshi et al.	6,269,308	B1	7/2001	Kodaka et al.
6,124,647	A	9/2000	Marcus et al.	6,274,221	B2	8/2001	Smith et al.
6,124,886	A	9/2000	DeLine et al.	6,276,821	B1	8/2001	Pastrick et al.
6,127,945	A	10/2000	Mura-Smith	6,276,822	B1	8/2001	Bedrosian et al.
6,128,576	A	10/2000	Nishimoto et al.	6,277,471	B1	8/2001	Tang
6,130,421	A	10/2000	Bechtel et al.	6,278,271	B1	8/2001	Schott
6,130,448	A	10/2000	Bauer et al.	6,278,377	B1	8/2001	DeLine et al.
6,132,072	A	10/2000	Turnbull et al.	6,278,941	B1	8/2001	Yokoyama
6,139,171	A	10/2000	Waldmann	6,280,068	B1	8/2001	Mertens et al.
6,139,172	A	10/2000	Bos et al.	6,280,069	B1	8/2001	Pastrick et al.
6,140,933	A	10/2000	Bugno et al.	6,281,804	B1	8/2001	Haller et al.
6,146,003	A	11/2000	Thau	6,286,965	B1	9/2001	Caskey et al.
6,148,261	A	11/2000	Obradovich et al.	6,286,984	B1	9/2001	Berg
6,149,287	A	11/2000	Pastrick et al.	6,289,332	B2	9/2001	Menig et al.
6,150,014	A	11/2000	Chu et al.	6,290,378	B1	9/2001	Buchalla et al.
6,151,065	A	11/2000	Steed et al.	6,291,906	B1	9/2001	Marcus et al.
6,151,539	A	11/2000	Bergholz et al.	6,294,989	B1	9/2001	Schofield et al.
6,152,590	A	11/2000	Furst et al.	6,296,379	B1	10/2001	Pastrick
6,154,149	A	11/2000	Tyckowski et al.	6,297,781	B1	10/2001	Turnbull et al.
6,154,306	A	11/2000	Varaprasad et al.	6,299,333	B1	10/2001	Pastrick et al.
6,157,294	A	12/2000	Urai et al.	6,300,879	B1	10/2001	Regan et al.
6,158,655	A	12/2000	DeVries, Jr. et al.	6,304,173	B2	10/2001	Pala et al.
6,161,865	A	12/2000	Rose et al.	6,305,807	B1	10/2001	Schierbeek
6,166,625	A	12/2000	Teowee et al.	6,310,611	B1	10/2001	Caldwell
6,166,629	A	12/2000	Hamma et al.	6,310,714	B1	10/2001	Lompfrey et al.
6,166,847	A	12/2000	Tench et al.	6,310,738	B1	10/2001	Chu
6,166,848	A	12/2000	Cammenga et al.	6,313,454	B1	11/2001	Bos et al.
6,167,755	B1	1/2001	Damson et al.	6,314,295	B1	11/2001	Kawamoto
6,169,955	B1	1/2001	Fultz	6,317,057	B1	11/2001	Lee
6,170,956	B1	1/2001	Rumsey et al.	6,317,248	B1	11/2001	Agrawal et al.
6,172,600	B1	1/2001	Kakinami et al.	6,318,870	B1	11/2001	Spooner et al.
6,172,601	B1	1/2001	Wada et al.	6,320,176	B1	11/2001	Schofield et al.
6,172,613	B1	1/2001	DeLine et al.	6,320,282	B1	11/2001	Caldwell
				6,320,612	B1	11/2001	Young
				6,324,295	B1	11/2001	Valery et al.
				6,326,613	B1	12/2001	Heslin et al.
				6,326,900	B2	12/2001	DeLine et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,329,925	B1	12/2001	Skiver et al.	6,516,664	B2	2/2003	Lynam
6,330,511	B2	12/2001	Ogura et al.	6,520,667	B1	2/2003	Mousseau
6,331,066	B1	12/2001	Desmond et al.	6,522,451	B1	2/2003	Lynam
6,333,759	B1	12/2001	Mazzilli	6,522,969	B2	2/2003	Kannonji
6,335,680	B1	1/2002	Matsuoka	6,534,884	B2	3/2003	Marcus et al.
6,336,737	B1	1/2002	Thau	6,539,306	B2	3/2003	Turnbull
6,341,523	B2	1/2002	Lynam	6,542,085	B1	4/2003	Yang
6,344,805	B1	2/2002	Yasui et al.	6,542,182	B1	4/2003	Chutorash
6,346,698	B1	2/2002	Turnbull	6,545,598	B1	4/2003	de Villeroche
6,347,880	B1	2/2002	Furst et al.	6,549,335	B1	4/2003	Trapani et al.
6,348,858	B2	2/2002	Weis et al.	6,550,949	B1	4/2003	Bauer et al.
6,351,708	B1	2/2002	Takagi et al.	6,553,308	B1	4/2003	Uhlmann et al.
6,353,392	B1	3/2002	Schofield et al.	6,568,839	B1	5/2003	Pastrick et al.
6,356,206	B1	3/2002	Takenaga et al.	6,572,233	B1	6/2003	Northman et al.
6,356,376	B1	3/2002	Tonar et al.	6,575,643	B2	6/2003	Takahashi
6,356,389	B1	3/2002	Nilsen et al.	6,580,373	B1	6/2003	Ohashi
6,357,883	B1	3/2002	Strumolo et al.	6,581,007	B2	6/2003	Hasegawa et al.
6,362,548	B1	3/2002	Bingle et al.	6,583,730	B2	6/2003	Lang et al.
6,363,326	B1	3/2002	Scully	6,591,192	B2	7/2003	Okamura et al.
6,366,213	B2	4/2002	DeLine et al.	6,593,565	B2	7/2003	Heslin et al.
6,370,329	B1	4/2002	Teuchert	6,593,984	B2	7/2003	Arakawa et al.
6,371,636	B1	4/2002	Wesson	6,594,065	B2	7/2003	Byker et al.
6,386,742	B1	5/2002	DeLine et al.	6,594,067	B2	7/2003	Poll et al.
6,390,529	B1	5/2002	Bingle et al.	6,594,090	B2	7/2003	Kruschwitz et al.
6,390,635	B2	5/2002	Whitehead et al.	6,594,583	B2	7/2003	Ogura et al.
6,396,397	B1	5/2002	Bos et al.	6,594,614	B2	7/2003	Studt et al.
6,396,637	B2	5/2002	Roest et al.	6,597,489	B1	7/2003	Guarr et al.
6,407,847	B1	6/2002	Poll et al.	6,611,202	B2	8/2003	Schofield et al.
6,408,247	B1	6/2002	Ichikawa et al.	6,611,227	B1	8/2003	Nebiyeloul-Kifle et al.
6,411,204	B1	6/2002	Bloomfield et al.	6,611,759	B2	8/2003	Brosche
6,412,959	B1	7/2002	Tseng	6,614,387	B1	9/2003	Deadman
6,412,973	B1	7/2002	Bos et al.	6,616,313	B2	9/2003	Furst et al.
6,415,230	B1	7/2002	Maruko et al.	6,616,764	B2	9/2003	Kramer et al.
6,416,208	B2	7/2002	Pastrick et al.	6,618,672	B2	9/2003	Sasaki et al.
6,417,786	B2	7/2002	Learman et al.	6,624,936	B2	9/2003	Kotchick et al.
6,418,376	B1	7/2002	Olson	6,627,918	B2	9/2003	Getz et al.
6,419,300	B1	7/2002	Pavao et al.	6,630,888	B2	10/2003	Lang et al.
6,420,036	B1	7/2002	Varaprasad et al.	6,636,258	B2	10/2003	Strumolo
6,420,975	B1	7/2002	DeLine et al.	6,638,582	B1	10/2003	Uchiyama et al.
6,421,081	B1	7/2002	Markus	6,642,840	B2	11/2003	Lang et al.
6,424,272	B1	7/2002	Gutta et al.	6,642,851	B2	11/2003	Deline et al.
6,424,273	B1	7/2002	Gutta et al.	6,648,477	B2	11/2003	Hutzel et al.
6,424,892	B1	7/2002	Matsuoka	6,657,708	B1	12/2003	Drevillon et al.
6,426,492	B1	7/2002	Bos et al.	6,661,830	B1	12/2003	Reed et al.
6,427,349	B1	8/2002	Blank et al.	6,665,592	B2	12/2003	Kodama
6,428,172	B1	8/2002	Hutzel et al.	6,670,207	B1	12/2003	Roberts
6,433,676	B2	8/2002	DeLine et al.	6,670,910	B2	12/2003	Delcheccolo et al.
6,433,680	B1	8/2002	Ho	6,671,080	B2	12/2003	Poll et al.
6,433,914	B1	8/2002	Lompfrey et al.	6,672,731	B2	1/2004	Schnell et al.
6,437,688	B1	8/2002	Kobayashi	6,672,734	B2	1/2004	Lammers
6,438,491	B1	8/2002	Farmer	6,672,744	B2	1/2004	DeLine et al.
6,439,755	B1	8/2002	Fant, Jr. et al.	6,672,745	B1	1/2004	Bauer et al.
6,441,872	B1	8/2002	Ho	6,674,370	B2	1/2004	Rodewald et al.
6,445,287	B1	9/2002	Schofield et al.	6,675,075	B1	1/2004	Engelsberg et al.
6,447,128	B1	9/2002	Lang et al.	6,678,083	B1	1/2004	Anstee
6,452,533	B1	9/2002	Yamabuchi et al.	6,678,614	B2	1/2004	McCarthy et al.
6,463,369	B2	10/2002	Sadano et al.	6,683,539	B2	1/2004	Trajkovic et al.
6,466,701	B1	10/2002	Ejiri et al.	6,683,969	B1	1/2004	Nishigaki et al.
6,472,977	B1	10/2002	Pochmuller	6,685,348	B2	2/2004	Pastrick et al.
6,473,001	B1	10/2002	Blum	6,690,268	B2	2/2004	Schofield et al.
6,474,853	B2	11/2002	Pastrick et al.	6,690,413	B1	2/2004	Moore
6,476,731	B1	11/2002	Miki et al.	6,693,517	B2	2/2004	McCarthy et al.
6,477,460	B2	11/2002	Kepler	6,693,518	B2	2/2004	Kumata et al.
6,477,464	B2	11/2002	McCarthy et al.	6,693,519	B2	2/2004	Keirstead
6,483,429	B1	11/2002	Yasui et al.	6,693,524	B1	2/2004	Payne
6,483,438	B2	11/2002	DeLine et al.	6,700,692	B2	3/2004	Tonar et al.
6,487,500	B2	11/2002	Lemelson et al.	6,709,136	B2	3/2004	Pastrick et al.
6,494,602	B2	12/2002	Pastrick et al.	6,717,610	B1	4/2004	Bos et al.
6,498,620	B2	12/2002	Schofield et al.	6,717,712	B2	4/2004	Lynam et al.
6,501,387	B2	12/2002	Skiver et al.	6,726,337	B2	4/2004	Whitehead et al.
6,512,624	B2	1/2003	Tonar et al.	6,727,808	B1	4/2004	Uselmann et al.
6,513,252	B1	2/2003	Schierbeek et al.	6,727,844	B1	4/2004	Zimmermann et al.
6,515,581	B1	2/2003	Ho	6,731,332	B1	5/2004	Yasui et al.
6,515,582	B1	2/2003	Teowee et al.	6,734,807	B2	5/2004	King
6,515,597	B1	2/2003	Wada et al.	6,736,526	B2	5/2004	Matsuba et al.
				6,737,964	B2	5/2004	Samman et al.
				6,738,088	B1	5/2004	Uskolovsky et al.
				6,744,353	B2	6/2004	Sjonell
				6,748,211	B1	6/2004	Isaac et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,756,912 B2	6/2004	Skiver et al.	7,199,767 B2	4/2007	Spero
6,757,109 B2	6/2004	Bos	7,209,277 B2	4/2007	Tonar et al.
6,759,113 B1	7/2004	Tang	7,215,473 B2	5/2007	Fleming
6,760,157 B1	7/2004	Allen et al.	7,245,336 B2	7/2007	Hiyama et al.
6,774,356 B2	8/2004	Heslin et al.	7,251,079 B2	7/2007	Capaldo et al.
6,774,810 B2	8/2004	DeLine et al.	7,255,451 B2	8/2007	McCabe et al.
6,778,904 B2	8/2004	Iwami et al.	7,255,465 B2	8/2007	DeLine et al.
6,784,129 B2	8/2004	Seto et al.	7,262,406 B2	8/2007	Heslin et al.
6,797,396 B1	9/2004	Liu et al.	7,262,916 B2	8/2007	Kao et al.
6,800,871 B2	10/2004	Matsuda et al.	7,265,342 B2	9/2007	Heslin et al.
6,801,283 B2	10/2004	Koyama et al.	7,268,841 B2	9/2007	Kasajima et al.
6,806,452 B2	10/2004	Bos et al.	7,269,327 B2	9/2007	Tang
6,810,323 B1	10/2004	Bullock et al.	7,269,328 B2	9/2007	Tang
6,824,281 B2	11/2004	Schofield et al.	7,274,501 B2	9/2007	McCabe et al.
6,832,848 B2	12/2004	Pastrick	7,286,280 B2	10/2007	Whitehead et al.
6,836,725 B2	12/2004	Millington et al.	7,290,919 B2	11/2007	Pan et al.
6,842,276 B2	1/2005	Poll et al.	7,292,208 B1	11/2007	Park et al.
6,846,098 B2	1/2005	Bourdelaïs et al.	7,308,341 B2	12/2007	Schofield et al.
6,847,487 B2	1/2005	Burgner	7,310,177 B2	12/2007	McCabe et al.
6,848,817 B2	2/2005	Bos et al.	7,311,428 B2	12/2007	DeLine et al.
6,853,491 B1	2/2005	Ruhle et al.	7,323,819 B2	1/2008	Hong et al.
6,870,655 B1	3/2005	Northman et al.	7,324,261 B2	1/2008	Tonar et al.
6,870,656 B2	3/2005	Tonar et al.	7,328,103 B2	2/2008	McCarthy et al.
6,871,982 B2	3/2005	Holman et al.	7,329,013 B2	2/2008	Blank et al.
6,877,888 B2	4/2005	DeLine et al.	7,338,177 B2	3/2008	Lynam
6,882,287 B2	4/2005	Schofield	7,344,284 B2	3/2008	Lynam et al.
6,891,563 B2	5/2005	Schofield et al.	7,349,143 B2	3/2008	Tonar et al.
6,902,284 B2	6/2005	Hutzel et al.	7,362,505 B2	4/2008	Hikmet et al.
6,906,632 B2	6/2005	DeLine et al.	7,370,983 B2	5/2008	DeWind et al.
6,912,396 B2	6/2005	Sziraki et al.	7,372,611 B2	5/2008	Tonar et al.
6,922,902 B2	8/2005	Schierbeek et al.	7,379,224 B2	5/2008	Tonar et al.
6,928,180 B2	8/2005	Stam et al.	7,379,225 B2	5/2008	Tonar et al.
6,928,366 B2	8/2005	Ockerse et al.	7,379,243 B2	5/2008	Horsten et al.
6,930,737 B2	8/2005	Weindorf et al.	7,411,732 B2	8/2008	Kao et al.
6,934,067 B2	8/2005	Ash et al.	7,412,328 B2	8/2008	Uhlmann et al.
6,946,978 B2	9/2005	Schofield	7,417,781 B2	8/2008	Tonar et al.
6,947,576 B2	9/2005	Stam et al.	7,420,159 B2	9/2008	Heslin et al.
6,947,577 B2	9/2005	Stam et al.	7,446,462 B2	11/2008	Lim et al.
6,951,410 B2	10/2005	Parsons	7,446,650 B2	11/2008	Schofield et al.
6,951,681 B2	10/2005	Hartley et al.	7,448,776 B2	11/2008	Tang
6,952,312 B2	10/2005	Weber et al.	7,452,090 B2	11/2008	Weller et al.
6,968,273 B2	11/2005	Ockerse et al.	7,467,883 B2	12/2008	DeLine et al.
6,972,888 B2	12/2005	Poll et al.	7,468,651 B2	12/2008	DeLine et al.
6,974,236 B2	12/2005	Tenmyo	7,471,438 B2	12/2008	McCabe et al.
6,975,215 B2	12/2005	Schofield et al.	7,477,439 B2	1/2009	Tonar et al.
6,977,702 B2	12/2005	Wu	7,480,149 B2	1/2009	DeWard et al.
6,980,092 B2	12/2005	Turnbull et al.	7,488,080 B2	2/2009	Skiver et al.
6,985,291 B2	1/2006	Watson et al.	7,490,007 B2	2/2009	Taylor et al.
6,992,718 B1	1/2006	Takahara	7,490,943 B2	2/2009	Kikuchi et al.
7,001,058 B2	2/2006	Inditsky	7,490,944 B2	2/2009	Blank et al.
7,004,592 B2	2/2006	Varaprasad et al.	7,494,231 B2	2/2009	Varaprasad et al.
7,004,593 B2	2/2006	Weller et al.	7,502,156 B2	3/2009	Tonar et al.
7,006,173 B1	2/2006	Hiyama et al.	7,510,287 B2	3/2009	Hook
7,009,751 B2	3/2006	Tonar et al.	7,511,872 B2	3/2009	Tonar et al.
7,012,543 B2	3/2006	DeLine et al.	7,526,103 B2	4/2009	Schofield et al.
7,041,965 B2	5/2006	Heslin et al.	7,538,316 B2	5/2009	Heslin et al.
7,042,616 B2	5/2006	Tonar et al.	7,540,620 B2	6/2009	Weller et al.
7,046,418 B2	5/2006	Lin et al.	7,547,467 B2	6/2009	Olson et al.
7,046,448 B2	5/2006	Burgner	7,551,354 B2	6/2009	Horsten et al.
7,057,681 B2	6/2006	Hinata et al.	7,571,042 B2	8/2009	Taylor et al.
7,092,052 B2	8/2006	Okamoto et al.	7,572,490 B2	8/2009	Park et al.
7,108,409 B2	9/2006	DeLine et al.	7,580,795 B2	8/2009	McCarthy et al.
7,125,131 B2	10/2006	Olczak	7,581,867 B2	9/2009	Lee et al.
7,132,064 B2	11/2006	Li et al.	7,586,566 B2	9/2009	Nelson et al.
7,149,613 B2	12/2006	Stam et al.	7,586,666 B2	9/2009	McCabe et al.
7,151,997 B2	12/2006	Uhlmann et al.	7,619,508 B2	11/2009	Lynam et al.
7,154,657 B2	12/2006	Poll et al.	7,626,749 B2	12/2009	Baur et al.
7,158,881 B2	1/2007	McCarthy et al.	7,633,567 B2	12/2009	Yamada et al.
7,160,017 B2	1/2007	Lee et al.	7,658,521 B2	2/2010	DeLine et al.
7,167,796 B2	1/2007	Taylor et al.	7,667,579 B2	2/2010	DeLine et al.
7,175,291 B1	2/2007	Li	7,695,174 B2	4/2010	Takayanagi et al.
7,184,190 B2	2/2007	McCabe et al.	7,711,479 B2	5/2010	Taylor et al.
7,188,963 B2	3/2007	Schofield et al.	9,487,144 B2	11/2016	Blank et al.
7,193,764 B2	3/2007	Lin et al.	9,609,757 B2	3/2017	Steigerwald
7,195,381 B2	3/2007	Lynam et al.	10,128,595 B2	11/2018	Conger et al.
			10,264,219 B2	4/2019	Mleczo et al.
			10,298,823 B2	5/2019	Sauer et al.
			10,313,572 B2	6/2019	Wohlte
			10,567,705 B2	2/2020	Ziegenspeck et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

10,583,782	B2	3/2020	Blank et al.	2003/0227546	A1	12/2003	Hilborn et al.
11,021,107	B2	6/2021	Blank et al.	2004/0004541	A1	1/2004	Hong
11,577,652	B2	2/2023	Blank et al.	2004/0027695	A1	2/2004	Lin
11,807,164	B2	11/2023	Blank et al.	2004/0032321	A1	2/2004	McMahon et al.
12,054,098	B2	8/2024	Blank et al.	2004/0032675	A1	2/2004	Weller et al.
2001/0019356	A1	9/2001	Takeda et al.	2004/0032676	A1*	2/2004	Drummond G02B 27/01
2001/0022616	A1	9/2001	Rademacher et al.				359/877
2001/0026215	A1	10/2001	Nakaho et al.	2004/0036768	A1	2/2004	Green
2001/0026316	A1	10/2001	Senatore	2004/0046870	A1	3/2004	Leigh Travis
2001/0030857	A1	10/2001	Futhey et al.	2004/0051634	A1	3/2004	Schofield et al.
2001/0045981	A1	11/2001	Gloger et al.	2004/0056955	A1	3/2004	Berberich et al.
2002/0003571	A1	1/2002	Schofield et al.	2004/0057131	A1	3/2004	Hutzel et al.
2002/0044065	A1	4/2002	Quist et al.	2004/0064241	A1	4/2004	Sekiguchi
2002/0049535	A1	4/2002	Rigo et al.	2004/0066285	A1	4/2004	Sekiguchi
2002/0072026	A1	6/2002	Lynam et al.	2004/0075603	A1	4/2004	Kodama
2002/0085155	A1	7/2002	Arikawa	2004/0077359	A1	4/2004	Bernas et al.
2002/0093826	A1	7/2002	Bos et al.	2004/0080404	A1	4/2004	White
2002/0113203	A1	8/2002	Heslin et al.	2004/0080431	A1	4/2004	White
2002/0126497	A1	9/2002	Pastrick	2004/0085196	A1	5/2004	Miller et al.
2002/0154007	A1	10/2002	Yang	2004/0085499	A1	5/2004	Baek
2002/0159270	A1*	10/2002	Lynam B60Q 3/74	2004/0090314	A1	5/2004	Iwamoto
			362/492	2004/0090317	A1	5/2004	Rothkop
2002/0172053	A1	11/2002	Pastrick et al.	2004/0096082	A1	5/2004	Nakai et al.
2002/0191409	A1	12/2002	Deline et al.	2004/0098196	A1	5/2004	Sekiguchi
2002/0196639	A1	12/2002	Weidel	2004/0105614	A1	6/2004	Kobayashi et al.
2003/0002165	A1	1/2003	Mathias et al.	2004/0107030	A1	6/2004	Nishira et al.
2003/0002179	A1	1/2003	Roberts et al.	2004/0107617	A1	6/2004	Shoen et al.
2003/0007261	A1	1/2003	Hutzel et al.	2004/0109060	A1	6/2004	Ishii
2003/0016125	A1	1/2003	Lang et al.	2004/0114039	A1	6/2004	Ishikura
2003/0016287	A1	1/2003	Nakayama et al.	2004/0128065	A1	7/2004	Taylor et al.
2003/0016542	A1	1/2003	Pastrick et al.	2004/0145457	A1	7/2004	Schofield et al.
2003/0020603	A1	1/2003	DeLine et al.	2004/0170008	A1	9/2004	Tenmyo
2003/0025596	A1	2/2003	Lang et al.	2004/0202001	A1	10/2004	Roberts et al.
2003/0025597	A1	2/2003	Schofield	2004/0243303	A1	12/2004	Padmanabhan
2003/0030546	A1	2/2003	Tseng	2004/0251804	A1	12/2004	McCullough et al.
2003/0030551	A1	2/2003	Ho	2005/0024591	A1	2/2005	Lian et al.
2003/0030724	A1	2/2003	Okamoto	2005/0024729	A1	2/2005	Ockerse et al.
2003/0035050	A1	2/2003	Mizusawa et al.	2005/0078347	A1	4/2005	Lin et al.
2003/0043269	A1	3/2003	Park	2005/0078389	A1	4/2005	Kulas et al.
2003/0048639	A1	3/2003	Boyd et al.	2005/0079326	A1	4/2005	Varaprasad et al.
2003/0052969	A1	3/2003	Satoh et al.	2005/0083577	A1	4/2005	Varaprasad et al.
2003/0058338	A1	3/2003	Kawauchi et al.	2005/0084658	A1	4/2005	Adams et al.
2003/0067383	A1	4/2003	Yang	2005/0099559	A1	5/2005	Lee et al.
2003/0069690	A1	4/2003	Correia et al.	2005/0111070	A1	5/2005	Lin et al.
2003/0076415	A1	4/2003	Strumolo	2005/0140855	A1	6/2005	Utsumi et al.
2003/0080877	A1	5/2003	Takagi et al.	2005/0168995	A1	8/2005	Kittelmann et al.
2003/0085806	A1	5/2003	Samman et al.	2005/0169003	A1	8/2005	Lindahl et al.
2003/0088361	A1	5/2003	Sekiguchi	2005/0172504	A1	8/2005	Ohm et al.
2003/0090568	A1	5/2003	Pico	2005/0185278	A1	8/2005	Horsten et al.
2003/0090569	A1	5/2003	Poehm Mueller	2005/0237440	A1	10/2005	Sugimura et al.
2003/0090570	A1	5/2003	Takagi et al.	2005/0270766	A1	12/2005	Kung et al.
2003/0095331	A1	5/2003	Bengochea et al.	2005/0270798	A1	12/2005	Lee et al.
2003/0098908	A1	5/2003	Misaiji et al.	2006/0007550	A1	1/2006	Tonar et al.
2003/0103141	A1	6/2003	Bechtel et al.	2006/0028730	A1	2/2006	V. Varaprasad et al.
2003/0103142	A1	6/2003	Hitomi et al.	2006/0038668	A1	2/2006	DeWard et al.
2003/0117522	A1	6/2003	Okada	2006/0050018	A1	3/2006	Hutzel et al.
2003/0117728	A1	6/2003	Hutzel et al.	2006/0061008	A1	3/2006	Karner et al.
2003/0122929	A1	7/2003	Minaudo et al.	2006/0139953	A1	6/2006	Chou et al.
2003/0122930	A1	7/2003	Schofield et al.	2006/0164230	A1	7/2006	DeWind et al.
2003/0133014	A1	7/2003	Mendoza	2006/0164725	A1	7/2006	Horsten et al.
2003/0137586	A1	7/2003	Lewellen	2006/0202111	A1	9/2006	Heslin et al.
2003/0141965	A1	7/2003	Gunderson et al.	2006/0255960	A1	11/2006	Uken et al.
2003/0146831	A1	8/2003	Berberich et al.	2006/0274218	A1	12/2006	Xue
2003/0147244	A1	8/2003	Tenmyo	2007/0041096	A1	2/2007	Nieuwkerk et al.
2003/0169158	A1	9/2003	Paul	2007/0058257	A1	3/2007	Lynam
2003/0169522	A1	9/2003	Schofield et al.	2007/0080585	A1	4/2007	Lyu
2003/0179293	A1	9/2003	Oizumi	2007/0118287	A1	5/2007	Taylor et al.
2003/0189754	A1	10/2003	Sugino et al.	2007/0120043	A1	5/2007	Heslin et al.
2003/0202096	A1	10/2003	Kim	2007/0132567	A1	6/2007	Schofield et al.
2003/0210369	A1	11/2003	Wu	2007/0162229	A1	7/2007	McCarthy et al.
2003/0214576	A1	11/2003	Koga	2007/0171037	A1	7/2007	Schofield et al.
2003/0214584	A1	11/2003	Ross	2007/0183066	A1	8/2007	Varaprasad et al.
2003/0214733	A1	11/2003	Fujikawa et al.	2007/0184284	A1	8/2007	Varaprasad et al.
2003/0222793	A1	12/2003	Tanaka et al.	2008/0002106	A1	1/2008	Van De Witte et al.
2003/0222983	A1	12/2003	Nobori et al.	2008/0013153	A1	1/2008	McCabe et al.
				2008/0068520	A1	3/2008	Minkey et al.
				2008/0094684	A1	4/2008	Varaprasad et al.
				2008/0094685	A1	4/2008	Varaprasad et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0180529	A1 *	7/2008	Taylor	B60Q 9/00	
					348/148	
2008/0180779	A1 *	7/2008	McCabe	B60Q 1/34	
					359/267	
2008/0180781	A1	7/2008	Varaprasad et al.			
2008/0183355	A1	7/2008	Taylor et al.			
2008/0201075	A1	8/2008	Taylor et al.			
2008/0212189	A1 *	9/2008	Baur	B60R 1/1207	
					359/872	
2008/0212215	A1	9/2008	Schofield et al.			
2008/0225538	A1	9/2008	Lynam et al.			
2008/0266389	A1 *	10/2008	DeWind	B60K 35/211	
					345/636	
2008/0291522	A1	11/2008	Varaprasad et al.			
2008/0308219	A1	12/2008	Lynam			
2009/0015736	A1 *	1/2009	Weller	B60R 1/10	
					362/494	
2009/0033837	A1	2/2009	Molsen et al.			
2009/0040465	A1	2/2009	Conner et al.			
2009/0040588	A1	2/2009	Tonar et al.			
2009/0040778	A1	2/2009	Takayanagi et al.			
2009/0052003	A1	2/2009	Schofield et al.			
2009/0080055	A1	3/2009	Baur et al.			
2009/0096937	A1	4/2009	Bauer et al.			
2009/0141331	A1	6/2009	Skiver et al.			
2009/0174776	A1	7/2009	Taylor et al.			
2009/0201137	A1	8/2009	Weller et al.			
2009/0219394	A1	9/2009	Heslin et al.			
2009/0231741	A1	9/2009	Weller et al.			
2009/0243824	A1 *	10/2009	Peterson	G06F 3/04886	
					348/148	
2009/0262422	A1	10/2009	Cross et al.			
2009/0290369	A1 *	11/2009	Schofield	B60S 1/0822	
					362/494	
2010/0085645	A1	4/2010	Skiver et al.			
2010/0091509	A1	4/2010	DeLine et al.			
2010/0201816	A1	8/2010	Lee et al.			
2014/0218529	A1	8/2014	Mahmoud et al.			
2014/0218535	A1	8/2014	Ihlenburg et al.			

* cited by examiner




FIG. 1




FIG. 9




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 12




FIG. 10




FIG. 13




FIG. 11




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25



FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35






FIG. 36



DISPLAY OFF
FIG. 37B



DISPLAY ON
FIG. 37A

VEHICULAR VIDEO CAMERA DISPLAY SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 18/502,129, filed Nov. 6, 2023, now U.S. Pat. No. 12,054,098, which is a continuation of U.S. patent application Ser. No. 18/167,930, filed Feb. 13, 2023, now U.S. Pat. No. 11,807,164, which is a continuation of U.S. patent application Ser. No. 17/303,404, filed May 28, 2021, now U.S. Pat. No. 11,577,652, which is a continuation of U.S. patent application Ser. No. 16/812,864, filed Mar. 9, 2020, now U.S. Pat. No. 11,021,107, which is a continuation of U.S. patent application Ser. No. 15/344,865, filed Nov. 7, 2016, now U.S. Pat. No. 10,583,782, which is a continuation of U.S. patent application Ser. No. 12/578,732, filed Oct. 14, 2009, now U.S. Pat. No. 9,487,144, which claims benefit of U.S. provisional applications, Ser. No. 61/219,214, filed Jun. 22, 2009, Ser. No. 61/187,069, filed Jun. 15, 2009, Ser. No. 61/117,301, filed Nov. 24, 2008, and Ser. No. 61/105,903, filed Oct. 16, 2008, which are hereby incorporated herein by reference in their entireties.

FIELD OF THE INVENTION

The present invention relates generally to the field of interior rearview mirror systems for vehicles and, more particularly, to interior rearview mirror systems which incorporate a display.

BACKGROUND OF THE INVENTION

It is known to provide a video display screen at an interior rearview mirror assembly of a vehicle, such as, for example, a video display screen of the type disclosed in U.S. Pat. No. 6,428,172 for REARVIEW MIRROR ASSEMBLY WITH UTILITY FUNCTIONS, and U.S. Pat. No. 6,175,300 for BLIND SPOT VIEWING SYSTEM, which are hereby incorporated herein by reference in their entireties. It has also been suggested to provide a mirror or a display which may be indexed in and out of a mirror case, such as from the bottom of the mirror case, such as also disclosed in U.S. Pat. No. 6,428,172, which is hereby incorporated herein by reference in its entirety.

SUMMARY OF THE INVENTION

The present invention provides an interior rearview mirror assembly having a video display screen which may display video images captured by a camera or image sensor of the vehicle.

According to an aspect of the present invention, an interior rearview mirror assembly for a vehicle comprises a casing, a variable reflectivity reflective element, such as positioned at a bezel portion of the casing, and a video display screen disposed in the casing and behind the reflective element. The video display screen is operable to display images that are viewable through the reflective element by a person viewing the rearview mirror assembly when it is normally mounted in a vehicle. The video display screen may function to brighten or enhance the intensity of the displayed images in response to a dimming condition of the variable reflectivity reflective element.

According to another aspect of the present invention, an interior rearview mirror assembly for a vehicle comprises a

casing, a reflective element, such as a prismatic reflective element, such as positioned at a bezel portion of the casing, and a video display screen disposed in the casing and behind the reflective element. The video display screen is operable to display images that are viewable through the reflective element by a person viewing the rearview mirror assembly when it is normally mounted in a vehicle. The mirror assembly includes a decoder that decodes the NTSC signal from a camera or image sensor of the vehicle. The decoder has a microprocessor that is operable to control the video display screen, such that the images are processed and displayed with a common microprocessor, thereby obviating the need for a separate microprocessor for the video display screen.

According to an aspect of the present invention, a mirror and compass system includes an interior rearview mirror assembly having a reflective element and a casing that are adjustable relative to a mounting structure. The mounting structure includes a mounting base. A compass chip having at least two magnetoresponsive sensing elements and compass circuitry established thereon is positioned at the mounting base. The compass chip has at least one connecting element for connecting to a vehicle wire harness that extends downward from the vehicle headliner (such as along the vehicle windshield and within a wire channel or wire guide element or the like) and that provides power to the compass chip.

These and other objects, advantages, purposes and features of the present invention will become apparent upon review of the following specification in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front elevation of an electro-optic interior rearview mirror assembly in accordance with the present invention, with the video display screen activated so that images are viewable through the reflective element;

FIGS. 2-4 are perspective views of an interior rearview mirror assembly in accordance with the present invention, with the compass chip disposed at an upper end of a wire management portion of the mirror assembly;

FIGS. 5-8 are perspective views of the compass chip incorporated into the interior rearview mirror assembly of FIGS. 2-4;

FIG. 9 is a perspective view of another interior rearview mirror assembly and compass chip in accordance with the present invention, with a compass chip disposed at a wire management element attachable to a mounting base of the mirror assembly;

FIGS. 10 and 11 are exploded perspective views of the interior rearview mirror assembly and compass chip of FIG. 9;

FIGS. 12 and 13 are perspective views of the mirror mounting base and the wire management element that incorporates a compass chip in accordance with the present invention;

FIGS. 14-31 are views of a display module displaying various images and/or icons and/or text information responsive to a control in accordance with the present invention;

FIG. 32 is a sectional view of an electrochromic mirror assembly;

FIG. 33 is a sectional view of another electrochromic mirror assembly, shown with a transparent display element in accordance with the present invention;

3

FIG. 34 is a sectional view of another electrochromic mirror assembly, shown with a transparent display element in accordance with the present invention;

FIG. 35 is schematic of a transparent OLED display suitable for use with the reflective element assembly of the present invention;

FIG. 36 is another schematic of a transparent OLED display suitable for use with the reflective element assembly of the present invention; and

FIGS. 37A and 37B are examples of a transparent OLED display suitable for use with the reflective element assembly of the present invention, shown in an activated and deactivated state.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings and the illustrative embodiments depicted therein, an interior rearview mirror assembly 10 for a vehicle includes a casing, a bezel portion 12 and a reflective element 14 positioned at and at least partially within the casing and/or bezel portion (FIG. 1). Mirror assembly 10 includes a video display screen device 16, which is disposed within the mirror casing and behind the reflective element 14. The video display screen device is operable to display information or images for viewing by the driver or other occupant or occupants of the vehicle when the video display screen device is activated, and is substantially not viewable or discernible when not activated, as discussed below.

Video display screen device or module 16 may comprise any type of video screen and is operable to display images in response to an input or signal from a control or imaging system. For example, the video display screen may comprise a multi-pixel liquid crystal module (LCM) or liquid crystal display (LCD), preferably a thin film transistor (TFT) multi-pixel liquid crystal display (such as discussed below), or the screen may comprise a multi-pixel organic electroluminescent display or a multi-pixel light emitting diode (LED), such as an organic light emitting diode (OLED) or inorganic light emitting diode display or the like, or a passive reflective and/or backlit pixelated display, or an electroluminescent (EL) display, or a vacuum fluorescent (VF) display or the like. For example, the video display screen may comprise a video screen of the types disclosed in U.S. Pat. Nos. 7,370,983; 7,338,177; 7,274,501; 7,255,451; 7,195,381; 7,184,190; 6,902,284; 6,690,268; 6,428,172; 6,420,975; 5,668,663 and/or 5,724,187, and/or U.S. patent application Ser. No. 10/538,724, filed Jun. 13, 2005 and published Mar. 9, 2006 as U.S. Publication No. 2006/0050018; Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. 2006/0061008; Ser. No. 12/091,525, filed Apr. 25, 2008, now U.S. Pat. No. 7,855,755; Ser. No. 09/585,379, filed Jun. 1, 2000; Ser. No. 10/207,291, filed Jul. 29, 2002, and/or U.S. provisional applications, Ser. No. 61/238,862, filed Sep. 1, 2009; Ser. No. 61/180,257, filed May 21, 2009; Ser. No. 61/174,596, filed May 1, 2009; and/or Ser. No. 61/156,184, filed Feb. 27, 2009, which are hereby incorporated herein by reference in their entireties.

Video display screen device 16 may be in communication with or may receive an input or video signal (such as a NTSC video signal or the like) from a corresponding imaging sensor or camera or imaging system and may display the image or images provided by the input or signal on the video display screen. Alternately, a video signal may be conveyed to the mirror assembly or system as a digital signal. The video display screen device or an imaging or vision system

4

of the vehicle may include a control, which may be in communication with the video display screen via a wireless communication link or via an electrical connector or wiring or cable or the like.

The control is operable to control the video display screen in response to an input or signal, such as a signal received from one or more cameras or image sensors of the vehicle, such as a video camera or sensor, such as a CMOS imaging array sensor, a CCD sensor or the like, such as the types disclosed in U.S. Pat. Nos. 5,550,677; 5,760,962; 6,396,397; 6,097,023; 5,877,897 and 5,796,094, and/or U.S. patent application Ser. No. 10/534,632, filed May 11, 2005, and/or U.S. provisional application Ser. No. 61/785,565, filed May 15, 2009, which are hereby incorporated herein by reference in their entireties, or from one or more imaging systems of the vehicle, such as a reverse or backup aid system, such as a rearwardly directed vehicle vision system utilizing principles disclosed in U.S. Pat. Nos. 5,550,677; 5,760,962; 5,670,935; 6,201,642; 6,396,397; 6,498,620; 6,717,610 and/or 6,757,109, which are hereby incorporated herein by reference in their entireties, a trailer hitching aid or tow check system, such as the type disclosed in U.S. Pat. No. 7,005,974, which is hereby incorporated herein by reference in its entirety, a cabin viewing or monitoring device or system, such as a baby viewing or rear seat viewing camera or device or system or the like, such as disclosed in U.S. Pat. Nos. 5,877,897 and/or 6,690,268, which are hereby incorporated herein by reference in their entireties, a video communication device or system, such as disclosed in U.S. Pat. No. 6,690,268, which is hereby incorporated herein by reference in its entirety, and/or the like. The imaging sensor or camera may be activated and the display screen may be activated in response to the vehicle shifting into reverse, such that the display screen is viewable by the driver and is displaying an image of the rearward scene while the driver is reversing the vehicle.

Optionally, the video display screen may be operable responsive to other cameras and/or navigation systems and/or the like, and may be operable at any time during operation of the vehicle. Thus, the video display screen may be operable during daytime and nighttime driving conditions and may be operable when the variable reflectivity reflective element is dimmed or darkened. Thus, the intensity of the display may be adjusted to account for a reduced transmissivity of the reflective element.

Optionally, and desirably, the intensity or brightness or contrast of the video display screen may be automatically adjusted in response to an ambient light sensor or glare detector, such as a sensor of the display screen device, or of the interior rearview mirror assembly or vehicle or of a console or module or the like, such as the types disclosed in U.S. Pat. Nos. 4,793,690 and/or 5,193,029, which are hereby incorporated herein by reference in their entireties. In applications where the display screen device is implemented with an electro-optic or electrochromic mirror reflective element assembly (such as shown in FIG. 1), the display screen device may be automatically adjusted in response to the ambient light sensor or glare detector associated with the electro-optic or electrochromic circuitry or system. The display intensity of the display screen may be adjusted in response to the photo sensor or light sensor, and may be increased during daytime lighting conditions and reduced at dusk or during nighttime lighting conditions. The intensity and/or contrast and/or brightness of the display may be substantially continuously adjusted or may be adjusted intermittently or in steps in response to the light sensor or sensors, such as by utilizing aspects of the displays

described in U.S. Pat. Nos. 7,370,983; 5,416,313 and 5,285,060, and/or U.S. patent application Ser. No. 12/091,525, filed Apr. 25, 2008, now U.S. Pat. No. 7,855,755, which are hereby incorporated herein by reference in their entirety.

Optionally, the video display screen may be operable to adjust the intensity of the displayed images in response to a degree of dimming of the electro-optic (such as electrochromic) reflective element of the mirror assembly. The video display screen thus may be adjusted responsive to an output signal of the glare light sensor or an output of the mirror reflective element dimming circuitry or the like. For example, as the reflective element is dimmed or darkened (such as in response to a detection of glare light at the mirror assembly) to reduce glare to the driver of the vehicle, the video display screen may be automatically brightened. Desirably, the video display screen is brightened relative to the degree of dimming so that the displayed images remain at a substantially constant intensity as viewed by the driver of the vehicle, so that the increasing/decreasing intensity of the video display is not readily discernible to the driver of the vehicle. Such an automatic intensity adjustment function is particularly suitable for a video display screen that may be operable in response to various camera inputs and/or navigation system inputs and/or the like, and not only responsive to a rear vision camera (where the dimming controls are typically deactivated when the vehicle is shifted into a reverse gear).

In such an application, the mirror dimming control may still be inhibited when the vehicle is shifted into a reverse gear, but will be active during other driving conditions, and the video display screen will also be active during reverse and forward driving conditions. Thus, when the video decoder (that may be part of the video display device or module) determines that there is a valid video signal, the video decoder may communicate to the mirror microprocessor to activate the back light of the display module, and the mirror circuitry and/or display circuitry may adjust the intensity of the video display screen in response to a detected ambient lighting condition and a detected glare lighting condition (and/or in response to a degree of dimming of the reflective element as set by the mirror circuitry). As the mirror reflective element is dimmed or darkened, the video display screen may re-brighten the video display intensity based on the EC coloring or dimming percentage in front of the video display screen. Likewise, as the mirror reflective element is bleached or undimmed, the video display screen may reduce its intensity accordingly.

Desirably, the display screen emits light that is bright enough to be readily viewable and discernible during high ambient lighting conditions, such as are typically encountered on a sunny day. Preferably, the display luminance (and especially for a TFT LCD display element showing video or full color video or still images) is greater than about 300 candelas per square meter (cd/m^2), more preferably greater than about 500 cd/m^2 , and more preferably greater than about 700 cd/m^2 . This is to help ensure that the driver can discern any video image being displayed against the sunlight streaming in through the rear window and incident at the display screen at the interior mirror assembly that will tend to wash-out the video image unless the video image is sufficiently bright. Optionally, the display screen may utilize aspects of the display element described in U.S. patent application Ser. No. 12/091,525, filed Apr. 25, 2008, now U.S. Pat. No. 7,855,755, which is hereby incorporated herein by reference in its entirety.

Conventionally, a video system may include a decoder for receiving and decoding video signals from the cameras or

image sensors, and the video system further includes a connection or communication of the signals to a microprocessor of the video display device. The likes of conventional prismatic video mirrors typically utilize a two board approach with two separate processors: one processor on the video display screen device or module (typically, the video display device is provided as a liquid crystal video screen device or module or LCM with integrated backlighting and various brightness enhancing means) and another processor on the printed circuit board or circuit element or mirror board or mirror PCB. The processor on the mirror PCB may be operable to control various functions, such as the video display dimming, the power supply to the video display device module, the human-machine interface (HMI) switch for turning the video display on/off, and to provide protection and regulated power supply to the video display module and back light.

Optionally, the present invention may provide a decoder that includes a microprocessor built into the package and with "OSD" (On Screen Display) capability. Thus, the control circuitry on the mirror circuit element or PCB may be moved into the decoder and thus combine the display module circuit element or PCB decoder electronics with the mirror circuit element or PCB electronics. Such combined circuitry can eliminate the need for an additional processor on the mirror PCB and will combine all feature control into the decoder. This saves system cost, improves EMC, reduces the PCB size and gives enhanced or full control of the video mirror system to one processor.

Optionally, such a combined circuitry decoder may include additional enhancement to the existing decoder chip so that the decoder may also control the dimming of a variable reflectivity reflective element or electro-optic or electrochromic reflective element. This would eliminate the mirror EC PCB assembly and would combine all the mirror electronics on a single or common circuit element or PCB that would have the decoder control all the video and reflective element dimming features.

For example, a decoder, such as a Techwell 8817 decoder available from Techwell Inc. of San Jose, CA, or other suitable decoder, may be disposed at a video display screen and may receive standard video signals, such as NTSC signals or PAL signals or the like, from one or more cameras of the vehicle. The decoder may decode the NTSC signals and may digitize the signals and send the digital signal to the display screen or LCD TFT screen. The decoder provides on screen display (OSD) capabilities and may provide other signals or messages with the video feed to the video screen.

Optionally, such a decoder (such as a Techwell 8817 Decoder or the like) may be implemented with a video screen for a prismatic video mirror application. For example, the decoder may have a microprocessor and/or other data processing resources, such as memory, converters (such as A/D converters and/or the like), and/or CAN/LIN controllers and/or the like, incorporated into the same integrated circuit chip or package and may include OSD capability too. Thus, as well as functioning as a decoder, the same chip or package can provide intelligence/data processing/control for another function/functions or accessory/accessories in the mirror assembly, such as automatic dimming control of an antiglare electrochromic rearview mirror and/or intensity control of display backlighting, such as responsive to a photosensor of the interior rearview mirror assembly. Current prismatic video mirrors may utilize a two board approach with two separate processors (one processor may be on the mirror PCB in order to control the video display dimming, power supply to the LCM or display screen, the

HMI Switch for turning the video display ON/OFF and/or supply protection and regulated power supply to the LCM or video display screen and back light.

For example, such a decoder, such as the Techwell 8817 Decoder, may include a board or substrate with circuitry established thereon, including a video decoder (that receives the standard video signal or NTSC signal), a microcontroller, OSD circuitry, image enhancement circuitry (which may include a built-in 2D de-interlacing engine and a high quality scalar, and may provide programmable hue, brightness, saturation, contrast, sharpness control with vertical peaking, programmable color transient improvement control, panorama/water-glass scaling, programmable Gamma correction tables, black/white stretch, programmable favorite color enhancement, and an LED controller (for controlling the backlighting LEDs of the TFT backlit video display. The decoder may also include other circuitry as desired or appropriate depending on the particular application of the decoder and video display module. The decoder may support a two-wire serial bus interface for interfacing with a bus system or network of the vehicle.

The present invention thus moves control circuitry, such as, for example, a microprocessor and allied circuitry associated with EC dimming of the mirror element, that is currently on the mirror printed circuit board or PCB into the decoder and combines the video display module or LCM PCB decoder electronics with at least a portion of the mirror PCB electronics into a single unitary integrated circuit or chip or package. Such combination and incorporation of the electronics onto a single decoder board limits or substantially precludes the need for an additional processor on the mirror PCB and combines all feature control into the decoder. The present invention thus reduces system cost, improves EMC, reduces PCB size and may provide full control of the video mirror system to one processor.

Optionally, the decoder of the present invention may be used in an electrochromic (EC) video mirror assembly. For example, the above described decoder may be carried over and with additional enhancement to the existing decoder chip could be a viable solution to also control the EC feature utilizing the decoder too. Such a configuration may limit or substantially preclude or eliminate the mirror EC PCB assembly and may combine all electronics on a single circuit element or board or PCB, whereby the decoder may control all the video and EC features.

Thus, the decoder of the present invention may be readily attached to or connected to a video display module or screen, such as at the rear of the display module. The decoder may be electrically connected to the wire or wires from the camera/cameras and to any other wires of the mirror assembly, whereby the decoder is ready for operation. The decoder thus provides video decoding functions and on screen display functions in a single decoder board. The NTSC (or other standard video input or signal) thus is received by the decoder and is decoded by the decoder, whereby the OSD of the decoder may generate the display signal to the video screen and may send the video display images by themselves or may mix the video signal/images with other display information, such as graphic overlays or textual information or iconistic display information or the like.

For example, and with reference to FIGS. 14 and 15, the decoder may control the video display screen to display video images of a scene captured by one or more cameras of the vehicle, and may generate a graphic overlay that is electronically generated and superimposed on the video image by the decoder. Optionally, the decoder may function to display on the video display other messages or signals for

viewing by the driver of the vehicle. For example, and with reference to FIGS. 16-31, the decoder may function to display camera status information, EC dimming status information, toll information and toll payment card status information, blind spot detection or object detection information, directional heading information, fuel gauge status information, telephone call status information or other telematics system information, vehicle fluid level status information, seat belt status information, tire pressure information, directional heading and/or temperature information, and/or the like.

Typically, a backlit video screen utilized in an interior rearview mirror is provided as a package or module that typically has a 2.4 inch to 4.3 inch diagonal dimension (typically around 3.5 inches) and an aspect ratio of width to height of about 4:3 or about 15:9 or 16:9, and typically has an active area of around 72 mm wide and 53 mm high for a typical 3.5 inch diagonal screen with a 4:3 aspect ratio, with around 70,000-80,000 or thereabouts TFT RGB pixel resolution, or a typical 16:9 aspect ratio screen may have an active area of around 71 mm wide and 43 mm high, with around 96,000 or thereabouts TFT RGB pixel resolution. The video screen module or package has a circuit board and its control circuitry disposed at a rear of the package or module, such as by utilizing aspects of U.S. Pat. Nos. 7,004,593 and 7,370,983, which are hereby incorporated herein by reference in their entireties. Preferably, the circuitry required for operation of the display itself (including the video decoding and control of the backlighting and/or the like) and of the associated rearview mirror (such as electrochromic dimming and/or the like) is established on a printed circuit board or equivalent that attaches at the rear of the video display screen module or package and is roughly dimensioned to be the same as or close to the size and shape of the video display screen module or package.

Thus, the decoder of the present invention may decode the video signal and may provide OSD capability and EC control capability, and may receive inputs from sensors (such as imaging sensors or photosensors or the like), and may receive switch inputs and may control various accessories in response to the user inputs or switch inputs. The decoder may share or access photo sensors to control the dimming of the display. The decoder thus provides a highly integrated TFT flat panel display controller at a reduced cost, and integrates a microprocessor in the single circuit element or board or chip. The decoder may provide UART capability, I²C capability, SPI capability and/or the like. Optionally, the decoder may include a transceiver or the like and the decoder may connect to or link to a LIN node of a network system of the vehicle.

Optionally, the mirror assembly may include or may be associated with a compass sensor and circuitry for a compass system that detects and displays the vehicle directional heading to a driver of the vehicle. Optionally, an integrated automotive "compass-on-a-chip" may be disposed in a cavity of the mounting base of the mirror (or within the mirror housing or in an attachment to the mirror mount or elsewhere within the mirror assembly such as to the rear of the video screen or to the rear of the mirror reflective element) and may comprise at least two magneto-responsive sensor elements (such as a Hall sensor or multiple Hall sensors), associated A/D and D/A converters, associated microprocessor(s) and memory, associated signal processing and filtering, associated display driver and associated LIN/CAN BUS interface and the like, all (or a sub-set thereof) created or disposed or commonly established onto a semiconductor chip surface/substrate or silicon substrate, such as utilizing

CMOS technology and/or fabrication techniques as known in the semiconductor manufacturing arts, and constituting an ASIC chip, such as utilizing principles described in U.S. Pat. Nos. 7,329,013 and/or 7,370,983, and/or U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. 2006/0061008, which are hereby incorporated herein by reference in their entirety, which are hereby incorporated herein by reference in their entirety, and/or such as by utilizing aspects of an EC driver-on-a-chip such as described in U.S. patent application Ser. No. 11/201,661, filed Aug. 11, 2005, now U.S. Pat. No. 7,480,149, which is hereby incorporated herein by reference in its entirety. The ASIC chip may be small (preferably less than approximately a two square centimeter area, more preferably less than approximately a 1.5 square centimeter area, and most preferably less than approximately a one square centimeter area or thereabouts) and readily packagable into the mirror assembly (or a feed from such a compass-on-a-chip may be provided to the mirror assembly from a compass-on-a-chip packaged elsewhere in the vehicle cabin remote from the mirror assembly such as in an instrument panel portion or in roof console portion). Such large scale integration onto the likes of the silicon substrate/chip can allow a compass functionality to be provided by a relatively small chip, and with appropriate pin out or electrical leads provided as is common in the electrical art.

As shown in FIGS. 2-4, a compass chip or compass module **30** may be disposed at an upper end of the mounting base **32** of a mirror assembly **34**, such as at an upper or connecting end of a wire management element **33** connected to or extending from the mounting base **32** of the mirror assembly. The compass chip **30** may have a connector or connecting elements **36** established on the chip substrate. As shown in FIGS. 3-8, compass chip or module **30** includes a housing **30a** having the connector **36** at one end and a housing portion **37** at the other end, with the compass chip circuitry **40** housed within the housing portion **37** and electrically connected to the connector terminals. In the illustrated embodiment, the connector **36** is at the upper end or region of the wire management element at the mounting base and at a portion of the wire management element or mounting base extension that mounts to or has attached to it a wire management element or channel or cover element **38** (FIGS. 3 and 4), such as a wire management system or element of the types described in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. 2006/0061008; and/or Ser. No. 11/584,697, filed Oct. 20, 2006, now U.S. Pat. No. 7,510,287, which are hereby incorporated herein by reference in their entirety.

A wire harness **42** of the vehicle may be routed along channel or cover element **38** and may plug into or readily connect to connector **36** of compass chip **30** to provide the electrical power and/or control to the compass system and to any other circuitry or device or system associated with or established on or connected to the compass chip. Thus, the compass chip is provided at the mounting base of the mirror assembly or at a wire management element at the mounting base of the mirror assembly, and may be readily connected to the vehicle wire harness to enhance the assembly processes at the vehicle assembly plant. The compass chip thus may provide all of the compass electronics and circuitry at the compass chip, whereby no electronics need be provided within the mirror assembly.

The integrated compass chip may be connected to a power in or supply lead or wiring harness (such as a wiring harness

that extends down from the headliner of the vehicle) and may connect to a wiring or harness of the mirror assembly. Preferably, the compass chip may connect between and in-line with the vehicle wiring harness and the mirror wiring harness (which may connect between the mounting base of the mirror assembly and the mirror casing, such as in the manner described in U.S. Pat. Nos. 7,329,013 and/or 7,370,983, and/or U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. 2006/0061008; and/or Ser. No. 11/584,697, filed Oct. 20, 2006, now U.S. Pat. No. 7,510,287, which are hereby incorporated herein by reference in their entirety), or in-line with another plug/socket connector of the vehicle. The integrated compass chip thus may be readily connected, such as via plug-in-socket type connections, to both wires or harnesses to electrically connect the compass chip to the power source and to a display or user interface or input at the mirror. The connectors of the compass chip may be selected such that when the compass chip is not selected as an option of the vehicle, the vehicle wiring harness connects to or plugs into the mirror harness or wiring in the same manner, such that common wiring harnesses and/or connectors may be used at the vehicle and mirror, regardless of whether or not the compass system is included. Thus, an electronic chip (such as an integrated compass-on-a-chip) may be connected in-line with an existing plug/socket arrangement in the vehicle such that the presence of the chip-in-line is largely unnoticed by the vehicle occupants.

Optionally, such a connection can be made to the compass chip via a plug-and-socket type connection between the vehicle wire harness and a connector established at the compass chip. Optionally, the compass chip (such as at the connector end of the compass chip) may include terminals extending therefrom or receiving portions established therein and configured to electrically connect to the vehicle wire harness at the upper region of the mounting base.

Optionally, the compass chip may be disposed at the mirror mounting base, whereby when the wire harness connects to the compass chip, the compass chip may be sealed or encased within the mirror mounting base. Optionally, the compass chip may be disposed inside a connector element and may be substantially sealed or encased therein to protect the circuitry on the compass chip.

For example, and with reference to FIGS. 9-13, a compass chip or compass module **130** may be disposed at an upper end or portion of a mounting base of a mirror assembly **134**, such as at an upper mounting base portion **132a** that is connected to or mounted at or extends from a lower mounting base portion **132b** of the mirror assembly **134**. The compass chip **130** may be disposed within the upper mounting base portion **132a**, which may have a wire **136** and/or a connector or connecting elements established at its upper end for connecting to a vehicle wire harness or the like. The compass chip or circuitry may be disposed within upper mounting portion **132a**, such as at or near the lower region of the upper mounting portion so as to be disposed at or near the fixedly mounted or attached lower mounting base **132b** (which may be fixedly secured to a mounting button or element **140** affixed or adhered to the vehicle windshield). The compass chip of the upper mounting base portion may be similar in construction to the compass chip **30**, described above, such that a detailed discussion of the compass chips need not be repeated herein.

In the illustrated embodiment, the connector or wire **136** extends from the upper end or region of the upper mounting base portion **132a** and may be routed along or within a wire management element or channel or cover element **138** that

11

routes and conceals the wire between the upper mounting base portion **132a** and the vehicle headliner at the upper region of the vehicle windshield. A wire harness of the vehicle may be routed along channel or cover element **138** and may plug into or readily connect to connector or wire **136** of compass chip **130** to provide the electrical power and/or control to the compass system and to any other circuitry or device or system associated with or established on or connected to the compass chip. Optionally, the upper end or portion of the upper mounting base portion may have a connector established thereat, whereby a vehicle wire harness may extend down from the headliner (and along and within a wire management element) for connection to the connector and compass chip at the upper mounting base portion.

As can be seen in FIGS. **10** and **11**, the upper mounting base portion **132a** and the lower mounting base portion **132b** may be configured so that the upper mounting base portion **132a** is readily connectable to the lower mounting base portion **132b**, such as via a plug and socket connecting configuration or the like. Thus, the upper mounting base portion **132a** may be readily mounted to or attached to or plugged into the lower mounting base portion **132b** to position the compass chip at or near the mounting base of the mirror assembly. Optionally, the mounting base portions **132a**, **132b** may include electrical connectors so as facilitate electrical connection of the compass chip and/or vehicle wire harness to electrical circuitry at the lower mounting base portion or at the mirror assembly (such as via a wire or cable or other electrical connection between the lower mounting base portion and the mirror casing or circuitry therein) when the upper mounting base portion is connected to or mounted at the lower mounting base portion.

Thus, the compass chip or compass module is provided at the mounting base of the mirror assembly and may be readily connected to the vehicle wire harness to enhance the assembly processes at the vehicle assembly plant. The compass chip thus may provide all of the compass electronics and circuitry at the compass chip, whereby no electronics need be provided within the mirror assembly (such that the compass chip may be suitable for application to base mirrors, such as base prismatic mirrors and the like).

Thus, the compass chip may be small enough to fit at or in the wire management structure or mounting base structure at the mirror mounting base and may readily connect to the vehicle wire harness to receive power and/or control from the vehicle wire harness. Optionally, the compass chip may include all circuitry and microprocessor needed to operate the compass system and any other associated accessories or systems, and the mirror assembly may not include any circuitry in its mirror casing. Optionally, and desirably, the compass chip or module or housing and/or the wire management element or the upper mounting portion is/are configured to support the compass sensors at an appropriate angle such that the sensors are generally horizontal when the compass chip is mounted along the windshield of the vehicle.

Optionally, such a compass-on-a-chip ASIC may also include the hardware and software required to receive an output from a temperature sensor (such as a thermocouple or thermostat that is located external the vehicle cabin in order to sense and monitor the temperature external to the vehicle) and to convert this signal to a reading in degrees Fahrenheit or Celsius, and to provide this reading via an on-chip temperature display driver and/or via a BUS protocol or via an on-chip wireless transmitter or the like to a digital or other type of temperature display so that the driver and/or

12

occupants of the vehicle can view the temperature being measured (such as the temperature external the vehicle and/or the temperature within the vehicle cabin). Thus, for example, a monolithic compass/temp-on-a-chip ASIC may be disposed in the likes of a mirror mount or within the mirror head/housing of an interior rearview mirror assembly, and it may provide both the external temperature readout and a compass direction heading readout to an information display at the mirror head/housing (or elsewhere in the vehicle, such as the instrument panel/cluster or at an overhead console or accessory module or the like). Optionally, such a chip or circuit board or circuitry may also or otherwise comprise EC driver circuitry for controlling/driving an electro-optic or electrochromic reflective element or cell, such as by utilizing aspects of the EC driver-on-a-chip such as described in U.S. patent application Ser. No. 11/201,661, filed Aug. 11, 2005, now U.S. Pat. No. 7,480,149, which is hereby incorporated herein by reference in its entirety.

The printed circuit board or equivalent may comprise a generally flat, rectangular element or substrate with conductive traces and circuitry disposed thereon. Because it is desired to provide sensing in the x-y directions (or in a horizontal plane), the compass sensor is preferably disposed so that the compass sensor elements are generally horizontal when the mirror assembly is installed in the vehicle.

The compass chip may be in communication with a compass display, which may provide a display region at the reflective element, and which includes ports or portions, which may comprise icons, characters or letters or the like representative of only the cardinal directional points, such as, for example, the characters N, S, E, W, formed or etched in the reflective film coating of the reflective element (and forming a transparent window therein), such as via techniques such as disclosed in commonly assigned U.S. Pat. Nos. 4,882,565 and/or 7,004,593, which are hereby incorporated by reference herein in their entireties. Optionally, however, reflective element may comprise a transmissive or display on demand (DOD) reflective element, and the compass display may be a display on demand (DOD) type of display, such as disclosed in commonly assigned U.S. Pat. Nos. 7,195,381; 6,690,268; 5,668,663 and 5,724,187, which are hereby incorporated by reference herein in their entireties, without affecting the scope of the present invention.

Optionally, the sensor may comprise a two-axis sensor (comprising two magneto-responsive sensor elements disposed at a fixed angle relative to each other, such as, preferably, orthogonally to each other, and disposed in the cavity generally parallel to the floor plane of the vehicle so as to be sensitive to the horizontal component of the Earth's magnetic field), or the sensor may comprise a three-axis sensor (comprising two magneto-responsive sensor elements disposed orthogonally to each other and disposed in the cavity, and a third magneto-responsive sensor element at a right angle (approximately ninety degrees) to the two sensor elements and disposed in the cavity, so that the three-axis sensor is sensitive to the horizontal component and to the vertical component of the Earth's magnetic field), without affecting the scope of the present invention. The sensor may be arranged at a desired angle to provide enhanced sensing in the horizontal directions when the mirror assembly is installed in the vehicle. For example, aspects of constructions such as are disclosed in U.S. Pat. Nos. 6,140,933 and 6,928,366, which are hereby incorporated herein by reference in their entireties, may be utilized.

Optionally, the compass system and compass circuitry may utilize aspects of the compass systems described in U.S.

Pat. Nos. 7,370,983; 7,249,860; 7,004,593; 6,642,851; 4,546,551; 5,699,044; 4,953,305; 5,576,687; 5,632,092; 5,677,851; 5,708,410; 5,737,226; 5,802,727; 5,878,370; 6,087,953; 6,173,508; 6,222,460 and/or 6,513,252, and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004 as International Publication No. WO 2004/103772, and/or European patent application published Oct. 11, 2000 under Publication No. EP 0 1043566, and/or U.S. provisional applications, Ser. No. 60/624,091, filed Nov. 1, 2004; Ser. No. 60/636,931, filed Dec. 17, 2004; Ser. No. 60/638,250, filed Dec. 21, 2004; Ser. No. 60/642,227, filed Jan. 7, 2005; and Ser. No. 60/653,787, filed Feb. 17, 2005, which are all hereby incorporated herein by reference in their entireties. The compass circuitry may include compass sensors, such as a magneto-responsive sensor, such as a magneto-resistive sensor, a magneto-capacitive sensor, a Hall sensor, a magneto-inductive sensor, a flux-gate sensor or the like. The sensor or sensors may be positioned at and within a base portion of the mirror assembly so that the sensor/sensors is/are substantially fixedly positioned within the vehicle, or may be attached or positioned within the mirror casing. Note that the magneto-responsive sensor used with the mirror assembly may comprise a magneto-responsive sensor, such as a magneto-resistive sensor, such as the types disclosed in U.S. Pat. Nos. 5,255,442; 5,632,092; 5,802,727; 6,173,501; 6,427,349 and 6,513,252 (which are hereby incorporated herein by reference in their entireties), or a magneto-inductive sensor, such as described in U.S. Pat. No. 5,878,370 (which is hereby incorporated herein by reference in its entirety), or a magneto-impedance sensor, such as the types described in PCT Publication No. WO 2004/076971, published Sep. 10, 2004 (which is hereby incorporated herein by reference in its entirety), or a Hall-effect sensor, such as the types described in U.S. Pat. Nos. 6,278,271; 5,942,895 and 6,184,679 (which are hereby incorporated herein by reference in their entireties). The sensor circuitry and/or the circuitry in the mirror housing and associated with the sensor may include processing circuitry. For example, a printed circuit board may include processing circuitry which may include compensation methods, such as those described in U.S. Pat. Nos. 4,546,551; 5,699,044; 4,953,305; 5,576,687; 5,632,092; 5,677,851; 5,708,410; 5,737,226; 5,802,727; 5,878,370; 6,087,953; 6,173,508; 6,222,460 and 6,642,851, which are all hereby incorporated herein by reference in their entireties. The compass sensor may be incorporated in or associated with a compass system and/or display system for displaying a directional heading of the vehicle to the driver, such as a compass system of the types described in U.S. Pat. Nos. 5,924,212; 4,862,594; 4,937,945; 5,131,154; 5,255,442; 5,632,092 and/or 7,004,593, and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772, which are all hereby incorporated herein by reference in their entireties.

Optionally, and as shown in FIG. 1, the mirror assembly may comprise an electro-optic or electrochromic mirror assembly and may include an electro-optic or electrochromic reflective element. The electrochromic mirror element of the electrochromic mirror assembly may utilize the principles disclosed in commonly assigned U.S. Pat. Nos. 6,690,268; 5,140,455; 5,151,816; 6,178,034; 6,154,306; 6,002,544; 5,567,360; 5,525,264; 5,610,756; 5,406,414; 5,253,109; 5,076,673; 5,073,012; 5,117,346; 5,724,187; 5,668,663; 5,910,854; 5,142,407 and/or 4,712,879, and/or U.S. provisional applications, Ser. No. 61/232,246, filed Aug. 7, 2009; Ser. No. 61/186,204, filed Jun. 11, 2009; and Ser. No.

61/164,593, filed Mar. 30, 2009, which are hereby incorporated herein by reference in their entireties, and/or as disclosed in the following publications: N. R. Lynam, "Electrochromic Automotive Day/Night Mirrors", SAE Technical Paper Series 870636 (1987); N. R. Lynam, "Smart Windows for Automobiles", SAE Technical Paper Series 900419 (1990); N. R. Lynam and A. Agrawal, "Automotive Applications of Chromogenic Materials", Large Area Chromogenics: Materials and Devices for Transmittance Control, C. M. Lampert and C. G. Granquist, EDS., Optical Engineering Press, Wash. (1990), which are hereby incorporated by reference herein in their entireties; and/or as described in U.S. Pat. No. 7,195,381, which is hereby incorporated herein by reference in its entirety. Optionally, the electrochromic circuitry and/or a glare sensor (such as a rearward facing glare sensor that receives light from rearward of the mirror assembly and vehicle through a port or opening along the casing and/or bezel portion and/or reflective element of the mirror assembly) and circuitry and/or an ambient light sensor and circuitry may be provided on one or more circuit boards of the mirror assembly. The mirror assembly may include one or more other displays, such as the types disclosed in U.S. Pat. Nos. 5,530,240 and/or 6,329,925, which are hereby incorporated herein by reference in their entireties, and/or display-on-demand transfective type displays, such as the types disclosed in U.S. Pat. Nos. 7,274,501; 7,255,451; 7,195,381; 7,184,190; 5,668,663; 5,724,187 and/or 6,690,268, and/or in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005; and/or Ser. No. 10/538,724, filed Jun. 13, 2005, and/or PCT Application No. PCT/US03/29776, filed Sep. 9, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633, which are all hereby incorporated herein by reference in their entireties. The thicknesses and materials of the coatings on the substrates, such as on the third surface of the reflective element assembly, may be selected to provide a desired color or tint to the mirror reflective element, such as a blue colored reflector, such as is known in the art and such as described in U.S. Pat. Nos. 5,910,854; 6,420,036 and/or 7,274,501, and in PCT Application No. PCT/US03/29776, filed Sep. 9, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633, which are all hereby incorporated herein by reference in their entireties.

For example, and with reference to FIG. 32, a mirror reflective element assembly **210** may comprise an electro-optic (such as electrochromic) mirror reflective element assembly with a first or front substrate **212** having a first or front surface **212a** (the surface generally facing the driver of a vehicle when the mirror reflective element assembly is normally mounted in the vehicle) and a second or rear surface **212b** and a second or rear substrate **214** having a third or front surface **214a** and a fourth or rear surface **214b**. A perimeter seal **216** is disposed between the front and rear substrates and spaces the substrates apart and defines an interpane cavity between the substrates with an electro-optic (such as electrochromic) medium **218** disposed within the interpane cavity and contacting a transparent conductive layer or coating **220** at the second surface **212b** of front substrate **212** and a metallic reflector layer or coating **222** at the third surface **214a** of rear substrate **214**. A light absorbing layer or coating or film **224** may be disposed at the rear or fourth surface **214b** of rear substrate **214**. Optionally, the third surface or rear surface of the rear substrate may have a transparent conductive coating established thereat and a metallic reflector may be disposed at the fourth surface or rear surface of the rear substrate. In such an embodiment, the

15

mirror reflective element assembly need not include the light absorbing layer at the rear surface of the rear substrate.

Optionally, and with reference to FIG. 33, a mirror reflective element assembly 210' may include a transparent organic light emitting diode (OLED) display element or device 230' disposed at a display region or portion of front substrate 212 and in front of the front substrate 212. In the illustrated embodiment, transparent OLED display 230' is disposed at first or front surface 212a of front substrate 212, with a thin or ultra-thin glass cover sheet 232' (such as a thin glass cover sheet having a thickness of less than about 1 mm and preferably less than about 0.5 mm or thereabouts and greater than 0.1 mm) disposed over the front substrate 212 and the OLED display 230'. The cover sheet 232' may be attached to the front substrate 212, such as via a laminating material 234' between the front surface 212a of front substrate 212 and a rear surface 232b' of cover sheet 232'. The reflective element assembly 210' includes transparent electrically conductive tracks or layers 236' disposed at the front or first surface 212a of front substrate 212 to facilitate electrical connection to the OLED display 230'. Optionally, the conductive tracks or layers 236' (such as transparent tracks or raceways of indium tin oxide (ITO) or the like) may extend over and encompass the perimeter edge of the front substrate so as to provide a wraparound electrically conductive track to ease electrical connection to the transparent OLED display. In this or in a similar manner, electrical power and/or signals may be delivered to the transparent OLED display via transparent conductors/transparent conductor paths established such as at the front surface of the front substrate and at or near the perimeter region of the reflective element assembly so as to be at least partially and preferably substantially non-discernible/non-visible to a driver viewing the reflective element assembly when the mirror assembly and reflective element assembly are normally mounted in the vehicle.

Optionally, and with reference to FIG. 34, a mirror reflective element assembly 210" may include a transparent organic light emitting diode (OLED) display element or device 230" that may comprise the front of the front substrate of the reflective element assembly. In the illustrated embodiment, OLED display 230" has a transparent electrically conductive layer or coating 220" disposed at its rear or second surface 230b" and a transparent electrically conductive layer 221" disposed at its front or first surface 230a". The transparent OLED display 230" thus encompasses substantially the entire reflective element assembly, and may have a thin or ultra-thin glass cover sheet 232" disposed over and laminated to OLED display 230" (such as at the transparent electrically conductive layer 221" at the front or first surface 230a" of transparent OLED display 230") via a laminating material 234". Optionally, the transparent OLED display may comprise an outer or front substrate or panel of the reflective element assembly, and the reflective element assembly may not include the thin or ultrathin cover sheet over the display.

The OLED display preferably comprises a substantially transparent display that is substantially transparent when not activated or energized. Optionally, for example, the OLED display may comprise a transparent OLED display element of the types commercially available from NeoView Kolon Co., Ltd. [see www.neoviewkolon.com]. For example, and as shown in FIGS. 35 and 36, the transparent OLED display may include an organic film structure and electrodes established at the front surface or first surface of a substrate, such as a glass substrate of the reflective element assembly. An encapsulation layer may encapsulate the transparent metal

16

cathodes and ITO anodes (or other transparent electrically conductive anodes), with an emission layer disposed between the metal cathode and ITO anode. As can be seen in FIG. 36, an electron transport layer, an emission layer, a hole transport layer and a hole injection layer are sandwiched between a transparent electrically conductive ITO anode (that is disposed on a glass substrate) and a transmissive metal cathode that has a very low to negligible reflection and a high transmission (such as at least at least about 50 percent transmissive of visible light therethrough, more preferably at least about 65 percent transmissive of visible light therethrough, and more preferably at least about 75 percent transmissive of visible light therethrough). Alternately, the low reflection/high transmittance metal cathode (which typically is a very thin metal thin film layer) may be replaced with a transparent conductive layer. Optionally, such as shown in FIG. 34, the glass substrate of the transparent OLED display may be coated at its rear surface with a transparent conductive coating (such as ITO or the like) and the electro-optic medium may abut the rear surface of the substrate of the transparent OLED display.

When an electric current is passed between the electrodes, light is emitted with a color that is dependent on the particular materials used in the construction of the OLED display. Such a transparent OLED display may be formed as a thin layer (such as a layer about 0.01 μm or thereabouts) with a metal layer or layers that has/have lower reflection and higher transmission properties as compared to higher reflective metallic materials typically used as electrodes. For example, a transparent OLED display of the mirror reflective element assembly of the present invention is preferably at least about 50 percent transmissive of visible light therethrough, more preferably at least about 65 percent transmissive of visible light therethrough, and more preferably at least about 75 percent transmissive of visible light therethrough, and is preferably substantially spectrally non-selective or untinted and presenting a water clear view therethrough, such that the presence of the transparent OLED display is not readily discernible in front of the mirror reflector when the display is not activated or energized and when a person is viewing the mirror reflective assembly when the reflective element assembly and mirror assembly are normally mounted in the vehicle (such as shown in FIG. 37B).

When the transparent OLED display is energized (such as shown in FIG. 37A), the transparent OLED display may display information at a display intensity of at least about 200 candelas per square meter (cd/m^2) and preferably at least about 400 cd/m^2 , and more preferably at least about 1,000 cd/m^2 , so as to exhibit good contrast against the reflections off the mirror reflector therebehind when viewed by the driver of the vehicle equipped with the reflective element assembly and transparent OLED display, particularly on a sunny day. Because the transparent OLED display is disposed at the front surface of the front substrate of the reflective element assembly, the display information displayed by the transparent OLED display need not pass through a transmissive mirror reflector coating at the third surface of the rear substrate, and thus the intensity of the display information is not reduced or attenuated by the mirror reflector of the mirror reflective element assembly. Optionally, and desirably, the intensity of the display may be controlled or adjusted responsive to a detected ambient light level at the mirror assembly and/or vehicle (such as responsive to an ambient light sensor of the mirror assembly of the like).

Because the transparent OLED display is disposed in front of the front surface of the reflective element assembly, the third surface reflector coating 222 at the front or third surface 214a of rear substrate 214 need not comprise a transreflective coating or layer (i.e., a metallic layer or layers that is partially transmitting of light therethrough and partially reflective of light incident thereon). However, optionally, the third surface reflector coating 222 may comprise a transreflective layer and the mirror reflective element assembly may have another display element disposed behind the rear or fourth surface 214b of rear substrate 214 and operable to transmit display information through the third surface reflector coating 222 for viewing by a person viewing the mirror assembly when the mirror assembly and reflective element assembly are normally mounted in a vehicle.

Thus, by placing a transparent OLED information display, such as a transparent OLED multipixel video display, at the front of the mirror reflective element assembly and in front of the mirror reflector, a video mirror can be formed (and may be suitable for use with the likes of a vision or imaging system of the vehicle, such as, for example, a reverse or backup aid system, such as a rearwardly directed vehicle vision system utilizing principles disclosed in U.S. Pat. Nos. 5,550,677; 5,760,962; 5,670,935; 6,201,642; 6,396,397; 6,498,620; 6,717,610 and/or 6,757,109, which are hereby incorporated herein by reference in their entireties, a trailer hitching aid or tow check system, such as the type disclosed in U.S. Pat. No. 7,005,974, which is hereby incorporated herein by reference in its entirety, a cabin viewing or monitoring device or system, such as a baby viewing or rear seat viewing camera or device or system or the like, such as disclosed in U.S. Pat. Nos. 5,877,897 and/or 6,690,268, which are hereby incorporated herein by reference in their entireties, a video communication device or system, such as disclosed in U.S. Pat. No. 6,690,268, which is hereby incorporated herein by reference in its entirety) without a need to utilize a transreflective mirror reflector, and being transparent, the images and/or icons and/or characters and/or the like displayed by the transparent OLED display can be displayed on demand and appear contrasted with the reflected scene in the mirror reflective element. The presence of the transparent OLED information display device (such as a transparent OLED video display screen) in front of the mirror reflector is substantially non-discernible to a viewer viewing the mirror reflective element assembly by reason of the transparent OLED device comprising a substantially transparent substrate. Optionally, although shown and described as being disposed at the front of an electro-optic mirror reflective element assembly, a non-electro-optic mirror reflective element (such as a prismatic reflective element or a flat or curved or bent single substrate reflective element or the like) may incorporate a transparent OLED display thereat, while remaining within the spirit and scope of the present invention.

Optionally, the interior rearview mirror assembly may comprise a prismatic mirror assembly or a non-electro-optic mirror assembly or an electro-optic or electrochromic mirror assembly. For example, the interior rearview mirror assembly may comprise a prismatic mirror assembly, such as the types described in U.S. Pat. Nos. 7,249,860; 6,318,870; 6,598,980; 5,327,288; 4,948,242; 4,826,289; 4,436,371 and 4,435,042; and PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772, which are hereby incorporated herein by reference in their entireties. Optionally, the prismatic reflective element may comprise a conventional prismatic reflective element or prism or may

comprise a prismatic reflective element of the types described in U.S. Pat. Nos. 7,420,756; 7,274,501; 7,249,860; 7,338,177 and/or 7,255,451, and/or PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633; and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; and U.S. provisional application Ser. No. 60/525,952, filed Nov. 26, 2003, which are all hereby incorporated herein by reference in their entireties, without affecting the scope of the present invention. A variety of mirror accessories and constructions are known in the art, such as those disclosed in U.S. Pat. Nos. 5,555,136; 5,582,383; 5,680,263; 5,984,482; 6,227,675; 6,229,319 and 6,315,421 (the entire disclosures of which are hereby incorporated by reference herein), that can benefit from the present invention.

Optionally, the display screen and/or mirror may include user interface inputs, such as buttons or switches or touch or proximity sensors or the like, with which a user may adjust one or more characteristics of the imaging sensor and/or imaging system, such as via the principles described in U.S. patent application Ser. No. 12/091,525, filed Apr. 25, 2008, now U.S. Pat. No. 7,855,755; and/or Ser. No. 11/239,980, filed Sep. 30, 2005, now U.S. Pat. No. 7,881,496, and/or U.S. provisional applications, Ser. No. 60/614,644, filed Sep. 30, 2004; Ser. No. 60/618,686, filed Oct. 14, 2004; and Ser. No. 60/628,709, filed Nov. 17, 2004, which are hereby incorporated herein by reference in their entireties. Optionally, the images captured by the imaging sensor or camera may be processed by the control to extract information or data for different applications or systems, such as described in U.S. patent application Ser. No. 11/239,980, filed Sep. 30, 2005, now U.S. Pat. No. 7,881,496, and/or U.S. provisional application Ser. No. 60/618,686, filed Oct. 14, 2004, which are hereby incorporated herein by reference in their entireties.

The control of the mirror assembly and/or the display screen may receive image data or the like from an imaging sensor or camera positioned elsewhere at or on or in the vehicle, such as at a rearward portion of the vehicle with a rearward exterior field of view, or such as at an interior portion (such as at or near or associated with the interior rearview mirror assembly or an accessory module or windshield electronics module or the like) of the vehicle with an interior field of view (such as into the vehicle cabin) or an exterior field of view (such as forwardly of and through the windshield of the vehicle). The signal from the camera or image data may be communicated to the control via various communication links or video transmission medium, such as wires or cables (such as a CAT-3 shielded twisted pair wire or a CAT-5 coaxial cable or the like) or a fiber optic cable or via wireless communication, such as IR signals or VHF or UHF signals or the like, or via a multiplex bus system of the vehicle or the like. For example, the connection or link between the imaging sensor or controls and the mirror assembly and/or display screen module may be provided via vehicle electronic or communication systems and the like, and may be connected via various protocols or nodes, such as BLUETOOTH®, SCP, UBP, J1850, CAN J2284, Fire Wire 1394, MOST, LIN, FLEXRAY™, Byte Flight and/or the like, or other vehicle-based or in-vehicle communication links or systems (such as WIFI and/or IRDA), or via wireless communications such as VHF or UHF signals, and/or the like, depending on the particular application of the mirror/display system and the vehicle.

The imaging sensor or camera may provide various image data signals, such as an NTSC signal or LVDS, PAL, analog RGB, component video, SECAM, S-video or the like. Optionally, the imaging system may be operable to selectively switch between, for example, PAL and NTSC, to adjust the imaging system and mirror/display system to accommodate European and U.S. applications.

The interior rearview mirror assembly may include a bezel portion and casing, such as described above, or the mirror assembly may comprise other types of casings or bezel portions or the like, such as described in U.S. Pat. Nos. 7,249,860; 6,439,755; 4,826,289 and 6,501,387; and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; and/or U.S. patent applications, and/or Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177; and/or U.S. provisional application Ser. No. 60/525,952, filed Nov. 26, 2003, which are all hereby incorporated herein by reference in their entireties, without affecting the scope of the present invention. For example, the mirror assembly may comprise a flush or frameless or bezelless reflective element, such as the types described in U.S. Pat. Nos. 7,255,451; 7,274,501 and/or 7,184,190, and/or in PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; PCT Application No. PCT/US03/35381, filed Nov. 5, 2003 and published May 21, 2004 as International Publication No. WO 2004/042457; and/or in U.S. patent application Ser. No. 11/140,396, filed May 27, 2005, now U.S. Pat. No. 7,360,932; Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. 2006/0061008; Ser. No. 11/912,576, filed Oct. 25, 2005, now U.S. Pat. No. 7,626,749; and/or Ser. No. 10/538,724, filed Jun. 13, 2005 and published Mar. 9, 2006 as U.S. Publication No. 2006/0050018; and/or in U.S. provisional applications, Ser. No. 60/563,342, filed Apr. 19, 2004; Ser. No. 60/629,926, filed Nov. 22, 2004; Ser. No. 60/624,320, filed Nov. 2, 2004; Ser. No. 60/681,250, filed May 16, 2005; Ser. No. 60/690,400, filed Jun. 14, 2005; Ser. No. 60/695,149, filed Jun. 29, 2005; and/or Ser. No. 60/730,334, filed Oct. 26, 2005, which are all hereby incorporated herein by reference in their entireties.

Optionally, the mirror assembly may comprise a modular mirror construction, and may include back housing portions or the like, such as cap portions of the types described in PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772, which is hereby incorporated herein by reference in its entirety. The display screen may be provided as a modular display screen and may be mountable or installable in the appropriate or suitable mirror casing to provide a modular mirror assembly and display screen. For example, a rear casing or cap portion may include the display screen module including the associated components, such as the rails and motor and the like, and may be attachable to a reflective element and/or bezel portion to assemble the modular mirror assembly. The display screen module thus may be provided as an optional component or accessory for a vehicle, and may be readily assembled to a common reflective element and/or bezel portion of the mirror assembly.

Optionally, the mirror casing and/or reflective element, and/or the display screen casing and/or display screen may include customized or personalized viewable characteristics, such as color or symbols or indicia selected by the vehicle manufacturer or owner of the vehicle, such as the customization characteristics described in PCT Application No.

PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; and/or U.S. patent application Ser. No. 11/912,576, filed Oct. 25, 2005, now U.S. Pat. No. 7,626,749; Ser. No. 11/243,783, filed Oct. 5, 2005 and published Apr. 20, 2006 as U.S. Publication No. 2006-0082192; and/or Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or U.S. provisional applications, Ser. No. 60/553,842, filed Mar. 17, 2004; Ser. No. 60/563,342, filed Apr. 19, 2004; Ser. No. 60/629,926, filed Nov. 22, 2004; Ser. No. 60/681,250, filed May 16, 2005; Ser. No. 60/690,400, filed Jun. 14, 2005; Ser. No. 60/695,149, filed Jun. 29, 2005; Ser. No. 60/730,334, filed Oct. 26, 2005; and/or Ser. No. 60/616,182, filed Oct. 5, 2004, which are hereby incorporated herein by reference in their entireties. For example, the frame or casing of the display module and/or the mirror assembly may be selected to have a desired color or combination of colors (or text or print or indicia thereon) to personalize the appearance of the mirror assembly. Optionally, the reflective element may include text or symbols or icons or other characters or indicia to provide a desired appearance or message at the mirror assembly or display screen, such as by utilizing aspects of the mirror assembly described in PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; and/or U.S. patent application Ser. No. 11/912,576, filed Oct. 25, 2005, now U.S. Pat. No. 7,626,749; Ser. No. 11/243,783, filed Oct. 5, 2005 and published Apr. 20, 2006 as U.S. Publication No. 2006-0082192, which are hereby incorporated herein by reference in their entireties. The icons or characters or indicia may be formed at or near or on the display screen, or may be provided via graphic overlays when the display screen is extended and operating, or may otherwise be formed or provided at or on or in the display screen casing or frame, without affecting the scope of the present invention. Optionally, the bezel or frame color or colors may be selected to be designer colors or may match or contrast the color of the mirror casing, and/or may have logos or icons or other indicia thereon. Optionally, the display screen module may include warnings or other statements or alerts or messages printed or otherwise formed on the bezel or frame portion of the display screen so that the messages or the like are readily viewable when the display screen is extended.

Optionally, the mirror assembly and/or prismatic or electrochromic reflective element may include one or more displays, such as for the accessories or circuitry described herein. The displays may be similar to those described above, or may be of types disclosed in U.S. Pat. Nos. 5,530,240 and/or 6,329,925, which are hereby incorporated herein by reference in their entireties, and/or may be display-on-demand or transfective type displays, such as the types disclosed in U.S. Pat. Nos. 7,195,381; 6,690,298; 5,668,663 and/or 5,724,187, and/or in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. 2006/0061008; and/or Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177; and/or in U.S. provisional applications, Ser. No. 60/525,952, filed Nov. 26, 2003; Ser. No. 60/717,093, filed Sep. 14, 2005; and/or Ser. No. 60/732,245, filed Nov. 1, 2005, and/or in PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633, which are all hereby incorporated herein by reference in their entireties. Optionally, a prismatic reflective element may comprise a display on demand or transfective prismatic element (such as described in PCT Application No. PCT/US03/29776, filed

Sep. 19, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633; and/or U.S. patent application Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177; and/or U.S. provisional application Ser. No. 60/525,952, filed Nov. 26, 2003, which are all hereby incorporated herein by reference in their entireties) so that the displays are viewable through the reflective element, while the display area still functions to substantially reflect light, in order to provide a generally uniform prismatic reflective element even in the areas that have display elements positioned behind the reflective element.

Optionally, the display and any associated user inputs may be associated with various accessories or systems, such as, for example, a tire pressure monitoring system or a passenger air bag status or a garage door opening system or a telematics system or any other accessory or system of the mirror assembly or of the vehicle or of an accessory module or console of the vehicle, such as an accessory module or console of the types described in U.S. Pat. Nos. 6,877,888; 6,824,281; 6,690,268; 6,672,744; 6,386,742 and 6,124,886, and/or, and/or PCT Application No. PCT/US03/03012, filed Jan. 31, 2003 and published Aug. 7, 2003 as International Publication No. WO 03/065084, and/or PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 and published Jul. 15, 2004 as International Publication No. WO 2004/058540, and/or PCT Application No. PCT/US04/15424, filed May 18, 2004 and published on Dec. 2, 2004, as International Publication No. WO 2004/103772, which are hereby incorporated herein by reference in their entireties.

Optionally, the user inputs of the mirror assembly or display or module may comprise other types of buttons or switches for controlling or activating/deactivating one or more electrical accessories or devices of or associated with the mirror assembly. The mirror assembly may comprise any type of switches or buttons, such as touch or proximity sensing switches, such as touch or proximity switches of the types described above, or the inputs may comprise other types of buttons or switches, such as those described in U.S. patent application Ser. No. 11/029,695, filed Jan. 5, 2005, now U.S. Pat. No. 7,253,723; and/or U.S. provisional applications, Ser. No. 60/553,517, filed Mar. 16, 2004; Ser. No. 60/535,559, filed Jan. 9, 2004; Ser. No. 60/690,401, filed Jun. 14, 2005; and Ser. No. 60/719,482, filed Sep. 22, 2005, which are hereby incorporated herein by reference in their entireties, or such as fabric-made position detectors, such as those described in U.S. Pat. Nos. 6,504,531; 6,501,465; 6,492,980; 6,452,479; 6,437,258 and 6,369,804, which are hereby incorporated herein by reference in their entireties. For example, the inputs may comprise a touch or proximity sensor of the types commercially available from TouchSensor Technologies, LLC of Wheaton, IL. The touch or proximity sensor may be operable to generate an electric field and to detect the presence of a conductive mass entering the field. When a voltage is applied to the sensor, the sensor generates the electric field, which emanates through any dielectric material, such as plastic or the like, at the sensor. When a conductive mass (such as a person's finger or the like, or metal or the like) enters the electric field, the sensor may detect a change in the field and may indicate such a detection. Other types of switches or buttons or inputs or sensors may be incorporated to provide the desired function, without affecting the scope of the present invention.

Optionally, the user inputs or buttons may comprise user inputs for a garage door opening system, such as a vehicle based garage door opening system of the types described in U.S. Pat. Nos. 6,396,408; 6,362,771; 7,023,322 and 5,798,688, and/or U.S. provisional applications, Ser. No. 60/502,

806, filed Sep. 12, 2003; and Ser. No. 60/444,726, filed Feb. 4, 2003, which are hereby incorporated herein by reference in their entireties. The user inputs may also or otherwise function to activate and deactivate a display or function or accessory, and/or may activate/deactivate and/or commence a calibration of a compass system of the mirror assembly and/or vehicle. The compass system may include compass sensors and circuitry within the mirror assembly or within a compass pod or module at or near or associated with the mirror assembly. Optionally, the user inputs may also or otherwise comprise user inputs for a telematics system of the vehicle, such as, for example, an ONSTAR® system as found in General Motors vehicles and/or such as described in U.S. Pat. Nos. 4,862,594; 4,937,945; 5,131,154; 5,255,442; 5,632,092; 5,798,688; 5,971,552; 5,924,212; 6,243,003; 6,278,377 and 6,420,975; 6,477,464; 6,946,978; 7,308,341; 7,167,796; 7,004,593 and/or 6,678,614, and/or PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 and published Jul. 15, 2004 as International Publication No. WO 2004/058540, and/or PCT Application No. PCT/US03/308877, filed Oct. 1, 2003 and published Apr. 15, 2004 as International Publication No. WO 2004/032568, which are all hereby incorporated herein by reference in their entireties.

Optionally, the mirror assembly may include one or more other accessories at or within the mirror casing, such as one or more electrical or electronic devices or accessories, such as antennas, including global positioning system (GPS) or cellular phone antennas, such as disclosed in U.S. Pat. No. 5,971,552, a communication module, such as disclosed in U.S. Pat. No. 5,798,688, a blind spot detection system, such as disclosed in U.S. Pat. Nos. 5,929,786 and/or 5,786,772, transmitters and/or receivers, such as a garage door opener or the like, a digital network, such as described in U.S. Pat. No. 5,798,575, a high/low headlamp controller, such as disclosed in U.S. Pat. Nos. 5,796,094 and/or 5,715,093, a memory mirror system, such as disclosed in U.S. Pat. No. 5,796,176, a hands-free phone attachment, a video device for internal cabin surveillance and/or video telephone function, such as disclosed in U.S. Pat. Nos. 5,760,962 and/or 5,877,897, a remote keyless entry receiver, lights, such as map reading lights or one or more other lights or illumination sources, such as disclosed in U.S. Pat. Nos. 6,690,268; 5,938,321; 5,813,745; 5,820,245; 5,673,994; 5,649,756; 5,178,448; 5,671,996; 4,646,210; 4,733,336; 4,807,096; 6,042,253; 5,669,698; 7,195,381; 6,971,775 and/or 7,249,860, microphones, such as disclosed in U.S. Pat. Nos. 6,243,003; 6,278,377 and/or 6,420,975; and/or U.S. patent application Ser. No. 10/529,715, filed Mar. 30, 2005, now U.S. Pat. No. 7,657,052; and/or PCT Application No. PCT/US03/30877, filed Oct. 1, 2003, and published Apr. 15, 2004 as International Publication No. WO 2004/032568, speakers, antennas, including global positioning system (GPS) or cellular phone antennas, such as disclosed in U.S. Pat. No. 5,971,552, a communication module, such as disclosed in U.S. Pat. No. 5,798,688, a voice recorder, a blind spot detection system, such as disclosed in U.S. Pat. Nos. 5,929,786 and/or 5,786,772, and/or U.S. patent application Ser. No. 10/427,051, filed Apr. 30, 2003, now U.S. Pat. No. 7,038,577; and Ser. No. 10/209,173, filed Jul. 31, 2002, now U.S. Pat. No. 6,882,287; and/or U.S. provisional application Ser. No. 60/638,687, filed Dec. 23, 2004, transmitters and/or receivers, such as for a garage door opener or a vehicle door unlocking system or the like (such as a remote keyless entry system), a digital network, such as described in U.S. Pat. No. 5,798,575, a high/low headlamp controller, such as a camera-based headlamp control, such as disclosed in U.S. Pat.

23

Nos. 5,796,094 and/or 5,715,093, a memory mirror system, such as disclosed in U.S. Pat. No. 5,796,176, a hands-free phone attachment, an imaging system or components or circuitry or display thereof, such as an imaging and/or display system of the types described in U.S. Pat. Nos. 6,690,268 and 6,847,487; and/or U.S. provisional applications, Ser. No. 60/614,644, filed Sep. 30, 2004; Ser. No. 60/618,686, filed Oct. 14, 2004; Ser. No. 60/628,709, filed Nov. 17, 2004; Ser. No. 60/644,903, filed Jan. 11, 2005; Ser. No. 60/667,049, filed Mar. 31, 2005; and/or U.S. patent application Ser. No. 11/105,757, filed Apr. 14, 2005, now U.S. Pat. No. 7,526,103, a video device for internal cabin surveillance (such as for sleep detection or driver drowsiness detection or the like) and/or video telephone function, such as disclosed in U.S. Pat. Nos. 5,760,962 and/or 5,877,897, a remote keyless entry receiver, a seat occupancy detector, a remote starter control, a yaw sensor, a clock, a carbon monoxide detector, status displays, such as displays that display a status of a door of the vehicle, a transmission selection (4wd/2wd or traction control (TCS) or the like), an antilock braking system, a road condition (that may warn the driver of icy road conditions) and/or the like, a trip computer, a tire pressure monitoring system (TPMS) receiver (such as described in U.S. Pat. Nos. 6,124,647; 6,294,989; 6,445,287; 6,472,979; 6,731,205 and/or 7,423,522, and/or U.S. provisional application Ser. No. 60/611,796, filed Sep. 21, 2004), and/or an ONSTAR® system, a compass, such as disclosed in U.S. Pat. Nos. 5,924,212; 4,862,594; 4,937,945; 5,131,154; 5,255,442 and/or 5,632,092, an alert system and/or components or elements thereof (such as described in U.S. provisional applications, Ser. No. 61/180,257, filed May 21, 2009; Ser. No. 61/156,184, filed Feb. 27, 2009; and Ser. No. 61/174,596, filed May 1, 2009, which are hereby incorporated herein by reference in their entireties), and/or any other accessory or circuitry or the like (with all of the above-referenced patents and PCT and U.S. patent applications being commonly assigned, and with the disclosures of the referenced patents and patent applications being hereby incorporated herein by reference in their entireties).

Optionally, the accessory or accessories, such as those described above and/or below, may be positioned at or within the mirror casing and may be included on or integrated in a printed circuit board positioned within the mirror casing, such as along a rear surface of the reflective element or elsewhere within a cavity defined by the casing, without affecting the scope of the present invention. The user actuable inputs and/or touch sensors and/or proximity sensors and displays described above may be actuable to control and/or adjust the accessories of the mirror assembly/system and/or overhead console and/or accessory module and/or vehicle. The connection or link between the controls and the display screen device and/or the navigation system and/or other systems and accessories of the mirror system may be provided via vehicle electronic or communication systems and the like, and may be connected via various protocols or nodes, such as BLUETOOTH®, SCP, UBP, J1850, CAN J2284, Fire Wire 1394, MOST, LIN, FLEXRAY™, Byte Flight and/or the like, or other vehicle-based or in-vehicle communication links or systems (such as WIFI and/or IRDA) and/or the like, or via VHF or UHF or other wireless transmission formats, depending on the particular application of the mirror/accessory system and the vehicle. Optionally, the connections or links may be provided via various wireless connectivity or links, without affecting the scope of the present invention.

Changes and modifications in the specifically described embodiments may be carried out without departing from the

24

principles of the present invention, which is intended to be limited only by the scope of the appended claims as interpreted according to the principles of patent law.

The invention claimed is:

1. A vehicular video camera display system, the vehicular video camera display system comprising:

an interior rearview mirror assembly disposed at an in-cabin side of a windshield of a vehicle equipped with the vehicular video camera display system;

wherein the interior rearview mirror assembly comprises a mirror head accommodating an electrochromic reflective element;

wherein the electrochromic reflective element comprises a front glass substrate and a rear glass substrate with an electrochromic medium sandwiched therebetween;

wherein the front glass substrate comprises a planar first side and a planar second side separated by a thickness of the front glass substrate, and wherein a transparent electrically conductive coating is disposed at the planar second side of the front glass substrate;

wherein the rear glass substrate comprises a planar third side and a planar fourth side separated by a thickness of the rear glass substrate, and wherein a mirror reflector is disposed at the planar third side of the rear glass substrate;

wherein the electrochromic medium is disposed in a cavity between the planar second side of the front glass substrate and the planar third side of the rear glass substrate;

wherein the cavity is established by a seal that spaces the planar second side of the front glass substrate from the planar third side of the rear glass substrate;

wherein the electrochromic medium contacts the transparent electrically conductive coating disposed at the planar second side of the front glass substrate and contacts the mirror reflector disposed at the planar third side of the rear glass substrate;

wherein the mirror reflector disposed at the planar third side of the electrochromic reflective element comprises a transreflective mirror reflector that at least partially reflects light incident thereon and that at least partially transmits incident light therethrough;

wherein a video display device is disposed in the mirror head behind the electrochromic reflective element;

wherein, with the interior rearview mirror assembly disposed at the in-cabin side of the windshield of the equipped vehicle, a video display screen of the video display device is operable to display video images that are viewable through the electrochromic reflective element by a driver of the equipped vehicle who is viewing the interior rearview mirror assembly disposed at the in-cabin side of the windshield of the equipped vehicle;

a rearward-viewing video camera disposed at the equipped vehicle;

the rearward-viewing video camera viewing at least rearward of the equipped vehicle;

the rearward-viewing video camera comprising a CMOS imaging array sensor operable to capture image data; wherein image data captured by the rearward-viewing video camera is provided to and processed at control circuitry;

wherein the control circuitry links to a vehicular bus network system of the equipped vehicle;

25

wherein image data captured by the rearward-viewing video camera is communicated as a digital signal from the rearward-viewing video camera via a cable to the control circuitry;
 wherein the cable comprises a coaxial cable;
 wherein the interior rearview mirror assembly comprises a video device operable for surveillance of an internal cabin of the equipped vehicle;
 wherein the video display device displays video images that are derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry; and
 wherein the control circuitry controls display at the video display device of the video images derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

2. The vehicular video camera display system of claim 1, wherein no part of the rear glass substrate extends beyond any part of the front glass substrate.

3. The vehicular video camera display system of claim 1, wherein the vehicular bus network system of the equipped vehicle comprises a Local Interconnect Network (LIN).

4. The vehicular video camera display system of claim 1, wherein the vehicular bus network system of the equipped vehicle comprises a Controller Area Network (CAN).

5. The vehicular video camera display system of claim 1, wherein the control circuitry is operable to generate at least one graphic overlay that is electronically generated and is superimposed on video images displayed at the video display device that are derived, at least in part, from the image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

6. The vehicular video camera display system of claim 1, wherein the control circuitry has Universal Asynchronous Receiver/Transmitter (UART) capability.

7. The vehicular video camera display system of claim 1, wherein the control circuitry has Inter-Integrated Circuit (I²C) capability.

8. The vehicular video camera display system of claim 1, wherein the control circuitry has Serial Peripheral Interface (SPI) capability.

9. The vehicular video camera display system of claim 1, wherein the control circuitry is disposed at the interior rearview mirror assembly.

10. The vehicular video camera display system of claim 9, wherein the control circuitry comprises circuitry operable to control dimming of the electrochromic reflective element.

11. The vehicular video camera display system of claim 10, wherein the interior rearview mirror assembly includes (i) a glare light sensor for sensing glare light at the electrochromic reflective element and (ii) an ambient light sensor for sensing ambient light at the interior rearview mirror assembly, and wherein the control circuitry controls dimming of the electrochromic reflective element responsive to sensing of glare light by the glare light sensor and to sensing of ambient light by the ambient light sensor.

12. The vehicular video camera display system of claim 10, wherein the control circuitry, when the electrochromic reflective element is dimmed from a higher reflectivity state to a lower reflectivity state, increases display luminance of video images displayed at the video display device for viewing by the driver of the equipped vehicle.

13. The vehicular video camera display system of claim 1, wherein the control circuitry comprises a decoder that decodes the digital signal communicated from the rearward-viewing video camera via the cable.

26

14. The vehicular video camera display system of claim 13, wherein the decoder interfaces with the vehicular bus network system of the equipped vehicle.

15. The vehicular video camera display system of claim 1, wherein the video display screen comprises a liquid crystal video display screen, and wherein the control circuitry controls at least one light emitting diode to provide back-lighting of the liquid crystal video display screen.

16. The vehicular video camera display system of claim 15, wherein the rearward-viewing video camera comprises a rear backup camera of the equipped vehicle.

17. The vehicular video camera display system of claim 1, wherein the control circuitry is operable to generate information that is superimposed on the video images displayed at the video display device that are derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

18. The vehicular video camera display system of claim 17, wherein the control circuitry is operable to generate textual information that is superimposed on the video images displayed at the video display device that are derived, at least in part, from the communication via the cable of captured image data from the rearward-viewing video camera to the control circuitry.

19. The vehicular video camera display system of claim 1, wherein the video display screen comprises an organic light emitting diode (OLED) video display screen.

20. The vehicular video camera display system of claim 1, wherein the control circuitry is operable to control display at the video display device of video images that have a display luminance greater than 700 cd/m².

21. The vehicular video camera display system of claim 1, wherein communication via the cable of captured image data from the rearward-viewing video camera to the control circuitry uses low-voltage differential signaling (LVDS).

22. The vehicular video camera display system of claim 1, wherein the video device, when operated, detects driver drowsiness.

23. The vehicular video camera display system of claim 1, wherein the coaxial cable comprises a CAT-5 coaxial cable.

24. A vehicular video camera display system, the vehicular video camera display system comprising:

an interior rearview mirror assembly disposed at an in-cabin side of a windshield of a vehicle equipped with the vehicular video camera display system;

wherein the interior rearview mirror assembly comprises a mirror head accommodating an electrochromic reflective element;

wherein the electrochromic reflective element comprises a front glass substrate and a rear glass substrate with an electrochromic medium sandwiched therebetween;

wherein the front glass substrate comprises a planar first side and a planar second side separated by a thickness of the front glass substrate, and wherein a transparent electrically conductive coating is disposed at the planar second side of the front glass substrate;

wherein the rear glass substrate comprises a planar third side and a planar fourth side separated by a thickness of the rear glass substrate, and wherein a mirror reflector is disposed at the planar third side of the rear glass substrate;

wherein no part of the rear glass substrate extends beyond any part of the front glass substrate;

wherein the electrochromic medium is disposed in a cavity between the planar second side of the front glass substrate and the planar third side of the rear glass substrate;

27

wherein the cavity is established by a seal that spaces the planar second side of the front glass substrate from the planar third side of the rear glass substrate;

wherein the electrochromic medium contacts the transparent electrically conductive coating disposed at the planar second side of the front glass substrate and contacts the mirror reflector disposed at the planar third side of the rear glass substrate;

wherein the mirror reflector disposed at the planar third side of the electrochromic reflective element comprises a transmissive mirror reflector that at least partially reflects light incident thereon and that at least partially transmits incident light therethrough;

wherein a video display device is disposed in the mirror head behind the electrochromic reflective element;

wherein, with the interior rearview mirror assembly disposed at the in-cabin side of the windshield of the equipped vehicle, a video display screen of the video display device is operable to display video images that are viewable through the electrochromic reflective element by a driver of the equipped vehicle who is viewing the interior rearview mirror assembly disposed at the in-cabin side of the windshield of the equipped vehicle;

a rearward-viewing video camera disposed at the equipped vehicle;

the rearward-viewing video camera viewing at least rearward of the equipped vehicle;

the rearward-viewing video camera comprising a CMOS imaging array sensor operable to capture image data;

wherein image data captured by the rearward-viewing video camera is provided to and processed at control circuitry;

wherein the control circuitry links to a vehicular bus network system of the equipped vehicle;

wherein the control circuitry comprises circuitry operable to control dimming of the electrochromic reflective element;

wherein image data captured by the rearward-viewing video camera is communicated as a digital signal from the rearward-viewing video camera via a cable to the control circuitry;

wherein the cable comprises a coaxial cable;

wherein the interior rearview mirror assembly comprises a video device operable for surveillance of an internal cabin of the equipped vehicle;

wherein the video display device displays video images that are derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry; and

wherein the control circuitry controls display at the video display device of the video images derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

25. The vehicular video camera display system of claim 24, wherein the vehicular bus network system of the equipped vehicle comprises a Controller Area Network (CAN).

26. The vehicular video camera display system of claim 24, wherein the control circuitry is operable to generate at least one graphic overlay that is electronically generated and is superimposed on video images displayed at the video display device that are derived, at least in part, from the image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

28

27. The vehicular video camera display system of claim 24, wherein the control circuitry is disposed at the interior rearview mirror assembly.

28. The vehicular video camera display system of claim 24, wherein the interior rearview mirror assembly includes (i) a glare light sensor for sensing glare light at the electrochromic reflective element and (ii) an ambient light sensor for sensing ambient light at the interior rearview mirror assembly, and wherein the control circuitry controls dimming of the electrochromic reflective element responsive to sensing of glare light by the glare light sensor and to sensing of ambient light by the ambient light sensor.

29. The vehicular video camera display system of claim 24, wherein the control circuitry, when the electrochromic reflective element is dimmed from a higher reflectivity state to a lower reflectivity state, increases display luminance of video images displayed at the video display device for viewing by the driver of the equipped vehicle.

30. The vehicular video camera display system of claim 24, wherein the control circuitry comprises a decoder that decodes the digital signal communicated from the rearward-viewing video camera via the cable, and wherein the decoder interfaces with the vehicular bus network system of the equipped vehicle.

31. The vehicular video camera display system of claim 24, wherein the video display screen comprises a liquid crystal video display screen, and wherein the control circuitry controls at least one light emitting diode to provide backlighting of the liquid crystal video display screen.

32. The vehicular video camera display system of claim 31, wherein the rearward-viewing video camera comprises a rear backup camera of the equipped vehicle.

33. The vehicular video camera display system of claim 24, wherein the control circuitry is operable to generate information that is superimposed on the video images displayed at the video display device that are derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

34. The vehicular video camera display system of claim 24, wherein communication via the cable of captured image data from the rearward-viewing video camera to the control circuitry uses low-voltage differential signaling (LVDS).

35. The vehicular video camera display system of claim 24, wherein the video device, when operated, detects driver drowsiness.

36. The vehicular video camera display system of claim 24, wherein the coaxial cable comprises a CAT-5 coaxial cable.

37. A vehicular video camera display system, the vehicular video camera display system comprising:

an interior rearview mirror assembly disposed at an in-cabin side of a windshield of a vehicle equipped with the vehicular video camera display system;

wherein the interior rearview mirror assembly comprises a mirror head accommodating an electrochromic reflective element;

wherein the electrochromic reflective element comprises a front glass substrate and a rear glass substrate with an electrochromic medium sandwiched therebetween;

wherein the front glass substrate comprises a planar first side and a planar second side separated by a thickness of the front glass substrate, and wherein a transparent electrically conductive coating is disposed at the planar second side of the front glass substrate;

wherein the rear glass substrate comprises a planar third side and a planar fourth side separated by a thickness of

29

the rear glass substrate, and wherein a mirror reflector is disposed at the planar third side of the rear glass substrate;

wherein the electrochromic medium is disposed in a cavity between the planar second side of the front glass substrate and the planar third side of the rear glass substrate;

wherein the cavity is established by a seal that spaces the planar second side of the front glass substrate from the planar third side of the rear glass substrate;

wherein the electrochromic medium contacts the transparent electrically conductive coating disposed at the planar second side of the front glass substrate and contacts the mirror reflector disposed at the planar third side of the rear glass substrate;

wherein the mirror reflector disposed at the planar third side of the electrochromic reflective element comprises a transmissive mirror reflector that at least partially reflects light incident thereon and that at least partially transmits incident light therethrough;

wherein a video display device is disposed in the mirror head behind the electrochromic reflective element;

wherein, with the interior rearview mirror assembly disposed at the in-cabin side of the windshield of the equipped vehicle, a video display screen of the video display device is operable to display video images that are viewable through the electrochromic reflective element by a driver of the equipped vehicle who is viewing the interior rearview mirror assembly disposed at the in-cabin side of the windshield of the equipped vehicle;

a rearward-viewing video camera disposed at the equipped vehicle;

the rearward-viewing video camera viewing at least rearward of the equipped vehicle;

the rearward-viewing video camera comprising a CMOS imaging array sensor operable to capture image data;

wherein image data captured by the rearward-viewing video camera is provided to and processed at control circuitry;

wherein the control circuitry links to a vehicular bus network system of the equipped vehicle;

wherein image data captured by the rearward-viewing video camera is communicated as a digital signal from the rearward-viewing video camera via a cable to the control circuitry;

wherein the cable comprises a coaxial cable;

wherein the control circuitry comprises a decoder that decodes the digital signal communicated from the rearward-viewing video camera via the cable;

wherein the video display screen comprises a liquid crystal video display screen, and wherein the control circuitry controls at least one light emitting diode to provide backlighting of the liquid crystal video display screen;

wherein the interior rearview mirror assembly comprises a video device operable for surveillance of an internal cabin of the equipped vehicle;

wherein the video display device displays video images that are derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry; and

30

wherein the control circuitry controls display at the video display device of the video images derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

38. The vehicular video camera display system of claim 37, wherein the vehicular bus network system of the equipped vehicle comprises a Controller Area Network (CAN).

39. The vehicular video camera display system of claim 37, wherein the control circuitry is operable to generate at least one graphic overlay that is electronically generated and is superimposed on video images displayed at the video display device that are derived, at least in part, from the image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

40. The vehicular video camera display system of claim 37, wherein the control circuitry is disposed at the interior rearview mirror assembly.

41. The vehicular video camera display system of claim 40, wherein the control circuitry comprises circuitry operable to control dimming of the electrochromic reflective element.

42. The vehicular video camera display system of claim 41, wherein the interior rearview mirror assembly includes (i) a glare light sensor for sensing glare light at the electrochromic reflective element and (ii) an ambient light sensor for sensing ambient light at the interior rearview mirror assembly, and wherein the control circuitry controls dimming of the electrochromic reflective element responsive to sensing of glare light by the glare light sensor and to sensing of ambient light by the ambient light sensor.

43. The vehicular video camera display system of claim 41, wherein the control circuitry, when the electrochromic reflective element is dimmed from a higher reflectivity state to a lower reflectivity state, increases display luminance of video images displayed at the video display device for viewing by the driver of the equipped vehicle.

44. The vehicular video camera display system of claim 37, wherein the decoder interfaces with the vehicular bus network system of the equipped vehicle.

45. The vehicular video camera display system of claim 37, wherein the rearward-viewing video camera comprises a rear backup camera of the equipped vehicle.

46. The vehicular video camera display system of claim 37, wherein the control circuitry is operable to generate information that is superimposed on the video images displayed at the video display device that are derived, at least in part, from image data communicated via the cable from the rearward-viewing video camera to the control circuitry.

47. The vehicular video camera display system of claim 37, wherein communication via the cable of captured image data from the rearward-viewing video camera to the control circuitry uses low-voltage differential signaling (LVDS).

48. The vehicular video camera display system of claim 37, wherein the video device, when operated, detects driver drowsiness.

49. The vehicular video camera display system of claim 37, wherein the coaxial cable comprises a CAT-5 coaxial cable.

* * * * *