

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250263987

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Juarez; Alejandro et al.

CURVILINEAR SEALING SYSTEM

Abstract

A sealing system connecting first and second tubular members includes a first curvilinear sealing surface on the first tubular member and a second curvilinear sealing surface on the second tubular member. Both the first and second curvilinear sealing surfaces are disposed between two sets of threading on the respective first and second tubular members. When the first and second tubular members are in a connected configuration, the first and second curvilinear sealing surfaces contact and interfere to form an annular curvilinear center seal. A relief pocket may be disposed adjacent to the first and/or second curvilinear sealing surfaces to contain excess lubricant between the first and second tubular members.

Inventors: Juarez; Alejandro (Cypress, TX), Raje; Nishikant V. (Houston, TX)

Applicant: HYDRIL COMPANY (Houston, TX)

Family ID: 1000008589736

Assignee: HYDRIL COMPANY (Houston, TX)

Appl. No.: 19/203580

Filed: May 09, 2025

Related U.S. Application Data

parent US continuation 18446934 20230809 parent-grant-document US 12297700 child US 19203580

parent US continuation 16883134 20200526 parent-grant-document US 11753876 child US 18446934

parent US continuation 15962043 20180425 parent-grant-document US 10697251 child US 16883134

us-provisional-application US 62505262 20170512

Publication Classification

Int. Cl.: E21B17/042 (20060101); E21B17/08 (20060101); F16L15/00 (20060101); F16L15/06 (20060101)

U.S. Cl.:

CPC E21B17/0423 (20130101); E21B17/08 (20130101); F16L15/002 (20130101); F16L15/06 (20130101); Y10T29/49881 (20150115)

Background/Summary

TECHNICAL FIELD

[0001] The present application relates to tubular connections, and more particularly, to a tubular connection seal configuration having contacting curvilinear surfaces.

BACKGROUND

[0002] This section is intended to introduce various aspects of art that may be related to various aspects of the present techniques, which are described and/or claimed below. This discussion is believed to be helpful in providing background information to facilitate a better understanding of the various aspects of the present disclosure. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art. The following descriptions and examples are not admitted to be prior art by virtue of their inclusion in this section.

[0003] The oil and gas industry is drilling upstream production wells of increasing depth and complexity to find and produce raw hydrocarbons. The industry routinely uses steel pipe, considered an Oil Country Tubular Good (OCTG) to protect the borehole (i.e., casing) and to control the fluids produced within the pipe (i.e., tubing). Such pipe, including casing and tubing, are made and transported in relatively short segments and installed in the borehole one segment at a time, with each segment being connected to the next. As the search for oil and gas has driven companies to drill deeper wells, pipes may be subject to increased complexity and magnitude of forces throughout their lifespans downhole. Industry demands have grown for casing, tubing, and connectors having increased tensile and pressure strengths. Furthermore, the developing area of deviated and horizontal wells have exacerbated this trend, further adding increased torsional loads as another requirement for casing and tubing connectors.

[0004] Connectors have been designed with varying thread, shoulder, and seal configurations. For example, two general connector thread configurations include a threaded and coupled connector and an integral connector. A thread and coupled connector includes a pin (i.e., a male threaded end) machined on relatively long joints of pipe and joined by the box (i.e., a female threaded end) machined on a relatively short coupling. An integral connector includes a pin threaded on a full-length pipe connected to a box threaded to another full-length pipe, and pin and box ends may be threaded onto opposite sides of each full-length pipe segment so that each segment may be connected for a length of a borehole. One type of shoulder and seal combination includes a center shoulder seal, which includes a sealing section in a connection disposed between at least two threaded portions. The sealing section of a pin or box may have direct contact with the sealing section of another pin or box and may function to prevent the passage of liquid or gas across the threads of the assembled connection. As industry demands connectors with increasingly high tensile strength, pressure strength, and torque, etc., the general features of connectors may be further designed and engineered to meet downhole performance criteria.

SUMMARY

[0005] This summary is provided to introduce a selection of concepts that are further described below in the detailed description. This summary is not intended to identify key or essential features of the claimed subject matter, nor is it intended to be used as an aid in limiting the scope of the claimed subject matter.

[0006] In one embodiment, a sealing system includes a first tubular member and a second tubular member. The first tubular member includes a first thread set and a second thread set and a first curvilinear sealing surface disposed axially between the first and second thread sets. The second tubular member includes a third thread set and a fourth thread set and a second curvilinear sealing surface disposed axially between the third and fourth thread sets. The first tubular member and the second tubular member are configured to connect when the first thread set engages with the third thread set and the second thread set engages with the fourth thread set. The first and second curvilinear sealing surfaces are configured to interfere at an interference region when the first and second tubular members connect.

[0007] Some embodiments include one or both of a first relief recess disposed on the first tubular member, between the first thread set and the first curvilinear sealing surface and a second relief recess disposed on the second tubular member, between the fourth thread set and the second curvilinear sealing surface. In some embodiments, the first, second, third, and fourth thread sets comprise square threads, wedge threads, variable pitch threads, or combinations of different thread geometries. In different embodiments, the first and second curvilinear sealing surfaces may have an elliptical curve, a circular curve, a toroidal curve, a varying-radius curve, or curve combinations of these curves. The first and second curvilinear surfaces may have identical curves or different curve geometries. Moreover, in different embodiments, the first and second curvilinear surfaces may be symmetrical or asymmetrical when the first and second tubular members connect. The interference region may be approximately centered between the first and second thread sets, or may be at any axial point between the first and second thread sets. In some embodiments, the sealing system is configured such that an axis of the annular seal may change without forming discontinuities in the annular seal.

[0008] In another embodiment, a method includes moving a first tubular member relative to a second tubular member, such that a pin end of the first tubular member enters and axially overlaps with a box end of the second tubular member. The method further includes rotating the first tubular member relative to the second tubular member, such that a first threading and a second threading on the first tubular member engages with a third threading and a fourth threading on the second tubular member, respectively. The method then involves connecting the first tubular member to the second tubular member, such that a first curvilinear surface on the first tubular member between the first and second threading contacts a second curvilinear surface on the second tubular member between the third and fourth threading. A contact force between the first and second curvilinear surfaces form an annular seal between the first and second tubular members.

[0009] In some embodiments, the contact force comprises a compressional force between the first and second curvilinear surfaces. Furthermore, in some embodiments, the contact force comprises a radial force extending along an annular dimension between the first and second tubular members to form the annular seal.

[0010] In some embodiments, rotating the first tubular member relative to the second tubular member comprises displacing lubricant between the pin end and the box end into at least one of a first recess on the first tubular member between the first thread and the first curvilinear surface and a second recess on the second tubular member between the fourth thread and the second curvilinear surface.

[0011] One or more embodiments include a connection having a curvilinear center seal. The connection includes a first tubular member having a first thread set and a second thread set and a first curvilinear surface disposed axially between the first and second thread sets and a second tubular member having a third thread set and a fourth thread set and a second curvilinear surface

disposed axially between the third and fourth thread sets. The first tubular member and the second tubular member connect when the first thread set engages with the third thread set and the second thread set engages with the fourth thread set to result in radial force between the first curvilinear surface and the second curvilinear surface.

[0012] In some embodiments, the first and third thread sets have wedge thread geometries, the second and fourth thread sets have wedge thread geometries, or the first, second, third, and fourth thread sets have wedge thread geometries.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] Embodiments of the present techniques are described with reference to the following figures. The same numbers are used throughout the figures to reference like features and components. Various embodiments may utilize elements and/or components other than those illustrated in the drawings, and some elements and/or components may not be present in various embodiments. Elements and/or components in the figures are not necessarily drawn to scale.

[0014] FIG. 1 is a partial cross-section of a center shoulder seal arrangement;

[0015] FIG. 2 is a partial cross-section of another center shoulder seal arrangement;

[0016] FIG. 3 is a partial cross-section of one embodiment of a center shoulder seal;

[0017] FIG. 4 is a partial cross-section of another embodiment of a center shoulder seal;

[0018] FIG. 5 is a partial cross-section of another embodiment of a center shoulder seal in which the location of primary sealing contact to opposite sides of the connection includes engaged threads to one side of the center-shoulder, but lacks any engaged threads to the other side of the center-shoulder;

[0019] FIG. 6 is a partial cross section of an embodiment of a center seal having contacting curvilinear surfaces;

[0020] FIG. 7A is a partial cross sectional diagram of an embodiment of a curvilinear surface on a center sealing surface of one tubular member;

[0021] FIG. 7B is an expanded view of the curvilinear portion of the center sealing surface depicted in FIG. 7B.;

[0022] FIG. 7C is a partial cross sectional diagram of an embodiment of a center sealing surface where opposite tubular members have contacting curvilinear surfaces; and

[0023] FIG. 8 is a partial cross sectional and three-quarter rendering of connected tubular members having contacting curvilinear surfaces at a center seal.

DETAILED DESCRIPTION

[0024] FIG. 1 is a center shoulder seal connection having five metal-to-metal seals: two metal-to-metal seals at the exterior beveled edges of the locked double shoulder seal **400** where sealing surfaces **418** and **438** are in contact and where sealing surfaces **422** and **442** are in contact; and, three zero clearance surfaces at the interior of the locked double shoulder seal **400**, one **410** at the wall surface where sealing cylindrical surfaces contact, another zero clearance surface where the annular face surface of the pin shoulder **420** contacts the box undercut surface **448**, and another zero clearance surface where the face surface of box shoulder **440** contacts pin undercut surface **428**. Thus, center-shoulder seal **400** forms a very close fitting metal-to-metal seal having mating metal-to-metal sealing surfaces which allow a build-up of stored energy within the seal upon power tightening of the assembled connection, such that upon the application of various loads on the pipe and also the connection, the seal will continue to perform and maintain sealing engagement. Notably, all of the metal-to-metal seals are formed within the axial space **450** between the sets of contacting annular faces of the center shoulder, and the metal-to-metal seals at the exterior beveled edges of shoulder seal **400**, each of which exhibits radial forces, are each located immediately

adjacent a respective one of the sets of contacting annular faces.

[0025] FIG. 2 is a center shoulder seal connection having at least two and up to seven metal-to-metal seals are established between the pin and box members. Three of the seven seals are frustum seals. A first outer frustum seal **120** is formed by the engagement of pin and box frustoconical surfaces at the radially outer side of the center shoulder and a second inner frustum seal **122** is formed between pin and box frustoconical surfaces at the radially inner side of the center shoulder. The third frustum seal is a center frustum seal **124** formed between intermediated pin and box center frustoconical surfaces. Two annular shoulder seals are formed. A first inner annular shoulder seal **126** a second outer annular shoulder seal **128**, each by engaged annular surfaces of the pin and box members. Two cylindrical seals are also formed. A first outer cylindrical seal **130** is formed by the engagement of pin and box outer seal cylindrical surfaces at the radially outer side and a second inner cylindrical seal **132** is formed by the engagement of pin and box seal cylindrical surfaces at the radially inner side. Notably, this arrangement also places each of the metal-to-metal seals that are exposed to significant radial and hoop forces (i.e., contacting seals **122** and **120**) immediately adjacent a respective one of the sets of contacting annular faces (i.e., at annular contacting seals **126** and **128**) and likewise within the axial space **150** between the two annular shoulder seals.

[0026] Referring to FIG. 3, a partial cross-section of a center shoulder connection **200** between two tubular members **202** and **204** is shown. Tubular member **202** forms the pin portion of the connection and tubular member **204** forms the box end of the connection. An axial centerline of the connection is shown at **206**, and it is recognized that a full cross-section of the center shoulder connection would include a mirror image of the components on the opposite side of the axial centerline (i.e., below the centerline **206** in FIG. 3).

[0027] A seal configuration on tubular member **202** includes an annular groove **208** and an annular tooth **210**. The annular groove **208** is defined by a radially inward facing (i.e., facing toward the centerline **206**) undercut surface **212**, an adjacent annular shoulder face **214** and an adjacent radially outward facing surface **216**. The annular tooth is defined by the radially inward facing undercut surface **212**, an annular tooth face **218** and a radially outward facing surface **220**. In the illustrated embodiment, the surface **216** includes a corner radius that transitions to the shoulder face **214**, and the surface **220** includes a corner radius that transitions to the tooth face **218**.

[0028] A seal configuration on the tubular member **204** includes an annular groove **222** and an annular tooth **224**. The annular groove **222** is defined by a radially outward facing undercut surface **226**, an adjacent annular shoulder face **228** and an adjacent radially inward facing surface **230**. The annular tooth **224** is defined by the radially outward facing undercut surface **226**, an annular tooth face **232** and a radially inward facing surface **234**. In the illustrated embodiment, the surface **230** includes a corner radius that transitions to the shoulder face **228**, and the surface **234** includes a corner radius that transitions to the tooth face **232**.

[0029] FIG. 3 shows the connection in made up condition, in which the annular tooth **224** is positioned within the annular groove **208** with the annular tooth face **232** engaging the annular shoulder face **214** to define one shoulder, which is represented by shoulder plane **236**. Likewise, the annular tooth **210** is positioned within the annular groove **222** with the annular tooth face **218** engaging the annular shoulder face **228** to define another shoulder, which is represented by shoulder plane **238**. In the illustrated embodiment the undercut surfaces **212** and **226** also engage each other, which can act as a further sealing location, as can the engaged shoulders. At opposite axial sides of the connection, engaged threaded sections or the tubular members are also shown schematically at **260** and **262**.

[0030] As illustrated, clearance may be provided between the radially outward facing surface **216** and the radially inward facing surface **234** in vicinity of the shoulder plane **236**. The location of primary sealing contact between the radially outward facing surface **216** and the radially inward facing surface **234**, which location is shown in FIG. 3 at **240**, is spaced axially away from the shoulder plane **236** to define a metal-to-metal seal contact area **242** (represented by interference of

the surfaces shown in cross-hatch) that is axially spaced from the shoulder plane **236**. As used herein the terminology “location of primary sealing contact” between two specified surfaces means the location of maximum contact pressure between the two surfaces. Thus, by way of example, in some embodiments surfaces **216** and **234** may make slight contact with each other in the vicinity of the shoulder plane **236** (e.g., within an axial region **246** between the shoulder planes **236** and **238**) while, at the same time, the location of primary sealing contact between the surfaces **216** and **234** is spaced further away from the shoulder plane **236**. Generally, the location of maximum contact pressure, and thus the location of primary sealing contact, will occur proximate the location of maximum interference between the surfaces.

[0031] Clearance may also be provided between the radially inward facing surface **230** and the radially outward facing surface **220** in vicinity of the shoulder plane **238** or, as noted above, only slight contact between the surfaces may occur in the vicinity of the shoulder plane **238**. Regardless, the location of primary sealing contact between the radially inward facing surface **230** and the radially outward facing surface **220**, which location is shown in FIG. 3 at **243**, is spaced axially away from the shoulder plane **238** to define a metal-to-metal seal contact area **244** (represented by interference of the surfaces shown in cross-hatch) that is axially spaced from the shoulder plane **238**. Notably, in the case of both primary seal contact areas **242** and **244** of the illustrated embodiment, the location of primary sealing contact is located outside of the axial region **246** of the connection defined between the two shoulders planes **236** and **238**.

[0032] The exact location of primary sealing contact between the surfaces (e.g., **216** and **234** or **220** and **230**) can vary based upon various factors, including the necessary torque limit required in the connection, as well as thickness and diameter of the tubular connection.

[0033] By way of example: the location of primary sealing contact **240** may be axially spaced from the shoulder plane **236** by between about 25 thousandths of an inch and about one inch; the location of primary sealing contact **243** may be axially spaced from the shoulder plane **238** by between about 25 thousandths of an inch and about one inch; the axial region **246** may extend from between about 20 thousandths of an inch and about 250 thousandths of an inch; a radial spacing between the radially outward facing surface **216** and the radially outward facing surface **220** in the shoulder plane **236** may be between about 40 thousandths of an inch and about 500 thousandths of an inch; and a radial spacing between the radially inward facing surface **230** and the radially inward facing surface **234** in the shoulder plane **238** may be between about 40 thousandths of an inch and about 500 thousandths of an inch.

[0034] In the illustrated embodiment, each of the surfaces **216**, **220**, **230** and **234** are shown as curvilinear surfaces. Such curvilinear surfaces may, by way of example, when considered in two dimensions along a plane that extends through and runs parallel to the central axis **206** of the connection, include elliptical curves, circular curves, varying radius curves of any suitable type (e.g., curve radius generally between about 0.5 inches and about 15 inches for most effective sealing), or combinations thereof, and the corresponding 3-D surface shapes produced upon rotation of any such curve about the central axis **206** of the connection. However, it is recognized that the surfaces need not be entirely curvilinear or, for that matter, curvilinear at all. For example, in one possible modified version of the embodiment of FIG. 3, surfaces **220** and **234** remain curvilinear, but surfaces **216** and **230** are made frustoconical, such that each location of primary sealing contact **240** and **243** is made with respect to an interference between a curvilinear surface and a frustoconical surface.

[0035] Referring to the alternative embodiment shown in FIG. 4, an embodiment of a center shoulder seal configuration **300** with axial centerline **306** in which the primary metal-to-metal contact seals are not formed by curvilinear surface portions is shown. In this arrangement, the pin end on tubular member **302** includes an annular groove **308** and an annular tooth **310**. The annular groove **308** is defined by a radially inward facing (i.e., facing toward the centerline **306**) undercut surface **312**, an adjacent annular shoulder face **314** and an adjacent radially outward facing surface

316. The annular tooth is defined by the radially inward facing undercut surface **312**, an annular tooth face **318** and a radially outward facing surface **320**. The box end on tubular member **304** includes an annular groove **322** and an annular tooth **324**. The annular groove **322** is defined by a radially outward facing undercut surface **326**, an adjacent annular shoulder face **328** and an adjacent radially inward facing surface **330**. The annular tooth **324** is defined by the radially outward facing undercut surface **326**, an annular tooth face **332** and a radially inward facing surface **334**.

[0036] Surface **316** includes cylindrical portion **316a** and frustoconical portion **316b**, while surface **334** includes cylindrical portion **334a** and frustoconical portion **334b**. Clearance may be provided between surface portions **316a** and **334a**, but the frustoconical portions **316b** and **334b** interfere in a manner to produce a location of primary sealing contact **340** that is axially spaced from shoulder plane **336**, represented by interference contact area **342**. Surface **320** includes cylindrical portion **320a** and frustoconical portion **320b**, while surface **330** includes cylindrical portion **330a** and frustoconical portion **330b**. Clearance may be provided between surface portions **320a** and **330a**, but the frustoconical portions **320b** and **330b** interfere in a manner to produce a location of primary sealing contact **343** that is axially spaced from shoulder plane **338**, represented by interference contact area **344**. To be most effective, the conical angle of each frustoconical portion **316b**, **334b**, **320b**, **330b** relative to the central axis **306** of the connection (e.g., represented in one instance in FIG. **4** by angle Θ relative to line **321** that runs parallel to the central axis **306**), as well as the conical angle of other embodiments incorporating frustoconical surface portions, may be between about 1° and about 7° . Engaged threaded sections **360** and **362** on opposite axial sides of the center shoulder are also shown. The axial locations of the seals and the radial thickness of the tubular members may be similar to that mentioned above with respect to the embodiment of FIG. **3**.

[0037] Referring now to FIG. **5**, an embodiment of a center shoulder seal configuration **500** with axial centerline **506** in which one side of the connection lacks engaged threads is shown. In this arrangement, the pin end on tubular member **502** includes an annular groove **508** and an annular tooth **510**. As in the previous embodiments, the annular groove **508** is defined by a radially inward facing (i.e., facing toward the centerline **506**) undercut surface, an adjacent annular shoulder face **514** and an adjacent radially outward facing surface **516**. The annular tooth **510** is defined by the radially inward facing undercut surface, an annular tooth face **518** and a radially outward facing surface **520**. The box end on tubular member **504** includes an annular groove **522** and an annular tooth **524**. The annular groove **522** is defined by a radially outward facing undercut surface, an adjacent annular shoulder face **528** and an adjacent radially inward facing surface **530**. The annular tooth **524** is defined by the radially outward facing undercut surface, an annular tooth face **532** and a radially inward facing surface **534**.

[0038] In the illustrated embodiment, surface **516** and surface **534** are configured such that the location of primary sealing contact **540** is spaced further from the axial region **546** between the shoulder planes **536** and **538** than the location of primary sealing contact **543** between surfaces **520** and **530**. In this arrangement, the location of primary sealing contact **540** may be axially spaced from the shoulder plane **536** by between about 25 thousandths of an inch and about two inches; the location of primary sealing contact **543** may be axially spaced from the shoulder plane **538** by between about 25 thousandths of an inch and about one inch; the axial region **546** may extend from between about 20 thousandths of an inch and about 250 thousandths of an inch; a radial spacing between the radially outward facing surface **516** and the radially outward facing surface **520** in the shoulder plane **536** may be between about 40 thousandths of an inch and about 500 thousandths of an inch; and a radial spacing between the radially inward facing surface **530** and the radially inward facing surface **534** in the shoulder plane **538** may be between about 40 thousandths of an inch and about 500 thousandths of an inch. In this case the location of primary sealing contact **540** will generally be within 1.75 inches of the axial region **546**.

[0039] Surfaces **516** and **534** include respective cylindrical surface portions **516A** and **534A** with

clearance provided. Surface portion **516A** is followed by a curvilinear surface portion **516B**, and surface portion **534A** is followed by a frustoconical surface portion **534B**, with location of primary sealing contact **540** occurring between portions **516B** and **534B**. Surface **530** includes a frustoconical portion **530A**, followed by another, steeper frustoconical portion **530B**, and surface **520** includes a curvilinear portion **520A** that transitions to a cylindrical portion **520B**. The location of primary sealing contact is between surface portion **530A** and surface portion **520A**. It is noted that other surface variations are possible as previously discussed. Engaged threaded sections **562** are located to one side of the center-shoulder, specifically the side that is closer to the outer diameter of the connection, while the opposite side of the connection lacks any engaged threads. Notably, on this opposite side of connection a gap **550** may be provided between the pin nose shoulder face and the box shoulder face as shown to prevent the pin nose section from yielding due to torque, compression and expansion of the material at high temperatures. The faces may, however, come into contact, such as at make-up, during compression or during material expansion. Also shown is a dope relief recess **560** in the surface **530** of box member **504** that will take-up excess thread dope as the connection makes up.

[0040] The configuration of FIG. 5 may be useful in connection with tubulars used in the geothermal markets, such as the steam assisted gravity drainage market. Although the FIG. 5 embodiment lacks any engaged threaded section at one side of the connection, it is recognized that variations are possible, including implementations in which an engaged threaded section is also provided on the side of the connection that includes the location of primary sealing contact **540** that is spaced further from the axial shoulder region **546**.

[0041] Embodiments of the present techniques include a center seal of a tubular connection having contacting curvilinear surfaces. While previous techniques have involved a tooth and groove configuration to produce the center shoulder seal, the present techniques do not necessarily involve a center tooth and groove seal. A center curvilinear sealing system produces an annular seal in a tubular connection between two curvilinear surfaces approximately centered between two thread sets. Such a system may result in a more robust sealing connection compared to previous techniques. For instance, it may be more difficult to produce a seal between the tooth and groove of a tubular connection due to the precise shapes of the tooth and groove. Additionally, previous sealing techniques may be susceptible to downhole or operational forces and torque which may damage a tooth and groove connection.

[0042] The annular seal formed in the center curvilinear sealing system may be relatively more flexible. For example, unexpected forces may cause an annular seal of a center curvilinear seal to shift or adjust, rather than buckle or break. As both contacting sealing surfaces have curved geometries, bends or twists may result in shifts in the region of interference between the contacting curvilinear surfaces of two connected tubular members. Due to the geometries of two curvilinear surfaces forming a curvilinear sealing system, the curvilinear sealing system may maintain an annular seal between two connected tubular members even if a length of multiple connections are subjected to bends, twists, torque, and/or torsion, in that an axis of the annular seal may change without forming discontinuities in the annular curvilinear seal.

[0043] FIG. 6 is a schematic illustration of a curvilinear sealing system **600** having a curvilinear surface geometry, where a pin **602** of a tubular component and a box **612** of another tubular component each have a curvilinear surface geometry configured to form a curvilinear seal. The pin **602** has a first set of threading **606**, a second set of threading **608**, and a center sealing surface **604** axially disposed between the first **606** and second **608** sets of threading. Similarly, the box **612** has a first set of threading **616**, a second set of threading **618**, and a center sealing surface **614** axially disposed between the first **616** and second **618** sets of threading. The first and second sets of threading of the curvilinear sealing system **600** may include wedge threads, square threads, variable pitch threads, a combination of threads, or any other thread geometry or combination of thread geometries suitable for use with the curvilinear center seal of the present techniques. For example,

a square thread may include threads having a square or near-square thread geometry with tapering and substantially no flank angle. A wedge thread may include threads having a “dovetail” shape where the thread geometry increases in thread width in the radial dimension between a pin member and box member. In some embodiments, a relief pocket **610**, **620** is disposed axially adjacent to the center sealing surface in the pin **602** of one tubular component and/or the box **612** of the other tubular component.

[0044] A set of partial cross sectional diagrams of one or more embodiments of a curvilinear sealing system is provided in FIGS. 7A-C, where FIG. 7A is a simplified cross sectional diagram of one tubular component **702** having a curvilinear sealing surface **704** and a relief pocket **710** disposed between two regions of threading **706** and **708**. The threading regions **706** and **708** have been simplified without depicting any thread geometry, as any thread geometry may be compatible with the present techniques. FIG. 7B is an expanded diagram of the curvilinear sealing surface **704** and relief pocket **710** depicted in FIG. 7A. Embodiments of the curvilinear sealing surface **704** include curvilinear surfaces which may be an arc, curve, or portion of an elliptical, circular, spherical, or otherwise curvilinear geometry. The curvilinear sealing surface **704** may have an elliptical curve, a circular or spherical curve, a curve having a varying radius, or a combination of different curves. For example, in one embodiment, a curvilinear surface **704** may have an elliptical curve in combination of a circular curve. The curvilinear sealing surface **704** may be convex with respect to a linear pitch line **712**, depicted as a dotted line in FIG. 7B, of the tubular component **702** between the two regions of threading **706** and **708**. In some embodiments, the effective curve radius for a curvilinear sealing surface is between 0.5 inches and 50 inches.

[0045] FIG. 7C is a simplified cross sectional diagram of an expanded view (as in FIG. 7B) of a connection, where opposing tubular components **702** and **714** each have a curvilinear center sealing surface **704** and **716** interfering with one another, forming a region of interference **720**, and may also be referred to as a curvilinear center seal **720**. In some embodiments, when the two tubular components **702** and **714** are connected, the curvilinear sealing surfaces **704** and **716** engage, and the contact area of the curvilinear sealing surfaces **704** and **716** of the center seal may be referred to as an interference **720** of the two surfaces. Interference may be a region where two surfaces are designed to overlap or intersect, such that when two interfering surfaces are engaged, they form an interfering contact area. When this interfering contact area extends over an annular dimension between two tubular components, the interfering contact area may form a seal between the two tubular components. In some embodiments, the contact force in the region of interference **720** may include a compressional force between the sealing surfaces **704** and **716**. The contact force in the region of interference **720** may also be described as a radial force extending along an annular dimension between the tubular components **702** and **714** to form the annular seal.

[0046] In some embodiments, the first and second curvilinear surfaces may have identical or different curve geometries. In some embodiments, the first and second curvilinear surfaces have approximately symmetrical curve radii when the first and second tubular members are in a connected configuration. However, in some embodiments, the first and second curvilinear surfaces may be offset, or may have different and/or nonsymmetrical curves when the first and second tubular members are connected.

[0047] In one embodiment, the curvilinear sealing surface in the first and second tubular members may be approximately at the center point between the first and second sets of threading. Further, in some embodiments, the interference may be approximately at the center of the first and second curvilinear sealing surfaces. For example, the interference between the two curvilinear sealing surfaces may be within 1 inch on either side from the center point between the two sets of threading. In different embodiments, the curvilinear sealing surface may be located and configured such that the curvilinear sealing surface and/or interference point may be at any point along the length of the connector, between first and second sets of threading. For example, in one embodiment, the interference point may be closer to one set of threading than the other.

Embodiments having different interference locations may be more suitable for different environments having different factors and requirements (e.g., torque requirements).

[0048] As depicted in FIG. 7C, a pin and box member may each have a relief pocket **710**, **718** respectively, axially disposed from the first and second curvilinear sealing surfaces **704**, **716**. The relief pocket **710**, **718** may be sized and located to contain thread lubricant (also referred to as dope) that is displaced as a pin and box member come together into a connected configuration. The containment of the thread lubricant may reduce pressure from lubricant which may otherwise be trapped in other clearances or recesses of the connection. In some embodiments, a relief pocket may be disposed at a distance of approximately 0.025 inches to 0.500 inches away from a curvilinear sealing surface. Furthermore, while two relief pockets are oppositely disposed, axially adjacent to the center seal, embodiments of the present disclosure include different configurations and placements of the relief pockets. For example, in some embodiments, a relief pocket of the pin may be aligned with a relief pocket of the box once the first and second tubular members are connected. In other embodiments, only one relief pocket (e.g., only one on a box member or only one on a pin member) may be used, or no relief pockets may be used.

[0049] FIG. 8 is a partial cross sectional and three-quarter rendering of connected tubular members **802**, **804** having contacting curvilinear surfaces at a center seal **806**. In some embodiments, a curvilinear sealing surface may be approximately centered between the two thread sets **808**, **810** of a pin end **802** and between the two thread sets **812**, **814** of a box end **804**. Moreover, in some embodiments, the interference of the contacting curvilinear sealing surfaces between the pin end and the box end forms an annular seal in the tubular connection which may be approximately centered between the engaged outer threads of the pin and box. In some embodiments, the curvilinear sealing system may be configured such that unexpected forces may cause the annular seal to shift or adjust, such that the axis of the annular seal is not always stationary. A curvilinear sealing system suitable for shifting or adjusting may be easier to operate and more robust than previous techniques, as the center seal may be maintained under various conditions.

[0050] Many modifications and other implementations set forth herein will be apparent having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the systems and methods described herein are not to be limited to the specific implementations disclosed and that modifications and other implementations are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense and not for purposes of limitation.

Claims

1. A sealing system comprising: a first tubular member having a first thread set and a first curvilinear sealing surface; and a second tubular member having a second thread set and a second curvilinear sealing surface; wherein: the first tubular member and the second tubular member are configured to connect when the first thread set engages with the second thread set; the first and second curvilinear sealing surfaces are configured to interfere at an interference region when the first and second tubular members connect; both the first and second curvilinear sealing surfaces are toroidal where such interference occurs.
2. The sealing system of claim 1, further comprising a first relief recess disposed on the first tubular member between the first thread set and the first curvilinear sealing surface.
3. The sealing system of claim 2, further comprising a second relief recess disposed on the second tubular member between the second thread set and the second curvilinear sealing surface.
4. The sealing system of claim 1, wherein the first and second curvilinear sealing surfaces comprise a curve radius between 0.5 inches to 50 inches.
5. The sealing system of claim 1, wherein the first and second curvilinear sealing surfaces are

symmetrical when the first and second tubular members connect.

6. The sealing system of claim 1, wherein the first and second curvilinear sealing surfaces are asymmetrical when the first and second tubular members connect.

7. The sealing system of claim 1, wherein the interference region forms an annular seal between the first and second tubular members, wherein the sealing system is configured such that an axis of the annular seal may change without forming discontinuities in the annular seal.

8. The sealing system of claim 1, wherein: the first tubular member comprises a pin member including a pin nose; and the first curvilinear sealing surface is located between the first thread set and the pin nose.

9. The sealing system of claim 8, wherein the first curvilinear sealing surface is the only curvilinear sealing surface disposed on the first tubular member.

10. The sealing system of claim 1, wherein the first thread set and the second thread set comprise wedge threads.

11. A method comprising: moving a first tubular member relative to a second tubular member, such that a pin end of the first tubular member enters and axially overlaps with a box end of the second tubular member; rotating the first tubular member relative to the second tubular member, such that a first threading on the first tubular member engages with a second threading on the second tubular member and connecting the first tubular member to the second tubular member, such that a first curvilinear sealing surface on the first tubular member contacts a second curvilinear sealing surface on the second tubular member; wherein: the first and second curvilinear sealing surfaces interfere at an interference region when the first and second tubular members connect; and both the first and second curvilinear sealing surfaces are toroidal where such interference occurs.

12. The method of claim 11, wherein rotating the first tubular member relative to the second tubular member comprises displacing lubricant between the pin end and the box end into a first recess on the first tubular member between the first threading and the first curvilinear sealing surface.

13. The method of claim 12, wherein rotating the first tubular member relative to the second tubular member comprises displacing lubricant between the pin end and the box end into a second recess on the second tubular member between the second threading and the second curvilinear sealing surface.

14. The method of claim 11, wherein the contact force comprises a compressional force between the first and second curvilinear sealing surfaces.

15. The method of claim 11, wherein the contact force comprises a radial force extending along an annular dimension between the first and second tubular members to form an annular seal.

16. The method of claim 11, wherein: the first tubular member comprises a pin member including a pin nose; and the first curvilinear sealing surface is located between the first threading and the pin nose.

17. The method of claim 16, wherein the first curvilinear sealing surface is the only curvilinear sealing surface disposed on the first tubular member.

18. The method of claim 11, wherein the first threading and the second threading comprise wedge threads.
