

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392301
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Nagakura; Hiroyuki et al.

Piston unit, top land member, and combination of piston unit parts

Abstract

A piston unit adapted to reciprocate in a cylinder includes a piston and a top land member attached to the piston. The piston includes a first portion including a piston end at one end surface side and fitted with the top land member. The first portion has a smaller outer diameter than a second portion such that there is a step therebetween. The second portion is the other portion of the piston than the first portion. The top land member has a groove wall forming surface opposed to a step surface that connects the outer circumferential surface of the first portion and the outer circumferential surface of the second portion. The first ring groove is defined by the groove wall forming surface, the step surface, and the outer circumferential surface of the first portion.

Inventors:	Nagakura; Hiroyuki (Tokyo, JP), Inamori; Shuichi (Tokyo, JP), Kawai; Kiyoyuki (Tokyo, JP)
Applicant:	TPR Co., Ltd. (Tokyo, JP)
Family ID:	1000008766325
Assignee:	TPR Co., Ltd. (Tokyo, JP)
Appl. No.:	18/851051
Filed (or PCT Filed):	February 07, 2023
PCT No.:	PCT/JP2023/003944
PCT Pub. No.:	WO2023/188834
PCT Pub. Date:	October 05, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250109722 A1	Apr. 03, 2025

Foreign Application Priority Data

JP 2022-052199 Mar. 28, 2022

Publication Classification

Int. Cl.: F02F5/00 (20060101); F02F3/00 (20060101); F16J9/12 (20060101)

U.S. Cl.:

CPC F02F5/00 (20130101); F02F3/00 (20130101); F16J9/12 (20130101);

Field of Classification Search

CPC: F16J (9/12); F16J (9/00); F02F (3/00); F02F (5/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1933943	12/1932	Towell	N/A	N/A
3914574	12/1974	Hill	92/260	F02F 3/003
4751871	12/1987	Burghardt et al.	N/A	N/A
4833977	12/1988	Hahtela et al.	N/A	N/A
2010/0162987	12/2009	Ishida	123/193.6	F16J 9/14
2014/0076265	12/2013	Mittler	123/193.6	F02F 5/00
2021/0164568	12/2020	Nango	N/A	F16J 9/206

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
S60-98748	12/1984	JP	N/A
S61-47456	12/1985	JP	N/A
S61-053543	12/1985	JP	N/A
S61-232366	12/1985	JP	N/A
S63-230947	12/1987	JP	N/A
H02-80750	12/1989	JP	N/A
2020-049536	12/2019	JP	N/A
102153963	12/2019	KR	N/A
WO-2019203358	12/2018	WO	N/A

OTHER PUBLICATIONS

Office Action in JP Application No. 2022-052199 dated Apr. 11, 2023, 8 pages. cited by applicant
Search Report in International Application No. PCT/JP2023/003944 dated Apr. 18, 2023, 2 pages. cited by applicant

Written Opinion in JP Application No. 2022-052199 dated Apr. 11, 2023, 6 pages. cited by applicant

Written Amendment in JP Application No. 2022-052199 dated Jun. 9, 2023, 7 pages. cited by applicant

Decision to Grant a Patent in JP Application No. 2022-052199 dated Jun. 19, 2023, 4 pages. cited

Primary Examiner: Teku; Abiy

Attorney, Agent or Firm: MARSHALL, GERSTEIN & BORUN LLP

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a piston unit, a top land member, and a combination of parts for a piston unit.

BACKGROUND ART

(2) Reciprocating engines and pneumatic equipment are known examples of mechanisms including a cylinder and a piston reciprocating therein. The internal combustion engine is an example of the reciprocating engine. To ensure sealing performance and to reduce friction, the internal combustion engine uses one or more piston rings that are fitted in one or more ring grooves provided on the outer circumferential surface of the piston to slide on the inner surface of the cylinder.

(3) Typical internal combustion engines, such as gasoline engines, use a combination of piston rings including a compression ring and an oil control ring. In their positional relationship along the axial direction of the piston, the compression ring is disposed closer to the combustion chamber, and the oil control ring is disposed closer to the crankcase. These piston rings slide on the inner surface of the cylinder to exercise their functions. The oil control ring, which is farthest from the combustion chamber, has the function of sealing against oil by scraping off excess engine oil (lubrication oil) adhering to the inner surface of the cylinder toward the crank, thereby preventing oil leakage into the combustion chamber (or oil rising), and the function of controlling the quantity of oil so as to adequately maintain a lubrication oil film on the inner wall surface of the cylinder, thereby preventing seizing of the piston during the operation of the internal combustion engine. The compression ring has the function of sealing against gases by maintaining the airtightness, thereby preventing leakage of the burned gas from the combustion chamber to the crankcase (or blow-by), and the function of sealing against oil by scraping off excess oil that has escaped from the scraping by the oil control ring, thereby preventing the oil rising.

CITATION LIST

Patent Literature

(4) [Patent Literature 1] Japanese Patent application Laid-Open No. S61-232366 [Patent Literature 2] Japanese Utility Model Application Laid-Open No. S61-047456 [Patent Literature 3] Japanese Patent application Laid-Open No. 2020-049536 [Patent Literature 4] Japanese Utility Model Application Laid-Open No. S60-098748

SUMMARY OF INVENTION

Technical Problem

(5) Conventional piston has a portion (called “top land”) having an outer diameter larger than the inner diameter of the piston rings between the top surface of the piston and the ring groove closest to the top surface. Therefore, when fitting a piston ring into the ring groove, it is necessary to expand the gap of the piston ring so as to make the inner diameter of the piston ring larger than the outer diameter of the top land. In this process, excessively expanding the gap can result in deformation or breakage of the piston ring due to stress. Moreover, the presence of the top land in conventional piston makes it impossible to attach gapless piston rings to them.

(6) The present invention has been made to address the above problem, and its object is to provide the technology that allows easy assembly of piston rings in a piston unit that is adapted to reciprocate in a cylinder.

Solution to Problem

(7) To solve the above problem, the present invention adopts the following features. According to the present invention, there is provided a piston unit adapted to reciprocate in a cylinder, comprising, a piston, a top land member attached to the piston, one or more ring grooves formed on the outer circumference of the piston, and one or more piston rings fitted in a first ring groove closest to one end surface of the piston among the one or more ring grooves to slide on the inner wall surface of the cylinder. The piston includes a first portion including the piston end at the one end surface side and fitted with the top land member. The first portion has a smaller outer diameter than a second portion such that there is a step therebetween, the second portion being the other portion of the piston than the first portion. The top land member has a groove wall forming surface opposed to a step surface that connects the outer circumferential surface of the first portion and the outer circumferential surface of the second portion, and the first ring groove is defined by the groove wall forming surface, the step surface, and the outer circumferential surface of the first portion.

(8) As above, the top land, which is the portion between one end surface of the piston and the first ring groove, of the piston unit according to the present invention is constituted by the top land member separate from the piston. Therefore, piston rings can be assembled to the piston to which the top land member is not attached. This eliminates the need to expand the piston rings so as to make the inner diameter of the piston rings larger than the outer diameter of the top land when attaching the piston rings to the piston. Therefore, even piston rings without gaps can easily be attached to the piston. In the case of a piston ring having a gap, the piston unit according to the present invention eliminates the need to expand the gap to make the inner diameter of the piston ring larger than the outer diameter of the top land, and therefore deformation or breakage of the ring due to excessive expansion of the gap can be prevented. Therefore, the piston unit according to the present invention allows easy assembly of the piston rings.

(9) The piston unit according to the present invention may further include one or more partition rings fitted in the first ring groove side by side with the one or more piston rings along the axial direction of the piston, and the one or more partition rings may be fitted to the outer circumferential surface of the first portion with a predetermined spacing to the inner wall of the cylinder.

(10) According to the present invention, at least one partition ring among the one or more partition rings may be a partition ring having no gap.

(11) According to the present invention, a plurality of piston rings may be fitted in the first ring groove, and the partition ring may be disposed between the piston ring closest to the one end surface of the piston and the piston ring second closest to the one end surface of the piston among the plurality of piston rings.

(12) According to the present invention, the top land member is formed as a ring that has an annular piston-fit surface fitted to the outer circumferential surface of the first portion as the inner circumferential surface.

(13) According to the present invention, the top land member may have an annular portion that has an annular piston-fit surface fitted to the outer circumferential surface of the first portion as the inner circumferential surface and a lid portion provided inside the annular portion to abut the one end surface of the piston.

(14) The piston unit according to the present invention may be designed to be mounted in a cylinder of an internal combustion engine.

(15) The present invention can be identified as a top land member attached to a piston adapted to reciprocate in a cylinder. According to the present invention, the piston has one or more ring grooves formed on its outer circumference. The piston includes a first portion including the piston

end at one end surface side and fitted with the top land member. The first portion has a smaller outer diameter than a second portion such that there is a step therebetween, the second portion being the other portion of the piston than the first portion. The first ring groove closest to the one end surface among the one or more ring grooves is fitted with one or more piston rings adapted to slide on the inner wall surface of the cylinder arranged side by side along the axial direction of the piston. The top land member according to the present invention has a groove wall forming surface opposed to a step surface that connects the outer circumferential surface of the first portion and the outer circumferential surface of the second portion, and the first ring groove may be defined by the groove wall forming surface, the step surface, and the outer circumferential surface of the first portion.

(16) The present invention can be identified as a combination of parts for the above-described piston unit. In other words, the present invention can be identified as a top land member attached to a piston adapted to reciprocate in a cylinder. The combination of parts for a piston unit may include a top land member fitted to a piston adapted to reciprocate in a cylinder, and one or more piston rings adapted to slide on the inner wall surface of the cylinder. The one or more piston rings are fitted in a first ring groove located closest to one end surface of the piston among one or more ring grooves formed on the outer circumference of the piston. The piston has a first portion including the piston end at the one end surface side and fitted with the top land member. The first portion has a smaller outer diameter than a second portion such that there is a step therebetween, the second portion being the other portion of the piston than the first portion. The top land member has a groove wall forming surface opposed to a step surface that connects the outer circumferential surface of the first portion and the outer circumferential surface of the second portion, and the first ring groove is defined by the groove wall forming surface, the step surface, and the outer circumferential surface of the first portion.

Advantageous Effects of the Invention

(17) According to the present invention, it is possible to easily assemble a piston ring in a piston unit adapted to reciprocate in a cylinder.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a cross sectional view of an internal combustion engine including a piston unit according to an embodiment.
- (2) FIG. 2 is a partial cross sectional view of the internal combustion engine according to the embodiment.
- (3) FIG. 3 is a cross sectional view illustrating a first ring groove according to the embodiment.
- (4) FIGS. 4A-4D are diagrams for illustrating variations of the mode of fitting between a top land member and a piston.
- (5) FIGS. 5A and 5B are diagrams schematically illustrating shapes of partition rings according to the embodiment.
- (6) FIG. 6 is a partial cross sectional view illustrating an internal combustion engine including a piston unit according to a first modification of the embodiment.
- (7) FIG. 7 is a partial cross sectional view illustrating an internal combustion engine including a piston unit according to a second modification of the embodiment.
- (8) FIG. 8 is a partial cross sectional view illustrating an internal combustion engine including a piston unit according to a third modification of the embodiment.
- (9) FIG. 9 is a cross sectional view illustrating an internal combustion engine including a piston unit according to a fourth modification of the embodiment.
- (10) FIG. 10 is a partial cross sectional view illustrating the internal combustion engine including

the piston unit according to the fourth modification of the embodiment.

(11) FIGS. 11A-11C are diagrams for illustrating variations of the mode of fitting between the top land member and the piston.

MODE FOR CARRYING OUT THE INVENTION

(12) In the following, a preferred embodiment of the present invention will be described. What is described in the following as the embodiment is a case where the technology according to the present invention is applied to an internal combustion engine as an example of the reciprocating engine. It should be understood, however, that the technology according to the present invention can be applied to any mechanism, not limited to the internal combustion engine, that has a piston reciprocating in a cylinder. For example, the technology according to the present invention can be applied to reciprocating engines, such as internal combustion engines, and pneumatic equipment, such as compressors. The structures and features described in the following description of the embodiment are not intended to limit the technical scope of the present invention only to them, unless otherwise stated.

(13) Overall Structure

(14) FIG. 1 is a cross sectional view of an internal combustion engine 100 including a piston unit 20 according to the embodiment. FIG. 2 is a partial cross sectional view of the internal combustion engine 100 including the piston unit 20 according to the embodiment. FIGS. 1 and 2 show cross sections taken along the center axis A1 of the piston 1. As illustrated in FIGS. 1 and 2, the internal combustion engine 100 according to the embodiment includes a cylinder 10 and the piston unit 20 mounted in the cylinder 10. The internal combustion engine 100 is designed in such a way that the piston unit 20 reciprocates in the cylinder 10. In the following description of the internal combustion engine, the side facing the combustion chamber indicated by reference numeral "30" will be referred to as the upper side, and the side facing the crankcase indicated by the reference numeral "40" will be referred to as the lower side.

(15) As illustrated in FIGS. 1 and 2, the piston unit 20 includes a piston 1, a top land member 2 attached to the piston 1, a first ring groove 3 provided on the outer circumference of the piston 1, a plurality of piston rings 4, 5, 6 fitted in the first ring groove 3, and a plurality of partition rings 7, 8 fitted in the first ring groove 3 side by side with the piston rings 4, 5, 6 along the axial direction of the piston 1. The top land member 2, the piston rings 4, 5, 6, and the partition rings 7, 8 can be regarded as parts for the piston unit. The first ring groove 3 is formed on the outer circumference of the piston 1 as a space delimited by a groove wall forming surface 24 of the top land member 2, a step surface 14 of the piston 1, and a first outer circumferential surface 12 of the piston 1 (see FIG. 3). The first ring groove 3 will be described in further detail later. The piston unit 20 according to the embodiment is designed to use a combination of three piston rings including two compression rings including a top ring 4 and a second ring 5 and one oil control ring 6 that are fitted in the first ring groove 3.

(16) In this specification, the top ring 4, the second ring 5, and the oil control ring 6 will also be referred to simply as the "piston rings" when describing them without distinguishing between them. The state in which the piston 1 with the piston rings and the partition rings assembled thereto (to constitute the piston unit 20) is mounted (or inserted) in the cylinder 10 as illustrated in FIGS. 1 and 2 will be referred to as "the state in use". As illustrated in FIG. 2, the direction along the center axis of the piston 1 (i.e. the axial direction) is defined as the up-and-down direction. Along the axial direction of the piston 1, the side facing the combustion chamber 30 of the internal combustion engine 100 (i.e. the upper side in FIG. 1) is defined as the upper side, and the opposite side or the side facing the crankcase 40 (i.e. the lower side in FIG. 1) is defined as the lower side. In the following, the parts of the piston unit 20 will be described.

(17) Piston

(18) As illustrated in FIG. 1, the piston 1 has a generally stepped cylindrical outer shape. The piston 1 has the center axis A1. Among the two axial end surfaces of the piston 1, the end surface on the

combustion chamber **30** side (i.e. the upper surface) constitutes the top surface **11** of the piston **1**. The top surface **11** is a flat surface that is perpendicular to the axial direction of the piston **1** and facing the combustion chamber **30**. The top surface **11** corresponds to the “one end surface of the piston” according to the present invention. However, the “one end surface of the piston” according to the present invention is not limited to the top surface, but it may be either one of the two axial end surfaces of the piston. The piston **1** has a hollow part **1c** that opens at the lower end surface of the piston **1** and a pin hole **1d** that extends through the piston **1** from the hollow part **1c** to the exterior of the piston **1**. A piston pin (not shown) is inserted through the pin hole **1d**. The piston **1** is linked with a crankshaft via the piston pin. In the present invention, the mechanism used to transmit the power of the piston is not limited. For example, it may be a mechanism that converts reciprocating motion of the piston into rotary motion by a piston and crank mechanism (slider-crank mechanism) or a scotch yoke mechanism, or a free crank mechanism that does not have a connection rod or a crank.

(19) As illustrated in FIG. **1**, the piston **1** is sectioned into a first portion **1a** and a second portion **1b** along the axial direction. The first portion **1a** is a cylindrical portion including the upper end of the piston **1** (or the end at the top surface **11** side) and extends a certain length. The second portion **1b** is the other portion of the piston **1** than the first portion **1a**, which has a cylindrical shape and extends below the first portion **1a**. The outer circumferential surface of the first portion **1a** is referred to as the first outer circumferential surface and indicated by reference numeral “**12**” in the drawings. The outer circumferential surface of the second portion **1b** is referred to as the second outer circumferential surface and indicated by reference numeral “**13**” in the drawings. The outer diameter of the first portion **1a** (namely, the largest diameter of the first outer circumferential surface **12**) is $D1$, and the outer diameter of the second portion **1b** (namely, the largest diameter of the second outer circumferential surface **13**) is $D2$. In this design of the piston **1**, $D1 < D2$. In other words, the outer diameter of the first portion **1a** is smaller than the outer diameter of the second portion **1b**. Therefore, there is a radial step between the first outer circumferential surface **12** and the second outer circumferential surface **13**. The first outer circumferential surface **12** is located radially inside the second outer circumferential surface **13**. The first outer circumferential surface **12** and the second outer circumferential surface **13** are connected by the step surface **14**. While the step surface **14** in this embodiment is designed as a flat surface that is perpendicular to the axial direction of the piston **1**, the step surface according to the present invention is not limited to this design. The portion (corner) that connects the first outer circumferential surface **12** and the step surface **14** may be shaped like a curved surface or a chamfered surface.

(20) As illustrated in FIG. **2**, the first outer circumferential surface **12** includes a constant diameter surface **121** and a tapered surface **122**. The constant diameter surface **121** is connected to the inner circumferential edge of the step surface **14** and extends upward from the inner circumferential edge of the step surface **14** along the axial direction of the piston **1**. The tapered surface **122** connects the upper end of the constant diameter surface **121** and the outer circumferential edge of the top surface **11** of the piston **1**. The tapered surface **122** is beveled in such a way that its diameter decreases (or it becomes closer to the center axis **A**) as it extends toward the top surface **11**. The second outer circumferential surface **13** is connected to the outer circumferential edge of the step surface **14** and extends downward along the axial direction of the piston **1**. In this internal combustion engine **100**, a gap of a predetermined distance is left between the second outer circumferential surface **13** of the piston **1** and the inner wall surface **101** of the cylinder **10** to provide a piston clearance **PC1**.

(21) Top Land Member

(22) The top land member **2** is a member that is attached to the first portion **1a** of the piston **1** to function as a substitute for the top land. The top land member **2** according to the embodiment is shaped like a ring. However, the shape of the top land member according to the present invention is not limited to a ring (or annular) shape. The top land member **2** according to the embodiment is continuous around the entire circumference without a gap. The top land member **2** has a land outer

circumferential surface **21**, a piston-fit surface **22**, a land end surface **23**, and a groove wall forming surface **24**.

(23) The land end surface **23** is the upper end surface of the top land member **2** and faces the combustion chamber **30**. The land end surface **23** of the top land member **2** and the top surface **11** of the piston **1** constitute the top surface (or the upper end surface) of the piston unit **20**. While the land end surface **23** according to the embodiment is a flat surface that is perpendicular to the axial direction of the piston **1**, the present invention is not limited by this.

(24) The groove wall forming surface **24** is the lower end surface of the top land member **2** and faces the crankcase **40**. As illustrated in FIG. 2, the groove wall forming surface **24** is opposed to the step surface **14** of the piston **1** with a distance therebetween. While the groove wall forming surface **24** is designed to be parallel to the step surface **14**, the present invention is not limited by this. The groove wall forming surface **24** may be slanted relative to the step surface **14**.

(25) The piston-fit surface **22** is an annular surface that constitutes the inner circumferential surface of the top land member **2**. The piston-fit surface **22** is fitted to the tapered surface of the first outer circumferential surface **12** of the first portion **1a**, whereby the top land member **2** is fixed to the first portion **1a** of the piston **1**. The piston-fit surface **22** of the top land member **2** is in intimate contact with the first outer circumferential surface **12** of the piston **1**. The piston-fit surface **22** is in contact with the first outer circumferential surface **12** around the entire circumference. Examples of the mode of attaching the top land member **2** to the piston include, but are not limited to, shrink fitting, friction bonding, using screws, screwing, adhesion, and welding.

(26) To match with the shape of the tapered surface **122**, the piston-fit surface **22** is slanted in such a way that its diameter decreases as it extends upward. The piston-fit surface **22** and the tapered surface **122** are fitted together, so that the top land member **2** is supported by the tapered surface **122** from below. This restricts the movement of the top land member **2** in the direction away from the top surface **11** (i.e. downward direction), so that a predetermined spacing between the groove wall forming surface **24** and the step surface **14** is kept.

(27) FIGS. 4A-4D are diagrams for illustrating variations of the mode of fitting between the top land member **2** and the piston **1**. As illustrated in FIG. 4A, the first outer circumferential surface **12** of the piston **1** and the piston-fit surface **22** of the top land member **2** may be surfaces extending along the axial direction. As illustrated in FIG. 4B, the first portion **1a** may be provided with a radial step that can receive the top land member **2** to restrict the downward movement of the top land member **2**. As illustrated in FIG. 4C, a portion of the inner circumferential surface of the top land member **2** may be expanded radially inward, and the first portion **1a** may be provided with a radial step that can receive this portion of the top land member **2** to restrict the downward movement of the top land member **2**. As illustrated in FIG. 4D, the piston-fit surface **22** of the top land member **2** may be partly slanted so that a portion of the piston-fit surface **22** is fitted to the constant diameter surface **121** and the other portion is fitted to the tapered surface **122**.

(28) The land outer circumferential surface **21** constitutes the outer circumferential surface of the top land member **2**. The land outer circumferential surface **21** constitutes a part of the outer circumferential surface of the piston unit **20**. More specifically, the land outer circumferential surface **21** serves as the outer circumferential surface of the top land. The outer diameter of the top land member **2** (namely, the largest diameter of the land outer circumferential surface **21**) is designed to be smaller than the inner diameter of the inner wall surface **101** of the cylinder **10**. Therefore, a predetermined spacing is left between the land outer circumferential surface **21** of the top land member **2** and the inner wall surface **101** of the cylinder **10**. In other words, the top land member **2** is spaced from the inner wall surface **101** of the cylinder **10**. The outer diameter of the top land member **2** is designed to be larger than the inner diameter of the piston rings **4**, **5**, **6**.

(29) As illustrated in FIG. 2, the top land member **2** is attached to the first portion **1a** in such a way that a predetermined distance between the groove wall forming surface **24** and the step surface **14** is kept along the axial direction of the piston **1**. Thus, the first ring groove **3** in which the piston

rings and the partition rings can be fitted is formed on the outer circumference of the piston **1**. FIG. **3** is a cross sectional view illustrating the first ring groove **3** according to the embodiment. In FIG. **3**, the first ring groove **3** is the dot-hatched area. As illustrated in FIG. **3**, the first ring groove **3** is defined by the groove wall forming surface **24** of the top land member **2**, the step surface **14** of the piston **1**, and the first outer circumferential surface **12** (more specifically, the constant diameter surface **121**) of the piston member **1**. The groove wall forming surface **24** serves as the upper inner wall of the first ring groove **3**, the step surface **14** serves as the lower inner wall of the first ring groove **3**, and the constant diameter surface **121** of the first outer circumferential surface **12** serves as the bottom wall of the first ring groove **3**. The first ring groove **3** configured as above is a groove having a rectangular cross sectional shape that extends annularly about the axis of the piston **1** around the entire circumference of the piston **1**. Since the piston-fit surface **22** is in contact with the first outer circumferential surface **12** around the entire circumference, the oil in the first ring groove **3** is prevented from leaking between the piston **1** and the top land member **2**.

(30) The material of the top land member **2** is not limited. For example, a steel, a cast iron, a copper alloy, or an aluminum alloy may be used. For example, a material having a coefficient of linear expansion that is different from the material of the piston **1** may be used for the top land member **2**.

(31) The surface of the top land member **2** may have a coating applied thereon that includes at least one of a resin coating layer, a nitrided coating layer, an anodic oxidation coating layer, a plated coating layer, a PVD coating layer, a paint coating layer, and a DLC coating layer. The resin coating refers to a coating made of a resin material. The nitrided coating refers to a coating that is produced by infiltrating nitride into a metal surface by nitriding. The plated coating refers to a coating produced by plating. Examples of the plated coating include an Ni—P plated coating and a chromium plated coating. The Ni—P plated coating refers to a coating produced by Ni—P plating. For example, the method of Ni—P plating may be electroless Ni—P plating, though the method is not limited to this. The chromium plated coating refers to a coating produced by chromium plating. Chromium plating is also called industrial chromium plating. The PVD (Physical Vapor Deposition) coating refers to a coating produced by PVD. The DLC (Diamond Like Carbon) coating refers to an amorphous hard carbon film that is made mainly of hydrocarbons and carbon isotopes. It is preferred that such a coating be applied to the piston-fit surface **22** and the groove wall forming surface **24**, which are the surfaces of the top land member **2** that are to be in contact with other parts. Applying such a coating can enhance the abrasion resistance of the top land member **2**, thereby preventing problems that might otherwise be caused by direct contact of their base members, such as adhesion of the top land member **2** and other members.

(32) The land end surface **23** and the land outer circumferential surface **21** of the top land member **2**, which face the combustion chamber **30**, may be provided with a heat insulation layer. The heat insulation layer is made of a material that can make the heat transfer between the combustion chamber **30** and the top land member **2** lower than that without the heat insulation layer. For example, the heat insulation layer may be a flame spray coating layer of a ceramic material (e.g. alumina or zirconia). Providing the heat insulation layer on the land end surface **23** of the top land member **2** can reduce rises in the temperature of the piston **1**.

(33) Piston Ring

(34) The piston rings **4**, **5**, **6** are sliding members that are attached to the piston **1** mounted in the cylinder **10** of the internal combustion engine **100** to slide on the inner wall surface **101** of the cylinder **10** with the reciprocating motion of the piston **1**. The three piston rings **4**, **5**, **6** are fitted in one first ring groove **3** in the piston unit **20** according to the embodiment.

(35) As illustrated in FIG. **2**, the top ring **4** is the compression ring that is set at the position closest to the top surface **11** of the piston **1** (i.e. the uppermost position) among the three piston rings. The top ring **4** used in this embodiment is designed to have a rectangular shape, in other words, its cross sectional shape is rectangular. The top ring **4** has an outer circumferential surface **41**, an inner circumferential surface **42**, a top surface **43**, and a bottom surface **44**. The top surface **43** and the

bottom surface **44** define the axial width of the top ring **4**. The outer circumferential surface **41** is shaped like a barrel surface that is curved in such a way as to bulge radially outward. The top ring **4** is assembled to the piston **1** in such a way that the top surface **43**, which is one of the two axial end surfaces of the top ring **4**, faces upward, the bottom surface **44**, which is the other axial end surface, faces downward, and the outer circumferential surface **41** is in sliding contact with the inner wall surface **101** of the cylinder **10** in the internal combustion engine **100**. The top ring **4** has a self-tension so that the outer circumferential surface **41** presses the inner wall surface **101** of the cylinder **10** in the state in use. Thus, the top ring **4** has the function of sealing against gases and oil. The shape of the top ring according to the present invention is not limited to the shape described above. A variety of shapes can be adopted for the top ring. For example, the outer circumference of the top ring may be straight faced or taper faced. The top ring may be designed to have a keystone shaped cross section, a half-keystone shaped cross section, or an internally beveled cross section.

(36) As illustrated in FIG. 2, the second ring **5** is the compression ring that is set at the position second closest to the top surface **11** of the piston **1** among the three piston rings. In other words, the second ring **5** is set between the top ring **4** and the oil control ring **6**. The second ring **5** has an outer circumferential surface **51**, an inner circumferential surface **52**, a top surface **53**, and bottom surface **54**. The top surface **53** and the bottom surface **54** define the axial width of the second ring **5**. The second ring **5** has a rectangular shape, and the outer circumferential surface **51** of the second ring **5** has a tapered shape so that its diameter increases as it extends downward. The second ring **5** is assembled to the piston **1** in such a way that the top surface **53**, which is one of the two axial end surfaces of the second ring **5**, faces upward, the bottom surface **54**, which is the other axial end surface, faces downward, and the outer circumferential surface **51** is in sliding contact with the inner wall surface **101** of the cylinder **10** in the internal combustion engine **100**. The second ring **5** has a self-tension so that the outer circumferential surface **51** presses the inner wall surface **101** of the cylinder **10** in the state in use. Thus, the second ring **5** has the function of sealing against gases and oil. The shape of the second ring according to the present invention is not limited to the shape described above. A variety of shapes can be adopted for the second ring. For example, the outer circumferential surface of the second ring may be barrel faced or straight faced. The second ring may be a scraper ring having an undercut or a napier ring. The second ring may be designed to have a keystone shaped cross section, a half-keystone shaped cross section, or an internally beveled cross section.

(37) As illustrated in FIG. 2, the oil control ring **6** is the piston ring that is set at the position farthest from the top surface **11** of the piston **1** (i.e. the lowermost position) among the three piston rings. As illustrated in FIG. 2, the oil control ring **6** is what is called a three-piece combined ring, which includes a pair of segments **61U**, **61L** (an example of a pair of sliding parts) and a spacer-expander **62** (an example of an expander).

(38) The two segments **61U**, **61L** are annular around the axis of the oil control ring **6**. The two segments **61U**, **61L** are provided independently from each other and juxtaposed along the axial direction. The upper segment **61U** is disposed on the upper side (or the top) of the spacer-expander **62**, and the lower segment **61L** is disposed on the lower side (or the bottom) of the spacer-expander **62**. The two segments **61U**, **61L** used in the oil control ring **6** described here have the same shape. However, according to the present invention, the two segments may have different shapes. In the following, the two segments **61U**, **61L** will also be simply referred to as the segment or segments **61** when describing them without distinguishing them. As illustrated in FIG. 2, the segment **61** has an outer circumferential surface **611**, an inner circumferential surface **612**, a top surface **613**, and a bottom surface **614**. The top surface **613** and the bottom surface **614** define the axial width of the segment **61**. Each segment **61** is assembled to the piston **1** in such a way that the top surface **613**, which is one of the two axial end surfaces of the segment **61**, faces upward, the bottom surface **614**, which is the other axial end surface, faces downward, and the outer circumferential surface **611** is in sliding contact with the inner wall surface **101** of the cylinder **10** in the internal combustion

engine **100**. The spacer-expander **62** is set between the two segments **61U**, **61L**. The spacer-expander **62** has a self-tension so that its diameter expands in the state in use. In consequence, the upper segment **61U** and the lower segment **61L** are biased radially outward by the spacer-expander **62**, so that the outer circumferential walls **611** of them press the inner wall surface **101** of the cylinder **10**. Thus, the function of sealing against oil is achieved. The shape of the oil control ring according to the present invention is not limited to the shape described above. For example, the oil control ring may be what is called a two piece oil control ring, which has an oil control ring body that is annular about its axis and provided with a pair of rails (an example of the pair of sliding parts) that extend radially outward and are juxtaposed along the axial direction, and a coil expander (an example of the expander) that biases the oil control ring body radially outward. The oil control ring may be designed to function as a single piece without a spacer-expander or a coil expander.

(39) Partition Ring

(40) The partition rings **7**, **8** are ring-shaped members that are fitted in the first ring groove **3** side by side with one or more piston rings (in the case described herein, the three piston rings **4**, **5**, **6**) along the axial direction of the piston **1** to function as substitutes for piston lands. The partition rings **7**, **8** used in this embodiment are each designed to have a rectangular shape, in other words, their cross sectional shape in the cross section perpendicular to the circumferential direction is rectangular. However, the present invention is not limited to this.

(41) As illustrated in FIG. **2**, the first ring groove **3** of the piston unit **20** is partitioned by the partition ring **7** disposed between the top ring **4** and the second ring **5**, and the partition ring **8** disposed between the second ring **5** and the oil control ring **6**.

(42) As illustrated in FIG. **2**, each of the partition rings **7**, **8** has an outer circumferential spacing surface **S1**, an inner circumferential fitting surface **S2**, an upper partition wall surface **S3**, and a lower partition wall surface **S4**. In the state in use, the upper partition wall surface **S3** faces toward the combustion chamber **30**, and the lower partition wall surface **S4** faces toward the crankcase **40**. The inner circumferential fitting surface **S2** is provided on the inner circumference of the partition rings **7**, **8**. In the state in use, the inner fitting surface **S2** is fitted to the constant diameter surface **121** of the first circumferential surface **12** in the first portion **1a** to stay in contact with the first outer circumferential surface **12**. In this embodiment, the inner circumferential fitting surface **S2** is in contact with the first outer circumferential surface **12** around the entire circumference. However, the present invention is not limited to this, just a portion of the inner circumferential fitting surface in contact with the outer circumferential surface of the first portion is sufficient. In this embodiment, the inner circumferential fitting surface **S2** is fitted to the first outer circumferential surface **12** in such a way that the partition ring **7**, **8** can slide on the first outer circumferential surface **12** along the axial direction. Therefore, the partition rings **7**, **8** can be displaced along the axial direction together with the piston rings **4**, **5**, **6**. Nevertheless, the present invention is not limited to this. The inner circumferential fitting surface may be fitted to the outer circumferential surface of the first portion in such a way that the partition rings cannot be displaced along the axial direction. The outer circumferential spacing surface **S1** is provided on the outer circumference of the partition rings **7**, **8** to connect the outer circumferential edge of the upper partition wall surface **S3** and the outer circumferential edge of the lower partition wall surface **S4**. In the state in use, the outer circumferential spacing surface **S1** leaves a predetermined spacing distance to the inner wall surface **101** of the cylinder **10**. Therefore, the partition rings **7**, **8** are spaced apart from the inner wall surface **101** of the cylinder **10**.

(43) The upper partition wall surfaces **S3** of the partition rings **7**, **8** may be either parallel to or slanted relative to the groove wall forming surface **24** of the top land member **2**. Likewise, the lower partition wall surfaces **S4** of the partition rings **7**, **8** may be either parallel to or slanted relative to the step surface **14** of the piston **1**. The edges of the partition rings **7**, **8** may be provided with chamfers or step-cuts.

(44) The partition rings **7**, **8** may or may not have a gap in them. FIGS. **5A** and **5B** are top views

(seen from above along the axial direction) that schematically illustrates shapes of the partition rings **7**, **8** according to the embodiment. As illustrated in FIG. 5A, the partition rings **7**, **8** may have a gap indicated by reference sign "G1". The gap G1 is formed between a pair of butt ends that are opposed to each other. As illustrated in FIG. 5B, the partition rings **7**, **8** may be continuous around the entire circumference without a gap.

(45) As illustrated in FIG. 2, the groove wall forming surface **24** of the top land member **2** and the upper partition wall surface S3 of the partition ring **7** define therebetween a space in which the top ring **4** can be set. The lower partition wall surface S4 of the partition ring **7** and the upper partition wall surface S3 of the partition ring **8** define therebetween a space in which the second ring **5** can be set. The lower partition wall surface S4 of the partition ring **8** and the step surface **14** of the piston **1** define therebetween a space in which the oil control ring **6** can be set. In this way, the partition ring **7** placed between the top ring **4** and the second ring **5** keeps the top ring **4** and the second ring **5** apart. The partition ring **8** placed between the second ring **5** and the oil control ring **6** keeps the second ring **5** and the oil control ring **6** apart. As above, the partition rings **7**, **8** are placed between the piston rings **4**, **5**, **6** to partition the first ring groove **3**, thereby allowing the three piston rings **4**, **5**, **6** to be set in the single first ring groove **3**. In this piston unit **20**, the partition ring **7** functions as a substitute for the second land, and the partition ring **8** functions as a substitute for the third land.

(46) The material of the partition rings **7**, **8** is not limited particularly. For example, partition rings made of a steel, a cast iron, a copper alloy, or aluminum alloy can be used. The surface of the partition rings **7**, **8** may have a coating applied thereon that includes at least one of a resin coating layer, a nitrided coating layer, an anodic oxidation coating layer, a plated coating layer, a PVD coating layer, a paint coating layer, and a DLC coating layer. It is preferred that such a coating be applied to the inner circumferential fitting surface S2, the upper partition wall surface S3, and the lower partition wall surface S4, which are the surfaces of the partition rings **7**, **8** that are to be in contact with other parts. Applying such a coating can enhance the abrasion resistance of the partition rings **7**, **8**, thereby preventing problems that might otherwise be caused by direct contact of their base members, such as adhesion of the partition rings **7**, **8** and other members.

(47) Process of Assembling the Piston Unit

(48) The piston unit **20** according to the embodiment is assembled in the following manner. Firstly, the piston rings **4**, **5**, **6** and the partition rings **7**, **8** are attached to the piston **1** to which the top land member **2** is not attached. The piston rings **4**, **5**, **6** and the partition rings **7**, **8** are attached to the first portion **1a** of the piston **1** in order from the ring farthest from the top surface **11** of the piston **1** (i.e. the oil control ring **6**, in the case of this embodiment). Thereafter, the top land member **2** is attached to the first portion **1a** of the piston **1** to form the first ring groove **3**, resulting in the piston unit **20** assembled as shown in FIG. 1. Examples of the method of attaching the partition rings **7**, **8** include, but are not limited to, shrink fitting, friction bonding, using screws, screwing, adhesion, and welding. In the case where friction bonding is used, the partition rings **7**, **8** are fitted to the piston **1** and then slid on the piston **1** so that they are bonded to the piston **1**.

Operation and Advantageous Effects

(49) As above, the piston unit **20** according to the embodiment has the piston **1**, the top land member **2** attached to the piston **1**, the first ring groove **3** formed on the outer circumference of the piston **1**, the plurality of piston rings **4**, **5**, **6** that are fitted in the first ring groove **3** to slide on the inner wall surface **101** of the cylinder **10**, and the plurality of partition rings **7**, **8** that are fitted in the first ring groove **3** side by side with the piston rings **4**, **5**, **6** along the axial direction of the piston **1**. The piston **1** has the first portion **1a** that includes its top surface **11** side end and to which the top land member **2** is attached. The outer diameter of the first portion **1a** is smaller than the outer diameter of the second portion **1b**, which is the other portion of the piston **1** than the first portion **1a**, so that there is a step between the first portion **1a** and the second portion **1b**. The top land member **2** has a groove wall forming surface **24** opposed to the step surface **14** that connects

the first outer circumferential surface **12** of the first portion **1a** and the second outer circumferential surface **13** of the second portion **1b**. The groove wall forming surface **24**, the step surface **14**, and the first outer circumferential surface **12** define the first ring groove **3** in the piston unit **20**.

(50) As above, the piston unit **20** uses the top land member **2** that is separate from the piston **1** and detachably attached to the piston **1** to constitute the top land, which is the portion between the top surface **11** of the piston **1** and the first ring groove **3**. Therefore, it is possible to assemble the piston rings **4**, **5**, **6** and the partition rings **7**, **8** to the piston **1** without the top land member **2** attached thereto. With this construction, in the process of assembly, it is not necessary to expand the piston rings **4**, **5**, **6** and the partition rings **7**, **8** to make their inner diameters larger than the outer diameter of the top land, and therefore it is possible to easily assemble the piston rings **4**, **5**, **6** and the partition rings **7**, **8** to the piston **1** even in the case where they do not have gaps. In other words, this construction allows a piston ring or a partition ring that does not have a gap (which will also be referred to as a gapless ring hereinafter) to easily be assembled to the piston. Moreover, in the case where the piston rings **4**, **5**, **6** and the partition rings **7**, **8** have gaps, the piston unit **20** constructed as above eliminates the need to expand them to make their inner diameters larger than the outer diameter of the top land in the process of assembly, and therefore deformation or breakage of the rings due to excessive expansion of their gaps can be prevented.

(51) As above, the piston unit **20** allows easy assembly of the piston rings **4**, **5**, **6** and the partition rings **7**, **8**. Likewise, the piston unit **20** allows easy detachment of the piston rings **4**, **5**, **6** and the partition rings **7**, **8**. Therefore, the piston unit **20** allows easy replacement of the piston rings **4**, **5**, **6** and the partition rings **7**, **8**, resulting in a longer life of the internal combustion engine **100**.

(52) According to the present invention, at least one partition ring among one or more partition rings fitted in the first ring groove may be a gapless ring, or at least one piston ring among one or more piston rings fitted in the first ring groove may be a gapless ring. This can prevent blow-by or oil rising through gaps from occurring. The use of gapless partition rings makes manufacturing of partition rings easier. In consequence, the manufacturing cost can be reduced, and the accuracy of dimension of the partition rings can be increased.

(53) Since the top land of the piston unit **20** is constituted by the top land member **2** separate from the piston **1**, the material and the surface processing for the top land can easily be made different from those for the piston **1**. Selecting an appropriate material and surface processing for the top land member **2** helps to prevent problems such as aluminum adhesion at the point of contact between the top ring **4** and the top land member **2** and to improve the abrasion resistance and the heat resistance of the top land member **2**.

(54) While the piston unit **20** according to the embodiment is provided with only one ring groove (only the first ring groove **3**), the piston unit according to the present invention may have a plurality of ring grooves formed on the outer circumference of the piston. What is taught by the present invention is that one or more piston rings are fitted in the first ring groove that is closest to one end surface (the top surface **11** in this embodiment) of the piston among a plurality of ring grooves. Therefore, the number of piston rings fitted in the first ring groove is not limited to three, but it may be two or less, or four or more. For example, two ring grooves may be provided on the outer circumference of the piston, two piston rings (top and second rings) may be fitted in the ring groove (first ring groove) closest to one end surface of the piston together with a partition ring, and one piston ring (oil control ring) may be fitted in the ring groove (second ring groove) second closest to the top surface, as described later in the second modification. The types of piston rings are not limited to the top ring, the second ring, and the oil control ring described above.

(55) When the internal combustion engine uses a plurality of piston rings attached to the piston, in the case where ring grooves are provided for the respective piston rings on a ring-by-ring basis, it is necessary to make the distances between the ring grooves short in order to make the axial length of the piston shorter. However, making the distances between the ring grooves shorter results in shorter widths of the piston lands between adjacent ring grooves, and therefore it is difficult to keep

the strength of the piston. In terms of the accuracy of finishing the ring grooves, it is difficult to make the axial length of the piston shorter. In contrast, in the case of the piston unit **20** according to the embodiment, the partition rings **7, 8** that are fitted to the first outer circumferential surface **12** of the first portion **1a** with a predetermined spacing to the inner wall surface **101** of the cylinder **10** function as substitutes for the piston lands that separate the piston rings **4, 5, 6** in the first ring groove **3**. Therefore, it is not necessary to provide ring grooves in which the piston rings **4, 5, 6** are fitted on a ring-by-ring basis on the piston **1**. In other words, the piston unit **20** according to the embodiment allows a plurality of piston rings (the piston rings **4, 5, 6** in this embodiment) to be fitted in one ring groove (the first ring groove **3**). Therefore, when the internal combustion engine uses a plurality of piston rings attached to the piston, it is possible to make the number of ring grooves smaller than in the case where ring grooves are formed for the respective piston rings on a ring-by-ring basis. This makes it easy to make the axial length of the piston **1** shorter. In consequence, the piston unit **20** is advantageous in reducing the weight of the piston and the weight of the internal combustion engine. The piston unit **20** also makes it possible to reduce the axial length of the piston **1** by reducing the widths of the piston rings and the partition rings. Since the number of ring grooves to be formed on the piston **1** is reduced, it is possible to enhance the strength of the piston, as compared to the case where ring grooves are formed for the respective piston rings on a ring-by-ring basis. This makes it possible to increase the power of the internal combustion engine.

(56) The piston unit **20** provided with the partition rings **7, 8** can reduce design constraints on the land volume. Here, the term “land volume” refers to the volume of a space (land space) enclosed by axially adjacent piston rings, the outer circumferential surface of the piston, and the inner wall surface of the cylinder. In this embodiment, since the partition rings **7, 8** serve as substitutes for piston lands, the space enclosed by the bottom surface **44** of the top ring **4**, the top surface **53** of the second ring **5**, the outer circumferential spacing surface **S1** of the partition ring **7**, and the inner wall surface **101** of the cylinder **10** constitutes the second land space, and the space enclosed by the bottom surface **54** of the second ring **5**, the top surface **613** of the upper segment **61U** of the oil control ring **6**, the outer circumferential spacing surface **S1** of the partition ring **8**, and the inner wall surface **101** of the cylinder **10** constitutes the third land space. Since the partition rings **7, 8** are members that are separate from the piston **1**, constraints on the reduction of the axial width of the partition rings **7, 8** in terms of strength are smaller than those for the piston lands. Therefore, the piston unit **20** can enjoy a higher degree of design freedom in terms of land volume. In consequence, it is possible to increase the degree of design freedom in terms of the function of pressure adjustment and the function as an oil reservoir to be exercised by the land space.

(57) The piston is typically made of an aluminum alloy, and there is a possibility that aluminum adhesion occurs at the point of contact between the piston ring and the piston. There also is a possibility that the piston wears with sliding between the piston and the piston ring. Since the piston unit **20** uses the partition ring **7** placed between the top ring **4** and the second ring **5** in place of the second land and the partition ring **8** placed between the second ring **5** and the oil control ring **6** in place of the third land, the number of points of contacts between the piston rings **4, 5, 6** and the piston **1** can be made smaller than in the case where the piston rings are separated by the piston lands. Therefore, it is possible to reduce problems such as aluminum adhesion that can be caused by direct contact of the piston rings **4, 5, 6** and the partition rings **7, 8**. It is also possible to prevent problems such as aluminum adhesion at the points of contact between the piston rings **4, 5, 6** and the partition rings **7, 8** and to improve the abrasion resistance and the heat resistance of the partition rings **7, 8** by selecting an appropriate material and surface processing for the partition rings **7, 8**.

(58) Since the piston unit **20** is designed in such a way that the first outer circumferential surface **12** of the piston **1** and the inner circumferential fitting surface **S2** of the partition rings **7, 8** are kept in contact with each other, oil rising and gas leakage through the inner circumference of the partition rings **7, 8** in the first ring groove **3** can be prevented. Since the first outer circumferential surface **12**

of the piston **1** and the inner circumferential fitting surface **S2** of the partition rings **7, 8** are kept in contact with each other, the heat of the piston **1** is transferred from the first outer circumferential surface **12** to the piston rings **4, 5, 6** through the inner circumferential fitting surface **S2** of the partition rings **7, 8**, and then dissipated to the cylinder **10**, with which the piston rings **4, 5, 6** are in sliding contact. To achieve cooling of the piston **1**, it is sufficient that at least a portion of the inner circumferential fitting surface **S2** is in contact with the first outer circumferential surface **12** of the piston **1**.

(59) While a plurality of partition rings (two partition rings **7, 8**) is fitted in the first ring groove **3** according to the embodiment, the number of partition rings fitted in the first ring groove is not limited to two, but it may be one, or three or more. In other words, one or more partition rings may be fitted in the first ring groove. For example, two piston rings (top and second rings) and one partition ring may be fitted in the first ring groove, and the partition ring may be disposed between the two piston rings as described later in the description of the second modification. For further example, one piston ring (top ring) and one partition ring may be fitted in the first ring groove, and the partition ring may be disposed between the bottom surface of the piston ring and the step surface of the piston (the lower inner wall of the ring groove). This design also can reduce the number of points of contact between the piston rings and the piston. The partition ring is not an essential part of the piston unit according to the present invention. The piston unit according to the present invention may not have a partition ring, as described later in the description of a third modification.

Modifications

(60) In the following, modifications of the embodiment will be described. The following description is mainly directed to features that are different from the features of the piston unit **20** described above. Similar features are denoted by the same reference signs and not described in further detail.

First Modification

(61) FIG. **6** is a partial cross sectional view of an internal combustion engine **100A** provided with a piston unit **20A** according to the first modification of the embodiment. The piston unit **20A** according to the first modification **1** is different from the piston unit **20** described above in the shape of the partition rings.

(62) As illustrated in FIG. **6**, a partition ring **7A** according to the first modification has a T-shape in the cross section perpendicular to the circumferential direction. The partition ring **7A** has an outer circumferential spacing surface **S1**, an inner circumferential fitting surface **S2**, an upper partition wall surface **S3**, a lower partition wall surface **S4**, an upper protruding portion **UP1** and a lower protruding portion **LP1**. A partition ring **8A** according to the first modification has an L-shape in the cross section perpendicular to the circumferential direction. The partition ring **8A** has an outer circumferential spacing surface **S1**, an inner circumferential fitting surface **S2**, an upper partition wall surface **S3**, a lower partition wall surface **S4**, and a lower protruding portion **LP1**. The upper protruding portion **UP1** is provided on the inside of the upper partition wall surface **S3** with respect to the radial direction of the piston **1** and protrudes upward (toward the combustion chamber **30**) above the upper partition wall surface **S3**. The lower protruding portion **LP1** is provided on the inside of the lower partition wall surface **S4** with respect to the radial direction of the piston **1** and protrudes downward (toward the crankcase **40**) below the lower partition wall surface **S4**.

(63) The upper protruding portion **UP1** of the partition ring **7A** abuts the groove wall forming surface **24** of the top land member **2** on the side of the inner circumferential surface **42** of the top ring **4** to restrict upward movement of the partition ring **7A**. The lower protruding portion **LP1** of the partition ring **7A** abuts the upper partition wall surface **S3** of the partition ring **8A** on the side of the inner circumferential surface **52** of the second ring **5** to restrict downward movement of the partition ring **7A** and upward movement of the partition ring **8A**. The lower protruding portion **LP1** of the partition ring **8A** abuts the step surface **14** of the piston **1** on the side of the inner

circumferential surface of the oil control ring **6** to restrict downward movement of the partition ring **8A**. In this way, the partition rings **7A**, **8A** are held along the axial direction of the piston **1**, whereby axial movement of them is restricted.

(64) In the piston unit **20A** according to the first modification, axial movement of the partition rings **7A**, **8A** is restricted by the upper protruding portion **UP1** and the lower protruding portions **LP2**, by which side clearances of the piston rings **4**, **5**, **6** can be left. The side clearance refers to a clearance formed between a piston ring and another member (top land member, partition ring, or piston) that is adjacent to the piston ring along the axial direction of the piston.

Second Modification

(65) FIG. **7** is a partial cross sectional view of an internal combustion engine **100B** provided with a piston unit **20B** according to the second modification of the embodiment. The piston unit **20B** according to the second modification has a second ring groove **102** formed on the second outer circumferential surface **13** of the piston **1**. In other words, the piston unit **20B** has a plurality of (two) ring grooves formed on the outer circumference of the piston **1**. The top ring **4**, the second ring **5**, and the partition ring **7** are fitted in the first ring groove **3**, and the partition ring **7** is disposed between the top ring **4** and the second ring **5**. The oil control ring **6** is fitted in the second ring groove **102**.

Third Modification

(66) FIG. **8** is a partial cross sectional view of an internal combustion engine **100C** provided with a piston unit **20C** according to the third modification of the embodiment. The piston unit **20C** according to the third modification is not provided with a partition ring. The piston unit **20C** according to the third modification has a second ring groove **102** and a third ring groove **103** that are formed on the second outer circumferential surface **13** of the piston **1** and arranged in order away from the top surface **11** of the piston **1**. In other words, the piston unit **20C** has a plurality of (three) ring grooves formed on the outer circumference of the piston **1**. The top ring **4** is fitted in the first ring groove **3**, the second ring **5** is fitted in the second ring groove **102**, and the oil control ring **6** is fitted in the third ring groove **103**.

Fourth Modification

(67) FIG. **9** is a cross sectional view of an internal combustion engine **100D** provided with a piston unit **20D** according to the fourth modification of the embodiment. FIG. **10** is a partial cross sectional view of the internal combustion engine **100D** provided with the piston unit **20D** according to the fourth modification of the embodiment. As illustrated in FIG. **9**, the piston unit **20D** according to the fourth modification is different from the piston unit **20** described above in that the top land member is shaped like a cap.

(68) As illustrated in FIGS. **9** and **10**, a top land member **2D** according to the fourth modification has an annular portion **2a** and a lid portion **2b**. As illustrated in FIG. **10**, the annular portion **2a** is an annular portion that has an inner circumferential surface that constitutes an annular piston-fit surface **22** fitted to the first outer circumferential surface **12** of the first portion **1a** of the piston **1**. According to the fourth modification, the groove wall forming surface **24** is constituted by the bottom end surface of the annular portion **2a**. According to the fourth modification, the land outer circumferential surface **21** is constituted by the outer circumferential surface of the annular portion **2a**. The lid portion **2b** is provided inside the annular portion **2a**. The lid portion **2b** fills the inside space of the annular portion **2a** except for a certain region including its lower end. Thus, a piston-fit surface **22** is provided inside the annular portion **2a**. According to the fourth modification, the land end surface **23** includes the top end surface of the annular portion **2a** and the top end surface of the lid portion **2b**. According to the fourth modification, the land end surface **23** of the top land member **2D** constitutes the top surface (top end surface) of the piston unit **20D**.

(69) As illustrated in FIG. **10**, the lid portion **2b** of the top land member **2D** covers the top surface **11** of the piston **1**. The lid portion **2b** abuts the top surface **11** of the piston **1**, so that the top land member **2D** is supported by the top surface **11** from below. This restricts the movement of the top

land member 2D in the direction away from the top surface 11 (i.e. downward direction), so that a predetermined spacing between the groove wall forming surface 24 and the step surface 14 is kept. (70) FIGS. 11A-11C are diagrams for illustrating variations of the mode of fitting of the top land member 2D and the piston 1. As illustrated in FIG. 11A, the first portion 1a may be provided with a radial step, to which the piston-fit surface 22 may be fitted. As illustrated in FIG. 11B, the piston-fit surface 22 of the top land member 2D may be slanted (or beveled) in its entirety so that it fits the tapered surface 122. As illustrated in FIG. 11C, the piston-fit surface 22 may be partly slanted (or beveled) so that a portion thereof fits the constant diameter surface 121 and the other portion thereof fits the tapered surface 122.

Others

(71) While preferred modes of the present invention have been described in the foregoing, the various modes described above can be adopted in any feasible combination.

REFERENCE SIGNS LIST

(72) 100, 100A, 100B, 100C, 100D: internal combustion engine 10: cylinder 20, 20A, 20B, 20C, 20D: piston unit 30: combustion chamber 40: crankcase 1: piston 2, 2D: top land member 3: first ring groove 4, 5, 6: piston ring 7, 7A, 8, 8A: partition ring

Claims

1. A piston unit adapted to reciprocate in a cylinder, comprising: a piston; a top land member attached to the piston; one or more ring grooves formed on an outer circumference of the piston; and one or more piston rings fitted in a first ring groove closest to one end surface of the piston among the one or more ring grooves to slide on an inner wall surface of the cylinder, wherein the piston includes a first portion including a piston end at a one end surface side and fitted with the top land member, the first portion having a smaller outer diameter than a second portion such that there is a step therebetween, the second portion being the other portion of the piston than the first portion, the top land member has a slanted piston-fit surface that attaches horizontally side-by-side to an equal length tapered surface of the first portion, the first ring groove is defined by the groove wall forming surface, the step surface, and the outer circumferential surface of the first portion, the top land member is formed as a ring that has an annular piston-fit surface fitted to the outer circumferential surface of the first portion as an inner circumferential surface, and wherein the piston-fit surface is slanted to have its diameter decrease as it extends upwards and the diameter of the tapered surface decreases in the same direction and fits to the outer circumferential surface of the first portion in such a way that the top land member is supported by the outer circumferential surface of the first portion from the other end surface of the piston side.
2. A piston unit according to claim 1, further comprising one or more partition rings fitted in the first ring groove side by side with the one or more piston rings along the axial direction of the piston, wherein the one or more partition rings are fitted to the outer circumferential surface of the first portion with a predetermined spacing to the inner wall of the cylinder.
3. A piston unit according to claim 2, wherein at least one partition ring among the one or more partition rings has no gap.
4. A piston unit according to claim 2, wherein a plurality of piston rings is fitted in the first ring groove, and the partition ring is disposed between the piston ring closest to the one end surface of the piston and the piston ring second closest to the one end surface of the piston among the plurality of piston rings.
5. A piston unit according to claim 1 mounted in a cylinder of an internal combustion engine.
6. A top land member attached to a piston adapted to reciprocate in a cylinder, wherein the piston has one or more ring grooves formed on its outer circumference, the piston includes a first portion including a piston end at one end surface side and fitted with the top land member, the first portion having a smaller outer diameter than a second portion such that there is a step therebetween, the

second portion being the other portion of the piston than the first portion, the first ring groove that is closest to the one end surface among the one or more ring grooves is fitted with one or more piston rings adapted to slide on an inner wall surface of the cylinder, the top land member has a slanted piston-fit surface that attaches horizontally side-by-side to an equal length tapered surface of the first portion, the first ring groove is defined by the groove wall forming surface, the step surface, and the outer circumferential surface of the first portion, the top land member is formed as a ring that has an annular piston-fit surface fitted to the outer circumferential surface of the first portion as an inner circumferential surface, and wherein the piston-fit surface is slanted to have its diameter decrease as it extends upwards and the diameter of the tapered surface decreases in the same direction and fits to the outer circumferential surface of the first portion in such a way that the top land member is supported by the outer circumferential surface of the first portion from the other end surface of the piston side.

7. A combination of piston unit parts, comprising: a top land member attached to a piston adapted to reciprocate in a cylinder; and one or more piston rings adapted to slide on an inner wall surface of the cylinder, the one or more piston rings being fitted in a first ring groove located closest to one end surface of the piston among one or more ring grooves formed on an outer circumference of the piston, wherein the piston includes a first portion including a piston end at a one end surface side and fitted with the top land member, the first portion having a smaller outer diameter than a second portion such that there is a step therebetween, the second portion being the other portion of the piston than the first portion, the top land member has a slanted piston-fit surface that attaches horizontally side-by-side to an equal length tapered surface of the first portion, the first ring groove is defined by the groove wall forming surface, the step surface, and the outer circumferential surface of the first portion, the top land member is formed as a ring that has an annular piston-fit surface fitted to the outer circumferential surface of the first portion as an inner circumferential surface, and wherein the piston-fit surface is slanted to have its diameter decrease as it extends upwards and the diameter of the tapered surface decreases in the same direction and fits to the outer circumferential surface of the first portion in such a way that the top land member is supported by the outer circumferential surface of the first portion from the other end surface of the piston side.
