United States Patent	12394914
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Huang; Chun-Lin

Antenna system

Abstract

An antenna system includes a signal feeding element, a first antenna element, a second antenna element, a first transmission line, and a second transmission line. The first antenna element is coupled to a first connection point. The second antenna element is coupled to a second connection point. The first transmission line is coupled between the signal feeding element and the first connection point. The second transmission line is coupled between the signal feeding element and the second connection point. The length of the second transmission line is substantially equal to that of the first transmission line. The first antenna element and the second antenna element substantially have opposite polarization directions. Therefore, the radiation pattern of the antenna system can provide a plurality of different gain peaks.

Inventors:	**Huang; Chun-Lin (Hsinchu, TW)**
Applicant:	**Wistron NeWeb Corp.** (Hsinchu, TW)
Family ID:	**1000008766162**
Assignee:	**WISTRON NEWEB CORP. (Hsinchu, TW)**
Appl. No.:	**18/350151**
Filed:	**July 11, 2023**

Publication Classification

Int. Cl.:	**H01Q21/24** (20060101); **H01Q1/38** (20060101)

U.S. Cl.:

CPC	**H01Q21/24** (20130101); **H01Q1/38** (20130101);

Field of Classification Search

CPC:	H01Q (1/38); H01Q (21/10); H01Q (21/24); H01Q (9/26)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7463209	12/2007	Tang et al.	N/A	N/A
9496932	12/2015	Prendergast	N/A	H04B 7/0691
9865920	12/2017	Kuo	N/A	H01Q 5/321
10840582	12/2019	Woo	N/A	H03H 7/38
2005/0266904	12/2004	Kitaji	455/101	H04B 7/0842
2014/0370804	12/2013	Dorning	455/41.1	H04B 5/263
2015/0130659	12/2014	Mori	342/175	G01S 13/88
2016/0036474	12/2015	Broyde	455/77	H01Q 21/0006
2016/0112991	12/2015	Chen	455/553.1	H04B 1/525
2017/0085005	12/2016	Aue	N/A	H04B 1/40
2019/0165447	12/2018	Furlan	N/A	H01Q 9/285
2019/0252785	12/2018	McMichael	N/A	H01Q 9/0428
2023/0369759	12/2022	Huang	N/A	H01Q 9/0407
2024/0291168	12/2023	Kim	N/A	H01Q 21/245

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101005156	12/2006	CN	N/A
200629654	12/2005	TW	N/A

Primary Examiner: Le; Thien M

Attorney, Agent or Firm: McClure, Qualey & Rodack, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS
(1) This application claims priority of Taiwan Patent Application No. 111127892 filed on Jul. 26, 2022, the entirety of which is incorporated by reference herein.
BACKGROUND OF THE INVENTION
Field of the Invention
(2) The disclosure generally relates to an antenna system, and more particularly, to an antenna system with a radiation pattern having multiple gain peaks.
Description of the Related Art

(3) With the advancements being made in mobile communication technology, mobile devices such as portable computers, mobile phones, multimedia players, and other hybrid functional portable electronic devices have become more common. To satisfy consumer demand, mobile devices can usually perform wireless communication functions. Some devices cover a large wireless communication area; these include mobile phones using 2G, 3G, and LTE (Long Term Evolution) systems and using frequency bands of 700 MHz, 850 MHz, 900 MHz, 1800 MHz, 1900 MHz, 2100 MHz, 2300 MHz, and 2500 MHz. Some devices cover a small wireless communication area; these include mobile phones using Wi-Fi systems and using frequency bands of 2.4 GHz, 5.2 GHz, and 5.8 GHz.

(4) Wireless access points are indispensable elements for mobile devices in a room to connect to the Internet at a high speed. However, since an indoor environment can experience serious signal reflection and multipath fading, wireless access points should process signals from a variety of transmission directions simultaneously. Accordingly, it has become a critical challenge for current designers to design a small-size antenna system with multiple radiation directions in the limited space of a wireless access point.

BRIEF SUMMARY OF THE INVENTION

(5) In an exemplary embodiment, the invention is directed to an antenna system that includes a signal feeding element, a first antenna element, a second antenna element, a first transmission line, and a second transmission line. The first antenna element is coupled to a first connection point. The second antenna element is coupled to a second connection point. The first transmission line is coupled between the signal feeding element and the first connection point. The second transmission line is coupled between the signal feeding element and the second connection point. The length of the second transmission line is substantially equal to the length of the first transmission line. The first antenna element and the second antenna element substantially have opposite polarization directions. Therefore, the radiation pattern of the antenna system can provide a plurality of different gain peaks.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The invention can be more fully understood by reading the subsequent detailed description and examples with references made to the accompanying drawings, wherein:

(2) FIG. **1** is a diagram of an antenna system according to an embodiment of the invention;

(3) FIG. **2** is a front view of an antenna system according to an embodiment of the invention;

(4) FIG. **3** is a radiation pattern of an antenna system according to an embodiment of the invention;

(5) FIG. **4** is a front view of an antenna system according to an embodiment of the invention;

(6) FIG. **5** is a radiation pattern of an antenna system according to an embodiment of the invention;

(7) FIG. **6** is a front view of an antenna system according to an embodiment of the invention;

(8) FIG. **7** is a radiation pattern of an antenna system according to an embodiment of the invention; and

(9) FIG. **8** is a front view of an antenna system according to another embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

(10) In order to illustrate the purposes, features and advantages of the invention, the embodiments and figures of the invention are shown in detail as follows.

(11) Certain terms are used throughout the description and following claims to refer to particular components. As one skilled in the art will appreciate, manufacturers may refer to a component by different names. This document does not intend to distinguish between components that differ in name but not function. In the following description and in the claims, the terms "include" and "comprise" are used in an open-ended fashion, and thus should be interpreted to mean "include, but

not limited to . . . ". The term "substantially" means the value is within an acceptable error range. One skilled in the art can solve the technical problem within a predetermined error range and achieve the proposed technical performance. Also, the term "couple" is intended to mean either an indirect or direct electrical connection. Accordingly, if one device is coupled to another device, that connection may be through a direct electrical connection, or through an indirect electrical connection via other devices and connections.

(12) The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(13) Furthermore, spatially relative terms, such as "beneath," "below," "lower," "above," "upper" and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(14) FIG. **1** is a diagram of an antenna system **100** according to an embodiment of the invention. For example, the antenna system **100** may be applied to a wireless access point, but it is not limited thereto. In the embodiment of FIG. **1**, the antenna system **100** at least includes a signal feeding element **110**, a first antenna element **121**, a second antenna element **122**, a first transmission line **130**, and a second transmission line **140**.

(15) The signal feeding element **110** may be implemented with one or more feeding metal elements. For example, the signal feeding element **110** may be coupled to an RF (Radio Frequency) module (not shown) for exciting the antenna system **100**. The first antenna element **121** is coupled to a first connection point FP**1**. The second antenna element **122** is coupled to a second connection point FP**2**. The shapes and types of the first antenna element **121** and the second antenna element **122** are not limited in the invention. For example, each of the first antenna element **121** and the second antenna element **122** may be a monopole antenna, a dipole antenna, a patch antenna, a loop antenna, a PIFA (Planar Inverted F Antenna), or a hybrid antenna.

(16) The shapes and types of the first transmission line **130** and the second transmission line **140** are not limited in the invention. The first transmission line **130** is coupled between the signal feeding element **110** and the first connection point FP**1**. The second transmission line **140** is coupled between the signal feeding element **110** and the second connection point FP**2**. It should be noted that the length L**2** of the second transmission line **140** is substantially equal to the length L**1** of the first transmission line **130**. In some embodiments, the first antenna element **121** and the second antenna element **122** substantially have opposite polarization directions. Thus, the radiation pattern of the antenna system **100** can provide a plurality of different gain peaks. With such a design, the antenna system **100** is configured to receive or transmit wireless signals in a variety of directions, thereby enhancing the whole communication quality of the relative device.

(17) The following embodiments will introduce different configurations and detailed structural features of the antenna system **100**. It should be understood that these figures and descriptions are merely exemplary, rather than limitations of the invention.

(18) FIG. **2** is a front view of an antenna system **200** according to an embodiment of the invention. FIG. **2** is similar to FIG. **1**. In the embodiment of FIG. **2**, the antenna system **200** includes a signal feeding element **210**, a first antenna element **221**, a second antenna element **222**, a first transmission line **230**, a second transmission line **240**, a first auxiliary antenna element **221**A, and a second auxiliary antenna element **222**A. In some embodiments, the antenna system **200** can cover an operational frequency band from 5150 MHz to 5850 MHz or from 5925 MHz to 7125 MHz. Therefore, the antenna system **200** can support the wideband operations of WLAN (Wireless Local Area Networks) 5 GHz or the next-generation Wi-Fi 6E.

(19) Each of the first antenna element **221**, the second antenna element **222**, the first auxiliary antenna element **221**A, and the second auxiliary antenna element **222**A may be implemented with a dipole antenna. The above antenna elements may be distributed over a top surface and a bottom surface of a dielectric substrate (in order to simplify the figure, the dielectric substrate is not displayed in FIG. **2**). Specifically, the first antenna element **221** and the first auxiliary antenna element **221**A are coupled to a first connection point FP**1**, so as to form a first antenna array. The second antenna element **222** and the second auxiliary antenna element **222**A are coupled to a second connection point FP**2**, so as to form a second antenna array. The first antenna array and the second antenna array may substantially have opposite polarization directions. For example, the polarization direction of the first antenna array may be parallel to −Y-axis, and the polarization direction of the second antenna array may be parallel to +Y-axis, but they are not limited thereto. In some embodiments, the first antenna element **221** and the second antenna element **222** are arranged in the same straight line, and the first auxiliary antenna element **221**A and the second auxiliary antenna element **222**A are arranged in another parallel straight line. It should be understood that the first auxiliary antenna element **221**A and the second auxiliary antenna element **222**A are used to improve the symmetry of the whole antenna system **200**, and they are optional components and may be omitted in other embodiments.

(20) The first transmission line **230** is coupled between the signal feeding element **110** and the first connection point FP**1**. The second transmission line **240** is coupled between the signal feeding element **110** and the second connection point FP**2**. The length of the second transmission line **240** may be substantially equal to the length of the first transmission line **230**. In some embodiments, the first transmission line **230** further includes a first widening portion **235**, and the second transmission line **240** further includes a second widening portion **245**, so as to fine-tune the impedance matching of the antenna system **200**. For example, each of the first widening portion **235** and the second widening portion **245** may substantially have a rectangular shape or a square shape. However, the invention is not limited thereto. In alternative embodiments, each of the first transmission line **230** and the second transmission line **240** may substantially have an equal-width straight-line shape.

(21) FIG. **3** is a radiation pattern of the antenna system **200** according to an embodiment of the invention (which may be measured on the YZ-plane). According to the measurement of FIG. **3**, the radiation pattern of the antenna system **200** can provide a first gain peak **291**, a second gain peak **292**, a third gain peak **293**, and a fourth gain peak **294**. A tilt angle θ**1** is formed between each of the above gain peaks and ±Z-axis. Generally, the antenna system **200** can provide a first main beam shifted upwardly and a second main beam shifted downwardly. The first main beam includes the first gain peak **291** and the third gain peak **293**. The second main beam includes the second gain peak **292** and the fourth gain peak **294**. For example, if the antenna system **200** is arranged horizontally along the XZ-plane on the middle floor of an apartment, the first gain peak **291** and the third gain peak **293** of the first main beam can be used to support high-floor communication, and the second gain peak **292** and the fourth gain peak **294** of the second main beam can be used to support low-floor communication, but they are not limited thereto. In some embodiments, the element sizes of the antenna system **200** will be described as follows. In the antenna system **200**, the center-to-center distance D**1** between the first antenna element **221** and the second antenna

element **222** (or the center-to-center distance D**1** between the first auxiliary antenna element **221**A and the second auxiliary antenna element **222**A) may be substantially equal to 0.64 free-space wavelength (0.64λ) of the operational frequency band of the antenna system **200**. The tilt angle θ**1** may be about 30 degrees. The above ranges of element sizes are calculated and obtained according to many experiment results, and they help to optimize the operational bandwidth and the impedance matching of the antenna system **200**. Other features of the antenna system **200** of FIG. **2** are similar to those of the antenna system **100** of FIG. **1**. Accordingly, the two embodiments can achieve similar levels of performance.

(22) FIG. **4** is a front view of an antenna system **400** according to an embodiment of the invention. FIG. **4** is similar to FIG. **2**. In the embodiment of FIG. **4**, besides the aforementioned elements, the antenna system **400** further includes a third antenna element **223**, a fourth antenna element **224**, a third transmission line **450**, a fourth transmission line **460**, a third auxiliary antenna element **223**A, and a fourth auxiliary antenna element **224**A. It should be understood that the shapes of the first transmission line **230** and the second transmission line **240** may be slightly changed to fine-tune the impedance matching of the antenna system **400**. In some embodiments, the antenna system **400** can cover an operational frequency band from 5150 MHz to 5850 MHz or from 5925 MHz to 7125 MHz.

(23) Each of the third antenna element **223**, the fourth antenna element **224**, the third auxiliary antenna element **223**A, and the fourth auxiliary antenna element **224**A may be implemented with a dipole antenna. Specifically, the third antenna element **223** and the third auxiliary antenna element **223**A are coupled to a third connection point FP**3**, so as to form a third antenna array. The fourth antenna element **224** and the fourth auxiliary antenna element **224**A are coupled to a fourth connection point FP**4**, so as to form a fourth antenna array. The third antenna array and the fourth antenna array may substantially have opposite polarization directions. For example, the polarization direction of the third antenna array may be parallel to −Y-axis, and the polarization direction of the fourth antenna array may be parallel to +Y-axis, but they are not limited thereto. In some embodiments, the first antenna element **221**, the second antenna element **222**, the third antenna element **223**, and the fourth antenna element **224** are arranged in the same straight line. The first auxiliary antenna element **221**A, the second auxiliary antenna element **222**A, the third auxiliary antenna element **223**A, and the fourth auxiliary antenna element **224**A are arranged in another parallel straight line.

(24) The third transmission line **450** is coupled between the first connection point FP**1** and the third connection point FP**3**. The fourth transmission line **460** is coupled between the second connection point FP**2** and the fourth connection point FP**4**. The length L**4** of the fourth transmission line **460** may be substantially equal to the length L**3** of the third transmission line **450**. In some embodiments, each of the third transmission line **450** and the fourth transmission line **460** substantially has a variable-width straight-line shape, so as to fine-tune the impedance matching of the antenna system **400**. However, the invention is not limited thereto. In alternative embodiments, each of the third transmission line **450** and the fourth transmission line **460** may substantially have an equal-width straight-line shape.

(25) FIG. **5** is a radiation pattern of the antenna system **400** according to an embodiment of the invention (which may be measured on the YZ-plane). According to the measurement of FIG. **5**, the radiation pattern of the antenna system **400** can provide a first gain peak **491**, a second gain peak **492**, a third gain peak **493**, and a fourth gain peak **494**. A tilt angle θ**2** is formed between each of the above gain peaks and ±Z-axis. Generally, the antenna system **400** can provide a first main beam shifted upwardly and a second main beam shifted downwardly. The first main beam includes the first gain peak **491** and the third gain peak **493**. The second main beam includes the second gain peak **492** and the fourth gain peak **494**. In some embodiments, the element sizes of the antenna system **400** will be described as follows. In the antenna system **400**, the center-to-center distance D**2** between the first antenna element **221** and the second antenna element **222** may be substantially

equal to 0.81 free-space wavelength (0.81λ) of the operational frequency band of the antenna system **400**. The length L**3** of the third transmission line **450** may be substantially equal to 1 effective wavelength (1 λg) of the operational frequency band of the antenna system **400**. The length L**4** of the fourth transmission line **460** may be substantially equal to 1 effective wavelength (1 λg) of the operational frequency band of the antenna system **400**. The tilt angle θ**2** may be about 15 degrees. In other words, after more antenna elements are used, the radiation gain of the antenna system **400** becomes higher, and the tilt angle θ**2** of its radiation pattern becomes smaller. It should be understood that the term "wavelength (λ)" over the disclosure means the wavelength in free space. If a dielectric material is used (e.g., a dielectric substrate), it may be modified to "effective wavelength (λg)" according to an effective dielectric constant between the dielectric material and the free space. Conversely, if no dielectric material is used, the effective wavelength (λg) may be the same as the free-space wavelength (λ). The above ranges of element sizes are calculated and obtained according to many experiment results, and they help to optimize the operational bandwidth and the impedance matching of the antenna system **400**. Other features of the antenna system **400** of FIG. **4** are similar to those of the antenna system **200** of FIG. **2**. Accordingly, the two embodiments can achieve similar levels of performance.

(26) FIG. **6** is a front view of an antenna system **600** according to an embodiment of the invention. FIG. **6** is similar to FIG. **4**. In the embodiment of FIG. **6**, besides the aforementioned elements, the antenna system **600** further includes a fifth antenna element **225**, a sixth antenna element **226**, a fifth transmission line **670**, a sixth transmission line **680**, a fifth auxiliary antenna element **225**A, and a sixth auxiliary antenna element **226**A. It should be understood that the shapes of the first transmission line **230**, the second transmission line **240**, the third transmission line **450**, and the fourth transmission line **460** may be slightly changed to fine-tune the impedance matching of the antenna system **600**. In some embodiments, the antenna system **600** can cover an operational frequency band from 5150 MHz to 5850 MHz or from 5925 MHz to 7125 MHz.

(27) Each of the fifth antenna element **225**, the sixth antenna element **226**, the fifth auxiliary antenna element **225**A, and the sixth auxiliary antenna element **226**A may be implemented with a dipole antenna. Specifically, the fifth antenna element **225** and the fifth auxiliary antenna element **225**A are coupled to a fifth connection point FP**5**, so as to form a fifth antenna array. The sixth antenna element **226** and the sixth auxiliary antenna element **226**A are coupled to a sixth connection point FP**6**, so as to form a sixth antenna array. The fifth antenna array and the sixth antenna array may substantially have opposite polarization directions. For example, the polarization direction of the fifth antenna array may be parallel to −Y-axis, and the polarization direction of the sixth antenna array may be parallel to +Y-axis, but they are not limited thereto. In some embodiments, the first antenna element **221**, the second antenna element **222**, the third antenna element **223**, the fourth antenna element **224**, the fifth antenna element **225**, and the sixth antenna element **226** are arranged in the same straight line. The first auxiliary antenna element **221**A, the second auxiliary antenna element **222**A, the third auxiliary antenna element **223**A, the fourth auxiliary antenna element **224**A, the fifth auxiliary antenna element **225**A, and the sixth auxiliary antenna element **226**A are arranged in another parallel straight line.

(28) The fifth transmission line **670** is coupled between the third connection point FP**3** and the fifth connection point FP**5**. The sixth transmission line **680** is coupled between the fourth connection point FP**4** and the sixth connection point FP**6**. The length L**6** of the sixth transmission line **680** may be substantially equal to the length L**5** of the fifth transmission line **670**. In some embodiments, each of the fifth transmission line **670** and the sixth transmission line **680** substantially has a variable-width straight-line shape, so as to fine-tune the impedance matching of the antenna system **600**. However, the invention is not limited thereto. In alternative embodiments, each of the fifth transmission line **670** and the sixth transmission line **680** may substantially have an equal-width straight-line shape.

(29) FIG. **7** is a radiation pattern of the antenna system **600** according to an embodiment of the

invention (which may be measured on the YZ-plane). According to the measurement of FIG. **7**, the radiation pattern of the antenna system **600** can provide a first gain peak **691**, a second gain peak **692**, a third gain peak **693**, and a fourth gain peak **694**. A tilt angle θ**3** is formed between each of the above gain peaks and ±Z-axis. Generally, the antenna system **600** can provide a first main beam shifted upwardly and a second main beam shifted downwardly. The first main beam includes the first gain peak **691** and the third gain peak **693**. The second main beam includes the second gain peak **692** and the fourth gain peak **694**. In some embodiments, the element sizes of the antenna system **600** will be described as follows. In the antenna system **600**, the center-to-center distance D**3** between the first antenna element **221** and the second antenna element **222** may be substantially equal to 0.998 free-space wavelength (0.998λ) of the operational frequency band of the antenna system **600**. The length L**5** of the fifth transmission line **670** may be substantially equal to 1 effective wavelength (1 λg) of the operational frequency band of the antenna system **600**. The length L**6** of the sixth transmission line **680** may be substantially equal to 1 effective wavelength (1 λg) of the operational frequency band of the antenna system **600**. The tilt angle θ**3** may be about 10 degrees. In other words, after more antenna elements are used, the radiation gain of the antenna system **600** further becomes higher, and the tilt angle θ**3** of its radiation pattern further becomes smaller. The above ranges of element sizes are calculated and obtained according to many experiment results, and they help to optimize the operational bandwidth and the impedance matching of the antenna system **600**. Other features of the antenna system **600** of FIG. **6** are similar to those of the antenna system **400** of FIG. **4**. Accordingly, the two embodiments can achieve similar levels of performance.

(30) Generally, the tilt angle of each gain peak of the radiation pattern of the aforementioned antenna system can be calculated using the following equation (1):

(31) $\quad = \dfrac{D}{N \text{ .Math. } } \text{ .Math. } \sin^{-1}(\dfrac{}{2 \text{ .Math. } D}) \quad (1)$

where "θ" represents the tilt angle, "D" represents the center-to-center distance between the first antenna element and the second antenna element, "λ" represents the free-space wavelength of the operational frequency band of the antenna system, and "N" represents a half of the total number of antenna elements (excluding auxiliary antenna element) (e.g., N may be equal to 1 in the embodiments of FIG. **1** and FIG. **2**, N may be equal to 2 in the embodiment of FIG. **4**, and N may be equal to 3 in the embodiment of FIG. **6**).

(32) The above equation (1) is designed on the condition that the center-to-center distance (D) is shorter than the free-space wavelength (λ) (i.e., D<λ). On the contrary, if the center-to-center distance (D) is longer than the free-space wavelength (λ) (i.e., D>λ), the tilt angle of each gain peak of the radiation pattern of the aforementioned antenna system can be calculated using the following equation (2):

(33) $\quad = \dfrac{}{N \text{ .Math. } D} \text{ .Math. } \sin^{-1}(\dfrac{}{2 \text{ .Math. } D}) \quad (2)$

(34) FIG. **8** is a front view of an antenna system **800** according to another embodiment of the invention. FIG. **8** is similar to FIG. **1**. In the embodiment of FIG. **8**, the antenna system **800** includes a signal feeding element **110**, a first antenna element **821**, a second antenna element **822**, a first transmission line **830**, a second transmission line **840**, and a ground plane **850**. Each of the first antenna element **821** and the second antenna element **822** may be a patch antenna. The ground plane **850** is adjacent to the first antenna element **821** and the second antenna element **822**. Similarly, the first antenna element **821** and the second antenna element **822** may substantially have opposite polarization directions, and the length of the second transmission line **840** may be substantially equal to the length of the first transmission line **830**. It should be noted that the term "adjacent" or "close" over the disclosure means that the distance (spacing) between two corresponding elements is smaller than a predetermined distance (e.g., 10 mm or shorter), but often does not mean that the two corresponding elements directly touch each other (i.e., the aforementioned distance/spacing therebetween is reduced to 0). In the antenna system **800**, the

center-to-center distance D**4** between the first antenna element **821** and the second antenna element **822** can be applied to the above equation (1) or (2), so as to calculate and obtain the tilt angle of the corresponding gain peak. Other features of the antenna system **800** of FIG. **8** are similar to those of the antenna system **100** of FIG. **1**. Accordingly, the two embodiments can achieve similar levels of performance.

(35) The invention proposes a novel antenna system. In comparison to the conventional design, the invention has at least the advantages of radiation pattern with multiple gain peaks, small size, and low manufacturing cost. Therefore, the invention is suitable for application in a variety of communication devices.

(36) Note that the above element sizes, element shapes, and frequency ranges are not limitations of the invention. An antenna designer can fine-tune these settings or values according to different requirements. It should be understood that the antenna system of the invention is not limited to the configurations of FIGS. **1**-**8**. The invention may merely include any one or more features of any one or more embodiments of FIGS. **1**-**8**. In other words, not all of the features displayed in the figures should be implemented in the antenna system of the invention.

(37) Use of ordinal terms such as "first", "second", "third", etc., in the claims to modify a claim element does not by itself connote any priority, precedence, or order of one claim element over another or the temporal order in which acts of a method are performed, but are used merely as labels to distinguish one claim element having a certain name from another element having the same name (but for use of the ordinal term) to distinguish the claim elements.

(38) While the invention has been described by way of example and in terms of the preferred embodiments, it should be understood that the invention is not limited to the disclosed embodiments. On the contrary, it is intended to cover various modifications and similar arrangements (as would be apparent to those skilled in the art). Therefore, the scope of the appended claims should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements.

Claims

1. An antenna system, comprising: a signal feeding element; a first antenna element, coupled to a first connection point; a second antenna element, coupled to a second connection point; a first transmission line, coupled between the signal feeding element and the first connection point; and a second transmission line, coupled between the signal feeding element and the second connection point, wherein a length of the second transmission line is substantially equal to that of the first transmission line; wherein the first antenna element and the second antenna element substantially have opposite polarization directions, such that a radiation pattern of the antenna system provides a plurality of different gain peaks; wherein the antenna system covers an operational frequency band; wherein a center-to-center distance between the first antenna element and the second antenna element is substantially equal to 0.64, 0.81 or 0.998 free-space wavelength of the operational frequency band.

2. The antenna system as claimed in claim 1, wherein the operational frequency band is from 5150 MHz to 5850 MHz or from 5925 MHz to 7125 MHz.

3. The antenna system as claimed in claim 2, further comprising: a third antenna element, coupled to a third connection point; a fourth antenna element, coupled to a fourth connection point; a third transmission line, coupled between the first connection point and the third connection point; and a fourth transmission line, coupled between the second connection point and the fourth connection point.

4. The antenna system as claimed in claim 3, wherein a length of each of the third transmission line and the fourth transmission line is substantially equal to 1 effective wavelength of the operational frequency band.

5. The antenna system as claimed in claim 3, further comprising: a third auxiliary antenna element, coupled to the third connection point; and a fourth auxiliary antenna element, coupled to the fourth connection point.

6. The antenna system as claimed in claim 3, further comprising: a fifth antenna element, coupled to a fifth connection point; a sixth antenna element, coupled to a sixth connection point; a fifth transmission line, coupled between the third connection point and the fifth connection point; and a sixth transmission line, coupled between the fourth connection point and the sixth connection point.

7. The antenna system as claimed in claim 6, wherein a length of each of the fifth transmission line and the sixth transmission line is substantially equal to 1 effective wavelength of the operational frequency band.

8. The antenna system as claimed in claim 6, further comprising: a fifth auxiliary antenna element, coupled to the fifth connection point; and a sixth auxiliary antenna element, coupled to the sixth connection point.

9. The antenna system as claimed in claim 1, wherein each of the first antenna element and the second antenna element is a dipole antenna.

10. The antenna system as claimed in claim 1, further comprising: a first auxiliary antenna element, coupled to the first connection point; and a second auxiliary antenna element, coupled to the second connection point.

11. The antenna system as claimed in claim 1, wherein each of the first antenna element and the second antenna element is a patch antenna.

12. The antenna system as claimed in claim 11, further comprising: a ground plane, disposed adjacent to the first antenna element and the second antenna element.

13. An antenna system, comprising: a signal feeding element; a first antenna element, coupled to a first connection point; a second antenna element, coupled to a second connection point; a first transmission line, coupled between the signal feeding element and the first connection point; and a second transmission line, coupled between the signal feeding element and the second connection point, wherein a length of the second transmission line is substantially equal to that of the first transmission line; wherein the first antenna element and the second antenna element substantially have opposite polarization directions, such that a radiation pattern of the antenna system provides a plurality of different gain peaks; wherein the antenna system covers an operational frequency band; wherein a tilt angle of each of the gain peaks is calculated using the following equation:

$$= \frac{D}{N \cdot \text{Math.}} \cdot \text{Math.} \sin^{-1}\left(\frac{}{2 \cdot \text{Math.} D}\right)$$ wherein "θ" represents the tile angle, "D" represents the center-to-center distance between the first antenna element and the second antenna element, "λ" represents a free-space wavelength of the operational frequency band, and "N" represents a half of a total number of antenna elements; wherein the center-to-center distance is shorter than the free-space wavelength.

14. An antenna system, comprising: a signal feeding element; a first antenna element, coupled to a first connection point; a second antenna element, coupled to a second connection point; a first transmission line, coupled between the signal feeding element and the first connection point; and a second transmission line, coupled between the signal feeding element and the second connection point, wherein a length of the second transmission line is substantially equal to that of the first transmission line; wherein the first antenna element and the second antenna element substantially have opposite polarization directions, such that a radiation pattern of the antenna system provides a plurality of different gain peaks; wherein the antenna system covers an operational frequency band; wherein a tilt angle of each of the gain peaks is calculated using the following equation:

$$= \frac{}{N \cdot \text{Math.} D} \cdot \text{Math.} \sin^{-1}\left(\frac{}{2 \cdot \text{Math.} D}\right)$$ wherein "θ" represents the tilt angle, "D" represents a center-to-center distance between the first antenna element and the second antenna element, "λ" represents a free-space wavelength of the operational frequency band, and "N" represents a half of a total

number of antenna elements; wherein the center-to-center distance is longer than the free-space wavelength.