

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250256919

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Hund, JR.; Henry Michael

---

### GRABBER FOR A FRONT LOADER REFUSE VEHICLE

---

#### Abstract

A grabber assembly has a beam assembly with a bracket. A grabber gear assembly is coupled with the bracket. The grabber gear assembly has a pair of gear mechanisms coupled with the bracket. Each gear mechanism has a shaft and a pair of thrust bearings, one at each end of the shaft. A grabber arm mounting pad is coupled with each shaft. A gear section is coupled with each shaft. The gear sections of each shaft mesh with one another to drive the grabber arm mounting pads. An actuating driver is coupled with one of the shafts to drive the grabber gear assembly and move the arms between an open and grasping position.

---

**Inventors:** Hund, JR.; Henry Michael (Cedar Bluff, AL)

**Applicant:** The Heil Co. (Chattanooga, TN)

**Family ID:** 59009550

**Appl. No.:** 19/192042

**Filed:** April 28, 2025

#### Related U.S. Application Data

parent US continuation 18430969 20240202 parent-grant-document US 12304731 child US 19192042

parent US continuation 17673542 20220216 parent-grant-document US 11945647 child US 18430969

parent US continuation 17035204 20200928 parent-grant-document US 11286110 child US 17673542

parent US continuation 16272476 20190211 parent-grant-document US 10787314 child US 17035204

parent US continuation 15606180 20170526 parent-grant-document US 10221012 child US 16272476

us-provisional-application US 62345177 20160603

---

## Publication Classification

**Int. Cl.:** B65F3/04 (20060101); B65F3/02 (20060101)

**U.S. Cl.:**

**CPC** B65F3/041 (20130101); B65F3/04 (20130101); B65F2003/023 (20130101); B65F2003/0276 (20130101); B65F2003/0279 (20130101); B65F2003/0283 (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/430,969, filed on Feb. 2, 2024, which is a continuation of U.S. application Ser. No. 17/673,542, filed on Feb. 16, 2022, now U.S. Pat. No. 11,945,647, which is a continuation of U.S. application Ser. No. 17/035,204, filed on Sep. 28, 2020, now U.S. Pat. No. 11,286,110, which is a continuation of U.S. application Ser. No. 16/272,476, filed on Feb. 11, 2019, now U.S. Pat. No. 10,787,314, which is a continuation of U.S. application Ser. No. 15/606,180, filed on May 26, 2017, now U.S. Pat. No. 10,221,012, which claims the benefit of U.S. Provisional Application No. 62/345,177, filed on Jun. 3, 2016. The entire disclosure of the above applications are incorporated herein by reference in their entirety.

### FIELD

[0002] The present disclosure relates to refuse vehicles and, more particularly, to a grabber arm for dumping refuse carts into a container.

### BACKGROUND

[0003] Various grabber types exist in the field. These grabbers appear to work satisfactory for their intended purposes. However, designers strive to improve the art. One disadvantage of existing grabbers is that they are unable to maneuver between refuse carts that are closely spaced to one another for pick up. When a consumer takes refuse carts to the curb, most will align and position their carts close together. This makes it difficult for an automatic grabber to pick up the individual closely spaced refuse carts. Accordingly, the operator must exit the vehicle to space the refuse carts apart from one another for pick up. Thus, the refuse carts may be individually picked up by the grabber and dumped into the vehicle container. The collection route down time when an operator is required to leave the vehicle is expensive to refuse collection companies.

[0004] Accordingly, the present disclosure provides the art with a grabber that enables pick up and dumping of closely spaced refuse carts with minimal exiting of the vehicle by the operator. The present disclosure provides a grabber assembly that is gear operated. The present disclosure provides positioning of the grabber arms close to one another.

### SUMMARY

[0005] According to a first aspect of the disclosure, a grabber assembly comprises a beam assembly with a bracket. A grabber gear assembly is coupled with the bracket. The gear assembly comprises a pair of gear mechanisms coupled with the bracket. Each gear mechanism includes a pair of spherical thrust bearings with a shaft having two ends. One of the pair of thrust bearings is positioned at each end on the shaft. A grabber arm mounting pad is coupled with the shaft. A gear section is coupled with the shaft. The gear section of each shaft meshes with the other to drive the grabber arm mounting pads. An actuating driver is coupled with one of the shafts to drive the grabber gear assembly. One of the pair of thrust bearings is secured with the beam assembly bracket. A pair of grabber arms is coupled with each one of the grabber arm mounting pads. The pair of grabber arms is manufactured from spring steel. The actuating driver is a cushioned

cylinder. A bracket extends from one of the shafts to couple with the actuating driver. The mounting pads include a bracket to secure with the shaft. The gear section may be coupled with the mounting pad bracket.

[0006] According to a second aspect of the disclosure, a refuse container and grabber arm comprises a container to receive refuse and a grabber arm to dump a refuse cart into the container. The grabber arm comprises a beam assembly with a bracket. A grabber gear assembly is coupled with the bracket. The gear assembly comprises a pair of gear mechanisms coupled with the bracket. Each gear mechanism includes a pair of spherical thrust bearings with the shaft having two ends. One of the pair of thrust bearings is positioned at each end on the shaft. A grabber arm mounting pad is coupled with the shaft. A gear section is coupled with the shaft. The gear section of each shaft meshes with the other to drive the grabber arm mounting pads. An actuating driver is coupled with one of the shafts to drive the grabber gear assembly. One of the pair of thrust bearings is secured with the beam assembly bracket. A pair of grabber arms is coupled with each one of the pair of grabber arm mounting pads. The pair of grabber arms is manufactured from spring steel. The actuating driver is a cushioned cylinder. A bracket extends from one of the shafts to couple with the actuating driver. The mounting pads include a bracket to secure with the shaft. The gear section may be coupled with the mounting pad bracket.

[0007] Further areas of applicability will become apparent from the description provided herein. The description and specific examples in this summary are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

## DRAWINGS

[0008] The drawings described herein are for illustrative purposes only of selected embodiments and not all possible implementations, and are not intended to limit the scope of the present disclosure.

[0009] FIG. 1 is a perspective view of a truck with an intermediate can and a grabber arm assembly.

[0010] FIG. 2 is a perspective view of the grabber arm assembly.

[0011] FIG. 3 is a perspective view of the grabber arm grasping a refuse cart.

[0012] FIG. 4 is a perspective view of the grabber gear assembly with the plate removed.

[0013] FIG. 5 is a front elevational view of the grabber gear assembly with the grabber arms, plate, and top bracket removed.

[0014] FIG. 6 is a rear elevational cross section view through FIG. 5 but including the top bracket.

[0015] FIG. 7 is a top elevational view of the grabber gear assembly with the beam, grabber arms, plate, and top bracket removed.

[0016] FIG. 8 is a perspective view of the grabber gear assembly with the grabber arms, plate, and top bracket removed.

---

## Description

### DETAILED DESCRIPTION

[0017] Example embodiments will now be described more fully with reference to the accompanying drawings.

[0018] Turning to the figures, in FIG. 1 a refuse collection vehicle is illustrated and designated with the reference numeral 10. The vehicle 10 includes a cab 12 with a chassis 14 that includes a primary collecting container 16. Also, a drivetrain, including wheels 18, moves the vehicle in a conventional manner. The vehicle 10 includes front loading arms 20 that include an intermediate can 22. The intermediate can 22 includes a grabber arm assembly 24.

[0019] Turning to FIG. 2, the grabber arm assembly 24 is illustrated. The grabber arm assembly 24 includes a beam assembly 26. The beam assembly 26 has an overall L-shape with a cylindrical bore

**28** to receive a pivot pin. The cylindrical bore **28** enables the beam **26**, as well as the grabber arm assembly **24**, to pivot with respect to the intermediate can **22**. The beam assembly **26** includes a bracket assembly **30** on one of the L-shaped legs **32**. The bracket assembly **30** includes a grabber gear assembly **34** that moves the grabber arms **36, 38** between the grasping and release positions. The grabber arms **36, 38** include belt members **40**. The belt members **40** contact the refuse carts **42** when grasping the refuse carts, as illustrated in FIG. 3. The arms **36, 38** are manufactured from a spring steel material. Also, a stop **44** is positioned on the bracket assembly **30** to keep gear assembly **34** from coming into contact with refuse carts **42**.

[0020] Turning to FIGS. 4 through 8, a better understanding of the grabber gear assembly **34** will be obtained.

[0021] The grabber gear assembly **34** includes a pair of gear mechanisms **50, 52**. The gear mechanisms **50, 52** are substantially identical and the explanation of one will apply to both. The gear mechanisms **50, 52** includes a pair of spherical thrust bearings **54, 56**. The first thrust bearing **54** is secured to the first bracket plate **58**. The second thrust bearing **56** is secured to the second bracket plate **60**. A shaft or pivot pin **62** is positioned between the thrust bearings **54, 56**. The shaft ends are connected with the thrust bearings **54, 56**. One of the shafts **62** includes a driver mounting bracket **64**.

[0022] The spherical thrust bearings **54, 56** can be the same or different. In the current illustration, they are the same. The thrust bearings include a housing **66**, outer ring **68** and inner ring member **70**. A fastener **72** abuts washer **74** which secures the ring member **70** on the shaft **62**. The spherical thrust bearings **54, 56** operates in a conventional manner. The housings **66** are secured with the bracket plates **58, 60** to secure the gear mechanisms **50, 52** with the bracket assembly **30**.

[0023] Each shaft **62** includes an arm pad mounting bracket **76, 78**. Each arm pad mounting bracket **76, 78** includes a mounting pad **80**. Shaft supports are coupled with the shaft **62** to secure the arm pad mounting brackets **76, 78** onto the shaft **62**.

[0024] Gear sections **86, 88** are mounted on the shafts **62**. The gear sections **86, 88** mesh with one another to provide rotational movement of the arm pad mounting supports **76, 78** which, in turn, move the arm pad mounting supports **76, 78** as well as the grabber arms **36, 38** between an opened and a grasping position.

[0025] An actuating driver **90** is coupled with the bracket **64** via a pin **92**. The actuating driver **90** can be a pneumatic or hydraulic cylinder or the like. The cylinder is a cushioned cylinder. The cushion cylinder enables a smooth operation of the cylinder to enable the opening and grasping of the grabber arms **36, 38**. The cylinder is retracted to close or grasp and extends to open. Thus, with the use of downstream hydraulics, any valve leakage or cylinder leakage of the pistons will cause the grabber to move the arms **36, 38** to their opened position.

[0026] The gear sections **86, 88** are used to time the grabber arms **36, 38** to enable the gear mechanisms **50, 52** to be positioned closer together by a factor of two compared with existing grabbers. This enables the beam assembly **26** to be reshaped and enable the grabber arms **36, 38** to be inserted between closely positioned refuse carts as illustrated in FIG. 3. Also, the grabber arms **36, 38**, due to the spring steel, can deflect. This enables the grabber belts **40** to automatically adjust for a variety of to be picked up refuse carts. The belts **40** tensioned from the grabber arms **36, 38** are sized to create a uniform load on the refuse carts. This provides a better grip on the cart. Also, rotation of the grabber gear assembly **34** is driven in an equal rotation so that both sides of a refuse cart will experience the same amount of force. The cushioned cylinder **90**, while enabling smooth operation, also reduces impact.

[0027] The self-aligning spherical thrust bearings provide a larger contact area as the arm moves from a pick up to a dump position. This permits angular misalignment and can withstand radial or heavy axial loads. This increases durability under rotational impact conditions such as lifting and dumping a refuse cart. The grabber arm may also be utilized on the chassis and dump directly into the primary container.

[0028] The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

## Claims

1. A grabber assembly comprising: a beam assembly; a bracket on the beam assembly; a grabber gear assembly coupled with the bracket; the grabber gear assembly comprising a pair of gear mechanisms coupled with the bracket, each gear mechanism including a pair of thrust bearings and a shaft with two ends, the shaft includes one of the pair of thrust bearings at each of its two ends; a grabber arm mounting pad coupled with the shaft; a gear section is coupled with each shaft, the gear sections of each shaft mesh with each other to drive the grabber arm mounting pads; and an actuating driver is coupled with one of the shafts to drive the grabber gear assembly.
2. The grabber assembly of claim 1, wherein one of the pair of thrust bearings is secured with the bracket on the beam.
3. The grabber assembly of claim 1, further comprising a pair of grabber arms, each grabber arm coupled with one of the grabber arm mounting pads.
4. The grabber assembly of claim 3, wherein the pair of grabber arms are manufactured from spring steel.
5. The grabber assembly of claim 1, wherein the actuating driver is a cushioned cylinder.
6. The grabber assembly of claim 1, wherein a bracket extends from one of the shafts to couple with the actuating driver.
7. The grabber assembly of claim 1, wherein the mounting pad includes a bracket to secure with the shaft and the gear section is coupled with the mounting pad bracket.
8. The grabber assembly of claim 1, wherein the thrust bearings are spherical thrust bearings.
9. A refuse container and grabber arm comprising: a container for receiving refuse; a grabber arm for dumping a refuse cart into the container, the grabber arm comprising: a beam assembly coupled with the container; a bracket on the beam assembly; a grabber gear assembly coupled with the bracket; the grabber gear assembly comprising a pair of gear mechanisms coupled with the bracket, each gear mechanism including a pair of thrust bearings and a shaft having two ends, the shaft includes one of the pair of thrust bearings at each of its ends; a grabber arm mounting pad is coupled with the shaft; a pair of grabber arms, each grabber arm coupled with one of the grabber arm mounting pads; a gear section is coupled with each shaft, the gear sections of each shaft mesh with one another to drive the grabber arm mounting pads; and an actuating driver is coupled with one of the shafts to drive the grabber gear assembly.
10. The refuse container and grabber arm of claim 9, wherein one of the pair of thrust bearings is secured with the bracket on the beam.
11. The refuse container and grabber arm of claim 9, wherein the pair of grabber arms is manufactured from spring steel.
12. The refuse container and grabber arm of claim 9, wherein the actuating driver is a cushioned cylinder.
13. The refuse container and grabber arm of claim 9, wherein a bracket extends from one of the shafts to couple with the actuating driver.
14. The refuse container and grabber arm of claim 9, wherein the mounting pad includes a bracket to secure with the shaft and the gear section is coupled with the mounting pad bracket.
15. The refuse container and grabber arm of claim 9, wherein the thrust bearings are spherical

thrust bearings.

**16.** A refuse vehicle comprising: a chassis with a cab and a primary collecting container and a drive train for moving the refuse vehicle; front loading arms on the refuse vehicle; a container for receiving refuse, the container coupled with the front loading arms; a grabber arm for dumping a refuse cart into the container, the grabber arm comprising: a beam assembly coupled with the container; a bracket on the beam assembly; a grabber gear assembly coupled with the bracket; the grabber gear assembly comprising a pair of gear mechanisms coupled with the bracket, each gear mechanism including a pair of thrust bearings and a shaft having two ends, the shaft includes one of the pair of thrust bearings at each of its ends; a grabber arm mounting pad is coupled with the shaft; a pair of grabber arms, each grabber arm coupled with one of the grabber arm mounting pads; a gear section is coupled with each shaft, the gear sections of each shaft mesh with one another to drive the grabber arm mounting pads; and an actuating driver is coupled with one of the shafts to drive the grabber gear assembly.

**17.** The refuse vehicle of claim 16, wherein one of the pair of thrust bearings is secured with the bracket on the beam.

**18.** The refuse vehicle of claim 16, wherein the pair of grabber arms is manufactured from spring steel.

**19.** The refuse vehicle of claim 16, wherein the actuating driver is a cushioned cylinder.

**20.** The refuse vehicle of claim 16, wherein a bracket extends from one of the shafts to couple with the actuating driver.

---