



US012389965B2

(12) **United States Patent**
Rodgers et al.

(10) **Patent No.:** **US 12,389,965 B2**

(45) **Date of Patent:** ***Aug. 19, 2025**

(54) **BELT LOOP CONNECTOR**

(71) Applicant: **SAMTECH, LLC**, Los Angeles, CA
(US)

(72) Inventors: **Frances M. Rodgers**, Ashland, OR
(US); **Tamra B. Perry**, Central Point,
OR (US)

(73) Assignee: **SAMTECH, LLC**, Los Angeles, CA
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **18/782,738**

(22) Filed: **Jul. 24, 2024**

(65) **Prior Publication Data**

US 2024/0373963 A1 Nov. 14, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/815,162, filed on
Jul. 26, 2022, now Pat. No. 12,070,091.

(51) **Int. Cl.**
A41F 9/00 (2006.01)
A41F 17/00 (2006.01)
A41F 17/02 (2006.01)
A41F 17/04 (2006.01)

(52) **U.S. Cl.**
CPC **A41F 9/007** (2013.01); **A41F 17/00**
(2013.01); **A41F 17/02** (2013.01); **A41F 17/04**
(2013.01)

(58) **Field of Classification Search**

CPC **A41F 9/007**; **A41F 17/00**; **A41F 17/02**;
A41F 17/04; **A41F 5/00**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

533,373 A	1/1895	Presby
695,629 A	3/1902	Shipley
932,640 A	8/1909	Pfiffner
1,897,261 A	2/1933	Killory
1,958,643 A	5/1934	Silverman
1,986,519 A	1/1935	Murray
1,998,085 A	4/1935	Wilcox

(Continued)

OTHER PUBLICATIONS

U.S. Non-Final Office Action for U.S. Appl. No. 17/815,162 mailed
Mar. 13, 2024.

(Continued)


Primary Examiner — Khaled Annis

(74) *Attorney, Agent, or Firm* — Sherman IP LLP;
Kenneth L. Sherman; Hemavathy Perumal

(57) **ABSTRACT**

One embodiment provides a garment system comprising an upper body garment comprising an interior surface and a first set of connectors positioned on the interior surface. The system further comprises a lower body garment comprising a second set of connectors positioned on a surface of the lower body garment. The first set of connectors and the second set of connectors are vertically aligned when a wearer wears the upper body garment and the lower body garment at the same time, and each connector of the second set of connectors is configured to releasably engage and interconnect with a connector of the first set of connectors to attach the upper body garment to the lower body garment.

20 Claims, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,104,487	A	1/1938	Kessler
2,274,382	A	2/1942	Richman
3,418,659	A	12/1968	Brown
3,789,431	A	2/1974	Rand
4,932,079	A	6/1990	Bridgewater
4,947,489	A	8/1990	Greenwood
5,276,923	A	1/1994	Cohen
5,309,572	A	5/1994	Seamans
5,313,669	A	5/1994	Rasdel et al.
5,754,982	A	5/1998	Gainer
6,223,352	B1	5/2001	Watlington
6,698,031	B2	3/2004	Lewis
7,047,567	B2	5/2006	Allen
7,168,103	B2	1/2007	Aldridge et al.
7,438,619	B2	10/2008	Staver et al.
8,011,019	B1	9/2011	Hassan
8,813,266	B1	8/2014	Green
8,918,915	B2	12/2014	Caulfield et al.
9,015,864	B2	4/2015	Evans et al.
10,827,791	B2	11/2020	Banta
11,350,676	B1	6/2022	Law
2001/0000361	A1	4/2001	Alger
2003/0014802	A1	1/2003	Benham
2003/0172431	A1	9/2003	Allen
2004/0133963	A1	7/2004	Jennings
2006/0010559	A1	1/2006	Hamlet
2007/0101477	A1	5/2007	Grilliot et al.

2007/0277283	A1	12/2007	Borowski et al.
2012/0117715	A1	5/2012	Weafer
2012/0204313	A1	8/2012	Evans et al.
2012/0246805	A1	10/2012	Jones
2013/0291277	A1	11/2013	Kirkwood
2014/0101814	A1	4/2014	Caulfield et al.
2014/0101815	A1	4/2014	Caulfield et al.
2014/0215690	A1	8/2014	Caulfield et al.
2014/0304899	A1	10/2014	Almonte et al.
2015/0040285	A1	2/2015	Mobayyen
2015/0101109	A1	4/2015	Herman
2016/0324238	A1	11/2016	Tran
2017/0196283	A1	7/2017	Hart
2017/0280780	A1	10/2017	Janes
2017/0325519	A1	11/2017	Willingham
2018/0132537	A1	5/2018	Siegfried
2019/0053558	A1	2/2019	Spencer
2019/0223529	A1	7/2019	Park
2019/0246726	A1	8/2019	Oliva
2022/0030996	A1	2/2022	Wenkman
2022/0225711	A1	7/2022	Wenkman
2022/0248773	A1	8/2022	Ambelang
2023/0292864	A1	9/2023	Horbatusck
2024/0032634	A1 *	2/2024	Rodgers A41F 17/02

OTHER PUBLICATIONS

U.S. Notice of Allowance for U.S. Appl. No. 17/815,162 mailed Apr. 30, 2024.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3B




FIG. 3A




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5

1

BELT LOOP CONNECTOR

TECHNICAL FIELD

One or more embodiments relate generally to garments, and in particular, a belt loop for connecting garments.

BACKGROUND

Belt loops are a series of loops around a waist level of a lower body garment (e.g., pants) that hold a belt and help to hold up the body garment on the individual wearing the garment.

SUMMARY

One embodiment provides a garment system comprising an upper body garment comprising an interior surface and a first set of connectors positioned on the interior surface. The system further comprises a lower body garment comprising a second set of connectors positioned on a surface of the lower body garment. The first set of connectors and the second set of connectors are vertically aligned when a wearer wears the upper body garment and the lower body garment at the same time, and each connector of the second set of connectors is configured to releasably engage and interconnect with a connector of the first set of connectors to attach the upper body garment to the lower body garment.

Another embodiment provides an article of clothing comprising an upper body garment and a lower body garment. The upper body garment comprises an interior surface and a first set of connectors positioned on the interior surface. The lower body garment comprises a second set of connectors positioned on a surface of the lower body garment. The first set of connectors and the second set of connectors are vertically aligned when a wearer wears the upper body garment and the lower body garment at the same time, and each connector of the second set of connectors is configured to releasably engage and interconnect with a connector of the first set of connectors to attach the upper body garment to the lower body garment.

These and other features, aspects and advantages of the one or more embodiments will become understood with reference to the following description, appended claims and accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates an example lower body garment, in one or more embodiments;

FIG. 1B illustrates a front view of the waistband area of the lower body garment in FIG. 1A, in one or more embodiments;

FIG. 1C illustrates a back view of the waistband area of the lower body garment in FIG. 1A, in one or more embodiments;

FIG. 2A illustrates an example upper body garment, in one or more embodiments;

FIG. 2B illustrates the bottom edge of the upper body garment in FIG. 2A, in one or more embodiments;

FIG. 3A illustrates an example connector of the lower body garment, wherein the connector is a side connector, in one or more embodiments;

FIG. 3B illustrates an example connector of the lower body garment, wherein the connector is a center connector, in one or more embodiments;

2

FIG. 4A illustrates a front view of an example connector of the lower body garment in an open position to engage and interconnect with an example connector of the upper body garment, in one or more embodiments;

FIG. 4B illustrates a side view of the example connector of the lower body garment in the open position to engage and interconnect with the example connector of the upper body garment, in one or more embodiments;

FIG. 4C illustrates the example connector of the lower body garment interconnect with the example connector of the upper body garment, in one or more embodiments;

FIG. 4D illustrates the garments attached together to form a unitary and integrated protective covering, in one or more embodiments; and

FIG. 5 illustrates an example pattern for stitching a hook and loop fastener to a connector, in one or more embodiments.

DETAILED DESCRIPTION

The following description is made for the purpose of illustrating the general principles of one or more embodiments and is not meant to limit the inventive concepts claimed herein. Further, particular features described herein can be used in combination with other described features in each of the various possible combinations and permutations. Unless otherwise specifically defined herein, all terms are to be given their broadest possible interpretation including meanings implied from the specification as well as meanings understood by those skilled in the art and/or as defined in dictionaries, treatises, etc.

One or more embodiments relate generally to garments, and in particular, a belt loop for connecting garments. One embodiment provides a garment system comprising an upper body garment comprising an interior surface and a first set of connectors positioned on the interior surface. The system further comprises a lower body garment comprising a second set of connectors positioned on a surface of the lower body garment. The first set of connectors and the second set of connectors are vertically aligned when a wearer wears the upper body garment and the lower body garment at the same time, and each connector of the second set of connectors is configured to releasably engage and interconnect with a connector of the first set of connectors to attach the upper body garment to the lower body garment.

Another embodiment provides an article of clothing comprising an upper body garment and a lower body garment. The upper body garment comprises an interior surface and a first set of connectors positioned on the interior surface. The lower body garment comprises a second set of connectors positioned on a surface of the lower body garment. The first set of connectors and the second set of connectors are vertically aligned when a wearer wears the upper body garment and the lower body garment at the same time, and each connector of the second set of connectors is configured to releasably engage and interconnect with a connector of the first set of connectors to attach the upper body garment to the lower body garment.

FIG. 1A illustrates an example lower body garment 10, in one or more embodiments. The lower body garment 10 is intended to be worn by a wearer. The lower body garment 10 comprises, but is not limited to, pants, shorts, etc. The lower body garment 10 includes a waistband area 11 extending downwards from a top edge 10T of the lower body garment 10 for a distance of about H_1 (FIG. 1B). For example, in one embodiment, the distance H_1 of the waistband area 11 is about 2 inches.

3

The top edge 10T defines a waist opening 12. The lower body garment 10 further includes two garment legs 13 providing two leg openings. Specifically, each garment leg 13 includes a leg opening designed/shaped for receiving a lower limb of the wearer, wherein the garment leg 13 covers (i.e., partially covers or fully covers) the lower limb. The waist opening 12 is opposite of the leg openings.

As shown in FIG. 1A, the lower body garment 10 includes one or more connectors 50 that are spaced apart and encircle the waistband area 11. In one embodiment, the connectors 50 are located on an exterior surface 15 of the lower body garment 10. In another embodiment, the connectors 50 are located on an interior surface of the lower body garment 10. As described in detail later herein, each connector 50 is located within proximity of the top edge 10T to releasably engage and interconnect with a corresponding connector 23 (FIG. 2A) of an upper body garment 20 (FIG. 2A). The lower body garment 10 and the upper body garment 20 attach together to form a unitary and integrated protective covering 30 (FIG. 4D) for the wearer that can protect the wearer from extreme weather and other hazardous conditions (e.g., flight suits worn by pilots, garments worn by firefighters, military personnel, industrial workers, etc.). For example, in one embodiment, the garments 10 and 20 are made from a fabric that is flame resistant or flame retardant, thereby protecting the wearer from flash fires, explosions, and open flames.

The lower body garment 10 may include a plurality of optional belt loops 14 (FIG. 1B) that are spaced apart and encircle the waistband area 11. Each belt loop 14 includes an opening designed/shaped for receiving a belt that encircles the waistband area 11. In one embodiment, the connectors 50 and the belt loops 14 are spaced apart along the waistband area 11. In another embodiment, the connectors 50 are located on top of the belt loops 14, such that at least one belt loop 14 includes a corresponding connector 50 on top the belt loop 14 (i.e., attached to an exterior surface of the belt loop 14).

FIG. 1B illustrates a front view of the waistband area 11 of the lower body garment 10 in FIG. 1A, in one or more embodiments. FIG. 1C illustrates a back view of the waistband area 11 of the lower body garment 10 in FIG. 1A, in one or more embodiments. As shown in FIG. 1B, in one embodiment, the connectors 50 include, on a front side of the waistband area 11, a first side connector 50R and a second side connector 50L located to the right and to the left, respectively, of a center of the waistband area 11. As shown in FIG. 1C, in one embodiment, the connectors 50 further include, on a rear side of the waistband area 11, a center connector 50C located at about the center of the waistband area 11.

In one embodiment, each connector 50 comprises a retaining member.

FIG. 2A illustrates an example upper body garment 20, in one or more embodiments. The upper body garment 20 is intended to be worn by a wearer. The upper body garment comprises, but is not limited to, a jacket, a coat, a shirt (e.g., a combat shirt), etc.

The upper body garment 20 includes an interior surface 21 and an opposite exterior surface 22. The interior surface 21 includes one or more connectors 23 that are spaced apart and spaced from a bottom edge 20B of the upper body garment 20. As described in detail later herein, each connector 23 is located within proximity of the bottom edge 20B to releasably engage and interconnect with a corresponding connector 50 (FIGS. 1A-1C) of the lower body garment 10.

4

In one embodiment, each connector 23 includes an optional tab member 24 that allows the wearer of the upper body garment 20 to more easily locate the connector 23 and pull on the tab member 24 when attaching the connector 23 to a corresponding connector 50 of the lower body garment 10.

FIG. 2B illustrates the bottom edge 20B of the upper body garment 20 in FIG. 2A, in one or more embodiments. As shown in FIG. 2B, in one embodiment, the connectors 23 include a first side connector 23R located to a right of a center of the interior surface 21, a second side connector 23L located to a left of the center of the interior surface 21, and a center connector 23C located at about the center of the interior surface 21. In one embodiment, the connectors 23 are spaced from the bottom edge 20B a distance DI of about 0.5 inches to about 12 inches. For example, in one embodiment, the connectors 23 are spaced about 4 inches from the bottom edge 20B.

As shown in FIG. 2B, in one embodiment, each connector 23 comprises a half loop member. Each connector 23 may be made from a cord, such as an elastic cord or a shock cord, with two ends. The ends of each connector 23 are spaced apart and permanently attached to a seam 25 of the interior surface 21 via bartacks 26 (i.e., the ends are bartacked). In sewing, a bartack is a stitch or a series of stitches used to reinforce parts of a garment that may be subject to stress or additional wear (e.g., belt loops, pocket corners, etc.). For example, in one embodiment, the ends of the connectors 23R and 23L are spaced apart by a distance of about 1.75 inches, and the ends of the connector 23C are spaced apart by a distance of about 3 inches. In one embodiment, a length of each bartack 26 is about 0.25 inches.

As stated above, each connector 23 of the upper body garment 20 corresponds to a particular connector 50 of the lower body garment 10 that the connector 23 releasably engages and interconnects with. With reference to FIGS. 1B and 2B, the first side connector 23R of the upper body garment 20 corresponds to the first side connector 50R of the lower body garment 10, such that the connectors 23R and 50R releasably engage and interconnect with each other to secure a right portion of the upper body garment 20 to the lower body garment 10. With reference to FIGS. 1B and 2B, the second side connector 23L of the upper body garment 20 corresponds to the second side connector 50L of the lower body garment 10, such that the connectors 23L and 50L releasably engage and interconnect with each other to secure a left portion of the upper body garment 20 to the lower body garment 10. With reference to FIGS. 1C and 2B, the center connector 23C of the upper body garment 20 corresponds to the center connector 50C of the lower body garment 10, such that the connectors 23C and 50C releasably engage and interconnect with each other to secure a center portion of the upper body garment 20 to the lower body garment 10. The connectors 23R, 23L, and 23C are in vertical alignment with the connectors 50R, 50L, and 50C when the garments 10 and 20 are donned by the wearer.

In another embodiment, the structure of the connectors 50 of the lower body garment 10 and the connectors 23 of the upper body garment 20 are reversed, such that the connectors 50 comprise half loop members and the connectors 23 comprise retaining members instead. In yet another embodiment, the connectors 50 of the lower body garment 10 comprise a first combination of half loop members and retaining members, and the connectors 23 of the upper body garment 20 comprise a second combination of half loop members and retaining members complementary to the first combination (i.e., each half loop member of one garment

releasably engages and interconnects with a corresponding retaining member of another garment).

FIG. 3A illustrates an example connector **50** of the lower body garment **10**, wherein the connector **50** is a side connector **50R** or **50L**, in one or more embodiments. In one embodiment, each side connector **50R**, **50L** comprises a one-piece retaining member **60**. The retaining member **60** is foldable at about a center **60C** into two ends/segments of about equal length. Specifically, the retaining member **60** includes a belt loop end **61** adjacent to the waistband area **11**, and a flap end **62** that is opposite of the belt loop end **61**. The belt loop end **61** and the flap end **62** form one continuous piece.

One or more portions of the retaining member **60** are directly and permanently attached to the lower body garment **10**. For example, in one embodiment, the center **60C** of the retaining member **60** is directly and permanently attached to the exterior surface **15** of the lower body garment **10** via a bartack **66** (FIG. 1B) (i.e., the retaining member **60** is bartacked) sewn at about the center **60C**. In one embodiment, the bartack **66** is located about 0.125 inches from the top edge **10T** of the lower body garment **10**.

As another example, in one embodiment, a portion of the belt loop end **61** is directly and permanently attached to the lower body garment **10**. For example, in one embodiment, a bottom edge of the belt loop end **61** is directly and permanently attached to the exterior surface **15** of the lower body garment **10** via a bartack **65** (i.e., the belt loop end **61** is bartacked) sewn at about the bottom edge. In one embodiment, a length of the bartack **65** is about 0.875 inches.

A portion of the belt loop end **61** that is in between the bartacks **65** and **66** form an opening **51** (FIGS. 4B-4C) designed/shaped for receiving a belt that encircles the waistband area **11**.

The retaining member **60** includes a fastener. In one embodiment, the fastener is a hook and loop fastener (e.g., VELCRO® hook and loop). Specifically, the belt loop end **61** includes a loop fastening material **63A** of the fastener, and the flap end **62** includes a hook fastening material **63B** of the fastener. In one embodiment, the belt loop end **61** includes an area **64A** within proximity of the center **60C** that does not include the loop fastening material **63A**, and the flap end **62** includes an area **64B** within proximity of the center **60C** that does not include the hook fastening material **63B**. In one embodiment, the areas **64A** and **64B** are lined with webbing. Without any fastening materials **63A** and **63B**, the areas **64A** and **64B** provide more vertical room for receiving and securing a connector **23**, and make it more likely for the fastening materials **63A** and **63B** to vertically align. Further, there is less surface area for dirt and other debris to get caught in the fastening materials **63A** and **63B**, thereby causing less wear and tear to the hook and loop fastener over time.

In another embodiment, the locations of the hook fastening material **63B** and the loop fastening material **63A** are reversed, such that the belt loop end **61** includes the hook fastening material **63B** and the flap end **62** includes the loop fastening material **63A** instead.

The flap end **62** is a flap that is releasably attached to the lower body garment **10** via the fastener. For example, in one embodiment, aligning and pressing the flap end **62** on top of and against the belt loop end **61** causes the hook fastening material **63B** to engage and fasten to the loop fastening material **63A**. In FIG. 3A, the flap end **62** is in an open position, i.e., the hook fastening material **63B** is not engaged and fastened to the loop fastening material **63A**.

In one embodiment, a length of the retaining member **60** is about 6.125 inches. In one embodiment, the length includes a length L_1 from a bottom edge of the belt loop end **61** to the center **60C**, and another length L_2 from a top edge of the flap end **62** to the center **60C**. In one embodiment, the lengths L_1 and L_2 are substantially similar. For example, in one embodiment, each of the lengths L_1 and L_2 is about 2.5 inches.

In one embodiment, a length L_3 of the loop fastening material **63A** is substantially similar to a length L_4 of the hook fastening material **63B**, such that the surface areas of the materials **63A**, **63B** are similarly sized for better grip. For example, in one embodiment, each of the lengths L_3 and L_4 is about 1.5 inches.

In one embodiment, a width W_1 of the retaining member **60** is about 1 inch.

In another embodiment, the fastener is another type of fastener such as, but not limited to, a snapfit connector (e.g., a cantilever snap, an annular snap, a trap, a dart, etc.), a push-pull connector, a buckle, a retaining ring, a snap, a cantilever spring fastener, a crush rib fastener, a carabiner, etc.

FIG. 3B illustrates an example connector **50** of the lower body garment **10**, wherein the connector **50** is a center connector **50C**, in one or more embodiments. In one embodiment, the center connector **50C** comprises a one-piece retaining member **70**. The retaining member **70** is foldable at about a center **70C** into two ends of about equal length. Specifically, the retaining member **70** includes a belt loop end **71** adjacent to the waistband area **11**, and a flap end **72** that is opposite of the belt loop end **71**. The belt loop end **71** and the flap end **72** form one continuous piece.

One or more portions of the retaining member **70** are directly and permanently attached to the lower body garment **10**. For example, in one embodiment, the center **70C** of the retaining member **70** is directly and permanently attached to the exterior surface **15** of the lower body garment **10** via a bartack **76** (FIG. 1C) (i.e., the retaining member **70** is bartacked) sewn at about the center **70C**. In one embodiment, the bartack **76** is located about 0.125 inches from the top edge **10T** of the lower body garment **10**.

As another example, in one embodiment, a portion of the belt loop end **71** is directly and permanently attached to the lower body garment **10**. For example, in one embodiment, a bottom edge of the belt loop end **71** is directly and permanently attached to the exterior surface **15** of the lower body garment **10** via a bartack **75** (i.e., the belt loop end **71** is bartacked) sewn at about the bottom edge. In one embodiment, a length of the bartack **75** is about 0.875 inches.

A portion of the belt loop end **71** that is in between the bartacks **75** and **76** form an opening **51** (FIGS. 4B-4C) designed/shaped for receiving a belt that encircles the waistband area **11**.

The retaining member **70** includes a fastener. In one embodiment, the fastener is a hook and loop fastener (e.g., VELCRO® hook and loop). Specifically, the belt loop end **71** includes a loop fastening material **73A** of the fastener, and the flap end **72** includes a hook fastening material **73B** of the fastener. In one embodiment, the belt loop end **71** includes an area **74A** within proximity of the center **70C** that does not include the loop fastening material **73A**, and the flap end **72** includes an area **74B** within proximity of the center **70C** that does not include the hook fastening material **73B**. In one embodiment, the areas **74A** and **74B** are lined with webbing. Without any fastening materials **73A** and **73B**, the areas **74A** and **74B** provide more vertical room for receiving and securing a connector **23**, and make it more

likely for the fastening materials **73A** and **73B** to vertically align. Further, there is less surface area for dirt and other debris to get caught in the fastening materials **73A** and **73B**, thereby causing less wear and tear to the hook and loop fastener over time.

In another embodiment, the locations of the hook fastening material **73B** and the loop fastening material **73A** are reversed, such that the belt loop end **71** includes the hook fastening material **73B** and the flap end **72** includes the loop fastening material **73A** instead.

The flap end **72** is a flap that is releasably attached to the lower body garment **10** via the fastener. For example, in one embodiment, aligning and pressing the flap end **72** on top of and against the belt loop end **71** causes the hook fastening material **73B** to engage and fasten to the loop fastening material **73A**. In FIG. 3B, the flap end **72** is in an open position, i.e., the hook fastening material **73B** is not engaged and fastened to the loop fastening material **73A**.

In one embodiment, a length of the retaining member **70** is about 8.125 inches. In one embodiment, the length includes a length L_5 from a bottom edge of the belt loop end **71** to the center **70C**, and another length L_6 from a top edge of the flap end **72** to the center **70C**. In one embodiment, the lengths L_5 and L_6 are substantially similar. For example, in one embodiment, each of the lengths L_5 and L_6 is about 3.5 inches.

In one embodiment, a length L_7 of the loop fastening material **73A** is substantially similar to a length L_8 of the hook fastening material **73B**, such that the surface areas of the materials **73A**, **73B** are similarly sized for better grip. For example, in one embodiment, each of the lengths L_7 and L_8 is about 2.25 inches.

In one embodiment, a width W_2 of the retaining member **70** is about 1 inch.

In another embodiment, the fastener is another type of fastener such as, but not limited to, a snapfit connector (e.g., a cantilever snap, an annular snap, a trap, a dart, etc.), a push-pull connector, a buckle, a retaining ring, a snap, a cantilever spring fastener, a crush rib fastener, a carabiner, etc.

FIG. 4A illustrates a front view of an example connector **50** of the lower body garment **10** in an open position to engage and interconnect with an example connector **23** of the upper body garment **20**, in one or more embodiments. FIG. 4B illustrates a side view of the example connector **50** in the open position to engage and interconnect with the example connector **23**, in one or more embodiments. FIG. 4C illustrates the example connector **50** interconnected with the example connector **23**, in one or more embodiments. FIG. 4D illustrates the garments **10** and **20** attached together to form a unitary and integrated protective covering **30**, in one or more embodiments. Once a wearer wears both the lower body garment **10** and the upper body garment **20**, the garments **10** and **20** can be attached together by engaging and interconnecting each connector **50** of the lower body garment **10** with a corresponding connector **23** of the upper body garment **20**. For example, connectors **50R**, **50L**, and **50C** of the lower body garment **10** are interconnected with connectors **23R**, **23L**, and **23C** of the upper body garment **20**, respectively.

To attach a connector **50** with a corresponding connector **23**, a fastener (e.g., hook and loop fasteners shown in FIGS. 3A-3B) of the connector **50** is released, causing a flap end (e.g., flap ends **62** and **72** shown in FIGS. 3A-3B) of the connector **50** to pivot upwards into an open position. When the flap end is in the open position, the wearer can pull on the connector **23** located on the interior surface **21** of the

upper body garment **20** and bring the connector **23** in close proximity to the flap end. The wearer places the flap end within the connector **23** (e.g., the flap end is placed through an opening formed by the half loop member of the connector **23**). Once the flap end has engaged the connector **23**, the flap end can be pivoted in a down wards direction into a closed position, as shown in FIG. 4C. When in the closed position, the fastener engages (e.g., hook fastening materials **63B**, **73B** and loop fastening materials **63A**, **73A** shown in FIGS. 3A-3B engage) causing a secure attachment between the connectors **50** and **23**.

Once the upper body garment **20** is attached to the lower body garment **10**, the upper body garment **20** is prevented from being forced up and separating from the lower body garment **10** and exposing the wearer.

FIG. 5 illustrates an example pattern **80** for stitching a hook and loop fastener to a connector **50**, in one or more embodiments. Loop fastening material (e.g., **63A**, **73A** in FIGS. 3A-3B) of the fastener is sewn to a belt loop end (e.g., **61**, **71** in FIGS. 3A-3B) of the connector **50** along a path **81** that forms an X for extra reinforcement. Hook fastening material (e.g., **63B**, **73B** in FIGS. 3A-3B) of the fastener is sewn to a flap end (e.g., **62**, **72** in FIGS. 3A-3B) of the connector **50** along a path **82** that forms a square/rectangle. In one embodiment, a bottom edge of the belt loop end and a top edge of the flap end are turned under and caught in the stitching for reinforcement. Stitching is visible on an exterior of the flap end to provide a wearer with a visual aid for aligning the hook fastening material to the loop fastening material.

References in the claims to an element in the singular is not intended to mean "one and only" unless explicitly so stated, but rather "one or more." All structural and functional equivalents to the elements of the above-described exemplary embodiment that are currently known or later come to be known to those of ordinary skill in the art are intended to be encompassed by the present claims. No claim element herein is to be construed under the provisions of 35 U.S.C. section 112, sixth paragraph, unless the element is expressly recited using the phrase "means for" or "step for."

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

The corresponding structures, materials, acts, and equivalents of all means or step plus function elements in the claims below are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. The description of the embodiments has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the invention.

Though the embodiments have been described with reference to certain versions thereof; however, other versions are possible. Therefore, the spirit and scope of the appended claims should not be limited to the description of the preferred versions contained herein.

What is claimed is:

1. A garment system comprising:

a first piece of body garment comprising a first type of connector; and

a second piece of body garment comprising a second type of connector configured to releasably engage and interconnect with the first type of connector to attach the first piece of body garment to the second piece of body garment;

wherein the second type of connector includes a one-piece continuous member foldable at about a center to define a pair of opposite segments;

wherein a first segment of the pair includes a first area with a first type of fastening material and a second area without the first type of fastening material;

wherein a second segment of the pair includes a third area with a second type of fastening material and a fourth area without the second type of fastening material; and

wherein a size of the first area with the first type of fastening material is substantially similar to a size of the third area with the second type of fastening material, such that, when the second type of connector engages and interconnects with the first type of connector, the second area without the first type of fastening material and the fourth area without the second type of fastening material provide space for receiving and retaining the first type of connector, and the first area with the first type of fastening material engages and fastens to an entirety of the third area with the second type of fastening material.

2. The garment system of claim 1, wherein the first piece of body garment and the second piece of body garment comprise an upper body garment and a lower body garment, respectively, and the first type of connector and the second type of connector are vertically aligned when a wearer wears the upper body garment and the lower body garment at the same time.

3. The garment system of claim 1, wherein the first type of connector is arranged on an interior surface of the first piece of body garment.

4. The garment system of claim 1, wherein the second type of connector is arranged on a surface of the second piece of body garment.

5. The garment system of claim 1, wherein the first type of connector comprises a half loop member.

6. The garment system of claim 1, wherein the first segment of the pair forms a belt loop for receiving a belt, and the second segment of the pair forms a flap for retaining the first type of connector to the second piece of body garment when the second type of connector engages and interconnects with the first type of connector.

7. The garment system of claim 6, wherein the belt loop is directly and permanently attached to the second piece of body garment, and the flap is removably attached to the second piece of body garment.

8. The garment system of claim 1, wherein a size of the first segment of the pair is substantially similar to a size of the second segment of the pair.

9. The garment system of claim 1, wherein first type of fastening material and the second type of fastening material are different types of fastening material.

10. The garment system of claim 1, wherein first type of fastening material and the second type of fastening material together form a hook and loop fastener.

11. The garment system of claim 1, wherein the first piece of body garment and the second piece of body garment

comprise at least one additional first type of connector and at least one additional second type of connector, respectively.

12. An article of clothing comprising:

a first body garment comprising a first connector; and

a second body garment comprising a second connector configured to releasably engage and interconnect with the first connector to attach the first body garment to the second body garment;

wherein the second connector includes a one-piece continuous member foldable at about a center to define a pair of opposite segments;

wherein a first segment of the pair includes a first area with a first fastening material and a second area without the first fastening material;

wherein a second segment of the pair includes a third area with a second fastening material and a fourth area without the second fastening material; and

wherein a size of the first area with the first fastening material is substantially similar to a size of the third area with the second fastening material, such that, when the second connector engages and interconnects with the first connector, the second area without the first fastening material and the fourth area without the second fastening material provide space for receiving and retaining the first connector, and the first area with the first fastening material engages and fastens to an entirety of the third area with the second fastening material.

13. The article of clothing of claim 12, wherein the first body garment and the second body garment comprise an upper body garment and a lower body garment, respectively, and the first connector and the second connector are vertically aligned when a wearer wears the upper body garment and the lower body garment at the same time.

14. The article of clothing of claim 12, wherein the first connector is arranged on an interior surface of the first body garment.

15. The article of clothing of claim 12, wherein the second connector is arranged on a surface of the second body garment.

16. The article of clothing of claim 12, wherein the first connector comprises a half loop member.

17. The article of clothing of claim 12, wherein the first segment of the pair forms a belt loop for receiving a belt, and the second segment of the pair forms a flap for retaining the first connector to the second body garment when the second connector engages and interconnects with the first connector.

18. The article of clothing of claim 17, the wherein belt loop is directly and permanently attached to the second body garment, and the flap is removably attached to the second body garment.

19. The article of clothing of claim 12, wherein first fastening material and the second fastening material are different types of fastening material.

20. The article of clothing of claim 12, wherein the first body garment and the second body garment comprise at least one additional first connector and at least one additional second connector, respectively.