United States Patent	12390046
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Patton; Brian R. et al.

Systems and methods for achieving a user-specified temperature profile in a cooking appliance through heating control algorithms

Abstract

In one embodiment, a method includes, by an electromagnetic device, accessing multiple previously recorded heating maps corresponding to a load disposed inside a cavity, where each heating map indicates a temperature profile change of the load as a function of one or more control parameter configurations, accessing a target temperature profile of the load, measuring a current temperature profile of the load, calculating a difference in temperature profiles between the current temperature profile of the load and the target temperature profile of the load, determining a first sequence of control parameter configurations to heat the load, wherein the first sequence is optimized to yield a temperature rise that achieves the target temperature profile of the load, emitting electromagnetic radiation into the cavity based on the first sequence of control parameter configurations.

Inventors: **Patton; Brian R. (San Francisco, CA), Ortega Avila; Santiago (Milpitas, CA), Lopez; Perdo Martinez (Mountain View, CA), Marks; Jacob A. (Stanford, CA), Parker; Ian David (Santa Barbara, CA), Kim; Catherine S. (San Jose, CA), Perdices-Gonzalez; Sergio (Sunnyvale, CA), Sadi; Sajid Hassan (San Jose, CA)**

Applicant: **Samsung Electronics Company, Ltd.** (Gyeonggi-do, KR)

Family ID: **1000008767834**

Assignee: **Samsung Electronics Company, Ltd. (Suwon-si, KR)**

Appl. No.: **17/707561**

Filed: **March 29, 2022**

U.S. Cl.:

CPC   **A47J36/32** (20130101); **A47J36/2483** (20130101); **F24C7/082** (20130101); **F24C7/087** (20130101);

Field of Classification Search

CPC: F24C (7/087); F24C (7/082); A47J (36/32); A47J (36/2483); H05B (6/6447)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9414444	12/2015	Libman	N/A	N/A
9807823	12/2016	Einziger	N/A	N/A
10223933	12/2018	Cheng	N/A	N/A
10268919	12/2018	Piekniewski	N/A	N/A
10819905	12/2019	Liu	N/A	N/A
11774105	12/2022	Chase	N/A	N/A
2009/0321427	12/2008	Hyde	N/A	N/A
2009/0321428	12/2008	Hyde	N/A	N/A
2010/0187224	12/2009	Hyde	N/A	N/A
2013/0269539	12/2012	Polt	N/A	N/A
2013/0306627	12/2012	Libman	219/709	H05B 6/687
2015/0289324	12/2014	Rober	N/A	N/A
2015/0366219	12/2014	Wersborg	N/A	N/A
2016/0029441	12/2015	Taylor	N/A	N/A
2016/0073453	12/2015	Hyde	N/A	N/A
2016/0192446	12/2015	Seddik	N/A	N/A
2016/0309548	12/2015	Libman	N/A	N/A
2017/0074522	12/2016	Cheng	N/A	N/A
2019/0116634	12/2018	Eadan	N/A	N/A
2019/0254127	12/2018	Ma	N/A	N/A
2019/0320507	12/2018	Guatta	N/A	N/A
2020/0187709	12/2019	Ayre	N/A	N/A
2020/0367692	12/2019	Stipe	N/A	N/A
2021/0145212	12/2020	Wang	N/A	A47J 36/321
2021/0267027	12/2020	Uno	N/A	N/A
2021/0307135	12/2020	Hooker	N/A	N/A
2021/0385917	12/2020	Kuchler	N/A	H05B 6/725
2021/0386239	12/2020	Eiter	N/A	N/A
2022/0141928	12/2021	Hong	N/A	N/A
2022/0264709	12/2021	Zoellner	N/A	A23L 5/15
2023/0269840	12/2022	Martinez Lopez	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106664753	12/2016	CN	N/A
109727657	12/2018	CN	N/A
110298902	12/2018	CN	N/A
H06229557	12/1993	JP	N/A
2001201057	12/2000	JP	N/A
2001317742	12/2000	JP	N/A

2004095501	12/2003	JP	N/A
3672767	12/2004	JP	N/A
2005315487	12/2004	JP	N/A
3792495	12/2005	JP	N/A
2015220189	12/2014	JP	N/A
2016-110750	12/2015	JP	N/A
2019070462	12/2018	JP	N/A
19990065353	12/1998	KR	N/A
10-0416286	12/2003	KR	N/A
2019-0069624	12/2018	KR	N/A
2021-0029722	12/2020	KR	N/A

OTHER PUBLICATIONS

Heat Map Microwave—a New invention; Mark Rober https://youtu_be/ptkzzNaZbZU, Feb. 11, 2015. cited by applicant

PCT Search Report and Written Opinion in Application No. PCT/KR2022/006554, Aug. 10, 2022. cited by applicant

Combustion Inc. Predictive Probe: https://combustion.inc/, 17 pages, pulled from website Feb. 10, 2022. cited by applicant

Khan, Tareq, "An Intelligent Microwave Oven with Thermal Imaging and Temperature Recommendation Using Deep Learning," Applied System Innovation, Mar. 13, 2020, doi: 10.3390/asi3010013, Accepted Feb. 13, 2020, Published: Feb. 17, 2020, www.mdpi.com/journal/asi, 17 pages. cited by applicant

PCT Search Report and Written Opinion in PCT/KR2023/095007, Jun. 14, 2023. cited by applicant

Non-final office action in U.S. Appl. No. 17/680,104, Dec. 5, 2024. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/316,497, Jun. 29, 2023. cited by applicant

"Miele adds electromagnetic waves to Wi-Fi oven for better cooking", by Ashlee Clark Thompson; https://www.cnet.com/reviews/miele-dialog-oven-preview/, Aug. 30, 2017. cited by applicant

"What is RF cooking?", Goji Food Solution; http://www.gojifoodsolutions.com/rf-cooking-technology, 2021. cited by applicant

"Put some swagger on your countertop and let June do the cooking." june; https://juneoven.com/pages/smart-oven, 2021. cited by applicant

"NNLC: Non-Negative Least Chi-square minimization and application to HPGe detectors," by Pierre D'esesquelles et al.; Cornell University, Journey Ref: J.Phys.G36:037001,Feb. 22, 2009. cited by applicant

"Software-Defined Cooking using a Microwave Oven", by Haojian Jin et al.; Cernegie Mellon University, Pittsburgh, PA, US, 2019. cited by applicant

"Solving Least Squares Problems," by Charles L. Lawson et al, Society for Industrial and Applied Mathematics, Philadelphia. Chapter 23 pp. 158-173, 1995. cited by applicant

Non-final Office Action in U.S. Appl. No. 17/316,497, Sep. 6, 2024. cited by applicant

Final Office Action in U.S. Appl. No. 17/316,497, Mar. 21, 2024. cited by applicant

European Patent Office Extended European Search Report in application No. 23760451.7-1002 / 4388821 PCT/KR2023095007, Nov. 8, 2024. cited by applicant

Final Office Action in U.S. Appl. No. 17/316,497, Jan. 16, 2025. cited by applicant

Final office action in U.S. Appl. No. 17/680,104, Dated May 6, 2025. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/316,497, Dated May 23, 2025 cited by applicant

Primary Examiner: Tran; Thien S

Background/Summary

TECHNICAL FIELD
(1) This disclosure relates generally to cooking appliances, and more particularly to user-specified

temperature profile control of microwave ovens and other cooking devices.
BACKGROUND
(2) Conventional cooking appliances typically heat food unevenly, often resulting in unsatisfactory food quality (e.g., regions either too hot or too cold), excessive user intervention (e.g., cycling the heat source on and off, and/or moving or rotating the food), potential degradation of the food being heated, minor accidents (e.g., unwanted boiling or spattering due to overheating), slow heating times, and so forth. Additionally, many conventional microwave ovens require the user to input a user-specified heating time duration in order to achieve a desired food temperature. Such a process may be fraught with uncertainty and may often be made more complex for users due to the cumbersome user interface options for entering the heating time durations. It may be thus useful to provide techniques to improve microwave oven devices.

Description

BRIEF DESCRIPTION OF THE DRAWINGS
(1) FIG. **1** illustrates an example diagram of a cooking appliance.
(2) FIGS. **2**A, **2**B, **2**C, and **2**D illustrate example diagram of a heating pattern within food being heated by absorption of RF energy in a microwave oven device.
(3) FIG. **3** illustrates an example diagram depicting heating maps.
(4) FIG. **4** illustrates an example diagram of calculating an optimal sequence of heating patterns to achieve a target temperature profile.
(5) FIG. **5** illustrates an example system diagram for providing a temperature profile-based cooking appliance.
(6) FIG. **6** illustrates an example diagram of a sequence of heating maps and corresponding array.
(7) FIG. **7** illustrates an example workflow diagram depicting a technique for implementing an open-loop heating control algorithm for a cooking appliance.
(8) FIG. **8** illustrates an example workflow diagram depicting a technique for achieving a target temperature profile through a closed-loop heating control algorithm.
(9) FIG. **9** illustrates an example workflow diagram depicting a technique for achieving a target temperature profile through an adaptive power control heating algorithm.
(10) FIG. **10** illustrates an example workflow diagram depicting a technique for achieving a target temperature profile through a tailored cost function algorithm.
(11) FIG. **11** illustrates a diagram of example temperature profiles measured with different implementations of the heating control algorithm.
(12) FIGS. **12**A and **12**B illustrate example diagrams depicting heating maps utilizing a temperature profile-based cooking appliance with multiple loads.
(13) FIGS. **13**A and **13**B illustrate example diagrams depicting an example workflow and an example user interface of a temperature profile-based cooking appliance.
(14) FIG. **14** illustrates a flow diagram of a method for achieving a user-specified temperature profile in a cooking appliance through heating control algorithms.
(15) FIG. **15** illustrates an example computer system.
DESCRIPTION OF EXAMPLE EMBODIMENTS
(16) FIG. **1** illustrates an example diagram **100** of a cooking appliance **102**. In particular embodiments, cooking appliance **102** may include a temperature profile-based electromagnetic cooking appliance **102**. In particular embodiments, a cooking appliance **102** may measure the pattern of electromagnetic energy absorbed by a load disposed inside a cavity when electromagnetic radiation is directed into the cavity. As used herein, "cavity" may be defined as an area in which food may cook within a cooking appliance **102**. As an example and not by way of limitation, toasting slots within a toaster to cook toast may be defined as a cavity. As another example and not by way of limitation, the cooking chamber within a microwave oven may be defined as a cavity. In particular embodiments, the cooking appliance **102** may include, for example, any of various cooking appliances **102** that may be suitable for heating or warming food, or otherwise directing electromagnetic energy to one or more loads disposed inside a cavity of the cooking appliance **102**. In particular embodiments, as further depicted by FIG. **1**, the cooking appliance **102** may

include, among other things, one or more processor(s) **104**, memory **106**, sensors **108**, radio frequency (RF) and microwave electronics **110**, a display panel **112**, input structures **114**, network interfaces **116**, a power source **118**, and an input/output (I/O) interface **120**. It should be noted that FIG. **1** is merely one example of a particular implementation and is intended to illustrate the types of components that may be included as part of the cooking appliance **102**.

(17) In particular embodiments, the one or more processor(s) **104** may be operably coupled with the memory **106** to perform various algorithms for providing a temperature profile-based cooking appliance. Such programs or instructions executed by the processor(s) **104** may be stored in any suitable article of manufacture that includes one or more tangible, computer-readable media at least collectively storing the instructions or routines, such as the memory **106**. The memory **106** may include any suitable articles of manufacture for storing data and executable instructions, such as random-access memory (RAM), read-only memory (ROM), rewritable flash memory, hard drives, and so forth. Also, programs (e.g., an operating system) encoded on such a computer program product may also include instructions that may be executed by the processor(s) **104** to enable the cooking appliance **102** to provide various functionalities.

(18) In particular embodiments, the sensors **108** may include, for example, one or more cameras (e.g., depth cameras), touch sensors, microphones, motion detection sensors, thermal detection sensors, light detection sensors, time of flight (ToF) sensors, ultrasonic sensors, infrared sensors, or other similar sensors that may be utilized to detect the physical state of the load (e.g., its temperature profile) or various user inputs (e.g., user voice inputs, user gesture inputs, user touch inputs, user instrument inputs, user motion inputs, and so forth). The RF and microwave electronics **110** may include, for example, any number of magnetrons, power amplifiers, signal generators, waveguides, antennas, integrated circuits, transistors, solid-state amplifiers, and/or one or more other devices that may be collectively suitable for directing electromagnetic energy (e.g., microwave energy) to a load (e.g., food, solids, liquids, and so forth) that may be disposed inside a cavity of the cooking appliance **102**. The display panel **112** may include any display architecture (e.g., AMLCD, AMOLED, micro-LED, and so forth), which may provide further means by which users may interact and engage with the cooking appliance **102**.

(19) In particular embodiments, the input structures **114** may include any physical structures utilized to control one or more global functions of the cooking appliance **102** (e.g., pressing a button to power "ON" or power "OFF" the cooking appliance **102**). The network interface **116** may include, for example, any number of network interfaces suitable for allowing the cooking appliance **102** to access and receive data over one or more cloud-based networks (e.g., a cloud-based service that may service hundreds or thousands of the cooking appliance **102** and the associated users corresponding thereto) and/or distributed networks. The power source **118** may include any suitable source of power, such as a rechargeable lithium polymer (Li-poly) battery and/or an alternating current (AC) power converter that may be utilized to power and/or charge the cooking appliance **102** for operation. Similarly, the I/O interface **120** may be provided to allow the cooking appliance **102** to interface with various other electronic or computing devices, such as one or more auxiliary electronic devices.

(20) Inhomogeneous heating is an intrinsic property of the cavity of an electromagnetic device (e.g., cooking appliance **102**) due to the standing-wave pattern that is established by the reflective walls. Within a source-free medium such as air or food, the RF radiation obeys the electromagnetic wave equation:

(21) $\nabla \times (\frac{1}{\mu})\nabla \times E - \omega^2 \in E = 0$ (Equation 1) $\nabla^2 E + \omega^2 \mu \in E = 0$ (Equation 2)

(22) In Equation 1 and Equation 2, E represents the complex vector electric field, μ represents the complex magnetic permeability of the material, $\in$ represents the complex dielectric permittivity of the material, and ω represents the angular frequency of the wave. Incident RF radiation may reflect off the electrically conducting oven walls, setting up a stationary standing wave pattern of constructive and destructive interference. Certain commercial cooking appliances **102** may operate with frequencies of 2400 megahertz (MHz) to 2500 MHz, resulting in a wavelength of 12 centimeters (cm). An empty commercial cooking appliance will tend to have a semi-regular pattern of standing wave nodes and anti-nodes separated by approximately half this length, or 6 cm. The RF wavelength may be smaller in dielectric materials, such as food. For example, food is heated by absorption of the electric field according to its electric and magnetic properties:

$\in = \in.sub.0(\in' + $ custom character $\in'')$ (Equation 3)

(23) In Equation 3, $\in'$ and $\in''$ are real-valued (and generally frequency-dependent) parameters of the

food, $\in$.sub.0 is a fundamental physical constant, and ⬚custom character is the imaginary unit. In the absence of magnetic dissipation, the power density P absorbed by the food may be calculated as:

(24) $P = \frac{1}{2}(\quad + \quad_0 \quad'') .$Math. E .Math. ^{2} (Equation4)

(25) In Equation 4, σ is the electrical conductivity. In Equation 4, P is measured in watts per cubic meter. The power deposition in the food is proportional to the squared magnitude of the electric field, which is fundamentally inhomogeneous within the cavity due to the standing-wave pattern. In particular embodiments, inhomogeneity is made worse by the fact that the food fundamentally changes the standing-wave pattern within the cavity, meaning that the heating pattern may generally not be determined a priori. The standing-wave pattern is affected not only by the food dielectric characteristics, but also by its geometry and placement within the cavity. For example, if the load is placed on a rotating turntable within the cavity, the standing-wave pattern throughout the cavity will be modulated as the turntable rotates, and regions of high heating within the food will not remain fixed with respect to either the food or the cavity coordinate system. As the inherent standing wave pattern cannot be predicted beforehand due to being strongly influenced by the food, any closed-loop control of the food requires active measurements of where the heat is being deposited.

(26) Inhomogeneous heating is also challenging with infrared (IR) radiant heating, used in broiling and toasting applications. The rate at which a food item heats not only depends on the placement and power of the radiant emitters within an appliance; it also depends on the infrared absorption coefficient of the food's surface, which may vary within the food itself. Further, evaporative cooling may strongly affect the surface heating rate of the load, and may also vary throughout the food due to inhomogeneity of the water content. Even with a multi-emitter system with independent control of each emitter's power, it may not be possible to achieve a controlled final temperature profile without some measurement of the spatially varying absorption rate within the food. The present embodiment is directed to techniques of deterministically modifying the heating patterns within a cooking appliance **102** to achieve a user's desired final temperature profile (e.g., homogenous or non-homogenous temperature profile) for the food placed in the cooking appliance **102**. In this way, regardless of the heating mechanism, if the system has knowledge about which heating patterns may be generated by different control parameter configurations of the cooking appliance **102**, the system may generate the user's desired temperature profile by open-loop and/or closed-loop control of cycling through one or more sequences of the control parameter configurations. Thus, it may be useful to provide a heating control algorithm to deterministically modify heating patterns.

(27) In particular embodiments, in cooking appliances **102**, the microwave energy may be generated by a magnetron (e.g., an analog high-power vacuum tube device that emits radiofrequency waves by resonant oscillation). Though efficient and inexpensive, magnetrons generally have poor frequency and phase control and may not be driven at intermediate powers. The standard approach to power regulation in a commercial cooking appliance is to cycle the magnetron power on and off with variable duty cycle. This relies on thermal diffusion within the food to even out the temperature but may be an imprecise and slow technique that invariably results in overheating or underheating some regions within the load (e.g., food). The conductive heat diffusion equation within a substance is parameterized by its density ρ, specific heat c.sub.p, and thermal conductivity k:

(28) $\quad c_p \frac{\partial T}{\partial t} = k\nabla^2 T$ (Equation5)

(29) This diffusion equation (e.g., Equation 5) relates the time derivative of the temperature at every point in the load to its Laplacian (derived from its spatial gradient). The combination k/ρc.sub.p is the thermal diffusivity a of the substance, with units cm.sup.2/sec. The characteristic time t.sub.diff for heat to diffuse a length ⬚custom character through the material is simplified as:

t.sub.diff=⬚custom character.sup.2/2α (Equation 6)

(30) In particular embodiments, the thermal diffusivity of beef is reported in the literature to be α.sub.beef≈0.0013 cm.sup.2/s. If two regions within a plate of beef are separated by 1 cm and heated to different temperatures, it may be deduced that it will take approximately 385 seconds for the temperature to even out substantially. Thus, heat diffusion may be too slow to even out hotspots or cold spots. For example, as previously determined through a power-cycled microwave heating experiment, the temperature of the food at the hot spot heats up dramatically when the emitter power is turned "ON", and then slowly falls while the emitter is "OFF". The temperature of the food at the cold spot is very slow to

equilibrate.

(31) In particular embodiments, cooking appliance **102** may have the ability to heat specific zones differently by controlling the power of individual heating control elements **530** placed throughout the cooking appliance **102**. In principle, this may allow the user to specify a desired final temperature profile for the food placed in the cooking appliance **102**, however, fully automated control may be difficult to achieve unless the cooking appliance **102** has knowledge of the spatial heating patterns associated with control parameters. This in turn requires spatial thermometry, which may be most critical when the heating patterns are non-uniform and difficult to predict in advance. Spatial thermometry may be most effective when a change in control parameters results in an immediate change in the heating pattern. These conditions may be met, for example, by radiofrequency (RF) cooking methods as well as broiling and toasting devices. The latter two cooking methods rely on heat via infrared radiation emitted by a set of elements and absorbed by the food's surface. However, inhomogeneities in the broiling and toasting process may arise from the uneven placement of heating elements, poorly controlled thermal losses from the appliance, variation in the food's color, variations in the food's water content, etc. RF cooking is fundamentally inhomogeneous within an enclosed cavity of the cooking appliance **102** due to the standing-wave pattern, and the electric field may not be predicted a priori because the electric field is strongly dependent on the shape, distribution, and dielectric properties of the object being heated. Without knowledge of where heat is being deposited within a food, predicting or controlling a final temperature of the food is generally not possible. Thus, it may be useful to provide intelligent heating algorithms to automatically adjust system control parameters to achieve a target temperature profile without further user interaction.

(32) FIGS. **2**A, **2**B, **2**C, and **2**D illustrate example diagrams **200** of a heating pattern within food being heated by absorption of RF energy in a microwave oven. For example, FIGS. **2**A, **2**B, **2**C, and **2**D illustrate that heating patterns within the food may be controlled either deterministically or non-deterministically through potential control parameters such as, variation of the cooking appliance **102** emitter frequency, power, and in the case of multi-emitter systems, relative phase among emitters; rotation or translation of the food; modification of the cavity geometry or electrical properties; and addition of refracting or reflecting elements (including so-called "mode stirrers") within the microwave propagation path. For example, FIGS. **2**A, **2**B, **2**C, and **2**D depict simulated heating patterns in a beef steak with realistic dielectric and thermal properties when the steak is irradiated with microwave energy in a multimode cavity. The simulated cavity has two emitters operating at the same frequency that is chosen to be 2.45 GHz (FIGS. **2**A and **2**B) or 2.50 GHz (FIGS. **2**C and **2**D), with relative electromagnetic phase of 0° (FIGS. **2**A and **2**C) or 90° (FIGS. **2**B and **2**D). Heating rates are plotted on a range of 0 W/cm.sup.3 to 2.5 W/cm.sup.3. Variation of the other parameters listed above result in qualitatively similar variations in the resulting heating patterns.

(33) In particular embodiments, to permit effective closed-loop temperature control to achieve a user's desired final temperature profile, the spatially dependent rate of heat deposition may be measured through Fast Pattern Temperature Imaging (FPTI) and/or Adaptive Fast Pattern Temperature Imaging (AFPTI). As an example and not by way of limitation, FPTI and/or AFPTI may measure spatially varying heat deposition via short-duration heating pulses and prompt spatial thermometry to detect small temperature increments in the object being heated, resulting in a two-dimensional image or heat map reflecting the heating rate in degrees per second. The techniques of Fast Pattern Temperature Imaging (FPTI) and/or Adaptive Fast Pattern Temperature Imaging (AFPTI) may utilize any sensors **108** that measure a spatial temperature profile of the load. As an example and not by way of limitation, infrared thermal imaging cameras may be placed outside the cavity of the microwave oven, thus shielded from microwave radiation and/or high temperatures. For example, the infrared thermal imaging cameras may measure the temperature profile of the food through a small aperture in the microwave cavity that permits optical access without allowing RF energy to escape the cavity.

(34) In particular embodiments, selecting a sequence of system control parameters may yield a user-specified final temperature profile, but only if the resulting heating patterns are known by the system. FPTI and/or AFPTI allow for measurement of heat spatial deposition within a load, resulting from each combination of the system control parameters. In appliances using radiative heating, the control parameters may include the phase, frequency of the microwave source(s), power of the microwave source(s), position of the load (which may be rotated or translated), or the position or angle of a reflective

or refractive element within the cavity (e.g., mode stirrer). Changes in one or more of the above-mentioned control parameters may yield differing standing-wave patterns. In particular embodiments, closed-loop control of particular control parameter combinations may result in a predictable temperature rise of a load disposed inside a cavity of an electromagnetic device (e.g., cooking appliance **102**). Prompt measurements of spatially varying heat deposition for varying control parameter combinations through FPTI and/or AFPTI may generate intelligent heating algorithms, which are particularly valuable in electromagnetic devices, where heat deposition may be intrinsically inhomogeneous, rapid, and difficult to predict a priori. Although the present embodiments demonstrate FPTI and/or AFPTI via radiometric infrared thermal imaging, this disclosure contemplates any suitable sensor **108** technology that yields a prompt and spatially resolved temperature map. In particular embodiments, alternate sensors **108** may include a network of thermistors or thermocouples places near or within the load, such as an array of solid-state thermometers built into the turntable or tray of a cooking appliance **102**.

(35) A single FPTI and/or AFPTI pattern may be measured with a noise floor of 50 millikelvin (mK) using a thermal imaging camera with low-cost uncooled microbolometer IR sensors. In this example, for characteristic peak heating rates of 1 Kelvin per second (K/s), ten heating patterns may be measured each second with a signal-to-noise ratio greater than 1 and an overall load temperature rise of less than or equal to 1 Kelvin (K). The heat deposition rate may be calculated as:

(36) $\text{Heatdeposition[Kelivn / second]} = \frac{\text{Temperature2 - Temperature1}}{t_2 - t_1}$ (Equation7)

(37) Equation 7, as demonstrated, is a spatially varying function throughout the load and on the surface of the load. If the heating patterns vary substantially as a function of the control parameters being varied, the overall temperature rise of the load may be slower than 1 K/s due to the "hot spot" of the directed heating moving throughout the food during the measurement process. In practice, the number of maps measured may be a function of the noise equivalent temperature difference (NETD) of the measurement device, the total time allowed for the FPTI and/or AFPTI measurement, and the maximum acceptable temperature rise.

(38) As previously discussed, FPTI and/or AFPTI yield measurements of spatially dependent heating of an object arising from a given set of control parameters. This may allow for the prediction of a future temperature profile of the load based upon the current temperature profile of the load and the chosen control parameters for subsequent heating of the load. Although the above descriptions of FPTI and/or AFPTI imply that individual heating patterns may be measured prior to the principal heating or cooking sequence, it is understood that knowledge of the heating patterns may be updated at any time the electromagnetic device (e.g., cooking appliance **102**) applies heat with a known set of control parameters. In particular embodiments, it may be advantageous to update knowledge of the heating maps during the main heating sequence to obtain an optimal signal-to-noise ratio. Equation 7 may be rewritten as the following vector equation:

(39) $K(p_z) = \frac{T_2 - T_1}{t_2 - t_1}$ (Equation8)

(40) In Equation 8, T.sub.1 is the initial temperature map and T.sub.2 is the final temperature map, each of which are represented as a two-dimensional vector of pixels T.sub.ij. Similarly, K is represented as a two-dimensional vector of heating rates K.sub.ij depending on vector p.sub.z, which describes the control parameter combinations (such as, for example, microwave frequency and/or the position of the mode stirrer) for the particular parameter combination z applied during the heating between times t.sub.1 and t.sub.2.

(41) FIG. **3** demonstrates example diagram **300** depicting heating maps. As an example and not by way of limitation, heat map **310** represents a temperature map T.sub.2, where temperature was measured at a later time t.sub.2. Heat map **310** may be plotted on a range of 0 to 25 degrees Celsius (° C.). In this example, heat map **320**, representing a temperature map T.sub.2, where temperature is measured at an earlier time t.sub.1, may be subtracted from heat map **310**, resulting in heat map **330**. Heat map **330** represents a heat map difference T.sub.2−T.sub.1, wherein the difference in temperature is plotted on a range of 0.0 to 4.0 K. In this example, heat map **340** may represent a heat map reflecting the differential

(42) $\frac{T_2 - T_1}{t_2 - t_1}$,

plotted on a range of 0.00 to 2.00 K/s. Finally, heat map **350** represents the FPTI heat map after performing optional post-processing steps to smooth, denoise, etc., plotted on a range of 0.00 to 2.00 K/s.

(43) FIG. **4** illustrates an example diagram **400** of calculating an optimal sequence of heating patterns to achieve a target temperature profile. As an example and not by way of limitation, as illustrated in FIG. **4**, the load disposed inside the cavity may have the starting temperature profile **402**, in which the left half has initial temperature profile T.sub.1, and the right half has an initial temperature profile T.sub.2, wherein temperature profile T.sub.2>T.sub.1. In particular embodiments, once the set of achievable heating patterns has been predicted or measured, an electromagnetic device (e.g., cooking appliance **102**) may then utilize one or more processors **104** to calculate the optimal sequence of control parameters that will yield heating patterns whose sum may achieve a target temperature profile. As an example and not by way of limitation, as illustrated in FIG. **4**, the target temperature profile for the load disposed inside the cavity may be a desired final temperature profile **404**, in which a first third has a final temperature profile T.sub.3, a second third has a final temperature profile T.sub.4, and a final third has a final temperature profile T.sub.5, wherein temperature profile T.sub.5>T.sub.4>T.sub.3. In particular embodiments, in order to achieve a desired final temperature profile **404** from the starting temperature profile **402**, the cooking appliance **102** may generally impose a sequential series of distinct heating patterns **406**, each arising from a different combination of control parameters. The net effect is the desired temperature rise, as illustrated by the optimum sequence and final temperature profile **408**, which reproduces the desired final temperature profile **404** as closely as possible. This is encapsulated in the following equation. Choose optimal t.sub.i such that:

$$\Sigma.\text{sub}.i \, t.\text{sub}.i \, \Delta T(p.\text{sub}.i) = (T.\text{sub}.\text{desired} - T.\text{sub}.\text{actual}) \qquad \text{(Equation 9)}.$$

(44) In Equation 9, (T.sub.desired−T.sub.actual) is the desired temperature rise map (essentially, a two-dimensional image), ΔT (p.sub.i) are the temperature increase maps for given parameter combinations p.sub.i, and t.sub.i are the times spent heating for each of those combinations. In particular embodiments, no single choice of control parameters may produce the desired temperature profile result, and thus the present embodiments include calculating the correct combination of heating patterns to direct to the load disposed inside the cavity of an electromagnetic device (e.g., cooking appliance **102**) such that the cumulative temperature rise results in the desired temperature profile or the best approximation thereof. Since an electromagnetic device may only add heat and not take heat away, the heating times t.sub.i for the patterns used in the series may all be non-negative. Thus, if the individual heating patterns ΔT(p.sub.i) are known for all possible permutations of control parameters, the non-negative parameters may be solved for by an optimization algorithm, such as non-negative least squares (NNLS). In particular embodiments, constant or temperature-dependent cooling rates of the load may be measured or estimated, and the heating patterns can be corrected for cooling effects to yield better accuracy in the prediction of temperature rise.

(45) In particular embodiments, a two-step process may be implemented for providing two-dimensional heat deposition maps. An optional compression of the heating pattern data via an image decomposition algorithm such as nonnegative matrix factorization may be utilized. This may serve to represent the set of potential heating patterns in a compact subspace and speed up computation. Subsequent calculation of a weighted series of heating patterns via a process such as, nonnegative least squares that best matches the heating profile may be utilized to achieve the target temperature map. In particular embodiments, nonnegative matrix factorization (NNMF) may include an algorithm to deconstruct a set of images as a nonnegative combination of nonnegative basis images, and may be represented mathematically as:

custom character=custom character×custom character   (Equation 10)

(46) In Equation 10, custom character is the reconstructed approximation of the original image set, custom character is a weighting matrix, and custom character is the set of basis images. Thus, Equation 10 may be utilized to generate heating maps for plausible food geometries and dielectric properties, in which NNMF may represent the full diversity of possible heating patterns within a very low-dimensional basis subspace.

(47) FIG. **5** illustrates an example system diagram **500** for providing a temperature profile-based cooking appliance **102**. As illustrated, load **510** is placed inside cooking appliance **102**. In particular embodiments, the load **510** may include one or more objects. In particular embodiments, cooking appliance **102** may be operated deterministically by controller **520** and one or more heating control elements **530** may be instructed by the controller **520** to perform mechanical and/or electronic means of modulating the standing-wave pattern with respect to the load **510** within the cavity of cooking appliance **102**. In particular embodiments, the desired temperature profile with respect to the load **510** and prior knowledge of the relationship between particular system control parameters and heat deposition with respect to the

load **510** may be stored by memory **106** of cooking appliance **102**. In particular embodiments, cooking appliance **102** may retrieve, via network interface **116**, data corresponding to the relationship between one or more system control parameters and heat deposition with respect to the load **510** from one or more datastores, databases, and/or other suitable method of obtaining prior heat maps with respect to the particular load **510**.

(48) In particular embodiments, heating control elements **530** may include control parameters such as RF frequency, phase, power, deterministically controlled turntable, mode stirrer positions, or any other mechanical or electronic means of modulating the standing-wave pattern within the cavity. As an example and not by way of limitation, for a toaster or broiler, heating control elements **530** may be individually controlled heat emitter powers. The one or more heating control elements **530** may be instructed by controller **520** to emit electromagnetic radiation into the cavity based on one or more sequences of control parameters to achieve a target spatial heating rate within the load **510** until a target temperature profile is achieved.

(49) In particular embodiments, detector **540** (e.g., an infrared (IR) camera, thermal camera) may image and/or measure the temperature profile of the load **510** with FPTI and/or AFPTI by directing a plurality of short-duration heating pulses at load **510** and performing prompt spatial thermometry to detect temperature increments in the load **510** before, during, and after heating, thereby generating heating maps. Based on these heating pattern measurements, controller **520** may calculate one or more sequences of control parameters to steer the heating pattern of load **510** towards a target temperature profile, as stored by controller **520**. In particular embodiments, the electromagnetic device (e.g., cooking appliance **102**) may generate updated sequences of control parameter configurations based on the spatial heating rate within the load **510** as indicated by the one or more heating maps. Based on measurements of the current temperature profile of the load **510** and in conjunction with previously measured heating maps stored by controller **520**, the controller **520** may calculate a sequence of control parameters and dwell times via an optimization algorithm, such as non-negative least squares (NNLS). The cooking appliance **102** may then apply heat at the prescribed dwell time for each combination of control parameters until the load **510** achieves the desired final temperature profile.

(50) In particular embodiments, for controller **520** to determine a heating control algorithm, the controller **520** may retrieve one or more data sets of heating patterns that have been previously measured by selecting various control parameter configurations and measure the current temperature profile of the load **510** and compare the current temperature profile load to the target temperature profile as specified by the user. As an example and not by way of limitation, the control parameter configurations may include one or more of a duration for applying the control parameter configuration, a radiation intensity, a radiation frequency, a radiation amplitude, a radiation phase, a radiation phase shift, a load rotation, a load translation, a mode stirrer configuration, etc. Although this disclosure discusses the previously mentioned examples of control parameter configurations, this disclosure contemplates any suitable control parameters and control parameter configurations. In particular embodiments, the controller **520** of cooking appliance **102** may calculate an optimal weighted sequence of control parameter configurations that may result in the target temperature profile. As an example and not by way of limitation, the controller **520** may set individual control parameters at a calculated duration of time before proceeding to implementing the next set of control parameters chosen by the control algorithm. In particular embodiments, the NNLS control algorithm may solve the following equation:

(51) $\underset{t_i}{\text{argmin}}$ .Math. $T_{\text{target}} - T_{\text{act}}$ - .Math.$_i$ $t_i K(p_i)$ .Math.   (Equation11)

(52) In Equation 11, T.sub.target(T.sub.act) represents the desired or target temperature profile, p.sub.i represents a vector representing the i.sup.th set of control parameters, K(p.sub.i) represents the heat rise map resulting from control parameter vector p.sub.i, t.sub.i represents the time the system spends heating the load at the i.sup.th set of control parameters, and |·| denotes the Euclidean norm calculated over the boundary or volume of the load. In particular embodiments, the first output of the heating algorithm is the resulting sequence of t.sub.i values (represented by vector t).

(53) In particular embodiments, the NNLS regression may determine weights for the heating maps associated with the control parameter combinations. The general form of the NNLS may be expressed by the following:

(54) $\underset{t_i}{\text{argmin}}$ .Math. At $- y$ .Math. $_2$, $t_i \geq 0 \forall i$ (Equation12)

(55) In Equation 12, matrix A represents the set of known heating maps in units of temperature rise per second for the different control parameters, as reduced from multiple dimensions into a 2D matrix. Vector y represents the heat map depicting the total temperature increase to bring the load from its current temperature profile to the desired one. Similarly, vector y is converted to a 1-D vector according to the same ordering as above. In Equation 12, t to be determined is the set of weights to be applied to each of these control parameter combinations. In Equation 11, each component would be equivalent to t.sub.i with units of seconds (i.e., dwell time at each setting). As an example and not by way of limitation, some entries of t may be zero, but all values of t must be non-negative. In particular embodiments, non-negative least chi-square minimization may be used to achieve similar results while taking into account knowledge of uncertainty in the temperature or heating maps.

(56) In particular embodiments, controller **520** of cooking appliance **102** may retrieve one or more previously recorded data sets of temperature rise profiles as a function of system control parameters and construct a two-dimensional (2D) data matrix by row-ordering the images as vector and concatenating the vectors along a second dimension that covers all control parameter permutations. In particular embodiments, controller **520** may separately save the mapping which indicates the correlation between each row in the **2D** matrix and the corresponding control parameter combination.

(57) In particular embodiments, this sequence may be ordered or truncated according the implementation of further closed-loop control of the system. As an example and not by way of limitation, different control parameters and sequences of control parameters may be applied in any order, or, alternatively, sorted to anticipate non-commutative effects such as cooling or thermal diffusion. As cooking appliance **102** can only add heat via control of one or more heating control elements **530** and not take away heat, the algorithm deployed by controller **520** is fundamentally non-negative. As a result, dwell times t are strictly non-negative. As an example and not by way of limitation, controller **520** may elect to order the sequence of control parameter combinations so as to minimize the time spend switching between subsequent configurations.

(58) FIG. **6** illustrates an example diagram **600** of a sequence of heating maps **610** and corresponding array **620**. As demonstrated in FIG. **6**, the sequence of heating maps **610** may be represented as images measuring 121×121 pixels, one image for each control parameter combination. In this example, the sequence of heating maps **610** were calculated for a solid-state RF oven as a function of twelve load rotations, three emitter frequencies, twelve emitter phases, and three vertical translations and transformed into 2D matrix **630** with 1296 rows (as a result of multiplying the control parameters 12×3×12×3) and 14,641 columns (121×121). As the control parameters are likely to be multidimensional, the sequence of heating maps may be two or three-dimensional, requiring the images of the heating maps to be ordered into a one-dimensional vector and then concatenated into a 2D matrix, as demonstrated by 2D matrix **630**. In practice, there may be multiple combinations of control parameter sequences that yield a similar result.

(59) FIG. **7** illustrates an example workflow diagram **700** depicting a technique for implementing an open-loop heating control algorithm for a cooking appliance **102**. In particular embodiments, the workflow diagram may begin at step **710**, wherein cooking appliance **102** may retrieve one or more previously recorded data sets of heating maps. As an example and not by way of limitation, cooking appliance **102** may retrieve the previously recorded datasets of heating maps by from memory **106** of the cooking appliance **102**. As another example and not by way of limitation, cooking appliance **102** may retrieve, via network interface **116**, the previously recorded datasets of heating maps from one or more datastores, databases, and/or other suitable method of obtaining prior heat maps with respect to the particular load **510**. In particular embodiments, at step **720**, cooking appliance **102** may retrieve a previously stored target temperature profile, wherein the target temperature profiles may be stored locally in memory **106** of cooking appliance, or retrieved by network interface **116** from one or more datastores, databases, and/or other external storage. In particular embodiments, the user may define a target temperature profile corresponding to the particular load **510** through a user interface of cooking appliance **102**.

(60) At step **730**, the electromagnetic device (e.g., cooking appliance **102**) may generate a current temperature map of the load **510** disposed inside the cavity. As an example and not by way of limitation, the electromagnetic device may perform the step in step **730** using detector **540** or any suitable thermal imagers to perform prompt spatial thermometry to determine the current temperature profile of the load

510. At step **740**, the heating gap may be determined by subtracting the current temperature of load **510** as measured in step **730** from the target temperature profile of step **720**. As used herein "heating gap" may refer to the difference in temperature between the target temperature profile of a particular load **510** and the measured current temperature of the particular load **510**.

(61) In particular embodiments, at step **750**, controller **520** of cooking appliance **102** may perform a NNLS regression to calculate the optimal weight vector t, as disclosed by Equations 11 and 12. As an example and not by way of limitation, based on the control parameter mapping in this basis, controller **520** may construct a sequence of control parameter combinations, wherein each control parameter combination is associated with a corresponding calculated dwell time t.sub.i. In particular embodiments, in response to step **750**, the heating control algorithm may sort the resulting sequence of control parameters according to one or more criteria, as in step **760**. As an example and not by way of limitation, the heating algorithm may sort the sequence of control parameters to start with heat maps that close the heating gap as defined in step **740** the fastest. As another example and not by way of limitation, the heating algorithm may start with applying control parameters according to data from the previously stored heat maps, indicating a particular heat map that applies the most heat to a region of the load **510** determined to be difficult to heat. In particular embodiments, at step **770**, the controller **520** may instruct one or more heating control elements **530** to apply heat to the load in accordance with the first set of control parameters p.sub.i indicated by the ordered sequence of step **760**. In particular embodiments, the cooking appliance **102** may maintain heating for the calculated dwell time t.sub.i. As an example and not by way of limitation, cooking appliance **102** may proceed to step through all non-zero dwell times t.sub.i in the sequence.

(62) FIG. **8** illustrates an example workflow diagram **800** depicting a technique for achieving a target temperature profile through a closed-loop heating control algorithm. In particular embodiments, by adding closed-loop control to the heating algorithm, the cooking appliance **102** may account for nonlinearities in the temperature rise and/or fall of the load **510** between sequential heating steps. In particular embodiments, cooling may be approximated by Newton's Law of Cooling:

(63)

$$\text{Heatdeposition}(T_{\text{Object}}, T_{\text{Ambient}})[\text{Kelvin / second}] = \frac{\text{Temperature2 - Temperature1}}{t_2 - t_1} - k(T_{\text{Object}} - T_{\text{Ambient}}) \quad \text{(Equation13)}$$

(64) In Equation 13, k is a constant that may be estimated from prior knowledge. The result of Equation 13 may be a nonlinear rise or fall in load **510** temperature as a function of time, which may result in inaccuracies between the predicted and achieved temperatures. Thus, by breaking the heating process into multiple steps and recalculating the optimal parameter sequence iteratively based upon the actual achieved temperature profile at the end of each step, cooking appliance **102** my approximate the cooling effects as linear for small increments to achieve closer accuracy in the final desired temperature profile. Further, a NNLS closed-loop control heating algorithm may compensate for the fact that many of the heating maps spanning the full parameter space may be unknown or imperfectly known prior to initiation of the initial heating sequence. In addition to generating an updated time sequence of control parameters periodically, the closed-loop heating control algorithm may also allow the cooking appliance **102** to update the originally measured heating maps with the new heating map measured every time a new combination of control parameters is applied.

(65) In particular embodiments, the workflow diagram may begin at step **710**, wherein one or more processors **104** of cooking appliance **102** may retrieve one or more previously recorded data sets of heating maps. As an example and not by way of limitation, cooking appliance **102** may retrieve the previously recorded datasets of heating maps by from memory **106** of the cooking appliance **102**. As another example and not by way of limitation, cooking appliance **102** may retrieve, via network interface **116**, the previously recorded datasets of heating maps from one or more datastores, databases, and/or other suitable method of obtaining prior heat maps with respect to the particular load **510**. In particular embodiments, at step **720**, cooking appliance **102** may retrieve a previously stored target temperature profile, wherein the target temperature profiles may be stored locally in memory **106** of cooking appliance, or retrieved by network interface **116** from one or more datastores, databases, and/or other external storage. In particular embodiments, the user may define a target temperature profile corresponding to the particular load **510** through a user interface of cooking appliance **102**.

(66) In particular embodiments, at step **730**, the electromagnetic device (e.g., cooking appliance **102**) may generate a current temperature map of the load **510** disposed inside the cavity. As an example and not by

way of limitation, the electromagnetic device may perform the step in step **730** using detector **540** or any suitable thermal imagers to perform prompt spatial thermometry to determine the current temperature profile of the load **510**. At step **740**, the heating gap may be determined by subtracting the current temperature of load **510** as measured in step **730** from the target temperature profile of step **720**. In step **750**, the heating algorithm of cooking appliance **102** may perform a non-negative least squares regression, as demonstrated in Equations 11 and 12. As an example and not by way of limitation, the heating algorithm may calculate the optimal weight vector t by NNLS, and based upon the control parameter mapping, construct a sequence of control parameters where each control parameter is associated with its respective calculated dwell time $t.sub.i$.

(67) In particular embodiments, in response to step **750**, the heating algorithm may sort the resulting sequence of control parameters according to one or more criteria, as disclosed by step **760**. As an example and not by way of limitation, the heating algorithm may determine one or more emission configurations and one or more dwell times during which electromagnetic radiation may be applied according to the one or more emission configurations. Further, the heating control algorithm may determine an order in which the one or more emission configurations and the one or more dwell times of the sequence of control parameter configurations are to be applied. As an example and not by limitation, the order may be determined by one or more criteria, wherein emitting electromagnetic radiation into the cavity of cooking appliance **102** is determined based on the order of the sequence of control parameter configurations. As an example and not by way of limitation, the heating algorithm may sort the sequence of control parameters in step **760** to start with heat maps that closes the temperature gap the fastest. As another example and not by way of limitation, the heating algorithm may start with the heat map that applies the most heat to the region of the load **510** determined to be difficult to heat. In particular embodiments, each emission configuration may comprise a radiation intensity of radiation to be emitted by one or more heating control elements **530** of cooking appliance **102**. As an example and not by way of limitation, controller **520** of cooking appliance **102** may be instructed to determine the radiation intensity for each control parameter configuration and scale the dwell times by the determined radiation intensities, as further discussed in FIG. **9**. In particular embodiments, the heating algorithm may automatically predict the total time it may take for the emission of electromagnetic radiation to yield the required temperature rise to achieve the target temperature profile of the load. In response to predicting the total time for the emission of electromagnetic radiation to yield the required temperature rise to achieve the target temperature profile of the load, the electromagnetic device may scale the radiation intensity of the one or more emission configurations to yield a specific heating time.

(68) In particular embodiments, in response to emitting electromagnetic radiation into the cavity, the electromagnetic device may determine a second temperature profile of the load **510**, wherein NNLS may be used to calculate dwell times corresponding to the control parameter configurations so as to minimize the squared error between the calculated temperature profile of the load after the electromagnetic radiation is emitted into the cavity for the calculated sequence of control parameters of step **810** and the target temperature profile as retrieved in step **720**. As an example and not by way of limitation, the electromagnetic device may use an asymmetric cost function to calculate the dwell times corresponding to the combination of control parameters in step **810**. For example, the asymmetric cost function may penalize over-heating and/or under-heating when reducing error between the target temperature profile as retrieved in step **720** and the calculated second temperature profile of the load **510** after electromagnetic radiation is emitted into the cavity of the electromagnetic device. In particular embodiments, radiation intensity may be recalculated and dwell times may be rescaled to achieve a target sum of dwell times.

(69) In particular embodiments, at step **810**, the electromagnetic device may apply a first combination of control parameters as previously determined in step **760**. As an example and not by way of limitation, the controller **520** may instruct one or more heating control elements **530** to emit heat into the cavity of the cooking device **102** for some time, after which the temperature of load **510** may be remeasured, and the heating maps (e.g., updated current temperature profile of load **510**) may be updated, as in step **820**. In particular embodiments, after the heating maps are updated in step **820**, the heating control algorithm may reperform steps **710** (e.g., retrieving previously recorded data sets of heating maps), **720** (e.g., determining a target temperature profile), and **730** (e.g., measuring the current temperature profile of load **510**). As displayed in FIG. **8**, the heating algorithm may continue to perform the closed-loop heating process by reperforming the steps outlined in steps **750**, **760**, **810**, and **820** until cooking appliance **102** determines

load **510** has achieved a sufficiently similar temperature profile as compared to the target temperature profile in step **720**. It is understood that each updated heating map as generated in step **820** may be stored with the plurality of previously recorded heating maps, as retrieved by cooking appliance **102** in step **710**. In particular embodiments, after the updated current temperature profile of the load is generated in step **820**, the electromagnetic device may calculate a difference between the updated current temperature profile of the load **510**, as in step **820**, and the target temperature profile of the load **510**, as retrieved in step **720**. As an example and not by way of limitation, the heating control algorithm of cooking appliance **102** may determine a second sequence of control parameter configurations to apply to achieve the termination criteria of step **830**, wherein in response to achieving the termination criteria with respect to the load **510**, the cooking appliance **102** may suspend emission of electromagnetic radiation into the cavity by the one or more heating control elements **530**.

(70) In particular embodiments, at step **830**, the heating algorithm may terminate when one or more termination criteria are met. As an example and not by way of limitation, NNLS may provide a natural termination criteria in that the calculated dwell times will reach zero if adding heat to the system will only increase the discrepancy between the measured current temperature in step **730** and the target temperature profile in step **720**. As another example and not by way of limitation, the heating algorithm may terminate the heating process in step **830** if any portion of the load **510** exceeds a threshold temperature. Although this disclosure contemplates the abovementioned termination criterion, this disclosure contemplates any suitable termination criterion.

(71) FIG. **9** illustrates an example workflow diagram **900** depicting a technique for achieving a target temperature profile through an adaptive power control heating algorithm. As discussed in FIG. **8**, closed-loop control of the heating algorithm requires a termination criterion. As used herein, "termination criterion" may refer to one or more criterion that when met, instructs the heating control algorithm to terminate. In particular embodiments, the termination criterion may be based on a comparison between the current temperature profile of the load **510** and the target temperature profile of the load **510**. For example, if the target temperature profile of the beef steak in FIGS. **2A-2D** (e.g., load **510**) is 62° C., the heating control algorithm may perform closed-loop control of the system until the beef steak reaches the target temperature profile of 62° C., upon which the heating algorithm may instruct heating control element **530** to terminate the emission of heat (e.g., radiation). In this example, where the termination criterion requires that the heating gap be 0° C., the control process may never terminate as it is generally not possible to achieve the target temperature profile to exact precision. In this case, the heating time may be very long and unpredictable. However, if the termination criterion is less strict, such as for example a heating discrepancy of <10° C. for all points of the load **510**, the heating time may be more predictable.

(72) In particular embodiments, an estimate of the remaining heating time may be derived in each iteration of the closed-loop control heating algorithm by summing the dwell times calculated by NNLS. In this example, however, the estimates of remaining heating time may fluctuate strongly between iterations when each iteration provides a dramatically different mean heating rate (e.g., a lower heating rate may require a longer dwell time to have an equivalent impact on the temperature profile as a higher heating rate). In particular embodiments, Adaptive Power Control (APC) may be employed to determine an accurate estimate of remaining heating time. In this example, APC may use one or more control parameters common to all cooking appliances **102** as an independent control parameter that when adjusted, achieves the pre-determined target heating time. As an example and not by way of limitation, the power or intensity of the heating source (e.g., heating control elements **530**) may be an example of an independent control parameter APC could adjust. In this example, increasing or decreasing the power or intensity of the heating control elements **530** may speed up or slow down the heating process. As an example and not by way of limitation, the heating rate may scale proportionally with the power of the heating source, such that an N-fold increase in the power may result in a uniform N-fold decrease in all weights calculated by the NNLS heating algorithm. In this way, APC may allow the system to ensure that the NNLS-predicted dwell times sum to the allotted remaining time in each iteration of the closed-loop algorithm. As a result, the cooking appliance **102** may adapt the overall heating power in conjunction with the elected heating patterns to achieve the target temperature profile of load **510** in a specified amount of time. As an example and not by way of limitation, a user may specify the amount of time allowed for cooking appliance **102** to achieve the target temperature profile of load **510**.

(73) In particular embodiments, the method of Adaptive Power Control (APC) may begin at step **710**

where one or more processors **104** of the electronic device (e.g., cooking appliance **102**) may instruct the electronic device to retrieve both one or more previously recorded data sets of heating maps for the possible control parameter combinations, excluding the total power or intensity of one or more heat sources, as input for the heating algorithm. As an example and not by way of limitation, cooking appliance **102** may retrieve the previously recorded datasets of heating maps by from memory **106** of the cooking appliance **102**. As another example and not by way of limitation, cooking appliance **102** may retrieve, via network interface **116**, the previously recorded datasets of heating maps from one or more datastores, databases, and/or other suitable method of obtaining prior heat maps with respect to the particular load **510**. In particular embodiments, at step **720**, cooking appliance **102** may retrieve a previously stored target temperature profile, wherein the target temperature profiles may be stored locally in memory **106** of cooking appliance, or retrieved by network interface **116** from one or more datastores, databases, and/or other external storage. In particular embodiments, the user may define a target temperature profile corresponding to the particular load **510** through a user interface of cooking appliance **102**.

(74) In particular embodiments, at step **730**, the electromagnetic device (e.g., cooking appliance **102**) may generate a current temperature map of the load **510** disposed inside the cavity. As an example and not by way of limitation, the electromagnetic device may perform the step in step **730** using detector **540** or any suitable thermal imagers to perform prompt spatial thermometry to determine the current temperature profile of the load **510**. At step **740**, the heating gap may be determined by subtracting the current temperature of load **510** as measured in step **730** from the target temperature profile of step **720**. In step **750**, the heating algorithm of cooking appliance **102** may perform a non-negative least squares regression, as demonstrated in Equations 11 and 12. As an example and not by way of limitation, the heating algorithm may calculate the optimal weight vector t by NNLS, and based upon the control parameter mapping, construct a sequence of control parameters where each control parameter is associated with its respective calculated dwell time t.sub.i.

(75) In particular embodiments, using the sum of all calculated dwell times t.sub.i, the heating algorithm may calculate the power factor, by which the present set of heating maps must be scaled to in order to achieve the target heating time, at step **910**. The power factor may be calculated by the following equation:

(76) 0 $\quad \text{PowerFactor} = \frac{.\text{Math.}_{i=0}^{i_{\text{Max}}} t_i}{\text{Targetheatingtime}}$ (Equation14)

(77) At step **920**, the heating algorithm may scale the applied total power (e.g., independent APC control parameter) by the power factor calculated in step **910**. For example, if the NNLS heating algorithm determines that the sum of all predicted dwell times is larger than the target heating time, the heating algorithm may adapt the overall heating power (e.g., increase the applied power) in conjunction with the elected heating patterns to achieve the target temperature profile of load **510** in a specified amount of time. As an example and not by way of limitation, the independent APC control parameter may be the net power applied to the load.

(78) In particular embodiments, at step **930**, the heating control algorithm may sort the resulting sequence of control parameters according to one or more criteria. As an example and not by way of limitation, the heating algorithm may sort the sequence of control parameters to start with heat maps that closes the heating gap as determined in step **740** the fastest. As another example and not by way of limitation, the heating algorithm may start with the map that applies the most heat to the region of the load **510** determined to be difficult to heat.

(79) At step **940**, the heating control algorithm may instruct the electromagnetic device to scale power on the one or more heating control elements **530** in accordance with the power factor calculated at step **910** and apply heat for the first one or more control parameter combinations. In response to applying the first one or more control parameter combinations, the heating algorithm may instruct the electromagnetic device to generate updated heating maps at step **820**. In particular embodiments, after performing the functions as in step **940**, a target heating time may be calculated in step **950**, wherein the target heating time, in combination with the previously recorded data sets of heating maps in step **710** may be used as input for step **910**, of calculating the power factor.

(80) In particular embodiments, after the heating maps are updated in step **820**, the heating control algorithm may reperform steps **710** (e.g., retrieving previously recorded data sets of heating maps), **720** (e.g., determining a target temperature profile), and **730** (e.g., measuring the current temperature profile of load **510**). In this way, the target heating time may be updated according to the elapsed time. Active

monitoring of the temperature rise during heating through the closed-loop control of steps **710**, **720**, **730**, **740**, **750**, **910**, **920**, **930**, **940**, **950**, and **820** results in accurate, real-time data sets for use in the next iteration of the closed-loop algorithm.

(81) As previously discussed in FIG. **8**, the heating algorithm may finish when termination criterion is met, as in step **830**. As an example and not by way of limitation, NNLS may provide a natural termination criteria in that the calculated dwell times will reach zero if adding heat to the system will only increase the discrepancy between the measured and the target temperature profiles. As another example and not by way of limitation, the heating algorithm may terminate the heating process if any portion of the load **510** exceeds a threshold temperature. Although this disclosure contemplates the abovementioned termination criterion, this disclosure contemplates any suitable termination criterion.

(82) FIG. **10** illustrates an example workflow diagram **1000** depicting a technique for achieving a target temperature profile through a tailored cost function algorithm. In particular embodiments, diagram **1000** may begin at step **710** where one or more processors **104** of the electronic device (e.g., cooking appliance **102**) may instruct the electronic device to retrieve both one or more previously recorded data sets of heating maps for the possible control parameter combinations, excluding the total power or intensity of one or more heat sources, as input for the heating algorithm. As an example and not by way of limitation, cooking appliance **102** may retrieve the previously recorded datasets of heating maps by from memory **106** of the cooking appliance **102**. As another example and not by way of limitation, cooking appliance **102** may retrieve, via network interface **116**, the previously recorded datasets of heating maps from one or more datastores, databases, and/or other suitable method of obtaining prior heat maps with respect to the particular load **510**. In particular embodiments, at step **720**, cooking appliance **102** may retrieve a previously stored target temperature profile, wherein the target temperature profiles may be stored locally in memory **106** of cooking appliance, or retrieved by network interface **116** from one or more datastores, databases, and/or other external storage. In particular embodiments, the user may define a target temperature profile corresponding to the particular load **510** through a user interface of cooking appliance **102**.

(83) In particular embodiments, at step **730**, the electromagnetic device (e.g., cooking appliance **102**) may generate a current temperature map of the load **510** disposed inside the cavity. As an example and not by way of limitation, the electromagnetic device may perform the step in step **730** using detector **540** or any suitable thermal imagers to perform prompt spatial thermometry to determine the current temperature profile of the load **510**. At step **740**, the heating gap may be determined by subtracting the current temperature of load **510** as measured in step **730** from the target temperature profile of step **720**.

(84) In particular embodiments, at step **1010**, the heating control algorithm may perform gradient-based optimization, which may or may not include NNLS. As an example and not by way of limitation, gradient-based optimization may construct a sequence of control parameters where each control parameter is associated with its respective calculated dwell time t.sub.i. Because the heating control algorithm may not indicate an order in which the resulting sequence of control parameters should be applied, the heating control algorithm may sort the sequence of control parameters according to one or more criteria, as in step **930**. As an example and not by way of limitation, the gradient-based heating algorithm may sort the sequence of control parameters to start with heat maps that closes the heating gap as determined in step **740** the fastest. As another example and not by way of limitation, the heating algorithm may start with the map that applies the most heat to the region of the load **510** determined to be difficult to heat. In particular embodiments, at step **1020**, a user may provide input as to a specified heating time and/or a desired temperature change through a user-interface of cooking appliance **102**. Based on the user-input in step **1020**, a cost function may be adjusted in step **1030**. As used herein, "cost function" may refer to a function used in the heating control algorithm to penalize particular properties and/or enforce sparsity in the output sequence. As an example and not by way of limitation, the cost function used in the heating control algorithm may be adjusted to penalize over-heating or under-heating of load **510**. As another example and not by way of limitation, the cost function used in the heating control algorithm may be used to enforce sparsity in the output sequence by minimizing the number of different control parameter configurations used by the heating control algorithm. In particular embodiments, the cost function may be the squared difference between the target temperature and measured current temperature, summed over a region of interest, wherein NNLS may be a method for minimizing this specific cost function.

(85) In particular embodiments, in response to the sequence of control parameters being sorted according

to a criteria, as in step **930**, the heating control algorithm may apply a first combination of control parameters in step **1040**. As an example and not by way of limitation, at step **1040**, the heating control algorithm may instruct the one or more heating control elements **530** of the electromagnetic device to emit electromagnetic radiation and/or control one or more control parameters in line with the first combination of control parameters as determined by sorting the sequence of control parameters in step **930**. In response to applying the first combination of control parameters, the heating control algorithm may instruct the electromagnetic device to generate updated heating maps at step **820**. In particular embodiments, after the heating maps are updated in step **820**, the heating control algorithm may reperform steps **710** (e.g., retrieving previously recorded data sets of heating maps), **720** (e.g., determining a target temperature profile), and **730** (e.g., measuring the current temperature profile of load **510**. In this way, the target heating time may be updated according to the elapsed time. Active monitoring of the temperature rise during heating through the closed-loop control of steps **710**, **720**, **730**, **740**, **1010**, **1020**, **1030**, **930**, and **1040** results in accurate, real-time data sets for use in the next iteration of the closed-loop algorithm.

(86) In particular embodiments, a heating algorithm other than NNLS may be utilized, as NNLS penalizes positive and negative errors equally, which may not accurately reflect a user's preference. For example, delicate foods such as shellfish will suffer irreversible degradations in quality if overheated. As an example and not by way of limitation, a user may indicate that the food being heated is delicate and be presented with an option in the user interface of the electromagnetic device to accept slower heating. As another example and not by way of limitation, the user may be presented with an option in the user interface of the electromagnetic device to accept slightly under-heated regions in the final temperature profile of the load to avoid overheating. In these cases, it may be preferred to choose a cost function in the heating algorithm that is not symmetric in the sign of the temperature error. In particular embodiments, gradient-based optimization may calculate the derivative of the cost function with respect to the variable parameters and then incrementally update estimation of those parameters by iteratively following the gradient that minimizes the cost function. In this embodiment, the cost function of the heating algorithm may be modified to penalize over-heating or under-heating of the load **510**. As an example and not by way of limitation, these cost functions may be differentiable, and a gradient-based optimization approach may be used to calculate the resulting parameter sequence.

(87) As previously discussed, the heating times spent at the individual parameter combinations p_i is denoted by $t_i.fwdarw.t$. In particular embodiments, $C(t, T_{target}, T_{act})$ may denote the cost function for the particular sequence, including a positive cost for deviation of the instantaneous actual temperature T_{act} from T_{target}, and load **510** may be assumed to begin at temperature T_0. In this example, it is understood that all temperatures may be spatially varying over the load, and the cost function is summed over all load positions. In this example, the final temperature profile at the end of the sequence is given by $T_{final}=T_0+\Sigma_i t_i K(p_i)$. For simplicity, the final temperature metric may be defined as the following:

(88) $$z = \frac{T_{final} - T_{target}}{T_0 - T_{target}} \quad \text{(Equation 15)}$$

(89) In Equation 15, the final temperature metric may be spatially summed over the load **510**. In particular embodiments, C may be added to the cost function C_z, in which C represents an added penalty for overheating, as represented by the following:

$C_z=\Theta(z)f_{+}(z)+\Theta(-z)f_{-}(z)$ (Equation 16)

(90) In Equation 16, f_{+} represents smooth polynomial functions of z for z<0 and z>0, and $\Theta(z)$ may represent the Heaviside function: $\Theta(z)=0$ for z<0 and 1 for z>0. Because $\Theta(z)$ is not differentiable, ultimately invalidating a gradient-based approach, $\Theta(z)$, by way of example may be replaced with the following sigmoid function:

$\sigma_k(z)=(1+e^{-2kz})^{-1}$ (Equation 17)

(91) Although this disclosure discusses the above sigmoid function, this disclosure contemplates any suitable smooth function to replace the above-mentioned Heaviside function. Equation 17 becomes $\Theta(z)$ in the limit that $k.fwdarw.\infty$. In this case, the derivative of the cost function with respect to z becomes:

$C_k'(z)=\sigma_k(z)[2k(1-\sigma_k(z))f_{+}(z)+f_{+}'(z)]+\sigma_k(-z)[2k(1-\sigma_k(-z))f_{-}(z)-f_{-}'(z)]$ (Equation 18)

(92) In particular embodiments, the cost function may be differentiated with respect to the sequence of dwell times t_i. As an example and not by way of limitation, methods such as gradient descent and/or

conjugate gradients may be used to determine an optimal sequence of control parameters. Although this disclosure discusses gradient descent and/or conjugate gradients for finding an optimal sequence, this disclosure contemplates any suitable method of determining an optimal sequence.

(93) FIG. **11** illustrates a diagram **1100** of example temperature profiles measured with different implementations of the heating control algorithm. Image **1110** demonstrates a typical temperature profile of a load **510** as measured for a standard cooking appliance **102** in the absence of a heating control algorithm, wherein no control parameter sequence was calculated or enacted. Image **1120** demonstrates results achieved by cooking appliance **102** when load **510** was heated according to a control parameter sequence as calculated by open-loop control of the heating control algorithm. Image **1130** demonstrates results achieved by cooking appliance **102** when load **510** was heated according to one or more control parameter sequences as calculated by closed-loop control of the heating control algorithm. Image **1140** demonstrates a user-specified target temperature profile. In this example, the user-specified target temperature profile is a homogenous temperature profile at 60° C. As demonstrated by the images of FIG. **11**, image **1130** most closely achieves the user-specified temperature profile of image **1140**.

(94) FIGS. **12**A-**12**B illustrate example diagrams **1200** and **1250**, depicting heating maps utilizing a temperature profile-based cooking appliance **102** with multiple loads **510**. For example, plate **1210** demonstrates three different foods, food **1220**, food **1230**, and food **1240**. The spatial deposition within each of foods **1220**, **1230**, and **1240** may vary for different control parameter configurations, as indicated in the corresponding heat maps of diagram **1200** as measured by FPTI and/or AFPTI. For example, each food **1220**, **1230**, **1240** may have a particular optimal final temperature profile and must be heated individually to a specific target temperature by the selection of an optimal sequence of control parameters by the heating control algorithm throughout the heating process. Example diagram **1250** of FIG. **12**B demonstrates the final temperature profile of plate **1210** showing different mean temperatures for each food **1220**, **1230**, and **1240**. In particular embodiments, each portion of the plate **1210** may be deterministically heated to a customized target temperature profile. Example diagrams **1200** and **1250** demonstrate active measurement of heating maps for each food **1220**, **1230**, and **1240** by deterministic control of system parameters to generate a user-specified heating pattern, wherein each food **1220**, **1230**, and **1240** may be heated to different target temperatures.

(95) FIGS. **13**A-**13**B illustrate example diagrams **1300** and **1360**, depicting an example workflow and an example user interface of a temperature profile-based cooking appliance **102**. In particular embodiments, the heating control algorithm may be combined with a user interface (UI) that allows the user to specify the desired temperature profile. As an example and not by way of limitation, the heating control algorithm and UI combination may create an ability to heat food to a user-specified result with minimal input and no need for the user to supervise or intervene during the cooking and/or heating process. For example, the UI may allow a user to define the desired outcome in terms of a temperature of load **510** or other qualitative measure of doneness of load **510**, rather than inputting estimates of a power level and heating time. In particular embodiments, cooking appliance **102** may provide a user with real-time information of the temperature profile of one or more loads **510** (e.g., thermal image and/or heat map) as well as quick access to the current measured temperature of the load **510**.

(96) In particular embodiments, the workflow of diagram **1300** may begin at step **1310**, where a user may add food (e.g., load **510**) into a cavity of the electromagnetic device (e.g., cooking appliance **102**), at step **1320**. In particular embodiments, the electromagnetic device may utilize computer vision to analyze the load **510** and display an image of the load **510** to a user via a user-interface of cooking appliance **102**. As an example and not by way of limitation, visible (e.g., RGB) images of load **510** may enable the system of cooking appliance **102** to differentiate between load **510** and a container, which is important for calculation of the heating control algorithm. The images may be displayed to a user on a UI (e.g., touch-enabled display) integrated within cooking appliance **102**, allowing a user to visualize the cooking process from the vantage point of an RGB camera. Although this disclosure discloses an RGB camera, this disclosure contemplates any suitable camera and/or optical sensor for imaging load **510**.

(97) In particular embodiments, at step **1340**, the load **510** may be identified from a database of previously stored images of various loads **510**, and display an image (e.g., visible and/or infrared-based thermal images) of the identified load **510** to a user via a UI integrated with cooking appliance **102**. In particular embodiments, at step **1340**, a target temperature profile of the identified load **510** may be recommended to the user via the UI integrated within cooking appliance **102**. As an example and not by way of limitation, a

thermal detector, thermal imager, and/or thermal camera may be installed on top of cooking appliance **102**, producing a heat map for display by the UI integrated within cooking appliance **102**. In particular embodiments, at step **1350**, the user may confirm a desired temperature profile via the UI of cooking appliance **102**. As an example and not by way of limitation, a temperature-based present may offer the user a "one-click user interaction," providing the user with an option to heat load **510** to their preferred target temperature profile without navigating through several steps in the UI of cooking appliance **102**. As an example, one-touch present buttons with a plurality of different temperature options may be displayed via a touch-enabled UI of cooking appliance **102** for user interaction. The desired temperature in step **1350** may become the target temperature profile as in step **720** of FIGS. **7**-**10**.

(98) In particular embodiments, diagram **1360** may display an example user interface (UI) of cooking appliance **102**. In particular embodiments, the UI of cooking appliance **102** may include module **1362**, displaying a current time for view by a user. In particular embodiments, UI of cooking appliance **102** may include module **1364**, displaying an image of the load **510** disposed inside the cavity of cooking appliance **102**. As an example and not by way of limitation, module **1364** may include a plurality of selectable cooking options, such as reheat, heat, warm, brown (e.g. lightly brown, darkly brown), beverage warming options (e.g., warm, hot, very hot), defrosting, etc., wherein a user may interact with the plurality of selectable cooking options via a touch-interface of cooking appliance **102**. In particular embodiments, the UI of cooking appliance **102** may include module **1366**, wherein an image of load **510** may be displayed along with a heat map (e.g., current temperature profile) of load **510**. As an example and not by way of limitation, module **1366** may display a current temperature of load **510**, where the current temperature may be updated in real-time throughout the heating process. As an example and not by way of limitation, module **1366** may include a selectable option to pause heating. As another example and not by way of limitation, module **1366** may include a selectable option to return to the interface of module **1364**.

(99) In particular embodiments, the UI of cooking appliance **102** may include module **1368**, wherein an image of load **510** may be displayed along with a heat map (e.g., current temperature profile) of load **510** and an indication of an amount of time left in the heating process. As an example and not by way of limitation, module **1368** may include a selectable option to pause or cancel heating. In particular embodiments, the UI of cooking appliance **102** may include module **1370**, where an image of load **510** may be displayed along with an indication that the heating process is complete.

(100) FIG. **14** illustrates a flow diagram **1400** of a method for achieving a user-specified temperature profile in a cooking appliance **102** through heating control algorithms. The method **1400** may be performed utilizing one or more electromagnetic devices (e.g., cooking appliance **102**) that may include hardware (e.g., a general purpose processor, a graphic processing unit (GPU), an application-specific integrated circuit (ASIC), a system-on-chip (SoC), a microcontroller, a field-programmable gate array (FPGA), a central processing unit (CPU), an application processor (AP), a visual processing unit (VPU), a neural processing unit (NPU), a neural decision processor (NDP), or any other processing device(s) that may be suitable for processing image data), software (e.g., instructions running/executing on one or more processors), firmware (e.g., microcode), or some combination thereof.

(101) In particular embodiments, the method **1400** may begin at block **1410** with the electromagnetic device (e.g., cooking appliance **102**) accessing a plurality of previously recorded heating maps corresponding to a load **510** disposed inside a cavity of the electromagnetic device. As an example and not by way of limitation, each heating map may indicate a temperature profile change of the load **510** as a function of one or more control parameter configurations. Cooking appliance **102** may access a plurality of previously recorded heating maps corresponding to a load **510** disposed inside a cavity of the electromagnetic device stored locally in memory **106** of cooking appliance **102** and/or retrieved by network interface **116** from one or more datastores, databases, and/or external storage locations.

(102) In particular embodiments, the method **1400** may continue at block **1430** with the electromagnetic device (e.g., cooking appliance **102**) generating a current temperature profile of the load **510** disposed inside the cavity of the electromagnetic device. As an example and not by way of limitation, the electromagnetic device may measure the current temperature of load **510** through the use of detector **540** or any suitable thermal imager to perform prompt spatial thermometry to determine the current temperature profile of the load. In particular embodiments, the method **1400** may continue at step **1440**, where the electromagnetic device may calculate a difference in temperature profiles between the current temperature profile of the load **510** (as generated in block **1430**) and the target temperature profile of the

load **510** (as retrieved in block **1420**). As an example and not by way of limitation, the difference in temperature profiles between the current profile of load **510** and the target temperature profile of load **510** may be referred to as a heating gap, wherein the heating gap may be determined by subtracting the current temperature of load **510** from the target temperature profile of load **510**.

(103) In particular embodiments, the method **1400** may continue at block **1450**, where the electromagnetic device may determine a first sequence of control parameter configurations to heat the load **510**. As an example and not by way of limitation, the first sequence of control parameter configurations to heat the load **510** may be based on a non-negative least squares regression to calculate an optimal weight vector t, as disclosed by Equations 11 and 12. In particular embodiments, controller **520** of cooking appliance **102** may construct a sequence of control parameter combinations, wherein each control parameter combination is associated with a corresponding calculated dwell time t.sub.i, and wherein the heating control algorithm may sort the resulting sequence of control parameters according to one or more criteria. In particular embodiments, the first sequence of control parameter configurations may contain one or more emission configurations and one or more dwell times between the one or more emission configurations. As an example and not by way of limitation, electromagnetic device may determine an order in which the one or more emission configurations and the one or more dwell times of the first sequence of control parameter configurations are to be applied. As another example and not by way of limitation, the order may be determined according one or more criteria, wherein emitting the electromagnetic radiation is based on the determined order.

(104) In particular embodiments, the method **1400** may continue at block **1460** with the electromagnetic device (e.g., cooking appliance **102**) emitting electromagnetic radiation into the cavity of the electromagnetic device based on the first sequence of control parameter configurations. Particular embodiments may repeat one or more steps of the method of FIG. **14**, where appropriate. Although this disclosure describes and illustrates particular steps of the method of FIG. **14** as occurring in a particular order, this disclosure contemplates any suitable steps of the method of FIG. **14** occurring in any suitable order. Moreover, although this disclosure describes and illustrates an example method for mapping heat deposition in a cooking appliance through fast pattern temperature imaging, including the particular steps of the method of FIG. **14**, this disclosure contemplates any suitable method for mapping heat deposition, including any suitable steps, which may include all, some, or none of the steps of the method of FIG. **14**, where appropriate. Furthermore, although this disclosure describes and illustrates particular components, devices, or systems carrying out particular steps of the method of FIG. **14**, this disclosure contemplates any suitable combination of any suitable components, devices, or systems carrying out any suitable steps of the method of FIG. **14**.

(105) Systems and Methods

(106) FIG. **15** illustrates an example computer system **1500** that may be utilized to achieve a user-specified temperature profile in a cooking appliance **102** through heating control algorithms, in accordance with the presently disclosed embodiments. In particular embodiments, one or more computer systems **1500** perform one or more steps of one or more methods described or illustrated herein. In particular embodiments, one or more computer systems **1500** provide functionality described or illustrated herein. In particular embodiments, software running on one or more computer systems **1500** performs one or more steps of one or more methods described or illustrated herein or provides functionality described or illustrated herein. Particular embodiments include one or more portions of one or more computer systems **1500**. Herein, reference to a computer system may encompass a computing device, and vice versa, where appropriate. Moreover, reference to a computer system may encompass one or more computer systems, where appropriate.

(107) This disclosure contemplates any suitable number of computer systems **1500**. This disclosure contemplates computer system **1500** taking any suitable physical form. As example and not by way of limitation, computer system **1500** may be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC) (e.g., a computer-on-module (COM) or system-on-module (SOM)), a desktop computer system, a laptop or notebook computer system, an interactive kiosk, a mainframe, a mesh of computer systems, a mobile telephone, a personal digital assistant (PDA), a server, a tablet computer system, an augmented/virtual reality device, or a combination of two or more of these. Where appropriate, computer system **1500** may include one or more computer systems **1500**; be unitary or distributed; span multiple locations; span multiple machines; span multiple data centers; or reside in a

cloud, which may include one or more cloud components in one or more networks.

(108) Where appropriate, one or more computer systems **1500** may perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein. As an example, and not by way of limitation, one or more computer systems **1500** may perform in real time or in batch mode one or more steps of one or more methods described or illustrated herein. One or more computer systems **1500** may perform at different times or at different locations one or more steps of one or more methods described or illustrated herein, where appropriate.

(109) In particular embodiments, computer system **1500** includes a processor **1502**, memory **1504**, storage **1506**, an input/output (I/O) interface **1508**, a communication interface **1510**, and a bus **1512**. Although this disclosure describes and illustrates a particular computer system having a particular number of particular components in a particular arrangement, this disclosure contemplates any suitable computer system having any suitable number of any suitable components in any suitable arrangement. In particular embodiments, processor **1502** includes hardware for executing instructions, such as those making up a computer program. As an example, and not by way of limitation, to execute instructions, processor **1502** may retrieve (or fetch) the instructions from an internal register, an internal cache, memory **1504**, or storage **1506**; decode and execute them; and then write one or more results to an internal register, an internal cache, memory **1504**, or storage **1506**. In particular embodiments, processor **1502** may include one or more internal caches for data, instructions, or addresses. This disclosure contemplates processor **1502** including any suitable number of any suitable internal caches, where appropriate. As an example, and not by way of limitation, processor **1502** may include one or more instruction caches, one or more data caches, and one or more translation lookaside buffers (TLBs). Instructions in the instruction caches may be copies of instructions in memory **1504** or storage **1506**, and the instruction caches may speed up retrieval of those instructions by processor **1502**.

(110) Data in the data caches may be copies of data in memory **1504** or storage **1506** for instructions executing at processor **1502** to operate on; the results of previous instructions executed at processor **1502** for access by subsequent instructions executing at processor **1502** or for writing to memory **1504** or storage **1506**; or other suitable data. The data caches may speed up read or write operations by processor **1502**. The TLBs may speed up virtual-address translation for processor **1502**. In particular embodiments, processor **1502** may include one or more internal registers for data, instructions, or addresses. This disclosure contemplates processor **1502** including any suitable number of any suitable internal registers, where appropriate. Where appropriate, processor **1502** may include one or more arithmetic logic units (ALUs); be a multi-core processor; or include one or more processors **1502**. Although this disclosure describes and illustrates a particular processor, this disclosure contemplates any suitable processor.

(111) In particular embodiments, memory **1504** includes main memory for storing instructions for processor **1502** to execute or data for processor **1502** to operate on. As an example, and not by way of limitation, computer system **1500** may load instructions from storage **1506** or another source (such as, for example, another computer system **1500**) to memory **1504**. Processor **1502** may then load the instructions from memory **1504** to an internal register or internal cache. To execute the instructions, processor **1502** may retrieve the instructions from the internal register or internal cache and decode them. During or after execution of the instructions, processor **1502** may write one or more results (which may be intermediate or final results) to the internal register or internal cache. Processor **1502** may then write one or more of those results to memory **1504**. In particular embodiments, processor **1502** executes only instructions in one or more internal registers or internal caches or in memory **1504** (as opposed to storage **1506** or elsewhere) and operates only on data in one or more internal registers or internal caches or in memory **1504** (as opposed to storage **1506** or elsewhere).

(112) One or more memory buses (which may each include an address bus and a data bus) may couple processor **1502** to memory **1504**. Bus **1512** may include one or more memory buses, as described below. In particular embodiments, one or more memory management units (MMUs) reside between processor **1502** and memory **1504** and facilitate accesses to memory **1504** requested by processor **1502**. In particular embodiments, memory **1504** includes random access memory (RAM). This RAM may be volatile memory, where appropriate. Where appropriate, this RAM may be dynamic RAM (DRAM) or static RAM (SRAM). Moreover, where appropriate, this RAM may be single-ported or multi-ported RAM. This disclosure contemplates any suitable RAM. Memory **1504** may include one or more memory devices **1504**, where appropriate. Although this disclosure describes and illustrates particular memory, this

disclosure contemplates any suitable memory.

(113) In particular embodiments, storage **1506** includes mass storage for data or instructions. As an example, and not by way of limitation, storage **1506** may include a hard disk drive (HDD), a floppy disk drive, flash memory, an optical disc, a magneto-optical disc, magnetic tape, or a Universal Serial Bus (USB) drive or a combination of two or more of these. Storage **1506** may include removable or non-removable (or fixed) media, where appropriate. Storage **1506** may be internal or external to computer system **1500**, where appropriate. In particular embodiments, storage **1506** is non-volatile, solid-state memory. In particular embodiments, storage **1506** includes read-only memory (ROM). Where appropriate, this ROM may be mask-programmed ROM, programmable ROM (PROM), erasable PROM (EPROM), electrically erasable PROM (EEPROM), electrically alterable ROM (EAROM), or flash memory or a combination of two or more of these. This disclosure contemplates mass storage **1506** taking any suitable physical form. Storage **1506** may include one or more storage control units facilitating communication between processor **1502** and storage **1506**, where appropriate. Where appropriate, storage **1506** may include one or more storages **1506**. Although this disclosure describes and illustrates particular storage, this disclosure contemplates any suitable storage.

(114) In particular embodiments, I/O interface **1508** includes hardware, software, or both, providing one or more interfaces for communication between computer system **1500** and one or more I/O devices. Computer system **1500** may include one or more of these I/O devices, where appropriate. One or more of these I/O devices may enable communication between a person and computer system **1500**. As an example, and not by way of limitation, an I/O device may include a keyboard, keypad, microphone, monitor, mouse, printer, scanner, speaker, still camera, stylus, tablet, touch screen, trackball, video camera, another suitable I/O device or a combination of two or more of these. An I/O device may include one or more sensors. This disclosure contemplates any suitable I/O devices and any suitable I/O interfaces **1506** for them. Where appropriate, I/O interface **1508** may include one or more device or software drivers enabling processor **1502** to drive one or more of these I/O devices. I/O interface **1508** may include one or more I/O interfaces **1506**, where appropriate. Although this disclosure describes and illustrates a particular I/O interface, this disclosure contemplates any suitable I/O interface.

(115) In particular embodiments, communication interface **1510** includes hardware, software, or both providing one or more interfaces for communication (such as, for example, packet-based communication) between computer system **1500** and one or more other computer systems **1500** or one or more networks. As an example, and not by way of limitation, communication interface **1510** may include a network interface controller (NIC) or network adapter for communicating with an Ethernet or other wire-based network or a wireless NIC (WNIC) or wireless adapter for communicating with a wireless network, such as a WI-FI network. This disclosure contemplates any suitable network and any suitable communication interface **1510** for it.

(116) As an example, and not by way of limitation, computer system **1500** may communicate with an ad hoc network, a personal area network (PAN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), or one or more portions of the Internet or a combination of two or more of these. One or more portions of one or more of these networks may be wired or wireless. As an example, computer system **1500** may communicate with a wireless PAN (WPAN) (such as, for example, a BLUETOOTH WPAN), a WI-FI network, a WI-MAX network, a cellular telephone network (such as, for example, a Global System for Mobile Communications (GSM) network), or other suitable wireless network or a combination of two or more of these. Computer system **1500** may include any suitable communication interface **1510** for any of these networks, where appropriate. Communication interface **1510** may include one or more communication interfaces **1510**, where appropriate. Although this disclosure describes and illustrates a particular communication interface, this disclosure contemplates any suitable communication interface.

(117) In particular embodiments, bus **1512** includes hardware, software, or both coupling components of computer system **1500** to each other. As an example, and not by way of limitation, bus **1512** may include an Accelerated Graphics Port (AGP) or other graphics bus, an Enhanced Industry Standard Architecture (EISA) bus, a front-side bus (FSB), a HYPERTRANSPORT (HT) interconnect, an Industry Standard Architecture (ISA) bus, an INFINIBAND interconnect, a low-pin-count (LPC) bus, a memory bus, a Micro Channel Architecture (MCA) bus, a Peripheral Component Interconnect (PCI) bus, a PCI-Express (PCIe) bus, a serial advanced technology attachment (SATA) bus, a Video Electronics Standards

Association local (VLB) bus, or another suitable bus or a combination of two or more of these. Bus **1512** may include one or more buses **1512**, where appropriate. Although this disclosure describes and illustrates a particular bus, this disclosure contemplates any suitable bus or interconnect.

(118) Miscellaneous

(119) Herein, "or" is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, "A or B" means "A, B, or both," unless expressly indicated otherwise or indicated otherwise by context. Moreover, "and" is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, "A and B" means "A and B, jointly or severally," unless expressly indicated otherwise or indicated otherwise by context.

(120) Herein, "automatically" and its derivatives means "without human intervention," unless expressly indicated otherwise or indicated otherwise by context.

(121) The embodiments disclosed herein are only examples, and the scope of this disclosure is not limited to them. Embodiments according to the invention are in particular disclosed in the attached claims directed to a method, a storage medium, a system and a computer program product, wherein any feature mentioned in one claim category, e.g. method, can be claimed in another claim category, e.g. system, as well. The dependencies or references back in the attached claims are chosen for formal reasons only. However, any subject matter resulting from a deliberate reference back to any previous claims (in particular multiple dependencies) can be claimed as well, so that any combination of claims and the features thereof are disclosed and can be claimed regardless of the dependencies chosen in the attached claims. The subject-matter which can be claimed comprises not only the combinations of features as set out in the attached claims but also any other combination of features in the claims, wherein each feature mentioned in the claims can be combined with any other feature or combination of other features in the claims. Furthermore, any of the embodiments and features described or depicted herein can be claimed in a separate claim and/or in any combination with any embodiment or feature described or depicted herein or with any of the features of the attached claims.

(122) The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, feature, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative. Additionally, although this disclosure describes or illustrates particular embodiments as providing particular advantages, particular embodiments may provide none, some, or all of these advantages.

Claims

1. A method comprising, by an electromagnetic device: accessing a plurality of previously recorded heating maps corresponding to a load disposed inside a cavity of the electromagnetic device, wherein each heating map indicates a temperature profile change of the load as a function of one or more control parameter configurations; accessing a target temperature profile of the load; measuring a current temperature profile of the load; calculating a difference in temperature profiles between the current temperature profile of the load and the target temperature profile of the load; determining a first temporal sequence of control parameter configurations to heat the load, wherein the first temporal sequence (1) is optimized to yield a temperature rise that achieves the target temperature profile of the load and (2) comprises a set of control parameter configurations, and for each control parameter configuration, a corresponding time at which to operate the electromagnetic device according to that respective control

parameter configuration, wherein: (1) the temporal sequence of control parameter configurations is determined subject to a constraint that each corresponding time must be non-negative; and (2) the first temporal sequence of control parameter configurations is determined before heating the load based on the set of control parameter configurations in the sequence; and emitting electromagnetic radiation into the cavity based on the first temporal sequence of control parameter configurations.

2. The method of claim 1, wherein determining the first temporal sequence of control parameter configurations comprises: determining one or more emission configurations; and determining one or more dwell times for which the one or more emission configurations are to be applied.

3. The method of claim 2, further comprising: determining an order in which the one or more emission configurations and the one or more dwell times of the first temporal sequence of control parameter configurations are to be applied, wherein the order is determined according to one or more criteria, wherein emitting electromagnetic radiation is based on the determined order.

4. The method of claim 2, wherein each emission configuration comprises a radiation intensity, and wherein the method further comprises: automatically predicting a total time of the emission of electromagnetic radiation required to yield a temperature rise that achieves the target temperature profile of the load; and scaling a radiation intensity of the one or more emission configurations to yield a specified heating time.

5. The method of claim 2, further comprising: in response to emitting electromagnetic radiation into the cavity, determining a second temperature profile of the load; and calculating, through a non-negative least square regression, the one or more dwell times corresponding to the first temporal sequence of control parameter configurations, wherein the non-negative least square regression yields a minimized squared error between the target temperature profile of the load and the second temperature profile of the load.

6. The method of claim 5, wherein calculating the one or more dwell times corresponding to the first temporal sequence of control parameter configurations further comprises determining an asymmetric cost function to penalize over-heating or under-heating when minimizing the squared error between the target temperature profile of the load and the second temperature profile of the load.

7. The method of claim 4, wherein the radiation intensity is recalculated and the one or more dwell times of the first temporal sequence of control parameter combinations are rescaled to yield a target sum of the one or more dwell times.

8. The method of claim 1, further comprising: in response to emitting electromagnetic radiation into the cavity, generating an updated current temperature profile of the load; calculating a difference between the updated current temperature profile of the load and the target temperature profile of the load; determining a second sequence of control parameter configurations to achieve one or more termination criteria with respect to the load; and in response to achieving the one or more termination criteria with respect to the load, suspending emission of electromagnetic radiation into the cavity.

9. The method of claim 8, further comprising: generating an updated set of heating maps; and storing the updated set of heating maps with the plurality of previously recorded heating maps.

10. The method of claim 1, wherein the control parameter configurations comprise one or more of: a radiation intensity, a radiation frequency, a radiation amplitude, a radiation phase, a radiation phase shift, a load rotation, a load translation, or a mode stirrer configuration.

11. An electronic device comprising: one or more displays; one or more non-transitory computer-readable storage media including instructions; and one or more processors coupled to the storage media, the one or more processors configured to execute the instructions to: access a plurality of previously recorded heating maps corresponding to a load disposed inside a cavity of the electromagnetic device, wherein each heating map indicates a temperature profile change of the load as a function of one or more control parameter configurations; access a target temperature profile of the load; measure a current temperature profile of the load; calculate a difference in temperature profiles between the current temperature profile of the load and the target temperature profile of the load; determine a first temporal sequence of control parameter configurations to heat the load, wherein the first temporal sequence (1) is optimized to yield a temperature rise that achieves the target temperature profile of the load and (2) comprises a set of control parameter configurations, and for each control parameter configuration, a corresponding time at which to operate the electromagnetic device according to that respective control parameter configuration, wherein; (1) the temporal sequence of control parameter configurations is determined subject to a constraint that each corresponding time must be non-negative; and (2) the first temporal sequence of control parameter

configurations is determined before heating the load based on the set of control parameter configurations in the sequence; and emit electromagnetic radiation into the cavity based on the first temporal sequence of control parameter configurations.

12. The electronic device of claim 11, wherein the processors are further configured to execute the instructions to: determine one or more emission configurations; and determine one or more dwell times for which the one or more emission configurations are to be applied.

13. The electronic device of claim 12, wherein the processors are further configured to execute the instructions to: determine an order in which the one or more emission configurations and the one or more dwell times of the first temporal sequence of control parameter configurations are to be applied, wherein the order is determined according to one or more criteria, wherein emitting electromagnetic radiation is based on the determined order.

14. The electronic device of claim 12, wherein each emission configuration comprises a radiation intensity and the processors are further configured to execute the instructions to: automatically predict a total time of the emission of electromagnetic radiation required to yield a temperature rise that achieves the target temperature profile of the load; and scale a radiation intensity of the one or more emission configurations to yield a specified heating time.

15. The electronic device of claim 12, wherein the processors are further configured to execute the instructions to: in response to emitting electromagnetic radiation into the cavity, determine a second temperature profile of the load; and calculate, through a non-negative least square regression, the one or more dwell times corresponding to the first temporal sequence of control parameter configurations, wherein the non-negative least square regression yields a minimized squared error between the target temperature profile of the load and the second temperature profile of the load.

16. The electronic device of claim 15, wherein calculating the one or more dwell times corresponding to the first temporal sequence of control parameter configurations further comprises instructions to determine an asymmetric cost function to penalize over-heating or under-heating when minimizing the squared error between the target temperature profile of the load and the second temperature profile of the load.

17. The electronic device of claim 14, wherein the radiation intensity is recalculated and the one or more dwell times of the first temporal sequence of control parameter combinations are rescaled to yield a target sum of the one or more dwell times.

18. The electronic device of claim 11, wherein the processors are further configured to execute the instructions to: in response to emitting electromagnetic radiation into the cavity, generate an updated current temperature profile of the load; calculate a difference between the updated current temperature profile of the load and the target temperature profile of the load; determine a second sequence of control parameter configurations to achieve one or more termination criteria with respect to the load; and in response to achieving the one or more termination criteria with respect to the load, suspend emission of electromagnetic radiation into the cavity.

19. The electronic device of claim 18, wherein the processors are further configured to execute the instructions to: generate an updated set of heating maps; and store the updated set of heating maps with the plurality of previously recorded heating maps.

20. The electronic device of claim 11, wherein the control parameter configurations comprise one or more of: a radiation intensity, a radiation frequency, a radiation amplitude, a radiation phase, a radiation phase shift, a load rotation, a load translation, or a mode stirrer configuration.

21. A computer-readable non-transitory storage media comprising instructions executable by a processor to: access a plurality of previously recorded heating maps corresponding to a load disposed inside a cavity of an electromagnetic device, wherein each heating map indicates a temperature profile change of the load as a function of one or more control parameter configurations; access a target temperature profile of the load; measure a current temperature profile of the load; calculate a difference in temperature profiles between the current temperature profile of the load and the target temperature profile of the load; determine a first temporal sequence of control parameter configurations to heat the load, wherein the first temporal sequence (1) is optimized to yield a temperature rise that achieves the target temperature profile of the load and (2) comprises a set of control parameter configurations, and for each control parameter configuration, a corresponding time at which to operate the electromagnetic device according to that respective control parameter configuration, wherein: (1) the temporal sequence of control parameter configurations is determined subject to a constraint that each corresponding time must be non-negative;

and (2) the first temporal sequence of control parameter configurations is determined before heating the load based on the set of control parameter configurations in the sequence; and emit electromagnetic radiation into the cavity based on the first temporal sequence of control parameter configurations.

22. The media of claim 21, wherein the instructions are further executable by the processor to: determine one or more emission configurations; and determine one or more dwell times for which the one or more emission configurations are to be applied.

23. The media of claim 22, wherein the instructions are further executable by the processor to: determine an order in which the one or more emission configurations and the one or more dwell times of the first temporal sequence of control parameter configurations are to be applied, wherein the order is determined according to one or more criteria, wherein emitting electromagnetic radiation is based on the determined order.

24. The media of claim 22, wherein each emission configuration comprises a radiation intensity and the instructions are further executable by the processor to: automatically predict a total time of the emission of electromagnetic radiation required to yield a temperature rise that achieves the target temperature profile of the load; and scale a radiation intensity of the one or more emission configurations to yield a specified heating time.

25. The media of claim 22, wherein the instructions are further executable by the processor to: in response to emitting electromagnetic radiation into the cavity, determine a second temperature profile of the load; and calculate, through a non-negative least square regression, the one or more dwell times corresponding to the first temporal sequence of control parameter configurations, wherein the non-negative least square regression yields a minimized squared error between the target temperature profile of the load and the second temperature profile of the load.

26. The media of claim 25, wherein the instructions calculating the one or more dwell times corresponding to the first temporal sequence of control parameter configurations are further executable by the processor to determine an asymmetric cost function to penalize over-heating or under-heating when minimizing the squared error between the target temperature profile of the load and the second temperature profile of the load.

27. The media of claim 22, wherein the radiation intensity is recalculated and the one or more dwell times of the first temporal sequence of control parameter combinations are rescaled to yield a target sum of the one or more dwell times.

28. The media of claim 21, wherein the instructions are further executable by the processor to: in response to emitting electromagnetic radiation into the cavity, generate an updated current temperature profile of the load; calculate a difference between the updated current temperature profile of the load and the target temperature profile of the load; determine a second sequence of control parameter configurations to achieve one or more termination criteria with respect to the load; and in response to achieving the one or more termination criteria with respect to the load, suspend emission of electromagnetic radiation into the cavity.

29. The media of claim 28, wherein the instructions are further executable by the processor to: generate an updated set of heating maps; and store the updated set of heating maps with the plurality of previously recorded heating maps.

30. The media of claim 21, wherein the control parameter configurations comprise one or more of: a radiation intensity, a radiation frequency, a radiation amplitude, a radiation phase, a radiation phase shift, a load rotation, a load translation, or a mode stirrer configuration.