

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12390283
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Misener; Anthony K. et al.

Malposition detection system

Abstract

A system, apparatus and method directed to detecting malposition of a medical device within a vessel of a patient, such as an Azygos vein. The medical device can include a multi-core optical fiber including a plurality of core fibers, where each of the plurality of core fibers includes a plurality of sensors is configured to reflect a light signal based on received incident light, and change a characteristic of the reflected light signal for use in determining a physical state of the multi-core optical fiber. The system can include a console having non-transitory computer-readable medium storing logic that, when executed, causes operations of providing a broadband incident light signal to the multi-core optical fiber, receiving reflected light signals, processing the reflected light signals, and determining whether the medical device has entered the Azygos vein of the patient based on the reflected light signals.

Inventors: Misener; Anthony K. (Bountiful, UT), Sowards; Steffan (Salt Lake City, UT), McLaughlin; William Robert (Bountiful, UT)

Applicant: Bard Access Systems, Inc. (Salt Lake City, UT)

Family ID: 1000008764601

Assignee: Bard Access Systems, Inc. (Salt Lake City, UT)

Appl. No.: 18/132231

Filed: April 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230248444 A1	Aug. 10, 2023

Related U.S. Application Data

division parent-doc US 17357561 20210624 US 11622816 20230411 child-doc US 18132231

Publication Classification

Int. Cl.: **A61B34/20** (20160101); **A61B5/06** (20060101); **G01D5/353** (20060101); **G02B6/02** (20060101)

U.S. Cl.:

CPC **A61B34/20** (20160201); **A61B5/068** (20130101); **G01D5/3538** (20130101); **G02B6/02042** (20130101); A61B2034/2061 (20160201)

Field of Classification Search

CPC: A61B (34/20); A61B (5/068); A61B (2034/2061); G01D (5/3538); G02B (6/02042)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4813429	12/1988	Eshel et al.	N/A	N/A
5099845	12/1991	Besz et al.	N/A	N/A
5163935	12/1991	Black et al.	N/A	N/A
5207672	12/1992	Roth et al.	N/A	N/A
5211165	12/1992	Dumoulin et al.	N/A	N/A
5275151	12/1993	Shockey et al.	N/A	N/A
5280786	12/1993	Wlodarczyk et al.	N/A	N/A
5423321	12/1994	Fontenot	N/A	N/A
5454807	12/1994	Lennox et al.	N/A	N/A
5460182	12/1994	Goodman et al.	N/A	N/A
5517997	12/1995	Fontenot	N/A	N/A
5622170	12/1996	Schulz	N/A	N/A
5740808	12/1997	Panescu et al.	N/A	N/A
5841131	12/1997	Schroeder et al.	N/A	N/A
5872879	12/1998	Hamm	N/A	N/A
5873842	12/1998	Brennen et al.	N/A	N/A
5879306	12/1998	Fontenot et al.	N/A	N/A
5906579	12/1998	Vander Salm et al.	N/A	N/A
6069698	12/1999	Ozawa et al.	N/A	N/A
6081741	12/1999	Hollis	N/A	N/A
6178346	12/2000	Amundson et al.	N/A	N/A
6208887	12/2000	Clarke	N/A	N/A
6245103	12/2000	Stinson	N/A	N/A
6319227	12/2000	Mansouri-Ruiz	N/A	N/A
6343227	12/2001	Crowley	N/A	N/A
6398721	12/2001	Nakamura et al.	N/A	N/A
6485482	12/2001	Belef	N/A	N/A
6564089	12/2002	Izatt et al.	N/A	N/A
6593884	12/2002	Gilboa et al.	N/A	N/A

6597941	12/2002	Fontenot et al.	N/A	N/A
6650923	12/2002	Lesh et al.	N/A	N/A
6673214	12/2003	Marchitto et al.	N/A	N/A
6685666	12/2003	Fontenot	N/A	N/A
6687010	12/2003	Horii et al.	N/A	N/A
6690966	12/2003	Rava et al.	N/A	N/A
6701181	12/2003	Tang et al.	N/A	N/A
6711426	12/2003	Benaron et al.	N/A	N/A
6816743	12/2003	Moreno et al.	N/A	N/A
6892090	12/2004	Verard et al.	N/A	N/A
6895267	12/2004	Panescu et al.	N/A	N/A
7132645	12/2005	Korn	N/A	N/A
7273056	12/2006	Wilson et al.	N/A	N/A
7344533	12/2007	Pearson et al.	N/A	N/A
7366562	12/2007	Dukesherer et al.	N/A	N/A
7366563	12/2007	Kleen et al.	N/A	N/A
7396354	12/2007	Rychnovsky et al.	N/A	N/A
7406346	12/2007	Kleen et al.	N/A	N/A
7515265	12/2008	Alfano et al.	N/A	N/A
7532920	12/2008	Ainsworth et al.	N/A	N/A
7587236	12/2008	Demos et al.	N/A	N/A
7603166	12/2008	Casscells, III et al.	N/A	N/A
7729735	12/2009	Burchman	N/A	N/A
7757695	12/2009	Wilson et al.	N/A	N/A
7758499	12/2009	Adler	N/A	N/A
7840253	12/2009	Tremblay et al.	N/A	N/A
7992573	12/2010	Wilson et al.	N/A	N/A
8032200	12/2010	Tearney et al.	N/A	N/A
8054469	12/2010	Nakabayashi et al.	N/A	N/A
8060187	12/2010	Marshik-Geurts et al.	N/A	N/A
8073517	12/2010	Burchman	N/A	N/A
8078261	12/2010	Imam	N/A	N/A
8187189	12/2011	Jung et al.	N/A	N/A
8267932	12/2011	Baxter et al.	N/A	N/A
8369932	12/2012	Cinbis et al.	N/A	N/A
8388541	12/2012	Messerly et al.	N/A	N/A
8571640	12/2012	Holman	N/A	N/A
8597315	12/2012	Snow et al.	N/A	N/A
8700358	12/2013	Parker, Jr.	N/A	N/A
8781555	12/2013	Burnside et al.	N/A	N/A
8798721	12/2013	Dib	N/A	N/A
8968331	12/2014	Sochor	N/A	N/A
8979871	12/2014	Tyc et al.	N/A	N/A
9060687	12/2014	Yamanaka et al.	N/A	N/A
9114226	12/2014	Lash et al.	N/A	N/A
9206309	12/2014	Appleby et al.	N/A	N/A
9360630	12/2015	Jenner et al.	N/A	N/A
9504392	12/2015	Caron et al.	N/A	N/A
9560954	12/2016	Jacobs et al.	N/A	N/A

9622706	12/2016	Dick et al.	N/A	N/A
9678275	12/2016	Griffin	N/A	N/A
10231753	12/2018	Burnside et al.	N/A	N/A
10258240	12/2018	Eberle et al.	N/A	N/A
10327830	12/2018	Grant et al.	N/A	N/A
10349890	12/2018	Misener et al.	N/A	N/A
10492876	12/2018	Anastassiou et al.	N/A	N/A
10568586	12/2019	Begin et al.	N/A	N/A
10631718	12/2019	Petroff et al.	N/A	N/A
10992078	12/2020	Thompson et al.	N/A	N/A
11123047	12/2020	Jaffer et al.	N/A	N/A
11525670	12/2021	Messerly et al.	N/A	N/A
2001/0014793	12/2000	Brugger et al.	N/A	N/A
2002/0198457	12/2001	Tearney et al.	N/A	N/A
2003/0092995	12/2002	Thompson	N/A	N/A
2004/0129555	12/2003	Marchitto et al.	N/A	N/A
2004/0161362	12/2003	Bogert	N/A	N/A
2004/0242995	12/2003	Maschke	N/A	N/A
2005/0033264	12/2004	Redinger	N/A	N/A
2005/0163424	12/2004	Chen	N/A	N/A
2005/0261598	12/2004	Banet et al.	N/A	N/A
2005/0278010	12/2004	Richardson	N/A	N/A
2006/0013523	12/2005	Childlers et al.	N/A	N/A
2006/0015136	12/2005	Besselink	N/A	N/A
2006/0036164	12/2005	Wilson et al.	N/A	N/A
2006/0189959	12/2005	Schneiter	N/A	N/A
2006/0200049	12/2005	Leo et al.	N/A	N/A
2006/0241395	12/2005	Kruger et al.	N/A	N/A
2006/0241492	12/2005	Boese et al.	N/A	N/A
2007/0156019	12/2006	Larkin et al.	N/A	N/A
2007/0201793	12/2006	Askins et al.	N/A	N/A
2007/0287886	12/2006	Saadat	N/A	N/A
2007/0287934	12/2006	Babaev	N/A	N/A
2007/0299425	12/2006	Waner et al.	N/A	N/A
2008/0039715	12/2007	Wilson et al.	N/A	N/A
2008/0077225	12/2007	Carlin et al.	N/A	N/A
2008/0082004	12/2007	Banet et al.	N/A	N/A
2008/0172119	12/2007	Yamasaki et al.	N/A	N/A
2008/0183128	12/2007	Morriss et al.	N/A	N/A
2008/0212082	12/2007	Froggatt et al.	N/A	N/A
2008/0285909	12/2007	Younge et al.	N/A	N/A
2008/0319290	12/2007	Mao et al.	N/A	N/A
2009/0054908	12/2008	Zand et al.	N/A	N/A
2009/0062634	12/2008	Say et al.	N/A	N/A
2009/0118612	12/2008	Grunwald	600/453	A61B 8/42
2009/0137952	12/2008	Ramamurthy et al.	N/A	N/A
2009/0234328	12/2008	Cox et al.	N/A	N/A
2009/0304582	12/2008	Rousso et al.	N/A	N/A
2009/0314925	12/2008	Van Vorhis et al.	N/A	N/A
2010/0016729	12/2009	Futrell	N/A	N/A

2010/0030063	12/2009	Lee et al.	N/A	N/A
2010/0030132	12/2009	Niezgoda et al.	N/A	N/A
2010/0063534	12/2009	Kugler et al.	N/A	N/A
2010/0114115	12/2009	Schlesinger et al.	N/A	N/A
2010/0286531	12/2009	Ryan et al.	N/A	N/A
2010/0312095	12/2009	Jenkins et al.	N/A	N/A
2011/0060229	12/2010	Hulvershorn et al.	N/A	N/A
2011/0090486	12/2010	Udd	N/A	N/A
2011/0144481	12/2010	Feer et al.	N/A	N/A
2011/0166442	12/2010	Sarvazyan	N/A	N/A
2011/0172591	12/2010	Babaev	N/A	N/A
2011/0172680	12/2010	Younge et al.	N/A	N/A
2011/0237958	12/2010	Onimura	N/A	N/A
2011/0242532	12/2010	McKenna	N/A	N/A
2011/0245662	12/2010	Eggers et al.	N/A	N/A
2011/0288405	12/2010	Razavi et al.	N/A	N/A
2011/0295108	12/2010	Cox et al.	N/A	N/A
2011/0313280	12/2010	Govari et al.	N/A	N/A
2012/0046562	12/2011	Powers et al.	N/A	N/A
2012/0065481	12/2011	Hunter	600/513	A61B 5/062
2012/0101413	12/2011	Beetel et al.	N/A	N/A
2012/0136242	12/2011	Qi et al.	N/A	N/A
2012/0143029	12/2011	Silverstein et al.	N/A	N/A
2012/0184827	12/2011	Shwartz et al.	N/A	N/A
2012/0184955	12/2011	Pivotto et al.	N/A	N/A
2012/0283747	12/2011	Popovic	N/A	N/A
2012/0289783	12/2011	Duindam et al.	N/A	N/A
2012/0321243	12/2011	Younge et al.	N/A	N/A
2013/0028554	12/2012	Wong et al.	N/A	N/A
2013/0072943	12/2012	Parmar	N/A	N/A
2013/0096482	12/2012	Bertrand et al.	N/A	N/A
2013/0104884	12/2012	Vazales et al.	N/A	N/A
2013/0188855	12/2012	Desjardins et al.	N/A	N/A
2013/0204124	12/2012	Duindam et al.	N/A	N/A
2013/0211246	12/2012	Parasher	N/A	N/A
2013/0296693	12/2012	Wenzel et al.	N/A	N/A
2013/0310668	12/2012	Young	N/A	N/A
2013/0317372	12/2012	Eberle et al.	N/A	N/A
2013/0324840	12/2012	Zhongping et al.	N/A	N/A
2014/0121468	12/2013	Eichenholz	N/A	N/A
2014/0221829	12/2013	Maitland et al.	N/A	N/A
2014/0275997	12/2013	Chopra et al.	N/A	N/A
2015/0029511	12/2014	T Hooft et al.	N/A	N/A
2015/0031987	12/2014	Pameijer et al.	N/A	N/A
2015/0080688	12/2014	Cinbis et al.	N/A	N/A
2015/0099979	12/2014	Caves et al.	N/A	N/A
2015/0119700	12/2014	Liang et al.	N/A	N/A
2015/0124264	12/2014	Ramachandran et al.	N/A	N/A
2015/0141854	12/2014	Eberle et al.	N/A	N/A

2015/0164571	12/2014	Saadat	600/109	A61N 7/022
2015/0190221	12/2014	Schaefer et al.	N/A	N/A
2015/0209113	12/2014	Burkholz et al.	N/A	N/A
2015/0209117	12/2014	Flexman et al.	N/A	N/A
2015/0254526	12/2014	Denissen	N/A	N/A
2015/0320977	12/2014	Vitullo et al.	N/A	N/A
2016/0018602	12/2015	Govari et al.	N/A	N/A
2016/0067449	12/2015	Misener	600/585	A61B 34/20
2016/0102969	12/2015	Verstege et al.	N/A	N/A
2016/0166326	12/2015	Bakker et al.	N/A	N/A
2016/0166341	12/2015	Iordachita et al.	N/A	N/A
2016/0184020	12/2015	Kowalewski et al.	N/A	N/A
2016/0213432	12/2015	Flexman et al.	N/A	N/A
2016/0331461	12/2015	Cheatham, III et al.	N/A	N/A
2016/0349044	12/2015	Marell et al.	N/A	N/A
2016/0354038	12/2015	Demirtas et al.	N/A	N/A
2017/0020394	12/2016	Harrington	N/A	N/A
2017/0079681	12/2016	Burnside et al.	N/A	N/A
2017/0082806	12/2016	Van Der Mark et al.	N/A	N/A
2017/0151027	12/2016	Walker et al.	N/A	N/A
2017/0173349	12/2016	Pfleiderer et al.	N/A	N/A
2017/0196479	12/2016	Liu et al.	N/A	N/A
2017/0201036	12/2016	Cohen et al.	N/A	N/A
2017/0215973	12/2016	Flexman et al.	N/A	N/A
2017/0231699	12/2016	Flexman et al.	N/A	N/A
2017/0273542	12/2016	Au	N/A	N/A
2017/0273565	12/2016	Ma et al.	N/A	N/A
2017/0273628	12/2016	Ofek et al.	N/A	N/A
2017/0290563	12/2016	Cole et al.	N/A	N/A
2017/0311901	12/2016	Zhao et al.	N/A	N/A
2017/0319279	12/2016	Fish et al.	N/A	N/A
2018/0008443	12/2017	Cole et al.	N/A	N/A
2018/0031493	12/2017	Tojo et al.	N/A	N/A
2018/0095231	12/2017	Lowell et al.	N/A	N/A
2018/0113038	12/2017	Janabi-Sharifi et al.	N/A	N/A
2018/0116551	12/2017	Newman et al.	N/A	N/A
2018/0140170	12/2017	Van Putten et al.	N/A	N/A
2018/0235709	12/2017	Donhowe et al.	N/A	N/A
2018/0239124	12/2017	Naruse et al.	N/A	N/A
2018/0240237	12/2017	Donhowe	N/A	A61B 34/10
2018/0250088	12/2017	Brennan et al.	N/A	N/A
2018/0264227	12/2017	Flexman et al.	N/A	N/A
2018/0279909	12/2017	Noonan et al.	N/A	N/A
2018/0289390	12/2017	Amorizzo et al.	N/A	N/A
2018/0289927	12/2017	Messerly	N/A	N/A
2018/0339134	12/2017	Leo	N/A	N/A
2018/0360545	12/2017	Cole et al.	N/A	N/A
2019/0059743	12/2018	Ramachandran et al.	N/A	N/A
2019/0060003	12/2018	Tuason	N/A	N/A

2019/0110844	12/2018	Misener et al.	N/A	N/A
2019/0231272	12/2018	Yamaji	N/A	N/A
2019/0237902	12/2018	Thompson et al.	N/A	N/A
2019/0247132	12/2018	Harks et al.	N/A	N/A
2019/0307331	12/2018	Saadat et al.	N/A	N/A
2019/0321110	12/2018	Grunwald et al.	N/A	N/A
2019/0343424	12/2018	Blumenkranz et al.	N/A	N/A
2019/0343702	12/2018	Smith	N/A	N/A
2019/0357875	12/2018	Qi et al.	N/A	N/A
2019/0365199	12/2018	Zhao et al.	N/A	N/A
2019/0374130	12/2018	Bydlon et al.	N/A	N/A
2020/0000526	12/2019	Zhao	N/A	N/A
2020/0030575	12/2019	Bogusky et al.	N/A	N/A
2020/0046434	12/2019	Graetzel et al.	N/A	N/A
2020/0054399	12/2019	Duindam et al.	N/A	N/A
2020/0121482	12/2019	Spector et al.	N/A	N/A
2020/0188036	12/2019	Ding et al.	N/A	N/A
2020/0297442	12/2019	Adebar et al.	N/A	N/A
2020/0305983	12/2019	Yampolsky et al.	N/A	N/A
2020/0315770	12/2019	Dupont et al.	N/A	N/A
2020/0394789	12/2019	Freund et al.	N/A	N/A
2021/0015470	12/2020	Prisco et al.	N/A	N/A
2021/0023341	12/2020	Decheek et al.	N/A	N/A
2021/0045814	12/2020	Thompson et al.	N/A	N/A
2021/0068911	12/2020	Walker et al.	N/A	N/A
2021/0100627	12/2020	Soper et al.	N/A	N/A
2021/0244311	12/2020	Zhao et al.	N/A	N/A
2021/0268229	12/2020	Sowards et al.	N/A	N/A
2021/0271035	12/2020	Sowards et al.	N/A	N/A
2021/0275257	12/2020	Prior et al.	N/A	N/A
2021/0298680	12/2020	Sowards et al.	N/A	N/A
2021/0330399	12/2020	Netravali et al.	N/A	N/A
2021/0401456	12/2020	Cox et al.	N/A	N/A
2021/0401509	12/2020	Misener et al.	N/A	N/A
2021/0402144	12/2020	Messerly	N/A	N/A
2022/0011192	12/2021	Misener et al.	N/A	N/A
2022/0034733	12/2021	Misener et al.	N/A	N/A
2022/0079683	12/2021	Bydlon et al.	N/A	N/A
2022/0096796	12/2021	McLaughlin et al.	N/A	N/A
2022/0110508	12/2021	Van Roosbroeck et al.	N/A	N/A
2022/0110695	12/2021	Sowards et al.	N/A	N/A
2022/0151568	12/2021	Yao et al.	N/A	N/A
2022/0152349	12/2021	Sowards et al.	N/A	N/A
2022/0160209	12/2021	Sowards et al.	N/A	N/A
2022/0172354	12/2021	Misener et al.	N/A	N/A
2022/0211442	12/2021	McLaughlin et al.	N/A	N/A
2022/0233246	12/2021	Misener et al.	N/A	N/A
2022/0369934	12/2021	Sowards et al.	N/A	N/A
2023/0081198	12/2022	Sowards et al.	N/A	N/A

2023/0097431	12/2022	Sowards et al.	N/A	N/A
2023/0101030	12/2022	Misener et al.	N/A	N/A
2023/0108604	12/2022	Messerly et al.	N/A	N/A
2023/0126813	12/2022	Sowards et al.	N/A	N/A
2023/0243715	12/2022	Misener et al.	N/A	N/A
2023/0251150	12/2022	Misener et al.	N/A	N/A
2023/0337985	12/2022	Sowards et al.	N/A	N/A
2023/0346479	12/2022	Muller et al.	N/A	N/A
2023/0414112	12/2022	Misener et al.	N/A	N/A
2024/0000515	12/2023	Misener et al.	N/A	N/A
2024/0050708	12/2023	Misener	N/A	N/A
2024/0099659	12/2023	Sowards et al.	N/A	N/A
2024/0108856	12/2023	Messerly	N/A	N/A
2024/0216077	12/2023	Thompson et al.	N/A	N/A
2024/0335237	12/2023	Sowards et al.	N/A	N/A
2024/0353275	12/2023	Misener et al.	N/A	N/A
2024/0383133	12/2023	Bydlon et al.	N/A	N/A
2024/0390644	12/2023	McLaughlin et al.	N/A	N/A
2025/0020453	12/2024	Thompson et al.	N/A	N/A
2025/0060266	12/2024	Messerly	N/A	N/A
2025/0186135	12/2024	McLaughlin et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101132730	12/2007	CN	N/A
111265309	12/2019	CN	N/A
113080937	12/2020	CN	N/A
102016109601	12/2016	DE	N/A
2240111	12/2009	EP	N/A
2907445	12/2014	EP	N/A
3545849	12/2018	EP	N/A
3705020	12/2019	EP	N/A
7366562	12/2022	JP	N/A
20190098512	12/2018	KR	N/A
99/64099	12/1998	WO	N/A
2006113394	12/2005	WO	N/A
2006122001	12/2005	WO	N/A
2007002323	12/2006	WO	N/A
2009155325	12/2008	WO	N/A
2011121516	12/2010	WO	N/A
2011141830	12/2010	WO	N/A
2011150376	12/2010	WO	N/A
2012064769	12/2011	WO	N/A
2015044930	12/2014	WO	N/A
2015074045	12/2014	WO	N/A
2016038492	12/2015	WO	N/A
2016051302	12/2015	WO	N/A
2016061431	12/2015	WO	N/A
2016149819	12/2015	WO	N/A
2018/096491	12/2017	WO	N/A

2019037071	12/2018	WO	N/A
2019046769	12/2018	WO	N/A
2019070423	12/2018	WO	N/A
2019230713	12/2018	WO	N/A
2020182997	12/2019	WO	N/A
2021030092	12/2020	WO	N/A
2021108688	12/2020	WO	N/A
2021108697	12/2020	WO	N/A
2021138096	12/2020	WO	N/A
2021216089	12/2020	WO	N/A
2022031613	12/2021	WO	N/A
2022081723	12/2021	WO	N/A
2022150411	12/2021	WO	N/A
2022/164902	12/2021	WO	N/A
2022245987	12/2021	WO	N/A
2023043954	12/2022	WO	N/A
2023049443	12/2022	WO	N/A
2023055810	12/2022	WO	N/A
2023076143	12/2022	WO	N/A
2023211752	12/2022	WO	N/A
2024006384	12/2023	WO	N/A
2024006441	12/2023	WO	N/A
2024064334	12/2023	WO	N/A
2024215665	12/2023	WO	N/A

OTHER PUBLICATIONS

Fiber Optic RealShape (FORS) technology—research. Philips. (Oct. 18, 2018). Retrieved Feb. 28, 2023, from <https://www.philips.com/a-w/research/research-programs/fors.html> (Year: 2018). cited by applicant

Jackle Sonja et al. “Three-dimensional guidance including shape sensing of a stentgraft system for endovascular aneurysm repair.” International Journal of Computer Assisted Radiology and Surgery, Springer DE. vol. 15, No. 6, May 7, 2020. cited by applicant

PCT/US2018/026493 filed Apr. 6, 2018 International Search Report and Written Opinion dated Jun. 22, 2018. cited by applicant

PCT/US2020/044801 filed Aug. 3, 2020 International Search Report and Written Opinion dated Oct. 26, 2020. cited by applicant

PCT/US2020/062396 filed Nov. 25, 2020 International Preliminary Report on Patentability dated Jan. 29, 2021. cited by applicant

PCT/US2020/062396 filed Nov. 25, 2020 International Search Report and Written Opinion dated Mar. 2, 2021. cited by applicant

PCT/US2020/062407 filed Nov. 25, 2020 International Preliminary Report on Patentability dated Jan. 25, 2021. cited by applicant

PCT/US2020/062407 filed Nov. 25, 2020 International Search Report and Written Opinion dated Mar. 11, 2021. cited by applicant

PCT/US2021/038899 filed Jun. 24, 2021 International Search Report and Written Opinion dated Oct. 6, 2021. cited by applicant

PCT/US2021/038954 filed Jun. 24, 2021 International Search Report and Written Opinion dated Oct. 28, 2021. cited by applicant

PCT/US2021/041128 filed Jul. 9, 2021 International Search Report and Written Opinion dated Oct. 25, 2021. cited by applicant

PCT/US2021/044216 filed Aug. 2, 2021 International Search Report and Written Opinion dated Nov. 18, 2021. cited by applicant

PCT/US2021/054802 filed Oct. 13, 2021 International Search Report and Written Opinion dated Feb. 2, 2022. cited by applicant

PCT/US2022/011347 filed Jan. 5, 2022 International Search Report and Written Opinion dated May 3, 2022. cited by applicant

PCT/US2022/013897 filed Jan. 26, 2022 International Search Report and Written Opinion dated May 11, 2022. cited by applicant

PCT/US2022/029894 filed May 18, 2022, International Search Report and Written Opinion dated Sep. 1, 2022. cited by applicant

PCT/US2022/043706 filed Sep. 16, 2022 International Search Report and Written Opinion dated Nov. 24, 2022. cited by applicant

PCT/US2022/044696 filed Sep. 26, 2022 International Search Report and Written Opinion dated Jan. 23, 2023. cited by applicant

PCT/US2022/045051 filed Sep. 28, 2022 International Search Report and Written Opinion dated Jan. 2, 2023. cited by applicant

PCT/US2022/047538 filed Oct. 24, 2022 International Search Report and Written Opinion dated Jan. 26, 2023. cited by applicant

U.S. Appl. No. 15/947,267, filed Apr. 6, 2018 Examiner's Answer dated Nov. 28, 2022. cited by applicant

U.S. Appl. No. 15/947,267, filed Apr. 6, 2018 Final Office Action dated Apr. 22, 2022. cited by applicant

U.S. Appl. No. 16/984,104, filed Aug. 3, 2020 Restriction Requirement dated Mar. 13, 2023. cited by applicant

U.S. Appl. No. 17/105,259, filed Nov. 25, 2020, Notice of Allowance dated Jul. 20, 2022. cited by applicant

U.S. Appl. No. 17/105,310, filed Nov. 25, 2020 Non-Final Office Action dated Feb. 22, 2023. cited by applicant

U.S. Appl. No. 17/357,186, filed Jun. 24, 2021 Restriction Requirement dated Mar. 7, 2023. cited by applicant

U.S. Appl. No. 17/357,561, filed Jun. 24, 2021 Non-Final Office Action dated Aug. 11, 2022. cited by applicant

U.S. Appl. No. 17/357,561, filed Jun. 24, 2021 Notice of Allowance dated Dec. 9, 2022. cited by applicant

U.S. Appl. No. 17/371,993, filed Jul. 9, 2021 Non-Final Office Action dated Jul. 12, 2022. cited by applicant

U.S. Appl. No. 17/371,993, filed Jul. 9, 2021 Notice of Allowance dated Nov. 3, 2022. cited by applicant

U.S. Appl. No. 17/392,002, filed Aug. 2, 2021, Corrected Notice of Allowability dated Feb. 23, 2023. cited by applicant

U.S. Appl. No. 17/392,002, filed Aug. 2, 2021, Non-Final Office Action dated Sep. 12, 2022. cited by applicant

U.S. Appl. No. 17/392,002, filed Aug. 2, 2021, Notice of Allowance dated Jan. 19, 2023. cited by applicant

U.S. Appl. No. 15/947,267, filed Apr. 6, 2018 Final Office Action dated Jun. 30, 2021. cited by applicant

U.S. Appl. No. 15/947,267, filed Apr. 6, 2018 Final Office Action dated Nov. 10, 2020. cited by applicant

U.S. Appl. No. 15/947,267, filed Apr. 6, 2018 Non-Final Office Action dated Mar. 12, 2021. cited by applicant

U.S. Appl. No. 15/947,267, filed Apr. 6, 2018 Non-Final Office Action dated May 29, 2020. cited by applicant

U.S. Appl. No. 15/947,267, filed Apr. 6, 2018 Non-Final Office Action dated Oct. 13, 2021. cited by applicant

U.S. Appl. No. 17/500,678, filed Oct. 13, 2021 Non-Final Office Action dated Mar. 15, 2023. cited by applicant

Dziuda L et al: "Monitoring Respiration and Cardiac Activity Using Fiber Bragg Grating-Based Sensor", IEEE Transactions on Biomedical Engineering vol. 59, No. 7, Jul. 2012 pp. 1934-1942. cited by applicant

Dziuda L. et al: "Fiber-optic sensor for monitoring respiration and cardiac activity", 2011 IEEE Sensors Proceedings : Limerick, Ireland, Oct. 2011 pp. 413-416. cited by applicant

EP 20893677.3 filed Jun. 22, 2022 Extended European Search Report dated Oct. 13, 2023. cited by applicant

EP 20894633.5 filed Jun. 22, 2022 Extended European Search Report dated Oct. 16, 2023. cited by applicant

PCT/US2021/052046 filed Sep. 24, 2021 International Search Report and Written Opinion dated Jan. 11, 2022. cited by applicant

PCT/US2023/026581 filed Jun. 29, 2023 International Search Report and Written Opinion dated Oct. 27, 2023. cited by applicant

U.S. Appl. No. 16/984,104, filed Aug. 3, 2020 Notice of Allowance dated Nov. 21, 2023. cited by applicant

U.S. Appl. No. 17/484,960, filed Sep. 24, 2021 Non-Final Office Action dated Oct. 5, 2023. cited by applicant

U.S. Appl. No. 17/500,678, filed Oct. 13, 2021 Advisory Action dated Dec. 7, 2023. cited by applicant

U.S. Appl. No. 18/135,337, filed Apr. 17, 2023 Non-Final Office Action dated Dec. 22, 2023. cited by applicant

U.S. Appl. No. 17/569,350, filed Jan. 5, 2022 Non-Final Office Action dated Jan. 8, 2024. cited by applicant

PCT/US2023/033471 filed Sep. 22, 2023 International Search Report and Written Opinion dated Dec. 21, 2023. cited by applicant

U.S. Appl. No. 17/500,678, filed Oct. 13, 2021 Non-Final Office Action dated Jan. 19, 2024. cited by applicant

U.S. Appl. No. 18/079,653, filed Dec. 12, 2022 Non-Final Office Action dated Feb. 6, 2024. cited by applicant

U.S. Appl. No. 18/135,337, filed Apr. 17, 2023 Notice of Allowance dated Mar. 8, 2024. cited by applicant

EP 20853352.1 filed Mar. 7, 2022 Extended European Search Report dated Jul. 27, 2023. cited by applicant

PCT/US2023/019239 filed Apr. 20, 2023 International Search Report and Written Opinion dated Jul. 20, 2023. cited by applicant

PCT/US2023/026487 filed Jun. 28, 2023 International Search Report and Written Opinion dated Sep. 6, 2023. cited by applicant

U.S. Appl. No. 16/984,104, filed Aug. 3, 2020 Final Office Action dated Sep. 21, 2023. cited by applicant

U.S. Appl. No. 16/984,104, filed Aug. 3, 2020 Non-Final Office Action dated Jun. 22, 2023. cited by applicant

U.S. Appl. No. 17/105,310, filed Nov. 25, 2020 Notice of Allowance dated Aug. 2, 2023. cited by applicant

U.S. Appl. No. 17/357,186, filed Jun. 24, 2021 Non Final Office Action dated May 30, 2023. cited

by applicant
U.S. Appl. No. 17/357,186, filed Jun. 24, 2021 Notice of Allowance dated Aug. 23, 2023. cited by applicant
U.S. Appl. No. 17/500,678, filed Oct. 13, 2021 Final Office Action dated Sep. 21, 2023. cited by applicant
U.S. Appl. No. 17/484,960, filed Sep. 24, 2021 Notice of Allowance dated Apr. 12, 2024. cited by applicant
U.S. Appl. No. 17/569,350, filed Jan. 5, 2022 Final Office Action dated Apr. 23, 2024. cited by applicant
U.S. Appl. No. 17/747,903, filed May 18, 2022 Restriction Requirement dated May 28, 2024. cited by applicant
U.S. Appl. No. 17/955,019, filed Sep. 28, 2022 Restriction Requirement dated Jun. 6, 2024. cited by applicant
U.S. Appl. No. 18/079,653, filed Dec. 12, 2022 Notice of Allowance dated Jun. 4, 2024. cited by applicant
U.S. Appl. No. 18/132,623, filed Apr. 10, 2023, Non-Final Office Action dated May 3, 2024. cited by applicant
U.S. Appl. No. 17/971,873, filed Oct. 24, 2022 Non-Final Office Action dated Jun. 6, 2024. cited by applicant
P.J. de Feyter, P. Kay, C. Disco, P.W. Serruys, "Reference chart derived from post-stent-implantation intravascular ultrasound predictors of 6-month expected restenosis on quantitative coronary angiography." *Circulation*. vol. 100, No. 17 (Year: 1999). cited by applicant
PCT/US2023/026581 filed Jun. 29, 2023 International Preliminary Report on Patentability dated Dec. 18, 2024. cited by applicant
U.S. Appl. No. 17/500,678, filed Oct. 13, 2021 Advisory Action dated Nov. 6, 2024. cited by applicant
U.S. Appl. No. 17/500,678, filed Oct. 13, 2021 Non-Final Office Action dated Dec. 4, 2024. cited by applicant
U.S. Appl. No. 17/569,350, filed Jan. 5, 2022 Notice of Allowance dated Nov. 7, 2024. cited by applicant
U.S. Appl. No. 17/585,219, filed Jan. 26, 2022 Restriction Requirement dated Dec. 2, 2024. cited by applicant
U.S. Appl. No. 17/853,590, filed Jun. 29, 2022 Non-Final Office Action dated Oct. 17, 2024. cited by applicant
U.S. Appl. No. 17/971,873, filed Oct. 24, 2022 Non-Final Office Action dated Dec. 27, 2024. cited by applicant
U.S. Appl. No. 18/132,623, filed Apr. 10, 2023, Notice of Allowance dated Nov. 19, 2024. cited by applicant
U.S. Appl. No. 18/383,809, filed Oct. 25, 2023 Non-Final Office Action dated Dec. 16, 2024. cited by applicant
Mayoral et al. Fiber Optic Sensors for Vital Signs Monitoring. A Review of Its Practicality in the Health Field. *Biosensors* (Basel). Feb. 23, 2021;11(2):58. doi: 10.3390/bios11020058. cited by applicant
U.S. Appl. No. 15/947,267, filed Apr. 6, 2018 Notice of Allowance dated Jul. 16, 2024. cited by applicant
U.S. Appl. No. 17/500,678, filed Oct. 13, 2021 Final Office Action dated Aug. 27, 2024. cited by applicant
U.S. Appl. No. 17/569,350, filed Jan. 5, 2022 Advisory Action dated Jul. 12, 2024. cited by applicant
U.S. Appl. No. 17/728,802, filed Apr. 25, 2022 Non-Final Office Action dated Aug. 28, 2024. cited

by applicant
U.S. Appl. No. 17/747,903, filed May 18, 2022 Non-Final Office Action dated Aug. 15, 2024. cited by applicant
U.S. Appl. No. 17/852,138, filed Jun. 28, 2022 Non-Final Office Action dated Sep. 18, 2024. cited by applicant
U.S. Appl. No. 17/955,019, filed Sep. 28, 2022 Non-Final Office Action dated Sep. 27, 2024. cited by applicant
U.S. Appl. No. 18/132,623, filed Apr. 10, 2023, Final Office Action dated Sep. 6, 2024. cited by applicant
U.S. Appl. No. 18/538,111, filed Dec. 13, 2023 Non-Final Office Action dated Aug. 9, 2024. cited by applicant
U.S. Appl. No. 18/607,144, filed Mar. 15, 2024 Non-Final Office Action dated Sep. 24, 2024. cited by applicant
U.S. Appl. No. 17/569,350, filed Jan. 5, 2022 Non-Final Office Action dated Aug. 12, 2024. cited by applicant
U.S. Appl. No. 17/585,219, filed Jan. 26, 2022 Non-Final Office Action dated Feb. 27, 2025. cited by applicant
U.S. Appl. No. 17/728,802, filed Apr. 25, 2022 Final Office Action dated Jan. 17, 2025. cited by applicant
U.S. Appl. No. 17/747,903, filed May 18, 2022 Final Office Action dated Jan. 27, 2025. cited by applicant
U.S. Appl. No. 17/852,138, filed Jun. 28, 2022 Notice of Allowance dated Feb. 12, 2025. cited by applicant
U.S. Appl. No. 17/853,590, filed Jun. 29, 2022 Notice of Allowance dated Mar. 5, 2025. cited by applicant
U.S. Appl. No. 17/952,645, filed Sep. 26, 2022 Non-Final Office Action dated Feb. 28, 2025. cited by applicant
U.S. Appl. No. 17/955,019, filed Sep. 28, 2022 Final Office Action dated Feb. 4, 2025. cited by applicant
U.S. Appl. No. 18/538,111, filed Dec. 13, 2023 Final Office Action dated Feb. 4, 2025. cited by applicant
U.S. Appl. No. 18/607,144, filed Mar. 15, 2024 Final Office Action dated Feb. 19, 2025. cited by applicant
Ogawa, K.; Koyama, S.; Ishizawa, H.; Fujiwara, S.; Fujimoto, K. Simultaneous Measurement of Heart Sound, PulseWave and Respiration with Single Fiber Bragg Grating Sensor. In Proceedings of the 2018 IEEE International Symposium on Medical Measurements and Applications (MeMeA), Rome, Italy, Jun. 11-13, 2018. cited by applicant
U.S. Appl. No. 17/500,678, filed Oct. 13, 2021 Final Office Action dated Jun. 11, 2025. cited by applicant
U.S. Appl. No. 17/585,219, filed Jan. 26, 2022 Notice of Allowance dated Jun. 17, 2025. cited by applicant
U.S. Appl. No. 17/728,802, filed Apr. 25, 2022 Advisory Action dated Apr. 4, 2025. cited by applicant
U.S. Appl. No. 17/728,802, filed Apr. 25, 2022 Non-Final Office Action dated May 19, 2025. cited by applicant
U.S. Appl. No. 17/747,903, filed May 18, 2022 Advisory Action dated Apr. 22, 2025. cited by applicant
U.S. Appl. No. 17/955,019, filed Sep. 28, 2022 Advisory Action dated Apr. 16, 2025. cited by applicant
U.S. Appl. No. 18/132,891, filed Apr. 10, 2023 Restriction Requirement dated Jun. 2, 2025. cited

by applicant

U.S. Appl. No. 18/383,809, filed Oct. 25, 2023 Notice of Allowance dated Apr. 30, 2025. cited by applicant

U.S. Appl. No. 18/538,111 filed Dec. 13, 2023 Notice of Allowance dated Apr. 23, 2025. cited by applicant

U.S. Appl. No. 18/607,144 filed Mar. 15, 2024 Notice of Allowance dated Apr. 5, 2025. cited by applicant

Primary Examiner: Turchen; Rochelle D

Attorney, Agent or Firm: Rutan & Tucker LLP

Background/Summary

PRIORITY (1) This application is a division of U.S. patent application Ser. No. 17/357,561, filed Jun. 24, 2021, now U.S. Pat. No. 11,622,816, which claims the benefit of priority to U.S. Provisional Application No. 63/044,911, filed Jun. 26, 2020, each of which is incorporated by reference in its entirety into this application.

BACKGROUND

(1) In the past, certain intravascular guidance of medical devices, such as guidewires and catheters for example, have used fluoroscopic methods for tracking tips of the medical devices and determining whether distal tips are appropriately localized in their target anatomical structures. However, such fluoroscopic methods expose patients and their attending clinicians to harmful X-ray radiation. Moreover, in some cases, the patients are exposed to potentially harmful contrast media needed for the fluoroscopic methods.

(2) More recently, electromagnetic tracking systems have been used involving stylets. Generally, electromagnetic tracking systems feature three components: a field generator, a sensor unit and control unit. The field generator uses several coils to generate a position-varying magnetic field, which is used to establish a coordinate space. Attached to the stylet, such as near a distal end (tip) of the stylet for example, the sensor unit includes small coils in which current is induced via the magnetic field. Based on the electrical properties of each coil, the position and orientation of the medical device may be determined within the coordinate space. The control unit controls the field generator and captures data from the sensor unit.

(3) Although electromagnetic tracking systems avoid line-of-sight reliance in tracking the tip of a stylet while obviating radiation exposure and potentially harmful contrast media associated with fluoroscopic methods, electromagnetic tracking systems are prone to interference. More specifically, since electromagnetic tracking systems depend on the measurement of magnetic fields produced by the field generator, these systems are subject to electromagnetic field interference, which may be caused by the presence of many different types of consumer electronics such as cellular telephones. Additionally, electromagnetic tracking systems are subject to signal drop out, depend on an external sensor, and are defined to a limited depth range.

(4) Disclosed herein is a system and method for determining whether a medical device inserted into a patient has deviated from a target advancement path and has entered the vessel of the patient based on one or more signals from the medical device.

SUMMARY

(5) Briefly summarized, some embodiments disclosed herein are directed to systems, apparatuses and methods for obtaining three-dimensional (3D) information (reflected light) corresponding to a trajectory and/or shape of a medical instrument, such as a catheter, a guidewire, or a stylet, during

advancement through a vasculature of a patient, and determining malposition of the medical instrument within a vessel of the patient, such as the Azygos vein. In some embodiments, the system is a fiber optic shape sensing system and methods thereof, configured to provide confirmation of tip placement or information passed/interpreted as an electrical signal. Some embodiments combine the fiber optic shape sensing functionality with one or more of intravascular electrocardiogram (ECG) monitoring, impedance/conductance sensing and blood flow directional detection. Although the examples herein are with respect to malposition into the Azygos vein, the invention described herein is not so limited. It should be appreciated that the invention described herein can be used to detect malposition of a medical device in any number of vessels and locations in a patient, and is not intended to be specific to malposition into the Azygos vein.

(6) More particularly, in some embodiments, the medical instrument includes a multi-core optical fiber, with each core fiber of the multi-core optical fiber is configured with an array of sensors (reflective gratings), which are spatially distributed over a prescribed length of the core fiber to generally sense external strain on those regions of the core fiber occupied by the sensor. The multi-core optical fiber is configured to receive broadband light from a console during advancement through the vasculature of a patient, where the broadband light propagates along at least a partial distance of the multi-core optical fiber toward the distal end. Given that each sensor positioned along the same core fiber is configured to reflect light of a different, specific spectral width, the array of sensors enable distributed measurements throughout the prescribed length of the multi-core optical fiber. These distributed measurements may include wavelength shifts having a correlation with strain experienced by the sensor.

(7) The reflected light from the sensors (reflective gratings) within each core fiber of the multi-core optical fiber is returned from the medical instrument for processing by the console. The physical state of the medical instrument may be ascertained based on analytics of the wavelength shifts of the reflected light. For example, the strain caused through bending of the medical instrument, and hence angular modification of each core fiber, causes different degrees of deformation. The different degrees of deformation alters the shape of the sensors (reflective grating) positioned on the core fiber, which may cause variations (shifts) in the wavelength of the reflected light from the sensors positioned on each core fiber within the multi-core optical fiber, as shown in FIGS. 2-5B and 7A-13.

(8) Specific embodiments of the disclosure include utilization of a stylet featuring a multi-core optical fiber and a conductive medium that collectively operate for tracking placement of a catheter or other medical device within a body of a patient. The stylet is configured to return information for use in identifying its physical state (e.g., shape length, shape, and/or form) of (i) a portion of the stylet (e.g., tip, segment of stylet, etc.) or a portion of a catheter inclusive of at least a portion of the stylet (e.g., tip, segment of catheter, etc.) or (ii) the entirety or a substantial portion of the stylet or catheter within the body of a patient (hereinafter, described as the “physical state of the stylet” or the “physical state of the catheter”). According to one embodiment of the disclosure, the returned information may be obtained from reflected light signals of different spectral widths, where each reflected light signal corresponds to a portion of broadband incident light propagating along a core of the multi-core optical fiber (hereinafter, “core fiber”) that is reflected back over the core fiber by a particular sensor located on the core fiber. One illustrative example of the returned information may pertain to a change in signal characteristics of the reflected light signal returned from the sensor, where wavelength shift is correlated to (mechanical) strain on the core fiber.

(9) In some embodiments in which the stylet includes a multi-core optical fiber, each core fiber utilizes a plurality of sensors and each sensor is configured to reflect a different spectral range of the incident light (e.g., different light frequency range). Based on the type and degree of strain asserted on each core fiber, the sensors associated with that core fiber may alter (shift) the wavelength of the reflected light to convey the type and degree of stain on that core fiber at those locations of the stylet occupied by the sensors. The sensors are spatially distributed at various

locations of the core fiber between a proximal end and a distal end of the stylet so that shape sensing of the stylet may be conducted based on analytics of the wavelength shifts. Herein, the shape sensing functionality is paired with the ability to simultaneously pass an electrical signal through the same member (stylet) through conductive medium included as part of the stylet.

(10) More specifically, in some embodiments each core fiber of the multi-core optical fiber is configured with an array of sensors, which are spatially distributed over a prescribed length of the core fiber to generally sense external strain those regions of the core fiber occupied by the sensor. Given that each sensor positioned along the same core fiber is configured to reflect light of a different, specific spectral width, the array of sensors enable distributed measurements throughout the prescribed length of the multi-core optical fiber. These distributed measurements may include wavelength shifts having a correlation with strain experienced by the sensor.

(11) According to one embodiment of the disclosure, each sensor may operate as a reflective grating such as a fiber Bragg grating (FBG), namely an intrinsic sensor corresponding to a permanent, periodic refractive index change inscribed into the core fiber. Stated differently, the sensor operates as a light reflective mirror for a specific spectral width (e.g., a specific wavelength or specific range of wavelengths). As a result, as broadband incident light is supplied by an optical light source and propagates through a particular core fiber, upon reaching a first sensor of the distributed array of sensors for that core fiber, light of a prescribed spectral width associated with the first sensor is reflected back to an optical receiver within a console, including a display and the optical light source. The remaining spectrum of the incident light continues propagation through the core fiber toward a distal end of the stylet. The remaining spectrum of the incident light may encounter other sensors from the distributed array of sensors, where each of these sensors is fabricated to reflect light with different specific spectral widths to provide distributed measurements, as described above.

(12) During operation, multiple light reflections (also referred to as “reflected light signals”) are returned to the console from each of the plurality of core fibers of the multi-core optical fiber. Each reflected light signal may be uniquely associated with a different spectral width. Information associated with the reflected light signals may be used to determine a three-dimensional representation of the physical state of the stylet within the body of a patient. Herein, the core fibers are spatially separated with the cladding of the multi-mode optical fiber and each core fiber is configured to separately return light of different spectral widths (e.g., specific light wavelength or a range of light wavelengths) reflected from the distributed array of sensors fabricated in each of the core fibers. A comparison of detected shifts in wavelength of the reflected light returned by a center core fiber (operating as a reference) and the surrounding, periphery core fibers may be used to determine the physical state of the stylet.

(13) During vasculature insertion and advancement of the catheter, the clinician may rely on the console to visualize a current physical state (e.g., shape) of a catheter guided by the stylet to avoid potential path deviations. As the periphery core fibers reside at spatially different locations within the cladding of the multi-mode optical fiber, changes in angular orientation (such as bending with respect to the center core fiber, etc.) of the stylet imposes different types (e.g., compression or tension) and degrees of strain on each of the periphery core fibers as well as the center core fiber. The different types and/or degree of strain may cause the sensors of the core fibers to apply different wavelength shifts, which can be measured to extrapolate the physical state of the stylet (catheter).

(14) Embodiments of the disclosure may include a combination of one or more of the methodologies to determine when a body of implementation (e.g., catheter, guidewire, and/or stylet) has deviated from its target trajectory (e.g., into the right atrium) and instead into an undesired location (e.g., the Azygos vein). Certain embodiments of the disclosure pertain to distal tip location detection using fiber optic shape sensing such that deviation of the body of implementation into the negative-Z plane (dorsal movement of the body of implementation) can be

detected and identified using analysis of reflected light through a multi-core optical fiber as discussed below. For example, the use of fiber optic shape sensing may analyze the reflected light in comparison to predetermined anatomical angles, deviation from an identified reference plane (with identified anterior/posterior orientation), and/or deviation from a predetermined anatomical frame.

(15) Further embodiments of the disclosure pertain to the use of fiber optic shape sensing to detect fluctuation of the body of implementation. For example, deviation of the advancement of the body of implementation out of the SVC into the Azygos vein is identified via a reduction in fluctuations in the body of implementation. Additionally, intravascular ECG monitoring may be combined with either or both of the fiber optic shape sensing methodologies referenced above to detect deviation of the advancement of the body of implementation into the Azygos vein as the detected P-wave of the intravascular ECG decreases in slightly in amplitude even as the body of implementation is advanced towards the sinoatrial (SA) node. Additionally, or in the alternative, impedance/conductance sensing may be combined with either or both of the fiber optic shape sensing methodologies and, optionally, the ECG intravascular ECG monitoring to detect deviation of the advancement of the body of implementation into the Azygos vein. For instance, as the body of implementation deviates into the Azygos vein the smaller diameter vessel is characterized by a varied impedance/conductance.

(16) In yet other embodiments, the direction of the blood flow may be utilized in combination with any of the fiber optic shape sensing methodologies, intravascular ECG monitoring and/or impedance/conductance sensing referenced above. For instance, as the body of implementation deviates into the Azygos vein, the flow of blood will change from in-line with the advancement of the body of implementation to against the advancement of the body of implementation, which may be detected using pulse oximetry and/or blood flow Doppler. For instance, detection using pulse oximetry includes measurement and analysis of the oxygen levels within the blood as the body of implementation advances through the vasculature. Specifically, analysis of the oxygen levels may vary from vessel to vessel such that detection of deviation of the distal tip of the body of implementation into the Azygos vein may be detected when the measured oxygen level decreases when the distal tip is in the heart. Specifically, the oxygen level may decrease as the distal tip of the body of implementation advances from a larger vessel (SVC) to a smaller vessel (Azygos vein).

(17) Some embodiments herein disclose a medical device system for detecting malposition of a medical device within a vessel of a patient, such as an Azygos vein, the system including the medical device comprising a multi-core optical fiber having a plurality of core fibers, each of the plurality of core fibers including a plurality of sensors distributed along a longitudinal length of a corresponding core fiber and each sensor of the plurality of sensors being configured to (i) reflect a light signal of a different spectral width based on received incident light, and (ii) change a characteristic of the reflected light signal for use in determining a physical state of the multi-core optical fiber and a console. The console includes one or more processors and a non-transitory computer-readable medium having stored thereon logic, when executed by the one or more processors, causes operations including providing a broadband incident light signal to the multi-core optical fiber, receiving reflected light signals of different spectral widths of the broadband incident light reflected by each of the plurality of sensors, processing the reflected light signals associated with the plurality of core fibers, and determining whether the medical device has entered the Azygos vein of the patient based on the reflected light signals.

(18) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on a shape of the medical device indicated by the reflected light signals. In some embodiments, the shape of the medical device is indicated by the reflected light signals is utilized as input to a machine-learning configured to process the input and provide a result indicating a confidence level as to whether the shape of the medical device indicates entry into the Azygos vein of the patient. In some embodiments, the determining operation determines

whether the medical device has entered the Azygos vein is based a result of heuristics performed on the shape of the medical device indicated by the reflected light signals. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on an amount of fluctuation of the medical device indicated by the reflected light signals.

(19) In particular embodiments, the amount of fluctuation of the medical device is an amount of fluctuation at a distal tip of the medical device. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and impedance sensing of advancement of the medical device through a vasculature of the patient. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on (i) the shape of the medical device indicated by the reflected light signals, (ii) electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient, and (iii) impedance sensing of the advancement of the medical device through the vasculature of the patient.

(20) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and detection of a direction of blood flow within a portion of a vasculature of the patient in which the medical device is currently disposed. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and one or more of (i) electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient, (ii) impedance sensing of the advancement of the medical device through the vasculature of the patient, or (iii) detection of a direction of blood flow within a portion of the vasculature of the patient in which the medical device is currently disposed.

(21) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on (i) the shape of the medical device indicated by the reflected light signals, (ii) electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient, (iii) impedance sensing of the advancement of the medical device through the vasculature of the patient, and (iv) detection of a direction of blood flow within a portion of the vasculature of the patient in which the medical device is currently disposed.

(22) In particular embodiments, the different types of strain include compression and tension. In other embodiments, the medical device includes an elongated shape and is inserted into a vasculature of the body of the patient. In some embodiments, the medical device is a stylet removably inserted into a lumen of a catheter assembly for placement of a distal tip of the catheter assembly in a superior vena cava of the vasculature. In yet other embodiments, at least two of the plurality of core fibers to experience different types of strain in response to changes in an orientation of the multi-core optical fiber. In yet further embodiments, each of the plurality of sensors is a reflective grating, where each reflective grating alters its reflected light signal by applying a wavelength shift dependent on a strain experienced by the reflective grating.

(23) Further embodiments relate to a method for placing a medical device into a body of a patient, the method comprising providing a broadband incident light signal to a multi-core optical fiber included within the medical device, wherein the multi-core optical fiber includes a plurality of core fibers, each of the plurality of core fibers including a plurality of reflective gratings distributed along a longitudinal length of a corresponding core fiber and each of the plurality of reflective gratings being configured to (i) reflect a light signal of a different spectral width based on received incident light, and (ii) change a characteristic of the reflected light signal for use in determining a physical state of the multi-core optical fiber, receiving reflected light signals of different spectral

widths of the broadband incident light reflected by each of a plurality of reflective gratings, processing the reflected light signals associated with the plurality of core fibers, and determining whether the medical device has entered the Azygos vein of the patient based on the reflected light signals.

(24) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on a shape of the medical device indicated by the reflected light signals. In some embodiments, the shape of the medical device is indicated by the reflected light signals is utilized as input to a machine-learning configured to process the input and provide a result indicating a confidence level as to whether the shape of the medical device indicates entry into the Azygos vein of the patient. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based a result of heuristics performed on the shape of the medical device indicated by the reflected light signals. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on an amount of fluctuation of the medical device indicated by the reflected light signals.

(25) In particular embodiments, the amount of fluctuation of the medical device is an amount of fluctuation at a distal tip of the medical device. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and impedance sensing of advancement of the medical device through a vasculature of the patient. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on (i) the shape of the medical device indicated by the reflected light signals, (ii) electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient, and (iii) impedance sensing of the advancement of the medical device through the vasculature of the patient.

(26) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and detection of a direction of blood flow within a portion of a vasculature of the patient in which the medical device is currently disposed. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and one or more of (i) electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient, (ii) impedance sensing of the advancement of the medical device through the vasculature of the patient, or (iii) detection of a direction of blood flow within a portion of the vasculature of the patient in which the medical device is currently disposed.

(27) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on (i) the shape of the medical device indicated by the reflected light signals, (ii) electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient, (iii) impedance sensing of the advancement of the medical device through the vasculature of the patient, and (iv) detection of a direction of blood flow within a portion of the vasculature of the patient in which the medical device is currently disposed.

(28) In particular embodiments, the different types of strain include compression and tension. In other embodiments, the medical device includes an elongated shape and is inserted into a vasculature of the body of the patient. In some embodiments, the medical device is a stylet removably inserted into a lumen of a catheter assembly for placement of a distal tip of the catheter assembly in a superior vena cava of the vasculature. In yet other embodiments, at least two of the plurality of core fibers to experience different types of strain in response to changes in an orientation of the multi-core optical fiber. In yet further embodiments, each of the plurality of

sensors is a reflective grating, where each reflective grating alters its reflected light signal by applying a wavelength shift dependent on a strain experienced by the reflective grating.

(29) Some embodiments disclose a non-transitory computer-readable medium having stored thereon logic that, when executed by the one or more processors, causes operations. The operations include providing a broadband incident light signal to a multi-core optical fiber included within the medical device, wherein the multi-core optical fiber includes a plurality of core fibers, each of the plurality of core fibers including a plurality of reflective gratings distributed along a longitudinal length of a corresponding core fiber and each reflective grating of the plurality of reflective gratings being configured to (i) reflect a light signal of a different spectral width based on received incident light, and (ii) change a characteristic of the reflected light signal for use in determining a physical state of the multi-core optical fiber, receiving reflected light signals of different spectral widths of the broadband incident reflected each of the plurality of reflective gratings, processing the reflected light signals associated with the plurality of core fibers, and determining whether the medical device has entered the Azygos vein of the patient based on the reflected light signals.

(30) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on a shape of the medical device indicated by the reflected light signals. In some embodiments, the shape of the medical device is indicated by the reflected light signals is utilized as input to a machine-learning configured to process the input and provide a result indicating a confidence level as to whether the shape of the medical device indicates entry into the Azygos vein of the patient. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based a result of heuristics performed on the shape of the medical device indicated by the reflected light signals. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on an amount of fluctuation of the medical device indicated by the reflected light signals.

(31) In particular embodiments, the amount of fluctuation of the medical device is an amount of fluctuation at a distal tip of the medical device. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and impedance sensing of advancement of the medical device through a vasculature of the patient. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on (i) the shape of the medical device indicated by the reflected light signals, (ii) electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient, and (iii) impedance sensing of the advancement of the medical device through the vasculature of the patient.

(32) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and detection of a direction of blood flow within a portion of a vasculature of the patient in which the medical device is currently disposed. In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on the shape of the medical device indicated by the reflected light signals and one or more of (i) electrocardiogram (ECG) monitoring of advancement of the medical device through a vasculature of the patient, (ii) impedance sensing of the advancement of the medical device through the vasculature of the patient, or (iii) detection of a direction of blood flow within a portion of the vasculature of the patient in which the medical device is currently disposed.

(33) In some embodiments, the determining operation determines whether the medical device has entered the Azygos vein is based on (i) the shape of the medical device indicated by the reflected light signals, (ii) electrocardiogram (ECG) monitoring of advancement of the medical device

through a vasculature of the patient, (iii) impedance sensing of the advancement of the medical device through the vasculature of the patient, and (iv) detection of a direction of blood flow within a portion of the vasculature of the patient in which the medical device is currently disposed.

(34) In particular embodiments, the different types of strain include compression and tension. In other embodiments, the medical device includes an elongated shape and is inserted into a vasculature of the body of the patient. In some embodiments, the medical device is a stylet removably inserted into a lumen of a catheter assembly for placement of a distal tip of the catheter assembly in a superior vena cava of the vasculature. In yet other embodiments, at least two of the plurality of core fibers to experience different types of strain in response to changes in an orientation of the multi-core optical fiber. In yet further embodiments, each of the plurality of sensors is a reflective grating, where each reflective grating alters its reflected light signal by applying a wavelength shift dependent on a strain experienced by the reflective grating.

(35) These and other features of the concepts provided herein will become more apparent to those of skill in the art in view of the accompanying drawings and following description, which disclose particular embodiments of such concepts in greater detail.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments of the disclosure are illustrated by way of example and not by way of limitation in the figures of the accompanying drawings, in which like references indicate similar elements and in which:

(2) FIG. 1A is an illustrative embodiment of a medical instrument monitoring system including a medical instrument with optic shape sensing and fiber optic-based oximetry capabilities in accordance with some embodiments;

(3) FIG. 1B is an alternative illustrative embodiment of the medical instrument monitoring system **100** in accordance with some embodiments;

(4) FIG. 2 is an exemplary embodiment of a structure of a section of the multi-core optical fiber included within the stylet **120** of FIG. 1A in accordance with some embodiments;

(5) FIG. 3A is a first exemplary embodiment of the stylet of FIG. 1A supporting both an optical and electrical signaling in accordance with some embodiments;

(6) FIG. 3B is a cross sectional view of the stylet of FIG. 3A in accordance with some embodiments;

(7) FIG. 4A is a second exemplary embodiment of the stylet of FIG. 1B in accordance with some embodiments;

(8) FIG. 4B is a cross sectional view of the stylet of FIG. 4A in accordance with some embodiments;

(9) FIG. 5A is an elevation view of a first illustrative embodiment of a catheter including integrated tubing, a diametrically disposed septum, and micro-lumens formed within the tubing and septum in accordance with some embodiments;

(10) FIG. 5B is a perspective view of the first illustrative embodiment of the catheter of FIG. 5A including core fibers installed within the micro-lumens in accordance with some embodiments;

(11) FIGS. 6A-6B are flowcharts of the methods of operations conducted by the medical instrument monitoring system of FIGS. 1A-1B to achieve optic 3D shape sensing in accordance with some embodiments;

(12) FIG. 7A is an exemplary embodiment of the medical instrument monitoring system of FIG. 1A during operation and insertion of the catheter into a patient in accordance with some embodiments;

(13) FIG. 7B is a detailed view of the stylet of FIG. 7A in the Superior Vena Cava (SVC) advancing toward the right atrium of the patient in accordance with some embodiments;

(14) FIG. 8 is a first illustration of a stylet advancing through a patient's vasculature toward the right atrium of the patient's heart in accordance with some embodiments;

(15) FIG. 9 is a second illustration of a stylet advancing through a patient's vasculature toward the right atrium of the patient's heart in accordance with some embodiments;

(16) FIGS. 10A-10C are illustrations depicting an electrode configuration that provides for acquisition of endovascular ECG data in accordance some embodiments;

(17) FIG. 11 is an illustration of an exemplary peripherally inserted central catheter in accordance with some embodiments; and

(18) FIG. 12 is an illustration of a system utilizing a second embodiment of a peripherally inserted central in conjunction with two electrode pads in accordance with some embodiments.

DETAILED DESCRIPTION

(19) Before some particular embodiments are disclosed in greater detail, it should be understood that the particular embodiments disclosed herein do not limit the scope of the concepts provided herein. It should also be understood that a particular embodiment disclosed herein can have features that can be readily separated from the particular embodiment and optionally combined with or substituted for features of any of a number of other embodiments disclosed herein.

(20) Regarding terms used herein, it should also be understood the terms are for the purpose of describing some particular embodiments, and the terms do not limit the scope of the concepts provided herein. Ordinal numbers (e.g., first, second, third, etc.) are generally used to distinguish or identify different features or steps in a group of features or steps, and do not supply a serial or numerical limitation. For example, "first," "second," and "third" features or steps need not necessarily appear in that order, and the particular embodiments including such features or steps need not necessarily be limited to the three features or steps. Labels such as "left," "right," "top," "bottom," "front," "back," and the like are used for convenience and are not intended to imply, for example, any particular fixed location, orientation, or direction. Instead, such labels are used to reflect, for example, relative location, orientation, or directions. Singular forms of "a," "an," and "the" include plural references unless the context clearly dictates otherwise.

(21) With respect to "proximal," a "proximal portion" or a "proximal end portion" of, for example, a probe disclosed herein includes a portion of the probe intended to be near a clinician when the probe is used on a patient. Likewise, a "proximal length" of, for example, the probe includes a length of the probe intended to be near the clinician when the probe is used on the patient. A "proximal end" of, for example, the probe includes an end of the probe intended to be near the clinician when the probe is used on the patient. The proximal portion, the proximal end portion, or the proximal length of the probe can include the proximal end of the probe; however, the proximal portion, the proximal end portion, or the proximal length of the probe need not include the proximal end of the probe. That is, unless context suggests otherwise, the proximal portion, the proximal end portion, or the proximal length of the probe is not a terminal portion or terminal length of the probe.

(22) With respect to "distal," a "distal portion" or a "distal end portion" of, for example, a probe disclosed herein includes a portion of the probe intended to be near or in a patient when the probe is used on the patient. Likewise, a "distal length" of, for example, the probe includes a length of the probe intended to be near or in the patient when the probe is used on the patient. A "distal end" of, for example, the probe includes an end of the probe intended to be near or in the patient when the probe is used on the patient. The distal portion, the distal end portion, or the distal length of the probe can include the distal end of the probe; however, the distal portion, the distal end portion, or the distal length of the probe need not include the distal end of the probe. That is, unless context suggests otherwise, the distal portion, the distal end portion, or the distal length of the probe is not a terminal portion or terminal length of the probe.

(23) The term "logic" may be representative of hardware, firmware or software that is configured to perform one or more functions. As hardware, the term logic may refer to or include circuitry

having data processing and/or storage functionality. Examples of such circuitry may include, but are not limited or restricted to a hardware processor (e.g., microprocessor, one or more processor cores, a digital signal processor, a programmable gate array, a microcontroller, an application specific integrated circuit “ASIC”, etc.), a semiconductor memory, or combinatorial elements.

(24) Additionally, or in the alternative, the term logic may refer to or include software such as one or more processes, one or more instances, Application Programming Interface(s) (API), subroutine(s), function(s), applet(s), servlet(s), routine(s), source code, object code, shared library/dynamic link library (dll), or even one or more instructions. This software may be stored in any type of a suitable non-transitory storage medium, or transitory storage medium (e.g., electrical, optical, acoustical or other form of propagated signals such as carrier waves, infrared signals, or digital signals). Examples of a non-transitory storage medium may include, but are not limited or restricted to a programmable circuit; non-persistent storage such as volatile memory (e.g., any type of random access memory “RAM”); or persistent storage such as non-volatile memory (e.g., read-only memory “ROM”, power-backed RAM, flash memory, phase-change memory, etc.), a solid-state drive, hard disk drive, an optical disc drive, or a portable memory device. As firmware, the logic may be stored in persistent storage.

(25) Referring to FIG. 1A, an illustrative embodiment of a medical instrument monitoring system including a medical instrument with optic shape sensing and fiber optic-based oximetry capabilities is shown in accordance with some embodiments. As shown, the system **100** generally includes a console **110** and a stylet assembly **119** communicatively coupled to the console **110**. For this embodiment, the stylet assembly **119** includes an elongate probe (e.g., stylet) **120** on its distal end **122** and a console connector **133** on its proximal end **124**, where the stylet **120** is configured to advance within a patient vasculature either through, or in conjunction with, a catheter **195**. The console connector **133** enables the stylet assembly **119** to be operably connected to the console **110** via an interconnect **145** including one or more optical fibers **147** (hereinafter, “optical fiber(s)”) and a conductive medium terminated by a single optical/electric connector **146** (or terminated by dual connectors. Herein, the connector **146** is configured to engage (mate) with the console connector **133** to allow for the propagation of light between the console **110** and the stylet assembly **119** as well as the propagation of electrical signals from the stylet **120** to the console **110**.

(26) An exemplary implementation of the console **110** includes a processor **160**, a memory **165**, a display **170** and optical logic **180**, although it is appreciated that the console **110** can take one of a variety of forms and may include additional components (e.g., power supplies, ports, interfaces, etc.) that are not directed to aspects of the disclosure. An illustrative example of the console **110** is illustrated in U.S. Pat. No. 10,992,078, the entire contents of which are incorporated by reference herein. The processor **160**, with access to the memory **165** (e.g., non-volatile memory or non-transitory, computer-readable medium), is included to control functionality of the console **110** during operation. As shown, the display **170** may be a liquid crystal diode (LCD) display integrated into the console **110** and employed as a user interface to display information to the clinician, especially during a catheter placement procedure (e.g., cardiac catheterization). In another embodiment, the display **170** may be separate from the console **110**. Although not shown, a user interface is configured to provide user control of the console **110**.

(27) For both of these embodiments, the content depicted by the display **170** may change according to which mode the stylet **120** is configured to operate: optical, TLS, ECG, or another modality. In TLS mode, the content rendered by the display **170** may constitute a two-dimensional (2D) or three-dimensional (3D) representation of the physical state (e.g., length, shape, form, and/or orientation) of the stylet **120** computed from characteristics of reflected light signals **150** returned to the console **110**. The reflected light signals **150** constitute light of a specific spectral width of broadband incident light **155** reflected back to the console **110**. According to one embodiment of the disclosure, the reflected light signals **150** may pertain to various discrete portions (e.g., specific spectral widths) of broadband incident light **155** transmitted from and sourced by the optical logic

180, as described below

(28) According to one embodiment of the disclosure, an activation control **126**, included on the stylet assembly **119**, may be used to set the stylet **120** into a desired operating mode and selectively alter operability of the display **170** by the clinician to assist in medical device placement. For example, based on the modality of the stylet **120**, the display **170** of the console **110** can be employed for optical modality-based guidance during catheter advancement through the vasculature or TLS modality to determine the physical state (e.g., length, form, shape, orientation, etc.) of the stylet **120**. In one embodiment, information from multiple modes, such as optical, TLS or ECG for example, may be displayed concurrently (e.g., at least partially overlapping in time).

(29) Referring still to FIG. **1A**, the optical logic **180** is configured to support operability of the stylet assembly **119** and enable the return of information to the console **110**, which may be used to determine the physical state associated with the stylet **120** along with monitored electrical signals such as ECG signaling via an electrical signaling logic **181** that supports receipt and processing of the received electrical signals from the stylet **120** (e.g., ports, analog-to-digital conversion logic, etc.). The physical state of the stylet **120** may be based on changes in characteristics of the reflected light signals **150** received at the console **110** from the stylet **120**. The characteristics may include shifts in wavelength caused by strain on certain regions of the core fibers integrated within an optical fiber core **135** positioned within or operating as the stylet **120**, as shown below. As discussed herein, the optical fiber core **135** may be comprised of core fibers **137.sub.1-137.sub.M** ($M=1$ for a single core, and $M \geq 2$ for a multi-core), where the core fibers **137.sub.1-137.sub.M** may collectively be referred to as core fiber(s) **137**. Unless otherwise specified or the instant embodiment requires an alternative interpretation, embodiments discussed herein will refer to a multi-core optical fiber **135**. From information associated with the reflected light signals **150**, the console **110** may determine (through computation or extrapolation of the wavelength shifts) the physical state of the stylet **120**, and also that of the catheter **195** configured to receive the stylet **120**.

(30) According to one embodiment of the disclosure, as shown in FIG. **1A**, the optical logic **180** may include a light source **182** and an optical receiver **184**. The light source **182** is configured to transmit the incident light **155** (e.g., broadband) for propagation over the optical fiber(s) **147** included in the interconnect **145**, which are optically connected to the multi-core optical fiber core **135** within the stylet **120**. In one embodiment, the light source **182** is a tunable swept laser, although other suitable light sources can also be employed in addition to a laser, including semi-coherent light sources, LED light sources, etc.

(31) The optical receiver **184** is configured to: (i) receive returned optical signals, namely reflected light signals **150** received from optical fiber-based reflective gratings (sensors) fabricated within each core fiber of the multi-core optical fiber **135** deployed within the stylet **120**, and (ii) translate the reflected light signals **150** into reflection data (from repository **192**), namely data in the form of electrical signals representative of the reflected light signals including wavelength shifts caused by strain. The reflected light signals **150** associated with different spectral widths may include reflected light signals **151** provided from sensors positioned in the center core fiber (reference) of the multi-core optical fiber **135** and reflected light signals **152** provided from sensors positioned in the periphery core fibers of the multi-core optical fiber **135**, as described below. Herein, the optical receiver **184** may be implemented as a photodetector, such as a positive-intrinsic-negative “PIN” photodiode, avalanche photodiode, or the like.

(32) As shown, both the light source **182** and the optical receiver **184** are operably connected to the processor **160**, which governs their operation. Also, the optical receiver **184** is operably coupled to provide the reflection data (from repository **192**) to the memory **165** for storage and processing by reflection data classification logic **190**. The reflection data classification logic **190** may be configured to: (i) identify which core fibers pertain to which of the received reflection data (from repository **192**) and (ii) segregate the reflection data stored with a repository **192** provided from

reflected light signals **150** pertaining to similar regions of the stylet **120** or spectral widths into analysis groups. The reflection data for each analysis group is made available to shape sensing logic **194** for analytics.

(33) According to one embodiment of the disclosure, the shape sensing logic **194** is configured to compare wavelength shifts measured by sensors deployed in each periphery core fiber at the same measurement region of the stylet **120** (or same spectral width) to the wavelength shift at a center core fiber of the multi-core optical fiber **135** positioned along central axis and operating as a neutral axis of bending. From these analytics, the shape sensing logic **194** may determine the shape the core fibers have taken in 3D space and may further determine the current physical state of the catheter **195** in 3D space for rendering on the display **170**.

(34) According to one embodiment of the disclosure, the shape sensing logic **194** may generate a rendering of the current physical state of the stylet **120** (and potentially the catheter **195**), based on heuristics or run-time analytics. For example, the shape sensing logic **194** may be configured in accordance with machine-learning techniques to access a data store (library) with pre-stored data (e.g., images, etc.) pertaining to different regions of the stylet **120** (or catheter **195**) in which reflected light from core fibers have previously experienced similar or identical wavelength shifts. From the pre-stored data, the current physical state of the stylet **120** (or catheter **195**) may be rendered. Alternatively, as another example, the shape sensing logic **194** may be configured to determine, during run-time, changes in the physical state of each region of the multi-core optical fiber **135** based on at least: (i) resultant wavelength shifts experienced by different core fibers within the optical fiber **135**, and (ii) the relationship of these wavelength shifts generated by sensors positioned along different periphery core fibers at the same cross-sectional region of the multi-core optical fiber **135** to the wavelength shift generated by a sensor of the center core fiber at the same cross-sectional region. It is contemplated that other processes and procedures may be performed to utilize the wavelength shifts as measured by sensors along each of the core fibers within the multi-core optical fiber **135** to render appropriate changes in the physical state of the stylet **120** (and/or catheter **195**), especially to enable guidance of the stylet **120**, when positioned at a distal tip of the catheter **195**, within the vasculature of the patient and at a desired destination within the body.

(35) The console **110** may further include electrical signaling logic **181**, which is positioned to receive one or more electrical signals from the stylet **120**. The stylet **120** is configured to support both optical connectivity as well as electrical connectivity. The electrical signaling logic **181** receives the electrical signals (e.g., ECG signals) from the stylet **120** via the conductive medium. The electrical signals may be processed by electrical signal logic **196**, executed by the processor **160**, to determine ECG waveforms for display.

(36) Additionally, the console **110** includes a fluctuation logic **198** that is configured to analyze at least a subset of the wavelength shifts measured by sensors deployed in each of the core fibers **137**. In particular, the fluctuation logic **198** is configured to analyze wavelength shifts measured by sensors of core fibers **137**, where such corresponds to an analysis of the fluctuation of the distal tip of the stylet **120** (or “tip fluctuation analysis”). In some embodiments, the fluctuation logic **198** measures analyzes the wavelength shifts measured by sensors at a distal end of the core fibers **137**. The tip fluctuation analysis includes at least a correlation of detected movements of the distal tip of the stylet **120** (or other medical device or instrument) with experiential knowledge comprising previously detected movements (fluctuations), and optionally, other current measurements such as ECG signals. The experiential knowledge may include previously detected movements in various locations within the vasculature (e.g., SVC, Inferior Vena Cava (IVC), right atrium, azygos vein, other blood vessels such as arteries and veins) under normal, healthy conditions and in the presence of defects (e.g., vessel constriction, vasospasm, vessel occlusion, etc.). Thus, the tip fluctuation analysis may result in a confirmation of tip location and/or detection of a defect affecting a blood vessel.

(37) It should be noted that the fluctuation logic **198** need not perform the same analyses as the shape sensing logic **194**. For instance, the shape sensing logic **194** determines a 3D shape of the stylet **120** by comparing wavelength shifts in outer core fibers of a multi-core optical fiber to a center, reference core fiber. The fluctuation logic **198** may instead correlate the wavelength shifts to previously measured wavelength shifts and optionally other current measurements without distinguishing between wavelength shifts of outer core fibers and a center, reference core fiber as the tip fluctuation analysis need not consider direction or shape within a 3D space.

(38) In some embodiments, e.g., those directed at tip location confirmation, the analysis of the fluctuation logic **198** may utilize electrical signals (e.g., ECG signals) measured by the electrical signaling logic **181**. For example, the fluctuation logic **198** may compare the movements of a subsection of the stylet **120** (e.g., the distal tip) with electrical signals indicating impulses of the heart (e.g., the heartbeat). Such a comparison may reveal whether the distal tip is within the SVC or the right atrium based on how closely the movements correspond to a rhythmic heartbeat.

(39) In various embodiments, a display and/or alert may be generated based on the fluctuation analysis. For instance, the fluctuation logic **198** may generate a graphic illustrating the detected fluctuation compared to previously detected tip fluctuations and/or the anatomical movements of the patient body such as rhythmic pulses of the heart and/or expanding and contracting of the lungs. In one embodiment, such a graphic may include a dynamic visualization of the present medical device moving in accordance with the detected fluctuations adjacent to a secondary medical device moving in accordance with previously detected tip fluctuations. In some embodiments, the location of a subsection of the medical device may be obtained from the shape sensing logic **194** and the dynamic visualization may be location-specific (e.g., such that the previously detected fluctuations illustrate expected fluctuations for the current location of the subsection). In alternative embodiments, the dynamic visualization may illustrate a comparison of the dynamic movements of the subsection to one or more subsections moving in accordance with previously detected fluctuations of one or more defects affecting the blood vessel.

(40) According to one embodiment of the disclosure, the fluctuation logic **198** may determine whether movements of one or more subsections of the stylet **120** indicate a location of a particular subsection of the stylet **120** or a defect affecting a blood vessel and, as a result, of the catheter **195**, based on heuristics or run-time analytics. For example, the fluctuation logic **198** may be configured in accordance with machine-learning techniques to access a data store (library) with pre-stored data (e.g., experiential knowledge of previously detected tip fluctuation data, etc.) pertaining to different regions (subsections) of the stylet **120**. Specifically, such an embodiment may include processing of a machine-learning model trained using the experiential knowledge, where the detected fluctuations serve as input to the trained model and processing of the trained model results in a determination as to how closely the detected fluctuations correlate to one or more locations within the vasculature of the patient and/or one or more defects affecting a blood vessel.

(41) In some embodiments, the fluctuation logic **198** may be configured to determine, during run-time, whether movements of one or more subsections of the stylet **120** (and the catheter **195**) indicate a location of a particular subsection of the stylet **120** or a defect affecting a blood vessel, based on at least (i) resultant wavelength shifts experienced by the core fibers **137** within the one or more subsections, and (ii) the correlation of these wavelength shifts generated by sensors positioned along different core fibers at the same cross-sectional region of the stylet **120** (or the catheter **195**) to previously detected wavelength shifts generated by corresponding sensors in a core fiber at the same cross-sectional region. It is contemplated that other processes and procedures may be performed to utilize the wavelength shifts as measured by sensors along each of the core fibers **137** to render appropriate movements in the distal tip of the stylet **120** and/or the catheter **195**.

(42) Referring to FIG. **1B**, an alternative exemplary embodiment of a medical instrument monitoring system **100** is shown. Herein, the medical instrument monitoring system **100** features a console **110** and a medical instrument **130** communicatively coupled to the console **110**. For this

embodiment, the medical instrument **130** corresponds to a catheter, which features an integrated tubing with two or more lumen extending between a proximal end **131** and a distal end **132** of the integrated tubing. The integrated tubing (sometimes referred to as “catheter tubing”) is in communication with one or more extension legs **140** via a bifurcation hub **142**. An optical-based catheter connector **144** may be included on a proximal end of at least one of the extension legs **140** to enable the catheter **130** to operably connect to the console **110** via an interconnect **145** or another suitable component. Herein, the interconnect **145** may include a connector **146** that, when coupled to the optical-based catheter connector **144**, establishes optical connectivity between one or more optical fibers **147** (hereinafter, “optical fiber(s)”) included as part of the interconnect **145** and core fibers **137** deployed within the catheter **130** and integrated into the tubing. Alternatively, a different combination of connectors, including one or more adapters, may be used to optically connect the optical fiber(s) **147** to the core fibers **137** within the catheter **130**. The core fibers **137** deployed within the catheter **130** as illustrated in FIG. 1B include the same characteristics and perform the same functionalities as the core fibers **137** deployed within the stylet **120** of FIG. 1A.

(43) The optical logic **180** is configured to support graphical rendering of the catheter **130**, most notably the integrated tubing of the catheter **130**, based on characteristics of the reflected light signals **150** received from the catheter **130**. The characteristics may include shifts in wavelength caused by strain on certain regions of the core fibers **137** integrated within (or along) a wall of the integrated tubing, which may be used to determine (through computation or extrapolation of the wavelength shifts) the physical state of the catheter **130**, notably its integrated tubing or a portion of the integrated tubing such as a tip or distal end of the tubing to read fluctuations (real-time movement) of the tip (or distal end).

(44) More specifically, the optical logic **180** includes a light source **182**. The light source **182** is configured to transmit the broadband incident light **155** for propagation over the optical fiber(s) **147** included in the interconnect **145**, which are optically connected to multiple core fibers **137** within the catheter tubing. Herein, the optical receiver **184** is configured to: (i) receive returned optical signals, namely reflected light signals **150** received from optical fiber-based reflective gratings (sensors) fabricated within each of the core fibers **137** deployed within the catheter **130**, and (ii) translate the reflected light signals **150** into reflection data (from repository **192**), namely data in the form of electrical signals representative of the reflected light signals including wavelength shifts caused by strain. The reflected light signals **150** associated with different spectral widths include reflected light signals **151** provided from sensors positioned in the center core fiber (reference) of the catheter **130** and reflected light signals **152** provided from sensors positioned in the outer core fibers of the catheter **130**, as described below.

(45) As noted above, the shape sensing logic **194** is configured to compare wavelength shifts measured by sensors deployed in each outer core fiber at the same measurement region of the catheter (or same spectral width) to the wavelength shift at the center core fiber positioned along central axis and operating as a neutral axis of bending. From these analytics, the shape sensing logic **190** may determine the shape the core fibers have taken in 3D space and may further determine the current physical state of the catheter **130** in 3D space for rendering on the display **170**.

(46) According to one embodiment of the disclosure, the shape sensing logic **194** may generate a rendering of the current physical state of the catheter **130**, especially the integrated tubing, based on heuristics or run-time analytics. For example, the shape sensing logic **194** may be configured in accordance with machine-learning techniques to access a data store (library) with pre-stored data (e.g., images, etc.) pertaining to different regions of the catheter **130** in which the core fibers **137** experienced similar or identical wavelength shifts. From the pre-stored data, the current physical state of the catheter **130** may be rendered. Alternatively, as another example, the shape sensing logic **194** may be configured to determine, during run-time, changes in the physical state of each region of the catheter **130**, notably the tubing, based on at least (i) resultant wavelength shifts

experienced by the core fibers **137** and (ii) the relationship of these wavelength shifts generated by sensors positioned along different outer core fibers at the same cross-sectional region of the catheter **130** to the wavelength shift generated by a sensor of the center core fiber at the same cross-sectional region. It is contemplated that other processes and procedures may be performed to utilize the wavelength shifts as measured by sensors along each of the core fibers **137** to render appropriate changes in the physical state of the catheter **130**.

(47) Referring to FIG. 2, an exemplary embodiment of a structure of a section of the multi-core optical fiber included within the stylet **120** of FIG. 1A is shown in accordance with some embodiments. The multi-core optical fiber section **200** of the multi-core optical fiber **135** depicts certain core fibers **137.sub.1-137.sub.M** ($M \geq 2$, $M=4$ as shown, see FIG. 3A) along with the spatial relationship between sensors (e.g., reflective gratings) **210.sub.11-210.sub.NM** ($N \geq 2$; $M \geq 2$) present within the core fibers **137.sub.1-137.sub.M**, respectively. As noted above, the core fibers **137.sub.1-137.sub.M** may be collectively referred to as “the core fibers **137**.”

(48) As shown, the section **200** is subdivided into a plurality of cross-sectional regions **220.sub.1-220.sub.N**, where each cross-sectional region **220.sub.1-220.sub.N** corresponds to reflective gratings **210.sub.11-210.sub.14 . . . 210.sub.N1-210.sub.N4**. Some or all of the cross-sectional regions **220.sub.1 . . . 220.sub.N** may be static (e.g., prescribed length) or may be dynamic (e.g., vary in size among the regions **220.sub.1 . . . 220.sub.N**). A first core fiber **137.sub.1** is positioned substantially along a center (neutral) axis **230** while core fiber **137.sub.2** may be oriented within the cladding of the multi-core optical fiber **135**, from a cross-sectional, front-facing perspective, to be position on “top” the first core fiber **137.sub.1**. In this deployment, the core fibers **137.sub.3** and **137.sub.4** may be positioned “bottom left” and “bottom right” of the first core fiber **137.sub.1**. As examples, FIGS. 3A-4B provides illustrations of such.

(49) Referencing the first core fiber **137.sub.1** as an illustrative example, when the stylet **120** is operative, each of the reflective gratings **210.sub.1-210.sub.N** reflects light for a different spectral width. As shown, each of the gratings **210.sub.11-210.sub.Ni** ($1 \leq i \leq M$) is associated with a different, specific spectral width, which would be represented by different center frequencies of **f.sub.1 . . . f.sub.N**, where neighboring spectral widths reflected by neighboring gratings are non-overlapping according to one embodiment of the disclosure.

(50) Herein, positioned in different core fibers **137.sub.2-137.sub.3** but along at the same cross-sectional regions **220-220.sub.N** of the multi-core optical fiber **135**, the gratings **210.sub.12-210.sub.N2** and **210.sub.13-210.sub.N3** are configured to reflect incoming light at same (or substantially similar) center frequency. As a result, the reflected light returns information that allows for a determination of the physical state of the optical fibers **137** (and the stylet **120**) based on wavelength shifts measured from the returned, reflected light. In particular, strain (e.g., compression or tension) applied to the multi-core optical fiber **135** (e.g., at least core fibers **137.sub.2-137.sub.3**) results in wavelength shifts associated with the returned, reflected light. Based on different locations, the core fibers **137.sub.1-137.sub.4** experience different types and degree of strain based on angular path changes as the stylet **120** advances in the patient.

(51) For example, with respect to the multi-core optical fiber section **200** of FIG. 2, in response to angular (e.g., radial) movement of the stylet **120** is in the left-veering direction, the fourth core fiber **137.sub.4** (see FIG. 3A) of the multi-core optical fiber **135** with the shortest radius during movement (e.g., core fiber closest to a direction of angular change) would exhibit compression (e.g., forces to shorten length). At the same time, the third core fiber **137.sub.3** with the longest radius during movement (e.g., core fiber furthest from the direction of angular change) would exhibit tension (e.g., forces to increase length). As these forces are different and unequal, the reflected light from reflective gratings **210.sub.N2** and **210.sub.N3** associated with the core fibers **137.sub.2** and **137.sub.3** will exhibit different changes in wavelength. The differences in wavelength shift of the reflected light signals **150** can be used to extrapolate the physical configuration of the stylet **120** by determining the degrees of wavelength change caused by

compression/tension for each of the periphery fibers (e.g., the second core fiber 137.sub.2 and the third core fiber 137.sub.3) in comparison to the wavelength of the reference core fiber (e.g., first core fiber 137.sub.1) located along the neutral axis 230 of the multi-core optical fiber 135. These degrees of wavelength change may be used to extrapolate the physical state of the stylet 120. The reflected light signals 150 are reflected back to the console 110 via individual paths over a particular core fiber 137.sub.1-137.sub.M.

(52) Referring to FIG. 3A, a first exemplary embodiment of the stylet of FIG. 1A supporting both an optical and electrical signaling is shown in accordance with some embodiments. Herein, the stylet 120 features a centrally located multi-core optical fiber 135, which includes a cladding 300 and a plurality of core fibers 137.sub.1-137.sub.M ($M \geq 2$; $M=4$) residing within a corresponding plurality of lumens 320.sub.1-320.sub.M. While the multi-core optical fiber 135 is illustrated within four (4) core fibers 1371-1374, a greater number of core fibers 137.sub.1-137.sub.M ($M > 4$) may be deployed to provide a more detailed three-dimensional sensing of the physical state (e.g., shape, etc.) of the multi-core optical fiber 135 and the stylet 120 deploying the optical fiber 135.

(53) For this embodiment of the disclosure, the multi-core optical fiber 135 is encapsulated within a concentric braided tubing 310 positioned over a low coefficient of friction layer 335. The braided tubing 310 may feature a “mesh” construction, in which the spacing between the intersecting conductive elements is selected based on the degree of rigidity desired for the stylet 120, as a greater spacing may provide a lesser rigidity, and thereby, a more pliable stylet 120.

(54) According to this embodiment of the disclosure, as shown in FIGS. 3A-3B, the core fibers 137.sub.1-137.sub.4 include (i) a central core fiber 137.sub.1 and (ii) a plurality of periphery core fibers 137.sub.2-137.sub.4, which are maintained within lumens 320.sub.1-320.sub.4 formed in the cladding 300. According to one embodiment of the disclosure, one or more of the lumen 320.sub.1-320.sub.4 may be configured with a diameter sized to be greater than the diameter of the core fibers 137.sub.1-137.sub.4. By avoiding a majority of the surface area of the core fibers 137.sub.1-137.sub.4 from being in direct physical contact with a wall surface of the lumens 320.sub.1-320.sub.4, the wavelength changes to the incident light are caused by angular deviations in the multi-core optical fiber 135 thereby reducing influence of compression and tension forces being applied to the walls of the lumens 320.sub.1-320.sub.M, not the core fibers 137.sub.1-137.sub.M themselves.

(55) As further shown in FIGS. 3A-3B, the core fibers 137.sub.1-137.sub.4 may include central core fiber 137.sub.1 residing within a first lumen 320.sub.1 formed along the first neutral axis 230 and a plurality of core fibers 137.sub.2-137.sub.4 residing within lumens 320.sub.2-320.sub.4 each formed within different areas of the cladding 300 radiating from the first neutral axis 230. In general, the core fibers 137.sub.2-137.sub.4, exclusive of the central core fiber 137.sub.1, may be positioned at different areas within a cross-sectional area 305 of the cladding 300 to provide sufficient separation to enable three-dimensional sensing of the multi-core optical fiber 135 based on changes in wavelength of incident light propagating through the core fibers 137.sub.2-137.sub.4 and reflected back to the console for analysis.

(56) For example, where the cladding 300 features a circular cross-sectional area 305 as shown in FIG. 3B, the core fibers 137.sub.2-137.sub.4 may be positioned substantially equidistant from each other as measured along a perimeter of the cladding 300, such as at “top” (12 o'clock), “bottom-left” (8 o'clock) and “bottom-right” (4 o'clock) locations as shown. Hence, in general terms, the core fibers 137.sub.2-137.sub.4 may be positioned within different segments of the cross-sectional area 305. Where the cross-sectional area 305 of the cladding 300 has a distal tip 330 and features a polygon cross-sectional shape (e.g., triangular, square, rectangular, pentagon, hexagon, octagon, etc.), the central core fiber 137.sub.1 may be located at or near a center of the polygon shape, while the remaining core fibers 137.sub.2-137.sub.M may be located proximate to angles between intersecting sides of the polygon shape.

(57) Referring still to FIGS. 3A-3B, operating as the conductive medium for the stylet 120, the

braided tubing **310** provides mechanical integrity to the multi-core optical fiber **135** and operates as a conductive pathway for electrical signals. For example, the braided tubing **310** may be exposed to a distal tip of the stylet **120**. The cladding **300** and the braided tubing **310**, which is positioned concentrically surrounding a circumference of the cladding **300**, are contained within the same insulating layer **350**. The insulating layer **350** may be a sheath or conduit made of protective, insulating (e.g., non-conductive) material that encapsulates both for the cladding **300** and the braided tubing **310**, as shown.

(58) Referring to FIG. **4A**, a second exemplary embodiment of the stylet of FIG. **1B** is shown in accordance with some embodiments. Referring now to FIG. **4A**, a second exemplary embodiment of the stylet **120** of FIG. **1B** supporting both an optical and electrical signaling is shown. Herein, the stylet **120** features the multi-core optical fiber **135** described above and shown in FIG. **3A**, which includes the cladding **300** and the first plurality of core fibers **137.sub.1-137.sub.M** ($M \geq 3$; $M=4$ for embodiment) residing within the corresponding plurality of lumens **320.sub.1-320.sub.M**. For this embodiment of the disclosure, the multi-core optical fiber **135** includes the central core fiber **137.sub.1** residing within the first lumen **320.sub.1** formed along the first neutral axis **230** and the second plurality of core fibers **137.sub.2-137.sub.4** residing within corresponding lumens **320.sub.2-320.sub.4** positioned in different segments within the cross-sectional area **305** of the cladding **300**. Herein, the multi-core optical fiber **135** is encapsulated within a conductive tubing **400**. The conductive tubing **400** may feature a “hollow” conductive cylindrical member concentrically encapsulating the multi-core optical fiber **135**.

(59) Referring to FIGS. **4A-4B**, operating as a conductive medium for the stylet **120** in the transfer of electrical signals (e.g., ECG signals) to the console, the conductive tubing **400** may be exposed up to a tip **410** of the stylet **120**. For this embodiment of the disclosure, a conductive epoxy **420** (e.g., metal-based epoxy such as a silver epoxy) may be affixed to the tip **410** and similarly joined with a termination/connection point created at a proximal end **430** of the stylet **120**. The cladding **300** and the conductive tubing **400**, which is positioned concentrically surrounding a circumference of the cladding **300**, are contained within the same insulating layer **440**. The insulating layer **440** may be a protective conduit encapsulating both for the cladding **300** and the conductive tubing **400**, as shown.

(60) Referring to FIG. **5A**, an elevation view of a first illustrative embodiment of a catheter including integrated tubing, a diametrically disposed septum, and micro-lumens formed within the tubing and septum is shown in accordance with some embodiments. Herein, the catheter **130** includes integrated tubing, the diametrically disposed septum **510**, and the plurality of micro-lumens **530.sub.1-530.sub.4** which, for this embodiment, are fabricated to reside within the wall **500** of the integrated tubing of the catheter **130** and within the septum **510**. In particular, the septum **510** separates a single lumen, formed by the inner surface **505** of the wall **500** of the catheter **130**, into multiple lumen, namely two lumens **540** and **545** as shown. Herein, the first lumen **540** is formed between a first arc-shaped portion **535** of the inner surface **505** of the wall **500** forming the catheter **130** and a first outer surface **555** of the septum **510** extending longitudinally within the catheter **130**. The second lumen **545** is formed between a second arc-shaped portion **565** of the inner surface **505** of the wall **500** forming the catheter **130** and a second outer surfaces **560** of the septum **510**.

(61) According to one embodiment of the disclosure, the two lumens **540** and **545** have approximately the same volume. However, the septum **510** need not separate the tubing into two equal lumens. For example, instead of the septum **510** extending vertically (12 o'clock to 6 o'clock) from a front-facing, cross-sectional perspective of the tubing, the septum **510** could extend horizontally (3 o'clock to 9 o'clock), diagonally (1 o'clock to 7 o'clock; 10 o'clock to 4 o'clock) or angularly (2 o'clock to 10 o'clock). In the later configuration, each of the lumens **540** and **545** of the catheter **130** would have a different volume.

(62) With respect to the plurality of micro-lumens **530.sub.1-530.sub.4**, the first micro-lumen

530.sub.1 is fabricated within the septum 510 at or near the cross-sectional center 525 of the integrated tubing. For this embodiment, three micro-lumens 530.sub.2-530.sub.4 are fabricated to reside within the wall 500 of the catheter 130. In particular, a second micro-lumen 530.sub.2 is fabricated within the wall 500 of the catheter 130, namely between the inner surface 505 and outer surface 507 of the first arc-shaped portion 535 of the wall 500. Similarly, the third micro-lumen 530.sub.3 is also fabricated within the wall 500 of the catheter 130, namely between the inner and outer surfaces 505/507 of the second arc-shaped portion 555 of the wall 500. The fourth micro-lumen 530.sub.4 is also fabricated within the inner and outer surfaces 505/507 of the wall 500 that are aligned with the septum 510.

(63) According to one embodiment of the disclosure, as shown in FIG. 5A, the micro-lumens 530.sub.2-530.sub.4 are positioned in accordance with a “top-left” (10 o'clock), “top-right” (2 o'clock) and “bottom” (6 o'clock) layout from a front-facing, cross-sectional perspective. Of course, the micro-lumens 530.sub.2-530.sub.4 may be positioned differently, provided that the micro-lumens 530.sub.2-530.sub.4 are spatially separated along the circumference 520 of the catheter 130 to ensure a more robust collection of reflected light signals from the outer core fibers 570.sub.2-570.sub.4 when installed. For example, two or more of micro-lumens (e.g., micro-lumens 530.sub.2 and 530.sub.4) may be positioned at different quadrants along the circumference 520 of the catheter wall 500.

(64) Referring to FIG. 5B, a perspective view of the first illustrative embodiment of the catheter of FIG. 5A including core fibers installed within the micro-lumens is shown in accordance with some embodiments. According to one embodiment of the disclosure, the second plurality of micro-lumens 530.sub.2-530.sub.4 are sized to retain corresponding outer core fibers 570.sub.2-570.sub.4, where the diameter of each of the second plurality of micro-lumens 530.sub.2-530.sub.4 may be sized just larger than the diameters of the outer core fibers 570.sub.2-570.sub.4. The size differences between a diameter of a single core fiber and a diameter of any of the micro-lumen 530.sub.1-530.sub.4 may range between 0.001 micrometers (μm) and 1000 μm , for example. As a result, the cross-sectional areas of the outer core fibers 570.sub.2-570.sub.4 would be less than the cross-sectional areas of the corresponding micro-lumens 530.sub.2-530.sub.4. A “larger” micro-lumen (e.g., micro-lumen 530.sub.2) may better isolate external strain being applied to the outer core fiber 570.sub.2 from strain directly applied to the catheter 130 itself. Similarly, the first micro-lumen 530.sub.1 may be sized to retain the center core fiber 570.sub.1, where the diameter of the first micro-lumen 530.sub.1 may be sized just larger than the diameter of the center core fiber 570.sub.1.

(65) As an alternative embodiment of the disclosure, one or more of the micro-lumens 530.sub.1-530.sub.4 may be sized with a diameter that exceeds the diameter of the corresponding one or more core fibers 570.sub.1-570.sub.4. However, at least one of the micro-lumens 530.sub.1-530.sub.4 is sized to fixedly retain their corresponding core fiber (e.g., core fiber retained with no spacing between its lateral surface and the interior wall surface of its corresponding micro-lumen). As yet another alternative embodiment of the disclosure, all the micro-lumens 530.sub.1-530.sub.4 are sized with a diameter to fixedly retain the core fibers 570.sub.1-570.sub.4.

(66) Referring to FIGS. 6A-6B, flowcharts of methods of operations conducted by the medical instrument monitoring system of FIGS. 1A-1B to achieve optic 3D shape sensing are shown in accordance with some embodiments. Herein, the catheter includes at least one septum spanning across a diameter of the tubing wall and continuing longitudinally to subdivide the tubing wall. The medial portion of the septum is fabricated with a first micro-lumen, where the first micro-lumen is coaxial with the central axis of the catheter tubing. The first micro-lumen is configured to retain a center core fiber. Two or more micro-lumen, other than the first micro-lumen, are positioned at different locations circumferentially spaced along the wall of the catheter tubing. For example, two or more of the second plurality of micro-lumens may be positioned at different quadrants along the circumference of the catheter wall.

(67) Furthermore, each core fiber includes a plurality of sensors spatially distributed along its length between at least the proximal and distal ends of the catheter tubing. This array of sensors is distributed to position sensors at different regions of the core fiber to enable distributed measurements of strain throughout the entire length or a selected portion of the catheter tubing. These distributed measurements may be conveyed through reflected light of different spectral widths (e.g., specific wavelength or specific wavelength ranges) that undergoes certain wavelength shifts based on the type and degree of strain.

(68) According to one embodiment of the disclosure, as shown in FIG. 6A, for each core fiber, broadband incident light is supplied to propagate through a particular core fiber (block **600**). Unless discharged, upon the incident light reaching a sensor of a distributed array of sensors measuring strain on a particular core fiber, light of a prescribed spectral width associated with the first sensor is to be reflected back to an optical receiver within a console (blocks **605-610**). Herein, the sensor alters characteristics of the reflected light signal to identify the type and degree of strain on the particular core fiber as measured by the first sensor (blocks **615-620**). According to one embodiment of the disclosure, the alteration in characteristics of the reflected light signal may signify a change (shift) in the wavelength of the reflected light signal from the wavelength of the incident light signal associated with the prescribed spectral width. The sensor returns the reflected light signal over the core fiber and the remaining spectrum of the incident light continues propagation through the core fiber toward a distal end of the catheter tubing (blocks **625-630**). The remaining spectrum of the incident light may encounter other sensors of the distributed array of sensors, where each of these sensors would operate as set forth in blocks **605-630** until the last sensor of the distributed array of sensors returns the reflected light signal associated with its assigned spectral width and the remaining spectrum is discharged as illumination.

(69) Referring now to FIG. 6B, during operation, multiple reflected light signals are returned to the console from each of the plurality of core fibers residing within the corresponding plurality of micro-lumens formed within a catheter, such as the catheter of FIG. 1B. In particular, the optical receiver receives reflected light signals from the distributed arrays of sensors located on the center core fiber and the outer core fibers and translates the reflected light signals into reflection data, namely electrical signals representative of the reflected light signals including wavelength shifts caused by strain (blocks **650-655**). The reflection data classification logic is configured to identify which core fibers pertain to which reflection data and segregate reflection data provided from reflected light signals pertaining to a particular measurement region (or similar spectral width) into analysis groups (block **660-665**).

(70) Each analysis group of reflection data is provided to shape sensing logic for analytics (block **670**). Herein, the shape sensing logic compares wavelength shifts at each outer core fiber with the wavelength shift at the center core fiber positioned along central axis and operating as a neutral axis of bending (block **675**). From this analytics, on all analytic groups (e.g., reflected light signals from sensors in all or most of the core fibers), the shape sensing logic may determine the shape the core fibers have taken in three-dimensional space, from which the shape sensing logic can determine the current physical state of the catheter in three-dimension space (blocks **680-685**).

(71) Referring now to FIG. 7A, an exemplary embodiment of the medical instrument monitoring system of FIG. 1A during operation and insertion of the catheter into a patient is shown in accordance with some embodiments. Herein, the catheter **195** generally includes integrated tubing with a proximal portion **720** that generally remains exterior to the patient **700** and a distal portion **730** that generally resides within the patient vasculature after placement is complete. The stylet **120** may be advanced through the catheter **195** to a desired position within the patient vasculature such that a distal end (or tip) **735** of the stylet **120** (and hence a distal end of the catheter **195**) is proximate the patient's heart, such as in the lower one-third ($\frac{1}{3}$) portion of the Superior Vena Cava ("SVC") for example. For this embodiment, various instruments may be placed at the distal end of the stylet **120** and/or the catheter **195** to measure pressure of blood in a certain heart chamber and

in the blood vessels, view an interior of blood vessels, or the like.

(72) During advancement through a patient vasculature, the stylet **120** receives broadband incident light **155** from the console **110** via optical fiber(s) **147** within the interconnect **145**, where the incident light **155** propagates to the core fibers **137** of the stylet **120**. According to one embodiment of the disclosure, the connector **146** of the interconnect **145** terminating the optical fiber(s) **147** may be coupled to the optical-based catheter connector **144**, which may be configured to terminate the core fibers **137** deployed within the stylet **120**. Such coupling optically connects the core fibers **137** of the stylet **120** with the optical fiber(s) **147** within the interconnect **145**. The optical connectivity is needed to propagate the incident light **155** to the core fibers **137** and return the reflected light signals **150** to the optical logic **180** within the console **110** over the interconnect **145**. As described below in detail, the physical state of the stylet **120** and the catheter **195** may be ascertained based on analytics of the wavelength shifts of the reflected light signals **150**.

(73) Referring to FIG. 7B, a detailed view of the stylet of FIG. 7A in the Superior Vena Cava (SVC) advancing toward the right atrium of the patient is shown in accordance with some embodiments. FIG. 7B illustrates a portion of FIG. 7A providing a detailed perspective of the vasculature proximate to the heart as well as the anatomy of the heart. Specifically, as the stylet **120** approaches the right atrium **746** through the SVC **742**, the stylet **120** may either advance into the right atrium **746** or deviate into the Azygos vein **743**. The stylet **120** is often used to locate a particular point in the vasculature at which point the catheter may be used to administer a medical procedure or medicament, where this point may be referred to as the “target site” (as shown in FIG. 8). Numerous methodologies for detecting deviation of the stylet **120** into the Azygos vein **743** are disclosed below.

(74) In some embodiments, the shape sensing logic **194** is configured to determine the shape the core fibers have taken in 3D space as the stylet **120** advances through a patient's vasculature and may further determine the current physical state of the stylet **120** (and hence the catheter **195**) in 3D space for rendering on the display **170**. According to one embodiment of the disclosure, the shape sensing logic **194** may generate a rendering of the current physical state of the catheter **195** based on the physical state of the stylet **120** based on heuristics or run-time analytics. For example, the shape sensing logic **196** may be configured in accordance with machine-learning techniques to access a data store (library) with pre-stored data (e.g., images, etc.) pertaining to different regions of the catheter **195** in which the core fibers **137** experienced similar or identical wavelength shifts.

(75) In some embodiments, a subset of the images included in the pre-stored data (or a separate set of images stored in the Azygos detection data **199**) may depict particular placements of the stylet **120** as its advancement progresses into the Superior Vena Cava (SVC) and nears the right atrium. Specifically, the subset of the images may include both images in which advancement of the stylet **120** is following a desired or expected path through the SVC and into the right atrium (e.g., to a predetermined target site), and images in which advancement of the stylet **120** deviates from the desired or expected path and enters into the Azygos vein. Further, following generation of the physical state of the stylet **120**, such may be compared using heuristics or run-time analytics to the subset of images depicting advancement along desired (expected) and undesired (unexpected) paths in order determine whether the stylet **120** has deviated into the Azygos vein. For example, the analyses performed by the Azygos detection logic **196** may result in a determination indicating whether stylet **120** and/or the catheter **195** have entered the Azygos vein.

(76) Referring to FIG. 8, a first illustration of a stylet advancing through a patient's vasculature toward the right atrium of the patient's heart is shown in accordance with some embodiments. As seen, the stylet **120** is advancing through the SVC **742** toward a target site **800** within the right atrium **746** but has deviated from a desired path into the Azygos vein **743**. In one embodiment, as the stylet **120** advances toward the Azygos vein **743** the reflected light generated by the sensors (reflective gratings) indicates such a curvature. The Azygos detection logic **198** obtains the generated physical state of the stylet **120** from the shape sensing logic **194** and, through heuristics

and/or run-analytics determines the generated physical state of the stylet indicates entry into the Azygos vein **743**. As referenced above, such a determination may be based on, at least in part, comparison through machine-learning tactics (and, optionally, in combination with image recognition algorithms) to a set of pre-stored images. For instance, a trained machine-learning model may provide an indication that the stylet **120** has entered into the Azygos vein **743** with a particular confidence level. As should be understood, the machine-learning model would previously trained using the pre-stored images of both (i) stylets advancing properly toward the right atrium **746** generation of the physical state of the stylet **120** generation of the physical state of the stylet **120** and (ii) stylets deviating into the Azygos vein **743**.

(77) Additionally, or as an alternative, the Azygos detection logic **198** may analyze the reflected light with respect to fluctuations of the stylet **120** during its advancement in order to determine whether the stylet **120** has deviated into the Azygos vein **743**. For instance, known or expected rates of fluctuation may be pre-stored as part of the Azygos detection data **199** for various areas of the human vasculature. These known rates of fluctuation may be compared to a current rate of fluctuation of the stylet **120** computed by the Azygos detection logic **198** based on the reflected light, which indicates movement of the stylet **120**. The difference in the fluctuations of the stylet **120** between the SVC **742** and the Azygos vein **743** may be a result of one or more several factors including more turbulent blood flow in the SVC **742**, a larger diameter of the SVC **742**, a difference in pulsatility between the SVC **742** and the Azygos vein **743**, and a difference in the volumes of interiors of the SVC **742** and the Azygos vein **743**. The amount or rate of fluctuation of the stylet **120** may be a combination of movement by the stylet **120**, especially the distal tip, in any direction within the particular portion of the vasculature through which the stylet **120** is currently traveling.

(78) In particular and referring again to FIG. **8**, the SVC **742** is illustrated as having a diameter (D1) **802** and the Azygos vein **743** is illustrated as having a diameter (D2) **804**, where the D2 **804** of the Azygos vein **743** is less than the D1 **802** of the SVC **742**. Thus, the larger diameter of the SVC **742** enables the stylet **120** to have a higher rate of fluctuation over a particular stretch of advancement than does the smaller diameter of the Azygos vein **743**, i.e., the stylet **120** is more limited in its physical movement upon deviating into the Azygos vein **743**.

(79) Additionally, the higher rate of fluctuations may be caused by the contraction of the cardiac muscle of the heart and the actuation of heart valves adjacent to the path of the blood. Specifically, these contractions and actuations interrupt the steady blow flow in the SVC **742**, where the steady blood flow is more broadly observed throughout the rest of the venous vasculature. In the regions immediately adjacent to the heart, e.g., the SVC, vessel properties are unable to flatten and filter these disruptions to steady blood flow resulting in an observable movement (fluctuation) within the stylet **120** when present in this region of the vasculature. Thus, the Azygos detection logic **198** may detect deviation into the Azygos vein **198** based on a lower rate of fluctuation that is at least in part caused by the contractions and actuations discussed above, where the rate of fluctuation is indicated in the reflected light.

(80) In yet other embodiments, the direction of blood flow may be utilized as an indicator that the stylet **120** has deviated into the Azygos vein **743**. Specifically, as illustrated in FIG. **8**, the direction of blood flow in the SVC **742** is illustrated via the arrow **806** (i.e., in-line with the direction of advancement of the stylet **120**) and the direction of blood flow in the Azygos vein **743** is illustrated via the arrow **808** (i.e., against the direction of advancement of the stylet **120**). Thus, utilizing data obtained through pulse oximetry and/or flow Doppler, typically in addition to one or more of the embodiments discussed herein, a directional flow detection logic **199** may determine that the stylet **120** has deviated into the Azygos vein **743**. The directional flow detection logic **199** may be a sub-logic module of the Azygos detection logic **198**. For example, technology implementing pulse oximetry and/or an optical-based Doppler (e.g., Doppler ultrasound) may integrated into the stylet **120** and provide the Azygos detection logic **198** with readings regarding blood oxygen levels and

blood flow velocity, which aid the Azygos detection logic **198** in determining whether the distal tip of the body of implementation has deviated into the Azygos vein.

(81) In some embodiments, the stylet **120** and/or the catheter **195** may be operable to perform intravascular ECG monitoring in addition to the fiber optic shape sensing functionality discussed previously. As indicated above, the console **110** may include the electrical signaling logic **181**, which is positioned to receive one or more electrical signals from the stylet **120** and/or catheter **195** when configured to obtain electrical signals, e.g., at a distal tip. Further, the stylet **120** is operable to support both optical connectivity as well as electrical connectivity. The electrical signaling logic **181** receives the electrical signals (e.g., ECG signals) from the stylet **120** via the conductive medium **144**. The electrical signals may be processed by electrical signal analytic logic **196**, executed by the processor **160**, to determine ECG waveforms for display.

(82) Referring to FIG. **9**, a second illustration of a stylet advancing through a patient's vasculature toward the right atrium of the patient's heart is shown in accordance with some embodiments. As is known and illustrated in FIG. **9**, the SA node **900** generates electrical impulses that control the sinus rhythm of the heart. Such as impulses are detectable by, for example, an electrode coupled to a distal tip of the stylet **120**. As the stylet **120** deviates into the Azygos vein **743**, the detected P-wave of the intravascular ECG decreases slightly in amplitude even as the stylet **120** is advanced toward the sinoatrial (SA) node **900**.

(83) Referring to now FIGS. **10A-10C**, illustrations depicting an electrode configuration that provides for acquisition of endovascular ECG data are shown in accordance some embodiments. With specific reference to FIG. **10A**, the illustration depicts a single lead configuration with a reference electrode **1006** that is, for example, attached to the patient's skin over the right arm and with a secondary electrode **1008** coupled to the stylet **120** or catheter **195**. It should be noted that the reference electrode **1006** is attached to the skin over the right arm for illustration purposes only with other configurations being possible depending on the type of ECG required. Such a configuration enables ECG data to be obtained from the SVC **1002** and inferior vena cava **1004**.

(84) With reference to FIG. **10B**, the illustration depicts a modified 3-lead configuration, with monitoring and guiding capabilities utilizing four electrodes. In such a configuration, three of the electrodes correspond to standard ECG electrodes: right arm (RA) **1010**, left arm (LA) **1012**, and left leg (LL) **1014** (not shown to proportion), wherein the left leg electrode **1014** is used as reference. The fourth electrode **1016** is attached through to the stylet **120** or catheter **195**. In this configuration, the console **110** and the electrical signal analytic logic **196** may perform two functions simultaneously or concurrently (at least partially overlapping in time): the three standard electrodes (**1010**, **1012**, **1014**) perform a monitoring function of the heart, while the fourth electrode **1016** allows for recording the ECG at the tip of the stylet **120** or catheter **195**. FIG. **10C** provides an illustration depicting a telemetry configuration with a single grounded lead **1018** in addition to the configuration as discussed in FIG. **10A** utilizing electrodes **1006** and **1008**. This configuration can be used to transmit ECGs remotely through a telemetry system configuration.

(85) Referring to now FIG. **11**, an illustration of an exemplary peripherally inserted central catheter is shown in accordance with some embodiments. The device **1100** comprises or is configured as a central venous catheter (CVC), such as, a peripherally inserted central catheter (PICC or PICC line), with a detector **1102** positioned at or near a distal end **1104** of device **1100**. Additionally, the device **1100** is configured with a multi-core optical fiber, which receives broadband incident light and reflects optical signals (light signals) to a console as discussed above. In some embodiments, the multi-core optical fiber may be integrated into an interior of the device **1100** (e.g., when the device **1100** is a guidewire or a stylet). In other embodiments, the multi-core optical fiber may be integrated into a wall of device **1100** (e.g., when the device **1100** is a catheter).

(86) The device **1100** itself comprises an elongated body **1106** that is made of a material that may permit delivery of device **1100** into a luminal organ (or an access route through another bodily part) of a patient and subsequent withdrawal from the patient without damaging the patient. For

example, elongated body **1106** may comprise silicone or one or more other polycarbonates so to prevent device **1100** from “sticking” to the vasculature of the patient during or after insertion. In various device **1100** embodiments, at least one lumen **1108** is defined within elongated body **1106**, and may define multiple lumens **1108**. In other embodiments (such as wire embodiments, for example), device **1100** would not have a lumen therethrough.

(87) The detector **1102** comprises a pair of detection electrodes **1114**, **1116** that are positioned in between a pair of excitation electrodes **1110**, **1112**. The detector **1102** is configured to generate an electric field and also to obtain multiple conductance measurements within the electric field as the detector **1102** is advanced through a patient's vasculature, wherein each of the multiple conductance measurements is indicative of a location of the detector **1102** within the patient's vasculature when the detector **1102** is positioned therein.

(88) Referring now to FIG. **12**, an illustration of a system utilizing a second embodiment of a peripherally inserted central in conjunction with two electrode pads is shown in accordance with some embodiments. In the embodiment shown in FIG. **12**, an electric field is generated by electrodes that are coupled to or positioned on the pads **1202**, **1204**. In such an embodiment, changes in conductance can be obtained using detector **1206**, which includes detection electrodes **1208**, **1210** that are similar to the detection electrodes **1114**, **1116**, for example) as the detector **1206** moves with stylet **1205** through the patient's vasculature.

(89) In such an embodiment, upon activation of distal excitation electrode **110** and proximal excitation electrode **112**, the electric field detectable by detection electrodes **1208**, **1210** of the detector **1206**. As stylet **1205** is advanced through the patient's vasculature, from vessels of smaller diameter/cross-sectional area to larger vessels and ultimately to the heart, stepwise changes (increases) in conductance can be identified, and the anticipated pulsatile nature of voltage change due to the pumping of the heart can also be identified, indicating delivery of a distal end of stylet **1205** to the right atrium.

(90) Specifically, in embodiments in which the pads **1202**, **1204** may themselves serve as the poles or excitation electrodes may be positioned upon the pads **1202**, **1204**, the stylet **1205** need not include excitation electrodes (such as excitation electrodes **1110**, **1112** of FIG. **11**) positioned thereon as the two poles are provided using pads **1202**, **1204** as shown in FIG. **12**. In some embodiments, one or more wires (not shown) may be connected to the pads **1202**, **1204** to transmit a current from an ECG/EKG device (and/or the console **110**), so to generate an electric field detectable by a stylet **1205**.

(91) As shown in FIG. **12**, the pads **1202**, **1034** are each positioned upon the patient's torso. While other locations may be used, the illustrated embodiment includes pad placement whereby the pad **1202** is positioned adjacent to a vein that the stylet **1205** will pass through on the way to the right atrium, and the pad **1204** is positioned adjacent to the right ventricle or the right atrium of the heart (or generally positioned away from the pad **1202**, such as on an opposing arm of a patient, at or near the patient's neck, elsewhere on the torso, etc.).

(92) In an embodiment in which the two pads **1202**, **1204** are poles and generate the electric field, when a detection portion of stylet **1205** is outside the field, conductance is generally high and voltage is very low, and when the detection portion of stylet **1205** moves back into the field, conductance significantly drops, while voltage increases.

(93) While some particular embodiments have been disclosed herein, and while the particular embodiments have been disclosed in some detail, it is not the intention for the particular embodiments to limit the scope of the concepts provided herein. Additional adaptations and/or modifications can appear to those of ordinary skill in the art, and, in broader aspects, these adaptations and/or modifications are encompassed as well. Accordingly, departures may be made from the particular embodiments disclosed herein without departing from the scope of the concepts provided herein.

Claims

1. A medical device system for detecting malposition of a medical device within a vasculature of a patient, the system comprising: the medical device configured for advancement through the vasculature of the patient, wherein the medical device comprises a multi-core optical fiber having a plurality of core fibers, each of the plurality of core fibers including a plurality of sensors distributed along a longitudinal length of a corresponding core fiber and each sensor of the plurality of sensors being configured to (i) reflect a light signal of a different spectral width based on received incident light, and (ii) change a characteristic of the reflected light signal for use in determining a physical state of the multi-core optical fiber; and a console including one or more processors and a non-transitory computer-readable medium having stored thereon logic, when executed by the one or more processors, causes operations including: receiving one or more signals from the medical device representing one or more parameters indicative of a location of a distal tip of the medical device within the vasculature of the patient, wherein the one or more signals correspond to reflected portions of a propagating light signal; processing the one or more signals to determine the location of the distal tip, and determining whether the medical device has deviated from a target advancement path and has entered an Azygos vein of the patient based on the one or more signals.
2. The system of claim 1, wherein determining whether the medical device has entered the Azygos vein is based on an amount of fluctuation of the medical device indicated by the reflected portions of the propagating light signal.
3. The system of claim 2, wherein the amount of fluctuation of the medical device is an amount of fluctuation at the distal tip of the medical device.
4. The system of claim 1, wherein determining whether the medical device has entered the Azygos vein is based on a shape of the medical device indicated by the reflected portions of the propagating light signal.
5. The system of claim 4, wherein the shape of the medical device indicated by the reflected portions of the propagating light signal is utilized as input to a machine-learning model configured to process the input and provide a result indicating a confidence level as to whether the shape of the medical device indicates entry into the Azygos vein of the patient.
6. The system of claim 4, wherein determining whether the medical device has entered the Azygos vein is based on a result of heuristics performed on the shape of the medical device indicated by the reflected portions of the propagating light signal.
7. The system of claim 1, wherein the one or more signals also include electrocardiogram (ECG) signals resulting from ECG monitoring of advancement of the medical device through the vasculature of the patient, and wherein determining whether the medical device has entered the Azygos vein is based at least in part on the ECG signals.
8. The system of claim 1, wherein the one or more signals also include voltage signals representing an impedance measured near the distal tip of the medical device, and wherein determining whether the medical device has entered the Azygos vein is based at least in part on the voltage signals.
9. The system of claim 1, wherein the one or more signals also include an indication of a blood flow direction near the distal tip of the medical device, and wherein determining whether the medical device has entered the Azygos vein is based at least in part on the blood flow direction near the distal tip of the medical device.
10. The system of claim 1, wherein the one or more signals also include an indication of a pulse oximetry reading obtained near the distal tip of the medical device, and wherein determining whether the medical device has entered the Azygos vein is based at least in part on the pulse oximetry reading.
11. The system of claim 1, wherein the one or more signals also include an indication of an optical-

based Doppler reading, and wherein determining whether the medical device has entered the Azygos vein is based at least in part on the optical-based Doppler reading.

12. The system of claim 1, wherein the medical device is a stylet removably inserted into a lumen of a catheter assembly for placement of the distal tip of the catheter assembly in a superior vena cava of the vasculature.
