

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394844
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Su; Huasheng et al.

End cover assembly, battery, electric device, battery cell, and manufacturing method thereof

Abstract

Provided are an end cover assembly, a battery, an electric device, a battery cell, and a manufacturing method thereof, pertaining to the technical field of batteries. The end cover assembly includes an end cover, a first electrode terminal, a second electrode terminal, a connecting member, and a pressure relief mechanism. The first electrode terminal is installed on the end cover; and the second electrode terminal is installed on the end cover. The connecting member is configured to be connected to the first electrode terminal and the second electrode terminal, where the connecting member is on a side of the end cover farther away from inside of the battery cell in a first direction. The pressure relief mechanism is disposed on the end cover, the pressure relief mechanism is at least partially located between the first electrode terminal and the second electrode terminal.

Inventors: Su; Huasheng (Ningde, CN), Xing; Chengyou (Ningde, CN), Wu; Yichen (Ningde, CN)

Applicant: CONTEMPORARY AMPEREX TECHNOLOGY (HONG KONG) LIMITED
(Hong Kong, CN)

Family ID: 1000008765327

Assignee: CONTEMPORARY AMPEREX TECHNOLOGY (HONG KONG) LIMITED
(Hong Kong, CN)

Appl. No.: 18/344861

Filed: June 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230344044 A1	Oct. 26, 2023

Foreign Application Priority Data

CN

202011642712.5

Dec. 30, 2020

Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/125104 20211020 PENDING child-doc US 18344861

Publication Classification

Int. Cl.: H01M50/166 (20210101); H01M10/0587 (20100101); H01M50/152 (20210101); H01M50/375 (20210101); H01M50/528 (20210101); H01M50/55 (20210101); H01M10/052 (20100101)

U.S. Cl.:

CPC H01M50/166 (20210101); H01M10/0587 (20130101); H01M50/152 (20210101); H01M50/375 (20210101); H01M50/528 (20210101); H01M50/55 (20210101); H01M10/052 (20130101); H01M2220/20 (20130101)

Field of Classification Search

CPC: H01M (50/166); H01M (10/0587); H01M (50/152); H01M (50/375); H01M (50/528); H01M (50/55); H01M (10/052); H01M (2220/20); H01M (50/3425); H01M (50/559); H01M (10/058); H01M (50/30)

USPC: 429/175

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2003/0022061	12/2002	Duprey	429/174	H01M 10/28
2005/0174092	12/2004	Dougherty et al.	N/A	N/A
2008/0220315	12/2007	Dougherty et al.	N/A	N/A
2011/0287286	12/2010	Ahn	429/56	H01M 50/3425
2014/0087217	12/2013	Zink et al.	N/A	N/A
2015/0214525	12/2014	Lim	429/53	H01M 10/0481
2018/0130981	12/2017	Liu	N/A	H01M 50/213
2019/0355943	12/2018	Chen et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102013513	12/2010	CN	N/A
106410079	12/2016	CN	N/A
207474505	12/2017	CN	N/A
108281578	12/2017	CN	N/A
208173680	12/2017	CN	N/A
110265616	12/2018	CN	N/A

111952515	12/2019	CN	N/A
211879534	12/2019	CN	N/A
211929598	12/2019	CN	N/A
112117425	12/2019	CN	N/A
214898799	12/2020	CN	N/A
0771037	12/1996	EP	N/A
2005276660	12/2004	JP	N/A
2010092592	12/2009	JP	N/A
4698159	12/2010	JP	N/A
2018026285	12/2017	JP	N/A
2020099368	12/2019	JP	N/A
2021193651	12/2020	JP	N/A

OTHER PUBLICATIONS

CN 106410079 A1 English Machine Translation (Year: 2017). cited by examiner
International Search Report received in the corresponding International Application
PCT/CN2021/125104, mailed Jan. 18, 2022. cited by applicant
Decision to Grant a Patent received in the counterpart Japanese application 2023-530681, mailed
on Nov. 26, 2024. cited by applicant
First Office Action received in the counterpart Chinese application 202011642712.5, mailed on
Dec. 2, 2022. cited by applicant
Notice of Grant of Invention Patent Right received in the counterpart Chinese application
202011642712.5, mailed on May 29, 2023. cited by applicant
The extended European search report received in the counterpart European application 21913354.3,
mailed on Sep. 9, 2024. cited by applicant
Notice of Reasons for Refusal received in the counterpart Japanese application 2023-530681,
mailed on Jun. 25, 2024. cited by applicant

Primary Examiner: Smith; Nicholas A

Assistant Examiner: Nguyen; Kevin

Attorney, Agent or Firm: K&L Gates LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of
International Application PCT/CN2021/125104, filed Dec. 30, 2020, which claims priority to
Chinese Patent Application No. 202011642712.5, filed on Dec. 30, 2020 and entitled “END
COVER ASSEMBLY, BATTERY, ELECTRIC DEVICE, BATTERY CELL, AND
MANUFACTURING METHOD THEREOF”, which are incorporated herein by reference in their
entireties.

TECHNICAL FIELD

(1) This application relates to the field of battery technologies, and specifically, to an end cover
assembly, a battery, an electric device, a battery cell, and a manufacturing method thereof.

BACKGROUND

(2) Most commonly used batteries in automobiles are lithium-ion batteries. As rechargeable
batteries, the lithium-ion batteries have advantages such as small size, high energy density, high

power density, large cycle count, and long storage time.

(3) The rechargeable battery usually includes a housing, an end cover assembly, and an electrode assembly. The end cover assembly covers the housing to provide sealed space for the electrode assembly and an electrolyte. Electric energy of the electrode assembly can be conducted by an electrode terminal of the end cover assembly to the outside of the housing.

(4) To ensure safety performance of the battery, a pressure relief mechanism is usually disposed in the end cover assembly. When internal pressure or temperature of the battery reaches a threshold, the internal pressure of the battery can be relieved through the pressure relief mechanism. An arrangement position of the pressure relief mechanism directly affects a capability of the pressure relief mechanism to relieve the internal pressure of the battery.

(5) Therefore, how the pressure relief mechanism is more properly arranged is a problem that needs to be urgently resolved in the battery technology.

SUMMARY

(6) Embodiments of this application provide an end cover assembly, a battery, an electric device, a battery cell, and a manufacturing method thereof, to ensure that a pressure relief mechanism is more properly arranged.

(7) According to a first aspect, an embodiment of this application provides an end cover assembly, applied to a battery cell and including: an end cover, a first electrode terminal, a second electrode terminal, a connecting member, and a pressure relief mechanism, where the first electrode terminal is installed on the end cover; the second electrode terminal is installed on the end cover; the connecting member is configured to be connected to the first electrode terminal and the second electrode terminal, where the connecting member is on a side of the end cover farther away from inside of the battery cell in a first direction; and the pressure relief mechanism is disposed on the end cover, where the pressure relief mechanism is at least partially located between the first electrode terminal and the second electrode terminal, and the pressure relief mechanism is configured to be actuated when internal pressure or temperature of the battery cell reaches a threshold, to relieve the internal pressure of the battery cell.

(8) In the foregoing solution, the pressure relief mechanism is disposed on the end cover, the pressure relief mechanism is at least partially located between the first electrode terminal and the second electrode terminal, and therefore, space of the end cover and between the first electrode terminal and the second electrode terminal is effectively used, so that the pressure relief mechanism is more properly arranged, and a larger-sized pressure relief mechanism can be disposed.

(9) In some embodiments, a projection of the connecting member in the first direction covers at least part of the pressure relief mechanism.

(10) In the foregoing solution, the projection of the connecting member in the first direction covers at least part of the pressure relief mechanism, so that the pressure relief mechanism effectively uses space, occupied by the connecting member, on the end cover, thereby properly using the space on the end cover.

(11) In some embodiments, the pressure relief mechanism includes an opening region, and the pressure relief mechanism is configured to relieve the internal pressure of the battery cell through the opening region when the internal pressure or temperature of the battery cell reaches the threshold; and a projection of the connecting member in the first direction covers a part of the opening region, and a projection of the opening region in the first direction exceeds the projection of the connecting member in the first direction.

(12) In the foregoing solution, the projection of the connecting member in the first direction covers the part of the opening region, and the projection of the opening region in the first direction exceeds the projection of the connecting member in the first direction. That is, the opening region is not completely blocked by the connecting member in the first direction, so that the internal pressure of the battery cell is more smoothly relieved through the opening region.

(13) In some embodiments, the opening region extends along a second direction, and the

connecting member extends along a third direction; and any two of the first direction, the second direction, and the third direction are perpendicular to each other.

(14) In the foregoing solution, any two of the extending direction of the opening region, the extending direction of the connecting member, and the first direction are perpendicular to each other. Such structure ensures that a region, blocked by the connecting member, of the opening region is smaller. Therefore, the internal pressure of the battery cell is more smoothly relieved through the opening region.

(15) In some embodiments, the opening region includes a first opening region and a second opening region, and the second opening region is arranged on at least one end of the first opening region in the second direction; the projection of the connecting member in the first direction covers at least part of the first opening region, a projection of the second opening region in the first direction exceeds the projection of the connecting member in the first direction, and width of the second opening region in the third direction is greater than width of the first opening region in the third direction; and any two of the first direction, the second direction, and the third direction are perpendicular to each other.

(16) In the foregoing solution, width of the second opening region that is not blocked by the connecting member in the third direction is greater than width of the first opening region that is at least partially blocked by the connecting member in the third direction. With such structure, the internal pressure of the battery cell is more smoothly relieved through the opening region.

(17) In some embodiments, the end cover assembly further includes a shielding member for shielding the pressure relief mechanism; and a first accommodation groove for accommodating the shielding member is provided on a side of the end cover closer to the connecting member.

(18) In the foregoing solution, the shielding member can shield the pressure relief mechanism, to provide good protection for the pressure relief mechanism. The first accommodation groove is provided on a side of the end cover closer to the connecting member, and the shielding member can be accommodated in the first accommodation groove, to reduce external space of the end cover that is occupied by the shielding member.

(19) In some embodiments, the shielding member is provided with a first through hole.

(20) In the foregoing solution, the shielding member is provided with a first through hole, and the first through hole has a pressure balancing function for balancing pressure in a region between the shielding member and the pressure relief mechanism and external pressure.

(21) In some embodiments, the first electrode terminal and the second electrode terminal have same polarity.

(22) In the foregoing solution, the polarities of the first electrode terminal and the second electrode terminal are the same. In other words, the connecting member is connected to the two electrode terminals with the same polarity. The connecting member has a function of collecting electric energy, thereby enlarging a connection area between the battery cell and a busbar.

(23) In some embodiments, the end cover assembly further includes a current collector, and the current collector is configured to be connected to the first electrode terminal, the second electrode terminal, and an electrode assembly of the battery cell; a discharge channel is disposed on the current collector; and an emission produced by the battery cell due to thermal runaway is able to be discharged to outside of the battery cell through the discharge channel and the pressure relief mechanism in sequence, to relieve the internal pressure of the battery cell.

(24) In the foregoing solution, the discharge channel is disposed on the current collector, and therefore, when the thermal runaway occurs in the battery cell, an internal emission of the battery cell can be discharged to outside of the battery cell through the discharge channel and the pressure relief mechanism in sequence, so that the emission produced due to the thermal runaway of the battery cell can be discharged in a timely manner, to relieve internal pressure of the battery cell.

(25) In some embodiments, the current collector includes a plurality of folding portions, a crease is formed between every two adjacent folding portions, each folding portion is provided with a

second through hole, and a plurality of second through holes jointly form the discharge channel.

(26) In the foregoing solution, the current collector is a folding structure including the plurality of folding portions, so that the current collector is easily disposed between the end cover and the electrode assembly, thereby reducing the space occupied by the current collector. Each folding portion is provided with a second through hole, and in the folded state of the current collector, the plurality of second through holes can jointly form the discharge channel.

(27) In some embodiments, projections of the plurality of second through holes in the first direction overlap at least part of the projection of the pressure relief mechanism in the first direction.

(28) In the foregoing solution, the projections of the plurality of second through holes in the second direction overlap at least part of the projection of the pressure relief mechanism in the first direction, so that the emission is less blocked by the current collector, and more smoothly discharged to the outside through the discharge channel and the pressure relief mechanism, allowing the emission to be more easily discharged to the outside of the battery cell.

(29) In some embodiments, projections of the plurality of second through holes in the first direction overlap at least part of a projection of a central hole of the electrode assembly in the first direction.

(30) In the foregoing solution, the projections of the plurality of second through holes in the first direction overlap at least part of the projection of the central hole of the electrode assembly in the first direction, and therefore, the discharge channel and the central hole of the electrode assembly jointly form a straight-through channel to balance pressure on both sides of the electrode assembly in an axial direction of the central hole, thereby reducing a risk of damage to the pressure relief mechanism caused by excessively high pressure on one side of the electrode assembly closer to the end cover.

(31) In some embodiments, a guide protruding portion is provided on at least one side of a part, provided with the second through hole, of at least one folding portion in an extending direction of the crease.

(32) In the foregoing solution, disposing the guide protruding portion on the folding portion can increase a current flow area of the part, provided with the second through hole, of the folding portion.

(33) In some embodiments, the plurality of folding portions include a first folding portion, a second folding portion, and a third folding portion connected in sequence; the first folding portion is configured to be electrically connected to the first electrode terminal and the second electrode terminal; the third folding portion is configured to be electrically connected to the electrode assembly; width of the first folding portion and width of the third folding portion are both greater than width of the second folding portion in an extending direction of the crease; and a guide protruding portion is provided on at least one side of a part, provided with the second through hole, of the second folding portion in the extending direction of the crease.

(34) In the foregoing solution, the width of the first folding portion and the width of the third folding portion are both larger than the width of the second folding portion. In this way, the width of the second folding portion is relatively small to reduce materials for the current collector, and it is also ensured that ensuring that the first folding portion is more easily connected to the first electrode terminal and the second electrode terminal, and that the third folding portion is more easily connected to the electrode assembly. Disposing the guide protruding portion on the second folding portion can increase a current flow area of the part, provided with the second through hole, of the second folding portion.

(35) According to a second aspect, an embodiment of this application provides a battery cell, including a housing, an electrode assembly, and the end cover assembly provided in any one of the embodiments of the first aspect, where the housing has an opening; the electrode assembly is accommodated in the housing; and the end cover is configured to cover the opening, and the first electrode terminal and the second electrode terminal are configured to be electrically connected to the electrode assembly.

(36) In the foregoing solution, the pressure relief mechanism in the battery cell effectively uses space of the end cover and between the first electrode terminal and the second electrode terminal, so that the pressure relief mechanism is more properly arranged, and a larger-sized pressure relief mechanism can be disposed.

(37) According to a third aspect, an embodiment of this application provides a battery, including a box and the battery cell provided in any one of the embodiments of the second aspect; and the battery cell is accommodated in the box.

(38) According to a fourth aspect, an embodiment of this application provides an electric device, including the battery cell provided in any one of the embodiments of the second aspect.

(39) According to a fifth aspect, an embodiment of this application further provides a manufacturing method of a battery cell, including: providing a housing, where the housing has an opening; providing an electrode assembly; providing an end cover assembly, where the end cover assembly includes: an end cover, a first electrode terminal, a second electrode terminal, a connecting member, and a pressure relief mechanism; the first electrode terminal is installed on the end cover; the second electrode terminal is installed on the end cover; the connecting member is configured to be connected to the first electrode terminal and the second electrode terminal, where the connecting member is on a side of the end cover farther away from inside of the battery cell in a first direction; and the pressure relief mechanism is disposed on the end cover, where the pressure relief mechanism is at least partially located between the first electrode terminal and the second electrode terminal, and the pressure relief mechanism is configured to be actuated when internal pressure or temperature of the battery cell reaches a threshold, to relieve the internal pressure of the battery cell; placing the electrode assembly in the housing; and covering the opening with the end cover, where the first electrode terminal and the second electrode terminal are configured to be electrically connected to the electrode assembly.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) To describe the technical solutions in the embodiments of this application more clearly, the following briefly describes the accompanying drawings required for describing the embodiments. It is appreciated that the accompanying drawings below only show some embodiments of this application and thus should not be considered as limitations on the scope. A person of ordinary skill in the art may still derive other related drawings from the accompanying drawings without creative efforts.

(2) FIG. 1 is a schematic structural diagram of a vehicle according to some embodiments of this application;

(3) FIG. 2 is a schematic structural diagram of a battery according to some embodiments of this application;

(4) FIG. 3 is an exploded view of a battery cell according to some embodiments of this application;

(5) FIG. 4 is an exploded view of an end cover assembly according to some embodiments of this application;

(6) FIG. 5 is an exploded view of an end cover assembly according to some other embodiments of this application;

(7) FIG. 6 is a schematic diagram of a connection from a connecting member to a first electrode terminal and a second electrode terminal according to some embodiments of this application;

(8) FIG. 7 is a top view of the end cover assembly shown in FIG. 4;

(9) FIG. 8 is a top view of the end cover assembly shown in FIG. 5;

(10) FIG. 9 is a schematic structural diagram of an end cover of the end cover assembly shown in FIG. 5;

- (11) FIG. 10 is a schematic diagram of a connection between a shielding member, a pressure relief mechanism, and an end cover according to some embodiments of this application;
- (12) FIG. 11 is a cross-sectional view of an end cover assembly according to some embodiments of this application;
- (13) FIG. 12 is a partial cross-sectional view of a battery cell according to some embodiments of this application;
- (14) FIG. 13 is a schematic structural diagram of a current collector (unfolded) of an end cover assembly according to some embodiments of this application; and
- (15) FIG. 14 is a flowchart of a manufacturing method of a battery cell according to some embodiments of this application.

REFERENCE SIGNS

(16) **10.** box; **11.** sealed space; **12.** first part; **13.** second part; **20.** battery cell; **21.** housing; **211.** opening; **22.** electrode assembly; **221.** central hole; **23.** end cover assembly; **231.** end cover; **2311.** first accommodation groove; **2312.** discharge hole; **2312a.** first hole; **2312b.** second hole; **2313.** second accommodation groove; **232.** first electrode terminal; **233.** second electrode terminal; **234.** connecting member; **2341.** first conductive segment; **2342.** second conductive segment; **2343.** insulation segment; **235.** pressure relief mechanism; **2351.** opening region; **2351a.** first opening region; **2351b.** second opening region; **236.** first insulation member; **2361.** groove; **237.** shielding member; **2371.** first through hole; **238.** current collector; **2381.** discharge channel; **2382.** folding portion; **2382a.** first folding portion; **2382b.** second folding portion; **2382c.** third folding portion; **2383.** crease; **2384.** second through hole; **2385.** guide protruding portion; **239.** second insulation member; **2391.** third through hole; **240.** riveting hole; **241.** sealing ring; **25.** protection member; **100.** battery; **200.** controller; **300.** motor; **1000.** vehicle; **Z.** first direction; **X.** second direction; and **Y.** third direction.

DESCRIPTION OF EMBODIMENTS

(17) To make the objectives, technical solutions, and advantages of the embodiments of this application clearer, the following clearly describes the technical solutions in the embodiments of this application with reference to the accompanying drawings in the embodiments of this application. Apparently, the embodiments described are some rather than all embodiments of this application. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of this application without creative efforts shall fall within the protection scope of this application.

(18) Unless otherwise defined, all technical and scientific terms used in this application shall have the same meanings as commonly understood by those skilled in the art to which this application relates. The terms used in the specification of this application are intended to merely describe the specific embodiments rather than to limit this application. The terms “include”, “comprise”, and any variations thereof in the specification and claims of this application as well as the foregoing description of drawings are intended to cover non-exclusive inclusions. In the specification, claims, or accompanying drawings of this application, the terms “first”, “second”, and the like are intended to distinguish between different objects rather than to indicate a particular order or relative importance.

(19) Reference to “embodiment” in this application means that specific features, structures, or characteristics described with reference to the embodiment may be included in at least one embodiment of this application. The word “embodiment” appearing in various places in the specification does not necessarily refer to the same embodiment or an independent or alternative embodiment that is exclusive of other embodiments.

(20) In the description of this application, it should be noted that unless otherwise specified and defined explicitly, the terms “mount”, “connect”, “join”, and “attach” should be understood in their general senses. For example, they may refer to a fixed connection, a detachable connection, or an integral connection, and may refer to a direct connection, an indirect connection via an intermediate

medium, or an internal communication between two elements. A person of ordinary skill in the art can understand specific meanings of these terms in this application based on specific situations. (21) In the embodiments of this application, the same reference signs denote the same components. For brevity, in different embodiments, detailed descriptions of the same components are not repeated. It should be understood that, as shown in the accompanying drawings, sizes such as thickness, length, and width of various components and sizes such as thickness, length, and width of integrated devices in the embodiments of this application are merely for illustrative purposes and should not constitute any limitations on this application.

(22) In this application, “a plurality of” means more than two (inclusive).

(23) In this application, the battery cell may include a lithium-ion secondary battery, a lithium-ion primary battery, a lithium-sulfur battery, a sodium-lithium-ion battery, a sodium-ion battery, a magnesium-ion battery, or the like. This is not limited in the embodiments of this application. The battery cell may be cylindrical, flat, cuboid, or of other shapes, which is not limited in the embodiments of this application either. Battery cells are typically divided into three types by packaging method: cylindrical cell, prismatic cell, and pouch cell. The type of battery is not limited in the embodiments of this application either.

(24) The battery mentioned in the embodiments of this application is a single physical module that includes one or more battery cells for providing a higher voltage and capacity. For example, the battery mentioned in this application may include a battery module, a battery pack, or the like. A battery typically includes a box configured to enclose one or more battery cells. The box can prevent liquids or other foreign matter from affecting charging or discharging of the battery cell.

(25) The battery cell includes an electrode assembly and an electrolyte. The electrode assembly includes a positive electrode plate, a negative electrode plate, and a separator. Working of the battery cell mainly relies on migration of metal ions between the positive electrode plate and the negative electrode plate. The positive electrode plate includes a positive electrode current collector and a positive electrode active substance layer. The positive electrode active substance layer is applied on a surface of the positive electrode current collector. The part of positive electrode current collector uncoated with the positive electrode active substance layer protrudes out of the part of positive electrode current collector coated with the positive electrode active substance layer and serves as a positive tab. A lithium-ion battery is used as an example, for which, the positive electrode current collector may be made of aluminum and the positive electrode active substance may be lithium cobaltate, lithium iron phosphate, ternary lithium, lithium manganate, or the like. The negative electrode plate includes a negative electrode current collector and a negative electrode active substance layer. The negative electrode active substance layer is applied on a surface of the negative electrode current collector. The part of negative electrode current collector uncoated with the negative electrode active substance layer protrudes out of the part of negative electrode current collector coated with the negative electrode active substance layer and serves as a negative tab. The negative electrode current collector may be made of copper, and the negative electrode active substance may be carbon, silicon, or the like. To allow a large current to pass through without any fusing, multiple positive tabs are provided and stacked together, and multiple negative tabs are provided and stacked together. The separator may be made of PP (polypropylene, polypropylene), PE (polyethylene, polyethylene), or the like. In addition, the electrode assembly may be a winding structure or a laminated structure, but the embodiments of this application are not limited thereto. (26) For the development of battery technology, many design factors need to be considered, for example, performance parameters such as energy density, cycle life, discharge capacity, and charge and discharge rate, as well as safety of the battery.

(27) For the battery cell, a main safety hazard originates from charging and discharging processes, and an appropriate ambient temperature design is also required. To effectively avoid unnecessary loss, usually at least three protective measures are taken for the battery cell. Specifically, the protective measures include at least a switch element, selection of an appropriate separator

material, and a pressure relief mechanism. The switch element refers to an element that can stop charging or discharging of the battery when temperature or resistance in the battery cell reaches a specific threshold. The separator is configured to separate a positive electrode plate and a negative electrode plate. When temperature rises to a specific numerical value, microscale (or even nanoscale) micropores attached to the separator may be automatically dissolved, so that metal ions cannot pass through the separator, thereby terminating a reaction inside the battery cell.

(28) The pressure relief mechanism is an element or a part that is actuated when the internal pressure or temperature of the battery cell reaches a predetermined threshold, so as to relieve internal pressure or temperature of the battery cell. The threshold design varies with a design requirement. The threshold may depend on the material used for one or more of the positive electrode plate, negative electrode plate, electrolyte, and separator in the battery cell. The pressure relief mechanism may be in a form of an explosion-proof valve, a rupture disk, a gas valve, a pressure relief valve, a safety valve, or the like, and may specifically use a pressure sensitive or temperature sensitive component or structure. To be specific, when internal pressure or temperature of the battery cell reaches the predetermined threshold, the pressure relief mechanism performs an action or a weak structure provided in the pressure relief mechanism is destroyed, thereby forming an opening or channel for relief of the internal pressure or temperature.

(29) “Actuate” mentioned in this application means that the pressure relief mechanism is put into action or is activated to a given state such that the internal pressure and temperature of the battery cell are relieved. The action that the pressure relief mechanism is put into may include but is not limited to, for example, cracking, breaking, tearing, or opening at least part of the pressure relief mechanism. When the pressure relief mechanism is actuated, the high-temperature and high-pressure substances inside the battery cell are discharged as emissions from an actuated site. In this way, the battery cell can relieve its pressure and temperature under controllable pressure or temperature, thereby avoiding more serious potential incidents.

(30) The emissions from the battery cell mentioned in this application include but are not limited to: electrolyte, fragments of positive and negative electrode plates and separator because of dissolution or breaking, high-temperature and high-pressure gases and flames produced by reactions, and the like.

(31) The pressure relief mechanism in the battery cell greatly influences the safety of the battery. For example, when a short circuit, overcharging, or the like occurs, thermal runaway may be caused inside the battery cell, resulting in a sudden rise in pressure or temperature. In this case, the pressure relief mechanism can be actuated to relieve the internal pressure and temperature to the outside, thus preventing the battery cell from exploding and catching fire.

(32) The inventors have found that in the battery cell, the pressure relief mechanism is generally arranged in a duct on the electrode terminal, and a size of the pressure relief mechanism is limited by a size of the electrode terminal. Because of improper arrangement of the pressure relief mechanism, a pressure relief mechanism of a large size cannot be arranged in the battery cell, and as a result, a pressure relief capability of the pressure relief mechanism is low.

(33) In view of this, an embodiment of this application provides a technical solution, at least part of a pressure relief mechanism is disposed between a first electrode terminal and a second electrode terminal, so that space of an end cover and between the first electrode terminal and the second electrode terminal can be effectively used to dispose a pressure relief mechanism of a larger size, thereby improving the pressure relief capability of the pressure relief mechanism.

(34) The technical solution described in the embodiments of this application is applicable to batteries and electric devices using a battery.

(35) The electric device may be a vehicle, a mobile phone, a portable device, a notebook computer, a ship, a spacecraft, an electric toy, an electric tool, or the like. The vehicle may be a fossil fuel vehicle, a natural gas vehicle, or a new energy vehicle. The new energy vehicle may be a battery electric vehicle, a hybrid electric vehicle, a range-extended electric vehicle, or the like. The

spacecraft includes an airplane, a rocket, a space shuttle, a spaceship, and the like. The electric toy includes a fixed or mobile electric toy, for example, a game console, an electric toy car, an electric toy ship, an electric toy airplane, and the like. The electric tool includes an electric metal cutting tool, an electric grinding tool, an electric assembly tool, and an electric railway-specific tool, for example, an electric drill, an electric grinder, an electric wrench, an electric screwdriver, an electric hammer, an electric impact drill, a concrete vibrator, and an electric planer. The embodiments of this application impose no special limitation on the foregoing electric device.

(36) For ease of description, the electric device being a vehicle is used as example for description of the following embodiments.

(37) Referring to FIG. 1, FIG. 1 is a schematic structural diagram of a vehicle **1000** according to some embodiments of this application. The vehicle **1000** is provided with a battery **100** inside, where the battery **100** may be disposed at the bottom, front or rear of the vehicle **1000**. The battery **100** may be configured to supply power to the vehicle **1000**. For example, the battery **100** may be used as an operational power source for the vehicle **1000**.

(38) The vehicle **1000** may further include a controller **200** and a motor **300**, where the controller **200** is configured to control the battery **100** to supply power to the motor **300**, for example, to satisfy power needs of start, navigation, and driving of the vehicle **1000**.

(39) In some embodiments of this application, the battery **100** can be used as not only the operational power source for the vehicle **1000** but also a driving power source for the vehicle **1000**, replacing or partially replacing fossil fuel or natural gas to provide driving traction for the vehicle **1000**.

(40) Referring to FIG. 2, FIG. 2 is a schematic structural diagram of a battery **100** according to some embodiments of this application. The battery **100** includes a box **10** and a battery cell **20**, and the battery cell **20** is accommodated in the box **10**.

(41) The box **10** is configured to provide a sealed space **11** for the battery cell **20**. In some embodiments, the box **10** may include a first part **12** and a second part **13**. The first part **12** and the second part **13** are engaged with each other to jointly define the sealed space **11** for accommodating the battery cell **20**. Certainly, a joint of the first part **12** and the second part **13** can be sealed by a sealing member (not shown in the figure), and the sealing member may be a sealing ring, a sealing adhesive, or the like.

(42) The first part **12** and the second part **13** may have a variety of shapes, for example, cuboid, cylinder, or the like. The first part **12** may be a hollow structure with one side open, and the second part **13** may also be a hollow structure with one side open, where the opening side of the second part **13** is engaged with the opening side of the first part **12** so as to form the box **10** having the sealed space **11**. Certainly, as shown in FIG. 2, the first part **12** may be a hollow structure with one side open, and the second part **13** may be a plate structure, where the second part **13** covers the opening side of the first part **12** so as to form the box **10** having the sealed space **11**.

(43) In the battery **100**, one or a plurality of battery cells **20** may be provided. If a plurality of battery cells **20** are provided, the plurality of battery cells **20** may be connected in series, parallel, or series-parallel, where being connected in series-parallel means a combination of series and parallel connections of the plurality of battery cells **20**. The plurality of battery cells **20** may be directly connected in series, parallel or series-parallel, and then an entirety of the plurality of battery cells **20** is accommodated in the box **10**; or certainly, the plurality of battery cells **20** may be connected in series, parallel or series-parallel first to form a battery module and then a plurality of battery modules are connected in series, parallel or series-parallel to form an entirety which is accommodated in the box **10**. The battery cell **20** may be cylindrical, flat, cuboid, or have other shapes. FIG. 2 shows an example of a cylindrical battery cell **20**.

(44) In some embodiments, the battery **100** may further include a busbar (not shown in the figure), and the plurality of battery cells **20** may be electrically connected through the busbar, so as to connect the plurality of battery cells **20** in series, parallel, or series-parallel.

(45) Referring to FIG. 3, FIG. 3 is an exploded view of a battery cell **20** according to some embodiments of this application. The battery cell **20** may include a housing **21**, an electrode assembly **22**, and an end cover assembly **23**. The housing **21** has an opening **211**, the electrode assembly **22** is accommodated in the housing **21**, and the end cover assembly **23** is configured to cover the opening **211**.

(46) The housing **21** may have various shapes, such as a cylindrical shape and a cuboid shape. The shape of the housing **21** may be determined based on a specific shape of the electrode assembly **22**. For example, if the electrode assembly **22** is a cylindrical structure, the housing **21** may use a cylindrical structure; or if the electrode assembly **22** is a cuboid structure, the housing **21** may use a cuboid structure. FIG. 3 shows an example of a cylindrical housing **21** and a cylindrical electrode assembly **22**.

(47) The housing **21** may be made of various materials, for example, copper, iron, aluminum, stainless steel, and aluminum alloy. This is not particularly limited in the embodiments of this application.

(48) The electrode assembly **22** may include a positive electrode plate (not shown in the figure), a negative electrode plate (not shown in the figure), and a separator (not shown in the figure). The electrode assembly **22** may be a wound structure formed by winding the positive electrode plate, the separator, and the negative electrode plate, or may be a stacked structure formed by stacking the positive electrode plate, the separator, and the negative electrode plate. The electrode assembly **22** further includes a positive tab (not shown in the figure) and a negative tab (not shown in the figure), a positive electrode current collector, uncoated with a positive electrode active substance layer, of the positive electrode plate may be used as the positive tab, and a negative electrode current collector, uncoated with a negative electrode active substance layer, of the negative electrode plate may be used as the negative tab.

(49) The end cover assembly **23** is configured to cover the opening **211** of the housing **21** to form a sealed accommodation space (not shown in the figure), and the accommodation space is configured to accommodate the electrode assembly **22**. The accommodation space is also configured to accommodate an electrolyte such as a liquid electrolyte. The end cover assembly **23** is used as a component for outputting electric energy of the electrode assembly **22**, and an electrode terminal in the end cover assembly **23** is configured to be electrically connected to the electrode assembly **22**. That is, the electrode terminal is electrically connected to a tab of the electrode assembly **22**. For example, the electrode terminal is connected to the tab through a current collector **238** (refer to FIG. 11), so as to electrically connect the electrode terminal to the tab.

(50) It should be noted that the housing **21** may have one or two openings **211**. If the housing **21** has one opening **211**, there may also be one end cover assembly **23**. Two electrode terminals can be disposed in the end cover assembly **23**. The two electrode terminals are respectively configured to be electrically connected to the positive tab and the negative tab of the electrode assembly **22**. The two electrode terminals in the end cover assembly **23** are respectively a positive electrode terminal and a negative electrode terminal. As shown in FIG. 3, if the housing **21** has two openings **211**, for example, the two openings **211** are disposed on two opposite sides of the housing **21**, there may also be two end cover assemblies **23**. The two end cover assemblies **23** respectively cover the two openings **211** of the housing **21**. In this case, an electrode terminal in one end cover assembly **23** may be a positive electrode terminal configured to be electrically connected to the positive tab of the electrode assembly **22**, and an electrode terminal in the other end cover assembly **23** is a negative electrode terminal configured to be electrically connected to the negative electrode plate of the electrode assembly **22**.

(51) In some embodiments, as shown in FIG. 3, the battery cell **20** may further include protection members **25** fixed on the tabs (not shown in the figure), and the protection members **25** are configured to insulate and isolate the tabs from the housing **21**. One protection member **25** isolates the positive tab of the electrode assembly **22** from the housing **21**, and the other protection member

25 isolates the negative tab of the electrode assembly **22** from the housing. For example, the protection member **25** is an adhesive tape bound to the tab.

(52) Referring to FIG. 4 and FIG. 5, FIG. 4 is an exploded view of an end cover assembly **23** according to some embodiments of this application, and FIG. 5 is an exploded view of an end cover assembly **23** according to some other embodiments of this application. The end cover assembly **23** may include an end cover **231**, a first electrode terminal **232**, a second electrode terminal **233**, a connecting member **234**, and a pressure relief mechanism **235**.

(53) The first electrode terminal **232** is installed on the end cover **231**; and the second electrode terminal **233** is installed on the end cover **231**, and the connecting member **234** is configured to be connected to the first electrode terminal **232** and the second electrode terminal **233**. The connecting member **234** is on a side of the end cover **231** farther away from the inside of the battery cell **20** (refer to FIG. 3) in a first direction Z. The pressure relief mechanism **235** is disposed on the end cover **231**, the pressure relief mechanism **235** is at least partially located between the first electrode terminal **232** and the second electrode terminal **233**, and the pressure relief mechanism **235** is configured to be actuated when internal pressure or temperature of the battery cell **20** reaches a threshold, to relieve the internal pressure of the battery cell **20**.

(54) The pressure relief mechanism **235** in the end cover assembly **23** with the foregoing structure effectively uses space of the end cover **231** and between the first electrode terminal **232** and the second electrode terminal **233**, so that the pressure relief mechanism **235** is more properly arranged, and a larger-sized pressure relief mechanism **235** can be disposed to improve a pressure relief capability of the pressure relief mechanism.

(55) The end cover **231** in the end cover assembly **23** is configured to cover the opening **211** of the housing **21** (refer to FIG. 3). The end cover **231** may have various shapes, such as a round shape and a rectangular shape. A shape of the end cover **231** depends on a shape of the housing **21**. If the housing **21** is a cylindrical structure, a round end cover **231** can be selected; or if the housing **21** is a cuboid structure, a rectangular end cover **231** can be selected. FIG. 4 and FIG. 5 show an example of a round end cover **231**.

(56) The first direction Z mentioned in this embodiment of this application is a thickness direction of the end cover **231**, and if the end cover **231** is a round structure, the first direction Z is also an axial direction of the end cover **231**.

(57) It should be noted that polarities of the first electrode terminal **232** and the second electrode terminal **233** of the end cover assembly **23** may be the same or different.

(58) In some embodiments, the polarities of the first electrode terminal **232** and the second electrode terminal **233** are the same, and the connecting member **234** is connected to the two electrode terminals with the same polarity. The connecting member **234** has a function of collecting electric energy, thereby enlarging a connection area between the battery cell **20** and a busbar.

(59) The first electrode terminal **232** and the second electrode terminal **233** may both be positive electrode terminals configured to be electrically connected to a positive tab of an electrode assembly **22**; or the first electrode terminal **232** and the second electrode terminal **233** may alternatively be both negative electrode terminals configured to be electrically connected to a negative tab of the electrode assembly **22**.

(60) In this embodiment, the battery cell **20** may have two end cover assemblies **23**, an electrode terminal in one end cover assembly **23** is a positive electrode terminal, and an electrode terminal in the other end cover assembly **23** is a negative electrode terminal. Certainly, structures of the two end cover assemblies **23** may be the same or different. For example, one end cover assembly **23** is provided with a pressure relief mechanism **235**, but the other end cover assembly **23** is not provided with a pressure relief mechanism **235**.

(61) When the polarities of the first electrode terminal **232** and the second electrode terminal **233** are the same, the connecting member **234** may be a conductor connected to the first electrode terminal **232** and the second electrode terminal **233**, so that current from the first electrode terminal

232 and the second electrode terminal **233** is collected and conducted to the connecting member **234**. When the two battery cells **20** are connected in series or in parallel through a busbar (not shown in the figure), the busbar may be connected to the connecting member **234**. For example, the busbar is welded to the connecting member **234**.

(62) In some embodiments, the polarities of the first electrode terminal **232** and the second electrode terminal **233** are opposite, one of the first electrode terminal **232** and the second electrode terminal **233** is a positive electrode terminal configured to be electrically connected to a positive tab of an electrode assembly **22**, and the other one of the first electrode terminal **232** and the second electrode terminal **233** is a negative electrode terminal configured to be electrically connected to a negative tab of the electrode assembly **22**.

(63) In this embodiment, the battery cell **20** may have one end cover assembly **23**.

(64) When the polarities of the first electrode terminal **232** and the second electrode terminal **233** are opposite, the connecting member **234** is connected between the first electrode terminal **232** and the second electrode terminal **233**, to fasten the first electrode terminal **232** and the second electrode terminal **233**.

(65) It can be understood that the first electrode terminal **232** and the second electrode terminal **233** are not electrically connected through the connecting member **234**. For example, referring to FIG. 6, FIG. 6 is a schematic structural diagram of a connection of the connecting member **234** to the first electrode terminal **232** and the second electrode terminal **233** according to some embodiments of this application. The connecting member **234** is a multi-segment structure. The connecting member **234** includes a first conductive segment **2341**, a second conductive segment **2342**, and an insulation segment **2343**, and the first conductive segment **2341** and the second conductive segment **2342** are connected through the insulation segment **2343**, to isolate the first conductive segment **2341** from the second conductive segment **2342**. The first conductive segment **2341** is connected to the first electrode terminal **232**, and the second conductive segment **2342** is connected to the second electrode terminal **233**. The first conductive segment **2341** is configured to be connected and fastened to one busbar (not shown in the figure), and the second conductive segment **2342** is configured to be connected and fastened to another busbar.

(66) In some embodiments, referring to FIG. 7 and FIG. 8, FIG. 7 is a top view of the end cover assembly **23** shown in FIG. 4; and FIG. 8 is a top view of the end cover assembly **23** shown in FIG. 5. A projection of the connecting member **234** in the first direction Z (refer to FIG. 4 and FIG. 5) covers at least part of the pressure relief mechanism **235**. That is, in the first direction Z, at least part of the pressure relief mechanism **235** is blocked by the connecting member **234**, so that the pressure relief mechanism **235** effectively uses space, occupied by the connecting member **234**, on the end cover **231**, thereby more properly using the space on the end cover **231**.

(67) The pressure relief mechanism **235** may have various structures. The pressure relief mechanism **235** may be an explosion-proof valve, a rupture disk, a gas valve, a pressure relief valve, a safety valve, or the like. The pressure relief mechanism **235** may alternatively be a weak part on the end cover **231**. Actuating the pressure relief mechanism **235** may be breaking a part of the pressure relief mechanism **235**. For example, the pressure relief mechanism **235** is the rupture disk, and a part of the rupture disk is broken under pressure inside the battery cell **20**. Alternatively, actuating the pressure relief mechanism **235** may be opening a part of the pressure relief mechanism **235**. For example, the pressure relief mechanism **235** is a pressure relief valve, and a pressure relief hole of the pressure relief valve is opened.

(68) In some embodiments, the pressure relief mechanism **235** includes an opening region **2351**, and the pressure relief mechanism **235** is configured to relieve the internal pressure of the battery cell **20** through the opening region **2351** when the internal pressure or temperature of the battery cell **20** reaches the threshold. A projection of the connecting member **234** in the first direction Z covers a part of the opening region **2351**, and a projection of the opening region **2351** in the first direction Z exceeds the projection of the connecting member **234** in the first direction Z. That is, at

least part of the opening region **2351** is not blocked by the connecting member **234**, so that the internal pressure of the battery cell **20** is more smoothly relieved through the opening region **2351**. (69) The opening region **2351** is a part opened when the pressure relief mechanism **235** is actuated. For example, the pressure relief mechanism **235** is a weak part of the end cover **231**, and the opening region **2351** is the weak part. For another example, the pressure relief mechanism **235** is a pressure relief valve, and the opening region **2351** is a pressure relief hole of the pressure relief valve. For still another example, the pressure relief mechanism **235** is a rupture disk, and the opening region **2351** is a to-be-destroyed part of the rupture disk.

(70) In some embodiments, as shown in FIG. 4 and FIG. 5, the pressure relief mechanism **235** is a rupture disk, the end cover **231** is provided with a discharge hole **2312**, and the rupture disk is fastened to the end cover **231** to seal the discharge hole **2312**. When the internal pressure or temperature of the battery cell **20** reaches a threshold, a region, located within a range of the discharge hole **2312**, of the rupture disk is destroyed, and an emission inside the battery **100** can be discharged through the discharge hole **2312** of the end cover **231**, thereby relieving the internal pressure of the battery cell **20**. It can be understood that a region, located within a range defined by a wall of the discharge hole **2312**, of the rupture valve is the opening region **2351**. For ease of description, hereinafter, the rupture disk is used as an example of the pressure relief mechanism **235**, and the opening region **2351** of the rupture disk is used as an example of the opening region **2351** of the pressure relief mechanism **235**.

(71) For example, the end cover **231** is round, and the discharge hole **2312** is disposed at a center of the end cover **231**.

(72) In some embodiments, the opening region **2351** extends along a second direction X, and the connecting member **234** extends along a third direction Y; and any two of the first direction Z, the second direction X, and the third direction Y are perpendicular to each other. Such structure ensures that a region, blocked by the connecting member **234**, of the opening region **2351** is smaller, and the internal pressure of the battery cell **20** is more smoothly relieved through the opening region **2351**.

(73) Because the opening region **2351** of the rupture disk is a region, located within a range defined by a wall of the discharge hole **2312**, of the rupture disk, an extending direction (the second direction X) of the opening region **2351** is an extending direction of the discharge hole **2312**.

(74) In some embodiments, as shown in FIG. 7, width of the discharge hole **2312** on the end cover **231** in the third direction Y remains substantially unchanged in the second direction X. For example, the discharge hole **2312** is a bar-shaped hole. The connecting member **234** is a block-shaped member extending along the third direction Y. The first electrode terminal **232** and the second electrode terminal **233** are spaced apart along the third direction Y, and are respectively on two sides of the discharge hole **2312** in the third direction Y.

(75) In some embodiments, as shown in FIG. 8, the opening region **2351** includes a first opening region **2351a** and a second opening region **2351b**, and the second opening region **2351b** is arranged on at least one end of the first opening region **2351a** in the second direction X. A projection of the connecting member **234** in the first direction Z (refer to FIG. 5) covers at least part of the first opening region **2351a**. That is, in the first direction Z, at least part of the first opening region **2351a** is blocked by the connecting member **234**. A projection of the second opening region **2351b** in the first direction Z exceeds the projection of the connecting member **234** in the first direction Z. That is, in the second direction X, at least part of the second opening region **2351b** is not blocked by the connecting member **234**. Width of the second opening region **2351b** in the third direction Y is greater than width of the first opening region **2351a** in the third direction Y. Such structure enlarges an area of the opening region **2351**, and therefore the internal pressure of the battery cell **20** is more smoothly relieved through the opening region **2351**.

(76) Referring to FIG. 9. FIG. 9 is a schematic structural diagram of an end cover **231** of the end cover assembly **23** shown in FIG. 5. The discharge hole **2312** includes a first hole **2312a** and a

second hole **2312b** communicating with each other, the second hole **2312b** is disposed on at least one end of the first hole **2312a** in the second direction X, the first hole **2312a** is corresponding to the first opening region **2351a** (refer to FIG. 8), and the second hole **2312b** is corresponding to the second opening region **2351b** (refer to FIG. 8).

(77) For example, a second opening region **2351b** is disposed on both ends of the first opening region **2351a**. In the second direction X, two ends of the first opening region **2351a** respectively exceed two sides of the connecting member **234**, so that the projection of the connecting member **234** in the first direction Z covers only a part of the first opening region **2351a**. That is, the connecting member **234** blocks only a part of the first opening region **2351a** in the first direction Z. It can be understood that a second hole **2312b** is disposed on both ends of the first hole **2312a**.

(78) The second opening region **2351b** may have various shapes, such as a round shape, a rectangular shape, or an elliptical shape. FIG. 8 shows an example of an elliptical second opening region **2351b**.

(79) It can be learned from the foregoing embodiments that the projection of the connecting member **234** in the first direction Z can cover at least part of the pressure relief mechanism **235** so as to effectively use space on the end cover **231** that is occupied by the connecting member **234**. In another embodiment, the projection of the connecting member **234** in the first direction Z may not cover the pressure relief mechanism **235**. That is, in the first direction Z, the pressure relief mechanism **235** is not blocked by the connecting member **234**. In this case, for example, the connecting member **234** may be an arc-shaped structure, the two ends of the connecting member **234** are respectively connected to the first electrode terminal **232** and the second electrode terminal **233**, and an axis of an arc of the connecting member **234** is arranged along the first direction Z.

(80) In some embodiments, as shown in FIG. 4 and FIG. 5, the end cover assembly **23** may further include a first insulation member **236**, at least part of the first insulation member **236** is disposed between the connecting member **234** and the end cover **231** to isolate the end cover **231** from the connecting member **234**.

(81) The first insulation member **236** has an insulation function, the first insulation member **236** is an insulation material, and may be made of a material such as rubber and plastic, and the plastic may be PBT (Polybutylene terephthalate, polybutylene terephthalate), PET (Polyethylene terephthalate, polyethylene terephthalate), PA (Polyamide, polyamide), or the like.

(82) In some embodiments, a groove **2361** is disposed on a side of the first insulation member **236** farther away from the end cover **231**, and the connecting member **234** is disposed in the groove **2361** to increase a creepage distance between the first insulation member **236** and the end cover **231**.

(83) It should be noted that, when the end cover assembly **23** is provided with the first insulation member **236**, the projection of the first insulation member **236** in the first direction Z may cover a part of the opening region **2351** of the pressure relief mechanism **235**, and the projection of the opening region **2351** in the first direction Z exceeds the projection of the first insulation member **236** in the first direction Z. That is, the pressure relief mechanism **235** is not completely blocked by the first insulation member **236** in the first direction Z.

(84) In some embodiments, referring to FIG. 10, FIG. 10 is a schematic diagram of a connection between a shielding member **237**, a pressure relief mechanism **235**, and an end cover **231** according to some embodiments of this application. The end cover assembly **23** may further include a shielding member **237** for shielding the pressure relief mechanism **235**, and a first accommodation groove **2311** for accommodating the shielding member **237** is provided on the side of the end cover **231** closer to the connecting member **234**, to reduce external space of the end cover **231** that is occupied by the shielding member **237**.

(85) For example, the shielding member **237** and the pressure relief mechanism **235** respectively block two ends of the discharge hole **2312**, so that the shielding member **237** shields the pressure relief mechanism **235**. The shielding member **237** has a good protection effect on the pressure relief

mechanism **235**, to reduce a risk that a foreign substance enters the discharge hole **2312** to contaminate and damage the pressure relief mechanism **235**.

(86) It should be noted that, relieving the internal pressure of the battery cell **20** through the pressure relief mechanism **235** may be detaching of the shielding member **237** from the end cover **231**, or damaging the shielding member **237**, so that the internal pressure of the battery cell **20** is smoothly relieved.

(87) For example, the shielding member **237** is a plate-shaped structure, and the shielding member **237** may be bound to the end cover **231**.

(88) In some embodiments, the shielding member **237** is provided with a first through hole **2371**, and the first through hole **2371** has a pressure balancing function for balancing pressure in a region between the shielding member **237** and the pressure relief mechanism **235** and external pressure, thereby preventing the shielding member from detaching from the end cover **231** or being damaged before the pressure relief mechanism **235** is actuated due to an excessively large region between the shielding member **237** and the pressure relief mechanism **235** (inner region of the discharge hole **2312**).

(89) For example, the shielding member **237** is a plate-shaped structure, depth of the first accommodation groove **2311** is greater than thickness of the shielding member **237**, and after the shielding member **237** is accommodated in the first accommodation groove **2311** on the end cover **231**, a gap between the shielding member **237** and the first insulation member **236** is enlarged, to reduce a risk of blocking the first through hole **2371** by the first insulation member **236**.

(90) In some embodiments, a second accommodation groove **2313** for accommodating the pressure relief mechanism **235** may be disposed on a side of the end cover **231** farther away from the connecting member **234**, to reduce the external space of the end cover **231** that is occupied by the pressure relief mechanism **235**.

(91) In some embodiments, as shown in FIG. 4 and FIG. 5, the end cover assembly **23** may further include a current collector **238** configured to be connected to the first electrode terminal **232**, the second electrode terminal **233**, and an electrode assembly **22** of the battery cell **20**. (refer to FIG. 3).

(92) It should be noted that if the first electrode terminal **232** and the second electrode terminal **233** in the end cover assembly **23** have the same polarity, for example, both the first electrode terminal **232** and the second electrode terminal **233** are negative electrode terminals, the end cover assembly **23** may include one current collector **238**, one end of the current collector **238** is connected to the first electrode terminal **232** and the second electrode terminal **233**, and the other end of the current collector **238** is connected to a negative tab of the electrode assembly **22**. Alternatively, if the first electrode terminal **232** and the second electrode terminal **233** in the end cover assembly **23** have opposite polarities, for example, the first electrode terminal **232** is a positive electrode terminal and the second electrode terminal **233** is a negative electrode terminal, the end cover assembly **23** may include two current collectors **238**, one end of one current collector **238** is connected to the first electrode terminal **232**, the other end of the current collector **238** is connected to a positive tab of the electrode assembly **22**, one end of the other current collector **238** is connected to the second electrode terminal **233**, and the other end of the other current collector **238** is connected to a negative tab of the electrode assembly **22**. FIG. 4 and FIG. 5 show an example of a first electrode terminal **232** and a second electrode terminal **233** with the same polarity.

(93) In some embodiments, the end cover assembly **23** may further include a second insulation member **239**, and at least part of the second insulation member **239** is disposed between the end cover **231** and the current collector **238**, to isolate the end cover **231** from the current collector **238**.

(94) The second insulation member **239** has an insulation function, the second insulation member **239** is an insulation material, and may be made of a material such as rubber and plastic, and the plastic may be PBT (Polybutylene terephthalate, polybutylene terephthalate), PET (Polyethylene terephthalate, polyethylene terephthalate), PA (Polyamide, polyamide), or the like.

(95) In some embodiments, referring to FIG. 11, FIG. 11 is a cross-sectional view of an end cover assembly **23** according to some embodiments of this application. For example, the first electrode terminal **232** and the second electrode terminal **233** have the same polarity, the connecting member **234**, the first insulation member **236**, the end cover **231**, the second insulation member **239**, and the current collector **238** are riveted together through the first electrode terminal **232** and the second electrode terminal **233**.

(96) As shown in FIG. 4 and FIG. 5, a riveting hole **240** used for the first electrode terminal **232** and the second electrode terminal **233** to pass through is disposed on each of the connecting member **234**, the first insulation member **236**, the end cover **231**, the second insulation member **239**, and the current collector **238**.

(97) In some embodiments, the end cover assembly **23** may further include a sealing ring **241**, the sealing ring **241** is provided between the first electrode terminal **232** and the end cover **231**, and the sealing ring **241** is provided between the second electrode terminal **233** and the end cover **231**, to seal the riveting holes **240** on the end cover **231**.

(98) In some embodiments, further referring to FIG. 11, the current collector **238** is provided with a discharge channel **2381**. An emission produced by the battery cell **20** due to thermal runaway can be discharged to outside of the battery cell **20** through the discharge channel **2381** and the pressure relief mechanism **235** in sequence, to relieve the internal pressure of the battery cell **20**. In other words, when the thermal runaway occurs in the battery cell **20**, an internal emission of the battery cell **20** can be discharged to outside of the battery cell **20** through the discharge channel **2381** and the pressure relief mechanism **235** in sequence, so that the emission produced due to the thermal runaway of the battery cell **20** can be discharged in a timely manner, to relieve internal pressure of the battery cell **20**.

(99) It should be noted that, that the emission produced due to the thermal runaway of the battery cell **20** can be discharged to the outside of the battery cell **20** through the discharge channel **2381** and the pressure relief mechanism **235** in sequence does not limit that the emission produced due to the thermal runaway of the battery cell **20** can be discharged to the outside of the battery cell **20** only through the discharge channel **2381** and the pressure relief mechanism **235** in sequence. The emission can alternatively be discharged to the outside of the battery cell **20** through another path. For example, some emissions are directly discharged to the outside of the battery cell **20** through the pressure relief mechanism **235**.

(100) In some embodiments, also referring to FIG. 13, the current collector **238** includes a plurality of folding portions **2382**, a crease **2383** is formed between every two adjacent folding portions **2382**, each folding portion **2382** is provided with a second through hole **2384**, and a plurality of second through holes **2384** jointly form the discharge channel **2381**.

(101) The current collector **238** being a folding structure helps to dispose the current collector **238** between the end cover **231** and the electrode assembly **22**, thereby reducing the space occupied by the current collector **238**. The current collector **238** has a folded state (refer to FIG. 5) and an unfolded state (refer to FIG. 4). In the folded state, the plurality of second through holes **2384** can jointly form the discharge channel **2381**.

(102) It should be noted that the discharge channel **2381** may alternatively be another structure. For example, the current collector **238** is a non-folding plate-shaped structure, and the current collector **238** is disposed flat. In this case, the discharge channel **2381** may be a hole or notch on the current collector **238**.

(103) In some embodiments, projections of the plurality of second through holes **2384** in the first direction Z at least partially overlap the projection of the pressure relief mechanism **235** in the first direction Z. That is, the plurality of first through holes **2371** are substantially aligned with the pressure relief mechanism **235** in the first direction Z. With such structure, the emission in the battery cell **20** is less blocked by the current collector **238**, the emission is more smoothly discharged to the outside through the discharge channel **2381** and the pressure relief mechanism

235, so that the emission is more easily discharged to the outside of the battery cell **20**.

(104) For example, the plurality of second through holes **2384** are substantially aligned with the opening region **2351** (refer to FIG. 7 and FIG. 8) of the pressure relief mechanism **235** in the first direction Z. It can be understood that the plurality of second through holes **2384** are aligned with the discharge hole **2312** on the end cover **231** in the first direction Z.

(105) In some embodiments, one or more third through holes **2391** may be disposed on the second insulation member **239**. At least one through hole is substantially aligned with the discharge channel **2381** and the pressure relief mechanism **235** in the first direction Z, so that the emission in the battery cell **20** is less blocked by the second insulation member **239**, helping the emission smoothly reach the pressure relief mechanism **235** through the discharge channel **2381**.

(106) In some embodiments, referring to FIG. 12, FIG. 12 is a partial cross-sectional view of a battery cell **20** according to some embodiments of this application. Projections of the plurality of second through holes **2384** in the first direction Z at least partially overlap a projection of a central hole **221** of the electrode assembly **22** in the first direction Z. That is, the plurality of second through holes **2384** are substantially aligned with the central hole **221** of the electrode assembly **22** in the first direction Z. With such structure, the discharge channel **2381** and the central hole **221** of the electrode assembly **22** jointly form a straight-through channel to balance pressure on both sides of the electrode assembly **22** in an axial direction of the central hole **221**, thereby reducing a risk of damage to the pressure relief mechanism **235** caused by excessively high pressure on one side of the electrode assembly **22** closer to the end cover **231**.

(107) For example, when the battery cell **20** is dropped, the electrode assembly **22** is displaced relative to the end cover **231** under action of inertia, space between the electrode assembly **22** and the end cover **231** is compressed, and pressure in the region between the electrode assembly **22** and the end cover **231** is increased. Because the discharge channel **2381** and the central hole **221** of the electrode assembly **22** jointly form the straight-through channel, a medium (such as gas) between the electrode assembly **22** and the end cover **231** can enter the central hole **221** of the electrode assembly **22** through the discharge channel **2381** of the current collector **238**, and finally reaches a side of the electrode assembly **22** farther away from the end cover **231** to balance the pressure on both the sides of the electrode assembly **22** in the axial direction of the central hole **221**.

(108) In some embodiments, referring to FIG. 13, FIG. 13 is a schematic structural diagram of a current collector **238** (in an unfolded state) of an end cover assembly **23** according to some embodiments of this application. A guide protruding portion **2385** is provided on at least one side of a part, provided with the second through hole **2384**, of at least one folding portion **2382** of the current collector **238** in an extending direction of the crease **2383**, to increase a current flow area of the part, provided with the second through hole **2384**, of the folding portion **2382**.

(109) The current collector **238** may have two, three, four or more folding portions **2382**.

(110) In some embodiments, as shown in FIG. 13, the current collector **238** includes a first folding portion **2382a**, a second folding portion **2382b**, and a third folding portion **2382c**, the first folding portion **2382a**, the second folding portion **2382b**, and the third folding portion **2382c** are connected in sequence, and the first folding portion **2382a** is configured to electrically connected to the first electrode terminal **232** (refer to FIG. 11) and the second electrode terminal **233** (refer to FIG. 11). The third folding portion **2382c** is configured to be electrically connected to the electrode assembly **22** (refer to FIG. 12).

(111) In some embodiments, as shown in FIG. 13, in the extending direction of the crease **2383**, width of the first folding portion **2382a** and width of the third folding portion **2382c** are both larger than width of the second folding portion **2382b**. With such structure, the width of the second folding portion **2382b** is relatively small to reduce materials for the current collector **238**, and it is also ensured that the first folding portion **2382a** is more easily connected to the first electrode terminal **232** and the second electrode terminal **233**, and that the third folding portion **2382c** is more easily connected to the electrode assembly **22**.

- (112) In some embodiments, a guide protruding portion **2385** is provided on at least one side of a part, provided with the second through hole **2384**, of the second folding portion **2382b** in the extending direction of the crease **2383**, to increase a current flow area of the part, provided with the second through hole **2384**, of the second folding portion **2382b**.
- (113) For example, a guide protruding portion **2385** is provided on both sides of a part, provided with the second through hole **2384**, of the second folding portion **2382b** in the extending direction of the crease **2383**.
- (114) Referring to FIG. **14**, FIG. **14** is a flowchart of a manufacturing method of a battery cell **20** according to some embodiments of this application. The manufacturing method of a battery cell **20** includes the following steps: **S100**. Provide a housing **21**, where the housing **21** has an opening **211**. **S200**. Provide an electrode assembly **22**. **S300**. Provide an end cover assembly **23**, where the end cover assembly **23** includes: an end cover **231**, a first electrode terminal **232**, a second electrode terminal **233**, a connecting member **234**, and a pressure relief mechanism **235**, where the first electrode terminal **232** is installed on the end cover **231**; the second electrode terminal **233** is installed on the end cover **231**; the connecting member **234** is configured to be connected to the first electrode terminal **232** and the second electrode terminal **233**, where the connecting member **234** is on a side of the end cover **231** farther away from inside of the battery cell **20** in a first direction **Z**; and the pressure relief mechanism **235** is disposed on the end cover **231**, where the pressure relief mechanism **235** is at least partially located between the first electrode terminal **232** and the second electrode terminal **233**, and the pressure relief mechanism **235** is configured to be actuated when internal pressure or temperature of the battery cell **20** reaches a threshold, to relieve the internal pressure of the battery cell **20**. **S400**. Place the electrode assembly **22** in the housing **21**. **S500**. Cover the opening **211** of the housing **21** with the end cover **231** of the end cover assembly **23**.
- (115) The first electrode terminal **232** and the second electrode terminal **233** are configured to be electrically connected to the electrode assembly **22**.
- (116) It should be noted that when the battery cell **20** is assembled in the foregoing manufacturing method of a battery cell **20**, a sequence of performing steps **S100**, **S200**, and **S300** is not limited. For example, step **S300** may be performed first, that is, the end cover assembly **23** is provided. Then, step **S200** is performed.
- (117) For a related structure of the battery cell **20** manufactured in the foregoing manufacturing method of a battery cell **20**, refer to the battery cell **20** provided in the foregoing embodiments.
- (118) It should be noted that, without conflict, the embodiments and features in the embodiments in this application may be combined with each other.
- (119) The foregoing embodiments are merely used to describe a technical solution in this application, but are not intended to limit this application. A person skilled in the art understands that this application may have various modifications and variations. Any modification, equivalent replacement, and improvement made without departing from the spirit and principle of this application shall fall within the protection scope of this application.

Claims

1. An end cover assembly, applied to a battery cell and comprising: an end cover; a first electrode terminal installed on the end cover; a second electrode terminal installed on the end cover; a connecting member, configured to be connected to the first electrode terminal and the second electrode terminal, wherein the connecting member is on a side of the end cover farther away from inside of the battery cell in a first direction; and a pressure relief mechanism, disposed on the end cover, wherein the pressure relief mechanism is at least partially located between the first electrode terminal and the second electrode terminal such that the pressure relief mechanism is disposed in a non-overlapping region through a direct axis connecting the first and second electrode terminals,

and the pressure relief mechanism is configured to be actuated when internal pressure or temperature of the battery cell reaches a threshold, to relieve the internal pressure of the battery cell; wherein the pressure relief mechanism comprises an opening region, and the pressure relief mechanism is configured to relieve the internal pressure of the battery cell through the opening region when the internal pressure or temperature of the battery cell reaches the threshold; and a projection of the connecting member in the first direction covers a part of the opening region, and a projection of the opening region in the first direction exceeds the projection of the connecting member in the first direction.

2. The end cover assembly according to claim 1, wherein the projection of the connecting member in the first direction covers at least part of the pressure relief mechanism and the connecting member is positioned at a height substantially the same as a height of the first and second electrode terminals in the first direction.

3. The end cover assembly according to claim 1, wherein the opening region extends along a second direction, and the connecting member extends along a third direction; any two of the first direction, the second direction, and the third direction are perpendicular to each other.

4. The end cover assembly according to claim 3, wherein the opening region comprises a first opening region and a second opening region, and the second opening region is arranged on at least one end of the first opening region in the second direction; the projection of the connecting member in the first direction covers at least part of the first opening region, a projection of the second opening region in the first direction exceeds the projection of the connecting member in the first direction, and width of the second opening region in the third direction is greater than width of the first opening region in the third direction; and any two of the first direction, the second direction, and the third direction are perpendicular to each other.

5. The end cover assembly according to claim 1, wherein the end cover assembly further comprises a shielding member for shielding the pressure relief mechanism; and a first accommodation groove for accommodating the shielding member is provided on a side of the end cover closer to the connecting member.

6. The end cover assembly according to claim 5, wherein the shielding member is provided with a first through hole.

7. The end cover assembly according to claim 1, wherein the first electrode terminal and the second electrode terminal have same polarity.

8. The end cover assembly according to claim 7, wherein the end cover assembly further comprises a current collector, and the current collector is configured to be connected to the first electrode terminal, the second electrode terminal, and an electrode assembly of the battery cell; a discharge channel is disposed on the current collector; and an emission produced by the battery cell due to thermal runaway is able to be discharged to outside of the battery cell through the discharge channel and the pressure relief mechanism in sequence, to relieve the internal pressure of the battery cell.

9. The end cover assembly according to claim 8, wherein the current collector comprises a plurality of folding portions, a crease is formed between every two adjacent folding portions, each folding portion is provided with a second through hole, and a plurality of second through holes jointly form the discharge channel.

10. The end cover assembly according to claim 9, wherein projections of the plurality of second through holes in the first direction overlap at least part of the projection of the pressure relief mechanism in the first direction.

11. The end cover assembly according to claim 9, wherein projections of the plurality of second through holes in the first direction overlap at least part of a projection of a central hole of the electrode assembly in the first direction.

12. The end cover assembly according to claim 9, wherein a guide protruding portion is provided on at least one side of a part, provided with the second through hole, of at least one folding portion

in an extending direction of the crease.

13. The end cover assembly according to claim 9, wherein the plurality of folding portions comprise a first folding portion, a second folding portion, and a third folding portion connected in sequence; the first folding portion is configured to be electrically connected to the first electrode terminal and the second electrode terminal; the third folding portion is configured to be electrically connected to the electrode assembly; width of the first folding portion and width of the third folding portion are both greater than width of the second folding portion in an extending direction of the crease; and a guide protruding portion is provided on at least one side of a part, provided with the second through hole, of the second folding portion in the extending direction of the crease.

14. A battery cell, comprising: a housing having an opening; an electrode assembly accommodated in the housing; and the end cover assembly according to claim 1, wherein an end cover is configured to cover the opening, and the first electrode terminal and the second electrode terminal are configured to be electrically connected to the electrode assembly.

15. A battery, comprising: a box; and the battery cell according to claim 14, wherein the battery cell is accommodated in the box.

16. An electric device, comprising the battery cell according to claim 14.

17. A manufacturing method of a battery cell, comprising: providing a housing, wherein the housing has an opening; providing an electrode assembly; providing an end cover assembly, wherein the end cover assembly comprises: an end cover; a first electrode terminal installed on the end cover; a second electrode terminal installed on the end cover; a connecting member, configured to be connected to the first electrode terminal and the second electrode terminal, wherein the connecting member is on a side of the end cover farther away from inside of the battery cell in a first direction; and a pressure relief mechanism, disposed on the end cover, wherein the pressure relief mechanism is at least partially located between the first electrode terminal and the second electrode terminal such that the pressure relief mechanism is disposed in a non-overlapping region through a direct axis connecting the first and second electrode terminals, and the pressure relief mechanism is configured to be actuated when internal pressure or temperature of the battery cell reaches a threshold, to relieve the internal pressure of the battery cell; wherein the pressure relief mechanism comprises an opening region, and the pressure relief mechanism is configured to relieve the internal pressure of the battery cell through the opening region when the internal pressure or temperature of the battery cell reaches the threshold; and a projection of the connecting member in the first direction covers a part of the opening region, and a projection of the opening region in the first direction exceeds the projection of the connecting member in the first direction; placing the electrode assembly in the housing; and covering the opening with the end cover, wherein the first electrode terminal and the second electrode terminal are configured to be electrically connected to the electrode assembly.
