

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12389366
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Edge; Stephen William et al.

---

### Systems and methods to facilitate location determination by beamforming of a positioning reference signal

---

#### Abstract

Techniques are provided for positioning of a mobile device in a wireless network using directional positioning reference signals (PRS), also referred to as PRS beamforming. In an example method, a plurality of directional PRSs are generated for at least one cell for a base station, such that each of the plurality of directional PRSs comprises at least one signal characteristic and a direction of transmission, either or both of which may be distinct or unique. The plurality of directional PRSs is transmitted within the at least one cell, such that each of the plurality of directional PRSs is transmitted in the direction of transmission. A mobile device may acquire and measure at least one of the directional PRSs which may be identified using the associated signal characteristic. The measurement may be used to assist position methods such as OTDOA and ECID and to mitigate multipath.

---

**Inventors:** Edge; Stephen William (Escondido, CA), Fischer; Sven (Nuremberg, DE), Pon; Rayman (Cupertino, CA)

**Applicant:** Qualcomm Incorporated (San Diego, CA)

**Family ID:** 65038430

**Assignee:** QUALCOMM Incorporated (San Diego, CA)

**Appl. No.:** 18/471115

**Filed:** September 20, 2023

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240023059 A1	Jan. 18, 2024

#### Related U.S. Application Data

continuation parent-doc US 17743431 20220512 US 12279228 child-doc US 18471115  
continuation parent-doc US 16782119 20200205 US 11496990 20221108 child-doc US 17743431  
continuation parent-doc US 15866538 20180110 US 10736074 20200804 child-doc US 16782119  
us-provisional-application US 62538952 20170731

---

## Publication Classification

**Int. Cl.:** **H04W64/00** (20090101); **G01S1/04** (20060101); **G01S5/02** (20100101); **G01S5/10** (20060101); **H04B7/0413** (20170101); **H04B7/0417** (20170101); **H04B7/0452** (20170101); **H04B7/08** (20060101); **H04L1/02** (20060101); **H04L1/04** (20060101); **H04L5/00** (20060101); **H04W4/029** (20180101); **H04W16/28** (20090101); **H04W24/10** (20090101); H04B7/06 (20060101); H04L1/06 (20060101); H04L5/22 (20060101); H04W4/02 (20180101)

## U.S. Cl.:

**CPC** **H04W64/006** (20130101); **G01S1/0428** (20190801); **G01S5/0226** (20130101); **G01S5/0236** (20130101); **G01S5/10** (20130101); **H04B7/0413** (20130101); **H04B7/0417** (20130101); **H04B7/0452** (20130101); **H04B7/0897** (20130101); **H04L1/02** (20130101); **H04L1/04** (20130101); **H04L5/005** (20130101); **H04W4/029** (20180201); **H04W16/28** (20130101); **H04W24/10** (20130101); **H04W64/003** (20130101); H04B7/0617 (20130101); H04L1/06 (20130101); H04L5/0007 (20130101); H04L5/0048 (20130101); H04L5/22 (20130101); H04W4/02 (20130101)

## Field of Classification Search

**CPC:** H04W (64/006); H04W (4/029); H04W (16/28); H04W (24/10); H04W (64/003); H04W (4/02); H04W (64/00); G01S (1/0428); G01S (5/0226); G01S (5/0236); G01S (5/10); G01S (5/02); H04B (7/0413); H04B (7/0417); H04B (7/0452); H04B (7/0897); H04B (7/0617); H04L (1/02); H04L (1/04); H04L (5/005); H04L (1/06); H04L (5/0007); H04L (5/0048); H04L (5/22)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7542504	12/2008	Chang et al.	N/A	N/A
8000273	12/2010	He et al.	N/A	N/A
8254329	12/2011	Ko et al.	N/A	N/A
8254344	12/2011	Akita et al.	N/A	N/A
8428157	12/2012	Kakura et al.	N/A	N/A
8654727	12/2013	Dai et al.	N/A	N/A
8675752	12/2013	Lahtonen et al.	N/A	N/A
8718001	12/2013	Zhang et al.	N/A	N/A
8750870	12/2013	Palanki et al.	N/A	N/A
8855068	12/2013	Qin et al.	N/A	N/A
9036538	12/2014	Palanki	N/A	N/A
9326283	12/2015	Shin et al.	N/A	N/A

9369250	12/2015	Liu	N/A	N/A
9651653	12/2016	Fischer et al.	N/A	N/A
9755712	12/2016	Bultan et al.	N/A	N/A
9763251	12/2016	Papasakellariou et al.	N/A	N/A
9794039	12/2016	Kwak et al.	N/A	N/A
9814015	12/2016	Xiao et al.	N/A	N/A
9913239	12/2017	Tinnakornsrisuphap et al.	N/A	N/A
10021667	12/2017	Akkarakaran et al.	N/A	N/A
10171210	12/2018	Gong et al.	N/A	N/A
10333670	12/2018	Rico Alvarino et al.	N/A	N/A
10716084	12/2019	Wang et al.	N/A	N/A
10736074	12/2019	Edge et al.	N/A	N/A
11082183	12/2020	Bao et al.	N/A	N/A
11239967	12/2021	Manolakos	N/A	N/A
11290229	12/2021	Chuang et al.	N/A	N/A
11350437	12/2021	Xiong et al.	N/A	N/A
11496265	12/2021	Bao	N/A	N/A
11496990	12/2021	Edge et al.	N/A	N/A
11777764	12/2022	Sun et al.	N/A	N/A
2003/0215035	12/2002	Amerga et al.	N/A	N/A
2005/0271012	12/2004	Agrawal et al.	N/A	N/A
2006/0128416	12/2005	Linebarger et al.	N/A	N/A
2007/0002813	12/2006	Tenny et al.	N/A	N/A
2010/0130230	12/2009	Aggarwal et al.	N/A	N/A
2011/0003551	12/2010	Kameno et al.	N/A	N/A
2012/0021758	12/2011	Gum et al.	N/A	N/A
2012/0231809	12/2011	Siomina et al.	N/A	N/A
2012/0252487	12/2011	Siomina et al.	N/A	N/A
2012/0287882	12/2011	Kim et al.	N/A	N/A
2013/0029669	12/2012	Boudreau et al.	N/A	N/A
2013/0165052	12/2012	Chuang	N/A	N/A
2013/0265962	12/2012	Ouchi et al.	N/A	N/A
2013/0324154	12/2012	Raghupathy et al.	N/A	N/A
2014/0073356	12/2013	Siomina et al.	N/A	N/A
2014/0349582	12/2013	Xiao et al.	N/A	N/A
2015/0018010	12/2014	Fischer	N/A	N/A
2015/0063228	12/2014	Aldana	N/A	N/A
2015/0118678	12/2014	Mandecki et al.	N/A	N/A
2015/0124673	12/2014	Ouchi et al.	N/A	N/A
2015/0133173	12/2014	Edge	455/456.6	G01S 5/08
2015/0188678	12/2014	Wu et al.	N/A	N/A
2015/0263837	12/2014	Patel et al.	N/A	N/A
2015/0289311	12/2014	Chang et al.	N/A	N/A
2015/0382205	12/2014	Lee et al.	N/A	N/A
2016/0065342	12/2015	Mirbagheri et al.	N/A	N/A
2016/0094326	12/2015	Moon et al.	N/A	N/A
2016/0095105	12/2015	Chen et al.	N/A	N/A
2016/0165458	12/2015	Peng et al.	N/A	N/A
2016/0192385	12/2015	Tooher et al.	N/A	N/A

2016/0226647	12/2015	Wang et al.	N/A	N/A
2017/0026794	12/2016	Baker et al.	N/A	N/A
2017/0104517	12/2016	Kakishima	N/A	H04B 7/0617
2017/0111880	12/2016	Park et al.	N/A	N/A
2017/0164315	12/2016	Smith	N/A	N/A
2017/0180194	12/2016	Noh et al.	N/A	N/A
2017/0201960	12/2016	Park et al.	N/A	N/A
2017/0238298	12/2016	Wang et al.	N/A	N/A
2017/0251497	12/2016	Larsson et al.	N/A	N/A
2017/0288830	12/2016	Fischer	N/A	N/A
2017/0324455	12/2016	Soriaga et al.	N/A	N/A
2018/0006787	12/2017	Chen et al.	N/A	N/A
2018/0020423	12/2017	Wang et al.	N/A	N/A
2018/0049151	12/2017	Yoon et al.	N/A	N/A
2018/0097596	12/2017	Palanivelu et al.	N/A	N/A
2018/0098314	12/2017	Rico Alvarino et al.	N/A	N/A
2018/0124787	12/2017	Wang et al.	N/A	N/A
2018/0192404	12/2017	Maaref et al.	N/A	N/A
2018/0198509	12/2017	Nilsson et al.	N/A	N/A
2018/0217228	12/2017	Edge et al.	N/A	N/A
2018/0287682	12/2017	Kwak et al.	N/A	N/A
2018/0295590	12/2017	Abedini et al.	N/A	N/A
2018/0324771	12/2017	Hosseini et al.	N/A	N/A
2018/0375710	12/2017	Chae	N/A	N/A
2019/0007152	12/2018	Yi et al.	N/A	N/A
2019/0013909	12/2018	Li et al.	N/A	N/A
2019/0020454	12/2018	Kim et al.	N/A	N/A
2019/0052443	12/2018	Cheng et al.	N/A	N/A
2019/0053287	12/2018	Lin et al.	N/A	N/A
2019/0068315	12/2018	Ryden et al.	N/A	N/A
2019/0068346	12/2018	Akkarakaran et al.	N/A	N/A
2019/0081660	12/2018	Han et al.	N/A	N/A
2019/0159182	12/2018	Ranta-Aho et al.	N/A	N/A
2019/0165913	12/2018	He et al.	N/A	N/A
2019/0166514	12/2018	Liu	N/A	N/A
2019/0174440	12/2018	Kwak et al.	N/A	N/A
2019/0174454	12/2018	Priyanto et al.	N/A	N/A
2019/0178976	12/2018	Xiong et al.	N/A	N/A
2019/0182899	12/2018	Ye et al.	N/A	N/A
2019/0190669	12/2018	Park et al.	N/A	N/A
2019/0273587	12/2018	Takeda et al.	N/A	N/A
2019/0285722	12/2018	Markhovsky et al.	N/A	N/A
2019/0349898	12/2018	Fu et al.	N/A	N/A
2020/0036556	12/2019	Wei et al.	N/A	N/A
2020/0091608	12/2019	Alpman et al.	N/A	N/A
2020/0213161	12/2019	Zhang et al.	N/A	N/A
2020/0220676	12/2019	Xu et al.	N/A	N/A
2020/0235877	12/2019	Manolakos et al.	N/A	N/A
2020/0267718	12/2019	Park et al.	N/A	N/A

2020/0275416	12/2019	Haghighat et al.	N/A	N/A
2020/0288482	12/2019	Yi et al.	N/A	N/A
2020/0296716	12/2019	Lin et al.	N/A	N/A
2020/0313732	12/2019	Yang et al.	N/A	N/A
2020/0336264	12/2019	Faxer et al.	N/A	N/A
2020/0351818	12/2019	Park et al.	N/A	N/A
2021/0006372	12/2020	Cha et al.	N/A	N/A
2021/0021447	12/2020	Sun	N/A	N/A
2021/0036825	12/2020	Choi et al.	N/A	N/A
2021/0070451	12/2020	Manolakos et al.	N/A	N/A
2021/0105812	12/2020	Rastegardoost et al.	N/A	N/A
2021/0120522	12/2020	Kim et al.	N/A	N/A
2021/0144743	12/2020	Rastegardoost et al.	N/A	N/A
2021/0176687	12/2020	Ko et al.	N/A	N/A
2021/0195620	12/2020	Yoshimura et al.	N/A	N/A
2021/0211957	12/2020	Kamohara et al.	N/A	N/A
2021/0227509	12/2020	Zhang	N/A	N/A
2021/0311158	12/2020	Akkarakaran et al.	N/A	N/A
2021/0351887	12/2020	Qi	N/A	N/A
2022/0095304	12/2021	Muruganathan et al.	N/A	N/A
2022/0132620	12/2021	Yoshimura et al.	N/A	N/A
2022/0377701	12/2021	Edge et al.	N/A	N/A
2023/0080106	12/2022	Ji et al.	N/A	N/A
2024/0113828	12/2023	Manolakos et al.	N/A	N/A
2024/0356700	12/2023	Manolakos et al.	N/A	N/A

#### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102422663	12/2011	CN	N/A
102461292	12/2011	CN	N/A
103004267	12/2012	CN	N/A
103703814	12/2013	CN	N/A
103944685	12/2013	CN	N/A
104488345	12/2014	CN	N/A
104885554	12/2014	CN	N/A
105164930	12/2014	CN	N/A
106105073	12/2015	CN	N/A
106341882	12/2016	CN	N/A
107733549	12/2017	CN	N/A
107733563	12/2017	CN	N/A
2418887	12/2011	EP	N/A
2663144	12/2012	EP	N/A
3041301	12/2015	EP	N/A
3306337	12/2017	EP	N/A
3490319	12/2018	EP	N/A
H07111675	12/1994	JP	N/A
2012523738	12/2011	JP	N/A
2012525724	12/2011	JP	N/A
2014216951	12/2013	JP	N/A

2016508217	12/2015	JP	N/A
2017098960	12/2016	JP	N/A
2020533860	12/2019	JP	N/A
20170030773	12/2016	KR	N/A
201828624	12/2017	TW	N/A
2007022715	12/2006	WO	N/A
2009096319	12/2008	WO	N/A
2010059940	12/2009	WO	N/A
2011085267	12/2010	WO	N/A
2011139201	12/2010	WO	N/A
2013112972	12/2012	WO	N/A
2013134724	12/2012	WO	N/A
2014105324	12/2013	WO	N/A
2014131349	12/2013	WO	N/A
2015027118	12/2014	WO	N/A
2015031031	12/2014	WO	N/A
2015138178	12/2014	WO	N/A
2016036840	12/2015	WO	N/A
2016065368	12/2015	WO	N/A
2016122757	12/2015	WO	N/A
2016155810	12/2015	WO	N/A
2016164085	12/2015	WO	N/A
2017040075	12/2016	WO	N/A
2017048064	12/2016	WO	N/A
2017126907	12/2016	WO	N/A
2017200708	12/2016	WO	N/A
2018013672	12/2017	WO	N/A
2018085145	12/2017	WO	N/A
2018126356	12/2017	WO	N/A
2018127137	12/2017	WO	N/A
2018128401	12/2017	WO	N/A
2019000180	12/2018	WO	N/A
2019047776	12/2018	WO	N/A
2019212246	12/2018	WO	N/A
2020001380	12/2019	WO	N/A
2020145873	12/2019	WO	N/A
2021071570	12/2020	WO	N/A

## OTHER PUBLICATIONS

“3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Physical Layer Procedures for Data (Release 16)”, 3GPP Standard, Technical Specification, 3GPP TS 38.214, 3rd Generation Partnership Project, Mobile Competence Centre, 650, Route Des Lucioles, F-06921, Sophia-Antipolis Cedex, France, vol. RAN WG1, No. V16.0.0, Dec. 2019, Jan. 14, 2020, XP051860777, pp. 1-147. cited by applicant

CATT: “DL Reference Signals for NR Positioning”, 3GPP TSG RAN WG1 #97, R1-1906305, V1.0 Final, 3rd Generation Partnership Project, Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cede, vol. RAN WG1, No. Reno, USA, May 13, 2019-May 17, 2019 May 13, 2019, XP051727755, pp. 1-17. cited by applicant

Ericsson: “DL Reference Signals for NR Positioning”, 3GPP TSG RAN WG1 Meeting #97, R1-1907508, Reno, NV, USA, May 13-17, 2019, 27 Pages. cited by applicant

Ericsson, "DL Reference Signals for NR Positioning", R1-1909424, 3GPP TSG-RAN WG1 Meeting #98, Prague, CZ, Aug. 26-30, 2019 (Year: 2019), 28 Pages. cited by applicant

Ericsson: "Downlink Positioning Solutions: Design and Evaluations", 3GPP TSG RAN WG1 96, R1-1903139 DL Positioning Solutions, 3rd Generation Partnership Project, Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1. No. Athens. Greece, Feb. 25, 2019-Mar. 1, 2019, Feb. 15, 2019, XP051600835, 28 Pages. cited by applicant

Ericsson: "RAT Dependent NR Positioning Solutions", [Online] 3GPP TSG-RAN WG1 #95, R1-1813592, RAT Dependent NR Positioning Solutions, 3rd Generation Partnership Project, Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1. No. Spokane, United States, Nov. 12, 2018-Nov. 16, 2018, Nov. 11, 2018, XP051555648, 17 Pages. cited by applicant

Ericsson: "Uplink Positioning Solutions: Design and Evaluations", 3GPP Draft, 3GPP TSG RAN WG1 #96, R1-1903140 UL Positioning Solutions, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1, No. Athens, Greece, Feb. 25, 2019-Mar. 1, 2019 Feb. 15, 2019 (Feb. 15, 2019), XP051600836, 7 Pages, figure 1 p. 3-p. 4. cited by applicant

ETSI TS 138 211: "5G, NR, Physical Channels and Modulation (3GPP TS 38.211 Version 15.2.0 Release 15)", V15.2.0 (Jul. 2018), 98 Pages, 2018. cited by applicant

ETSI TS 138 211 V16.2.0, "Physical Channels and Modulation", 5G, NR, 3GPP TS 38.211, version 16.2.0, Release 16, Jul. 2020, pp. 1-135. cited by applicant

European Search Report—EP20214356—Search Authority—Munich—Mar. 30, 2021. cited by applicant

European Search Report—EP21178315—Search Authority—Berlin—Nov. 9, 2021. cited by applicant

European Search Report—EP21181854—Search Authority—Munich—Sep. 9, 2021. cited by applicant

European Search Report—EP23151386—Search Authority—Berlin—Mar. 15, 2023. cited by applicant

Fischer S., "Observed Time Difference of Arrival (OTDOA) Positioning in 3GPP LTE", Qualcomm Technologies Inc, Jun. 6, 2014, XP055284784, pp. 1-62, Figures 6-4, Section 6.3 LPP Procedures. cited by applicant

Huawei, et al., "Downlink Based Solutions for NR Positioning", 3GPP TSG RAN WG1 Ad-Hoc Meeting 1901, R1-1900036, 3rd Generation Partnership Project, Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1, No. Taipei, Jan. 21, 2019-Jan. 25, 2019, Jan. 20, 2019, XP051592962, 7 Pages. cited by applicant

Indian Patent Application No. 201941012233, filed Mar. 28, 2019, 102 pages. cited by applicant

Intel Corporation: "Design of Downlink Reference Signals for NR Positioning", 3GPP TSG RAN WG1 Meeting #97, R1-1906821, Reno, USA, May 13-17, 2019, pp. 1-17. cited by applicant

Intel Corporation: "DL Reference Signals for NR Positioning", R1-1908659 Intel—NRPOS DLRS, 3rd Generation Partnership Project, Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1, No. Prague, Czech Republic, Aug. 26, 2019-Aug. 30, 2019, Aug. 17, 2019, XP051765267, 27 pages. cited by applicant

Intel Corporation: "Offline Discussion Outcome on DL Reference Signals for NR", 3GPP TSG RAN WG1 Meeting #96bis, R1-1905847, Xi'an, China, Apr. 8-12, 2019, pp. 1-12. cited by applicant

International Preliminary Report on Patentability—PCT/US2018/039677, The International Bureau of WIPO—Geneva, Switzerland, Feb. 13, 2020. cited by applicant

International Preliminary Report on Patentability—PCT/US2020/014404 The International Bureau of WIPO—Geneva, Switzerland, Jul. 29, 2021. cited by applicant

International Preliminary Report on Patentability—PCT/US2020/024617 The International Bureau of WIPO—Geneva, Switzerland, Oct. 7, 2021. cited by applicant

International Preliminary Report on Patentability—PCT/US2020/026024, The International Bureau of WIPO—Geneva, Switzerland, Nov. 11, 2021. cited by applicant

International Preliminary Report on Patentability—PCT/US2020/048793 The International Bureau of WIPO—Geneva, Switzerland, Mar. 31, 2022. cited by applicant

International Search Report and Written Opinion—PCT/US2017/038723—ISA/EPO—Sep. 29, 2017. cited by applicant

International Search Report and Written Opinion—PCT/US2018/039677—ISA/EPO—Oct. 16, 2018. cited by applicant

International Search Report and Written Opinion—PCT/US2020/014404—ISA/EPO—Apr. 14, 2020. cited by applicant

International Search Report and Written Opinion—PCT/US2020/024617—ISA/EPO—Jun. 24, 2020. cited by applicant

International Search Report and Written Opinion—PCT/US2020/026024—ISA/EPO—Jun. 16, 2020. cited by applicant

International Search Report and Written Opinion—PCT/US2020/048793—ISA/EPO—Mar. 1, 2021. cited by applicant

Keating R., et al., “Overview of Positioning in 5G New Radio”, 2019 16th International Symposium on Wireless Communication Systems, IEEE, Aug. 27, 2019, XP033636268, pp. 320-324, p. 323-p. 324. cited by applicant

LG Electronics: “Discussion on Potential Enhancements for Indoor Positioning”, 3GPP Draft, R1-150229 Discussion on potential enhancements for indoor positioning, 3rd Generation Partnership Project (3GPP), vol. RAN WG1, Athens, Greece; Feb. 8, 2015, pp. 1-4, XP050933443, retrieved from the Internet: URL: [http://www.3gpp.org/ftp/Meetings\\_3GPP\\_SYNC/RAN1/Docs/](http://www.3gpp.org/ftp/Meetings_3GPP_SYNC/RAN1/Docs/). cited by applicant

Media Tek Inc: “Views on Potential Positioning Techniques”, R1-1812373, 3GPP TSG-RAN WG1 Meeting #95, Spokane, USA, Nov. 12-Nov. 16, 2018, Date of Publication: Nov. 3, 2018, 6 Pages, [http://www.3gpp.Org/Ftp/Tsg\\_ran/WG1\\_RL1/TSGR1\\_95/Docs/R1-1812373.Zip](http://www.3gpp.Org/Ftp/Tsg_ran/WG1_RL1/TSGR1_95/Docs/R1-1812373.Zip). cited by applicant

Mediatek Inc: “On Downlink OTDOA and Angle based Techniques”, 3GPP TSG-RAN WG1 #96 Meeting, R1-1903239, Athens, Greece, Feb. 25-Mar. 1, 2019, 8 Pages. cited by applicant

Mediatek Inc: “On Downlink OTDOA Technique: Potential Reference Signal Design”, 3GPP Draft, 3GPP TSG-RAN WG1 Ad-Hoc Meeting 1901, R1-1900203 On downlink OTDOA Technique\_FINAL, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1, No. Taipei, Taiwan, Jan. 21, 2019-Jan. 25, 2019, Jan. 20, 2019 (Jan. 20, 2019), XP051593127, 6 Pages, Sections 1-5, figures 4-5. cited by applicant

Mediatek Inc: “Reference Signal Design for NR Positioning”, 3GPP Draft, 3GPP TSG-RAN WG1 #96bis Meeting, R1-1904500 DL Rs Design\_Final, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre , 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1. No. Xi'an, China, Apr. 8, 2019-Apr. 12, 2019, Apr. 3, 2019 (Apr. 3, 2019), XP051707240, 24 Pages, Sections 1-4, figures 2e, 2f. cited by applicant

NextNAV: “Synchronization for OTDOA Simulations”, R1-150691, 3GPP TSG RAN WG1 Meeting #80, Athens, Greece, Feb. 9-13, 2015, 3 Pages. cited by applicant

Nokia., et al., “Views on DL and UL Reference Signals for NR Positioning”, 3GPP TSG RAN WG1 #96bis, R1-1905262, 3rd Generation Partnership Project, Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Anti Polis Cedex, France, vol. RAN WG1, No. Xi'an, China, Apr. 8, 2019-Apr. 12, 2019, Apr. 2, 2019, XP051707399, 8 Pages, Sections 1-3, figure 3, The whole document. cited by applicant



Partial International Search Report—PCT/US2020/048793—ISA/EPO—Nov. 24, 2020. cited by applicant

Shin E., et al., “Sounding Reference Signal Measurement in LTE System”, 18th International Conference on Advanced Communication Technology (ICACT), Mar. 3, 2016, pp. 755-758. cited by applicant

Specification of U.S. Appl. No. 62/726,480, filed Sep. 4, 2018, 28 Pages. cited by applicant

Specification of U.S. Appl. No. 62/740,459, filed Oct. 3, 2018, 12 Pages. cited by applicant

Taiwan Search Report—TW109110003—TIPO—Jul. 25, 2023. cited by applicant

VIVO: “Discussion on DL RS for NR Positioning”, R1-1908174, 3GPP TSG RAN WG1 #98, Prague, CZ, Aug. 26-30, 2019, 13 Pages. cited by applicant

White Paper: “An Overview of LTE Positioning”, Feb. 2012, SPIRENT, 16 Pages. cited by applicant

Xinwei: “Discussion on Indoor Positioning Enhancement Aided by EB/FD-MIMO”, R1-154700, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1, No. Beijing, China, Aug. 24, 2015-Aug. 28, 2015, Aug. 14, 2015, XP050993741, 3 Pages. cited by applicant

Sony: “Discussion on OTDOA NR Positioning”, 3GPP TSG RAN WG2 Meeting #104, R2-1817081, Spokane, USA, Nov. 12-16, 2018, 3 pages. cited by applicant

Ericsson: “DL and UL Reference Signals for NR Positioning”, 3GPP TSG RAN WG1 96, R1-1905461, Xi'an, P.R. China, Apr. 8, 2019-Apr. 12, 2019, Apr. 3, 2019, pp. 1-15. cited by applicant

U.S. Appl. No. 62/740,459, inventor Chiao-Yao; Chuang, filed Oct. 3, 2018. cited by applicant

Taiwan Search Report—TW107123552—TIPO—Dec. 22, 2021. cited by applicant

Taiwan Search Report—TW109102041—TIPO—Mar. 7, 2023. cited by applicant

Ericsson: “DFT size for Uplink Transmissions”, 3GPP TSG-RAN WG1 #47, R1-063127, Riga, Latvia, Nov. 6, 2006-Nov. 10, 2006, 2 Pages, Nov. 1, 2006. cited by applicant

VIVO: “Views on NR Downlink Positioning Techniques”, 3GPP TSG RAN WG1 Ad-Hoc Meeting 1901, R1-1900149, Taipei, Jan. 21-25, 2019, 6 Pages. cited by applicant

---

*Primary Examiner:* Casca; Fred A

*Attorney, Agent or Firm:* QUALCOMM Incorporated

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 17/743,431, filed May 12, 2022, entitled “SYSTEMS AND METHODS TO FACILITATE LOCATION DETERMINATION BY BEAMFORMING OF A POSITIONING REFERENCE SIGNAL,” which is a continuation of U.S. patent application Ser. No. 16/782,119, now U.S. Pat. No. 11,496,990, filed Feb. 5, 2020, entitled “SYSTEMS AND METHODS TO FACILITATE LOCATION DETERMINATION BY BEAMFORMING OF A POSITIONING REFERENCE SIGNAL,” which is a continuation of U.S. application Ser. No. 15/866,538, now U.S. Pat. No. 10,736,074, filed Jan. 10, 2018, entitled “SYSTEMS AND METHODS TO FACILITATE LOCATION DETERMINATION BY BEAMFORMING OF A POSITIONING REFERENCE SIGNAL,” which claims the benefit of U.S. Provisional Application No. 62/538,952, filed Jul. 31, 2017, entitled “SYSTEMS AND METHODS TO FACILITATE LOCATION DETERMINATION BY BEAMFORMING OF A POSITIONING REFERENCE SIGNAL,” each of which is assigned to the assignee hereof and of which the entire contents are hereby incorporated herein by reference for all purposes.

## BACKGROUND

(1) Obtaining the location or position of a mobile device that is accessing a wireless network may be useful for many applications including, for example, emergency calls, personal navigation, asset tracking, locating a friend or family member, etc. Existing position methods include methods based on measuring radio signals transmitted from a variety of devices including satellite vehicles (SVs) and terrestrial radio sources in a wireless network such as base stations and access points. In methods based on terrestrial radio sources, a mobile device may measure the timing of signals received from two or more base stations and determine times of arrival, time differences of arrival and/or receive time-transmit time differences. Combining these measurements with known locations for the base stations and known transmission times from each base station may enable location of the mobile device using such position methods as Observed Time Difference Of Arrival (OTDOA) or Enhanced Cell ID (ECID).

(2) To further help location determination (e.g. for OTDOA), Positioning Reference Signals (PRS) may be transmitted by base stations in order to increase both measurement accuracy and the number of different base stations for which timing measurements can be obtained by a mobile device. However, location accuracy may be impaired by a number of factors including errors, imprecision in location measurements and multipath effects, where a PRS signal may be reflected, refracted or scattered by intervening obstacles such as trees, walls, buildings and traffic. Methods and techniques to mitigate or overcome such factors may thus be beneficial.

## SUMMARY

(3) An example of a method, at a first base station, for supporting positioning of a mobile device, according to the disclosure includes generating a plurality of directional positioning reference signals (PRSs) for at least one cell for the base station, such that each of the plurality of directional PRSs comprises at least one signal characteristic and a direction of transmission, and transmitting the each of the plurality of directional PRSs within the at least one cell, such that each of the plurality of directional PRSs is transmitted in the direction of transmission.

(4) Implementations of such a method may include one or more of the following features. The at least one signal characteristic may include a frequency, a frequency shift, a code sequence, a muting pattern, a transmission time, or any combination thereof. Transmitting the plurality of directional PRSs within the at least one cell may include directing the plurality of directional PRSs through a controllable antenna array configured to beamform each directional PRS in the direction of transmission. The direction of transmission may include a continuous range of horizontal angles, a continuous range of vertical angles, or a combination thereof. At least one of the plurality of directional PRSs may be detectable by the mobile device to facilitate location determination of the mobile device at a location-capable device based on an observed time difference of arrival (OTDOA) position method, an angle of departure (AOD) position method, or an Enhanced Cell ID (ECID) position method, or any combination thereof. The at least one of the plurality of directional PRSs may be detectable by the mobile device based on the direction of transmission for the at least one of the plurality of directional PRSs, the at least one signal characteristic for the at least one of the plurality of directional PRSs, or a combination thereof. The method may further include sending at least one of the direction of transmission for the at least one of the plurality of directional PRSs or the at least one signal characteristic for the at least one of the plurality of directional PRSs to the mobile device. The sending may be based on broadcast within the at least one cell. The location determination at the location-capable device may include determining a presence or absence of multipath for the least one of the plurality of directional PRSs based on a direction of transmission for the least one of the plurality of directional PRSs and an approximate location for the mobile device, such that determining the location of the mobile device at the location-capable device is based, at least in part, on the determined presence or absence of multipath. The approximate location for the mobile device may be based, at least in part, on a

serving cell for the mobile device. The location-capable device may include a second base station different to the first base station, the mobile device or a Location Management Function (LMF), and such that the method further includes sending the direction of transmission for the at least one of the plurality of directional PRSs to the location-capable device. The at least one cell may be a serving cell for the mobile device. At least one of the at least one signal characteristic and the direction of transmission for each of the plurality of directional PRSs may be unique.

(5) An example of a method, at a mobile device, for supporting positioning of the mobile device, according to the disclosure includes receiving, at the mobile device, a first directional positioning reference signal (PRS) transmitted by a first base station within at least one cell for the first base station, such that the first directional PRS comprises at least one first signal characteristic and a first direction of transmission, obtaining at least one first measurement for the first directional PRS based, at least in part, on the at least one first signal characteristic, and facilitating location determination of the mobile device at a location-capable device based, at least in part, on the at least one first measurement.

(6) Implementations of such a method may include one or more of the following features. The at least one first signal characteristic may include a carrier frequency, a frequency shift, a code sequence, a muting pattern, a bandwidth, a transmission time, or any combination thereof. The first directional PRS may be transmitted from the first base station through a controllable antenna array configured to beamform the first directional PRS in the first direction of transmission. The first direction of transmission may include a continuous range of horizontal angles, a continuous range of vertical angles, or a combination thereof. The method may further include receiving the at least one first signal characteristic for the first directional PRS from the first base station or from a Location Management Function (LMF). The at least one first measurement for the first directional PRS may include a Time Of Arrival (TOA), a Reference Signal Time Difference (RSTD), a Received Signal Strength Indication (RSSI), a Reference Signal Received Power (RSRP), a Reference Signal Received Quality (RSRQ), an Angle of Arrival (AOA), a signal propagation time, a detection of the at least one signal characteristic, or any combination thereof. The location determination of the mobile device at the location-capable device may be based on an observed time difference of arrival (OTDOA) position method, an angle of departure (AOD) position method, or an Enhanced Cell ID (ECID) position method, or any combination thereof. The location determination of the mobile device at the location-capable device may include determining a presence or absence of multipath for the first directional PRS based on the first direction of transmission and an approximate location for the mobile device, such that determining the location of the mobile device at the location-capable device is based, at least in part, on the determined presence or absence of multipath. The approximate location for the mobile device may be based, at least in part, on a serving cell for the mobile device. The location-capable device may include the first base station, or a Location Management Function (LMF), and such that the method further includes sending the at least one first measurement for the first directional PRS to the location-capable device. The method may include receiving, at the mobile device, a second directional PRS transmitted by a second base station within at least one cell for the second base station, such that the second directional PRS comprises at least one second signal characteristic and a second direction of transmission, and such that the at least one second signal characteristic and the second direction of transmission for the second directional PRS are, respectively, different from the at least one first signal characteristic and the first direction of transmission for the first directional PRS, obtaining at least one second measurement for the second directional PRS based, at least in part, on the at least one second signal characteristic for the second directional PRS, and facilitating location determination of the mobile device at the location-capable device based, at least in part, on the at least one first measurement and the at least one second measurement. The at least one cell for the first base station may be a serving cell for the mobile device. At least one of the at least one first signal characteristic and the first direction of transmission for the first directional PRS may be

unique.

(7) An example of a method, at a location-capable device, for supporting positioning of a mobile device, according to the disclosure includes obtaining at least one first measurement from the mobile device for a first directional positioning reference signal (PRS) transmitted by a first base station in at least one cell for the first base station, such that the first directional PRS comprises at least one first signal characteristic and a first direction of transmission, and determining the location of the mobile device based, at least in part, on the at least one first measurement and the first direction of transmission.

(8) Implementations of such a method may include one or more of the following features. The at least one first signal characteristic may include a carrier frequency, a frequency shift, a code sequence, a muting pattern, a bandwidth, a transmission time, or any combination thereof. The first directional PRS may be transmitted from the first base station through a controllable antenna array configured to beamform the first directional PRS in the first direction of transmission. The first direction of transmission may include a continuous range of horizontal angles, a continuous range of vertical angles, or a combination thereof. The location-capable device may include the mobile device, and such that the method further includes receiving the at least one first signal characteristic and the first direction of transmission from the first base station or from a Location Management Function (LMF). The first direction of transmission may be received from the first base station by receiving a broadcast signal from the first base station. The location-capable device may include the first base station, or a Location Management Function (LMF), and such that the method further includes receiving the at least one first measurement from the mobile device. The method may also include sending the at least one first signal characteristic to the mobile device. The at least one first measurement for the first directional PRS may include a Time Of Arrival (TOA), a Reference Signal Time Difference (RSTD), a Received Signal Strength Indication (RSSI), a Reference Signal Received Power (RSRP), a Reference Signal Received Quality (RSRQ), an Angle of Arrival (AOA), a signal propagation time, a detection of the at least one first signal characteristic, or any combination thereof. Determining the location of the mobile device may be based on an observed time difference of arrival (OTDOA) position method, an angle of departure (AOD) position method, or an Enhanced Cell ID (ECID) position method, or any combination thereof. The method may include determining a presence or absence of multipath for the first directional PRS based on the first direction of transmission and an approximate location for the mobile device, such that determining the location of the mobile device is based, at least in part, on the determined presence or absence of multipath. The approximate location for the mobile device may be based, at least in part, on a serving cell for the mobile device. The method may include obtaining at least one second measurement from the mobile device for a second directional PRS transmitted by a second base station in at least one cell for the second base station, such that the second directional PRS comprises at least one second signal characteristic and a second direction of transmission, and such that the at least one second signal characteristic and the second direction of transmission for the second directional PRS are, respectively, different from the at least one first signal characteristic and the first direction of transmission for the first directional PRS, and determining the location of the mobile device based, at least in part, on the at least one first measurement, the at least one second measurement, the first direction of transmission for the first directional PRS and the second direction of transmission for the second directional PRS. The at least one cell for the first base station may be a serving cell for the mobile device. At least one of the at least one first signal characteristic and the first direction of transmission for the first directional PRS may be unique.

(9) Other and further objects, features, aspects, and advantages of the present disclosure will become better understood with the following detailed description of the accompanying drawings.

---

## Description

## BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram of an example communication system.
- (2) FIG. 2 is a diagram of an example configuration of beamformed (directional) positioning reference signals (PRS) transmitted from a base station.
- (3) FIG. 3A is a diagram illustrating an example implementation of using directional (beamformed) PRS signals for location determination functionality.
- (4) FIG. 3B is a diagram illustrating another example implementation of using directional PRS signals to facilitate location determination functionality.
- (5) FIG. 4 is a diagram illustrating mitigation of multipath effects using a directional PRS signal.
- (6) FIG. 5 is a signaling flow diagram showing messages sent between components of a communication network during a location session.
- (7) FIG. 6 is a diagram of a structure of an example LTE subframe sequence with PRS positioning occasions.
- (8) FIG. 7 is a diagram illustrating further aspects of PRS transmission for a cell supported by a wireless node.
- (9) FIG. 8 is a flowchart of an example procedure, generally performed at a network node, to support and facilitate positioning of a mobile device.
- (10) FIG. 9 is a flowchart of an example procedure, generally performed at a mobile device, to facilitate positioning of the mobile device.
- (11) FIG. 10 is a flowchart of an example procedure, generally performed at a location-capable device, to facilitate positioning of a mobile device.
- (12) FIG. 11 is a schematic diagram of an example wireless node (such as a base station, access point, or server).
- (13) FIG. 12 is a schematic diagram of a mobile device (e.g., a UE).
- (14) Like reference symbols in the various drawings indicate like elements, in accordance with certain example implementations. In addition, multiple instances of an element may be indicated by following a first number for the element with a hyphen and a second number or by a letter. For example, multiple instances of an element **110** may be indicated as **110-1**, **110-2**, **110-3** etc. and/or as **110a**, **110b**, **110c** etc. When referring to such an element using only the first number, any instance of the element is to be understood (e.g. elements **110** in the previous example would refer to elements **110-1**, **110-2** and **110-3** and/or to **110a**, **110b** and **110c**).

## DETAILED DESCRIPTION

- (15) Obtaining the location or position of a mobile device that is accessing a wireless network may be useful for many applications including, for example, emergency calls, personal navigation, asset tracking, locating a friend or family member, etc. Existing position methods include methods based on measuring radio signals transmitted from a variety of devices including satellite vehicles (SVs) and terrestrial radio sources in a wireless network such as base stations and access points. In methods based on terrestrial radio sources, a mobile device may measure the timing of signals received from two or more base stations and determine signal strengths, times of arrival, time differences of arrival and/or receive time-transmit time differences. Combining these measurements with known locations for the base stations and possibly known transmission times from each base station may enable location of the mobile device using such position methods as Observed Time Difference Of Arrival (OTDOA) or Enhanced Cell ID (ECID). Such terrestrial based position methods may be employed in wireless networks that support different wireless technologies such as Long Term Evolution (LTE) and Fifth Generation (5G) (also referred to as New Radio (NR)) as defined by an organization known as the Third Generation Partnership Project (3GPP).
- (16) Described herein are systems, devices, methods, media and other implementations for directional positioning reference signals (PRS), also referred to as PRS beamforming. PRS signals are used to support positioning using, for example, the OTDOA position method, and may be

transmitted for different cells in a network at the same set of times or at different sets of times. For example, in the case of LTE access, a PRS may be transmitted during PRS positioning occasions which may occur at fixed periodic intervals, with each positioning occasion comprising one or more consecutive subframes (e.g., LTE subframes of 1 ms duration each). Cells using the same carrier frequency may be synchronized and use PRS positioning occasions that occur at the same set of times. Although this would normally create interference in the case of other signals, a PRS for any cell can be made non-interfering with (e.g. orthogonal to) the PRS for any other nearby cell. This can be achieved using: (i) a different sequence of frequency subcarriers across consecutive OFDM symbols in an LTE subframe (referred to as a frequency shift or vshift), (ii) a different PRS code sequence, (iii) a different muting sequence in which PRS positioning occasions are muted according to a different periodic muting pattern, and/or (iv) different transmission times (e.g. which may be a variant of (iii)).

(17) In the case of LTE or 5G communication technologies, a PRS may also be made non-interfering with (e.g. orthogonal to) another PRS by beamforming, using, for example, an antenna array at a base station (e.g. an eNodeB for LTE or a gNB for 5G). With beamforming, a signal (e.g., a PRS) is broadcast over a narrow continuous range of horizontal and/or vertical directions, e.g., directions with a horizontal span of 5 or 10 degrees (or smaller or larger). Transmitting different signals over a small angular range within a cell may also be referred to as spatial multiplexing. Similar to other approaches used to inhibit or prevent interference of PRS from different cells, a first directional (beamformed) PRS can be made non-interfering with any other second directional PRS transmitted from the same base station by ensuring that the directions in which the first directional PRS is transmitted are all different to the directions in which the second directional PRS is transmitted. When this non-interfering condition is achieved, the direction of transmission for the first directional PRS may be considered as, and may be referred to as being, unique (in the context of transmission from the given base station). In practice, achieving perfect non-interference may be difficult or impossible due to the existence of side lobes and back lobes. Hence, a first directional PRS may be considered to be, and may be referred to as being, transmitted in a unique direction when the signal strength for any second directional PRS transmitted by the same base station is substantially weaker in this particular unique direction (e.g. weaker by at least 10 decibels (dB)).

(18) A directional PRS may have other signal characteristics, in addition to a unique direction of transmission, which allow it to be distinguished from another directional PRS and other non-directional PRS (e.g. transmitted throughout a cell coverage area). These other signal characteristics may include a particular carrier frequency, a particular frequency shift (or vshift), a particular PRS code sequence, a particular muting sequence, a particular bandwidth, and/or a particular set of transmission times. One of more of these signal characteristics may be different to the corresponding signal characteristics for other directional PRS and/or other non-directional PRS transmitted by the same base station and/or by other nearby base stations. When a particular first signal characteristic for a first directional PRS differs from a corresponding second signal characteristic for any other second directional PRS transmitted from the same base station and/or from other nearby base stations, the first signal characteristic may be considered as, and may be referred to as being, unique. When a particular first combination of two or more different signal characteristics for a first directional PRS differ from a second combination of two or more corresponding signal characteristics for any other second directional PRS transmitted from the same base station and/or from other nearby base stations, the first combination of two or more signal characteristics may be considered as, and may be referred to as being, unique.

(19) A unique signal characteristic or a unique combination of signal characteristics may enable a directional PRS to be identified by both a mobile device and a location-capable device such as a location server. For example, a directional PRS may be defined according to its signal characteristics which may include a particular unique signal characteristic or a particular unique combination of signal characteristics and may further be assigned an identifier (ID) such a PRS ID,

a transmission point (TP) ID or physical cell ID (PCI). Such an identifier may also be used to identify a non-directional PRS that is broadcast throughout a cell, which may avoid the need to define and implement different types of identifiers for directional PRS and non-directional PRS. By detecting and measuring a directional PRS that has a given unique signal characteristic or a given unique combination of signal characteristics and a unique identifier, a UE can be both aware of which directional PRS has been measured and can identify the directional PRS to a location-capable device such as a location server using the unique identifier (e.g. when any measurement for the directional PRS is provided by the UE to the location-capable device).

(20) The implementations described herein include a method, at a first base station or other processor-based wireless node, for supporting positioning of a mobile device (e.g. a UE), with the method including generating a plurality of directional PRSs for at least one cell for the first base station, with each of the plurality of directional PRSs comprising at least one signal characteristic and a direction of transmission, and transmitting the each of the plurality of directional PRSs within the at least one cell, with each of the plurality of directional PRSs being transmitted in the direction of transmission. The at least one signal characteristic for a particular directional PRS may be indicative of the respective direction of transmission for that particular directional PRS. The direction of transmission for the particular directional PRS may be a unique or distinctive direction from a continuous range of horizontal angles, a continuous range of vertical angles, or a combination thereof. In some embodiments, the at least one signal characteristic may include one or more of, for example, a frequency shift, a PRS code sequence, a muting pattern, and/or a transmission time. In some embodiments, transmitting the plurality of directional PRSs within the at least one cell may include directing the plurality of directional PRSs through a controllable antenna array configured to beamform each directional PRS in the direction of transmission. At least one of the plurality of directional PRSs may be detectable by the mobile device to facilitate location determination of the mobile device at a location-capable device (which may be one or more of the first base station, another base station, the mobile device, or a Location Management Function (LMF)) based on an observed time difference of arrival (OTDOA) position method, an angle of departure (AOD) position method, or an Enhanced Cell ID (ECID) position method, or any combination thereof.

(21) Also described herein are systems, devices, methods, media, and other implementations to facilitate positioning of a mobile device, including a method comprising receiving, at the mobile device, a first directional PRS transmitted by a first base station within at least one cell for the first base station, with the first directional PRS comprising at least one signal characteristic and a direction of transmission, and obtaining at least one first measurement for the first directional PRS based, at least in part, on the at least one signal characteristic. The method further includes facilitating location determination of the mobile device at a location-capable device based, at least in part, on the at least one first measurement. Also disclosed are methods, systems, media, devices, and other implementations, including a method, at a location-capable device, for supporting positioning of a mobile device, with the method including obtaining at least one first measurement from the mobile device for a first directional PRS transmitted by a first base station in at least one cell for the first base station, where the first directional PRS comprises at least one signal characteristic and a direction of transmission. The method further includes determining the location of the mobile device based, at least in part, on the at least one first measurement and the direction of transmission. The location-capable device may include one or more of, the first base station, another base station, the mobile device, and/or a location server (such as an LMF).

(22) FIG. 1 shows a diagram of a communication system **100**, according to an embodiment. The communication system **100** may be configured to implement directional PRS transmission and reception. Here, the communication system **100** comprises a user equipment (UE) **105**, and components of a Fifth Generation (5G) network comprising a Next Generation (NG) Radio Access Network (RAN) (NG-RAN) **135** and a 5G Core Network (5GC) **140**. A 5G network may also be

referred to as a New Radio (NR) network; NG-RAN **135** may be referred to as a 5G RAN or as an NR RAN; and 5GC **140** may be referred to as an NG Core network (NGC). Standardization of an NG-RAN and 5GC is ongoing in 3GPP. Accordingly, NG-RAN **135** and 5GC **140** may conform to current or future standards for 5G support from 3GPP. The communication system **100** may further utilize information from satellite vehicles (SVs) **190** for a Global Navigation Satellite System (GNSS) like GPS, GLONASS, Galileo or Beidou or some other local or regional Satellite Positioning System (SPS) such as IRNSS, EGNOS or WAAS. Additional components of the communication system **100** are described below. The communication system **100** may include additional or alternative components.

(23) It is noted that FIG. **1** provides only a generalized illustration of various components, any or all of which may be utilized as appropriate, and each of which may be duplicated or omitted as necessary. Specifically, although only one UE **105** is illustrated, it will be understood that many UEs (e.g., hundreds, thousands, millions, etc.) may utilize the communication system **100**. Similarly, the communication system **100** may include a larger (or smaller) number of SVs **190**, gNBs **110**, ng-eNBs **114**, AMFs **115**, external clients **130**, and/or other components. The illustrated connections that connect the various components in the communication system **100** include data and signaling connections which may include additional (intermediary) components, direct or indirect physical and/or wireless connections, and/or additional networks. Furthermore, components may be rearranged, combined, separated, substituted, and/or omitted, depending on desired functionality.

(24) While FIG. **1** illustrates a 5G-based network, similar network implementations and configurations may be used for other communication technologies, such as 3G, Long Term Evolution (LTE), etc. Implementations described herein (be they for 5G technology or for other communication technologies and protocols) may be used to transmit (or broadcast) directional PRSs from base stations (e.g. gNBs **110**, ng-eNBs **114**), receive and measure directional PRSs at UEs (e.g. UE **105**) and compute a location for a UE **105** at a location-capable device such as the UE **105**, a gNB **110** or LMF **120** based on measurements at the UE **105** for directional PRSs.

(25) The UE **105** may comprise and/or may be referred to as a device, a mobile device, a wireless device, a mobile terminal, a terminal, a mobile station (MS), a Secure User Plane Location (SUPL) Enabled Terminal (SET), or by some other name. Moreover, UE **105** may correspond to a cellphone, smartphone, laptop, tablet, PDA, tracking device, navigation device, Internet of Things (IoT) device, or some other portable or moveable device. Typically, though not necessarily, the UE **105** may support wireless communication using one or more Radio Access Technologies (RATs) such as Global System for Mobile communication (GSM), Code Division Multiple Access (CDMA), Wideband CDMA (WCDMA), LTE, High Rate Packet Data (HRPD), IEEE 802.11 Wi-Fi (also referred to as Wi-Fi), Bluetooth® (BT), Worldwide Interoperability for Microwave Access (WiMAX), 5G new radio (NR) (e.g., using the NG-RAN **135** and 5GC **140**), etc. The UE **105** may also support wireless communication using a Wireless Local Area Network (WLAN) which may connect to other networks (e.g. the Internet) using a Digital Subscriber Line (DSL) or packet cable for example. The use of one or more of these RATs may allow the UE **105** to communicate with an external client **130** (e.g. via elements of 5GC **140** not shown in FIG. **1**, or possibly via a Gateway Mobile Location Center (GMLC) **125**) and/or allow the external client **130** to receive location information regarding the UE **105** (e.g., via the GMLC **125**).

(26) The UE **105** may include a single entity or may include multiple entities such as in a personal area network where a user may employ audio, video and/or data I/O devices and/or body sensors and a separate wireline or wireless modem. An estimate of a location of the UE **105** may be referred to as a location, location estimate, location fix, fix, position, position estimate or position fix, and may be geographic, thus providing location coordinates for the UE **105** (e.g., latitude and longitude) which may or may not include an altitude component (e.g., height above sea level, height above or depth below ground level, floor level or basement level). Alternatively, a location



of the UE **105** may be expressed as a civic location (e.g., as a postal address or the designation of some point or small area in a building such as a particular room or floor). A location of the UE **105** may also be expressed as an area or volume (defined either geographically or in civic form) within which the UE **105** is expected to be located with some probability or confidence level (e.g., 67%, 95%, etc.) A location of the UE **105** may further be a relative location comprising, for example, a distance and direction or relative X, Y (and Z) coordinates defined relative to some origin at a known location which may be defined geographically, in civic terms, or by reference to a point, area, or volume indicated on a map, floor plan or building plan. In the description contained herein, the use of the term location may comprise any of these variants unless indicated otherwise. When computing the location of a UE, it is common to solve for local x, y, and possibly z coordinates and then, if needed, convert the local coordinates into absolute ones (e.g. for latitude, longitude and altitude above or below mean sea level).

(27) Base stations (BSs) in the NG-RAN **135** shown in FIG. **1** include NR Node Bs, also referred to as gNBs, **110-1** and **110-2** (collectively and generically referred to herein as gNBs **110**). Pairs of gNBs **110** in NG-RAN **135** may be connected to one another—e.g. directly as shown in FIG. **1** or indirectly via other gNBs **110**. Access to the 5G network is provided to UE **105** via wireless communication between the UE **105** and one or more of the gNBs **110**, which may provide wireless communications access to the 5GC on behalf of the UE **105** using 5G. In FIG. **1**, the serving gNB for UE **105** is assumed to be gNB **110-1**, although other gNBs (e.g. gNB **110-2**) may act as a serving gNB if UE **105** moves to another location or may act as a secondary gNB to provide additional throughput and bandwidth to UE **105**.

(28) Base stations (BSs) in the NG-RAN **135** shown in FIG. **1** may also include a next generation evolved Node B, also referred to as an ng-eNB, **114**. Ng-eNB **114** may be connected to one or more gNBs **110** in NG-RAN **135**—e.g. directly as shown in FIG. **1** or indirectly via other gNBs **110** and/or other ng-eNBs. An ng-eNB **114** may provide LTE wireless access and/or evolved LTE (eLTE) wireless access to UE **105**. Some gNBs **110** (e.g. gNB **110-2**) and/or ng-eNB **114** in FIG. **1** may be configured to function as positioning-only beacons which may transmit signals (e.g. directional PRS) to assist positioning of UE **105** but may not receive signals from UE **105** or from other UEs.

(29) As noted, while FIG. **1** depicts nodes configured to communicate according to 5G communication protocols, nodes configured to communicate according to other communication protocols, such as, for example, an LTE protocol or IEEE 802.11x protocol, may be used. For example, in an Evolved Packet System (EPS) providing LTE wireless access to UE **105**, a RAN may comprise an Evolved Universal Mobile Telecommunications System (UMTS) Terrestrial Radio Access Network (E-UTRAN) which may comprise base stations comprising evolved Node Bs (eNBs). A core network for EPS may comprise an Evolved Packet Core (EPC). An EPS may then comprise an E-UTRAN plus EPC, where the E-UTRAN corresponds to NG-RAN **135** and the EPC corresponds to 5GC **140** in FIG. **1**. The methods and techniques described herein for support of UE **105** positioning using directional PRS may be applicable to such other networks—e.g. for directional PRS transmission from an eNB and/or from a WiFi IEEE 802.11 access point (AP).

(30) The gNBs **110** and ng-eNB **114** can communicate with an Access and Mobility Management Function (AMF) **115**, which, for positioning functionality, communicates with a Location Management Function (LMF) **120**. The AMF **115** may support mobility of the UE **105**, including cell change and handover and may participate in supporting a signaling connection to the UE **105** and possibly data and voice bearers for the UE **105**. The LMF **120** may support positioning of the UE **105** when UE accesses the NG-RAN **135** and may support position procedures/methods such as Assisted GNSS (A-GNSS), Observed Time Difference of Arrival (OTDOA), Real Time Kinematics (RTK), Precise Point Positioning (PPP), Differential GNSS (DGNSS), Enhanced Cell ID (ECID), angle of arrival (AOA), angle of departure (AOD), and/or other position methods. The LMF **120** may also process location services requests for the UE **105**, e.g., received from the AMF

**115** or from the **GMLC 125**. The **LMF 120** may be connected to **AMF 115** and/or to **GMLC 125**. The **LMF 120** may be referred to by other names such as a Location Manager (LM), Location Function (LF), commercial LMF (CLMF) or value added LMF (VLMF). In some embodiments, a node/system that implements the **LMF 120** may additionally or alternatively implement other types of location-support modules, such as an Enhanced Serving Mobile Location Center (E-SMLC) or a Secure User Plane Location (SUPL) Location Platform (SLP). It is noted that in some embodiments, at least part of the positioning functionality (including derivation of a **UE 105**'s location) may be performed at the **UE 105** (e.g., using signal measurements obtained by **UE 105** for signals transmitted by wireless nodes such as **gNBs 110** and **ng-eNB 114**, and assistance data provided to the **UE 105**, e.g. by **LMF 120**).

(31) The Gateway Mobile Location Center (**GMLC 125**) may support a location request for the **UE 105** received from an external client **130** and may forward such a location request to the **AMF 115** for forwarding by the **AMF 115** to the **LMF 120** or may forward the location request directly to the **LMF 120**. A location response from the **LMF 120** (e.g. containing a location estimate for the **UE 105**) may be similarly returned to the **GMLC 125** either directly or via the **AMF 115** and the **GMLC 125** may then return the location response (e.g., containing the location estimate) to the external client **130**. The **GMLC 125** is shown connected to both the **AMF 115** and **LMF 120**, though only one of these connections may be supported by **5GC 140** in some implementations.

(32) As further illustrated in FIG. 1, the **LMF 120** may communicate with the **gNBs 110** and/or **ng-eNB 114** using a New Radio Position Protocol A (which may be referred to as **NPPa** or **NRPPa**), which may be defined in 3GPP Technical Specification (TS) 38.455. **NRPPa** may be the same as, similar to, or an extension of the LTE Positioning Protocol A (**LPPa**) defined in 3GPP TS 36.455, with **NRPPa** messages being transferred between a **gNB 110** and the **LMF 120**, and/or between an **ng-eNB 114** and the **LMF 120**, via the **AMF 115**. As further illustrated in FIG. 1, **LMF 120** and **UE 105** may communicate using an LTE Positioning Protocol (**LPP**), which may be defined in 3GPP TS 36.355. **LMF 120** and **UE 105** may also or instead communicate using a New Radio Positioning Protocol (which may be referred to as **NPP** or **NRPP**), which may be the same as, similar to, or an extension of **LPP**. Here, **LPP** and/or **NPP** messages may be transferred between the **UE 105** and the **LMF 120** via the **AMF 115** and a serving **gNB 110-1** or serving **ng-eNB 114** for **UE 105**. For example, **LPP** and/or **NPP** messages may be transferred between the **LMF 120** and the **AMF 115** using a 5G Location Services Application Protocol (**LCS AP**) and may be transferred between the **AMF 115** and the **UE 105** using a 5G Non-Access Stratum (**NAS**) protocol. The **LPP** and/or **NPP** protocol may be used to support positioning of **UE 105** using UE assisted and/or UE based position methods such as **A-GNSS**, **RTK**, **OTDOA** and/or **ECID**. The **NRPPa** protocol may be used to support positioning of **UE 105** using network based position methods such as **ECID** (e.g. when used with measurements obtained by a **gNB 110** or **ng-eNB 114**) and/or may be used by **LMF 120** to obtain location related information from **gNBs 110** and/or **ng-eNBs 114**, such as parameters defining directional **PRS** transmission from **gNBs 110** and/or **ng-eNB 114**.

(33) With a UE assisted position method, **UE 105** may obtain location measurements and send the measurements to a location server (e.g. **LMF 120**) for computation of a location estimate for **UE 105**. For example, the location measurements may include one or more of a Received Signal Strength Indication (**RSSI**), Round Trip signal propagation Time (**RTT**), Reference Signal Time Difference (**RSTD**), Reference Signal Received Power (**RSRP**) and/or Reference Signal Received Quality (**RSRQ**) for **gNBs 110**, **ng-eNB 114** and/or a **WLAN AP**. The location measurements may also or instead include measurements of **GNSS** pseudorange, code phase and/or carrier phase for **SVs 190**. With a UE based position method, **UE 105** may obtain location measurements (e.g. which may be the same as or similar to location measurements for a UE assisted position method) and may compute a location of **UE 105** (e.g. with the help of assistance data received from a location server such as **LMF 120** or broadcast by **gNBs 110**, **ng-eNB 114** or other base stations or **APs**). With a network based position method, one or more base stations (e.g. **gNBs 110** and/or **ng-eNB**

**114**) or APs may obtain location measurements (e.g. measurements of RSSI, RTT, RSRP, RSRQ or Time Of Arrival (TOA) for signals transmitted by UE **105**) and/or may receive measurements obtained by UE **105**, and may send the measurements to a location server (e.g. LMF **120**) for computation of a location estimate for UE **105**.

(34) Information provided by the gNBs **110** and/or ng-eNB **114** to the LMF **120** using NRPPa may include timing and configuration information for directional PRS transmission and location coordinates. The LMF **120** can then provide some or all of this information to the UE **105** as assistance data in an LPP and/or NPP message via the NG-RAN **135** and the 5GC **140**.

(35) An LPP or NPP message sent from the LMF **120** to the UE **105** may instruct the UE **105** to do any of a variety of things, depending on desired functionality. For example, the LPP or NPP message could contain an instruction for the UE **105** to obtain measurements for GNSS (or A-GNSS), WLAN, and/or OTDOA (or some other position method). In the case of OTDOA, the LPP or NPP message may instruct the UE **105** to obtain one or more measurements (e.g. RSTD measurements) of PRS signals and/or directional PRS signals transmitted within particular cells supported by particular gNBs **110** and/or the ng-eNB **114** (or supported by some other type of base station such as an eNB or WiFi AP). The UE **105** may send the measurements back to the LMF **120** in an LPP or NPP message (e.g. inside a 5G NAS message) via the serving gNB **110-1** (or serving ng-eNB **114**) and the AMF **115**.

(36) As noted, while the communication system **100** is described in relation to 5G technology, the communication system **100** may be implemented to support other communication technologies, such as GSM, WCDMA, LTE, etc., that are used for supporting and interacting with mobile devices such as the UE **105** (e.g., to implement voice, data, positioning, and other functionalities). In some such embodiments, the 5GC **140** may be configured to control different air interfaces. For example, in some embodiments, 5GC **140** may be connected to a WLAN using a Non-3GPP InterWorking Function (N3IWF, not shown FIG. 1) in the 5GC **150**. For example, the WLAN may support IEEE 802.11 WiFi access for UE **105** and may comprise one or more WiFi APs. Here, the N3IWF may connect to the WLAN and to other elements in the 5GC **150** such as AMF **115**. In some other embodiments, both the NG-RAN **135** and the 5GC **140** may be replaced by other RANs and other core networks. For example, in an EPS, the NG-RAN **135** may be replaced by an E-UTRAN containing eNBs and the 5GC **140** may be replaced by an EPC containing a Mobility Management Entity (MME) in place of the AMF **115**, an E-SMLC in place of the LMF **120** and a GMLC that may be similar to the GMLC **125**. In such an EPS, the E-SMLC may use LPPa in place of NRPPa to send and receive location information to and from the eNBs in the E-UTRAN and may use LPP to support positioning of UE **105**. In these other embodiments, positioning of a UE **105** using directional PRSs may be supported in an analogous manner to that described herein for a 5G network with the difference that functions and procedures described herein for gNBs **110**, ng-eNB **114**, AMF **115** and LMF **120** may, in some cases, apply instead to other network elements such as eNBs, WiFi APs, an MME and an E-SMLC.

(37) As noted, in some embodiments, positioning functionality may be implemented, at least in part, using PRS transmissions and/or directional PRS transmissions, sent by base stations (such as the gNBs **110** and/or ng-eNB **114**) that are within range of the UE whose position is to be determined (e.g., the UE **105** of FIG. 1). The UE may, in some instances, use the difference in the arrival times of downlink radio signals (e.g., directional PRS transmissions) from a plurality of base stations (such as gNBs **110**, ng-eNB **114**, etc.) to compute the UE's position. For example, if a signal from one base station is received at a time  $t_{sub.1}$ , and a signal from another base station is received at a time  $t_{sub.2}$ , then the OTDOA or RSTD may be computed according to  $t_{sub.2} - t_{sub.1}$ .

(38) FIG. 2 illustrates an example configuration **200** of directional PRS transmission (or PRS beamforming) at a base station **202** (represented by the small solid circle) that supports three (3) cell sectors A (marked as sector **210**), B (marked as sector **220**), and C (marked as sector **230**). The

base station **202** may be similar to or the same as any of gNBs **110** or ng-eNB **114** in FIG. 1, or may be some other base station (e.g., an eNB) or WiFi AP. Each cell sector (also referred to herein as cell) has a coverage area that, in the example illustration of FIG. 2, is a circle sector with a central angle of 120 degrees. In the example of FIG. 2, within each cell sector, six (6) separate directional PRS signals may be broadcast over (approximately) non-overlapping circle sectors with central angles of 20 degrees each. Other sector configurations and apportionment for directional PRS signals, with beamwidth and beam shape characteristics that may be controlled based on the antenna configuration implemented for the base station **202**, may be realized. The separate directional PRS signals in FIG. 2 are labelled  $A_n$ ,  $B_n$  and  $C_n$  where, in this example,  $1 \leq n \leq 6$ . In order to distinguish the separate directional PRS signals  $A_n$ ,  $B_n$  and  $C_n$  (e.g., so that a UE and/or a location server can determine which directional PRS signal a UE is measuring) and/or to reduce interference, the directional PRS signals can be made orthogonal in various ways as described previously, e.g., by assigning each directional PRS a different (or unique) vshift value, a different (or unique) PRS code sequence, a different (or unique) muting pattern, a different (or unique) set of transmission times, or a different (or unique) combination of two or more of these signal characteristics.

(39) The directional PRSs shown in FIG. 2 each span a continuous range of horizontal angles (or horizontal directions) within each circle sector that have a coverage of 20 degrees in a horizontal plane. Each directional PRS shown in FIG. 2 may also span a continuous but limited range of vertical angles (or vertical directions), such as angles that are angles of elevation ranging from zero degrees (which may coincide with a horizontal direction) to 20 degrees (which may coincide with a direction elevated at 20 degrees to the horizontal). Further, there may be other directional PRS signals, not shown in FIG. 2, that may share the same ranges of horizontal angles shown in FIG. 2 but may have different ranges of vertical angles. As an example, for each directional PRS shown in FIG. 2, there may be one directional PRS (shown in FIG. 2) with angles of elevation between zero and 20 degrees, another directional PRS (not shown in FIG. 2) with angles of elevation between 20 and 40 degrees and a third directional PRS (not shown in FIG. 2) with angles of elevation between 40 and 60 degrees, where each of these directional PRSs has the same range of horizontal angles. In another example, directional PRS signals may not be directional horizontally (e.g. may be transmitted throughout the coverage area of a particular cell) but may have different ranges of vertical angles. Control of directional PRS signals transmitted by an antenna array for base station **202** may be done by, for example, selecting individual antennas (or individual antenna elements) of the base station's **202** antenna array to transmit signals, controlling relative phases and amplitudes of signals directed through the various selected antennas (or antenna elements) of the array, etc.

(40) One convenient way to treat directional PRS signals  $P_n$  in any cell sector  $P$  (e.g., where  $P$  represents in FIG. 2 one of A, B or C) may be to treat each directional PRS signal as corresponding to a different transmitter or different cell, e.g., as if each directional PRS signal  $P_n$  is transmitted by a different antenna such as an antenna associated with a distinct remote radio head for the cell sector  $P$ . A directional PRS signal  $P_n$  could then be assigned a distinct PRS ID associated with a distinct PRS code sequence and/or a distinct vshift for the directional PRS signal  $P_n$ . In some embodiments, a directional PRS signal could be assigned a distinct transmission point ID. For LTE access by a UE **105**, this would allow a location server (e.g. an E-SMLC, SUPL SLP or LMF such as LMF **120**) to provide assistance data to the UE **105** for the directional PRS signals  $P_n$  using existing capability in LPP. The assistance data can make a UE **105** aware of the existence of the directional PRS signals and the signal characteristics and other parameters for each directional PRS signal (e.g., a PRS ID, transmission point ID, carrier frequency, bandwidth, position occasion periodicity and number of subframes, muting pattern, expected RSTD measurement, etc.) and allow the UE **105** to make RSTD measurements for OTDOA positioning. This support may not require any changes to LPP (or NPP) since the location server could treat each directional PRS  $P_n$  the same as a PRS transmitted by a distinct radio head or distinct Distributed Antenna System

(DAS) antenna for the cell sector P (as already supported in LPP).

(41) In some embodiments, two or more different directional PRS signals  $P_n$  may be transmitted at the same time by base station **202** but in a manner that allows any one PRS signal  $P_i$  to be distinguished from any other PRS signal  $P_j$  by a UE **105** (e.g., by using a different frequency, different frequency shift or different PRS code sequence). In another embodiment, one PRS signal may be transmitted by base station **202** in a cell (e.g. cell A, B or C) in different directions at different non-overlapping times, using beamforming. For example, the base station **202** for the cell sector A in FIG. 2 may transmit a directional PRS signal using beamforming in a direction coinciding with directional PRS A1 for a time interval T1, may then change the direction of PRS signal transmission to coincide with directional PRS A2 for a time interval T2, and may subsequently change the direction of directional PRS signal transmission to coincide with directional PRS signals A3, A4, A5 and A6 for time intervals T3, T4, T5 and T6, respectively. If the time intervals T1, T2, . . . T6 are substantially non-overlapping, there may be no ambiguity regarding which directional PRS signal a UE **105** has measured if the time interval during which the directional PRS signal is measured can be obtained and compared with the known transmission intervals T1, T2, . . . Tn. Moreover, the order in which the angle of directional PRS transmission is changed in a cell may be varied, e.g., with the angle (of transmission, relative to some reference point or reference line) changed to correspond to any permutation of the different PRS signals A1, A2, . . . A6. For example, in one embodiment, the base station **202** may change the angle of directional PRS transmission in a cyclic manner (e.g. by transmitting directional PRS signals in the order A1, A2, . . . A6 or in the reverse order) and/or may rotate directional PRS transmission in a circle (e.g. by transmitting directional PRS signals in the order A1, A2, . . . A6, followed by B1, B2, . . . B6 and then by C1, C2, . . . C6). A UE **105** that measures a PRS signal for the cell sector A may determine the time of measurement using timing information included as part of the directional PRS signal or timing information sent separately using another signal transmitted for the cell sector A (e.g. an omnidirectional cell-specific reference signal), or by obtaining the time using timing provided by a different cell S such as the cell sector B or cell sector C in FIG. 2 or a serving cell for the UE **105** if different to cell sectors A, B and C. In the latter case, if the timing difference between cells A and S is known (e.g. due to synchronizing transmission timing of cells A and S using GPS or GNSS or determining the transmission timing of cells A and S relative to GPS or GNSS), the measurement time for a directional PRS signal relative to cell S can be used to determine the measurement time relative to the cell sector A, and thus which directional PRS signal was measured.

(42) There are several ways in which directional PRS signals may be utilized for location determination (e.g., to perform OTDOA positioning) for a UE **105**. In a first example, directional PRS signals may be used to obtain direct information on the location of a UE **105**. For example, if a UE **105** is able to receive and measure directional PRS A5 in FIG. 2, the UE **105** is determined to be within the coverage area of directional PRS A5, and not somewhere else in the coverage area of cell sector A. This may be used to improve the accuracy of UE location.

(43) FIG. 3A shows a diagram **300** illustrating the use of directional (beamformed) PRS signals for location determination functionality. In this example, a UE **105** (not shown) measures or detects, for example, the directional PRS signal marked as PRS A5 in FIG. 2. The UE **105** may also measure/detect another directional PRS signal, namely, the directional PRS D2, transmitted from another cell D with a different antenna location to cell sector A. For example, cell D may be supported by a gNB **110** (or ng-eNB **114**) in FIG. 1, which may be different to a gNB **110** that supports cell sector A. The UE **105** can then be inferred to be within the intersection region **310** of the two directional PRS beams as shown in FIG. 3A. The example in FIG. 3A may be referred to as positioning based on an angle of departure (AOD) position method.

(44) The location determination according to FIG. 3A may be performed at a location-capable device that knows the locations of the base station antennas for cells A and D and the precise

directions of the directional PRSs A5 and D2. For example, the location-capable device may be the base station for cell A, the base station for cell D, the LMF **120** or the UE **105** (e.g. if the UE **105** is provided with the locations of the base station antennas for cells A and D and the precise directions of the directional PRSs by another entity such as a serving base station or the LMF **120**).

(45) FIG. 3B includes a diagram **320** showing another example implementation of using directional PRS signals to facilitate location determination functionality. In the example of FIG. 3B a UE **105** (not shown) measures/detects the PRS A5 of FIG. 2. Here the UE **105** and/or the gNB **110** for cell A (or some other wireless node such as ng-eNB **114**) measures the signal propagation time or round trip signal propagation time (RTT) between the UE **105** and the antenna for cell A. If the RTT has a measured value of  $2T$  plus or minus an uncertainty of  $U$ , the distance between the UE and the antenna for cell A would be given by  $(T \cdot c)$  with an uncertainty of  $(U \cdot c)$  where  $c$  is the speed of light, and assuming line of sight (LOS) transmission. In this example, a determination may be made, based on the identity of the particular directional PRS detected by the UE **105**, and the measured timing information (e.g., RTT), that the UE **105** is located in a region **330** depicted in FIG. 3B. The example in FIG. 3B may be referred to as positioning based on Enhanced Cell ID (ECID).

(46) The location determination according to FIG. 3B may be performed at a location-capable device that knows the location of the base station antenna for cell A, the precise direction of the directional PRS A5 and the measured RTT and its uncertainty. For example, the location-capable device may be the base station for cell A, the LMF **120** or the UE **105** (e.g. if the UE **105** is provided with the location of the base station antenna for cell A, the precise direction of the directional PRS A5 and optionally information to assist RTT determination, by another entity such as the base station for cell A).

(47) In a further example implementation, directional (beamformed) PRS may be used to mitigate error/inaccurate positioning due to measurement of multipath signals. With multipath, a signal transmitted in a cell may undergo reflection, refraction and/or scattering from one or more surfaces, objects (e.g., walls and roofs of buildings) or materials (e.g. water, air) so that the signal received by a UE may not be a line of sight (LOS) signal, but rather some redirection of a signal transmitted from a source that may or may not be in the UE's LOS. This will normally increase the signal propagation time to a UE compared to any LOS signal leading to errors in time-based position methods such as OTDOA.

(48) FIG. 4 includes a diagram **400** illustrating two signals, namely, **S1** (marked as a signal **412**) and **S2** (marked as a signal **414**), reaching a UE **420** in a cell supported by a base station **410**. The UE **420** may be similar to or the same as the UE **105** of FIG. 1. The base station **410** may be similar to or the same as any of the gNBs **110** or ng-eNB **114** of FIG. 1, or to some other base station, such as an eNB supporting LTE communication, or some other node or access point. In the example depicted in FIG. 4, the signal **S1** is a LOS signal directly received from the base station **410**, while the signal **S2** is a multipath signal, also referred to as a non-LOS (NLOS) signal, resulting from reflection of a signal **416** that originated from the base station **410**. Since the multipath (NLOS) signal **S2** does not travel to the UE entirely along a straight line, it would typically initially travel from the cell antenna in a different direction to the signal **S1**, as shown in FIG. 4. Thus, if the cell is using directional PRSs, signals **S1** and **S2** would typically correspond to different directional PRS signals (e.g., if the beam angles are narrow enough). For example, if the cell served by the base station **410** corresponds to the cell A of FIG. 2, and if signal **S1** corresponds to the directional PRS signal A3, signal **S2** might correspond to another directional PRS such as A2 or A4. A location server (or the UE **420**) that knows the approximate location of the UE **420** could therefore direct the UE **420** to measure signal **S1** (e.g., directional PRS A3 in FIG. 2) but not direct the UE **420** to measure signal **S2** (e.g., directional PRS A2 or A4 in FIG. 2) by providing assistance data only for signal **S1**. This would prevent or inhibit the UE **420** from measuring a multipath signal and improve the chance of measuring a LOS signal. Because different directional PRS signals may be

associated, in some embodiments, with different (or unique) signal characteristics (e.g., different PRS IDs, different frequency shifts (vshift), different PRS code sequences, different muting patterns, different transmission times, etc.), the UE **420** may thus be configured to measure a directional PRS signal associated with some particular signal characteristic value (e.g., a particular PRS code sequence or a particular vshift value) or some particular combination of signal characteristic values (e.g. a particular PRS code sequence value and a particular vshift value) that is/are associated with an expected LOS directional PRS signal (such as signal **S1 412** in FIG. **4** or signal **A3** in FIG. **2**). However, UE **420** may not be configured to measure (or may be configured to not measure) a directional PRS signal that is not expected to be LOS (e.g. directional PRS **A2** or **A4** in FIG. **2**) that is associated with some other signal characteristic value or some other combination of signal characteristic values.

(49) In another aspect, UE **105** may have multiple antennas (e.g. an antenna array) that allow UE **105** to selectively receive and measure signals that arrive from certain directions and to filter out and ignore signals that arrive from other directions. A location server (e.g. LMF **120**) may provide UE **105** with the direction of transmission for the LOS signal **S1 412** but may not provide information for the NLOS signal **S2 414/416**. UE **105** may then use the multiple antennas (e.g. antenna array) to receive and measure signals with the same direction of transmission as signal **S1** which may enable UE **105** to measure a TOA or RSTD (or other signal characteristic) for signal **S1**. The use of multiple antennas or an antenna array at UE **105** to tune reception to a particular direction of transmission may reduce interference to signal **S1** from other signals (such as signal **S2**) and may enable improved acquisition of signal **S1** by UE **105** and higher measurement accuracy.

(50) Directional (beamformed) PRS signals may also be used to mitigate multipath effects in situations where a location server (or UE **420**) may not have the approximate location of the UE **420**, or does not provide information to the UE **420** for only LOS signals. In this case, a location server (or the UE **420**) may receive (or obtain) some measurements (e.g. OTDOA RSTD measurements) from the UE **420** for multipath signals (such as the signal **S2 414** in FIG. **4**) as well as measurements (e.g. OTDOA RSTD measurements) for LOS signals (such as the signal **S1 412** in FIG. **4**). The location server (or UE **420**) may obtain an initial position for the UE **420** using all of the measurements provided (or obtained) by the UE **420**. The location server (or UE **420**) can then identify directional PRS signals whose coverage areas do not include the determined location and tentatively identify these signals as multipath signals. The location server (or UE **420**) can then re-determine the UE **420** location using only measurements for signals not identified as multipath signals. The process may be iterated by again identifying directional PRS signals whose coverage areas do not include the new location and treating these as multipath signals. Directional PRS signals initially tentatively identified as multipath signals may no longer need to be identified as multipath signals if the new UE **420** location is now within their coverage areas. Variants of this example procedure can also be used in situations in which the location determination procedure uses directional information as well as RSTD measurements to determine the initial (and any subsequent) UE **420** location.

(51) In another aspect, UE **420** may measure an angle of arrival (AOA) for a directional PRS as well as other characteristics such as a TOA and/or RSTD. If the UE **420** measured AOA is consistent with (e.g. is equal to or approximately equal to) the direction of transmission for the measured directional PRS, the UE **420** or a location-capable device such as an E-SMLC or LMF **120** may assume that the directional PRS measured by UE **420** is LOS (e.g. such as being signal **S1 412** in FIG. **4**). Conversely, if the UE **420** measured AOA is not consistent with (e.g. is not equal to and not approximately equal to) the direction of transmission for the measured directional PRS, the UE **420** or a location-capable device such as an E-SMLC or LMF **120** may assume that the directional PRS measured by UE **420** is NLOS or multipath (e.g. such as being signal **S2 414/416** in FIG. **4**).

(52) The above example embodiments, discussed (in part) in references to FIGS. 3A, 3B, and 4, can be used to improve location determination for a UE **105** for UE assisted OTDOA, when, for example, the UE **105** provides measurements of directional PRSs to a location-capable device such as a gNB **110**, ng-eNB **114** or LMF **120** for determination of the location of UE **105**. The embodiments can also be used to improve location determination for UE based OTDOA for UE **105** when, for example, the network (e.g. a gNB **110** or ng-eNB **114**) or a location server (e.g. the LMF **120**) provides the UE **105** with information on directional PRSs (e.g. directional PRS transmission directions and signal characteristics) as well as base station coordinates and other PRS parameters. For example, for either UE assisted OTDOA or UE based OTDOA, a gNB **110** or an ng-eNB **114** in the communication system **100** of FIG. 1 could broadcast information for directional PRSs transmitted by this gNB **110** or ng-eNB **114** and possibly directional PRSs transmitted by other nearby gNBs **110** and/or ng-eNBs **114**.

(53) FIG. 5, and with further reference to FIG. 1, shows a signaling flow **500** that illustrates the various messages sent between components of a communication network, such as the communication system **100** depicted in FIG. 1, during a location session using LPP and/or NPP (also referred to as an LPP/NPP session) between the UE **105** and a location server corresponding to the LMF **120**. While the signaling flow **500** is discussed, for ease of illustration, in relation to a 5G communication network implementation, similar messaging may be realized for other communication technologies or protocols (such as EPS or WLAN). Furthermore, in some embodiments, the UE **105** itself may be configured to determine its location using, for example, assistance data provided to it (e.g. by LMF **120** or by a serving gNB **110-1**). The positioning protocol used for signaling flow **500** may be LPP, NPP or LPP combined with NPP (e.g. where an LPP message includes an embedded NPP message). Messages for the positioning protocol are accordingly referred to below as LPP/NPP messages to indicate that the messages are for LPP, NPP or LPP combined with NPP. However, other positioning protocols are also possible such as the LPP Extensions (LPPe) protocol defined by the Open Mobile Alliance (OMA).

(54) In some embodiments, a location session for UE **105** can be triggered when the LMF **120** receives a location request for UE **105** at action **501**. Depending on the scenario, the location request may come to the LMF **120** from the AMF **115** or from the GMLC **125** depicted in FIG. 1. The LMF **120** may then query the AMF **115** for information for the UE **105**. The AMF **115** may then send information for the UE **105** to the LMF **120** (not shown in FIG. 5). The information may indicate that UE **105** has 5G (or LTE or eLTE) wireless access (for the example embodiments of FIG. 5), and may provide a current 5G serving cell for UE **105** (e.g. a cell supported by gNB **110-1** which may be a serving gNB for UE **105**) and/or may indicate that the UE **105** supports location using LPP and/or NPP. Some or all of this information may have been obtained by the AMF **115** from UE **105** and/or from the gNB **110-1**, e.g., when the UE **105** attaches to and registers with the 5GC **140**.

(55) To begin the LPP/NPP session (e.g., and based on an indication of UE **105** support for LPP and/or NPP with 5G wireless access), the LMF **120** sends an LPP/NPP Request Capabilities message at action **502** to the AMF **115** serving the UE **105** (e.g. using 5G LCS AP). The AMF **115** may include the LPP/NPP Request Capabilities message within a 5G NAS transport message, at action **503**, which is sent to the UE **105** (e.g., via a NAS communication path in the NG-RAN **135**, as illustrated in FIG. 1). The UE **105** responds to the AMF **115** with an LPP/NPP Provide Capabilities message at action **504**, also within a 5G NAS transport message. The AMF **115** extracts the LPP/NPP Provide Capabilities message from the 5G NAS transport message and relays the LPP/NPP Provide Capabilities message to the LMF **120** (e.g., using 5G LCS AP) at action **505**. Here, the LPP/NPP Provide Capabilities message sent at actions **504** and **505** may indicate the positioning capabilities of the UE **105**, e.g., the position methods and associated assistance data supported by the UE **105** (such as A-GNSS positioning, OTDOA positioning, ECID positioning, WLAN positioning, etc.) while accessing a 5G network. In the case of some position methods (e.g.



OTDOA positioning), the capabilities may indicate if the UE **105** is able to measure, or able to improve measurement for, directional PRS signals. For example, the capabilities may indicate that the UE **105** is able to tune PRS reception to a particular expected direction of arrival for a directional PRS using multiple antennas. However, in an aspect, a UE **105** may acquire and measure a directional PRS in the same way as a non-directional PRS (e.g. a PRS that is transmitted throughout an entire cell coverage area) and may not need to be aware of whether a PRS is a directional PRS or non-directional PRS. In this aspect, the capabilities may not indicate UE support for a directional PRS.

(56) Based on the positioning capabilities of the UE **105** received at action **505** and possibly based on the location request received at action **501** (e.g. a location accuracy requirement included in the location request received at action **501**), the LMF **120** may select one or more position methods to locate UE **105** at action **506**. For example, the LMF may select OTDOA and/or ECID at action **506** in association with directional PRS transmitted from gNBs **110** and/or from ng-eNB **114**.

(57) Based on the position method(s) selected at action **506** and the assistance data indicated by the UE **105** as being supported at action **505**, the LMF **120** may determine assistance data for the UE **105** to support the selected position method(s). LMF **120** may then send an NRPPa Information Request message at action **507**, which may be relayed to the serving node gNB **110-1** by the AMF **115** (at action **508**). The NRPPa Information Request may request location related information for gNB **110-1**, such as the location of gNB **110-1**, PRS configuration parameters for gNB **110-1** and/or information concerning broadcast of assistance data by the gNB **110-1**. The NRPPa Information Request sent at actions **507** and **508** may include a request for configuration parameters related to directional PRSs (e.g. a request for a direction of transmission, a range of horizontal angles, a range of vertical angles and/or other signal characteristics for each directional PRS transmitted by gNB **110-1**). The serving node gNB **110-1** responds with an NRPPa Information Response message, at action **509**, which may be relayed to the LMF **120** by the AMF **115** at action **510**. The NRPPa Information Response may provide some or all of the location related information requested at actions **507** and **508**. For example, when configuration parameters for PRSs and/or directional PRSs are requested at actions **507** and **508**, the NRPPa Information Response may provide signal characteristics and other configuration information for each PRS and/or each directional PRS supported by gNB **110-1**. In the case of a directional PRS, the provided information may include a direction of transmission, a range of horizontal angles, a range of vertical angles and/or other signal characteristics (e.g. a carrier frequency, frequency shift (or vshift), bandwidth, code sequence, periodicity of positioning occasions, duration of a positioning occasion, and/or muting sequence). Actions **507-510** may be repeated by the LMF **120** to obtain location related information (e.g. configuration parameters for directional PRSs) from other gNB **110s** and/or ng-eNBs nearby to UE **105**, such as gNB **110-2** and ng-eNB **114** (not shown in FIG. 5).

(58) In some implementations, serving gNB **110-1**, and/or other gNBs **110** and ng-eNBs such as gNB **110-2** and ng-eNB **114** (not shown in FIG. 5) may broadcast assistance data to UE **105** (and to other UEs) at action **511** and/or may provide assistance data to UE **105** by point to point means, e.g. using a Radio Resource Control Protocol (RRC) for 5G access (not shown in FIG. 5). The broadcast may use System Information Blocks (SIBs) for an RRC protocol in some implementations. The assistance data may include configuration parameters and signal characteristics for PRS signals and/or directional PRS signals that are transmitted by the sending gNB **110** and/or that are transmitted by other nearby gNBs **110** and/or ng-eNB **114**. The configuration parameters and signal characteristics for PRS signals and/or directional PRS signals broadcast by gNB **110-1** (and/or by other gNBs **110** and/or ng-eNB **114**) may be the same as the configuration parameters and signal characteristics for PRS signals and/or directional PRS signals described further down for the location related information sent at actions **512** and **513**. In some embodiments, actions **512** and **513**, as described next, may not occur—e.g. if all location related information can be broadcast to UE by gNB **110-1** and/or by other gNBs **110** and/or ng-eNB **114**.

(59) The LMF **120** may send some or all of the assistance data received at action **510**, and possibly other assistance data already known to the LMF **120**, to the UE **105** via an LPP/NPP Provide Assistance Data message sent to the AMF **115** at action **512**, and relayed to the UE **105** by the AMF **115** in a 5G NAS transport message at action **513**. In the case of OTDOA positioning, the assistance data can include the identities of a reference cell and neighbor cells supported by gNBs **110** and/or by ng-eNB **114** and may include information for each cell, such as the cell carrier frequency, and configuration parameters for each PRS transmitted within the cell. The assistance data may also include configuration parameters and signal characteristics that are associated with different directional PRS signals that can be beamformed by the antenna arrays of gNBs **110** and/or ng-eNB **114**. For example, in such embodiments, the assistance data may include, for each directional PRS transmitted by the reference cell or a neighbor cell, such information as a PRS ID, a transmission point ID, a physical cell ID, a code sequence, a muting pattern, a frequency shift (vshift), a periodicity and duration of positioning occasions etc. The information included in the assistance data sent at actions **512** and **513** for each directional PRS may be the same as information that can be included for a non-directional PRS, in which case the assistance data may not identify a directional PRS or provide any distinct assistance data. However, in an aspect, the assistance data sent by LMF **120** at actions **512** and **513** may include distinct information for a directional PRS, such as an identification of a directional PRS, a direction of transmission, a range of horizontal angles and/or a range of vertical angles. In some implementations, information for directional PRSs such as that just described may be sent by LMF **120** at actions **512** and **513** when the position method(s) selected at action **506** include(s) ECID, OTDOA, and/or other position methods (e.g. AOA, AOD, WLAN) that make use of directional PRS measurements by UE **105**.

(60) The NAS Transport message transmitted at the action **513** can be followed by an LPP/NPP Request Location Information message, again sent from the LMF **120** to AMF **115**, at action **514**, which is relayed to the UE **105** in a 5G NAS transport message by AMF **115** at action **515**. The LPP/NPP Request Location Information message may request one or more location measurements from UE **105** and/or a location estimate according to, for example, the position method(s) selected at action **506** and/or the position capabilities of UE **105** sent to LMF **120** at actions **504** and **505**. The positioning measurements may, for example, include TOA measurements for OTDOA or ECID, RSTD measurements for OTDOA, measurements of an AOA, RTT, RSRP, RSRQ and/or one way signal propagation delay for ECID, etc. Some of the positioning measurements may further be specified or allowed to be measured for directional PRSs—e.g. directional PRSs for which configuration parameters and signal characteristics may have been provided, as previously described for actions **511**, **512** and **513**.

(61) At action **516**, the UE **105** can subsequently obtain some or all of the location measurements (and other information) requested at actions **514** and **515**. The location measurements may be made based, in part, on the directional PRSs transmitted by the serving gNB **110-1** and/or by other nearby gNBs **110** and/or ng-eNB **114**. For example, for OTDOA, the directional PRSs may be transmitted by gNBs **110** and/or ng-eNB **114** within the reference cell and/or neighbor cells. The measurements obtained at action **516** may comprise some or all of the measurements requested at action **515** or implied at action **515** if action **515** requests a location estimate from UE **105**. UE **105** may measure a directional PRS (e.g. for the reference cell or a neighbor cell in the case of OTDOA or for a serving cell or neighbor cell in the case of ECID) based on configuration parameters and signal characteristics provided for the directional PRS in the location related information received at action **511** and/or at action **513**. For example, UE **105** may use one or more of a PRS ID, a transmission point ID, a physical cell ID, a code sequence, a muting pattern, a frequency shift (vshift), a periodicity and duration of positioning occasions for a directional PRS to acquire the directional PRS and measure characteristics such as a AOA, TOA, RSTD, RSSI, RSRP, RSRQ, RTT etc. In some aspects, UE **105** may also or instead use distinct (or unique) information for a directional PRS, if received at action **511** and/or at action **513**, to acquire and measure the

directional PRS. The distinct (or unique) information may include an identification of a directional PRS, a direction of transmission, a range of horizontal angles and/or a range of vertical angles. For example, as described in relation to FIG. 4, in some implementations, the UE 105 may selectively measure directional PRSs that are expected to be LOS and ignore directional PRSs that are expected to be not received or to be NLOS (or multipath). In addition, or instead, UE 105 may use multiple antennas or an antenna array to selectively receive and measure a directional PRS received for a particular direction of transmission and filter out and ignore any signals including directional PRSs received for other directions of transmission.

(62) In some embodiments, at least some of the location measurements obtained at action 516 are provided in an LPP/NPP Provide Location Information message, which is sent from the UE 105 to the AMF 115 in a 5G NAS transport message at action 517. The AMF 115 extracts the LPP/NPP Provide Location Information message from the 5G NAS transport message, and relays it to the LMF 120 (e.g., using 5G LCS AP) at action 518. With this information, the LMF 120 can then determine the UE 105 location at action 519. The LMF 120 may employ one or more of the techniques described in association with FIGS. 3A, 3B and 4 to determine the location of UE 105. For example, when the location measurements returned by UE 105 at actions 517 and 518 include measurements for one or more directional PRSs (e.g. measurements of TOA, RSRP, RSRQ, RSTD, RTT), the LMF 120 may identify a directional PRS for which a measurement was provided using a PRS ID or TP ID (e.g. which may be associated with a particular code sequence and/or frequency shift (vshift)) or a time of measurement (e.g. TOA measurement) and may then use one or more of the techniques described for FIGS. 3A-4 such as ECID, AOA or OTDOA.

(63) Following location determination at action 519, LMF 120 may send the determined location at action 520 to the entity (e.g. GMLC 125 or AMF 115) which sent the location request at action 501.

(64) In some embodiments, UE 105 may determine a location for UE 105 following action 516 (not shown in FIG. 5). The location may be determined by UE 105 as just described for action 519 using techniques described in association with FIGS. 3A-4. The location determination by UE 105 may be based on location related information received by UE 105 at action 511 and/or at actions 512 and 513 including location related information described previously and other information such as the locations of antennas for gNBs 110 and/or ng-eNB 114 and any transmission timing differences for gNBs 110 and/or ng-eNB 114. UE 105 may then return the determined location to LMF 120 at actions 517 and 518 instead of returning location measurements. In this embodiment, action 519 may not occur.

(65) FIG. 6 shows a structure of an example LTE subframe sequence 600 with PRS positioning occasions. Subframe sequence 600 may be applicable to broadcast of PRS and directional PRS from ng-eNB 114 in communication system 100. While FIG. 6 provides an example of a subframe sequence for LTE, similar subframe sequence implementations may be realized for other communication technologies/protocols, such as 5G and NR. For example, a gNB 110 in communication system 100 may broadcast a PRS, a directional PRS or other type of reference signal (RS) or directional RS (e.g. a Tracking Reference Signal (TRS)) that is similar to subframe sequence 600. In FIG. 6, time is represented horizontally (e.g., on an X axis) with time increasing from left to right, while frequency is represented vertically (e.g., on a Y axis) with frequency increasing (or decreasing) from bottom to top. As shown in FIG. 6, downlink and uplink LTE Radio Frames 610 may be of 10 ms duration each. For downlink Frequency Division Duplex (FDD) mode, Radio Frames 610 are organized, in the illustrated embodiments, into ten subframes 612 of 1 ms duration each. Each subframe 612 comprises two slots 614, each of, for example, 0.5 ms duration.

(66) In the frequency domain, the available bandwidth may be divided into uniformly spaced orthogonal subcarriers 616. For example, for a normal length cyclic prefix using, for example, 15 kHz spacing, subcarriers 616 may be grouped into a group of twelve (12) subcarriers. Each grouping, which comprises the 12 subcarriers 616, is termed a resource block and, in the example

above, the number of subcarriers in the resource block may be written as  $N_{\text{sub.SC.sup.RB}}=12$ . For a given channel bandwidth, the number of available resource blocks on each channel **622**, which is also called the transmission bandwidth configuration **622**, is indicated as  $N_{\text{sub.RB.sup.DL}}$ . For example, for a 3 MHz channel bandwidth in the above example, the number of available resource blocks on each channel **622** is given by  $N_{\text{sub.RB.sup.DL}}=15$ .

(67) In the communication system **100** illustrated in FIG. 1, an ng-eNB **114** or a gNB **110**, such as either of the gNBs **110-1**, or **110-2**, may transmit frames, or other physical layer signaling sequences, supporting PRS signals (i.e. a downlink (DL) PRS) according to frame configurations either similar to, or (e.g. in the case of ng-eNB **114**) the same as that, shown in FIG. 6 and (as described later) in FIG. 7, which may be measured and used for UE (e.g., UE **105**) position determination. As noted, other types of wireless nodes and base stations (e.g. an eNB or WiFi AP) may also be configured to transmit PRS signals configured in a manner similar to (or the same as) that depicted in FIGS. 6 and 7. Since transmission of a PRS by a wireless node or base station is directed to all UEs within radio range, a wireless node or base station can also be considered to transmit (or broadcast) a PRS. Further, in some implementations, a directional PRS, as described in relation to FIGS. 1-5, may have a frame configuration similar to or the same as that shown and described for FIGS. 6 and 7.

(68) A PRS, which has been defined in 3GPP LTE Release-9 and later releases, may be transmitted by wireless nodes (e.g. eNBs, ng-eNB **114**) after appropriate configuration (e.g., by an Operations and Maintenance (O&M) server). A PRS may be transmitted in special positioning subframes that are grouped into positioning occasions. For example, in LTE, a PRS positioning occasion can comprise a number  $N_{\text{sub.PRS}}$  of consecutive positioning subframes where the number  $N_{\text{sub.PRS}}$  may be between 1 and 160 (e.g. may include the values 1, 2, 4 and 6 as well as other values). The PRS positioning occasions for a cell supported by a wireless node may occur periodically at intervals, denoted by a number  $T_{\text{sub.PRS}}$ , of millisecond (or subframe) intervals where  $T_{\text{sub.PRS}}$  may equal 5, 10, 20, 40, 80, 160, 320, 640, or 1280 (or any other appropriate value). As an example, FIG. 6 illustrates a periodicity of positioning occasions where  $N_{\text{sub.PRS}}$  equals 4 **618** and  $T_{\text{sub.PRS}}$  is greater than or equal to 20 **620**. In some embodiments,  $T_{\text{sub.PRS}}$  may be measured in terms of the number of subframes between the start of consecutive positioning occasions.

(69) Within each positioning occasion, a PRS may be transmitted with a constant power. A PRS can also be transmitted with zero power (i.e., muted). Muting, which turns off a regularly scheduled PRS transmission, may be useful when PRS signals between different cells overlap by occurring at the same or almost the same time. In this case, the PRS signals from some cells may be muted while PRS signals from other cells are transmitted (e.g. at a constant power). Muting may aid signal acquisition and TOA and RSTD measurement, by UEs (such as the UE **105** depicted in FIGS. 1 and 5 and the UE **420** in FIG. 4), of PRS signals that are not muted (by avoiding interference from PRS signals that have been muted). Muting may be viewed as the non-transmission of a PRS for a given positioning occasion for a particular cell. Muting patterns (also referred to as muting sequences) may be signaled (e.g. using LPP or NPP) to a UE using bit strings. For example, in a bit string signaled to indicate a muting pattern, if a bit at position  $j$  is set to '0', then the UE may infer that the PRS is muted for a  $j_{\text{sup.th}}$  positioning occasion.

(70) To further improve hearability of PRS, positioning subframes may be low-interference subframes that are transmitted without user data channels. As a result, in ideally synchronized networks, PRSs may receive interference from other cell PRSs with the same PRS pattern index (i.e., with the same frequency shift), but not from data transmissions. The frequency shift, in LTE, for example, is defined as a function of a PRS ID for a cell or TP (denoted as  $N_{\text{sub.ID.sup.PRS}}$ ) or as a function of a Physical Cell Identifier (PCI) (denoted as  $N_{\text{sub.ID.sup.cell}}$ ) if no PRS ID is assigned, which results in an effective frequency re-use factor of 6.

(71) To also improve hearability of a PRS (e.g., when PRS bandwidth is limited such as with only 6

resource blocks corresponding to 1.4 MHz bandwidth), the frequency band for consecutive PRS positioning occasions (or consecutive PRS subframes) may be changed in a known and predictable manner via frequency hopping. In addition, a cell supported by a wireless node may support more than one PRS configuration, where each PRS configuration may comprise a distinct frequency offset (vshift), a distinct carrier frequency, a distinct bandwidth, a distinct code sequence, and/or a distinct sequence of PRS positioning occasions with a particular number of subframes (N.sub.PRS) per positioning occasion and a particular periodicity (T.sub.PRS). In some implementation, one or more of the PRS configurations supported in a cell may be for a directional PRS and may then have additional distinct characteristics such as a distinct direction of transmission, a distinct range of horizontal angles and/or a distinct range of vertical angles. Further enhancements of a PRS may also be supported by a wireless node.

(72) As discussed herein (e.g. for actions **511**, **512** and **513** of signaling flow **500**), in some embodiments, OTDOA assistance data may be provided to a UE **105** by a location server (e.g., the LMF **120** of FIG. **1**, an E-SMLC, etc.) for a “reference cell” and one or more “neighbor cells” or “neighboring cells” relative to the “reference cell.” For example, the assistance data may provide the center channel frequency of each cell, various PRS configuration parameters (e.g., N.sub.PRS, T.sub.PRS, muting sequence, frequency hopping sequence, PRS ID, PRS bandwidth), a cell global ID, PRS signal characteristics associated with a directional PRS, and/or other cell related parameters applicable to OTDOA or some other position method (e.g. ECID).

(73) PRS-based positioning by a UE **105** may be facilitated by indicating the serving cell for the UE **105** in the OTDOA assistance data (e.g. with the reference cell indicated as being the serving cell). In the case of a UE **105** with 5G wireless access, the reference cell may be chosen by the LMF **120** as some cell (e.g. supported by a gNB **110**) with good coverage at the expected approximate location of the UE **105** (e.g., as indicated by the known 5G serving cell for the UE **105**).

(74) In some embodiments, OTDOA assistance data may also include “expected RSTD” parameters, which provide the UE **105** with information about the RSTD values the UE **105** is expected to measure at its current location between the reference cell and each neighbor cell, together with an uncertainty of the expected RSTD parameter. The expected RSTD, together with the associated uncertainty, may define a search window for the UE **105** within which the UE **105** is expected to measure the RSTD value. OTDOA assistance information may also include PRS configuration information parameters, which allow a UE **105** to determine when a PRS positioning occasion occurs on signals received from various neighbor cells relative to PRS positioning occasions for the reference cell, and to determine the PRS sequence transmitted from various cells in order to measure a signal Time of Arrival (TOA) or RSTD.

(75) Using the RSTD measurements, the known absolute or relative transmission timing of each cell, and the known position(s) of wireless node physical transmitting antennas for the reference and neighboring cells, the UE **105**'s position may be calculated (e.g., by the UE **105**, by the LMF **120**, or by some other node such as a gNB **110** or ng-eNB **114**). More particularly, the RSTD for a neighbor cell “k” relative to a reference cell “Ref”, may be given as (TOA.sub.k–TOA.sub.Ref), where the TOA values may be measured modulo one subframe duration (1 ms) to remove the effects of measuring different subframes at different times. TOA measurements for different cells may then be converted to RSTD measurements (e.g. as defined in 3GPP TS 36.214 entitled “Physical layer; Measurements”) and sent to the location server (e.g., the LMF **120** or an E-SMLC) by the UE **105**. Using (i) the RSTD measurements, (ii) the known absolute or relative transmission timing of each cell, (iii) the known position(s) of physical transmitting antennas for the reference and neighboring cells, and/or (iv) directional PRS characteristics such as a direction of transmission, the UE **105**'s position may be determined.

(76) FIG. **7** illustrates further aspects of PRS transmission for a cell supported by a wireless node (such as an ng-eNB **114** or a gNB **110**). Again, PRS transmission for LTE is assumed in FIG. **7**

although the same or similar aspects of PRS transmission to those shown in and described for FIG. 7 may apply to 5G, NR and/or other wireless technologies. FIG. 7 shows how PRS positioning occasions are determined by a System Frame Number (SFN), a cell specific subframe offset ( $\Delta_{\text{sub.PRS}}$ ) and the PRS Periodicity ( $T_{\text{sub.PRS}}$ ) **720**. Typically, the cell specific PRS subframe configuration is defined by a “PRS Configuration Index”  $I_{\text{sub.PRS}}$  included in the OTDOA assistance data. The PRS Periodicity ( $T_{\text{sub.PRS}}$ ) **720** and the cell specific subframe offset ( $\Delta_{\text{sub.PRS}}$ ) are defined based on the PRS Configuration Index  $I_{\text{sub.PRS}}$ , in 3GPP TS 36.211 entitled “Physical channels and modulation,” as illustrated in Table 1 below.

(77) TABLE-US-00001 TABLE 1 PRS configuration PRS periodicity  $T_{\text{sub.PRS}}$  PRS subframe offset Index  $I_{\text{sub.PRS}}$  (subframes)  $\Delta_{\text{sub.PRS}}$  (subframes)

0-159	160	$I_{\text{sub.PRS}}$ 160-479	320
$I_{\text{sub.PRS}}$ 160	480-1119	640	$I_{\text{sub.PRS}}$ 480
1120-2399	1280	$I_{\text{sub.PRS}}$ 1120	2400-2404
5	$I_{\text{sub.PRS}}$ 2400	2405-2414	10
$I_{\text{sub.PRS}}$ 2405	2415-2434	20	$I_{\text{sub.PRS}}$ 2415
2435-2474	40	$I_{\text{sub.PRS}}$ 2435	2475-2554
80	$I_{\text{sub.PRS}}$ 2475	2555-4095	Reserved

(78) A PRS configuration is defined with reference to the System Frame Number (SFN) of a cell that transmits PRS. PRS instances, for the first subframe of the  $N_{\text{sub.PRS}}$  downlink subframes comprising a first PRS positioning occasion, may satisfy:

$$(10 \times n_{\text{sub.f}} + \lfloor n_{\text{sub.s}}/2 \rfloor - \Delta_{\text{sub.PRS}}) \bmod T_{\text{sub.PRS}} = 0 \quad (1)$$

where  $n_{\text{sub.f}}$  is the SFN with  $0 \leq n_{\text{sub.f}} \leq 1023$ ,  $n_{\text{sub.s}}$  is the slot number within the radio frame defined by  $n_{\text{sub.f}}$  with  $0 \leq n_{\text{sub.s}} \leq 19$ ,  $T_{\text{sub.PRS}}$  is the PRS periodicity, and  $\Delta_{\text{sub.PRS}}$  is the cell-specific subframe offset.

(79) As shown in FIG. 7, the cell specific subframe offset  $\Delta_{\text{sub.PRS}}$  **752** may be defined in terms of the number of subframes transmitted starting from System Frame Number 0 (Slot ‘Number 0’, marked as slot **750**) to the start of the first (subsequent) PRS positioning occasion. In FIG. 7, the number of consecutive positioning subframes **718** ( $N_{\text{sub.PRS}}$ ) equals 4.

(80) In some embodiments, when a UE **105** receives a PRS configuration index  $I_{\text{sub.PRS}}$  in the OTDOA assistance data for a particular cell, the UE **105** may determine the PRS periodicity  $T_{\text{sub.PRS}}$  and PRS subframe offset  $\Delta_{\text{sub.PRS}}$  using Table 1. The UE **105** may then determine the radio frame, subframe and slot when a PRS is scheduled in the cell (e.g., using equation (1)). The OTDOA assistance data may be determined by, for example, the LMF **120** or an E-SMLC and includes assistance data for a reference cell, and a number of neighbor cells supported by various wireless nodes.

(81) Typically, PRS occasions from all cells in a network that use the same frequency are aligned in time and may have a fixed known time offset relative to other cells in the network that use a different frequency. In SFN-synchronous networks all wireless nodes (e.g. gNBs, ng-eNBs, eNBs, etc.) may be aligned on both frame boundary and system frame number. Therefore, in SFN-synchronous networks all cells supported by the various wireless nodes may use the same PRS configuration index for any particular frequency of PRS transmission. On the other hand, in SFN-asynchronous networks, the various wireless nodes may be aligned on a frame boundary, but not system frame number. Thus, in SFN-asynchronous networks the PRS configuration index for each cell may be configured separately by the network so that PRS occasions align in time.

(82) A UE **105** may determine the timing of the PRS occasions (e.g., in an LTE network or a 5G network such as that in communication system **100**) of the reference and neighbor cells for OTDOA positioning, if the UE **105** can obtain the cell timing (e.g., SFN or Frame Number) of at least one of the cells, e.g., the reference cell or a serving cell (e.g. which may be performed as part of action **516** in FIG. 5). The timing of the other cells may then be derived by the UE **105** based, for example, on the assumption that PRS occasions from different cells overlap.

(83) As defined by 3GPP (e.g., in 3GPP TS 36.211), for LTE systems, the sequence of subframes used to transmit PRS (e.g., for OTDOA positioning) may be characterized and defined by a number of parameters, as described previously, comprising: (i) a reserved block of bandwidth (BW), (ii) the configuration index  $I_{\text{sub.PRS}}$ , (iii) the duration  $N_{\text{sub.PRS}}$ , (iv) an optional muting pattern; and

(v) a muting sequence periodicity  $T_{\text{sub.PRS}}$  which can be implicitly included as part of the muting pattern in (iv) when present. In some cases, with a fairly low PRS duty cycle,  $N_{\text{sub.PRS}}=1$ ,  $T_{\text{sub.PRS}}=160$  subframes (equivalent to 160 ms), and  $BW=1.4, 3, 5, 10, 15$  or 20 MHz. To increase the PRS duty cycle, the  $N_{\text{sub.PRS}}$  value can be increased to six (i.e.,  $N_{\text{sub.PRS}}=6$ ) and the bandwidth (BW) value can be increased to the system bandwidth (i.e.,  $BW=\text{LTE system bandwidth in the case of LTE}$ ). An expanded PRS with a larger  $N_{\text{sub.PRS}}$  (e.g., greater than six) and/or a shorter  $T_{\text{sub.PRS}}$  (e.g., less than 160 ms), up to the full duty cycle (i.e.,  $N_{\text{sub.PRS}}=T_{\text{sub.PRS}}$ ), may also be used in later versions of LPP according to 3GPP TS 36.355. A directional PRS (e.g. as described in association with FIGS. 1-5) may be configured as just described according to 3GPP TSs and may, for example, use a low PRS duty cycle (e.g.  $N_{\text{sub.PRS}}=1$ ,  $T_{\text{sub.PRS}}=160$  subframes) or a high duty cycle.

(84) FIG. 8 shows a flowchart of an example procedure **800**, performed at a first base station, configured to transmit signaling (e.g., according to LTE, NR or 5G protocols), to support and facilitate positioning of a mobile device (e.g. the UE **105** or UE **420**). The procedure **800** may be performed by a base station such as the base station **410** in FIG. 4, the base station **202** in FIG. 2, an eNB for LTE, a gNB for 5G or NR such as a gNB **110** in FIG. 1, or an ng-eNB for 5G such as ng-eNB **114** in FIG. 1. The procedure **800** may also be supported by a positioning only beacon that transmits signals (e.g. NR or LTE signals) but does not receive signals.

(85) The procedure **800** includes generating at block **810** (by the first base station) a plurality of directional positioning reference signals (PRSs) for at least one cell for the first base station, with each of the plurality of directional PRSs comprising at least one signal characteristic and a direction of transmission. The at least one cell may be a serving cell for the mobile device. In an embodiment, at least one of the at least one signal characteristic and the direction of transmission may be unique (e.g. may be different to a corresponding at least one signal characteristic and/or a corresponding direction of transmission, respectively, for any other directional PRS transmitted for the at least one cell, by the first base station or by other nearby base stations).

(86) The procedure **800** further includes transmitting at block **820** each of the plurality of directional PRSs within the at least one cell, wherein each of the plurality of directional PRSs is transmitted in the direction of transmission. The at least one signal characteristic for any directional PRS in the plurality of directional PRSs may indicate the direction of transmission for that directional PRS. For example, the at least one signal characteristic may identify the directional PRS, and may thereby indicate a known direction of transmission for this directional PRS, due to being different to a corresponding at least one signal characteristic for any other directional PRS in the plurality of directional PRSs. Thus, the at least one signal characteristic may be used to reduce or remove, for example, multipath interference, or to otherwise facilitate location determination for the mobile device as described in relation to FIGS. 3A-4.

(87) The at least one signal characteristic may comprise, for example, a frequency (e.g. a carrier frequency), a frequency shift, a code sequence, a muting pattern, a transmission time or set of transmission times, or some combination of these. In some embodiments, transmitting the plurality of directional PRSs at block **820** may include directing the plurality of directional PRSs through a controllable antenna array (of the base station) configured to beamform each directional PRS in the respective direction of transmission. In some embodiments, the direction of transmission (for a particular directional PRS) may include a first angle from a continuous range of horizontal angles, and/or a second angle from a continuous range of vertical angles. In some embodiments, the direction of transmission for a particular directional PRS may comprise a continuous range of horizontal angles, a continuous range of vertical angles, or a combination thereof. In some embodiments, the direction of transmission for a particular directional PRS may be selected from a set of discrete directions of transmission (e.g., represented as an angle or a plurality of angles). The directional PRSs may be transmitted in substantially non-overlapping directions that are each associated with the at least one signal characteristic that allows identification of each directional

PRS (and thus allows determination of the direction of transmission for each directional PRS).

(88) In some embodiments, at least one of the plurality of directional PRSs transmitted at block **820** may be detectable by the mobile device to facilitate location determination of the mobile device at a location-capable device based on an observed time difference of arrival (OTDOA) position method, an angle of departure (AOD) position method, and/or an Enhanced Cell ID (ECID) position method. Other position methods that utilize the transmitted directional PRS signals may also be used. As noted, a location determination operation at a location-capable device may be performed at one or more of, for example, the first base station (transmitting the directional PRS), a second base station different from the first base station, the mobile device, a location server (e.g., an LMF **120**, an SLP or an E-SMLC), and/or other types of devices. In these embodiments, the first base station may send the direction of transmission for the at least one of the plurality of directional PRSs and/or other configuration parameters and signals characteristics for the at least one of the plurality of directional PRSs to the location-capable device—e.g. as at actions **509** and **510** in signaling flow **500** when LMF **120** is the location-capable device or as at action **511** when UE **105** is the location-capable device.

(89) In embodiments where at least one of the plurality of directional PRSs transmitted at block **820** is detectable by the mobile device to facilitate location determination of the mobile device at a location-capable device, the at least one of the plurality of directional PRSs may be detectable by the mobile device based on the direction of transmission for the at least one of the plurality of directional PRSs, the at least one signal characteristic for the at least one of the plurality of directional PRSs, or a combination thereof. For example, the at least one signal characteristic for the at least one of the plurality of directional PRSs may be used by the mobile device to acquire and measure the at least one of the plurality of directional PRSs. For example, the mobile device may integrate the directional PRS signal using coherent or non-coherent integration over a period of time such as the duration of one positioning occasion and may compare or correlate the integrated signal with an expected signal that has the same at least one signal characteristic, which may enable the mobile device to detect and measure the directional PRS. In some of these embodiments, the at least one signal characteristic may comprise a single signal characteristic that is different from a corresponding single signal characteristic for other PRS and/or other directional PRS signals that may be received by the mobile device. Alternatively, in some of these embodiments, the at least one signal characteristic may comprise a combination of two or more signal characteristics that are collectively different from a corresponding combination of two or more signal characteristics for other PRS and/or other directional PRS signals that may be received by the mobile device. In some of these embodiments, the mobile device may use the direction of transmission for the at least one of the plurality of directional PRSs detectable by the mobile device to detect this directional PRS by using multiple antennas or an antenna array to selectively receive only signals transmitted in the direction of transmission for this directional PRS as described in association with FIG. 4.

(90) In some embodiments, the procedure **800** may further comprise sending at least one of the direction of transmission or the at least one signal characteristic for at least one of the plurality of directional PRSs to the mobile device. The sending may be based on broadcast within the at least one cell or on point to point transfer—e.g. as described for action **511** in signaling flow **500** in the case of broadcast.

(91) In embodiments where at least one of the plurality of directional PRSs transmitted at block **820** is detectable by the mobile device to facilitate location determination of the mobile device at a location-capable device, the location determination operation at the location-capable device may include determining a presence or absence of multipath for the at least one of the plurality of directional PRSs based on the associated direction of transmission for the at least one of the plurality of directional PRSs and an approximate location for the mobile device. Here, determining the location of the mobile device at the location-capable device may be based, at least in part, on



the determined presence or absence of multipath. For example, and as described for FIG. 4, when a presence of multipath is determined, determining the location of the mobile device may include disregarding (e.g. ignoring) the at least one of the plurality of directional PRSs transmitted at block **820**. Conversely, and as also described for FIG. 4, when an absence of multipath is determined, determining the location of the mobile device may include using the at least one of the plurality of directional PRSs transmitted at block **820** (e.g. using a measurement obtained by the mobile device for the at least one of the plurality of directional PRSs). The approximate location for the mobile device may be based, at least in part, on a serving cell for the mobile device or on a previous determination of the location of the mobile device. For example, the previous determination may be based, at least in part, on the at least one of the plurality of directional PRSs transmitted at block **820** and detectable by the mobile device (e.g. based on a measurement obtained by the mobile device for the at least one of the plurality of directional PRSs).

(92) FIG. 9 shows a flowchart of an example procedure **900**, generally performed at a mobile device (e.g., a UE such as the UE **105** in FIGS. 1 and 5 or the UE **420** in FIG. 4), for supporting positioning of the mobile device. The procedure **900** includes receiving at block **910**, at the mobile device, a first directional positioning reference signal (PRS) transmitted by a first base station (e.g. a gNB **110**, an ng-eNB **114** or an eNB) within at least one cell for the first base station, with the first directional PRS comprising at least one first signal characteristic and a first direction of transmission. The at least one cell may be a serving cell for the mobile device—e.g. if the first base station is gNB **110-1** in FIG. 1 and the mobile device is UE **105**. As noted, the at least one first signal characteristic may include one or more of, for example, a carrier frequency, a frequency shift (e.g. a vshift), a code sequence (e.g. a PRS code sequence), a muting pattern, a bandwidth, and/or a transmission time (or a set of transmission times). In some embodiments, the first directional PRS is transmitted from the first base station through a controllable antenna array configured to beamform the first directional PRS in the first direction of transmission. As also noted, the first direction of transmission may include (or be defined) by a direction with a continuous range of horizontal angles, and/or a continuous range of vertical angles.

(93) With continued reference to FIG. 9, the procedure **900** further includes obtaining at block **920** at least one first measurement for the first directional PRS based, at least in part, on the at least one first signal characteristic. Block **920** may correspond to action **516** or part of action **516** in signaling flow **500**. The at least one first measurement for the first directional PRS obtained at block **920** may include, for example, a Time Of Arrival (TOA), a Reference Signal Time Difference (RSTD), a Received Signal Strength Indication (RSSI), a Reference Signal Received Power (RSRP), a Reference Signal Received Quality (RSRQ), an Angle of Arrival (AOA), a signal propagation time, a round trip signal propagation time (RTT), a detection of the at least one first signal characteristic, and/or any combination of these. The at least one first signal characteristic for the first directional PRS may be used by the mobile device to acquire and measure the first directional PRS signal at block **920**. For example, the mobile device may integrate the first directional PRS and other received signals using coherent or non-coherent integration over a period of time such as the duration of one PRS positioning occasion and may compare or correlate the integrated signal with an expected signal that has the same at least one first signal characteristic, which may enable the mobile device to detect and measure the first directional PRS. In some embodiments, the at least one first signal characteristic may comprise a single signal characteristic that is different from a corresponding single signal characteristic for other PRS and/or other directional PRS signals that may also be received by the mobile device. In other embodiments, the at least one first signal characteristic may comprise a combination of two or more signal characteristics that are collectively different from a corresponding combination of two or more signal characteristics for other PRS and/or other directional PRS signals that may be received by the mobile device. In some embodiments, the mobile device may use the first direction of transmission for the first directional PRS to acquire and measure the first directional PRS at block

**920** by using multiple antennas or an antenna array to selectively receive only signals transmitted in the first direction of transmission as described in association with FIG. 4. In some embodiments, the at least one first signal characteristic for the first directional PRS may be received by the mobile device (e.g. prior to performing block **920**) from the first base station (e.g. as described for action **511** of signaling flow **500**) or from a location server such as an E-SMLC, SLP or LMF **120** (e.g. as described for actions **512** and **513** of signaling flow **500**).

(94) The procedure **900** further includes facilitating at block **930** location determination of the mobile device at a location-capable device based, at least in part, on the at least one first measurement. The location determination for block **930** may correspond to action **519** in signaling flow **500**. As discussed herein, the location-capable device, where at least some of the location determination operations may be performed, may include one or more of, for example, the mobile device, the first base station, some other base station, and/or a location server (e.g. the LMF **120** of FIG. 1, an E-SMLC, an SLP, etc.) The location determination of the mobile device at the location-capable device may be based on, for example, an observed time difference of arrival (OTDOA) position method, an angle of departure (AOD) position method, an Enhanced Cell ID (ECID) position method, or on some combination of these, and may employ one or more of the techniques described herein in association with FIGS. 3A, 3B and 4. When the location-capable device corresponds to the first base station or a location server (e.g. an E-SMLC, SLP or LMF **120**), facilitating the location determination in block **930** may include sending the at least one first measurement for the first directional PRS to the location-capable device—e.g. as at actions **517** and **518** in signaling flow **500** when the location-capable device is LMF **120**.

(95) In some embodiments, location determination of the mobile device at the location-capable device may include determining a presence or absence of multipath for the first directional PRS based on the first direction of transmission for the first directional PRS and an approximate location for the mobile device. Here, determining the location of the mobile device may be based, at least in part, on the determined presence or absence of multipath. For example, and as described for FIG. 4, when a presence of multipath is determined, determining the location of the mobile device may include disregarding (e.g. ignoring) the at least one first measurement obtained at block **920**. Conversely, and as also described for FIG. 4, when an absence of multipath is determined, determining the location of the mobile device may include using the at least one first measurement obtained at block **920** in the location determination. The approximate location for the mobile device may be based, at least in part, on a serving cell for the mobile device or on a previous determination of the location of the mobile device based, at least in part, on the at least one first measurement.

(96) In some embodiments, location determination of the mobile device may be implemented based on measurements by the mobile device of multiple directional PRS signals. Thus, in such embodiments, the procedure **900** may further include receiving, at the mobile device, a second directional PRS transmitted by a second base station within at least one cell for the second base station, with the second directional PRS including at least one second signal characteristic and a second direction of transmission, and with the at least one second signal characteristic and the second direction of transmission for the second directional PRS being, respectively, different from the at least one first signal characteristic and the first direction of transmission for the first directional PRS. The procedure **900**, in such embodiments, may also include obtaining at least one second measurement for the second directional PRS based, at least in part, on the at least one second signal characteristic for the second directional PRS, and facilitating location determination of the mobile device at the location-capable device based, at least in part, on the at least one first measurement and the at least one second measurement.

(97) In some embodiments of the procedure **900**, at least one of the at least one first signal characteristic and the first direction of transmission may be unique (e.g. may be different to a corresponding signal characteristic and/or corresponding direction of transmission, respectively, for

any other directional PRS transmitted within the at least one cell, by the first base station or by some other nearby base station).

(98) FIG. 10 shows a flowchart of an example procedure **1000**, generally performed at a location-capable device for supporting positioning of a mobile device such as the UE **105** of FIGS. 1 and 5 or the UE **420** of FIG. 4. The procedure **1000** may be performed by the mobile device, by a base station such as an eNB, ng-eNB **114** or a gNB **110**, or by a location server such as an E-SMLC, SLP or the LMF **120**.

(99) The procedure **1000** includes obtaining at block **1010** at least one first measurement from the mobile device for a first directional positioning reference signal (PRS) transmitted by a first base station in at least one cell for the first base station, where the first directional PRS comprises at least one first signal characteristic and a first direction of transmission. The at least one cell may be a serving cell for the mobile device—e.g. if the first base station corresponds to gNB **110-1** and the mobile device corresponds to UE **105**. The at least one first measurement may be obtained at block **1010** directly if the location-capable device is the mobile device, or may be obtained at block **1010** by being received at the location-capable device from the mobile device if the location-capable device is a base station (e.g. the first base station) or a location server (e.g. the LMF **120**). For example, the at least one first measurement may be received from the mobile device in an Radio Resource Control (RRC) message if the location-capable device is a base station or may be received from the mobile device in an LPP, NPP or NRPP message if the location-capable device is a location server (e.g. as described for actions **517** and **518** for signaling flow **500** for a location server corresponding to LMF **120**).

(100) The procedure **1000** further includes determining at block **1020** a location of the mobile device based, at least in part, on the at least one first measurement and the first direction of transmission. In some embodiments where the location-capable device is a location server (e.g. LMF **120**), block **1020** may correspond to action **519** in signaling flow **500**.

(101) As discussed herein, the at least one first signal characteristic may comprise a carrier frequency, a frequency shift (e.g. a vshift), a code sequence (e.g. a PRS code sequence), a muting pattern, a bandwidth, a transmission time (or a set of transmission times), or some combination of these. The first direction of transmission may include a continuous range of horizontal angles, and/or a continuous range of vertical angles. In some embodiments, the first directional PRS may be transmitted from the first base station through a controllable antenna array configured to beamform the first directional PRS in the first direction of transmission. The at least one first measurement for the first directional PRS may include a Time Of Arrival (TOA), a Reference Signal Time Difference (RSTD), a Received Signal Strength Indication (RSSI), a Reference Signal Received Power (RSRP), a Reference Signal Received Quality (RSRQ), an Angle of Arrival (AOA), a signal propagation time, a round trip signal propagation time (RTT), a detection of the at least one first signal characteristic, and/or some combination of these.

(102) In some embodiments, the location-capable device may include the mobile device, and the procedure **1000** may further include, in such embodiments, receiving the at least one first signal characteristic and/or the first direction of transmission from the first base station or from a location server such as an E-SMLC, SLP or an LMF (e.g. LMF **120**). The at least one first signal characteristic and/or the first direction of transmission may be received from the first base station by receiving a broadcast signal from the first base station—e.g. as described for action **511** in signaling flow **500**. The at least one first signal characteristic and/or the first direction of transmission may be received from a location server (e.g. LMF **120**) by receiving an LPP or NPP message from the location server—e.g. as described for actions **512** and **513** in signaling flow **500**.

(103) In some embodiments, the location-capable device may include the first base station or a location server (e.g. an E-SMLC, SLP or the LMF **120**), and, in such embodiments, the procedure **1000** may further include sending the at least one first signal characteristic and/or the first direction of transmission to the mobile device. For example, when the location-capable device includes the

first base station, the at least one first signal characteristic and/or the first direction of transmission may be sent to the mobile station using broadcasting—e.g. as described for action **511** in signaling flow **500**. For example, when the location-capable device includes the location server (e.g. LMF **120**), the at least one first signal characteristic and/or the first direction of transmission may be sent to the mobile device in an LPP or NPP message—e.g. as described for actions **512** and **513** in signaling flow **500**.

(104) In some embodiments, and as described previously herein, the at least one first signal characteristic and/or the first direction of transmission may enable or assist the mobile device to acquire and measure the first directional PRS and to obtain the at least one first measurement of the first directional PRS (e.g. at block **1010** if the mobile device is the location-capable device or prior to block **1010** if the location-capable device includes the first base station or a location server). For example, the mobile device may integrate the first directional PRS and other received signals using coherent or non-coherent integration over a period of time such as the duration of one PRS positioning occasion and may compare or correlate the integrated signal with an expected signal that has the same at least one first signal characteristic, which may enable the mobile device to detect and measure the first directional PRS.

(105) In some embodiments, determining the location of the mobile device at block **1020** may be based on an observed time difference of arrival (OTDOA) position method, an angle of departure (AOD) position method, an Enhanced Cell ID (ECID) position method, or on some combination of these. The procedure **1000** may also include, in such embodiments, determining a presence or absence of multipath for the first directional PRS based on the first direction of transmission and an approximate location for the mobile device, where determining the location of the mobile device is based, at least in part, on the determined presence or absence of multipath. For example, and as described for FIG. 4, when a presence of multipath is determined, determining the location of the mobile device at block **1020** may include disregarding (e.g. ignoring) the at least one first measurement obtained at block **1010**. Conversely, and as also described for FIG. 4, when an absence of multipath is determined, determining the location of the mobile device at block **1020** may include using the at least one first measurement obtained at block **1010** in the location determination at block **1020**. The approximate location for the mobile device may be based, at least in part, on a serving cell for the mobile device or on a previous determination of the location of the mobile device based, at least in part, on the at least one first measurement obtained at block **1010**.

(106) In some embodiments, location determination of the mobile device at block **1020** may be implemented based on measurements by the mobile device of multiple directional PRS signals. Thus, in such embodiments, the procedure **1000** may further include obtaining at least one second measurement from the mobile device for a second directional PRS transmitted by a second base station in at least one cell for the second base station, with the second directional PRS including at least one second signal characteristic and a second direction of transmission, and with the at least one second signal characteristic and the second direction of transmission for the second directional PRS being, respectively, different from the at least one first signal characteristic and the first direction of transmission for the first directional PRS. In such embodiments, the procedure **1000** may also include determining the location of the mobile device based, at least in part, on the at least one first measurement, the at least one second measurement, the first direction of transmission for the first directional PRS and the second direction of transmission for the second directional PRS.

(107) In some embodiments of the procedure **1000**, at least one of the at least one first signal characteristic and the first direction of transmission for the first directional PRS may be unique (e.g. may be different to a corresponding signal characteristic and/or corresponding direction of transmission, respectively, for any other directional PRS transmitted within the at least one cell, by the first base station or by some other nearby base station).

(108) FIG. 11 shows a schematic diagram of an example wireless node **1100**, such as a base station, access point, or server, which may be similar to, and be configured to have a functionality similar

that, of any of the various nodes depicted, for example, in FIGS. 1, 2, 4 and 5 (e.g., the gNBs **110-1** and **110-2**, the ng-eNB **114**, base station **202**, base station **410**, LMF **120**, components of the 5GC **140**), or otherwise discussed herein (e.g. such as an E-SMLC or SLP). The wireless node **1100** may include one or more communication modules **1110a-n**, which may be electrically coupled to one more antennas **1116a-n** for communicating with wireless devices, such as, for example, the UE **105** of FIGS. 1 and 5. Each of the communication modules **1110a-1110n** may include a respective transmitter **1112a-n** for sending signals (e.g., downlink messages, which may be arranged in frames, and may include directional positioning reference signals such as those described herein) and, optionally (e.g., for nodes configured to receive and process uplink communications) a respective receiver **1114a-n**. In embodiments in which the implemented node includes both a transmitter and a receiver, the communication module comprising the transmitter and receiver may be referred to as a transceiver. The node **1100** may also include a network interface **1120** to communicate with other network nodes via wireline means (e.g., by sending and receiving queries and responses). For example, the node **1100** may be configured to communicate (e.g., via wired or wireless backhaul communication) with a gateway, or other suitable device of a network, to facilitate communication with one or more core network nodes (e.g., any of the other nodes and elements shown in FIGS. 1 and 5). Additionally, and/or alternatively, communication with other network nodes may also be performed using the communication modules **1110a-n** and/or the respective antennas **1116a-n**.

(109) The node **1100** may also include other components that may be used with embodiments described herein. For example, the node **1100** may include, in some embodiments, a processor (also referred to as a controller) **1130** to manage communications with other nodes (e.g., sending and receiving messages), to generate communication signals (including to generate directional PRS signals), and to provide other related functionality, including functionality to implement the various processes and methods described herein. Thus, for example, the processor, in combination with other modules/units of the node **1100**, may be configured to cause the node **1100**, when functioning as a base station (e.g. a gNB **110** or ng-eNB **114**), to generate a plurality of directional positioning reference signals (PRSs) for at least one cell for the base station, with each of the plurality of directional PRSs including at least one signal characteristic and a direction of transmission, and transmit the each of the plurality of directional PRSs within the at least one cell, with each of the plurality of directional PRSs being transmitted in the direction of transmission. Similarly, for example, the processor, in combination with other modules/units of the node **1100**, may be configured to cause the node **1110**, when functioning as a location-capable device, to obtain at least one first measurement from a mobile device for a first directional positioning reference signal (PRS) transmitted by a base station in at least one cell for the base station, with the first directional PRS comprising at least one first signal characteristic and a first direction of transmission, and to determine a location of the mobile device based, at least in part, on the at least one first measurement and the first direction of transmission.

(110) The processor **1130** may be coupled to (or otherwise communicate with) a memory **1140**, which may include one or more modules (implemented in hardware or software) to facilitate controlling the operation of the node **1100**. For example, the memory **1140** may include an application module **1146** with computer code for various applications required to perform the operation of the node **1100**. For example, the processor **1130** may be configured (e.g., using code provided via the application module **1146**, or some other module in the memory **1140**) to control the operation of the antennas **1116a-n** so as to adjustably control the antennas' transmission power and phase, gain pattern, antenna direction (e.g., the direction at which a resultant radiation beam from the antennas **1116a-n** propagates), antenna diversity, and other adjustable antenna parameters for the antennas **1116a-n** of the node **1100**. Control of the antennas **1116a-n** of the node **1100**, which together constitute an antenna array for the node **1100**, may allow, for example, directional PRS signals to be beamformed and transmitted in particular directions characterized, in part, by a

direction angle and beamwidth. In some embodiments, the antennas' configuration may be controlled according to pre-stored configuration data provided at the time of manufacture or deployment of the node **1100**, or according to data obtained from a remote device (such as a central server sending data representative of the antenna configuration, and other operational parameters, that are to be used for the node **1100**). The wireless node **1100** may also be configured, in some implementations, to perform location data services, or perform other types of services, for multiple wireless devices (clients) communicating with the wireless node **1100** (or communicating with a server coupled to the wireless node **1100**), and to provide location data and/or assistance data to such multiple wireless devices.

(111) In addition, in some embodiments, the memory **1140** may also include neighbor relations controllers (e.g., neighbor discovery modules) **1142** to manage neighbor relations (e.g., maintaining a neighbor list **1144**) and to provide other related functionality. In some embodiments, the node **1110** may also include one or more sensors (not shown) and other devices (e.g., cameras).

(112) FIG. **12** illustrates a user equipment (UE) **1200** for which various procedures and techniques described herein can be utilized. The UE **1200** may, in implementation and/or functionality, be similar to or the same as any of the other UEs described herein, including the UE **105** depicted in FIGS. **1** and **5** and the UE **420** in FIG. **4**. Furthermore, the implementation illustrated in FIG. **12** may also be used to implement, at least in part, some of the nodes and devices illustrated throughout the present disclosure, including such nodes and devices as base stations (e.g. gNBs **110**, ng-eNB **114**, eNBs, etc.), location servers (e.g. LMF **120**), and other components and devices illustrated in and described for FIGS. **1-10**.

(113) The UE **1200** includes a processor **1211** (or processor core) and memory **1240**. As described herein, the UE **1200** is configured to detect and process directional positioning reference signals (PRS) that are used to facilitate location determination operations. The UE **1200** may optionally include a trusted environment operably connected to the memory **1240** by a public bus **1201** or a private bus (not shown). The UE **1200** may also include a communication interface **1220** and a wireless transceiver **1221** configured to send and receive wireless signals **1223** (which may include LTE or NR frames comprising directional PRS signals) via a wireless antenna **1222** over a wireless network (such as the NG-RAN **135** and 5GC **140** of FIG. **1**). The wireless transceiver **1221** is connected to the bus **1201** via the communication interface **1220**. Here, the UE **1200** is illustrated as having a single wireless transceiver **1221**. However, the UE **1200** can alternatively have multiple wireless transceivers **1221** and/or multiple wireless antennas **1222** to support multiple communication standards such as WiFi, CDMA, Wideband CDMA (WCDMA), Long Term Evolution (LTE), 5G, NR, Bluetooth® short-range wireless communication technology, etc.

(114) The communication interface **1220** and/or wireless transceiver **1221** may support operations on multiple carriers (waveform signals of different frequencies). Multi-carrier transmitters can transmit modulated signals simultaneously on the multiple carriers. Each modulated signal may be a Code Division Multiple Access (CDMA) signal, a Time Division Multiple Access (TDMA) signal, an Orthogonal Frequency Division Multiple Access (OFDMA) signal, a Single-Carrier Frequency Division Multiple Access (SC-FDMA) signal, etc. Each modulated signal may be sent on a different carrier and may carry pilot, control information, overhead information, data, etc.

(115) The UE **1200** may also include a user interface **1250** (e.g., display, keyboard, touchscreen, graphical user interface (GUI)), and a Satellite Positioning System (SPS) receiver **1255** that receives SPS signals **1259** (e.g., from SPS satellites) via an SPS antenna **1258** (which may be the same antenna as wireless antenna **1222** or may be different). The SPS receiver **1255** can communicate with a single global navigation satellite system (GNSS) or multiple such systems. A GNSS can include, but is not limited to, Global Positioning System (GPS), Galileo, Glonass, Beidou (Compass), etc. SPS satellites are also referred to as satellites, space vehicles (SVs), etc. The SPS receiver **1255** measures the SPS signals **1259** and may use the measurements of the SPS signals **1259** to determine the location of the UE **1200**. The processor **1211**, memory **1240**, Digital

Signal Processor (DSP) **1212** and/or specialized processor(s) (not shown) may also be utilized to process the SPS signals **1259**, in whole or in part, and/or to compute (approximately or more precisely) the location of the UE **1200**, in conjunction with SPS receiver **1255**. Alternatively, the UE **1200** may support transfer of the SPS measurements to a location server (e.g., E-SMLC, an LMF, such as the LMF **120** of FIG. **1**, etc.) that computes the UE location instead. Storage of information from the SPS signals **1259** or other location signals is performed using a memory **1240** or registers (not shown). While only one processor **1211**, one DSP **1212** and one memory **1240** are shown in FIG. **12**, more than one of any, a pair, or all of these components could be used by the UE **1200**. The processor **1211** and DSP **1212** associated with the UE **1200** are connected to the bus **1201**.

(116) The memory **1240** can include a non-transitory computer-readable storage medium (or media) that stores functions as one or more instructions or code. Media that can make up the memory **1240** include, but are not limited to, RAM, ROM, FLASH, disc drives, etc. In general, the functions stored by the memory **1240** are executed by general-purpose processor(s), such as the processor **1211**, specialized processors, such as the DSP **1212**, etc. Thus, the memory **1240** is a processor-readable memory and/or a computer-readable memory that stores software (programming code, instructions, etc.) configured to cause the processor(s) **1211** and/or DSP(s) **1212** to perform the functions described. Alternatively, one or more functions of the UE **1200** may be performed in whole or in part in hardware.

(117) A UE **1200** can estimate its current position within an associated system using various techniques, based on other communication entities within view and/or information available to the UE **1200**. For instance, the UE **1200** can estimate its position using information obtained from base stations (e.g. gNBs, ng-eNBs), access points (APs) associated with one or more wireless local area networks (WLANs), personal area networks (PANs) utilizing a short-range wireless communication technology such as Bluetooth® wireless technology or ZIGBEE®, etc., Global Navigation Satellite System (GNSS) or other Satellite Positioning System (SPS) satellites, and/or map data obtained from a map server or other server (e.g., an LMF, an E-SMLC or SLP). In some cases, a location server, which may be an E-SMLC, SLP, Standalone Serving Mobile Location Center (SAS), or an LMF, etc., may provide assistance data to the UE **1200** to allow or assist the UE **1200** to acquire signals (e.g. signals from WLAN APs, signals from cellular base stations (including directional PRS signals), GNSS satellites, etc.) and make location related measurements using these signals. The UE **1200** may then provide the measurements to the location server to compute a location estimate (which may be known as “UE assisted” positioning) or may compute a location estimate itself (which may be known as “UE based” positioning) based on the measurements and possibly based also on other assistance data provided by the location server (e.g. such as orbital and timing data for GNSS satellites, configuration parameters for the directional PRS signals, the precise location coordinates of WLAN APs and/or cellular base stations for use in OTDOA, AOD and/or ECID positioning, etc.)

(118) In one embodiment, the UE **1200** may include a camera **1230** (e.g., front and/or back facing) such as, for example, complementary metal-oxide-semiconductor (CMOS) image sensors with appropriate lens configurations. Other imaging technologies such as charge-coupled devices (CCD) and back side illuminated CMOS may be used. The camera **1230** may be configured to obtain and provide image information to assist in positioning of the UE **1200**. In an example, one or more external image processing servers (e.g. remote servers) may be used to perform image recognition and provide location estimation processes. The UE **1200** may include other sensors **1235** which may also be used to compute, or used to assist in computing, a location for the UE **1200**. The other sensors **1235** may include inertial sensors (e.g. accelerometers, gyroscopes, magnetometers, a compass, any of which may be implemented based on micro-electro-mechanical-system (MEMS), or based on some other technology), as well as a barometer, thermometer, hygrometer and other sensors.

(119) As noted, in some embodiments the UE **1200** may be configured to receive (e.g., via the wireless transceiver **1221**), a first directional positioning reference signal (PRS) transmitted by a first base station within at least one cell for the first base station, with the first directional PRS comprising at least one signal characteristic and a direction of transmission. In such embodiments, the UE **1200** may further be configured to obtain at least one first measurement for the first directional PRS based, at least in part, on the at least one signal characteristic, and to facilitate location determination of the UE **1200** at a location-capable device (which may include the UE **1200**, and/or may further include the first base station, some other base station, a remote location server, etc.) based, at least in part, on the at least one first measurement.

(120) Substantial variations may be made in accordance with specific desires. For example, customized hardware might also be used, and/or particular elements might be implemented in hardware, software (including portable software, such as applets, etc.), or both. Further, connection to other computing devices such as network input/output devices may be employed.

(121) Configurations may be described as a process which is depicted as a flow diagram or block diagram. Although each may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process may have additional steps not included in the figure. Furthermore, examples of the methods may be implemented by hardware, software, firmware, middleware, microcode, hardware description languages, or any combination thereof. When implemented in software, firmware, middleware, or microcode, the program code or code segments to perform the necessary tasks may be stored in a non-transitory computer-readable medium such as a storage medium. Processors may perform the described tasks.

(122) Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly or conventionally understood. As used herein, the articles “a” and “an” refer to one or to more than one (i.e., to at least one) of the grammatical object of the article. By way of example, “an element” means one element or more than one element. “About” and/or “approximately” as used herein when referring to a measurable value such as an amount, a temporal duration, and the like, encompasses variations of  $\pm 20\%$  or  $\pm 10\%$ ,  $\pm 5\%$ , or  $\pm 0.1\%$  from the specified value, as such variations are appropriate in the context of the systems, devices, circuits, methods, and other implementations described herein. “Substantially” as used herein when referring to a measurable value such as an amount, a temporal duration, a physical attribute (such as frequency), and the like, also encompasses variations of  $\pm 20\%$  or  $\pm 10\%$ ,  $\pm 5\%$ , or  $\pm 0.1\%$  from the specified value, as such variations are appropriate in the context of the systems, devices, circuits, methods, and other implementations described herein.

(123) As used herein, including in the claims, “or” as used in a list of items prefaced by “at least one of” or “one or more of” indicates a disjunctive list such that, for example, a list of “at least one of A, B, or C” means A or B or C or AB or AC or BC or ABC (i.e., A and B and C), or combinations with more than one feature (e.g., AA, AAB, ABBC, etc.). Also, as used herein, unless otherwise stated, a statement that a function or operation is “based on” an item or condition means that the function or operation is based on the stated item or condition and may be based on one or more items and/or conditions in addition to the stated item or condition.

(124) As used herein, a mobile device or station (MS) refers to a device such as a cellular or other wireless communication device, a smartphone, tablet, personal communication system (PCS) device, personal navigation device (PND), Personal Information Manager (PIM), Personal Digital Assistant (PDA), laptop or other suitable mobile device which is capable of receiving wireless communication and/or navigation signals, such as navigation positioning signals. The term “mobile station” (or “mobile device” or “wireless device”) is also intended to include devices which communicate with a personal navigation device (PND), such as by short-range wireless, infrared, wireline connection, or other connection—regardless of whether satellite signal reception, assistance data reception, and/or position-related processing occurs at the device or at the PND.



Also, “mobile station” is intended to include all devices, including wireless communication devices, computers, laptops, tablet devices, etc., which are capable of communication with a server, such as via the Internet, WiFi, or other network, and to communicate with one or more types of nodes, regardless of whether satellite signal reception, assistance data reception, and/or position-related processing occurs at the device, at a server, or at another device or node associated with the network. Any operable combination of the above are also considered a “mobile station.” A mobile device may also be referred to as a mobile terminal, a terminal, a user equipment (UE), a device, a Secure User Plane Location Enabled Terminal (SET), a target device, a target, or by some other name.

(125) While some of the techniques, processes, and/or implementations presented herein may comply with all or part of one or more standards, such techniques, processes, and/or implementations may not, in some embodiments, comply with part or all of such one or more standards.

(126) Although particular embodiments have been disclosed herein in detail, this has been done by way of example for purposes of illustration only, and is not intended to be limiting with respect to the scope of the appended claims, which follow. In particular, it is contemplated that various substitutions, alterations, and modifications may be made without departing from the spirit and scope of the invention as defined by the claims. Other aspects, advantages, and modifications are considered to be within the scope of the following claims. The claims presented are representative of the embodiments and features disclosed herein. Other unclaimed embodiments and features are also contemplated. Accordingly, other embodiments are within the scope of the following claims.

## Claims

1. A first base station, for supporting positioning of a mobile device, comprising: a memory; a transmitter; and at least one processor operably coupled to the memory and the transmitter and configured to: obtain at least one first signal characteristic of a first directional positioning reference signal (PRS), and a first direction of transmission of the first directional PRS, to be transmitted by the first base station; produce a second directional PRS that is unique relative to the first directional PRS by producing the second directional PRS to have at least one second signal characteristic that is different from the at least one first signal characteristic and to have a second direction of transmission that is different from the first direction of transmission; transmit, via the transmitter, the first directional PRS in the first direction of transmission and the second directional PRS in the second direction of transmission; and obtain at least one measurement from the mobile device for the first directional PRS based on assistance data for the first directional PRS as a line of sight directional PRS and no assistance data for the second directional PRS as a non-line of sight PRS.
2. The first base station of claim 1, wherein the at least one processor is configured to produce the second directional PRS that is unique relative to the first directional PRS by producing the second directional PRS such that the second directional PRS and the first directional PRS have different frequencies, or different frequency shifts, or different code sequences, or different muting patterns, or different transmission times, or any combination of any two or more thereof.
3. The first base station of claim 1, wherein the first direction of transmission and the second direction of transmission comprises a respective range of horizontal angles, or a respective range of vertical angles, or a combination thereof.
4. The first base station of claim 1, wherein the at least one processor is configured to send, via the transmitter to the mobile device, the at least one second signal characteristic of the second directional PRS.
5. A method, at a first base station, for supporting positioning of a mobile device, the method comprising: obtaining at least one first signal characteristic of a first directional positioning

reference signal (PRS), and a first direction of transmission of the first directional PRS, to be transmitted by the first base station; producing a second directional PRS that is unique relative to the first directional PRS by producing the second directional PRS to have at least one second signal characteristic that is different from the at least one first signal characteristic and to have a second direction of transmission that is different from the first direction of transmission; transmitting, via a transmitter, the first directional PRS in the first direction of transmission and the second directional PRS in the second direction of transmission; and obtaining at least one measurement from the mobile device for the first directional PRS based on assistance data for the first directional PRS as a line of sight directional PRS and no assistance data for the second directional PRS as a non-line of sight PRS.

6. The method of claim 5, wherein producing the second directional PRS that is unique relative to the first directional PRS comprises producing the second directional PRS such that the second directional PRS and the first directional PRS have different frequencies, or different frequency shifts, or different code sequences, or different muting patterns, or different transmission times, or any combination of any two or more thereof.

7. The method of claim 5, wherein each of the first direction of transmission and the second direction of transmission comprises a respective range of horizontal angles, or a respective range of vertical angles, or a combination thereof.

8. The method of claim 5, further comprising sending, from the first base station to the mobile device, the at least one second signal characteristic of the second directional PRS.

9. A first base station, for supporting positioning of a mobile device, comprising: means for obtaining at least one first signal characteristic of a first directional positioning reference signal (PRS), and a first direction of transmission of the first directional PRS, to be transmitted by the first base station; means for producing a second directional PRS that is unique relative to the first directional PRS by producing the second directional PRS to have at least one second signal characteristic that is different from the at least one first signal characteristic and to have a second direction of transmission that is different from the first direction of transmission; means for transmitting the first directional PRS in the first direction of transmission and the second directional PRS in the second direction of transmission; and means for obtaining at least one measurement from the mobile device for the first directional PRS based on assistance data for the first directional PRS as a line of sight directional PRS and no assistance data for the second directional PRS as a non-line of sight PRS.

10. The first base station of claim 9, wherein the means for producing the second directional PRS that is unique relative to the first directional PRS comprise means for producing the second directional PRS such that the second directional PRS and the first directional PRS have different frequencies, or different frequency shifts, or different code sequences, or different muting patterns, or different directions of transmission from the first base station, or any combination of any two or more thereof.

11. The first base station of claim 9, first direction of transmission and the second direction of transmission comprises a respective range of horizontal angles, or a respective range of vertical angles, or a combination thereof.

12. The first base station of claim 9, further comprising means for sending, to the mobile device, the at least one second signal characteristic of the second directional PRS.

13. A non-transitory processor-readable storage medium comprising processor-readable instructions configured to cause one or more processors of a first base station to support the positioning of a mobile device, comprising: code for obtaining at least one first signal characteristic of a first directional positioning reference signal (PRS), and a first direction of transmission of the first directional PRS, to be transmitted by the first base station; code for producing a second directional PRS that is unique relative to the first directional PRS by producing the second directional PRS to have at least one second signal characteristic that is different from the at least one first signal

characteristic and to have a second direction of transmission that is different from the first direction of transmission; code for transmitting the first directional PRS in the first direction of transmission and the second directional PRS in the second direction of transmission; and code for obtaining at least one measurement from the mobile device for the first directional PRS based on assistance data for the first directional PRS as a line of sight directional PRS and no assistance data for the second directional PRS as a non-line of sight PRS.

14. The non-transitory processor-readable storage medium of claim 13, wherein the code for producing the second directional PRS that is unique relative to the first directional PRS-comprises code for producing the second directional PRS such that the second directional PRS and the first directional PRS have different frequencies, or different frequency shifts, or different code sequences, or different muting patterns, or different transmission times, or any combination of any two or more thereof.

15. The non-transitory processor-readable storage medium of claim 13, wherein each of the first direction of transmission and the second direction of transmission comprises a respective range of horizontal angles, or a respective range of vertical angles, or a combination thereof.

16. The non-transitory processor-readable storage medium of claim 13, further comprising code for sending, to the mobile device, the at least one second signal characteristic of the second directional PRS.

---