

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250266076

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Rehmeyer; James S. et al.

MEMORY WITH PER DIE TEMPERATURE-COMPENSATED REFRESH CONTROL

Abstract

Memory devices, systems, and associated methods with per die temperature-compensated refresh control, and associated methods, are disclosed herein. In one embodiment, a memory device includes a plurality of memory cells and a sensor configured to measure a temperature of the memory device. The memory device determines a frequency at which it is receiving refresh commands. The memory device is further configured to skip refresh operations of the memory cells based, at least in part, on the determination and on the temperature of the memory device.

Inventors: Rehmeyer; James S. (Boise, ID), Johnson; Jason M. (Nampa, ID), Lee; Joo-Sang (Frisco, TX)

Applicant: Lodestar Licensing Group LLC (Evanston, IL)

Family ID: 1000008589614

Appl. No.: 19/202844

Filed: May 08, 2025

Related U.S. Application Data

parent US continuation 18241700 20230901 parent-grant-document US 12315550 child US 19202844

parent US continuation 17545966 20211208 parent-grant-document US 11776612 child US 18241700

parent US continuation 16921729 20200706 parent-grant-document US 11200939 child US 17545966

Publication Classification

Int. Cl.: G11C11/406 (20060101); G06F11/30 (20060101)

U.S. Cl.:

CPC **G11C11/40626** (20130101); **G06F11/3037** (20130101); **G06F11/3058** (20130101);
G11C11/40607 (20130101); **G11C11/40622** (20130101);

Background/Summary

[0001] CROSS-REFERENCE TO RELATED APPLICATION(S) [0002] This application is a continuation of U.S. application Ser. No. 18/241,700, filed Sep. 1, 2023, which is a continuation of U.S. application Ser. No. 16/921,729, filed Jul. 6, 2020, which is a continuation of U.S. application Ser. No. 17/545,966, filed Dec. 8, 2021, which is a continuation of U.S. application Ser. No. 16/921,729, filed Jul. 6, 2020; each of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0003] The present disclosure is related to memory systems, devices, and associated methods. In particular, the present disclosure is related to memory devices with per die temperature-compensated refresh control, and associated systems and methods.

BACKGROUND

[0004] Memory devices are widely used to store information related to various electronic devices such as computers, wireless communication devices, cameras, digital displays, and the like. Memory devices are frequently provided as internal, semiconductor, integrated circuits, and/or external removable devices in computers or other electronic devices. There are many different types of memory, including volatile and non-volatile memory. Volatile memory, including static random-access memory (SRAM), dynamic random-access memory (DRAM), and synchronous dynamic random-access memory (SDRAM), among others, may require a source of applied power to maintain its data. Non-volatile memory, by contrast, can retain its stored data even when not externally powered. Non-volatile memory is available in a wide variety of technologies, including flash memory (e.g., NAND and NOR) phase change memory (PCM), ferroelectric random-access memory (FeRAM), resistive random-access memory (RRAM), and magnetic random-access memory (MRAM), among others. Improving memory devices, generally, may include increasing memory cell density, increasing read/write speeds or otherwise reducing operational latency, increasing reliability, increasing data retention, reducing power consumption, or reducing manufacturing costs, among other metrics.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] Many aspects of the present disclosure can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale. Instead, emphasis is placed on illustrating clearly the principles of the present disclosure. The drawings should not be taken to limit the disclosure to the specific embodiments depicted, but are for explanation and understanding only.

[0006] FIG. 1 is a block diagram schematically illustrating a memory system configured in accordance with various embodiments of the present technology.

[0007] FIG. 2 is a block diagram schematically illustrating a memory device configured in accordance with various embodiments of the present technology.

[0008] FIG. 2A is a block diagram schematically illustrating a refresh control circuit configured in accordance with various embodiments of the present technology.

[0009] FIGS. 3 and 4 are flow diagrams illustrating routines of memory devices configured in

accordance with various embodiments of the present technology.

[0010] FIG. 5 is a schematic view of a system that includes a memory device configured in accordance with various embodiments of the present technology.

DETAILED DESCRIPTION

[0011] The technology disclosed herein relates to memory devices (and associated systems and methods) configured to skip refresh operations based, at least in part, on their internal temperatures. In one embodiment, a memory system comprises a memory controller and a plurality of memory devices. The memory controller is configured to monitor at least one temperature of the memory system. When a monitored temperature reaches or exceeds a threshold temperature value, the memory controller increases the frequency at which the controller sends refresh commands to the memory devices. The controller further notifies the memory devices of the frequency increase. In turn, each memory device monitors its internal temperature and skips refresh operations when its internal temperature does not meet or exceed the threshold temperature value. In this manner, those memory devices of the memory system having internal temperatures greater than or equal to the threshold temperature value are refreshed at the higher frequency, thereby reducing the amount of power consumed or required by the memory system during refresh operations.

[0012] To ameliorate data retention at higher temperatures, memory systems can be configured to increase the frequency at which their memory devices are refreshed when temperatures of the systems exceed a threshold temperature value. Memory systems often, however, monitor temperature sensors that generate temperature measurements representing temperatures of groups of memory devices (e.g., on dual in-line memory modules (DIM Ms)). That is, memory systems can be configured to increase the frequency at which refresh commands are issued to every memory device of the system based on a temperature measurement that is generically associated with a group of memory devices. Large temperature variations (e.g., 10-30° C. or more), however, are often observed across memory devices of these groups. Thus, the generic temperature measurements are often not accurate indications of the internal temperatures of every memory device in a group. As a result, several memory devices (e.g., one or more placements of DRAM on a DIMM that contain sixteen or eighteen such placements) may be operating at internal temperatures below the threshold temperature value even when the generic temperature measurement exceeds the threshold temperature value. Because data loss due to temperature is less of a concern in memory devices having internal temperatures below the threshold temperature value, increasing the frequency at which these cooler memory devices are refreshed constitutes a waste of power. Moreover, memory devices are typically not notified of when the frequency at which they are receiving refresh commands from the memory controller has been increased. As a result, memory devices are often unable to determine whether it is appropriate to skip the additional refresh commands received from the memory controller under the increased frequency. As future generations of memory systems include a greater number of memory devices and/or include memory devices positioned at tighter pitches relative to one another, these future memory systems are expected to demand or consume an even greater amount of power and/or to run at higher temperatures. Accordingly, drawbacks of the foregoing refresh approaches involve significant power demands for future memory systems with greater refresh frequencies, more memory devices, and/or higher power density.

[0013] To address these concerns, several embodiments of the present technology are directed to memory devices (e.g., volatile memory devices), systems including memory devices (e.g., DIM Ms), and methods of operating memory devices in which individual memory devices are configured to monitor their internal temperatures and to skip refresh operations at least when (a) refresh commands are issued at a greater-than-normal frequency and (b) their internal temperatures are below a threshold temperature value. In particular, an individual memory device of the present technology is configured to receive an indication (e.g., from a memory controller) that refresh commands are being issued in accordance with a faster-than-normal refresh rate. In turn, the

individual memory device is configured to compare (i) a temperature measurement generated by a temperature sensor internal to the memory device to (ii) a threshold temperature value. When the temperature measurement exceeds (and/or meets) the threshold temperature value, the memory device is configured to refresh memory cells of the memory device in accordance with the faster-than-normal refresh rate to ameliorate data retention at the higher temperatures. Otherwise, the memory device is configured to skip executing at least a subset (e.g., every other, every third, etc.) of refresh commands received (e.g., from a memory controller), thereby reducing the amount of power required or consumed by the memory device during refresh operations.

[0014] In the illustrated embodiments below, the memory systems and devices are primarily described in the context of devices incorporating DRAM storage media. Memory systems and devices configured in accordance with other embodiments of the present technology, however, can include other types of memory systems and devices incorporating other types of storage media, including PCM, SRAM, FRAM, RRAM, MRAM, read only memory (ROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), ferroelectric, magnetoresistive, and other storage media, including non-volatile, flash (e.g., NAND and/or NOR) storage media. Furthermore, a person skilled in the art will understand that the technology may have additional embodiments and that the technology may be practiced without several of the details of the embodiments described below with reference to FIGS. 1-5.

[0015] As used herein, the terms “memory system” and “memory device” refer to systems and devices configured to temporarily and/or permanently store information related to various electronic devices. Accordingly, the term “memory device” can refer to a single memory die and/or to a memory package containing one or more memory dies. Similarly, the term “memory system” can refer to a system including one or more memory dies (e.g., a memory package) and/or to a system (e.g., a dual in-line memory module (DIMM)) including one or more memory packages.

[0016] FIG. 1 is a block diagram schematically illustrating a memory system **100** (e.g., a dual in-line memory module (DIMM)) configured in accordance with various embodiments of the present technology. The memory system **100** can be connected to any one of a number of electronic devices that is capable of utilizing memory for the temporary or persistent storage of information, or a component thereof. For example, the memory system **100** can be operably connected to a host device (not shown). The host device may be a computing device such as a desktop or portable computer, a server, a hand-held device (e.g., a mobile phone, a tablet, a digital reader, a digital media player), or some component thereof (e.g., a central processing unit, a co-processor, a dedicated memory controller, etc.). The host device may be a networking device (e.g., a switch, a router, etc.) or a recorder of digital images, audio, and/or video; a vehicle; an appliance; a toy; or any one of a number of other products. In one embodiment, the host device may be connected directly to the memory system **100**, although, in other embodiments, the host device may be indirectly connected to the memory system **100** (e.g., over a networked connection or through intermediary devices).

[0017] As shown, the memory system **100** includes a memory controller **101** (e.g., a field programming gate array (FPGA) or other suitable memory controller) and one or more memory devices **104** (e.g., one or more dynamic random-access memory (DRAM) devices) electrically connected to the memory controller **101** via a printed circuit board (PCB) **102** (e.g., via one or more electrical contacts and/or traces). The memory controller **101** can be configured to control one or more operations of the memory system **100**. For example, the memory controller **101** can control refresh operations of the memory devices **104**. In particular, the memory controller **101** can issue a refresh command to direct one or more of the memory devices **104** to initiate their respective refresh operations.

[0018] Individual memory devices **104** of the memory system **100** can include a package substrate **103** and one or more memory dies **200**. As illustrated in FIG. 1, each of the memory devices **104** includes a first memory die **200a** attached to the package substrate **103**, and a second memory die

200b stacked on top of the first memory die **200a**. In some embodiments, the first and second memory dies **200a** and **200b** are each electrically connected to the package substrate **103** (e.g., via one or more electrical contacts and/or traces), which in turn can be electrically connected to the PCB **102**. Although the devices **104** illustrated in FIG. 1 are dual die packages (DDP), one or more memory devices **104** configured in accordance with other embodiments of the present technology can include a greater or lesser number of memory dies **200** (e.g., one memory die or more than two memory dies) than illustrated. In these and other embodiments, the orientation of the memory dies included in a memory device **104** can vary. For example, the first and second memory dies **200a** and **200b** illustrated in FIG. 1 are each oriented face down (e.g., toward the package substrate **103**) in a back-to-face orientation. In other embodiments, the first memory die **200a** and/or the second memory die **200b** can be oriented face up (e.g., away from the package substrate **103**) such that the first and second memory dies **202a** and **202b** are arranged in a face-to-back, face-to-face, and/or back-to-back orientation on a package substrate **103**. In these and still other embodiments, the first and second memory dies **200a** and **200b** can be arranged side-by-side on the package substrate **103**, as opposed to the stacked arrangement illustrated in FIG. 1.

[0019] In some embodiments, the memory system **100** can further include one or more temperature sensors. In the illustrated embodiment, the memory system **100** includes a temperature sensor **108** positioned within the PCB **102**. In other embodiments, the temperature sensor **108** can be positioned at other locations within the memory system **100**. For example, the temperature sensor **108** can be positioned within one or more of the package substrates **103**, within one or more of the memory dies **200** (e.g., within the first and/or second memory dies **200a** and/or **200b**), within the memory controller **101**, and/or within another component (not shown) of the memory system **100**. As described in greater detail below with respect to FIG. 2, the memory system **100** additionally or alternatively includes one or more temperature sensors (not shown in FIG. 1) internal to all or a subset of the memory dies **200** of the memory system **100**. Such internal temperature sensors are expected to provide more accurate indications of an individual memory device's **104** and/or an individual memory die's **200** internal temperature than provide by the temperature sensor **108**.

[0020] In operation, the temperature sensor **108** is configured to generate one or more temperature measurements indicating the temperature of the memory system **100**. In the illustrated embodiment, the temperature sensor **108** corresponds to each of the memory devices **104** of the memory system **100**. Thus, temperature measurements generated by the temperature sensor **108** generically represent the temperature of each of the memory devices **104**. In other embodiments, the temperature sensor **108** can correspond to a subset of the memory devices **104** and/or to one or more other components (e.g., the memory controller **101**, the PCB **102**, or another component) of the memory system **100**. In these and still other embodiments, the memory system can include one or more other temperature sensors similar to the temperature sensor **108**, each of which can correspond to a subset of the memory devices **104** and/or to one or more other components (e.g., the memory controller **101**, the PCB **102**, or another component) of the memory system **100**. In contrast, the one or more temperature sensors internal to the memory dies **200** of the memory system **100** are configured to generate temperature measurements representing the temperature of only a corresponding memory die **200**.

[0021] The temperature sensor **108** and/or the one or more temperature sensors internal to the memory die(s) **200** can be electrically connected to the memory controller **101** such that temperature measurements generated by the temperature sensor(s) are communicated to the memory controller **101**. In these embodiments, the memory controller **101** can monitor the temperature measurements to determine a frequency at which to send refresh commands to the memory devices **104**. As a specific example, the memory controller **101** can compare (i) a temperature measurement generated by the temperature sensor **108** and/or by one or more temperature sensors internal to the memory die(s) **200** to (ii) a threshold temperature value (e.g., 85° C.). In some embodiments, the threshold temperature value can indicate a temperature

threshold above (and/or at) which there is a concern that data retention issues will arise due to the temperatures of the memory devices **104** (e.g., of the memory dies **200**) at a given refresh rate (e.g., at a standard, default, or normal refresh rate). Stated another way, the threshold temperature value can indicate a temperature threshold below (and/or at) which there is little concern that data retention issues will arise due to the temperatures of the memory devices **104** at the given refresh rate. Thus, if the memory controller **101** determines that a temperature measurement generated by the temperature sensor **108** and/or the temperature sensor(s) internal to the memory die(s) **200** is less than (and/or equal to) the threshold temperature value, the memory controller **101** can issue refresh commands to the memory devices **104** in accordance with the given refresh rate. For example, the memory controller **101** can issue refresh commands to the memory devices **104** every 7.8 μ s for double data rate fourth generation (DDR4) memory devices or every 3.9 μ s for double data rate fifth generation (DDR5) memory devices. The term “1X refresh mode” will be used hereinafter to indicate that the memory controller **101** is issuing (or that a memory device **104** or a memory die **200** is receiving) refresh commands in accordance with a normal or default refresh rate.

[0022] On the other hand, if the memory controller **101** determines that the temperature measurement is greater than (and/or equal to) the threshold temperature value, the memory controller **101** can issue refresh commands to the memory device **104** in accordance with a refresh rate faster than the given refresh rate. For the sake of clarity and understanding, the faster refresh rate will be discussed hereinafter in the context of being twice the given refresh rate such that refresh commands are issued to the memory devices **104** twice as fast than in accordance with the given refresh rate. Thus, the term “2X refresh mode” will be used hereinafter to indicate that the memory controller **101** is issuing (or that a memory device **104** or memory die **200** is receiving) refresh commands in accordance with a faster refresh rate. Continuing with the numbers from the above example, the memory controller **101** in the 2X refresh mode can issue a refresh command to the memory devices **104** every 3.9 μ s for DDR4 memory devices or every 1.95 μ s for DDR5 memory devices. A person of ordinary skill in the art will readily recognize that a faster refresh rate can be another multiple (other than twice) faster than the given refresh rate. Such other multiples and corresponding refresh rates fall within the scope of the present technology.

[0023] In some embodiments, the memory controller **101** can be configured to issue refresh commands to the memory devices **104** in accordance with the 1X refresh mode by default. Additionally, or alternatively, the memory controller **101** can be configured to issues refresh commands to each of the memory devices **104** in accordance with the 2X refresh mode when a specified number (e.g., one or more) temperature measurements generated by the temperature sensor **108** are greater than (or equal to) a specified threshold temperature value (e.g., 85° C.). In these and other embodiments, the memory controller **101** can be configured to issue refresh commands to each of the memory devices **104** in accordance with the 2X refresh mode when a specified number (e.g., one or more) temperature measurements generated by a specified number (e.g., one or more) of temperature sensors positioned internal to a specified number (e.g., one or more) memory dies **200** are greater than (or equal to) a specified threshold temperature value (e.g., 85° C. or another threshold temperature value). In some embodiments, the memory controller **101** is configured to continue issuing refresh commands to each of the memory devices **104** in accordance with the 2X refresh mode until a specified number (e.g., one or more) of temperature measurements generated by the temperature sensor **108** and/or by a specified number (e.g., one or more) temperature sensors positioned internal to a specified number (e.g., one or more) memory dies **200** are less than (or equal to) a specified threshold temperature value (e.g., 85° C. or another threshold temperature value). In these and still other embodiments, the memory controller **101** can be configured to issue refresh commands to each of the memory devices **104** in accordance with the 1X refresh mode and/or the 2X refresh mode in response to one or more commands received from a host device or another component communicatively connected to the memory controller **101**.

[0024] As discussed above, large temperature variations (e.g., 10-30° C. or more) are often observed across memory devices of a memory system and/or of a memory DIMM. Thus, the temperature measurements generated by the temperature sensor **108** of FIG. **1** may be accurate indications of the internal temperatures of only a subset of the memory dies **200** of the memory system **100**. In other words, one or more of the memory dies **200** may include temperatures below the threshold temperature value even when a temperature measurement generated by the temperature sensor **108** exceeds (and/or meets) a specified threshold temperature value. Because data loss due to temperature is less of a concern in memory dies **200** having internal temperatures below the threshold temperature value, increasing the frequency at which these cooler memory dies **200** are refreshed would constitute a waste of power. That is, if a memory die **200** having an internal temperature below (and/or at) the specified threshold temperature value is sufficiently refreshed under the 1X refresh mode, the cooler memory die **200** would be refreshed at least twice as often as required by changing the refreshing scheme of the cooler memory die **200** to the 2X refresh mode when temperature measurements generated by the temperature sensor **108** and/or by one or more temperature sensors positioned internal to one or more other memory devices **104** or memory dies **200** of the memory system **100** indicate that the other memory devices **104** or memory dies **200** have temperatures above (and/or at) the specified threshold temperature value. In other words, at least every other refresh operation of the cooler memory die **200** under the 2X refresh mode would constitute a waste of power. Furthermore, without an indication that the refresh scheme was changed from the 1X refresh mode to the 2X refresh mode, this cooler memory die **200** would not be able to determine that it is being refreshed under the 2X refresh mode and that it is appropriate to skip at least a subset of the refresh commands received from the memory controller **101** given the cooler memory die's **200** temperature.

[0025] To address these concerns (and as discussed in greater detail below with respect to FIGS. **2** and **3**), the memory controller **101** is configured to notify the memory devices **104** and/or the memory dies **200** of the current refresh scheme (i.e., whether the memory controller **101** is issuing refresh commands in accordance with the 1X refresh mode or in accordance with the 2X refresh mode). In turn, the memory devices **104** and/or memory dies **200** of the memory system **100** are able to use the notification to determine when it is appropriate to skip refresh operations based, at least in part, on their respective internal temperatures.

[0026] FIG. **2** is a block diagram schematically illustrating a memory device **200** (e.g., a memory die **200**, such as a first memory die **200a** and/or a second memory die **200b** of FIG. **1**) configured in accordance with various embodiments of the present technology. The memory device **200** may employ a plurality of external terminals that include command and address terminals coupled to a command bus and an address bus to receive command signals CM D and address signals ADDR, respectively. The memory device may further include a chip select terminal to receive a chip select signal CS, clock terminals to receive clock signals CK and CK F, data clock terminals to receive data clock signals WCK and WCK F, data terminals DQ, RDQS, DBI, and DMI to receive data signals, and power supply terminals VDD, VSS, and VDDQ.

[0027] The power supply terminals of the memory device **200** may be supplied with power supply potentials VDD and VSS. These power supply potentials VDD and VSS can be supplied to an internal voltage generator circuit **270**. The internal voltage generator circuit **270** can generate various internal potentials VPP, VOD, VARY, VPERI, and the like based on the power supply potentials VDD and VSS. The internal potential VPP can be used in the row decoder **240**, the internal potentials VOD and VARY can be used in sense amplifiers included in the memory array **250** of the memory device **200**, and the internal potential VPERI can be used in many other circuit blocks.

[0028] The power supply terminals may also be supplied with power supply potential VDDQ. The power supply potential VDDQ can be supplied to the IO circuit **260** together with the power supply potential VSS. The power supply potential VDDQ can be the same potential as the power supply

potential VDD in an embodiment of the present technology. The power supply potential VDDQ can be a different potential from the power supply potential VDD in another embodiment of the present technology. However, the dedicated power supply potential VDDQ can be used for the IO circuit **260** so that power supply noise generated by the IO circuit **260** does not propagate to the other circuit blocks.

[0029] The clock terminals and data clock terminals may be supplied with external clock signals and complementary external clock signals. The external clock signals CK, CKF, WCK, WCKF can be supplied to a clock input circuit **220**. The CK and CKF signals can be complementary, and the WCK and WCKF signals can also be complementary. Complementary clock signals can have opposite clock levels and transition between the opposite clock levels at the same time. For example, when a clock signal is at a low clock level a complementary clock signal is at a high level, and when the clock signal is at a high clock level the complementary clock signal is at a low clock level. Moreover, when the clock signal transitions from the low clock level to the high clock level the complementary clock signal transitions from the high clock level to the low clock level, and when the clock signal transitions from the high clock level to the low clock level the complementary clock signal transitions from the low clock level to the high clock level.

[0030] Input buffers included in the clock input circuit **220** can receive the external clock signals. For example, when enabled by a CKE signal from a command decoder **215**, an input buffer can receive the CK and CKF signals and the WCK and WCKF signals. The clock input circuit **220** can receive the external clock signals to generate internal clock signals ICLK. The internal clock signals ICLK can be supplied to an internal clock circuit **230**. The internal clock circuit **230** can provide various phase and frequency controlled internal clock signals based on the received internal clock signals ICLK and a clock enable signal CKE from the command decoder **215**. For example, the internal clock circuit **230** can include a clock path (not shown in FIG. **2**) that receives the internal clock signal ICLK and provides various clock signals to the command decoder **215**. The internal clock circuit **230** can further provide input/output (IO) clock signals. The IO clock signals can be supplied to an input/output (IO) circuit **260** and can be used as a timing signal for determining an output timing of read data and the input timing of write data. The IO clock signals can be provided at multiple clock frequencies so that data can be output from and input into the memory device **200** at different data rates. A higher clock frequency may be desirable when high memory speed is desired. A lower clock frequency may be desirable when lower power consumption is desired. The internal clock signals ICLK can also be supplied to a timing generator **235** and thus various internal clock signals can be generated that can be used by the command decoder **215**, the column decoder **245**, and/or other components of the memory device **200**.

[0031] The memory device **200** may include an array of memory cells, such as memory array **250**. The memory cells of the memory array **250** may be arranged in a plurality of memory regions, and each memory region may include a plurality of word lines (WL), a plurality of bit lines (BL), and a plurality of memory cells arranged at intersections of the word lines and the bit lines. In some embodiments, a memory region can be a one or more memory banks or another arrangement of memory cells. In these and other embodiments, the memory regions of the memory array **250** can be arranged in one or more groups (e.g., groups of memory banks, one or more logical memory ranks or dies, etc.). Memory cells in the memory array **250** can include any one of a number of different memory media types, including capacitive, magnetoresistive, ferroelectric, phase change, or the like. The selection of a word line WL may be performed by a row decoder **240**, and the selection of a bit line BL may be performed by a column decoder **245**. Sense amplifiers (SAM P) may be provided for corresponding bit lines BL and connected to at least one respective local I/O line pair (LIOT/B), which may in turn be coupled to at least respective one main I/O line pair (MIOT/B), via transfer gates (TG), which can function as switches. The memory array **250** may also include plate lines and corresponding circuitry for managing their operation.

[0032] The command terminals and address terminals may be supplied with an address signal and a

bank address signal from outside the memory device **200**. The address signal and the bank address signal supplied to the address terminals can be transferred, via a command/address input circuit **205**, to an address decoder **210**. The address decoder **210** can receive the address signals and supply a decoded row address signal (XADD) to the row decoder **240**, and a decoded column address signal (YADD) to the column decoder **245**. The address decoder **210** can also receive the bank address signal (BADD) and supply the bank address signal to both the row decoder **240** and the column decoder **245**.

[0033] The command and address terminals can be supplied with command signals CMD, address signals ADDR, and chip selection signals CS (e.g., from the memory controller **101** and/or a host device). The command signals may represent various memory commands (e.g., including access commands, which can include read commands and write commands). The chip selection signals CS may be used to select the memory device **104** and/or the memory device **200** to respond to commands and addresses provided to the command and address terminals. When an active CS signal is provided to the memory device **200**, the commands and addresses can be decoded and memory operations can be performed. The command signals CMD may be provided as internal command signals ICMD to a command decoder **215** via the command/address input circuit **205**. The command decoder **215** may include circuits to decode the internal command signals ICMD to generate various internal signals and commands for performing memory operations, for example, a row command signal to select a word line and a column command signal to select a bit line. The internal command signals can also include output and input activation commands, such as a clocked command CMDCK (not shown) to the command decoder **215**.

[0034] The command decoder **215** may further include one or more registers **218** for tracking various counts or values (e.g., counts of refresh commands received by the memory device **200** or self-refresh operations performed by the memory device **200**) and/or for storing various operating conditions for the memory device **200** to perform certain functions, features, and modes (refresh modes, test modes, etc.). As such, in some embodiments, registers **218** (or a subset of the registers **218**) may be referred to as mode registers. As a specific example, the memory device **200** may be placed into a refresh mode by programming certain bits of the registers **218**. Once the memory device **200** is placed into the refresh mode, the memory device **200** can use certain address bits received in the address signals ADDR to determine the frequency at which refresh commands are being sent to the memory device **200** (e.g., by a memory controller **101**). For example, the memory device **200** can monitor a specific address bit in ADDR signals received by the memory device **200** (e.g., from the memory controller **101**) to determine a current refresh scheme (e.g., 1X refresh mode, 2X refresh mode, etc.) of the corresponding memory system **100**. Continuing with this example, the memory device **200** can determine that the memory device **200** is receiving refresh commands in accordance with the 1X refresh mode when the address bit in the ADDR signals received by the memory device **200** is in a first state (e.g., a “high” or “1” state) or that the memory device **200** is receiving refresh commands in accordance with the 2X refresh mode when the address bit is in a second state (e.g., a “low” or “0” state). In other words, a memory controller **101** or other component of a memory system that includes the memory device **200** can notify the memory device **200** of the frequency at which refresh commands are being sent to the memory device **200** using one or more address bits in the ADDR signals sent to the memory device **200**.

[0035] When a read command is issued to the memory device **200**, and a row address and a column address are timely supplied to the memory device **200**, read data can be read from memory cells in the memory array **250** designated by the row address and the column address. The read command may be received by the command decoder **215**, which can provide internal commands to the IO circuit **260** so that read data can be output from the data terminals DQ, RDQS, DBI, and DMI via read/write (RW) amplifiers **255** and the IO circuit **260** according to the RDQS clock signals. The read data may be provided at a time defined by read latency information RL that can be programmed in the memory device **200**, for example in the mode register **218**. The read latency

information RL can be defined in terms of clock cycles of the CK clock signal. For example, the read latency information RL can be a number of clock cycles of the CK signal after the read command is received by the memory device **200** when the associated read data is provided. [0036] When a write command is issued to the memory device **200**, and a row address and a column address are timely supplied to the memory device **200**, write data can be supplied to the data terminals DQ, DBI, and DMI over DQ lines connected to the memory device **200** according to the WCK and WCKF clock signals. The write command may be received by the command decoder **215**, which can provide internal commands to the IO circuit **260** so that the write data can be received by data receivers in the **10** circuit **260**, and supplied via the IO circuit **260** and the RW amplifiers **255** to the memory array **250** over IO lines of the memory device **200**. The write data may be written in the memory cell designated by the row address and the column address. The write data may be provided to the data terminals at a time that is defined by write latency WL information. The write latency WL information can be programmed in the memory device **200**, for example, in the mode register **218**. The write latency WL information can be defined in terms of clock cycles of the CK clock signal. For example, the write latency information WL can be a number of clock cycles of the CK signal after the write command is received by the memory device **200** when the associated write data is received.

[0037] The memory array **250** may be refreshed or maintained to prevent data loss, either due to charge leakage or imprint effects. A refresh operation may be initiated by the memory device **200**, by the memory system **100** (e.g., by the memory controller **101** of FIG. **1**), and/or by a host device, and may include accessing one or more rows (e.g., WL) and discharging cells of the accessed row to a corresponding SAMP. While the row is opened (e.g., while the accessed WL is energized), the SAMP may compare the voltage resulting from the discharged cell to a reference. The SAMP may then write back a logic value (e.g., charge the cell) to a nominal value for the given logic state. In some cases, this write back process may increase the charge of the cell to ameliorate the discharge issues discussed above. In other cases, the write back process may invert the data state of the cell (e.g., from high to low or low to high), to ameliorate hysteresis shift, material depolarization, or the like. Other refresh schemes or methods may also be employed.

[0038] In one approach, the memory device **200** may be configured to refresh the same row of memory cells in every memory bank of the memory array **250** simultaneously. In another approach, the memory device **200** may be configured to refresh the same row of memory cells in every memory bank of the memory array **250** sequentially. In still another approach, the memory device **200** can further include circuitry (e.g., one or more registers, latches, embedded memories, counters, etc.) configured to track row (e.g., word line) addresses, each corresponding to one of the memory banks in the memory array **250**. In this approach, the memory device **200** is not constrained to refresh the same row in each memory bank of the memory array **250** before refreshing another row in one of the memory banks.

[0039] Regardless of the refresh approach, the memory device **200** can be configured to refresh memory cells in the memory array **250** within a given refresh rate or time window (e.g., 32 ms, 28 ms, 25 ms, 23 ms, 21 ms, 18 ms, 16 ms, 8 ms, etc.), known as tREF. In these embodiments, a corresponding memory device **104** and/or the memory system **100** can be configured to supply refresh commands to the memory device **200** in accordance with a specified minimum cadence tREFI. For example, the memory device **104** and/or the memory system **100** can be configured to supply one or more refresh commands to the memory device **200** in accordance with the 1X refresh mode at least every 7.8 μ s for DDR4 memory devices (3.9 μ s for DDR5) such that an approximate minimum of 4000 refresh commands (8000 refresh commands for DDR5) are supplied to the memory device **200** within a 32 ms time window. As another example, the memory device **104** and/or the memory system **100** can be configured to supply one or more refresh commands to the memory device **200** in accordance with the 2X refresh mode at least every 3.9 μ s for DDR4 memory devices (1.95 μ s for DDR5) such than an approximate minimum of 8000 refresh

commands (16000 refresh commands for DDR5) are supplied to the memory device **200** within a 32 ms time window.

[0040] As discussed above, refresh operations of a memory system **100** and/or a memory device **200** are current-intensive operations that demand and consume a large amount of power.

Furthermore, data loss due to temperature is less of a concern in memory devices **200** having internal temperatures below one or more threshold temperature values. Therefore, increasing the frequency at which cooler memory devices **200** are refreshed to ameliorate data retention in other memory devices **200** having higher temperatures would constitute a waste of power.

[0041] To address this concern, the memory device **200** illustrated in FIG. 2 includes at least one internal temperature sensor **243**. The temperature sensor **243** is configured to generate temperature measurements representing the temperature of only the memory device **200**. In some embodiments, the temperature measurements are communicated to the command decoder **215** and/or to a memory controller **101** communicatively coupled to the temperature sensor **243**. As discussed in greater detail below with respect to FIG. 3, the memory device **200** can determine whether to skip one or more refresh operations based, at least in part, on the internal temperature of the memory device **200** and on the frequency at which the memory device **200** is receiving refresh commands (indicated in the notification received via the address bits of address signals ADDR received by the memory device **200**). As such, each memory device **200** of the memory system **100** can determine whether to skip refresh operations based on its own temperature such that only memory devices **200** having internal temperatures above a threshold temperature value are refreshed in accordance with the 2X refresh mode. In this manner, the total amount of power required or consumed by the memory device **200** for refresh operations is reduced and/or minimized, thereby reducing the total amount of power required or consumed by a corresponding memory system **100**.

[0042] FIG. 2A is a block diagram schematically illustrating a refresh control circuit **280** of a memory device **200** (FIG. 2), configured in accordance with various embodiments of the present technology. As shown, the refresh control circuit **280** includes a delay element **281**; inverters **282**, **283**, and **287**; a NAND gate **284**; AND gates **285**, **288**, and **290**; a $\frac{1}{2}$ divider circuit **286**; and an OR gate **289**. A person of ordinary skill in the art will readily appreciate that the refresh control circuit **280** illustrated in FIG. 2A is but one implementation of a refresh control circuit configured in accordance with various embodiments of the present technology. Therefore, a person of ordinary skill in the art will also readily recognize that a refresh control circuit can include other components in addition to or in lieu of any one or more of the components of the refresh control circuit **280**, and still fall within the scope of the present technology. For example, the refresh control circuit **280** is illustrated with a $\frac{1}{2}$ divider circuit **286** to enable the memory device to skip every other refresh command, but the refresh control circuit **280** can include other divider circuits (e.g., a $\frac{1}{3}$ divider circuit to skip every third refresh command) in other embodiments in addition to or in lieu of the $\frac{1}{2}$ divider circuit **286**.

[0043] As illustrated in FIG. 2A, a refresh command signal REF (e.g., a refresh clock signal REFCLK) is received (e.g., from a command decoder **215** (FIG. 2) of the memory device **200**) and is input (i) into the AND gate **285** via the delay element **281** and (ii) into the AND gate **290**. The AND gate **285** additionally receives an inverted refresh management signal RFM, an inverted logical product of an inverted mode register signal and a command address bit signal (illustrated as mode register signal MR4[3] and command address bit signal CA8 in FIG. 2A), and a same bank in progress signal. In some embodiments, the command address bit signal CA8 is asserted when the memory device **200** is in 1X refresh mode and is not asserted when the memory device **200** is in 2X refresh mode. The output of the AND gate **285** is input into the $\frac{1}{2}$ divider circuit **286** in addition to a set signal SET. In turn, the output of the $\frac{1}{2}$ divider circuit **286** is input into the OR gate **289** in addition to the refresh management signal RFM and the logical product of the inverted mode register signal and the command address bit signal (again, illustrated as mode register signal MR4[3] and command address bit signal CA8 in FIG. 2A). The output of the OR gate **289** is input

into the AND gate **290**, and the logical product of the output of the OR gate **289** and the refresh command signal REF is output from the AND gate **290** as an internal refresh signal REF Internal. [0044] In operation, the refresh control circuit **280** is configured to enable the memory device **200** to execute a refresh command (e.g., to output the internal refresh signal REF Internal in a high state) whenever (i) the refresh management signal RFM is asserted, (ii) the mode register signal MR4[3] is not asserted while the command address bit signal CA8 is asserted, and/or (iii) the output of the $\frac{1}{2}$ divider circuit **286** is high. The output of the $\frac{1}{2}$ divider circuit **286** is high whenever (i) the output of the AND gate **285** is high (e.g., when (a) the refresh command signal REF is asserted, (b) the same bank in progress signal is asserted, (c) the refresh management signal is not asserted, and (d) the mode register signal MR4[3] is not asserted while the command address bit signal CA8 is asserted) and (ii) the set signal SET is asserted. In some embodiments, the set signal SET is asserted whenever the mode register signal MR4[3] is not asserted, the temperature of the memory device **200** is greater than or equal to a threshold temperature value (e.g., 85° C.), during set refresh (SFR) mode of the memory device **200**, and/or upon entering and exiting fine granular refresh (FGR) mode of the memory device **200**. In other words, the refresh control circuit **280** is configured to cause the memory device **200** to skip every other refresh command whenever the refresh management signal is not asserted, the memory device is in 2X refresh mode, and the temperature of the memory device **200** is below the threshold temperature value. A person of ordinary skill in the art will readily recognize, however, that the refresh control circuit **280** can be configured to cause the memory device **200** to skip refresh commands/operations upon the occurrence of other events in addition to or in lieu of the events discussed above.

[0045] FIG. **3** is a flow diagram illustrating a routine **300** of a memory device configured in accordance with various embodiments of the present technology. The routine **300** is illustrated as a set of steps, blocks, operations, or processes **301-311**. In some embodiments, one or more of the steps **301-311** may be implemented, at least in part, in the form of executable code stored on non-transitory, tangible, machine readable media. All or a subset of the steps **301-311** of the routine **300** can be executed, at least in part, by various components of a memory device (e.g., a memory device **104** of FIG. **1** and/or a memory device **104/200** of FIGS. **1** and **2**). In these and other embodiments, one or more of the steps **301-311** can be executed, at least in part, by one or more components of a memory system, such as a memory controller, a PCB, a package substrate, and/or a memory die. In these and still other embodiments, one or more of the steps **301-311** can be executed, at least in part, by a host device operably connected to the memory system, by a manufacturer, by an end user, or by an intermediary party.

[0046] As shown, the routine **300** begins at step **301** by determining a temperature of the memory device. For example, the routine **300** determines a temperature of the memory device using one or more temperature measurements generated by a temperature sensor internal to the memory device.

[0047] At step **302**, the routine **300** receives an indication of a frequency at which the memory device is receiving refresh commands. Such an indication can, for example, notify the routine **300** of a refresh scheme or mode (e.g., a 1X refresh mode, a 2X refresh mode, etc.) of a memory system (e.g., of a memory controller and/or a host device) that includes or is communicatively connected to the memory device. In some embodiments, a refresh mode of the memory device is enabled by programming certain bits of a mode register of the memory device. In these embodiments, the routine **300** can receive the indication via one or more address bits in address signals received by the memory device (e.g., when the memory device registers a refresh command, after the mode register is programmed to place the memory device into the refresh mode, etc.).

[0048] At step **303**, the routine **300** determines the frequency at which the memory device is receiving refresh commands. In some embodiments, the routine **300** determines the frequency based, at least in part, on the indication received at step **302**. For example, the routine **300** can monitor the one or more address bits in address signals received by the memory device to determine the frequency. Continuing with this example, the routine **300** can determine that the

memory device is receiving refresh commands at a frequency consistent with a 2X refresh mode (step **303**, “Y”) when a specified address bit in the address signals received by the memory device is in a first state (e.g., a “low” or “0” state), and the routine **300** can accordingly proceed to step **304** to compare the temperature of the memory device determined at step **301** to a first threshold temperature value. Alternatively, the routine **300** can determine that the memory device is receiving refresh commands at a frequency consistent with a 1X refresh mode (step **303**, “N”) when the specified address bit in the address signals received by the memory device is in a second state (e.g., a “high” or “1” state), and the routine **300** can accordingly proceed to step **309** to compare the temperature of the memory device determined at step **301** to a third threshold temperature value. [0049] For the sake of clarity and understanding, the frequency at which the memory device is receiving refresh commands in the illustrated embodiment is consistent with one of only two possible refresh schemes (e.g., the 1X refresh mode and the 2X refresh mode). In other embodiments, however, the frequency can be consistent with any number of other possible refresh schemes. In such embodiments, the flow diagram of FIG. **3** can include a corresponding number of additional decision steps (similar to step **303**) for determining the frequency at which the memory device is receiving refresh commands, as well as a corresponding number of additional steps (similar to steps **304-311**) for determining a number and/or pattern of refresh commands/operations to skip.

[0050] At step **304**, the routine **300** determines whether the temperature of the memory device determined at step **301** is greater than or equal to a first threshold temperature value. In some embodiments, the first threshold temperature value can be a temperature above (and/or at) which there is a concern that data retention issues will arise in memory cells of the memory device.

[0051] For example, the first threshold temperature value can be equal to or greater than 70° C. (e.g., 85° C.). In some embodiments, the first threshold temperature value can be the same threshold temperature value as or similar a similar threshold temperature value to the threshold temperature value used by a memory controller to determine the frequency at which to send refresh commands to the memory device, as discussed in greater detail above with respect to FIG. **1**. If the routine **300** determines that the temperature of the memory device is greater than or equal to the first threshold temperature value, the routine **300** can accordingly proceed to step **305** to refresh the memory device in accordance with the 2X refresh mode. In other words, the routine **300** can execute a refresh operation for every refresh command received by the memory device. On the other hand, if the routine **300** determines that the temperature of the memory device determined at step **301** is not greater than or equal to the first threshold temperature value, the routine **300** can accordingly proceed to step **306**.

[0052] At step **306**, the routine **300** determines whether the temperature of the memory device determined at step **301** is greater than or equal to a second threshold temperature value. In some embodiments, the second threshold temperature value can be a temperature above (and/or at) which there is concern that data retention issues will arise if the memory device is not regularly refreshed according to a specified refresh rate (e.g., according to the 1X refresh mode). For example, the second threshold temperature value can be between about 45° C. and about 60° C. If the routine **300** determines that the temperature of the memory device is greater than or equal to the second threshold temperature value, the routine **300** can accordingly proceed to step **307** to skip a first number of refresh operations. In some embodiments, the first number of refresh operations corresponds to skipping half of the refresh commands received by the memory device in accordance with the 2X refresh mode. Thus, the routine **300** can execute a refresh operation for every other refresh command (or another pattern of refresh commands) received by the memory device to effectively refresh the memory device in accordance with the 1X refresh mode. As a specific example, in response to receiving a first refresh command directing the memory device to execute a refresh operation, the memory device can execute a refresh operation. In response to receiving a second refresh command directing the memory device to execute a refresh operation,

however, the memory device ignores and/or masks the second refresh command such that the memory device refrains from executing a refresh operation. In other embodiments, the first number of refresh operations can correspond to skipping a different number of refresh commands received by the memory device in accordance with the 2X refresh mode.

[0053] In some embodiments, the routine **300** track refresh commands received by the memory device. For example, the routine **300** can (i) use a counter (e.g., a register of the memory device) to track whether a last refresh command received by the memory device was executed or ignored, (ii) use a value of the counter to determine whether to perform a refresh operation in response to receiving a current refresh command, and/or (iii) update the value of the counter accordingly after skipping or executing the current refresh command. As another example, when skipping every nth refresh command, the routine **300** can (i) use a counter to track how many refresh operations have been executed in response to receiving refresh commands, (ii) skip executing a refresh operation in response to receiving a refresh command after a value of the counter reaches $n-1$, and (iii) reset the value of the counter to zero after skipping a refresh operation in response to receiving the nth refresh command. In these and other embodiments, the routine **300** can use more than one counter to skip various patterns of refresh operations. For example, the routine **300** can (i) use a first counter to refrain from executing a refresh operation in response to receiving every other refresh command and (ii) use a second counter to refrain from executing an additional one of every three refresh operations that would otherwise be executed in response to receiving every other refresh command when monitoring only the first counter.

[0054] Referring again to block **306**, if the routine **300**, on the other hand, determines that the temperature of the memory device is not greater than or equal to the second threshold temperature value, the routine **300** can accordingly proceed to step **308** to skip a second number of refresh operations. The second number of refresh operations can be greater than the first number of refresh operations. For example, the second number of refresh operations can correspond to skipping every other refresh command received by the memory device in accordance with the 2X refresh mode, as well as skipping an additional one of every three refresh commands that would otherwise be executed by the routine **300** at step **307**. Continuing with this example, for every group of six consecutive refresh commands received by the memory device, the routine **300** can skip the sixth refresh command received by the memory device in addition to the first, third, and fifth refresh commands received by the memory device. In other words, the routine **300** (at step **308**) in this example would execute two of every three refresh commands that would otherwise be executed by the routine **300** at step **307**. In other embodiments, the second number of refresh operations can correspond to skipping a different number and/or pattern of refresh commands received by the memory device in accordance with the 2X refresh mode.

[0055] Returning again to step **303**, if the routine **300** determines that the memory device is receiving refresh commands at a frequency consistent with the 1X refresh mode (step **303**, “N”), the routine **300** proceeds to step **309**. At step **309**, the routine **300** determines whether the temperature of the memory device determined at step **301** is greater than or equal to a third threshold temperature value. In some embodiments, the third threshold temperature value can be a temperature above (and/or at) which there is concern that data retention issues will arise if the memory device is not regularly refreshed according to a specified refresh rate (e.g., according to the 1X refresh mode). For example, the third threshold temperature value can be the same as second threshold temperature value. In other embodiments, the third threshold temperature value can be a different threshold temperature value than the second threshold temperature value.

[0056] If the routine **300** determines that the temperature of the memory device is greater than or equal to the third threshold temperature value, the routine **300** can accordingly proceed to step **310** to refresh the memory device according to the 1X refresh mode. In other words, the routine **300** can execute a refresh operation for every refresh command received by the memory device. On the other hand, if the routine **300** determines that the temperature of the memory device determined at

step **301** is not greater than or equal to the third threshold temperature value, the routine can accordingly proceed to step **311**.

[0057] At step **311**, the routine **300** skips a third number of refresh commands received by the memory device. In some embodiments, the third number of refresh operations corresponds to skipping one third of the refresh commands received by the memory device in accordance with the 1X refresh mode. Thus, in these embodiments, the routine **300** can skip every third (or another pattern) of refresh commands received by the memory device. In other embodiments, the third number of refresh operations can correspond to skipping a different number of refresh commands received by the memory device in accordance with the 1X refresh mode.

[0058] Although the steps **301-311** of the routine **300** are discussed and illustrated in a particular order, the method illustrated by the routine **300** in FIG. 3 is not so limited. In other embodiments, the steps **301-311** can be performed in a different order. For example, any of the steps **301-311** of the routine **300** can be performed before, during, and/or after any of the other steps **301-311** of the routine **300**. As a specific example, step **302** and/or step **303** can be performed before and/or during step **301**. Moreover, a person of ordinary skill in the relevant art will readily recognize that the illustrated method can be altered and still remain within these and other embodiments of the present technology. For example, one or more of the steps **301-311** of the routine **300** illustrated in FIG. 3 can be omitted and/or repeated in some embodiments. As a specific example, steps **306** and/or step **308** can be omitted in some embodiments such that the routine **300** proceeds to step **307** after determining that the temperature of the memory device is not greater than or equal to the first threshold temperature. As another specific example, steps **309** and/or step **311** can be omitted in some embodiments such that the routine **300** proceeds to step **310** after determining that the refresh scheme is not the 2X refresh mode at step **303**. In these and other embodiments, one or more of the steps **301-311** of the routine **300** can be combined (at least in part). In these and still other embodiments, the routine **300** can include additional steps than shown in FIG. 3. For example, the routine **300** can compare the temperature of the memory device determined at step **301** to one or more additional threshold temperatures (e.g., one or more additional threshold temperatures above and/or below the first, second, and/or third threshold temperatures) and/or can accordingly skip different numbers of refresh operations (e.g., numbers greater than and/or less than the first, second, and/or third numbers of refresh operations) based, at least in part, on the additional comparisons.

[0059] FIG. 4 is a flow diagram illustrating a routine **400** of a memory device configured in accordance with various embodiments of the present technology. The routine **400** is illustrated as a set of steps, blocks, operations, or processes **410**, **420**, and **430**. In some embodiments, one or more of the steps **410**, **420**, and **430** may be implemented, at least in part, in the form of executable code stored on non-transitory, tangible, machine readable media. All or a subset of the steps **410**, **420**, and **430** of the routine **400** can be executed, at least in part, by various components of a memory device (e.g., a memory device **104** of FIG. 1 and/or a memory device **104/200** of FIGS. 1 and 2). In these and other embodiments, one or more of the steps **410**, **420**, and **430** can be executed, at least in part, by one or more components of a memory system, such as a memory controller, a PCB, a package substrate, and/or a memory die. In these and still other embodiments, one or more of the steps **410**, **420**, and **430** can be executed, at least in part, by a host device operably connected to the memory system, by a manufacturer, by an end user, or by an intermediary party.

[0060] The routine **400** begins at block **410** by determining a temperature of the memory device. In some embodiments, the routine **400** determines a temperature of the memory device using one or more temperature measurements generated by a temperature sensor internal to the memory device.

[0061] At block **420**, the routine **400** continues by determining a frequency at which refresh commands are being received by and/or sent to the memory device. In some embodiments, the routine **400** determines the frequency by receiving a notification indicating the frequency. For example, the routine **400** can receive the notification via one or more address bits in address signals

received by the memory device (e.g., when the memory device registers a refresh command, after a mode register of the memory device is programmed to place the memory device into a refresh mode, etc.). Continuing with this example, the routine **400** can determine the frequency by monitoring the one or more address bits in the address signals. In one embodiment, the routine **400** can determine the frequency is a first frequency when a specified address bit in the address signals received by the memory device is in a first state (e.g., a “low” or “0” state), and can determine the frequency is a second frequency when the specified address bit is in a second state (e.g., a “high” or “1” state).

[0062] At block **430**, the routine **400** continues by skipping refresh operations based, at least in part, on the temperature of the memory device determined at block **410** and on the frequency at which the memory device is receiving and/or is being sent refresh commands. For example, when the memory device is receiving refresh commands at a higher frequency, the routine **400** can (i) skip a first number (e.g., zero) of refresh operations when the temperature is at or above a first threshold temperature value, (ii) skip a second number of (e.g., corresponding to every other) refresh operations when the temperature is below the first threshold temperature value, and/or (iii) skip a third number (e.g., greater than the second number) of refresh operations when the temperature is below a second threshold temperature value (e.g., less than the first threshold temperature value). Additionally, or alternatively, when the memory device is receiving refresh commands at a lower frequency, the routine **400** can (i) skip a first number (e.g., zero) of refresh operations when the temperature is below the first threshold temperature value and/or (ii) skip a second number (e.g., greater than the first number, corresponding to every third, etc.) of refresh operations when the temperature is below a second threshold temperature value (e.g., less than the first threshold temperature value). In some embodiments, skipping refresh operations includes (i) receiving one or more refresh commands directing the memory device to execute one or more refresh operations and (ii) in response to receiving the one or more refresh commands, refraining from executing at least a subset of the one or more refresh operations.

[0063] Although the steps **410**, **420**, and **430** of the routine **400** are discussed and illustrated in a particular order, the method illustrated by the routine **400** in FIG. **4** is not so limited. In other embodiments, the steps **410**, **420**, and **430** can be performed in a different order. For example, any of the steps **410**, **420**, and **430** of the routine **400** can be performed before, during, and/or after any of the other steps **410**, **420**, and **430** of the routine **400**. As a specific example, step **420** can be performed before and/or during step **410**. Moreover, a person of ordinary skill in the relevant art will readily recognize that the illustrated method can be altered and still remain within these and other embodiments of the present technology. For example, one or more of the steps **410**, **420**, and **430** of the routine **400** illustrated in FIG. **4** can be omitted and/or repeated in some embodiments. In these and other embodiments, one or more of the steps **410**, **420**, and **430** of the routine **400** can be combined (at least in part). In these and still other embodiments, the routine **400** can include additional steps than shown in FIG. **4**.

[0064] FIGS. **3** and **4** and the corresponding discussion above assumes that a single refresh operation executed in response to a single refresh command received by a memory device refreshes every memory cell in a memory array of the memory device. Refresh operations executed in response to a single refresh command in other embodiments, however, can refresh a single memory region representing a subset of the memory cells in the memory array of the memory device. For example, a single refresh operation executed in response to receiving a single refresh command in some embodiments can refresh a single memory bank in every memory bank group of the memory array. In these embodiments, the routine **300** of FIG. **3** and/or the routine **400** can skip greater numbers of refresh operations received by the memory device to achieve a desired refresh rate of the entire memory array. For example, the routine **300** can skip greater number of refresh operations received by the memory device at steps **307**, **308**, and/or **311** to achieve a desired refresh rate of the entire memory array. For the sake of clarity and understanding, consider the following

numerical example. Assuming that the memory array of a memory device includes four memory banks arranged in four memory bank groups, the memory device would need to execute four refresh operations in response to receiving four consecutive refresh commands to refresh the entire memory array. Thus, in this example, each executed refresh operation refreshes a single memory bank in every memory bank group. Therefore, to skip the first number (e.g., half) of the refresh operations, the routine **300** at step **307** could alternate between (i) executing four refresh operations in a row in response to receiving four consecutive refresh commands and (ii) skipping four refresh operations in a row in response to receiving the next four consecutive refresh commands.

[0065] FIG. **5** is a schematic view of a system that includes a memory device configured in accordance with various embodiments of the present technology. Any one of the foregoing memory systems, devices, and/or dies described above with reference to FIGS. **1-4** can be incorporated into any of a myriad of larger and/or more complex systems, a representative example of which is system **590** shown schematically in FIG. **5**. The system **590** can include a semiconductor device assembly **500**, a power source **592**, a driver **594**, a processor **596**, and/or other subsystems and components **598**. The semiconductor device assembly **500** can include features generally similar to those of the memory systems, devices, and/or dies described above with reference to FIGS. **1-4**, and can, therefore, include various features of programmable die refresh stagger. The resulting system **590** can perform any of a wide variety of functions, such as memory storage, data processing, and/or other suitable functions. Accordingly, representative systems **590** can include, without limitation, hand-held devices (e.g., mobile phones, tablets, digital readers, and digital audio players), computers, vehicles, appliances, and other products. Components of the system **590** may be housed in a single unit or distributed over multiple, interconnected units (e.g., through a communications network). The components of the system **590** can also include remote devices and any of a wide variety of computer readable media.

Conclusion

[0066] The above detailed descriptions of embodiments of the technology are not intended to be exhaustive or to limit the technology to the precise form disclosed above. Although specific embodiments of, and examples for, the technology are described above for illustrative purposes, various equivalent modifications are possible within the scope of the technology, as those skilled in the relevant art will recognize. For example, while steps are presented and/or discussed in a given order, alternative embodiments can perform steps in a different order. Furthermore, the various embodiments described herein can also be combined to provide further embodiments.

[0067] From the foregoing, it will be appreciated that specific embodiments of the technology have been described herein for purposes of illustration, but well-known structures and functions have not been shown or described in detail to avoid unnecessarily obscuring the description of the embodiments of the technology. Where the context permits, singular or plural terms can also include the plural or singular term, respectively. Moreover, unless the word “or” is expressly limited to mean only a single item exclusive from the other items in reference to a list of two or more items, then the use of “or” in such a list is to be interpreted as including (a) any single item in the list, (b) all of the items in the list, or (c) any combination of the items in the list. Where the context permits, singular or plural terms can also include the plural or singular term, respectively. Additionally, the terms “comprising,” “including,” “having” and “with” are used throughout to mean including at least the recited feature(s) such that any greater number of the same feature and/or additional types of other features are not precluded. As used herein, the phrase “and/or” as in “A and/or B” refers to A alone, B alone, and both A and B.

[0068] From the foregoing, it will also be appreciated that various modifications can be made without deviating from the technology. For example, various components of the technology can be further divided into subcomponents, or that various components and functions of the technology can be combined and/or integrated. Furthermore, although advantages associated with certain embodiments of the technology have been described in the context of those embodiments, other

embodiments can also exhibit such advantages, and not all embodiments need necessarily exhibit such advantages to fall within the scope of the technology. Accordingly, the disclosure and associated technology can encompass other embodiments not expressly shown or described herein.

Claims

1. A double data rate (DDR) memory device, comprising: a plurality of memory cells; a mode register configured to indicate a refresh mode of the DDR memory device from among two or more candidate refresh modes, the refresh mode associated with a first frequency; and a sensor configured to measure a temperature of the DDR memory device, wherein the DDR memory device is configured to perform, based at least in part on the refresh mode of the DDR memory device, one or more refresh operations in accordance with a second frequency different from the first frequency, the second frequency based at least in part on the temperature of the DDR memory device.
2. The DDR memory device of claim 1, wherein the two or more candidate refresh modes comprises at least a first refresh mode and a fine granular refresh (FGR) mode.
3. The DDR memory device of claim 1, wherein: the one or more refresh operations are performed in accordance with the second frequency based at least in part on the temperature being less than a threshold temperature; and the threshold temperature is 85 degrees Celsius.
4. The DDR memory device of claim 1, wherein the DDR memory device is configured to: receive an indication of the first frequency associated with a frequency at which refresh commands are received at the DDR memory device, wherein performing the one or more refresh operations is based at least in part on the indication.
5. The DDR memory device of claim 1, wherein DDR memory device is configured to: receive a refresh command comprising a command address bit signal that indicates the first frequency.
6. The DDR memory device of claim 1, wherein the second frequency is half of the first frequency.
7. The DDR memory device of claim 1, wherein the DDR memory device is further configured to: receive a command for programming a value of the mode register; and operate in the refresh mode based at least in part on the value of the mode register.
8. A method, comprising: monitoring a mode register of a data double rate (DDR) memory device, wherein a value of the mode register indicates a refresh mode of the DDR memory device from among two or more candidate refresh modes, the refresh mode associated with a first frequency; measuring, using a sensor of the DDR memory device, a temperature of the DDR memory device; and performing, based at least in part on the refresh mode of the DDR memory device, one or more refresh operations in accordance with a second frequency different from the first frequency, the second frequency based at least in part on the temperature of the DDR memory device.
9. The method of claim 8, wherein the two or more candidate refresh modes comprises at least a first refresh mode and a fine granular refresh (FGR) mode.
10. The method of claim 8, wherein: the one or more refresh operations are performed in accordance with the second frequency based at least in part on the temperature being less than a threshold temperature; and the threshold temperature is 85 degrees Celsius.
11. The method of claim 8, further comprising: receiving an indication of the first frequency associated with a frequency at which refresh commands are received at the DDR memory device, wherein performing the one or more refresh operations is based at least in part on the indication.
12. The method of claim 8, further comprising: receiving a refresh command comprising a command address bit signal that indicates the first frequency.
13. The method of claim 8, wherein the second frequency is half of the first frequency.
14. The method of claim 8, further comprising: receiving a command for programming the value of the mode register; and operating in the refresh mode based at least in part on the value of the mode register.

- 15.** A non-transitory computer-readable medium storing code, the code comprising instructions executable by one or more processors to: monitor a mode register of a data double rate (DDR) memory device, wherein a value of the mode register indicates a refresh mode of the DDR memory device from among two or more candidate refresh modes, the refresh mode associated with a first frequency; measure, using a sensor of the DDR memory device, a temperature of the DDR memory device; and perform, based at least in part on the refresh mode of the DDR memory device, one or more refresh operations in accordance with a second frequency different from the first frequency, the second frequency based at least in part on the temperature of the DDR memory device.
- 16.** The non-transitory computer-readable medium of claim 15, wherein the two or more candidate refresh modes comprises at least a first refresh mode and a fine granular refresh (FGR) mode.
- 17.** The non-transitory computer-readable medium of claim 15, wherein: the one or more refresh operations are performed in accordance with the second frequency based at least in part on the temperature being less than a threshold temperature; and the threshold temperature is 85 degrees Celsius.
- 18.** The non-transitory computer-readable medium of claim 15, wherein the instructions are further executable by the one or more processors to: receive an indication of the first frequency associated with a frequency at which refresh commands are received at the DDR memory device, wherein performing the one or more refresh operations is based at least in part on receiving the indication.
- 19.** The non-transitory computer-readable medium of claim 15, wherein the instructions are further executable by the one or more processors to: receive a refresh command comprising a command address bit signal that indicates the first frequency.
- 20.** The non-transitory computer-readable medium of claim 15, wherein the second frequency is half of the first frequency.
-