

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391338
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Kapsaskis; Christopher et al.

Bilge system

Abstract

A bilge pump system for removing residual fluid from a vessel surface, includes at least one collection unit having a collection base with a collection inlet and a collection outlet, and a pump having a pump inlet flow-connected by at least one tube to the collection outlet. A discharge tube is flow-connected to the pump outlet, wherein the collection inlet comprises at least one opening on a bottom face of the collection base arranged to be on the vessel surface. A sponge is arranged within the opening of the collection base and in liquid communication with the vessel surface. The sponge can be fitted into place by lips or lugs protruding from the collection base.

Inventors: Kapsaskis; Christopher (Freehold, NJ), Cirillo; Joseph (Manalapan, NJ), Grassi; Zachary (Freehold, NJ), Kosowski; John (Oak Brook, IL), Yaoru; Ye (Xiamen, CN)

Applicant: SEAFLO Marine & RV North America LLC (South Bend, IN)

Family ID: 1000008766473

Assignee: Seaflo Marine & RV North America, LLC (South Bend, IN)

Appl. No.: 18/241931

Filed: September 04, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240208613 A1	Jun. 27, 2024

Related U.S. Application Data

continuation parent-doc US 16442041 20190614 US 11745830 child-doc US 18241931

Publication Classification

Int. Cl.: **B63B13/00** (20060101); **B63J4/00** (20060101); **F04B11/00** (20060101); **F04B43/02** (20060101); **F04B49/02** (20060101); **F04D13/08** (20060101); **F04D29/70** (20060101)

U.S. Cl.:

CPC **B63B13/00** (20130101); **B63J4/002** (20130101); **F04B11/0016** (20130101); **F04B43/02** (20130101); **F04B49/02** (20130101); **F04D29/708** (20130101); **F04D13/08** (20130101)

Field of Classification Search

CPC: B63B (13/00); F04B (43/02); F04B (11/0016); F04B (49/02); B63J (4/002); F04D (13/08); F04D (29/708)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2977922	12/1960	Skovranek	417/297.5	B63B 13/00
3007430	12/1960	Breneman	114/183A	F03B 13/20
3946694	12/1975	Belsky	440/88P	F04B 53/1037
6837174	12/2004	Baurley	114/183R	F04F 1/02
11745830	12/2022	Kapsaskis	114/183R	F04B 53/005

Primary Examiner: Bertheaud; Peter J

Attorney, Agent or Firm: Erickson Law Group, PC

Background/Summary

(1) This application is a continuation of US Ser. No. 16/442,041, filed Jun. 14, 2019.

BACKGROUND

(1) Vessels, such as boats or ships can have a bilge pump for removing water collecting on a bottom of the vessel. However, most bilge pumps are impeller pumps which are flooded suction pumps, and leave a residual amount of water in the compartment. This residual water can lead to mold, mildew, mustiness, odors, rot and can affect hull integrity.

(2) U.S. Pat. No. 6,837,174 discloses a pneumatic bilge liquid removal system including an air compressor having inlet and outlet ports pneumatically coupled to a valve system. The air compressor pressurizes a collection chamber via the outlet port causing the bilge liquid in the collection chamber to discharge through the discharge tube. Then, the air compressor creates a negative pressure in the collection chamber via the inlet port causing any bilge liquid to be drawn into and accumulate in the collection chamber via collection tubes. This is a somewhat complicated system that requires an air compressor, a controlled valve system and a collection chamber.

(3) The present inventors have realized that it would be desirable to provide a bilge pump system that is useful to empty the residual amount of water in a boat's bilge, or other water containing compartments.

(4) The present inventors have recognized the desirability to provide such a bilge pump system that did not have the drawbacks of the prior systems, is cost effectively manufactured, and is more easily operated and maintained.

SUMMARY

(5) The exemplary embodiments of the invention provide a bilge pump system for removing residual fluid from a vessel surface, including at least one collection unit having a collection base with a collection inlet and a collection outlet, and a pump having a pump inlet flow-connected by at least one tube to the collection outlet. A discharge tube is flow-connected to the pump outlet, wherein the collection inlet comprises at least one opening on a bottom face of the collection base arranged to be on the vessel surface.

(6) The bilge pump system advantageously includes a sponge arranged within the opening of the collection base and in liquid communication with the vessel surface. The sponge can be fitted into place by lips or lugs protruding from the collection base.

(7) The collection base can include a check valve to prevent backflow into the collection base.

(8) The pump can advantageously be a diaphragm pump.

(9) A user-programmable timer switch can be used to turn on and off the pump.

(10) A single pump can be flow connected to multiple collection units. A control valve can be arranged between each collection unit and the pump inlet. The control valve can be pneumatic, electric, or a solenoid valve.

(11) The embodiments of the present invention provide a residual bilge pump system that is effective to remove residual liquid from a vessel beyond that which is removed by a primary bilge pump. For example, the embodiment of the present invention provides a residual bilge pump system that is effective to remove residual water from a boat or ship beyond that which is removed by a primary bilge pump.

(12) The embodiments of the present invention can use a diaphragm pump activated by a user-programmable timer to evacuate the residual amount of bilge water, through a small diameter tube connected to a suction foot attached to a weighted collection base incorporating a sponge. The small diameter tube is connected to a suction unit. The suction unit uses a self-priming diaphragm pump to suction the liquid entering the collection base into the small diameter tube to be discharged. The suction unit can suction from a great distance away from the collection base.

(13) Advantageously the timer is built into the suction unit. This allows the user to activate the pump for as many minutes as desired. For example a user can select as many as 16 activations a day, to as little as one activation per week. This allow the user to custom tailor activation to their vessel's need. The timer can be hidden behind a water-tight lid with an o-ring gasket. This suction unit can discharge residual water overboard via a thru hull, or discharge the residual water into a holding container.

(14) Numerous other advantages and features of the present invention will become readily apparent from the following detailed description of the invention and the embodiments thereof, from the claims and from the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a bilge pump system according to an embodiment of the invention;

(2) FIG. 2 is a schematic view of the system shown in FIG. 1;

(3) FIG. 3 is a plan view of the system shown in FIG. 1; and

(4) FIG. 4 is an elevation view of the system shown in FIG. 1, taken from line 4-4 of FIG. 3;

(5) FIG. 5 is a schematic view of an alternate bilge pump system according to an alternate

embodiment of the invention.

DETAILED DESCRIPTION

(6) While this invention is susceptible of embodiment in many different forms, there are shown in the drawings, and will be described herein in detail, specific embodiments thereof with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the invention to the specific embodiments illustrated.

(7) This application incorporates by reference US Ser. No. 16/442,041, filed Jun. 14, 2019, in its entirety.

(8) FIGS. 1-4 illustrate one embodiment of a bilge pump system **10** according to the invention. The system includes a suction unit **16**, connected to a collection unit **20**, by suction tubes **24**, **26**. The suction unit **16** is connected to a discharge tube **28**. A pneumatic, electric, or solenoid operated valve **32** can be flow connected between the suction tubes **24**, **26**. The solenoid valve is useful if more than one collection unit **20** is used. For one collection unit **20**, the solenoid valve can be eliminated and a single suction tube **24** can connect the collection unit **20** to the suction unit **16**.

(9) The collection unit **20** includes a collection base **34** with a weight **36** built in (encapsulated in ultrasonically welded plastic) to help hold the base down onto the floor if it is not attached. The top of the collection base **34** can use a "¼" PUSH FIT" fitting **40**, which allows the suction tube **24**, such as a ¼" tube, to easily be installed onto the collection base **34** by just forcing it in with a user's hand, without need for a tool. The collection base can also incorporate a check-valve **42**. The check valve **42** ensures liquid that has moved past the collection base, does not drip back down into the collection base. The base also incorporates two lugs **44**, **46** with holes which allows for screw-down mounting of the base. The collection base also incorporates two bosses **48**, **49** that each accept a screw, for different attaching methods and brackets for securing the collection base.

(10) A strainer **52** is used to catch any debris that may have made it past the collection base, and prevents debris from being sucked into the suction unit **16**, preventing damage. The suction tubes can use "¼" PUSH FIT" fittings, which allows ¼" line to easily be installed onto the strainer by just forcing it in by hand without the need for a tool.

(11) The collection base **34** has an open bottom face **54** that is closed by a sponge **56**. The sponge can be held in place in the base **34** by lugs or lips **51**, **52** protruding inward from the base. The sponge enhances the collection of water or other fluid that otherwise would be very shallow on the vessel surface. The base has peripheral holes **57** exposing the sponge to allow water to reach the sponge.

(12) The suction unit **16** shown in FIG. 2 includes a housing **58** containing a self-priming diaphragm pump **62**, a timer **66**, a check valve **70**, an electrical connection **72** for the pump **62**, an internal suction tube **78** and an internal discharge tube **79**. The pump **62** suctions the liquid entering the collection base **34** through the sponge **56**, through the check valve **42**, through the suction tubes **24**, **26** and solenoid valve **32** if present, through the strainer **52**, through the internal suction tube **78**, through the pump **62**, through the internal discharge tube **79** and the check valve **70**, through the outlet **80**, and through the discharge tube **28** to an external collection location to be disposed of or collected. The housing **58** can include flanges **92**, **94** (FIG. 2) having screw holes for attaching the housing to a floor or wall or bracket or four feet **95a**, **95b**, **95c**, **95d** (FIGS. 1, 3 and 4) with screw holes for attaching the housing to a floor or wall or bracket.

(13) The suction unit **16** can be configured to effectively suction liquid from the collection base **34** from over 25 feet away from the collection base **34**. The diaphragm pump **62** can be activated by a timer **66** that can be built into the unit **16**. This timer is user-programmable. This allows the user to activate the pump **62** for as many minutes as desired, such as 16 activations a day, to as little as one activation per week. This allows the user to custom tailor activation to their vessel's need. This timer **66** can be hidden behind a water-tight lid **72** with a o-ring gasket **76**. A discharge outlet **80** of the unit **16** can be a ½" barbed fitting connected to the discharge tube **28**, which can be a ½ inch tube. The tube **28** can be discharged overboard via a thru hull, collected into a holding container, or

otherwise removed from the vessel floor.

(14) FIG. 5 illustrates an enhanced system **100** wherein multiple suction tubes **26** (four shown) are connected to a manifold **110** that is connected to multiple pneumatic, electric, or solenoid operated valves **32** (four shown) that are connected to multiple suction tubes **24** (four shown), each tube connected to a collection unit **20** (four shown). In this way, different surfaces of a vessel that are likely to collect water or other fluid can be serviced by plural collection units **20** and only one suction unit **16**. The solenoid operated valves **32** can be controlled to connect suction to one collection unit **20** at a time, or combinations of collection units **20** at a time.

(15) From the foregoing, it will be observed that numerous variations and modifications may be effected without departing from the spirit and scope of the invention. It is to be understood that no limitation with respect to the specific apparatus illustrated herein is intended or should be inferred.
US

Claims

1. A bilge pump system for removing residual fluid from a vessel surface, comprising: a collection unit having a collection base with a collection inlet and a collection outlet, an electrically-driven diaphragm pump having a pump inlet flow-connected by at least one tube to the collection outlet, a pump outlet, and a discharge tube flow-connected to the pump outlet, wherein the collection inlet comprises at least one opening on a bottom face of the collection base arranged to be on the vessel surface, and a user-programmable timer to control operation of the electrically-driven diaphragm pump.
2. The bilge pump system according to claim 1, comprising a sponge arranged within the at least one opening of the collection base.
3. The bilge pump system according to claim 2, wherein the sponge is fitted into place by lips or lugs protruding from the collection base.
4. The bilge pump system according to claim 1, wherein the at least one opening comprises a plurality of openings.
5. The bilge pump system according to claim 1, wherein the collection base is weighted.
6. The bilge pump system according to claim 1, wherein the at least one tube between the pump inlet and the outlet of the collection base is affixed with at least one push fit fitting.
7. The bilge pump system according to claim 1, wherein the collection base includes a check valve to prevent backflow into the collection base.
8. The bilge pump system according to claim 1, comprising an inline strainer upstream of the pump inlet to avoid clogging the pump.
9. The bilge pump system according to claim 1, comprising a timer switch in signal communication with the user-programmable timer to turn on and off the pump.
10. The bilge pump system according to claim 1, comprising pneumatic, electric, or solenoid valves, and at least one second collection unit having a second collection base with a second collection inlet and a second collection outlet, the diaphragm pump inlet flow-connected by at least one second tube to the second collection outlet, wherein the second collection inlet comprises at least one second opening on a second bottom face of the second collection base arranged to be on the vessel surface; wherein one of said pneumatic, electric or solenoid valves is flow-connected between the pump inlet and the first collection inlet and between the pump inlet and the second collection inlet in order to select flow from either or both of the first and second collection units.
11. The bilge pump according to claim 1, wherein the pump is enclosed by a housing and the housing also encloses the user-programmable timer.
12. The bilge pump according to claim 11, wherein the housing includes screw-holding protrusions to fasten the housing to an external surface.
13. The bilge pump according to claim 1, comprising multiple collection units, each collection unit

having a collection base with a collection inlet and a collection outlet, the pump inlet flow-connected by multiple tubes to the collection outlets, wherein each collection inlet comprises at least one opening on a bottom face of the collection base arranged to be on the vessel surface.

14. The bilge pump according to claim 13, further comprising controllable valves each flow connected between the pump inlet and one collection outlet.
