

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12395734
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Ogura; Hideki et al.

---

### Image capture apparatus and control method thereof

---

#### Abstract

An image capture apparatus detects a subject area from an image that has been shot and enlarges a focus detection area in a case where the subject area is not detected or a reliability that the detected subject area corresponds to an intended subject is determined to be low. The image capture apparatus enlarges the focus detection area based on the distances previously obtained by the obtainment unit.

---

**Inventors:** Ogura; Hideki (Kanagawa, JP), Kanda; Akihiko (Kanagawa, JP), Yashima; Hiroshi (Kanagawa, JP), Hamano; Hideyuki (Kanagawa, JP)

**Applicant:** CANON KABUSHIKI KAISHA (Tokyo, JP)

**Family ID:** 1000008764391

**Assignee:** CANON KABUSHIKI KAISHA (Tokyo, JP)

**Appl. No.:** 18/159741

**Filed:** January 26, 2023

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230247290 A1	Aug. 03, 2023

#### Foreign Application Priority Data

JP	2022-015819	Feb. 03, 2022
----	-------------	---------------

---

#### Publication Classification

**Int. Cl.:** H04N23/67 (20230101); G06T7/20 (20170101); G06V10/25 (20220101); G06V10/74 (20220101)

## U.S. Cl.:

CPC     **H04N23/675** (20230101); **G06T7/20** (20130101); **G06V10/25** (20220101); **G06V10/761** (20220101); G06T2207/10148 (20130101)

## Field of Classification Search

**CPC:**     H04N (23/675)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0047941	12/2006	Iwane	348/E5.045	H04N 23/611
2008/0068487	12/2007	Morita	345/428	H04N 23/61
2009/0009651	12/2008	Takayanagi	396/89	H04N 23/673
2009/0095880	12/2008	Otsuki	250/201.2	G02B 7/36
2009/0262230	12/2008	Sugiura	348/E5.022	H04N 5/145
2010/0097484	12/2009	Yata	348/222.1	H04N 23/61
2010/0289937	12/2009	Hada	348/E5.022	H04N 23/635
2013/0002884	12/2012	Nakagawara	348/169	H04N 23/635
2014/0139724	12/2013	Yasuda	348/349	H04N 23/635
2020/0099853	12/2019	Sanno	N/A	H04N 23/675
2021/0203856	12/2020	Hirose	N/A	H04N 23/611
2023/0370714	12/2022	Sanno	N/A	H04N 23/632

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2009-284462	12/2008	JP	N/A
2010072284	12/2009	JP	G02B 7/11

### OTHER PUBLICATIONS

Suzuki et al.; JP-2010072284-A; Focusing Unit for Camera; English Translation; Apr. 2, 2010; pp. 1-9 (Year: 2010). cited by examiner

---

*Primary Examiner:* Segura; Cynthia

*Attorney, Agent or Firm:* Cowan, Liebowitz & Latman, P.C.

---

## Background/Summary

### BACKGROUND OF THE INVENTION

#### Field of the Invention

(1) The present invention relates to an image capture apparatus and a control method thereof, and particularly relates to automatic focus detection (AF) techniques.

#### Description of the Related Art

(2) A subject tracking function is known in which focus detection that tracks the motion of a specific subject is realized by continuously detecting a subject area and setting a focus detection

area to the detected subject area (Japanese Patent Laid-Open No. 2009-284462).

(3) It becomes difficult to continue the subject tracking function when the target subject area is no longer detected. For example, in a swimming scene, the subject tracking function for the face of a swimmer may not work well because the swimmer's head moves in and out of the water, the face is hidden by the hands, and so on.

(4) If the subject tracking function cannot be used, it is necessary to shoot images while changing the shooting range of the camera to follow the motion of the subject such that the area to be focused on (the swimmer's face, in the above example) is located within the focus detection area. This is an operation similar to a panning shot, and is not easy.

#### SUMMARY OF THE INVENTION

(5) The present invention in one aspect provides an image capture apparatus and a control method thereof capable of providing a function that assists in shooting moving subjects for which continuous detection is difficult.

(6) According to an aspect of the present invention, there is provided an image capture apparatus comprising one or more processors that execute a program stored in a memory and thereby function as: a detection unit configured to detect a subject area from an image that has been shot; an obtainment unit configured to obtain a distance in the image between a focus detection area that is set and the subject area detected; and an enlargement unit configured to enlarge the focus detection area in a case where the subject area is not detected or a reliability that the detected subject area corresponds to an intended subject is determined to be low, wherein the enlargement unit enlarges the focus detection area based on the distances previously obtained by the obtainment unit.

(7) According to another aspect of the present invention, there is provided an image capture apparatus comprising one or more processors that execute a program stored in a memory and thereby function as: a motion detection unit configured to detect motion of the image capture apparatus; a determination unit configured to determine whether the image capture apparatus is undergoing a framing action based on the motion of the image capture apparatus; and an enlargement unit configured to enlarge a focus detection area based on the motion of the image capture apparatus in a case where the determination unit determines that the image capture apparatus is undergoing a framing action.

(8) According to a further aspect of the present invention, there is provided a control method executed by an image capture apparatus, the control method comprising: detecting a subject area from an image that has been shot; obtaining a distance between a focus detection area that is set and the subject area detected; and enlarging the focus detection area in a case where the subject area is not detected or a reliability that the detected subject area corresponds to an intended subject is determined to be low, wherein in the enlarging, the focus detection area is enlarged based on the distances previously obtained.

(9) According to another aspect of the present invention, there is provided a control method executed by an image capture apparatus, the control method comprising: detecting motion of the image capture apparatus; determining whether the image capture apparatus is undergoing a framing action based on the motion of the image capture apparatus; and enlarging a focus detection area based on the motion of the image capture apparatus in a case where the image capture apparatus is determined to be undergoing a framing action.

(10) According to a further aspect of the present invention, there is provided a non-transitory machine-readable medium that stores a program for causing a computer of an image capture apparatus to function as: a detection unit configured to detect a subject area from an image that has been shot; an obtainment unit configured to obtain a distance in the image between a focus detection area that is set and the subject area detected; and an enlargement unit configured to enlarge the focus detection area in a case where the subject area is not detected or a reliability that the detected subject area corresponds to an intended subject is determined to be low, wherein the

enlargement unit enlarges the focus detection area based on the distances previously obtained by the obtainment unit.

(11) According to another aspect of the present invention, there is provided a non-transitory machine-readable medium that stores a program for causing a computer of an image capture apparatus to function as: a motion detection unit configured to detect motion of the image capture apparatus; a determination unit configured to determine whether the image capture apparatus is undergoing a framing action based on the motion of the image capture apparatus; and an enlargement unit configured to enlarge a focus detection area based on the motion of the image capture apparatus in a case where the determination unit determines that the image capture apparatus is undergoing a framing action.

(12) Further features of the present invention will become apparent from the following description of exemplary embodiments (with reference to the attached drawings).

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram illustrating an example of the functional configuration of a digital camera serving as an example of an image processing apparatus according to an embodiment.
- (2) FIG. 2 is a diagram schematically illustrating a pixel array according to an embodiment.
- (3) FIGS. 3A and 3B are a schematic plan view and a schematic cross-sectional view of a pixel according to an embodiment.
- (4) FIG. 4 is a diagram illustrating correspondence between a pixel in an image sensor according to an embodiment and a pupil intensity distribution.
- (5) FIGS. 5A and 5B are diagrams illustrating a relationship between a defocus amount and an image shift amount according to an embodiment.
- (6) FIG. 6 is a diagram illustrating a focus detection area according to an embodiment.
- (7) FIG. 7 is a flowchart pertaining to shooting mode operation according to an embodiment.
- (8) FIG. 8 is a flowchart pertaining to image capturing/recording processing according to an embodiment.
- (9) FIG. 9 is a flowchart pertaining to subject tracking AF processing according to an embodiment.
- (10) FIG. 10 is a flowchart pertaining to subject detection/tracking processing according to an embodiment.
- (11) FIG. 11 is a flowchart illustrating processing for setting a focus detection area according to a first embodiment.
- (12) FIGS. 12A to 12C are diagrams illustrating a method for setting a focus detection area according to the first embodiment.
- (13) FIGS. 13A and 13B are diagrams illustrating a method for setting a focus detection area according to the first embodiment.
- (14) FIGS. 14A and 14B are diagrams illustrating a method for setting a focus detection area according to the first embodiment.
- (15) FIGS. 15A and 15B are diagrams illustrating a method for setting a focus detection area according to the first embodiment.
- (16) FIG. 16 is a chart showing settings for a focus detection area according to the first embodiment.
- (17) FIG. 17 is a flowchart illustrating predictive AF processing according to the first embodiment.
- (18) FIGS. 18A and 18B are diagrams illustrating an image plane shift amount of a subject and a prediction curve according to the first embodiment.
- (19) FIG. 19 is a flowchart illustrating processing for setting a focus detection area according to a second embodiment.

- (20) FIGS. **20A** to **20C** are diagrams illustrating examples of framing by a skilled photographer.
- (21) FIGS. **21A** to **21C** are diagrams illustrating examples of framing by a unskilled photographer.
- (22) FIGS. **22A** and **22B** are diagrams illustrating different examples of scenes to be shot according to the second embodiment.
- (23) FIGS. **23A** and **23B** are diagrams illustrating a method for setting a focus detection area according to the second embodiment.
- (24) FIGS. **24A** and **24B** are diagrams illustrating a method for setting a focus detection area according to the second embodiment.
- (25) FIGS. **25A** and **25B** are diagrams illustrating a method for setting a focus detection area according to the second embodiment.
- (26) FIGS. **26A** and **26B** are diagrams illustrating a method for setting a focus detection area according to the second embodiment.
- (27) FIGS. **27A** and **27B** are diagrams illustrating a method for setting a focus detection area according to the second embodiment.

## DESCRIPTION OF THE EMBODIMENTS

(28) Hereinafter, embodiments will be described in detail with reference to the attached drawings. Note, the following embodiments are not intended to limit the scope of the claimed invention. Multiple features are described in the embodiments, but limitation is not made to an invention that requires all such features, and multiple such features may be combined as appropriate.

Furthermore, in the attached drawings, the same reference numerals are given to the same or similar configurations, and redundant description thereof is omitted.

(29) Note that the following embodiments will describe a case where the present invention is applied in an image capture apparatus such as a digital camera. However, an image capture function is not essential to the present invention, and the present invention can be implemented in any electronic device. Examples of such an electronic device include computer devices (personal computers, tablet computers, media players, PDAs, and the like), mobile phones, smartphones, game consoles, robots, drones, and dashboard cameras. These are merely examples, however, and the present invention can be applied in other electronic devices as well.

(30) Overall Configuration

(31) FIG. **1** is a block diagram illustrating an example of the functional configuration of a digital camera **100** serving as an example of an image processing apparatus according to the present embodiment. The digital camera **100** (called simply a “camera **100**” hereinafter) has an image capturing optical system which includes a first lens group **101**, an aperture stop **102**, a second lens group **103**, and a third lens group **105**, and which forms an optical image of a subject on an image capturing plane of an image sensor **107**.

(32) The first lens group **101** is located closest to the front (the subject side) of the plurality of lens groups included in the image capturing optical system, and can move along an optical axis OA. The position of the first lens group **101** is controlled by a zoom actuator **111**. The zoom actuator **111** moves the first lens group **101** and the second lens group **103** in tandem in the optical axis direction by driving a cam cylinder (not shown), for example.

(33) The aperture stop **102** has an aperture amount which can be adjusted by an aperture actuator **112**, and functions as a mechanical shutter when capturing still images. Note that a mechanical shutter separate from the aperture stop **102** and a shutter actuator that drives the mechanical shutter may be provided.

(34) The second lens group **103** moves integrally with the aperture stop **102**, as well as in tandem with the first lens group **101** along the optical axis OA. The angle of view of the image capturing optical system (the focal length) is determined according to the positions of the first lens group **101** and the second lens group **103**.

(35) The third lens group **105** is capable of moving along the optical axis OA. The position of the third lens group **105** is controlled by a focus actuator **114**. The focal length of the image capturing

optical system is determined by the position of the third lens group. The third lens group is called a focus lens.

(36) An optical low-pass filter **106** is provided to reduce false colors, moiré, and the like in captured images.

(37) The image sensor **107** is, for example, a CMOS image sensor or CCD sensor image sensor having a rectangular pixel array (also called a “pixel area”) constituted by m pixels in the horizontal direction and n pixels in the vertical direction, arranged two-dimensionally. Each pixel is provided with a color filter based on the primary color Bayer array and an on-chip microlens, for example. Note that the image sensor **107** may be a three-plate color image sensor.

(38) Note that in the present embodiment, the image capturing optical system, the zoom actuator **111**, the aperture actuator **112**, the focus actuator **114**, a focus drive circuit **126**, an aperture drive circuit **128**, and a zoom drive circuit **129** are provided in the camera **100**. However, these constituent elements may be provided in a lens unit which can be attached to and removed from the camera **100**.

(39) A flash **115** is a light source that illuminates the subject. The flash **115** includes a flash emission device that uses a xenon tube, or a light-emitting diode (LED) that emits continuous light. An automatic focus detection (AF) auxiliary light source **116** projects a predetermined pattern image through a projection lens. This improves the focus detection performance for low-luminance or low-contrast subjects.

(40) A CPU **121** controls the operation of the image capture apparatus **100** as a whole. The CPU **121** includes an A/D converter, a D/A converter, a communication interface circuit, and the like. By loading a program stored in a ROM **135** into a RAM **136** and executing the program, the CPU **121** controls each part of the image capture apparatus **100** and realizes the functions of the image capture apparatus **100**, such as automatic focus detection, image capturing, image processing, recording, and the like. Some of the functions realized by the CPU **121** by executing programs may be implemented by hardware circuits separate from the CPU **121**. Reconfigurable circuits such as FPGAs may be used for some of the circuits as well. For example, some calculations may be performed by a dedicated hardware circuit to reduce the time required for the calculations for focus detection (described later).

(41) The communication interface circuit included in the CPU **121** supports one or more standards for wired and wireless communication. The image capture apparatus **100** can communicate with external devices directly or via other devices through the communication interface circuit.

(42) A flash control circuit **122** controls the lighting of the flash **115** in synchronization with image capture operation. An auxiliary light source drive circuit **123** controls the lighting of the AF auxiliary light source **116** in synchronization with focus detection processing. An image sensor drive circuit **124** controls the image capture operation by the image sensor **107**, as well as performing A/D conversion on signals obtained from the image capture operation and transmitting those image signals to the CPU **121**.

(43) An image processing circuit **125** can apply various types of image processing to image data, such as gamma conversion, color interpolation, encoding, decoding, evaluation value generation, detection of feature areas, and the like. Additionally, the image processing circuit **125** obtains posture information of a subject for each subject area detected by a subject detection unit **140** (described later).

(44) The posture information to be obtained by the image processing circuit **125** is assumed to be determined in advance according to the type of the subject. For example, when the subject is a human, the image processing circuit **125** is assumed to obtain the positions of a plurality of joints as the posture information of the subject. The image processing circuit **125** detects the positions of the top of the head, the neck, the shoulders, the elbows, the wrists, the hips, the knees, and the ankles as the positions of the joints, for example. However, the joint positions detected by the image processing circuit **125** may be only some of these, and other joint positions may be detected

as well. In addition to the joint positions, information such as axes connecting joints to each other, the position of the center of gravity of the subject, and the like may be detected as the posture information. The image processing circuit **125** can detect any information on the posture of the subject as the posture information.

(45) The image processing circuit **125** determines a main subject using position information on a detected feature area and the obtained posture information on the subject. The image processing circuit **125** may use a result of determining the main subject in other image processing (e.g., white balance adjustment processing). The image processing circuit **125** stores image data in the RAM **136** in association with the posture information on the subject detected from the image data, the position, size and the like of the feature area, position information on the center of gravity, the face, the pupils, and the like of the subject determined to be the main subject, and the like.

(46) The focus drive circuit **126** drives the focus actuator **114** based on commands, which include drive amounts and drive directions of the focus lens, supplied from the CPU **121**. As a result, the third lens group **105** moves along the optical axis OA, and the focal length of the image capturing optical system changes.

(47) The aperture drive circuit **128** controls the diameter, and the opening and closing, of the aperture stop **102** by driving the aperture actuator **112**. The zoom drive circuit **129** changes the focal length (angle of view) of the image capturing optical system by, for example, driving the zoom actuator **111** in response to a user instruction and moving the first lens group **101** and the second lens group **103** along the optical axis OA.

(48) A display unit **131** includes, for example, a liquid crystal display device (LCD). The display unit **131** displays information pertaining to the image capture mode of the image capture apparatus **100**, a preview image before an image is captured, a confirmation image after an image is captured, an indicator of the focus detection area (sometimes also referred to as an AF frame), a focus state display image during focus detection, or the like.

(49) An operation unit **132** is constituted by a power switch, a release switch, a zoom operation switch, an image capture mode selection switch, and the like. The release switch includes two switches, namely SW1, which turns on when depressed halfway, and SW2, which turns on when fully depressed. A recording medium **133** is, for example, a semiconductor memory card that can be attached to and removed from the image capture apparatus **100**, and still image data and moving image data obtained from capturing are recorded into the recording medium **133**.

(50) Note that if the display unit **131** is a touch screen, a touch panel, a combination of a touch panel and a GUI displayed in the display unit **131**, or the like may be used as the operation unit **132**. For example, the configuration can be such that when a tap operation on the touch panel is detected during a live view display, focus detection is performed using an image area corresponding to the tapped position as the focus detection area.

(51) Note that contrast information of captured image data can also be calculated by the image processing circuit **125**, with the CPU **121** executing contrast AF. In contrast AF, the contrast information is calculated sequentially while moving the focus lens group **105** and changing the focal length of the image capturing optical system, and the focus lens position where the contrast information peaks is set as the in-focus position.

(52) In this manner, the image capture apparatus **100** can perform both image plane-based phase-detection AF and contrast AF, and one of these can be used selectively, or both in combination, according to the situation.

(53) The subject detection unit **140** can be configured using a convolutional neural network (CNN), for example. By configuring a CNN using parameters generated through machine learning (dictionary data), an area of a specific subject present within an image expressed by image data can be detected. The subject detection unit **140** may be implemented using dedicated hardware configured to be capable of executing operation of processing using a CNN at high speeds, such as a graphics processing unit (GPU), a neural processing unit (NPU), or the like.

(54) The machine learning for generating the dictionary data can be implemented using any publicly-known method, such as supervised learning or the like. Specifically, the CNN can be trained using a data set that associates input images with whether a target subject is present in the image, for each of subject types. The trained CNN or the parameters thereof can be stored in a dictionary data storage unit **141** as the dictionary data. Note that the training of the CNN may be performed by a device different from the camera **100**. When a trained CNN is to be used for subject detection processing on a captured image, an image of the same size as the input images used when training the CNN is cut out from the captured image and input to the CNN. The area where a target subject appears can be estimated by inputting the cutout position to the CNN while sequentially changing that cutout position.

(55) Note that the subject area may be detected using another method, such as detecting an object area in the image and then using feature quantities for each type of subject to determine which type of subject the object area is. The configuration of the neural network, the learning method, and the like can be changed according to the detection method which is used.

(56) The subject detection unit **140** can be implemented through any publicly-known method as long as the number, position, size, and reliability of an area estimated to contain a pre-set type of subject can be output with respect to an input image.

(57) By repeatedly applying subject detection processing while switching the dictionary data, the subject detection unit **140** can apply subject detection processing for a plurality of types of subjects to one frame's worth of image data. The CPU **121** can determine the dictionary data to be used in the subject detection processing from among a plurality of instances of dictionary data stored in the dictionary data storage unit **141**, based on priority levels set in advance for the subject types, setting values of the camera **100**, and the like.

(58) The type of the subject may be, for example, a part of the human body, organs of the human body (the face, the pupils, the torso, or the like), or subjects aside from humans (animals, inanimate objects (tools, vehicles, buildings, and the like)), and so on, but is not limited thereto. Separate dictionary data is prepared for subjects having different features.

(59) Dictionary data for detecting a human body may be prepared separately as dictionary data for detecting the human body (contours) and dictionary data for detecting the organs of the human body. The dictionary data for detecting the organs of the human body may be prepared individually for each type of organ.

(60) A motion detection unit **142** is a sensor that detects, for example, an angular velocity around each of x, y, and z axes, and acceleration in the x, y, and z axis directions. The CPU **121** can detect motion of the camera **100** based on the output of the motion detection unit **142**. The detected motion includes motion intended by the photographer, as with framing, and motion not intended by the photographer, as with camera shake. Here, "framing" is an operation that moves the shooting range in a certain direction without changing the angle of view of the camera **100**, including panning and/or tilting. The CPU **121** uses the detected motion of the camera **100** for image stabilization, setting the focus detection area (described later), and the like.

(61) Image Sensor

(62) The pixel array and pixel structure of the image sensor **107** will be described with reference to FIGS. 2 to 3B. The left-right direction in FIG. 2 corresponds to an x direction (a horizontal direction); the up-down direction, to a y direction (a vertical direction); and a direction orthogonal to the x and y directions (perpendicular to the paper), to a z direction (an optical axis direction). The example illustrated in FIG. 2 illustrates the pixel (unit pixel) array of the image sensor **107** in a range of four columns by four rows, and a sub-pixel array in a range of eight columns by four rows.

(63) A two-column by two-row pixel group **200**, for example, has a pixel **200R** having spectral sensitivity to a first color red (R) in an upper-left position, a pixel **200G** having spectral sensitivity to a second color green (G) in upper-right and lower-left positions, and a pixel **200B** having spectral sensitivity to a third color blue (B) in a lower-right position. Furthermore, each pixel (unit



pixel) is divided into two parts in the x direction ( $N_x$  divisions) and one part in the y direction ( $N_y$  divisions) (a division number  $N_{\text{sub.LF}} = N_x \times N_y$ ), and is therefore constituted by a plurality of sub-pixels, namely a first sub-pixel **201** and a second sub-pixel **202** (from a first sub-pixel to an  $N_{\text{sub.LF}}$ -th sub-pixel).

(64) In the example illustrated in FIG. 2, by dividing each pixel of the image sensor **107** into two sub-pixels aligned in the horizontal direction, it is possible to generate a number of viewpoint images equal to the division number  $N_{\text{sub.LF}}$  and a captured image that is a composite of all the viewpoint images from an image signal obtained from a single capture. Note that the pixels may be divided in two directions, and the number of divisions per direction is not limited. As such, it can be said that the viewpoint images are images generated from the signals of some of the plurality of sub-pixels, and the captured image is an image generated from the signals of all the sub-pixels. In the present embodiment, as an example, a pixel period  $P$  of the image sensor **107** in the horizontal and vertical directions is  $6\ \mu\text{m}$ , a horizontal pixel number  $N_{\text{sub.H}} = 6000$ , and a vertical pixel number  $N_{\text{sub.V}} = 4000$ . A total pixel number  $N$  is therefore  $N_{\text{sub.H}} \times N_{\text{sub.V}} = 24$  million. If a horizontal period  $P_{\text{sub.S}}$  of the sub-pixels is  $3\ \mu\text{m}$ , a total sub-pixel number  $N_{\text{sub.S}} = N_{\text{sub.H}} \times (P/P_{\text{sub.S}}) \times N_{\text{sub.V}} = 48$  million.

(65) FIG. 3A is a plan view of one pixel **200G** of the image sensor **107** illustrated in FIG. 2, viewed from a light receiving surface-side (+z side) of the image sensor **107**. The z axis is set in the direction perpendicular to the paper surface in FIG. 3A, and the front side is defined as the positive direction in the z axis. Additionally, the y axis is set in the up-down direction orthogonal to the z axis, and “upward” is defined as the positive direction in the y axis; and the x axis is set in the left-right direction orthogonal to the z axis and y axis, and “rightward” is defined as the positive direction of the x axis. FIG. 3B is a cross-sectional view taken from the -y side along an a-a cut line in FIG. 3A.

(66) As illustrated in FIGS. 3A and 3B, microlenses **305** are formed on the light receiving surface-side (the +z direction) of each pixel **200G**, and incident light is focused by the microlenses **305**. Furthermore, a plurality of photoelectric conversion units having two divisions are formed, with two divisions in the x (horizontal) direction and one division in the y (vertical) direction, for a first photoelectric conversion unit **301** and a second photoelectric conversion unit **302**. The first photoelectric conversion unit **301** and the second photoelectric conversion unit **302** correspond to the first sub-pixel **201** and the second sub-pixel **202**, respectively, in FIG. 2. Described more generally, when the photoelectric conversion unit of each pixel is divided into  $N_x$  divisions in the x direction and  $N_y$  divisions in the y direction, and the division number  $N_{\text{sub.LF}}$  of the photoelectric conversion unit is  $N_{\text{sub.LF}} = N_x \times N_y$ , first to  $N_{\text{sub.LF}}$ -th photoelectric conversion units correspond to the first to  $N_{\text{sub.LF}}$ -th sub-pixels.

(67) The first photoelectric conversion unit **301** and the second photoelectric conversion unit **302** are two independent pn junction photodiodes, constituted by a p-type well layer **300** and two divided n-type layers **301** and **302**. If necessary, the units may surround an intrinsic layer and be formed as a pin structure photodiode. In each pixel, a color filter **306** is formed between the microlens **305**, and the first photoelectric conversion unit **301** and second photoelectric conversion unit **302**. If necessary, the spectral transmittance of the color filter **306** may be changed for each pixel or each photoelectric conversion unit, or the color filter may be omitted.

(68) The light incident on the pixel **200G** is focused by the microlens **305**, further spectrally divided by the color filter **306**, and then received by the first photoelectric conversion unit **301** and the second photoelectric conversion unit **302**, respectively. In the first photoelectric conversion unit **301** and the second photoelectric conversion unit **302**, electrons and holes are produced in pairs according to the amount of light received, and electrons are stored after being separated by a barrier layer. On the other hand, the holes are discharged to the exterior of the image sensor **107** through a p-type well layer connected to a constant voltage source (not shown). The electrons accumulated in the first photoelectric conversion unit **301** and the second photoelectric conversion unit **302** are

transferred to an electrostatic capacitance unit (FD) via a transfer gate and converted into voltage signals.

(69) Note that in the present embodiment, the microlenses **305** correspond to an optical system in the image sensor **107**. The optical system in the image sensor **107** may be configured to use microlenses as in the present embodiment, or may be configured to use a material having a different refractive index, such as a waveguide or the like. Additionally, the image sensor **107** may be a backside-illuminated image sensor having circuits and the like on the surface opposite the surface having the microlenses **305**, or may be a stacked image sensor including some circuits such as the image sensor drive circuit **124**, the image processing circuit **125**, and the like. Materials other than silicon may be used as the semiconductor substrate, and for example, an organic material may be used as the photoelectric conversion material.

(70) Pupil Division

(71) A pupil division function of the image sensor **107** according to the present embodiment will be described next with reference to FIGS. **4** and **5A**.

(72) FIG. **4** illustrates a cross-sectional view of an a-a cross-section of the pixel **200G** arranged in the image sensor **107** of the present embodiment illustrated in FIG. **3A**, seen from the +y side, as well as a pupil plane located a distance Z in the z axis direction (the direction of the optical axis OA) from an image capturing plane **600** of the image sensor **107**. Note that in FIG. **4**, the x axis and the y axis of the cross-sectional view are inverted with respect to FIGS. **3A** and **3B** in order to correspond to the coordinate axes of the exit pupil plane. The image capturing plane **600** of the image sensor **107** is located on an image formation plane of the image capturing optical system.

(73) A pupil intensity distribution (first pupil intensity distribution) **501** is, through the microlens **305**, in a substantially conjugate relationship with the light receiving surface of the first photoelectric conversion unit **301**, a center of gravity position of which is eccentric in the -x direction. Accordingly, the first pupil intensity distribution **501** corresponds to a pupil area in which light can be received by the first sub-pixel **201**. The center of gravity position of the first pupil intensity distribution **501** is eccentric to a +xp side on the pupil plane. Likewise, a pupil intensity distribution (second pupil intensity distribution) **502** is, through the microlens **305**, in a substantially conjugate relationship with the light receiving surface of the second photoelectric conversion unit **302**, a center of gravity position of which is eccentric in the +x direction.

(74) Accordingly, the second pupil intensity distribution **502** corresponds to a pupil area in which light can be received by the second sub-pixel **202**. The center of gravity of the second pupil intensity distribution **502** is eccentric to a -xp side on the pupil plane. A pupil intensity distribution **500** is a pupil area in which light can be received by the entire pixel **200G** when all of the first photoelectric conversion units **301** and the second photoelectric conversion units **302** (the first sub-pixels **201** and the second sub-pixels **202**) are combined. In other words, the first pupil intensity distribution **501** is eccentric to the +xp side on the pupil plane relative to the center of the pupil intensity distribution **500**, and the second pupil intensity distribution **502** is eccentric to the -xp side on the pupil plane relative to the center of the pupil intensity distribution **500**.

(75) Additionally, in FIG. **4**, a pupil area **500** is a pupil area through which light can be received by the entire pixel **200G** when the photoelectric conversion units **301** and the photoelectric conversion units **302** (the first sub-pixels **201** and the second sub-pixels **202**) are all combined.

(76) FIG. **5A** is a schematic diagram illustrating the correspondence relationship between the image sensor and pupil divisions according to the present embodiment. Light fluxes passing through different partial pupil areas, namely a first partial pupil area **501** and a second partial pupil area **502**, are incident on each (image capturing) pixel of the image sensor from an image capturing plane **800** at different angles, and are received by the photoelectric conversion units **301** and **302** divided into  $2 \times 1$ . Although the pupil area is pupil-divided into two in the horizontal direction in the present embodiment, pupil division may also be implemented in the vertical direction if necessary.

(77) Image capturing pixels, each having the first sub-pixel **201** which receives the light flux

passing through the first partial pupil area **501** of the image capturing optical system and the second sub-pixel **202** which receives the light flux passing through the second partial pupil area **502** of the image capturing optical system that is different from the first partial pupil area, are arranged in the image sensor **107**. Accordingly, each image capturing pixel receives a light flux passing through the pupil area **500**, which is a combination of the first partial pupil area **501** and the second partial pupil area **502** of the image capturing optical system.

(78) Note that instead of every pixel of the image sensor **107** having a plurality of photoelectric conversion units (sub-pixels), an image capturing pixel, a pixel having only the first sub-pixel, and a pixel having only the second sub-pixel may be arranged separately. Alternatively, a pixel having two sub-pixels and a pixel having one photoelectric conversion unit for two sub-pixels may be arranged.

(79) In the present embodiment, the image processing circuit **125** generates one instance of phase detection AF image data (a first focus detection signal (an A image)) by concatenating a plurality of signals obtained by adding the outputs of the four first sub-pixels **201** for each unit of repetition of the color filters illustrated in FIG. 2. Additionally, the image processing circuit **125** generates a second focus detection signal (a B image) by concatenating a plurality of signals obtained by adding the outputs of the four second sub-pixels **202** for each unit of repetition of the color filters.

(80) In this manner, the first and second sub-pixels **201** and **202** are used to generate focus detection signals, and are therefore also called focus detection pixels. By adding the outputs of the same type of sub-pixels present within the unit of repetition of the color filters, a signal reflecting the respective color components of R, G, and B is obtained, which can be treated as a luminance signal with little spectral sensitivity bias. Note that when obtaining a captured image, the signal is obtained by adding the output of the first sub-pixel **201** and the output of the second sub-pixel **202** in units of pixels.

(81) Relationship Between Defocus Amount and Image Shift Amount

(82) A relationship between an image shift amount in a pair of focus detection signals (the A image and the B image) generated by the image processing circuit **125**, and a defocus amount of the optical system with respect to the subject (a focus condition) in the present embodiment, will be described next. FIG. 5B is a diagram schematically illustrating the relationship between the defocus amount and an image shift amount between the first focus detection signal (the A image) and the second focus detection signal (the B image). The image sensor **107** is arranged on the image capturing plane **800**, and as described with reference to FIGS. 4 and 5A, the exit pupil of the image capturing optical system is divided into two areas, namely the first partial pupil area **501** and the second partial pupil area **502**.

(83) A magnitude of a defocus amount  $d$  is a distance from an image formation position of the subject to the image capturing plane **800**. When the defocus amount  $d$  is negative ( $d < 0$ ), this indicates a forward focus state in which the image formation position of the subject is on the subject side of the image capturing plane **800**, whereas when the defocus amount  $d$  is positive ( $d > 0$ ), this indicates a rearward focus state in which the image formation position of the subject is on the opposite side of the subject from the image capturing plane **800**. The magnitude of the defocus amount  $d$  is 0 in an in-focus state, in which the image formation position of the subject is located on the image capturing plane **800**. FIG. 5A illustrates an example in which a subject **801** is in an in-focus state ( $d = 0$ ), and a subject **802** is in a forward focus state ( $d < 0$ ). The forward focus state ( $d < 0$ ) and the rearward focus state ( $d > 0$ ) will be collectively referred to as a defocus state ( $|d| > 0$ ).

(84) In the forward focus state ( $d < 0$ ), of the light flux from the subject **802**, a light flux passing through the first partial pupil area **501** (the second partial pupil area **502**) is first focused at a position further on the subject side than the image capturing plane **800**. The light flux then spreads to a width  $\Gamma 1$  ( $\Gamma 2$ ) centered on a center of gravity position  $G 1$  ( $G 2$ ) of the light flux, becoming a blurry image at the image capturing plane **800**. The blurry image is converted into an electrical

signal by the first sub-pixel **201** (the second sub-pixel **202**) in each of the plurality of pixels which receives the light flux. Then, as described above, the phase detection AF unit generates the first focus detection signal (the A image) from the signal from the first sub-pixel **201**, and generates the first focus detection signal (the B image) from the signal from the second sub-pixel **202**. Accordingly, the A image (the B image) is recorded as a subject image in which the subject **802** is blurred at the width  $\Gamma 1$  ( $\Gamma 2$ ) at the center of gravity position  $G1$  ( $G2$ ) on the image capturing plane **800**.

(85) The blur width  $\Gamma 1$  ( $\Gamma 2$ ) of the subject image increases roughly proportionally with an increase in the magnitude of the defocus amount  $d$ . Similarly, a magnitude  $|p|$  of an image shift amount  $p$  of the subject image between the first focus detection signal and the second focus detection signal ( $p$ =a difference between the center of gravity positions of the light fluxes, i.e.,  $G1-G2$ ) also increases roughly proportionally with an increase in the magnitude  $|d|$  of the defocus amount  $d$ . In the rearward focus state ( $d>0$ ), the magnitude  $|d|$  of the defocus amount has a similar relationship with the blur width of the subject image and the image shift amount  $p$ , except that the direction in which the A image and the B image are shifted is opposite from that in the forward focus state.

(86) Accordingly, the magnitude of the image shift amount between the A image and the B image increases with the increase in the magnitude of the defocus amount. The image sensor **107** that generates the first focus detection signal and the second focus detection signal, and the CPU **121** that calculates the defocus amount from the image shift amount  $p$ , function as a focus detection means.

(87) Focus Detection Area

(88) The area, of the pixel area of the image sensor **107**, which is used to generate the first focus detection signal and the second focus detection signal (that is, a focus detection area), will be described next. FIG. **6** illustrates an example of unit focus detection areas set in an effective pixel area **1000** of the image sensor **107**, overlaid with an indicator (an AF frame) of the focus detection areas displayed in the display unit **131** during focus detection. The indicator is displayed in order to inform the user of candidates for the unit focus detection areas that can be set, the unit focus detection area currently set, the unit focus detection area selected by the camera **100**, and the like. The unit focus detection area where the indicator is displayed and the unit focus detection area used by the camera **100** for focus control do not necessarily match.

(89) Although the present embodiment assumes that a total of 25 unit focus detection areas, namely five in the row ( $x$ ) direction and five in the column ( $y$ ) direction, are set, this is merely one example, and a greater or smaller number of unit focus detection areas may be set. The sizes, positions, and spacing of the unit focus detection areas may be different as well.

(90) In FIG. **6**, a unit focus detection area  $n$ -th in the horizontal direction and an  $m$ -th in the vertical direction are denoted as  $A(n,m)$ . In addition, a rectangular frame-shaped indicator representing the  $A(n,m)$  unit focus detection area is denoted as  $I(n,m)$ . The signals obtained from the first sub-pixels **201** and the second sub-pixels **202** in the unit focus detection area are used to generate the A image and the B image used to detect the defocus amount in that unit focus detection area. Additionally, the indicator  $I(n,m)$  is normally displayed superimposed on the live view image.

(91) Here, the unit focus detection area  $A(n,m)$  for which the indicator  $I(n,m)$  is not displayed is used in a supplementary manner when the main subject has left the unit focus detection area  $A(n,m)$  for which the indicator  $I(n,m)$  is displayed.

(92) In the present embodiment, a focus detection area **1001** can be set so as to include the unit focus detection area  $A(n,m)$  for which the indicator  $I(n,m)$  is displayed and the unit focus detection area  $A(n,m)$  for which the indicator  $I(n,m)$  is not displayed. Although the focus detection area **1001** is set so as to encompass all 25 of the unit focus detection areas in FIG. **6**, unit focus detection areas not included in the focus detection area **1001** may be present as well.

(93) When all of the pixels in the effective pixel area **1000** include the first sub-pixel **201** and the second sub-pixel **202**, as in the image sensor **107**, the positions, sizes, and the like of the focus

detection areas may be set dynamically. For example, the focus detection may be performed using an area including a plurality of unit focus detection areas centered on a position specified by the user. In the present embodiment, the unit focus detection areas are set so as to obtain a higher-resolution focus detection result when obtaining a defocus map, which will be described later. For example, each of a total of 9600 areas, obtained by dividing the effective pixel area **1000** into 120 parts in the horizontal direction and 80 parts in the vertical direction, is set as a unit focus detection area. Then, the focus detection area can be set such that the unit focus detection area A in which the indicator I is displayed, and the unit focus detection areas A in the periphery thereof for which the indicator I is not displayed, are included.

(94) Operation in Image Capture Mode

(95) Operational steps performed in an image capture mode of the camera **100** will be described with reference to the flowchart in FIG. 7. The camera **100** operates in the image capture mode when the power is turned on and startup processing is complete.

(96) In the image capture mode, the camera **100** stands by for the input of a user instruction while causing the display unit **131** to function as an EVF by continually capturing a moving image and displaying the obtained moving image in the display unit **131**.

(97) In step S1, the CPU **121** starts driving the image sensor **107** through the image sensor drive circuit **124** to capture a moving image for display in the display unit **131**. Thereafter, the image sensor **107** outputs an analog image signal at a predetermined frame rate.

(98) Upon obtaining one frame's worth of the analog image signal from the image sensor **107**, the CPU **121** applies correlated double sampling, A/D conversion, and the like to generate a digital image signal. The CPU **121** outputs the digital image signal to the image processing circuit **125**. The image processing circuit **125** applies demosaicing and the like to the digital image signal, and generates display image data. The image processing circuit **125** writes the display image data into a video memory region in the RAM **136**, for example. Additionally, the image processing circuit **125** generates, from the digital image signal, evaluation values used in AE processing, and outputs the evaluation values to the CPU **121**. Furthermore, for each of the plurality of unit focus detection areas, the image processing circuit **125** generates, and outputs to the CPU **121**, the first and second focus detection signals, based on the signals read out from the pixels included in the unit focus detection area.

(99) Note that when the first and second sub-pixels **201** and **202** are configured as separate pixels (that is, do not share the same microlens), the pixel coordinates from which the signal is obtained from the first sub-pixel **201** and the pixel coordinates for which the signal is obtained from the second sub-pixel **202** are different. Accordingly, the image processing circuit **125** generates the first and second focus detection signals by interpolating the signals such that signal pairs of the first and second sub-pixels **201** and **202** are present at the same pixel position.

(100) In step S2, the CPU **121** supplies the display image data, which is stored in a video memory region of the RAM **136**, to the display unit **131**, and causes one frame of a live view image to be displayed. The user can adjust an image capture range, exposure conditions, and the like while viewing the live view image displayed in the display unit **131**. The CPU **121** determines the exposure conditions based on the evaluation values obtained from the image processing circuit **125**, and displays an image indicating the determined exposure conditions (shutter speed, aperture value, image capture ISO sensitivity) along with an image of the indicator I illustrated in FIG. 6 in the display unit **131** superimposed on the live view image. The photographer adjusts the shooting range such that the subject area to be focused on in the live view image overlaps with the indicator I.

(101) Thereafter, the CPU **121** executes the operation of step S2 each time image capturing is completed for one frame. As a result, the display unit **131** functions as an EVF.

(102) In step S3, the CPU **121** determines whether the release switch included in the operation unit **132** being depressed halfway (SW1 turning on) has been detected. The CPU **121** repeats step S3 if it is determined that SW1 turning on has not been detected. On the other hand, the CPU **121**

executes step S300 if it is determined that SW1 turning on has been detected.

(103) In step S300, the CPU 121 executes subject tracking automatic focus detection (AF) processing. In step S300, the CPU 121 applies subject detection processing to the display image data, determines the focus detection area, and so on. The CPU 121 also executes predictive AF processing and the like to suppress a drop in the AF accuracy caused by a time difference between when the AF processing is executed and when the release switch being fully depressed (SW2 turning on) is detected. The operation performed in step S300 will be described in detail later.

(104) In step S5, the CPU 121 determines whether SW2 turning on has been detected. The CPU 121 executes step S3 if it is determined that SW2 turning on has not been detected. On the other hand, the CPU 121 executes image capturing/recording processing in step S400 if it is determined that SW2 turning on has been detected. The operation performed in step S400 will be described in detail later.

(105) In step S7, the CPU 121 determines whether a main switch included in the operation unit 132 turning off has been detected. The CPU 121 ends the operation of the image capture mode if it is determined that the main switch turning off has been detected. On the other hand, the CPU 121 executes step S3 if it is determined that the main switch turning off has not been detected.

(106) Although the subject detection processing and the AF processing are described as being executed in response to a determination that SW1 turning on has been detected, the processing may be executed at other times. If the subject tracking AF processing of step S300 is executed before SW1 turning on is detected, the half-press operation can be omitted, and image capturing can be started immediately with a full-press operation.

(107) Image Capturing/Recording Processing

(108) The image capturing/recording processing executed by the CPU 121 in step S400 in FIG. 7 will be described next with reference to the flowchart illustrated in FIG. 8.

(109) In step S401, the CPU 121 determines the exposure conditions (shutter speed, aperture value, image capture ISO sensitivity, and the like) through AE processing based on the evaluation values generated by the image processing circuit 125. Then, the CPU 121 controls the operation of the respective units to capture a still image according to the determined exposure conditions.

(110) In other words, the CPU 121 transmits the aperture value and the shutter speed to the aperture drive circuit 128 and drives the aperture stop 102. The CPU 121 also controls charge accumulation operation of the image sensor 107 through the image sensor drive circuit 124.

(111) In step S402, the CPU 121 reads out one frame's worth of an analog image signal from the image sensor 107 through the image sensor drive circuit 124. Note that the signals of one of the first and second sub-pixels 201 and 202 are also read out for at least the pixels within the focus detection area.

(112) In step S403, the CPU 121 applies analog-to-digital (A/D) conversion to the signal that was read out in step S402 to obtain a digital image signal. The CPU 121 also applies defective pixel correction processing to the digital image signal using the image processing circuit 125. The defective pixel correction processing is processing of supplementing signals read out from pixels from which normal signals cannot be read out (defective pixels) with signals read out from surrounding normal pixels.

(113) In step S404, the CPU 121 causes the image processing circuit 125 to generate a still image data file for recording, as well as the first and second focus detection signals. The image processing circuit 125 applies image processing, encoding processing, and the like to the digital image signal after the defective pixel correction processing, and generates still image data for recording. The image processing may include, for example, demosaicing (color interpolation) processing, white balance adjustment processing, y correction (tone correction) processing, color conversion processing, edge enhancement processing, and the like. The image processing circuit 125 also applies, to the still image data, encoding processing using a method based on the format of the data file that stores the still image data.

(114) In step **S405**, the CPU **121** records, in the recording medium **133**, the image data file which holds the still image data generated in step **S404** and the signals of the sub-pixels read out from the focus detection area in step **S402**.

(115) In step **S406**, the CPU **121** records apparatus property information as property information of the camera **100** in association with the image data file recorded in step **S405** in the recording medium **133**.

(116) The apparatus property information includes the following information, for example. image capture conditions (aperture value, shutter speed, image capture sensitivity, and the like) information on the image processing applied to the digital image signal by the image processing circuit **125** information on a light reception sensitivity distribution of the image capturing pixels and the sub-pixels in the image sensor **107** information on vignetting of the image capture light flux within the camera **100** information on the distance from the mounting surface of the image capturing optical system to the image sensor **107** in the camera **100** information on manufacturing error in the camera **100**

(117) The information on the light reception sensitivity distribution of the image capturing pixels and the sub-pixels (called simply “light reception sensitivity distribution information” hereinafter) is information on a light reception sensitivity of the image sensor **107** according to a distance from a point of intersection between the image sensor **107** and the optical axis. The light reception sensitivity depends on the microlenses **305** and the photoelectric conversion units **301** and **302** in the pixels, and may therefore be information on those elements. The light reception sensitivity distribution information may be information on changes in the sensitivity relative to the incident angle of light.

(118) In step **S407**, the CPU **121** records lens property information, as property information of the image capturing optical system, in the recording medium **133** in association with the still image data file recorded in step **S405**.

(119) The lens property information includes the following information, for example. information on the exit pupil information on frames in the lens barrel and the like which cause vignetting of the light flux information on the focal length, F number, and the like during image capture information on aberration in the image capturing optical system information on manufacturing error in the image capturing optical system the position of the focus lens **105** during image capture (a subject distance)

(120) Next, in step **S408**, the CPU **121** records image-related information, as information on the still image data, in the recording medium **133** in association with the still image data file recorded in step **S405**. The image-related information includes, for example, information on focus detection operation before image capture, information on movement of the subject, and information on focus detection accuracy.

(121) Note that in steps **S406** to **S408**, the CPU **121** may store the apparatus property information, the lens property information, and the image-related information in the RAM **136** in association with the image data file recorded in step **S405**.

(122) In step **S409**, the CPU **121** generates display image data by causing the image processing circuit **125** to scale the still image data, and displays the generated display image data in the display unit **131**. The user can therefore confirm the captured image. The CPU **121** ends the image capturing/recording processing when a pre-set display time passes.

(123) Subject Tracking AF Processing

(124) The subject tracking AF processing performed in step **S300** of FIG. 7 will be described next with reference to the flowchart in FIG. 9.

(125) In step **S301**, the CPU **121** calculates the image shift amount (a phase difference) between the first and second focus detection signals generated for each of the plurality of unit focus detection areas in step **S2**. The image shift amount between the signals can be obtained as a relative position where the amount of correlation between the signals is maximum. The CPU **121** calculates

a defocus amount as a focus condition for each unit focus detection area, from the calculated image shift amount.

(126) As described above, in the present embodiment, each of a total of 9600 areas, obtained by dividing the effective pixel area **1000** into 120 parts in the horizontal direction and 80 parts in the vertical direction, is set as a unit focus detection area. The CPU **121** generates data in which the defocus amount calculated for each unit focus detection area is associated with the position of the area (a defocus map). The CPU **121** stores the generated defocus map in the RAM **136**, for example.

(127) In step **S302**, the CPU **121** executes subject detection processing using the subject detection unit **140**. The subject detection unit **140** detects areas of at least one type of subject, and outputs, to the CPU **121**, a detection result including the type of the subject, the position and size of the area, the reliability of the detection, and the like for each detected area.

(128) Additionally, the CPU **121** performs processing for detecting the position of the subject and the current frame (tracking processing) based on the result of the subject detection processing in the current frame and the result of the subject detection processing in past frames. Note that when the subject cannot be detected through subject detection processing using a trained CNN included in the subject detection unit **140**, the CPU **121** can estimate the position of the subject in the current frame through tracking processing using another method, such as template matching or the like. This will be described in detail later.

(129) In step **S303**, the CPU **121** sets the focus detection area based on the result of the subject detection processing performed in step **S302**. In the present embodiment, the CPU **121** determines the main subject intended by the photographer based on the information of the detected subject, motion of the camera **100**, and the like. The CPU **121** then sets a focus detection area including at least one appropriate unit focus detection area in the area of the main subject determined, and keeps the area of the main subject in focus. The setting of the focus detection area will be described in detail later.

(130) In step **S304**, the CPU **121** obtains the defocus amounts of the unit focus detection areas included in the focus detection area set in step **S303**. The defocus amounts obtained here may be those calculated in step **S301**, or may be defocus amounts calculated again for a new frame. The defocus amount for at least one unit focus detection area present in the periphery of the focus detection area set in step **S303** may be obtained as well.

(131) In step **S305**, the CPU **121** performs the predictive AF processing using the defocus amounts obtained in step **S304** and the defocus amounts obtained in the past. This is processing which is necessary when there is time lag between the timing of the focus detection and the timing of image exposure, and is processing that controls AF by predicting the position of the subject after a predetermined time relative to the timing of focus detection. This will be described in detail later.

(132) In step **S306**, the CPU **121** executes focus adjustment processing for capturing the next frame based on the defocus amount predicted in step **S305** for the main subject. The CPU **121** converts the defocus amount into a drive direction and drive amount of the focus lens, controls the focus actuator **114** through the focus drive circuit **126**, and drives the focus lens **105**. This will be described in detail later. Once the driving of the focus lens **105** is complete, the CPU **121** ends the subject tracking AF processing.

(133) Subject Detection/Tracking Processing

(134) The subject detection/tracking processing performed in step **S302** of FIG. **9** will be described in detail next with reference to the flowcharts in FIG. **10**.

(135) In step **S2000**, the CPU **121** sets the dictionary data to be used by the subject detection unit **140** by determining the type of subject to be detected by the subject detection unit **140**. The type of subject to be detected can be determined based on a pre-set priority level, settings in the camera **100** (e.g., a shooting mode), and the like. For example, assume that dictionary data for “person”, “vehicle”, and “animal” is stored in the dictionary data storage unit **141**. Note that the subject types



may be classified in more detail. For example, dictionary data such as “dog”, “cat”, “bird”, “cow”, or the like may be stored instead of “animal”, and “four-wheeled vehicle”, “two-wheeled vehicle”, “train”, “airplane”, or the like may be stored instead of “vehicle”.

(136) When the camera **100** is set to a shooting mode for shooting a specific type of subject, the CPU **121** sets the dictionary data for that subject type. For example, if a portrait mode or a sports mode is set, dictionary data for “person” is set. If a “panning shooting mode” is set, the dictionary data for “vehicle” is set as well.

(137) When the camera **100** is not set to a shooting mode for shooting a specific type of subject, the CPU **121** sets the dictionary data for the subject according to a pre-set priority level. For example, dictionary data for “person” and “animal” can be set.

(138) The method of determining the type of the dictionary data and the dictionary data to be set is not limited to the method described here. One or more instances of the dictionary data may be set. If one instance is set, subjects which can be detected using one instance of dictionary data can be detected with high frequency. If a plurality of instances of dictionary data are set, a plurality of types of subjects can be detected by switching dictionaries on a frame-by-frame basis. Note that if the processing time allows, a plurality of types of subjects may be detected for the same frame.

(139) In step **S2001**, the CPU **121** applies detection processing for the subject to the image of the current frame using the subject detection unit **140**. Assume here that the subject to be detected is a “person”. The subject detection unit **140** applies the subject detection processing to the image of the current frame using the “person” dictionary data stored in the dictionary data storage unit **141**. The subject detection unit **140** outputs a detection result to the CPU **121**. At this time, the CPU **121** may display the subject detection result in the display unit **131**. The CPU **121** also stores the detected subject area in the RAM **136**.

(140) Note that when “person” dictionary data is set, the subject detection unit **140** detects a plurality of types of areas having different granularities with respect to the person, such as a “whole body” area, a “face” area, and an “eye” area. It is desirable that local areas, such as a person's eyes and face, be detected for use in focus detection, exposure control, and the like, but these may not be detected due to the face not facing forward or being hidden by other subjects. On the other hand, it is unlikely that the whole body will be completely undetectable. Accordingly, areas of a plurality of types having different granularities are detected, which increases the likelihood that some area of the “person” can be detected.

(141) Note that the dictionary data can be configured to detect areas of a plurality of types having different granularities for types of subjects other than people. For example, if “vehicle” dictionary data is set, the dictionary data can be configured such that the subject detection unit **140** detects the “head” and/or “face” area of an occupant in addition to the area of the entire vehicle (including a rider on a two-wheeled vehicle and an occupant of a racecar).

(142) In step **S2002**, the CPU **121** executes subject tracking processing by applying template matching processing to the current frame using the subject area most recently detected in step **S2001** as a template. The image itself of the subject area may be used as the template, or information obtained from the subject area, such as luminance information, color histogram information, feature point information such as corners and edges, or the like may be used as a template. Any publicly-known method for matching, updating a template, or the like can be used. The CPU **121** saves the position and size of the area most closely resembling the template in the current frame (the subject area), motion of the area between frames, the detection reliability of the area, and the like in the RAM **136** as a result of the tracking processing.

(143) The tracking processing in step **S2002** may be performed only when no subject is detected in step **S2001**. By detecting, in the current frame, an area similar to the subject area detected in the past, stable subject detection/tracking processing can be achieved. The CPU **121** ends the subject detection/tracking processing by ending the tracking processing.

(144) Setting Focus Detection Area

(145) Next, the setting of the focus detection area in step S303 of FIG. 9 will be described in detail with reference to the flowchart in FIG. 11.

(146) In step S4000, the CPU 121 obtains, from the RAM 136, the result of the subject detection/tracking processing performed in step S302 of FIG. 9 (subject detection information). The subject detection information may be, for example, the position (e.g., center of gravity coordinates), the size, motion, the detection reliability, and the like of the subject area, for example.

(147) In step S4001, the CPU 121 obtains information pertaining to motion of the camera 100 from the output of the motion detection unit 142.

(148) In step S4002, the CPU 121 determines a reliability that the subject area for which the information was obtained in step S4000 is the subject intended by the photographer. The CPU 121 obtains image coordinates of the unit focus detection area set by the user (or the indicator (AF frame) corresponding to the unit focus detection area). Although the following will describe a case where the image coordinates of the indicator are obtained, the configuration can be implemented in a similar manner even if the image coordinates of the unit focus detection area are obtained.

(149) The CPU 121 calculates a distance between the indicator and the subject area on the image sensor 107 as an indicator of the reliability that the subject intended by the photographer has been detected (that the detected subject area is the area of the subject intended by the photographer). If a plurality of subject areas are detected, the distance can be calculated for the subject area having the highest detection reliability, or the subject area closest to the indicator among subject areas for which the detection reliability is at least a predetermined value. Note that if a plurality of indicators are being displayed, the CPU 121 calculates the distance between the subject area and the indicator closest to the subject area. Additionally, if the position of the indicator is within the subject area, the distance may be calculated as 0.

(150) Then, if the calculated distance is less than a threshold, the CPU 121 determines that there is a high reliability of the subject intended by the photographer being detected, and executes step S4003. Note that the threshold is, for example, a distance between adjacent unit focus detection areas in each of the x direction and the y direction, and the distance can be determined to be at least the threshold when both an x component and a y component of the distance are at least the threshold. However, this is merely an example, and the threshold may be set, the distance may be generated, and so on through different methods.

(151) On the other hand, if the calculated distance is at least the threshold, the CPU 121 determines that there is a low reliability of the subject intended by the photographer being detected, and executes step S4005. Of course, if not even one subject area is detected, or, for example, if there is not even one subject area having a detection reliability that is at least the threshold, the CPU 121 can determine that there is a low reliability of the subject intended by the photographer being detected.

(152) The CPU 121 adds the result of the determination of step S4002 to the information of the subject area stored in the RAM 136.

(153) In step S4003, the CPU 121 stores the distance (positional shift) between the position of the subject area and the position of the indicator, calculated in step S4002, in the RAM 136. The CPU 121 stores the distance between the position of the subject area and the position of the indicator in time series, for a predetermined number of the most recent times. This time series data of the distances depends on the motion of the subject, the skill of the photographer, and the like, and is therefore reset (deleted) when the shooting date, the subject type, or the like changes, after which the storage starts again.

(154) In step S4004, the CPU 121 sets the focus detection area for the case where the subject intended by the photographer is detected. In this case, the CPU 121 sets the focus detection area including the unit focus detection areas where the indicator is displayed and the unit focus detection areas present within the subject area. Unit focus detection areas adjacent to the subject area may also be included. The CPU 121 then executes step S4007.

(155) On the other hand, in step **S4005**, the CPU **121** obtains a history (time series data) of the distance or positional shift in the positions between the indicator and the subject area calculated in step **S4003**, which are stored in the RAM **136**.

(156) In step **S4006**, using the time series data of the distance obtained in step **S4005**, the CPU **121** sets the focus detection area for the case where the subject intended by the photographer is not detected. The time series data of the distance reflects the influence of (1) the framing skill of the photographer, (2) motion characteristics of the subject (movement speed, acceleration, and the like), (3) the focal length of the optical imaging system, which corresponds to an amount of fluctuation in the angle of view during framing, and the like. For example, when the photographer's framing skill is low, variance in the distance tends to be greater than when the photographer's skill is high, and the average value of the distance also tends to be greater.

(157) The CPU **121** separates each distance included in the time series data into an x direction component and a y direction component, and calculates a standard deviation for each direction. The CPU **121** then sets a focus detection area having a length that includes the indicator position, and is a predetermined multiple of the standard deviation in the x direction and the y direction. For example, if the distance follows a normal distribution, setting a focus detection area having a size double the standard deviation in each direction centered on the position of the indicator makes it possible for the subject to be contained within the focus detection area at a probability of approximately 95%.

(158) It is necessary to set the focus detection area to include the subject intended by the photographer. However, if the focus detection area is larger than the subject area, there is a possibility that the camera will focus on other subjects present in the background or the foreground of the intended subject. Accordingly, it is necessary to appropriately set the size of the focus detection area. Dynamically determining the focus detection area based on the time series data of the distance makes it possible to suppress the possibility of other subjects being focused on while increasing the possibility that the subject will fall within the focus detection area.

(159) The size of the focus detection area can be determined dynamically through another method as well. For example, if the number of distance samples included in the time series data is low (less than or equal to a threshold), the size of the focus detection area may be determined based on a standard deviation calculated without separating the distance into the direction components.

(160) Additionally, the focus detection area need not be rectangular as long as it is an area that encompasses a plurality of unit focus detection areas. Accordingly, the focus detection area can be set to any shape, such as a diamond, an ellipse, or the like. The focus detection area may be an asymmetrical shape that is larger in the direction of movement of the subject.

(161) The focus detection area may also be set taking into account the motion information of the camera, obtained in step **S4001**. For example, when a framing speed is a second speed that is faster than a first speed, the size of the focus detection area from the position of the indicator, in the framing direction, can be greater than when the framing speed is the first speed.

(162) Once the focus detection area is set in step **S4006**, the CPU **121** executes step **S4007**.

(163) In step **S4007**, the CPU **121** selects the unit focus detection area  $A(n,m)$  included in the focus detection area set in step **S4004** or step **S4006**. The CPU **121** then causes the indicator  $I(n,m)$  corresponding to the selected unit focus detection area  $A(n,m)$  to be displayed in addition to the indicators already displayed. Through this, the photographer can know the focus detection area which the camera **100** has set. Note that the user may be capable of setting whether to display the additional indicators.

(164) Once the processing of step **S4007** ends, the CPU **121** ends the setting of the focus detection area.

(165) Specific Example of Setting Focus Detection Area

(166) A specific example of setting the focus detection area in step **S4004** or step **S4006** of FIG. **11** will be described next with reference to FIGS. **12A** to **13B**.

(167) FIGS. **12A** to **12C** schematically illustrate a scene in which a human subject swimming the butterfly moves in the horizontal direction from left to right, while the user sets one unit focus detection area in which the indicator **I** is displayed and performs framing with the camera **100** so that the subject is positioned in the indicator **I**. The detected subject area is indicated by **M**, the focus detection area by **1001**, and the indicator by **I**.

(168) At the point in time indicated in FIG. **12A**, the indicator **I** is located slightly ahead in the direction of movement from the head of the subject which the photographer is attempting to bring into focus. In this scene, the subject's head is hidden under the water, or is above the water but hidden by splashing water or the hands. It is therefore not easy to frame the image such that the indicator **I** overlaps with the head, and the indicator **I** is in a position shifted from the head.

(169) In FIG. **12A**, the head of the subject is detected as the subject area **M**, and is close to the indicator **I** in terms of distance (is less than or equal to the threshold). Therefore, in step **S4002** of FIG. **11** described earlier, the CPU **121** determines that there is a high reliability of the subject area **M** corresponding to the intended subject. As a result, in step **S4004**, the CPU **121** sets the focus detection area **1001** based on the subject area **M**. Although an example of setting the focus detection area **1001** with a slightly larger subject area **M** is described here, the subject area **M** may be set as-is as the focus detection area **1001**.

(170) FIG. **12B** illustrates a case where the head is out of the water, but the subject area **M** is not detected due to the arms and water splashing. In this case, in step **S4002** of FIG. **11**, the CPU **121** determines that there is a low reliability of the subject area **M** corresponding to the intended subject. As a result, in step **S4006**, the CPU **121** sets the focus detection area based on the time series data of the distance between the subject area **M** and the indicator **I** detected in the past.

(171) FIG. **12B** illustrates an example of the focus detection area **1001** set when there is little variance in the time series data of the distance between the indicator and the subject area. The primary component of the distance between the indicator and the subject area is in the horizontal direction, which is the direction of the subject's movement. Accordingly, the CPU **121** sets the focus detection area **1001** at a size in the horizontal direction, which is the direction of the subject's movement, that is enlarged centered on the indicator **I**. Although not illustrated in FIG. **12B**, the CPU **121** sets the focus detection area **1001** such that the number of unit focus detection areas included in the horizontal direction is greater than that in FIG. **12A**.

(172) FIG. **12C** illustrates a case where the head has moved below the water and the subject area **M** is not detected. In this case, the CPU **121** sets the focus detection area **1001** similar to that illustrated in FIG. **12B**. An example of the focus detection area **1001** set when there is a large amount of variance in the time series data of the distance between the indicator and the subject area is illustrated here.

(173) For example, if the photographer's framing skill is low, the subject may be hidden from view, resulting in large amounts of variance in the distance. Variance in the distance is particularly great in the direction of the subject's movement (the horizontal direction). By determining the size of the focus detection area according to the magnitude of the variance in the distance, a focus detection area having a larger size is set for a photographer who has low framing skill than a focus detection area set for a photographer who has high framing skill. In FIG. **12C**, a larger focus detection area **1001** is set in both the horizontal direction and the vertical direction than in FIG. **12B**, but particularly in the direction of the subject's movement (the horizontal direction).

(174) FIGS. **13A** and **13B** schematically illustrate a scene in which a human subject performing a dive in a competition moves in the vertical direction from top to bottom, while the user sets one unit focus detection area in which the indicator **I** is displayed and performs framing with the camera **100** so that the subject is positioned in the indicator **I**.

(175) FIG. **13A** illustrates an example of the focus detection area **1001** set when the subject area **M** is detected. The subject area **M** is in a position slightly shifted from the indicator **I**, but is close to the indicator **I** in terms of distance (is less than or equal to the threshold). Therefore, in step **S4002**

of FIG. 11 described earlier, the CPU 121 determines that there is a high reliability that the subject area M is the intended subject. As a result, in step S4004, the CPU 121 sets the focus detection area 1001 based on the subject area M. Although an example of setting the focus detection area 1001 with a slightly larger subject area M is described here, the subject area M may be set as-is as the focus detection area 1001.

(176) FIG. 13B illustrates an example of the focus detection area 1001 set when the posture of the subject is almost the same as in FIG. 13A, but the subject area M cannot be detected due to the arms and the head overlapping. In this case, in step S4002 of FIG. 11, the CPU 121 determines that there is a low reliability that the subject area M is the intended subject. As a result, in step S4006, the CPU 121 sets the focus detection area based on the time series data of the distance between the subject area M and the indicator I detected in the past.

(177) In the scenes illustrated in FIGS. 13A and 13B, the subject is moving in the vertical direction, and thus the primary component of the distance between the indicator and the subject area is the vertical direction. Accordingly, the CPU 121 sets the focus detection area 1001 at a size in the vertical direction, which is the direction of the subject's movement, that is enlarged centered on the indicator I. Here, although the area is enlarged by the same amount in the vertical direction with respect to the indicator I, the area may be enlarged to a greater extent in the direction of the subject's movement.

(178) For example, FIG. 14A illustrates another example of a focus detection area set when the subject area cannot be detected or when the distance between the indicator and the subject area exceeds a threshold. Here, the direction of the subject's movement is the right direction in the drawing, and thus when the focus detection area is enlarged in the horizontal direction, the enlargement amount or enlargement rate is made greater in the right direction than in the left direction with respect to the indicator I.

(179) Additionally, whether the framing action lags behind the movement of the subject (e.g., the average value of the distance is a negative value) or is ahead of the movement of the subject (e.g., the average value is a positive value) can be determined based on the time series data of the distance which is referenced. If the framing operation is determined to be lagging behind the movement of the subject, the enlargement amount or the enlargement rate in the forward direction of the movement may be increased compared to when the framing action is determined to be ahead of the movement of the subject.

(180) FIG. 14B illustrates the same situation as FIG. 14A, but in a state where the indicator I overlaps the subject's head and the shot is well-framed. In this case, it can be determined that the distance is small and there is little variance based on the time series data of the distance. In such a case, the focus detection area 1001 can be set slightly enlarged in the direction of the subject's movement without inadvertently enlarging the focus detection area.

(181) FIGS. 15A and 15B illustrate examples of the focus detection area 1001 set using basically the same method as in FIGS. 14A and 14B, except that the direction of the subject's movement is the vertical direction (top to bottom). However, the examples in FIGS. 15A and 15B are larger than the examples in FIGS. 14A and 14B because the speed at which the subject is moving is greater, and thus the downward enlargement, which corresponds to the direction of movement, is greater than in the examples illustrated in FIGS. 14A and 14B.

(182) The speed at which the subject is moving can be detected using a shooting interval, a distance traveled between images shot, the subject distance, the motion information of the camera 100, or the like, but may also be detected by another method.

(183) The time series data of the distance calculated in step S4003 and stored in the RAM 136 may be used, for example, without being reset while it is determined that a similar scene is being shot continuously. The CPU 121 can determine that the camera 100 is continuously shooting a similar scene when, for example, the camera 100 is determined to be repeatedly performing similar framing based on the motion information of the camera 100. Alternatively, the time series data of

the distance may be reset at the point in time when one instance of framing ends.

(184) Additionally, in setting the focus detection area **1001**, information obtained from a neural network trained using data from the dictionary data storage unit **141** and the motion detection unit **142** may be taken into account. This makes it possible to set a focus detection area **1001** that is better suited to the characteristics of the individual photographer.

(185) Setting Focus Detection Area According to Distance and Framing Amount

(186) Thus far, a method has been described for determining the size of the focus detection area based on the variance (e.g., the standard deviation) and the magnitude (e.g., the average value) of the distance between the indicator position and the subject area calculated a plurality of times as time passes. However, the size of the focus detection area can be determined through another method as well.

(187) FIG. **16** illustrates an example of determining the size (range) of the focus detection area based on a combination of the magnitude (e.g., the average value) of the distance between the indicator and the subject area, obtained from time series data, and the magnitude (e.g., the average value) of a framing amount. The magnitude of the framing amount (speed or acceleration) can be obtained from the motion of the camera **100** detected by the motion detection unit **142**.

(188) Here, the magnitude of the distance and the magnitude of the framing amount are assumed to be classified into two categories using predetermined thresholds for each, and the size of the focus detection area is assumed to be determined according to four different combinations. Note that at least one of the magnitudes may be classified into three or more categories.

(189) For example, the CPU **121** calculates a representative value (e.g., the average value) of the magnitude of the distance between the indicator and the subject area from the time series data obtained in step **S4005**. The CPU **121** also calculates the framing amount of the camera **100** based on the motion of the camera **100** detected by the motion detection unit **142**. The CPU **121** classifies each of the representative value of the magnitude of the distance and the framing amount as “large” or “small” by comparing the representative value of the magnitude of the distance and the framing amount with respective thresholds. The CPU **121** obtains one of focus detection area ranges A to D by referring to a table stored in the ROM **135** based on the combination of the classification results. The ranges A to D may be, for example, enlargement rates relative to a reference size (e.g., the size of the indicator I).

(190) Basically, the enlargement rate is greater when the distance between the indicator and the subject area is large than when that distance is small. This is because the photographer's framing skill is considered to be low when the distance is large. The enlargement rate is greater when the framing amount is greater, too, than when the framing amount is small. This is because the subject is considered to be moving faster when the framing amount is large. Accordingly, of A through D, A is the largest and D is the smallest. For B and C, the magnitude relationship between B and C can vary according to the threshold used for the classification.

(191) Note that the table in FIG. **16** may be prepared for both the x direction and the y direction. In this case, the representative value of the magnitude of the distance and the magnitude of the framing amount are also obtained in both the x direction and the y direction. By preparing enlargement rates for each direction, the focus detection area can be set at an enlargement rate corresponding to the direction of the subject's movement.

(192) Predictive AF Processing

(193) The predictive AF processing in step **S305** of FIG. **9** will be described in detail next with reference to the flowchart in FIG. **17**.

(194) In step **S6001**, the CPU **121** determines whether the subject is a moving object moving in the optical axis direction. If the subject is determined to be a moving object moving in the optical axis direction, step **S6002** is executed, and if not, step **S6009** is executed. Whether the subject is a moving object moving in the optical axis direction can be determined based on changes in the defocus amount in the subject area or changes in the focal length by referring to time series data of

the defocus map.

(195) In step **S6002**, the CPU **121** determines whether an image plane speed of the subject is high. If the speed is high, step **S6003** is executed, and if not, step **S6009** is executed. The CPU **121** can determine that the image plane speed is high if, for example, an amount of inter-frame movement of the subject area (a difference in the defocus amount between frames arising due to movement in the optical axis direction) is at least a threshold.

(196) In step **S6003**, the CPU **121** sets a number of time series data to be used to predict the subject position. FIG. **18A** is a diagram illustrating an example of the change over time of an image plane position of the subject. The horizontal axis represents time and the vertical axis represents the amount of movement on the image plane. The black circles indicate a time series of the amount of movement of the subject area detected in the past (the defocus amount, because this is movement in the optical axis direction). FIG. **18A** illustrates a case where the amount of movement of the subject on the image plane increases as time passes. The position of the subject area in the future is predicted from the time series data.

(197) If the image plane speed or acceleration of the subject is low, prediction error will not increase even if the number of time series data used for the prediction is increased. Rather, increasing the number reduces the impact of defocus amount error on the predicted position.

(198) On the other hand, if the image plane speed or acceleration of the subject is high, increasing the number of time series data used for prediction will result in more data from periods when the image plane speed is low also being used for the prediction, which in turn produces more error in the predicted position.

(199) Therefore, in the present embodiment, when the image plane speed or acceleration is determined to be high, the number of time series data of the amount of movement of the subject, which is used to calculate the prediction curve, is smaller than when the image plane speed or acceleration is determined to be low. Reducing the number of time series data reduces the number of data from older periods of low image plane speed or acceleration, which makes it possible to suppress a drop in the accuracy of the predicted position, particularly with respect to subjects for which the speed increases over time.

(200) In step **S6004**, the CPU **121** sets a range over which focus movement is possible. The range over which focus movement is possible will be described with reference to FIG. **18B**. In FIG. **18B**, the horizontal axis represents time, the vertical axis represents a position of the subject on the image plane, the solid line represents a focus position, and the dotted line represents the range over which focus movement is possible.

(201) When the subject is a moving object, the subject can leave the set focus detection area with ease. If focus control is performed in a state where the subject has left the focus detection area, the focal length can vary greatly. Accordingly, when the subject comes back to the focus detection area, it takes a long time for the subject to come into focus. Therefore, the CPU **121** estimates a range of distance over which the subject moves based on the image plane movement speed of the subject, the subject distance, and the like, and limits the range over which focus movement is possible (a permissible range for change in the focal length).

(202) Then, the CPU **121** does not drive the focus lens when the predicted image plane position (distance) of the subject has changed from the current focal length beyond the permissible range. This makes it possible to suppress situations where the subject suddenly becomes blurry, even when the subject has unintentionally left the focus detection area.

(203) In step **S6005**, the CPU **121** calculates the predicted position (the distance) of the subject. For example, the CPU **121** can predict the image plane position of the subject by obtaining an equation for a prediction curve through multivariate analysis (e.g., the least squares method) using time series data of past image plane positions and times, and substituting the time when a still image is shot into the equation for the prediction curve.

(204) In step **S6006**, the CPU **121** changes a focus movement speed. The CPU **121** sets the image

plane movement speed of the focus according to the image plane movement speed of the subject estimated based on the image plane position of the subject, predicted in step **S6005**, and the time series data of past image plane positions. In the example in FIG. **18A**, the image plane movement speed of the subject is estimated to be increasing as time passes, and thus the CPU **121** increases the image plane movement speed of the focus.

(205) In step **S6007**, the CPU **121** determines whether the image plane position (the distance) of the subject predicted in step **S6005** is within the range over which focus movement is possible set in step **S6004**. The CPU **121** executes step **S6008** if the predicted image plane position of the subject is determined to be within the range over which focus movement is possible, and ends the predictive AF processing without driving the focus lens if not.

(206) In step **S6008**, the CPU **121** drives the focus lens **105** to bring the position predicted in step **S6005** into focus, and ends the predictive AF processing.

(207) Note that step **S6008** may be executed when the predicted image plane position of the subject is not determined to be in the range over which focus movement is possible for a predetermined number of consecutive times (or a predetermined length of time). In this case, the CPU **121** resets the time series data pertaining to the image plane position of the subject, and generates new time series data.

(208) As described thus far, according to the present embodiment, when the subject area cannot be detected, the focus detection area is enlarged based on past data pertaining to the distance between the subject area and the focus detection area. Accordingly, when, for example, a photographer is shooting a moving subject while framing the shot with the camera, a focus detection area can be set having a size appropriate to the photographer's framing skill. This makes it possible to increase the likelihood of performing focus control on the intended subject even when the photographer's framing skill is low, while reducing the risk of focusing on unintended subjects as a result of unnecessarily enlarging the focus detection area.

## Second Embodiment

(209) A second embodiment will be described next. The present embodiment is the same as the first embodiment aside from operation for setting the focus detection area. Accordingly, only the operational steps for setting the focus detection area in the present embodiment will be described below. Note that the present embodiment is also assumed to be implemented using the camera **100**.

(210) FIG. **19** is a flowchart pertaining to operational steps for setting the focus detection area, executed by the CPU **121** in the present embodiment.

(211) In step **S3001**, the CPU **121** obtains image coordinates of the indicator (the AF frame) of the unit focus detection area set by the user. As described in the first embodiment, the image coordinates of the unit focus detection area may be used instead of the indicator.

(212) In step **S3002**, the CPU **121** obtains information pertaining to motion of the camera **100** from the output of the motion detection unit **142**.

(213) In step **S3003**, the CPU **121** determines whether a framing action is being taken using the camera **100**, based on the motion of the camera **100** detected in step **S3002**. The CPU **121** executes step **S3004** if it is determined that a framing action is being taken using the camera **100**, and executes step **S3008** if not. The determination as to whether motion of the camera **100** indicates a framing action can be made through a publicly-known method and will therefore not be described in detail here. If it is determined that a framing action is being taken, the CPU **121** also obtains the direction and amount of the framing (e.g., the amount of movement in the image coordinate system between frames).

(214) In step **S3008**, a framing action is not being taken with the camera **100**, and thus the CPU **121** determines that the photographer can easily aim at the subject intended by the indicator currently set. As a result, the CPU **121** sets the unit focus detection area corresponding to the indicator currently set as the final focus detection area, and ends the setting processing. Note that step **S3007** is executed when there are a plurality of unit focus detection areas corresponding to the



indicator currently set.

(215) In step **S3004**, the CPU **121** obtains, from the RAM **136**, the result of the subject detection/tracking processing performed in step **S302** of FIG. **9** (subject detection information). The subject detection information may be, for example, the position (e.g., center of gravity coordinates), the size, motion, the detection reliability, and the like of the subject area, for example.

(216) In step **S3005**, the CPU **121** determines a reliability that the subject area for which the information was obtained in step **S3004** is the subject intended by the photographer. This determination can be made in a similar manner as the determination in step **S4002** in the first embodiment. Then, the CPU **121** executes step **S3006** if it is determined there is a high reliability that the subject intended by the photographer is detected, and executes step **S3009** if not.

(217) In step **S3006**, the CPU **121** sets the focus detection area for when the intended subject is detected and a framing action is being performed. The CPU **121** enlarges the focus detection area in at least the framing direction, and in a manner that unit focus detection areas overlapping with the subject area are included. If the framing direction is the horizontal direction, the CPU **121** can enlarge the focus detection area in both the right direction and the left direction.

(218) Additionally, in step **S3006**, the CPU **121** can correct the size of the enlarged focus detection area according to the motion of the camera **100**. For example, the CPU **121** corrects the focus detection area to be enlarged even more, or maintains the enlargement, in the direction in which a subject area is determined to have a high reliability as the subject intended by the photographer in step **S3005**. On the other hand, the CPU **121** corrects the enlargement rate of the focus detection area in other directions to be relatively lower, or does not perform the enlargement.

(219) As described earlier, simply enlarging the focus detection area increases the possibility that the focus detection area will include the background, unintended subjects, or the like. Accordingly, the focus detection area is not enlarged in the direction where the subject area is not present, or the enlargement amount is smaller than in the direction where the subject area is present.

(220) In step **S3009**, the CPU **121** enlarges the focus detection area according to the framing direction and the framing amount. When shooting while framing the shot, it is easy for positional shift to arise between the subject and the indicator in the framing direction. For example, in framing in the horizontal direction, it is easy for positional shift to arise between the subject and the indicator in the horizontal direction. The magnitude of the positional shift is affected by the framing speed or acceleration.

(221) Accordingly, in step **S3009**, where the information of the subject area cannot be used, the focus detection area is enlarged at least in the framing direction if, based on the motion information of the camera **100**, the positional shift between the indicator and the subject is expected to be large. This increases the probability of the subject being included in the focus detection area, and makes it possible to suppress situations where the background is focused on when the indicator is off the subject. The enlargement amount or the enlargement rate can be determined such that the amount is greater when the framing amount is a second amount than when the framing amount is a first amount (where the second amount is greater than the first amount). The enlargement amount or the enlargement rate can be determined by storing a function or a table that associates framing amounts with enlargement amounts or enlargement rates in the ROM **135** in advance, and using an enlargement amount or an enlargement rate according to the framing amount. Note that the enlarging of the focus detection area may be skipped when the framing amount is less than or equal to a threshold.

(222) Step **S3009** is executed when a subject area having a detection reliability that is at least a threshold is not detected, or is not present near the indicator. In such a case, enlarging the focus detection area in at least the framing direction increases the likelihood of the subject being included in the focus detection area.

(223) In step **S3007**, the CPU **121** selects an appropriate unit focus detection area from the focus detection area set in step **S3006**, step **S3008**, or step **S3009**. For example, the CPU **121** selects the

unit focus detection area corresponding to the closest distance in the defocus map corresponding to the focus detection area. Alternatively, the CPU **121** selects the unit focus detection area closest to the center of the shooting range within the focus detection area. This is because the subject at the closest distance among the subjects included in the focus detection area, the subject closest to the center of the shooting range, or the like is highly likely to be the subject intended by the photographer. Note that the unit focus detection area may be selected through another method.

(224) In this manner, the size of the focus detection area is controlled according to whether it is highly likely that the area of the subject intended by the photographer is detected, and whether framing is underway. Accordingly, the focus detection area can be set to an appropriate size according to the situation of the subject, the photographer's framing skill, and the like, which makes it possible to increase the likelihood that focus control will be performed appropriately, even if the indicator is off the intended subject, the intended subject cannot be detected, or the like.

(225) Specific examples of setting the focus detection area in the present embodiment will be described next with reference to FIGS. **20A** to **27B**.

(226) FIGS. **20A** to **20C** schematically illustrate a scene in which a human subject swimming the butterfly moves in the horizontal direction from left to right, while the user sets one unit focus detection area in which the indicator **I** is displayed and performs framing with the camera **100** so that the subject is positioned in the indicator **I**.

(227) FIGS. **20A** to **20C** illustrate examples of framing by a skilled photographer. In FIGS. **20A** and **20B**, the detected subject area **M** and the indicator **I** substantially coincide. Even in the situation in FIG. **20C**, where the face is below the water and the subject area **M** is not detected, the indicator **I** is positioned on the head of the subject. When framing is performed as illustrated in FIGS. **20A** to **20C**, it is highly likely that the focus will be controlled appropriately even without enlarging the focus detection area.

(228) On the other hand, FIGS. **21A** to **21C** illustrate framing in the same scene as in FIGS. **20A** to **20C**, but with the indicator **I** and the subject area **M** shifted from each other. This is likely to occur when the photographer's framing skill is low, when the speed at which the subject is moving is not constant, or the like.

(229) FIGS. **22A** and **22B** schematically illustrate a scene in which a subject performing a dive in a competition moves in the vertical direction from top to bottom, while the user sets one unit focus detection area in which the indicator **I** is displayed and performs framing with the camera **100** so that the subject is positioned in the indicator **I**.

(230) FIG. **22A** illustrates an example of framing by a skilled photographer. Meanwhile, FIG. **22B** illustrates framing in the same scene as in FIG. **22A**, but with the indicator **I** and the subject area **M** shifted from each other. Note that in FIGS. **22A** and **22B**, the face is partially hidden behind the arm and the subject area is therefore not detected.

(231) Shift between the indicator **I** and the subject area **M** (or the intended part) is affected by the direction and speed of the framing, as well as the speed at which the subject is moving and the acceleration. For example, when the framing is in the horizontal direction, shift in the horizontal direction will increase. Additionally, when the subject is moving fast and the framing is also fast, the shift will increase. The framing is more difficult when the acceleration of the subject is greater, which ultimately increases the shift.

(232) FIGS. **23A** to **24B** illustrate examples of setting the focus detection area in step **S3009**, in the same scene as that illustrated in FIGS. **20A** to **21C**. The area of the intended subject has not been detected, and the focus detection area is therefore set based on the information on the motion of the camera **100** (the framing).

(233) Here, the focus detection area **1001** is set having been enlarged in the horizontal direction (both the left and right directions) centered on the indicator **I**, as a result of framing in the horizontal direction being detected. A greater framing amount is detected in FIGS. **23A** and **23B** than in FIGS. **24A** and **24B**, and thus the enlargement amount or the enlargement rate is greater

than in FIGS. **24A** and **24B**. Specifically, two unit focus detection areas A each are added on the left and right in FIGS. **23A** and **23B**, and the focus detection area **1001** including five unit focus detection areas A is set. Meanwhile, one unit focus detection area A each is added on the left and right in FIGS. **24A** and **24B**, and the focus detection area **1001** including three unit focus detection areas A is set.

(234) FIGS. **25A** to **26B** illustrate examples of setting the focus detection area in step **S3006**, in the same scene as that illustrated in FIGS. **20A** to **21C**. The area of the intended subject is detected, and thus the focus detection area is enlarged based on the information on the motion of the camera **100** (the framing), after which the size of the focus detection area is corrected according to the positional relationship between the indicator I and the subject area M.

(235) First, the focus detection area **1001** is temporarily set having been enlarged by the same amount in the horizontal direction (both the left and right directions) centered on the indicator I, as a result of framing in the horizontal direction being detected. The enlargement amount or the enlargement rate is set such that at least one unit focus detection area A overlapping the subject area M is included. In the example in FIGS. **25A** and **25B**, the distance between the indicator I and the subject area M is greater than in the example in FIGS. **26A** and **26B**, and thus the amount by which the focus detection area is enlarged in the left-right direction is greater than in the example in FIGS. **26A** and **26B**.

(236) Thereafter, the enlargement rate or the enlargement amount is corrected to be reduced in the direction, among the two opposing enlargement directions centered on the indicator I, where the subject area M detected as the area of the subject intended by the photographer is not present. FIGS. **25A** to **26B** illustrate an example in which correction is performed to avoid enlargement in the direction, of the framing direction (the horizontal direction), that is to the right of the indicator I, where the subject area M is not present.

(237) FIGS. **27A** and **27B** illustrate an example of setting the focus detection area **1001** in a case where the state of the subject changes from the state illustrated in FIGS. **25A** and **25B** or FIGS. **26A** and **26B**, and the subject area M is no longer detected. FIG. **27A** illustrates a case where the subject's head (face) is hidden under the water, and FIG. **27B** illustrates a case where the subject's head (face) is hidden by the hands or water splashing.

(238) In this case, the CPU **121** switches the method for enlarging the focus detection area based on the information on the motion of the camera **100** (the framing, described with reference to FIGS. **23A** and **23B**, and sets the focus detection area **1001**.

(239) Although examples of setting the focus detection area in a case where the framing direction is the horizontal direction have been described with reference to FIGS. **20A** to **27B**, the focus detection area can be set in a similar manner when the framing direction is the vertical direction or a diagonal direction.

(240) In the present embodiment, the focus detection area is enlarged according to the framing direction and the framing amount when an area of the subject thought to be intended by the photographer is not detected. Accordingly, the focus detection area is enlarged more when the photographer is unable to predict the subject's motion well and unintentionally increases the framing amount. As such, the likelihood that the subject is included in the focus detection area can be increased, and major changes in the focal state of the subject can be suppressed.

(241) Additionally, when an area of the subject thought to be intended by the photographer is detected, the focus detection area is enlarged to include the area of the subject, and the size of the focus detection area is corrected such that unnecessary enlargement is not performed. Accordingly, the likelihood that the focus will be controlled to the subject intended by the photographer can be increased while suppressing the possibility of the focus being controlled to the background or other subjects.

## OTHER EMBODIMENTS

(242) Embodiment(s) of the present invention can also be realized by a computer of a system or

apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a ‘non-transitory computer-readable storage medium’) to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)<sup>TM</sup>), a flash memory device, a memory card, and the like.

(243) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(244) This application claims the benefit of Japanese Patent Application No. 2022-015819 filed on Feb. 3, 2022 which is hereby incorporated by reference herein in its entirety.

## Claims

1. An image capture apparatus comprising one or more processors that execute a program stored in a memory and thereby function as: a detection unit configured to detect a subject area from an image that has been shot; an obtainment unit configured to obtain a distance in the image between a focus detection area that is set and the subject area detected; and an enlargement unit configured to enlarge the focus detection area in a case where the subject area is not detected or a reliability that the detected subject area corresponds to an intended subject is determined to be low, wherein the enlargement unit enlarges the focus detection area based on the distances previously obtained by the obtainment unit.
2. The image capture apparatus according to claim 1, wherein the enlargement unit enlarges the focus detection area based on a variance in the distances.
3. The image capture apparatus according to claim 2, wherein the focus detection area is enlarged based on a magnitude that is a predetermined multiple of a magnitude of the variance in the distances.
4. The image capture apparatus according to claim 1, wherein the enlargement unit enlarges the focus detection area based on a representative value of the distances.
5. The image capture apparatus according to claim 4, wherein the enlargement unit enlarges the focus detection area more in a case where the representative value of the distances is a second value than in a case where the representative value of the distances is a first value, the second value being greater than the first value.
6. The image capture apparatus according to claim 4, wherein the enlargement unit enlarges the focus detection area based on a representative value of the distances and a framing amount of the image capture apparatus.
7. The image capture apparatus according to claim 1, wherein the enlargement unit enlarges the focus detection area more in a forward direction of a direction of movement of a subject.

8. The image capture apparatus according to claim 1, wherein the image capture apparatus is capable of setting a plurality of unit focus detection areas, and the enlargement unit enlarges the focus detection area so as to include two or more of the plurality of the unit focus detection areas.

9. A control method executed by an image capture apparatus, the control method comprising: detecting a subject area from an image that has been shot; obtaining a distance between a focus detection area that is set and the subject area detected; and enlarging the focus detection area in a case where the subject area is not detected or a reliability that the detected subject area corresponds to an intended subject is determined to be low, wherein in the enlarging, the focus detection area is enlarged based on the distances previously obtained.

10. A non-transitory machine-readable medium that stores a program for causing a computer of an image capture apparatus to function as: a detection unit configured to detect a subject area from an image that has been shot; an obtainment unit configured to obtain a distance in the image between a focus detection area that is set and the subject area detected; and an enlargement unit configured to enlarge the focus detection area in a case where the subject area is not detected or a reliability that the detected subject area corresponds to an intended subject is determined to be low, wherein the enlargement unit enlarges the focus detection area based on the distances previously obtained by the obtainment unit.

---