

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267237

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

TANEICHI; Satoshi et al.

IMAGE MANAGEMENT SYSTEM, IMAGE MANAGEMENT METHOD, AND COMPUTER PROGRAM PRODUCT

Abstract

The present invention is concerning to an image management system that communicates with a first communication terminal via a communication network, the image management system comprising: an image storage unit configured to store image data; a receiving unit configured to receive, from the first communication terminal, link information that includes image identification information for identifying the image data and includes predetermined-area information that indicates a predetermined area in the image data; and a transmitting unit configured to transmit, to the first communication terminal, the image data that is indicated by the image identification information included in the link information received by the receiving unit and the predetermined-area information included in the link information.

Inventors: TANEICHI; Satoshi (Tokyo, JP), ITO; Takeshi (Tokyo, JP), WATANABE; Masanori (Tokyo, JP)

Applicant: Ricoh Company, Ltd. (Tokyo, JP)

Family ID: 1000008586683

Assignee: Ricoh Company, Ltd. (Tokyo, JP)

Appl. No.: 19/202187

Filed: May 08, 2025

Foreign Application Priority Data

JP	2012-288475	Dec. 28, 2012
----	-------------	---------------

Related U.S. Application Data

parent US continuation 17970597 20221021 parent-grant-document US 12328527 child US 19202187

parent US continuation 17142258 20210106 parent-grant-document US 11509825 child US 17970597
parent US continuation 16581775 20190925 parent-grant-document US 10911670 child US 17142258
parent US continuation 16153877 20181008 parent-grant-document US 10484604 child US 16581775
parent US continuation 15646130 20170711 parent-grant-document US 10136057 child US 16153877
parent US continuation 15151119 20160510 parent-grant-document US 9736371 child US 15646130
parent US continuation 14107403 20131216 parent-grant-document US 9363463 child US 15151119

Publication Classification

Int. Cl.: **H04N5/765** (20060101); **H04N1/00** (20060101); **H04N1/32** (20060101); **H04N1/327** (20060101); **H04N5/262** (20060101); **H04N5/76** (20060101); **H04N5/77** (20060101); **H04N21/2743** (20110101); **H04N21/414** (20110101); **H04N21/4223** (20110101); **H04N21/4728** (20110101); **H04N21/6587** (20110101); **H04N21/81** (20110101); **H04N23/698** (20230101)

U.S. Cl.:

CPC **H04N5/765** (20130101); **H04N1/00217** (20130101); **H04N1/32101** (20130101); **H04N1/32776** (20130101); **H04N5/2628** (20130101); **H04N5/772** (20130101); **H04N21/2743** (20130101); **H04N21/41407** (20130101); **H04N21/4223** (20130101); **H04N21/4728** (20130101); **H04N21/6587** (20130101); **H04N21/8153** (20130101); **H04N23/698** (20230101); **H04N5/76** (20130101); **H04N2201/3226** (20130101); **H04N2201/325** (20130101); **H04N2201/3276** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The application is a continuation of U.S. application Ser. No. 17/970,597, filed Oct. 21, 2022, which is a continuation of U.S. application Ser. No. 17/142,258, filed Jan. 6, 2021 (now U.S. Pat. No. 11,509,825), which is a continuation of and claims the benefit of priority under 35 U.S.C. § 120 from U.S. application Ser. No. 16/581,775 filed Sep. 25, 2019 (now U.S. Pat. No. 10,911,670), which is a continuation of U.S. application Ser. No. 16/153,877, filed Oct. 8, 2018 (now U.S. Pat. No. 10,484,604), which is a continuation of U.S. application Ser. No. 15/646,130, filed Jul. 11, 2017 (now U.S. Pat. No. 10,136,057), which is a continuation of U.S. application Ser. No. 15/151,119, filed May 10, 2016 (now U.S. Pat. No. 9,736,371), which is a continuation of U.S. application Ser. No. 14/107,403, filed Dec. 16, 2013 (now U.S. Pat. No. 9,363,463), and claims the benefit of priority under 35 U.S.C. § 119 from Japanese Patent Application No. 2012-288475, filed Dec. 28, 2012, the entire contents of each of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present invention relates to a communication with a predetermined communication terminal via a communication network.

2. Description of the Related Art

[0003] Recently, systems have been provided to share the same image with multiple users, where the image data captured by a digital camera, or the like, is uploaded by a user into a server on the Internet and the image data is downloaded from the server by another user (see Japanese Patent Application Laid-open No. 2011-120201).

[0004] For example, if another user downloads the image data illustrated in FIG. 28, a display 315 of a communication terminal 3, such as a smartphone, first displays the image of a predetermined area in the image data by default, as illustrated in FIG. 29. When the user touches the display 315 with the user's finger to operate it, the image data for representing the whole can be displayed as illustrated in FIG. 28.

[0005] However, according to a default setting, the predetermined-area image illustrated in FIG. 29 is generally a local image around the center of the composition that is obtained when captured by a digital camera, or the like; therefore, a problem occurs in that a user who uploads the image may not always be able to initially show to another user the local image to which the user pays attention or which is a recommended sight.

SUMMARY OF THE INVENTION

[0006] It is an object of the present invention to at least partially solve the problems in the conventional technology.

[0007] According to the present invention, there is provided: an image management system that communicates with a first communication terminal via a communication network, the image management system comprising: an image storage unit configured to store image data; a receiving unit configured to receive, from the first communication terminal, link information that includes image identification information for identifying the image data and predetermined-area information that indicates a predetermined area in the image data; and a transmitting unit configured to transmit, to the first communication terminal, the image data that is indicated by the image identification information included in the link information received by the receiving unit and the predetermined-area information included in the link information.

[0008] The present invention also provides an image management method performed by an image management system that includes an image storage unit that stores image data and that communicates with a first communication terminal via a communication network, the image management method comprising: receiving, from the first communication terminal, link information that includes image identification information for identifying the image data and predetermined-area information that indicates a predetermined area in the image data; reading the image data from the image storage unit on the basis of the image identification information included in the link information received at the receiving; and transmitting, to the first communication terminal, the image data read at the reading and the predetermined-area information included in the link information received at the receiving.

[0009] The present invention also provides a computer program product comprising a non-transitory computer-readable medium that contains a computer program that, when executed by a computer, cause the computer to perform operations comprising: receiving, from the first communication terminal, link information that includes image identification information for identifying the image data and predetermined-area information that indicates a predetermined area in the image data; reading the image data from the image storage unit on the basis of the image identification information included in the link information received at the receiving; and transmitting, to the first communication terminal, the image data read at the reading and the predetermined-area information included in the link information received at the receiving.

[0010] The above and other objects, features, advantages and technical and industrial significance of this invention will be better understood by reading the following detailed description of presently preferred embodiments of the invention, when considered in connection with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] FIG. 1 is a schematic view of an image sharing system according to an embodiment of the present invention;

[0012] FIG. 2A is a left side view of a capturing device, FIG. 2B is a front view of the capturing device, and FIG. 2C is a plan view of the capturing device;

[0013] FIG. 3 is a diagram that illustrates an image illustrating how the capturing device is used;

[0014] FIG. 4A is a diagram that illustrates the hemispheric image (the front) captured by the capturing device, FIG. 4B is a diagram that illustrates the hemispheric image (the back) captured by the capturing device, and FIG. 4C is a diagram that illustrates the image represented by using the Mercator projection;

[0015] FIG. 5A is a diagram that illustrates the image represented by using the Mercator projection and the area of a shared selection image, and FIG. 5B is a diagram that illustrates the shared selection image;

[0016] FIG. 6 is a diagram of a captured-image selection list that presents shared selection images;

[0017] FIG. 7 is a diagram that schematically illustrates a process to post and acquire image data;

[0018] FIG. 8 is a diagram that illustrates a fully-spherical panoramic image;

[0019] FIG. 9 is a diagram that illustrates a virtual camera and the location of a predetermined area in a case where the fully-spherical panoramic image is a three-dimensional solid sphere;

[0020] FIG. 10A is a three-dimensional perspective view of FIG. 9, and FIG. 10B is a diagram that illustrates a communication terminal where a predetermined-area image is presented on a display;

[0021] FIG. 11 is a diagram that illustrates the communication terminal where a predetermined-area image is presented on a display;

[0022] FIG. 12 is a diagram that illustrates the relation between predetermined-area information and a predetermined-area image;

[0023] FIG. 13 is a diagram that illustrates the details of link information;

[0024] FIG. 14 is a diagram that illustrates a posting-view screen;

[0025] FIG. 15 is a hardware configuration diagram of the capturing device;

[0026] FIG. 16 is a hardware configuration diagram of the communication terminal;

[0027] FIG. 17 is a hardware configuration diagram of an image management system or a link-information management system;

[0028] FIG. 18 is a functional block diagram of the communication terminal, the image management system, and the link-information management system according to the embodiment;

[0029] FIG. 19 is a conceptual diagram that illustrates an image management table;

[0030] FIG. 20 is a conceptual diagram that illustrates a thumbnail management table;

[0031] FIG. 21 is a conceptual diagram that illustrates a user management table;

[0032] FIG. 22 is a conceptual diagram that illustrates a related-person management table;

[0033] FIG. 23 is a conceptual diagram that illustrates a posted-data management table;

[0034] FIG. 24 is a sequence diagram that illustrates a process to upload image data;

[0035] FIG. 25 is a sequence diagram that illustrates a process to generate and upload a thumbnail;

[0036] FIG. 26 is a sequence diagram that illustrates a process to upload a thumbnail and link information;

[0037] FIG. 27 is a sequence diagram that illustrates a process to download image data;

[0038] FIG. 28 is a diagram that illustrates a captured image; and

[0039] FIG. 29 is a diagram that illustrates a partial image of the captured image that is presented on the display of the communication terminal.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0040] Exemplary embodiments of the present invention are explained in detail below with

reference to FIGS. **1** to **27**.

Outline of the Embodiment

[0041] First, an explanation is given, with reference to FIGS. **1** to **14**, of the outline of the present embodiment. FIG. **1** is a schematic view of an image sharing system according to the present embodiment.

[0042] As illustrated in FIG. **1**, the image sharing system according to the present embodiment is configured by using a capturing device **1**, a plurality of communication terminals (**3a**, **3b**), an image management system **5**, and a link-information management system **7**. Furthermore, the communication terminals (**3a**, **3b**) are used by users (A, B), respectively. In an example illustrated in the present embodiment, the capturing device **1** is operated by the user A. In the following, any communication terminal out of the communication terminals (**3a**, **3b**) is represented as the “communication terminal **3**”.

[0043] Furthermore, the capturing device **1** is a digital camera that captures fully-spherical panoramic images or omnidirectional images. The capturing device **1** may be a generally-used digital camera or, if a camera is installed on the communication terminal **3**, the communication terminal **3** may be a digital camera. In the present embodiment, in order to facilitate explanations, an explanation is given by using a digital camera that captures fully-spherical panoramic images or omnidirectional images. The communication terminal **3** is a computer, such as a smartphone, tablet terminal, notebook PC, desktop PC, or Personal Data Assistance (PDA). Furthermore, the image management system **5** and the link-information management system **7** are the server computers.

[0044] The capturing device **1** is capable of communicating with the communication terminal **3** by using a short-range wireless technology in accordance with a Near Field Communication (NFC) standard, Bluetooth (registered trademark), Wireless Fidelity (WiFi), or the like. Furthermore, the communication terminal **3** is capable of communicating with the image management system **5** and the link-information management system **7** via a communication network **9**. The communication network **9** is configured by using a radio communication network, such as 3rd Generation (3G), Worldwide Interoperability for Microwave Access (WiMAX), or Long Term Evolution (LTE), base stations (**9a**, **9b**), and the Internet. A wire communication may be performed between the capturing device **1** and the communication terminal **3** and between the communication terminal **3** and the communication network **9**.

[0045] A communication terminal **3a** is an example of a second communication terminal, and a communication terminal **3b** is an example of a first communication terminal.

[0046] Next, an explanation is given, with reference to FIGS. **2(a)**, **2(b)**, and **2(c)**, of the external of the capturing device **1**. FIG. **2(a)** is a left side view of the capturing device, FIG. **2(b)** is a front view of the capturing device, and FIG. **2(c)** is a plan view of the capturing device.

[0047] As illustrated in FIG. **2(a)**, the capturing device **1** has a size such that a person is able to hold it with one hand of the person. Furthermore, as illustrated in FIGS. **2(a)**, **2(b)**, and **2(c)**, an imaging element **103a** is provided on the front side (the anterior side) of the upper section of the capturing device **1**, and an imaging element **103b** is provided on the back side (the rear side) thereof. Moreover, as illustrated in FIG. **2(b)**, an operating unit **115**, such as a shutter button, is provided on the front side of the capturing device **1**.

[0048] Next, an explanation is given, with reference to FIG. **3**, of the situation where the capturing device **1** is used. FIG. **3** is a diagram that illustrates an image illustrating how the capturing device is used. As illustrated in FIG. **3**, the capturing device **1** is held by a user's hand and is used to capture objects around the user. In this case, objects around the user are captured by the imaging element **103a** and the imaging element **103b** that are illustrated in FIGS. **2(a)**, **2(b)**, and **2(c)**, whereby two hemispheric images can be obtained.

[0049] Next, an explanation is given, with reference to FIGS. **4(a)**, **4(b)**, and **4(c)**, of the images captured by the capturing device **1** and the combined image. FIG. **4(a)** is a diagram that illustrates the hemispheric image (the front) captured by the capturing device, FIG. **4(b)** is a diagram that

illustrates the hemispheric image (the back) captured by the capturing device, and FIG. 4(c) is a diagram that illustrates the image represented by using the Mercator projection (hereafter, referred to as a “Mercator image”).

[0050] As illustrated in FIG. 4(a), the image captured by the imaging element **103a** is the hemispheric image (the front side) that is distorted due to a fish-eye lens **102a**, which will be described later. Furthermore, as illustrated in FIG. 4(b), the image captured by the imaging element **103b** is the hemispheric image (the back side) that is distorted due to a fish-eye lens **102b**, which will be described later. The hemispheric image (the front side) and the hemispheric image (the back side) that is reversed 180 degrees are combined by the capturing device **1** so that the Mercator image is generated as illustrated in FIG. 4(c).

[0051] Next, an explanation is given, with reference to FIGS. 5(a), 5(b), and 6, of shared selection image data that is transmitted from the capturing device **1** to the communication terminal **3**. FIG. 5(a) is a diagram that illustrates the image represented by using the Mercator projection and the area of a shared selection image, and FIG. 5(b) is a diagram that illustrates the shared selection image. Furthermore, FIG. 6 is a diagram of a captured-image selection list that presents shared selection images.

[0052] As illustrated in FIG. 5(a), the area indicated by a dashed line in the Mercator image is used by the capturing device **1** so that the shared selection image data illustrated in FIG. 5(b) is generated. The shared selection image data is transmitted from the capturing device **1** to the communication terminal **3a**. As illustrated in FIG. 6, a shared image selection list SL that presents each shared selection image CE is displayed on a display **315** of the communication terminal **3a**. For example, buildings in a commercial area are displayed as the shared selection image CE, and the time and date (Sep. 20, 2011, 11:21) that the original image (the captured image illustrated in FIG. 5(a)) of the shared selection image CE is captured is displayed.

[0053] Next, an explanation is given, with reference to FIGS. 6 to 14, of the outline of a process to post and acquire image data according to the present embodiment. FIG. 6 is a diagram of a captured-image selection list that presents shared selection images. Furthermore, FIG. 7 is a diagram that illustrates a process to post and acquire image data.

[0054] First, when the user A selects the desired shared selection image CE illustrated in FIG. 6, the communication terminal **3a** acquires, from the capturing device **1**, the original image (the captured image) that is related to the above selected shared selection image CE (Step S1 in FIG. 7). Open Graphics Library for Embedded Systems (OpenGL ES) is used in the communication terminal **3a** so that the fully-spherical panoramic image illustrated in FIG. 8 is generated from the captured image (the Mercator image) illustrated in FIG. 5(a) (Step S2 in FIG. 7). OpenGL ES is a graphics library that is used for visualizing two-dimensional (2D) and three-dimensional (3D) data. FIG. 8 is a diagram that illustrates the fully-spherical panoramic image. The fully-spherical panoramic image may be a still image or moving image. For example, the Mercator image illustrated in FIG. 5(a) is attached to a solid sphere so that the fully-spherical panoramic image illustrated in FIG. 8 is generated.

[0055] Next, an explanation is given, with reference to FIGS. 7, 9, 10(a), and 10(b), of a process to generate and display an image at a predetermined area (hereafter, referred to as a “predetermined-area image”) of a fully-spherical panoramic image. FIG. 9 is a diagram that illustrates a virtual camera and the location of a predetermined area in a case where a fully-spherical panoramic image is a three-dimensional solid sphere. The virtual camera corresponds to the viewing location of the user who sees the fully-spherical panoramic image that is displayed as a three-dimensional solid sphere. Furthermore, FIG. 10(a) is a three-dimensional perspective view of FIG. 9, and FIG. 10(b) is a diagram that illustrates a communication terminal where a predetermined-area image is presented on the display.

[0056] The fully-spherical panoramic image illustrated in FIG. 8 is illustrated as a three-dimensional solid sphere CS. If the solid sphere CS of the fully-spherical panoramic image is

generated as illustrated, a virtual camera IC is located at the center of the fully-spherical panoramic image and can rotate about three axes, i.e., rotate from side to side and up and down about the center and rotate (roll) with respect to the point of view from the center, as illustrated in FIG. 9. A predetermined area T of the fully-spherical panoramic image can be determined by using predetermined-area information on the location of the virtual camera IC on the fully-spherical panoramic image. The predetermined-area information is represented by using the x-coordinate (rH), the y-coordinate (rV), and the angle of view α (angle). Thus, the zoom for the predetermined area T can be achieved by enlarging or reducing the range of the angle of view α (the circular arc). [0057] The image at the predetermined area T of the fully-spherical panoramic image illustrated in FIG. 10(a) is displayed as a predetermined-area image on the display 315 of the communication terminal 3a as illustrated in FIG. 10(b). In this case, the predetermined-area image is a partial image P.sub.0 that represents part of the fully-spherical panoramic image. The partial image P.sub.0 is the image that is presented by using the predetermined-area information (x, y, α)=(0, 0, 34) that is set by default with respect to the fully-spherical panoramic image illustrated in FIG. 8.

[0058] On the display 315 is displayed a predetermined-area image display region 3110 that displays a predetermined-area image, a thumbnail display region 3120 that displays the thumbnail of a predetermined-area image, and a comment display region 3130 that displays a user's comment.

[0059] Next, if the user A desires to display, on the display 315, the predetermined-area image to which the user A pays attention, and if the communication terminal 3a enables an operation via a touch panel, the user A moves the user's finger in contact with the display 315 vertically and horizontally, whereby the desired predetermined-area image illustrated in FIG. 11 is displayed. Furthermore, if the communication terminal 3a is a personal computer, or the like, the user A performs an input operation by using a mouse, or the like, so as to move it vertically and horizontally, whereby the desired predetermined-area image illustrated in FIG. 11 can be displayed. In this case, the predetermined-area image is a partial image P.sub.1 that illustrates part of the fully-spherical panoramic image.

[0060] Here, an explanation is given, with reference to FIG. 12, of the relation between predetermined-area information and a predetermined-area image. FIG. 12 is a diagram that illustrates the relation between predetermined-area information and a predetermined-area image.

[0061] As illustrated in FIG. 12, in the case of the diagonal angle of view 2L of the predetermined area T that is defined by the angle of view α of the virtual camera IC, a center point CP is the parameters (x, y) of the predetermined-area information. In the present embodiment, if the user A touches the display 315 with the user's finger to operate it so that the predetermined-area image (the partial image P.sub.1) is displayed as illustrated in FIG. 11, the predetermined-area information (x, y, α) is, for example, (230, 439, 35).

[0062] Furthermore, f is the distance from the virtual camera IC to the center point CP. The trigonometric function generally defined by the following Equation (1) is provided in FIG. 12.

$$Lf = \tan(\alpha/2) \quad (1)$$

[0063] Next, as illustrated in FIG. 7, after the communication terminal 3a transmits the image data to the image management system 5 via the communication network 9, the communication terminal 3a also transmits the predetermined-area information (Step S3). The image data is the image data on the Mercator image illustrated in FIG. 4(c), and the predetermined-area information is the predetermined-area information (230, 439, 35) that indicates the predetermined-area image (the partial image P.sub.1) illustrated in FIG. 11. Thus, the image management system 5 assigns, to the image data, the image ID (identification) for identifying the image data and also relates the image data to the image ID for management (Step S4). Furthermore, the image management system 5 generates link information (Step S4). As illustrated in FIG. 13, the link information includes the URL of the image management system 5, the image ID, and the predetermined-area information. Moreover, the image management system 5 generates thumbnail data of the image data (Step S4).

The URL is an example of specific information.

[0064] The image management system **5** then transmits the link information and the thumbnail data to the link-information management system **7** (Step **S5**). Accordingly, the link-information management system **7** manages the link information and the thumbnail data (Step **S6**).

[0065] When the communication terminal **3b** of the user B connects to the link-information management system **7** and requests display of corresponding image data, the link-information management system **7** transmits the link information to the communication terminal **3b** of the user B (Step **S7**).

[0066] In this case, the communication terminal **3b** displays a posting-view screen **3200** illustrated in FIG. **14**. The posting-view screen **3200** displays a user image **3210** that represents the appearance of the user A, a user name **3220** of the user A, a thumbnail **3230** of the image data, and a comment **3240** from the user A. Specifically, the thumbnail **3230** is an image obtained by reducing the size of the predetermined-area image (the partial image P.sub.1) illustrated in FIG. **11** and is not the image obtained by reducing the size of the predetermined-area image (the partial image P.sub.0) illustrated in FIG. **10(b)**. Thus, the user B can view the thumbnail of the desired predetermined-area image (the partial image P.sub.1) to which the user A pays attention or which is a recommended sight.

[0067] Next, the user B operates the communication terminal **3b** so as to select a thumbnail, and then the communication terminal **3b** transmits the link information to the image management system **5** (Step **S8**). Accordingly, the image management system **5** transmits, to the communication terminal **3b**, the image data related to the image ID that is extracted from the link information and transmits the predetermined-area information that is extracted from the link information (Step **S9**). With respect to the image data, the communication terminal **3b** then performs an operation to identify an area in the image data by using the predetermined-area information. Thus, the communication terminal **3b** displays the predetermined-area image (the partial image P.sub.1) illustrated in FIG. **11** instead of the predetermined-area image (the partial image P.sub.0) illustrated in FIG. **10(b)**.

[0068] As described above, the communication terminal **3b** downloads a captured image; however, this is not a limitation and the communication terminal **3a** may download a captured image.

Hardware Configuration According to the Embodiment

[0069] Next, a detailed explanation is given, with reference to FIGS. **15** to **17**, of hardware configurations of the capturing device, the communication terminal, the image management system, and the link-information management system according to the present embodiment.

[0070] First, an explanation is given, with reference to FIG. **15**, of a hardware configuration of the capturing device **1**. FIG. **15** is a hardware configuration diagram of the capturing device. In the following, the capturing device **1** is an omnidirectional capturing device that uses two imaging elements; however, three or more imaging elements may be used. Furthermore, the device does not necessarily need to be dedicated to omnidirectional capturing; therefore, an omnidirectional capturing unit may be additionally attached to a commonly used digital camera, smartphone, or the like, so that the device has substantially the same functionality as the capturing device **1**.

[0071] As illustrated in FIG. **15**, the capturing device **1** includes a capturing unit **101**, an image processing unit **104**, a capturing control unit **105**, a central processing unit (CPU) **111**, a read only memory (ROM) **112**, a static random access memory (SRAM) **113**, a dynamic random access memory (DRAM) **114**, an operating unit **115**, a network I/F **116**, a communication unit **117**, an antenna **117a**, and an electronic compass **118**.

[0072] Furthermore, the capturing unit **101** includes wide-angle lenses (what are called fish-eye lenses) **102a** and **102b** that have an angle of view of equal to or greater than 180° so as to form a hemispheric image and includes the two imaging elements **103a** and **103b** that are provided in relation to the wide-angle lenses. The imaging elements **103a** and **103b** include an image sensor, such as a complementary metal oxide semiconductor (CMOS) sensor or charge coupled device

(CCD) sensor, that converts an optical image formed by the fish-eye lens into image data using an electric signal for output; a timing generation circuit that generates horizontal or vertical synchronization signals for the image sensor, pixel clocks, or the like; a group of registers in which various commands, parameters, or the like, necessary for operations of the imaging element are set; and the like.

[0073] Each of the imaging elements **103a** and **103b** of the capturing unit **101** is connected to the image processing unit **104** via a parallel I/F bus. Furthermore, the imaging elements **103a** and **103b** of the capturing unit **101** are connected to the capturing control unit **105** via a serial I/F bus (an I2C bus, or the like). The image processing unit **104** and the capturing control unit **105** are connected to the CPU **111** via a bus **110**. Furthermore, the ROM **112**, the SRAM **113**, the DRAM **114**, the operating unit **115**, the network I/F **116**, the communication unit **117**, an electronic compass **118**, and the like, are connected to the bus **110**.

[0074] The image processing unit **104** acquires the image data that is output from the imaging elements **103a** and **103b** via the parallel I/F bus, performs a predetermined operation on the image data, and performs an operation to combine the image data so as to generate data on the Mercator image illustrated in FIG. 4(c).

[0075] Generally, the capturing control unit **105** uses the capturing control unit **105** as a master device and the imaging elements **103a** and **103b** as slave devices and uses the I2C bus to set commands, or the like, in the group of registers in the imaging elements **103a** and **103b**. Necessary commands, and the like, are received from the CPU **111**. Furthermore, the capturing control unit **105** also uses the I2C bus to acquire status data, and the like, from the group of registers in the imaging elements **103a** and **103b** and feeds it to the CPU **111**.

[0076] Moreover, the capturing control unit **105** instructs the imaging elements **103a** and **103b** to output image data when the shutter button of the operating unit **115** is pressed. In some cases, the capturing device has a preview function or a function that supports a movie display by using a display. In this case, image data is continuously output from the imaging elements **103a** and **103b** at a predetermined frame rate (frame/minute).

[0077] Furthermore, as described below, the capturing control unit **105** also functions as a synchronization control unit that synchronizes the image data output timings of the imaging elements **103a** and **103b** in cooperation with the CPU **111**. In the present embodiment, a display unit is not provided in the capturing device; however, a display unit may be provided.

[0078] The CPU **111** controls the overall operation of the capturing device **1** and performs necessary operations. The ROM **112** stores various programs for the CPU **111**. The SRAM **113** and the DRAM **114** are working memories that store a program executed by the CPU **111**, data that is being processed, and the like. Especially, the DRAM **114** stores the image data that is being processed by the image processing unit **104** or the data on the processed Mercator image.

[0079] The operating unit **115** is a generic term for various operation buttons, the power switch, the shutter button, the touch panel that has both display and operation functions, and the like. Users operate an operation button so as to input various capturing modes, capturing conditions, and the like.

[0080] The network I/F **116** is a generic term for interface circuits (a USB I/F, and the like) for external media, such as an SD card, a personal computer, or the like. Furthermore, in some cases, it is possible that the network I/F **116** is a network interface regardless of whether it is wireless or wired. Data on a Mercator image stored in the DRAM **114** is recorded in an external medium via the network I/F **116** or, if needed, is transmitted to an external device, such as the communication terminal **3**, via the network I/F **116** that is a network I/F.

[0081] The communication unit **117** communicates with an external device, such as the communication terminal **3**, via the antenna **117a** installed in the capturing device **1** by using a short-range wireless technology, such as Wireless Fidelity (WiFi) or NFC. The communication unit **117** is also capable of transmitting Mercator image data to an external device, such as the

communication terminal **3**.

[0082] The electronic compass **118** calculates the orientation and the tilt (the roll angle) of the capturing device **1** by using the earth magnetism and outputs the orientation/tilt information. The orientation/tilt information is an example of metadata in accordance with Exif and is used for image processing, such as image correction, on a captured image. The metadata includes various types of data, such as a thumbnail of image data, the capturing time and date of an image, or the data volume of image data.

[0083] Next, an explanation is given, with reference to FIG. **16**, of a hardware configuration of the communication terminal **3**. FIG. **16** is a hardware configuration diagram in a case where the communication terminal is a smartphone.

[0084] As illustrated in FIG. **16**, the communication terminal **3** includes a CPU **301** that controls the overall operation of the communication terminal **3**; a ROM **302** that stores basic input/output programs; a random access memory (RAM) **303** that is used as a work area for the CPU **301**; an electrically erasable and programmable ROM (EEPROM) **304** that performs reading or writing of data under the control of the CPU **301**; a CMOS sensor **305** that is an imaging element that captures an object and acquires the image data under the control of the CPU **301**; an electromagnetic compass or gyrocompass that detects the earth magnetism; various acceleration/orientation sensors **306**, such as an acceleration sensor; and a medium drive **308** that controls reading or writing (storing) of data from or to a recording medium **307**, such as a flash memory. The recording medium **307** is configured to be installed or removed, and the already recorded data is read from or new data is written and stored in the recording medium **307** under the control of the medium drive **308**.

[0085] The EEPROM **304** stores the operating system (OS) executed by the CPU **301**, other programs, and various types of data. Furthermore, a CCD sensor may be used instead of the CMOS sensor **305**.

[0086] The communication terminal **3** further includes a sound input unit **311** that converts sound into a sound signal; a sound output unit **312** that converts a sound signal into sound; an antenna **313a**; a communication unit **313** that communicates with the nearest base station **9a**, or the like, on the basis of a wireless communication signal by using the antenna **313a**; a Global Positioning System (GPS) receiving unit **314** that receives a GPS signal including the positional information (the latitude, longitude, and altitude) on the communication terminal **3** by using a GPS satellite or Indoor Messaging System that is an indoor GPS; the display **315** that is a liquid crystal display, organic EL display, or the like, that displays the image of an object, various icons, and the like; a touch panel **316** that is mounted on the display **315** and is made up of a pressure-sensitive or static panel so as to detect the touch location on the display **315** that is touched by a finger, stylus, or the like; and a bus line **310**, such as an address bus or data bus, that electrically connects the above-described units.

[0087] The sound input unit **311** includes a microphone that inputs sound, and the sound output unit **312** includes a speaker that outputs sound.

[0088] Next, an explanation is given, with reference to FIG. **17**, of a hardware configuration of the image management system **5** and the link-information management system **7**. FIG. **17** is a hardware configuration diagram of the image management system **5** or the link-information management system **7**. The image management system **5** and the link-information management system **7** are generally-used server computers; therefore, the configuration of the image management system **5** is explained below, and an explanation of the configuration of the link-information management system **7** is omitted.

[0089] The image management system **5** includes a CPU **501** that controls the overall operation of the image management system **5**; a ROM **502** that stores programs, such as IPL, that are used for driving the CPU **501**; a RAM **503** that is used as a work area for the CPU **501**; an HD **504** that stores various types of data, such as programs for the image management system **5**; a hard disk

drive (HDD) **505** that controls reading or writing of various types of data from or to the HD **504** under the control of the CPU **501**; a medium drive **507** that controls reading or writing (storing) of data from or to a recording medium **506**, such as a flash memory; a display **508** that displays various types of information, such as a cursor, menus, windows, characters, or images; a network I/F **509** that is used for data communication via the communication network **9**; a keyboard **511** that includes a plurality of keys to input characters, numbers, various instructions, or the like; a mouse **512** that selects or executes various instructions, select an object to be processed, moves the cursor, or the like; a CD-ROM (compact disc read only memory) drive **514** that controls reading or writing of various types of data from or to a CD-ROM **513** that is an example of a removable recording medium; and a bus line **510**, such as an address bus or data bus, that electrically connects the above-described components as illustrated in FIG. **17**.

Functional Configuration According to the Embodiment

[0090] Next, an explanation is given, with reference to FIG. **18**, of a functional configuration according to the present embodiment. FIG. **18** is a functional block diagram of the communication terminal **3**, the image management system **5**, and the link-information management system **7** that are included in the image sharing system according to the present embodiment. In FIG. **18**, the communication terminal **3**, the image management system **5**, and the link-information management system **7** can perform data communication via the communication network **9**.

Functional Configuration of the Communication Terminal

[0091] As illustrated in FIG. **18**, the communication terminal **3** includes a transmitting and receiving unit **31**, an operation input receiving unit **32**, a display control unit **33**, and a storage/read unit **39**. Each of the units is a function or means that is implemented when any of the components illustrated in FIG. **15** is operated in accordance with a command received from the CPU **111** that follows the program for the communication terminal **3** that is loaded from the SRAM **113** into the DRAM **114**.

[0092] Furthermore, the communication terminal **3** includes a storage unit **3000** that is configured by using the ROM **112**, the SRAM **113**, and the DRAM **114** that are illustrated in FIG. **15**.

Each Functional Configuration of the Communication Terminal

[0093] Next, a detailed explanation is further given, with reference to FIGS. **16** and **18**, of each functional configuration of the communication terminal **3**.

[0094] The transmitting and receiving unit **31** of the communication terminal **3** is principally implemented due to operations of the communication unit **313** and the CPU **301** that are illustrated in FIG. **16** so as to transmit and receive various types of data (or information) to and from the image management system **5** or the link-information management system **7** via the communication network **9**.

[0095] The operation input receiving unit **32** is principally implemented due to operations of the touch panel **316** and the CPU **301** so as to receive various selections or inputs from users.

[0096] The display control unit **33** is principally implemented due to an operation of the CPU **301** so as to perform control to display various images, characters, or the like, on the display **315**.

[0097] The storage/read unit **39** stores various types of data (or information) in the storage unit **3000** or reads various types of data (or information) from the storage unit **3000**.

Functional Configuration of Image Management System

[0098] Next, a detailed explanation is given, with reference to FIGS. **17** and **18**, of each functional configuration of the image management system **5**. The image management system **5** includes a transmitting and receiving unit **51**, an identification-information assignment unit **52**, a thumbnail generation unit **53**, a link-information generation unit **54**, an extraction unit **55**, and a storage/read unit **59**. Each of the units is a function or means that is implemented when any of the components illustrated in FIG. **17** is operated in accordance with a command received from the CPU **501** that follows the program for the image management system **5** that is loaded from the HD **504** into the RAM **503**.

[0099] Furthermore, the image management system 5 includes a storage unit **5000** that is configured by using the RAM **503** and the HD **504** that are illustrated in FIG. **17**. An image management DB **5001** is established in the storage unit **5000** and is configured by using an image management table, which will be described later. Furthermore, a thumbnail management DB **5002** is established in the storage unit **5000** and is configured by using a thumbnail management table, which will be described later.

Image Management Table

[0100] FIG. **19** is a conceptual diagram that illustrates an image management table. In the image management table, user ID for identifying a user, image ID for identifying image data, and the file name of the image data are stored in relation to one another for management. The user ID is an example of user identification information for uniquely identifying a user. The user identification information includes a service usage number, employee number, student ID number, citizen number based on a national identity numbering system, or the like. The image ID is an example of image identification information.

Thumbnail Management Table

[0101] FIG. **20** is a conceptual diagram that illustrates a thumbnail management table. In the thumbnail management table, thumbnail ID for identifying a thumbnail, image ID, and the file name of thumbnail data are stored in relation to one another for management. The thumbnail ID is an example of thumbnail identification information.

Each Functional Configuration of Image Management System

[0102] Next, a detailed explanation is given, with reference to FIGS. **17** and **18**, of each functional configuration of the image management system 5.

[0103] The transmitting and receiving unit **51** of the image management system 5 is principally implemented due to operations of the network I/F **509** and the CPU **501** that are illustrated in FIG. **17** so as to transmit and receive various types of data (or information) to and from the communication terminal 3 or the link-information management system 7 via the communication network 9.

[0104] The identification-information assignment unit **52** is principally implemented due to an operation of the CPU **501** that is illustrated in FIG. **17** so as to assign image ID to, for example, the image data on the Mercator image received by the transmitting and receiving unit **51** and attach the image ID to the header section of the image data, thereby managing the image data. Furthermore, the identification-information assignment unit **52** assigns thumbnail ID to the thumbnail data generated by the thumbnail generation unit **53** and attaches the thumbnail ID to the header section of the thumbnail data.

[0105] The thumbnail generation unit **53** is principally implemented due to an operation of the CPU **501** that is illustrated in FIG. **17** so as to generate thumbnail data from the predetermined area T of the image data as illustrated in FIGS. **9** to **12** by using the image data that is indicated by the image ID received by the transmitting and receiving unit **51** and by using the predetermined area T that is indicated by the predetermined-area information received by the transmitting and receiving unit **51**.

[0106] The link-information generation unit **54** is principally implemented due to an operation of the CPU **501** that is illustrated in FIG. **17** so as to link the URL of the image data indicated by the image ID received by the transmitting and receiving unit **51**, the image ID assigned by the identification-information assignment unit **52**, and the predetermined-area information received by the transmitting and receiving unit **51**, thereby generating the link information illustrated in FIG. **13**.

[0107] The extraction unit **55** is principally implemented due to an operation of the CPU **501** that is illustrated in FIG. **17** so as to extract the image ID and the predetermined-area information from the link information received by the transmitting and receiving unit **51**.

[0108] The storage/read unit **59** stores various types of data (or information) in the storage unit

5000 or reads various types of data (or information) from the storage unit **5000**.

Functional Configuration of Image Management System

[0109] Next, a detailed explanation is given, with reference to FIGS. **17** and **18**, of a functional configuration of the link-information management system **7**. The link-information management system **7** includes a transmitting and receiving unit **71**, a posting-view generation unit **72**, and a storage/read unit **79**. Each of the units is a function or means that is implemented when any of the components illustrated in FIG. **17** is operated in accordance with a command received from the CPU **501** that follows the program for the link-information management system **7** that is loaded from the HD **504** into the RAM **503**.

[0110] Furthermore, the link-information management system **7** includes a storage unit **7000** that is configured by using the RAM **503** and the HD **504** that are illustrated in FIG. **17**. A user management DB **7001**, a related-person management DB **7002**, and a posted-data management DB **7003** are established in the storage unit **7000**. The user management DB **7001** is made up of a user management table, which will be described later. The related-person management DB **7002** is made up of a related-person management table. The posted-data management DB **7003** is made up of a posted-data management table.

User Management Table

[0111] FIG. **21** is a conceptual diagram that illustrates the user management table. In the user management table, user ID, password used for user authentication, user image indicating the image of a user, and user personal information indicating the name of a user, or the like, are related for management.

Related-Person Management Table

[0112] FIG. **22** is a conceptual diagram that illustrates the related-person management table. In the related-person management table, the user ID of each registrant (user) is related to the user ID of a person (user) related to the registrant for management. An example of the related person includes the registrant's friend, family, employee of the same company, or the like.

Posted-Data Management Table

[0113] FIG. **23** is a conceptual diagram that illustrates the posted-data management table. In the posted-data management table, each user ID is related, for management, to the link information, the file name of thumbnail data, and the comment posted by the user.

Each Functional Configuration of Image Management System

[0114] Next, a detailed explanation is given, with reference to FIG. **18**, of each functional configuration of the link-information management system **7**.

[0115] The transmitting and receiving unit **71** of the link-information management system **7** is principally implemented due to operations of the network I/F **509** and the CPU **501** that are illustrated in FIG. **17** so as to transmit and receive various types of data (or information) to and from the communication terminal **3** or the image management system **5** via the communication network **9**.

[0116] The posting-view generation unit **72** is principally implemented due to an operation of the CPU **501** that is illustrated in FIG. **17** so as to generate the posting view illustrated in FIG. **14** on the basis of the posted-data management table.

[0117] The storage/read unit **79** stores various types of data (or information), such as image data, in the storage unit **7000** or reads various types of data (or information), such as image data, from the storage unit **7000**.

Process or Operation According to the Embodiment

[0118] Next, an explanation is given, with reference to FIG. **24**, of a process performed when the user A uses the communication terminal **3a** to upload image data on the captured image illustrated in FIG. **4(c)**. FIG. **24** is a sequence diagram that illustrates a process to upload the image data.

[0119] A communication performed among the communication terminal **3**, the image management system **5**, and the link-information management system **7** via the communication network **9** is a

HyperText Transfer Protocol (HTTP) communication using an HTTP protocol. The communication terminal **3a** corresponds to an HTTP client, and the image management system **5** and the link-information management system **7** correspond to HTTP servers.

[0120] First, the user A imports the image data on the captured image illustrated in FIG. **4(c)** from the capturing device **1** to the storage unit **3000** of the communication terminal **3a**. Next, the user A selects the image data that is to be uploaded, and then the operation input receiving unit **32** of the communication terminal **3a** receives a selection of the image data to be uploaded (Step **S11**).

[0121] The transmitting and receiving unit **31** of the communication terminal **3a** then transmits, to the image management system **5** via the communication network **9**, the user ID of the user A and the image data to be uploaded, thereby requesting the image to be registered (Step **S12**). Thus, the transmitting and receiving unit **51** of the image management system **5** receives the user ID and the image data.

[0122] Next, the identification-information assignment unit **52** of the image management system **5** assigns the image ID to the image data received at Step **S12** and attaches the image ID to the header section of the image data (Step **S13**).

[0123] The storage/read unit **59** then stores the user ID and the file name of the image data received at Step **S12** and the image ID assigned at Step **S13** in the image management table (see FIG. **19**) in relation to one another for management and also stores the image data in the storage unit **5000** for management (Step **S14**).

[0124] The transmitting and receiving unit **51** then transmits the image ID assigned at Step **S13** to the communication terminal **3a** via the communication network **9** so as to notify that the registration has been completed (Step **S15**). Thus, the transmitting and receiving unit **31** of the communication terminal **3a** receives the image ID. The storage/read unit **39** of the communication terminal **3a** stores the image ID for management (Step **S16**). In this situation, if the user A or the user B downloads the image data, the display **315** presents the predetermined-area image (the partial image P.sub.0) illustrated in FIG. **10(b)**; therefore, it is difficult for the user A or the user B to instantly recognize which image data has been downloaded. Hence, the user A performs the operation after Step **S21**, which is described below, whereby the downloaded image data can be easily recognized.

[0125] Next, an explanation is given, with reference to FIG. **25**, of a process to generate and upload a thumbnail. FIG. **25** is a sequence diagram that illustrates a process to generate and upload a thumbnail.

[0126] As illustrated in FIG. **25**, the user A uses the communication terminal **3a** to select the image data that is to be downloaded, and then the operation input receiving unit **32** of the communication terminal **3a** receives a selection of the image data to be downloaded (Step **S21**). Thus, the storage/read unit **39** reads the image ID of the selected image data from the storage unit **3000**.

[0127] The transmitting and receiving unit **31** of the communication terminal **3a** then transmits, to the image management system **5** via the communication network **9**, the image ID of the image data to be requested, thereby requesting the image (Step **S22**). Thus, the transmitting and receiving unit **51** of the image management system **5** receives the image ID.

[0128] Next, the storage/read unit **59** of the image management system **5** searches the image management table (see FIG. **19**) by using the image ID received at Step **S22** as a search key so as to extract the file name of the corresponding image data and also reads the image data that has the file name from the storage unit **5000** (Step **S23**).

[0129] The transmitting and receiving unit **51** then transmits, to the communication terminal **3a** via the communication network **9**, the image data read at the above-described Step **S23** and the image ID received at the above-described Step **S22** (Step **S24**). Thus, the transmitting and receiving unit **31** of the communication terminal **3a** receives the image data and the image ID, whereby the download of the image data is completed. In this situation, the communication terminal **3a** still displays the predetermined-area image (the partial image P.sub.0) illustrated in FIG. **10(b)** by

default.

[0130] The operation input receiving unit **32** of the communication terminal **3a** receives an operation from the user A, and thus the display control unit **33** changes the predetermined-area image (the partial image P.sub.0) illustrated in FIG. **10(b)** to the predetermined-area image (the partial image P.sub.1) illustrated in FIG. **11** (Step S25). At that time, the operation input receiving unit **32** receives an input of the comment (e.g., “the image of the first building”) from the user and also receives a request to display the predetermined-area image illustrated in FIG. **11** by default (Step S25).

[0131] Next, the transmitting and receiving unit **31** transmits, to the image management system **5** via the communication network **9**, the image ID, the predetermined-area information indicating the partial image P.sub.1, the comment, and the user ID so as to instruct the image management system **5** to post the link information (Step S26). Thus, the transmitting and receiving unit **51** of the image management system **5** receives the image ID, the predetermined-area information indicating the partial image P.sub.1, the comment, and the user ID.

[0132] The storage/read unit **59** then searches the image management table (see FIG. **19**) by using the image ID received at Step S26 as a search key so as to extract the file name of the corresponding image data and then read the image data from the storage unit **5000** by using the file name (Step S27). The thumbnail generation unit **53** generates thumbnail data from the predetermined area T of the image data as illustrated in FIGS. **9** to **12** by using the image data read at Step S27 and the predetermined area T indicated by the predetermined-area information received at Step S26 (Step S28).

[0133] The identification-information assignment unit **52** then assigns thumbnail ID to the thumbnail data generated at Step S28 and attaches the thumbnail ID to the header section of the thumbnail data (Step S29). The storage/read unit **59** then stores, in the thumbnail management table (see FIG. **20**), the thumbnail ID assigned at Step S29, the image ID received at Step S26, and the thumbnail data generated at Step S28 in relation to one another for management (Step S30).

[0134] The link-information generation unit **54** then links the URL of the image data indicated by the image ID received at Step S26, the image ID received at Step S26, and the predetermined-area information received at Step S26, thereby generating the link information illustrated in FIG. **13** (Step S31).

[0135] Next, an explanation is given, with reference to FIG. **26**, of a process to upload a thumbnail and link information. FIG. **26** is a sequence diagram that illustrates a process to upload a thumbnail and link information.

[0136] First, the transmitting and receiving unit **51** of the image management system **5** transmits, to the link-information management system **7** via the communication network **9**, the link information that is generated at the above-described Step S31 and the comment and the user ID that are received at the above-described Step S26 so as to request the link-information management system **7** to post the link information (Step S41). Thus, the transmitting and receiving unit **71** of the link-information management system **7** receives the link information, the comment, and the user ID.

[0137] The storage/read unit **79** of the link-information management system **7** then stores the user ID, the link information, and the comment, which are received at the above-described Step S41, in relation to one another for management in the posted-data management table (see FIG. **23**) (Step S42). In this situation, the link-information management system **7** does not manage thumbnail data. Therefore, the transmitting and receiving unit **71** accesses the image management system **5** that is indicated by the URL included in the link information so as to request the URL of the thumbnail data (Step S43). Thus, the transmitting and receiving unit **51** of the image management system **5** receives the request for the URL of the thumbnail data.

[0138] Next, the transmitting and receiving unit **51** of the image management system **5** transmits the URL of the thumbnail data to the link-information management system **7** via the communication network **9** (Step S44). Thus, the transmitting and receiving unit **71** of the link-

information management system 7 receives the URL of the thumbnail data.

[0139] The transmitting and receiving unit 71 of the link-information management system 7 accesses the image management system 5 that is indicated by the URL of the thumbnail data so as to request thumbnail data (Step S45). Thus, the transmitting and receiving unit 51 of the image management system 5 receives the request for the thumbnail data.

[0140] The transmitting and receiving unit 51 of the image management system 5 then transmits the thumbnail data to the link-information management system 7 via the communication network 9 (Step S46). Thus, the transmitting and receiving unit 71 of the link-information management system 7 receives the thumbnail data. The storage/read unit 79 additionally stores the file name of the thumbnail data received at the above-described Step S46 in the empty field section for the file name of the thumbnail data in the posted-data management table (see FIG. 23) and also stores the thumbnail data in the storage unit 7000 for management (Step S47).

[0141] Next, an explanation is given, with reference to FIG. 27, of a process to download image data. FIG. 27 is a sequence diagram that illustrates a process to download image data.

[0142] First, the communication terminal 3b transmits the user ID of the user B and the password to the link-information management system 7 via the communication network 9 so as to request login (Step S51). Thus, the link-information management system 7 receives the user ID of the user B and the password.

[0143] The storage/read unit 79 of the link-information management system 7 then determines whether the user ID and the password, which are transmitted at the above-described Step S51, are managed in the user management table (see FIG. 21) so as to perform user authentication (Step S52).

[0144] If it is determined that, as a result of the authentication, the same pair is managed and the user B is an authenticated user, the storage/read unit 79 searches the related-person management table (see FIG. 22) by using the user ID of the user B as a search key so as to read the user ID of the corresponding related person (Step S53).

[0145] Next, the posting-view generation unit 72 generates the posting-view screen illustrated in FIG. 14 (Step S54). Here, an explanation is given of a method of generating the posting-view screen. First, the storage/read unit 79 searches the user management table (see FIG. 21) by using the user ID (the user ID of the user A) read at the above-described Step S53 as a search key so as to read the file name of the corresponding user image data and the user personal information. Furthermore, the storage/read unit 79 searches the posted-data management table (see FIG. 23) by using the above-described user ID (the user ID of the user A) as a search key so as to read the corresponding link information, the file name of the thumbnail data, and the comment. Moreover, the file name of the user image data and the user personal information are read. The posting-view generation unit 72 generates the posting-view screen 3200 illustrated in FIG. 14. On the posting-view screen 3200, the user image 3210 is generated by using the image data indicated by the file name of the user image in the user management table (see FIG. 21). Furthermore, the “user A” 3220 is generated by using the user name indicated by the user personal information in the user management table (see FIG. 21). Moreover, the thumbnail 3230 is generated by using the thumbnail indicated by the file name of the thumbnail data in the posted-data management table (see FIG. 23). The “image of the first building” 3240 is generated by using the comment in the posted-data management table (see FIG. 23). The above-described link information is embedded in the thumbnail 3220 and the comment of “the image of the first building” 3240, and hyperlinks are attached thereto.

[0146] The transmitting and receiving unit 71 of the link-information management system 7 then transmits, to the communication terminal 3b via the communication network 9, the data on the posting-view screen generated at Step S54 (Step S55). Thus, the transmitting and receiving unit 31 of the communication terminal 3b receives the data on the posting-view screen. The display 315 of the communication terminal 3b then presents the posting-view screen illustrated in FIG. 14. As the

display **315** presents the thumbnail of the predetermined-area image (the partial image P.sub.1) illustrated in FIG. **11** instead of the thumbnail of the predetermined-area image (the partial image P.sub.0) illustrated in FIG. **10(b)**, the user B is able to easily determine whether the image data is to be downloaded.

[0147] Next, the operation input receiving unit **32** of the communication terminal **3b** receives, from the user B, a press of the thumbnail **3230** or the comment of “the image of the first building” **3240** on the posting-view screen **3200**, thereby receiving a selection of the link information (Step S56).

[0148] The transmitting and receiving unit **31** then transmits, to the image management system **5** via the communication network **9**, the link information (see FIG. **13**) selected at the above-described Step S56 so as to request the image data (Step S57). Thus, the transmitting and receiving unit **51** of the image management system **5** receives the link information.

[0149] The extraction unit **55** then extracts the image ID and the predetermined-area information from the link information received at the above-described Step S57 (Step S58). The storage/read unit **59** searches the image management table (see FIG. **19**) by using the image ID extracted at Step S58 as a search key so as to extract the file name of the corresponding image data and also reads the image data that has the file name from the storage unit **5000** (Step S59).

[0150] The transmitting and receiving unit **51** then transmits, to the communication terminal **3b** via the communication network **9**, the image data read at Step S59 and the image ID and the predetermined-area information extracted from the link information at Step S58 (Step S60). Thus, the transmitting and receiving unit **31** of the communication terminal **3b** receives the image data, the image ID, and the predetermined-area information.

[0151] As illustrated in FIG. **11**, the display control unit **33** of the communication terminal **3b** then generates and displays the predetermined-area image (the partial image P.sub.1) from the predetermined area T of the image data by using the image data and the predetermined-area information received at Step S60 (Step S61).

Principal Advantage of the Present Embodiment

[0152] As described above, in the present embodiment, the image management system **5** transmits, to the communication terminal **3b**, not only the image data but also the predetermined-area information that indicates the predetermined area T in the image data. Thus, it is possible to change the predetermined-area image that is set by default to be a local image around the center of the composition obtained when captured by a digital camera, or the like. Thus, an advantage is produced such that the user A is able to initially show to the user B the local image to which the user A pays attention or which is a recommended sight.

Additional Notes of the Embodiment

[0153] In the above-described embodiment, as illustrated in FIG. **13**, the link information includes the URL that indicates the location of the image management system **5** in the communication network **9**; however, this is not a limitation. For example, the link information may not include the URL and may be indicated by using the image ID and the predetermined-area information only. In this case, a user operates the communication terminal **3** to input the URL.

[0154] The image management system **5** and the link-information management system **7** according to the above-described embodiment may be configured by using a single computer or may be configured by using a plurality of computers to which each unit (function, means, or storage unit) is separated and assigned arbitrarily.

[0155] Furthermore, a recording medium, such as a CD-ROM, that stores each program according to the above-described embodiment or the HD **504** that stores the program may be provided as a program product in the country and overseas.

[0156] As described above, according to the present invention, the image management system transmits, to the first communication terminal, not only the image data but also the predetermined-area information that indicates the predetermined area in the image data. Thus, it is possible to change the predetermined-area image that is set, by default, to be a local image around the center of

the composition that is obtained when captured by a digital camera, or the like. Thus, an advantage is produced such that the user who uploads the image is able to initially show to another user the local image to which the user pays attention or which is a recommended sight.

[0157] Although the invention has been described with respect to specific embodiments for a complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art that fairly fall within the basic teaching herein set forth.

Claims

1. An image management system, comprising: circuitry configured to receive panoramic image data from a second terminal; circuitry configured to receive link information from a first terminal which is different from the second terminal, the link information corresponding to the panoramic image data, the link information being transmitted from and managed in a link information management system that is to communicate via a communication network with the image management system and is different from the image management system; and circuitry configured to transmit the panoramic image data to the first terminal so that the first terminal displays the panoramic image.
