



US012391526B2

(12) **United States Patent**
Smith et al.

(10) **Patent No.:** **US 12,391,526 B2**

(45) **Date of Patent:** ***Aug. 19, 2025**

(54) **JACKSTAND FOR AUTOMATED TRAILER
LOADING DOCK**

B66F 5/02 (2006.01)

B66F 5/04 (2006.01)

(71) Applicant: **Outrider Technologies, Inc.**, Brighton,
CO (US)

(52) **U.S. Cl.**
CPC **B66F 5/00** (2013.01); **B60D 1/665**
(2013.01); **B60R 9/06** (2013.01); **B66F 5/025**
(2013.01); **B66F 5/04** (2013.01)

(72) Inventors: **Andrew F. Smith**, Bend, OR (US);
Martin Edward Sotola, Boulder, CO
(US); **Peter James**, Denver, CO (US);
Lawrence S. Klein, Bend, OR (US);
Matthew Steven Johannes, Arvada,
CO (US); **Jonathan Record**, Highlands
Ranch, CO (US); **Garold McKinney**,
Colorado Springs, CO (US)

(58) **Field of Classification Search**
CPC B60S 9/04; B60S 9/00; B60S 9/20; B60S
9/16; B66F 5/00; B66F 5/02; B66F 5/04
See application file for complete search history.

(73) Assignee: **Outrider Technologies, Inc.**, Brighton,
CO (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,377,957 A 1/1995 Mosley
5,709,286 A 1/1998 Mead et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

FOREIGN PATENT DOCUMENTS

FR 2777025 A1 10/1999

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US2022/
017003, mailed Jun. 24, 2022, 12 pages.

(Continued)

(21) Appl. No.: **18/419,334**

(22) Filed: **Jan. 22, 2024**

(65) **Prior Publication Data**

US 2024/0158213 A1 May 16, 2024

Primary Examiner — Lee D Wilson

(74) *Attorney, Agent, or Firm* — Cozen O'Connor

Related U.S. Application Data

(63) Continuation of application No. 17/675,568, filed on
Feb. 18, 2022, now Pat. No. 11,878,897.

(Continued)

(57) **ABSTRACT**

Automated jackstand systems and methods deploy a jack-
stand to support a front end of a trailer parked at an
automated loading dock. The jackstand prevents collapse of
the trailer's landing gear and prevents upending of the trailer
during loading and unloading. Advantageously, by deploy-
ing the jackstand automatically, presence of personnel in the
yard where tractors and trailers are moving is not required.


(51) **Int. Cl.**

B66F 5/00 (2006.01)

B60D 1/66 (2006.01)

B60R 9/06 (2006.01)

20 Claims, 24 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 63/151,601, filed on Feb. 19, 2021.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,868,379	A	2/1999	Ellis	
6,089,544	A	7/2000	Ellis	
7,143,869	B1	12/2006	Chance	
8,191,865	B2	6/2012	Polins et al.	
10,065,689	B2	9/2018	Wiegel et al.	
10,662,043	B2	5/2020	De Jong	
11,878,897	B2 *	1/2024	Smith	B60D 1/665
2006/0119089	A1	6/2006	Rivers et al.	
2016/0001749	A1	1/2016	Kimener	
2019/0315319	A1	10/2019	Williams	
2020/0398910	A1	12/2020	Di Biase	
2022/0267127	A1 *	8/2022	Smith	B60D 1/665
2024/0158213	A1 *	5/2024	Smith	B66F 5/00

OTHER PUBLICATIONS

U.S. Appl. No. 17/675,568, Ex Parte Quayle Action dated Jun. 28, 2023, 6 pages.

* cited by examiner




FIG. 1




FIG. 4




FIG. 3




FIG. 2




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12






FIG. 13






FIG. 16




FIG. 17






FIG. 18






FIG. 21




Fig. 22




FIG. 23




FIG. 24




FIG. 25






FIG. 26






FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 36B




FIG. 36A




FIG. 35




FIG. 37




FIG. 38




FIG. 39





FIG. 40






FIG. 42




FIG. 43




FIG. 44

1

JACKSTAND FOR AUTOMATED TRAILER LOADING DOCK

RELATED APPLICATION

This application is a continuation of pending U.S. patent application Ser. No. 17/675,568, titled "Jackstand for Automated Trailer Loading Dock," filed Feb. 18, 2022, and which claims priority to U.S. Patent Application Ser. No. 63/151,601, titled "Jackstand for Automated Trailer Loading Dock," filed Feb. 19, 2021. Each of the aforementioned applications are incorporated herein by reference in their entirety.

BACKGROUND

Trucking is an essential part of modern commerce where trucks transport materials and finished goods across the continent within their large interior spaces. Such goods are loaded and unloaded at various facilities such as manufacturers, ports, distributors, retailers, and end users. Large over-the road (OTR) trucks typically consist of a tractor or cab unit and a separate detachable trailer that is removably interconnected to the tractor via hitching apparatus that includes a fifth-wheel on the tractor that physically couples with a kingpin on the trailer.

Challenges in trucking relate to docking, loading and unloading of goods to and from trailers. Warehouses and good distribution facilities have yards with multiple loading docks to allow concurrent loading and/or unloading of multiple trailers. A tractor positions its trailer at one of the docks and the tractor detaches, leaving the trailer at the loading dock. When the trailer is loaded and/or unloaded, a tractor (same or different one) couples with the trailer and moves it away from the dock.

SUMMARY

Safety is of utmost concern within the yard where many trailers may be parked for loading/unloading while others are being maneuvered to and from the docks. While parked at a loading dock, it is important to support the trailer as it is being loaded and unloaded, which occurs from the rear of the trailer, requiring that a front portion of the trailer be loaded first and unloaded last. This requirement makes the trailer susceptible to problems that arise when landing gear (the retractable legs positioned towards the front end of the trailer that are lowered when the tractor detaches) collapses and/or allows up-ending (when the landing gear is mounted to far from the front) of the detached trailer due to heavy front loading. Safety requires manual positioning of support (e.g., a jackstand) beneath the front end of the trailer after the tractor decouples and prior to the loading or unloading, and then removal of the support prior to the trailer being recoupled to the tractor and moved away from the loading dock. This manual handling of the support is a safety concern for the person(s) handling the support and is particularly undesirable when movement of the trailers within the yard is automated.

In one embodiment, an automated jackstand system supports a front end of a trailer parked at a loading dock. The automated jackstand system includes: a jackstand, having: a jack pad; a vertically extendable component coupling at a first end with the jack pad; a collar positioned on the vertically extendable component; and a mechanical socket positioned on the collar and mechanically geared to extend the vertically extendable component when rotated in a first

2

direction and to retract the vertically extendable component when rotated in a second direction opposite the first direction. The automated jackstand system also includes a grabber positioned at a back end of a yard tractor and having: at least two retractable claws operable by a first motor to removably couple with the collar; and a drive bit operable by a second motor and shaped and sized to mechanically couple with the mechanical socket, wherein the drive bit is positioned between the at least two retractable claws. The automated jackstand system also includes a controller, having machine-readable instructions stored in non-transitory memory that, when executed by a processor, control the first motor and the second motor to deploy the jackstand to support the front end of the trailer.

In another embodiment, a jackstand includes a jack pad, a vertically extendable component coupling at a first end with the jack pad, a collar positioned on the vertically extendable component, a fiducial marking positioned on the collar in a location for imaging by an imager located external to the jackstand, and a mechanical socket positioned on the collar and mechanically geared to extend the vertically extendable component when rotated in a first direction and to retract the vertically extendable component when rotated in a second direction opposite the first direction.

In another embodiment, an automated jackstand supports a front end of a trailer parked at a loading dock. The automated jackstand including: a baseplate; a vertical support coupled to the baseplate by a pivot positioned at a lower end of the vertical support; a jack pad positioned at a top end of the vertical support; an actuator positioned at the baseplate to generate a linear motion parallel to the baseplate; an arm having a first end pivotably coupled to the vertical support and a second end pivotably coupled to the actuator; and wherein the linear motion causes the arm to move the vertical support between a horizontal position and a vertical position.

In another embodiment, an automated jackstand system supports a trailer parked at a loading dock. The automated jackstand system including: a stepped block; a horizontally extendable component coupling at a first end with the stepped block; and a controller for remotely extending the horizontally extendable component to press the stepped block against a first side surface at a front end of the trailer.

In another embodiment, an automated jackstand system supports a trailer parked at a loading dock. The automated jackstand system includes: a jack pad; a vertically extendable component coupling at a first end with the jack pad; and a controller for remotely extending the vertically extendable component to press the jack pad against a lower surface of a front end of the trailer.

In another embodiment, an automated jackstand system supports a front end of a trailer parked at a loading dock. The automated jackstand system includes: a vertical post; a swing arm supported at one end by the vertical post; a first motor mechanically coupled with the vertical post and the swing arm, the first motor being operable to rotate the swing arm about the vertical post; a jackstand coupled with a distal end of the swing arm; and a second motor operable to extend and retract a vertical support of the jackstand.

In another embodiment, an automated jackstand system supports a front end of a trailer parked at a loading dock. The automated jackstand system includes: a vertical post; a swing arm supported at one end by the vertical post; a return spring for returning the swing arm to a resting position; a cable mechanically coupled with the vertical post and the swing arm; and a jackstand coupled with a distal end of the swing arm.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a perspective view showing one example jackstand for an automated trailer loading dock in a warehouse yard, in embodiments.

FIGS. 2-4 show one example automated jackstand that is pivotably movable between a flush position and a deployed position, in embodiments.

FIGS. 5-9 show one example jackstand that may be positioned manually and automatically extended beneath a trailer, in embodiments.

FIGS. 10-15 show one example jackstand that is embedded into the ground of a loading dock for automatic deployment beneath a trailer, in embodiments.

FIGS. 16-20 show one example jackstand mounted on a track for automatic positioning and deployment beneath a trailer, in embodiments.

FIGS. 21-24 show one example jackstand apparatus that uses at least one stepped block to support a trailer at a loading dock, in embodiments.

FIGS. 25-28 show one example jackstand apparatus with a swing arm for deploying a jackstand beneath a front end of a trailer, in embodiments.

FIGS. 29-32 shows one example post mounted jackstand apparatus that includes a vertical post secured at ground level to support two rotatable arms that position and deploy a jackstand beneath a front end of trailer, in embodiments.

FIGS. 33-39 show one example jackstand that is deployable by a grabber of a yard tractor, in embodiments.

FIGS. 40-42 show one example scissor jackstand installed in a recess in the ground and autonomously deployed to provide support to a front end of a trailer at a loading dock, in embodiments.

FIG. 43 shows one example jackstand apparatus with cable deployment mechanism that rotates a jackstand from a resting position to beneath a front end of a trailer, in embodiments.

FIG. 44 shows one example jackstand apparatus with a cable retrieval mechanism that rotates a jackstand from beneath a front end of a trailer to a resting position away from the trailer, in embodiments.

DETAILED DESCRIPTION OF THE EMBODIMENTS

One aspect of the present embodiments includes the realization that when jackstands are employed at a distribution centers and production facilities to prevent a collapse of a detached trailer due to trailer landing gear failure or to prevent up-ending of the detached trailer due to heavy front loading when the landing gear is mounted further back, a driver and/or ground personnel are required to locate and properly position a jackstand under the front of the trailer each time the trailer detaches from a tractor unit, and that the driver and/or ground personnel are also required to retract and stow the jackstand prior to attaching a tractor unit and moving the trailer. The present embodiments solve this problem by automatically deploying a jackstand at the front end of a trailer to provide safety and support of the trailer once the tractor unit detaches.

FIG. 1 is a perspective view showing example jackstands 100 for an automated trailer loading dock 102 in a warehouse yard 104. Each jackstand 100 is coupled with an controller 106 that moves, under control of a yard automation server 110, jackstand 100 to provide safety support of a detached trailer 108 at loading dock 102. In certain embodiments, trailers 108 within yard 104 are moved by a

yard tractor 112 that is controlled by yard automation server 110. For example, yard automation server 110 may control yard tractor 112 to position trailer 108 at loading dock 102 for loading/unloading and move trailer 108 away from loading dock 102 when loading/unloading is completed. Accordingly, yard automation server 110 automatically deploys jackstand 100 after yard tractor 112 decouples from trailer 108, and automatically retracts jackstand 100 prior to yard tractor 112 recoupling with trailer 108. Advantageously, jackstand 100 provides safety for loading and unloading of trailers at loading dock 102 without requiring manual deployment.

Although jackstand 100 is shown embedded into the ground, jackstand 100 may represent any of the following embodiments.

Automated Jackstands

FIGS. 2-4 show an automated jackstand 200 in which the trailer jackstand is pivotably movable between a flush position against the ground (FIG. 2) and an auto-deployed position, in which it pivots (curved arrow 212, about pivot axle 220) on its base 230. In this upright, deployed position (FIG. 3), the jack pads 240 on spaced apart legs 250 confront the bottom of the trailer 108. The jack pads 240 are then moved upwardly (arrows 320) on telescoping members 410 of the legs 250 until they pressurably engage the bottom of the trailer 108.

Hydraulic or pneumatic pistons can be used to drive the telescoping members 410. Likewise, a hydraulic, pneumatic or electromechanical system, with appropriate locking device(s), can be used to pivot the jackstand from a grounded orientation (FIG. 2) to a deployed orientation (FIGS. 3 and 4). The engagement of the jack pads 240 with the bottom of the trailer 108, provides further support for the landing gear 270, as well as the added benefit of securing the trailer against skidding away from the loading dock in the manner of wheel chocks. The automated jackstand 100 may either be permanently anchored to the ground for specific length trailers, or alternately, may be mounted on a sliding track that rides beneath the trailer, thereby allowing flexibility of variable trailer lengths, communicated via yard automation server 110 to a jackstand controller 106, which also controls pivoting deployment. In certain embodiments, jackstand 200 is manually deployed by a person at the dock once trailer 108 is parked at the dock and the tractor 112 has detached. In other embodiments, jackstand 200 is automatically deployed by yard automation server 110, for example, when yard tractor 112 indicates that trailer 108 is positioned at dock 102 and is detached.

One or more sensors may be used to ensure correct deployment of jackstand 200. In one embodiment, a pressure sensor or a force sensor is coupled with jack pad 240 to sense pressure of jack pad 240 against the bottom of the trailer 108. In another embodiment, pressure sensors are configured to sense pressure within a supply line to a lower chamber of a hydraulic cylinder that moves the jack pads 240 upwards, whereby an increase in pressure indicates contact of jack pads 240 against the bottom of the trailer 108. In another embodiment where telescoping members 410 of the legs 250 are moved by electric motor, a current sensor may sense current driving the motor, whereby an increase in current indicates pressure of jack pads 240 against the bottom of the trailer 108. In another embodiment, one or more inertial measurement units (IMU) and/or accelerometers are coupled with jack pads 240 or telescoping members 410 to sense when jack pads 240 contact the bottom of the trailer

5

108. In another embodiment, jack pads 240 include at least one limit switch that is depressed when jack pads 240 are pressed against the bottom of the trailer 108. In another embodiment, jackstand 200 includes at least one ultrasonic and/or laser range finder type sensor that measures a distance/range between jack pads 240 and the bottom of the trailer 108. In another embodiment, at least one jack pad 240 includes an inductive sensor that senses proximity of the bottom of the trailer 108 when a fifth-wheel plate of trailer 108 is magnetic and/or ferrous. These sensors provide feedback that allows controller 106 to determine when jackstand 200 is correctly deployed.

Trolley-Jack Style

FIGS. 5-9 show one example jackstand 500 that may be positioned manually and automatically extended (e.g., deployed) beneath trailer 108. FIG. 5 is a plan view and FIG. 6 is a side elevation of jackstand 500 in an extended state. FIG. 7 is a side elevation of jackstand 500 in a retracted state. FIG. 8 is a plan view of a loading dock 802 showing jackstand 500 positioned to support a front end of a long trailer 108 (e.g., 57 feet, shown in dashed outline). FIG. 9 is a side elevation of loading dock 802 with jackstand 500 extended to support the front end of trailer 108. FIGS. 5-9 are best viewed together with the following description.

Jackstand 500 includes a baseplate 502 that has a handle 504 positioned at one end and at least one wheel 506 (e.g., shown with two wheels 506(1) and 506(2)) positioned at an opposite end. Handle 504 allows a person to lift that end of jackstand 500 such that jackstand 500 may roll on wheel(s) 506. In certain embodiments, wheels 506 are positioned such that, when baseplate 502 is flat on the ground, wheels 506 provide no support, but when handle 504 is lifted, wheels 506 contact the ground to provide support of baseplate 502. Baseplate 502 may include a dense rubber mat affixed to a lower surface of the baseplate to provide better grip of a concrete surface (which may have micro grit/pebbles, etc.). Jackstand 500 has at least one leg 602 that is pivotably attached to one end of baseplate 502 and has a jack pad 508 pivotably attached to the opposite end. A first end of a deployment arm 510 is pivotably attached to the at least one leg 602 and an opposite end of the deployment arm 510 is pivotably attached to a carriage 512 mechanically coupled with an actuator 514 (e.g., a linear actuator). In one example, actuator 514 is a screw mechanism that includes a threaded rod that is turned by a motor to move carriage 512, also threaded and mechanically engaged with actuator 514, in a straight line along a plane parallel to baseplate 502. In another embodiment, actuator 514 is a hydraulic piston that moves carriage 512 in a straight line along a plane parallel to baseplate 502. As carriage 512 moves, deployment arm 510 moves leg 602 between a flat position shown in FIG. 7 to a vertical position shown in FIG. 6.

In certain embodiments, leg 602 is sized to press jack pad 508 against a lower surface of trailer 108, as shown in FIG. 9, as leg 602 reaches a vertical position. In other embodiments, leg 602 is sized to reach a vertical position without jack pad 508 contacting the lower surface of trailer 108, and leg 602 includes an extension mechanism (not shown) that extends vertically to press jack pad 508 against the lower surface of trailer 108. The extension mechanism could be any one or more of a screw jack, a hydraulic jack, a scissor jack, and so on.

Advantageously, jackstand 500 may be easily repositioned to accommodate trailers of different sizes. For example, as shown in FIG. 8, for a short trailer 109,

6

jackstand 500 may be moved to position 850 prior to deployment beneath a front end of short trailer 109. This is particularly beneficial for accommodating trailers of non-standard lengths at loading dock 802. Further, since jackstand 500 folds down flat when not deployed, jackstand 500 is below the ground clearance height of trailer 108 and may thereby be left in position as trailer 108 is moved in and/or out of loading dock 802. Jackstand 500 may be remotely deployed by a controller 106 via a coupling 810 (e.g., an electrical cable and/or a hydraulic and/or pneumatic hose) and may be semi-autonomously controlled by yard automation server 110.

One or more sensors may be used to ensure correct deployment of jackstand 500. In one embodiment, a pressure sensor or a force sensor is coupled with jack pad 508 to sense pressure of jack pad 508 against the bottom of trailer 108. In another embodiment, pressure sensors are configured to sense pressure within a supply line to a lower chamber of a hydraulic cylinder within extendable leg 602 that moves the jack pads 508 upwards, whereby an increase in pressure indicates contact of jack pads 508 against the bottom of trailer 108. In another embodiment, one or more inertial measurement units (IMU) and/or accelerometers are coupled with jack pads 508 to sense when jack pads 508 contact the bottom of trailer 108. In another embodiment, jack pads 508 include at least one limit switch that is depressed (e.g., coupled to a pin that extends above the top surface of jack pad 508) when jack pads 508 are pressed against the bottom of trailer 108. In another embodiment, jackstand 500 includes at least one ultrasonic and/or laser range finder type sensor that measures a distance/range between jack pads 508 and the bottom of trailer 108. In another embodiment, jack pad 508 includes an inductive sensor that senses proximity of the bottom of trailer 108 when a fifth-wheel plate of trailer 108 is magnetic and/or ferrous. These sensors provide feedback that allows controller 106, or a person when manually controlled, to determine when jackstand 500 is correctly deployed.

Embedded Style

FIGS. 10, 11, 14 and 15 show one example jackstand 1000 that is embedded into the ground of a loading dock 1402 (e.g., loading dock 102, FIG. 1) and may be automatically extended (e.g., deployed) beneath a trailer (e.g., trailer 108, FIG. 1). FIGS. 12 and 13 show one example jackstand 1200, similar to jackstand 1000 of FIGS. 10 and 11 but is configured with an enlarged jack pad 1208 for improved contact and force distribution across a bottom surface of trailer 108. FIGS. 10-15 are best viewed together with the following description.

Jackstand 1000 includes a piston 1002 operable to move a jack pad 1008 in a vertical direction between ground level 1050 and a front end lower surface of a trailer 108. That is, when not deployed, a top surface 1010 of jack pad 1008 is positioned substantially at ground level 1050, and piston 1002 is operable to raise jack pad 1008 to a height greater than a lower surface of the trailer front end. Accordingly, jackstand 1000 can support the weight at the front end of trailer 108. In the examples of FIGS. 10, 11, 14 and 15, jack pad 1008 is circular, but could be of any shape or size that is suitable for contacting and supporting the front end of trailer 108. For example, as shown in FIGS. 12 and 13, jackstand 1200 is similar to jackstand 1000 but jack pad 1008 is replaced with jack pad 1208 that is rectangular to provide improved contact and load distribution across the lower surface of the front end of trailer 108. An upper

surface **1210** of jack pad **1208** is substantially at ground level **1050** when jackstand **1200** is not deployed.

As shown in FIGS. **14** and **15**, one or more jackstands **1000** and/or **1200** may be embedded into the ground of a loading dock (e.g., loading dock **102**, FIG. **1**) and may be automatically extended (e.g., deployed) beneath a trailer **108**. Particularly, one or more jackstands **1000** and/or **1200** are positioned to accommodate different lengths of trailer. As shown in the example of FIG. **14**, jackstand **1000** is positioned to be beneath a front of trailer **108** and jackstand **1200** is positioned to be at a front of short trailer **109**. Advantageously, multiple jackstands **1000/1200** (e.g., of either type) may be positioned within loading to accommodate trailers of different lengths. For example, commonly used trailer lengths include 20, 40, 45, 48, and 53 feet. As described above, controller **106** may be controlled by yard automation server **110** to deploy the appropriate jackstand **1000/1200**, since yard automation server **110** is aware of the length of each trailer **108/109** being positioned at loading docks **1402**.

One or more sensors may be used to ensure correct deployment of jackstands **1000** and/or **1200**. In one embodiment, a pressure sensor or a force sensor is coupled with jack pad **1008/1208** to sense pressure of jack pad **1008/1208** against the bottom of trailer **108**. In another embodiment, pressure sensors are configured to sense pressure within a supply line **1004** to a lower chamber of a hydraulic cylinder that moves the jack pad **1008/1208** upwards, whereby an increase in pressure indicates contact of jack pad **1008/1208** against the bottom of trailer **108**. In another embodiment, one or more inertial measurement units (IMU) and/or accelerometers are coupled with jack pad **1008/1208** to sense when jack pad **1008/1208** contacts the bottom of trailer **108**. In another embodiment, jack pad **1008/1208** includes at least one limit switch that is depressed when jack pad **1008/1208** are pressed against the bottom of trailer **108**. In another embodiment, jackstand **1000/1200** includes at least one ultrasonic and/or laser range finder type sensor that measures a distance/range between jack pad **1008/1208** and the bottom of trailer **108**. In another embodiment, jack pad **1008/1208** includes one or more inductive sensors that senses proximity of the bottom of trailer **108** when a fifth-wheel plate of trailer **108** is magnetic and/or ferrous. These sensors provide feedback that allows controller **106** to determine when jackstand **1000/1200** is correctly deployed.

Central Track Mount

FIGS. **16-20** show one example jackstand **1600** mounted on a track **1612** for automatic positioning and deployment beneath a trailer. FIG. **16** is a side elevation showing jackstand **1600** in a deployed position. FIG. **17** is a top view showing jackstand **1600** in a folded position. FIG. **18** is a side elevation showing jackstand **1600** in the folded position. FIG. **19** is a top view of jackstand **1600** positioned centrally in a loading dock **1902**. FIG. **20** is a side elevation showing jackstand **1600** deployed in loading dock **1902** of FIG. **19**. FIGS. **16-20** are best viewed together with the following description.

Jackstand **1600** includes a baseplate **1602** that pivotably supports a first end of an extendable leg **1604** that is moved (about the pivot) between a horizontal position and a vertical position by a deployment arm **1606**. A jack pad **1608** is pivotably attached to a second end (opposite the first end) of extendable leg **1604** and may be positioned by extendable leg **1604** to press against an under surface of a front end of trailer **108**. In certain embodiments, deployment arm **1606** is

a hydraulic piston. In other embodiments, deployment arm **1606** is a screw mechanism that raises and lowers extendable leg **1604**.

Baseplate **1602** also include a plurality of wheels **1610** aligned and positioned to run on tracks **1612** that may be positioned at or below ground level within loading dock **1902**. In certain embodiments, wheels **1610** are driven by a motor **1702**, under control of controller **106**, to move along track **1612**. However, other components (e.g., hydraulic rams, screw mechanism, cables, belt, rack-and-pinion, and so on) may be used to move baseplate **1602** along tracks **1612**. Although shown as wheels running on top of a track, other arrangements are envisaged for preventing the baseplate from becoming derailed from the tracks. In certain embodiments, one or more sensors and/or encoders are included to determine a location of baseplate **1602** along tracks **1612**. In one example, motor **1702** includes an encoder to measure movement of baseplate **1602**. In another example, baseplate **1602** includes a horizontal laser/ultrasonic rangefinder that measures a distance between baseplate **1602** and dock **1902**. In another example, a linear potentiometer is used to measure distance between baseplate **1602** and dock **1902**. In another example, baseplate **1602** includes a camera for capturing images indicative of a distance between baseplate **1602** and dock **1902**.

In certain embodiments, jackstand **1600** includes one or more of a vertical laser/ultrasonic rangefinder, and a camera, that provides input to enable controller **106** to detect a front end of trailer **108**, and thereby position baseplate **1602** beneath a front end of trailer **108**. In certain embodiments, tractor **112** may provide a location of the front end of trailer **108** to controller **106** and/or yard automation server **110** when dropping trailer **108** at dock **1902**.

In FIGS. **16-20**, extendable leg **1604** is shown as a hydraulic piston, but extendable leg **1604** may be implemented in other ways without departing from the scope hereof. In one example, extendable leg **1604** is implemented as a scissor mechanism driven by an electric motor that raises and lowers jack pad **1608** relative to baseplate **1602**. In another example, extendable leg **1604** is implemented as a screw mechanism, driven by an electric motor, that raises and lowers jack pad **1608** relative to baseplate **1602**.

As shown in FIG. **19**, track **1612** may be aligned with a center line **1904** of loading dock **1902** such that wheels of trailer **108**, when maneuvered into loading dock **1902**, straddle jackstand **1600**. Where loading dock **1902** is angled, track **1612** may also be angled. Jackstand **1600** folds down flat, as shown in FIGS. **17-19**, such that a highest point of jackstand **1600** is below a ground clearance height of trailer **108**. Yard automation server **110** may instruct controller **106** to retract jackstand **1600** prior to movement of trailer **108** to or from loading dock **1902**. In certain embodiments, yard automation server **110** may also position baseplate **1602** nearer to the dock to reduce likelihood of wheels of trailer **108** running over jackstand **1600** during maneuvering into and out of loading dock **1902**. However, since jackstand **1600** is substantially flat and durable, even when run over by wheels of trailer **108**, neither trailer **108** nor jackstand **1600** are likely damaged. In the example of FIG. **20**, track **1612** is positioned below a surface of the ground, thereby further reducing likelihood of damage from inadvertent contact between a wheel of trailer **108** and jackstand **1600**.

One or more sensors may be used to ensure correct deployment of jackstand **1600**. In one embodiment, a pressure sensor or a force sensor is coupled with jack pad **1608** to sense pressure of jack pad **1608** against the bottom of trailer **108**. In another embodiment, pressure sensors are

configured to sense pressure within a supply line to a lower chamber of a hydraulic cylinder within extendable leg **1604** that moves the jack pad **1608** upwards, whereby an increase in pressure indicates contact of jack pad **1608** against the bottom of trailer **108**. In another embodiment, one or more inertial measurement units (IMU) and/or accelerometers are coupled with jack pad **1608** to sense when jack pad **1608** contacts the bottom of trailer **108**. In another embodiment, jack pad **1608** includes at least one limit switch that is depressed when jack pad **1608** presses against the bottom of trailer **108**. In another embodiment, jackstand **1600** includes at least one ultrasonic and/or laser range finder type sensor that measures a distance/range between jack pad **1608** and the bottom of trailer **108**. In another embodiment, jack pad **1608** includes an inductive sensor that senses proximity of the bottom of trailer **108** when a fifth-wheel plate of trailer **108** is magnetic and/or ferrous. These sensors provide feedback that allows controller **106** to determine when jackstand **1000/1200** is correctly deployed.

Stepped Supports

FIGS. **21-24** show one example jackstand apparatus **2100** that uses at least one stepped block **2102** to support trailer **108** at a loading dock **2122**. FIG. **21** is an end elevation showing a front of trailer **108** positioned at loading dock **2122**, decoupled from yard tractor **112**, prior to deployment of stepped blocks **2102** of jackstand apparatus **2100**. FIG. **22** is an end elevation, similar to FIG. **21**, showing the front of trailer **108** with stepped blocks **2102** of jackstand apparatus **2100** deployed to support the front of trailer **108**. FIG. **23** is a top view of jackstand apparatus **2100** positioned on both sides of loading dock **2122**. FIG. **24** is a side elevation showing jackstand apparatus **2100** deployed in loading dock **2122** of FIG. **21**. FIGS. **21-24** are best viewed together with the following description.

In the example of FIGS. **21-24**, jackstand apparatus **2100** has two similar parts **2101(1)** and **2101(2)**, each part **2101** being positioned at opposite sides of loading dock **2122**, with each part **2101** having stepped block **2102(1)** and **2102(2)** having the stepped part facing towards trailer **108**. Although only one part **2101** could be used to support trailer **108**, the use of two separate parts **2101(1)** and **2101(2)** eliminates the possibility of trailer **108** twisting upon collapse. The following description applies to both parts **2101** of jackstand apparatus **2100**.

Jackstand apparatus **2100** includes a baseplate **2104** that has a plurality of wheels **2106** aligned to run along tracks **2108**. For example, wheels **2106** may be driven by an electric motor **2107** to move baseplate **2104** along track **2108** in order to position stepped block **2102** for trailers of different length. However, other components (e.g., hydraulic rams, screw mechanism, cables, belt, rack-and-pinion, and so on) may be used to move baseplate **2104** along tracks **2108**. Although shown as wheels running on top of a track, other arrangements are envisaged that prevent the baseplate from becoming derailed from the tracks. Jackstand apparatus **2100** includes an extendable arm **2112** coupled at one end with stepped block **2102** and at the other end with baseplate **2104** via a post **2110**. As shown in FIG. **23**, each of tracks **2108(1)** and **2108(2)** is positioned on a different side of loading dock **2122** and running substantially parallel to trailer **108**. As baseplate is driven along tracks **2108**, post **2110** and extendable arm **2112** move stepped block **2102** in a direction substantially parallel to trailer **108** such that stepped block **2102** may be positioned at a front end of trailer **108**, irrespective of the trailer's length. In certain

embodiments, stepped block **2102** may include wheels/casters **2114** to facilitate maneuverability of stepped block **2102** by extendable arm **2112**.

In certain embodiments, one or more sensors and/or encoders are included to determine a location of baseplate **2104** along tracks **2108**. In one example, motor **2107** includes an encoder to measure movement of baseplate **2104**. In another example, baseplate **2104** includes a horizontal laser/ultrasonic rangefinder that measures a distance between baseplate **2104** and dock **2122**. In another example, a linear potentiometer is used to measure distance between baseplate **2104** and dock **2122**. In another example, baseplate **2104** includes a camera for capturing images indicative of a distance between baseplate **2104** and dock **2122** and/or a position of baseplate **2104** with respect to a front end of trailer **108**.

As shown in FIGS. **21-24**, extendable arm **2112** may be implemented as a hydraulic piston; however, extendable arm **2112** may be implemented in other ways, including a scissor mechanism, a screw mechanism, and so on, without departing from the scope hereof. Extendable arm **2112** is extended to push stepped block **2102** beneath a corresponding side of trailer **108**. Extendable arm **2112** is extended until a part of stepped block contacts a corresponding side of trailer **108**. Stepped block **2102** prevents a front end of trailer **108** from collapse when the underside of the trailer contacts one of the steps of stepped block **2102**. Each track **2108** is positioned between adjacent loading docks **2122** and may support at least two jackstands such that adjacent loading docks share the same track **2108**.

One or more sensors may be used to ensure correct deployment of jackstand apparatus **2100**. In one embodiment, a pressure sensor or a force sensor is coupled with stepped block **2102** to sense pressure of stepped block **2102** against a side of trailer **108**. In another embodiment, pressure sensors are configured to sense pressure within a supply line to a lower chamber of a hydraulic cylinder within extendable arm **2112** that moves stepped block **2102** laterally, whereby an increase in pressure indicates contact of stepped block **2102** against the side of the trailer **108**. In another embodiment, one or more inertial measurement units (IMU) and/or accelerometers are coupled with stepped block **2102** to sense when stepped block **2102** contacts the side of the trailer **108**. In another embodiment, stepped block **2102** includes at least one limit switch that is depressed when stepped block **2102** presses against the side of the trailer **108**. In another embodiment, jackstand apparatus **2100** includes at least one ultrasonic and/or laser range finder type sensor that measures a distance/range between stepped block **2102** and the side of trailer **108**. In another embodiment, stepped block **2102** includes at least one inductive sensor that senses proximity of the side of trailer **108** when magnetic and/or ferrous. These sensors provide feedback that allows controller **106** to determine when jackstand apparatus **2100** is correctly deployed.

Swing Arm Deployment

FIGS. **25-28** show one example jackstand apparatus **2500** with a swing arm **2502** for deploying a jackstand **2550** beneath a front end of trailer **108**. In certain embodiments, jackstand **2550** is a conventional jackstand that is deployed by jackstand apparatus **2500**. FIG. **25** is an end elevation showing jackstand apparatus **2500** with a swing arm **2502** deploying a jackstand **2550**. FIG. **26** is a top view of jackstand apparatus **2500** of FIG. **25**. FIG. **27** is a top view of a loading dock

11

Jackstand apparatus **2500** includes a baseplate **2504** with a plurality of wheels **2506** aligned to run along tracks **2508**. In certain embodiments, wheels **2506** are driven by an electric motor **2602** to move baseplate **2504** along track **2508** to accommodate trailers of different length. However, other components (e.g., hydraulic rams, screw mechanism, cables, belt, rack-and-pinion, and so on) may be used to move baseplate **2504** along tracks **2508**. Although shown as wheels running on top of a track, other arrangements are envisaged for preventing the baseplate from becoming derailed from the tracks. A vertical post **2510** couples with baseplate **2504** and pivotably supports a first end of swing arm **2502**. A motor **2512** is mechanically coupled with vertical post **2510** and swing arm **2502** is operable to rotate swing arm **2502** around vertical post **2510**. A distal second end, opposite the first end, of swing arm **2502** couples with a jackstand **2550** that includes a vertical support **2552** and a jack pad **2558** attached at a top end of vertical support **2552**. In certain embodiments, jackstand **2550** may include wheels/casters **2560** to facilitate movement of jackstand **2550** by swing arm **2502**. Controller **106** controls baseplate **2504** and swing arm **2502** to position jackstand **2550** beneath a lower surface of a front end of trailer **108**.

In certain embodiments, one or more sensors and/or encoders are included to determine a location of baseplate **2504** along tracks **2508**. In one example, motor **2602** includes an encoder to measure movement of baseplate **2504**. In another example, baseplate **2504** includes a horizontal laser/ultrasonic rangefinder that measures a distance between baseplate **2504** and dock **2702**. In another example, a linear potentiometer is used to measure distance between baseplate **2504** and dock **2702**. In another example, baseplate **2504** includes a camera for capturing images indicative of a distance between baseplate **2504** and dock **2702** and/or a position of baseplate **2504** with respect to a front end of trailer **108**.

As shown in FIG. 27, track **2508** is located in an area adjacent loading dock **2702**, and runs parallel to trailers positioned at loading dock **2702**. Track **2508** may thus be positioned between adjacent loading docks in yard **104**. Controller **106** controls the position of baseplate **2504** on track **2508**, controls an angle of rotation of swing arm **2502** relative to baseplate **2504**, and controls a motor **2514** that extends and retracts vertical support **2552**. As shown in FIG. 27, dashed outline **2501** represents a “parked” position for jackstand apparatus **2500** that allows movement of trailer **108** to and from loading dock **2702**.

In one example of operation, after yard tractor **112** has positioned trailer **108** at loading dock **2702** and decoupled therefrom, yard automation server **110** causes controller **106** to move baseplate **2504** to align with a front end of trailer **108**, and then causes controller **106** to rotate swing arm **2502** to position jackstand **2550** beneath the front end of trailer **108**, and to extend vertical support such that jack pad **2558** contacts the lower surface of the front end of trailer **108** and a bottom end of jackstand **2550** contact the ground. Thereby, jackstand **2550** provides additional support at the front end of trailer **108**. When trailer is ready to depart from loading dock **2702**, yard automation server **110** causes controller **106** to retract jackstand **2550**, rotate swing arm **2502** relative to baseplate **2504** such that it is parallel to tracks **2508**, and then move baseplate **2504** to an end of track **2508** (e.g., position of dashed outline **2501**).

One or more sensors may be used to ensure correct deployment of jackstand **2550**. In one embodiment, a pressure sensor or a force sensor is coupled with jack pad **2558** to sense pressure of jack pad **2558** against the bottom of

12

trailer **108**. In another embodiment, a current sensor measures current of motor **2514** that moves the jack pad **1608** upwards, whereby an increase in current indicates contact of jack pad **2558** against the bottom of trailer **108**. In another embodiment, one or more inertial measurement units (IMU) and/or accelerometers are coupled with jack pad **2558** to sense when jack pad **2558** contacts the bottom of trailer **108**. In another embodiment, jack pad **2558** includes at least one limit switch that is depressed when jack pad **2558** presses against the bottom of trailer **108**. In another embodiment, jackstand **2550** includes at least one ultrasonic and/or laser range finder type sensor that measures a distance/range between jack pad **2558** and the bottom of trailer **108**. In another embodiment, jack pad **2558** includes an inductive sensor that senses proximity of the bottom of trailer **108** when a fifth-wheel plate of trailer **108** is magnetic and/or ferrous. These sensors provide feedback that allows controller **106** to determine when jackstand **2550** is correctly deployed.

Post Mounted Jackstands

FIGS. 29-32 shows one example post mounted jackstand apparatus **2900** that includes a vertical post **2910** secured (e.g., using a flange **2912** that is bolted to concrete, etc.) at ground level **2520** to support two rotatable arms **2902** that position and deploy a jackstand beneath a front end of trailer **108**. FIG. 29 is an end elevation of jackstand apparatus **2900** in a deployed position. FIG. 30 is a top view of jackstand apparatus **2900** in a parked position. FIG. 31 is a top view showing a plurality of jackstand apparatus **2900** positioned adjacent and between loading docks **3102(1)** and **3102(2)**. FIG. 32 is an end elevation showing five jackstand apparatus **2900** supporting front ends of four trailers in four loading docks **3202**. FIGS. 29-32 are best viewed together with the following description.

Vertical post **2910** is secured (e.g., using a flange **2912** that is bolted to concrete, etc.) at ground level **2520** to support two rotatable arms **2902**, each having a motor **2914** that operates to rotate rotatable arm **2902** around vertical post **2910**. In certain embodiments, flange **2912** is a baseplate similar to baseplate **502** of FIG. 5, that is repositionable using a handle and wheels. However, the baseplate is of sufficient mass to prevent movement of rotatable arms **2902** and jackstands **2950** from modifying a position of the baseplate. The baseplate may include a dense rubber mat affixed to a lower surface of the baseplate to provide better grip of a concrete surface (which may have micro grit/pebbles, etc.).

In certain embodiments, motor **2914** and/or rotatable arm **2902** includes an encoder for determining an angle of rotatable arm **2902**. A distal end of each rotatable arm **2902** supports a jackstand **2950** formed as a vertical support **2952** coupled at a top end with a jack pad **2958**. Vertical support **2952** is extendable (e.g., a hydraulic piston, screw mechanism, scissor mechanism, etc.) to press jack pad **2958** against a lower surface of a front end of trailer **108** and the ground, and thereby provides safety and support to trailer **108**. In certain embodiments, jackstand **2950** includes wheels/casters **2960** to facilitate maneuverability of jackstand **2950** by rotatable arm **2902**.

Controller **106** controls rotation of rotatable arm **2902** about vertical post **2910** and also controls extension and retraction of vertical support **2952**. As shown in FIG. 31, by positioning each jackstand apparatus **2900** adjacent and/or between each loading dock **3102** and near an expected front end of trailer **108** when at the loading dock, jackstands **2950**

13

may be deployed into none, either, or both of the adjacent loading docks. Although shown with two rotatable arms 2902, post 2910 may be fitted with only one rotatable arm 2902, such as when positioned adjacent to only one loading dock 3102. Using jackstand apparatus 2900(2) as an example, jackstand 2950(3) is rotated and positioned under a front corner of trailer 108(1) in loading dock 3102(1) and jackstand 2950(4) is rotated and positioned under a front corner of trailer 108(2) in loading dock 3102(2). Advantageously, deployment (e.g., rotation and extension) of jackstands 2950 are independently controlled and jackstands 2950 supporting a first trailer 108 may be retracted without affecting jackstands 2950 supporting other trailers.

One or more sensors may be used to ensure correct deployment of each jackstand 2950. In one embodiment, a pressure sensor or a force sensor is coupled with jack pad 2958 to sense pressure of jack pad 2958 against the bottom of trailer 108. In another embodiment, a current sensor measures current of motor 2954 that moves the jack pad 2958 upwards, whereby an increase in current indicates contact of jack pad 2958 against the bottom of trailer 108. In another embodiment, one or more IMUs and/or accelerometers are coupled with jack pad 2958 to sense when jack pad 2958 contacts the bottom of trailer 108. In another embodiment, jack pad 2958 includes at least one limit switch that is depressed when jack pad 2958 presses against the bottom of trailer 108. In another embodiment, jackstand 2550 includes at least one ultrasonic and/or laser range finder type sensor that measures a distance/range between jack pad 2958 and the bottom of trailer 108. In another embodiment, jack pad 2958 includes an inductive sensor that senses proximity of the bottom of trailer 108 when a fifth-wheel plate of trailer 108 is magnetic and/or ferrous. These sensors provide feedback that allows controller 106 to determine when jackstand 2550 is correctly deployed.

Tractor Deployed Jackstand

FIGS. 33-39 show one example jackstand 3300 that is deployable by a grabber 3302 of yard tractor 112. FIG. 33 is a side elevation illustrating a rear end of yard tractor 112 fitted with grabber 3302 that is carrying jackstand 3300 in a horizontal position. FIG. 34 is similar to FIG. 33, but with jackstand 3300 rotated to a vertical orientation. FIG. 35 is a top view showing grabber 3302 in further example detail. FIG. 36A shows jackstand 3300 in further example detail. FIG. 36B shows a second jackstand 3650 in further example detail. FIG. 37 shows jackstand 3300 deployed from yard tractor 112 to support trailer 108. FIGS. 33-37 are best viewed together with the following description. FIG. 38 is a top view showing a jackstand cassette 3802 attached to a back end of yard tractor 112 of FIG. 1. FIG. 39 is an end view of the jackstand cassette 3802 attached to the back end of yard tractor 112. FIGS. 33-39 are best viewed together with the following description.

Jackstand 3300 includes a vertical leg 3406 that is extendable and has a jack pad 3408 coupled to a top end thereof. A collar 3602 is positioned on vertical leg 3406 for coupling with grabber 3302. Collar 3602 may include a drive socket 3604 that, when turned, extends and retracts vertical leg 3406. Collar 3602 may also include a fiducial marker 3610 to facilitate alignment of grabber 3302 with jackstand 3300. For example, a camera 3508 mounted to grabber 3302 may capture one or more images of fiducial marker 3610 to facilitate alignment of grabber 3302 with jackstand 3300 when recoupling therewith. Grabber 3302 includes two retractable claws 3502 and 3504 that are sized to couple

14

with, and secure, collar 3602. Retractable claws 3502 and 3504 are controlled by a motor 3306. In certain embodiments, grabber 3302 is movable (e.g., by a motor, not shown) in a vertical direction, relative to tractor 112, to facilitate coupling with, and positioning of, jackstand 3300. In certain embodiments, grabber 3302 is extendable and retractable (e.g., by motor 3808 of FIG. 38) in a horizontal direction, towards and away from tractor 112, to facilitate coupling with, and positioning of, jackstand 3300.

Grabber 3302 also includes a drive bit 3506 that is sized and shaped to mechanically engage with drive socket 3604 (e.g., when retractable claws 3502 and 3504 are securely coupled with collar 3602). Drive bit 3506 is independently driven by a motor 3308 to extend and retract vertical leg 3406. Grabber 3302 is rotatable at joint 3304 by a motor 3310 to rotate jackstand 3300 to a horizontal orientation to reduce risk of damage when carried by yard tractor 112. FIG. 36B shows a second jackstand 3650 that includes collar 3652, positioned between two opposed extendable legs 3656(1) and 3656(2), for coupling with grabber 3302, a jack pad 3658 positioned at a top end of extendable leg 3656(1) and a foot pad 3662 positioned at a bottom end of extendable leg 3656(2). Collar 3652 includes a drive socket 3654 that, when turned by drive bit 3506 of grabber 3302, simultaneously extends, or retracts depending upon direction, extendable legs 3656(1) and 3656(2). Collar 3652 may also include a fiducial marker 3660 to facilitate alignment of grabber 3302 with jackstand 3650. Advantageously, jackstand 3650 may be carried by yard tractor 112, while held by grabber 3302 in a vertically orientation, since extendable leg 3656(2), when retracted, lifts foot pad 3662 off the ground.

In one example of operation, jackstand 3300 is carried in a horizontal position, as shown in FIG. 33, by yard tractor 112 while yard tractor 112 is coupled with trailer 108. For example, jackstand 3300 is carried as yard tractor 112 maneuvers trailer 108 into loading dock 3702. Yard tractor 112 then decouples from trailer 108, leaving trailer 108 standing on its landing gear 3704, and begins to move forward, stopping with jackstand 3300 positioned beneath the front end of trailer 108. Yard tractor 112 then rotates grabber 3302 at joint 3304 to rotate jackstand 3300 to a vertical position. Yard tractor 112 rotates drive bit 3506 to extend vertical leg 3406 until jackstand 3300 provides support to trailer 108 from the ground. Yard tractor 112 then retracts claws 3502 and 3504 to release jackstand 3300, and moves forward leaving jackstand 3300 in place. This process is reversed for yard tractor 112 to recouple with trailer 108, collecting and stowing jackstand 3300 at the rear of yard tractor 112.

In certain embodiments, unused jackstands 3300 may be stored at a repository (e.g., a designated location with the yard for storing jackstands 3300), whereby yard tractor 112 may retrieve each jackstand 3300 as needed, such as when successive operations of yard tractor 112 position trailer 108 at a dock and deploy jackstand 3300, and deposit jackstand 3300 when not needed, such as when successive operations of yard tractor 112 retrieve jackstand 3300 and move trailer 108 away from a dock. Yard tractor 112 may track the position of each jackstand 3300 within the repository and is thereby aware of which specific locations within the repository contain an unused jackstand. In certain embodiments, yard automation server 110 tracks jackstands 3300 within the repository and directs yard tractor 112 to retrieve and deposit jackstands 3300 as needed.

In certain embodiments, as shown in FIGS. 38 and 39, a rear end of yard tractor 112 (shown with a fifth-wheel 3806) is fitted with a jackstand cassette 3802 that slides horizon-

15

tally, under control of a motor **3804** to position a jackstand **3650** in front of grabber **3302** as needed. Grabber **3302** is retractable by a motor **3808** into yard tractor **112** to allow cassette **3802** to slide horizontally, and is extended by motor **3808** to engage (grab) jackstand **3650** positioned in front of grabber **3302**. Motor **3808** may then extend grabber **3302** further from yard tractor **112** to deploy jackstand **3650** as described above. Similarly, grabber **3302** may be controlled to position and release jackstand **3650** within an empty slot of jackstand cassette **3802**. Jackstand cassette **3802** may then slide horizontally to move the released jackstand **3650** away from grabber **3302**, thereby allowing grabber **3302** to retrieve a deployed jackstand **3650**. In the example of FIGS. **38** and **39**, jackstand cassette **3802** is shown storing four jackstands **3650(1)-(4)**, but may be configured to store more or fewer jackstands without departing from the scope hereof. Advantageously, jackstand cassette **3802** allows to yard tractor **112** to perform multiple consecutive jackstand deployments and multiple jackstand retrievals without having to fetch or deposit the jackstands within a designated repository within the yard until the storage of jackstand cassette **3802** is exhausted.

Embedded Scissor Jacks

FIGS. **40-42** show one example scissor jackstand **4000** that may be installed in a recess **4004** in the ground and autonomously deployed to provide support to a front end of trailer **108** at a loading dock **4002**. FIG. **40** is an end elevation showing scissor jackstand **4000** supporting a front end of trailer **108**. FIG. **41** is a side elevation showing scissor jackstand **4000** supporting the front end of trailer **108**. FIG. **42** is a top view showing a plurality of scissor jackstands **4000** embedded into the ground at strategic positions to support front ends of trailers of different lengths. FIGS. **40-42** are best viewed together with the following description.

Scissor jackstand **4000** is substantially flat when retracted. In certain embodiments, scissor jackstand may be position on the ground. However, in certain embodiments, scissor jackstand **4000** is positioned in a substantially flat recess in the ground such that scissor jackstand does not significantly protrude above ground level when retracted. Advantageously, when retracted, scissor jackstand **4000** provides no ground clearance issues as trailer **108** is maneuvered in and out of loading dock **4002**.

Scissor jackstand **4000** is activated by controller **106** and may be autonomously controlled by yard automation server **110**. For example, yard automation server **110** may deploy a particular one of scissor jackstands **4000** based on knowledge of trailer movement.

Deployment Mechanisms

FIG. **43** shows one example jackstand apparatus **4300** with a cable deployment mechanism that rotates a jackstand **4350** from a resting position **4352** to beneath a front end of a trailer. Jackstand apparatus **4300** includes a plate **4302** that mounts flush to the ground (e.g., a concrete pad) using at least one fastener **4303** (e.g., a bolt), a post **4304** mounted to plate **4302** that rotatably supports a swing arm **4306** with a jackstand **4350** at a distal end. Post **4304** includes a return spring **4308** that provides a mechanical force to return swing arm **4306** and jackstand **4350** to a resting position **4352**. A radiused cable guide **4310** is mechanically coupled with a rotatable portion of post **4304** and/or with swing arm **4306**. A cable **4312** is attached at a first end to radiused cable guide

16

4310 and at a second end to a manual actuator **4314** (e.g., a ratcheted lever or cable wheel), which may be positioned within a building (e.g., warehouse) of a loading dock **4316**.

In one example of operation, an operator uses actuator **4314** to pull cable **4312**, causing swing arm **4306** to rotate about post **4304**, compressing return spring **4308**, and to position jackstand **4350** beneath a front end of trailer **108** at the loading dock. To retract jackstand **4350**, the operator releases actuator **4314**, thereby releasing cable **4312**, and allowing return spring **4308** to move swing arm **4306** and jackstand **4350** back towards resting position **4352**. Jackstand apparatus **4300** is easily installed, requiring only that plate be fixed to the ground at a position near a front end of trailer **108**, and that actuator **4314** be secured at a convenient location for manual operation. Although shown with resting position **4352** being located further away from the actuator **4314** (e.g., the warehouse) than post **4304**, jackstand apparatus **4300** may be configured to have resting position **4352** located in the opposite orientation (e.g., 180 degrees opposed) from post **4304**, and with cable **4312** and radiused cable guide **4310** also reversed, such that swing arm **4306** rotates in the opposite direction and away from actuator **4314** (e.g., the warehouse) without departing from the scope hereof. Advantageously, this may reduce the extent to which jackstand apparatus **4300** extends outward from dock **4316**.

Jackstand **4350** may be similar to either or both of jackstands **2550** of FIG. **25** and **2950** of FIG. **29**, and include a motor that extends and retracts a vertical support of jackstand **4350**, whereby jackstand apparatus **4300** may include an electrical cable **4318** to support power and/or control signals to jackstand **4350**, and thereby allow remote operation of jackstand **4350**.

FIG. **44** shows one example jackstand apparatus **4400** with a cable retrieval mechanism that rotates a jackstand **4450** from beneath a front end of a trailer to a resting position away from the trailer. Jackstand apparatus **4400** is similar to jackstand apparatus **4300** of FIG. **43**, but with reversed operation. Jackstand apparatus **4400** includes a plate **4402** that mounts flush to the ground (e.g., a concrete pad) using at least one fastener **4403** (e.g., a bolt), a post **4404** mounted to plate **4402** that rotatably supports a swing arm **4406** with a jackstand **4450** at a distal end. Post **4404** includes a return spring **4408** that provides a mechanical force to return swing arm **4406** and jackstand **4450** to a resting position **4452**. A radiused cable guide **4410** is mechanically coupled with a rotatable portion of post **4404** and/or with swing arm **4406**. A cable **4412** is attached at a first end to radiused cable guide **4410** and at a second end to a manual actuator **4414** (e.g., a ratcheted lever or cable wheel), which may be positioned within a building (e.g., warehouse) of a loading dock **4416**.

In one example of operation, an operator uses actuator **4414** to pull cable **4412**, causing swing arm **4406** to rotate about post **4404**, compressing return spring **4408**, and to position jackstand **4450** away from a front end of trailer **108** at the loading dock. To position jackstand **4450** beneath the front end of trailer **108**, the operator releases actuator **4414**, thereby releasing cable **4412**, and allowing return spring **4408** to move swing arm **4406** and jackstand **4450** back towards resting position **4452**, and thereby beneath the front end of trailer **108**. Jackstand apparatus **4400** is easily installed, requiring only that plate be fixed to the ground at a position near a front end of trailer **108**, and that actuator **4414** be secured at a convenient location for manual operation. Although shown with swing arm **4406** rotating away from actuator **4414** (e.g., the warehouse) when moving from resting position **4452**, cable **4412** and radiused cable guide

17

4410 may be reversed such that swing arm 4406 rotates towards actuator 4414 (e.g., warehouse) without departing from the scope hereof. Advantageously, this may reduce the extent to which jackstand apparatus 4400 extends outward from dock 4416.

Jackstand 4450 may be similar to either or both of jackstands 2550 of FIG. 25 and 2950 of FIG. 29 and includes a motor that extends and retracts a vertical support of jackstand 4450, whereby jackstand apparatus 4400 may include an electrical cable 4418 to supply power and/or control signals to jackstand 4450, and thereby allow remote operation of jackstand 4450.

Changes may be made in the above methods and systems without departing from the scope hereof. It should thus be noted that the matter contained in the above description or shown in the accompanying drawings should be interpreted as illustrative and not in a limiting sense. The following claims are intended to cover all generic and specific features described herein, as well as all statements of the scope of the present method and system, which, as a matter of language, might be said to fall therebetween. For example, features may be combined as follows:

Combination of Features

(A1) An automated jackstand system supports a front end of a trailer parked at a loading dock. The automated jackstand system includes: a jackstand, having: a jack pad; a vertically extendable component coupling at a first end with the jack pad; a collar positioned on the vertically extendable component; and a mechanical socket positioned on the collar and mechanically geared to extend the vertically extendable component when rotated in a first direction and to retract the vertically extendable component when rotated in a second direction opposite the first direction. The automated jackstand system also includes a grabber positioned at a back end of a yard tractor and having: at least two claws operable by a first motor to removably couple with the collar; and a drive bit operable by a second motor and shaped and sized to mechanically couple with the mechanical socket, wherein the drive bit is positioned between the at least two claws. The automated jackstand system also includes a controller, having machine-readable instructions stored in non-transitory memory that, when executed by a processor, control the first motor and the second motor to deploy the jackstand to support the front end of the trailer.

(A2) The embodiment (A1) further including: a fiducial marking positioned on the collar; a camera positioned on the yard tractor for imaging the fiducial marking; and further machine-readable instructions stored in the non-transitory memory that, when executed by the processor, control the yard tractor to align the grabber with the fiducial marking when coupling with the jackstand.

(A3) In either of the embodiments (A1) or (A2), the vertically extendable component having a first portion extendable in a first vertical direction to move the jack pad upwards to press against a bottom surface of the front end of the trailer.

(A4) Any of the embodiments (A1)-(A3) further including a foot pad coupled with a second extendable portion of the vertically extendable component, the second extendable portion being extendable in a second vertical direction, opposite to the first vertical direction, to press the foot pad against the ground.

(A5) Any of the embodiments (A1)-(A4) further including a third motor operable to move the grabber in a vertical direction relative to the yard tractor.

18

(A6) Any of the embodiments (A1)-(A5) further including a third motor for extending the grabber in a horizontal direction.

(A7) Any of the embodiments (A1)-(A6) further including a jackstand cassette positioned at the back end of the yard tractor for storing the jackstand when at least one undeployed, the jackstand cassette being operable to move horizontally to position the jackstand in front of the grabber.

(B1) A jackstand includes a jack pad, a vertically extendable component coupling at a first end with the jack pad, a collar positioned on the vertically extendable component, a fiducial marking positioned on the collar in a location for imaging by an imager located external to the jackstand, and a mechanical socket positioned on the collar and mechanically geared to extend the vertically extendable component when rotated in a first direction and to retract the vertically extendable component when rotated in a second direction opposite the first direction.

(B2) In the embodiment (B1), the vertically extendable component having a first portion extendable in a first vertical direction to move the jack pad upwards to press against a bottom surface of the front end of the trailer.

(B3) Either of the embodiments (B1) or (B2) further including a foot pad coupled with a second extendable portion of the vertically extendable component, the second extendable portion being extendable in a second vertical direction, opposite to the first vertical direction, to press the foot pad against the ground.

(B4) In any of the embodiments (B1)-(B3), the jackstand sized and shaped to fit within a jackstand cassette located on a tractor.

(C1) An automated jackstand supports a front end of a trailer parked at a loading dock. The automated jackstand including: a baseplate; a vertical support coupled to the baseplate by a pivot positioned at a lower end of the vertical support; a jack pad positioned at a top end of the vertical support; an actuator positioned at the baseplate to generate a linear motion parallel to the baseplate; an arm having a first end pivotably coupled to the vertical support and a second end pivotably coupled to the actuator; and wherein the linear motion causes the arm to move the vertical support between a horizontal position and a vertical position.

(C2) The embodiment (C1) further including: at least two wheels positioned at a first plate end of the baseplate; a handle positioned at a second plate end, opposite the first plate end, of the baseplate; and wherein the at least two wheels support the baseplate only when the handle is lifted and the baseplate is at an angle relative to the ground.

(C3) Either of the embodiments (C1) or (C2) further including: a plurality of wheels coupled with the baseplate and aligned to run on tracks positioned at or below ground level within loading dock; and a drive motor for moving the automated jackstand along the tracks.

(C4) Any of the embodiments (C1)-(C3) further including at least one of a sensor and an encoder for determining a position of the automated jackstand along the tracks.

(C5) In any of the embodiments (C1)-(C4), the drive motor is controllable by a remote controller operable to position the automated jackstand beneath the front end of the trailer based on the determined position.

(C6) In any of the embodiments (C1)-(C5), the actuator including a hydraulic piston.

(C7) In any of the embodiments (C1)-(C6), the actuator including a motor driven screw mechanism.

(C8) In any of the embodiments (C1)-(C7), the actuator is remotely controlled by a controller.

(C9) In any of the embodiments (C1)-(C8), the actuator is remotely controlled by a person.

(D1) An automated jackstand system supports a trailer parked at a loading dock. The automated jackstand system including: a stepped block; a horizontally extendable component coupling at a first end with the stepped block; and a controller for remotely extending the horizontally extendable component to press the stepped block against a first side surface at a front end of the trailer.

(D2) The embodiment (D1) further including: a track aligned with a length of the trailer and adjacent to a trailer parking area of the loading dock; a baseplate having a plurality of wheels aligned with the track, the baseplate supporting the horizontally extendable component; and a motor coupled to drive at least one wheels to position the baseplate along the track.

(E1) An automated jackstand system supports a trailer parked at a loading dock. The automated jackstand system includes: a jack pad; a vertically extendable component coupling at a first end with the jack pad; and a controller for remotely extending the vertically extendable component to press the jack pad against a lower surface of a front end of the trailer.

(E2) In the embodiment (E1), the vertically extendable component including a hydraulic piston that is at least partially embedded into the ground.

(E3) In either of the embodiments (E1) or (E2), the vertically extendable component including a scissor mechanism that is at least partially embedded into the ground.

(E4) In any of the embodiments (E1)-(E3), the vertically extendable component including a screw mechanism that is at least partially embedded into the ground.

(E5) In any of the embodiments (E1)-(E4), the jack pad including one of a horizontal disc and a horizontal beam.

(E6) Any of the embodiments (E1)-(E5), further including at least one sensor for sending feedback indicative of correct deployment of the automated jackstand system to the controller.

(E7) Any of the embodiments (E1)-(E6), further including a track aligned with a length of the trailer and positioned centrally within a trailer parking area of the loading dock; a baseplate having a plurality of wheels aligned with the track, the baseplate supporting the vertically extendable component; and a motor coupled to drive at least one wheels to position the baseplate along the track.

(F1) An automated jackstand system supports a front end of a trailer parked at a loading dock. The automated jackstand system includes: a vertical post; a swing arm supported at one end by the vertical post; a first motor mechanically coupled with the vertical post and the swing arm, the first motor being operable to rotate the swing arm about the vertical post; a jackstand coupled with a distal end of the swing arm; and a second motor operable to extend and retract a vertical support of the jackstand.

(F2) The embodiment (F1) further including a controller for controlling operation of the first motor to position the jackstand beneath the front end of the trailer, and for controlling the second motor to extend the vertical support of the jackstand to support the front end of the trailer.

(F3) Either of the embodiments (F1) or (F2) further including: a track aligned with a length of the trailer and adjacent to a trailer parking area of the loading dock; a baseplate having a plurality of wheels aligned with the track, the baseplate supporting the vertical post; and a motor coupled to drive at least one wheels to position the baseplate along the track.

(F4) Any of the embodiments (F1)-(F3) further including at least one wheel/caster positioned beneath the jackstand.

(G1) An automated jackstand system supports a front end of a trailer parked at a loading dock. The automated jackstand system includes: a vertical post; a swing arm supported at one end by the vertical post; a return spring for returning the swing arm to a resting position; a cable mechanically coupled with the vertical post and the swing arm; and a jackstand coupled with a distal end of the swing arm.

(G2) In the embodiment (G1), pulling the cable rotates the swing arm and the jackstand about the vertical post to position the jackstand beneath the front end of the trailer.

(G3) Either of the embodiments (G1) or (G2) further including a motor operable to extend and retract a vertical support of the jackstand.

What is claimed is:

1. An automated jackstand system for supporting a trailer parked at a loading dock, comprising:

a jack pad;
a vertically extendable component coupling at a first end with the jack pad, the vertically extendable component at least partially embedded into the ground; and
a controller for remotely extending the vertically extendable component to press the jack pad against a lower surface of a front end of the trailer.

2. The automated jackstand system of claim 1, the jack pad comprising one of a horizontal disc and a horizontal beam.

3. The automated jackstand system of claim 1, further comprising at least one sensor for sending feedback indicative of correct deployment of the automated jackstand system to the controller.

4. The automated jackstand system of claim 1, further comprising:

a track aligned with a length of the trailer and positioned centrally within a trailer parking area of the loading dock;
a baseplate having a plurality of wheels aligned with the track, the baseplate supporting the vertically extendable component.

5. The automated jackstand system of claim 4, further comprising a motor coupled to drive at least one wheels to position the baseplate along the track.

6. The automated jackstand of claim 1, the vertically extendable component comprising a scissor mechanism.

7. The automated jackstand of claim 1, the vertically extendable component being foldable between a deployed and not-deployed state.

8. The automated jackstand of claim 1, wherein, in the not-deployed state, the vertically extendable component is below a ground clearance height.

9. An automated jackstand system for supporting a trailer parked at a loading dock, comprising:

a jack pad;
a vertically extendable component coupling at a first end with the jack pad;
a track aligned with a length of the trailer and positioned centrally within a trailer parking area of the loading dock;
a baseplate having a plurality of wheels aligned with the track, the baseplate supporting the vertically extendable component; and
a controller for remotely extending the vertically extendable component to press the jack pad against a lower surface of a front end of the trailer.

21

10. The automated jackstand system of claim **9**, the vertically extendable component comprising a hydraulic piston that is at least partially embedded into the ground.

11. The automated jackstand system of claim **9**, the vertically extendable component comprising a scissor mechanism that is at least partially embedded into the ground.

12. The automated jackstand system of claim **9**, the vertically extendable component comprising a screw mechanism that is at least partially embedded into the ground.

13. The automated jackstand system of claim **9**, the jack pad comprising one of a horizontal disc and a horizontal beam.

14. The automated jackstand system of claim **9**, further comprising at least one sensor for sending feedback indicative of correct deployment of the automated jackstand system to the controller.

22

15. The automated jackstand of claim **9**, the vertically extendable component being foldable between a deployed and not-deployed state.

16. The automated jackstand of claim **9**, wherein, in the not-deployed state, the vertically extendable component is below a ground clearance height.

17. The automated jackstand of claim **9**, further comprising a motor coupled to drive at least one wheels to position the baseplate along the track.

18. The automated jackstand of claim **9**, further comprising at least one of a sensor or encoder for determining a location of the baseplate along the track.

19. The automated jackstand of claim **9**, further comprising a sensing device that provides input to the controller, the controller using the input to detect a front end of a trailer.

20. The automated jackstand of claim **19**, the sensing device being at least one of a rangefinder and a camera.

* * * * *