

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250257613

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

BATARSEH; Sameeh Issa

---

### **DOWNHOLE LASER BORING AND PERFORATING TOOL AND METHOD OF USING SAME**

---

#### **Abstract**

A system includes a laser generating source, a downhole assembly, and a plurality of optical pathways extending between the laser generating source and the downhole assembly. The downhole assembly includes a tool housing, a plurality of reflectors, a plurality of reshaping lenses, and a main beam optical assembly. The reflectors are each movable between an activated position and a deactivated position, and are arranged to reflect energy beams radially outward away from the tool housing when in the activated position. The reshaping lenses are arranged to receive and redirect the energy beams when the reflectors are in the deactivated position. The main beam optical assembly is operable to combine the energy beams received from the reshaping lenses into a combined energy beam that is axially directed when the reflectors are in the deactivated position.

---

**Inventors:** BATARSEH; Sameeh Issa (Dhahran, SA)

**Applicant:** SAUDI ARABIAN OIL COMPANY (Dhahran, SA)

**Family ID:** 95398626

**Assignee:** SAUDI ARABIAN OIL COMPANY (Dhahran, SA)

**Appl. No.:** 18/438262

**Filed:** February 09, 2024

---

#### **Publication Classification**

**Int. Cl.: E21B7/15 (20060101); B23K26/06 (20140101); B23K26/12 (20140101); B23K26/382 (20140101); B23K103/00 (20060101)**

**U.S. Cl.:**

**CPC E21B7/15 (20130101); B23K26/0643 (20130101); B23K26/0648 (20130101); B23K26/123 (20130101); B23K26/382 (20151001); B23K2103/50 (20180801)**

---

## **Background/Summary**

### **FIELD OF THE DISCLOSURE**

[0001] The present disclosure relates generally to downhole well perforation and boring and, more particularly, to downhole tooling for conventional and non-conventional reservoirs utilizing laser technology.

### **BACKGROUND OF THE DISCLOSURE**

[0002] Wellbores may be stimulated to enhance the flow of hydrocarbons from a subterranean formation to the wellbore. To produce hydrocarbons from the targeted formation, the hydrocarbons in the formation need to flow from the formation to the wellbore in order to be produced and flow to the surface, and formation permeability facilitates the flow from the formation to the wellbore. When formation permeability is low, the wellbore may be stimulated to enhance flow, wherein such stimulation may be applied around the wellbore and into the formation in order to build a network of tunnels in the formation through which the hydrocarbons may flow.

[0003] Part of the stimulation process entails perforating casing and cement that lines the wellbore in order to reach the surrounding formation, such that the ensuing hydraulic fracturing operation will reach deeper into the formation and enhance production therefrom. Various types of tooling exists to perform such perforating operations, including tooling that utilizes laser technology. Such existing laser tooling, however, is ineffective at delivering high power laser energy at depth. In particular, it incurs significant energy loss when utilized at depth, for example, energy loss can reach up to 60% of power loss when transmitted 10,000 feet; and, when delivering high energy, for example, 20 kilo-Watts (“kW”), the loss of energy manifests in significant heat generations that can damage the transmission equipment.

[0004] A need, therefore, exists for improved tooling that is able to effectively deliver high power laser energy at depth.

### **SUMMARY OF THE DISCLOSURE**

[0005] Various details of the present disclosure are hereinafter summarized to provide a basic understanding. This summary is not an extensive overview of the disclosure and is neither intended to identify certain elements of the disclosure, nor to delineate the scope thereof. Rather, the primary purpose of this summary is to present some concepts of the disclosure in a simplified form prior to the more detailed description that is presented hereinafter.

[0006] According to an embodiment consistent with the present disclosure, a system includes a laser generating source, first and second optical pathways operatively connected to the laser generating source for receiving first and second energy beams, respectively, and a downhole assembly in communication with the laser generating source via the first and second optical pathways. The downhole assembly includes a tool housing extending along a tool axis and having opposing downhole and uphole ends, the first and second optical pathways being operable to direct the first and second energy beams to the tool housing, respectively, a first reflector and a second reflector each movable between an activated position and a deactivated position, the first and second reflectors being arranged to reflect the first and second energy beams, respectively, radially

outward and away from the tool axis when in the activated position, a first reshaping lens and a second reshaping lens each arranged within the interior space, the first and second reshaping lenses being arranged to receive and redirect the first and second energy beams, respectively, when the first and second reflectors are in the deactivated position, and a main beam optical assembly operable to combine the first and second energy beams received from the first and second reshaping lenses into a combined energy beam that is directed along the tool axis when the first and second reflectors are in the deactivated position.

[0007] In another embodiment, a system includes a laser generating source and a downhole assembly. The downhole assembly includes a tool housing extending along a tool axis and having opposing downhole and uphole ends, the tool housing defining an interior space that extends between the downhole and uphole ends. The downhole assembly also includes first and second optical pathways extending between the laser generating source and the tool housing, the first and second optical pathways each having an input end in optical communication with the laser generating source and an output end from which energy is discharged, the first and second optical pathways each configured to conduct energy between the input and output ends. The downhole assembly includes first and second reflectors arranged within the interior space and each being movable between an activated position and a deactivated position, the first reflector being aligned with the output end of the first optical pathway to receive energy discharged therefrom when in the activated position, and the second reflector being aligned with the output end of the second optical pathway to receive energy discharged therefrom when in the activated position. The downhole assembly includes first and second reshaping lenses arranged within the interior space, the first reshaping lens being aligned with the output end of the first optical pathway to receive energy discharged therefrom when the first reflector is in the deactivated position, and the second reshaping lens being aligned with the output end of the second optical pathway to receive energy discharged therefrom when the second reflector is in the deactivated position. The downhole assembly includes a main beam optical assembly at least partially arranged in the interior space and operable to combine energy received from the first and second reshaping lenses, wherein, when in the activated positions, the first and second reflectors redirect energy received from the output ends of the first and second optical pathways, respectfully, radially outward and away from the tool axis, and wherein, when the first and second reflectors are in the deactivated position, the main beam optical assembly combines energy received from the first and second reshaping lenses, and directs combined energy axially along the tool axis.

[0008] In a further embodiment, a method includes conveying a downhole assembly into a wellbore on coiled tubing, the coiled tubing having first and second optical pathways extending therein between the downhole assembly and a laser generating source, the downhole assembly having a tool housing that extends along a tool axis, transmitting first and second energy beams to the downhole assembly via the first and second optical pathways, respectively, arranging first and second reflectors within the downhole assembly in an activated position and thereby reflecting the first and second energy beams radially outward and away from the tool axis, arranging the first and second reflectors within the downhole assembly in a deactivated position and thereby conveying the first and second energy beams to first and second reshaping lenses, respectively, and with a main beam optical assembly included in the downhole assembly, combining the first and second energy beams received from the first and second reshaping lenses into a combined energy beam, and directing the combined energy beam out of the tool housing along the tool axis.

[0009] Any combinations of the various embodiments and implementations disclosed herein can be used in a further embodiment, consistent with the disclosure. These and other aspects and features can be appreciated from the following description of certain embodiments presented herein in accordance with the disclosure and the accompanying drawings and claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is schematic of a laser boring and perforating system, according to one or more embodiments of the present disclosure.

[0011] FIG. 2 is a cross section of a downhole assembly of the laser boring and perforating system of FIG. 1 when located downhole and when in the activated position, according to one or more embodiments of the present disclosure.

[0012] FIG. 3 is a cross section of the downhole assembly of FIG. 2 when in the deactivated position, according to one or more embodiments of the present disclosure.

[0013] FIG. 4 is an embodiment of a downhole assembly incorporating more than one stage of reflectors, according to one or more embodiments of the present disclosure.

[0014] FIG. 5 is an embodiment of a downhole assembly, incorporating a plurality of reflectors and a rotational head that is operable to both emit one or more lasers beams and rotate.

### DETAILED DESCRIPTION

[0015] Embodiments of the present disclosure will now be described in detail with reference to the accompanying Figures. Like elements in the various figures may be denoted by like reference numerals for consistency. Further, in the following detailed description of embodiments of the present disclosure, numerous specific details are set forth in order to provide a more thorough understanding of the claimed subject matter. However, it will be apparent to one of ordinary skill in the art that the embodiments disclosed herein may be practiced without these specific details. In other instances, well-known features have not been described in detail to avoid unnecessarily complicating the description. Additionally, it will be apparent to one of ordinary skill in the art that the scale of the elements presented in the accompanying Figures may vary without departing from the scope of the present disclosure.

[0016] Embodiments in accordance with the present disclosure generally relate to a downhole well perforation and boring system utilizing laser technology. The downhole well perforation and boring system includes a downhole assembly operable to discharge a plurality of radially-directed laser beams or an individual axially-directed laser beam that is relatively higher power laser than as compared to the individual radially-directed laser beams. Each radially-directed laser beam is delivered to the downhole assembly via an individual fiber optic cable and is of relatively low power, such that there will be less energy loss in cases where the fiber optic cable is of substantial length (e.g., when utilized in a downhole operation). The downhole assembly includes a plurality of reflectors that are each operable to redirect energy received from the fiber optics radially outward; and, while the radially directed laser beams are of relatively lower power, they are still operable for perforating the sidewalls of the wellbore and casing. However, the downhole assembly is still able to discharge a high power laser by directing the energy from each of the fiber optic cables, past the reflectors, to a plurality of reshaping lenses that in turn direct the energy to a main beam optical assembly, which combines the energy into the individual axially-directed laser beam that is a relatively higher power laser.

[0017] FIG. 1 is a schematic depiction of an example laser boring and perforating system **100**, according to one or more embodiments of the present disclosure. The laser boring and perforating system **100** (hereinafter “the system **100**”) includes a laser generating source **102** and a downhole assembly **104**. The downhole assembly **104** (hereinafter “the assembly **104**”) is a downhole tool configured to be deployed into a wellbore **106** formed in the earth **108**. In the illustrated example, the laser generating source **102** is provided on a surface **110** of the earth **108** into which the wellbore **106** is drilled. The surface **110** may alternately be referred to as a “well surface”.

[0018] The laser generating source **102** includes an electrical power source and a laser generator operatively coupled to the electrical power source. The electrical power source may supply

relatively low power to the laser, rather than high power, as the laser generating source **102** will be transmitting separate lasers to the assembly **104**, as described below. While the electrical power source may be capable of providing various levels or calibrations, in embodiments, a power range of about 2 kilo Watts (kW) to 10 KW is utilized.

[0019] The system **100** includes a plurality of optical pathways **112** extending between the laser generating source **102** and the assembly **104**. Stated differently, the laser generating source **102** and the assembly **104** are operatively coupled via the plurality of optical pathways **112** such that electromagnetic radiation generated at the laser generating source **102** can be conveyed to the assembly **104** via the optical pathways **112**. In embodiments, each of the optical pathways **112** is a fiber optic cable. The laser generating source **102** is operable to generate a plurality of separate laser beams, and each of the separate laser beams is transmitted to the tool via one of the plurality of optical pathways **112**. The separate laser beams sent by the laser generating source **102** to each of the plurality of optical pathways **112** will be of relatively lower power, resulting in less power loss than if a relatively higher power laser was transmitted through each of the plurality of optical pathways **112**. Moreover, each of the individual lasers of relatively low power may be combined into a main laser beam of relatively higher power without exhibiting the aforementioned power loss, as described below.

[0020] In embodiments, the system **100** may include coiled tubing **114** to protect the plurality of optical pathways **112** and provide a means of raising and lowering the assembly **104** within the wellbore **106**. The optical pathways **112** may be arranged concentrically within the coiled tubing **114**. The coiled tubing **114** may be provided and stored on a rotatable spool **116**, and unwound therefrom when lowering the assembly **104** into the wellbore **106** or wound thereon when raising the assembly **104**. The rotatable spool **116** of the coiled tubing **114** is rotated to advance and retract the coiled tubing **114**. The coiled tubing **114** comprises a continuous length of flexible pipe capable of being wound onto and unwound from the rotatable spool **116**. In some applications, as illustrated, the rotatable spool **116** may be arranged directly on the well surface **110**, but could alternatively be mounted to a transport vehicle (e.g., a truck), a production rig (e.g., such as an offshore platform or the like), or may otherwise be skid-mounted.

[0021] The system **100** may include a drive assembly **118** configured to assist in controlling lowering or raising of the assembly **104** and advancing or retracting the coiled tubing **114**. In embodiments, the drive assembly **118** is operably connected to the rotatable spool **116** to control rotation of the spool and thereby wind or unwind the coiled tubing **114** from the rotatable spool **116**. In some embodiments, the drive assembly **118** may comprise a motor operably connected to the rotatable spool **116** and arranged to rotate the rotatable spool **116**. In the illustrated embodiment, rotation of the rotatable spool **116** may be controlled by the drive assembly **118** which is mounted on the rotatable spool **116**, such as a hydraulic motor or a chain-and-sprocket drive assembly.

[0022] In addition, the system **100** may include a support structure **120**. The support structure **120** may include various structures and/or mechanisms, such as a derrick, crane, mast, tripod, or other similar type of structure. In embodiments, an injector **121** is operably connected to the support structure **120** to control advancement and retraction of the coiled tubing **114**. In the illustrated embodiment, the coiled tubing **114** is guided from the rotatable spool **116** to the injector **121** via a tubing guide arch **119**, alternately referred to as a “gooseneck.” The tubing guide arch **119** supports the coiled tubing **114** through a bending radius and guides the coiled tubing **114** into the injector **121**, alternately referred to as an “injector head”. The injector **121** is designed to grip the outer diameter of the coiled tubing **114** and provide the force required to convey the coiled tubing **114** into the wellbore **106** and subsequently retrieve the coiled tubing **114**. The injector **121** is designed to support the full weight of the coiled tubing **114**, and allows an operator to control the rate of lowering the coiled tubing **114** into the wellbore **106**.

[0023] The system **102** may further include a well control stack **123** operatively coupled to the

injector **121** and interposing the injector **121** and a wellhead **125**. The wellhead **125** constitutes the surface termination of the wellbore **106**, and the wellbore **106** extends therefrom. The well control stack **123** can include a stripper assembly that provides the necessary pressure control and lubrication for the coiled tubing **114** as the coiled tubing **114** is conveyed into or retrieved from the wellbore **106**. The well control stack **123** can also include a blowout preventer or “BOP”, which includes a plurality of hydraulically-operated rams used to mechanically seal off the wellbore **106** at the surface **110** if well control is lost.

[0024] The plurality of optical pathways **112** extend from the laser generating source **102** and into the coiled tubing **114**. The distal (downhole) end of the coiled tubing **114** is connected to the assembly **104**, and an uphole end (obscured from view) is connected to the rotatable spool **116**. At the uphole end of the coiled tubing **114**, the plurality of optical pathways **112** enter the coiled tubing **114** from the laser generating source **102**.

[0025] In some embodiments, the assembly **104** may include a centering assembly **122** operable to center the assembly **104** within the wellbore **106**. In the illustrated embodiment, the centering assembly **122** includes a plurality of stabilizing plates **124**, which are adjustable to center the assembly **104** in wellbores **106** of differing diameters. In embodiments, the stabilizing plates **124** are hydraulically activatable. In other embodiments, the stabilizing plates **124** are movable and adjustable via an electric motor. In even other embodiments, the stabilizing plates **124** are adjustable but without any type of motor, but are instead manually adjusted at the surface **110** to center the assembly **104** within the wellbore **106** of a particular diameter. The stabilizing plates **124** may be radially extended from the assembly **104** until they contact walls of the wellbore **106** to thereby center or otherwise position the assembly **104** in a desired position within the wellbore **106** (e.g., within the center of the wellbore **106**).

[0026] In the embodiment illustrated in FIG. 1, the system **100** further includes a master controller **126**. The master controller **126** is operably connected to the assembly **104**, the laser generating source **102**, the centering assembly **122**, the drive assembly **118**, and/or the injector **121**.

Accordingly, the master controller **126** is operable to control the various components and sub-systems of the system **100**. For example, the operator may utilize the master controller **126** to activate or deactivate the centering assembly **122** and thereby center the assembly **104** within the wellbore **106**. Similarly, the operator may utilize the master controller **126** to turn on the laser generating source **102** and/or to raise or lower the assembly **104**.

[0027] As illustrated, the control system **126** may include a computer or computer unit **130** having a display or graphical user interface that allows an operator to manage operation of the assembly **104**, the laser generating source **102**, the centering assembly **122**, the drive assembly **118**, and/or the injector **121**. The computer **130** may also display data and information obtained from the assembly **104** during operation. The computer **130** may have a processor and a computer readable medium on which programmable instructions may be stored. The computer readable medium can include a nonvolatile or non-transitory memory with data and instructions that are accessible to the processor and executable thereby. The computer readable medium may also be pre-programmed or selectively programmable with instructions for operating the assembly **104** or any of the method steps described herein.

[0028] FIGS. 2-3 illustrate a cross section of the assembly **104** of FIG. 1 when located downhole of the wellbore **106**, according to one or more embodiments of the present disclosure. As shown, the assembly **104** includes a tool housing **202**. The tool housing **202** extends along a tool axis A and includes a downhole end **204** and an uphole end **206**. In addition, the tool housing **202** defines an interior space **208** that extends between the downhole end **204** and the uphole end **206**. In the illustrated example, the tool housing **202** is cylindrical in shape, but the tool housing **202** may have other geometries in other embodiments.

[0029] As shown in FIG. 1, the plurality of optical pathways **112** extend to the tool housing **202** within the coiled tubing **114**. Each optical pathway **112** is configured to direct an individual laser

beam B generated by the laser generating source **102** (FIG. **1**) into the interior space **208** of the tool housing **202**. In embodiments, the optical pathways **112** extend through the tool housing **202** and into the interior space **208**. In the illustrated embodiment, a base **210** is provided at the uphole end **206** of the tool housing **202** and the plurality of optical pathways **112** extend through the base **210**. [0030] Each optical pathway **112** includes an input end **212** (FIG. **1**) and an output end **214**. The input end **212** of the optical pathways **112** is connected to the laser generating source **102** such that each optical pathway **112** is in communication with the laser of the laser generating source **102** (FIG. **1**) to receive and conduct/transmit the laser beams B. The laser beams B exit their respective optical pathway **112** at the output end **214**. In the illustrated embodiment, a collimator **216** is provided at the output end **214** of each optical pathway **112**.

[0031] The collimators **216** may be mounted within the interior space **208** of the tool housing **202** and function to align the electromagnetic radiation emitted therefrom in a uniform column in the form of the laser beams B. Here, each of the collimators **216** is provided within the interior space **208** of the tool housing **202** and oriented such that it directs the laser beam B associated with it through the interior space **208** parallel to the tool axis A.

[0032] The assembly **104** further includes a plurality of reflectors **220**, such as mirrors. In the illustrated embodiment, the reflectors **220** include a pair of reflectors (i.e., first and second reflectors); however, more or less than two reflectors may be utilized. Also in the illustrated embodiment, the pair of reflectors **220** are positioned proximate to each other and at the same position measured along tool axis A, such that the pair of reflectors **220** defines a single (or first) stage of reflectors. However, as described below, the assembly **103** may include one or more additional stages of reflectors positioned elsewhere along the tool axis A. Also in the illustrated embodiment, each reflector **220** is positioned at opposite sides of the tool housing **202** (e.g., angularly opposite), such that they are positioned about 180° apart from each other. However, the reflectors **220** may be provided elsewhere about the tool housing **202**.

[0033] Each reflector **220** is associated with one of the collimators **216** and one of the optical pathways **112**. In addition, each reflector **220** is able to be positioned in the path of the laser beam B discharged from the collimator **216** associated therewith, as shown in FIG. **2**. As described herein, the reflectors **220** are each movable between an activated position, as shown in FIG. **2**, and a deactivated position, as shown in FIG. **3**. In the illustrated embodiment, the assembly **104** includes at least one motor **222** operable to transition one or more of the reflectors **220** between the activated and deactivated positions. In the illustrated embodiment, each reflector **220** is operatively coupled to a discrete motor **222** to move the corresponding reflector **220** as indicated by rotational arrow R. However, in other embodiments, more than one of the reflectors **220** may be operatively coupled to the same motor **222** such that they are movable in unison via an individual motor **222**. In the illustrated embodiment, The motors **222** are mounted within the interior space **208** of the tool housing **202**. The motors **222** may be in communication with the master controller **126** (FIG. **1**) such that they may be controlled from the surface **110**. Thus, the operator may utilize the master controller **126** to move the reflectors **220** between the activated and deactivated positions.

[0034] When in the activated position, the reflectors **220** are each angled or oriented such that they are operable to redirect or reflect the associated laser beam B radially outward and away from the tool axis A. In the illustrated embodiment, a plurality of side ports **224** are formed in the tool housing **202** and positioned such that each laser beam B may be directed out of the tool housing **202** through a corresponding one of the side ports **224**. In embodiments, a lens or transparent cover may be provided in each side port **224**, such that the interior space **208** of the tool housing **202** may remain sealed from the ambient environment while permitting the laser beams B to exit the tool housing **202**. When the reflectors **220** are in the activated position and redirecting/reflecting the laser beams B radially outward from the tool housing **202**, the laser beams B will penetrate the sides of the wellbore **106** to create perforations **226**. In applications where the wellbore **106** is lined with casing or another type of wellbore liner, the laser beams B may also be operable to penetrate

the casing. In the illustrated embodiment, the reflectors **220** redirect the laser beams B radially outward from the tool housing **202** generally parallel to each other and oriented in the same plane. However, the radially redirected laser beams B need not be in the same plane or parallel to each other.

[0035] The assembly **104** also includes a plurality reshaping lenses **230**. Each reshaping lens **230** is arranged within the interior space **208** of the tool housing **202**. During use, the laser beams B are transmitted along the tool axis A and, when the reflectors **220** are in the deactivated position, the laser beams B will each travel axially along the tool axis A further down the interior space **208** of the tool housing **202** (than when in the activated position), such that the laser beams B bypass the plurality of reflectors **220** and contact the reshaping lenses **230**. As best seen in FIG. 3, the reshaping lenses **230** combine the individual laser beams B into a combined main laser beam B' that exits the downhole end **204** of the tool housing **202**. Thus, when the plurality of reflectors **220** are in the deactivated position, the assembly **104** is operable direct the combined main laser beam B' axially down bore as described below.

[0036] In the illustrated embodiment, each reshaping lens **230** is supported within the interior space **208** via a support **232**. The supports **232** may be holders made from various types of material, such as materials that resist heating up, such as copper. In embodiments, the supports **232** are attached via mechanical fasteners, such as bolts or screws. In addition, each reshaping lens **230** is associated with one of the reflectors **220**, one of the collimators **216**, and one of the optical pathways **112**. Further, each reshaping lens **230** is positioned within the path of one of the laser beams B, so that the laser beam B will contact and interact with the reshaping lens **230** when the corresponding reflector **220** is in the deactivated position. For example, when the reflectors **220** are in the activated position, the laser beams B are redirected out of the tool housing **202**, as described above with reference to FIG. 2. In contrast, when the reflectors **220** are in the deactivated position, as shown in FIG. 3, each laser beam B is directed to a corresponding one of the reshaping lenses **230**. Thus, the reshaping lenses **230** are operable to redirect the laser beams B, for example, when the reflectors **220** are in the deactivated position. As shown, each reshaping lens **230** receives and redirects one of the laser beams B, and the reshaping lenses **230** are each configured to redirect its associated laser beam B radially inward toward the tool axis A and the downhole end **204**, such that the laser beams B converge together at a focal point F.

[0037] Still referring to FIG. 3, the assembly **104** also includes a main beam optical assembly **300**. The main beam optical assembly **300** is operable to receive the individual laser beams B received from the reshaping lenses **230**, and combine the individual laser beams B into the main beam B'. The main beam optical assembly **300** may be provided at or near the downhole end **204** of the tool housing **202**, and may be at least partially arranged within the interior space **208** of the tool housing **202**.

[0038] In the illustrated embodiment, the uphole end of the main beam optical assembly **300** is positioned at the focal point F. As illustrated, the main beam optical assembly **300** includes a first focusing lens **302** positioned at the focal point F, a second focusing lens **304** positioned downhole of the first focusing lens **302**, and a third focusing lens **306** positioned downhole of the second focusing lens **304**. As shown, in the illustrated embodiment, the third focusing lens **306** is positioned closest to the downhole end **204** and the first focusing lens **302** is positioned closest to the uphole end **206**, and the second focusing lens **304** interposes the first and third focusing lenses **302**, **306**. The focusing lenses **302**, **304**, **306** are operable to combine the individual laser beams B into the combined main laser beam B' which is more powerful than any of the individual laser beams B. In addition, the focusing lenses **302**, **304**, **306** are operable to manipulate the shape of the combined main laser beam B' into a desired shape and strength suitable for boring. Thus, the focusing lenses **302**, **304**, **306** are operable to merge the individual beams B and reshape them into the main laser beam B'.

[0039] Also in the illustrated embodiment, the main beam optical assembly **300** includes a nozzle



**310** at the downhole end of the main beam optical assembly **300**. During use, the combined main laser beam **B'** exits the main beam optical assembly **300** at the nozzle **310**. The nozzle **310** includes baffles **312** configured to facilitate shaping of the combined main laser beam **B'**.

[0040] As mentioned above, the tool housing **202** includes an opening **313** at the downhole end **204** thereof. In the illustrated embodiment, the assembly **104** further includes a distal lens **314** arranged in the opening **313**. The distal lens **314** is configured to permit the combined main laser beam **B'** to be transmitted through the distal lens **314**, such that the combined main laser beam **B'** may be directed downhole from the assembly **104**. In embodiments, the cover distal lens is a transparent cover and operable from inhibit particulate and substances present in the wellbore **106** from entering the interior space **208** of the tool housing **202** and/or the main beam optical assembly **300**. In embodiments, the distal lens **314** is integral with the main beam optical assembly **300**. For example, the distal lens **314** may be supported within the nozzle **310** thereof, for example, within the baffles **312**.

[0041] During operation, significant heat generation may occur within the main beam optical assembly **310**, the focusing lenses **302**, **304**, **306**, and/or the distal lens **314** may be exposed to high temperatures due to their interaction with the combined main laser beam **B'**. To provide cooling and otherwise control heat generation, an inert gas **G** may be utilized to cool the optics of the main beam optical assembly **310**. In an embodiment, the inert gas **G** is provided in a first space defined between the first focusing lens **302** and the second focusing lens **304**, in a second space defined between the second focusing lens **304** and the third focusing lens **306**, and/or in a third space defined between the third focusing lens **306** and the distal lens **314**. In embodiments, the inert gas **G** includes Nitrogen; however, other gases may be utilized in addition to or in lieu of Nitrogen. In addition to cooling the optics, utilization of the inert gas **G** ensures the downhole path of the combined main laser beam **B'** within the assembly **104** is clearer than would otherwise be if traveling through ambient air.

[0042] The combined main laser beam **B'** exiting the assembly **104**, which has more power and energy than the individual laser beams **B**, is directed axially downhole and can be used to perform a drilling or boring function within the wellbore **106**. As will be appreciated, drilling or boring may be utilized to deepen the wellbore **106**. As shown in FIG. 3, the main laser beam **B'** expands radially outward (relative to the tool axis **A**) as it travels axially downhole, such that it is operable to enlarge the wellbore **106** in order to permit the assembly **104** to travel there-through. However, when the reflectors **210** are in the activated position, as shown in FIG. 2, the individual laser beams **B** are directed radially outward to create the perforations **226**. As mentioned above, the individual laser beams **B** are transmitted to the assembly **104** via each optical pathway **112**, which are of relatively lower power than the main laser beam **B'**. However, less power loss occurs when transmitting relatively lower power through the optical pathways **112** as compared if relatively higher power were conveyed therethrough. Thus, the system **100** is more efficient than conventional systems that would convey relatively higher power to the downhole assembly via a single optical pathway. Moreover, the assembly **104** is still operable to generate the main laser beam **B'** by aggregating the individual laser beams **B**, which is of relatively higher power and suitable for operations in which higher power is desirable, such as laser drilling.

[0043] While FIGS. 2-3 illustrate an embodiment of the assembly **104** having a pair of reflectors **120** arranged as a single stage, one or more additional stages of reflectors may be provided. FIG. 4 illustrates another example downhole assembly **400** incorporating several stages of reflectors, according to one or more additional embodiments of the present disclosure.

[0044] As with the assembly **104** described above, the downhole assembly **400** (hereinafter "the assembly **400**") includes a tool housing **402** that extends along a tool axis **A'**, and the tool housing **402** includes an uphole end **404** and a downhole end **406**.

[0045] In the illustrated embodiment, the downhole assembly **400** (hereinafter, the assembly **400**) includes a first stage **412**, a second stage **414**, and a third stage **416** (collectively, the stages **412**,

**414, 416**). The first stage **412** is closest to the uphole end **404**, the third stage **416** is closest to the downhole end **406**, and the second stage **414** interposes the first and third stages **412, 416**. While three stages **412, 414, 416** are included in the assembly **400**, more or less than three stages may be included, without departing from the scope of the disclosure.

[0046] In the illustrated embodiment, each stage **412, 414, 416** is configured to discharge four separate laser beams **b** out of the tool housing **402**, radially outward from the tool axis **A'**. Thus, in the illustrated embodiment, each stage **412, 414, 416** may include four reflectors that are operable to radially redirect electromagnetic (laser) energy as described above with reference to the plurality of reflectors **220** (FIGS. 2 and 3). In the illustrated embodiment, each reflector in the first stage **412** is positioned within the tool housing **402** at ninety-degree intervals, such that the laser beams **b** emitted from the first stage **412** are directed radially outward within a plane and at orientations that are perpendicular to neighboring laser beams **b**. The reflectors in the second and third stages **414, 416** are similarly positioned to direct their laser beams **b** in a similar manner; however, the reflectors in any one or more of the stages may be differently positioned to direct their laser beam **b** in a different orientation or direction.

[0047] In the illustrated embodiment, the assembly **400** is operable to activate the laser beams **b** of all of the stages **412, 414, 416** at the same time (simultaneously). As shown, FIG. 4 depicts an example where twelve laser beams **b** are being directed radially outward of the tool housing **402**. Thus, in this embodiment, the assembly **400** would include twelve optical pathways (not shown) and associated collimators (i.e., a collimator on each of the twelve reflectors), each responsible for sending one laser beam **b** to the associated reflector, such that all twelve laser beams **b** may be simultaneously directed radially outward of the tool housing **402** as shown. The assembly **400** may further include at least one reshaping lens (e.g., twelve associated reshaping lenses, with each reshaping lens associated with one of the optical pathways) operable for redirecting the energy from each optical pathway into a combined main laser beam (not shown). Here, each individual reshaping lens may be aligned with one of the reflectors and one of the optical pathways. Similarly in this embodiment, the assembly **400** is operable to deactivate all of the laser beams **b** of all of the stages **412, 414, 416** at the same time, such that the energy from all twelve of the optical pathways may be directed axially toward the downhole end **406** of the tool housing **402**, combined into a main laser beam via the reshaping lens(es), and then the main laser beam may be emitted out of the downhole end **406** of the tool housing **402**, wherein the main laser beam exhibits a higher energy than any of the discrete laser beams **b** which are each of relatively lower power.

[0048] In other embodiments, however, the stages **412, 414, 416** may be separately activatable and separately deactivatable. In such embodiments, the assembly **400** could include four optical pathways (not shown) and associated collimators, each responsible for sending one of the laser beams **b** to one of the four reflectors of one of the stages **412, 414, 416**, such that the four laser beams **b** may be directed radially outward of the tool housing **402**, one stage at a time. In such embodiments, a first reflector in the first stage **412**, a first reflector in the second stage **414**, and a first reflector in the third stage **416** may all be in alignment with each other and with one of the four optical pathways, such that the first reflector in the first stage **412** may receive the energy beam, such that the first reflector in the second stage **414** may receive the energy beam when the first reflector in the first stage **412** is in the deactivated position, and such that the first reflector in the third stage **416** may receive the energy beam when the first reflector in the first stage **412** and the first reflector in the second stage **414** are in the deactivated positions.

[0049] Moreover, in such embodiments, the assembly **400** includes four reshaping lenses each in alignment with one of the four optical pathways such that, when the all of the reflectors are in the deactivated position, energy from the four optical pathways may be directed axially toward the downhole end **406** and then redirected the reshaping lenses and combined into a main laser beam that is emitted out of the downhole end **406** of the tool housing **402**. For example, the reflectors in the first stage **412** may be activated to cause the laser beams **b** in that stage to be radially directed

out of the tool housing **402**, and then either or both of the second stage **414** and/or the third stage **416** may be selectively activated to thereby cause the laser beams **b** associated therewith to also be radially directed out of the tool housing **402**; or, the stages **412**, **414**, **416** may all be simultaneously deactivated, and then the energy from the four optical pathways may be directed axially toward the downhole end **406** and then redirected by one or more reshaping lenses and combined into a main laser beam that is emitted out of the downhole end **406** of the tool housing **402**, wherein the main laser beam exhibits a higher energy than any of the discrete laser beams **b** which are each of relatively lower power. In embodiments, less than all of the stages **412**, **414**, **416** may be activated to radially direct the laser beams **b** associated therewith out of the tool housing **402**, while the remaining one or more stages **412**, **414**, **416** are deactivated such that energy associated with such deactivated reflectors may be directed axially toward the downhole end **406** and then redirected by one or more reshaping lenses and combined into a main laser beam that is emitted out of the downhole end **406** of the tool housing **402**.

[0050] FIG. 5 illustrates yet another example downhole assembly **500**, according to one or more additional embodiments of the present disclosure. As with the assemblies **104** and **400** described above, the downhole assembly **500** (hereinafter “the assembly **500**”) includes a tool housing **502** that extends along a tool axis **A''**, and the tool housing **502** includes a downhole end **504** and an uphole end **506**. In the illustrated embodiment, the assembly **500** includes a rotational head **508** that is operable to both emit one or more laser beams and rotate, as indicated by rotational arrow **R'**, wherein rotation of the rotational head **508** affects direction and/or emission of the one or more laser beams. As shown, the rotational head **508** is arranged within the interior space of the tool housing **502** and is operatively connected to one or more of the optical pathways, as described above. Also, as described with reference to the assembly **104**, the assembly **500** includes a main beam optical assembly **510** that is operable to receive one or more laser beams received from the rotational head **508**, and combine/direct it/them into a main beam **B**. The main beam optical assembly **510** may be provided at or near the downhole end **504** of the tool housing **502**, and may be at least partially arranged within the interior space of the tool housing **502**.

[0051] In addition, the assembly **500** includes a plurality of reflectors **520** arranged within the interior space of the tool housing **502**. Also, the housing **502** includes a plurality of exit ports **524**, with each of the exit ports **524** corresponding with one of the reflectors **520** such that a beam redirected by one of the reflectors **520** passes through an associated one of the exit ports **524**.

[0052] In some embodiments, the rotational head **508** is connected to just one optical pathway (not shown) that delivers a single laser beam. In these embodiments, the rotational head **508** is rotatable between at least two positions, an activated position where the rotational head **508** splits the single laser beam into separate laser beams **b'**, and a deactivated position where the rotational head **508** directs the single laser beam distally down through the interior space of the tool body **502** towards the main beam optical assembly **510**, wherein the main beam optical assembly **510** is operable to receive the single laser (not shown), and focus it and then direct it axially out of the tool housing **502** distally along the tool axis **A''**. In the illustrated embodiment, the rotational head **508** is depicted in the activated position, such that the single laser beam and the distally projected focused main beam is not shown. However, when in the illustrated activated position, the rotational head **508** splits the single laser beam into separate laser beams **b'** and directs each separate laser beam **b'** toward a respective one of the reflectors **520**, wherein the reflectors **520**, in turn, redirect their respective laser beam **b'** radially outward through the respective exit port **524** and into the formation, as detailed above.

[0053] In other embodiments, the rotational head **508** is connected to multiple optical pathways (not shown) that each deliver a single laser beam **b'**. In these embodiments, the rotational head **508** is rotatable between at least two positions, an activated position where the rotational head **508** directs each of the separate laser beams **b'** towards a respective one of the reflectors **520**, and a deactivated position where the rotational head **508** directs each of the separate laser beams **b'**

distally down through the interior space of the tool body **502** towards the main beam optical assembly **510**, wherein the main beam optical assembly **510** is operable to receive each of the separate laser beams  $b'$  (not shown), and focus them and combine them into an axially directed main beam that may be projected distally out of the tool housing **502** along the tool axis  $A''$ . In the illustrated embodiment, the rotational head **508** is depicted in the activated position, such that the distally projected combined main beam is not shown. However, when in the illustrated activated position, the rotational head **508** directs each laser beam  $b'$  toward a respective reflector **520**, wherein the reflectors **520**, in turn, each redirect their respective laser beam  $b'$  radially outward through the respective exit port **524** and into the formation, as detailed above.

[0054] The assembly **500** may include a motor (not shown) that is operably connected to the rotational head **508** and configured to rotate the rotational head **508** as indicated by the arrow  $R'$ . The motor may be arranged within the interior space of the tool housing **502**, and may be in communication with the master controller **126** (FIG. **1**) such that it may be controlled from the surface **110**. Thus, the operator may utilize the master controller **126** to move the rotational head **508** between the activated and deactivated positions.

[0055] In embodiments, the reflectors **520** may be fixed within the tool housing **502**, such that they cannot be moved or adjusted. In other embodiments, the reflectors **520** are adjustable within the tool housing **502**, such that the operator may move them to adjust their orientation and thereby adjust the manner in which they redirect the separate laser beams  $b'$  radially outward from the tool housing **502**. In such examples, the operator may pre-set or pre-adjust the reflectors **520** into a desired orientation (before using the assembly **500** downhole (e.g., when the assembly **500** is at the surface **110**), and then lower the assembly **500** downhole with the reflectors **520** having already been pre-adjusted in a desired orientation. In even other embodiments, the reflectors **520** may be motorized and adjustable when the assembly **500** is downhole, as described above with respect to the assemblies **104** and **400**.

[0056] Embodiments disclosed herein include:

[0057] A. A system, comprising: a laser generating source; first and second optical pathways operatively connected to the laser generating source for receiving first and second energy beams, respectively; and a downhole assembly in communication with the laser generating source via the first and second optical pathways, the downhole assembly including: a tool housing extending along a tool axis and having opposing downhole and uphole ends, the first and second optical pathways being operable to direct the first and second energy beams to the tool housing, respectively; a first reflector and a second reflector each movable between an activated position and a deactivated position, the first and second reflectors being arranged to reflect the first and second energy beams, respectively, radially outward and away from the tool axis when in the activated position; a first reshaping lens and a second reshaping lens each arranged within the interior space, the first and second reshaping lenses being arranged to receive and redirect the first and second energy beams, respectively, when the first and second reflectors are in the deactivated position; and a main beam optical assembly operable to combine the first and second energy beams received from the first and second reshaping lenses into a combined energy beam that is directed along the tool axis when the first and second reflectors are in the deactivated position.

[0058] B. A system, comprising: a laser generating source; and a downhole assembly that includes: a tool housing extending along a tool axis and having opposing downhole and uphole ends, the tool housing defining an interior space that extends between the downhole and uphole ends; first and second optical pathways extending between the laser generating source and the tool housing, the first and second optical pathways each having an input end in optical communication with the laser generating source and an output end from which energy is discharged, the first and second optical pathways each configured to conduct energy between the input and output ends; first and second reflectors arranged within the interior space and each being movable between an activated position and a deactivated position, the first reflector being aligned with the output end of the first optical

pathway to receive energy discharged therefrom when in the activated position, and the second reflector being aligned with the output end of the second optical pathway to receive energy discharged therefrom when in the activated position; first and second reshaping lenses arranged within the interior space, the first reshaping lens being aligned with the output end of the first optical pathway to receive energy discharged therefrom when the first reflector is in the deactivated position, and the second reshaping lens being aligned with the output end of the second optical pathway to receive energy discharged therefrom when the second reflector is in the deactivated position; and a main beam optical assembly at least partially arranged in the interior space and operable to combine energy received from the first and second reshaping lenses, wherein, when in the activated positions, the first and second reflectors redirect energy received from the output ends of the first and second optical pathways, respectfully, radially outward and away from the tool axis, and wherein, when the first and second reflectors are in the deactivated position, the main beam optical assembly combines energy received from the first and second reshaping lenses, and directs combined energy axially along the tool axis.

[0059] C. A method comprising: conveying a downhole assembly into a wellbore on coiled tubing, the coiled tubing having first and second optical pathways extending therein between the downhole assembly and a laser generating source, the downhole assembly having a tool housing that extends along a tool axis; transmitting first and second energy beams to the downhole assembly via the first and second optical pathways, respectively; arranging first and second reflectors within the downhole assembly in an activated position and thereby reflecting the first and second energy beams radially outward and away from the tool axis; arranging the first and second reflectors within the downhole assembly in a deactivated position and thereby conveying the first and second energy beams to first and second reshaping lenses, respectively; and with a main beam optical assembly included in the downhole assembly, combining the first and second energy beams received from the first and second reshaping lenses into a combined energy beam; and directing the combined energy beam out of the tool housing along the tool axis.

[0060] Each of embodiments A through C may have one or more of the following additional elements in any combination: **Element 1:** wherein the tool housing includes a first side port associated with the first reflector and a second side port associated with the second reflector, the first reflector being operable to redirect the first energy beam through the first side port when in the activated position, and the second reflector being operable to redirect the second energy beam through the second side port when in the activated position. **Element 2:** further comprising a transparent cover arranged within each of the first and second side ports.

[0061] **Element 3:** further comprising a third reflector and a fourth reflector each movable between an activated position and a deactivated position, wherein the third reflector is arranged to reflect the first energy beam radially outward and away from the tool axis when in the activated position and when the first reflector is in the deactivated position, and the fourth reflector is arranged to reflect the second energy beam radially outward away from the tool axis when in the activated position and when the second reflector is in the deactivated position. **Element 4:** wherein, when the first, second, third, and fourth reflectors are all in the deactivated position, the first and second energy beams travel past the first, second, third, and fourth reflectors and are combined into the combined beam. **Element 5:** wherein the third and fourth reflectors are positioned closer to the downhole end than the first and second reflectors, the third reflector being aligned with the first optical pathway and the first reflector, and the fourth reflector being aligned with the second optical pathway and the second reflector. **Element 6:** wherein the first reshaping lens is aligned with the first optical pathway, the first reflector, and the third reflector, and the second reshaping lens is aligned with the second optical pathway, the second reflector, and the fourth reflector. **Element 7:** further comprising: third and fourth optical pathways operatively connected to the laser generating source for receiving third and fourth energy beams, respectively, the third and fourth optical pathways each extending between the laser generating source and the tool housing and being operable to

direct the third and fourth energy beams, respectively, to the tool housing, the downhole assembly further including: third and fourth reflectors each movable between an activated position and a deactivated position, the third and fourth reflectors being arranged to reflect the third and fourth energy beams radially outward and away from the tool axis when in the activated position. **Element 8:** wherein the downhole assembly further includes third and fourth reshaping lenses each arranged within the interior space, the third and fourth reshaping lenses being arranged to receive and redirect the third and fourth energy beams, respectively, to the main beam optical assembly when the third and fourth reflectors are in the deactivated position. **Element 9:** wherein, when the first, second, third, and fourth reflectors are all simultaneously in the deactivated position, the main beam optical assembly is operable to combine the first, second, third, and fourth energy beams into the combined energy beam. **Element 10:** wherein the first, second, third, and fourth reflectors are operable to simultaneously redirect the first, second, third, and fourth energy beams, respectively, when in the activated positions. **Element 11:** wherein the third and fourth reflectors are positioned closer to the downhole end than the first and second reflectors. **Element 12:** wherein the first and second optical pathways each comprise an input end in optical communication with the laser generating source and an output end, the downhole assembly further including: a first collimator provided at the output end of the first optical pathway and a second collimator provided at the output end of the second optical pathway. **Element 13:** wherein the downhole assembly further includes a centering assembly operable to center the tool housing within a wellbore. **Element 14:** wherein an inert gas is provided within the main beam optical assembly. **Element 15:** wherein the tool housing defines an opening at the downhole end, and the main beam optical assembly further includes a distal lens provided in the opening. **Element 16:** wherein the downhole assembly further includes at least one motor operable to move the first and second reflectors between the activated and deactivated positions. **Element 17:** wherein the first and second optical pathways are arranged within coiled tubing connected to the downhole assembly, the system further comprising: a rotatable spool around which the coiled tubing may be provided, and a drive assembly operable to control winding or unwinding of the coiled tubing about the rotatable spool.

[0062] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, for example, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “contains,” “containing,” “includes,” “including,” “comprises,” and/or “comprising,” and variations thereof, when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0063] Terms of orientation are used herein merely for purposes of convention and referencing and are not to be construed as limiting. However, it is recognized these terms could be used with reference to an operator or user. Accordingly, no limitations are implied or to be inferred. In addition, the use of ordinal numbers (e.g., first, second, third, etc.) is for distinction and not counting. For example, the use of “third” does not imply there must be a corresponding “first” or “second.” Also, if used herein, the terms “coupled” or “coupled to” or “connected” or “connected to” or “attached” or “attached to” may indicate establishing either a direct or indirect connection, and is not limited to either unless expressly referenced as such.

[0064] The use of directional terms such as above, below, upper, lower, upward, downward, left, right, uphole, downhole and the like are used in relation to the illustrative embodiments as they are depicted in the figures, the upward direction being toward the top of the corresponding figure and the downward direction being toward the bottom of the corresponding figure, the uphole direction being toward the surface of the well and the downhole direction being toward the toe of the well.

[0065] While the disclosure has described several exemplary embodiments, it will be understood by those skilled in the art that various changes can be made, and equivalents can be substituted for

elements thereof, without departing from the spirit and scope of the invention. In addition, many modifications will be appreciated by those skilled in the art to adapt a particular instrument, situation, or material to embodiments of the disclosure without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiments disclosed, or to the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims. Moreover, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, or component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative.

## Claims

1. A system, comprising: a laser generating source; first and second optical pathways operatively connected to the laser generating source for receiving first and second energy beams, respectively; and a downhole assembly in communication with the laser generating source via the first and second optical pathways, the downhole assembly including: a tool housing extending along a tool axis and having opposing downhole and uphole ends and defining an interior space extending between the downhole and uphole ends, the first and second optical pathways being operable to direct the first and second energy beams to the tool housing, respectively; a first reflector and a second reflector each movable between an activated position and a deactivated position, the first and second reflectors being arranged to reflect the first and second energy beams, respectively, radially outward and away from the tool axis when in the activated position; a first reshaping lens and a second reshaping lens each arranged within the interior space, the first and second reshaping lenses being arranged to receive and redirect the first and second energy beams, respectively, when the first and second reflectors are in the deactivated position; and a main beam optical assembly operable to combine the first and second energy beams received from the first and second reshaping lenses into a combined energy beam that is directed along the tool axis when the first and second reflectors are in the deactivated position.
2. The system of claim 1, wherein the tool housing includes a first side port associated with the first reflector and a second side port associated with the second reflector, the first reflector being operable to redirect the first energy beam through the first side port when in the activated position, and the second reflector being operable to redirect the second energy beam through the second side port when in the activated position.
3. The system of claim 2, further comprising a transparent cover arranged within each of the first and second side ports.
4. The system of claim 1, further comprising a third reflector and a fourth reflector each movable between an activated position and a deactivated position, wherein the third reflector is arranged to reflect the first energy beam radially outward and away from the tool axis when in the activated position and when the first reflector is in the deactivated position, and the fourth reflector is arranged to reflect the second energy beam radially outward away from the tool axis when in the activated position and when the second reflector is in the deactivated position.
5. The system of claim 4, wherein, when the first, second, third, and fourth reflectors are all in the deactivated position, the first and second energy beams travel past the first, second, third, and fourth reflectors and are combined into the combined beam.
6. The system of claim 4, wherein the third and fourth reflectors are positioned closer to the downhole end than the first and second reflectors, the third reflector being aligned with the first optical pathway and the first reflector, and the fourth reflector being aligned with the second optical pathway and the second reflector.

7. The system of claim 6, wherein the first reshaping lens is aligned with the first optical pathway, the first reflector, and the third reflector, and the second reshaping lens is aligned with the second optical pathway, the second reflector, and the fourth reflector.

8. The system of claim 1, further comprising: third and fourth optical pathways operatively connected to the laser generating source for receiving third and fourth energy beams, respectively, the third and fourth optical pathways each extending between the laser generating source and the tool housing and being operable to direct the third and fourth energy beams, respectively, to the tool housing, the downhole assembly further including: third and fourth reflectors each movable between an activated position and a deactivated position, the third and fourth reflectors being arranged to reflect the third and fourth energy beams radially outward and away from the tool axis when in the activated position.

9. The system of claim 8, wherein the downhole assembly further includes third and fourth reshaping lenses each arranged within the interior space, the third and fourth reshaping lenses being arranged to receive and redirect the third and fourth energy beams, respectively, to the main beam optical assembly when the third and fourth reflectors are in the deactivated position.

10. The system of claim 9, wherein, when the first, second, third, and fourth reflectors are all simultaneously in the deactivated position, the main beam optical assembly is operable to combine the first, second, third, and fourth energy beams into the combined energy beam.

11. The system of claim 8, wherein the first, second, third, and fourth reflectors are operable to simultaneously redirect the first, second, third, and fourth energy beams, respectively, when in the activated positions.

12. The system of claim 8, wherein the third and fourth reflectors are positioned closer to the downhole end than the first and second reflectors.

13. The system of claim 1, wherein the first and second optical pathways each comprise an input end in optical communication with the laser generating source and an output end, the downhole assembly further including: a first collimator provided at the output end of the first optical pathway and a second collimator provided at the output end of the second optical pathway.

14. The system of claim 1, wherein the downhole assembly further includes a centering assembly operable to center the tool housing within a wellbore.

15. The system of claim 1, wherein an inert gas is provided within the main beam optical assembly.

16. The system of claim 1, wherein the tool housing defines an opening at the downhole end, and the main beam optical assembly further includes a distal lens provided in the opening.

17. The system of claim 1, wherein the downhole assembly further includes at least one motor operable to move the first and second reflectors between the activated and deactivated positions.

18. The system of claim 1, wherein the first and second optical pathways are arranged within coiled tubing connected to the downhole assembly, the system further comprising: a rotatable spool around which the coiled tubing may be provided, and a drive assembly operable to control winding or unwinding of the coiled tubing about the rotatable spool.

19. A system, comprising: a laser generating source; and a downhole assembly that includes: a tool housing extending along a tool axis and having opposing downhole and uphole ends, the tool housing defining an interior space that extends between the downhole and uphole ends; first and second optical pathways extending between the laser generating source and the tool housing, the first and second optical pathways each having an input end in optical communication with the laser generating source and an output end from which energy is discharged, the first and second optical pathways each configured to conduct energy between the input and output ends; first and second reflectors arranged within the interior space and each being movable between an activated position and a deactivated position, the first reflector being aligned with the output end of the first optical pathway to receive energy discharged therefrom when in the activated position, and the second reflector being aligned with the output end of the second optical pathway to receive energy discharged therefrom when in the activated position; first and second reshaping lenses arranged



within the interior space, the first reshaping lens being aligned with the output end of the first optical pathway to receive energy discharged therefrom when the first reflector is in the deactivated position, and the second reshaping lens being aligned with the output end of the second optical pathway to receive energy discharged therefrom when the second reflector is in the deactivated position; and a main beam optical assembly at least partially arranged in the interior space and operable to combine energy received from the first and second reshaping lenses, wherein, when in the activated positions, the first and second reflectors redirect energy received from the output ends of the first and second optical pathways, respectfully, radially outward and away from the tool axis, and wherein, when the first and second reflectors are in the deactivated position, the main beam optical assembly combines energy received from the first and second reshaping lenses, and directs combined energy axially along the tool axis.

**20.** A method, comprising: conveying a downhole assembly into a wellbore on coiled tubing, the coiled tubing having first and second optical pathways extending therein between the downhole assembly and a laser generating source, the downhole assembly having a tool housing that extends along a tool axis; transmitting first and second energy beams to the downhole assembly via the first and second optical pathways, respectively; arranging first and second reflectors within the downhole assembly in an activated position and thereby reflecting the first and second energy beams radially outward and away from the tool axis; arranging the first and second reflectors within the downhole assembly in a deactivated position and thereby conveying the first and second energy beams to first and second reshaping lenses, respectively; and with a main beam optical assembly included in the downhole assembly, combining the first and second energy beams received from the first and second reshaping lenses into a combined energy beam; and directing the combined energy beam out of the tool housing along the tool axis.

---