

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394072
Kind Code	B1
Date of Patent	August 19, 2025
Inventor(s)	Spiteri; Conrad

Generating a three-dimensional topography of a training environment

Abstract

A method for adaptive user training and gaming utilizing a media player is disclosed that includes acquiring images from cameras surrounding a training environment and attempting to segment a ball and a human in each of the images, wherein when failing to segment either the ball or the human in a first image, the first image is rejected from further processing. The operations additionally include creating masks of the ball and the human, extracting features for both the ball and the human in each of the remaining images, and computing surface information of the training environment using photoclinometry. For each of the remaining images, the operations includes computing a distance between the ball and the human. Additionally, the operations include identifying an image having the greatest distance between the ball and the human and computing a three-dimensional topography from the identified image.

Inventors:	Spiteri; Conrad (Thames Ditton, GB)
Applicant:	TOCA Football, Inc. (Costa Mesa, CA)
Family ID:	1000007227979
Assignee:	TOCA Football, Inc. (Costa Mesa, CA)
Appl. No.:	18/224987
Filed:	July 21, 2023

Related U.S. Application Data

continuation parent-doc US 17562270 20211227 US 11745077 child-doc US 18224987
continuation parent-doc US 16686003 20191115 US 11207582 20211228 child-doc US 17562270

Publication Classification

Int. Cl.: A63B69/00 (20060101); **A63B71/06** (20060101); **G06T7/292** (20170101); **G06V20/40** (20220101); A63B69/40 (20060101)

U.S. Cl.:

CPC **G06T7/292** (20170101); **A63B69/002** (20130101); **A63B71/0622** (20130101); **G06V20/44** (20220101); A63B69/0053 (20130101); A63B2069/402 (20130101); A63B69/406 (20130101); A63B2225/50 (20130101)

Field of Classification Search

CPC: G06T (7/507); G06V (40/23)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2440274	12/1947	Ibisch	N/A	N/A
3913552	12/1974	Yarur et al.	N/A	N/A
3918711	12/1974	Zak	N/A	N/A
3989246	12/1975	Brown et al.	N/A	N/A
4025071	12/1976	Hodges	N/A	N/A
4029315	12/1976	Bon	N/A	N/A
4150825	12/1978	Wilson	N/A	N/A
4442823	12/1983	Floyd et al.	N/A	N/A
4535992	12/1984	Slagle	N/A	N/A
4645458	12/1986	Williams	N/A	N/A
4726616	12/1987	Schmidt	N/A	N/A
4751642	12/1987	Silva et al.	N/A	N/A
4882676	12/1988	Van De Kop et al.	N/A	N/A
4915384	12/1989	Bear	N/A	N/A
4919428	12/1989	Perkins	N/A	N/A
5107820	12/1991	Salansky	N/A	N/A
5125653	12/1991	Kovacs et al.	N/A	N/A
5188367	12/1992	Gipe et al.	N/A	N/A
5264765	12/1992	Pecorino et al.	N/A	N/A
5342041	12/1993	Agulnek et al.	N/A	N/A
5344137	12/1993	Komori	N/A	N/A
5359986	12/1993	Magrath, III et al.	N/A	N/A
5361455	12/1993	Kiefer	N/A	N/A
5365427	12/1993	Soignet et al.	N/A	N/A
5438518	12/1994	Bianco et al.	N/A	N/A
5447314	12/1994	Yamazaki et al.	N/A	N/A
5464208	12/1994	Pierce	N/A	N/A
5465978	12/1994	Magnone et al.	N/A	N/A
5489099	12/1995	Rankin et al.	N/A	N/A
5490493	12/1995	Salansky	N/A	N/A
5498000	12/1995	Cuneo	N/A	N/A
5529205	12/1995	Corney et al.	N/A	N/A

5556106	12/1995	Jurcisin	N/A	N/A
5649523	12/1996	Scott	N/A	N/A
5683302	12/1996	Harrell et al.	N/A	N/A
5697791	12/1996	Nashner et al.	N/A	N/A
5722384	12/1997	Cox	N/A	N/A
5768151	12/1997	Lowy et al.	N/A	N/A
5860873	12/1998	Karasavas	N/A	N/A
5868578	12/1998	Baum	N/A	N/A
5873797	12/1998	Garn	N/A	N/A
5882204	12/1998	Iannazo et al.	N/A	N/A
5897445	12/1998	Sanders	N/A	N/A
5911214	12/1998	Andrews	N/A	N/A
5938545	12/1998	Cooper et al.	N/A	N/A
6042492	12/1999	Baum	N/A	N/A
6073489	12/1999	French et al.	N/A	N/A
6082350	12/1999	Crews et al.	N/A	N/A
6098458	12/1999	French et al.	N/A	N/A
6179720	12/2000	Rankin et al.	N/A	N/A
6182649	12/2000	Battersby et al.	N/A	N/A
6190271	12/2000	Rappaport et al.	N/A	N/A
6237583	12/2000	Ripley et al.	N/A	N/A
6263279	12/2000	Bianco et al.	N/A	N/A
6308565	12/2000	French et al.	N/A	N/A
6320173	12/2000	Vock et al.	N/A	N/A
6533675	12/2002	Funk	N/A	N/A
6539931	12/2002	Trajkovic et al.	N/A	N/A
6565448	12/2002	Cameron et al.	N/A	N/A
6707487	12/2003	Aman et al.	N/A	N/A
6774349	12/2003	Vock et al.	N/A	N/A
6816185	12/2003	Harmath	N/A	N/A
7040998	12/2005	Jolliffe et al.	N/A	N/A
7082938	12/2005	Wilmot	N/A	N/A
7100791	12/2005	Berger	N/A	N/A
7227977	12/2006	Dotsenko	356/601	G06V 40/19
7335116	12/2007	Petrov	N/A	N/A
7559163	12/2008	Ofuji et al.	N/A	N/A
7610909	12/2008	Greene, Jr.	N/A	N/A
7815525	12/2009	Small	N/A	N/A
7850536	12/2009	Fitzgerald	N/A	N/A
7882831	12/2010	Alger	N/A	N/A
7920052	12/2010	Costabile	N/A	N/A
8142267	12/2011	Adams	N/A	N/A
8164830	12/2011	Astill	N/A	N/A
8210959	12/2011	Balardeta et al.	N/A	N/A
8292733	12/2011	Crawford et al.	N/A	N/A
8444499	12/2012	Balardeta et al.	N/A	N/A
8597142	12/2012	Mayles et al.	N/A	N/A
8617008	12/2012	Marty et al.	N/A	N/A
8705799	12/2013	White et al.	N/A	N/A
8840483	12/2013	Steusloff et al.	N/A	N/A

8893698	12/2013	Boehner	N/A	N/A
8992346	12/2014	Raposo	N/A	N/A
9010309	12/2014	Lewis et al.	N/A	N/A
9017188	12/2014	Joseph et al.	N/A	N/A
9050519	12/2014	Ehlers et al.	N/A	N/A
9162134	12/2014	Schwartz	N/A	N/A
9216330	12/2014	Beck et al.	N/A	N/A
9233292	12/2015	Joseph et al.	N/A	N/A
9469945	12/2015	Khurgin	N/A	N/A
9586099	12/2016	Holthouse	N/A	N/A
9616346	12/2016	Nicora et al.	N/A	N/A
9625321	12/2016	Cavallaro et al.	N/A	N/A
9724584	12/2016	Campbell et al.	N/A	N/A
9782648	12/2016	DeCarlo	N/A	N/A
9901776	12/2017	Mettler	N/A	N/A
9901804	12/2017	Vollbrecht et al.	N/A	N/A
9968837	12/2017	Johnston	N/A	N/A
9999823	12/2017	Chen et al.	N/A	N/A
10092793	12/2017	Marty et al.	N/A	N/A
10300361	12/2018	Khazanov et al.	N/A	N/A
10360685	12/2018	Marty et al.	N/A	N/A
10380409	12/2018	Thornbrue et al.	N/A	N/A
10398957	12/2018	Altshuler et al.	N/A	N/A
10456645	12/2018	Joo et al.	N/A	N/A
10486024	12/2018	Joo et al.	N/A	N/A
10486043	12/2018	Joo et al.	N/A	N/A
10489656	12/2018	Lee et al.	N/A	N/A
10600334	12/2019	Zhang et al.	N/A	N/A
10653936	12/2019	Ganzer	N/A	N/A
10695637	12/2019	Hennessy et al.	N/A	N/A
10974121	12/2020	Thornbrue et al.	N/A	N/A
11207582	12/2020	Lewis et al.	N/A	N/A
11514590	12/2021	Spiteri	N/A	N/A
2002/0148455	12/2001	Trajkovic et al.	N/A	N/A
2003/0008731	12/2002	Anderson et al.	N/A	N/A
2003/0092497	12/2002	Holcomb	N/A	N/A
2003/0109322	12/2002	Funk et al.	N/A	N/A
2003/0142210	12/2002	Carlbom et al.	N/A	N/A
2003/0195052	12/2002	Cohen et al.	N/A	N/A
2004/0058749	12/2003	Pirritano et al.	N/A	N/A
2004/0061324	12/2003	Howard	N/A	N/A
2004/0063521	12/2003	Oister et al.	N/A	N/A
2004/0171388	12/2003	Couronne et al.	N/A	N/A
2004/0185952	12/2003	Marshall	N/A	N/A
2005/0143199	12/2004	Saroyan	N/A	N/A
2005/0197198	12/2004	Otten et al.	N/A	N/A
2005/0227792	12/2004	McCreary et al.	N/A	N/A
2005/0272517	12/2004	Funk et al.	N/A	N/A
2005/0288119	12/2004	Wang et al.	N/A	N/A
2006/0063574	12/2005	Richardson et al.	N/A	N/A

2006/0103086	12/2005	Niemeyer et al.	N/A	N/A
2006/0118096	12/2005	Cucjen et al.	N/A	N/A
2006/0236993	12/2005	Cucjen et al.	N/A	N/A
2006/0247070	12/2005	Funk et al.	N/A	N/A
2006/0281061	12/2005	Hightower et al.	N/A	N/A
2007/0021226	12/2006	Tyroler	N/A	N/A
2007/0021242	12/2006	Krickler	N/A	N/A
2007/0238539	12/2006	Dawe et al.	N/A	N/A
2008/0146365	12/2007	Miesak	N/A	N/A
2008/0192116	12/2007	Tamir et al.	N/A	N/A
2008/0219509	12/2007	White	382/107	A63B 24/0021
2008/0237251	12/2007	Barber	N/A	N/A
2008/0287207	12/2007	Manwaring	N/A	N/A
2008/0300071	12/2007	Valaika	N/A	N/A
2008/0312010	12/2007	Marty et al.	N/A	N/A
2009/0048039	12/2008	Holthouse et al.	N/A	N/A
2009/0074246	12/2008	Distante et al.	N/A	N/A
2009/0127809	12/2008	Meers	N/A	N/A
2009/0210078	12/2008	Crowley	N/A	N/A
2010/0032904	12/2009	Yasuoka et al.	N/A	N/A
2010/0041498	12/2009	Adams	N/A	N/A
2010/0090428	12/2009	Meers et al.	N/A	N/A
2010/0137079	12/2009	Burke et al.	N/A	N/A
2010/0148445	12/2009	Wilkins	N/A	N/A
2010/0151955	12/2009	Holden	N/A	N/A
2010/0184534	12/2009	Chan et al.	N/A	N/A
2010/0210377	12/2009	Lock	N/A	N/A
2010/0261557	12/2009	Joseph et al.	N/A	N/A
2011/0028230	12/2010	Balardeta et al.	N/A	N/A
2011/0143848	12/2010	Balardeta et al.	N/A	N/A
2011/0143849	12/2010	Balardeta et al.	N/A	N/A
2011/0151986	12/2010	Denton et al.	N/A	N/A
2011/0224025	12/2010	Balardeta et al.	N/A	N/A
2011/0304497	12/2010	Molyneux et al.	N/A	N/A
2012/0015753	12/2011	Denton et al.	N/A	N/A
2012/0015754	12/2011	Balardeta et al.	N/A	N/A
2012/0029666	12/2011	Crowley et al.	N/A	N/A
2012/0157200	12/2011	Scavezze et al.	N/A	N/A
2012/0172148	12/2011	Freeman	N/A	N/A
2012/0238381	12/2011	Denton et al.	N/A	N/A
2012/0303207	12/2011	Reindl	N/A	N/A
2012/0309554	12/2011	Gibbs et al.	N/A	N/A
2012/0322568	12/2011	Lindeman	N/A	N/A
2013/0005512	12/2012	Joseph et al.	N/A	N/A
2013/0018494	12/2012	Amini	N/A	N/A
2013/0095961	12/2012	Marty et al.	N/A	N/A
2013/0104869	12/2012	Lewis et al.	N/A	N/A
2013/0157786	12/2012	Joseph et al.	N/A	N/A
2013/0210563	12/2012	Hollinger	N/A	N/A

2013/0225305	12/2012	Yang et al.	N/A	N/A
2013/0271458	12/2012	Andriluka et al.	N/A	N/A
2013/0317634	12/2012	French et al.	N/A	N/A
2013/0324310	12/2012	Leech et al.	N/A	N/A
2014/0003666	12/2013	Park et al.	N/A	N/A
2014/0128171	12/2013	Anderson	N/A	N/A
2014/0330411	12/2013	Lochmann	N/A	N/A
2015/0116501	12/2014	McCoy et al.	N/A	N/A
2015/0202508	12/2014	Wise, Jr.	N/A	N/A
2015/0292261	12/2014	Chou	N/A	N/A
2016/0008662	12/2015	Cronin et al.	N/A	N/A
2016/0023042	12/2015	Cherry	N/A	N/A
2016/0023083	12/2015	Tawwater et al.	N/A	N/A
2016/0074735	12/2015	Dawe et al.	N/A	N/A
2016/0158626	12/2015	Dolige et al.	N/A	N/A
2016/0193500	12/2015	Webster et al.	N/A	N/A
2017/0021259	12/2016	Dismuke	N/A	N/A
2017/0095716	12/2016	Lewis	N/A	A63B 69/40
2017/0120132	12/2016	Shin et al.	N/A	N/A
2017/0157484	12/2016	Altshuler et al.	N/A	N/A
2017/0182361	12/2016	Tuxen et al.	N/A	N/A
2017/0189753	12/2016	Polifka	N/A	N/A
2017/0203182	12/2016	Spelman et al.	N/A	N/A
2017/0259144	12/2016	Eddie	N/A	N/A
2017/0259145	12/2016	Kline	N/A	N/A
2017/0274262	12/2016	Sanchez et al.	N/A	N/A
2017/0291093	12/2016	Janssen	N/A	N/A
2017/0304705	12/2016	Hermendorfer	N/A	N/A
2017/0319930	12/2016	Lewis et al.	N/A	N/A
2017/0333777	12/2016	Spivak et al.	N/A	N/A
2017/0340943	12/2016	Pierotti et al.	N/A	N/A
2017/0368439	12/2016	Khazanov	N/A	A63B 24/0075
2018/0036590	12/2017	DeAngelis et al.	N/A	N/A
2018/0036616	12/2017	McKenney	N/A	N/A
2018/0056124	12/2017	Marty et al.	N/A	N/A
2018/0071577	12/2017	Swartz et al.	N/A	N/A
2018/0137363	12/2017	Campagnoli et al.	N/A	N/A
2018/0140917	12/2017	Song et al.	N/A	N/A
2018/0189971	12/2017	Hildreth	N/A	N/A
2018/0290019	12/2017	Rahimi et al.	N/A	N/A
2018/0301169	12/2017	Ricciardi	N/A	N/A
2018/0302610	12/2017	Masuda	N/A	H04N 13/117
2018/0318715	12/2017	Dawe et al.	N/A	N/A
2019/0087661	12/2018	Lee et al.	N/A	N/A
2020/0298087	12/2019	Hermendorfer et al.	N/A	N/A
2021/0146218	12/2020	Lewis et al.	N/A	N/A
2021/0146220	12/2020	Hall	N/A	A63B 63/004
2021/0279896	12/2020	Tong et al.	N/A	N/A
2022/0001236	12/2021	Mooney	N/A	G06F 18/00

2022/0051419	12/2021	Spiteri	N/A	N/A
2022/0391620	12/2021	Spiteri	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2005248763	12/2009	AU	N/A
2476010	12/2004	CA	N/A
2931744	12/2013	CA	N/A
2892188	12/2006	CN	N/A
1824352	12/2009	CN	N/A
102389634	12/2011	CN	N/A
202223857	12/2011	CN	N/A
103706088	12/2013	CN	N/A
205964896	12/2016	CN	N/A
104504694	12/2016	CN	N/A
19938761	12/2000	DE	N/A
102015225776	12/2016	DE	N/A
1477825	12/2003	EP	N/A
1897599	12/2007	EP	N/A
1913981	12/2007	EP	N/A
2227299	12/2009	EP	N/A
2218483	12/2016	EP	N/A
3188810	12/2016	EP	N/A
3242728	12/2016	EP	N/A
2196859	12/1990	GB	N/A
2337385	12/1998	GB	N/A
2442070	12/2007	GB	N/A
2487047	12/2011	GB	N/A
2487209	12/2011	GB	N/A
2505417	12/2013	GB	N/A
2539837	12/2015	GB	N/A
2544561	12/2016	GB	N/A
2560032	12/2017	GB	N/A
2010112956	12/2009	JP	N/A
101579382	12/2014	KR	N/A
20160124254	12/2015	KR	N/A
20170104700	12/2016	KR	N/A
101799650	12/2016	KR	N/A
M353032	12/2008	TW	N/A
M551080	12/2016	TW	N/A
95/21661	12/1994	WO	N/A
2003032006	12/2002	WO	N/A
2006126976	12/2005	WO	N/A
2007037705	12/2006	WO	N/A
2009138929	12/2008	WO	N/A
2010102037	12/2009	WO	N/A
2011106888	12/2010	WO	N/A
2012/161768	12/2011	WO	N/A
2014021549	12/2013	WO	N/A
2015112646	12/2014	WO	N/A

OTHER PUBLICATIONS

“HitTrax,” <https://www.hittrax.com>, last accessed Aug. 23, 2021. cited by applicant

Anon., “Epipolar geometry” https://en.wikipedia.org/wiki/Epipolar_geometry, last accessed May 4, 2020. cited by applicant

Anonymous: “From Fashion to Football Vision Pushes the Envelope of Entertainment” Nov. 24, 2014; Nov. 24, 2014; URL: <https://www.automate.org/industry-insights/from-fashion-to-football-vision-pushes-the-envelope-of-entertainment>. cited by applicant

C. Spiteri et al. “Quasi-thematic feature detection and tracking for future rover long-distance autonomous navigation.” Conference: Symposium on Advanced Space Technologies in Robotics and Automation, vol. 12, May 2013. cited by applicant

C. Spiteri, “Planetary Robotic Vision Processing for Terrain Assessment,” Section 6.1.1—Doctoral Thesis, Surrey Space Centre, Faculty of Engineering and Physical Sciences, University of Surrey. 2018. cited by applicant

C. Spiteri, “System and Method for Object Tracking and Metric Generation,” filed Aug. 13, 2020, U.S. Appl. No. 16/993,035 including its prosecution history. cited by applicant

C. Spiteri, “System and Method for Object Tracking Using a Subsection of a Sequence of Images,” filed Jul. 14, 2023, U.S. Appl. No. 18/222,283 including its prosecution history. cited by applicant

C. Spiteri, “System and Method for Object Tracking,” filed Aug. 13, 2020, U.S. Appl. No. 16/993,030 Including its prosecution history. cited by applicant

C. Spiteri, “System, Method and Apparatus for Object Tracking and Human Pose Estimation,” filed Nov. 28, 2022, U.S. Appl. No. 17/994,834 including its prosecution history. cited by applicant

C. Spiteri, et al. “Structure Augmented Monocular Saliency for Planetary Rovers,” Robotics and Autonomous Systems, vol. 88, Feb. 2017, pp. 1-10. cited by applicant

Careless James: “Bringing The Matrix to the NFL TV Tech,” Sep. 9, 2013; Sep. 9, 2013 Retrieved from the Internet URL: <https://www.tvtechnology.com/news/bringing-the-matrix-to-the-nfl>. cited by applicant

Costa Brandon: “The Next Big Thing How Replay Technologies freeD System is Taking Sports TV by Storm,” Oct. 11, 2013; Oct. 11, 2013; URL: <https://www.sportsvideo.org/2013/10/11/the-next-big-thing-how-replay-technologies-freed-system-is-taking-sports-tv-by-storm/>. cited by applicant

E. J. Lewis et al., “Ball Throwing Machine and Method,” filed Feb. 9, 2015, U.S. Appl. No. 14/617,599 Including its prosecution history. cited by applicant

E. J. Lewis et al., “Ball Throwing Machine and Method,” filed Jul. 27, 2017, U.S. Appl. No. 15/662,150 Including its prosecution history. cited by applicant

E. J. Lewis et al., “Ball Throwing Machine and Method,” filed Nov. 2, 2011, U.S. Appl. No. 13/287,749 including its prosecution history. cited by applicant

E. J. Lewis et al., “Detection of the Speed of an Object Passing Through a Goal Plane,” filed Mar. 28, 2023, U.S. Appl. No. 18/191,755 including its prosecution history. cited by applicant

E. J. Lewis et al., “Goal Apparatus,” filed Sep. 19, 2018, U.S. Appl. No. 29/663,886 including its prosecution history. cited by applicant

E. J. Lewis et al., “System and Method for a User Adaptive Training and Gaming Platform,” filed Dec. 27, 2021, U.S. Appl. No. 17/562,270 including its prosecution history. cited by applicant

E. J. Lewis et al., “System and Method for a User Adaptive Training and Gaming Platform,” filed Nov. 15, 2019, U.S. Appl. No. 16/686,003 including its prosecution history. cited by applicant

E. J. Lewis et al., “System and Method for Object Tracking in Coordination With a Ball-Throwing Machine,” filed Aug. 17, 2020, U.S. Appl. No. 16/995,289 including its prosecution history. cited by applicant

E. J. Lewis et al., “System, Apparatus and Method for an Intelligent Goal,” filed Oct. 25, 2018, U.S. Appl. No. 16/171,127 including its prosecution history. cited by applicant

E. J. Lewis et al., “System, Apparatus and Method for Ball Throwing Machine and Intelligent Goal,” filed Dec. 9, 2016, U.S. Appl. No. 15/374,984 including its prosecution history. cited by applicant

PCT/US2020/060355 filed Nov. 13, 2020 International Search Report and Written Opinion dated Feb. 5, 2021. cited by applicant

PCT/US2021/025250 filed Mar. 31, 2021 International Search Report and Written Opinion dated Nov. 12, 2021. cited by applicant

R. I. Hartley et al. “Triangulation” CVIU—Computer Vision and Image Understanding, vol. 68, No. 2, pp. 146-157, Nov. 1997. cited by applicant

R. Sára, “3D Computer Vision” pp. 85-88, 100, 91-95. Oct. 30, 2012. cited by applicant

S. Plumer et al., “System and Method for Altering the Motion of a Foosball,” filed Mar. 7, 2023, U.S. Appl. No. 18/180,109 including its prosecution history. cited by applicant

S. Plumer et al., “System and Method for Foosball Table Implementing Playing Obstacles,” filed Mar. 4, 2021, U.S. Appl. No. 17/192,766 including its prosecution history. cited by applicant

U.S. Appl. No. 16/686,003, filed Nov. 15, 2019 Advisory Action dated Aug. 10, 2021. cited by applicant

U.S. Appl. No. 16/686,003, filed Nov. 15, 2019 Final Office Action dated May 19, 2021. cited by applicant

U.S. Appl. No. 16/686,003, filed Nov. 15, 2019 Non-Final Office Action dated Dec. 7, 2020. cited by applicant

U.S. Appl. No. 16/686,003, filed Nov. 15, 2019 Notice of Allowance dated Sep. 1, 2021. cited by applicant

U.S. Appl. No. 16/993,030, filed Aug. 13, 2020 Non-Final Office Action dated Nov. 26, 2021. cited by applicant

U.S. Appl. No. 16/993,030, filed Aug. 13, 2020 Notice of Allowance dated Jul. 22, 2022. cited by applicant

U.S. Appl. No. 16/993,035, filed Aug. 13, 2020 Final Office Action dated Jan. 18, 2022. cited by applicant

U.S. Appl. No. 16/993,035, filed Aug. 13, 2020 Final Office Action dated Nov. 7, 2022. cited by applicant

U.S. Appl. No. 16/993,035, filed Aug. 13, 2020 Non-Final Office Action dated Jun. 29, 2022. cited by applicant

U.S. Appl. No. 16/993,035, filed Aug. 13, 2020 Non-Final Office Action dated Sep. 20, 2021. cited by applicant

U.S. Appl. No. 16/993,035, filed Aug. 13, 2020 Notice of Allowance dated Mar. 7, 2023. cited by applicant

U.S. Appl. No. 17/562,270, filed Dec. 27, 2021 Non-Final Office Action dated Nov. 25, 2022. cited by applicant

U.S. Appl. No. 17/562,270, filed Dec. 27, 2021 Notice of Allowance dated May 15, 2023. cited by applicant

Primary Examiner: Johnson; Frank

Attorney, Agent or Firm: Rutan & Tucker, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/562,270 filed Dec. 27, 2021, which is a continuation of U.S. patent application Ser. No. 16/686,003 filed Nov. 15, 2019, now U.S. Pat. No. 11,207,582 issued Dec. 28, 2021, the entire contents of both are incorporated by reference herein.

FIELD

(1) Embodiments of the disclosure relate to the field of user adaptive training and entertainment platforms. More specifically, one embodiment of the disclosure relates to a system for providing a player with a plurality of soccer balls from a ball-throwing machine according to a selected program wherein a plurality of cameras obtains tracking data.

BACKGROUND

(2) In soccer, to be in control of the ball is of importance to every level of player. The ability to control an awkward bouncing ball quickly and effectively gives the player with the ball the immediate advantage. First touch is often the difference between success and failure in most situations during the match. Additionally, accuracy in passing and shooting a ball is essential in developing a well-rounded game.

(3) As players get older, the game gets faster and demands more speed. Consequently, there is a greater need for accurate shooting and passing. Often, players cannot always place a ball, either to score a goal or even to place a shot within a specific location of the goal—e.g., out of the reach of the goalie; therefore, a player may miss out on an opportunity to score a goal.

(4) Players can improve the accuracy of their shooting and passing by performing shooting and passing drills. Often, however, a player is unable to concentrate on keeping track of the location of each pass or shot within a goal or other area during drills involving several balls. Therefore, by the end of the drill, a player typically does not remember his/her accuracy and cannot determine whether he/she is improving based on results of previous drills.

(5) Additionally, although players may utilize video recording to review their training sessions or game play, a player may not understand the proper mechanics of performing certain moves or drills, and as a result, fail to learn anything from merely watching a video recording. Video recording technologies exist in which a video is captured of a ball (such as a golf ball) being hit from a static position with computer analysis performed on the player's swing. However, most sports are not limited to hitting a static ball; therefore, current technologies used to analyze a golf swing cannot be applied to analyze all aspects of other sports in which a critical component of the game is receiving a moving object.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The features disclosed herein are described below with reference to the drawings. Throughout the drawings, reference numbers are re-used to indicate correspondence between referenced elements. The drawings are provided to illustrate embodiments of the inventions described herein and not to limit the scope thereof.

(2) FIG. 1 illustrates an embodiment of a networked environment including a training and entertainment ball-throwing (TEBT) system, in accordance with some embodiments;

(3) FIG. 2 illustrates a second embodiment of the networked environment including a training and entertainment ball-throwing (TEBT) system, in accordance with some embodiments;

(4) FIG. 3 illustrates an embodiment of a plurality of interconnected, networked environments including the training and entertainment ball-throwing (TEBT) system of FIG. 2, in accordance with some embodiments;

(5) FIG. 4 is an exemplary embodiment of a logical representation of the training and entertainment

ball-throwing (TEBT) system of FIG. 1, in accordance with some embodiments;

(6) FIG. 5 is an exemplary embodiment of a first flowchart illustrating operations of the training and entertainment ball-throwing (TEBT) system of any of FIGS. 1-4, in accordance with some embodiments.

(7) FIG. 6 illustrates an exemplary embodiment of a second flowchart illustrating operations of the training and entertainment ball-throwing (TEBT) system of FIG. 1, in accordance with some embodiments;

(8) FIG. 7 illustrates an exemplary embodiment of a logical representation of a dynamic image tracking system that may be included in the training and entertainment ball-throwing (TEBT) system of FIG. 1 is shown in accordance with some embodiments; and

(9) FIGS. 8A-8B illustrate an exemplary embodiment of a first flowchart illustrating operations of dynamic image tracking system of FIG. 7 in accordance with some embodiments.

DETAILED DESCRIPTION

I. Introduction

(10) As described above, a soccer player's first touch of the ball is an important core skill to develop. A touch can be as simple as receiving a slow pass on the ground or as difficult as taking a top speed knuckling ball out of the air and straight down onto one's foot. First touch development is a continual process; youth and professionals alike perpetually train to ever improve their first touch and ball handling skills. The skill of touch is typically trained by players forming pairs and passing the ball to one another. This training method can produce results but tends to fall short in providing a disciplined approach to training that enables progress measurement and goal-oriented improvement. Further, this technique requires a player to find another individual with which to practice, which is not always practical, particularly for serious athletes who devote significant time to their training. In addition, in order to continually improve one's shooting accuracy, a goal or some form of target is required that is able to withstand repeated physical impact.

(11) Even when a player is able to find another to practice with and/or find a goal or other physical target, a player may practice by repeatedly receiving balls to be trapped, practicing performing various dribbling moves, and/or striking the ball at the goal. However, repeatedly performing the same movements in an improper form leads to the development of bad habits and may prevent the player from reaching his or her full potential. Therefore, without any instruction as to how the player is receiving a ball, passing or otherwise striking the ball, and/or performing various moves, the player may form bad habits.

(12) Additionally, some find enjoyment and entertainment value in physical activity; however, such physical activity may not involve participation in an organized and officiated league, or traditional exercise routines (lifting weights, yoga classes, etc.). Instead, the enjoyment and entertainment value may be obtained through participation in sport-centric activities that are similar to training exercises discussed above but are focused on the entertain aspect (e.g., comparing goals scored against others players in a social environment compared to analyzing a player's footwork and ball-striking motion). Various entertainment embodiments will be discussed below.

(13) This disclosure describes a networked environment that enables a player to perform programs using a specialized ball-throwing machine intended to improve a player's first touch and ball control, among other benefits and receive feedback based on recorded video of the player's performance. In one example, the networked environment may include a practice area (an open space), a ball-throwing machine, one or more targets and a plurality of cameras surrounding the practice area. The terms “program” and “training program” may be used interchangeably throughout the disclosure as embodiments of the disclosure may be either directed to social or entertainment purposes (“program”) and/or directed to athletic training purposes (“training program”). Specifically, the use of “training program” or “training” with respect to an embodiment does not exclude interchangeability of the terms.

(14) At a high level, a training program that indicates a pattern for receiving balls by the player and

a movements to be performed by the player is selected. Selection of the training program may be done by the player or a trainer via a network device such as a tablet, mobile phone, or computer. The selected training program is then relayed to at least the ball-throwing machine, which throws or otherwise ejects a series of balls, in this example soccer balls, toward the player who subsequently shoots or passes each ball at a particular target (or portion of a target) based on the selected training program. The plurality of cameras may be initiated at the time the ball-throwing machine is initiated and record video of the player and each ball.

(15) A second network device (e.g., a local computing device or a remote server device) may include logic that analyzes the video captured by the plurality of cameras to detect the movements of the player and each ball and determine the accuracy of the movements based on the selected training program. The analysis may include determinations of whether each ball was trapped properly, a particular dribble-move was accurately performed with each ball, each ball was shot or passed at the proper target accurately, etc. The results of the analysis may then be provided to the player for his/her review. The results may also be entered into a data store and combined with past analysis results to provide the player with a historical and/or cumulative view of his/her performances. In some embodiments, the analysis may be performed in real-time and result in a determination of an anticipated trajectory of each ball beyond the confines of the practice area. The anticipated trajectory may be displayed providing the player with some real-time feedback (e.g., whether the player theoretically would have scored a goal or passed to a correct virtual teammate).

(16) In some embodiments, the ball-throwing machine may be designed to throw, lob, pitch, or otherwise eject soccer balls toward a player, who can trap the balls or practice other ball control skills. Upon receipt of the ball, the player may pass, shoot or otherwise strike the ball at a goal or at another target (such as a wall). In some instances, a wall or a projector screen may serve as the target and have displayed thereon a visual illustration of a goal, a soccer field with players, etc. For example, a display device such as a projector provides a visual illustration on a wall or a projector screen based on the selected training program (e.g., of movements to be performed, statistics, and/or an image such as a goalie standing in front of a goal). As referenced above, the analysis of the movements of the player and each ball may be performed in real-time such that an anticipated trajectory of each ball is determined. The anticipated trajectory of each ball may then be displayed by the projector on the wall or projector screen.

(17) The game of soccer is commonly known in some countries as “football” or “association football.” For convenience, this specification refers solely to the term “soccer,” although such usage should be considered synonymous with “football” and “association football.” Further, embodiments of the networked environments discussed below can be used or adapted for sports other than soccer, some examples of which are described below.

II. Terminology

(18) In the following description, certain terminology is used to describe various features of the invention. For example, each of the terms “logic,” “engine,” and “component” may be representative of hardware, firmware or software that is configured to perform one or more functions. As hardware, the term logic (or component) may include circuitry having data processing and/or storage functionality. Examples of such circuitry may include, but are not limited or restricted to a hardware processor (e.g., microprocessor, one or more processor cores, a digital signal processor, a programmable gate array, a microcontroller, an application specific integrated circuit “ASIC”, etc.), a semiconductor memory, or combinatorial elements.

(19) Additionally, or in the alternative, the logic (or component) may include software such as one or more processes, one or more instances, Application Programming Interface(s) (API), subroutine(s), function(s), applet(s), servlet(s), routine(s), source code, object code, shared library/dynamic link library (dll), or even one or more instructions. This software may be stored in any type of a suitable non-transitory storage medium, or transitory storage medium (e.g., electrical, optical, acoustical or other form of propagated signals such as carrier waves, infrared signals, or

digital signals). Examples of a non-transitory storage medium may include, but are not limited or restricted to a programmable circuit; non-persistent storage such as volatile memory (e.g., any type of random access memory “RAM”); or persistent storage such as non-volatile memory (e.g., read-only memory “ROM”, power-backed RAM, flash memory, phase-change memory, etc.), a solid-state drive, hard disk drive, an optical disc drive, or a portable memory device. As firmware, the logic (or component) may be stored in persistent storage.

(20) Herein, a “communication” generally refers to related data that is received, transmitted, or exchanged within a communication session. The data may include a plurality of packets, where a “packet” broadly refers to a series of bits or bytes having a prescribed format. Alternatively, the data may include a collection of data that may take the form of an individual or a number of packets carrying related payloads, e.g., a single webpage received over a network.

(21) The term “computerized” generally represents that any corresponding operations are conducted by hardware in combination with software and/or firmware.

(22) The term “object” generally relates to content (or a reference to access such content) having a logical structure or organization that enables it to be classified for purposes of analysis for malware. The content may include an executable (e.g., an application, program, code segment, a script, dynamic link library “dll” or any file in a format that can be directly executed by a computer such as a file with an “.exe” extension, etc.), a non-executable (e.g., a storage file; any document such as a Portable Document Format “PDF” document; a word processing document such as Word® document; an electronic mail “email” message, web page, etc.), or simply a collection of related data. Additionally, the term object may refer to an instance of an executable that is executing (“a process”). In one embodiment, an object may be an image data such as one or more images and/or videos. In another embodiment, an object may be a set of instructions that are executable by one or more processors. The object may be retrieved from information in transit (e.g., one or more packets, one or more flows each being a plurality of related packets, etc.) or information at rest (e.g., data bytes from a storage medium).

(23) The term “network device” may be construed as any electronic computing system with the capability of processing data and connecting to a network. Such a network may be a public network such as the Internet or a private network such as a wireless data telecommunication network, wide area network, a type of local area network (LAN), or a combination of networks. Examples of a network device may include, but are not limited or restricted to, an endpoint (e.g., a laptop, a mobile phone, a tablet, a computer, etc.), a standalone appliance, a server, a router or other intermediary communication device, a firewall, etc.

(24) The term “rules” refers to logic used in executing certain operations, wherein execution may vary (or not occur) based on a rule. Each rule is capable of being represented as a logical expression for example, such as an “if this, then that” statement, where “this” represents a condition, and “that” represents the conclusion. The conclusion is applied when the condition is met by analysis of parameters (predetermined or dynamically obtained). The term “implicated rules,” as used herein, are the one or more specific rules applied in reaching a verdict, reflecting predetermined or dynamically obtained parameters and the conclusions drawn from them based on the logical expressions.

(25) According to one embodiment of the disclosure, rules may also provide configuration information containing parameter values such as, for example, threshold values used in detection (e.g., specifying a time a player has a ball, a velocity of a pass or shot, a number of goals, etc.). Rules may be stored in a rules store (e.g., a repository) in persistent memory of a network device and are typically updated frequently (periodically or aperiodically).

(26) Finally, the terms “or” and “and/or” as used herein are to be interpreted as inclusive or meaning any one or any combination. Therefore, “A, B or C” or “A, B and/or C” mean “any of the following: A; B; C; A and B; A and C; B and C; A, B and C.” An exception to this definition will occur only when a combination of elements, functions, steps or acts are in some way inherently

mutually exclusive.

(27) As this invention is susceptible to embodiments of many different forms, it is intended that the present disclosure is to be considered as an example of the principles of the invention and not intended to limit the invention to the specific embodiments shown and described.

III. General Architecture

(28) Referring to FIG. 1, an embodiment of a networked environment including a training and entertainment ball-throwing (TEBT) system is shown in accordance with some embodiments. Generally, the TEBT system **100** includes a networked resource **102**, a network device **104**, a playing field **106** and a plurality of camera devices **108.sub.1-108.sub.M** (wherein $M \geq 1$, and $M=2$ for this example). In some embodiments, the components shown in FIG. 1 comprising the TEBT system **100** may be referred to as an “environment,” wherein a first environment may be communicatively coupled with a second environment, as seen in FIG. 3. In addition in such embodiments, certain components as such a networked resource and/or a network device may be shared among two or more environments. As will be discussed with respect to FIG. 3, the networked resource **302** is shared between the environment **304** and the environment **320**.

(29) Referring to FIG. 1, the networked resource **102** may be, for example, a computer device or a server device that is configured to receive and store data related to the operations performed by components of the environment **100** or actions observed and/or captured by the components of the environment **100** (e.g., data being the visual data captured by the camera devices **108.sub.1-108.sub.M** of a player receiving and playing a ball toward a goal). The received data may generally be referred to herein as “metrics” or “metric data.” In addition, the networked resource **102** may include non-transitory computer-readable medium having stored thereon instructions that may be transmitted to other components within the environment **100** (or outside of the environment **100**). For example, the networked resource **102** may have stored thereon instructions to be provided to the camera devices **108.sub.1-108.sub.M** to begin recording.

(30) Additionally, the networked resource **102** may include logic configured to store the metric data in one or more player profiles. The logic may perform operations to combine data stored within a player profile with newly received metric data in order to create a historical perspective. Further, as will be discussed below, a dynamic image tracking system may be included within logic of the networked resource **102** (as seen in FIG. 7 for example). The operations performed by the dynamic image tracking system as well as additional operations that may be performed by logic of the networked resource **102** will be discussed in detail below.

(31) The network device **104** may be, for example, a mobile device or tablet that is configured to receive input from a user (e.g., a trainer). In some embodiments, the received user input may be provided to the networked resource **102** and utilized by the networked resource **102** to determine instructions to be provided to other components within the environment **100** (or external thereto). In other embodiments, the network device **104** may determine instructions to be provided to other components and either instruct the networked resource **102** as to the instructions to be provided and/or provide the instructions directly. With respect to the latter embodiment, the network device **104** may have stored thereon certain instructions to be provided to components within the environment **100**.

(32) The playing field **106** as seen in FIG. 1 is depicted as a soccer field. However, the type of playing field is not intended to be limited to a soccer field, and the sport played thereon is not intended to be limited to soccer (or otherwise referred to as football). For convenience, examples described herein use the sport “soccer”; however, embodiments of the networked environments may utilized for other sports or physical activities, including but not limited or restricted to, softball, baseball, hockey, tennis, golf, lacrosse, Frisbee, ping pong, rugby and/or basketball.

(33) With respect to the camera devices (“cameras”) **108.sub.1-108.sub.M**, the cameras **108.sub.1-108.sub.M** are configured to receive instructions, either via wired and/or wireless communications, from the networked resource **102** and/or the network device **104**. In particular, the cameras

108.sub.1-108.sub.M are positioned around and/or within the playing field **106** in order to capture multiple perspectives of one or more players (for purposes of ease, “player”) on the playing field **106**. A plurality of cameras are utilized as, at times, the movement of the player may occlude the ball and/or generally occlude moves performed by the player. As will be discussed below, the networked resource **102** may include a dynamic image tracking system that is configured to receive visual data captured by the cameras **108.sub.1-108.sub.M** and perform processing thereon to segment a ball and a human (i.e., the player), extract features to generate a list of feature descriptors and compute surface information using photoclinometry therefrom. The depiction of the cameras **108.sub.1-108.sub.M** in FIG. 1 should not be construed as the intended positioning of the cameras **108.sub.1-108.sub.M**, as the cameras **108.sub.1-108.sub.M** may be positioned at various locations around the playing field **106**, which may include the positioning illustrated in FIG. 1.

(34) Referring now to FIG. 2, a second embodiment of the networked environment including a training and entertainment ball-throwing (TEBT) system is shown in accordance with some embodiments. The environment **200** includes the networked resource **102**, a network device **104** and the cameras **108.sub.1-108.sub.M** of FIG. 1. In addition, the environment **200** includes a playing field **202** that may represent a soccer field, a portion of a soccer field or an area on which soccer may be played or practiced. The playing field **202** may include one or more goals **204.sub.1-204.sub.N** (wherein $N \geq 1$, $N=2$ for this embodiment) and a ball-throwing machine **206**.

(35) The ball-throwing machine **206** includes an outer housing and one or more exterior wheels enabling the ball-throwing machine **206** to be easily movable. Additionally, the ball-throwing machine **206** includes a hopper that stores balls to later be ejected or thrown and a ball delivery device (e.g., one or more wheels and a motor(s)) that imparts speed, spin, and/or other features of trajectory to a ball. The motor(s) are coupled to the wheels controlling the spin of each wheel. Further, one or more actuators are included in the ball-throwing machine **206** to control an angle of the ball delivery device. The ball-throwing machine may throw a plurality of balls on the playing field **202** in accordance with a program or a training program (e.g., specified sequence of instructions). The ball-throwing machine is discussed in detail in U.S. Pat. No. 9,010,309, filed Nov. 2, 2011, titled “Ball Throwing Machine and Method,” the disclosure of which is hereby incorporated herein by reference in its entirety.

(36) An “intelligent goal” (or simply “goal”) takes the concept of a traditional soccer goal and adds a plurality of sensors and, optionally, one or more lights and/or one or more speakers. In one embodiment, a goal may include two side posts and a crossbar among other supporting posts with a net coupled thereto to receive soccer balls that cross through a goal plane formed by the side posts and crossbar. The side posts and/or crossbar may each include one or more sensors that are configured to detect the presence of a soccer ball crossing the goal plane. The intelligent goal having a plurality of sensors is discussed in detail in U.S. Pat. No. 10,118,078, filed Dec. 9, 2016, titled “System, Apparatus and Method for Ball Throwing Machine and Intelligent Goal,” the disclosure of which is hereby incorporated herein by reference in its entirety.

(37) Further illustrated in FIG. 2 is a player **208** and a ball **210**. In addition, the environment **200** includes a visual display device **212**, e.g., a television screen or other display. The display device **212** may provide visual and/or audio instructions to the player **208**. The instructions may correspond to a program selected by a trainer (or the player directly) regarding how to receive one or more balls, one or more moves to be performed with each ball, how to shoot or pass each ball, at which goal to shoot or pass, etc. The display device **212** may also provide additional information such as metric data (e.g., statistics indicating the status of the player **208** for the current program and/or in the past) and/or social data (e.g., metric data pertaining to other players, such as for competition or entertainment purposes). The display device **212** may also provide visual instructions such as examples of moves to perform, e.g., videos played in real time and/or slow motion. The visual instructions may be of a simple graphic; however, the visual instructions may be a recording of an actual person, such as of a trainer, celebrity or professional athlete performing

various moves. The visual instructions may be displayed at various perspectives enabling the player **208** to obtain a complete understanding as to how to perform certain moves (e.g., where to position one's legs, etc.). The display device **212** may also provide a visual indication of a particular goal **204.sub.1-204.sub.N** at which to pass or shoot and/or a portion of the goal **204.sub.1-204.sub.N** at which to pass or shoot.

(38) Further, the display device **212** may include one or more speakers for providing audio instructions that accompany the visual displays discussed above. In addition, the speakers may provide music and/or audio cues or alerts prior to, during and/or following a program. The audio and/or visual displays may be a result of instructions and/or communications provided to the display device **212** from the networked resource **102** and/or the network device **104**. For instance, the user input received by the network device **104** may correspond to selection of a program (e.g., a first training program) that includes provision of a plurality of balls at varying speeds and elevations to the player **208** wherein the player **208** is to pass or shoot each ball at a particular goal **204.sub.1-204.sub.N**. In some embodiments, the user input or a representation or indication thereof may be provided to the network resource **102** from the network device **104**, wherein the networked resource **102** determines and transmits specific corresponding instructions and data to the display device **212**. In alternative embodiments, the network device **104** determines and transmits specific corresponding instructions and data to the display device **212**. Similarly, the networked resource **102** or the network device **104** may determine and transmit specific instructions and data to cause initiation of the ball-throwing machine **206**, the cameras **108.sub.1-108.sub.M** and/or the goals **204.sub.1-204.sub.N**, when applicable.

(39) During operations comprising performance of a first program, the cameras **108.sub.1-108.sub.M** may capture visual data of the player **208** performing the specific moves and passing/shooting as instructed by the first program. As will be discussed below, the captured visual data may be processed to analyze movements of the player **210** in order to provide feedback as to how accurately the player **210** performed specific movements or passed/shot the ball in accordance with the first program.

(40) Referring now to FIG. 3, an embodiment of a plurality of interconnected, networked environments including the TEBT system of FIG. 2 is shown in accordance with some embodiments. FIG. 3 illustrates a plurality of networked environments including the environment **200** of FIG. 2, the environment **304** and the environment **320**, each communicatively coupled to the networked resource **302**. The environment **304** includes a network device **306**, a playing field **308**, a plurality of cameras **310.sub.1-310.sub.P** (wherein $P \geq 1$, $P=3$ for this embodiment), a plurality of goals **312.sub.1-312.sub.2**, although an alternative number of goals may be included, a ball-throwing machine **314**, a display device **316** (e.g., a projector) and a visual display receiving device **318** (e.g., a projector screen). The display device **316** may cause the display of any of the displays discussed above with respect to the display device **212**, wherein the visual display is displayed on the visual display receiving device **318**.

(41) In addition, the environment **320** includes a network device **322** a playing field **324**, a plurality of cameras **326.sub.1-326.sub.3**, although an alternative number of cameras **326** may be included, a ball-throwing machine **328**, a display device **330** (e.g., a projector) and a visual display receiving device **332** (e.g., a wall). The display device **330** may cause the display of any of the displays discussed above with respect to the display device **212**, wherein the visual display is displayed on the visual display receiving device **332**. In addition to the displays discussed above with respect to the display device **212**, the display device **330** may operate with the visual display receiving device **332** to display a scene on the visual display receiving device **332**, such as one or more goals, one or more players or other depictions. In such embodiments, the depictions may take the place of the goals **204.sub.1-204.sub.N** or the goals **312.sub.1-312.sub.2** such that the player shoots or passes each ball directly at the visual display receiving device **332**. The cameras **326.sub.1-326.sub.3** capture visual data of the player receiving, handling and passing/shooting the ball. The visual data

is provided to the dynamic image tracking system which processes the data to determine an anticipated trajectory of the ball beyond the confines of the playing field **324** (e.g., the anticipated trajectory extending beyond the visual display receiving device **332**, e.g., a wall), which is then depicted by the display device **330** on the visual display receiving device **332**.

(42) In at least the environment **320**, the player may receive instruction pertaining to a selected program on the visual display receiving device **332**, receive a ball from the ball-throwing machine **328**, and pass or shoot the ball directly at the visual display receiving device **332** with the cameras **326.sub.1-326.sub.3** capturing visual data thereof. The visual data is then processed by the dynamic image tracking system to determine (i) accuracy of the player's movements and ball striking, and (ii) anticipated trajectory of the ball. The anticipated trajectory of the ball is then provided to the display device **330**, which causes its display on the visual display receiving device **332**.

Additionally, the anticipated trajectory of the ball may result in display of predetermined visuals (e.g., crowd celebrations, player movement, additional instructions, a visual summary of the player's movements and ball striking, etc.).

(43) As referenced above, the embodiments discussed herein may be used for both athletic training purposes (e.g., to improve one's first touch of a soccer ball) as well as for entertainment purposes within a social environment. As one example of the former, the environments of FIG. **3** may represent practice areas within one or more training facilities in which video of each ball thrown to a player and the player's subsequent movements during a training session is recorded by the plurality of cameras. The video may be then analyzed to determine not only the accuracy at which the player performed a training program within the training session but also the form and speed of the player's movements. Thus, FIG. **3** may be implemented to present a plurality of environments directed to an athletic training purpose.

(44) However, in some embodiments, one or more of the environments of FIG. **3** may be implemented to provide users with a social environment revolving around soccer. For instance, one or more of the environments may enable selection of various video games to be display on the corresponding display device or display receiving device (e.g., where the display receiving device displays a meteor field and the player is to shoot soccer balls at meteors). Additionally, multi-player games may be provided (wherein the players may take turns in the same environment, or may be located remotely in separate environments, potentially hundreds or thousands of miles apart). There is no limit on the type or number of programs that may be provided (as either training-focused programs or social-oriented programs).

IV. Logical Representation

(45) Referring now to FIG. **4**, an exemplary embodiment of a logical representation the training and entertainment ball-throwing (TEBT) system of FIG. **1** is shown in accordance with some embodiments. The network device **400**, in an embodiment, may include a housing, which may be made entirely or partially of a hardened material (e.g., hardened plastic, metal, glass, composite or any combination thereof) that protects the circuitry within the housing, namely one or more processors **402** that are coupled to a communication interface **404** via a first transmission medium. The communication interface **404**, in combination with a communication logic **408**, enables communications with external network devices to receive communications as well as updates for the TEBT system **410**. According to one embodiment of the disclosure, the communication interface **404** may be implemented as a physical interface including one or more ports for wired connectors. Additionally, or in the alternative, the communication interface **404** may be implemented with one or more radio units for supporting wireless communications with other electronic devices. The communication interface logic **408** may include logic for performing operations of receiving and transmitting one or more objects via the communication interface **404** to enable communication between the TEBT system **410** and network devices via a network (e.g., the internet) and/or cloud computing services, not shown.

(46) The processor(s) **402** is further coupled to a persistent storage **406** (e.g., non-transitory,

computer-readable medium) via a second transmission medium. According to one embodiment of the disclosure, the persistent storage **406** may have stored thereon the TEBT system **410**, which may include the following logic modules: a program selection receiving logic **412**, an instruction generation logic **414**, a metrics receiving logic **416**, a player profile logic **418**, and a graphical user interface (GUI) generation logic **420**. The operations of these software modules, upon execution by the processor(s) **402**, are described above. Of course, it is contemplated that some or all of this logic may be implemented as hardware, and if so, such logic could be implemented separately from each other.

(47) Referring to FIG. 5, an exemplary embodiment of a first flowchart illustrating operations of the training and entertainment ball-throwing (TEBT) system of any of FIGS. 1-4 is shown in accordance with some embodiments. Each block illustrated in FIG. 5 represents an operation performed in the method **500** performed by a TEBT system, such as any of the TEBT systems **100**, **200**, **320** and/or **410**. It should be understood that not every operation illustrated in FIG. 5 is required. In fact, the transmission of certain sets of instructions may be optional to complete aspects of the method **500**. The discussion of the operations of method **500** may be done so with reference to any of FIGS. 1-4.

(48) Herein, the method **500** starts when data pertaining to a selection of a first training program is received (block **502**). The first training program may refer to a predetermined (although optionally dynamically adjustable) program that corresponds to instructions for display of visual data, playing of audio data, and/or initiation of a sequence performed by a ball-throwing machine. For example, the first training program may be directed to training or entertainment purposes. Following the receipt of the data pertaining to the selection of the first training program, the method **500** includes transmitting instructions to cause the activation of a media player configured to display visual data corresponding to the first training program (block **504**). The term “media player” may refer to any of the display device **212** (e.g., a television or other network device having or connected to a display screen) and/or the projectors **316** and **330**.

(49) Transmission of the instructions may include media data of the first training program from the network device **104**, **306** or **322** to the media player (directly or via the network resource **102** or **302**). Alternatively, the instructions transmitted may include an indication of media data to display, wherein the media data is stored on the media player, or is at least accessible by the media player, e.g., stored on a remote, non-transitory computer-readable medium. The indication of the media data may include a name of the media data file to be displayed or other unique identifier.

(50) Optionally, following the transmission of instructions causing activation of a media player, the method **500** may include the receipt of verification data that verifies the display of the visual data corresponding to the selected first training program (block **506**). Transmission of verification data from the media player to the sending network device or network resource is an optional feature.

(51) In addition to the transmission of instructions to cause display of visual data, the method **500** includes transmitting instructions to cause the activation of a ball-throwing machine configured to impart motion to one or more balls in accordance with the selected first training program (block **508**). Transmission of the instructions may include a ball-throwing sequence of the first training program from the network device **104**, **306** or **322** to the ball-throwing machine **206**, **314** or **328** (directly or via the network resource **102** or **302**). Alternatively, the instructions transmitted may include an indication of ball-throwing sequence to be performed, wherein the ball-throwing sequence is stored on the ball-throwing machine **206**, **314** or **328**, or is at least accessible by the ball-throwing machine **206**, **314** or **328**, e.g., stored on a remote, non-transitory computer-readable medium. The indication of the ball-throwing sequence may include a name of a file to be executed or other unique identifier.

(52) Following the transmission of instructions causing activation of the ball-throwing machine, the method **500** may include the receipt and recordation of data indicating metrics associated with performance of the selected first training program (block **510**). The recorded data may include any

parameters or statistics associated with the first training program including, but not limited or restricted to, a ball count, a recording of how each ball was thrown (speed, direction, angle, loft, etc.), number of goals scored in accordance with the first training program (e.g., accurate goal received the corresponding ball), location of scored goal (e.g., upper, middle, bottom of goal), various timestamps (start/stop of first training program, for each ball thrown, for each goal, etc.), a recording of any dynamic alterations made to the first training program (e.g., based user input from a trainer/player, based on data from sensors such as cameras, wearables such as a heart rate monitor, etc.) wherein an alteration may include any change to the first training program such as a number of balls throwing, how each ball is thrown, the interval between balls, etc.). The recorded data may be obtained from any source (based applicability) including manual user input, recorded and analyzed video content, obtained sensor data (from wearables and/or sensors within an intelligent goal).

(53) Finally, following the transmission of instructions causing activation of the ball-throwing machine, the method **500** includes recording an indication of at least partial performance of the selected first training program in a user profile corresponding to the user receiving the one or more balls (block **512**). Any of the recorded data discussed with respect to block **510** may be incorporated into a player profile. The incorporation may include: (i) combining the recorded data with previously stored data so as to develop a cumulative history of a player's training, and/or (ii) individual recordation to enable retrieval of data pertaining to one or more training sessions. The player profile may be stored in cloud storage and retrievable via any network device (e.g., by providing authentication credentials).

(54) Referring to FIG. **6**, an exemplary embodiment of a second flowchart illustrating operations of the training and entertainment ball-throwing (TEBT) system of FIG. **1** is shown in accordance with some embodiments. Each block illustrated in FIG. **6** represents an operation performed in the method **600** performed by a TEBT system, such as any of the TEBT systems **100**, **200**, **320** and/or **410**. Herein, the method **600** starts when data indicating performance of a first program is received (block **602**). As discussed above with respect to FIG. **5**, the first program may refer to a predetermined (although optionally dynamically adjustable) program, which may be, for example, a training program or an entertainment program. In the embodiment illustrated in FIG. **6**, the first program corresponds to at least a first set of instructions that are executable by a ball-throwing machine.

(55) Following receipt of the data indicating performance of a first program, the received data is recorded in a user profile corresponding to a first user, i.e., the user receiving one or more balls thrown by the ball-throwing machine (block **604**). Upon the addition of the received data to the user profile, the received data is correlated with previously stored data within the user profile corresponding to additional programs previously completed, or partially completed, by the first user to produce updated user statistics (block **606**).

(56) Following the generation of the updated user statistics, instructions that cause the rendering of a GUI are generated (block **608**). In some specific embodiments, the GUI may display at least an identification of the user and the updated user statistics. Additionally, as an optional feature, the GUI may display a social networking aspect that includes profile information of additional users, and/or a ranking display that illustrates a comparison of a plurality of users, optionally including the first user.

(57) In one embodiment, following the generation of the instructions to cause the rendering of a GUI, the instructions are transmitted to a network device for the rendering of the GUI on a display screen of the network device (block **610**). For example, the network device may be a user's mobile device or tablet. Optionally, the GUI may be rendered on a display screen (block **612**). More specifically in such an embodiment, the GUI may be rendered on a display screen of a local computing device (e.g., a laptop or desktop computer) that either includes or is coupled to a display screen, wherein the local computing device may perform one or more of the operations discussed

with respect to blocks **602-610**.

V. Dynamic Image Tracking System Logical Representation

(58) Referring now to FIG. 7, an exemplary embodiment of a logical representation of a dynamic image tracking system that may be included in the TEBT system of FIG. 1 is shown in accordance with some embodiments. The network device **700**, in an embodiment, may include a housing, which may be made entirely or partially of a hardened material (e.g., hardened plastic, metal, glass, composite or any combination thereof) that protects the circuitry within the housing, namely one or more processors **702** that are coupled to a communication interface **704** via a first transmission medium. The communication interface **704**, in combination with a communication logic **708**, enables communications with external network devices to receive communications as well as updates for the dynamic image tracking system **710**. According to one embodiment of the disclosure, the communication interface **704** may be implemented as a physical interface including one or more ports for wired connectors. Additionally, or in the alternative, the communication interface **704** may be implemented with one or more radio units for supporting wireless communications with other electronic devices. The communication interface logic **708** may include logic for performing operations of receiving and transmitting one or more objects via the communication interface **704** to enable communication between the dynamic image tracking system **710** and network devices via a network (e.g., the internet) and/or cloud computing services, not shown.

(59) The processor(s) **702** is further coupled to a persistent storage **706** (e.g., non-transitory, computer-readable medium) via a second transmission medium. According to one embodiment of the disclosure, the persistent storage **706** may have stored thereon the dynamic image tracking system **710**, which may include the following logic modules: an image acquisition logic **712**, an image segmentation logic **714**, an object recognition and classification logic **716**, a distance computation logic **718**, a three-dimensional (3D) topography generation logic **720** and an outlier rejection logic **724**. The TEBT system **410** may include, or have access to, an image data store **722** that may store data (still images and/or video). Various logic modules of the TEBT system **410** may query the image data store **722** to retrieve or otherwise manipulate data stored therein. Recording of various data extracted or determined with respect to the images or video stored on the image data store **724** is discussed below and such recordings may be stored in the image data store **724**. The operations of these software modules, upon execution by the processor(s) **702**, are described below with respect to various example embodiments. Of course, it is contemplated that some or all of this logic may be implemented as hardware, and if so, such logic could be implemented separately from each other.

VI. Dynamic Image Tracking System Exemplary Methodology

(60) Referring now to FIGS. **8A-8B**, an exemplary embodiment of a first flowchart illustrating operations of dynamic image tracking system of FIG. 7 is shown in accordance with some embodiments. Each block illustrated in FIGS. **8A-8B** represents an operation performed in the method **800** of performing dynamic image tracking. Herein, the method **800** starts when data is acquired from a plurality of cameras, e.g., the cameras **108.sub.1-108.sub.M** of FIG. 1 (block **802**). In particular, the data may comprise a series of still images or video data. When the data comprises video data, the dynamic image tracking system may extract individual frames from the video data, wherein each frame represents a still image. Following the acquisition of data from the plurality of cameras, the method may perform operations comprising two separate paths, starting with blocks **804** and **814** respectively, as seen in FIG. **8A**. In some embodiments, the two paths may be performed in parallel. However, in other embodiments, the two paths may be performed serially or concurrently (at least overlapping in time).

(61) Although the paths may be performed in either order, the path starting block **804** will be discussed first. Referring to a first path, with the dynamic image tracking system attempts to segment the ball in each of the images (block **804**). The segmentation of the ball or balls may be

made up of various embodiments or a combination of embodiments depending on the modulus operand. In one embodiment the segmentation process may be a rule-based system that differentiates the ball or balls from the background using a color space thresholding, contrast thresholding, illumination thresholding or any other such expert method that is fine-tuned accordingly to create a binary image. The rules may be generated based on experiential knowledge. Other rule-based systems have been contemplated and are within the scope of the disclosure. The size, location and any other relevant features of each separate or disjointed object within each image is then recorded.

(62) In another embodiment, the ball segmentation process may be based on shape recognition. In such an embodiment, logic of the dynamic image tracking system analyzes each image for circular objects within the each images and records certain data, including but not limited or restrict to, a size, a location and any other relevant features of these circular objects.

(63) In yet another embodiment, the ball segmentation process may involve a background subtraction method (also referred to as “foreground detection”). Such a method includes generating an “understanding” of the background utilizing multiple previous images or a duration of video made up of multiple frames, to create a background image. For example, a template background image may be generated by comparing pixels from a plurality of previous images such that a determination is made as to whether each pixel is represented by a common value across the plurality of images (e.g., indicating that the pixel corresponds to a still region, e.g., non-moving object). The template, e.g., the understanding, may be considered to be the background image. The image being processed is subsequently subtracted from the background image with the resultant output being a binary image of what is not considered background. In essence, this method detects objects that have either changed position in respect to the background or were introduced into the image. This method is also known as motion detection. Similarly, to other embodiments, a size, a location and any other relevant features of each object may then be recorded.

(64) In yet another embodiment a machine learning or artificial intelligence method may be employed. Such a method may utilize a pre-trained object classifier, such as but not limited to, the You-Only-Look-Once (YOLO) library or any other machine learning or artificial intelligence method configured to classify and/or recognize an object, such as a ball, within an image. If a non-pre-trained artificial intelligence logic module is used, a dataset of images containing balls is first collected and annotated for training of the artificial intelligence logic module. Additionally, a dataset of other objects that may be found in the images may be collected and annotated for additional training. Most of the datasets are subsequently used to train the machine learning classifier while the remainder are used to test and validate the resultant classifier. Similar to other embodiments, the size, location and any other relevant features of each object is recorded.

(65) In any of the embodiments discussed above, an outlier rejection logic **724** may be included in and employed by the dynamic image tracking system to refine the selection of the intended object (e.g., a ball) based on the recorded features. The outlier rejection logic **724** may perform operations including a semantic classification based on the recorded features described above. A first set of features of the recorded features (determined via experiential knowledge) are selected based on higher level thematic descriptors such as Hu invariant moments. The semantic classification may include computerized operations that determine a set of feature descriptor values that define the object. For example, a soccer ball may have: a roundness feature descriptor value of approximately 1; a “perimeter over area” feature descriptor value of approximately $2r/r_{sup}^2$ (wherein ‘r’ refers to the radius of the object); a bounding box ratio feature descriptor value of approximately 1:1; and a skewness feature descriptor value of approximately 0. The values that define certain objects, such as a soccer ball, may be determined via experiential knowledge and/or machine learning.

(66) The process of selecting the first set of features includes selection of features in accordance with experiential knowledge and based on variation and distribution of the feature descriptors to determine the median and upper/lower thresholds thereof for a particular installation. Factors

considered for a particular installation include the size of the studio, the positioning of the cameras, the lenses used, and camera parameters. In some embodiments, the selection process may be via machine learning algorithms. In other embodiments, one or more predetermined rule sets may be utilized to select a set of features. In other embodiments, manual selection may be utilized. In yet further embodiments, a combination of machine learning techniques, predetermined rule sets and/or manual selection may be utilized.

(67) In some embodiments, the thematic descriptors are made up of 7 values. The thematic descriptor values may be compared to the feature descriptor values and thresholds discussed above. If the thematic descriptor values are outside a corresponding threshold then the feature under analysis is determined to not be a representation of the desired object. Following analysis, these thematic descriptors are compared to a template representing the first features that represent a ball. Following the comparison, each detected object is presented in a list that is ordered by a closest match to the template. In addition, the outlier rejection logic 724 operations may include performance of RANSAC, K-Means Clustering, K-Nearest Neighbor, etc.

(68) Following segmentation of the ball in each of the images, the dynamic image tracking system makes a determination with respect to each image as to whether a ball was detected (block 806). The determination may involve a thresholding of the template matching process (e.g., the background subtraction process) discussed above, a voting process of the most closely matched features or any other relevant method that determines whether the selected feature or features represent a ball. In one embodiment, the voting process in determining the “most closely matched features” includes operations of determining the set of features having the lowest standard deviation from the template discussed above.

(69) When a ball is not detected in an image, the image is rejected, e.g., no longer in consideration with respect to the first path (block 808). However, when a ball is determined to be present within an image, the dynamic image tracking system creates a mask of the ball (block 810). The mask is made up of, for example, zeros, “Not a Number” (NaN) values or any other identifier that indicates one or more pixels (which may be referred to as a “region”) is not a Region of Interest (RoI) on the areas that do not contain the detected ball. In contrast, the regions determined to contain a ball are filled with each pixel's original pixel value.

(70) Following the creation of the mask of the ball, features are extracted for each image in which a ball is detected (block 812). In performing the feature extraction, various feature extraction algorithms may be utilized including Speeded-Up Robust Features (SURF), Harris Corner Detector and Scale-Invariant Feature Transform (SIFT); however, other feature extraction algorithms have been contemplated and are within the scope of the disclosure. In some embodiments, the features are only extracted for the RoI, which results in a lower computational cost and, hence, improved performance of the method 800.

(71) Following the creation of the mask of the ball and the performance of feature extraction operations, the feature descriptors are listed and surface information is computed using photogrammetry (block 814). In some embodiments, operations comprising a photogrammetry process are performed that transform a 2D image into a surface map representing varying depth within the 2D image. The operations further recreate a 3D relief of the ball from one or more images. From the 3D relief, detailed pixel-based features are extracted. In some embodiments, the detailed pixel-based features may be derived from Harris Corners as determined by any of the SIFT, Harris Corner Detector and/or SURF operations; however, the photogrammetry processing results in the addition of a 3rd dimension to the Harris Corners to generate the detailed pixel-based features. Therefore, the detailed pixel-based features may be analyzed in 3D space (3×2D rotations). 3×2D rotation may refer to the roll (rotation around a front-to-back axis), pitch (rotation around a side-to-side axis) and yaw (rotation around a vertical axis); however, the rotations are typically concurrent, not serial and, thus, refer to a rigid body.

(72) Determining the 3D structure of the ball will lead to a more accurate approximation of a

Euclidean distance discussed below. In addition, the photoclino-metry process also enables additional information to be extracted such as but not limited to, ball spin and forces acting on the ball based on changes in pixel values extracted from the RoI within a group images (e.g., within a specific time frame).

(73) Referring to a second path beginning with block **816**, the dynamic image tracking system attempts to segment one or more users in each of the images (block **816**). Although a plurality of users (or “players”) may utilize a single environment concurrently, the method **800** will use the phrase “user” for the sake of clarity and convenience; however, the disclosure is not intended to be limited to a single user and instead applies equally to a plurality of concurrent users as the same process applies for a first user as for a second user. The segmentation strategies utilized in the second path are similar to those of the first path, however, the machine learning method as described may provide more accurate results due to the variation in the appearance of a user.

However, other feature extraction processes have been contemplated and are within the scope of the disclosure. The resultant of block **816** is a list containing bounding box information that indicates the position of the user. The bounding box information may include an Axis-aligned minimum bounding box for the user, which may be defined as the user's minimum bounding box subject to the constraint that the edges of the box are parallel to the (Cartesian) coordinate axes.

(74) Following segmentation of the user in each of the images, the dynamic image tracking system makes a determination with respect to each image as to whether a user was detected (block **818**). The system utilizes the output of the previous block (block **816**) as a logical truth table to determine if the image contains a user. In some embodiments, the logical truth table refers to whether a bounding box representation may be found within the list containing the bounding box information for the image. When a bounding box is available, then the image and information is used.

(75) When a user is not detected in an image, the image is rejected. e.g., no longer in consideration with respect to the second path (block **808**). However, when a user is determined to be present in an image, the dynamic image tracking system creates a mask of the user in a similar manner as discussed with respect to block **810** (block **820**). For each masked image, detailed pixel-based features are extracted in a similar manner as discussed with respect to block **812** (block **822**).

(76) Following the creation of the mask of the user and the performance of feature extraction operations, the feature descriptors are listed and surface information is computed using photoclino-metry (block **824**). In a similar manner as discussed above with respect to block **814**, operations comprising a photoclino-metry process transform a 2D image into a surface map representing varying depth within the 2D image. Further, the options recreate a 3D relief of the user from one or more images. From the 3D relief, detailed pixel-based features are extracted. Determining the 3D structure of the user will lead to a more accurate approximation of a Euclidean distance discussed below.

(77) Referring now to FIG. **8B**, subsequent to the completion of the computation of the surface information with respect to both the ball and the user, the method **800** continues with the computation of the Euclidean distance between the ball and the user (block **826**). The features contain three-dimensional information enabling the relationship (e.g., a “straight line distance”) between the ball and the user to be extrapolated in the form of three distances made up of a maxima value, a minima value, and a mean value. The three distances may include: the maxima (the largest Euclidean distance between the edges of the two objects); the minima (the smallest Euclidean distance between the edges of the two objects); and the mean (the Euclidean distance between the centroids of the two objects).

(78) Once the Euclidean distance has been determined for each image, the image that maximizes the Euclidean distance between the ball and the user is identified (block **828**).

(79) In determining the image that maximizes the Euclidean distance, the images are ranked against each other. In some embodiments, the minima is considered first, such that when a first image has a

larger minima value than a second image, the first image is placed above the second image in a ranking (e.g., a list). Such a comparison is performed between each image.

(80) When two images have similar minima values, then the mean is considered when comparing the two images (e.g., the image with the larger mean is ranked above the other). The term “similar” may be within a predefined threshold of each other. Further, when both the minima and mean are similar (according to corresponding minima and mean thresholds), the maxima is considered (e.g., the image with the larger maxima is ranked above the other). Should all three values be the same or similar based on the corresponding thresholds, then the image timestamp (in nano seconds) is considered, wherein preference for ordering based on timestamps (e.g., earlier or later) may be provided as a default setting or extracted from a configuration file.

(81) Using the image that maximizes the Euclidean distance between the ball and the user is identified, a three-dimensional (3D) topography is computed based on the image (block **830**). This utilizes triangulation techniques to determine the position of the ball and user in three-dimensional space; thus, in some embodiments, the topography of the entire image is not computed resulting in lower computational cost and improved performance. In addition, should more than two images selected for the image pair utilized in block **830** be determined to include the ball and/or the user, these additional images may be used as a validation of the triangulation computation.

(82) While the above detailed description has shown, described, and pointed out novel features as applied to various embodiments, it will be understood that various omissions, substitutions, and changes in the form and details of the devices or algorithms illustrated can be made without departing from the spirit of the disclosure. As will be recognized, certain embodiments of the inventions described herein can be embodied within a form that does not provide all of the features and benefits set forth herein, as some features can be used or practiced separately from others.

Claims

1. A computerized method comprising: acquiring data from a plurality of cameras surrounding a training environment, the data including a plurality of images; attempting to segment a ball and a human in each of the plurality of images, wherein responsive to failing to segment either the ball or the human in a first image, rejecting the first image from further processing; creating a mask of the ball and a mask of the human; extracting features for both the ball and the human in each of the plurality of images that were not rejected from further processing; computing surface information of the training environment using a photoclinometry process; for each of the plurality of images that were not rejected from further processing, computing a distance between the ball and the human; identifying an image of the plurality of images having a greatest distance between the ball and the human; and computing a three-dimensional topography from the identified image.
2. The computerized method of claim 1, wherein the distance between the ball and the human is a Euclidean distance.
3. The computerized method of claim 1, wherein the photoclinometry process includes operations that transform a two-dimensional (2D) image into a surface map representing varying depth within the 2D image.
4. The computerized method of claim 1, wherein the data acquired from the plurality of cameras includes images or videos that capture the ball, wherein a ball-throwing machine has imparted motion to the ball.
5. The computerized method of claim 1, wherein computing the three-dimensional topography from the identified image includes utilization of a triangulation technique to determine a position of the ball and a position of the human in three-dimensional space.
6. The computerized method of claim 1, wherein extracting the features for both the ball and the human in each of the plurality of images that were not rejected from further processing includes: recreating a three-dimensional relief of the user and of the ball, and extracting pixel-based features

of the ball and of the human from the three-dimensional relief, wherein the pixel-based features extracted from the three-dimensional relief are used in determining the greatest distance between the ball and the human.

7. The computerized method of claim 1, further comprising: determining an image to be displayed to the human based on the three-dimensional topography computed from the identified image.

8. A computing device, comprising: one or more processors; and a non-transitory computer-readable medium having stored thereon instructions that, when executed by the processor, cause the processor to perform operations including: acquiring data from a plurality of cameras surrounding a training environment, the data including a plurality of images, attempting to segment a ball and a human in each of the plurality of images, wherein responsive to failing to segment either the ball or the human in a first image, rejecting the first image from further processing, creating a mask of the ball and a mask of the human, extracting features for both the ball and the human in each of the plurality of images that were not rejected from further processing, computing surface information of the training environment using a photoclinometry process, for each of the plurality of images that were not rejected from further processing, computing a distance between the ball and the human, identifying an image of the plurality of images having a greatest distance between the ball and the human, and computing a three-dimensional topography from the identified image.

9. The computing device of claim 8, wherein the distance between the ball and the human is a Euclidean distance.

10. The computing device of claim 8, wherein the photoclinometry process includes operations that transform a two-dimensional (2D) image into a surface map representing varying depth within the 2D image.

11. The computing device of claim 8, wherein the data acquired from the plurality of cameras includes images or videos that capture the ball, wherein a ball-throwing machine has imparted motion to the ball.

12. The computing device of claim 8, wherein computing the three-dimensional topography from the identified image includes utilization of a triangulation technique to determine a position of the ball and a position of the human in three-dimensional space.

13. The computing device of claim 8, wherein extracting the features for both the ball and the human in each of the plurality of images that were not rejected from further processing includes: recreating a three-dimensional relief of the user and of the ball, and extracting pixel-based features of the ball and of the human from the three-dimensional relief, wherein the pixel-based features extracted from the three-dimensional relief are used in determining the greatest distance between the ball and the human.

14. The computing device of claim 8, further comprising: determining an image to be displayed to the human based on the three-dimensional topography computed from the identified image.

15. A non-transitory storage medium having stored thereon instructions that, when executed, cause performance of operations including: acquiring data from a plurality of cameras surrounding a training environment, the data including a plurality of images, attempting to segment a ball and a human in each of the plurality of images, wherein responsive to failing to segment either the ball or the human in a first image, rejecting the first image from further processing, creating a mask of the ball and a mask of the human, extracting features for both the ball and the human in each of the plurality of images that were not rejected from further processing, computing surface information of the training environment using a photoclinometry process, for each of the plurality of images that were not rejected from further processing, computing a distance between the ball and the human, identifying an image of the plurality of images having a greatest distance between the ball and the human, and computing a three-dimensional topography from the identified image.

16. The non-transitory storage medium of claim 15, wherein the distance between the ball and the human is a Euclidean distance.

17. The non-transitory storage medium of claim 15, wherein the photoclinometry process includes

operations that transform a two-dimensional (2D) image into a surface map representing varying depth within the 2D image.

18. The non-transitory storage medium of claim 15, wherein the data acquired from the plurality of cameras includes images or videos that capture the ball, wherein a ball-throwing machine has imparted motion to the ball.

19. The non-transitory storage medium of claim 15, wherein computing the three-dimensional topography from the identified image includes utilization of a triangulation technique to determine a position of the ball and a position of the human in three-dimensional space.

20. The non-transitory storage medium of claim 15, wherein extracting the features for both the ball and the human in each of the plurality of images that were not rejected from further processing includes: recreating a three-dimensional relief of the user and of the ball, and extracting pixel-based features of the ball and of the human from the three-dimensional relief, wherein the pixel-based features extracted from the three-dimensional relief are used in determining the greatest distance between the ball and the human.
