

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12386417
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Woods; Michael

---

### Systems and methods for augmented reality

---

#### Abstract

Configurations are disclosed for presenting virtual reality and augmented reality experiences to users. An augmented reality display system comprises a handheld component housing an electromagnetic field emitter, the electromagnetic field emitter emitting a known magnetic field, the head mounted component coupled to one or more electromagnetic sensors that detect the magnetic field emitted by the electromagnetic field emitter housed in the handheld component, wherein a head pose is known, and a controller communicatively coupled to the handheld component and the head mounted component, the controller receiving magnetic field data from the handheld component, and receiving sensor data from the head mounted component, wherein the controller determining a hand pose based at least in part on the received magnetic field data and the received sensor data.

---

<b>Inventors:</b>	<b>Woods; Michael (Mountain View, CA)</b>
<b>Applicant:</b>	<b>MAGIC LEAP, INC. (Plantation, FL)</b>
<b>Family ID:</b>	<b>56848278</b>
<b>Assignee:</b>	<b>Magic Leap, Inc. (Plantation, FL)</b>
<b>Appl. No.:</b>	<b>18/168797</b>
<b>Filed:</b>	<b>February 14, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230195216 A1	Jun. 22, 2023

#### Related U.S. Application Data

continuation parent-doc US 17813442 20220719 US 11619988 child-doc US 18168797  
continuation parent-doc US 17137107 20201229 US 11429183 20220830 child-doc US 17813442  
continuation parent-doc US 15062104 20160305 ABANDONED child-doc US 17137107

Publication Classification

Int. Cl.: G06F3/01 (20060101); G01S19/42 (20100101); G06F3/03 (20060101); G06F3/0346 (20130101); G06T19/00 (20110101); G02B27/01 (20060101)

U.S. Cl.:

CPC G06F3/012 (20130101); G01S19/42 (20130101); G06F3/017 (20130101); G06F3/0304 (20130101); G06F3/0346 (20130101); G06T19/006 (20130101); G02B27/017 (20130101); G02B2027/0187 (20130101)

Field of Classification Search

CPC: G06F (3/011); G06F (3/012); G06F (3/04815); G06F (3/0346); G06T (19/006); G06T (7/70); G06T (7/10); G06T (2207/10004); G06T (2207/10028); G06T (2207/20221); G02B (27/017); G02B (2027/0112); G02B (2027/0125); G02B (2027/0127); G02B (2027/0132); G02B (2027/0138); G02B (2027/014); G02B (2027/0187); G01B (7/004); G01S (17/08); G01S (13/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4462165	12/1983	Lewis	N/A	N/A
5280265	12/1993	Kramer et al.	N/A	N/A
5583974	12/1995	Winner et al.	N/A	N/A
5592401	12/1996	Kramer	N/A	N/A
5684498	12/1996	Welch et al.	N/A	N/A
5784115	12/1997	Bozdagi	N/A	N/A
5844530	12/1997	Tosaki	N/A	N/A
5930741	12/1998	Kramer	N/A	N/A
6064749	12/1999	Hirota	382/103	G06V 10/245
6377401	12/2001	Bartlett	N/A	N/A
6407736	12/2001	Regan	N/A	N/A
6590536	12/2002	Walton	342/463	G01S 3/146
6701296	12/2003	Kramer et al.	N/A	N/A
6891533	12/2004	Alcorn et al.	N/A	N/A
7375529	12/2007	Dupuis et al.	N/A	N/A
7443154	12/2007	Merewether et al.	N/A	N/A
7542869	12/2008	Gandelsman	702/152	G01D 5/22
8165352	12/2011	Mohanty et al.	N/A	N/A
8401308	12/2012	Nakamura et al.	N/A	N/A
8446426	12/2012	Gonion	N/A	N/A

8950867	12/2014	Macnamara	N/A	N/A
8989775	12/2014	Shaw	N/A	N/A
9013505	12/2014	Thorton	N/A	N/A
9160727	12/2014	Saylor et al.	N/A	N/A
9215293	12/2014	Miller	N/A	N/A
9417452	12/2015	Schowengerdt et al.	N/A	N/A
9465129	12/2015	Olsson et al.	N/A	N/A
9639935	12/2016	Douady-Plevin et al.	N/A	N/A
9671566	12/2016	Abovitz et al.	N/A	N/A
9791700	12/2016	Schowengerdt	N/A	N/A
9814430	12/2016	Berme et al.	N/A	N/A
9874749	12/2017	Bradski et al.	N/A	N/A
9952673	12/2017	Kramer et al.	N/A	N/A
10130429	12/2017	Weir	N/A	N/A
10338677	12/2018	Guenter	N/A	N/A
10481689	12/2018	Jeromin	N/A	N/A
10721280	12/2019	Heppner et al.	N/A	N/A
10843067	12/2019	Peuhkurinen et al.	N/A	N/A
10942252	12/2020	Chen et al.	N/A	N/A
10964119	12/2020	Nourai et al.	N/A	N/A
11176901	12/2020	Hunt et al.	N/A	N/A
11315214	12/2021	Liebenow et al.	N/A	N/A
2001/0043738	12/2000	Sawney et al.	N/A	N/A
2002/0033803	12/2001	Holzrichter et al.	N/A	N/A
2002/0113756	12/2001	Tuceryan	348/E13.052	G02B 27/017
2002/0180727	12/2001	Guckenberger et al.	N/A	N/A
2003/0052965	12/2002	Junkins et al.	N/A	N/A
2003/0092448	12/2002	Forstrom et al.	N/A	N/A
2003/0120448	12/2002	Moriya et al.	N/A	N/A
2003/0227470	12/2002	Genc	345/633	G06F 3/017
2003/0234823	12/2002	Sato et al.	N/A	N/A
2004/0140949	12/2003	Takagi	N/A	N/A
2004/0174337	12/2003	Kubota et al.	N/A	N/A
2004/0201857	12/2003	Foxlin	N/A	N/A
2005/0107870	12/2004	Wang et al.	N/A	N/A
2005/0156601	12/2004	Dupuis et al.	N/A	N/A
2006/0161871	12/2005	Hotelling et al.	N/A	N/A
2006/0253804	12/2005	Fukushima et al.	N/A	N/A
2007/0049374	12/2006	Ikeda et al.	N/A	N/A
2007/0072674	12/2006	Ohta et al.	N/A	N/A
2007/0126733	12/2006	Yang et al.	N/A	N/A
2007/0273644	12/2006	Mondine Natucci	N/A	N/A
2007/0298883	12/2006	Feldman et al.	N/A	N/A
2008/0024523	12/2007	Tomite et al.	N/A	N/A
2008/0133521	12/2007	Podilchuk	N/A	N/A
2008/0275667	12/2007	Ohta	N/A	N/A
2008/0309884	12/2007	O'Dor et al.	N/A	N/A
2009/0005166	12/2008	Sato	N/A	N/A

2009/0051653	12/2008	Barney et al.	N/A	N/A
2009/0115406	12/2008	Anderson et al.	N/A	N/A
2009/0173886	12/2008	Chowdhury	N/A	N/A
2009/0184825	12/2008	Anderson	N/A	N/A
2010/0066676	12/2009	Kramer et al.	N/A	N/A
2010/0085423	12/2009	Lange	N/A	N/A
2010/0103205	12/2009	Lisaka et al.	N/A	N/A
2010/0141261	12/2009	Overby et al.	N/A	N/A
2010/0277476	12/2009	Johansson et al.	N/A	N/A
2010/0302152	12/2009	Kirigaya	N/A	N/A
2010/0309292	12/2009	Ho et al.	N/A	N/A
2011/0018874	12/2010	Hasselgreen et al.	N/A	N/A
2011/0025603	12/2010	Underkoffler et al.	N/A	N/A
2011/0184950	12/2010	Skaiff et al.	N/A	N/A
2011/0199088	12/2010	Bittar et al.	N/A	N/A
2011/0238399	12/2010	Ophir et al.	N/A	N/A
2011/0248987	12/2010	Mitchell	N/A	N/A
2011/0263329	12/2010	Miyazaki et al.	N/A	N/A
2011/0292997	12/2010	An et al.	N/A	N/A
2011/0298748	12/2010	Chen et al.	N/A	N/A
2011/0304699	12/2010	Ito et al.	N/A	N/A
2011/0304708	12/2010	Ignatov	N/A	N/A
2012/0038549	12/2011	Mandella et al.	N/A	N/A
2012/0099800	12/2011	Llano et al.	N/A	N/A
2012/0117076	12/2011	Austermann et al.	N/A	N/A
2012/0194516	12/2011	Newcombe et al.	N/A	N/A
2012/0206451	12/2011	Tian et al.	N/A	N/A
2012/0206452	12/2011	Geisner et al.	N/A	N/A
2012/0236030	12/2011	Border et al.	N/A	N/A
2012/0328196	12/2011	Kasahara et al.	N/A	N/A
2013/0002614	12/2012	Nowatzyk et al.	N/A	N/A
2013/0083011	12/2012	Geisner et al.	N/A	N/A
2013/0084984	12/2012	Gagner et al.	N/A	N/A
2013/0117377	12/2012	Miller	N/A	N/A
2013/0128230	12/2012	Macnamara	N/A	N/A
2013/0147790	12/2012	Hildreth et al.	N/A	N/A
2013/0169626	12/2012	Balan et al.	N/A	N/A
2013/0225199	12/2012	Shaw	N/A	N/A
2013/0230211	12/2012	Tanabiki et al.	N/A	N/A
2013/0241773	12/2012	Laine	N/A	N/A
2013/0278635	12/2012	Maggiore	N/A	N/A
2013/0290222	12/2012	Gordo et al.	N/A	N/A
2013/0312009	12/2012	Kramer et al.	N/A	N/A
2013/0321462	12/2012	Salter et al.	N/A	N/A
2013/0346168	12/2012	Zhou et al.	N/A	N/A
2014/0006026	12/2013	Lamb et al.	N/A	N/A
2014/0011589	12/2013	Barney et al.	N/A	N/A
2014/0037140	12/2013	Benhimane et al.	N/A	N/A
2014/0062841	12/2013	Ishikawa et al.	N/A	N/A
2014/0075060	12/2013	Sharp et al.	N/A	N/A

2014/0080428	12/2013	Rhoads et al.	N/A	N/A
2014/0119598	12/2013	Ramachandran et al.	N/A	N/A
2014/0139226	12/2013	Jaaskelainen et al.	N/A	N/A
2014/0145932	12/2013	Underkoffler et al.	N/A	N/A
2014/0176591	12/2013	Klein et al.	N/A	N/A
2014/0181587	12/2013	Sridharan et al.	N/A	N/A
2014/0195988	12/2013	Kramer et al.	N/A	N/A
2014/0212027	12/2013	Hallquist et al.	N/A	N/A
2014/0222409	12/2013	Efrat et al.	N/A	N/A
2014/0225822	12/2013	Underkoffler et al.	N/A	N/A
2014/0225978	12/2013	Saban et al.	N/A	N/A
2014/0267420	12/2013	Schowengerdt et al.	N/A	N/A
2014/0267646	12/2013	Na'Aman et al.	N/A	N/A
2014/0285375	12/2013	Crain	N/A	N/A
2014/0287806	12/2013	Balachandreswaran	463/7	A63F 13/285
2014/0298269	12/2013	Underkoffler et al.	N/A	N/A
2014/0306866	12/2013	Miller et al.	N/A	N/A
2014/0321702	12/2013	Schmalstieg	N/A	N/A
2014/0323148	12/2013	Schmalstieg et al.	N/A	N/A
2014/0325373	12/2013	Kramer et al.	N/A	N/A
2014/0354548	12/2013	Lee	N/A	N/A
2015/0002542	12/2014	Chan et al.	N/A	N/A
2015/0016777	12/2014	Abovitz et al.	N/A	N/A
2015/0019651	12/2014	Kazi et al.	N/A	N/A
2015/0029218	12/2014	Williams et al.	N/A	N/A
2015/0040074	12/2014	Hofmann et al.	N/A	N/A
2015/0070347	12/2014	Hofmann et al.	N/A	N/A
2015/0071525	12/2014	Routhier et al.	N/A	N/A
2015/0077326	12/2014	Kramer et al.	N/A	N/A
2015/0092015	12/2014	Stafford	N/A	N/A
2015/0097719	12/2014	Balachandreswaran	342/147	G02B 27/017
2015/0100380	12/2014	Jones, Jr. et al.	N/A	N/A
2015/0100593	12/2014	Underkoffler et al.	N/A	N/A
2015/0161476	12/2014	Kurz et al.	N/A	N/A
2015/0163345	12/2014	Cornaby et al.	N/A	N/A
2015/0172568	12/2014	Choe et al.	N/A	N/A
2015/0177831	12/2014	Chan et al.	N/A	N/A
2015/0178554	12/2014	Kanaujia et al.	N/A	N/A
2015/0178939	12/2014	Bradski et al.	N/A	N/A
2015/0205126	12/2014	Schowengerdt	N/A	N/A
2015/0205364	12/2014	Underkoffler et al.	N/A	N/A
2015/0205388	12/2014	Osterhout	N/A	N/A
2015/0215611	12/2014	Wu et al.	N/A	N/A
2015/0221133	12/2014	Groten et al.	N/A	N/A
2015/0234477	12/2014	Abovitz et al.	N/A	N/A
2015/0243080	12/2014	Steinbach et al.	N/A	N/A
2015/0262372	12/2014	Cardoso et al.	N/A	N/A
2015/0301592	12/2014	Miller	N/A	N/A

2015/0302652	12/2014	Miller et al.	N/A	N/A
2015/0309264	12/2014	Abovitz et al.	N/A	N/A
2015/0309563	12/2014	Connor	N/A	N/A
2015/0310310	12/2014	Hesch	N/A	N/A
2015/0324198	12/2014	Alsup et al.	N/A	N/A
2015/0339857	12/2014	O'Connor et al.	N/A	N/A
2015/0346495	12/2014	Welch et al.	N/A	N/A
2015/0358539	12/2014	Catt	N/A	N/A
2015/0371082	12/2014	Csaszar et al.	N/A	N/A
2015/0373369	12/2014	Jalai et al.	N/A	N/A
2015/0379772	12/2014	Hoffman	N/A	N/A
2016/0005233	12/2015	Fraccaroli et al.	N/A	N/A
2016/0012643	12/2015	Kezele et al.	N/A	N/A
2016/0016752	12/2015	Helseth et al.	N/A	N/A
2016/0018896	12/2015	Kramer et al.	N/A	N/A
2016/0021511	12/2015	Jin et al.	N/A	N/A
2016/0026253	12/2015	Bradski et al.	N/A	N/A
2016/0033768	12/2015	Pedrotti	345/8	G02B 27/0149
2016/0041048	12/2015	Blum et al.	N/A	N/A
2016/0098095	12/2015	Gonzalez-Banos et al.	N/A	N/A
2016/0104311	12/2015	Allyn	N/A	N/A
2016/0117822	12/2015	Yii et al.	N/A	N/A
2016/0133201	12/2015	Border et al.	N/A	N/A
2016/0147065	12/2015	Border et al.	N/A	N/A
2016/0147070	12/2015	Border et al.	N/A	N/A
2016/0171644	12/2015	Gruber	N/A	N/A
2016/0180151	12/2015	Philbin et al.	N/A	N/A
2016/0180592	12/2015	Bean et al.	N/A	N/A
2016/0187974	12/2015	Mallinson	463/32	G06F 1/163
2016/0189680	12/2015	Paquette	N/A	N/A
2016/0203624	12/2015	Anderson	N/A	N/A
2016/0210783	12/2015	Tomlin et al.	N/A	N/A
2016/0240008	12/2015	Haddick et al.	N/A	N/A
2016/0259032	12/2015	Hehn	N/A	N/A
2016/0259404	12/2015	Woods	N/A	N/A
2016/0262608	12/2015	Krueger	N/A	N/A
2016/0282619	12/2015	Oto	N/A	N/A
2016/0294958	12/2015	Zhang et al.	N/A	N/A
2016/0299567	12/2015	Crisler et al.	N/A	N/A
2016/0327789	12/2015	Klug et al.	N/A	N/A
2016/0378863	12/2015	Shlens et al.	N/A	N/A
2016/0379092	12/2015	Kutliroff	N/A	N/A
2017/0011555	12/2016	Li et al.	N/A	N/A
2017/0032220	12/2016	Medasani et al.	N/A	N/A
2017/0076328	12/2016	Suzuki	N/A	N/A
2017/0098406	12/2016	Kobayashi	N/A	N/A
2017/0109916	12/2016	Kurz et al.	N/A	N/A
2017/0126988	12/2016	Holzer et al.	N/A	N/A

2017/0148206	12/2016	Donner et al.	N/A	N/A
2017/0155887	12/2016	Zhou	N/A	N/A
2017/0160798	12/2016	Lanman et al.	N/A	N/A
2017/0161853	12/2016	Gossweiler et al.	N/A	N/A
2017/0161919	12/2016	Schroeder	N/A	N/A
2017/0177082	12/2016	Michail et al.	N/A	N/A
2017/0184387	12/2016	Lefevre et al.	N/A	N/A
2017/0205903	12/2016	Miller et al.	N/A	N/A
2017/0213473	12/2016	Ribeira et al.	N/A	N/A
2017/0243324	12/2016	Mierle et al.	N/A	N/A
2017/0244811	12/2016	Mckenzie et al.	N/A	N/A
2017/0345220	12/2016	Bates	N/A	N/A
2017/0345398	12/2016	Fuchs et al.	N/A	N/A
2017/0359570	12/2016	Holzer et al.	N/A	N/A
2018/0039083	12/2017	Miller et al.	N/A	N/A
2018/0047332	12/2017	Kuwahara	N/A	N/A
2018/0053284	12/2017	Rodriguez et al.	N/A	N/A
2018/0054712	12/2017	Ahuja et al.	N/A	N/A
2018/0107346	12/2017	Wilson	N/A	N/A
2018/0203235	12/2017	Fix et al.	N/A	N/A
2018/0213359	12/2017	Reinhardt et al.	N/A	N/A
2018/0267309	12/2017	Klug et al.	N/A	N/A
2018/0268518	12/2017	Nourai et al.	N/A	N/A
2018/0268519	12/2017	Liebenow et al.	N/A	N/A
2018/0268610	12/2017	Nourai et al.	N/A	N/A
2018/0301076	12/2017	Trythall	N/A	N/A
2018/0315362	12/2017	Newton	N/A	N/A
2018/0365882	12/2017	Croxsford et al.	N/A	N/A
2019/0015167	12/2018	Draelos et al.	N/A	N/A
2019/0056693	12/2018	Gelman et al.	N/A	N/A
2019/0064526	12/2018	Connor	N/A	N/A
2019/0066353	12/2018	Anderson et al.	N/A	N/A
2019/0066365	12/2018	Schmalsteig et al.	N/A	N/A
2019/0155374	12/2018	Miller et al.	N/A	N/A
2019/0156504	12/2018	Jiang et al.	N/A	N/A
2019/0333263	12/2018	Melkote Krishnaprasad et al.	N/A	N/A
2019/0355176	12/2018	Evans	N/A	N/A
2020/0005517	12/2019	Anderson et al.	N/A	N/A
2020/0027194	12/2019	Nourai et al.	N/A	N/A
2020/0184712	12/2019	Schmalstieg et al.	N/A	N/A
2020/0209978	12/2019	Pahud et al.	N/A	N/A

#### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017214748	12/2017	AU	N/A
2017305227	12/2018	AU	N/A
2018234921	12/2020	AU	N/A
2021204725	12/2021	AU	N/A

2021290369	12/2021	AU	N/A
2022200841	12/2022	AU	N/A
2142338	12/1993	CA	N/A
2358682	12/1993	CA	N/A
101093586	12/2006	CN	N/A
101530325	12/2008	CN	N/A
103792661	12/2013	CN	N/A
104011788	12/2013	CN	N/A
104866829	12/2014	CN	N/A
105404393	12/2015	CN	N/A
2887311	12/2014	EP	N/A
2001-208529	12/2000	JP	N/A
2007-128009	12/2006	JP	N/A
2012-43308	12/2011	JP	N/A
2012-96027	12/2011	JP	N/A
2012-515899	12/2011	JP	N/A
2015-52832	12/2014	JP	N/A
2016-528476	12/2015	JP	N/A
2000-353249	12/2019	JP	N/A
10-2013-0052625	12/2012	KR	N/A
10-2014-0034252	12/2013	KR	N/A
10-2015-0092165	12/2014	KR	N/A
10-2016-0013939	12/2015	KR	N/A
10-2016-0023888	12/2015	KR	N/A
WO 94/04938	12/1993	WO	N/A
WO 2009/091563	12/2008	WO	N/A
WO 2014/160342	12/2013	WO	N/A
WO 2015134958	12/2014	WO	N/A
WO 2016/038240	12/2015	WO	N/A
WO 2016141373	12/2015	WO	N/A
WO 2017003769	12/2016	WO	N/A
WO 2017096396	12/2016	WO	N/A
WO 2017136833	12/2016	WO	N/A
WO 9720244	12/2018	WO	N/A
WO 2020/023383	12/2019	WO	N/A



## OTHER PUBLICATIONS

T. Auer and A. Pinz, "Building a hybrid tracking system: integration of optical and magnetic tracking," Proceedings 2nd IEEE and ACM International Workshop on Augmented Reality (IWAR'99), San Francisco, CA, USA, pp. 13-22 (Year: 1999). cited by examiner

Foreign OA for JP Patent Appln. No. 2022-172932 dated Sep. 1, 2023. cited by applicant

Foreign Exam Report for NZ Patent Appln. No. 784780 dated Aug. 21, 2023. cited by applicant

Foreign Exam Report for NZ Patent Appln. No. 784786 dated Aug. 25, 2023. cited by applicant

Foreign Exam Report for NZ Patent Appln. No. 784790 dated Aug. 28, 2023. cited by applicant

Foreign OA for JP Patent Appln. No. 2023-104864 dated Oct. 3, 2023 (with English translation). cited by applicant

Foreign NOA for AU Patent Appln. No. 2022200841 dated May 16, 2023. cited by applicant

Foreign NOA for JP Patent Appln. No. 2021-503570 dated Jun. 2, 2023. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/659,284 dated Jun. 5, 2023. cited by applicant

Foreign NOA for JP Patent Appln. No. 2021-41375 dated Jun. 5, 2023. cited by applicant

Foreign Exam Report for CA Patent Appln. No. 3055218 dated May 19, 2023. cited by applicant

Foreign Amendment for KR Patent Appln. No. 10-2021-7012722 dated Jun. 12, 2023. cited by applicant

Foreign Response for CA Patent Appln. No. 3011377 dated Jun. 16, 2023. cited by applicant

Foreign NOA for CA Patent Appln. No. 2979560 dated Jun. 1, 2023. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 17837488.0 dated Mar. 16, 2023. cited by applicant

Ferhat Altaï et al: "Physical Human Activity Recognition Using Wearable Sensors", Sensors, vol. 15, No. 12, Dec. 11, 2015 (Dec. 11, 2015 ), pp. 31314-31338, XP055397645, DOI: 10.3390/s151229858. cited by applicant

Aryabrata Basu et al: "Immersive 3DUI on one dollar a day", 3D User Interfaces (3DUI), 2012 IEEE Symposium on, IEEE, Mar. 4, 2012 (Mar. 4, 2012), pp. 97-100, XP032169260, DOI: 10.1109/3DUI.2012.6184191, ISBN : 978-1-4673-1204-2. cited by applicant

Foreign OA for KR Patent Appln. No. 10-2022-7041575 dated Feb. 24, 2023. cited by applicant

Foreign Response for KR Patent Appln. No. 10-2022-7005613 dated Mar. 24, 2023. cited by applicant

Foreign NOA for IL Patent Appln. No. 294134 dated Feb. 26, 2023. cited by applicant

Foreign Response for JP Patent Appln. No. 2021-503570 dated Mar. 27, 2023. cited by applicant

Foreign NOA for IL Patent Appln. No. 290142 dated Feb. 27, 2023. cited by applicant

Foreign Response for CN Patent Appln. No. 201880007856.8 dated Apr. 4, 2023. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/514,606 dated Apr. 5, 2023. cited by applicant

Foreign Exam Report for CA Patent Appln. No. 3054619 dated Mar. 28, 2023. cited by applicant

Foreign OA for CN Patent Appln. No. 201880018310.2 dated Mar. 7, 2023 (with English translation). cited by applicant

Foreign Response for JP Patent Appln. No. 2021-41375 dated Apr. 19, 2023. cited by applicant

Foreign Response for AU Patent Appln. No. 2022200841 dated Apr. 20, 2023. cited by applicant

Foreign OA for CN Patent Appln. No. 201880018506.1 dated Mar. 8, 2023 (with English translation). cited by applicant

Foreign Response for CA Patent Appln. No. 2979560 dated Apr. 27, 2023. cited by applicant

Foreign NOA for JP Patent Appln. No. 2021-168082 dated May 15, 2023. cited by applicant

Foreign OA for KR Patent Appln. No. 10-2021-7012722 dated Apr. 19, 2023 (with English translation). cited by applicant

Foreign OA for CN Patent Appln. No. 201780054387.0 dated Apr. 28, 2023. cited by applicant

Amendment Response to NFOA for U.S. Appl. No. 17/652,964 dated May 8, 2023. cited by applicant

Foreign Exam Report for CA Patent Appln. No. 3054617 dated Apr. 6, 2023. cited by applicant

Foreign Response for CN Patent Appln. No. 201880018506.1 dated Jun. 27, 2023. cited by applicant

Foreign Response for CN Patent Appln. No. 201780054387.0 dated Jun. 26, 2023. cited by applicant

Foreign Response for CN Patent Appln. No. 201880018310.2 dated Jul. 17, 2023. cited by applicant

Foreign Exam Report for CA Patent Appln. No. 3011377 dated Feb. 22, 2023. cited by applicant

Foreign Exam Report for AU Patent Appln. No. 2022200841 dated Feb. 13, 2023. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/514,606 dated Feb. 6, 2023. cited by applicant

Foreign NOA for CN Patent Appln. No. 201980049056.7 dated Feb. 21, 2023. cited by applicant

Foreign OA for JP Patent Appln. No. 2022-100963 dated Jul. 27, 2023 (with English translation). cited by applicant

Foreign Response for KR Patent Appln. No. 10-2022-7041575 dated Aug. 23, 2023. cited by applicant

Foreign NOA for CA Patent Appln. No. 3054619 dated Aug. 28, 2023. cited by applicant

Foreign NOA for CN Patent Appln. No. 201780054387.0 dated Sep. 1, 2023. cited by applicant

Foreign Response for CN Patent Appln. No. 201880007856.8 dated Sep. 15, 2023. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2022-7005613 dated Jul. 20, 2023. cited by applicant

Foreign Response for CA Patent Appln. No. 3054619 dated Jul. 25, 2023. cited by applicant

Foreign Response for EP Patent Appln. No. 17837488.0 dated Jul. 27, 2023. cited by applicant

Foreign NOA for CN Patent Appln. No. 201880018506.1 dated Jul. 14, 2023. cited by applicant

Final Office Action for U.S. Appl. No. 17/652,964 dated Aug. 10, 2023. cited by applicant

Foreign Exam Report for NZ Patent Appln. No. 744300 dated Aug. 11, 2023. cited by applicant

Non-Final Office Action for U.S. Appl. No. 14/641,376 dated Apr. 14, 2016. cited by applicant

Response to Non-Final office action filed Sep. 12, 2016 for U.S. Appl. No. 14/641,376. cited by applicant

Final Office Action for U.S. Appl. No. 14/641,376 dated Nov. 14, 2016. cited by applicant

Response to Final Office action filed Mar. 14, 2017 for U.S. Appl. No. 14/641,376. cited by applicant

PCT International Search Report and Written Opinion for International Appln. No. PCT/US15/19339, Applicant Magic Leap, Inc., Forms PCT/ISA/210, 220, and 237, dated Jun. 24, 2015 (10 pages). cited by applicant

PCT International Search Report and Written Opinion for International Appln. No. PCT/US16/21095, Applicant Magic Leap, Inc., forms PCT/ISA/210, 220, and 237, dated May 31, 2016 (12 pages). cited by applicant

PCT International Search Report and Written Opinion for International Appln. No. PCT/US16/65001, Applicant Magic Leap, Inc., forms PCT/ISA/210, 220, and 237, dated Feb. 16, 2017 (16 pages). cited by applicant

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2017/016722, Applicant Magic Leap, Inc., forms PCT/ISA/210, 220, and 237, dated Apr. 14, 2017 (24 pages). cited by applicant

Notice of Allowance dated Aug. 14, 2017 for U.S. Appl. No. 14/641,376. cited by applicant

Preliminary Amendment filed Aug. 24, 2017 for U.S. Appl. No. 15/425,837. cited by applicant

Non-Final Office Action dated Dec. 6, 2017 for U.S. Appl. No. 15/062,104. cited by applicant

Voluntary Amendment for Canadian Appln. No. 2979560 filed Oct. 6, 2017, 24 pages. cited by applicant

Voluntary Amendment for Japanese Appln. No. 2017-546703 filed Nov. 7, 2017, 7 pages. cited by applicant

Response to Non-Final office action filed Mar. 6, 2018 for U.S. Appl. No. 15/062,104. cited by applicant

Final Office Action filed Apr. 30, 2018 for U.S. Appl. No. 15/062,104. cited by applicant

Coiliot, C., Moutoussamy, J., Boda, M., and Leroy, P.: New ferromagnetic core shapes for induction sensors, J. Sens. Sens. Syst., 3, 1-8, <https://doi.org/10.5194/jsss-3-1-2014>, 2014. cited by applicant

Non-Final Office Action mailed Apr. 5, 2018 for U.S. Appl. No. 15/425,837. cited by applicant

Response to Non-Final Office Action filed Jul. 5, 2018 for U.S. Appl. No. 15/425,837. cited by applicant

Pre appeal brief filed Aug. 30, 2018 for U.S. Appl. No. 15/062,104. cited by applicant

Notice of Allowance dated Sep. 6, 2018 for U.S. Appl. No. 15/425,837. cited by applicant

Extended European Search Report dated Oct. 16, 2018 for EP Application No. 16759643.6. cited by applicant

Amendment After Allowance dated Nov. 15, 2018 for U.S. Appl. No. 15/425,837. cited by applicant

Non final Office Action mailed Nov. 29, 2018 for U.S. Appl. No. 15/369,646. cited by applicant

Extended European Search Report dated Jan. 7, 2019 for EP Application No. 16871733.8. cited by applicant

Song Yafei et al.: Fast Estimation of Relative Poses for 6-DOF Image Localization, 2015 IEEE International Conference on Multimedia Big Data, IEEE; Apr. 20, 2015, pp. 156-163, XP033173496. cited by applicant

Ng Joe Yue-Hei et al.: Exploiting local features from deep networks for image retrieval, 2015 IEEE Conference on Computer Vision and Pattern recognition workshops (CVPRW), IEEE; Jun. 7, 2015, pp. 53-61, XP032795533. cited by applicant

Bay Herbert et al.: SURF: Speeded Up Robust Features, International Conference on Simulation, Modeling and Programming for Autonomous Robots, Simpar 2010, Lecture Notes in Computer Science; Lect Notes Computer; May 7, 2006, pp. 404-417, XP047429677. cited by applicant

Alex Kendall et al.: PoseNet: A Convolutional Network for Real-Time 6-DOF Camera Relocalization, <https://arxiv.org/pdf/1505.07427v3.pdf>, Nov. 23, 2015; XP055536871. cited by applicant

Extended European Search Report dated Jan. 17, 2019 for EP Application No. 17748352.6. cited by applicant

Nair Rahul et al.: "A Survey on Time-of-Flight Stereo Fusion", Oct. 9, 2015, Medical Image Computing and Computer Assisted Intervention—MICCAI 2015, 18th International Conference, Munich, Germany, Oct. 5-9, 2015; Proceedings; Lecture Notes in Computer Science; Lect Notes Computer; Springer International Publishing, CH, XP047148654. cited by applicant

Zhu J J et al.: Joint depth and alpha matte optimization via fusion of stereo and time-of-flight sensor, 2009 IEEE Conference on Computer Vision and Pattern recognition (CVPR), IEEE; Jun. 20, 2009, pp. 453-460, XP002700137. cited by applicant

Amendment After Non-Final Office Action dated Feb. 28, 2019 for U.S. Appl. No. 15/369,646. cited by applicant

PCT International Search Report and Written Opinion for International Appln. No.

PCT/US18/22884, Applicant Magic Leap, Inc., forms PCT/ISA/210, 220, and 237, dated May 21, 2018 (13 pages). cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/923,560 dated Jan. 2, 2019. cited by applicant

Amendment Response to Non-Final Office Action for U.S. Appl. No. 15/923,560 dated Apr. 1, 2019. cited by applicant

PCT International Search Report and Written Opinion for International Appln. No.

PCT/US18/22993, Applicant Magic Leap, Inc., forms PCT/ISA/210, 220, and 237, dated Jun. 8, 2018 (13 pages). cited by applicant

PCT Invitation to Pay Additional Fees for International Appln. No. PCT/US18/23011, Applicant Magic Leap, Inc. dated May 25, 2018 (18 pages). cited by applicant

PCT International Search Report and Written Opinion for International Appln. No. PCT/US18/23011, Applicant Magic Leap, Inc. dated Jul. 23, 2018 (18 pages). cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/924,078 dated Mar. 21, 2019. cited by applicant

Reply brief filed May 6, 2019 for U.S. Appl. No. 15/062,104. cited by applicant

Response to Extended European Search Report dated May 13, 2019 for EP Application No. 16759643.6. cited by applicant

Non Final Office action mailed Jun. 17, 2019 for U.S. Appl. No. 15/924,011. cited by applicant

Tian et al., View Synthesis Techniques for 3D Video, Proc. SPIE 7443, Applications of Digital Image Processing XXXII, 74430T, Sep. 2009 (Year: 2009). cited by applicant

Final Office Action dated Jun. 21, 2019 for U.S. Appl. No. 15/369,646. cited by applicant

Response to Non-Final Office Action filed Jun. 21, 2019 for U.S. Appl. No. 15/924,078. cited by applicant

Response to Restriction Requirement filed Jul. 22, 2019 for U.S. Appl. No. 15/877,359. cited by applicant

Final Office Action for U.S. Appl. No. 15/923,560 dated Jul. 11, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/665,335 dated Apr. 22, 2019. cited by applicant

Response to Non-Final Office Action for U.S. Appl. No. 15/665,335 dated Jul. 22, 2019. cited by applicant

Response to Restriction Requirement filed Mar. 18, 2019 for U.S. Appl. No. 15/665,335. cited by applicant

PCT International Search Report and Written Opinion for International Patent Appln. No. PCT/US2017/044762 dated Oct. 5, 2017 (8 pages). cited by applicant

Response to Extended European Search Report dated Jul. 30, 2019 for European Application No. 16871733.8, (12 pages). cited by applicant

Final Office Action for U.S. Appl. No. 15/924,078 dated Aug. 9, 2019. cited by applicant

Response to Final Office Action and AFCP for U.S. Appl. No. 15/369,646, filed Aug. 21, 2019. cited by applicant

Response Non Final Office action filed Sep. 12, 2019 for U.S. Appl. No. 15/924,011. cited by applicant

Advisory Action dated Sep. 6, 2019 for U.S. Appl. No. 15/369,646. cited by applicant

RCE and Response to Final Office Action for U.S. Appl. No. 15/369,646, filed Sep. 19, 2019. cited by applicant

Office Action for Chinese Appln. No. 201680025479.1 dated Jul. 23, 2019, 16 pages w/English translation. cited by applicant

Response to Final Office Action and AFCP for U.S. Appl. No. 15/924,078, filed Oct. 9, 2019. cited by applicant

Response to Final Office Action for U.S. Appl. No. 15/923,560, filed Oct. 10, 2019. cited by applicant

1st Examination Report dated Oct. 1, 2019 for European Application No. 16759643.6. cited by applicant

Non-Final Office Action mailed on Oct. 21, 2019 for U.S. Appl. No. 15/877,359. cited by applicant

Final office action mailed Oct. 22, 2019 for U.S. Appl. No. 15/924,011. cited by applicant

Advisory Action mailed Oct. 22, 2019 for U.S. Appl. No. 15/924,078. cited by applicant

Non-Final Office Action mailed on Oct. 30, 2019 for U.S. Appl. No. 16/220,617. cited by applicant

Non-Final Office Action mailed on Oct. 31, 2019 for U.S. Appl. No. 15/923,560. cited by applicant

RCE and Response to Final Office Action filed Nov. 11, 2019 for U.S. Appl. No. 15/924,078. cited by applicant

Non Final Office Action dated Nov. 8, 2019 for U.S. Appl. No. 15/369,646. cited by applicant

Final office action mailed Aug. 9, 2019 for U.S. Appl. No. 15/924,078. cited by applicant

Office Action for Israeli Appln. No. 254300 dated Oct. 27, 2019, 7 pages w/English translation. cited by applicant

Response to Office Action for Chinese Appln. No. 201680025479.1 filed Nov. 26, 2019, 9 pages w/English translation of claims. cited by applicant

Extended European Search Report dated Nov. 21, 2019 for European Application No. 18767086.4. cited by applicant

Extended European Search Report for European Appln. No. 17837488.0 dated Jul. 11, 2019 (10 pages). cited by applicant

Robert Earl Patterson, et al. "Low-Level Factors in Human Factors of Stereoscopic 3D Displays", ProQuest Ebook Central, Springer, London, Dec. 29, 2014. doi:10.1007/978-1-4471-6651-1\_4, chapter 4.2; 4.3. cited by applicant

Jannick Rolland, et al. "The past, present and future of head-mounted display designs"; Nov. 8, 2004, Proc. SPIE 5638, p. 368. cited by applicant

RCE and Response to Final Office Action for U.S. Appl. No. 15/665,335, filed Dec. 4, 2019. cited by applicant

PCT International Search Report and Written Opinion for International Patent Appln. No. PCT/US2019/042819, dated Dec. 4, 2019 (12 pages). cited by applicant

PCT Invitation to Pay Additional Fees for International Patent Appln. No. PCT/US2019/042819, dated Sep. 18, 2019 (2 pages). cited by applicant

Lee, Y., et al., "Estimating Gaze Depth Using Multi-Layer Perceptron," Published by IEEE, retrieved electronically on Apr. 12, 2019 (5 pages). cited by applicant

Extended European Search Report for European Appln. No. 18766694.6 dated Nov. 21, 2019 (9 pages). cited by applicant

Theohari S Theohari S et al. "The Magic of the Z-Buffer: A Survey", Journal of WSCG, Plzen, Czech Republic, Feb. 5, 2001, XP55640849. cited by applicant

Amir H. Behzadan et al: "Scalable 1-14 Algorithm for Resolving Incorrect Occlusion in Dynamic Augmented Reality Engineering Environments : Scalable algorithm for resolving incorrect occlusion", Computer-Aided Civil and Infrastructure Engineering, vol. 25, No. I, Jan. 1, 2010, pp. 3-19, XP55640847. cited by applicant

Breen D E et al: "Interactive occlusion 1-14 and automatic object placement for augmented reality", Computer Graphics Forum, Wiley-Blackwell Publishing Ltd, GB, vol. 15, No. 3, Aug. 26, 1996, pp. 11-22, XP002515919. cited by applicant

Mark WR et al: "Post-Rendering 3D 1-14 Warping", Proceedings of 1997 Symposium on Interactive 3 D Graphics Apr. 27-30, 1997 Providence, RI, USA; ACM, New York, NY, USA, Apr. 27, 1997, pp. 7-16, XP000725355. cited by applicant

Amendment After Final Office Action for U.S. Appl. No. 15/924,011 dated Dec. 19, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 16/22,630 dated Dec. 26, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/924,078 dated Jan. 13, 2020. cited by applicant

Extended European Search Report for European Appln. No. 18742228.2 dated Jan. 13, 2020 (8 pages). cited by applicant

Amendment After non-final Office Action for U.S. Appl. No. 15/877,359 dated Jan. 21, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/924,011 dated Jan. 23, 2020. cited by applicant

Response to Extended European Search Report for European Appln. No. 17837488.0 filed Jan. 28, 2020 (23 pages). cited by applicant

Amendment After non-final Office Action for U.S. Appl. No. 16/220,617 dated Jan. 30, 2020. cited by applicant

Amendment After non-final Office Action for U.S. Appl. No. 15/923,560 dated Jan. 31, 2020. cited

by applicant

Response to Examination Report filed Feb. 11, 2020 for European Application No. 16759643.6.

cited by applicant

Amendment After non-final Office Action for U.S. Appl. No. 15/369,646 dated Feb. 10, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/220,617 dated Feb. 20, 2020. cited by applicant

Response to Office Action filed Feb. 20, 2020 for Israeli Patent Application No. 254300, (3 pages). cited by applicant

Foreign Office Action for Japanese Patent Appln. No. 2017-546703 dated Mar. 10, 2020. cited by applicant

Amendment After non-final Office Action for U.S. Appl. No. 15/924,078 dated Apr. 13, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/369,646 dated Apr. 8, 2020. cited by applicant

Final Office Action for U.S. Appl. No. 15/877,359 dated Apr. 16, 2020. cited by applicant

Foreign Office Action for Israeli Patent Application No. 259766 dated Mar. 1, 2020. cited by applicant

Amendment After non-final Office Action for U.S. Appl. No. 16/220,630 dated Apr. 27, 2020. cited by applicant

Non-Final Office Action for U.S. Appl. No. 16/848,496 dated May 18, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/923,560 dated May 19, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/924,078 dated May 18, 2020. cited by applicant

Foreign Office Action for CN Patent Appln. No. 201680025479.1 dated Apr. 7, 2020. cited by applicant

Jiang, P., etc., "Electro-magnetic Tracking System for Capsule-typed Telemetric Device", Optics and Precision Engineering, vol. 15, No. 8, pp. 1247-1252, Aug. 2007. cited by applicant

1st Examination Report dated Jun. 24, 2020 for New Zealand Patent Application No. 743271. cited by applicant

Foreign Office Action for CN Patent Appln. No. 201680025479.1 dated Jun. 18, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/220,630 dated Jun. 8, 2020. cited by applicant

Response to Extended European Search Report for European Appln. No. 18767086.4 filed Jun. 15, 2020 (84 pages). cited by applicant

Response to Extended European Search Report for European Appln. No. 18766694.6 filed Jun. 19, 2020 (78 pages). cited by applicant

1st Examiner's Report for AU European Patent Appln. No. 2016225963 dated Jul. 1, 2020. cited by applicant

Foreign Office Action Response for JP Patent Appln. No. 2017-546703 dated Jun. 1, 2020. cited by applicant

Extended European Search Report for EP Patent Appln. No. 18768030.1 dated Jun. 18, 2020. cited by applicant

Mark, W., et al., "Post-Rendering 3D Warping", Proceedings of 1997 Symposium on 3D Graphics, Apr. 27-30, 1997, Providence, RI, USA, pp. 7-ff, XP058285072. cited by applicant

Amendment Response to Non-Final Office Action for U.S. Appl. No. 16/848,496 dated Jul. 22, 2019. cited by applicant

Foreign Exam Report for NZ Patent Appln. No. 735465 dated Jul. 22, 2020. cited by applicant

1st Examination Report for NZ Patent Appln. No. 734200 dated Jun. 15, 2020. cited by applicant

Foreign Submission Reply for EP Patent Appln No. 18766694.6 dated Jun. 19, 2020. cited by applicant

Foreign Examination Report for EP Patent Appln. No. 17837488.0 dated Jul. 22, 2020. cited by applicant

Response to Extended European Search Report for European Appln. No. 18742228.2 dated Aug. 10, 2020 (86 pages). cited by applicant

Notice of Allowance for U.S. Appl. No. 15/923,560 dated Aug. 25, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/848,496 dated Aug. 24, 2020. cited by applicant

Foreign Office Action for KR Patent Appln. No. 10-2019-7006281 dated Aug. 28, 2020. cited by applicant

Non-Final Office Action for U.S. Appl. No. 16/945,613 dated Sep. 3, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/220,630 dated Sep. 11, 2020. cited by applicant

Foreign Office Action for JP Patent Application No. 2019-505238 dated Sep. 10, 2020 (no translation available). cited by applicant

Notice of Allowance for U.S. Appl. No. 15/369,646 dated Sep. 22, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/220,630 dated Sep. 23, 2020. cited by applicant

Non-Final Office Action for U.S. Appl. No. 16/809,346 dated Oct. 16, 2020. cited by applicant

1st Examination Report for AU Patent Appln. No. 2017214748 dated Oct. 14, 2020. cited by applicant

Non-Final Office Action for U.S. Appl. No. 16/518,431 dated Oct. 27, 2020. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 18767086.4 dated Sep. 23, 2020. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 18766694.6 dated Sep. 23, 2020. cited by applicant

N Stewart et al: "An improved z-buffer CSG rendering algorithm", Proceedings of the Eurographics / SIGGRAPH Workshop on Graphics Hardware. Lisbon, Aug. 31-Sep. 1, 1998; pp. 25-30, XP058111343. cited by applicant

Wolberg G et al: "Separable image warping with spatial lookup tables", Computer Graphics, ACM, US, vol. 23, No. 3, Jul. 1, 1989, pp. 369-378, XP058214788. cited by applicant

R T Stevens: "Primitive", In: "Quick Reference to Computer Graphics Terms a Division of Harcourt Brace & Company", Jan. 1, 1995, XP55730228, p. 166. cited by applicant

J D Foley: "The z-buffer algorithm", In: "Computer Graphics—Principles and Practice", Addison-Wesley, Jan. 1, 1990 (Jan. 1, 1990), XP55731635, pp. 668-672. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/848,496 dated Nov. 2, 2020. cited by applicant

Foreign OA Response for KR Patent Appln. No. 10-2019-7006281 dated Oct. 28, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/938,578 dated Nov. 19, 2020. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 18742228.2 dated Oct. 1, 2020. cited by applicant

Foreign OA Response for EP Patent Appln. No. 17837488.0 dated Nov. 20, 2020. cited by applicant

Foreign OA Response for IL Patent Application No. 259766 dated Nov. 25, 2020. cited by applicant

1st Exam Report for AU Patent Application No. 2016365422 dated Nov. 4, 2020. cited by applicant

Foreign OA Response for JP Patent Application No. 2019-505238 dated Dec. 1, 2020. cited by applicant

Response to Non-Final Office Action for U.S. Appl. No. 16/945,613, filed Dec. 3, 2020. cited by applicant

Foreign Final OA for JP Patent Appln. No. 2017-546703 dated Nov. 20, 2020. cited by applicant

Foreign OA for KR Patent Appln. No. 10-2019-7006281 dated Dec. 15, 2020. cited by applicant

Foreign Exam Report for AU Patent Appln. No. 2017305227 dated Dec. 16, 2020. cited by applicant

Foreign NOA for IL Patent Application No. 259766 dated Nov. 29, 2020. cited by applicant

Amendment Response to NFOA for U.S. Appl. No. 16/809,346 dated Jan. 11, 2020. cited by applicant

Foreign OA For JP Patent Appln. No. 2019-505238 dated Jan. 12, 2021. cited by applicant

Foreign OA for JP Patent Appln. No. 2018-540434 dated Dec. 17, 2020. cited by applicant

Response to Non-Final Office Action for U.S. Appl. No. 16/518,431, filed Jan. 27, 2021. cited by applicant

Foreign Response for JP Patent Appln. No. 2019-510409 dated Jan. 28, 2021. cited by applicant

Foreign OA for IL Patent Appln. No. 254300 dated Nov. 15, 2020. cited by applicant

Foreign Response for NZ Patent Appln. No. 735465 dated Jan. 21, 2021. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2019-7022837 dated Jan. 27, 2021. cited by applicant

Foreign Final OA for KR Patent Appln. No. 10-2019-7006281 dated Jan. 27, 2021. cited by applicant

Foreign Response for EP Patent Appln. No. 18742228.2 dated Feb. 11, 2021. cited by applicant

Foreign Response for EP Patent Appln. No. 18768030.1 dated Jan. 18, 2021. cited by applicant

Foreign OA for JP Patent Appln. No. 2019-539183 dated Feb. 19, 2021. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 16871733.8 dated Jan. 11, 2021. cited by applicant

Final Office Action for U.S. Appl. No. 16/518,431 dated Mar. 2, 2021. cited by applicant

Foreign OA for JP Patent Appln. No. 2018-528977 dated Feb. 16, 2021. cited by applicant

Sumit Chopra et al., "Learning a Similarity Metric Discriminatively, with Application to Face Verification", 2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05), US, IEEE, Jun. 20, 2005, vol. 1, pp. 539-546 (a document showing a well-known technique). cited by applicant

Florian Schroff et al., "FaceNet: A Unified Embedding for Face Recognition and Clustering", 2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), US, IEEE, Jun. 7, 2015, pp. 815-823 (a document showing a well-known technique). cited by applicant

Foreign Exam Report for IN Patent Appln. No. 201747032796 dated Mar. 10, 2021. cited by applicant

Final Office Action for U.S. Appl. No. 16/945,613 dated Mar. 18, 2021. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/809,346 dated Mar. 22, 2021. cited by applicant

Foreign OA for CN Patent Appln. No. 201780010073.0 dated Jan. 21, 2021. cited by applicant

Foreign Exam Report for AU Patent Appln. No. 2018233733 dated Mar. 11, 2021. cited by applicant

Foreign Exam Report for AU Patent Appln. No. 2018236457 dated Mar. 10, 2021. cited by applicant

Foreign Response for AU Patent Appln. No. 2018236457 dated Mar. 26, 2021. cited by applicant

Foreign Exam Report for AU Patent Appln. No. 2018234921 dated Mar. 11, 2021. cited by applicant

Foreign Response for AU Patent Appln. No. 2017214748 dated Mar. 29, 2021. cited by applicant

Foreign Exam Report for AU Patent Appln. No. 2018210015 dated Feb. 23, 2021. cited by applicant

Foreign Response for AU Patent Appln. No. 2018210015 dated Mar. 12, 2021. cited by applicant

Foreign Exam Report for NZ Patent Appln. No. 735465 dated Feb. 15, 2021. cited by applicant

Foreign Response for NZ Patent Appln. No. 735465 dated Mar. 31, 2021. cited by applicant

Foreign Response for AU Patent Appln. No. 2016225963 dated Mar. 31, 2021. cited by applicant

Foreign Response for EP Patent Appln. No. 18767086.4 dated Apr. 6, 2021. cited by applicant

Foreign Response for EP Patent Appln. No. 18766694.6 dated Apr. 6, 2021. cited by applicant

Foreign Notice of Acceptance for AU Patent Appln. No. 2018210015 dated Mar. 24, 2021. cited by applicant

Foreign NOA for IL Patent Appln. No. 267946 dated Apr. 7, 2021. cited by applicant

Foreign Response for JP Patent Appln. No. 2019-505238 dated Apr. 16, 2021. cited by applicant

Foreign OA for KR Patent Appln. No. 10-2017-7028140 dated Apr. 21, 2021. cited by applicant

Foreign Response for JP Patent Appln. No. 2018-540434 dated May 17, 2021. cited by applicant

Foreign Response for EP Patent Appln. No. 16871733.8 dated May 17, 2021. cited by applicant

Foreign Response for JP Patent Appln. No. 2019-539183 dated May 17, 2021. cited by applicant



Foreign Exam Report for EP Patent Appln. No. 16759643.6 dated Apr. 29, 2021. cited by applicant  
Foreign Response for AU Patent Appln. No. 2016365422 dated May 14, 2021. cited by applicant  
Foreign Response for JP Patent Appln. No. 2018-528977 dated May 13, 2021. cited by applicant  
Foreign Response for CN Patent Appln. No. 201780010073.0 dated Jun. 4, 2021. cited by applicant  
Notice of Allowance for U.S. Appl. No. 16/945,613 dated Jun. 9, 2021. cited by applicant  
Foreign OA for CN Patent Appln. No. 201880018442.5 dated Apr. 1, 2021. cited by applicant  
Non-Final Office Action for U.S. Appl. No. 17/022,317 dated Jun. 10, 2021. cited by applicant  
Foreign Exam Report for IN Patent Appln. No. 201847023727 dated Jun. 15, 2021. cited by applicant  
Foreign Amendment for KR Patent Appln. No. 10-2017-7028140 dated Jun. 15, 2021. cited by applicant  
Foreign OA for IL Patent Appln. No. 260614 dated Mar. 22, 2021. cited by applicant  
Foreign NOA for JP Patent Appln. No. 2019-539183 dated Jun. 21, 2021. cited by applicant  
2nd Exam Report for EP Patent Appln. No. 17837488.0 dated May 28, 2021. cited by applicant  
Non-Final Office Action for U.S. Appl. No. 16/518,431 dated Jun. 23, 2021. cited by applicant  
Response to Final Office Action for U.S. Appl. No. 16/945,613, filed May 17, 2021. cited by applicant  
RCE Response to Final Office Action for U.S. Appl. No. 16/518,431 dated Jun. 1, 2021. cited by applicant  
Foreign FOA for JP Patent Appln. No. 2018-528977 dated Jun. 7, 2021. cited by applicant  
Foreign NOA for IL Patent Appln. No. 254300 dated Apr. 22, 2021. cited by applicant  
Foreign Response for IL Patent Appln. No. 254300 dated Mar. 14, 2021. cited by applicant  
Foreign FOA for JP Patent Appln. No. 2018-540434 dated Jun. 14, 2021. cited by applicant  
Foreign Exam Report for CA Patent Appln. No. 2979560 dated Jun. 15, 2021. cited by applicant  
Foreign Exam Report for EP Patent Appln. No. 2016365422 dated Jun. 11, 2021. cited by applicant  
Foreign OA for KR Patent Appln. No. 10-2019-7030322 dated Jul. 15, 2021. cited by applicant  
Foreign OA for JP Patent Appln. No. 2019-550189 dated Jul. 13, 2021. cited by applicant  
Foreign OA for JP Patent Appln. No. 2019-505238 dated Jul. 2, 2021. cited by applicant  
Foreign Response for IL Patent Appln. No. 260614 dated Jul. 21, 2021. cited by applicant  
Non-Final Office Action for U.S. Appl. No. 16/922,145 dated Jul. 22, 2021. cited by applicant  
Notice of Allowance for U.S. Appl. No. 16/945,613 dated Aug. 3, 2021. cited by applicant  
English Translation of Foreign OA for JP Patent Appln. No. 2019-550189 dated Jul. 8, 2021. cited by applicant  
Foreign OA for JP Patent Appln. No. 2019-550231 dated Jul. 26, 2021. cited by applicant  
Foreign OA for JP Patent Appln. No. 2019-550200 dated Jul. 26, 2021. cited by applicant  
Foreign NOA for NZ Patent Appln. No. 735465 dated Jul. 22, 2021. cited by applicant  
Foreign Response for CN Patent Appln. No. 201880018442.5 dated Aug. 12, 2021. cited by applicant  
Foreign OA for CN Patent Appln. No. 201780010073.0 dated Jul. 9, 2021. cited by applicant  
Foreign NOA for KR Patent Appln. No. 10-2017-7028140 dated Aug. 23, 2021. cited by applicant  
Foreign Exam Report for IN Patent Appln. No. 201947005860 dated Aug. 18, 2021. cited by applicant  
Decision to Grant for EP Patent Appln. No. 18742228.2 dated Aug. 19, 2021. cited by applicant  
Foreign Exam Report for AU Patent Appln. No. 2021204725 dated Aug. 24, 2021. cited by applicant  
Foreign NOA for JP Patent Appln. No. 2018-548394 dated Sep. 7, 2021. cited by applicant  
Foreign Response for EP Patent Appln. No. 16759643.6 dated Sep. 3, 2021. cited by applicant  
Foreign Response for IN Patent Appln. No. 201747032796 dated Sep. 8, 2021. cited by applicant  
Foreign Response for AU Patent Appln. No. 2018234921 dated Sep. 15, 2021. cited by applicant  
Foreign Response for KR Patent Appln. No. 10-2019-7030322 dated Sep. 13, 2021. cited by

applicant

Foreign Response for KR Patent Appln. No. 10-2019-7030321 dated Sep. 10, 2021. cited by applicant

Foreign Response for AU Patent Appln. No. 2016365422 dated Sep. 16, 2021. cited by applicant

Foreign Response for CN Patent Appln. No. 201780010073.0 dated Sep. 22, 2021. cited by applicant

Foreign Response for JP Patent Appln. No. 2019-505238 dated Sep. 27, 2021. cited by applicant

Foreign Response for KR Patent Appln. No. 10-2019-7029900 dated Sep. 17, 2021. cited by applicant

Foreign Exam Report for IN Patent Appln. No. 201847025793 dated Sep. 22, 2021. cited by applicant

Foreign Response for AU Patent Appln. No. 2018233733 dated Oct. 1, 2021. cited by applicant

Foreign NOA for JP Patent Appln. No. 2019-505238 dated Oct. 5, 2021. cited by applicant

Foreign Response for EP Patent Appln. No. 17837488.0 dated Oct. 5, 2021. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/022,317 dated Oct. 6, 2021. cited by applicant

Foreign Response for JP Patent Appln. No. 2019-550189 dated Oct. 8, 2021. cited by applicant

Foreign Notice of Acceptance for AU Patent Appln. No. 2018234921 dated Sep. 27, 2021. cited by applicant

3rd Exam Report for AU Patent Appln. No. 2016365422 dated Oct. 11, 2021. cited by applicant

Foreign Notice of Appeal for JP Patent Appln. No. 2018-540434 dated Oct. 13, 2021. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 18767086.4 dated Sep. 1, 2021. cited by applicant

Foreign Response for CA Patent Appln. No. 2979560 dated Oct. 13, 2021. cited by applicant

Foreign NOA for IL Patent Appln. No. 268916 dated Sep. 12, 2021. cited by applicant

Amendment Response to NFOA for U.S. Appl. No. 16/922,145 dated Oct. 18, 2021. cited by applicant

Foreign Response for AU Patent Appln. No. 2016365422 dated Oct. 22, 2021. cited by applicant

Foreign Response for JP Patent Appln. No. 2019-550200 dated Oct. 22, 2021. cited by applicant

Foreign Response for JP Patent Appln. No. 2019-550231 dated Oct. 22, 2021. cited by applicant

Extended European Search Report for EP Patent Appln. No. 19840248.9 dated Sep. 29, 2021. cited by applicant

Schmeing Michael et al: "Faithful Disocclusion Filling in Depth Image Based Rendering Using Superpixel-Based Inpainting", IEEE Transactions on Multimedia, IEEE Service Center, US, vol. 17, No. 12, Dec. 1, 2015 (Dec. 1, 2015), pp. 2160-2173, XP011589953, ISSN: 1520-9210, DOI: 10.1109/TMM.2015.2476372 [retrieved on Nov. 13, 2015]. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 18766694.6 dated Sep. 24, 2021. cited by applicant

Foreign NOA for IL Patent Appln. No. 268911 dated Oct. 27, 2021. cited by applicant

Non-Final Office Action for U.S. Appl. No. 17/091,278 dated Nov. 18, 2021. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/518,431 dated Nov. 17, 2021. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2019-7030321 dated Nov. 4, 2021. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/922,145 dated Nov. 19, 2021. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/937,510 dated Dec. 1, 2021. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2019-7029900 dated Nov. 18, 2021. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2019-7030322 dated Nov. 18, 2021. cited by applicant

Foreign OA for CN Patent Appln. No. 201780010073.0 dated Oct. 29, 2021. cited by applicant

Foreign NOA for IL Patent Appln. No. 268962 dated Nov. 28, 2021. cited by applicant

Foreign Response for EP Patent Appln. No. 18742228.2 dated Dec. 7, 2021. cited by applicant

Foreign OA for CN Patent Appln. No. 201680080997.3 dated Sep. 29, 2021. cited by applicant

2nd Exam Report for CA Patent Appln. No. 2979560 dated Nov. 25, 2021. cited by applicant

Foreign NOA for JP Patent Appln. No. 2019-550189 dated Dec. 14, 2021. cited by applicant

Foreign NOA for JP Patent Appln. No. 2019-550200 dated Dec. 14, 2021. cited by applicant

Non-Final Office Action for U.S. Appl. No. 17/178,524 dated Dec. 15, 2021. cited by applicant

Foreign NOA for AU Patent Appln. No. 2017305227 dated Dec. 1, 2021. cited by applicant

Foreign OA for JP Patent Appln. No. 2019-550231 dated Dec. 14, 2021. cited by applicant

Non-Final Office Action for U.S. Appl. No. 17/137,107 dated Dec. 21, 2021. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/022,317 dated Dec. 22, 2021. cited by applicant

Foreign Response for CN Patent Appln. No. 201780010073.0 dated Dec. 31, 2021. cited by applicant

Foreign Exam Report for IN Patent Appln. No. 201947030779 dated Jan. 4, 2022. cited by applicant

Foreign Response for EP Patent Appln. No. 18767086.4 dated Jan. 11, 2022. cited by applicant

Foreign NOA for CN Patent Appln. No. 201880018442.5 dated Jan. 12, 2022. cited by applicant

Foreign Exam Report for IN Patent Appln. No. 201947040457 dated Feb. 3, 2022. cited by applicant

Foreign Exam Report for IN Patent Appln. No. 201947040458 dated Feb. 4, 2022. cited by applicant

Foreign Exam Report for IN Patent Appln. No. 201947040852 dated Feb. 1, 2022. cited by applicant

Foreign OA for KR Patent Appln. No. 10-2021-7006131 dated Feb. 9, 2022 (with English translation). cited by applicant

Amendment Response to NFOA for U.S. Appl. No. 17/091,278 dated Feb. 18, 2022. cited by applicant

Foreign OA for JP Patent Appln. No. 2017-546703 dated Feb. 3, 2022 (with English translation). cited by applicant

Notice of Allowance for U.S. Appl. No. 16/518,431 dated Feb. 24, 2022. cited by applicant

Foreign OA for JP Patent Appln. No. 2022-002800 dated Feb. 8, 2022 (with English translation). cited by applicant

Foreign Response for JP Patent Appln. No. 2019-550231 dated Mar. 8, 2022. cited by applicant

Foreign OA for JP Patent Appln. No. 2022-2802 dated Feb. 8, 2022 (with English translation). cited by applicant

Foreign NOA for JP Patent Appln. No. 2019-550231 dated Mar. 11, 2022. cited by applicant

Amendment Response to NFOA for U.S. Appl. No. 17/178,524 dated Mar. 15, 2022. cited by applicant

Amendment Response to NFOA for U.S. Appl. No. 17/137,107 dated Mar. 21, 2022. cited by applicant

Foreign Response for CA Patent Appln. No. 2979560 dated Mar. 24, 2022. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/091,278 dated Mar. 28, 2022. cited by applicant

Foreign Summons for Oral Proceedings for EP Patent Appln. No. 16871733.8 dated Mar. 15, 2022. cited by applicant

Foreign Response for IN Patent Appln. No. 201847025793 dated Mar. 21, 2022 in English. cited by applicant

Foreign Response for EP Patent Appln. No. 18766694.6 dated Apr. 4, 2022. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/178,524 dated Apr. 6, 2022. cited by applicant

Foreign Exam Report for AU Patent Appln. No. 2022201750 dated Apr. 6, 2022. cited by applicant

Foreign Exam Report for AU Patent Appln. No. 2021290369 dated Mar. 29, 2022. cited by applicant

Foreign NOA for IL Patent Appln. No. 264489 dated Mar. 21, 2022 in English. cited by applicant

Foreign Response for KR Patent Appln. No. 10-2021-7006131 dated Apr. 11, 2022. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/137,107 dated Apr. 20, 2022. cited by applicant

Foreign NOA for CN Patent Appln. No. 201780010073.0 dated Apr. 6, 2022. cited by applicant  
Non-Final Office Action for U.S. Appl. No. 17/353,434 dated Apr. 28, 2022. cited by applicant  
Foreign Response for EP Patent Appln. No. 19840248.9 dated Apr. 29, 2022. cited by applicant  
Foreign Response for JP Patent Appln. No. 2017-546703 dated May 5, 2022. cited by applicant  
Foreign NOA for IL Patent Appln. No. 260614 dated Mar. 16, 2022. cited by applicant  
Foreign Response for JP Patent Appln. No. 2022-2802 dated May 9, 2022. cited by applicant  
Foreign Response for JP Patent Appln. No. 2022-2800 dated May 9, 2022. cited by applicant  
Extended European Search Report for EP Patent Appln. No. 21196532.2 dated Mar. 28, 2022. cited by applicant  
Foreign NOA for JP Patent Appln. No. 2022-2800 dated May 24, 2022. cited by applicant  
Foreign NOA for JP Patent Appln. No. 2022-2802 dated May 24, 2022. cited by applicant  
Foreign Exam Report for AU Patent Appln. No. 2022200841 dated May 19, 2022. cited by applicant  
Foreign Response for JP Patent Appln. No. 2021-41375 dated May 30, 2022. cited by applicant  
Foreign Examiner's Report for CA Patent Appln. No. 2979560 dated May 31, 2022. cited by applicant  
Foreign OA for JP Patent Appln. No. 2021-116964 dated Jun. 6, 2022. cited by applicant  
Foreign Response for AU Patent Appln. No. 2021204725 dated Jul. 15, 2022. cited by applicant  
Foreign NOA for IL Patent Appln. No. 284939 dated May 31, 2022 in English. cited by applicant  
Foreign Intent to Grant for EP Patent Appln. No. 16759643.6 dated Jul. 21, 2022. cited by applicant  
Foreign OA for JP Patent Appln. No. 2021-41375 dated Jul. 4, 2022 (with English translation). cited by applicant  
Amendment Response to NFOA for U.S. Appl. No. 17/353,434 dated Jul. 28, 2022. cited by applicant  
Foreign NOA for JP Patent Appln. No. 2017-546703 dated Aug. 3, 2022. cited by applicant  
Foreign OA for CN Patent Appln. No. 201980049056.7 dated Aug. 3, 2022 (with English translation). cited by applicant  
Foreign NOA for IL Patent Appln. No. 284404 dated Jul. 31, 2022 in English. cited by applicant  
Foreign NOA for AU Patent Appln. No. 2021204725 dated Jul. 26, 2022. cited by applicant  
Notice of Allowance for U.S. Appl. No. 17/353,434 dated Aug. 15, 2022. cited by applicant  
Foreign Exam Report for NZ Patent Appln. No. 750261 dated Aug. 5, 2022. cited by applicant  
Foreign FOA for KR Patent Appln. No. 10-2021-7006131 dated Aug. 25, 2022 with English translation. cited by applicant  
Foreign Response for KR Patent Appln. No. 10-2022-7005613 dated Aug. 29, 2022. cited by applicant  
Foreign Notification Prior to Acceptance for IL Patent Appln. No. 290308 dated Sep. 4, 2022 in English. cited by applicant  
Non-Final Office Action for U.S. Appl. No. 17/514,606 dated Sep. 20, 2022. cited by applicant  
Foreign Response for AU Patent Appln. No. 2021290369 dated Sep. 29, 2022. cited by applicant  
Foreign Response for CA Patent Appln. No. 2979560 dated Sep. 30, 2022. cited by applicant  
Foreign Response for IN Patent Appln. No. 201947030779 dated Sep. 30, 2022 in English. cited by applicant  
Foreign Response for JP Patent Appln. No. 2021-41375 dated Oct. 3, 2022. cited by applicant  
Foreign NOA for JP Patent Appln. No. 2021-116964 dated Oct. 3, 2022. cited by applicant  
Foreign Exam Report for NZ Patent Appln. No. 790720 dated Sep. 27, 2022. cited by applicant  
Foreign OA for CN Patent Appln. No. 201780054387.0 dated Sep. 30, 2022 (with English translation). cited by applicant  
Foreign Notice of Acceptance for AU Patent Appln. No. 2021290369 dated Oct. 10, 2022. cited by applicant  
Foreign Response for IN Patent Appln. No. 201947040457 dated Oct. 20, 2022 in English. cited by

applicant

Foreign Response for IN Patent Appln. No. 201947040852 dated Oct. 21, 2022 in English. cited by applicant

Foreign Response for EP Patent Appln. No. 21196532.2 dated Oct. 27, 2022. cited by applicant

Foreign Response for IN Patent Appln. No. 201947040460 dated Oct. 25, 2022 in English. cited by applicant

Foreign Response for IN Patent Appln. No. 201947040458 dated Oct. 26, 2022 in English. cited by applicant

Foreign OA for JP Patent Appln. No. 2021-168082 dated Oct. 14, 2022 (with English translation). cited by applicant

Foreign Response for CN Patent Appln. No. 201980049056.7 dated Nov. 25, 2022. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/813,442 dated Dec. 2, 2022. cited by applicant

Amendment Response to NFOA for U.S. Appl. No. 17/514,606 dated Dec. 19, 2022. cited by applicant

Foreign Exam Report for CA Patent Appln. No. 2979560 dated Jan. 10, 2023. cited by applicant

Foreign OA for JP Patent Appln. No. 2021-503570 dated Dec. 27, 2022 (with English translation). cited by applicant

Foreign Response for AU Patent Appln. No. 2022200841 dated Jan. 16, 2023. cited by applicant

Foreign Response for JP Patent Appln. No. 2021-168082 dated Jan. 16, 2023. cited by applicant

Foreign OA for CN Patent Appln. No. 201880007856.8 dated Nov. 30, 2022 (with English translation). cited by applicant

Foreign OA for KR Patent Appln. No. 10-2022-7005613 dated Dec. 26, 2022 (with English translation). cited by applicant

Foreign NOA for IL Patent Appln. No. 293782 dated Dec. 18, 2022 in English. cited by applicant

Non-Final Office Action for U.S. Appl. No. 17/652,964 dated Feb. 8, 2023. cited by applicant

Foreign OA for JP Patent Appln. No. 2021-41375 dated Jan. 25, 2023 (with English translation). cited by applicant

Foreign Response for CN Patent Appln. No. 201780054387.0 dated Feb. 15, 2023. cited by applicant

Foreign Response for CN Patent Appln. No. 202311439457.8 dated Feb. 25, 2024. cited by applicant

Foreign OA for NZ Patent Appln. No. 744300 dated Feb. 26, 2024. cited by applicant

Foreign OA Response for KR Patent Appln. No. 10-2018-7025638 dated Mar. 4, 2024. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 18767086.4 dated Feb. 9, 2024. cited by applicant

Foreign NOA for IL Patent Appln. No. 297825 dated Apr. 15, 2024 in English. cited by applicant

Foreign Response for CN Patent Appln. No. 202310425037.8 dated May 14, 2024. cited by applicant

Foreign OA for KR Patent Appln. No. 10-2024-7001408 dated May 13, 2024. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 18768030.1 dated May 6, 2024. cited by applicant

Foreign NOA for IL Patent Appln. No. 296028 dated Apr. 8, 2024 in English. cited by applicant

Foreign OA for CN Patent Appln. No. 202110029355.3 dated May 28, 2024 (with English translation). cited by applicant

Foreign NOA for JP Patent Appln. No. 2023-105887 dated Jun. 3, 2024. cited by applicant

Foreign Exam Report Response for EP Patent Appln. No. 18767086.4 dated Jun. 10, 2024. cited by applicant

Foreign NOA for CN Patent Appln. No. 202310425037.8 dated May 28, 2024. cited by applicant

Foreign OA for CN Patent Appln. No. 202311134808.4 dated Jun. 13, 2024 (with English translation). cited by applicant

Foreign NOA for CN Patent Appln. No. 202210650785.1 dated Jun. 25, 2024. cited by applicant

Foreign Response for KR Patent Appln. No. 10-2024-7001408 dated Jul. 8, 2024. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2018-7025638 dated Jul. 18, 2024. cited by applicant

Foreign Exam Report for EP Patent Appln. No. 21196532.2 dated Jul. 25, 2024. cited by applicant

Notice of Allowance for U.S. Appl. No. 18/237,046 dated Aug. 9, 2024. cited by applicant

Foreign NOA for NZ Patent Appln. No. 744300 dated Aug. 12, 2024. cited by applicant

Notice of Allowance for U.S. Appl. No. 18/237,046 dated Sep. 5, 2024. cited by applicant

Foreign NOA for IL Patent Appln. No. 298822 dated Aug. 29, 2024 in English. cited by applicant

Foreign OA Response for CN Patent Appln. No. 202110029355.3 dated Sep. 27, 2024. cited by applicant

Foreign Response for CN Patent Appln. No. 202311134808.4 dated Oct. 11, 2024. cited by applicant

Foreign OA for CN Patent Appln. No. 202311439457.8 dated Oct. 1, 2024 (with English translation). cited by applicant

Foreign OA for KR Patent Appln. No. 10-2023-7036095 dated Oct. 21, 2024 (with English translation). cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2024-7001408 dated Oct. 28, 2024. cited by applicant

Foreign NOA for JP Patent Appln. No. 2024-24423 dated Nov. 13, 2024. cited by applicant

Foreign NOA for EP Patent Appln. No. 18766694.6 dated Nov. 22, 2024. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2024-7034640 dated Dec. 6, 2024. cited by applicant

Foreign OA Response for KR Patent Appln. No. 10-2023-7036095 dated Dec. 16, 2024. cited by applicant

Foreign NOA for CN Patent Appln. No. 202311134808.4 dated Dec. 15, 2024. cited by applicant

Foreign Response for CN Patent Appln. No. 202311439457.8 dated Jan. 15, 2025. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2022-7041575 dated Oct. 13, 2023. cited by applicant

Foreign NOA for KR Patent Appln. No. 10-2021-7012722 dated Oct. 16, 2023. cited by applicant

Foreign Response for JP Patent Appin. No. 2022-100963 dated Oct. 31, 2023. cited by applicant

Foreign NOA for CN Patent Appln. No. 201880018310.2 dated Oct. 25, 2023. cited by applicant

Foreign NOA for IL Patent Appln. No. 303182 dated Oct. 31, 2023 in English. cited by applicant

Response After Final for U.S. Appl. No. 17/652,964 dated Nov. 10, 2023. cited by applicant

Foreign Response for CN Patent Appln. No. 201880007856.8 dated Nov. 21, 2023. cited by applicant

Foreign OA for IL Patent Appln. No. 298822 dated Sep. 27, 2023. cited by applicant

Foreign NOA for IL Patent Appin. No. 301449 dated Oct. 12, 2023. cited by applicant

Foreign Response for JP Patent Appln. No. 2022-172932 dated Dec. 1, 2023. cited by applicant

Foreign NOA for JP Patent Appln. No. 2022-100963 dated Dec. 4, 2023. cited by applicant

Foreign NOA for JP Patent Appln. No. 2022-172932 dated Dec. 21, 2023. cited by applicant

Foreign NOA for CA Patent Appln. No. 3011377 dated Dec. 15, 2023. cited by applicant

Foreign NOA for CN Patent Appln. No. 201880007856.8 dated Dec. 12, 2023. cited by applicant

Foreign Response for JP Patent Appln. No. 2023-104864 dated Dec. 26, 2023. cited by applicant

Foreign NOA for IL Patent Appln. No. 303275 dated Decmeber 11, 2023 in English. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/652,964 dated Dec. 26, 2023. cited by applicant

Foreign OA for KR Patent Appln. No. 10-2018-7025638 dated Jan. 3, 2024. cited by applicant

Foreign NOA for JP Patent Appln. No. 2023-104864 dated Jan. 23, 2024. cited by applicant

Foreign OA for CN Patent Appln. No. 202310425037.8 dated Jan. 21, 2024. cited by applicant

Foreign Refusal Order for IN Patent Appln. No. 201747032796 dated Jan. 24, 2024 in English. cited by applicant

Foreign Exam Report Response for NZ Patent Appln. No. 744300 dated Feb. 1, 2024. cited by applicant  
Foreign NOA for KR Patent Appln. No. 10-2023-7036095 dated Apr. 29, 2025. cited by applicant  
Foreign NOA for EP Patent Appln. No. 18767086.4 dated May 27, 2025. cited by applicant  
Foreign OA for JP Patent Appln. No. 2024-103818 dated May 20, 2025 (with English translation). cited by applicant

---

*Primary Examiner:* Earles; Bryan

*Attorney, Agent or Firm:* Vista IP Law Group, LLP

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED U.S. PATENT APPLICATIONS (1) The present disclosure is a continuation of pending U.S. patent application Ser. No. 17/813,442, filed Jul. 19, 2022 and entitled “SYSTEMS AND METHODS FOR AUGMENTED REALITY,” which is a continuation of U.S. patent application Ser. No. 17/137,107, filed Dec. 29, 2020 and entitled “SYSTEMS AND METHODS FOR AUGMENTED REALITY,” which is a continuation of U.S. patent application Ser. No. 15/062,104, filed Mar. 5, 2016 and entitled “SYSTEMS AND METHODS FOR AUGMENTED REALITY,” which claims priority to U.S. Provisional Patent Application Ser. No. 62/128,993, filed Mar. 5, 2015 and entitled “ELECTROMAGNETIC TRACKING SYSTEM AND METHOD FOR AUGMENTED REALITY,” and also claims priority to U.S. Provisional Patent Application Ser. No. 62/292,185, filed Feb. 5, 2016 and entitled “SYSTEMS AND METHODS FOR AUGMENTED REALITY,”. The entire contents of the aforementioned patent applications are hereby explicitly incorporated by reference into the present disclosure for all purposes.

## **BACKGROUND**

(1) Modern computing and display technologies have facilitated the development of systems for so called “virtual reality” or “augmented reality” experiences, wherein digitally reproduced images or portions thereof are presented to a user in a manner wherein they seem to be, or may be perceived as, real. A virtual reality, or “VR”, scenario typically involves presentation of digital or virtual image information without transparency to other actual real-world visual input. An augmented reality, or “AR”, scenario typically involves presentation of digital or virtual image information as an augmentation to visualization of the actual world around the user.

(2) For example, referring to FIG. 1, an augmented reality scene 4 is depicted wherein a user of an AR technology sees a real-world park-like setting 6 featuring people, trees, buildings in the background, and a concrete platform 1120. In addition to these items, the user of the AR technology may also perceive a robot statue 1110 standing upon the real-world platform 1120, and a cartoon-like avatar character 2 flying around the park. Of course, the virtual elements 2 and 1110 do not exist in the real world, but the user perceives these virtual objects as being part of, and as interacting with objects of the real world (e.g., 6, 1120, etc.). It should be appreciated, the human visual perception system is very complex, and producing such an AR scene that facilitates a comfortable, natural-feeling, rich presentation of virtual image elements amongst other virtual or real-world imagery elements is challenging.

(3) For instance, head-worn AR displays (e.g., helmet-mounted displays, or smart glasses) may be coupled to a user's head, and thus may move when the user's head moves. If the user's head motions are detected by the display system, the data being displayed can be updated to take the change in head pose into account. The head pose may be utilized to appropriately render virtual content to the user. Thus any small variation may disrupt and/or diminish the delivery or timing of virtual content

that is delivered to the user's AR display.

(4) As an example, if a user wearing a head-worn display views a virtual representation of a three-dimensional (3-D) object on the display and walks around the area where the 3-D object appears, that 3-D object can be re-rendered for each viewpoint, giving the user the perception that he or she is walking around an object that occupies real space. If the head-worn display is used to present multiple objects within a virtual space (for instance, a rich virtual world), measurements of head pose (i.e., the location and orientation of the user's head) can be used to re-render the scene to match the user's dynamically changing head location and orientation, and provide an increased sense of immersion in the virtual space. Similarly, when a user of AR technology is interacting with the virtual world, he or she may use an object or his/her hand to point to objects or to select options. In order for this interaction to occur, localization of the object or the user's hand to an accurate degree is also important. Thus, both head pose, and "hand pose" are both crucial, and localization techniques must be used in order to accurately depict virtual content to the user.

(5) In AR systems, detection and/or calculation of head pose and/or hand pose can facilitate the AR display system to render virtual objects such that they appear to occupy a space in the real world in a manner that is congruent to the objects of the real world. Presenting an AR scene realistically such that the virtual content does not seem jarring/disorienting in relation to one or more real objects improves the user's enjoyment of the AR experience. In addition, detection of the position and/or orientation of a real object, such as a handheld device (which also may be referred to as a "totem"), haptic device, or other real physical object, in relation to the user's head or AR system may also facilitate the display system in presenting display information to the user to enable the user to interact with certain aspects of the AR system efficiently.

(6) It should be appreciated that in AR applications, placement of virtual objects in spatial relation to physical objects (e.g., presented to appear spatially proximate a physical object in two or three dimensions) is a non-trivial problem. For example, head movement may significantly complicate placement of virtual objects in a view of an ambient environment. This may be true whether the view is captured as an image of the ambient environment and then projected or displayed to the end user, or whether the end user perceives the view of the ambient environment directly. For instance, head movement may cause the field of view of the user to change. This may, in turn, require an update to where various virtual objects are displayed in the field of view of the end user. Similarly, movement of the hand (in case of a handheld object) when used to interact with the system provides the same challenge. These movements may be fast and typically need to be accurately detected and localized at a high refresh rate and low latency.

(7) Additionally, head and/or hand movements may occur at a large variety of ranges and speeds. The speed may vary not only between different types of head movements, but within or across the range of a single movement. For instance, speed of head movement may initially increase (e.g., linearly or otherwise) from a starting point, and may decrease as an ending point is reached, obtaining a maximum speed somewhere between the starting and ending points of the head movement. Rapid movements may even exceed the ability of the particular display or projection technology to render images that appear uniform and/or as smooth motion to the end user.

(8) Head or hand tracking accuracy and latency (i.e., the elapsed time between when the user moves his or her head/hand and the time when the image gets updated and displayed to the user) have been challenges for VR and AR systems. Especially for display systems that fill a substantial portion of the user's visual field with virtual elements, it is critical that the accuracy of tracking is high and that the overall system latency is very low from the first detection of motion to the updating of the light that is delivered by the display to the user's visual system. If the latency is high, the system can create a mismatch between the user's vestibular and visual sensory systems, and generate a user perception scenario that can lead to motion sickness or simulator sickness. If the system latency is high, the apparent location of virtual objects may appear unstable during rapid head motions.



(9) In addition to head-worn display systems, other display systems can also benefit from accurate and low-latency head pose detection. These may include head-tracked display systems in which the display is not worn on the user's body, but is, e.g., mounted on a wall or other surface. The head-tracked display may act like a window onto a scene, and as a user moves his head relative to the "window" the scene is re-rendered to match the user's changing viewpoint. Other systems may include a head-worn projection system, in which a head-worn display projects light onto the real world.

(10) Additionally, in order to provide a realistic AR experience, AR systems may be designed to be interactive with the user. For example, multiple users may play a ball game with a virtual ball and/or other virtual objects. One user may "catch" the virtual ball, and throw the ball back to another user. In another embodiment, a first user may be provided with a totem (e.g., a physical "bat" communicatively coupled to the AR system) to hit the virtual ball. In other embodiments, a virtual user interface may be presented to the AR user to allow the user to select one of many options. The user may use totems, haptic devices, wearable components, or simply touch the virtual screen to interact with the system.

(11) Detecting a pose and an orientation of the user (e.g., the user's head and hand), and detecting a physical location of real objects in space may enable the AR system to display virtual content in an effective and enjoyable manner. However, such accurate detection of head and hand pose may be difficult to achieve. In other words, the AR system must recognize a physical location of a real object (e.g., user's head, totem, haptic device, wearable component, user's hand, etc.) and correlate the physical coordinates of the real object to virtual coordinates corresponding to one or more virtual objects being displayed to the user. This process can be improved by highly accurate sensors and sensor recognition systems that track a position and orientation of one or more objects at rapid rates. Current approaches do not perform localization at satisfactory speed or precision standards.

(12) There, thus, is a need for a better localization system in the context of AR and VR devices.

#### SUMMARY

(13) Embodiments of the present invention are directed to devices, systems and methods for facilitating virtual reality and/or augmented reality interaction for one or more users.

(14) In one aspect, an augmented reality (AR) display system comprises an electromagnetic field emitter to emit a known magnetic field, an electromagnetic sensor to measure a parameter related to a magnetic flux measured at the electromagnetic sensor as a result of the emitted known magnetic field, wherein world coordinates of the electromagnetic sensor are known, a controller to determine pose information relative to the electromagnetic field emitter based at least in part on the measure parameter related to the magnetic flux measured at the electromagnetic sensor, and a display system to display virtual content to a user based at least in part on the determined pose information relative to the electromagnetic field emitter.

(15) In one or more embodiments, the electromagnetic field emitter resides in a mobile component of the AR display system. In one or more embodiments, the mobile component is a hand-held component. In one or more embodiments, the mobile component is a totem.

(16) In one or more embodiments, the mobile component is a head-mounted component of the AR display system. In one or more embodiments, the AR display system further comprises a head-mounted component that houses the display system, wherein the electromagnetic sensor is operatively coupled to the head-mounted component. In one or more embodiments, the world coordinates of the electromagnetic sensor is known based at least in part on SLAM analysis performed to determine head pose information, wherein the electromagnetic sensor is operatively coupled to a head-mounted component that houses the display system.

(17) In one or more embodiments, the AR display further comprises one or more cameras operatively coupled to the head-mounted component, and wherein the SLAM analysis is performed based at least on data captured by the one or more cameras. In one or more embodiments, the electromagnetic sensors comprise one or more inertial measurement units (IMUs).

(18) In one or more embodiments, the pose information corresponds to at least a position and orientation of the electromagnetic field emitter relative to the world. In one or more embodiments, the pose information is analyzed to determine world coordinates corresponding to the electromagnetic field emitter. In one or more embodiments, the controller detects an interaction with one or more virtual contents based at least in part on the pose information corresponding to the electromagnetic field emitter.

(19) In one or more embodiments, the display system displays virtual content to the user based at least in part on the detected interaction. In one or more embodiments, the electromagnetic sensor comprises at least three coils to measure magnetic flux in three directions. In one or more embodiments, the at least three coils are housed together at substantially the same location, the electromagnetic sensor being coupled to a head-mounted component of the AR display system.

(20) In one or more embodiments, the at least three coils are housed at different locations of the head-mounted component of the AR display system.

(21) The AR display system of claim 1, further comprising a control and quick release module to decouple the magnetic field emitted by the electromagnetic field emitter. In one or more embodiments, the AR display system further comprises additional localization resources to determine the world coordinates of the electromagnetic field emitter. In one or more embodiments, the additional localization resources comprises a GPS receiver. In one or more embodiments, the additional localization resources comprises a beacon.

(22) In one or more embodiments, the electromagnetic sensor comprises a non-solid ferrite cube. In one or more embodiments, the electromagnetic sensor comprises a stack of ferrite disks. In one or more embodiments, the electromagnetic sensor comprises a plurality of ferrite rods each having a polymer coating. In one or more embodiments, the electromagnetic sensor comprises a time division multiplexing switch.

(23) In another aspect, a method to display augmented reality comprises emitting, through an electromagnetic field emitter, a known magnetic field, measuring, through an electromagnetic sensor, a parameter related to a magnetic flux measured at the electromagnetic sensor as a result of the emitted known magnetic field, wherein world coordinates of the electromagnetic sensor are known, determining pose information relative to the electromagnetic field emitter based at least in part on the measured parameter related to the magnetic flux measured at the electromagnetic sensor, and displaying virtual content to a user based at least in part on the determined pose information relative to the electromagnetic field emitter.

(24) In one or more embodiments, the electromagnetic field emitter resides in a mobile component of the AR display system. In one or more embodiments, the mobile component is a hand-held component. In one or more embodiments, the mobile component is a totem. In one or more embodiments, the mobile component is a head-mounted component of the AR display system.

(25) In one or more embodiments, the method further comprises housing the display system in a head-mounted component, wherein the electromagnetic sensor is operatively coupled to the head-mounted component. In one or more embodiments, the world coordinates of the electromagnetic sensor is known based at least in part on SLAM analysis performed to determine head pose information, wherein the electromagnetic sensor is operatively coupled to a head-mounted component that houses the display system.

(26) In one or more embodiments, further comprises capturing image data through one or more cameras that are operatively coupled to the head-mounted component, and wherein the SLAM analysis is performed based at least on data captured by the one or more cameras. In one or more embodiments, the electromagnetic sensors comprise one or more inertial measurement units (IMUs).

(27) In one or more embodiments, the pose information corresponds to at least a position and orientation of the electromagnetic field emitter relative to the world. In one or more embodiments, the pose information is analyzed to determine world coordinates corresponding to the

electromagnetic field emitter. In one or more embodiments, the method further comprises detecting an interaction with one or more virtual contents based at least in part on the pose information corresponding to the electromagnetic field emitter.

(28) In one or more embodiments, the method further comprises displaying virtual content to the user based at least in part on the detected interaction. In one or more embodiments, the electromagnetic sensor comprises at least three coils to measure magnetic flux in three directions. In one or more embodiments, the at least three coils are housed together at substantially the same location, the electromagnetic sensor being coupled to a head-mounted component of the AR display system. In one or more embodiments, the at least three coils are housed at different locations of the head-mounted component of the AR display system.

(29) In one or more embodiments, the method further comprises decoupling the magnetic field emitted by the electromagnetic field emitter through a control and quick release module. In one or more embodiments, the method further comprises determining the world coordinates of the electromagnetic field emitter through additional localization resources. In one or more embodiments, the additional localization resources comprises a GPS receiver. In one or more embodiments, the additional localization resources comprises a beacon.

(30) In yet another aspect, an augmented reality display system, comprises a handheld component housing an electromagnetic field emitter, the electromagnetic field emitter emitting a known magnetic field, a head mounted component having a display system that displays virtual content to a user, the head mounted component coupled to one or more electromagnetic sensors that detect the magnetic field emitted by the electromagnetic field emitter housed in the handheld component, wherein a head pose is known, and a controller communicatively coupled to the handheld component and the head mounted component, the controller receiving magnetic field data from the handheld component, and receiving sensor data from the head mounted component, wherein the controller determines a hand pose based at least in part on the received magnetic field data and the received sensor data, wherein the display system modifies the virtual content displayed to the user based at least in part on the determined hand pose.

(31) In one or more embodiments, the handheld component is mobile. In one or more embodiments, the handheld component is a totem. In one or more embodiments, the handheld component is a gaming component. In one or more embodiments, the head pose is known based at least in part on SLAM analysis.

(32) In one or more embodiments, the AR display system further comprises one or more cameras operatively coupled to the head-mounted component, and wherein the SLAM analysis is performed based at least on data captured by the one or more cameras. In one or more embodiments, the electromagnetic sensor comprises one or more inertial measurement units (IMUs).

(33) In one or more embodiments, the head pose corresponds to at least a position and orientation of the electromagnetic sensor relative to the world. In one or more embodiments, the hand pose is analyzed to determine world coordinates corresponding to the handheld component. In one or more embodiments, the controller detects an interaction with one or more virtual contents based at least in part on the determined hand pose.

(34) In one or more embodiments, the display system displays the virtual content to the user based at least in part on the detected interaction. In one or more embodiments, the electromagnetic sensor comprises at least three coils to measure magnetic flux in three directions. In one or more embodiments, the at least three coils are housed together at substantially the same location. In one or more embodiments, the at least three coils are housed at different locations of the head-mounted component.

(35) In one or more embodiments, the AR display system further comprises a control and quick release module to decouple the magnetic field emitted by the electromagnetic field emitter. In one or more embodiments, the AR display system further comprises additional localization resources to determine the hand pose. In one or more embodiments, the additional localization resources

comprises a GPS receiver. In one or more embodiments, the additional localization resources comprises a beacon.

(36) Additional and other objects, features, and advantages of the invention are described in the detail description, figures and claims.

(37) Additional and other objects, features, and advantages of the invention are described in the detail description, figures and claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The drawings illustrate the design and utility of various embodiments of the present invention. It should be noted that the figures are not drawn to scale and that elements of similar structures or functions are represented by like reference numerals throughout the figures. In order to better appreciate how to obtain the above-recited and other advantages and objects of various embodiments of the invention, a more detailed description of the present inventions briefly described above will be rendered by reference to specific embodiments thereof, which are illustrated in the accompanying drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

(2) FIG. 1 illustrates a plan view of an AR scene displayed to a user of an AR system according to one embodiment.

(3) FIGS. 2A-2D illustrate various embodiments of wearable AR devices

(4) FIG. 3 illustrates an example embodiment of a user of a wearable AR device interacting with one or more cloud servers of the AR system.

(5) FIG. 4 illustrates an example embodiment of an electromagnetic tracking system.

(6) FIG. 5 illustrates an example method of determining a position and orientation of sensors, according to one example embodiment.

(7) FIG. 6 illustrates an example diagram of utilizing an electromagnetic tracking system to determine head pose.

(8) FIG. 7 illustrates an example method of delivering virtual content to a user based on detected head pose.

(9) FIG. 8 illustrates a schematic view of various components of an AR system according to one embodiment having an electromagnetic transmitter and electromagnetic sensors.

(10) FIGS. 9A-9F illustrate various embodiments of the control and quick release module.

(11) FIG. 10 illustrates one simplified embodiment of the AR device.

(12) FIGS. 11A and 11B illustrate various embodiments of placement of the electromagnetic sensors on the head-mounted AR system.

(13) FIGS. 12A-12E illustrate various embodiments of a ferrite cube to be coupled to the electromagnetic sensors.

(14) FIG. 13A-13C illustrate various embodiments of circuitry of the electromagnetic sensors.

(15) FIG. 14 illustrates an example method of using an electromagnetic tracking system to detect head and hand pose.

(16) FIG. 15 illustrates another example method of using an electromagnetic tracking system to detect head and hand pose.

### DETAILED DESCRIPTION

(17) Referring to FIGS. 2A-2D, some general componentry options are illustrated. In the portions of the detailed description which follow the discussion of FIGS. 2A-2D, various systems, subsystems, and components are presented for addressing the objectives of providing a high-

quality, comfortably-perceived display system for human VR and/or AR.

(18) As shown in FIG. 2A, an AR system user **60** is depicted wearing a head mounted component **58** featuring a frame **64** structure coupled to a display system **62** positioned in front of the eyes of the user. A speaker **66** is coupled to the frame **64** in the depicted configuration and positioned adjacent the ear canal of the user (in one embodiment, another speaker, not shown, is positioned adjacent the other ear canal of the user to provide for stereo/shapeable sound control). The display **62** may be operatively coupled **68**, such as by a wired lead or wireless connectivity, to a local processing and data module **70** which may be mounted in a variety of configurations, such as fixedly attached to the frame **64**, fixedly attached to a helmet or hat **80** as shown in the embodiment of FIG. 2B, embedded in headphones, removably attached to the torso **82** of the user **60** in a backpack-style configuration as shown in the embodiment of FIG. 2C, or removably attached to the hip **84** of the user **60** in a belt-coupling style configuration as shown in the embodiment of FIG. 2D.

(19) The local processing and data module **70** may comprise a power-efficient processor or controller, as well as digital memory, such as flash memory, both of which may be utilized to assist in the processing, caching, and storage of data, which may be (a) captured from sensors which may be operatively coupled to the frame **64**, such as image capture devices (such as cameras), microphones, inertial measurement units, accelerometers, compasses, GPS units, radio devices, and/or gyros; and/or (b) acquired and/or processed using the remote processing module **72** and/or remote data repository **74**, possibly for passage to the display **62** after such processing or retrieval. The local processing and data module **70** may be operatively coupled (**76, 78**), such as via a wired or wireless communication links, to the remote processing module **72** and remote data repository **74** such that these remote modules (**72, 74**) are operatively coupled to each other and available as resources to the local processing and data module **70**.

(20) In one embodiment, the remote processing module **72** may comprise one or more relatively powerful processors or controllers configured to analyze and process data and/or image information. In one embodiment, the remote data repository **74** may comprise a relatively large-scale digital data storage facility, which may be available through the internet or other networking configuration in a “cloud” resource configuration. In one embodiment, all data may be stored and all computation may be performed in the local processing and data module, allowing fully autonomous use from any remote modules.

(21) Referring now to FIG. 3, a schematic illustrates coordination between the cloud computing assets **46** and local processing assets, which may, for example reside in head mounted componentry **58** coupled to the user's head **120** and a local processing and data module **70**, coupled to the user's belt **308**; therefore the component **70** may also be termed a “belt pack” **70**, as shown in FIG. 3. In one embodiment, the cloud **46** assets, such as one or more cloud server systems **110** are operatively coupled **115**, such as via wired or wireless networking (wireless being preferred for mobility, wired being preferred for certain high-bandwidth or high-data-volume transfers that may be desired), directly to (**40, 42**) one or both of the local computing assets, such as processor and memory configurations, coupled to the user's head **120** and belt **308** as described above. These computing assets local to the user may be operatively coupled to each other as well, via wired and/or wireless connectivity configurations **44**, such as the wired coupling **68** discussed below in reference to FIG. 8. In one embodiment, to maintain a low-inertia and small-size subsystem mounted to the user's head **120**, primary transfer between the user and the cloud **46** may be via the link between the subsystem mounted at the belt **308** and the cloud, with the head mounted subsystem **120** primarily data-tethered to the belt-based subsystem **308** using wireless connectivity, such as ultra-wideband (“UWB”) connectivity, as is currently employed, for example, in personal computing peripheral connectivity applications.

(22) With efficient local and remote processing coordination, and an appropriate display device for a user, such as the user interface or user display system **62** shown in FIG. 2A, or variations thereof,

aspects of one world pertinent to a user's current actual or virtual location may be transferred or "passed" to the user and updated in an efficient fashion. In other words, a map of the world may be continually updated at a storage location which may partially reside on the user's AR system and partially reside in the cloud resources. The map (also referred to as a "passable world model") may be a large database comprising raster imagery, 3-D and 2-D points, parametric information and other information about the real world. As more and more AR users continually capture information about their real environment (e.g., through cameras, sensors, IMUs, etc.), the map becomes more and more accurate and complete.

(23) With a configuration as described above, wherein there is one "model" of the world that can reside on cloud computing resources and be distributed from the cloud server, such a world can be "passable" to one or more users in a relatively low bandwidth form. This may be preferable to transferring real-time video data or similar complex information from one AR system to another. The augmented experience of the person standing near the statue (i.e., as shown in FIG. 1) may be informed by the cloud-based world model, a subset of which may be passed down to the person's local display device to complete the view. A person sitting at a remote display device (e.g., a personal computer sitting on a desk), can efficiently download that same section of information from the cloud and have it rendered on the personal computer display. In yet another embodiment, yet another user may be present in real-time at the park, and may take a walk in that park, with a friend (e.g., the person at the personal computer) joining the user through a shared AR and/or VR experience. In order to render the park scene to the friend, the AR system may detect a location of the street, a location of the trees in the park, a location of the statue, etc. This location may be uploaded to the passable world model in the cloud, and the friend (at the personal computer) can download the portion of the passable world from the cloud, and then start "walking along" with the AR user in the park. Of course, in some embodiments, the friend may be rendered as an avatar in the passable world model to the AR user in the park such that the AR user can walk alongside the virtual friend in the park.

(24) More particularly, in order to capture details of the world such that it can be passed on to the cloud (and subsequently to other AR users) 3-D points pertaining to various objects may be captured from the environment, and the pose (i.e., vector and/or origin position information relative to the world) of the cameras that capture those images or points may be determined. These 3-D points may be "tagged", or associated, with this pose information. It should be appreciated that there may be a large number of AR systems capturing the same points in any given environment. For example, points captured by a second camera (of a second AR system) may be utilized to determine the head pose of the second camera. In other words, one can orient and/or localize a second camera based upon comparisons with tagged images from a first camera. Then, this information may be utilized to extract textures, make maps, and create one or more virtual copies of the real world.

(25) In one or more embodiments, the AR system can be utilized to capture both 3-D points and the 2-D images that produced the points. As discussed above, these points and images may be sent out to the cloud storage and processing resource (e.g., the servers **110** of FIG. 3), in some embodiments. In other embodiments, this information may be cached locally with embedded pose information (i.e., the tagged images) such that tagged 2-D images are sent to the cloud along with 3-D points. If a user is observing a dynamic scene, the user may also send additional information up to the cloud servers. In one or more embodiments, object recognizers may run (either on the cloud resource or on the local system) in order to recognize one or more objects in the captured points. More information on object recognizers and the passable world model may be found in U.S. patent application Ser. No. 14/205,126, entitled "SYSTEM AND METHOD FOR AUGMENTED AND VIRTUAL REALITY", which is incorporated by reference in its entirety herein, along with the following additional disclosures, which related to augmented and virtual reality systems such as those developed by Magic Leap, Inc. of Fort Lauderdale, Florida: U.S. patent application Ser. No.

14/641,376; U.S. patent application Ser. No. 14/555,585; U.S. patent application Ser. No. 14/212,961; U.S. patent application Ser. No. 14/690,401; U.S. patent application Ser. No. 13/663,466; and U.S. patent application Ser. No. 13/684,489.

(26) In order to capture points that can be used to create the “passable world model,” it is helpful to accurately know the user's location, pose and orientation with respect to the world. More particularly, the user's position must be localized to a granular degree, because it may be important to know the user's head pose, as well as hand pose (if the user is clutching a handheld component, gesturing, etc.). In one or more embodiments, GPS and other localization information may be utilized as inputs to such processing. Highly accurate localization of the user's head, totems, hand gestures, haptic devices etc. are desirable in processing images and points derived from a particular AR system, and also in order to displaying appropriate virtual content to the user.

(27) One approach to achieve high precision localization may involve the use of an electromagnetic field coupled with electromagnetic sensors that are strategically placed on the user's AR head set, belt pack, and/or other ancillary devices (e.g., totems, haptic devices, gaming instruments, etc.). Electromagnetic tracking systems typically comprise at least an electromagnetic field emitter and at least one electromagnetic field sensor. The electromagnetic sensors may measure electromagnetic fields with a known distribution. Based on these measurements a position and orientation of a field sensor relative to the emitter is determined.

(28) Referring now to FIG. 4, an example system of an electromagnetic tracking system (e.g., such as those developed by organizations such as the Biosense® division of Johnson & Johnson Corporation, Polhemus®, Inc. of Colchester, Vermont, and manufactured by Sixense® Entertainment, Inc. of Los Gatos, California, and other tracking companies) is illustrated. In one or more embodiments, the electromagnetic tracking system comprises an electromagnetic field emitter **402** which is configured to emit a known magnetic field. As shown in FIG. 4, the electromagnetic field emitter **402** may be coupled to a power supply **410** (e.g., electric current, batteries, etc.) to provide power to the electromagnetic field emitter **402**.

(29) In one or more embodiments, the electromagnetic field emitter **402** comprises several coils (e.g., at least three coils positioned perpendicular to each other to produce a field in the x, y and z directions) that generate magnetic fields. These magnetic fields are used to establish a coordinate space. This may allow the system to map a position of the sensors **404** in relation to the known magnetic field, which, in turn, helps determine a position and/or orientation of the sensors **404**. In one or more embodiments, the electromagnetic sensors **404a**, **404b**, etc. may be attached to one or more real objects. The electromagnetic sensors **404** may comprise smaller coils in which current may be induced through the emitted electromagnetic field. Generally, the “sensor” components **404** may comprise small coils or loops, such as a set of three differently-oriented (i.e., such as orthogonally oriented relative to each other) coils coupled together within a small structure such as a cube or other container, that are positioned/oriented to capture incoming magnetic flux from the magnetic field emitted by the electromagnetic emitter **402**. By comparing currents induced through these coils, and by knowing the relative position and orientation of the coils relative to each other, a relative position and orientation of a sensor **404** relative to the electromagnetic emitter **402** may be calculated.

(30) One or more parameters pertaining to a behavior of the coils in the electromagnetic tracking sensors **404** and the inertial measurement unit (“IMU”) components operatively coupled to the electromagnetic tracking sensors **404** may be measured in order to detect a position and/or orientation of the sensor **404** (and the object to which it is attached to) relative to a coordinate system to which the electromagnetic field emitter **402** is coupled. Of course this coordinate system may be translated into a world coordinate system, in order to determine a location or pose of the electromagnetic field emitter in the real world. In one or more embodiments, multiple sensors **404** may be used in relation to the electromagnetic emitter **402** to detect a position and orientation of each of the sensors **404** within the coordinate space associated with the electromagnetic field

emitter **402**.

(31) It should be appreciated that in some embodiments, head pose may already be known based on sensors on the headmounted component of the AR system, and SLAM analysis performed based on sensor data and image data captured through the headmounted AR system. However, it may be important to know a position of the user's hand (e.g., a handheld component like a totem, etc.) relative to the known head pose. In other words, it may be important to know a hand pose relative to the head pose. Once the relationship between the head (assuming the sensors are placed on the headmounted component) and hand is known, a location of the hand relative to the world (e.g., world coordinates) can be easily calculated.

(32) In one or more embodiments, the electromagnetic tracking system may provide 3-D positions (i.e., X, Y and Z directions) of the sensors **404**, and may further provide location information of the sensors **404** in two or three orientation angles. In one or more embodiments, measurements of the IMUs may be compared to the measurements of the coil to determine a position and orientation of the sensors **404**. In one or more embodiments, both electromagnetic (EM) data and IMU data, along with various other sources of data, such as cameras, depth sensors, and other sensors, may be combined to determine the position and orientation of the electromagnetic sensors **404**.

(33) In one or more embodiments, this information may be transmitted (e.g., wireless communication, Bluetooth, etc.) to a controller **406**. In one or more embodiments, pose information (e.g., position and orientation) corresponding to the sensors **404** may be reported at a relatively high refresh rate to the controller **406**. Conventionally, an electromagnetic emitter **402** may be coupled to a relatively stable and large object, such as a table, operating table, wall, or ceiling, etc. and one or more sensors **404** may be coupled to smaller objects, such as medical devices, handheld gaming components, totems, frame of the head-mounted AR system, or the like.

(34) Alternatively, as described below in reference to FIG. 6, various features of the electromagnetic tracking system may be employed to produce a configuration wherein changes or deltas in position and/or orientation between two objects that move in space relative to a more stable global coordinate system may be tracked. In other words, a configuration is shown in FIG. 6 wherein a variation of an electromagnetic tracking system may be utilized to track position and orientation changes between a head-mounted component and a hand-held component, while head pose relative to the global coordinate system (say of the room environment local to the user) is determined otherwise, such as by simultaneous localization and mapping ("SLAM") techniques using outward-capturing cameras which may be coupled to the head mounted component of the AR system.

(35) Referring back to FIG. 4, the controller **406** may control the electromagnetic field emitter **402**, and may also capture measurement data from the various electromagnetic sensors **404**. It should be appreciated that the various components of the system may be coupled to each other through any electro-mechanical or wireless/Bluetooth means. The controller **406** may also store data regarding the known magnetic field, and the coordinate space in relation to the magnetic field. This information may then be used to detect the position and orientation of the sensors **404** in relation to the coordinate space corresponding to the known electromagnetic field, which can then be used to determine world coordinates of the user's hand (e.g., location of the electromagnetic emitter).

(36) One advantage of electromagnetic tracking systems is that they can produce highly accurate tracking results with minimal latency and high resolution. Additionally, the electromagnetic tracking system does not necessarily rely on optical trackers, thereby making it easier to track sensors/objects that are not in the user's line-of-vision.

(37) It should be appreciated that the strength of the electromagnetic field ("v") drops as a cubic function of distance ("r") from a coil transmitter (e.g., electromagnetic field emitter **402**). One or more algorithms may be formulated based on a distance of the sensors from the electromagnetic field emitter. The controller **406** may be configured with such algorithms to determine a position and orientation of the sensor/object at varying distances away from the electromagnetic field



emitter. Given the rapid decline of the strength of the electromagnetic field as one moves farther away from the electromagnetic emitter, improved results, in terms of accuracy, efficiency and low latency, may be achieved at closer distances. In typical electromagnetic tracking systems, the electromagnetic field emitter is powered by electric current (e.g., plug-in power supply) and has sensors located within a 20 ft. radius away from the electromagnetic field emitter. A shorter radius between the sensors and field emitter may be more desirable in many applications, including AR applications.

(38) Referring now to FIG. 5, an example flowchart describing a functioning of a typical electromagnetic tracking system is briefly described. At **502**, a known electromagnetic field is emitted. In one or more embodiments, the electromagnetic field emitter may generate a magnetic field. In other words, each coil of the emitter may generate an electric field in one direction (e.g., x, y or z). The magnetic fields may be generated with an arbitrary waveform. In one or more embodiments, each of the axes may oscillate at a slightly different frequency.

(39) At **504**, a coordinate space corresponding to the electromagnetic field may be determined. For example, the controller **406** of FIG. 4 may automatically determine a coordinate space around the electromagnetic emitter based on parameters of the electromagnetic field. At **506**, a behavior of the coils at the sensors (which may be attached to a known object) may be detected/measured. For example, a current induced at the coils may be measured. In other embodiments, a rotation of a coil, or other quantifiable behavior may be tracked and measured. At **508**, this measurement may be used to determine/calculate a position and orientation of the sensor(s) and/or known object. For example, the controller may consult a mapping table that correlates a behavior of the coils at the sensors to various positions or orientations. Based on these calculations, the position and orientation of the sensors (or object attached thereto) within the coordinate space may be determined. In some embodiments, the pose/location information may be determined at the sensors. In other embodiment, the sensors communicate data detected at the sensors to the controller, and the controller may consult the mapping table to determined pose information relative to the known magnetic field (e.g., coordinates relative to the handheld component).

(40) In the context of AR systems, one or more components of the electromagnetic tracking system may need to be modified in order to facilitate accurate tracking of mobile components. As described above, tracking the user's head pose and orientation is helpful in many AR applications. Accurate determination of the user's head pose and orientation allows the AR system to display the right virtual content to the user in the appropriate position in the AR display. For example, the virtual scene may comprise a monster hiding behind a real building. Depending on the pose and orientation of the user's head in relation to the building, the view of the virtual monster may need to be modified such that a realistic AR experience is provided.

(41) In other embodiments, a position and/or orientation of a totem, haptic device or some other means of interacting with a virtual content may be important in enabling the AR user to interact with the AR system. For example, in many gaming applications, the AR system must detect a position and orientation of a real object in relation to virtual content. Or, when displaying a virtual interface, a position of a totem, user's hand, haptic device or any other real object configured for interaction with the AR system must be known in relation to the displayed virtual interface in order for the system to understand a command, etc. Conventional localization methods including optical tracking and other methods are typically plagued with high latency and low resolution problems, which makes rendering virtual content challenging in many AR applications.

(42) In one or more embodiments, the electromagnetic tracking system, discussed above may be adapted to the AR system to detect position and orientation of one or more objects in relation to an emitted electromagnetic field. Typical electromagnetic systems tend to have large and bulky electromagnetic emitters (e.g., **402** in FIG. 4), which may make them less-than-ideal for use in AR applications. However, smaller electromagnetic emitters (e.g., in the millimeter range) may be used to emit a known electromagnetic field in the context of the AR system.

(43) Referring now to FIG. 6, an electromagnetic tracking system may be incorporated into an AR system as shown, with an electromagnetic field emitter **602** incorporated as part of a hand-held controller **606**. In one or more embodiments, the hand-held controller may be a totem to be used in a gaming application. In other embodiments, the hand-held controller may be a haptic device that may be used to interact with the AR system (e.g., via a virtual user interface). In yet other embodiments, the electromagnetic field emitter may simply be incorporated as part of the belt pack **70**, as shown in FIG. 2D. The hand-held controller **606** may comprise a battery **610** or other power supply that powers the electromagnetic field emitter **602**.

(44) It should be appreciated that the electromagnetic field emitter **602** may also comprise or be coupled to an IMU component **650** that is configured to assist in determining position and/or orientation of the electromagnetic field emitter **602** relative to other components. This may be useful in cases where both the electromagnetic field emitter **602** and the sensors **604** (discussed in further detail below) are mobile. In some embodiments, placing the electromagnetic field emitter **602** in the hand-held controller rather than the belt pack, as shown in the embodiment of FIG. 6, ensures that the electromagnetic field emitter does not compete for resources at the belt pack, but rather uses its own battery source at the hand-held controller **606**.

(45) In one or more embodiments, electromagnetic sensors **604** may be placed on one or more locations on the user's headset **58**, along with other sensing devices such as one or more IMUs or additional magnetic flux capturing coils **608**. For example, as shown in FIG. 6, sensors **604**, **608** may be placed on either side of the head set **58**. Since these sensors **604**, **608** are engineered to be rather small (and hence may be less sensitive, in some cases), it may be important to include multiple sensors in order to improve efficiency and precision of the measurements.

(46) In one or more embodiments, one or more sensors **604**, **608** may also be placed on the belt pack **620** or any other part of the user's body. The sensors **604**, **608** may communicate wirelessly or through Bluetooth® with a computing apparatus **607** (e.g., the controller) that determines a pose and orientation of the sensors **604**, **608** (and the AR headset **58** to which they are attached) in relation to the known magnetic field emitted by the electromagnetic field emitter **602**. In one or more embodiments, as shown in FIG. 6, the computing apparatus **607** may reside at the belt pack **620**. In other embodiments, the computing apparatus **607** may reside at the headset **58** itself, or even the hand-held controller **604**. In one or more embodiments, the computing apparatus **607** may receive the measurements of the sensors **604**, **608**, and determine a position and orientation of the sensors **604**, **608** in relation to the known electromagnetic field emitted by the electromagnetic field emitter **602**.

(47) In one or more embodiments, a mapping database **632** may be consulted to determine the location coordinates of the sensors **604**, **608**. The mapping database **632** may reside in the belt pack **620** in some embodiments. In the illustrated embodiment, the mapping database **632** resides on a cloud resource **630**. As shown in FIG. 6, the computing apparatus **607** communicates wirelessly to the cloud resource **630**. The determined pose information in conjunction with points and images collected by the AR system may then be communicated to the cloud resource **630**, and then be added to the passable world model **634**.

(48) As described above, conventional electromagnetic emitters may be too bulky for use in AR devices. Therefore, the electromagnetic field emitter may be engineered to be compact, using smaller coils compared to traditional systems. However, given that the strength of the electromagnetic field decreases as a cubic function of the distance away from the field emitter, a shorter radius between the electromagnetic sensors **604** and the electromagnetic field emitter **602** (e.g., about 3-3.5 ft.) may reduce power consumption while maintaining acceptable field strength when compared to conventional systems such as the one detailed in FIG. 4.

(49) In one or more embodiments, this feature may be utilized to prolong the life of the battery **610** that powers the controller **606** and the electromagnetic field emitter **602**. Alternatively, this feature may be utilized to reduce the size of the coils generating the magnetic field at the electromagnetic

field emitter **602**. However, in order to get the same strength of magnetic field, the power of the electromagnetic field emitter **602** may need to be increased. This allows for an electromagnetic field emitter unit **602** that may fit compactly at the hand-held controller **606**.

(50) Several other changes may be made when using the electromagnetic tracking system for AR devices. In one or more embodiments, IMU-based pose tracking may be used. In such embodiments, maintaining the IMUs as stable as possible increases an efficiency of the pose detection process. The IMUs may be engineered such that they remain stable up to 50-100 milliseconds, which results in stable signals with pose update/reporting rates of 10-20 Hz. It should be appreciated that some embodiments may utilize an outside pose estimator module (because IMUs may drift over time) that may enable pose updates to be reported at a rate of 10-20 Hz. By keeping the IMUs stable for a reasonable amount of time, the rate of pose updates may be dramatically decreased to 10-20 Hz (as compared to higher frequencies in conventional systems).

(51) Yet another way to conserve power of the AR system may be to run the electromagnetic tracking system at a 10% duty cycle (e.g., only pinging for ground every 100 milliseconds). In other words, the electromagnetic tracking system operates for 10 milliseconds out of every 100 milliseconds to generate a pose estimate. This directly translates to power savings, which may, in turn, affect size, battery life and cost of the AR device.

(52) In one or more embodiments, this reduction in duty cycle may be strategically utilized by providing two hand-held controllers (not shown) rather than just one. For example, the user may be playing a game that requires two totems, etc. Or, in a multi-user game, two users may have their own totems/hand-held controllers to play the game. When two controllers (e.g., symmetrical controllers for each hand) are used rather than one, the controllers may operate at offset duty cycles. The same concept may also be applied to controllers utilized by two different users playing a multi-player game, for example.

(53) Referring now to FIG. 7, an example flow chart describing the electromagnetic tracking system in the context of AR devices is described. At **702**, the hand-held controller **606** emits a magnetic field. At **704**, the electromagnetic sensors **604** (placed on headset **58**, belt pack **620**, etc.) detect the magnetic field. At **706**, a position and orientation of the headset/belt is determined based on a behavior of the coils/IMUs **608** at the sensors **604**. In some embodiments, the detected behavior of the sensors **604** is communicated to the computing apparatus **607**, which in turn determines the position and orientation of the sensors **604** in relation to the electromagnetic field (e.g., coordinates relative to the hand-held component). Of course, it should be appreciated that these coordinates may then be converted to world coordinates, since the head pose relative to the world may be known through SLAM processing, as discussed above.

(54) At **708**, the pose information is conveyed to the computing apparatus **607** (e.g., at the belt pack **620** or headset **58**). At **710**, optionally, the passable world model **634** may be consulted determine virtual content to be displayed to the user based on the determined head pose and hand pose. At **712**, virtual content may be delivered to the user at the AR headset **58** based on the correlation. It should be appreciated that the flowchart described above is for illustrative purposes only, and should not be read as limiting.

(55) Advantageously, using an electromagnetic tracking system similar to the one outlined in FIG. 6 enables pose tracking at a higher refresh rate and lower latency (e.g., head position and orientation, position and orientation of totems, and other controllers). This allows the AR system to project virtual content with a higher degree of accuracy, and with lower latency when compared to optical tracking techniques for calculating pose information.

(56) Referring to FIG. 8, a system configuration is illustrated featuring many sensing components, similar to the sensors described above. It should be appreciated that the reference numbers of FIGS. 2A-2D, and FIG. 6 are repeated in FIG. 8. A head mounted wearable component **58** is shown operatively coupled **68** to a local processing and data module **70**, such as a belt pack (similar to FIG. 2D), here using a physical multicore lead which also features a control and quick release

module **86** as described below in reference to FIGS. **9A-9F**. The local processing and data module **70** may be operatively coupled **100** to a hand held component **606** (similar to FIG. **6**). In one or more embodiments, the local processing module **70** may be coupled to the hand-held component **606** through a wireless connection such as low power Bluetooth®. In one or more embodiments, the hand held component **606** may also be operatively coupled **94** directly to the head mounted wearable component **58**, such as by a wireless connection such as low power Bluetooth®.

(57) Generally, where IMU data is passed in order to detect pose information of various components, a high-frequency connection may be desirable, such as in the range of hundreds or thousands of cycles/second or higher. On the other hand, tens of cycles per second may be adequate for electromagnetic localization sensing, such as by the sensor **604** and transmitter **602** pairings. Also shown is a global coordinate system **10**, representative of fixed objects in the real world around the user, such as a wall **8**. Cloud resources **46** also may be operatively coupled **42, 40, 88, 90** to the local processing and data module **70**, to the head mounted wearable component **58**, to resources which may be coupled to the wall **8** or other item fixed relative to the global coordinate system **10**, respectively. The resources coupled to the wall **8** or having known positions and/or orientations relative to the global coordinate system **10** may include a Wi-Fi transceiver **114**, an electromagnetic emitter **602** and/or receiver **604**, a beacon or reflector **112** configured to emit or reflect a given type of radiation, such as an infrared LED beacon, a cellular network transceiver **110**, a RADAR emitter or detector **108**, a LIDAR emitter or detector **106**, a GPS transceiver **118**, a poster or marker having a known detectable pattern **122**, and a camera **124**.

(58) The head mounted wearable component **58** features similar components, as illustrated, in addition to lighting emitters **130** configured to assist the camera **124** detectors, such as infrared emitters **130** for an infrared camera **124**. In one or more embodiments, the head mounted wearable component **58** may further comprise one or more strain gauges **116**, which may be fixedly coupled to the frame or mechanical platform of the head mounted wearable component **58** and configured to determine deflection of such platform in between components such as electromagnetic receiver sensors **604** or display elements **62**, wherein it may be valuable to understand if bending of the platform has occurred, such as at a thinned portion of the platform, such as the portion above the nose on the eyeglasses-like platform depicted in FIG. **8**.

(59) The head mounted wearable component **58** may also include a processor **128** and one or more IMUs **102**. Each of the components preferably are operatively coupled to the processor **128**. The hand held component **606** and local processing and data module **70** are illustrated featuring similar components. As shown in FIG. **8**, with so many sensing and connectivity means, such a system is likely to be heavy, large, relatively expensive, and likely to consume large amounts of power. However, for illustrative purposes, such a system may be utilized to provide a very high level of connectivity, system component integration, and position/orientation tracking. For example, with such a configuration, the various main mobile components (**58, 70, 606**) may be localized in terms of position relative to the global coordinate system using Wi-Fi, GPS, or Cellular signal triangulation; beacons, electromagnetic tracking (as described above), RADAR, and LIDIR systems may provide yet further location and/or orientation information and feedback. Markers and cameras also may be utilized to provide further information regarding relative and absolute position and orientation. For example, the various camera components **124**, such as those shown coupled to the head mounted wearable component **58**, may be utilized to capture data which may be utilized in simultaneous localization and mapping protocols, or “SLAM”, to determine where the component **58** is and how it is oriented relative to other components.

(60) Referring to FIGS. **9A-9F**, various aspects of the control and quick release module **86** are depicted. Referring to FIG. **9A**, two outer housing **134** components are coupled together using a magnetic coupling configuration which may be enhanced with mechanical latching. Buttons **136** for operation of the associated system may be included. FIG. **9B** illustrates a partial cutaway view with the buttons **136** and underlying top printed circuit board **138** shown. Referring to FIG. **9C**,

with the buttons **136** and underlying top printed circuit board **138** removed, a female contact pin array **140** is visible. Referring to FIG. **9D**, with an opposite portion of housing **134** removed, the lower printed circuit board **142** is visible. With the lower printed circuit board **142** removed, as shown in FIG. **9E**, a male contact pin array **144** is visible.

(61) Referring to the cross-sectional view of FIG. **9F**, at least one of the male pins or female pins are configured to be spring-loaded such that they may be depressed along each pin's longitudinal axis. In one or more embodiments, the pins may be termed “pogo pins” and may generally comprise a highly conductive material, such as copper or gold. When assembled, the illustrated configuration may mate **46** male pins with female pins, and the entire assembly may be quick-release decoupled in half by manually pulling it apart and overcoming a magnetic interface **146** load which may be developed using north and south magnets oriented around the perimeters of the pin arrays **140**, **144**.

(62) In one embodiment, an approximate 2 kg load from compressing the 46 pogo pins is countered with a closure maintenance force of about 4 kg. The pins in the arrays **140**, **144** may be separated by about 1.3 mm, and the pins may be operatively coupled to conductive lines of various types, such as twisted pairs or other combinations to support USB 3.0, HDMI 2.0, I2S signals, GPIO, and MIPI configurations, and high current analog lines and grounds configured for up to about 4 amps/5 volts in one embodiment.

(63) Referring to FIG. **10**, it is helpful to have a minimized component/feature set to be able to minimize the weight and bulk of the various components, and to arrive at a relatively slim head mounted component, for example, such as that of head mounted component **58** featured in FIG. **10**. Thus various permutations and combinations of the various components shown in FIG. **8** may be utilized.

(64) Referring to FIG. **11A**, an electromagnetic sensing coil assembly (**604**, e.g., 3 individual coils coupled to a housing) is shown coupled to a head mounted component **58**. Such a configuration adds additional geometry (i.e., a protrusion) to the overall assembly which may not be desirable. Referring to FIG. **11B**, rather than housing the coils in a box or single housing as in the configuration of FIG. **11A**, the individual coils may be integrated into the various structures of the head mounted component **58**, as shown in FIG. **11B**. For example, x-axis coil **148** may be placed in one portion of the head mounted component **58** (e.g., the center of the frame). Similarly, the y-axis coil **150** may be placed in another portion of the head mounted component **58** (e.g., either bottom side of the frame). Similarly, the z-axis coil **152** may be placed in yet another portion of the head mounted component **58** (e.g., either top side of the frame).

(65) FIGS. **12A-12E** illustrate various configurations for featuring a ferrite core coupled to an electromagnetic sensor to increase field sensitivity. Referring to FIG. **12A**, the ferrite core may be a solid cube **1202**. Although the solid cube may be most effective in increasing field sensitivity, it may also be the most heavy when compared to the remaining configurations depicted in FIGS. **12B-12E**. Referring to FIG. **12B**, a plurality of ferrite disks **1204** may be coupled to the electromagnetic sensor. Similarly, referring to FIG. **12C**, a solid cube with a one axis air core **1206** may be coupled to the electromagnetic sensor. As shown in FIG. **12C**, an open space (i.e., the air core) may be formed in the solid cube along one axis. This may decrease the weight of the cube, while still providing the necessary field sensitivity. In yet another embodiment, referring to FIG. **12D**, a solid cube with a three axis air core **1208** may be coupled to the electromagnetic sensor. In this configuration, the solid cube is hollowed out along all three axes, thereby decreasing the weight of the cube considerably. Referring to FIG. **12E**, ferrite rods with plastic housing **1210** may also be coupled to the electromagnetic sensor. It should be appreciated that the embodiments of FIGS. **12B-12E** are lighter in weight than the solid core configuration of FIG. **12A** and may be utilized to save mass, as discussed above.

(66) Referring to FIGS. **13A-13C**, time division multiplexing (“TDM”) may be utilized to save mass as well. For example, referring to FIG. **13A**, a conventional local data processing

configuration is shown for a 3-coil electromagnetic receiver sensor, wherein analog currents come in from each of the X, Y, and Z coils (**1302**, **1304** and **1306**), go into a separate pre-amplifier **1308**, go into a separate band pass filter **1310**, a separate pre-amplifier **1312**, through an analog-to-digital converter **1314**, and ultimately to a digital signal processor **1316**.

(67) Referring to the transmitter configuration of FIG. **13B**, and the receiver configuration of FIG. **13C**, time division multiplexing may be utilized to share hardware, such that each coil sensor chain doesn't require its own amplifiers, etc. This may be achieved through a TDM switch **1320**, as shown in FIG. **13B**, which facilitates processing of signals to and from multiple transmitters and receivers using the same set of hardware components (amplifiers, etc.). In addition to removing sensor housings, and multiplexing to save on hardware overhead, signal to noise ratios may be increased by having more than one set of electromagnetic sensors, each set being relatively small relative to a single larger coil set. Also, the low-side frequency limits, which generally are needed to have multiple sensing coils in close proximity, may be improved to facilitate bandwidth requirement improvements. It should be noted that there may be a tradeoff with multiplexing, in that multiplexing generally spreads out the reception of radiofrequency signals in time, which results in generally coarser signals. Thus, larger coil diameters may be required for multiplexed systems. For example, where a multiplexed system may require a 9 mm-side dimension cubic coil sensor box, a non-multiplexed system may only require a 7 mm-side dimension cubic coil box for similar performance. Thus, it should be noted that there may be tradeoffs in minimizing geometry and mass.

(68) In another embodiment wherein a particular system component, such as a head mounted component **58** features two or more electromagnetic coil sensor sets, the system may be configured to selectively utilize the sensor and electromagnetic emitter pairing that are closest to each other to optimize the performance of the system.

(69) Referring to FIG. **14**, in one embodiment, after a user powers up his or her wearable computing system **160**, a head mounted component assembly may capture a combination of IMU and camera data (the camera data being used, for example, for SLAM analysis, such as at the belt pack processor where there may be more RAW processing horsepower present) to determine and update head pose (i.e., position and orientation) relative to a real world global coordinate system **162**. The user may also activate a handheld component to, for example, play an augmented reality game **164**, and the handheld component may comprise an electromagnetic transmitter operatively coupled to one or both of the belt pack and head mounted component **166**. One or more electromagnetic field coil receiver sets (e.g., a set being 3 differently-oriented individual coils) coupled to the head mounted component may be used to capture magnetic flux from the electromagnetic transmitter. This captured magnetic flux may be utilized to determine positional or orientational difference (or "delta"), between the head mounted component and handheld component **168**.

(70) In one or more embodiments, the combination of the head mounted component assisting in determining pose relative to the global coordinate system, and the hand held assisting in determining relative location and orientation of the handheld relative to the head mounted component, allows the system to generally determine where each component is located relative to the global coordinate system, and thus the user's head pose, and handheld pose may be tracked, preferably at relatively low latency, for presentation of augmented reality image features and interaction using movements and rotations of the handheld component **170**.

(71) Referring to FIG. **15**, an embodiment is illustrated that is somewhat similar to that of FIG. **14**, with the exception that the system has many more sensing devices and configurations available to assist in determining pose of both the head mounted component **172** and a hand held component **176**, **178**, such that the user's head pose, and handheld pose may be tracked, preferably at relatively low latency, for presentation of augmented reality image features and interaction using movements and rotations of the handheld component **180**.

(72) Specifically, after a user powers up his or her wearable computing system **160**, a head mounted component captures a combination of IMU and camera data for SLAM analysis in order to determined and update head pose relative a real-world global coordinate system. The system may be further configured to detect presence of other localization resources in the environment, like Wi-Fi, cellular, beacons, RADAR, LIDAR, GPS, markers, and/or other cameras which may be tied to various aspects of the global coordinate system, or to one or more movable components **172**.

(73) The user may also activate a handheld component to, for example, play an augmented reality game **174**, and the handheld component may comprise an electromagnetic transmitter operatively coupled to one or both of the belt pack and head mounted component **176**. Other localization resources may also be similarly utilized. One or more electromagnetic field coil receiver sets (e.g., a set being 3 differently-oriented individual coils) coupled to the head mounted component may be used to capture magnetic flux from the electromagnetic transmitter. This captured magnetic flux may be utilized to determine positional or orientational difference (or “delta”), between the head mounted component and handheld component **178**.

(74) Thus, the user's head pose and the handheld pose may be tracked at relatively low latency for presentation of AR content and/or for interaction with the AR system using movement or rotations of the handheld component **180**.

(75) Various exemplary embodiments of the invention are described herein. Reference is made to these examples in a non-limiting sense. They are provided to illustrate more broadly applicable aspects of the invention. Various changes may be made to the invention described and equivalents may be substituted without departing from the true spirit and scope of the invention. In addition, many modifications may be made to adapt a particular situation, material, composition of matter, process, process act(s) or step(s) to the objective(s), spirit or scope of the present invention. Further, as will be appreciated by those with skill in the art that each of the individual variations described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present inventions. All such modifications are intended to be within the scope of claims associated with this disclosure.

(76) The invention includes methods that may be performed using the subject devices. The methods may comprise the act of providing such a suitable device. Such provision may be performed by the end user. In other words, the “providing” act merely requires the end user obtain, access, approach, position, set-up, activate, power-up or otherwise act to provide the requisite device in the subject method. Methods recited herein may be carried out in any order of the recited events which is logically possible, as well as in the recited order of events.

(77) Exemplary aspects of the invention, together with details regarding material selection and manufacture have been set forth above. As for other details of the present invention, these may be appreciated in connection with the above-referenced patents and publications as well as generally known or appreciated by those with skill in the art. The same may hold true with respect to method-based aspects of the invention in terms of additional acts as commonly or logically employed.

(78) In addition, though the invention has been described in reference to several examples optionally incorporating various features, the invention is not to be limited to that which is described or indicated as contemplated with respect to each variation of the invention. Various changes may be made to the invention described and equivalents (whether recited herein or not included for the sake of some brevity) may be substituted without departing from the true spirit and scope of the invention. In addition, where a range of values is provided, it is understood that every intervening value, between the upper and lower limit of that range and any other stated or intervening value in that stated range, is encompassed within the invention.

(79) Also, it is contemplated that any optional feature of the inventive variations described may be set forth and claimed independently, or in combination with any one or more of the features

described herein. Reference to a singular item, includes the possibility that there are plural of the same items present. More specifically, as used herein and in claims associated hereto, the singular forms “a,” “an,” “said,” and “the” include plural referents unless the specifically stated otherwise. In other words, use of the articles allow for “at least one” of the subject item in the description above as well as claims associated with this disclosure. It is further noted that such claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent basis for use of such exclusive terminology as “solely,” “only” and the like in connection with the recitation of claim elements, or use of a “negative” limitation.

(80) Without the use of such exclusive terminology, the term “comprising” in claims associated with this disclosure shall allow for the inclusion of any additional element—irrespective of whether a given number of elements are enumerated in such claims, or the addition of a feature could be regarded as transforming the nature of an element set forth in such claims. Except as specifically defined herein, all technical and scientific terms used herein are to be given as broad a commonly understood meaning as possible while maintaining claim validity.

(81) The breadth of the present invention is not to be limited to the examples provided and/or the subject specification, but rather only by the scope of claim language associated with this disclosure.

## Claims

1. An augmented reality (AR) display system, comprising: a first component comprising an electromagnetic field emitter to emit a known magnetic field; a second component comprising an electromagnetic sensor to measure a parameter related to a magnetic flux at the electromagnetic sensor as a result of the emitted known magnetic field; a camera coupled to one of the first and second components, and which captures image data; a controller for: determining pose information relative to the electromagnetic field emitter based at least in part on the measured parameter related to the magnetic flux at the electromagnetic sensor, and determining head pose information utilizing the image data; communicating and adding the pose information and head pose information to a passable world model; consulting the passable world model to determine virtual content to be displayed to a user based on the determined head pose and hand pose; and a display system to display the determined virtual content to the user based at least in part on both the determined pose information relative to the electromagnetic field emitter and the head pose information, wherein the pose information is different than the head pose information.
2. The system of claim 1, wherein the first component is a hand-held component, and wherein the second component is a head-mounted component.
3. The system of claim 2, wherein the hand-held component comprises a totem.
4. The system of claim 2, wherein the head-mounted component comprises the display system.
5. The system of claim 1, wherein the first component is a head-mounted component, and wherein the second component is a handheld component.
6. The system of claim 5, wherein the hand-held component comprises a totem.
7. The system of claim 5, wherein the hand-held component comprises a gaming component.
8. The system of claim 1, wherein: the electromagnetic sensor comprises at least three coils to measure magnetic flux in three directions; and the at least three coils are integrated into the second component at different locations in the second component.
9. The system of claim 1, wherein the head pose information determined utilizing the image data, is determined based at least in part on a SLAM analysis utilizing the image data.
10. The system of claim 1, wherein the controller is configured to determine world coordinates of the electromagnetic sensor based at least in part on a SLAM analysis of the image data utilized to determine head pose information.
11. The system of claim 9, further comprising inertial measurement units (IMUs) and wherein the head pose information determined utilizing the image data, is determined based at least in part on a



SLAM analysis utilizing IMU data.

12. The system of claim 1, wherein the pose information corresponds to at least a position and orientation of the electromagnetic field emitter relative to the world, and the head pose information corresponds to at least a location and orientation of the user's head relative to the world.

13. The system of claim 1, wherein the controller is configured to analyze the pose information to determine world coordinates corresponding to the electromagnetic field emitter.

14. The system of claim 1, wherein the controller is configured to detect an interaction with one or more virtual contents based at least in part on the pose information corresponding to the electromagnetic field emitter, and instruct the display system to display virtual content to the user based at least in part on the detected interaction.

15. The system of claim 1, further comprising an additional localization resource, wherein the controller is configured to determine world coordinates of the electromagnetic field emitter using at least additional localization information from the localization resource.

16. The system of claim 15, wherein the additional localization resource comprises a GPS receiver.

17. The system of claim 15, wherein the additional localization resource comprises a beacon.

18. The system of claim 1, wherein the electromagnetic sensor comprises at least one of: a stack of ferrite disks; a plurality of ferrite rods each having a polymer coating; and a time division multiplexing switch.

19. An augmented reality (AR) display system, comprising: an electromagnetic field emitter that emits a known magnetic field; an electromagnetic sensor that measures a parameter related to a magnetic flux at the electromagnetic sensor as a result of the emitted known magnetic field; a camera coupled to a head-mounted component, and which captures image data; a controller that: determines pose information relative to the electromagnetic field emitter based at least in part on the measured parameter related to the magnetic flux at the electromagnetic sensor, and determines head pose information utilizing the image data; and a display system that displays virtual content on to a user based at least in part on both the determined pose information relative to the electromagnetic field emitter and the head pose information, and a control and release module adapted to decouple the head-mounted component from the electromagnetic sensor, wherein the pose information is different than the head pose information.

20. An augmented reality (AR) display system, comprising: a hand-held component comprising an electromagnetic field emitter to emit a known magnetic field; a head-mounted component comprising an electromagnetic sensor that measures a parameter related to a magnetic flux at the electromagnetic sensor as a result of the emitted known magnetic field; a camera coupled to the head-mounted component to capture image data; a controller to: receive magnetic field data from said hand-held component; receive sensor data from the electromagnetic sensor of the head-mounted component; determine pose information relative to the electromagnetic field emitter based at least in part on the measured parameter related to the magnetic flux at the electromagnetic sensor, and determine head pose information utilizing the image data; and a display system that displays virtual content to a user based at least in part on both the determined pose information relative to the electromagnetic field emitter and the head pose information, wherein the pose information is different than the head pose information and wherein the controller further determines a hand pose based at least in part on the received magnetic field data and the received sensor data and the display system modifies the virtual content displayed to the user based at least in part on the determined hand pose; and a control and release module adapted to decouple the head-mounted component from the magnetic field emitted by the electromagnetic sensor, wherein the release module comprises an internal magnetic interface load.

21. The system of claim 19, wherein the release module comprises an internal magnetic interface load.

22. The system of claim 19, wherein the pose information corresponds to at least a position and orientation of the electromagnetic field emitter relative to the world, and the head pose information

corresponds to at least a location and orientation of the user's head relative to the world.

23. The system of claim 1, wherein the communicating and adding the pose information and head pose information to a passable world model includes communicating wirelessly with a cloud network that contains the passable world model.

24. The system of claim 1, wherein the electromagnetic sensor comprises a time division multiplexing switch.

---