

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250259977

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Yang; Sheng-Chieh et al.

SEMICONDUCTOR PACKAGES

Abstract

A semiconductor package includes a first integrated circuit, a first waveguide, a second integrated circuit and a first redistribution layer structure. The first integrated circuit includes an optical coupler. The first waveguide is optically coupled to the optical coupler. The second integrated circuit is electrically connected to the first integrated circuit through the first redistribution layer structure.

Inventors: Yang; Sheng-Chieh (Hsinchu, TW), Hsieh; Ching-Hua (Hsinchu, TW), Lin; Chih-Wei (Hsinchu County, TW), Chen; Yu-Hao (Hsinchu, TW)

Applicant: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Family ID: 74679182

Assignee: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Appl. No.: 19/096727

Filed: April 01, 2025

Related U.S. Application Data

parent US continuation 18315463 20230510 parent-grant-document US 12300684 child US 19096727

parent US continuation 17578372 20220118 parent-grant-document US 11688725 child US 18315463

parent US continuation 16866561 20200505 parent-grant-document US 11233039 child US 17578372

us-provisional-application US 62893774 20190829

Publication Classification

Int. Cl.: H01L25/16 (20230101); H01L23/498 (20060101)

U.S. Cl.:

CPC H01L25/167 (20130101); H01L23/49822 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application of and claims the priority benefit of a prior application Ser. No. 18/315,463, filed on May 10, 2023 and now allowed, which is a continuation application of and claims the priority benefit of U.S. application Ser. No. 17/578,372, filed on Jan. 18, 2022, now issued as U.S. Pat. No. 11,688,725, which is a continuation application of and claims the priority benefit of U.S. application Ser. No. 16/866,561, filed on May 5, 2020, now issued as U.S. Pat. No. 11,233,039, which claims the priority benefit of U.S. provisional application Ser. No. 62/893,774, filed on Aug. 29, 2019. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

[0002] Optical signals are usable for high speed and secure data transmission between two devices. In some applications, a device capable of optical data transmission includes at least an integrated circuit (IC or “chip”) having a laser die for transmitting and/or receiving optical signals. Also, the device usually has one or more other optical or electrical components, a waveguide for the transmission of the optical signals, and a support, such as a substrate of a printed circuit board, on which the chip equipped with the laser die and the one or more other components are mounted. Various approaches for mounting a chip equipped with a laser die on a substrate have been studied.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

[0004] FIG. 1A to FIG. 1E are schematic cross-sectional views of a method of forming a semiconductor package in accordance with some embodiments.

[0005] FIG. 2 is another cross-sectional view an optical coupler of FIG. 1B.

[0006] FIG. 3 is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments.

[0007] FIG. 4A to FIG. 4F are schematic cross-sectional views of a method of forming a semiconductor package in accordance with some embodiments.

[0008] FIG. 5 is a top view of an optical coupler of FIG. 4B.

[0009] FIG. 6 is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments.

[0010] FIG. 7 is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments.

[0011] FIG. 8 is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments.

[0012] FIG. 9 is a schematic cross-sectional view of a semiconductor package in accordance with

some embodiments.

[0013] FIG. **10** is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments.

[0014] FIG. **11** is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments.

DETAILED DESCRIPTION

[0015] The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

[0016] Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

[0017] In addition, terms, such as “first,” “second,” “third,” “fourth,” and the like, may be used herein for ease of description to describe similar or different element(s) or feature(s) as illustrated in the figures, and may be used interchangeably depending on the order of the presence or the contexts of the description.

[0018] Other features and processes may also be included. For example, testing structures may be included to aid in the verification testing of the 3D packaging or 3DIC devices. The testing structures may include, for example, test pads formed in a redistribution circuit structure or on a substrate that allows the testing of the 3D packaging or 3DIC, the use of probes and/or probe cards, and the like. The verification testing may be performed on intermediate structures as well as the final structure. Additionally, the structures and methods disclosed herein may be used in conjunction with testing methodologies that incorporate intermediate verification of known good dies to increase the yield and decrease costs.

[0019] FIG. **1A** to FIG. **1E** are schematic cross-sectional views of a method of forming a semiconductor package in accordance with some embodiments.

[0020] Referring to FIG. **1A**, a carrier **C** with a de-bonding layer **DB** coated thereon is provided. In some embodiments, the carrier **C** may be a glass carrier, a ceramic carrier, a metal carrier or any other carrier suitable for carrying a semiconductor wafer or a reconstituted wafer for the manufacturing method of the semiconductor package. In some embodiments, the de-bonding layer **DB** may be any other material suitable for bonding and debonding the carrier **C** from the above layers or wafer disposed thereon. The de-bonding layer **DB** includes, for example, a light-to-heat conversion (“LTHC”) layer, and such layer enables debonding from the carrier by applying laser irradiation. In some alternative embodiments, a buffer layer may be formed between the de-bonding layer **DB** and the carrier **C**. In some embodiments, a dielectric layer **DI** is formed over the de-bonding layer **DB**. In some embodiments, the dielectric layer **DI** is, for example, polymer such as polyimide, benzocyclobutene (“BCB”), polybenzoxazole (“PBO”), or the like. In some alternative embodiments, the dielectric layer **DI** may include non-organic dielectric materials such

as silicon oxide, silicon nitride, silicon carbide, silicon oxynitride, or the like. However, the materials of the carrier C, the de-bonding layer DB and the dielectric layer DI are merely for illustration, and the disclosure is not limited thereto.

[0021] Then, a plurality of conductive posts **102** are provided over the dielectric layer DI. The conductive posts **102** may be copper pillars. In some embodiments, the conductive posts **102** are separated from each other, to define a first region **101a** for an electrical integrated circuit and a second region **101b** for a photonic integrated circuit. That is, the electrical integrated circuit and the photonic integrated circuit will be then disposed in the first region **101a** and the second region **101b** respectively. However, the disclosure is not limited thereto.

[0022] Referring to FIG. 1B, an electrical integrated circuit **110** and a photonic integrated circuit **120** are disposed between the conductive posts **102** over the dielectric layer DI. For example, the electrical integrated circuit **110** is picked and placed onto the dielectric layer DI in the first region **101a**, and the photonic integrated circuit **120** is picked and placed onto the dielectric layer DI in the second region **101b**. In some embodiments, a die attach film is located between the electrical integrated circuit **110** and the dielectric layer DI for adhering the electrical integrated circuit **110** onto the dielectric layer DI. Similarly, a die attach film is located between the photonic integrated circuit **120** and the dielectric layer DI for adhering the photonic integrated circuit **120** onto the dielectric layer DI.

[0023] In some embodiments, the electrical integrated circuit **110** includes a substrate **111**, a conductive pad **112**, passivation layers **113a**, **113b**, a conductive post **114** and a protection layer **115**. The substrate **111** includes an elementary semiconductor such as silicon or germanium and/or a compound semiconductor such as silicon germanium, silicon carbide, gallium arsenic, indium arsenide, gallium nitride or indium phosphide. In some embodiments, the substrate **111** is a semiconductor-on-insulator (SOI) substrate. In some alternative embodiments, the substrate **111** may take the form of a planar substrate, a substrate with multiple fins, nanowires or any other form known to people having ordinary skill in the art. Depending on the requirements of design, the substrate **111** may be a P-type substrate or an N-type substrate and may have doped regions therein. The doped regions may be configured for an N-type device or a P-type device.

[0024] The electrical integrated circuit **110** may include a device layer formed in or on the substrate **111**. In some embodiments, the device layer may include transistors, resistors, capacitors, inductors, and/or the like. The conductive pad **112** may be formed on and electrically connected to the device layer and may be a pad of an interconnect structure. The conductive pad **112** is an aluminum contact pad, for example. The passivation layers **113a**, **113b** may be sequentially formed on the substrate **111** and expose a portion of the conductive pad **112**. In some embodiments, a material of the passivation layer **113a** is different from a material of the passivation layer **113b**. A material of the passivation layer **113a**, **113b** may include silicon oxide, silicon oxynitride, silicon nitride, BCB, PBO, polyimide or a combination thereof. The conductive post **114** is disposed on and electrically connected to the conductive pad **112**. The conductive post **114** is a copper pillar or copper alloy pillar, for example. The protection layer **115** covers the conductive post **114** and the passivation layers **113a**, **113b**. In some alternative embodiments, before placing the electrical integrated circuit **110** over the carrier C, the conductive post **114** is uncovered (i.e., bare dies not molded or encapsulated). A material of the protection layer **115** may include silicon oxide, silicon nitride, silicon oxynitride, a low-k material, a photo-sensitive material such as a siloxane based inorganic-organic hybrid material, polyimide, a combination thereof, or the like.

[0025] In some embodiments, the photonic integrated circuit **120** includes a substrate **121**, the optical coupler OC and an optical transceiver OT. The substrate **121** may be divided into two regions: an electro-interconnection region **121a** and an optical region **121b**. The substrate **121** includes silicon, silicon oxide, aluminum oxide, sapphire, germanium, silicon germanium, gallium arsenic, gallium nitride, indium arsenide, indium phosphide or any other suitable material. In some embodiments, the substrate **121** may include an epitaxial layer. For example, the substrate **121** has

an epitaxial layer overlying a bulk semiconductor. Further, the substrate **121** may be strained for performance enhancement. The epitaxial layer may include a semiconductor material different from those of the bulk semiconductor such as a layer of silicon germanium overlying bulk silicon or a layer of silicon overlying a bulk silicon germanium formed by a process including selective epitaxial growth (SEG). Furthermore, the substrate **121** may include a semiconductor-on-insulator (SOI) structure such as a buried dielectric layer. In one embodiment, the substrate **121** includes silicon with **(100)** crystal orientation. The electro-connection region **121a** includes a plurality of patterned dielectric layers and patterned conductive layers that provide interconnections (e.g., wiring) between the various components, circuitry, and input/output of an IC device. For example, the electro-interconnection region **121a** includes a conductive pad **122** on the substrate **121**, passivation layers **123a**, **123b** partially covering the substrate **121**, a conductive post **124** and a protection layer **125**. The conductive pad **122**, the passivation layers **123a**, **123b**, the conductive post **124** and the protection layer **125** may be similar to the conductive pad **112**, the passivation layers **113a**, **113b**, the conductive post **114** and the protection layer **115** respectively. In some embodiments, the optical transceiver OT is disposed in the optical region **121b**. The optical transceiver OT is embedded in the substrate **121**, for example. The optical transceiver OT includes an optical receiver such as a photodiode and an optical transmitter such as a laser diode.

[0026] FIG. **1B** is a schematic cross-sectional view along a first line, and FIG. **2** is another cross-sectional view along a second line which is substantially perpendicular to the first line. Referring to FIGS. **1B** and **2**, in some embodiments, the optical coupler OC is disposed in the optical region **121b**. In some embodiments, the optical coupler OC includes a plurality of waveguides **126**, **127**. The waveguide **126** may be a silicon waveguide, and the waveguide **127** may be a polymer waveguide. The waveguide **126** is formed over the substrate **121**. In some embodiments, a material of the waveguide **126** is silicon, silicon oxynitride, polyimide or any other suitable material. A material of the waveguide **127** is different from the material of the waveguide **126**, and a material of the waveguide **127** is a polymer material such as a photo-sensitive polymer. The photo-sensitive polymer may be a negative photo-sensitive polymer or a positive photo-sensitive polymer. In some embodiments, the waveguide **126** is disposed adjacent to an edge of the substrate **121**, for example. The waveguide **127** is disposed on the waveguide **126** and the passivation layer **123a**, for example. As shown in FIG. **2**, in some embodiments, the waveguide **127** is partially disposed in the waveguide **126** and partially covered by the passivation layer **123b**, for example. In some embodiments, the waveguide **127** may be also referred to as a core layer.

[0027] Then, a waveguide WG is formed over the photonic integrated circuit **120** to optically couple with the optical coupler OC. In some embodiments, the waveguide WG is formed at an edge of the photonic integrated circuit **120**. The waveguide WG is disposed on and in direct and physical contact with the waveguide **127**, for example. In some embodiments, the waveguide WG is an optical fiber. In some embodiments, the waveguide WG is extended beyond the optical coupler OC and protruded from the edge of the photonic integrated circuit **120**. In some embodiments, edges of the waveguide **126**, the waveguide **127** and the substrate **121** are substantially aligned with one another, and the waveguide WG is extended beyond the edges of the waveguide **126**, the waveguide **127** and the substrate **121**. In some embodiments, the protection layer **125** may be also referred to as a cladding layer. In some embodiments, the waveguide WG is entirely exposed. In some embodiments, an outer sidewall of the protection layer **125** is substantially perpendicular to a surface of the substrate **121**. However, the disclosure is not limited thereto. In some alternative embodiments, the outer sidewall of the protection layer **125** is inclined with respect to a surface of the substrate **121**.

[0028] Referring to FIG. **1C**, an encapsulant **130** is formed over the carrier C to encapsulate the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102**. In some embodiments, the encapsulant **130** fills between or surrounds the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102**. In some embodiments, a first

surface **130a** (i.e., top surface) of the encapsulant **130** is substantially coplanar with top surfaces of the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102**. In some embodiments, the first surface **130a** of the encapsulant **130** is substantially flush with top surfaces of the conductive post **114** and the protection layer **115** of the electrical integrated circuit **110**, the conductive post **124** and the protection layer **125** of the photonic integrated circuit **120** and the conductive posts **102**. The encapsulant **130** is formed by a molding process and a planarization process, for example. In some embodiments, as shown in FIG. **1B**, the top surfaces of the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102** are illustrated as being substantially coplanar with each other before forming the encapsulant **130**. However, the disclosure is not limited thereto. In some alternative embodiments, the top surfaces of the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102** may be not flush with each other before performing the planarization process. That is, the planarization process may remove portions of the conductive post **114**, the protection layer **115**, the conductive post **124**, the protection layer **125** and/or the conductive posts **102**.

[0029] Then, a redistribution layer structure **140** is formed over the first surface **130a** of the encapsulant **130** to electrically connect to the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102**. As shown in FIG. **1C**, the waveguide WG is exposed without being covered by the redistribution layer structure **140**. In some embodiments, the redistribution layer structure **140** includes a plurality of dielectric layers **142** and a plurality of conductive patterns **144** in the dielectric layers **142**. The conductive patterns **144** are electrically connected to each other. The conductive patterns **144** includes conductive lines, conductive vias or the like. In some embodiments, a material of the conductive patterns **144** includes aluminum, titanium, copper, nickel, tungsten, silver and/or alloys thereof. In some embodiments, a material of the dielectric layers **142** includes silicon oxide, silicon oxynitride, silicon nitride, BCB, PBO, polyimide or a combination thereof. In some embodiments, the bottommost conductive patterns **144** of the redistribution layer structure **140** are electrically connected to the conductive post **114** of the electrical integrated circuit **110**, the conductive post **124** of the photonic integrated circuit **120** and the conductive posts **102** respectively. However, the disclosure is not limited thereto.

[0030] After that, a plurality of conductive terminals **146** are formed over and electrically connected to the redistribution layer structure **140**. In some embodiments, the conductive terminals **146** are electrically connected to the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102** through the redistribution layer structure **140**. In some embodiments, the conductive terminals **146** are, for example, solder balls or ball grid array (“BGA”) balls. In some embodiments, the conductive terminals **146** may be placed on the conductive patterns **144** (e.g., under-ball metallurgy patterns) through a ball placement process or any other suitable process.

[0031] Referring to FIG. **1D**, the dielectric layer DI is de-bonded from the de-bonding layer DB such that the structure of FIG. **1C** is separated from the carrier C. That is, the carrier C is removed. In some embodiments, the de-bonding layer DB (e.g., the LTHC release layer) may be irradiated by an UV laser such that the dielectric layer DI adhered on a second surface **130b** (i.e., bottom surface) of the encapsulant **130** is peeled from the carrier C. Then, the formed structure is turned upside down and disposed on a frame F. As illustrated in FIG. **1D**, the dielectric layer DI is then patterned such that a plurality of contact openings O are formed to partially expose the conductive posts **102**. The number of the contact openings O corresponds to the number of the conductive posts **102**. In some embodiments, the contact openings O of the dielectric layer DI are formed by a laser drilling process, a mechanical drilling process or any other suitable process.

[0032] Then, a memory **160** is disposed on and electrically connected to the conductive posts **102**. In some embodiments, the memory **160** is disposed over the second surface **130b** of the encapsulant **130**. In some embodiments, the memory **160** is electrically connected to the conductive posts **102** through a plurality of conductive terminals **162** such as micro-bumps therebeneath. In

some embodiments, the memory **160** includes a substrate **161**, a first die **163** on the substrate **161**, a second die **164** stacked on the first die **163** and an encapsulant **165** encapsulating the first die **163** and the second die **164**. The substrate **161**, the first die **163** and the second die **164** respectively have a plurality of conductive pads **161a**, **163a**, **164a**, for example. The conductive terminals **162** are electrically connected to the conductive pads **161a**. In some embodiments, the memory **160** further includes a plurality of conductive wires **166** encapsulated by the encapsulant **165**. The conductive wires **166** are formed between the conductive pads **161a** of the substrate **161** and the conductive pads **163a** of the first die **163**, to electrically connect the substrate **161** and the first die **163**. Similarly, the conductive wires **166** are formed between the conductive pads **161a** of the substrate **161** and the conductive pads **164a** of the second die **164**, to electrically connect the substrate **161** and the second die **164**.

[0033] Referring to FIG. 1E, the structure in FIG. 1D is de-bonded from the frame F, and a semiconductor package **100** is formed. In some embodiments, the semiconductor package **100** includes a unit U1 and the waveguide WG optically coupled to the unit U1. In some embodiments, the unit U1 includes the electrical integrated circuit **110**, the photonic integrated circuit **120** and the memory **160**. In some embodiments, as shown in FIG. 3, the unit U1 of the FIG. 1E may be connected to another unit U2 by the waveguide WG therebetween, so as to form a semiconductor package **10**. In some embodiments, the unit U2 has a configuration similar to the unit U1. However, the disclosure is not limited thereto. In some alternative embodiments, the units U1, U2 may have different configuration.

[0034] FIG. 4A to FIG. 4F are schematic cross-sectional views of a method of forming a semiconductor package in accordance with some embodiments. Referring to FIG. 4A, a redistribution layer structure **140** is formed over a carrier C, and a plurality of conductive posts **102** are formed on the redistribution layer structure **140**. In some embodiments, a de-bonding layer DB and a dielectric layer DI are sequentially formed on the carrier C, and the redistribution layer structure **140** is formed on the dielectric layer DI. In some embodiments, the redistribution layer structure **140** is a back-side redistribution layer structure. The redistribution layer structure **140** includes a plurality of dielectric layers **142** and a plurality of conductive patterns **144** in the dielectric layers **142**. The conductive patterns **144** are electrically connected to each other. The conductive posts **102** are electrically connected to the uppermost conductive patterns **144** of the redistribution layer structure **140**. In some embodiments, two conductive posts **102** are disposed immediately adjacent to each other, to define a first region **101a** for an electrical integrated circuit and a second region **101b** for a photonic integrated circuit. That is, the electrical integrated circuit and the photonic integrated circuit will be then disposed in the first region **101a** and the second region **101b** respectively. However, the disclosure is not limited thereto. In some alternative embodiments, one conductive post or more than two conductive posts may be disposed to separate the first region **101a** and the second region **101b**. Materials and/or forming methods of the carrier C, the conductive posts **102** and the redistribution layer structure **140** may be similar to or substantially the same as those of the carrier C, the conductive posts **102** and the redistribution layer structure **140** described above, and thus details are omitted herein.

[0035] Referring to FIG. 4B, then, an electrical integrated circuit **110** and a photonic integrated circuit **120** are disposed on the redistribution layer structure **140**. For example, the electrical integrated circuit **110** is picked and placed onto the dielectric layer DI in the first region **101a**, and the photonic integrated circuit **120** is picked and placed onto the dielectric layer DI in the second region **101b**. In some embodiments, the photonic integrated circuit **120** includes a substrate **121** including an electro-interconnection region **121a** and an optical region **121b**, a conductive pad **122** and a conductive post **124** in the electro-interconnection region **121a** and an optical transceiver OT and an optical coupler OC in the optical region **121b**. In some embodiments, the photonic integrated circuit **120** further includes a passivation layer **123** is disposed on the substrate **121**, and the conductive pad **122**, the conductive post **124** and the optical coupler OC are disposed in the

passivation layer **123**. The passivation layer **123** may be a single layered or multiple layered structure. In some embodiments, the electrical integrated circuit **110** and the photonic integrated circuit **120** may be similar to the electrical integrated circuit **110** and the photonic integrated circuit **120** of FIG. **1E**, and the main difference is described below.

[0036] FIG. **5** is a top view of an optical coupler of FIG. **4B**. Referring to FIGS. **4B** and **5**, the optical coupler OC includes a waveguide **126** and a grating **128**, for example. In some embodiments, the waveguide **126** may be a silicon waveguide, and the grating **128** may be a metal grating. A material of the waveguide **126** may be silicon nitride. The grating **128** may be formed directly on the waveguide **126** or have some spacing therebetween. In some embodiments, the grating **128** changes the direction of an incident optical signal light, and the waveguide **126** guides the optical signal light towards the optical transceiver OT. The electrical signal generated by the optical transceiver OT from the optical signal can be sent through the electro-connection region **121a** interconnected to a desired part of the photonic integrated circuit **120**. A material of the grating **128** may be copper, aluminum or any other suitable material. In some embodiments, as shown in FIG. **5**, the waveguide **126** and the grating **128** have a triangular shape for coupling the optical signal on the wide right side that narrows towards the left side. In some alternative embodiments, the waveguide **126** and the grating **128** may have any other suitable shape.

[0037] Then, a waveguide WG is formed over the photonic integrated circuit **120** to optically couple with the optical coupler OC. In some embodiments, the waveguide WG is formed at an edge of the photonic integrated circuit **120**. The waveguide WG is disposed on and in direct and physical contact with the grating **128**, for example. In some embodiments, the waveguide WG is an optical fiber. In some embodiments, the waveguide WG is extended beyond the optical coupler OC and protruded from the edge of the photonic integrated circuit **120**. For example, the waveguide WG is extended beyond the edges of the passivation layer **123** and the substrate **121**.

[0038] Referring to FIG. **4C**, an encapsulant **130** is formed over the carrier C to encapsulate the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102**. In some embodiments, the encapsulant **130** fills between or surrounds the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102**. A first surface **130a** (i.e., top surface) of the encapsulant **130** is substantially coplanar with top surfaces of the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102**. In some embodiments, the first surface **130a** of the encapsulant **130** is substantially flush with top surfaces of the conductive post **114** and the protection layer **115** of the electrical integrated circuit **110**, the conductive post **124**, the protection layer **125** and the grating **128** of the photonic integrated circuit **120** and the conductive posts **102**.

[0039] Then, a redistribution layer structure **150** is formed over the first surface **130a** of the encapsulant **130** to electrically connect to the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102**. In some embodiments, the redistribution layer structure **150** is separated from the waveguide WG. That is, a horizontal distance is formed between the redistribution layer structure **150** and the waveguide WG. In some embodiments, the redistribution layer structure **150** includes a plurality of dielectric layers **152** and a plurality of conductive patterns **154** in the dielectric layers **152**. The conductive patterns **154** are electrically connected to each other. The conductive patterns **154** includes conductive lines, conductive vias or the like. In some embodiments, a material of the conductive patterns **154** includes aluminum, titanium, copper, nickel, tungsten, silver and/or alloys thereof. In some embodiments, a material of the dielectric layer **152** includes silicon oxide, silicon oxynitride, silicon nitride, BCB, PBO, polyimide or a combination thereof. In some embodiments, the bottommost conductive patterns **154** of the redistribution layer structure **150** are electrically connected to the conductive post **114** of the electrical integrated circuit **110**, the conductive post **124** of the photonic integrated circuit **120** and the conductive posts **102** respectively. However, the disclosure is not limited thereto. In some embodiments, an outer sidewall of the redistribution layer structure **150** is substantially flush with a

sidewall of the encapsulant **130**. However, the disclosure is not limited thereto.

[0040] Referring to FIG. **4D**, the dielectric layer **DI** is de-bonded from the de-bonding layer **DB** such that the structure of FIG. **4C** is separated from the carrier **C**. That is, the carrier **C** is removed. Then, the formed structure is turned upside down and disposed on a frame **F1**. In some embodiments, the de-bonding layer **DB** (e.g., the LTHC release layer) may be irradiated by an UV laser such that the dielectric layer **DI** adhered on a second surface **130b** (i.e., bottom surface) of the encapsulant **130** is peeled from the carrier **C**. After that, the dielectric layer **DI** is then patterned such that a plurality of contact openings **O** are formed to partially expose some of the conductive patterns **144**. Then, a plurality of conductive terminals **146** are formed over and electrically connected to the redistribution layer structure **140**. In some embodiments, the conductive terminals **146** are electrically connected to the electrical integrated circuit **110**, the photonic integrated circuit **120** and the conductive posts **102** through the redistribution layer structure **140**. In some embodiments, the conductive terminals **146** are, for example, solder balls or ball grid array (“BGA”) balls.

[0041] Referring to FIG. **4E**, the structure of FIG. **4D** is de-bonded from the frame **F1**, and is turned upside down and disposed on a frame **F2**. Then, a memory **160** is disposed on and electrically connected to the redistribution layer structure **150**. In some embodiments, the memory **160** is joined onto the redistribution layer structure **150** through a plurality of conductive terminals **162** and an underfill **168**. The conductive terminals **162** are disposed on a surface of the memory **160** and electrically connected to a plurality of conductive pads **160a** of the memory **160**. After bonding, the conductive terminals **162** are electrically connected to the conductive patterns **154** of the redistribution layer structure **150**. The underfill **168** is dispensed aside the conductive terminals **162** to protect the electrical connection between the conductive terminals **162** of the memory **160** and the conductive patterns **154** of the redistribution layer structure **150** and securely adhere the memory **160** onto the redistribution layer structure **150**.

[0042] Referring to FIG. **4F**, the structure in FIG. **4E** is de-bonded from the frame **F2**, and a semiconductor package **100** is formed. In some embodiments, the semiconductor package **100** includes a unit **U1** and the waveguide **WG** optically coupled to the unit **U1**. In some embodiments, the unit **U1** includes the electrical integrated circuit **110**, the photonic integrated circuit **120** and the memory **160**. In some embodiments, as shown in FIG. **6**, the unit **U1** of the FIG. **4F** may be connected to another unit **U2** by the waveguide **WG** therebetween, so as to form a semiconductor package **10**. In some embodiments, the unit **U2** has a configuration similar to the unit **U1**. However, the disclosure is not limited thereto. In some alternative embodiments, the units **U1**, **U2** may have different configuration.

[0043] FIG. **7** is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments. The semiconductor package of FIG. **7** may be similar to the semiconductor package of FIG. **3**, and thus the same reference numerals are used to refer to the same and liked parts, and its detailed description will be omitted herein. The difference is illustrated in details below.

[0044] Referring to FIG. **7**, a semiconductor package **10** includes a plurality of units **U1**, **U2** and a waveguide **WG** between the units **U1**, **U2**. In some embodiments, the unit **U1**, **U2** includes a redistribution layer structure **140**, an electrical integrated circuit **110**, a photonic integrated circuit **120**, a plurality of memories **160** and an encapsulant **130**. In some embodiments, the electrical integrated circuit **110**, the photonic integrated circuit **120** and the memories **160** are disposed on a first side of the redistribution layer structure **140** and encapsulated by the encapsulant **130**. The electrical integrated circuit **110** and the photonic integrated circuit **120** are disposed side by side in a first direction **D1** (e.g., horizontal direction). The memories **160** are stacked on the electrical integrated circuit **110** in a second direction **D2** (e.g., vertical direction) substantially perpendicular to the first direction **D1**, for example. In some embodiments, the memories **160** and the electrical integrated circuit **110** are stacked vertically and electrically connected by conductive terminals **162**

such as micro-bumps. In some embodiments, a plurality of conductive posts **102** are disposed between the photonic integrated circuit **120** and the electrical integrated circuit **110** and between the photonic integrated circuit **120** and the memory **160**. The conductive posts **102** penetrate the encapsulant **130**. In some embodiments, the redistribution layer structure **140** includes a plurality of dielectric layers **142** and a plurality of conductive patterns **144** in the dielectric layers **142**. A plurality of conductive terminals **146** are disposed on a second side opposite to the first side of the redistribution layer structure **140** and electrically connected to the redistribution layer structure **140**. By the redistribution layer structure **140**, the electrical integrated circuit **110** and the photonic integrated circuit **120** are electrically connected. The configurations of the electrical integrated circuit **110** and the photonic integrated circuit **120** may be similar to or substantially the same as the configurations of the electrical integrated circuit **110** and the photonic integrated circuit **120** of FIG. **1E** or FIG. **4F**, and thus the details are omitted herein. However, the electrical integrated circuit **110** and the photonic integrated circuit **120** may have any other suitable configuration.

[0045] In some embodiments, the unit **U1**, **U2** are disposed side by side and separated from each other. In some embodiments, the waveguide **WG** is optically coupled to optical transceivers **OT** of the photonic integrated circuits **120** respectively, so as to connect the units **U1**, **U2**. In some embodiments, the waveguide **WG** is disposed between and on the optical transceivers **OT** over the encapsulants **130**, for example.

[0046] FIG. **8** is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments. The semiconductor package of FIG. **7** may be similar to the semiconductor package of FIG. **3**, and thus the same reference numerals are used to refer to the same and liked parts, and its detailed description will be omitted herein. The difference is illustrated in details below.

[0047] Referring to FIG. **8**, a semiconductor package **10** includes a plurality of units **U1**, **U2** and a waveguide **WG** between the units **U1**, **U2**. In some embodiments, the unit **U1**, **U2** includes a redistribution layer structure **140**, an electrical integrated circuit **110**, a photonic integrated circuit **120**, a memory **160** and an encapsulant **130**. In some embodiments, the electrical integrated circuit **110**, the photonic integrated circuit **120** and the memory **160** are disposed side by side in a first direction **D1** (e.g., horizontal direction) on the redistribution layer structure **140** and encapsulated by the encapsulant **130**. In some alternative embodiments, the electrical integrated circuit **110** is disposed between the photonic integrated circuit **120** and the memory **160**. However, the disclosure is not limited thereto. In some alternative embodiments, the photonic integrated circuit **120** is disposed between the electrical integrated circuit **110** and the memory **160**, or the memory **160** is disposed between the electrical integrated circuit **110** and the photonic integrated circuit **120**. In some embodiments, a plurality of conductive posts **102** are disposed between the photonic integrated circuit **120** and the electrical integrated circuit **110** and between the electrical integrated circuit **110** and the memory **160**. The conductive posts **102** penetrate the encapsulant **130**. The configurations of the electrical integrated circuit **110** and the photonic integrated circuit **120** may be similar to or substantially the same as the configurations of the electrical integrated circuit **110** and the photonic integrated circuit **120** of FIG. **1E** or FIG. **4F**, and thus the details are omitted herein. However, the electrical integrated circuit **110** and the photonic integrated circuit **120** may have any other suitable configuration.

[0048] In some embodiments, the units **U1**, **U2** are bonded to each other in a face to face configuration. After bonding, the unit **U2** is disposed on the unit **U1** in a second direction **D2** (e.g., vertical direction) substantially perpendicular to the first direction **D1**. In some embodiments, the electrical integrated circuits **110**, the photonic integrated circuits **120** and the memories **160** are disposed between the redistribution layer structures **140**. In some embodiments, the waveguide **WG** is disposed in a dielectric layer **170** on the unit **U1**, and the unit **U2** is disposed on the waveguide **WG** and the dielectric layer **170**. In some embodiments, the waveguide **WG** is optically coupled to optical transceivers **OT** of the units **U1**, **U2** respectively, so as to connect the units **U1**, **U2**. In some

embodiments, a plurality of conductive vias **172** are further formed in the dielectric layer **170** to electrically connect the conductive posts **102** of the units **U1**, **U2**. In some embodiments, a plurality of conductive terminals **146** are disposed under the redistribution layer structure **140** of the unit **U1**. However, the disclosure is not limited thereto.

[0049] In some embodiments, the optical transceiver OT of the unit **U2** is partially overlapped with the optical transceiver OT of the unit **U1** in the second direction **D2**. For example, the optical transceiver OT of the unit **U2** is disposed directly on the optical transceiver OT of the unit **U1**. However, the disclosure is not limited thereto. In some alternative embodiments, as shown in FIG. **9**, the optical transceiver OT of the unit **U2** is not overlapped with the optical transceiver OT of the unit **U1** in the second direction **D2**. For example, the photonic integrated circuit **120** of the unit **U2** is disposed above the electrical integrated circuit **110** of the unit **U1**. The memory **160** of the unit **U2** is disposed above the electrical integrated circuit **110** of the unit **U1**. The electrical integrated circuit **110** of the unit **U2** is disposed above the memory **160** of the unit **U1**. In other words, the optical transceivers OT of the units **U1**, **U2** are disposed offset from each other. In some embodiments, the waveguide WG is extended between the optical transceivers OT of the units **U1**, **U2** in the first direction **D1** (e.g., horizontal direction) substantially perpendicular to the second direction **D2**, to optically couple the optical transceivers OT respectively, so as to connect the units **U1**, **U2**.

[0050] FIG. **10** is a schematic cross-sectional view of a semiconductor package in accordance with some embodiments. The elements of the semiconductor package **100** of FIG. **10** may be similar to the elements of the semiconductor package **100** of FIG. **1E**, and thus the same reference numerals are used to refer to the same and liked parts, and its detailed description will be omitted herein. The difference is illustrated in details below.

[0051] In some embodiments, the semiconductor package **100** includes a plurality of electrical integrated circuits **110**, a plurality of memories **160**, a photonic integrated circuit **120**, a waveguide WG, a redistribution layer structure **140** and an encapsulant **130**. In some embodiments, the memories **160** and the photonic integrated circuit **120** are disposed side by side, and the photonic integrated circuit **120** is disposed between the electrical integrated circuits **110**. In some embodiments, the electrical integrated circuits **110** are disposed over and electrically connected to the memories **160**, respectively. In some embodiments, the electrical integrated circuits **110** are electrically connected to an optical transceiver OT of the photonic integrated circuit **120**. For example, conductive pads **112** of the electrical integrated circuits **110** are electrically connected to conductive pads **122** of the photonic integrated circuit **120**, and the conductive pads **122** are electrically connected to conductive pads **180** of the optical transceiver OT by connective patterns **182**. The waveguide WG is optically coupled to the optical transceiver OT. In some embodiments, the electrical integrated circuits **110**, the photonic integrated circuit **120**, the memories **160** and the waveguide WG are disposed over a first side of the redistribution layer structure **140** and encapsulated by the encapsulant **130**. In some embodiments, a plurality of conductive posts **102** are disposed between and electrically connected to the electrical integrated circuit **110** and the redistribution layer structure **140**. The conductive posts **102** penetrate the encapsulant **130**. In some embodiments, a plurality of conductive terminals **146** are disposed on a second side opposite to the first side of the redistribution layer structure **140**. In some embodiments, by the photonic integrated circuit **120**, a plurality of the electrical integrated circuits **110** are connected. Furthermore, the semiconductor package **100** may be connected to another semiconductor package through the waveguide WG. The configurations of the electrical integrated circuit **110** and the photonic integrated circuit **120** may be similar to or substantially the same as the configurations of the electrical integrated circuit **110** and the photonic integrated circuit **120** of FIG. **1E** or FIG. **4F**, and thus the details are omitted herein. However, the electrical integrated circuit **110** and the photonic integrated circuit **120** may have any other suitable configuration.

[0052] In some embodiments, as shown in FIG. **11**, a plurality of units **U** are arranged in an array

on a wafer W, and the units U are connected to each other by a waveguide (not shown) therebetween. The wafer is a semiconductor wafer, a reconstituted wafer or any other suitable wafer for carrying the semiconductor package. The units U may include an electrical integrated circuit **110**, a photonic integrated circuit **120** and a memory **160**. In some embodiments, the unit U and the waveguide may be similar to the unit U1 and the waveguide WG of FIG. 1E, 4F, 7, 8, 9 or 10. However, the disclosure is not limited thereto. In some alternative embodiments, the units U and the waveguide may have any other suitable configuration. Further, in some alternative embodiments, the units U may be horizontally arranged in an array, and further vertically stacked on one another. Accordingly, one system packaged on one wafer may be achieved.

[0053] In some embodiments, by using integrated fan-out (InFO) technique and the waveguide, optical interconnection between the photonic integrated circuit and the electrical integrated circuit are realized. Accordingly, ultra-speed signal transmission may be obtained, and the semiconductor package may be applied in multi-core high performance computing (HPC) applications. In addition, multiple dies such as the photonic integrated circuit, the electrical integrated circuit and the memory may be easily integrated without using an interposer. Conventionally, the interposer includes semiconductor materials such as silicon, and thus using the interposer increases the cost of manufacturing the semiconductor package. Accordingly, a form factor (or a thickness) of the semiconductor package and/or a cost for manufacturing the semiconductor package may become reduced.

[0054] According to some embodiments, a semiconductor package includes a first redistribution layer structure, a photonic integrated circuit, an electronic integrated circuit, a waveguide and a memory. The photonic integrated circuit is disposed over and electrically connected to the first redistribution layer structure, and includes an optical transceiver and an optical coupler. The electronic integrated circuit is disposed over and electrically connected to the first redistribution layer structure. The waveguide is optically coupled to the optical coupler. The memory is electrically connected to the electronic integrated circuit.

[0055] According to some embodiments, a semiconductor package includes a first unit, a second unit and a waveguide. The first unit includes a first photonic integrated circuit, a first electronic integrated circuit and a first memory electrically connected to each other, and the first photonic integrated circuit includes a first optical transceiver. The second unit includes a second photonic integrated circuit, a second electronic integrated circuit and a second memory electrically connected to each other, and the second photonic integrated circuit includes a second optical transceiver. The waveguide is disposed between and optically coupled to the first optical transceiver and the second optical transceiver.

[0056] According to some embodiments, a semiconductor package includes a redistribution layer structure, a plurality of memories, a photonic integrated circuit, a plurality of electronic integrated circuits and a waveguide. The memories are disposed over and electrically connected to the redistribution layer structure. The photonic integrated circuit includes an optical transceiver and is disposed between the memory devices over the redistribution layer structure. The electronic integrated circuits are respectively disposed over and electrically connected to the memories and the photonic integrated circuit. The waveguide is disposed between the electronic integrated circuits and optically coupled to the optical transceiver.

[0057] According to some embodiments, a semiconductor package includes a photonic integrated circuit, an electronic integrated circuit and a waveguide. The photonic integrated circuit includes an optical coupler. The electronic integrated circuit is disposed aside the photonic integrated circuit. The waveguide is optically coupled to the optical coupler, wherein the waveguide is disposed at an edge of the photonic integrated circuit and protrudes from the edge of the photonic integrated circuit.

[0058] According to some embodiments, a semiconductor package includes a first photonic integrated circuit, a second photonic integrated circuit and a waveguide. The first photonic

integrated circuit includes a first optical transceiver. The second photonic integrated circuit includes a second optical transceiver. The waveguide is disposed between and optically coupled to the first optical transceiver and the second optical transceiver.

[0059] According to some embodiments, a semiconductor package includes a photonic integrated circuit, a plurality of electronic integrated circuits and a waveguide. The photonic integrated circuit includes an optical transceiver. The electronic integrated circuits are disposed over and electrically connected to the photonic integrated circuit. The waveguide is disposed between the electronic integrated circuits and optically coupled to the optical transceiver.

[0060] According to some embodiments, a semiconductor package includes a first integrated circuit and a first waveguide. The first integrated circuit includes an optical coupler. The first waveguide is optically coupled to the optical coupler, wherein the first waveguide protrudes beyond the optical coupler.

[0061] According to some embodiments, a semiconductor package includes a first integrated circuit and a first waveguide. The first integrated circuit includes an optical coupler. The first waveguide is optically coupled to the optical coupler, wherein the first waveguide is partially overlapped with the optical coupler.

[0062] According to some embodiments, a semiconductor package includes a first integrated circuit, a second integrated circuit and a first waveguide. The first integrated circuit includes a first optical transceiver. The second integrated circuit includes a second optical transceiver. The first waveguide extends between the first integrated circuit and the second integrated circuit.

[0063] According to some embodiments, a semiconductor package includes a first integrated circuit, a first waveguide, a second integrated circuit and a first redistribution layer structure. The first integrated circuit includes an optical coupler. The first waveguide is optically coupled to the optical coupler. The second integrated circuit is electrically connected to the first integrated circuit through the first redistribution layer structure.

[0064] According to some embodiments, a semiconductor package includes a first waveguide and an optical coupler. The optical coupler is optically coupled to the first waveguide, wherein the optical coupler includes a second waveguide and a grating between the first waveguide and the second waveguide.

[0065] According to some embodiments, a semiconductor package includes a first waveguide, a second waveguide and a third waveguide. The first waveguide is disposed in a first passivation layer. The second waveguide is disposed on the first waveguide and optically coupled to the first waveguide. The third waveguide is disposed on the second waveguide and over the first passivation layer.

[0066] The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A semiconductor package, comprising: a first integrated circuit, comprising an optical coupler; a first waveguide, optically coupled to the optical coupler; a second integrated circuit; and a first redistribution layer structure, wherein the second integrated circuit is electrically connected to the first integrated circuit through the first redistribution layer structure.

2. The semiconductor package as claimed in claim 1, wherein the first integrated circuit and the

second integrated circuit are encapsulated in an encapsulant.

3. The semiconductor package as claimed in claim 1, wherein the first integrated circuit and the second integrated circuit are disposed on a first surface of the first redistribution layer structure.

4. The semiconductor package as claimed in claim 3, further comprising a through via between the first integrated circuit and the second integrated circuit and a third integrated circuit electrically connected to the first redistribution layer structure through the through via.

5. The semiconductor package as claimed in claim 1, further comprising a second redistribution layer structure, wherein the first integrated circuit and the second integrated circuit are disposed between the first redistribution layer structure and the second redistribution layer structure.

6. The semiconductor package as claimed in claim 1, wherein the first waveguide protrudes from a first sidewall of the first redistribution layer structure and beyond the first integrated circuit.

7. The semiconductor package as claimed in claim 1, wherein the first waveguide is overlapped with the optical coupler.

8. The semiconductor package as claimed in claim 1, wherein the optical coupler comprises a second waveguide.

9. The semiconductor package as claimed in claim 8, wherein the optical coupler further comprises a third waveguide, and the third waveguide is disposed between the first waveguide and the second waveguide.

10. The semiconductor package as claimed in claim 8, wherein a sidewall of the second waveguide is substantially flush with a sidewall of the third waveguide.

11. A semiconductor package, comprising: a first waveguide; and an optical coupler, optically coupled to the first waveguide, wherein the optical coupler comprises a second waveguide and a grating between the first waveguide and the second waveguide.

12. The semiconductor package as claimed in claim 11, wherein the first waveguide protrudes beyond the optical coupler.

13. The semiconductor package as claimed in claim 11, wherein the first waveguide, the second waveguide and the grating are overlapped.

14. The semiconductor package as claimed in claim 11, further comprising an encapsulant encapsulating the grating, wherein a sidewall of the encapsulant is substantially flush with a sidewall of the second waveguide.

15. The semiconductor package as claimed in claim 11, further comprising an optical transceiver, wherein the second waveguide is disposed between the optical transceiver and the grating.

16. A semiconductor package, comprising: a first waveguide in a first passivation layer; a second waveguide on the first waveguide and optically coupled to the first waveguide; and a third waveguide on the second waveguide and over the first passivation layer.

17. The semiconductor package as claimed in claim 16, wherein the third waveguide protrudes beyond the first waveguide and the second waveguide.

18. The semiconductor package as claimed in claim 16, wherein the second waveguide is disposed in a second passivation layer on the first passivation layer.

19. The semiconductor package as claimed in claim 16, wherein a sidewall of the first waveguide is substantially flush with a sidewall of the second waveguide.

20. The semiconductor package as claimed in claim 16, further comprising an optical transceiver under the first waveguide, the second waveguide and the third waveguide.
