

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent	12392234
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Perrin; Cédric et al.

### Modular borehole imaging apparatus and methods

#### Abstract

The present disclosure introduces an apparatus including a toolstring for use in a tubular extending into a subterranean formation. The toolstring includes modular components that include one or more caliper modules and a power and control (P/C) module. The one or more caliper modules each include radially rotatable fingers for sensing an internal diameter of the tubular. The P/C module is operable for distributing power and control signals to the one or more caliper modules. The caliper and P/C modules are mechanically and electrically interconnected by common lower interfaces of the caliper and P/C modules.

**Inventors:** Perrin; Cédric (Clamart, FR), Lopes; Jose Luis (Clamart, FR), Jacquart; Sébastien (Clamart, FR), Delgado; Miguel (Clamart, FR), Becker; Florian (Clamart, FR), Das Neves; Pedro Alexandre (Clamart, FR), Kalyanraman; Ram Sunder (Richmond, TX), Talghani; Syed (Katy, TX), He; Alexis (Clamart, FR), Leong; Chew Yeong (Tananger, NO), Kherroubi; Josselin (Clamart, FR)

**Applicant:** Schlumberger Technology Corporation (Sugar Land, TX)

**Family ID:** 1000008762634

**Assignee:** SCHLUMBERGER TECHNOLOGY CORPORATION (Sugar Land, TX)

**Appl. No.:** 18/154069

**Filed:** January 13, 2023

#### Prior Publication Data

Document Identifier	Publication Date
US 20230220762 A1	Jul. 13, 2023

#### Foreign Application Priority Data

EP	19306641	Dec. 12, 2019
----	----------	---------------

#### Related U.S. Application Data

continuation parent-doc US 17247268 20201207 US 11555395 child-doc US 18154069

#### Publication Classification

**Int. Cl.:** E21B47/002 (20120101); E21B47/01 (20120101); E21B47/08 (20120101); G01V1/40 (20060101)

**U.S. Cl.:**

**CPC** E21B47/0025 (20200501); E21B47/01 (20130101); E21B47/08 (20130101); G01V1/40 (20130101);

#### Field of Classification Search

**CPC:** E21B (47/0025); E21B (47/002); E21B (47/08); G01V (1/40); G01V (11/005); G01B (7/13); G01B (7/287)

#### References Cited

##### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2719363	12/1954	Montgomery	175/321	E21B 47/08
2771686	12/1955	Hamontre	33/544.3	E21B 47/08

2908085	12/1958	Price et al.	N/A	N/A
3061734	12/1961	Broome	307/26	E21B 47/08
4192380	12/1979	Smith	166/66.4	E21B 23/14
4299033	12/1980	Kinley	33/544.3	E21B 47/08
4559709	12/1984	Beseme	33/544.3	G01B 7/287
4673890	12/1986	Copland et al.	N/A	N/A
5299359	12/1993	Estes	702/7	G01B 7/13
5531112	12/1995	Young	166/117.7	G01F 1/74
5565624	12/1995	Deboaisne	702/10	E21B 47/08
5947213	12/1998	Angle	166/255.2	E21B 23/14
6112809	12/1999	Angle	175/45	E21B 47/26
6560889	12/2002	Lechen	N/A	N/A
7272504	12/2006	Akimov	702/9	E21B 47/12
7884951	12/2010	Prouvost	356/625	E21B 47/08
8024868	12/2010	Brannigan	33/544.3	E21B 47/08
8484858	12/2012	Brannigan	33/544.3	E21B 47/08
8849059	12/2013	Scherteler	382/300	G06T 3/4061
8925213	12/2014	Sallwasser	N/A	N/A
9803468	12/2016	Sallwasser	N/A	N/A
10605582	12/2019	Ohmer et al.	N/A	N/A
10954780	12/2020	Ge	N/A	E21B 47/08
2008/0149348	12/2007	DiFoggio	166/381	H02N 2/101
2008/0266577	12/2007	Prouvost	385/13	E21B 47/08
2010/0319991	12/2009	Brannigan	175/40	E21B 47/08
2012/0055711	12/2011	Brannigan	175/50	E21B 47/08
2012/0239345	12/2011	Fraser et al.	N/A	N/A
2014/0354855	12/2013	Venkataraman	348/239	G02B 13/0015
2015/0285607	12/2014	Helmores	33/558.2	G01B 5/12
2015/0315904	12/2014	Manclossi	702/9	E21B 47/085
2016/0290047	12/2015	Foucher	N/A	E21B 23/01
2017/0321540	12/2016	Lu	N/A	G01V 1/40
2017/0322332	12/2016	Cooper	N/A	G01V 1/40
2018/0172418	12/2017	Ohmer	N/A	G01B 3/26
2018/0196005	12/2017	Fanini et al.	N/A	N/A
2021/0180442	12/2020	Perrin	N/A	G01V 1/40
2021/0180444	12/2020	Perrin	N/A	G01B 7/13
2022/0316318	12/2021	Almulhim et al.	N/A	N/A

#### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2139626	12/1992	CN	N/A
101434053	12/2008	CN	N/A
102102510	12/2010	CN	N/A
102128594	12/2010	CN	N/A
203493482	12/2013	CN	N/A
103837118	12/2013	CN	N/A
204044050	12/2013	CN	N/A
204532342	12/2014	CN	N/A
109489596	12/2018	CN	N/A
3147424	12/1982	DE	N/A
1640561	12/2007	EP	N/A
2652678	12/2015	EP	N/A
818861	12/1958	GB	N/A
2291973	12/1995	GB	N/A
2520884	12/2013	RU	N/A
2013082057	12/2012	WO	N/A
2016115012	12/2015	WO	N/A
2016178939	12/2015	WO	N/A
2016201583	12/2015	WO	N/A

#### OTHER PUBLICATIONS

Brochure: Gyrodata, <http://www.gyrodata.com/services/logging-services/multi-finger-caliper-logging/>—downloaded on Dec. 1, 2020 (4 pages). cited by applicant

Govell: Multi-Finger Caliper (MFC)

[https://static1.squarespace.com/static/5c5146db4eddecf7a88e4a5d/t/5faa2af93511d8442bae0831/1604987705666/WellIntegrity\\_MFC%2Bcombine+new.pdf](https://static1.squarespace.com/static/5c5146db4eddecf7a88e4a5d/t/5faa2af93511d8442bae0831/1604987705666/WellIntegrity_MFC%2Bcombine+new.pdf)—downloaded on Dec. 1, 2020 (6 pages). cited by applicant

Gelman A. et al., Borehole Image Correspondence and Automated Alignment, ICASSP 2017, New Orleans, USA, Mar. 5-9, 2017 (5 pages). cited by applicant

Partial European Search Report issued in EP Application 19306641.2, dated Nov. 13, 2020 (9 pages). cited by applicant

Extended European Search Report issued in EP Application 19306640.4 dated Nov. 13, 2020, 10 pages. cited by applicant

Office Action issued in U.S. Appl. No. 17/247,268 dated May 16, 2022, 23 pages. cited by applicant

Extended Search Report issued in European Patent Application No. 22163388.6 dated Nov. 9, 2022, 7 pages. cited by applicant  
Exam Report issued in EP Application 19306641.2 dated Dec. 1, 2022, 5 pages. cited by applicant  
Notice of Allowance issued in U.S. Appl. No. 17/247,271 dated Jan. 17, 2023, 29 pages. cited by applicant  
Substantive Exam issued in Saudi Arabia Patent Application No. 120420277 dated Sep. 18, 2023, 12 pages. cited by applicant  
First Office Action issued in Chinese Patent Application No. 2020114284216 dated Dec. 30, 2024, 17 pages with English Translation. cited by applicant

---

Primary Examiner: Gay; Jennifer H

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of U.S. patent application Ser. No. 17/247,268, titled “Modular Borehole Imaging Apparatus and Methods,” filed Dec. 7, 2020, now U.S. Pat. No. 11,555,395, which claims priority to, and the benefit of the earlier filing date of, EP Patent Application No. 19/306,641.2, titled “Modular Borehole Imaging Apparatus and Methods,” filed Dec. 12, 2019, the entirety of which is hereby incorporated herein by reference.

### BACKGROUND OF THE INVENTION

(1) Assessment of oil/gas well corrosion during the production phase of a well is a complex problem of identifying and characterizing casing corrosion and other defects of various forms caused by many factors. For example, such assessment may not adequately characterize small localized faults (e.g., ditches and holes) in the casing and/or cement securing the casing in the well, may not accurately estimate the operating envelope of the well (e.g., based on the topology of faults and their grouping), and may not adequately identify and quantify reductions in the residual thickness of the casing wall. Moreover, existing assessment means may not be operable in some conditions encountered in the well during the production phase (e.g., gas, live production fluids, clear liquids).

### SUMMARY OF THE DISCLOSURE

(2) This summary is provided to introduce a selection of concepts that are further described below in the detailed description. This summary is not intended to identify indispensable features of the claimed subject matter, nor is it intended for use as an aid in limiting the scope of the claimed subject matter.

(3) The present disclosure introduces an apparatus including a toolstring for use in a tubular extending into a subterranean formation. The toolstring includes modular components that include one or more caliper modules and a power and control (P/C) module. The one or more caliper modules each include radially rotatable fingers for sensing an internal diameter of the tubular. The P/C module is operable for distributing power and control signals to the one or more caliper modules. The caliper and P/C modules are mechanically and electrically interconnected by common lower interfaces of the caliper and P/C modules.

(4) The present disclosure also introduces an apparatus including a toolstring for use in a tubular extending into a subterranean formation. The toolstring includes modular components that include one or more caliper modules and a power and control (P/C) module. The one or more caliper modules each include radially rotatable fingers for sensing an internal diameter of the tubular. The P/C module is operable for distributing power and control signals to the one or more caliper modules. The caliper and P/C modules each have an upper and a lower interface, and the lower interfaces of the caliper and P/C modules are identical. The caliper and P/C modules are mechanically and electrically interconnectable via interconnection of upper interface of the caliper and lower interface of the P/C modules.

(5) The present disclosure also introduces a method including obtaining first and second borehole image logs that are each a two-dimensional matrix. Depths of measurements of a parameter in a borehole are depicted along a first dimension of the matrix, azimuths of the measurements of the parameter in the borehole are depicted along a second dimension of the matrix, and values of the measurements of the parameter are depicted by different colors at the corresponding measurement depths and azimuths. The method also includes aligning the second borehole image log to the first borehole image log with respect to depth, then aligning the depth-aligned second borehole image log to the first borehole image log with respect to azimuth, and then merging the depth- and azimuth-aligned second borehole image log with the first borehole image log to obtain a third borehole image log having a resolution greater than each resolution of the first and second borehole image logs.

(6) The present disclosure also introduces a method including running a toolstring to a target depth in a borehole. The toolstring includes an first (generally upper) tool and a second (generally lower) tool. The first tool is a multi-finger caliper (MFC) module. The method also includes extending sensing fingers of the MFC module. The method also includes logging with standard parameters until a defect is detected via operation of the MFC module at a first resolution, and then logging a zone of interest containing the defect via operation of the second tool at a second resolution greater than the first resolution.

(7) The present disclosure also introduces a method including measuring an internal diameter of a tubular with an MFC module having measuring fingers distributed azimuthally around the MFC module. Each finger contacts the tubular at a respective contacting point. The method also includes determining the eccentricity of the MFC module at least at a particular depth based on at least three internal diameter measurements and deriving the azimuth of the contacting points of each measuring finger with the tubular. The method also includes building a borehole image log that is a two-dimensional matrix. Depths of measurements of the internal diameter in a borehole are depicted along a first dimension of the matrix, azimuths of the measurements of the internal diameter in the borehole are depicted along a second dimension of the matrix, and values of the internal diameter measurements are depicted by different colors at the corresponding measurement depths and azimuths. Building the borehole image log includes defining each measurement azimuth at the at least particular depth as the azimuth of the contacting point between the corresponding measuring finger and the tubular.

(8) These and additional aspects of the present disclosure are set forth in the description that follows, and/or may be learned by a person having ordinary skill in the art by reading the material herein and/or practicing the principles described herein. At least some aspects of the present disclosure may be achieved via means recited in the attached claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure is understood from the following detailed description when read with the accompanying figures. It is emphasized

that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

(2) FIG. 1 is a schematic view of at least a portion of an example implementation of apparatus according to one or more aspects of the present disclosure.

(3) FIG. 2 is a schematic view of at least a portion of an example implementation of a multi-finger caliper (MFC) system according to one or more aspects of the present disclosure.

(4) FIG. 3 is a schematic view of at least a portion of an example implementation of a power and control (P/C) module of the MFC system according to one or more aspects of the present disclosure.

(5) FIG. 4 is a schematic view of at least a portion of another example implementation of a P/C module of the MFC system according to one or more aspects of the present disclosure.

(6) FIG. 5 is a schematic view of at least a portion of an example implementation of a caliper module of the MFC system according to one or more aspects of the present disclosure.

(7) FIG. 6 is a schematic view of at least a portion of an example implementation of a centralizer module of the MFC system according to one or more aspects of the present disclosure.

(8) FIG. 7 is an electrical schematic view of a portion of an example implementation of a toolstring comprising modules of the MFC system according to one or more aspects of the present disclosure.

(9) FIG. 8 is a schematic view of at least a portion of an example implementation of a toolstring comprising components of the MFC system according to one or more aspects of the present disclosure.

(10) FIG. 9 is a sectional view of the toolstring shown in FIG. 8.

(11) FIG. 10 is a sectional view of another implementation of a toolstring similar to the toolstring shown in FIGS. 8 and 9.

(12) FIG. 11 is a flow-chart diagram of at least a portion of an example implementation of a logging method according to one or more aspects of the present disclosure.

(13) FIG. 12 is a flow-chart diagram of at least a portion of an example implementation of a method of merging borehole image logs according to one or more aspects of the present disclosure.

(14) FIG. 13 is an example borehole image log.

(15) FIG. 14 depicts an example toolstring, eccentric within a casing, according to one or more aspects of the present disclosure.

(16) FIG. 14BIS depicts a flow-chart diagram of at least a portion of an example implementation of a method of building an image using the toolstring.

(17) FIG. 15 depicts pixels in rows of example borehole image logs before and after merging according to the method depicted in FIG. 12.

(18) FIG. 16 is a schematic view of at least a portion of an example implementation of apparatus according to one or more aspects of the present disclosure.

#### DETAILED DESCRIPTION

(19) It is to be understood that the following disclosure provides many different embodiments, or examples, for implementing different features of various embodiments. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for simplicity and clarity, and does not in itself dictate a relationship between the various embodiments and/or configurations discussed. Moreover, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed interposing the first and second features, such that the first and second features may not be in direct contact.

(20) FIG. 1 is a schematic view of at least a portion of an example implementation of a wellsite system **100** to which one or more aspects of the present disclosure may be applicable. The wellsite system **100** may be onshore or offshore. In the example wellsite system **100** shown in FIG. 1, a toolstring **104** is conveyed into a borehole **108** via a wireline, slickline, and/or other conveyance means **112**. The example wellsite system **100** may be utilized for evaluation of the borehole **108**, cement **116** securing casing **120** within the borehole **108**, a tubular (not shown) secured in the casing **120** (e.g., production services tubing), and/or a subterranean formation **124** penetrated by the borehole **108**.

(21) The toolstring **104** is suspended in the borehole **108** from the lower end of the conveyance means **112**. The conveyance means **112** may be a single- or multi-conductor slickline or wireline logging cable spooled on a drum **113** of a winch **115** at the surface **128** of the wellsite from whence the borehole **108** extends. The wellsite surface **128** is the generally planar surface of the terrain (i.e., Earth's surface), a floor of a rig (not shown) at the wellsite, or other equipment at the wellsite, which is perpendicularly penetrated by the borehole **108**. Operation of the winch **115** rotates the drum **113** to reel in the conveyance means **112**, thus pulling the toolstring **104** in an uphole direction **101** in the borehole **108**, and to reel out the conveyance means **112**, thus moving the toolstring **104** in a downhole direction **102** in the borehole **108**. The conveyance means **112** may include at least one conductor that facilitates data communication between the toolstring **104** and surface equipment **132** disposed at the wellsite surface **128**, including through one or more slip rings, cables, and/or other conductors **133** electrically connecting the one or more conductors of the conveyance means **112** with the surface equipment **132**. However, in other implementations, such communication conductor(s) may not exist or may otherwise not facilitate data communication, in which case data may be stored downhole until the toolstring **104** is retrieved from the borehole **108**.

(22) Although not illustrated as such in FIG. 1, the winch **115** may be disposed on a service vehicle or a stationary skid/platform. The service vehicle or stationary skid/platform may also contain at least a portion of the surface equipment **132**.

(23) The toolstring **104** comprises a plurality of modules **136** each comprising an elongated housing and/or mandrel carrying various electronic and/or mechanical components. For example, at least one of the modules **136** may be or comprise at least a portion of a device for measuring a feature and/or characteristic of the borehole **108**, the casing **120**, the cement **116**, and/or the formation **124**, and/or a device for obtaining sidewall or inline core and/or fluid (liquid and/or gas) samples from the borehole **108** and/or formation **124**. Other implementations of the downhole toolstring **104** within the scope of the present disclosure may include additional or fewer components or modules **136** relative to the example implementation depicted in FIG. 1.

(24) The wellsite system **100** also includes a data processing system that may include at least a portion of one or more of the surface equipment **132**, control devices and/or other electrical and/or mechanical devices in one or more of the modules **136** of the toolstring **104** (such as a downhole controller **140**), a remote computer system (not shown), communication equipment, and/or other equipment. The data processing system may include one or more computer systems or devices and/or may be a distributed computer system. For example, collected data or information may be stored, distributed, communicated to a human wellsite operator, and/or processed locally (downhole

or at surface) or remotely.

(25) The data processing system may, individually or in combination with other system components, perform the methods and/or processes described below, or portions thereof. For example, the data processing system may include processor capability for collecting caliper, acoustic, ultrasonic, and/or other data related to the evaluation of the cement **116**, the casing **120**, and/or the formation **124** according to one or more aspects of the present disclosure. Methods and/or processes within the scope of the present disclosure may be implemented by one or more computer programs that run in a processor located, for example, in one or more modules **136** of the toolstring **104** and/or the surface equipment **132**. Such programs may utilize data received from the downhole controller **140** and/or other modules **136** via the conveyance means **112**, and may transmit control signals to operative elements of the toolstring **104**. The programs may be stored on a tangible, non-transitory, computer-usable storage medium associated with the one or more processors of the downhole controller **140**, other modules **136** of the toolstring **104**, and/or the surface equipment **132**, or may be stored on an external, tangible, non-transitory, computer-usable storage medium that is electronically coupled to such processor(s). The storage medium may be one or more known or future-developed storage media, such as a magnetic disk, an optically readable disk, flash memory, or a readable device of another kind, including a remote storage device coupled over a communication link, among other examples.

(26) At least one of the modules **136** may be or comprise a multi-finger measuring or caliper (MFC) tool operable for acquiring measurements of the diameter of the inner wall of the casing **120** (or another tubular, such as production tubing). For example, the measuring fingers move radially in response to undulations of the inner diameter (ID) **144** of the casing **120** as the toolstring **104** is conveyed in the uphole direction **101**, thereby detecting changes in the ID **144** of the casing **120**. That is, the MFC tool transforms such radial movement of the tips of the fingers into a linear translational motion measured by a displacement sensor, such as a linear variable differential transformer (LVDT) sensor, permitting measurements in one direction. The multiple fingers are distributed around the circumference of the MFC tool, such that a mapping of a measured section of the casing **120** can be generated by integrating the different measuring points associated with the different fingers. In drilling and production environments, these tools may be utilized to evaluate corrosion, erosion, wear, bending, eccentricity, buckling, holes, and other faults in the borehole **108**, the casing **120**, and/or a tubular (not shown) installed in the casing **120**. The MFC tool may also be used to measure the accumulation of scale, paraffin, and/or other deposits on the inner wall of the casing **120**.

(27) Existing MFC tools are generally offered in three tool sizes to cover the range of existing casings and conveyance types, namely, a small MFC tool with 24 fingers and an outer diameter (OD) of about 1.7 centimeters (cm), a medium MFC tool with 40 fingers and an OD of about 7.0 cm, and a large MFC tool with 60 fingers and an OD of about 8.6 cm. However, supporting three different MFC tool sizes increases financial costs, logistics complexity, and related maintenance operations.

(28) FIG. **2** is a schematic diagram of at least a portion of an example implementation of an MFC system **200** according to one or more aspects of the present disclosure. The example MFC system **200** supports different types of conveyances supported by the three MFC tool sizes to which the industry is accustomed. The example MFC system **200** also supports combinability with the sizes, connectors, and interoperability of the different non-MFC tools commonly assembled in toolstrings having an MFC tool. The example MFC system **200** is also able to mechanically support the load of such toolstrings, even those with larger ODs (e.g., modules with an OD of about 8.6 cm or greater). The example MFC system **200** may be utilized in casing, other tubulars (e.g., production tubing), and boreholes of the various IDs to which the industry is accustomed. Accordingly, the example MFC system **200** may offer a financial benefit over existing systems, in that a single instance of the MFC system **200** may replace the conventional three different-sized MFC tools. The example MFC system **200** may offer similar benefits in the context of logistics and/or maintenance.

(29) The MFC system **200** has a modular architecture comprising one or more power and control (P/C) modules **210**, **220**, a caliper module **230**, and a centralizer module **240**. Each toolstring (e.g., toolstring **104** in FIG. **1**) comprising components of the MFC system **200** includes one of the P/C modules **210**, **220**, one or two (or more) instances of the caliper module **230**, and optionally one or two (or more) instances of the centralizer module **240**. Each P/C module **210**, **220** is operable for distributing power and control signals to the one or more caliper modules **230** and the one or more centralizer modules **240**. Each caliper module **230** comprises a plurality of radially rotatable fingers **234** for sensing an ID of a casing, other tubular, or borehole. Each centralizer module **240** is operable for centralizing the one or more caliper modules **230** within the casing, other tubular, or borehole.

(30) The MFC system **200** may also comprise an adapter **250** for mechanically and electrically connecting the P/C module **210** to a conventional or future-developed telemetry module **252** configured for slickline operations. For example, the adapter **250** may mechanically and electrically connect the P/C module **210**, which may have a first OD and a predetermined number of electrical connection pins (e.g., 22 pins), with the telemetry module **252**, which may have a different OD and the same or a different number of electrical connection pins (here, e.g., 22 as well). The telemetry module **252** may comprise one or more telemetry boards (or cartridges) **254** operable for data communication over a slickline cable **256**. The telemetry module **252** may also comprise a battery pack and/or other electrical energy storage means **255**, such as for electrically powering the one or more telemetry boards **254**. A conventional or future-developed slickline logging head **258** may mechanically and electrically connect the slickline telemetry module **252** with the slickline cable **256**.

(31) The MFC system **200** may also comprise an adapter **260** for mechanically and electrically connecting the P/C module **220** to a conventional or future-developed telemetry module **262** configured for production services (PS) wireline operations. For example, the adapter **260** may mechanically and electrically connect the P/C module **220**, which has the first OD and the predetermined number of electrical connection pins, with the telemetry module **252**, which may have a different OD and the same or a different number of electrical connection pins (here, e.g., 22 as well). The telemetry module **262** may comprise one or more telemetry boards (or cartridges) **264** operable for data communication over a PS wireline cable **266**. A conventional or future-developed PS wireline logging head **268** may mechanically and electrically connect the PS wireline telemetry module **262** with the PS wireline cable **266**.

(32) The MFC system **200** may also comprise an adapter **270** for mechanically and electrically connecting the P/C module **220** to a conventional or future-developed telemetry module **272** configured for wireline logging operations. For example, the adapter **270** may mechanically and electrically connect the P/C module **220**, which has the first OD and a predetermined number of electrical connection pins, with the telemetry module **252**, which may have a different OD (e.g., about 8.6 cm) and the same or a different number of electrical connection pins (e.g., 31 pins). A conventional or future-developed wireline logging head **274** may mechanically and electrically connect the wireline logging telemetry module **272** with the wireline cable **276**.

(33) The MFC system **200** may also comprise a conventional bottom nose device **280** for forming the downhole end of the toolstring, an adapter **282** for mechanically and electrically connecting the lowermost caliper module **230** or centralizer module **240** (e.g., having the first OD (e.g., about 5.4 cm) and a predetermined number (e.g., 22) of electrical connection pins) to a smaller-diameter toolstring component (e.g., having a different, smaller OD (e.g., about 4.3 cm) and the predetermined number (e.g., 22) or a different number of electrical connection pins), and/or an adapter **284** for mechanically and electrically connecting the lowermost module **230**, **240** (e.g., having an OD

of about 5.4 cm and 22 electrical connection pins) to a larger-diameter toolstring component (e.g., having a larger OD (e.g., about 8.6 cm) and a different number (e.g., 31) of electrical connection pins). The lowermost module **230**, **240** may be connected to one of the bottom nose device **280**, the adapter **282**, or the adapter **284**. Alternatively, the lowermost module **230**, **240** may be connected directly to another toolstring component **286**, such as another downhole tool, such as a corrosion platform tool, having for example at least an ultrasonic transducer and/or an electromagnetic sensor.

(34) FIG. **3** is a schematic view of at least a portion of an example implementation of the P/C module **210** according to one or more aspects of the present disclosure. The P/C module **210** comprises an upper interface **211** and a lower interface **212** for mechanical and electrical connection of the P/C module **210** to neighboring components of the toolstring. The mechanical portions of the upper and lower interfaces **211**, **212** may comprise threads and/or other means (not shown) for mechanically coupling with the neighboring toolstring components. The electrical portions of the upper and lower interfaces **211**, **212** may comprise electrical connection pins/sockets and/or other means (not shown) for electrically coupling with the neighboring toolstring components.

(35) The P/C module **210** also comprises a master board (or cartridge) **214** that includes various integrated circuit (IC) components (chips, modules, etc.), electrical connections, and other devices collectively operable to dictate and manage the different functions of the caliper and centralizer modules **230**, **240**, such as to control motor actuations, memory, and other functions of the modules **230**, **240**. The master board **214** also interfaces to one or more telemetry boards **254** of the telemetry module **252**, such that surface equipment (e.g., surface equipment **132** of FIG. **1**, which may include a depth time recorder, or DTR) may be utilized to perform data acquisition, tool control, and power distribution to the components of the MFC system **200** in the toolstring. The P/C module **210** also comprises a battery pack and/or other electrical energy storage means **216**, and the master board **214** controls distribution of electrical power from the electrical energy storage means **216** to the caliper and centralizer modules **230**, **240**. The P/C module **210** also comprises a memory board (or cartridge) **218** operable to acquire and save data generated and/or acquired via operation of the P/C module **210**, the caliper module(s) **230**, the centralizer module(s) **240**, and/or other modules/tools of the toolstring.

(36) FIG. **4** is a schematic view of at least a portion of an example implementation of the P/C module **220** according to one or more aspects of the present disclosure. The P/C module **220** comprises an upper interface **221** and a lower interface **222** for mechanical and electrical connection of the P/C module **220** to neighboring components of the toolstring. The upper and lower interfaces **221**, **222** are substantially similar or identical to the upper and lower interfaces **211**, **212** of the P/C module **220**.

(37) The P/C module **220** also comprises a master board (or cartridge) **224** that includes various IC components (chips, modules, etc.), electrical connections, and other devices collectively operable to dictate and manage the different functions of the caliper and centralizer modules **230**, **240**, such as to control motor actuations, memory, and other functions of the modules **230**, **240**. The master board **224** also interfaces to one or more telemetry boards **264** of the telemetry module **262**, and to the telemetry module **272**, such that surface equipment (e.g., surface equipment **132** of FIG. **1**, such as Schlumberger's Wireline Acquisition Front-End, or WAFE) may be utilized to perform data acquisition, tool control, and power distribution to the components of the MFC system **200** in the toolstring. The P/C module **220** also comprises one or more power supplies **226**, such as to convert high voltage (e.g., 200 VDC) on the PS wireline cable **266** or wireline cable **276** to a lower voltage (e.g., 12 VDC), and the master board **224** controls distribution of electrical power from the power supply **226** to the caliper and centralizer modules **230**, **240**. The P/C module **220** also comprises a memory board (or cartridge) **228** operable to acquire and save data generated and/or acquired via operation of the P/C module **220**, the caliper module(s) **230**, the centralizer module(s) **240**, and/or other modules/tools of the toolstring.

(38) FIG. **5** is a schematic view of at least a portion of an example implementation of the caliper module **230** according to one or more aspects of the present disclosure. The caliper module **230** comprises an upper interface **231** and a lower interface **232** for mechanical and electrical connection of the caliper module **230** to neighboring components of the toolstring. The lower interface **232** is substantially similar or identical to the lower interfaces **212**, **222** of the P/C modules **210**, **220**.

(39) The caliper module **230** comprises an electric motor **235** driven by a controller **236**. The motor **235** is operable to move an actuator **237** and/or other means for actively extending ("opening") and retracting ("closing") the sensing fingers **234**. A data acquisition device **238** receives caliper data from a block **239** of sensors each corresponding to one of the fingers **234**. For example, the displacement of each individual finger **234** may be linked to a linear displacement sensor (such as a differential variable reluctance transducer (DVRT), an inductive sensor, and/or other sensors) that translates radial displacement of the radially outer tip of that finger **234** to linear motion. The linear displacements are converted to electrical signals (e.g., via inductance variation) via the sensors **239** and/or the data acquisition device **238**. The electric signals may be further converted to digital signals, whether by the data acquisition device **238** or the master boards **214**, **224** of the P/C modules **210**, **220**. The digital signals may be conveyed to surface via the slickline cable **256** or wireline cable **266**, **276**. The digital signals may also or instead be saved to downhole memory, such as of the data acquisition device **238** and/or the memory boards **218**, **228** of the P/C modules **210**, **220**.

(40) During acquisition of the caliper data, the position (e.g., depth and azimuth) of the caliper module **230** may also be acquired in real-time. For example, the caliper module **230** (or another component of the MFC system **200**) may comprise various position sensors **233** operable in acquiring the position data in real-time. A position sensor **233** may be associated with each finger **234** of the caliper module **230**. Such sensors **233** may comprise one or more accelerometers (e.g., three-axis accelerometers), gyroscopic sensors (e.g., three-axis gyroscopic sensors), load cells, and/or other sensors. In some implementations, the position sensors **233** may comprise a combination of sensor types, such as three-axis accelerometers and three-axis gyroscopic sensors.

(41) FIG. **6** is a schematic view of at least a portion of an example implementation of the centralizer module **240** according to one or more aspects of the present disclosure. The centralizer module **240** comprises an upper interface **241** and a lower interface **242** for mechanical and electrical connection of the centralizer module **240** to neighboring components of the toolstring. The upper interface **241** is substantially similar or identical to the upper interface **231** of the caliper module **230**. The lower interface **242** is substantially similar or identical to the lower interfaces **212**, **222** of the P/C modules **210**, **220** and the lower interface **232** of the caliper module **230**. The centralizer module **240** may otherwise be, comprise, or function via conventional or future-developed centralizing means.

(42) For example, the centralizer module **240** may comprise an electric motor **243** driven by a controller **244**. The motor **243** may be operable to move an actuator **245** and/or other means for actively extending ("opening") and retracting ("closing") a plurality of centralizing arms **246**. Although only two centralizing arms **246** are depicted in the example implementation shown in FIG. **6**, other implementations within the scope of the present disclosure may have more than two centralizing arms **246**. When the actuator **245** is in a retracted position (as depicted in FIG. **6** by solid lines), the centralizing arms **246** may be in retracted positions (also depicted in FIG. **6** by solid lines). Extension of the actuator **245** (as depicted in FIG. **6** by dashed lines **247**) may extend the centralizing arms **246** to extended positions (as depicted in FIG. **6** by dashed lines **248**). Retraction of the actuator **245** permits retraction of the centralizing arms **246**, perhaps in conjunction with one or more springs and/or other biasing means (not shown) urging the centralizing arms **246** toward their retracted

positions.

(43) Extension of the centralizing arms **246** aids in urging the caliper module(s) **230** to a central position within the casing, other tubular, or borehole being investigated by the caliper module(s) **230**. One or more implementations of toolstrings within the scope of the present disclosure may include an instance of the centralizer module **240** at each end of each caliper module **230**. Other toolstring implementations within the scope of the present disclosure may include two or more instances of the caliper module **230** coupled end-to-end between two opposing instances of the centralizer module **240**.

(44) FIG. 7 is an electrical schematic view of an example implementation of a portion of a toolstring **300** comprising the P/C module **220**, an upper instance **302** of the centralizer module **240**, an upper instance **304** of the caliper module **230**, a lower instance **306** of the caliper module **230**, and a lower instance **308** of the centralizer module **240**. The lower interface **222** of the P/C module **220**, the lower interfaces **232** of the caliper modules **230**, and the lower interfaces **242** of the centralizer modules **240** each comprise substantially similar electrical connections (pins, sockets, etc.) for a direct current (DC) power-out connection **310** (depicted in FIG. 7 by heavy lines), a first-signal-out connection **312** (depicted in FIG. 7 by double lines), a second-signal-out connection **314** (depicted in FIG. 7 by dashed double lines), and an alternating current (AC) power-out connection **316** (depicted in FIG. 7 by dotted lines). The upper interfaces **231** of the caliper modules **230** and the upper interfaces **241** of the centralizer modules **240** each comprise substantially similar electrical connections (pins, sockets, etc.) for a DC power-in connection **318**, a first-signal-in connection **320**, a second-signal-in connection **322**, and an AC power-in connection **324**.

(45) Accordingly, the example implementation depicted in FIG. 7 illustrates that the lower interfaces (**212**, **222**, **232**, **242**) of the P/C modules **210**, **220**, the caliper modules **230**, and the centralizer modules **240** may be substantially similar, or even identical, and that the upper interfaces (**231**, **241**) of the caliper modules **230** and the centralizer modules **240** may be substantially similar, or even identical. Such similarity may be with regard to the number, type, size, and physical location of the electrical connections. Although not illustrated in FIG. 7, such similarity may also be with regard to the type, size, and physical location of the means for mechanical coupling with the neighboring modules of the toolstring.

(46) The upper interface **221** of the P/C module **220** depicted in the example schematic shown in FIG. 7 includes electrical connections (pins, sockets, etc.) for a telemetry connection **326** and an AC power-in connection **328**. At least one of the power supplies **226** is connected to the AC power-in connection **328** and outputs DC power (via a connection **330**) to the DC power-out connection **310**. The AC power-out connection **316** is connected to the AC power-in connection **328**. One or more connections **332** of the master board **224** are also connected to the AC power-in connection **328**. A connection **334** of the master board **224** is connected to a connection **336** of the memory board **228**. A connection **338** of the memory board is connected to the telemetry connection **326**. A connection **340** of the master board **224** is connected to DC power (between connections **330** and **310**). A first-signal-out connection **342** of the master board **224** is connected to the first-signal-out connection **312** of the P/C module **220**, and a second-signal-out connection **344** of the master board **224** is connected to the second-signal-out connection **314** of the P/C module **220**. The P/C module **210** described above may have similar connections to those of the P/C module **220** depicted in FIG. 7.

(47) The controller **244** of each centralizer module **240** depicted in FIG. 7 includes a connection **346** to DC power, a connection **348** to the first-signal connections **312**, **320**, a connection **350** to the second-signal-in connection **322** of that centralizer module **240**, and a connection **352** to the second-signal-out connection **314** of that centralizer module **240**. The AC power-out connection **316** is connected to the AC power-in connection **324**.

(48) The controller **236** of each caliper module **230** depicted in FIG. 7 includes a connection **354** to DC power, a connection **356** to the first-signal connections **312**, **320**, a connection **358** to the second-signal-in connection **322** of that caliper module **230**, and a connection **360** to the second-signal-out connection **314** of that caliper module **230**. The AC power-out connection **316** is connected to the AC power-in connection **324**.

(49) FIG. 8 is a schematic view of an example implementation of a toolstring **400** comprising components of the MFC system **200** according to aspects of the present disclosure. The toolstring **400** may form at least a portion of, and/or otherwise be utilized as, a corrosion measurement system for assessing corrosion levels and locations of casing or other tubulars (e.g., the casing **120** of FIG. 1). The toolstring **400** includes the wireline logging head **268** connecting the toolstring **400** to the wireline cable **266**. The telemetry module **262** is connected to the wireline logging head **268**. The adapter **260** connects the P/C module **220** to the telemetry module **262**. An upper instance **402** of the centralizer module **240** is connected to the P/C module **220**. An upper instance **404** of the caliper module **230** is connected to the upper instance **402** of the centralizer module **240**. A lower instance **406** of the caliper module **230** is connected to the upper instance **404** of the caliper module **230**. A lower instance **408** of the centralizer module **240** is connected to the lower instance **406** of the caliper module **230**. One or more other tools **410** may be connected to the lower instance **408** of the centralizer module **240**, such as an ultrasonic measurement tool, and electromagnetic measurement tool (such as for measuring eddy currents), and/or other acoustic measurement tools. The bottom nose **280** may form the downhole end of the toolstring **400**.

(50) The sensing fingers **234** of the upper instance **404** of the caliper module **230** are designated by reference number **412** in FIG. 8. Similarly, the sensing fingers **234** of the lower instance **406** of the caliper module **230** are designated by reference number **414**. The sensing fingers **412** of the upper instance **404** of the caliper module **230** may be azimuthally aligned with the sensing fingers **414** of the lower instance **406** of the caliper module **230**, as depicted in FIG. 9, which is a sectional view of the toolstring **400**. However, in other implementations, the sensing fingers **412** of the upper instance **404** of the caliper module **230** may be azimuthally offset relative to the sensing fingers **414** of the lower instance **406** of the caliper module **230**, as depicted in FIG. 10, which is a sectional view of another implementation of a toolstring **401** identical to the toolstring **400** other than the azimuthal offset of the sensing fingers **412**, **414**. For clarity purposes, the sensing fingers **412** are depicted in FIG. 10 by solid lines, while the sensing fingers **414** are depicted by dashed lines.

(51) Apparatus according to one or more aspects of the present disclosure may permit easier management of tool maintenance. For example, if a module of the toolstring is not functioning properly at a job location, a replacement module can be shipped to the job location instead of shipping an entire replacement toolstring. Moreover, the modules of the present disclosure may be used separately. For example, the centralizer module **240** may be added to an additional tool to form (at least partially) a toolstring that doesn't include a caliper module **230**.

(52) Further, the configuration of the toolstring may be adapted to the particular job, for instance, the number of centralizer modules **240** depending on the toolstring length. Such flexibility permits, for example, having just one size of caliper module **230** to log different diameters of casings. Indeed, if a greater casing diameter is logged, two (or more) caliper modules **230** may be directly connected, including with azimuthally offset fingers **234**, which permits a greater resolution relative to utilizing just one caliper module **230**. The position sensors **233** permit combining the data obtained with both caliper modules **230**, as described below.

(53) FIG. 11 is a flow-chart diagram of at least a portion of an example implementation of a method **500** according to one or more aspects

of the present disclosure. The method **500** is one example of various methods within the scope of the present disclosure that may be performed utilizing, or otherwise in conjunction with, toolstrings comprising components of the MFC system **200** depicted in FIG. 2. For example, the method **500** depicted in FIG. 11 may be performed utilizing the toolstring **400** depicted in FIGS. 8 and 9, or the toolstring **401** depicted in FIG. 10. Thus, the following description refers to FIGS. 8-11, collectively.

(54) The method **500** comprises running **505** the toolstring **400** to total depth within a borehole (e.g., the borehole **108** depicted in FIG. 1). During this phase, the sensing fingers **412**, **414** of the caliper modules **404**, **406** and the centralizing arms **246** of the centralizer modules **402**, **408** are retracted. The caliper modules **404**, **406** are then centralized within the casing, other tubular, or borehole being examined (e.g., casing **120** depicted in FIG. 1) by extending **510** the centralizing arms **246** of the centralizer modules **402**, **408**. The sensing fingers **412**, **414** of the caliper modules **404**, **406** are then extended **515**, thus contacting the ID of the casing, tubular, or borehole being examined. As described above, the extension **510** of the centralizing arms **246** of the centralizer modules **402**, **408** and the extension **515** of the sensing fingers **412**, **414** of the caliper modules **404**, **406** may be controlled by the master board **224** of the P/C module **220**, such as via corresponding control signals sent to the controllers **244** of the centralizer modules **402**, **408** and the controllers **236** of the caliper modules **404**, **406**.

(55) Logging **520** then begins utilizing standard parameters. For example, the logging **520** may be performed by pulling the toolstring **400** in the uphole direction at a speed of about 550 meters per hour (m/hr) while the MFC sensors **239**, the position sensors **233**, and the data acquisition devices **238** cooperate to obtain MFC data at a first resolution and corresponding position data. The logging **520** with the standard parameters continues until the MFC examination run is complete, as depicted in FIG. 11 by determination **525**, or until a defect is detected, as depicted in FIG. 11 by determination **530**. The defects that may be detected **530** may include corrosion or deformation of a form or shape of the casing, tubular, or borehole being examined. If no defects are detected **530** and the MFC examination run is complete **525**, then logging ends **535**, the sensing fingers **412**, **414** of the caliper modules **404**, **406** are retracted **540**, the centralizing arms **246** of the centralizer modules **402**, **408** are retracted **545**, and the toolstring **400** is pulled **550** out of the borehole.

(56) However, if a defect is detected **530** before the MFC examination run is complete **525**, then logging **555** with refined parameters begins via several actions performed by the P/C module **220**. For example, a request may be sent to the surface equipment to decrease the speed at which the toolstring **400** is pulled in the uphole direction through a vertical zone of interest containing the detected **530** defect. The zone of interest may extend uphole from the detected **530** defect to a predetermined length between about one meter and about ten meters, such as about five meters. The speed at which the toolstring **400** is pulled in the uphole direction through the zone of interest may be reduced relative to the speed of the standard parameters. For example, the reduced speed may be about 180 m/hr. The reduced speed permits the lower caliper module **406** to acquire MFC data in the zone of interest at a higher resolution than the MFC data obtained by the upper caliper module **404** when the defect was initially detected **530** and/or relative to the one or more additional tools **410** to acquire data. Reducing the velocity of displacement also reduces the bouncing effect the fingers could undergo while pulling at full regime, increasing measurement accuracy.

(57) The higher resolution MFC data acquired by the lower caliper module **406** may be acquired through the same longitudinal paths traversed by the sensing fingers **412** of the upper caliper module **404** if the sensing fingers **414** of the lower caliper module **406** are azimuthally aligned with the sensing fingers **412** of the upper caliper module **404**, as depicted in FIG. 9, or through different longitudinal paths azimuthally offset from the paths traversed by the sensing fingers **412** of the upper caliper module **404** if the sensing fingers **414** of the lower caliper module **406** are azimuthally offset relative to the sensing fingers **412** of the upper caliper module **404**, as depicted in FIG. 10. The higher resolution may be obtained because the additional tool **410** offers a greater resolution. The second resolution is greater than the first resolution utilized during the logging **520** with the standard parameters. For example, the second resolution may be two, three, four, or more times the first resolution.

(58) Instead of or in addition to decreasing the speed at which the toolstring **400** is pulled uphole through the zone of interest, the refined parameters utilized during the logging **555** may pertain to adjustments to operational parameters of the additional tools **410** (via, for example, control signals received from the P/C module **220**), such that the parameters measured by the additional tools are adapted in view of the detected defect by setting up the additional tool with predefined operational parameters.

(59) If the full MFC examination run is not complete after the zone of interest is logged **555** with the refined parameters, as depicted in FIG. 11 by determination **560**, then the logging **520** with the standard parameters continues until the MFC examination run is complete **525** or another defect is detected **530**. However, if the full MFC examination run is complete **560** after the zone of interest is logged **555** with the refined parameters, then logging ends **535**, the sensing fingers **412**, **414** of the caliper modules **404**, **406** are retracted **540**, the centralizing arms **246** of the centralizer modules **402**, **408** are retracted **545**, and the toolstring **400** is pulled **550** out of the borehole.

(60) During the logging **520** with the standard parameters, the lower caliper module **406** may be operating to acquire MFC and position data at the same resolution that the upper caliper module **404** is acquiring MFC and position data, or the lower caliper module **406** may be in a sleep mode in which no MFC data is being acquired. During the logging **555** with the refined parameters, the lower caliper module **406** may acquire the MFC and position data at the higher second resolution, while the upper caliper module **404** may acquire the MFC and position data at the second resolution or the lower first resolution.

(61) FIG. 12 is a flow-chart diagram of at least a portion of an example implementation of a method **600** of merging first and second borehole image logs according to one or more aspects of the present disclosure, so as to obtain a third borehole image log having a resolution greater than each resolution of the first and second logs. The first and second borehole image logs may be the MFC data acquired by the upper and lower instances of the caliper module **230** in the same toolstring, such as the upper and lower caliper modules **404**, **406** depicted in FIG. 9, perhaps via performance of the method **500** depicted in FIG. 11. However, the first and second borehole image logs may also be obtained via other methods (within the scope of the present disclosure or otherwise), whether via utilization of toolstrings comprising components of the MFC system **200** described above, other toolstrings within the scope of the present disclosure, and/or other tools, including tools not operable to obtain MFC data. The first and second borehole image logs may be obtained utilizing a toolstring comprising two caliper modules **230** during a single examination run, by a toolstring comprising one caliper module **230** during two examination runs, or by a first toolstring comprising one caliper module **230** (or more) during a first examination run and a second toolstring comprising one caliper module **230** (or more) during a second examination run.

(62) The first and second borehole image logs are each a two-dimensional (2D) matrix, wherein depths of measurements of a parameter in a casing, tubular, or borehole (hereafter collectively "borehole") are depicted along a first dimension of the matrix, azimuths of the measurements of the parameter in the borehole are depicted along a second dimension of the matrix, and values of the measurements of the parameter are depicted by different colors at the corresponding measurement depths and azimuths. An example borehole image log is depicted in FIG. 13.

(63) The method **600** comprises aligning **605** the second borehole image log to the first borehole image log with respect to depth. Such



alignment **605** may comprise converting **610** the first borehole image log into a first one-dimensional (1D) log relating the parameter measurements to depth, converting **615** the second borehole image log into a second 1D log relating the parameter measurements to depth, performing **620** a positioning and/or compression and/or dilation adjustment of the second 1D log relative to the first 1D log sufficient to match the second 1D log to the first 1D log, and performing **625** the same positioning and/or compression adjustment on the second (2D) borehole image log. Such positioning adjustment is necessary as the logging of each zone may not have been performed at the same speed with the caliper modules. The positioning and/or compression and/or dilation adjustment may be performed with any appropriate algorithm, such as a warping algorithm. Converting **610**, **615** the first and second borehole image logs into the respective first and second 1D logs may comprise obtaining minimum, maximum, and average values of the parameter measurements at each depth at which a parameter measurement exists in both of the first and second borehole image logs. Such adjustment is possible because it realigns both caliper data relative to low frequency details of the image, such as manufacturing patterns including casing collars.

(64) The depth-aligned **605** second borehole image log is then aligned **630** to the first borehole image log with respect to azimuth. Such alignment **630** may comprise, at each depth at which a parameter measurement exists in both the first borehole image log and the depth-aligned **605** second borehole image log, rotating the depth-aligned **605** second borehole image log sufficient to match the depth-aligned **605** second borehole image log to the first borehole image log based on cross-correlation of data of the first and second images at each depth for each rotation angle of the second borehole image at a predetermined depth. In other words, several rotation angles are tested for the second borehole image at a predetermined depth, and the correlation with the first image at the predetermined depth is calculated and the rotation angle having the maximal correlation value is selected.

(65) It is to be noted that measurements obtained by the fingers **234** may not be regularly distributed in the azimuthal direction on the image. In this case, the disclosure may include a method **660** as shown on FIG. **14BIS**. This method includes measuring (**662**) the internal diameter of the caliper with a MFC module **230** as already described. Then, the caliper module(s) **230** may be utilized (**664**) to determine eccentricity of the toolstring (or portion thereof) in the borehole at one depth (at least) based on at least three measurements of the measuring fingers **234**. From this measurement, the azimuth of the contacting points of each measuring finger **234** and the tubular may be derived (**666**). An 2D image as presented above may be built (**668**) taking into account the eccentricity by defining the measurement azimuth as the azimuth of the contacting point of the finger on the tubular (**670**), versus regularly distributing the measurement azimuths. For example, as depicted in FIG. **14**, if an image contains 100 pixels in an azimuthal dimension, then in a first azimuthal measurement zone **690**, two measurement values **692** may be disposed so that they are separated by just one pixel, while in a second azimuthal measurement zone **694**, two measurement values **696** may be disposed on the image so that they are separated by two pixels. This may permit obtaining an accurate indication of defects in the casing (or other tubular), including dimensions of the defects.

(66) The depth- and azimuth-aligned **630** second borehole image log is then merged **640** with the first borehole image log to obtain a third borehole image log having a resolution greater than each resolution of the first and second borehole image logs. The merging **640** may comprise super-resolution of the first borehole image log utilizing the depth- and azimuth-aligned **630** second borehole image log.

(67) For example, each row in the first borehole image log comprises a number P of pixels. FIG. **15** depicts an example row **700** in the first borehole image log, and an example row **710** in the depth- and azimuth-aligned **630** second borehole image log, wherein each row **700**, **710** comprises ten pixels (i.e., P=10), and each pixel comprises a numeric value of the measured parameter and is shaded corresponding to the numeric value. Merging **640** the depth- and azimuth-aligned **630** second borehole image log with the first borehole image log may be contemplated in terms of each row in the first borehole image log. For example, for each pixel in an array of N pixels, wherein N is greater than P, and wherein each of the N pixels corresponds to one of a plurality of azimuthal ranges that collectively span the row in the first borehole image log, the merging **640** may comprise setting **645** a value of the measured parameter for that pixel equal to an average of values of the parameter measurements in the first borehole log and the depth- and azimuth-aligned **630** second borehole image log that correspond to azimuthal locations within the azimuthal range corresponding to that pixel. Thus, continuing with the example shown in FIG. **15**, an empty array **720** of twenty pixels (i.e., N=20) is depicted in vertical alignment with the azimuthally-corresponding pixels **730** of the first borehole image log row **700** and the azimuthally-corresponding pixels **740** of the depth- and azimuth-aligned **630** second borehole image log row **710**, and row **750** depicts setting **645** the pixel values equal to the average parameter measurements. For each pixel corresponding to an azimuthal range in which no parameter measurements in the first borehole log and the depth- and azimuth-aligned **630** second borehole image log exist, the measured parameter value for that pixel is set **650** to an interpolated value determined utilizing the value set **645** for neighboring pixels, as depicted by row **760** in FIG. **15**. It can also be noted on FIG. **15** that the measured values of the second caliper are not regularly distributed in a row **740** of the depth- and azimuth-aligned **630** second borehole image log, which is a representation corresponding to an eccentric caliper as explained above.

(68) The set **645** average values may be mean averages with no weighting or other discrimination between the first borehole image log and the depth- and azimuth-aligned **630** second borehole image log. However, the set **645** average values may be weighted averages giving more influence to the first borehole image log, such as in implementations in which the depth-alignment **605** and/or the azimuth-alignment **630** of the second borehole image log may be suspected of introducing processing errors. Such weighting may be based on predetermined and/or user-defined values.

(69) The number N may be at least twice as big as a maximum theoretical resolution M. For example, if the first and second borehole image logs comprise MFC data according to aspects described above, M may be based on a quotient of the width of the sensing fingers **234** and the ID of the casing, tubular, or borehole examined. More generally, M may be related to the resolution of the device that measures tool azimuth, such as  $M=360/\text{azimuth resolution}$ . For example, if the azimuth is precise to 0.1 degrees, then  $M=3600$ .

(70) Implementations of the method **600** within the scope of the present disclosure may also be utilized to merge more than two borehole image logs. In such implementations, the first borehole image log may be considered to be a reference borehole image log, whereas second, third, fourth, etc., borehole image logs may be considered to be candidate borehole image logs. Each candidate borehole image log is depth-aligned **605** to the reference borehole image log. Each depth-aligned **605** candidate borehole image log is then azimuth-aligned **630** to the reference borehole image log. The depth- and azimuth-aligned **630** candidate borehole image logs are then merged **640** with the reference borehole image log, such as via the above-described averaging **645** and interpolation **650**.

(71) FIG. **16** is a schematic view of at least a portion of an example implementation of a processing system **800** according to one or more aspects of the present disclosure. The processing system **800** may execute example machine-readable instructions to implement at least a portion of one or more of the methods and/or processes described herein, and/or to implement a portion of one or more of the example downhole tools described herein. The processing system **800** may be or comprise, for example, one or more processors, controllers, special-purpose computing devices, servers, personal computers, personal digital assistant (PDA) devices, smartphones, internet appliances, and/or other types of computing devices. The entirety or a portion of the processing system **800** may be implemented within downhole apparatus described above, including for performing at least a portion of the method **500** shown in FIG. **11**, the method **600** shown in FIG. **12**, and/or

other aspects described above. For example, at least a portion of the processing system **800** shown in FIG. **16** may be utilized in the environment of FIG. **1** in conjunction with MFC and/or other borehole image log acquisition and/or processing according to one or more aspects of the present disclosure. One or more components or functions of the processing system **800** may also or instead be implemented in wellsite surface equipment, perhaps including the surface equipment **132** depicted in FIG. **1**. One or more components or functions of the processing system **800** may also or instead be implemented in the P/C modules **210**, **220**, the caliper modules **230**, and/or the centralizer modules **240** described above.

(72) The processing system **800** may comprise a processor **812**, such as a general-purpose programmable processor, for example. The processor **812** may comprise a local memory **814** and may execute program code instructions **832** present in the local memory **814** and/or another memory device. The processor **812** may execute, among other things, machine-readable instructions or programs to implement the methods and/or processes described herein. The programs stored in the local memory **814** may include program instructions or computer program code that, when executed by an associated processor, cause a controller and/or control system implemented in surface equipment and/or a downhole tool to perform tasks as described herein. The processor **812** may be, comprise, or be implemented by one or more processors of various types operable in the local application environment, and may include one or more general-purpose processors, special-purpose processors, microprocessors, digital signal processors (DSPs), field-programmable gate arrays (FPGAs), application-specific ICs (ASICs), processors based on a multi-core processor architecture, and/or other processors.

(73) The processor **812** may be in communication with a main memory **817**, such as via a bus **822** and/or other communication means. The main memory **817** may comprise a volatile memory **818** and a non-volatile memory **820**. The volatile memory **818** may be, comprise, or be implemented by random-access memory (RAM), static RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), RAMBUS DRAM (RDRAM), and/or other types of RAM devices. The non-volatile memory **820** may be, comprise, or be implemented by read-only memory, flash memory, and/or other types of memory devices. One or more memory controllers (not shown) may control access to the volatile memory **818** and/or the non-volatile memory **820**.

(74) The processing system **800** may also comprise an interface circuit **824**. The interface circuit **824** may be, comprise, or be implemented by various types of standard interfaces, such as an Ethernet interface, a universal serial bus (USB), a third-generation input/output (3GIO) interface, a wireless interface, and/or a cellular interface, among other examples. The interface circuit **824** may also comprise a graphics driver card. The interface circuit **824** may also comprise a communication device, such as a modem or network interface card, to facilitate exchange of data with external computing devices via a network, such as via Ethernet connection, digital subscriber line (DSL), telephone line, coaxial cable, cellular telephone system, and/or satellite, among other examples.

(75) One or more input devices **826** may be connected to the interface circuit **824**. One or more of the input devices **826** may permit a user to enter data and/or commands for utilization by the processor **812**. Each input device **826** may be, comprise, or be implemented by a keyboard, a mouse, a touchscreen, a trackpad, a trackball, an image/code scanner, and/or a voice recognition system, among other examples.

(76) One or more output devices **828** may also be connected to the interface circuit **824**. One or more of the output devices **828** may be, comprise, or be implemented by a display device, such as a liquid crystal display (LCD), a light-emitting diode (LED) display, and/or a cathode ray tube (CRT) display, among other examples. One or more of the output devices **828** may also or instead be, comprise, or be implemented by a printer, speaker, and/or other examples.

(77) The processing system **800** may also comprise a mass storage device **830** for storing machine-readable instructions and data. The mass storage device **830** may be connected to the interface circuit **824**, such as via the bus **822**. The mass storage device **830** may be or comprise a floppy disk drive, a hard disk drive, a compact disk (CD) drive, and/or digital versatile disk (DVD) drive, among other examples. The program code instructions **832** may be stored in the mass storage device **830**, the volatile memory **818**, the non-volatile memory **820**, the local memory **814**, and/or on a removable storage medium **834**, such as a CD or DVD.

(78) The mass storage device **830**, the volatile memory **818**, the non-volatile memory **820**, the local memory **814**, and/or the removable storage medium **834** may each be a tangible, non-transitory storage medium. The modules and/or other components of the processing system **800** may be implemented in accordance with hardware (such as in one or more IC chips, such as an ASIC), or may be implemented as software or firmware for execution by a processor. In the case of firmware or software, the implementation can be provided as a computer program product including a computer readable medium or storage structure containing computer program code (i.e., software or firmware) for execution by the processor.

(79) In view of the entirety of the present disclosure, including the figures and the claims, a person having ordinary skill in the art will readily recognize that the present disclosure introduces an apparatus comprising a toolstring for use in a tubular extending into a subterranean formation, wherein the toolstring comprises a plurality of modular components that includes: one or more caliper modules each comprising a plurality of radially rotatable fingers for sensing an internal diameter of the tubular; and a power and control (P/C) module operable for distributing power and control signals to the one or more caliper modules; wherein the caliper and P/C modules each have an upper and a lower interface, wherein the lower interfaces of the caliper and P/C modules are identical, wherein the caliper and P/C modules are mechanically and electrically interconnectable via interconnection of upper interface of the caliper and lower interface of the P/C modules.

(80) In addition to the above, the person having ordinary skill in the art will readily recognize that the present disclosure introduces an apparatus comprising a toolstring for use in a tubular extending into a subterranean formation, wherein the toolstring comprises a plurality of modular components that includes: one or more caliper modules each comprising a plurality of radially rotatable fingers for sensing an internal diameter of the tubular; and a power and control (P/C) module operable for distributing power and control signals to the one or more caliper modules; wherein the wherein the caliper and P/C modules are mechanically and electrically interconnected via common lower interfaces of the caliper and P/C modules

(81) The plurality of modular components may further include one or more centralizer modules operable for centralizing the one or more caliper modules within the tubular, the P/C module may be operable for distributing power and control signals to the one or more centralizer modules, wherein the caliper, P/C and centralizer modules each have lower and upper interfaces, wherein the upper interfaces of at least the caliper and centralizer modules are identical, wherein the lower interfaces of the caliper, P/C and centralizer modules are identical, wherein the caliper, centralizer, and P/C modules are mechanically and electrically interconnectable via interconnection of the upper interface of a first module with the lower interface of a second module, wherein the first and second modules are distinct modules and wherein the first module includes at least one of the caliper and centralizer module, and with the second module includes at least one of the caliper, P/C and centralizer modules.

(82) The plurality of modular components may further include one or more centralizer modules operable for centralizing the one or more caliper modules within the tubular, the P/C module may be operable for distributing power and control signals to the one or more

centralizer modules; and the caliper, centralizer, and P/C modules may be mechanically and electrically interconnected by: common upper interfaces of the caliper and centralizer modules; and common lower interfaces of the caliper, centralizer, and P/C modules.

(83) The toolstring may be configured for conveyance within the tubular via one of a plurality of different types of conveyance means, and the modular components may be operable for use with each of the different types of conveyance means. The toolstring may further comprise: a logging head for connecting with the one type of conveyance means but not with at least one of the other types of conveyance means; and a telemetry module connected between the logging head and the P/C module, wherein the telemetry module may be operable with the one type of conveyance means but not with at least one of the other types of conveyance means. The toolstring may further comprise one of a plurality of different adapters, the different adapters may each be for use with one of the different types of conveyance means but not with at least one of the other types of conveyance means, and the one adapter may be connected between the telemetry module and the P/C module.

(84) The P/C module may comprise memory for storing data generated by the one or more caliper modules.

(85) The caliper module may be operable to actively open and close the fingers.

(86) Each caliper module may be operable to sense the internal diameter of the tubular by measuring displacement of each finger via, for each finger, a linear displacement sensor that translates radial displacement of the finger to linear displacement of an outer tip of the finger in contact with the internal diameter of the tubular. Each caliper module may be operable to: convert the linear displacement of each finger to an electrical analog signal; and convert the electrical analog signal to a digital signal.

(87) The toolstring may comprise at least a first and a second caliper module, and the fingers of the second caliper module may be azimuthally offset relative to the fingers of the first caliper module. The lower interface of one of the first and second caliper modules may be connected to an upper interface of the other of the first and second caliper modules.

(88) The one or more caliper modules may comprise one or more position sensors operable for determining depth and/or azimuth of the one or more caliper modules comprising the one or more position sensors.

(89) The toolstring may further comprise an additional tool for performing an additional measurement, and the P/C module may be configured to command operation of the additional tool based on data obtained by the one or more caliper modules.

(90) The P/C module may be configured to command a change in an operating parameter of the apparatus based on data obtained by the one or more caliper modules.

(91) The present disclosure also introduces a method comprising: obtaining first and second borehole image logs that are each a two-dimensional matrix, wherein depths of measurements of a parameter in a borehole are depicted along a first dimension of the matrix, azimuths of the measurements of the parameter in the borehole are depicted along a second dimension of the matrix, and values of the measurements of the parameter are depicted by different colors at the corresponding measurement depths and azimuths; then aligning the second borehole image log to the first borehole image log with respect to depth; then aligning the depth-aligned second borehole image log to the first borehole image log with respect to azimuth; and then merging the depth- and azimuth-aligned second borehole image log with the first borehole image log to obtain a third borehole image log having a resolution greater than each resolution of the first and second borehole image logs.

(92) Aligning the second borehole image log to the first borehole image log with respect to depth may comprise: converting the first borehole image log into a first one-dimensional log relating the parameter measurements to depth; converting the second borehole image log into a second one-dimensional log relating the parameter measurements to depth; performing a positioning and/or compression and/or dilation adjustment of the second one-dimensional log relative to the first one-dimensional log sufficient to match the second one-dimensional log to the first one-dimensional log; and performing the same positioning and/or compression and/or dilation adjustment on the second borehole image log. Converting the first and second borehole image logs into the respective first and second one-dimensional logs may comprise obtaining minimum, maximum, and average values of the parameter measurements at each depth at which a parameter measurement exists in both of the first and second borehole image logs. Aligning the depth-aligned second borehole image log to the first borehole image log with respect to azimuth may comprise, at each depth at which a parameter measurement exists in both the first borehole image log and the depth-aligned second borehole image log, rotating the depth-aligned second borehole image log sufficient to match the depth-aligned second borehole image log to the first borehole image log.

(93) Merging the depth- and azimuth-aligned second borehole image log with the first borehole image log may comprise super-resolution of the first borehole image log utilizing the depth- and azimuth-aligned second borehole image log.

(94) The measured parameter may be internal diameter of a tubular in the borehole.

(95) Each row in the first borehole image log may comprise a number P of pixels, and merging the depth- and azimuth-aligned second borehole image log with the first borehole image log may comprise, for each row in the first borehole image log: for each pixel in an array of N pixels, wherein N is greater than P, and wherein each of the N pixels corresponds to one of a plurality of azimuthal ranges that collectively span the row in the first borehole image log, setting a value of the measured parameter for that pixel equal to an average of values of the parameter measurements in the first borehole log and the depth- and azimuth-aligned second borehole image log that correspond to azimuthal locations within the azimuthal range corresponding to that pixel; and then for each pixel corresponding to an azimuthal range in which no parameter measurements in the first borehole log and the depth- and azimuth-aligned second borehole image log exist, setting the measured parameter value for that pixel to an interpolated value determined utilizing the set values for neighboring pixels. N may be at least twice as big as a maximum theoretical resolution.

(96) The present disclosure also introduces a method comprising: running a toolstring to a target depth in a borehole, wherein the toolstring comprises a first (in particular upper) tool and a second (in particular lower) tool, and wherein the first tool is an MFC module; extending sensing fingers of the MFC module; and logging with standard parameters until a defect is detected via operation of the MFC module at a first resolution, and then logging a zone of interest containing the defect via operation of the second tool at a second resolution greater than the first resolution.

(97) The MFC module may be a first MFC module, the second tool may be a second MFC module, logging the zone of interest may comprise logging with refined parameters, and the refined parameters may include a lower logging speed than of the standard parameters.

(98) The second tool may be an ultrasonic tool or an electromagnetic tool.

(99) The present disclosure also introduces a method comprising: measuring an internal diameter of a tubular with an MFC module comprising a plurality of measuring fingers distributed azimuthally around the MFC module, wherein each finger contacts the tubular at a respective contacting point; determining the eccentricity of the MFC module at least at a particular depth based on at least three internal diameter measurements and deriving the azimuth of the contacting points of each measuring finger with the tubular; and building a borehole image log that is a two-dimensional matrix, wherein depths of measurements of the internal diameter in a borehole are depicted along a first dimension of the matrix, azimuths of the measurements of the internal diameter in the borehole are depicted along a second

dimension of the matrix, and values of the internal diameter measurements are depicted by different colors at the corresponding measurement depths and azimuths, and wherein building the borehole image log includes defining each measurement azimuth at the at least particular depth as the azimuth of the contacting point between the corresponding measuring finger and the tubular.

(100) The foregoing outlines features of several embodiments so that a person having ordinary skill in the art may better understand the aspects of the present disclosure. A person having ordinary skill in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same functions and/or achieving the same benefits of the embodiments introduced herein. A person having ordinary skill in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions and alterations herein without departing from the spirit and scope of the present disclosure.

(101) The Abstract at the end of this disclosure is provided to comply with 37 C.F.R. § 1.72(b) to permit the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims.

## Claims

1. An apparatus comprising: a tool string for use in a tubular extending into a subterranean formation, wherein the tool string comprises a plurality of modular components that includes: a first and a second caliper module each comprising a plurality of radially rotatable fingers for sensing an internal diameter of the tubular, wherein the fingers are distributed around the circumference of the tool string and wherein the fingers of the second caliper module are azimuthally offset relative to the fingers of the first caliper module, wherein the fingers comprise sensing fingers for gathering caliper data, wherein the caliper data comprises data acquired from each one of the sensing fingers; wherein the caliper modules comprise an actuator for actively extending and retracting the fingers of the caliper modules; and a power and control (P/C) module operable for distributing power and control signals to the first and second caliper modules; wherein the caliper and P/C modules each have an upper and a lower interface, wherein the lower interfaces of the caliper and P/C modules are identical, wherein the caliper and P/C modules are mechanically and electrically interconnectable via interconnection of the upper interface of the first caliper module and the lower interface of the P/C module, and wherein the first caliper module includes a first controller, the second caliper module includes a second controller, and the first and second controllers are electrically connected to a master board of the P/C module in parallel by a first signal connection and in series by a second signal connection.
2. The apparatus of claim 1 wherein: the plurality of modular components further includes one or more centralizer modules operable for centralizing the first and second caliper modules within the tubular; the P/C module is operable for distributing power and control signals to the one or more centralizer modules; and wherein each of the one or more centralizer modules has lower and upper interfaces, wherein the upper interfaces of at least the first and second caliper and the one or more centralizer modules are identical, wherein the lower interfaces of the one or more centralizer modules are identical to the lower interfaces of the first and second caliper modules and the P/C module, wherein the first and second caliper modules, the one or more centralizer modules, and the P/C module are mechanically and electrically interconnectable via interconnection of the upper interface of a first module with the lower interface of a second module, wherein the first and second modules are distinct modules and wherein the first module includes at least one of the first or second caliper modules or one of the one or more centralizer modules, and wherein the second module includes at least one of the first or second caliper modules, the P/C module or one of the one or more centralizer modules.
3. The apparatus of claim 1 wherein the tool string is configured for conveyance within the tubular via one of a plurality of different types of conveyance, and wherein the modular components are operable for use with each of the different types of conveyance.
4. The apparatus of claim 3 wherein the tool string further comprises: a logging head for connecting with one type of conveyance but not with at least one of other types of conveyance; and a telemetry module connected between the logging head and the P/C module, wherein the telemetry module is operable with the one type of conveyance but not with at least one of the other types of conveyance.
5. The apparatus of claim 4 wherein the tool string further comprises one adapter of a plurality of different adapters, wherein the different adapters are each for use with one of the different types of conveyance but not with at least one of other types of conveyance, and wherein the one adapter is connected between the telemetry module and the P/C module.
6. The apparatus of claim 1 wherein the azimuthally offset fingers distributed around the circumference of the tool string enable mapping of a measured section of the tubular by integrating different measuring points, each measuring point associated with a different one of the sensing fingers.
7. The apparatus of claim 1 wherein the lower interface of one of the first and second caliper modules is connected to an upper interface of the other of the first and second caliper modules.
8. The apparatus of claim 1 wherein the first and second caliper modules comprise one or more position sensors operable for determining depth and/or azimuth of the first and second caliper modules comprising the one or more position sensors.
9. The apparatus of claim 1 wherein the tool string further comprises an additional tool for performing an additional measurement, and wherein the P/C module is configured to command operation of the additional tool based on data obtained by the first and second caliper modules.
10. The apparatus of claim 1 wherein the P/C module is configured to command a change in an operating parameter of the apparatus based on data obtained by the first and second caliper modules.
11. The apparatus of claim 1, wherein the caliper data gathered by each of the sensing fingers is received by a data acquisition device on the corresponding first or second caliper modules.
12. The apparatus of claim 1, wherein the P/C module is configured to send control signals to the first and second caliper modules to extend or retract the fingers of the first and second caliper modules.
13. A method comprising: running a tool string to a target depth in a borehole, wherein the tool string comprises a power and control (P/C) module, a first multi-finger caliper (MFC) module, and a second MFC module, wherein the first MFC module comprises a plurality of sensing fingers and wherein the sensing fingers are in a retracted position when running to the target depth; extending the plurality of sensing fingers of the first MFC module from the retracted position to an extended position, wherein each of the sensing fingers are configured to gather caliper data and transmit the caliper data to a block of sensors on the first MFC module; and logging with standard parameters until a defect is detected via operation of the first MFC module at a first resolution, and then logging a zone of interest containing the defect via operation of the second MFC module at a second resolution greater than the first resolution, wherein the sensing fingers of the first MFC module are distributed around the circumference of the tool string, thereby enabling mapping of a measured section of the borehole by integrating different measuring points in the caliper data associated with each of the sensing fingers, and wherein

the first MFC module includes a first controller, the second MFC module includes a second controller, and the first and second controllers are electrically connected to a master board of the P/C module in parallel by a first signal connection and in series by a second signal connection.

14. The method of claim 13 wherein: logging the zone of interest comprises logging with refined parameters; and the refined parameters include a lower logging speed than of the standard parameters.

15. The method of claim 14 wherein sensing fingers of the second MFC module are distributed around the circumference of the tool string and azimuthally offset from the sensing fingers of the first MFC module, and wherein logging the zone of interest comprises logging with each of the first and second MFC modules, which permits logging the zone of interest at the second resolution.

16. The method of claim 14, wherein the caliper data gathered by each of the sensing fingers is received by the block of sensors and transmitted to a data acquisition device on the first MFC module.

17. The method of claim 14, wherein the first MFC module comprises an actuator configured to actively extend and retract the plurality of sensing fingers of the first MFC module and wherein extending comprises engaging the actuator to extend the sensing fingers to the extended position.

18. The method of claim 14, further comprising retracting the sensing fingers of the first MFC module when logging is completed.

19. The method of claim 13 wherein the tool string further comprises an ultrasonic tool or an electromagnetic tool.

---