

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255681

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

EYRE; Nicholas J. et al.

SURGICAL ROBOTICS SYSTEMS WITH IMPROVED ROBOTIC ARMS

Abstract

A robotic surgical system can include one or more adjustable arm supports that support one or more robotic arms. The adjustable arm supports and/or robotic arms can be configured to be deployed from low mount positions, for example, from positions below the surface of the table. The robotic arms can include a plurality of joints providing a plurality of degrees of freedom. The joints may be grouped into a proximal shoulder, an elbow, and a distal wrist. The robotic arms can include one or more redundant degrees of freedom. An insertion mechanism, associated with the robotic arm and configured for providing insertion of an instrument along an assertion axis, can be provided at a distal end of the robotic arms.

Inventors: EYRE; Nicholas J. (Sunnyvale, CA), HILL; Aren Calder (Mountain View, CA), WEHRMANN; Sven (Redwood City, CA), WILSON; Colin Allen (Burlingame, CA), HUANG; Yanan (Foster City, CA), WILSON; Jason Tomas (Redwood City, CA), MINTZ; David Stephen (Mountain View, CA)

Applicant: Auris Health, Inc. (Santa Clara, CA)

Family ID: 67213389

Appl. No.: 19/186479

Filed: April 22, 2025

Related U.S. Application Data

parent US continuation 18440678 20240213 parent-grant-document US 12329477 child US 19186479

parent US continuation 17146035 20210111 ABANDONED child US 18440678

parent US continuation 16235062 20181228 parent-grant-document US 10888386 child US 17146035

us-provisional-application US 62618500 20180117

Publication Classification

Int. Cl.: **A61B34/30** (20160101); **A61B17/00** (20060101); **A61G13/04** (20060101); **A61G13/06** (20060101); **A61G13/08** (20060101); **A61G13/10** (20060101)

U.S. Cl.:

CPC **A61B34/30** (20160201); **A61G13/04** (20130101); **A61G13/06** (20130101); **A61G13/08** (20130101); **A61G13/10** (20130101); A61B2017/00477 (20130101); A61B2034/301 (20160201); A61B2034/306 (20160201); A61G2210/50 (20130101)

Background/Summary

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/440,678, filed Feb. 13, 2024, published as U.S. Publication No. 2024/0252262, which is a continuation of U.S. application Ser. No. 17/146,035, filed Jan. 11, 2021, published as U.S. Publication No. 2021/0205034, now abandoned, which is a continuation of U.S. application Ser. No. 16/235,062, filed Dec. 28, 2018, now U.S. Pat. No. 10,888,386, which claims priority to U.S. Provisional Application No. 62/618,500, filed Jan. 17, 2018, each of which is incorporated herein by reference. Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57.

BACKGROUND

Field

[0002] This description generally relates to surgical or medical robotics, and particularly to a robotics system configurable for a variety of surgical or medical procedures.

Description

[0003] Robotic technologies have a range of applications. In particular, robotic arms help complete tasks that a human would normally perform. For example, factories use robotic arms to manufacture automobiles and consumer electronics products. Additionally, scientific facilities use robotic arms to automate laboratory procedures such as transporting microplates. Recently, physicians have started using robotic arms to help perform surgical procedures. For instance, physicians use robotic arms to control surgical instruments inside a patient. However, existing medical systems including robotic arms have a high capital cost and are typically specialized to perform limited types of surgical procedures. Thus, physicians or their assistants may need to obtain multiple robotic arm systems to accommodate a range of surgical procedures. Manually reconfiguring a robotic arm system for each surgical procedure is also time-consuming and physically demanding for the physicians.

SUMMARY

[0004] A surgical (or medical) robotics system with robotic arms is configurable to perform a variety of surgical (or medical) procedures. A surgical robotics system can include one or more adjustable arm supports that support one or more robotic arms. The adjustable arm supports can be configured to attach to either a table, a column support of the table, or a base of the table to deploy the adjustable arm supports and robotic arms from a position below the table. In some examples, the adjustable arm supports include at least three or four degrees of freedom that allow for adjustment of the position of a bar or rail to which the robotic arms are mounted. One of the degrees of freedom can allow the adjustable arm support to be adjusted vertically relative to the table. A robotic surgical system can include two adjustable arm supports, each supporting one or

more robotic arms. The two adjustable arm supports can be independently adjusted. For example, each arm support can be adjusted to a different height relative to the table.

[0005] A surgical robotics system can also include one or more robotic arms. The one or more robotic arms can be configured to be mounted to the adjustable arm supports. In some embodiments, the robotic arms are configured to be deployed from low mount positions, for example, from positions below the surface of the table, although in other embodiments, the robotic arms can be deployed from positions above the surface of the table. The robotic arms can include a plurality of joints providing a plurality of degrees of freedom. In some embodiments, the robotic arms can include one or more redundant degrees of freedom.

[0006] In a first aspect, a system can include a table, a table support below the table, an arm support coupled to at least one of the table or table support, and a first robotic arm coupled to the arm support. The first robotic arm can include a proximal portion and a distal portion and at least four powered joints between the proximal portion and the distal portion, wherein each of the joints is capable of being actuated independently of the other joints, wherein the first robotic arm comprises an instrument drive mechanism configured to drive a surgical instrument. The system can also include an insertion mechanism associated with the first robotic arm to provide insertion of the instrument along an insertion axis, and a second robotic arm coupled to the arm support.

[0007] The system may also include one or more of the following features in any combination: (a) wherein the first robotic arm is translatable relative to the second robotic arm; (b) wherein the insertion mechanism is built within the instrument itself independently of the first robotic arm; (c) wherein the insertion mechanism is built within the first robotic arm; (d) wherein the insertion mechanism is configured to translate the instrument drive mechanism relative to an insertion body housing to translate the instrument along the insertion axis; (e) wherein the first robotic arm is capable of at least seven degrees of freedom, wherein at least one of the degrees of freedom is redundant; and/or (f) wherein the first robotic arm and the second robotic arm are capable of being stowed beneath the table.

[0008] In another aspect, a system includes a table, a table support below the table, an arm support coupled to at least one of the table or table support, and a first robotic arm coupled to the arm support, wherein the first robotic arm comprises a proximal link and a distal link and at least three joints coupled to a distal end of the distal link, wherein each of the joints is capable of being actuated independently of the other joints, wherein the first robotic arm comprises an instrument drive mechanism configured to drive a surgical instrument. The system may also include an insertion mechanism associated with the first robotic arm to provide insertion of the instrument along an insertion axis.

[0009] The system may also include one or more of the following features in any combination: (a) wherein at least two of the joints are rotary joints; (b) wherein at least one of the joints comprises an insertion axis; (c) wherein at least one of the joints rolls the instrument about the instrument axis; (d) wherein the at least one joint that rolls the instrument about the instrument axis is part of the first robotic arm or part of the instrument itself; (e) a second robotic arm coupled to the arm support; (f) wherein the first robotic arm is translatable relative to the second robotic arm; and/or (g) wherein the first robotic arm is capable of at least seven degrees of freedom, wherein at least one of the degrees of freedom is redundant.

[0010] In another aspect, a system includes a table, a table support for supporting the table, an arm support coupled to at least one of the table or the table support, and a first robotic arm coupled to the arm support, the first robotic arm capable of being stowed below the table and elevated. The first robotic arm includes a proximal portion and a distal portion, wherein the proximal portion comprises a base coupled to the arm support and the distal portion comprises an instrument drive mechanism comprising a plurality of motors, wherein the instrument drive mechanism is configured to drive a surgical instrument attached thereto. The system also includes a plurality of powered joints between the proximal portion and the distal portion thereby accommodating

movement of the instrument in multiple degrees of freedom, wherein each of the joints is capable of being actuated independently of the other joints, an insertion mechanism associated with the first robotic arm to provide insertion of the instrument along an insertion axis, and a second robotic arm coupled to the arm support, the second robotic arm capable of being stowed below the table and elevated.

[0011] The system may also include one or more of the following features in any combination: (a) wherein the insertion mechanism is built within the instrument itself independently of the first robotic arm; (b) wherein the first robotic arm is capable of at least seven degrees of freedom, wherein at least one of the degrees of freedom is redundant; (c) wherein the first robotic arm comprises proximal link and a distal link, wherein at least three joints are coupled to a distal end of the distal link, and wherein at least two of the joints coupled to the distal end of the distal link are rotary joints; and/or (d) wherein the surgical instrument comprises an endoscopic instrument.

[0012] In a another aspect, a system can include a table for supporting a patient positioned on the table, a table support below the table, and an arm support coupled to at least one of the table or table support. The system can also include a first robotic arm coupled to the arm support, wherein the first robotic arm comprises a proximal portion and a distal portion and at least four powered joints between the proximal portion and the distal portion, wherein each of the joints is capable of being actuated independently of the other joints, wherein the first robotic arm comprises an instrument drive mechanism configured to drive a surgical instrument. The system can also include an insertion mechanism associated with the first robotic arm to provide insertion of the instrument along an insertion axis. The system may include a second robotic arm coupled to the arm support.

[0013] The system may include one or more of the following features in any combination: (a) wherein the first robotic arm is translatable relative to the second robotic arm; (b) wherein the insertion mechanism is built within the instrument itself independently of the first robotic arm; (c) wherein the insertion mechanism is built within the first robotic arm; (d) wherein the insertion mechanism is configured to translate the instrument drive mechanism relative to an insertion body housing to translate the instrument along the insertion axis; (e) wherein the first robotic arm is capable of at least five degrees of freedom; (f) wherein the first robotic arm is capable of at least six degrees of freedom; (g) wherein the first robotic arm is capable of at least seven degrees of freedom; (h) wherein at least one of the seven degrees of freedom is redundant; (i) a second arm support, wherein the arm support and second arm support can have a height differential; (j) wherein the arm support is capable of adjusting its tilt angle; (k) wherein the first robotic arm and the second robotic arm are capable of being stowed beneath the table; (l) wherein the table support comprises a base, wherein the first robotic arm and the second robotic arm are capable of being stowed in the base; (m) at least one computer-readable memory having stored thereon executable instructions, and at least one processor in communication with the at least one computer-readable memory and configured to execute the instructions to cause the system to move the first and second robotic arms from a stowed position in the base to a vertically elevated position adjacent the table; (n) an instrument having a handle attached to the instrument drive mechanism of the first robotic arm; (o) wherein roll is provided in the handle of the instrument or the instrument drive mechanism; (p) wherein the first robotic arm further comprises a second instrument drive mechanism; and/or (q) wherein the arm support is capable of vertical adjustment relative to the table.

[0014] In another aspect, a system can include a table, a table support for supporting the table, an arm support coupled to at least one of the table or the table support, and a first robotic arm coupled to the arm support, the first robotic arm capable of being stowed below the table and elevated. The first robotic arm can include a proximal portion and a distal portion, wherein the proximal portion comprises a base coupled to the arm support and the distal portion comprises an instrument drive mechanism comprising a plurality of motors, wherein the instrument drive mechanism is configured to drive a surgical instrument attached thereto; and a plurality of powered joints

between the proximal portion and the distal portion thereby accommodating movement in multiple degrees of freedom, wherein each of the joints is capable of being actuated independently of the other joints. The system can include an insertion mechanism associated with the first robotic arm to provide insertion of the instrument along an insertion axis. The system may include a second robotic arm coupled to the arm support, the second robotic arm capable of being stowed below the table and elevated.

[0015] The system may include one or more of the following features in any combination: (a) at least one computer-readable memory having stored thereon executable instructions, and at least one processor in communication with the at least one computer-readable memory and configured to execute the instructions to cause the system to at least move the first and second robotic arms from a stowed position to a vertically elevated position adjacent the table; (b) wherein the first robotic arm is capable of rolling the instrument about its axis, inserting the surgical instrument along its axis, and pitching and yawing the instrument about a point along its axis; (c) wherein the insertion mechanism is built within the instrument itself independently of the first robotic arm; (d) wherein the instrument drive mechanism is part of a wrist of the first robotic arm; (e) wherein the wrist comprises the instrument drive mechanism and an insertion body housing, wherein the insertion mechanism is configured to translate the instrument drive mechanism relative to the insertion body housing to translate the instrument along the insertion axis; (f) wherein at least one of the first robotic arm and the second robotic arm is capable of translating along the arm support; (g) wherein the first robotic arm comprises a wrist with at least three powered rotational joints, and wherein the wrist is capable of pitch and yaw; and/or (h) wherein at least one of the first robotic arm and the second robotic arm holds a camera.

[0016] In another aspect, provided is a method that can include: moving a robotic arm from a stowed position, in which the robotic arm is located below a surface of a patient-support table, to an active position, in which at least a distal portion of the robotic arm is located above the surface of the table; wherein, in the active position, an axis of an instrument coupled to the distal portion of the robotic arm is aligned with a port into a body of a patient on the surface of the table. In some embodiments, the robotic arm is attached to at least one of the table or a table support positioned below the table.

[0017] In another aspect, a system is provided that can include a robotic arm comprising: a base configured to mount to an arm support; a proximal link comprising a proximal end and a distal end, the proximal end of the proximal link connected to the base by a shoulder; a distal link comprising a proximal end and a distal end, the proximal end of the distal link connected to the distal end of the proximal link by an elbow; and a wrist at the distal end of the distal link. The system can include at least one computer-readable memory having stored thereon executable instructions, and at least one processor in communication with the at least one computer-readable memory and configured to execute the instructions to cause the system to at least move the robotic arm from a stowed position, in which the robotic arm is located below a surface of a table configured to support a patient, to an active position, in which at least a distal portion of the robotic arm is located above the surface of the table. In some embodiments, in the active position, an axis of an instrument coupled to the distal portion of the robotic arm is aligned with a port into a body of a patient on the surface of the table. In some embodiments, the robotic arm is attached to at least one of the table or a table support positioned below the table.

[0018] In another aspect provided is a method that can include: inserting, with a robotic arm, an instrument into a patient through a port, the instrument located at a distal end of the robotic arm; manipulating, with the robotic arm, at least one of pitch, yaw, or roll of the instrument relative to the port; and manipulating the robotic arm to adjust a position of a proximal end of the robotic arm relative to the port.

[0019] The method can include one or more of the following features in any combination: (a) wherein manipulating the instrument with the robotic arm and manipulating the robotic arm occur

simultaneously; and/or (b) wherein further manipulating the robotic arm to adjust the position of the proximal end of the robotic arm does not affect the position or orientation of the instrument attached to the distal end of the robotic arm.

[0020] In another aspect, provided is a method that can include: inserting, with a robotic arm, an instrument into a patient through a port, the instrument located at a distal end of the robotic arm; and manipulating the robotic arm to adjust the position of a proximal end of the robotic arm relative to the port without affecting the position or orientation of the instrument. The method may also include manipulating, with the robotic arm, at least one of pitch, yaw, or roll of the instrument relative to the port.

[0021] In another aspect, provided is a system that can include a first robotic arm coupled to the arm support, the robotic arm comprising: a base configured to mount to an arm support; a proximal link comprising a proximal end and a distal end, the proximal end of the proximal link connected to the base by a powered shoulder; a distal link comprising a proximal end and a distal end, the proximal end of the distal link connected to the distal end of the proximal link by a powered elbow; a powered wrist at the distal end of the distal link; and an insertion mechanism at a distal end of the robotic arm and configured to provide insertion of an instrument along an insertion axis, the insertion mechanism attached to the wrist. The system may also include a port, wherein the instrument extends through the port to assist in a surgical procedure.

[0022] In some embodiments, the system may include one or more of the following features in any combination: (a) wherein at least one of the shoulder, elbow or wrist is motorized; (b) wherein the insertion mechanism comprises a mechanism built within the instrument itself to provide insertion of the instrument along the insertion axis; (c) wherein the insertion mechanism comprises a shaft of the instrument moving relative to a handle of the instrument along the insertion axis; (d) wherein the insertion mechanism comprises an instrument drive mechanism that is configured to translate along an insertion body housing to provide insertion of the instrument along the insertion axis; (e) wherein the wrist comprises at least two degrees of freedom; (f) wherein the wrist is capable of pitch and yaw; (g) wherein the elbow comprises at least one degree of freedom; (h) wherein the shoulder comprises at least two degrees of freedom; (i) wherein the at least two degrees of freedom of the shoulder includes at least pitch and yaw or pitch and translation; (j) wherein the base is configured to mount to the arm support via a linear joint configured to allow the base to translate along a rail of the arm support; and/or (k) wherein the shoulder, the elbow, and the wrist are configured to provide at least six degrees of freedoms to allow the robotic arm to position the instrument at a remote center and control at least pitch, yaw, and roll of the instrument about the remote center.

[0023] In another aspect, provided is a system that can include a table, an arm support positioned relative to the table, and a robotic arm coupled to the arm support. The robotic arm can include a base configured to mount to the arm support; a proximal link comprising a proximal end and a distal end, the proximal end of the proximal link connected to the base by a powered shoulder; a distal link comprising a proximal end and a distal end, the proximal end of the distal link connected to the distal end of the proximal link by a powered elbow; and a powered wrist at the distal end of the distal link and configured to couple to an instrument. In some embodiments, the shoulder, the elbow, and the wrist are configured to provide at least six degrees of freedoms to allow the robotic arm to position the instrument at a remote center and control at least pitch, yaw, and roll of the instrument about the remote center, and wherein the base is translatable relative to the arm support. The system can include an insertion mechanism at a distal end of the robotic arm and configured to provide insertion of an instrument along an insertion axis, and a port, wherein the instrument extends through the port to assist in a surgical procedure.

[0024] The system can include one or more of the following features in any combination: (a) wherein the wrist comprises a joint configured to provide at least three degrees of freedom to permit adjustment of at least pitch, yaw, and roll of an instrument; (b) wherein the wrist comprises

a partial spherical joint; (c) wherein the base is configured to mount to an arm support via a linear joint configured to allow the base to translate along a rail of the arm support, the arm support is located below a surface of a table, and the table configured to support a patient; and/or (d) wherein the rail is located below the surface of the table.

[0025] In another aspect, provided is a system that can include a robotic arm comprising a base configured to mount to an arm support; a proximal link comprising a proximal end and a distal end, the proximal end of the proximal link connected to the base by a shoulder; a distal link comprising a proximal end and a distal end, the proximal end of the distal link connected to the distal end of the proximal link by an elbow; and a wrist at the distal end of the distal link. The system can also include at least one computer-readable memory having stored thereon executable instructions, and at least one processor in communication with the at least one computer-readable memory and configured to execute the instructions to cause the system to at least: actuate at least one of the wrist, the elbow, and the shoulder to adjust a position of the robotic arm; position an instrument with the robotic arm such that an axis of the instrument extends through a remote center aligned with a port in the body of the patient; and in response to receiving a command, actuate at least one of the wrist, the elbow, and the shoulder, to manipulate the instrument according to the command.

[0026] The system can include one or more of the following features in any combination: (a) wherein the instructions, when executed cause the system to actuate at least one of the wrist, the elbow, and the shoulder to adjust a position of the robotic arm relative to at least one of a patient, a table support the patient, a medical imaging device, and an additional robotic arm; (b) wherein the additional robotic arm is mounted to the arm support; (c) an arm support mounted to a column supporting the table, the arm support including a rail, the base of the robotic arm mounted to the rail via a linear motorized joint; (d) wherein the instructions, when executed, further cause the at least one processor to cause the system to actuate at least the linear motorized joint to translate the base along the rail; (e) wherein the rail is located below a surface of the table; and/or (f) wherein the instructions, when executed, further cause the system to actuate at least the linear joint to translate the base along the rail in response to the command simultaneously with actuating at least one of the wrist, the elbow, and the shoulder, to manipulate the instrument according to the command.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] FIG. 1 is an isometric view of a surgical robotics system according to an embodiment.

[0028] FIG. 2A is an isometric view of a table of the surgical robotics system according to one embodiment.

[0029] FIG. 2B is a top view of the table according to one embodiment.

[0030] FIG. 2C is a top view of a swivel segment of a table according to one embodiment.

[0031] FIG. 2D is a top view of a swivel segment of the table according to one embodiment.

[0032] FIG. 2E is an isometric exploded view of components of a swivel mechanism according to one embodiment.

[0033] FIG. 2F is a cross sectional view of the swivel mechanism shown in FIG. 2E according to one embodiment.

[0034] FIG. 2G is a bottom view of the swivel mechanism shown in FIG. 2E according to one embodiment.

[0035] FIG. 2H is an isometric view of a folding segment of the table according to one embodiment.

[0036] FIG. 2I is another isometric view of a folding segment of the table according to one embodiment.

[0037] FIG. 2J is an isometric view of a trapdoor of the table according to one embodiment.

[0038] FIG. 2K is an isometric view of pivots of the table according to one embodiment.

[0039] FIG. 2L is a side view of the table rotated about an axis of pitch according to one embodiment.

[0040] FIG. 2M is an isometric view of the table rotated about an axis of row according to one embodiment.

[0041] FIG. 3A is a side cutaway view of a column of the surgical robotics system according to one embodiment.

[0042] FIG. 3B is an isometric cutaway view of the column according to one embodiment.

[0043] FIG. 3C is a top view of the column according to one embodiment.

[0044] FIG. 4A is an isometric view of a surgical robotics system with a column-mounted robotic arm according to one embodiment.

[0045] FIG. 4B is an isometric view of a surgical robotics system with column-mounted robotic arms according to one embodiment.

[0046] FIG. 5A is an isometric view of a column ring of the surgical robotics system according to one embodiment.

[0047] FIG. 5B is a bottom view of a set of column rings underneath a table according to one embodiment.

[0048] FIG. 5C is an isometric view of the set of column rings mounted to a column according to one embodiment.

[0049] FIG. 5D is an isometric cutaway view of an arm mount of a column ring according to one embodiment.

[0050] FIG. 5E is an isometric cutaway view of the arm mount in a telescoped configuration according to one embodiment.

[0051] FIG. 6A is an isometric view of a robotic arm of the surgical robotics system according to one embodiment.

[0052] FIG. 6B is an isometric view of an arm segment joint of the robotic arm according to one embodiment.

[0053] FIG. 6C is an isometric view of another arm segment joint of the robotic arm according to one embodiment.

[0054] FIG. 7A is an isometric view of a surgical robotics system with column-mounted arms configured to access the lower body area of a patient according to one embodiment.

[0055] FIG. 7B is a top view of the surgical robotics system with column-mounted arms configured to access the lower body area of the patient according to one embodiment.

[0056] FIG. 7C is an isometric view of an imaging device and a surgical robotics system with column-mounted arms configured to access the lower body area of a patient according to one embodiment.

[0057] FIG. 7D is a top view of the imaging device and the surgical robotics system with column-mounted arms configured to access the lower body area of the patient according to one embodiment.

[0058] FIG. 7E is an isometric view of the surgical robotics system with column-mounted arms configured to access the core body area of a patient according to one embodiment.

[0059] FIG. 7F is an isometric view of the surgical robotics system with column-mounted arms configured to access the upper body area of a patient according to one embodiment.

[0060] FIG. 8A is an isometric view of a base of a surgical robotics system according to one embodiment.

[0061] FIG. 8B is an isometric view of open panels of the base according to one embodiment.

[0062] FIG. 8C is an isometric view of robotic arms stowed inside a base of a surgical robotics system according to one embodiment.

[0063] FIG. 8D is an isometric view of robotic arms stowed underneath a table of a surgical

robotics system according to one embodiment.

[0064] FIG. **8E** is an isometric view of robotic arms stowed above a base of a surgical robotics system according to one embodiment.

[0065] FIG. **8F** is another isometric view of robotic arms stowed above a base of a surgical robotics system according to one embodiment.

[0066] FIG. **8G** is an isometric view of outrigger casters on a base of a surgical robotics system according to one embodiment.

[0067] FIG. **8H** is another isometric view of the outrigger casters on the base of the surgical robotics system according to one embodiment.

[0068] FIG. **8I** is a side view of an outrigger caster in a mobile configuration according to one embodiment.

[0069] FIG. **8J** is a side view of the outrigger caster in a stationary configuration according to one embodiment.

[0070] FIG. **9A** is an isometric view of a surgical robotics system with a rail-mounted robotic arm according to one embodiment.

[0071] FIG. **9B** is an isometric view of a surgical robotics system with rail-mounted robotic arms according to one embodiment.

[0072] FIG. **10A** is an isometric view of base rails of a surgical robotics system according to one embodiment.

[0073] FIG. **10B** is an isometric view of arm mounts on the base rail according to one embodiment.

[0074] FIG. **10C** is an isometric cutaway view of an arm mount on the base rail according to one embodiment.

[0075] FIG. **10D** is cross sectional views of the base rail according to one embodiment.

[0076] FIG. **11** is an isometric view of a surgical robotics system with column-mounted robotics arms and rail-mounted robotic arms according to one embodiment.

[0077] FIG. **12** is an isometric view of a surgical robotics system with column-mounted robotics arms on a platform separate from a table and a base of the surgical robotics system according to one embodiment.

[0078] FIG. **13A** is an isometric view of a surgical robotics system with an adjustable arm support according to one embodiment.

[0079] FIG. **13B** is an end view of the surgical robotics system with an adjustable arm support of FIG. **13A**.

[0080] FIG. **14A** is an end view of a surgical robotics system with two adjustable arm supports mounted on opposite sides of a table according to one embodiment.

[0081] FIG. **14B** is an isometric view of a surgical robotics system with two adjustable arm supports and a plurality of robotic arms configured for a laparoscopic procedure according to one embodiment.

[0082] FIG. **14C** is an isometric view of a surgical robotics system with two adjustable arm supports and a plurality of robotic arms configured for a laparoscopic procedure according to one embodiment.

[0083] FIG. **15A** is an isometric view of a surgical robotics systems with two adjustable arm supports that are configured to translate to adjust the position of the adjustable arm supports according to one embodiment.

[0084] FIG. **15B** is an isometric view of a surgical robotics system with an adjustable arm support and robotic arm configured for an endoscopic procedure according to one embodiment.

[0085] FIG. **16** is an isometric view of a surgical robotics system with an adjustable arm support configured with a rail capable of tilting according to one embodiment.

[0086] FIG. **17A** is an isometric view of a surgical robotics system with adjustable arm supports positioned to allow access for a C-arm of a medical imaging device according to one embodiment.

[0087] FIG. **17B** is an isometric view of the surgical robotics system of FIG. **17A** with the

adjustable arm supports positioned to allow access for the C-arm of the medical imaging device according to another embodiment.

[0088] FIG. **18A** is an isometric view of a surgical robotics system with adjustable arm supports positioned in a deployed configuration according to one embodiment.

[0089] FIG. **18B** is an isometric view of a surgical robotics system with adjustable arm supports positioned in a stowed configuration according to one embodiment.

[0090] FIG. **19** is a flow chart illustrating a method for operating a surgical robotics system with adjustable arm supports according to one embodiment.

[0091] FIG. **20** is a block diagram of a surgical robotics system with adjustable arm supports according to one embodiment.

[0092] FIG. **21** is an isometric view of a robotic arm according to one embodiment.

[0093] FIG. **22** is an overhead view of a robotic surgical system including a plurality of robotic arms performing a laparoscopic procedure according to one embodiment.

[0094] FIG. **23** is an isometric view of a robotic arm that includes two instrument drive mechanisms according to one embodiment.

[0095] FIG. **24** is an isometric view of an instrument with an instrument based insertion architecture attached to a distal end of a robotic arm according to one embodiment.

[0096] FIG. **25A** is a side view of a robotic arm with an insertion axis body positioned in a first orientation according to one embodiment.

[0097] FIG. **25B** is a side view of the robotic arm of FIG. **25A** with the insertion axis body positioned in a second orientation according to one embodiment.

[0098] FIG. **26A** is a side view of a robotic arm configured with an attached cannula according to one embodiment.

[0099] FIG. **26B** is a side view of a robotic arm configured with a detached cannula according to one embodiment.

[0100] FIG. **27A** is an isometric view of a system including a plurality of robotic arms performing a laparoscopic procedure, wherein one of the arms is configured with an attached cannula, according to one embodiment.

[0101] FIG. **27B** is an isometric view of a system including a plurality of robotic arms performing a laparoscopic procedure, wherein one of the arms is configured with a detached cannula, according to one embodiment.

[0102] FIG. **28** is an isometric view of a robotic arm that includes a wrist having an additional rotational joint according to one embodiment.

[0103] FIG. **29A** is an isometric view of a robotic arm that includes a tilted base according to one embodiment.

[0104] FIG. **29B** is a side view of the robotic arm of FIG. **29A** according to one embodiment.

[0105] FIG. **30** is an isometric view of a robotic arm with a telescoping link according to one embodiment.

[0106] FIG. **31** illustrates a perspective view of an instrument device manipulator for a surgical robotic system, according to one embodiment.

[0107] FIG. **32** illustrates a side view of the instrument device manipulator of FIG. **31**, according to one embodiment.

[0108] FIG. **33** illustrates a front-perspective exploded view of an example surgical tool secured to the instrument device manipulator of FIG. **31**, according to one embodiment.

[0109] FIG. **34** illustrates a back-perspective exploded view of an example surgical tool secured to the instrument device manipulator of FIG. **31**, according to one embodiment.

[0110] FIG. **35** illustrates a zoomed-in, perspective view of an actuation mechanism for engagement and disengagement of a surgical tool from a surgical tool holder, according to one embodiment.

[0111] FIGS. **36A** and **36B** illustrate a process of engaging and disengaging a surgical tool from a

sterile adapter, according to one embodiment.

[0112] FIGS. **37A** and **37B** illustrate a process of engaging and disengaging a surgical tool from a sterile adapter, according to an additional embodiment.

[0113] FIG. **38A** illustrates a perspective view of a mechanism for rolling a surgical tool holder within an instrument device manipulator, according to one embodiment.

[0114] FIG. **38B** illustrates a cross-sectional view of an instrument device manipulator, according to one embodiment.

[0115] FIGS. **38C** and **38D** illustrates partially exploded, perspective views of the internal components of an instrument device manipulator and certain electrical components thereof, according to one embodiment.

[0116] FIG. **38E** illustrates a zoomed-in, perspective view of electrical components of an instrument device manipulator for roll indexing the surgical tool holder, according to one embodiment.

[0117] FIG. **39** illustrates a side view of an instrument having an instrument based insertion architecture, according to one embodiment.

[0118] FIG. **40** illustrates a schematic diagram showing a first actuation mechanism for actuating an end effector, according to one embodiment.

[0119] FIG. **41** illustrates a zoomed-in side view of a first actuation mechanism of the instrument of FIG. **39**, according to one embodiment.

[0120] FIG. **42** illustrates a zoomed-in perspective view of a first actuation mechanism of the instrument of FIG. **39**, according to one embodiment.

[0121] FIG. **43** illustrates a view of a pulley and cable of the instrument of FIG. **39**, prior to actuation of the pulley, according to one embodiment.

[0122] FIG. **44** illustrates a view of a pulley and cable of the instrument of FIG. **39**, following actuation of the pulley, according to one embodiment.

[0123] FIG. **45** illustrates a side view of a second actuation mechanism including a spool for shaft translation, according to one embodiment.

[0124] FIG. **46** illustrates a perspective view of an alternative spool using a single cable for shaft translation, according to one embodiment.

[0125] FIG. **47** illustrates a perspective view of an alternative spool using more than one cable for shaft translation, according to one embodiment.

[0126] FIG. **48** illustrates a front view of a handle including the spool of FIG. **46**, according to one embodiment.

[0127] FIG. **49** illustrates a schematic diagram showing an alternative architecture for actuating an end effector and shaft translation, according to one embodiment.

[0128] FIG. **50A** illustrates a zoomed-in front view of an instrument incorporating the alternative architecture for actuating an end effector and shaft insertion of FIG. **49**, according to one embodiment.

[0129] FIG. **50B** illustrates a top perspective view of an instrument incorporating the alternative architecture for actuating an end effector and shaft insertion of FIG. **49**, according to one embodiment.

[0130] FIG. **51** illustrates a top perspective view of a handle and shaft of an instrument, according to one embodiment.

[0131] FIG. **52A** illustrates a schematic view of a cross-section of an instrument shaft utilizing the insertion architecture shown in FIG. **40**, according to one embodiment.

[0132] FIG. **52B** illustrates a schematic view of a cross-section of an instrument shaft utilizing the insertion architecture shown in FIG. **49**, according to one embodiment.

[0133] FIG. **53** illustrates a schematic diagram showing an architecture for driving a knife in a vessel sealer, according to one embodiment.

[0134] FIG. **54** illustrates a schematic diagram showing an alternative architecture for driving a

knife in a vessel sealer, according to one embodiment.

[0135] FIG. **55** illustrates a schematic diagram showing yet another alternative architecture for driving a knife in a vessel sealer, according to one embodiment.

[0136] FIG. **56** illustrates a schematic diagram showing an architecture for making a rigid camera an insertion instrument, according to one embodiment.

[0137] FIG. **57** shows a first insertion architecture that allows a camera to be separated from an insertion handle, according to one embodiment.

[0138] FIGS. **58** and **59** show a second insertion architecture that allows a camera to be separated from an insertion handle, according to one embodiment.

[0139] FIG. **60** illustrates a diagram showing an alternative architecture for shaft translation, according to another embodiment.

[0140] FIG. **61** shows a side cross-sectional view of an instrument having multiple seals to prevent air leakage from a patient.

[0141] FIG. **62** shows a front cross-sectional view of the instrument having the multiple seals.

[0142] Reference will now be made in detail to several embodiments, examples of which are illustrated in the accompanying figures. It is noted that wherever practicable similar or like reference numbers may be used in the figures and may indicate similar or like functionality. The figures depict embodiments of the described system (or method) for purposes of illustration only. One skilled in the art will readily recognize from the following description that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles described herein.

DETAILED DESCRIPTION

I. System Overview

[0143] FIG. **1** is an isometric view of a surgical robotics system **100** according to an embodiment. A user, e.g., a physician or assistant, uses the surgical robotics system **100** to perform robotically-assisted surgery on a patient. The surgical robotics system **100** includes a table **101**, column **102**, and base **103** physically coupled together. Although not shown in FIG. **1**, the table **101**, column **102**, and/or base **103** may house, connect to, or use electronics, fluidics, pneumatics, aspiration, or other electrical and mechanical components that support the function of the surgical robotics system **100**.

[0144] The table **101** provides support for a patient undergoing surgery using the surgical robotics system **100**. Generally, the table **101** is parallel to the ground, though the table **101** may change its orientation and configuration to facilitate a variety of surgical procedures. The table **101** is further described with reference to FIGS. **2A-I** in Section II. Table.

[0145] The column **102** is coupled to the table **101** on one end and coupled to the base **103** on the other end. Generally, the column **102** is cylindrically shaped to accommodate column rings coupled to the column **102**, which are further described with reference to FIGS. **5A-E** in Section V. Column Ring, however the column **102** may have other shapes such as oval or rectangular. The column **102** is further described with reference to FIGS. **3A-B** in Section III. Column.

[0146] The base **103** is parallel to the ground and provides support for the column **102** and the table **101**. The base **103** may include wheels, treads, or other means of positioning or transporting the surgical robotics system **100**. The base **103** is further described with reference to FIGS. **8A-E** in Section VIII. Base.

[0147] Alternative views and embodiments of the surgical robotics system **100** including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/162,486 filed May 15, 2015 and U.S. Provisional Application No. 62/162,467 filed May 15, 2015.

II. Table

[0148] FIG. **2A** is an isometric view of a table **201A** of the surgical robotics system **100** according to one embodiment. The table **201A** is an embodiment of the table **101** in FIG. **1**. The table **201A**

includes a set of one or more segments. Generally, a user changes the configuration of the table **201A** by configuring the set of segments. The surgical robotics system **100** may also configure the segments automatically, for example, by using a motor to reposition a segment of the set of segments. An example set of segments is shown in FIG. 2A, and includes a swivel segment **210**, center segment **212**, foldable segment **214**, detachable segment **216**, and table base **218**. The swivel segment **210**, center segment **212**, and foldable segment **214** are coupled to the table base **218**. FIG. 2A shows the detachable segment **216** separated from the table base **218**, though the detachable segment **216** may also be coupled to the table base **218**. In various implementations, additional or fewer segments may be used.

[0149] An advantage of configuring the set of segments of the table **201A** is that a configured table **201A** may provide greater access to a patient on the table **201A**. For instance, the surgical robotics system **100** performs a surgical procedure on the patient that requires access to the groin area of the patient. When a patient is laying face-up on a typical surgical bed, there is more access to the patient's head, arms, and legs than to the patient's groin area. Since the groin area is located toward the center of the patient's body, the legs often obstruct access to the groin area. The detachable segment **216** is detachable from the table **201A**. The table **201A** without the detachable segment **216** provides greater access to the groin area of a patient lying on the table **201A** with the patient's head toward the side of the table **201A** with the swivel segment **210**. In particular, removing the detachable segment **216** opens more space, for example, to insert a surgical instrument into the groin area. If additional space is required to access the groin area, the foldable segment **214** may be folded down, away from the patient (further described in FIG. 2H). The center segment **212** includes a cutout section **220**, which also provides greater access to the groin area.

[0150] The swivel segment **210** pivots laterally relative to the table **201A**. The swivel segment **210** includes an arcuate edge **222** and the center segment **212** also includes an arcuate edge **224**. Due to the arcuate edges, there is minimal gap between the swivel segment **210** and the center segment **212** as the swivel segment **210** pivots away from or toward the table **201A**. A configuration of the table **201A** with the swivel segment **210** pivoted away from the table **201A** provides greater access to the groin area because the other segments of the table **201A** are not obstructing the groin area. An example of this configuration is further described with respect to FIGS. 7C-D in Section VII. A. Lower Body Surgery. Additionally, the swivel segment **210** also includes a cutout section **226**, which provides yet greater access to the groin area.

[0151] FIG. 2B is a top view of the table **201A** according to one embodiment. Specifically, FIG. 2B shows the table base **218** with a partial cutaway view and a portion of the swivel segment **210**. Components inside the swivel segment **210** are exposed for purposes of illustration. The table base **218** includes double curved rails **230**, that is, two curved linear rails (also referred to as a first bearing subassembly). The swivel segment **210** also includes double curved rails **232** (also referred to as a second bearing subassembly). The first bearing assembly coupled to the second bearing assembly may be referred to as a bearing mechanism. The double curved rails **230** of the table base **218** engage with the double curved rails **232** of the swivel segment **210**. Both double curved rails are concentric to a virtual circle **234**. The swivel segment **210** pivots about an axis passing through a point **236** at the center of the virtual circle **234** perpendicular to the plane of the table base **218**. The double curved rails **230** of the table base **218** include a first carriage **238** and a second carriage **240**. Similarly, the double curved rails **232** of the swivel segment **210** include a first carriage **242** and a second carriage **244**. The carriages provide structural support and negate moment loads, which enables the double curved rails to support high cantilevered loads up to at least 500 pounds. For instance, pivoting a patient away from the table **201A** generates a high cantilevered load on the double curved rails supporting the patient's weight. The table base **218** and swivel segment **210** may include additional load-sharing components such as rollers, cam followers, and bearings. In some embodiments, the swivel segment **210** and table base **218** each include a single curved rail instead of double curved rails. Further, each curved rail may include additional or fewer carriages.

[0152] FIG. 2C is a top view of the swivel segment **210** of the table **201A** according to one embodiment. The center of mass **250** illustrates the center of mass of the swivel segment **210** and a patient (not shown) lying on the swivel segment **210**. The swivel segment **210** is pivoted at an angle α about the axis **236**. Compared to the center of mass **246** shown in FIG. 2D, the center of mass **250** is closer toward the table base **218** (corresponding to table base **218B** in FIG. 2D), even though the swivel segments in both FIG. 2C and FIG. 2D are each pivoted at the same angle α . Keeping the center of mass **250** close toward the table **218** helps the swivel segment **210** support greater cantilever loads—due to the patient—without tipping over the surgical robotics system. In some embodiments, the swivel segment **210** may be rotated up to an angle of 30 degrees or 45 degrees relative to table base **218**, while keeping the center of mass of the swivel segment **210** above the table **201A**.

[0153] FIG. 2D is a top view of a swivel segment **210A** of a table **201B** according to one embodiment. Specifically, the table **201B** includes a table base **218A** and a swivel segment **210A**. The table **201B** does not include double curved rails, but instead includes a swivel mechanism **278** that is further described below with reference to FIGS. 2E-G. The center of mass **246** illustrates the center of mass of the swivel segment **210A** and a patient (not shown) lying on the swivel segment **210A**. The swivel segment **210A** is pivoted at an angle α about an axis **248**. Accordingly, the center of mass **246** is positioned off of the table base **218A**.

[0154] FIG. 2E is an isometric exploded view of components of a swivel mechanism **278** (which can also be referred to as a bearing mechanism) of the table **201B** according to one embodiment. The swivel mechanism **278** includes a first bearing subassembly coupled to a second bearing subassembly. In particular, the swivel mechanism **278** includes a harmonic drive motor **280**, static plate **281**, shim **282**, inner bearing race **283**, bearing **284**, outer bearing race cleat **285**, inner bearing race support **286**, static ring **287**, motor housing mount **288**, encoder strip **289**, drive plate **290**, encoder sensor **291**, and swivel insert **292**. The motor housing mount **288** is stationary relative to the table base **218A**. The harmonic drive motor **280** rotates the swivel segment **210A** about the axis **248**. The first bearing subassembly includes the components described above that are coupled to the table base **218A**. The second bearing subassembly includes the components described above that are coupled to the swivel segment **210A**.

[0155] FIG. 2F is a cross sectional view of the swivel mechanism **278** shown in FIG. 2E according to one embodiment. The harmonic drive motor **280** is coupled to the motor housing mount **288**. The motor housing mount **288** is coupled to the static ring **287** and the static plate **281**. The static plate **281** is coupled to the table base **218A** using the shim **282** such that the harmonic drive motor **280** is also stationary relative to the table base **218A**.

[0156] The harmonic drive motor **280** includes a driving axle **294** coupled to a driving face **296** such that the driving axle **294** and driving face **296** rotate together. The driving face **296** is coupled to the drive plate **290**. The drive plate **290** is coupled to the inner bearing race support **286**. The inner bearing race support **286** is coupled to the swivel insert **292** and the inner bearing race cleat **283**. The inner bearing race support **286** is movably coupled to the table base **218A** by the bearing **284** (e.g., a cross roller bearing). The swivel insert **292** is coupled to the swivel segment **210A** such that rotating the driving axle **294** and driving face **296** causes the swivel segment **210A** to rotate in the same direction. Though not shown in FIG. 2F, the swivel mechanism **278** may include additional components between the static plate **281** and the inner bearing race cleat **283** to provide additional stability, e.g., in the form of a physical hard stop. Further, though not shown in FIG. 2F, the encoder sensor **291** is coupled to the motor housing mount **288** by the encoder strip **289**. The encoder sensor **291** records information about the rotation of the swivel segment **210A**, e.g., the position of the swivel segment **210A** up to an accuracy of 0.1 degrees at 0.01 degree resolution. FIG. 2F shows several screws (or bolts) that are used to couple components of the swivel mechanism, though it should be noted that the components may be coupled using other methods, e.g., welding, press fit, gluing, etc.

[0157] The swivel mechanism **278** allows the harmonic drive motor **280** to rotate the swivel segment **210A** with precise control, while supporting a load of up to 500 pounds, e.g., from a patient lying on the swivel segment **210A**. In particular, the harmonic drive motor **280** may rotate the swivel segment **210A** up to a rotational velocity of 10 degrees per second, and up to 45 degrees in either direction about the axis **248**. Further, the swivel segment **210A** is rotated such that the maximum velocity of the center of mass of the patient is 100 millimeters per second, and the time to the maximum velocity is 0.5 seconds. In some embodiments, one of the bearings of the swivel mechanism is a cross roller bearing e.g., with ball bearings with a bearing friction coefficient of approximately 0.0025—that helps further provide stability to allow the precise rotation of the swivel segment **210A**, while maintaining cantilever loads from the patient's weight. The harmonic drive motor **280** can generate up to 33 Newton meters of torque to rotate the swivel segment **210A** with the weight of the patient. In some embodiments, the harmonic drive motor **280** includes an internal brake with a holding torque of at least 40 Newton meters.

[0158] FIG. 2G is a bottom view of the swivel mechanism shown in FIG. 2E according to one embodiment. The harmonic drive motor **280** is exposed such that electrical wires, e.g., from a column of the surgical robotics system, may be coupled to the harmonic drive motor **280** to provide control signals to the harmonic drive motor **280**.

[0159] FIG. 2H is an isometric view of a foldable segment **214C** of a table **201C** according to one embodiment. The table **201C** is an embodiment of table **201A** in FIG. 2A. The table **201C** also includes a center segment **212C** coupled to a table base **218C**. The foldable segment **214C** rotates using bearings about an axis **252** parallel to the table base **218C**. The foldable segment **214C** is rotated such that the foldable segment **214C** is orthogonal to the table base **218C** and the center segment **212C**. In other embodiments, the foldable segment **214C** may be rotated to other angles relative to the table base **218C** and the center segment **212C**. The foldable segment **214C** includes a cutout section **254**, for example, to provide greater access to a patient lying on the table **201C**. In other embodiments, the foldable segment **214C** does not include a cutout section.

[0160] FIG. 2I is another isometric view of a foldable segment **214D** of a table **201D** according to one embodiment. The table **201D** is an embodiment of table **201A** in FIG. 2A. The foldable segment **214D** is rotated such that the foldable segment **214D** and the table base **218D** is positioned at an angle β relative to each other. The table **201D** includes a mechanism for the foldable segment **214D** and the center segment **212D** to maintain the rotated position while supporting the weight of a patient on the table **201D**. For example, the mechanism is a friction brake at the joint of the foldable segment **214D** and the center segment **212D** that holds the two segments at the angle β . Alternatively, the foldable segment **214D** rotates about the center segment **212D** using a shaft and the mechanism is a clutch that locks the shaft, and thus keeps the two segments at a fixed position. Though not shown in FIG. 2I, the table **201D** may include motors or other actuators to automatically rotate and lock the foldable segment **214D** to a certain angle relative to the center segment **212D**. Rotating the foldable segment **214D** is advantageous, for example, because the corresponding configuration of the table **201D** provides greater access to the area around the abdomen of a patient lying on the table **201D**.

[0161] FIG. 2J is an isometric view of a trapdoor **256** of a table **201E** according to one embodiment. The table **201E** is an embodiment of table **201A** in FIG. 2A. Specifically, the table **201E** includes the trapdoor **256** and a drainage component **258** positioned below the trapdoor **256**. The trapdoor **256** and drainage component **258** collect waste materials such as fluid (e.g., urine), debris (e.g., feces) that are secreted or released by a patient lying on the table during a surgical procedure. A container (not shown) may be positioned below the drainage component **258** to collect and store the waste materials. The trapdoor **256** and drainage component **258** are advantageous because they prevent waste materials from soiling or de-sterilizing equipment such as other components of the surgical robotic system **100** or other surgical tools in an operating room with the surgical robotic system **100**.

[0162] FIG. 2K is an isometric view of pivots of the table **201A** according to one embodiment. Specifically, the table **201A** includes a first pivot **260** and a second pivot **262**. The table **201A** rotates about a first axis **264**. A user, e.g., a physician, may rotate the table **201A** about the first axis **264** or the second axis **266** manually or assisted by the surgical robotics system **100**. The surgical robotics system **100** may also rotate the table **201A** automatically, for example, by using control signals to operate a motor coupled to the first pivot **260** or the second pivot **262**. The motor **280** is coupled to the first pivot **260**. Rotation of the table **201A** may provide greater access to certain areas of a patient lying on the table **201A** during a surgical procedure. Specifically, the table **201A** is configured to orient a patient lying on the table **201A** in a Trendelenburg position by rotating about the first axis **264**. Rotation of the table **201A** is further described in FIGS. 2L-M.

[0163] FIG. 2L is a side view of the table **201A** rotated about the axis of pitch **264** according to one embodiment. Specifically, the table **201A** is rotated to an angle γ relative to a plane **268** parallel to the ground.

[0164] FIG. 2M is an isometric view of the table **201A** rotated about the axis of roll **266** according to one embodiment. Specifically, the table **201A** is rotated to an angle δ relative to the plane **268** parallel to the ground. The table **201A** is illustrated as transparent to expose components underneath the table **201A**. The table includes a set of rails **270**. The table **201A** may translate laterally along an axis **266** parallel to the set of rails **270**. The surgical robotics system **100** translates the table **201A** laterally using, for example, a motor or other means of actuation (not shown). A user of the surgical robotics system **100** may also manually translate the table **201A**, or with assistance from the surgical robotics system **100**.

[0165] Alternative views and embodiments of the table **201A** including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/235,394 filed Sep. 30, 2015.

III. Column

[0166] FIG. 3A is a side cutaway view of the column **102** of the surgical robotics system **100** according to one embodiment. The column **102** includes electrical and mechanical and other types of components to perform functions of the surgical robotics system **100**. The column **102** includes a pitch rotation mechanism **310**, column telescoping mechanism **320**, ring telescoping mechanisms **330A** and **330B**, and ring rotation mechanisms **340A** and **340B**. The ring rotation mechanisms **340A** and **340B** are further described in FIG. 3B.

[0167] The surgical robotics system **100** rotates the table **101** about the axis of pitch **264** (also illustrated previously in FIGS. 2K-L) using the pitch rotation mechanism **310**. The pitch rotation mechanism **310** includes a pitch rotation motor **312**, right angle gearbox **314**, pitch rotation lead screw **316**, and pitch rotation bracket **318**. The pitch rotation motor **312** is coupled to the right angle gearbox **314**. The pitch rotation motor **312** is orthogonal to the pitch rotation lead screw **316**. The pitch rotation lead screw **316** is movably coupled to the pitch rotation bracket **318**. The right angle gearbox **314** is coupled to the pitch rotation lead screw **316**. Output rotation of the pitch rotation motor **312** causes translational motion of the pitch rotation lead screw along an axis **311**. Accordingly, translational motion of the pitch rotation lead screw **318** causes the table **101** to rotate about the axis of pitch **264**.

[0168] The surgical robotics system **100** translates the table vertically using the column telescoping mechanism **320**. The column telescoping mechanism **320** includes a column telescoping motor **322**, column telescoping lead screw **324**, and column telescoping rail **326**. The column telescoping motor **322** is coupled to the column telescoping lead screw **324**. The column telescoping motor **322** and the column telescoping lead screw **324** are stationary relative to the base **103**. The column telescoping lead screw **324** is engaged with the column telescoping rail **326**. Output rotation of the column telescoping motor **322** causes the column telescoping rail **326** to translate along a vertical axis **321** along the column telescoping lead screw **324**. As the column telescoping rail **326** translates in the positive direction along the vertical axis **321**, the height of the column **102** and the

table **101** increases.

[0169] The column **102** also includes a lower column segment **350**, middle column segment **352**, and upper column segment **354**. The lower column segment **350** is coupled to the base **103** and stationary relative to the base **103**. The middle column segment **352** is movably coupled to the lower column segment **350**. The upper column segment **354** is movably coupled to the middle column segment **352**. In other embodiments, a column **102** may include additional or fewer column segments.

[0170] The upper column segment **354** and/or the middle column segment **352** also translate along the vertical axis **321** to extend the height of the column **102**. Similarly, as the column telescoping rail **326** translates in the negative direction along the vertical axis **321**, the height of the column **102** and the table **101** decreases. Further, the upper column segment **354** and/or the middle column segment **352** also translate along the vertical axis **321**, collapsing over the lower column segment **350**. A table **101** with adjustable height is advantageous because the table **101** facilitates a variety of surgical procedures. Specifically, one surgical procedure requires a patient lying on the table **101** to be positioned at a height lower than the height of a patient lying on the table **101** for a different surgical procedure. In some embodiments, the column telescoping mechanism **320** uses other means of actuation such as hydraulics or pneumatics instead of—or in addition to—motors.

[0171] The surgical robotics system **100** translates column rings **305A** and **305B** vertically using the ring telescoping mechanisms **330A** and **330B**. The ring telescoping mechanism **330A** includes a ring telescoping motor **332**, ring telescoping lead screw **334**, and ring telescoping rail **336**. Column rings are further described with reference to FIGS. 5A-E in Section V. Column Ring. Column rings **305A** and **305B** are movably coupled to the column **102** and translate along a vertical axis **331**. Generally, a column **102** includes a ring telescoping mechanism for each column ring of the column **102**. Specifically, the column **102** includes ring telescoping mechanism **330A** and second ring telescoping mechanism **330B**. The ring telescoping motor **332** is coupled to the ring telescoping lead screw **334**. The ring telescoping motor **332** and the ring telescoping lead screw **334** are stationary relative to the base **103**. The ring telescoping lead screw **334** is engaged with the ring telescoping rail **336**. The ring telescoping rail **336** is coupled to the column ring **305A**. Output rotation of the ring telescoping motor **332** causes the ring telescoping rail **336** to translate along the vertical axis **331** and along the ring telescoping lead screw **334**. As the ring telescoping rail **336** translates in the positive direction or negative direction along the vertical axis **331**, the height of a corresponding column ring increases or decreases, respectively.

[0172] FIG. 3B is an isometric cutaway view of the column **102** according to one embodiment. The column **102** includes a first accordion panel **360A** and a second accordion panel **360B**. The accordion panels **360A** and **360B** extend or fold as the surgical robotics system **100** translates column rings **305A** and **305B** in the positive direction or negative direction along the vertical axis **331**, respectively. The accordion panels **360A** and **360B** are advantageous because they protect electrical and mechanical and other types of components inside the column **102** (e.g., the pitch rotation mechanism **310**, column telescoping mechanism **320**, ring telescoping mechanisms **330A** and **330B**, and ring rotation mechanisms **340A** and **340B**) from becoming soiled or de-sterilized by fluid waste and other hazards. FIG. 3B shows an isometric view of the ring rotation mechanism **340A**, while the ring rotation mechanism **340B** is obscured by the column **102**.

[0173] The surgical robotics system **100** rotates column rings **305A** and **305B** using the ring rotation mechanisms **340A** and **340B**, respectively. The ring telescoping rail **336** is coupled to the ring rotation motor **342** by a ring rotation bracket **344**. The ring rotation motor **342** is coupled to a set of gears **346**. The set of gears **346** includes a driving gear **346G**. The driving gear **346G** is engaged with a column ring rail **348** of the column ring **305A**. Output rotation of the ring rotation motor **342** causes the set of gears **346** and the driving gear **346G** to rotate. Accordingly, the rotation of the driving gear **346G** causes the column ring **305A** to rotate about a vertical axis **341** concentric to the column **102**. The column **102** includes another ring rotation mechanism **340B** corresponding

to the column ring **305B**. Generally, both ring rotation mechanisms **340A** and **340B** and column rings **305A** and **305B** will be substantially the same, however in other implementations they may be constructed using different mechanisms.

[0174] FIG. **3C** is a top view of the ring rotation mechanism **340A** according to one embodiment. For purposes of clarity, FIG. **3C** only shows the driving gear **346G**, the column ring **305A**, and the column ring rail **348** of the ring rotation mechanism **340A**. In an example use case, the surgical robotics system **100** rotates the driving gear **346G** clockwise to rotate the column ring rail **348**—and thus, the column ring **305A**—clockwise about the vertical axis **341**.

[0175] Alternative views and embodiments of the column **103** including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/162,486 filed May 15, 2015 and U.S. Provisional Application No. 62/162,467 filed May 15, 2015.

IV. Column-Mounted Robotic Arms

[0176] FIG. **4A** is an isometric view of a surgical robotics system **400A** with a column-mounted robotic arm **470A** according to one embodiment. The surgical robotics system **400A** includes a set of robotic arms, a set of column rings, table **401A**, column **402A**, and base **403A**. The surgical robotics system **400A** is an embodiment of the surgical robotics system **100** shown in FIG. **1**. Generally, the set of robotics arms includes one or more robotic arms, such as robotic arm **470A**, where the robotic arms are coupled to one or more column rings, such as column ring **405A**. Column rings are described in more detail with respect to FIGS. **5A-E** in Section V. Column Ring below. Robotic arms are described in more detail with respect to FIGS. **6A-C** in Section VI. Robotic Arm below. Column rings **405A** are movably coupled to the column **402A**. Thus, a robotic arm **470A** attached to a column **405A** may be referred to as a column-mounted robotic arm **470A**. As introduced above, the surgical robotics system **400A** uses robotic arms **470A** to perform surgical procedures on a patient lying on the table **401A**.

[0177] FIG. **4B** is an isometric view of a surgical robotics system **400B** with column-mounted robotic arms according to one embodiment. The surgical robotics system **400B** is an embodiment of the surgical robotics system **400A** shown in FIG. **4A**. The surgical robotics system **400B** includes multiple robotic arms, i.e., a first robotic arm **470B**, second robotic arm **470C**, third robotic arm **470D**, and fourth robotic arm **470E**, as well as multiple column rings, i.e., a first column ring **405B** and second column ring **405C**. In other embodiments, the surgical robotics system **400B** may include additional or fewer robotic arms and/or column rings. Further, the robotic arms may be coupled to column rings in various configurations. For example, three robotic arms may be coupled to a column ring. Additionally, the surgical robotics system **400B** may include three column rings each coupled to two robotic arms.

[0178] Alternative views and embodiments of the surgical robotics system **400B** including the above mentioned components with column-mounted robotic arms are further illustrated and described at least in U.S. Provisional Application No. 62/162,486 filed May 15, 2015 and U.S. Provisional Application No. 62/162,467 filed May 15, 2015.

V. Column Ring

[0179] FIG. **5A** is an isometric view of a column ring **505** of a surgical robotics system for example, surgical robotics system **100**, **400A**, or **400B**—according to one embodiment.

[0180] The column ring **505** includes a column ring rail **510**, arm mount pivot **512**, arm mount base **514**, and a set of arm mounts. The set of arm mounts includes one or more arm mounts.

Specifically, the set of arm mounts in FIG. **5A** includes a first arm mount **506A** and a second arm mount **506B**. Generally, each arm mount of the set of arm mounts and the arm mount base **514** are cylindrically shaped.

[0181] The first arm mount **506A** and the second arm mount **506B** are movably coupled the arm mount base **514**. The first arm mount **506A** and the second arm **506B** mount may rotate—together or independently—about the axis **511** concentric to the arm mount base **514**. For example, the

surgical robotics system **400B** rotates the first arm mount **506A** and the second arm mount **506B** using a motor or other means of actuation (not shown) inside the arm mount base **514** or arm mounts. In some embodiments, the first arm mount **506A** and the second arm mount **506B** rotate at predetermined increments, e.g., increments of 15 degrees.

[0182] The arm mount base **514** is coupled to the arm mount pivot **512**. The arm mount pivot **512** uses a motor or other means of actuation (not shown) inside the arm mount pivot **512** to rotate the arm mount base **514** about the axis **521** orthogonal to the axis **511**. The arm mount pivot **512** is coupled to, and stationary relative to, the column ring rail **510**. Rotating the arm mount base **514** is advantageous because robotic arms (and arm mounts) coupled to the arm mount base **514** may be reoriented in response to rotation of the table **401B**. Accordingly, robotic arms coupled to the arm mounts of the arm mount base **514** have greater access to a patient lying on the table **401B**.

[0183] FIG. **5B** is a bottom view of the set of column rings underneath the table **401B** of FIG. **4B** according to one embodiment. The set of column rings includes the first column ring **405B** and the second column ring **405C**. Note that FIG. **5B** shows the first column ring **405B** and the second column ring **405C** aligned such that the arm mounts are on the same side of the table **401B**, while FIG. **4B** shows the first column ring **405B** and the second column ring **405C** positioned such that the arm mounts are on opposite sides of the table **401B**. The surgical robotics system **400B** may rotate the column rings **405B** and **405C** to position the arm mounts in other configurations. For example, two arm mounts are positioned on one side of the table **401B** and two arm mounts are positioned on an opposite side of the table **401B**. By rotating column rings independently from each other around the column, the surgical robotics system **400B** may configure the arm mounts—and thus, robotic arms mounted to the arm mounts—in a greater number of possible positions. Due to this configurability, the surgical robotics system **400B** accommodates a variety of surgical procedures because the robotic arms can access any area (e.g., upper body, core body, or lower body) of the body of a patient lying on the table **401B**. In some embodiments, each arm mount of the column rings include a notch **516** which facilitates the attachment of a robotic arm to the arm mount.

[0184] FIG. **5C** is an isometric view of the set of column rings mounted to the column **402B** of FIG. **4B** according to one embodiment. Similarly to FIG. **5B**, FIG. **5C** shows all the arm mounts aligned on the same side of the surgical robotics system **400B**.

[0185] FIG. **5D** is an isometric cutaway view of an arm mount **506C** of a column ring according to one embodiment. The arm mount **506C** includes an arm mount telescoping mechanism **520** and a set of arm mount segments. The arm mount telescoping mechanism **520** includes an arm mount telescoping motor **522**, arm mount telescoping lead screw **524**, and arm mount telescoping rail **526**. Generally, the set of arm mount segments includes one or more arm mount segments. Specifically, the set of arm mount segments in FIG. **5D** includes a lower arm mount segment **530**, middle arm mount segment **532**, and upper arm mount segment **534**. A robotic arm segment **571** (e.g., of the robotic arm **470B** in FIG. **4B**) is coupled to the upper arm mount segment **534**. The middle arm mount segment **532** and the upper arm mount segment **534** are movably coupled to the lower arm mount segment **530**. The lower arm mount segment **530** is coupled to an arm mount base (e.g., arm mount base **514** in FIG. **5A**).

[0186] The surgical robotics system **400B** translates the arm mount **506C** along an axis **531** using the arm mount telescoping mechanism **520**. In FIG. **5D**, the axis **531** is in a horizontal orientation, though it should be noted that, in other embodiments, the axis **531** is in a vertical or any other orientation. The arm mount telescoping motor **522** is coupled to the arm mount telescoping rail **526**. The arm mount telescoping rail **526** is engaged with the arm mount telescoping lead screw **524**. The arm mount telescoping lead screw **524** is stationary relative to the lower arm mount segment **530**. Output rotation of the arm mount telescoping motor **522** causes the arm mount telescoping rail **526** to translate along the vertical axis **531**. Translation of the arm mount **506C** is advantageous because, if the arm mount **506C** is extended, a robotic arm mounted to the arm mount

506C may have greater access to a patient lying on the table **401B** during a surgical procedure. [0187] FIG. 5E is an isometric cutaway view of the arm mount **506C** in a telescoped configuration according to one embodiment. In the telescoped configuration, the upper arm mount segment **534** and the middle arm mount segment **532** extend in the positive axis **531** direction to facilitate extension of the arm mount **506C**.

[0188] Alternative views and embodiments of the column ring **505** including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/162,486 filed May 15, 2015 and U.S. Provisional Application No. 62/162,467 filed May 15, 2015.

VI. Robotic Arm

[0189] FIG. 6A is an isometric view of a robotic arm **670** of a surgical robotics system for example, surgical robotics system **100**, **400A**, or **400B**-according to one embodiment. Generally, the robotic arm **670** includes a set of robotic arm segments such as robotic arm segments **671**, **672**, **673**, **674**, **675**, **676**, and **677**. Each arm segment is movably coupled to at least one other arm segment at an arm segment joint. In particular, the first arm segment **671** is movably coupled to the second arm segment **672**, the second arm segment **672** is movably coupled to the third arm segment **673**, and so forth. The first arm segment **671** is movably coupled to an arm mount (e.g., arm mount **506A** in FIG. 5A). The seventh arm segment **677** (or the last arm segment of a set of arm segments including a number of arm segments different than seven), is coupled to a surgical instrument. The seventh arm segment **677** may also include mechanisms to hold a surgical instrument such as a clamp or robotic fingers. The robotic arm **670** uses electrical and mechanical components, such as motors, gears, and sensors, inside the robotic arm segments to rotate the arm segments at the arm segment joints.

[0190] The robotic arm **670** receives control signals from a robotic arm control system, for example, housed in the column **402B** in FIG. 4B. In some embodiments, the robotic arm **670** receives control signals from a robotic arm control system located outside of the column **402B** or separate from the surgical robotics system **400B**. Generally, the robotic arm **670** may include sensors that provide sensor data to the robotic arm control system. Specifically, pressure sensors provide force feedback signals and encoders or potentiometers provide measurements of rotation of arm segments. The robotic arm control system uses the sensor data to generate the control signals provided to the robotic arm **670**. Since each arm segment may rotate with respect to another adjacent segment, each arm segment provides an additional degree of freedom to the mechanical system of the robotic arm **670**. By rotating the robotic arm segments, the surgical robotics system **400B** positions a surgical instrument coupled to the robotic arm **670** such that the surgical instrument has access to a patient undergoing a surgical procedure. Configurations of robotic arms of the surgical robotics system **400B** are further described with reference to FIGS. 7A-F in Section VII. System Orientations for Performing Surgical Procedures.

[0191] FIG. 6B is an isometric view of an arm segment joint **610** of the robotic arm **670** according to one embodiment. The first arm segment **671A** and the second arm segment **672A** are embodiments of any of the arm segments in FIG. 6A. The arm segments **671A** and **672A** are cylindrically shaped and joined at the plane **612**. The first arm segment **671A** rotates relative to the second arm segment **672A** about an axis **611** perpendicular to the plane **612**. Further, the axis **611** is perpendicular to the plane **614** of the second arm segment **672A** and perpendicular to the plane **616** of the first arm segment **671A**. That is, the axis **611** is longitudinal relative to the arm segments **671A** and **672A**.

[0192] FIG. 6C is an isometric view of another arm segment joint **620** of the robotic arm **670** according to one embodiment. The arm segments **671B** and **672B** are joined at the plane **622**. Unlike the cylindrically shaped arm segments shown in FIG. 6B, the arm segments **671B** and **672B** each include a curved section **628** and **630**, respectively. The first arm segment **671B** rotates relative to the second arm segment **672B** about an axis **621** perpendicular to the plane **622**. The axis

621 is not perpendicular to the plane **624** of the arm segment **672B** and not perpendicular to the plane **626** of the arm segment **671B**. In some embodiments, the axis of rotation is perpendicular to a plane of one arm segment, but not perpendicular to a plane of the other arm segment of an arm segment joint.

[0193] Alternative views and embodiments of the robotic arm **670** including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/162,486 filed May 15, 2015 and U.S. Provisional Application No. 62/162,467 filed May 15, 2015.

VII. System Orientations for Performing Surgical Procedures

[0194] The surgical robotics system **400B** in FIG. **4B** performs a variety of surgical procedures using column-mounted robotic arms of the set of robotic arms. The surgical robotics system **400B** configures the column-mounted robotic arms to access portions of a patient lying on the table **401B** before, during, and/or after a surgical procedure. The column-mounted robotic arms access portions near the groin of the patient for surgical procedures such as ureteroscopy, percutaneous nephrolithotomy (PCNL), colonoscopy, and fluoroscopy. The column-mounted robotic arms to access portions near the core (e.g., abdomen) area the patient for surgical procedures such as prostatectomy, colectomy, cholecystectomy, and inguinal hernia. The column-mounted robotic arms to access portions near the head of the patient for surgical procedures such as bronchoscopy, endoscopic retrograde cholangiopancreatography (ERCP).

[0195] The surgical robotics system **400B** automatically reconfigures the column-mounted robotic arms, column rings, column, and table to perform different surgical procedures. The features of each subsystem and component of the surgical robotics system **400B** enable the same set of robotics arms to access a large working volume, and multiple working volumes (based on the configuration), to perform a variety of surgical procedures on the patient. In particular, as mentioned above, the robotic arms may be configured in a first configuration to access the patients' groin area, in a second configuration to access the patients' abdomen area, and in a third configuration to access the patients' head area, in addition to other possible configurations. The degrees of freedom provided by the arm segments of the robotic arms, column rings, column, and table contribute to the wide range of configurations. The surgical robotics system **400B** includes a computer system that stores computer program instructions, for example within a non-transitory computer-readable storage medium such as a persistent magnetic storage drive, solid state drive, etc. When executed by a processor of the computer system, the instructions cause the components of the surgical robotics system **400B** to automatically reconfigure without the need for intervention, or with minimal intervention, from a user, e.g., a physician. For example, based on the instructions, the computer system sends an electronic control signal to motors of the robotics arms. In response to receiving the control signal, the motors rotate arm segments of the robotics arms into a certain position. The physician or another user may design a configuration of the surgical robotics system by creating the instructions and providing the instructions to the computer system. For example, the instructions are uploaded to a database of the computer system. The automatic configurability of the surgical robotics system **400B** is an advantage because the automatic configurability saves resources. Specifically, the surgical robotics system **400B** reduces the amount of time taken by users to setup the surgical robotics system **400B** for a surgical procedure. Further, by using the surgical robotics system **400B** for a variety of surgical procedures, users reduce the amount of surgical equipment that they need to purchase, maintain, store, and learn to operate.

[0196] Alternative views and embodiments of use cases of the surgical robotics system **400B** with column-mounted robotic arms including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/162,486 filed May 15, 2015 and U.S. Provisional Application No. 62/162,467 filed May 15, 2015.

VII. A. Lower Body Surgery

[0197] FIG. **7A** is an isometric view of a surgical robotics system **700A** with column-mounted arms

configured to access the lower body area of a patient **708** according to one embodiment. The surgical robotics system **700A** is an embodiment of—though includes more components than—the surgical robotics system **400B** in FIG. **4B**. Specifically, the surgical robotics system **700A** includes a set of robotic arms (including five robotic arms in total) and a set of three column rings. A first robotic arm **770A** and a second robotic arm **770B** are coupled to a first column ring **705A**. A third robotic arm **770C** and a fourth robotic arm **770D** are coupled to a second column ring **705B**. A fifth robotic arm **770E** is coupled to a third column ring **705C**. FIG. **7A** shows a wireframe of the patient **708** lying on the table **701** undergoing a surgical procedure, e.g., ureteroscopy, requiring access to the lower body area of the patient **708**. Legs of the patient **708** are not shown as to not obscure portions of the surgical robotics system **700A**.

[0198] The surgical robotics system **700A** configures the set of robotic arms to perform a surgical procedure on the lower body area of the patient **708**. Specifically, the surgical robotics system **700A** configures the set of robotic arms to manipulate a surgical instrument **710**. FIG. **7A** shows the set of robotic arms inserting the surgical instrument **710** along a virtual rail **790** into the groin area of the patient **708**. Generally, a virtual rail **790** is a co-axial trajectory along which the set of robotic arms translates a surgical instrument (typically a telescoping instrument). The second robotic arm **770B**, the third robotic arm **770C**, and the fifth robotic arm **770E** are coupled, e.g., holding, the surgical instrument **710**. The first robotic arm **770A** and the fourth robotic arm **770D** are stowed to the sides of the surgical robotics system because they are not necessarily required to for the surgical procedure—or at least part of the surgical procedure—shown in FIG. **7A**. The robotic arms are configured such that they manipulate the surgical instrument **710** from a distance away from the patient **708**. This is advantageous, for example, because there is often limited space available closer toward the patient's body or there is a sterile boundary around the patient **708**. Further, there may also be a sterile drape around surgical equipment. During a surgical procedure, only sterile objects are allowed pass the sterile boundary. Thus, the surgical robotics system **700A** may still use robotic arms that are positioned outside of the sterile boundary and that are covered with sterilized drapes to perform a surgical procedure.

[0199] In one embodiment, the surgical robotics system **700A** configures the set of robotic arms to perform an endoscopy surgical procedure on the patient **708**. The set of robotic arms hold an endoscope, e.g., the surgical instrument **710**. The set of robotic arms insert the endoscope into the patient's body via an opening in the groin area of the patient **708**. The endoscope is a flexible, slender, and tubular instrument with optical components such as a camera and optical cable. The optical components collect data representing images of portions inside the patient's body. A user of the surgical robotics system **700A** uses the data to assist with performing the endoscopy.

[0200] FIG. **7B** is a top view of the surgical robotics system **700A** with column-mounted arms configured to access the lower body area of the patient **708** according to one embodiment.

[0201] FIG. **7C** is an isometric view of an imaging device **740** and a surgical robotics system **700B** with column-mounted arms configured to access the lower body area of a patient **708** according to one embodiment. The surgical robotics system **700B** is an embodiment of the surgical robotics system **400B** in FIG. **4B**. The surgical robotics system **700B** includes a pair of stirrups **720** that support the legs of the patient **708**, and thus exposing the groin area of the patient **708**. Generally, the imaging device **740** captures images of body parts or other objects inside a patient **708**. The imaging device **740** may be a C-arm, also referred to as a mobile C-arm, which is often used for fluoroscopy type surgical procedures, or another type of imaging device. A C-arm includes a generator, detector, and imaging system (not shown). The generator is coupled to the bottom end of the C-arm and faces upward toward the patient **708**. The detector is coupled to the top end of the C-arm and faces downward toward the patient **708**. The generator emits X-ray waves toward the patient **708**. The X-ray waves penetrate the patient **708** and are received by the detector. Based on the received X-ray waves, the imaging system **740** generates the images of body parts or other objects inside the patient **708**. The swivel segment **210** of the table **401B** is rotated laterally such

that the groin area of the patient **708** is aligned in between the generator and detector of the C-arm imaging device **740**. The C-arm is a physically large device with a footprint that needs to be stationed underneath the patient. In particular, the generator of the C-arm needs to be underneath the operative area of the patient, e.g., the abdomen area. In typical surgical beds mounted to a column, the column interferes with the positioning of the C-arm generator, e.g., because the column is also underneath the operative area. In contrast, due to the configurability of the swivel segment **210**, the surgical robotics system **700B** may configure the table **401B** such that the C-arm, the robotic arms, and a user (e.g., physician) have a sufficient range of access to perform a surgical procedure on a working area the patient's body. In one example use case, the table **401B** is translated laterally along a longitudinal axis of the table **401B** such that the robotic arms can access the groin or lower abdomen area of a patient on the table **401B**. In another example use case, by rotating the swivel segment **210** away from the column **402B**, the generator of the C-arm **740** may be positioned underneath the groin area of the patient **708**. The swivel segment **210**—with a patient lying on the swivel segment **210**—may be rotated at least to 45 degrees relative to a longitudinal axis of the table **401B** without tipping over the surgical robotics system. In particular, the surgical robotics system does not tip because the center of mass of the surgical robotics system (e.g., the center of mass of the combined, at least, table, bed, and base) is positioned above a footprint of the base. Outrigger casters, further described with reference to FIGS. **8G-J** in Section V III. Base, may provide further stability to prevent the surgical robotics system from tipping over when a swivel segment is rotated away from the table.

[0202] The surgical robotics system **700B** uses a set of column-mounted robotic arms to manipulate a surgical instrument **710**. Each of the robotic arms is coupled to, e.g., holding, the surgical instrument **710**. The surgical robotics system **700B** uses the robotic arms to insert the surgical instrument **710** into the groin area of the patient along a virtual rail **790**.

[0203] FIG. **7D** is a top view of the imaging device **740** and the surgical robotics system **700B** with column-mounted arms configured to access the lower body area of the patient **708** according to one embodiment.

VII. B. Core Body Surgery

[0204] FIG. **7E** is an isometric view of the surgical robotics system **700B** (or **400B**) with column-mounted arms configured to access the core body area of a patient **708** according to one embodiment. The surgical robotics system **700B** has been reconfigured from the configuration shown in FIG. **7C-D** where the robotic arms access the lower body area of the patient **708**. In embodiments where the table includes a swivel segment **210**, the swivel segment **210** of the table is rotated in-line with the rest of the table. The patient **708** lying on the table **401B** is undergoing a surgical procedure, e.g., prostatectomy or laparoscopy, requiring access to the core body area of the patient **708**. Each robotic arm is manipulating a surgical instrument to perform the surgical procedure. The surgical robotics system **700B** raises the column rings **405B** and **405C** toward the table **401B** so that the robotic arms have greater access the patient **708**. Further, the surgical robotics system **700B** rotates the column rings such that two of the robotic arms extend from one side of the table **401B** and the other two robotic arms extend from the opposite side of the **401B**. Thus, the robotic arms are less likely to interfere with each other (e.g., a robotic arm blocking the motion of another robotic arm) during the surgical procedure.

VII.C. Upper Body Surgery

[0205] FIG. **7F** is an isometric view of the surgical robotics system **700B** (or **400B**) with column-mounted arms configured to access the upper body area of a patient **708** according to one embodiment. The surgical robotics system **700B** has been reconfigured from the configuration shown in FIG. **7E** where the robotic arms access the core body area of the patient **708**. In embodiments where the table includes a swivel segment **210**, the swivel segment **210** of the table is rotated in-line with the rest of the table. The patient **708** lying on the table **401B** is undergoing a surgical procedure, e.g., bronchoscopy, requiring access to the upper body area of the patient **708**,

specifically the head of the patient **708**. The robotic arm **470C** and the robotic arm **470D** are inserting a surgical instrument **710D**, e.g., a bronchoscope, into the mouth of the patient **708** along a virtual rail **790**. The robotic arm **470B** is coupled to, e.g., holding, an introducer **750**. The introducer **750** is a surgical instrument that directs the bronchoscope into the mouth of the patient **708**. Specifically, the trajectory of the bronchoscope along the virtual rail **790** begins parallel to the patient **708**. The introducer **750** changes the angle of the virtual rail **790** just before the bronchoscope enters the mouth. The robotic arm **470E** (not shown in FIG. 7F) is not used for the surgical procedure, and thus is stowed away.

VIII. Base

[0206] FIG. **8A** is an isometric view of a base **403A** of a surgical robotics system **800A** according to one embodiment. The surgical robotics system **800A** is an embodiment of the surgical robotics system **400B** in FIG. **4B**. The surgical robotics system **800A** stores column-mounted robotic arms and/or column rings (not shown) inside the base **403B** when the robotic arms are not in use. The base **403B** includes a first panel **820A** and a second panel **820B** that cover stored robotic arms. The first panel **820A** and the second panel **820B** are advantageous because they prevent waste materials from de-sterilizing or otherwise contaminating stored robotic arms.

[0207] FIG. **8B** is an isometric view of open panels of the base **403B** according to one embodiment. The first panel **820A** and the second panel **820B** pivot away from the column **802A** such that column-mounted robotic arms have access to inside the base **403B**. The first panel **820A** includes a cutout **830A** and the second panel **820B** includes a cutout **830B**. The cutouts **830A** and **830B** conform to the shape of the column **402B** such that the panels **820A** and **820B** form a seal around the column **402B** when closed. The surgical robotics system **800A** may automatically open and close the first panel **820A** and the second panel **820B** using motors or other means of actuation. A user of the surgical robotics system **800A** may also manually open and close the first panel **820A** and the second panel **820B**.

[0208] FIG. **8C** is an isometric view of a robotic arm stowed inside a base **403B** of a surgical robotics system **800B** according to one embodiment. The surgical robotics system **800B** is an embodiment of the surgical robotics system **400B** in FIG. **4B**. The surgical robotics system **800B** stores column-mounted robotic arms **470B** and **470D** and column rings **405B** and **405C** inside the base **403B** when the robotic arms are not in use. The base **403B** includes a first panel **820A** and a second panel **820B** that cover stored robotic arms and column rings. The first panel **820A** includes a cutout **830C**. The second panel **820B** also includes a cutout (not shown due to being obscured by other components). The cutouts conform to the shape of the column **402B** such that the panels **820A** and **820B** form a seal around the column **402B** when closed.

[0209] The first panel **820A** and a second panel **820B** translate laterally to provide access for the robotic arms and column rings into the base **403B**. FIG. **8C** shows the first panel **820A** and a second panel **820B** translated to form an opening. The opening may be large enough to provide access for a robotic arm, but not too large as to still provide protection to the robotic arms even when the panels are open. The robotic arm **470D** and column ring **405C** are stowed inside the base **403B**. The robotic arm **470B** and column ring **405B** are outside the base **403B**, though they may also be stowed inside the base **403B**. The surgical robotics system **800B** may automatically open and close the first panel **820A** and the second panel **820B** using motors or other means of actuation. A user of the surgical robotics system **800B** may also manually open and close the first panel **820A** and the second panel **820B**.

[0210] FIG. **8D** is an isometric view of robotic arms stowed underneath the table **701** of the surgical robotics system **700A** according to one embodiment. Specifically, the arm segments of each robotic arm rotate such that the robotic arm is in a compact configuration for stowage. The surgical robotics system **700A** raises the first column ring **705A** and the second column ring **705B**, and lowers the third column ring **705C** toward the center of the column **702**. This way, the robotic arms have enough space in the stowed configuration without interfering with each other. In one

embodiment, the column **702** includes covers (e.g., similar to panels **820A** and **820B**) over the robotics arms to protect the robotic arms from contamination or damage.

[0211] FIG. **8E** is an isometric view of robotic arms stowed above the base **403B** of the surgical robotics system **400B** according to one embodiment. The robotic arms **470B**, **470C**, **470D**, and **470E** are in a stowed configuration. Specifically, the arm segments of each robotic arm rotate such that the robotic arm is in a compact configuration for stowage. The surgical robotics system **400B** lowers the first column ring **405B** and the second column ring **405C** along the column **402B** such that the stowed robotic arms rest on the base **403B** and are away from the table **401B**. A cover (not shown) such as a drape or panel may be used to cover the stowed robotic arms for protection from de-sterilization or other contamination.

[0212] FIG. **8F** is another isometric view of robotic arms stowed above the base **403B** of the surgical robotics system **800C** according to one embodiment. The robotic arms are rail-mounted instead of column-mounted. Rail-mounted robotic arms are further described with reference to FIGS. **9A-B** and FIGS. **10A-D** in Section IX. Rail-Mounted Robotic Arms and Section X. Rails, respectively. The surgical robotics system **800C** is an embodiment of the surgical robotics system **900B** further described with reference to FIG. **9B** in Section IX. Rail-Mounted Robotic Arms. The robotic arms **870C**, **870D**, **870E**, **870F**, **870G**, and **870H** are in a stowed configuration.

[0213] FIG. **8G** is an isometric view of outrigger casters on a base **803** of a surgical robotics system according to one embodiment. The base **803** shown in FIG. **8G** includes four outrigger casters **840A**, **840B**, **840C**, and **840D**, each substantially the same as each other and positioned at a different corner of the base **803**, though it should be noted that, in other embodiments, a base may include any number of outrigger casters positioned in other locations on the base. The outrigger casters **840A**, **840B**, **840C**, and **840D** are each in a mobile configuration, i.e., the caster wheel physically contacts the ground. Thus, a user of the surgical robotics system may transport the surgical robotics system using the caster wheels, e.g., to a storage area when the surgical robotics system is not in use.

[0214] FIG. **8H** is another isometric view of the outrigger casters **840A**, **840B**, **840C**, and **840D** on the base **803** of the surgical robotics system according to one embodiment. The outrigger casters **840A**, **840B**, **840C**, and **840D** are each in a stationary configuration, i.e., the outrigger caster is rotated such that the caster wheel does not physically contact the ground. Thus, the surgical robotics system may be stabilized and immobilized during a surgical procedure.

[0215] FIG. **8I** is a side view of the outrigger caster **840A** in a mobile configuration according to one embodiment. The outrigger caster **840A** includes a caster wheel **842** movably coupled to an outrigger mount **844**. The outrigger mount **844** is coupled to a foot **846**. The first linkage **848** is movably coupled to the outrigger mount **844** by the first hinge **850**. The second linkage **852** is movably coupled to the outrigger mount **844** by the second hinge **854**. In the mobile configuration, the caster wheel **842** may rotate to move the outrigger caster **840** along the ground.

[0216] FIG. **8J** is a side view of the outrigger caster **840A** in a stationary configuration according to one embodiment. In the stationary configuration, the caster wheel **842** may freely rotate, but the caster wheel **842** does not move the outrigger caster **840A** because the caster wheel **842** is not physically in contact with the ground. The surgical robotics system (or a user) rotates the outrigger caster **840A**, e.g., 90 degrees, to change the outrigger caster **840A** from the mobile configuration to the stationary configuration. Thus, the foot **846** now physically contacts the ground, and helps prevent the surgical robotics system from moving. The foot **846** may have a larger footprint relative to the caster wheel **842** to provide additional stability on the ground. The linkages **848** and **852** are positioned such that they do not interfere with the rotational path of the outrigger caster **840A**. Combining the caster wheel **842** and the foot **846** in the outrigger caster **840A** is advantageous, e.g., because the outrigger caster **840A** allows the surgical robotics system to change between the mobile and stationary configurations using a compact mechanism, compared to having separate mechanisms for casters and stabilization. Further, in use cases of surgical robotics systems

including swivel segments that rotate a patient lying on the swivel segment away from a corresponding table (e.g., as illustrated in FIGS. 7C-D), the feet of outrigger casters (in the stationary configuration) help prevent the surgical robotics system from tipping over due to the center of mass of the patient extending beyond the table base.

[0217] Alternative views and embodiments of the base **403B** including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/203,530 filed Aug. 11, 2015.

IX. Rail-Mounted Robotic Arms

[0218] FIG. **9A** is an isometric view of a surgical robotics system **900A** with a rail-mounted robotic arm according to one embodiment. The surgical robotics system **900A** includes a set of robotic arms (including at least arm **470A**) and a set of base rails (including at least base rail **980A**). The robotic arm **470A** is coupled to the base rail **980A**. Base rails are further described with respect to FIGS. **10A-D** in Section X. Rails below. The base rail **980A** is movably coupled to the base **103**. Thus, the robotic arm **470A** may be referred to as a rail-mounted robotic arm **470A**.

[0219] FIG. **9B** is an isometric view of a surgical robotics system **900B** with rail-mounted robotic arms according to one embodiment. The surgical robotics system **900B** includes robotic arms **470B**, **470C**, **470D**, and **470E** each coupled to a first base rail **980B** or a second base rail **980C**. The first base rail **980B** and the second base rail **980C** are movably coupled to the base **103**.

[0220] In other embodiments, the surgical robotics system **900B** may include additional or fewer robotic arms and/or base rails. Further, the robotic arms may be coupled to base rails in various configurations. For example, three robotic arms may be coupled to a base rail. Additionally, the surgical robotics system **900B** may include three base rails each coupled to a robotic arm.

[0221] The surgical robotics system **900B** may translate robotic arms mounted to a base rail by translating the base rails relative to the base **103**. Base rails may translate beyond the starting footprint of the base **103**, which allows the robotic arms to operate in a larger volume of space. Further, the surgical robotics system **900B** may translate robotic arms mounted to a base rail independently from each other by translating the robotic arms relative to the base rail. This is advantageous, for example, because the surgical robotics system **900B** may position the robotic arms in different configurations to perform a variety of surgical procedures.

[0222] Alternative views and embodiments of the surgical robotics system **900B** with rail-mounted robotic arms including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/193,604 filed Jul. 17, 2015 and U.S. Provisional Application No. 62/201,518 filed Aug. 5, 2015.

X. Rails

[0223] FIG. **10A** is an isometric view of base rails of a surgical robotics system **1000** according to one embodiment. A base rail includes a set of one or more arm mounts each movably coupled to the base rail. Further, each arm mount is an embodiment of the arm mount **506A** or **506B** previously described with reference to FIG. **5A** in Section V. Column Ring. Specifically, the base rail **980B** includes arm mounts **1006A**, **1006B**, and **1006C**.

[0224] FIG. **10B** is an isometric view of arm mounts on the base rail **980B** according to one embodiment. The arm mounts **1006A**, **1006B**, and **1006C** each include a belt and pinion assembly. Specifically, the belt and pinion assembly of arm mount **1006A** includes a bracket **1012**, motor **1014**, belt **1016**, and pinion **1018**. The belt and pinion assemblies of arm mount **1006B** and **1006C** are constructed similarly.

[0225] The surgical robotics system **1000** translates arm mounts—and thus, robotic arms mounted to the arm mounts—along base rails using the belt and pinion assemblies. Specifically, the arm mount **1006A** is movably coupled to a channel **1020** of the base rail **980B** by the bracket **1012**. The bracket **1012** is coupled to motor **1014**, belt **1016**, and pinion **1018**. The motor **1014** is coupled to the pinion **1018** by the belt **1016**. Thus, output rotation of the motor **1014** causes the pinion **1018** to rotate. The pinion **1018** is engaged with a rail lead screw **1010** of the base rail **980B**. Rotation of

the pinion **1018** causes the arm mount **1006A** to translate along the base rail **980B** parallel to the rail lead screw **1010**.

[0226] FIG. **10C** is an isometric cutaway view of an arm mount **1006A** on the base rail **980B** according to one embodiment. The arm mount **1006A** includes a belt and pinion assembly. Specifically, the belt and pinion assembly includes a motor **1014**, belt **1016**, pinion **1018**, and bearing **1022**. The surgical robotics system **1000** translates the arm mount **1006A**—and thus, a robotic arm mounted to the arm mount **1006A**—along the base rail **980B** using the belt and pinion assembly. The motor **1014** is coupled to the pinion **1018** by the belt **1016**. Thus, output rotation of the motor **1014** causes the pinion **1018** to rotate. The pinion **1018** is coupled to the bearing **1022**. In some embodiments, the bearing **1022** forms a rack and pinion assembly with the base rail **980B**. Specifically, the bearing **1022** is a gear (i.e., the pinion) and is engaged with a rack **1024** of the base rail **980B**. Rotation of the pinion **1018** causes the bearing **1022** to translate along the base rail **980B** parallel to the rack **1024**. Thus, the arm mount **1006A** also translates along the base rail **980B**.

[0227] FIG. **10D** is cross sectional views of the base rail **980B** according to one embodiment. The cross sectional view **1000A** shows a basic profile of an embodiment of the base rail **980B**. The cross sectional view **1000B** shows a reinforced profile of an embodiment of the base rail **980B**. The lower segment **1030B** of the reinforced profile is larger in size than the lower segment **1030A** of the basic profile. Thus, the reinforced profile is an advantage, for example, because it enables the base rail **980B** to withstand greater loads relative to the basic profile. Both the basic and the reinforced profiles have a T-slot attachment **1040**, which engages with a corresponding T-slot on a base of a surgical robotics system.

[0228] Alternative views and embodiments of the base rails **980A**, **980B**, and **980C** including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/193,604 filed Jul. 17, 2015 and U.S. Provisional Application No. 62/201,518 filed Aug. 5, 2015.

XI. Alternate Configurations

XI.A. Hybrid Configuration

[0229] FIG. **11** is an isometric view of a surgical robotics system **1100** with column-mounted robotics arms and rail-mounted robotic arms according to one embodiment. Due to the hybrid configuration including both column-mounted robotics arms and rail-mounted robotic arms, the surgical robotics system **1100** may configure the robotic arms in a greater number of (or different types of) positions compared to surgical robotics systems with column-mounted robotics arms only or rail-mounted robotic arms only. Further, the surgical robotics system **1100** takes advantage of the rotational motion of robotic arms using the column rings as well as translational motion of the robotic arms using the base rails.

XI. B. Cart-Based Robotic Arm Column

[0230] FIG. **12** is an isometric view of a surgical robotics system **1200** with column-mounted robotics arms on a column **402B** and base **403B** separate, e.g., as a free standing cart, from a table **101**, column **102**, and base **103** of the surgical robotics system **1200** according to one embodiment. The surgical robotics system **1200** configures the robotic arms to access the lower body area of patient **708** lying on the table **101**. In one embodiment, mounting the robotic arms on a cart including the column **402B** separate from the column **102** coupled to the table **101** with the patient is advantageous. For example, because the surgical robotics system **1200** may configure the robotic arms to a greater number of (or different types of) positions compared to surgical robotics systems with robotics arms mounted to the same column as the table, which are limited at least in the angles where the table extends past the column **102**. Further, the cart may include outrigger casters (e.g., previously described with reference to FIGS. **8G-J** in Section VIII. Base) that allow users to more easily transport the robotic arms or keep the cart stationary. Mounting the robotic arms separately can also reduce the number of components and complexity of the column coupled to the table with the patient.

[0231] Alternative views and embodiments of the surgical robotics system **1100**, the surgical robotics system **1200**, and other surgical robotics systems including the above mentioned components are further illustrated and described at least in U.S. Provisional Application No. 62/162,486 filed May 15, 2015, U.S. Provisional Application No. 62/162,467 filed May 15, 2015, U.S. Provisional Application No. 62/193,604 filed Jul. 17, 2015, U.S. Provisional Application No. 62/201,518 filed Aug. 5, 2015, U.S. Provisional Application No. 62/203,530 filed Aug. 11, 2015, and U.S. Provisional Application No. 62/235,394 filed Sep. 30, 2015.

XII. Adjustable Arm Supports

[0232] Robotic surgical (or medical) systems can include adjustable arm supports as described in this section for supporting one or more robotic arms. The adjustable arm supports can be configured to attach to either a table, a column support of the table, or a base of the table to deploy the adjustable arm supports and robotic arms from a position below the table. In some embodiments, the adjustable arm supports can be attached to a bed (or table) or a cart positioned adjacent to a bed. In some examples, the adjustable arm supports includes a bar, track, or rail on which one or more robotic arms are mounted. In some embodiments, the adjustable arm supports include at least three or four degrees of freedom that allow for adjustment of the position of the bar, track, or rail. One of the degrees of freedom can allow the adjustable arm support to be adjusted vertically relative to the table. These and other features of the adjustable arm supports will be described in detail with reference to the examples of FIGS. **13A-20**.

[0233] FIGS. **13A** and **13B** are isometric and end views, respectively, of a surgical robotics system **1300** that includes an adjustable arm support **1305** according to one embodiment. The adjustable arm support **1305** can be configured to support one or more robotic arms (see, for example, FIGS. **14A-15B**) relative to a table **1301**. As will be described in greater detail below, the adjustable arm support **1305** can be configured so that it can move relative to the table **1301** to adjust and/or vary the position of the adjustable arm support **1305** and/or any robotic arms mounted to the adjustable arm support **1305** relative to the table **1301**. For example, the adjustable arm support **1305** may include one or more degrees of freedom relative to the table **1301** to allow adjustment of the adjustable arm support **1305**. Although the system **1300** illustrated in FIGS. **13A** and **13B** includes only a single adjustable arm support **1305**, in some embodiments, systems can include multiple adjustable arm supports (see, e.g., system **1400** of FIG. **14A**, which includes two adjustable arm supports **1305A**, **1305B**).

[0234] Surgical robotics systems including adjustable arm supports **1305** as described in this section can be designed to address one or more issues of known surgical robotics systems. For example, one issue with some surgical robotics systems is that they may be bulky, occupying large amounts of room space. This is often because large and elaborate support structures have been necessary to position robotic arms to perform robotic surgical procedures. Some surgical robotics systems include robotic arm support structures that support a plurality of robotic arms above a table that supports a patient during the robotic surgical procedure. For example, some surgical robotics systems include support structures that suspend one or more robotic arms over a table. These support structures are quite large and bulky because, for example, they must extend over and above the table.

[0235] Another issue with some surgical robotics systems is that they can be overly cumbersome. Due to, for example, the large and bulky support structures required by some surgical robotics systems as described above, these systems are not easily moved, which can be disadvantageous. Before and after surgery, it can be desirable to quickly and smoothly clear the robotic arms from a surgical area to provide easy access for loading a patient onto or removing a patient from the table. This has proven to be difficult with some surgical robotics systems because of the large and bulky support structures and the cumbersome nature of these systems. Some surgical robotics systems are not easily stored or moved.

[0236] Further, some surgical robotics systems have limited flexibility or versatility. That is, some

surgical robotics systems are designed for a particular surgical procedure, and accordingly, do not work well for other types of surgical procedures. For example, a surgical robotics system that is configured for laparoscopic surgery may not work well for endoscopic surgery, or vice versa. In some instances, this is because the robotic arms used during the procedures need to be positioned in different locations relative the patient and/or table during different types of surgical procedures, and the support structures of conventional surgical robotics systems are not capable of accommodating the different positions of the robotic arms. Further, as mentioned above, some surgical robotics systems include support structures that suspend one or more robotic arms above the patient and table. It may be difficult to perform certain medical procedures with robotic arms mounted in this position.

[0237] Finally, some surgical robotics systems include robotic arms that are fixedly mounted to their corresponding support structures, and/or support structures themselves that are fixedly mounted or positioned. These systems may rely on articulation of the robotic arms alone to adjust the position of the robotic arms and/or surgical tools mounted thereto. Because the arms and/or supports are fixed in position, this can greatly limit the overall flexibility of these systems. The fixed nature of the robotic arms and/or supports of some systems may further limit the ability of these systems to avoid collisions between the arms and/or other objects (e.g., the patient, the table, other equipment, etc.) during surgery.

[0238] As shown in FIGS. **13A** and **13B**, for example, the system **1300**, including the adjustable arm support **1305**, as well as the other systems described in this application, can be configured to address (e.g., reduce or eliminate) one or more of the issues associated with some surgical robotics systems discussed above. For example, the systems described herein can be less bulky than some systems. The systems described herein can occupy less physical space than some systems. The systems described herein can be less cumbersome than some systems. For example, the systems described herein can be readily mobile and/or can be configured to store the arm supports and robotic arms quickly and easily to allow convenient access to the patient and/or table. The systems described herein can be highly flexible and configured for use in a wide variety of surgical procedures. For example, in some embodiments, the systems are configured for both laparoscopic and endoscopic procedures. The systems described herein can be configured to reduce collisions between the various robotic arms and other objects in the operating room.

[0239] In some embodiments, one or more of these advantages can be achieved by inclusion of one or more adjustable arm supports **1305** as described herein. As mentioned above, the adjustable arm supports **1305** can be configured so as to be able to move relative to the table **1301** to adjust and/or vary the position of the adjustable arm support **1305** and/or any robotic arms mounted to the adjustable arm support **1305** relative to the table **1301**. For example, the adjustable arm supports **1305** can be capable of being stowed (for example, below the table **1301**) and subsequently elevated for use. In some embodiments, the adjustable arm supports **1305** can be stowed in or in proximity to a base that supports the table **1301**. In some embodiments, the adjustable arm supports **1305** can be stowed in one or more recesses formed along a central longitudinal axis of the base. In other embodiments, the adjustable arm supports **1305** can be stowed in one or more recesses offset from a central longitudinal axis of the base. Upon elevation, the adjustable arm supports **1305** can be positioned near the patient, but below the table **1301** (e.g., below the upper surface of the table **1301**). In other embodiments, the arm supports **1305** can be raised above the table **1301** (e.g., above the upper surface of the table). Such a configuration can be useful, for example, when an adjustable arm support is positioned behind a patient lying on his side.

[0240] In some embodiments, the adjustable arm support **1305** is attached to the bed with a support structure that provides several degrees of freedom (e.g., lift, lateral translation, tilt, etc.). In the illustrated embodiment of FIGS. **13A** and **13B**, the arm support **1305** is configured with four degrees of freedom, which are illustrated with arrows in FIG. **13A**. A first degree of freedom allows for adjustment of the adjustable arm support in the z-direction (e.g., Z-lift). For example, as will be

described below, the adjustable arm support **1305** can include a carriage **1309** configured to move up or down along or relative to a column **1302** supporting the table **1301**. A second degree of freedom can allow the adjustable arm support **1305** to tilt. For example, the adjustable arm support **1305** can include a rotary joint, which can, for example, permit the arm support **1305** to be aligned with a bed in a Trendelenburg position. A third degree of freedom can allow the adjustable arm support to pivot up as shown. As will be described below, this degree of freedom can be used to adjust a distance between the side of the table **1301** and the adjustable arm support **1305**. A fourth degree of freedom can permit translation of the adjustable arm support **1305** along a longitudinal length of the table. Arm supports **1305** that include one or more of these degrees of freedom can address one or more of the issues associated with some systems noted above by providing a highly positionable support to which various robotic arms can be attached. The adjustable arm support **1305** can allow for adjustment of the position of the robotic arms relative to, for example, the table **1301**. In some embodiments, these degrees of freedom can be controlled serially, in which one movement is performed after another. In other embodiments, different degrees of freedom can be controlled in parallel. For example, in some embodiments, one or more linear actuators can provide both Z-lift and tilt.

[0241] These degrees of freedom, as well as other features of the adjustable arm support **1305**, will now be described in greater detail with continued reference to FIGS. **13A** and **13B**, which are isometric and end views, respectively, of the surgical robotics system **1300**, which includes the adjustable arm support **1305** according to one embodiment. In the illustrated embodiment, the system **1300** includes the table **1301**. In some embodiments, the table **1301** may be similar to the tables described above. In the illustrated embodiment, the table **1301** is supported by a column **1302**, which is mounted to a base **1303**. The base **1303** can be configured to rest on a support surface, such as a floor. Thus, the base **1303** and the column **1302** support the table **1301** relative to the support surface. FIG. **13B**, a illustrates support surface plane **1331**. In some embodiments, the table **1301** can be supported by one or more supports, wherein one of the supports comprises the column **1302**. For example, the table **1301** can be supported by a Stewart mechanism comprising a plurality of parallel actuators.

[0242] The system **1300** can also include the adjustable arm support **1305**. In the illustrated embodiment, the adjustable arm support **1305** is mounted to the column **1302**. In other embodiments, the adjustable arm support **1305** can be mounted to the table **1301** or the base **1303**. As mentioned above, the adjustable arm support **1305** is configured so that the position of the adjustable arm support **1305** can be adjusted relative to the table **1301**. In some embodiments, the position of the adjustable arm support **1305** can also be adjusted relative to the column **1302** and/or base **1303**.

[0243] The adjustable arm support **1305** can include a carriage **1309**, a bar or rail connector **1311**, and a rail **1307**. One or more robotic arms can be mounted to the rail **1307**, as shown, for example, in FIGS. **14A-15B**. For example, in some embodiments, one, two, three, or more robotic arms can be mounted to the rail **1307**. Further, in some embodiments, the robotic arms that are mounted to the rail can be configured to move (e.g., translate) along the rail **1307**, such that the position of the robotic arms on the rail **1307** can be adjusted relative to one another, thereby reducing the risk of collision between the robotic arms. This will be described in greater detail below. In the illustrated embodiment, the rail **1307** is connected to the bar or rail connector **1311**. The bar or rail connector **1311** is connected to the carriage **1309**. The carriage is connected to the column **1302**. Other arrangements are possible.

[0244] The column **1302** can extend along a first axis **1323**. In some embodiments, the first axis **1323** is parallel to the z-axis as illustrated. In some embodiments, the first axis **1323** is a vertical axis. For example, the first axis **1323** can be perpendicular to the support surface or floor on which the system **1300** rests.

[0245] The carriage **1309** can be attached to the column **1302** by a first joint **1313**. The first joint

1313 can be configured to allow the carriage **1309** (and accordingly the adjustable arm support **1305**) to move relative to the column **1302**. In some embodiments, the first joint **1313** is configured to allow the carriage **1309** to move along the column **1302** (for example, up and down along the column **1302**). In some embodiment, the first joint **1313** is configured to allow the carriage **1309** to move along the first axis **1323** (for example, back and forth along the first axis **1323**). The first joint **1313** can comprise a linear or prismatic joint. The first joint **1313** can comprise a powered joint, such as a motorized or hydraulic joint. The first joint **1313** can be configured to provide the first degree of freedom (e.g., Z-lift) for the adjustable arm support **1305**.

[0246] The adjustable arm support **1305** can include a second joint **1315** as shown. The second joint **1315** can be configured to provide the second degree of freedom (tilt) for the adjustable arm support **1305**. The second joint **1315** can be configured to allow the adjustable arm support **1305** to rotate around a second axis **1325** that is different than the first axis **1323**. In some embodiments, the second axis **1325** is perpendicular to the first axis **1323**. In some embodiments, the second axis **1325** need not be perpendicular relative to the first axis **1323**. For example, in some embodiments, the second axis **1325** is at an acute angle to the first axis **1323**. In some embodiments, the second axis **1325** extends in the y-direction. In some embodiments, the second axis **1325** may lie in a plane that is parallel to the support surface or floor on which the system **1300** rests. The second joint **1315** can comprise a rotational joint. The second joint **1315** can comprise a powered joint, such as a motorized or hydraulic joint.

[0247] In the illustrated embodiment, the second joint **1315** is formed between the carriage **1309** and the column **1302**, such that the carriage **1309** can rotate about the second axis **1325** relative to the column **1302**. In other embodiments, the second joint **1315** can be positioned in other locations. For example, the second joint **1315** can be positioned between the carriage **1309** and the rail connector **1311**, or between the rail connector **1311** and the rail **1307**.

[0248] As noted above, the second joint **1315** can be configured to allow the adjustable arm support **1305** to rotate about the second axis **1325** to allow for the second degree of freedom (tilt) for the adjustable arm support **1305**. As will be described in greater detail with reference to FIG. **16** below, rotating the adjustable arm support **1305** about the second axis **1325** can allow adjustment of a tilt angle of the adjustable arm support **1305**. That is, an angle of tilt of the bar or rail **1307** can be adjusted by rotating the adjustable arm support **1305** about the second axis **1325** (see FIG. **16**).

[0249] The adjustable arm support **1305** can include a third joint **1317** as shown. The third joint **1317** can be configured to provide the third degree of freedom (pivot up) for the adjustable arm support **1305**. The third joint **1317** can be configured as a rotational joint to allow the rail connector **1311** to rotate around a third axis **1327** that is different from the first axis **1323** and the second axis **1325**. In some embodiments, the third axis **1327** can be perpendicular to the second axis **1325**. In other embodiments, the third axis **1327** need not be parallel to the second axis **1325**. For example, the third axis **1327** can beat an acute angle relative to the second axis **1325**. In some embodiments, the third axis **1327** extends in the x-direction. In some embodiments, the third axis **1327** may lie in a plane that is parallel to the support surface or floor on which the system **1300** rests. The third axis **1327** may lie in the same plane or a different plane than the second axis **1325**. When the adjustable arm support **1305** is positioned as shown in FIGS. **13A** and **13B**, the third axis **1327** can be perpendicular to the first axis **1323**; however, as the adjustable arm support **1305** is rotated about the second joint **1315**, the angle between the first axis **1323** and the third axis **1327** can vary. In some embodiments, the third axis **1327** can be parallel to the rail **1307**.

[0250] When configured as a rotational joint, the third joint **1317** can allow the rail connector **1311** to rotate around the third axis **1327**. As the rail connector **1311** rotates around the third axis **1327**, a distance (for example, measured along the y-direction) between an edge of the table **1301** and the rail **1307** can be adjusted. For example, the distance between the edge of the table **1301** and the rail **1307** would increase as the rail connector **1311** is rotated downward from the position shown in FIG. **13B**. Thus, the third joint **1317** can be configured to provide a degree of freedom that allows

adjustment of the positioning of the rail **1307** along the y-direction. Further, when configured as a rotational joint, the third joint **1317** can also allow additional adjustment of the position of the rail **1307** along the z-direction. For example, the height of the rail **1307** (along the z-direction) would decrease as the rail connector **1311** is rotated downward from the position shown in FIG. **13B**. In some embodiments, the third joint **1317** can allow the rail **1307** to pivot upwards in a “biceps curl” type fashion from a stowed position to an elevated position.

[0251] As best seen in FIG. **13B**, in the illustrated embodiment, the third joint **1317** is positioned on a first end of the rail connector **1311** that connects the rail connector **1311** to the carriage. An additional joint **1319** can be included at a second end of the rail connector **1311** that connects the rail connector **1311** to the rail **1307**. In some embodiments, the position of the third joint **1317** and the additional joint **1319** can be reversed. In some embodiments, the additional joint **1319** is mechanically constrained to the third joint **1317** such that the third joint **1317** and the additional joint **1319** rotate together. For example, the third joint **1317** and the additional joint **1319** can be mechanically constrained via a four-bar linkage. Other methods for mechanical constraint are also possible. Mechanical constraint between the third joint **1317** and the additional joint **1319** can be configured to maintain an orientation of the rail **1307** as the rail connector **1311** is rotated about the third axis **1327**. For example, mechanical constraint between the third joint **1317** and the additional joint **1319** can be configured such that, as the rail connector **1311** rotates, an upper surface of the rail **1307** (to which one or more robotic arms can be mounted) continue to face in the same direction. In the illustrated example of FIGS. **13A** and **13B**, the upper face of the rail **1307** is facing upwards (in the z-direction). Mechanical constraint between the third joint **1317** and the additional joint **1319** can be configured such that the upper face of the rail **1307** remains facing upwards (in the z-direction) as the rail connector **1311** rotates. In some embodiments, mechanical constraint can be replaced with a software-defined constrained. For example, each of the third joint **1317** and the additional joint **1319** can be a powered joint, and software can be used to constrain rotation of each joint together.

[0252] In some embodiments, the third joint **1317** can comprise a linear joint or prismatic joint (in place of the rotation joint described above and illustrated in the figures) configured to allow linear displacement of the rail **1307** toward and away from the column **1302** (for example, along the y-direction).

[0253] The third joint **1317** can comprise a powered joint. In some embodiments, the third joint **1317** can comprise a motorized or hydraulic joint.

[0254] The adjustable arm support **1305** can include a fourth joint **1321** as shown. The fourth joint **1321** can be configured to provide the fourth degree of freedom (translation) for the adjustable arm support **1305**. For example, the fourth joint **1321** can be configured to allow the rail **1307** to translate back and forth relative to, for example, the table **1301**, the column **1302**, the carriage **1309**, and/or the rail connector **1311**. The rail **1307** can extend along a fourth axis **1329**. The fourth joint **1321** can be configured to allow the rail **1307** to translate along the fourth axis **1329**. In some embodiments, the fourth axis **1329** can be parallel to third axis **1327**. In other embodiments, the fourth axis **1329** can be at a non-parallel (e.g., an acute angle) to third axis **1327**. In some embodiments, the fourth axis **1329** can be perpendicular to the second axis **1325**. In other embodiments, the fourth axis **1329** can be at a non-perpendicular angle (e.g., an acute angle) to the second axis **1325**. When the adjustable arm support **1305** is positioned as shown in FIGS. **13A** and **13B**, the fourth axis **1329** can be perpendicular to the first axis **1323**; however, as the adjustable arm support **1305** is rotated about the second joint **1315**, the angle between the first axis **1323** and the fourth axis **1329** can vary.

[0255] The fourth joint **1321** can comprise a linear or prismatic joint. The fourth joint **1321** can comprise a powered joint, such as a motorized or hydraulic joint. In the illustrated embodiment, the fourth joint **1321** is positioned between the bar or rail connector **1311** and the rail **1307**.

[0256] As will be described in greater detail below with reference to FIGS. **15A** and **15B**,

translation of the rail **1307** can be configured to provide increased longitudinal reach (for example, along the x-direction) for the system **1300**. This may improve the flexibility of the system **1300**, allowing the system **1300** to be used in a wider variety of surgical procedures.

[0257] In some embodiments, the adjustable arm support **1305** is configured to allow for variable positioning of the rail **1307** relative to the table **1301**. In some embodiments, the position of the rail **1307** remains below a support surface plane **1333** that is parallel with an upper surface of the table **1301**. This may be advantageous as it may improve the ability to maintain a sterile field above the table support surface plane **1333** during a medical procedure. In the operating environment, medical personal may desire to maintain a sterile field above the surface of the table. As such, there may be heightened requirements or stricter procedures for equipment that is positioned above the surface of the table. For example, equipment positioned above the surface of the table may need to be draped. As such, it may be desirable, and some medical personal may prefer, that the arm support is maintained below the surface of the table. In some instances, when the arm support is maintained below the surface of the table, it may not need to be draped. In other embodiments, however, the adjustable arm support **1305** can adjust the position of the rail **1307** such that it is positioned above the table support surface plane **1333**.

[0258] In some embodiments, the adjustable arm support **1305** is attached to the base **1303**, the column **1302**, or the table **1301** at a position below the table support surface plane **1333**. As will be described below with reference to FIGS. **18A** and **18B**, this may advantageously permit the adjustable arm support **1305** (and any attached robotic arms) to be moved to a stowed configuration in which the adjustable arm support **1305** (and any attached robotic arms) are stowed below the table **1301** (see FIG. **18B**). This may advantageously make the system **1300** less bulky and/or less cumbersome when compared to previously known surgical robotics systems.

[0259] Movement of the arm support **1305** (for example, movement of one or more of the first, second, third, or fourth joints **1313**, **1315**, **1317**, **1321**) may be controlled and/or commanded in several ways. For example, the system **1300** can include a controller (e.g., a pendant) either on the bed (patient side) or a surgeon console. As another example, buttons (or other actuation mechanisms) could be included on one or more of the components of the adjustable arm support **1305** (or on one or more of the connected robotic arms). As another example, movement of the adjustable arm support **1305** can be provided automatically by system software, for example, for adjustment within the robot's null space (while maintaining the tooltip position commanded by the surgeon). Additionally, movement of the adjustable arm support **1305** can be provided automatically by system software during setup, deployment, draping, or other workflow steps when tools are not inserted into the patient. Other examples are also possible.

[0260] FIGS. **13A** and **13B** illustrate an embodiment that includes one adjustable arm support **1305**. As noted previously, some systems can include more than one adjustable arm support **1305**, each supporting one or more robotic arms. In such systems, each adjustable arm support can be configured as described above. Further, in such systems, each adjustable arm support can be controlled independently.

[0261] FIG. **14A** is an end view of a surgical robotics system **1400A** with two adjustable arm supports **1305A**, **1305B** mounted on opposite sides of the table **1301** according to one embodiment. Each of the adjustable arm supports **1305A**, **1305B** can be configured as described above. In the illustrated embodiment, a first adjustable arm support **1305A** is positioned on a first side of the table **1301** (e.g., the right side as shown in the figure), and a second adjustable arm support **1305B** is positioned on a second side of the table **1301** (e.g., the left side as shown in the figure). The second side can be opposite the first side.

[0262] Further, a first robotic arm **1402A** is illustrated attached to the bar or rail **1307A** of the first adjustable arm support **1305A**, and a second robotic arm **1402B** is illustrated attached to the bar or rail **1307B** of the second adjustable arm support **1305B**. As illustrated, the first robotic arm **1402A** includes a base **1404A** attached to the rail **1307A**. The distal end of the first robotic arm **1402A**

includes an instrument drive mechanism **1406A**. The instrument drive mechanism **1406A** can be configured to attach to one or more robotic medical instruments or tools. Similarly, the second robotic arm **1402B** includes a base **1404B** attached to the rail **1307B**. The distal end of the second robotic arm **1402B** includes an instrument drive mechanism **1406B**. The instrument drive mechanism **1406B** can be configured to attach to one or more robotic medical instruments or tools. Example robotic arms configured for use with the adjustable arm supports **1305** are described below in greater detail in Section XIII (see FIGS. **21-30**).

[0263] FIG. **14A** illustrates that the adjustable arm supports **1305A**, **1305B** can be independently controlled and positioned. As illustrated, the first adjustable arm support **1305A** is positioned at a first height along the first axis **1323**, and the second adjustable arm support **1305B** is positioned at a second height along the first axis **1323**. In some embodiments, the second height can be different and independent from the first height. In other embodiments, the second height can be substantially equivalent to the first height.

[0264] In the embodiment in FIG. **14A**, the carriage **1309A** of the first adjustable arm support **1305A** is positioned at a first height along the first axis **1323**, and the carriage **1309B** of the second adjustable arm support **1305B** is positioned at a second height along the first axis **1323** different than the first height. Thus, a height difference **H 1** can exist between the carriages **1309A**, **1309B** of the first and second adjustable arm supports **1305A**, **1305B**. In other embodiments, the carriages **1309A**, **1309B** of the first and second adjustable arm supports **1305A**, **1305B** can be positioned at the same height.

[0265] Further, FIG. **14A** illustrates the position of the bar or rail connectors **1311A**, **1311B** of the first and second adjustable arm supports **1305A**, **1305B**, which can also be independently adjusted to have different orientations. For example, as illustrated, the rail connector **1311A** of the first adjustable arm support **1305A** is rotated downwardly, and the rail connector **1311B** of the second adjustable arm support **1305B** is rotated upwardly. A height difference **H 2** can exist between the rails **1307A**, **1307B** of the first and second adjustable arm supports **1305A**, **1305B**, as illustrated. Further, in this position, each of the rail connectors **1311A**, **1311B**, of the first and second adjustable arm supports **1305A**, **1305B** is positioned at a different distance from the first axis **1323**. For example, the rail connector **1311A** of the first adjustable arm support **1305A** is positioned at a first distance **D1** from the first axis **1323**, and the rail connector **1311B** of the second adjustable arm support **1305B** is positioned at a second distance **D2** from the first axis **1323**. This distance **D1** can be different than the distance **D2**. In some embodiments, the rail connectors **1311A**, **1311B**, of the first and second adjustable arm supports **1305A**, **1305B** can be rotated to the same degree and/or the distance **D1** can be equal to the distance **D2**.

[0266] FIG. **14A** illustrates that the adjustable arm supports **1305A**, **1305B** can each be positioned or adjusted independently to provide different positions at which the robotic arms attached thereto are supported. FIG. **14A** illustrates only one example among many. The adjustable arm supports **1305** can have continuous movement (e.g., vertical or longitudinal) and can be stopped at any point as desired by a surgeon or clinician. This can be beneficial, for example, in creating a height differential between the arm supports, which can be advantageous for certain types of surgeries, such as when one set of robotic arms needs to reach low and the other needs to reach over a patient. For example, as shown in FIG. **14A**, the second adjustable arm support **1305B** with attached robotic arm **1402B** is raised higher than the first adjustable arm support **1305A** with attached robotic arm **1402A**. This position may be especially helpful when the patient is on its side (e.g., lateral decubitus), such as in a nephrectomy procedure, although one skilled in the art will appreciate that a differential can be beneficial in other procedures as well. FIGS. **14B** and **14C** provide additional examples.

[0267] FIG. **14B** is an isometric view of a surgical robotics system **1400B** with two adjustable arm supports **1305A**, **1305B** and a plurality of robotic arms **1402A**, **1402B**, **1402C**, **1402D** configured for a laparoscopic procedure according to one embodiment. In the illustrated embodiment, a first

adjustable arm support **1305A** supports a first robotic arm **1402A**, and a second adjustable arm support **1305B** supports a second robotic arm **1402B**, a third robotic arm **1402C**, and a fourth robotic arm **1402D**.

[0268] The first robotic arm **1402A** can be configured to translate back and forth along the rail **1307A** of the first adjustable arm support **1305A**. That is, the first robotic arm **1402A** can be configured to translate along the fourth axis **1329A**. This can allow for adjustment of the first robotic arm **1402A** relative to the rail **1307A**. Similarly, the second robotic arm **1402B**, the third robotic arm **1402C**, and the fourth robotic arm **1402D** can each be configured to translate back and forth along the rail **1307B** of the second adjustable arm support **1305B**. That is, the second robotic arm **1402B**, the third robotic arm **1402C**, and the fourth robotic arm **1402D** can be configured to translate along the fourth axis **1329B** of the second adjustable arm support **1305B**. This can allow for adjustment of the second robotic arm **1402B**, the third robotic arm **1402C**, and the fourth robotic arm **1402D** relative to the rail **1307B**. Further, each of the second robotic arm **1402B**, the third robotic arm **1402C**, and the fourth robotic arm **1402D** can be independently moved along the rail **1307B** such that the spacing between each of the second robotic arm **1402B**, the third robotic arm **1402C**, and the fourth robotic arm **1402D** can be adjusted. Among other things, FIG. **14B** illustrates that in some embodiments, the position of each robotic arm **1402** along the corresponding rail **1307** of the corresponding arm support **1305** can be independently controlled and adjusted.

[0269] Further, FIG. **14B** illustrates another example of a height differential between the first and second arm supports **1305A**, **1305B**. In the illustrated embodiment, a patient **10** is positioned on his or her side during a laparoscopic procedure. The first adjustable arm support **1305A** is positioned in a high position (but below the surface of the table **1301**) such that the first robotic arm **1402A** can reach over the patient **10**. As illustrated, the second adjustable arm support **1305B** is positioned at a lower position such that the second robotic arm **1402B**, the third robotic arm **1402C**, and the fourth robotic arm **1402D** can access an anterior side of the patient.

[0270] In some embodiments, one or more of the robotic arms **1402A**, **1402B**, **1402C**, **1402D** can operate laparoscopic surgical instruments or tools, and one or more of the other of the **1402A**, **1402B**, **1402C**, **1402D** can operate a camera laparoscopically inserted into the patient. In some embodiments, the one or more laparoscopic surgical instruments and the camera can be sized and configured to extend through one or more laparoscopic ports in a patient.

[0271] FIG. **14C** is an isometric view of a surgical robotics system **1400C** with two adjustable arm supports **1305A**, **1305B** and a plurality of robotic arms **1402A**, **1402B**, **1402C**, **1402D**, **1402E** configured for a laparoscopic procedure according to one embodiment. In the illustrated embodiment, a first adjustable arm support **1305A** supports a first robotic arm **1402A** and a second robotic arm **1402B**, and a second adjustable arm support **1305B** supports a third robotic arm **1402C**, a fourth robotic arm **1402D**, and a fifth robotic arm **1402E**.

[0272] In the illustrated embodiment, the table **1301** supporting the patient **10** is positioned at an angle relative to the floor. That is, rather than being parallel, as illustrated for example, in FIG. **14B**, a table surface plane **1333** is angled with respect to a support surface plane **1331**. The first adjustable arm support **1305A**, positioned on the lower side of the table **1301**, can be positioned in a low position such that the first robotic arm **1402A** and the second robotic arm **1402B** can access the patient **10**. As illustrated, the second adjustable arm support **1305B** is positioned at a higher position (which may be lower than the table support surface **1333**) such that the third robotic arm **1402C**, the fourth robotic arm **1402D**, and the fifth robotic arm **1402E** can reach over and access the patient **10**.

[0273] FIG. **15A** is an isometric view of a surgical robotics systems with two adjustable arm supports **1305A**, **1305B** that are configured to translate to adjust the position of the adjustable arm supports **1305A**, **1305B** according to one embodiment. As described previously, the adjustable arm support **1305** can include a fourth joint **1321** configured to allow the rail **1307** to translate along the

fourth axis **1329** relative to the base **1303**, column **1302**, table **1301**, carriage **1309**, and/or rail connector **1311**. FIG. 15A illustrates that, in embodiments that include two adjustable arm supports **1305A**, **1305B**, the rail **1307A**, **1307B** of each adjustable arm support **1305A**, **1305B** can be translated along its corresponding axis **1329A**, **1329B**, independently of the other rail. For example, in FIG. 15A, the rail **1307A** can translate back and forth along the axis **1329A**, independently from the rail **1307B**, which can also translate back and forth along the axis **1329B**.

[0274] In other embodiments, rails **1307** are not configured to translate along the axis **1329**. For example, in some embodiments, longer rails **1307** can be used in lieu of translating rails. In some embodiments, translation of the rails **1307** permits shorter rails **1307** to be used while still maintaining the overall versatility and flexibility of the system. In some embodiments, shorter rails **1307** (with or without translation) can improved the ability of system to bestowed below the table **1301** (see FIG. 18B).

[0275] FIG. 15B is an isometric view of a surgical robotics system **1500B** with an adjustable arm support **1305** and robotic arm **1402** configured for an endoscopic procedure according to one embodiment. FIG. 15B illustrates that, in some embodiments, a system including an adjustable arm support **1305** can be configured to provide a long longitudinal range of motion that can be useful, for example, in an endoscopic procedure, such as a ureteroscopy, wherein an endoscope is inserted into the patient through the groin area. For example, as shown in FIG. 15B, the rail **1307** can be translated all the way toward the foot of the table **1301**. From there, the arm **1402** can further extend longitudinally to position an instrument between the legs of the patient **10** for access to the groin area. Although only one robotic arm **1402** is illustrated in FIG. 15B, in other embodiments, multiple robotic arms, either mounted on the same adjustable arm support **1305** or an additional arm support **1305** can be configured for use in an endoscopic procedure. FIG. 15B provides only one example of an endoscopic procedure. Systems including adjustable arm supports **1305** can be used in other types of endoscopic procedures, such as bronchoscopy, for example.

[0276] FIG. 16 is an isometric view of a surgical robotics system **1600** with an adjustable arm support **1305** configured with a rail **1307** capable of tilting according to one embodiment. As discussed previously, an arm support can include a second joint **1315** configured to allow the arm support **1305** to tilt. In the illustrated embodiment of FIG. 16, the second joint **1315** is positioned between the carriage **1309** and the rail connector **1311**, although, as discussed previously, other positions for the second joint **1315** are possible. The second joint **1315** can be rotational joint configured to rotate or provide adjustment of the arm support **1305** about the second axis **1325**. As shown in FIG. 16, by rotating or providing adjustment of the arm support **1305** about the second axis **1325**, a tilt angle **1335** of the axis **1329** can be adjusted. The tilt angle **1335** can be measured between, for example, the axis **1329** (of the rail **1307**) and the x-axis, the support surface plane **1331**, or the table surface plane **1333**.

[0277] In some embodiments, the second joint **1315** permits tilting of the rail relative to the table **1301**. In some embodiments, the table **1301** can also pivot or tilt (for example to a Trendelenburg position), and the second joint **1315** can allow the adjustable support arm **1315** to follow the pivoting or tilting of the table **1301**. This can allow surgical arms **1402** to remain in position a relative to the patient **10** and/or table **1301** as the table **1301** pivots or tilts. This may be advantageous as a surgeon or clinician may desire to pivot or tilt the table **1301** intraoperatively. In some embodiments, the second joint **1315** pivots or tilts to allow the rail **1307** to remain parallel with the table **1301** as the table tilts. In some embodiments, the rail **1307** need not remain parallel with the table **1301**.

[0278] FIGS. 17A and 17B illustrate that systems including adjustable arm supports **1305** may provide improved access for medical imaging devices. As described above, the position of the adjustable arm support **1305** can be adjusted so as to allow access to or accommodate a medical imaging device, such as a C-arm. In addition to providing improved access for medical imaging devices, the adjustable arm supports also provide improved access for clinicians.

[0279] FIG. 17A is an isometric view of a surgical robotics system **1700A** with adjustable arm supports **1305A**, **1305B** positioned to allow access for a C-arm **1704** of a medical imaging device **1702** according to one embodiment. As shown, the second adjustable arm support **1305B** is positioned near the floor, so as to be positioned below the C-arm **1704** of the medical imaging device. The first adjustable arm support **1305A** is positioned near the table **1301** such that the robotic arm can access the patient.

[0280] FIG. 17B is an isometric view of the surgical robotics system **1700B** with the adjustable arm supports **1305A**, **1305B** positioned to allow access for the C-arm **1704** of the medical imaging device **1702** according to another embodiment. In the illustrated embodiment, the first adjustable arm support **1305A** is positioned near the table **1301**, such that the C-arm **1704** partially surrounds the first adjustable arm support **1305A**.

[0281] The adjustability of the adjustable arm supports **1305** can advantageously allow the systems to work with will other types of medical imaging devices as well.

[0282] FIGS. 18A and 18B illustrate that systems including adjustable arm supports **1305** can be configured to allow the adjustable arm supports **1305** and corresponding robotic arms **1402** to stow conveniently below the table **1301**. This may advantageously provide that the systems are less bulky and cumbersome than some surgical robotics systems. The adjustable arm supports **1305** can transition between a stowed configuration (FIG. 18B) and a deployed configuration (FIG. 18A).

[0283] FIG. 18A is an isometric view of a surgical robotics system **1800A** with an adjustable arm support **1305** positioned in a deployed configuration according to one embodiment. As shown, the adjustable arm support **1305** has been adjusted such that the rail **1307** is positioned adjacent to a side of the table **1301**, and a robotic arm **1402** has been deployed so as to access the patient **10**. FIG. 18A also illustrates that the base **1303** can include a recess **1337**. The recess **1337** can be configured to receive the arm support **1305** in the stowed configuration, as shown for example, in FIG. 18B.

[0284] FIG. 18B is an isometric view of a surgical robotics system **1800B** with adjustable arm supports **1305A**, **1305B** positioned in a stowed configuration according to one embodiment. As shown, bar or rails **1307A**, **1307B** of each arm support are received into recesses **1337** in the base **1303**. In some embodiments, the robotic arms **1402A**, **1402B**, **1402C** can fold over the arm supports **1305A**, **1305B** as shown. A stowed configuration, for example, with the arm supports **1305A**, **1305B** stored in recesses **1337** below the table **1301**, as shown in FIG. 18B, can advantageously make the system less bulky and cumbersome. In other embodiments, both the arm supports and robotic arms can be stored into recesses in the base **1303**. While embodiments described herein illustrate an arm support in a low position relative to the table, in other embodiments, adjustable arm supports can be provided from an elevated or suspended position above the table. These adjustable arm supports in a suspended position can have attributes similar to those that are positioned lower, including independent adjustability, height differential relative to one another, tilt, and longitudinal translation.

[0285] In some embodiments, systems including adjustable arm supports **1305** can be configured to be mobile. For example, in some embodiments, the base **1303** can include wheels to allow the system to be easily repositioned (see, e.g., FIG. 14A). For example, the system could have a separate transport cart that lifts it off the floor and moves it. In some embodiments, the system is not permanently affixed in the operating room.

[0286] FIG. 19 is a flow chart illustrating a method **1900** for operating a surgical robotics system with adjustable arm supports according to one embodiment. For example, the method **1900** can be used to operate any of the systems described above with reference to FIGS. 13A-18B. In some embodiments, the method **1900** can be stored as computer readable instructions stored in a memory. A processor can access the memory and execute the computer readable instructions to perform the method **1900**.

[0287] The method **1900** begins at block **1902** which involves receiving a command. In some

embodiments, the command is received from a physician, nurse, physician assistant, surgeon staff, etc. The command may relate to the positioning of at least one of a first robotic arm, a medical instrument coupled to an end effector of the robotic first arm, and/or an arm support coupled to a base of the first robotic arm. In some embodiments, the command may be a command to stow or deploy the system.

[0288] In some embodiments, a first command actuates the at least one joint to adjust the position of the arm support along a vertical axis of the column, a second command actuates a second joint for pivoting up the arm support, a third command actuates a third joint for tilting the arm support and a fourth command causes longitudinal translation of the arm support.

[0289] At block **1904**, the method **1900** involves actuating at least one joint of an adjustable arm support to adjust a position of a bar or rail of the arm support based on the received command. For example, the method **1900** may actuate one or more of the first joint, the second joint, the third joint, and/or the fourth joint. This may cause the arm support to move in one or more of its degrees of freedom.

[0290] The method **1900** may further include raising the arm support, the first robotic arm, and the second robotic arm from a stowed position below the table; positioning the arm support, the first robotic arm and the second robotic arm adjacent the table; adjusting a position of the arm support relative to the table via at least one of the first command, second command, third command, or fourth command, and adjusting a position of the first robotic arm relative to the second robotic arm along the rail of the support joint in preparation for a surgical procedure. In some embodiments, the arm support is positioned below an upper surface of the table.

[0291] In some embodiments, the method **1900** is executed by a controller for executing one or more commands based on a kinematics model, wherein the one or more commands control the positioning of one or more of the first robotic arm, the medical instrument coupled to an end effector of the robotic first arm; and an arm support coupled to a base of the first robotic arm and to a column supporting a patient-support table, wherein the arm support comprises at least one joint and a rail configured to support the first robotic arm.

[0292] FIG. **20** is a block diagram of a surgical robotics system **2000** with adjustable arm supports **1305A**, **1305B** according to one embodiment. As shown, the system **2000** includes a processor **2002** in communication with a memory **2004**. The processor **2002** and memory **2004** can be configured to execute, for example, the method **1900** described above.

[0293] The system also includes the table **1301**. In the illustrated embodiments, two adjustable arm supports **1305A**, **1305B** are coupled to the table **1301**. The adjustable arm supports **1305A**, **1305B** can be coupled to the table **1301**, a column **1302** supporting a table, or a base **1303** supporting the column. Each of the adjustable arm supports **1305A**, **1305B** is in communication with the processor **2002** such that the process can adjust the position of the adjustable arm supports **1305A**, **1305B**.

[0294] In the illustrated embodiment, a set of robotic arms is attached to each of the adjustable arm supports **1305A**, **1305B**. For example, robotic arms **1402A**, **1402B** are coupled to adjustable arm support **1305A**, and robotic arms **1402C**, **1402D** are coupled to adjustable arm support **1305B**. In other embodiments, other numbers of robotic arms (e.g., one, three, four, etc.) can be coupled to each arm support **1305A**, **1305B**. Example robotic arms are described in section XIII below. In some embodiments, as the arm supports support multiple robotic arms, the stiffness of the arm supports can be increased. This increased stiffness provides an added benefit of stability when used with multiple arms, as this can reduce the shaking of the robotic arms during a surgical process.

[0295] In some embodiments, the processor **2002** is configured to execute instructions stored in the memory **2004** to adjust a position of the bar or rail along the first axis in response to receiving a command. The command can comprise a command to adjust a position of a robotic medical tool coupled to a robotic arm coupled to the arm support. In some embodiments, the processor **2002** is further configured to execute the instructions to cause the system to at least adjust a position of a

rail or the arm supports **1305A**, **1305B** in response to a physician selected procedure. In some embodiments, the processor **2002** is further configured to execute the instructions to cause the system **2000** to at least adjust a position of the rail to avoid a collision between the robotic arm and at least one of: the table, a patient, an additional robotic arm, and a medical imaging device. The system **2000** may further be configured to avoid collision with other items in the environment of the system, such as, pendants, stirrups, things that clip onto the bed rail, a nurse, etc.). In addition to collision avoidance, the processor **2002** can further be configured to adjust the position of the arm supports **1305A**, **1305B** to optimize pose or improve manipulability of the robotic arms **1402A**, **1402B**, **1402C**, **1402D**.

XIII. Robot Arms Associated with Adjustable Arm Supports

[0296] The adjustable arm supports described above can be configured to mount to the table, the column, or the base, and can be adjustable (moveable in various degrees of freedom) to support robotic arms positioned on the adjustable arm supports. As the adjustable arm supports can be configured to mount below the surface of the table, in accordance with some embodiments, it can be advantageous to employ certain types of robotic arms with the adjustable arm supports. In some embodiments, the arms support(s) and/or the robotic arms coupled thereto can be mounted at least partially or wholly above the surface of the table. This section outlines certain features of robotic arms configured for use with the adjustable arm supports described above.

[0297] The robotic arms described in this section can be optimized for low mount positions relative to a table top (e.g., below a table top), which can face challenges such as collisions with the tabletop and other robotic arms. One skilled in the art will appreciate, however, that the robotic arms described in this section are not limited to low mount positions, and include features that are beneficial when attached to arm supports that are positioned above a surface of a table or suspended above a patient. In some embodiments, the robotic arms include several degrees of freedom (e.g., seven degrees of freedom) with at least one redundant degree freedom to provide greater flexibility to the robotic arm. As used herein, a robotic arm with redundant degrees of freedom can be one that contains more degrees of freedom than are necessary to perform a given task, and can accomplish the task in a wide variety of ways. For example, a robotic arm with redundant degrees of freedom can contain more degrees of freedom than are necessary to position an end effector (e.g., the end of a tool) in a desired location in a patient, and can achieve the desired position of the end effector in a wide variety of ways.

[0298] The robotic arms described in this section can further be optimized for rotating a tool with an end effector about a given point in space (e.g., the “remote center;” as used herein, a remote center can be considered as a fixed point around which a medical instrument rotates, with no physical revolute joint of the robotic system physically located at the remote center) while being supported, in some embodiments, by a mount point below the remote center (e.g., below a table top). The robotic arms can be optimized to operate in close proximity to (e.g., within a defined distance of) other robotic arm(s).

[0299] In some embodiments, the robotic arms described in this section may address (e.g., mitigate, resolve or eliminate) one or more issues that can occur in an operating room. For example, issues that the robotic arms and systems described in this application are designed to address can include operating in a limited space. In particular, space may be limited for a system with robotic arms coming from below a table. The issues that the robotic arms and systems described in this application are designed to address can include collisions with other robotic arms and/or other objects in the environment (e.g., the table, patient, doctors, medical imaging equipment, etc.). Additionally, the issues that the robotic arms and systems described in this application are designed to address can include challenges associated with a system coming from below a table. Such a system may need added flexibility to perform particular surgical procedures in which the robotic arms must position tools so as to access patient locations that are positioned above the laparoscopic ports (e.g., a ventral hernia procedure), e.g., to avoid collisions (e.g., with the table). The features

and advantages of the robotic arms described herein will become apparent from the following discussion of FIGS. **21-30**.

[0300] FIG. **21** is an isometric view of a robotic arm **2100** according to one embodiment. The robotic arm **2100** can be configured for use with the adjustable arm support(s) **1305** described above. The robotic arm **2100** extends between a proximal portion **2101** and a distal portion **2103**. The proximal portion **2101** can be configured to mount or attach to an adjustable arm support **1305**. For example, the proximal portion **2101** of the robotic arm **2100** can be configured to mount or attach to a bar, track, or rail **1307** of an adjustable arm support **1305**. As described above, the adjustable arm support **1305** can be configured with one or more degrees of freedom so as to position the robotic arm **2100** relative to a table. In some embodiments, the adjustable arm support **1305** and/or the robotic arm **2100** are configured to transition between a stowed state and a deployed state. In the stowed state, the adjustable arm support **1305** and the robotic arm **2100** may be positioned below the table (see, e.g., FIG. **18B**). In the deployed state, at least a portion of the robotic arm **2100** may extend above the surface of the table (see, e.g., FIG. **18A**). The adjustable arm support **1305** may be positioned below the surface of the table in the deployed state. In some embodiments, the adjustable arm support **1305** (or a bar or rail **1307** thereof) may be positioned above the surface of the table in the deployed state.

[0301] An instrument driver **2115**, also referred to as an instrument drive mechanism (ID M), can be positioned at the distal portion **2103** of the robotic arm **2100**. The instrument driver **2115** can be configured to attach or connect to a medical instrument. The instrument can be, for example, a laparoscopic instrument, an endoscopic instrument, a camera, etc. The instrument driver **2115** may be configured to actuate the instrument. For example, the instrument driver **2115** may include one or more motors, pulleys, capstans, or cables configured to actuate the instrument. As will be described below (see Section XIV), an insertion mechanism associated with the robotic arm **2100** may be included at the distal portion **2103** of the robotic arm **2100** and configured to insert (or retract) at least a portion of the instrument along an axis. As explained below, the insertion mechanism can be configured as part of the robotic arm **2100** itself (e.g., FIG. **21**) or as part of the instrument attached to the instrument driver **2115** (e.g., FIG. **24**).

[0302] The robotic arm **2100** may comprise a plurality of components arranged serially. The components can be connected by one or more joints (e.g., motorized or hydraulic joints) configured to allow movement or articulation of the robotic arm **2100**. As illustrated, for some embodiments, the joints can be grouped into the shoulder **2117**, the elbow **2119**, and the wrist **2121** as shown in FIG. **21**. That is, in some embodiments, the robotic arm **2100** includes the shoulder **2117**, the elbow **2119**, and the wrist **2121**, and that one or more of the shoulder **2117**, the elbow **2119**, and the wrist **2121** can include a plurality of joints. For example, in the illustrated example, the shoulder **2117** includes three joints, the elbow **2119** includes one joint, and the wrist **2121** includes two joints. Stated another way, in some embodiments, one or more of the shoulder **2117**, the elbow **2119**, or the wrist **2121** can provide more than one degree of freedom for the robotic arm **2100**. For example, in the illustrated embodiment, the shoulder **2117** is configured to provide three degrees of freedom, the elbow **2119** is configured to provide one degree of freedom, and the wrist **2121** is configured to provide two degrees of freedom. In some embodiments, the wrist can include an insertion degree of freedom such that the robotic arm **2100** can include at least seven degrees of freedom in accordance with some embodiments. In other embodiments, the shoulder **2117**, the elbow **2119**, or the wrist **2121** can be configured with other numbers of joints and/or to provide other numbers of degrees of freedom.

[0303] The shoulder **2117** can be located generally at the proximal portion **2101** of the robotic arm **2100**. The wrist **2121** can be located generally at the distal portion **2103** of the robotic arm **2100**. The elbow **2119** can be located generally between the proximal portion **2101** and the distal portion **2103**. In some embodiments, the elbow **2119** is located between the proximal link **2109** and the distal link **2111**. In some embodiments, the robotic arm **2100** can include other joints or regions of

joints than those illustrated in FIG. 21. For example, the robotic arm **211** could include a second elbow (comprising one or more joints) between the elbow **2119** and the wrist **2121** and/or between the elbow **2110** and the shoulder **2117**.

[0304] The various degrees of freedom of the robotic arm **2100** of FIG. 21 are illustrated with arrows. The arrows are intended to indicate the motions provided by each degree of freedom. The illustrated embodiment includes the following degrees of freedom. Not all degrees of freedom need be included in all embodiments, and in other embodiments, additional degrees of freedom can be included. The joints providing the various degrees of freedom can be powered joints, such as motorized joints or hydraulically powered joints, for example.

[0305] As illustrated, the robotic arm **2100** includes a degree of freedom **2151** permitting shoulder translation. This degree of freedom can allow the robotic arm **2100** to move along the arm support **1305**. For example, this degree of freedom can allow the robotic arm **2100** to move linearly along the arm support **1305**, for example, along the rail **1307** of the arm support. When multiple robotic arms **2100** are attached to the arm support **1305**, the translation advantageously reduces the risk of collision between the different arms.

[0306] The robotic arm **2100** can also include a degree of freedom **2153** permitting shoulder yaw. The degree of freedom **2153** can permit, for example, rotation of the shoulder housing **2107** (and correspondingly the remainder of the robotic arm **2100**) relative to the base **2105**.

[0307] The robotic arm **2100** can also include a degree of freedom **2155** permitting shoulder pitch. This degree of freedom **2155** can permit, for example, adjustment of the proximal link **2109** relative to the shoulder housing **2107**. For example, this degree of freedom can be used to adjust an angle of the proximal link **2109**.

[0308] The shoulder **2117** can be configured to provide the shoulder yaw degree of freedom **2153** and the shoulder pitch degree of freedom **2155**. For example, the shoulder **2117** can include one or more joints near the arm support **1305** that can allow the proximal link **2109** to point from the base **2105** of the arm **2100** in any direction. In some embodiments, these shoulder degrees of freedom can be arranged such that the proximal and distal links, for example, point inward toward the remote center (see, for example, FIG. 22).

[0309] The robotic arm **2100** can also include a degree of freedom **2157** permitting elbow pitch. This degree of freedom **2157** can permit adjustment of the distal link **2111** relative to the proximal link **2109**. For example, this degree of freedom **2157** can permit adjustment of an angle between the distal link **2111** and the proximal link **2109**. This degree of freedom can be provided by the elbow **2119**. In some embodiments, this degree of freedom is provided by a pivot joint that ensures that the distal link **2111** and the proximal link **2109** remain aligned (for example within a single plane or parallel planes). This alignment advantageously reduces the risk of collision among the arms, as the arms fan out and stay away from one another. Further, as described below, due to the enhanced motion of the wrist **2121** (e.g., providing multiple degrees of freedom), the motion at the elbow **2119** can be minimized, with the fastest motions of the robotic arm **2100** occurring at the wrist **2121**.

[0310] The robotic arm **2100** can also include a degree of freedom **2159** permitting wrist yaw. This degree of freedom **2159** can allow adjustment of a component connected to the distal link **2111** relative to the distal link **2111**. For example, this degree of freedom **2159** can allow adjustment between an insertion axis body **2113** or an instrument driver **2115** and the distal link **2111**. In some embodiments, this degree of freedom **2159** is used to adjust an angle of rotation of the component attached to the distal link **2111** relative to the distal link **2111**. Rotation can be measured, for example, around an axis of the distal link **2111**.

[0311] The robotic arm **2100** can also include a degree of freedom **2161** permitting wrist pitch. This degree of freedom **2161** can allow additional adjustment of the component connected to the distal link **2111** relative to the distal link **2111**. In some embodiment, this degree of freedom **2161** permits adjustment of an angle of tilt between the component connected to the distal link **2111** and

the distal link **2111**.

[0312] The robotic arm **2100** can also include a degree of freedom **2163** permitting instrument driver roll. This degree of freedom **2163** can be configured allow an instrument attached to the instrument driver (or the instrument driver itself) to be rolled around its axis.

[0313] In some embodiments, the wrist **2121** is configured to provide the wrist yaw, wrist pitch, and instrument driver roll degrees of freedom. In some embodiments, the wrist **2121** may comprise a partially spherical or spherical joint in some embodiments. The wrist **2121** can allow the robotic arm **2100** to pitch and yaw an instrument connected thereto about a remote center while minimizing movement of the robotic arm's other links. In other words, the wrist **2121** can allow motion to be minimized on other parts of the robotic arm **2100**, such as the elbow **2119**. The wrist **2121** can allow the instrument or tool to be delivered close to a patient, without having to move the whole robotic arm **2100**, thereby reducing the risk of collisions between the robotic arm **2100** and other objects in the environment.

[0314] An insertion degree of freedom **2165** can also be associated with the robotic arm **2100**. The insertion degree of freedom can be configured to permit insertion (or retraction) of the instrument (or tool) attached to the instrument driver mechanism **2115** along an axis of the instrument or an axis of the instrument driver **2115**. This axis, which can be referred to as an insertion axis, can be coaxial with the axis of rotation for the instrument driver roll degree of freedom **2163** discussed above. In some embodiments, the instrument can be inserted a certain depth into a patient via the insertion axis. The instrument can be held in the instrument driver **2115**, and the instrument driver **2115** can translate relative to the insertion axis body **2113**. In some embodiments, the insertion axis (or the insertion degree of freedom) allows the insertion depth in the patient to be decoupled from the pitch and yaw motion of the tool shaft (e.g., caused by the wrist **2121**). That is, in some embodiments, insertion of the instrument can be accomplished without requiring movement or articulation of the arm **2100**.

[0315] As noted above, in some embodiments, the insertion degree of freedom can be provided by (e.g., built into) the robotic arm **2100**. The robotic arm **2100** of FIG. **21** illustrates an embodiment in which the insertion degree of freedom can be provided by (e.g., built into) the robotic arm **2100**. As shown, the robotic arm **2100** includes an insertion axis body (or housing) **2113** attached (via one or more joints of the wrist **2121**) to the distal link **2111**. The insertion axis body **2113** can extend along an axis. The axis of the insertion axis body **2113** can be parallel to the insertion axis. The instrument driver **2115** can be attached to the insertion axis body **2113**. A joint between the instrument driver **2115** and the insertion axis body **2113** can be configured to allow the instrument driver **2115** to translate along the insertion axis body **2113** (e.g., back and forth along the insertion axis body **2113**). As the instrument driver **2115** translates along the insertion axis body **2113**, an instrument attached to the instrument driver **2115** can be inserted (or retracted) along the insertion axis.

[0316] In some embodiments, the wrist **2121** (positioned on a distal portion **2103** of the robotic arm **2100**) combined with the insertion degree of freedom (also provided at the distal portion **2103** of the robotic arm **2100**) may provide unique advantages, especially when deployed in connection with the adjustable arm supports **1305** discussed above. For example, this arrangement can provide one or more robotic arms **2100** that can be stowed and subsequently deployed in a compact fashion. This can, for example, aid in collision avoidance and make the robotic arms **2100** more successful or useful in setups where the end effector is above the incision.

[0317] In some embodiments, the insertion degree of freedom can be provided by (e.g., built into) the instrument that is attached to the robotic arm **2100**. For example, the instrument can include an instrument based insertion architecture that allows the at least a portion of the instrument to be inserted along the insertion axis. In this embodiment, the robot arm loses a degree of freedom, as the insertion degree of freedom is built in the instrument itself. In such embodiments, the instrument driver **2115** can be attached to (via one or more joints of the wrist **2121**), for example, to

the distal link **2111**. The instrument can comprise a handle and a shaft. The instrument handle can be attached to the instrument driver **2115**, and the instrument can provide insertion of at least a portion of the instrument along the instrument axis (for example, relative to the handle). Examples of embodiments in which the insertion degree of freedom can be provided by (e.g., built into) the instrument that is attached to the robotic arm **2100** are described in greater detail below with reference to FIG. **24**.

[0318] In some embodiments, six or more degrees of freedom (e.g., seven or eight) may be desirable to provide sufficient manipulability to perform a robotic medical procedure. For example, it may be desirable to have a robot arm with three degrees of freedom to position the instrument in three-dimensional space, for example, at a remote center, and three additional degrees of freedom to control the pitch, yaw, and roll of the instrument about the remote center. In some embodiments, it may be advantageous to include additional degrees of freedom beyond the six degrees of freedom required. These degrees of freedom can be referred to as redundant degrees of freedom. Redundant degrees of freedom can be advantageous, for example, in multi-arm setups, for optimizing arm pose and avoiding collisions. In some embodiments, redundant degrees of freedom can allow the robotic arm to be repositioned while maintaining the instrument position and the base position stationary. In some embodiments, the robotic arm **2100** includes three, four, five, six, seven, eight, nine, ten, or more degrees of freedom. In some embodiments, the robotic arm **2100** includes one, two, three, four, five, or more redundant degrees of freedom.

[0319] In addition to the robotic arm **2100** having the mechanisms described above for accommodating the multiple degrees of freedom described, the arm support **1305** on which robotic arm **2100** is mounted (and to which other robotic arms can also be mounted) can also provide additional degrees of freedom as discussed in the preceding section. Further, in some embodiments, multiple adjustable arm supports **1305** can be provided (for example, on opposite sides of the table), each supporting one or more robotic arms **2100**. In some of these embodiments, all of the robotic arms **2100** on one side of the table are mounted on a shared translation bar, track, or rail **1307**. These two rails **1307**, one on each side of the bed, can be positioned independently of each other, and could foreseeably have three degrees of freedom (e.g., lift, lateral translation, and tilt) as described above. Placing multiple robotic arms **2100** on a shared rail **1307** can reduce the set-up degrees of freedom necessary for a system and can provide a good stiffness path to ground.

[0320] FIG. **22** is an overhead view of a robotic surgical system **2200** including a plurality of robotic arms **2100A**, **2100B**, **2100C**, **2100D**, **2100E** performing a laparoscopic according to one embodiment. The robotic arms **2100A**, **2100B**, **2100C** are mounted on a first adjustable arm support **1305A**, and the robotic arms **2100D**, **2100E** are mounted on a second adjustable arm support **1305B**, located opposite the first adjustable arm support **1305A**. As shown, the robotic arms **2100A**, **2100B**, **2100C**, **2100D**, **2100E** are holding laparoscopic tools or instruments. The robotic arms **2100A**, **2100B**, **2100C**, **2100D**, **2100E** can insert the laparoscopic tools through laparoscopic ports (e.g., laparoscopic ports **2202A**, **2202C**, **2202D**) to gain access to a treatment site within the patient. In some embodiments, for each robotic arm **2100**, the corresponding laparoscopic port **2202** can be positioned at a remote center of the robotic arm **2100**. That is, an insertion axis of the robotic arm can be aligned with and extend through the remote center. The robotic arm **2100** can be configured to manipulate the pitch, roll, and yaw of the instrument about the remote center. In the present embodiment, the adjustable arm supports **1305A**, **1305B** are sized and configured to support multiple arms. As the adjustable arm supports **1305A**, **1305B** can have a thickness to support these arms, the adjustable arm supports have added stability to reduce the risk of shakiness.

[0321] FIG. **22** also illustrates that, in some embodiments, the robotic arm **2100** can be configured such that the wrist **2121** and the shoulder base **2105** of the robotic arm can lie along a substantially straight line **2250** when viewed from above. This is illustrated, for example, with respect to the wrist **2121A** and shoulder base **2105A** of the robotic arm **2100**. In some embodiments, the wrist

2121, elbow **2119** and shoulder **2117** can lie along a substantially straight line **2250** (from a top down view). In some embodiments, the wrist **2121**, elbow **2119** and shoulder **2117** can substantially align in a plane that is perpendicular to a table. Advantageously, by being substantially aligned in the same plane, the plane of the robotic arm remains substantially perpendicular to the table during a surgical procedure. This configuration is desirable as it allows one robot arms to avoid one another, and is in part enabled by the wrist configuration. In some embodiments, the robotic arm can be positioned such that the wrist **2121**, elbow **2119** and shoulder **2117** lie in a plane and the plane need not be parallel to the table. For example, the plane may be at an acute angle relative to the table.

[0322] FIG. **23** is an isometric view of an alternative robotic arm **2300** that includes two instrument drivers **2115A**, **2115B** according to one embodiment. In the illustrated embodiment, the two instrument drivers **2115A**, **2115B** are positioned at the distal portion **2103** of the robotic arm **2300**. Each of the instrument drivers **2115A**, **2115B** can be configured to receive a corresponding instrument. In some embodiments, the instruments are telescoping instruments, wherein one instrument is positioned within a working channel of the other instrument. For example, one instrument can be an endoscope and the other instrument can be an outer sheath that surrounds the endoscope. The instrument drivers **2115A**, **2115B** can be configured to drive their corresponding instrument independently. In some embodiments, each instrument can be inserted along an insertion axis. In some embodiments, the two axes are coaxial, such as the insertion axis **2305** illustrated. In the illustrated embodiment, one or both of the instrument drivers **2115A**, **2115B** can be configured to translate along the insertion axis body **2113** to provide insertion or retraction of the instruments. In other embodiments, the insertion of the tools is provided by the instruments themselves, as described below. In some embodiments, one or both of the instrument drivers can be removable.

[0323] FIG. **24** is an isometric view of an instrument **2400** with an instrument based insertion architecture attached to a distal end of an alternative robotic arm **2100** according to one embodiment. As mentioned above, in some embodiments, the instrument **2400** itself has an architecture that allows it to translate at least a portion of the instrument **2400** along an insertion axis. This can minimize the movement of the robot arm **2100** during insertion. For example, in the embodiment of FIG. **21**, the insertion drive mechanism **2115** moves along the insertion axis body **2113** to provide insertion along the insertion axis. In contrast, in the embodiment of FIG. **24**, the insertion drive mechanism **2415** can remain in the same position, while the architecture of the instrument **2400** itself causes at least a portion of the instrument **2400** to be inserted.

[0324] As illustrated, the instrument can comprise an instrument shaft **2406** and a cannula **2402** attached to an instrument handle (not shown). The instrument handle can be configured to attach and couple to the instrument driver **2415**. The instrument shaft **2406** can, in some embodiments, extend through the instrument handle and/or the instrument driver **2415**. The instrument driver **2415** can be attached to the wrist **2121** at the distal end of the robotic arm **2100**. The instrument **2400** can have a built-in architecture whereby the instrument shaft **2406** translates relative to the handle.

[0325] In some other robotic systems, a portion of the robotic arm often translates in order to achieve insertion (thereby increasing swing mass caused by the robot arm). In the present embodiment of FIG. **24**, the instrument **2400** itself has an architecture that accommodates insertion. Thus, in this and similar embodiments, the insertion axis is eliminated from the robotic arm **2100** and the overall size and motion of the robotic arm **2100** can be reduced. This can remove one degree of freedom from the robotic arm **2100**, but does not reduce the capability of the robotic **2100**, as the degree of freedom is moved to the instrument **2400** itself rather than the robotic arm **2100**. Section XIV, below, provides several examples of such instrument-based insertion architectures.

[0326] An additional advantage that may be present in some embodiments, like that shown in FIG.

24, is that an offset angle or distance between the wrist **2121** and the instrument roll axis or insertion axis can be reduced. In some embodiments, this allows for more reach with shorter links and less elbow motion for the robotic arm **2100**. Another advantage of the present embodiment in FIG. **24** is that the instrument driver can be below the wrist. This can be beneficial for particular procedures, such as ventral hernia type procedures.

[0327] FIGS. **25A** and **25B** illustrate that, in some embodiments, the robotic arm **2100** can be configured such that the insertion axis body **2113** can be configured to be generally reversible. In some embodiments, having an ability to operate a robotic arm **2100** with an instrument driver **2115** far from the remote center can mitigate arm collisions. To facilitate this, the robotic arm **2100** can be configured such that a cannula can be mounted on either side **2113A**, **2113B** of the insertion axis housing **2113**. This can be used to changes the distance of separation between the remote center and the wrist **2121**. This can provide an additional option to control to vary the position of the robotic arm **2100**.

[0328] FIG. **25A** is a side view of a robotic arm **2500A** with the insertion axis body **2113** positioned in a first orientation according to one embodiment. As shown, the instrument driver **2115** is positioned on a first side **2113A** of the insertion axis body **2113**. Further, the insertion axis body **2113** is oriented so as to be positioned away from a remote center. As shown, this generally brings the wrist **2121** closer to the remote center.

[0329] In contrast, FIG. **25B** is a side view of a robotic arm **2500B** with the insertion axis body positioned in a second orientation according to one embodiment. As shown, the instrument driver **2115** is positioned on a second side **2113B** of the insertion axis body **2113**. Further, the insertion axis body **2113** is oriented so as to be positioned toward from a remote center. As shown, this generally moves the wrist **2121** away from the remote center.

[0330] In some embodiments, the instrument driver **2115** is detachable such that it can be removed and attached to either side **2113A**, **2113B** of the insertion axis body **2113**. In some embodiments, to move from the first position shown in FIG. **25A** to the second position shown in FIG. **25B**, the wrist **2121** is pivoted over the top of the robotic arm. In other embodiments, to move between the first and second positions, the wrist **2121** can be rotated about robotic arm. In these embodiments, the instrument driver **2115** can be removed and/or flipped so as to be oriented in the opposite direction, or the instrument driver **2115** can be reversible such that the instrument can be attached to either side of the instrument driver, **2115**.

[0331] FIGS. **26A** and **26B** illustrate that, in some embodiments, the robotic arm **2100** can be operated with a detached cannula. This can provide similar functionality as the reversible insertion axis body **2113** described above (i.e., allowing varying position of the wrist **2121** relative to the remote center), in embodiments, that do not include an insertion axis body, such as the embodiments that include instruments that provide insertion as discussed above with reference to FIG. **24**. This can effectively give the robotic arm **211** one additional null space degree of freedom, as it allows the distance between the wrist **2121** and the cannula to dynamically change while holding the tool tip stationary.

[0332] FIG. **26A** is a sideview of a robotic arm **2600A** configured with an attached cannula **2602** according to one embodiment. As shown, the cannula **2602** is attached to the instrument driver **2115**. FIG. **26B** is a side view of a robotic arm **2600B** configured with a detached cannula **2602** according to one embodiment. As shown, the cannula **2602** is detached from the instrument driver **2115**. In this configuration, the cannula **2602** is free to move along the insertion axis as the instrument is inserted or retracted. Comparing FIGS. **26A** and **26B**, it can be seen that by detaching the cannula **2602**, the instrument driver **2115** and/or wrist **2121** can be moved back relative to the cannula **2602** and or tool tip **2604**.

[0333] This is further illustrated in FIG. **27A** (attached cannula) and **27B** (detached cannula). FIG. **27A** is an isometric view of a system including a plurality of robotic arms (e.g., **2701A**, **2702A**) performing a laparoscopic procedure, wherein one of the arms **2701A** is configured with an

attached cannula, according to one embodiment. As shown in FIG. 27A, in some embodiments, without detached cannula operation (i.e., with the cannula attached), the middle arm **2701A** may have limited room (illustrated by the distance **2703A**) to yaw before hitting the camera arm **2702A**. FIG. 27B is an isometric view of a system including a plurality of robotic arms (e.g., **2701B**, **2702B**) performing a laparoscopic procedure, wherein one of the arms **2701B** is configured with a detached cannula, according to one embodiment. As shown in FIG. 27B, in some embodiments, with detached cannula operation, the middle arm **2701B** can have more room (illustrated by the distance **2703B**) to yaw before hitting the camera arm **2702B**. Comparing FIGS. 27A and 27B, it can be seen that distance **2703B** is larger than distance **2703A**. As illustrated in these figures, the wrist of the robotic arm can be moved away from the remote center when the cannula is detached. This can provide additional room for maneuvering the robotic arms. In other embodiments, a cannula can stay attached and the remote center can move slightly along the length of the cannula. In other embodiments, cannulas can be made longer to allow for a remote center to be even farther from the wrist.

[0334] In some instances, the performance of the robotic arm **2100** can be improved by inclusion of one or more of the features discussed below. For example, the present inventors have determined that the robotic arm **2100** (for example, as shown in FIG. 21) may experience several singularities during use. The singularities may represent areas of degraded performance. For example, a singularity can occur when different axes of the robotic arm align, thereby losing a degree of freedom. Other example, singularities that have been identified can include: (i) base yaw intersects spherical wrist; (ii) an overly extended arm (e.g., with elbow pitch close to 180 degrees); and (iii) an under extended arm (e.g., with wrist close to plus or minus 90 degrees or elbow close to 0 degrees). The features illustrated in FIGS. 28-29B may address one or more of these singularities.

[0335] FIG. 28 is an isometric view of a robotic arm **2800** that includes a wrist **2821** having an additional rotational joint according to one embodiment. By comparison with the robotic arm **2100** of FIG. 21, the robotic arm **2800** may include a similar shoulder **2117** and elbow **2119**. However, the robotic arm **2800** includes an additional axis at the wrist **2821**. For example, the robotic arm **2100** described above includes a wrist **2121** that provides two degrees of freedom, while the robotic arm **2800** includes a wrist **2821** that provides four degrees of freedom. In some embodiments, it may be desirable to add an additional rotary axis to the wrist. In some embodiments, this rotary axis does not need a high range of motion, but can be employed by control algorithms to help keep other joints away from singularity. Adding an additional redundant degree of freedom to the wrist **2821** can allow for additional possibilities of collision avoidance (especially around tightly arranged ports on the midline) in addition to allowing for singularity avoidance. The additional degree of freedom provided by the wrist **2821** can, in some embodiments, help make arm performance more uniform through the arm's workspace and can reduce peak joint requirements necessary to achieve desired tool speeds. In some embodiments, the wrist can include additional degrees of freedom, for example, three, four, five, or more degrees of freedom. These can include, for example, an instrument insertion degree of freedom, an instrument roll degrees of freedom, and one or more rotational/pivoting degrees of freedom.

[0336] FIGS. 29A and 29B are isometric and side views, respectively of a robotic arm **2900** that includes a tilted base **2905** according to one embodiment. As best seen in FIG. 29B, the base **2905** can be tilted by an angle **2906**. The base **2905** can be tilted to adjust the yaw angle of the base. In some embodiments, this can help address the singularity that occurs when the base yaw intersects the wrist **2121** by increasing the effective distance between the axis of the base yaw joint and the wrist **2121** (as shown in FIG. 29B). In some embodiments, the tilt angle **2906** can be about 5 degrees, about 10 degrees, about 15 degrees, about 20 degrees, about 25 degrees, or about 30 degrees, 35 degrees, about 40 degrees, about 45 degrees, about 50 degrees, about 55 degrees, about 60 degrees, about 65 degrees, about 70 degrees, about 75 degrees, about 80 degrees, or about 85 degrees.

[0337] FIG. 30 is an isometric view of an alternative robotic arm 3000 that includes a telescoping link 3109. The robotic arm 3000 shares many features as previous embodiments, including a proximal portion 3001 and a distal portion 3003. The robotic arm 3000 comprises a plurality of joints arranged serially, including a shoulder, elbow and wrist, between the proximal portion 3001 and the distal portion 3003. In addition, the robotic arm 3000 includes at least a proximal link 3109 and a distal link 3111.

[0338] In some embodiments, at least one of the proximal link 3109 and the distal link 3111 comprises a prismatic telescoping joint. In the illustrated embodiment, proximal link 3109 comprises a prismatic telescoping joint 3120, whereby an inner member telescopes within an outer member. By providing the telescoping joint 3120, the robotic arm 3000 is advantageously capable of having a greater reach, thereby making it easier to use in different surgical approaches. Furthermore, such a telescoping joint 3120 can make the robotic arm 3000 suitable for use with larger-sized patients.

[0339] The robotic arms described in this section can be configured for use with the adjustable arm supports described in the preceding section. These robotic arms may be particularly advantageous when deployed from a mounting position that is below a surface of a table.

[0340] In general, to avoid collisions with a parallelogram remote center robot (commonly used in laparoscopic procedures), robotic arms are desirably set-up such that when looking from above, a straight line passes from the arm base through the remote center and into the workspace. These three points would reside in a plane that is substantially perpendicular to a table or floor. If the workspace is not aligned as such, the arms must be heavily yawed to one side, causing collisions. Conventional robotic surgical systems employ overhead support structures as described above to provide enough flexibility to allow the robotic arms to access most workspaces. However, arms coming from below and mounted alongside the table, as are arms mounted to the adjustable arm supports, may require a different structure to function as desired.

[0341] For example, in some embodiments, robotic arms configured for use with the adjustable arm supports differ from traditional parallelogram remote center robot. In one example, a robotic arm configured for use with the adjustable arm supports can comprise a shoulder with at least two degrees of freedom, an elbow with at least one degree of freedom, and wrist with at least two degrees of freedom. The kinematics associated with such an arm allow the arm base to be positioned arbitrarily relative to the workspace, allowing for setups that would be challenging for a parallelogram remote center robot mounted alongside a bed.

[0342] Further, in some embodiments, a robotic arm configured for use with the adjustable arm supports may include a wrist configured with at least three degrees of freedom. In some embodiments, the wrist can be semi-spherical or spherical. Such a wrist can allow the robotic arm to roll its wrist joint such that an instrument driver positioned at the distal end of the robotic arm can be below the arm wrist. This can enable procedures where target workspaces are far above ports.

[0343] Other surgical robotic arms include a mechanically constrained remote center with no redundant degrees of freedom. That is, for any remote center position, the distance to the base is mechanically constrained. Robotic Arms coming from below the bed, as is the case with robotic arm mounted on the adjustable arm supports described above, can be limited by their mount structures and cannot reach the optimal configurations to make parallelogram robot arms excel. To address this issue, robotic arms configured for use with the adjustable arm supports described above can include one or more redundant degrees of freedom. The redundant degrees of freedom can allow the arms to be jogged within their null space without moving the tool tip, allowing for intraoperative collision avoidance that is not possible in previously known surgical robotic arms. In addition, when the arms are jogged within their null space, they advantageously can avoid collisions among one another, as well as with a bed, patient, c-arm, etc.

XIV. Instrument-Based Insertion Architectures

[0344] As mentioned briefly above, some instruments that can be used with the robotic arms and instrument drive mechanisms described above can include an instrument-based insertion architecture. An instrument-based insertion architecture can reduce reliance on the robotic arm when linearly inserting an instrument. In particular, the systems, devices and methods described in this section provide examples of instruments having instrument-based linear insertion architectures. The instrument-based insertion architectures described in this section can be implemented with the robotic arms and adjustable arm supports described in the preceding sections.

[0345] FIG. 31 illustrates a perspective view of an instrument device manipulator (IDM) 4300 for a surgical robotic system, and FIG. 32 is a side view of the IDM 4300, according to one embodiment. The IDM 4300 is configured to attach a surgical tool or instrument to a robotic surgical arm in a manner that allows the surgical tool to be continuously rotated or “rolled” about an axis of the surgical tool. The IDM 4300 includes a base 4302 and a surgical tool holder assembly 4304 coupled to the base. The surgical tool holder assembly 4304 serves as a tool holder for holding an instrument 118. The surgical tool holder assembly 4304 further includes an outer housing 4306, a surgical tool holder 4308, an attachment interface 4310, a passage 4312, and a plurality of torque couplers 4314. In some embodiments, the passage 4312 comprises a through bore that extends from one face of the IDM 4300 to an opposing face of the IDM 4300. The IDM 4300 may be used with a variety of surgical tools (not shown in FIG. 31), which may include a handle and an elongated body (e.g., a shaft), and which may be for a laparoscope, an endoscope, or other types of end-effectors of surgical tools or instruments.

[0346] The base 4302 removably or fixedly mounts the IDM 4300 to a surgical robotic arm of a surgical robotic system. In the embodiment of FIG. 31, the base 4302 is fixedly attached to the outer housing 4306 of the surgical tool holder assembly 4304. In alternative embodiments, the base 4302 may be structured to include a platform which is adapted to rotatably receive the surgical tool holder 4308 on the face opposite from the attachment interface 4310. The platform may include a passage aligned with the passage 4312 to receive the elongated body of the surgical tool and, in some embodiments, an additional elongated body of a second surgical tool mounted coaxially with the first surgical tool or instrument.

[0347] The surgical tool holder assembly 4304 is configured to secure a surgical tool to the IDM 4300 and rotate the surgical tool relative to the base 4302. Mechanical and electrical connections are provided from the surgical arm to the base 4302 and then to the surgical tool holder assembly 4304 to rotate the surgical tool holder 4308 relative to the outer housing 4306 and to manipulate and/or deliver power and/or signals from the surgical arm to the surgical tool holder 4308 and ultimately to the surgical tool. Signals may include signals for pneumatic pressure, electrical power, electrical signals, and/or optical signals.

[0348] The outer housing 4306 provides support for the surgical tool holder assembly 4304 with respect to the base 4302. The outer housing 4306 is fixedly attached to the base 4302 such that it remains stationary relative to the base 4302, while allowing the surgical tool holder 4308 to rotate freely relative to the outer housing 4306. In the embodiment of FIG. 31, the outer housing 4306 is cylindrical in shape and fully circumscribes the surgical tool holder 4308. The outer housing 4306 may be composed of rigid materials (e.g., metals or hard plastics). In alternative embodiments, the shape of the housing may vary.

[0349] The surgical tool holder 4308 secures a surgical tool to the IDM 4300 via the attachment interface 4310. The surgical tool holder 4308 is capable of rotating independent of the outer housing 4306. The surgical tool holder 4308 rotates about a rotational axis 4316, which co-axially aligns with the elongated body of a surgical tool such that the surgical tool rotates with the surgical tool holder 4308.

[0350] The attachment interface 4310 is a face of the surgical tool holder 4308 that attaches to the surgical tool. The attachment interface 4310 includes a first portion of an attachment mechanism that reciprocally mates with a second portion of the attachment mechanism located on the surgical

tool, which will be discussed in greater detail with regards to FIGS. 36A and 36B. In some embodiments, the attachment interface **4310** comprises a plurality of torque couplers **4314** that protrude outwards from the attachment interface **4310** and engage with respective instrument inputs on the surgical tool. In some embodiments, a surgical drape, coupled to a sterile adapter, may be used to create a sterile boundary between the IDM **4300** and the surgical tool. In these embodiments, the sterile adapter may be positioned between the attachment interface **4310** and the surgical tool when the surgical tool is secured to the IDM **4300** such that the surgical drape separates the surgical tool and the patient from the IDM **4300** and the surgical robotics system. [0351] The passage **4312** is configured to receive the elongated body of a surgical tool when the surgical tool is secured to the attachment interface **4310**. In the embodiment of FIG. 31, the passage **4312** is co-axially aligned with the longitudinal axis of the elongated body of the surgical tool and the rotational axis **4316** of the surgical tool holder **4308**. The passage **4312** allows the elongated body of the surgical tool to freely rotate within the passage **4312**. This configuration allows the surgical tool to be continuously rotated or rolled about the rotational axis **4316** in either direction with minimal or no restrictions.

[0352] The plurality of torque couplers **4314** are configured to engage and drive the components of the surgical tool when the surgical tool is secured to the surgical tool holder **4308**. Each torque coupler **4314** is inserted into a respective instrument input located on the surgical tool. The plurality of torque couplers **4314** may also serve to maintain rotational alignment between the surgical tool and the surgical tool holder **4308**. As illustrated in FIG. 31, each torque coupler **4314** is shaped as a cylindrical protrusion that protrudes outwards from the attachment interface **4310**. Notches **4318** may be arranged along the outer surface area of the cylindrical protrusion. In some embodiments, the arrangement of the notches **4318** creates a spline interface. The instrument inputs on the surgical tool are configured to have a complementary geometry to the torque couplers **4314**. For example, while not shown in FIG. 31, the instrument inputs of the surgical tool may be cylindrical in shape and have a plurality of ridges that reciprocally mate with the plurality of notches **4318** on each torque coupler **4314** and thus impart a torque on the notches **4318**. In alternate embodiments, the top face of the cylindrical protrusion may include the plurality of notches **4318** configured to mate with a plurality of ridges in respective instrument inputs. In this configuration, each torque coupler **4314** fully engages with its respective instrument input.

[0353] Additionally, each torque coupler **4314** may be coupled to a spring that allows the torque coupler to translate. In the embodiment of FIG. 31, the spring causes each torque coupler **4314** to be biased to spring outwards away from the attachment interface **4310**. The spring is configured to create translation in an axial direction, i.e., protract away from the attachment interface **4310** and retract towards the surgical tool holder **4308**. In some embodiments, each torque coupler **4314** is capable of partially retracting into the surgical tool holder **4308**. In other embodiments, each torque coupler **4314** is capable of fully retracting into the surgical tool holder **4308** such that the effective height of each torque coupler is zero relative to the attachment interface **4310**. In the embodiment of FIG. 31, the translation of each torque coupler **4314** is actuated by an actuation mechanism, which will be described in further detail with regards to FIGS. 35-36. In various embodiments, each torque coupler **4314** may be coupled to a single spring, a plurality of springs, or a respective spring for each torque coupler.

[0354] In addition, each torque coupler **4314** is driven by a respective actuator that causes the torque coupler to rotate in either direction. Thus, once engaged with an instrument input, each torque coupler **4314** is capable of transmitting power to tighten or loosen pull-wires within a surgical tool, thereby manipulating a surgical tool's end-effectors. In the embodiment of FIG. 31, the IDM **4300** includes five torque couplers **4314**, but the number may vary in other embodiments depending on the desired number of degrees of freedom for a surgical tool's end-effectors. In some embodiments, a surgical drape, coupled to a sterile adapter, may be used to create a sterile boundary between the IDM **4300** and the surgical tool. In these embodiments, the sterile adapter

may be positioned between the attachment interface **4310** and the surgical tool when the surgical tool is secured to the IDM **4300**, and the sterile adapter may be configured to transmit power from each torque coupler **4314** to the respective instrument input.

[0355] The embodiment of the IDM **4300** illustrated in FIG. **31** may be used in various configurations with a surgical robotic system. The desired configuration may depend on the type of surgical procedure being performed on a patient or the type of surgical tool being used during the surgical procedure. For example, the desired configuration of the IDM **4300** may be different for an endoscopic procedure than for a laparoscopic procedure.

[0356] In a first configuration, the IDM **4300** may be removably or fixedly attached to a surgical arm such that the attachment interface **4310** is proximal to a patient during the surgical procedure. In this configuration, hereinafter referred to as “front-mount configuration,” the surgical tool is secured to the IDM **4300** on a side proximal to the patient. A surgical tool for use with the front-mount configuration is structured such that the elongated body of the surgical tool extends from a side that is opposite of the attachment interface of the surgical tool. As a surgical tool is removed from the IDM **4300** in a front-mount configuration, the surgical tool will be removed in a proximal direction to the patient.

[0357] In a second configuration, the IDM **4300** may be removably or fixedly attached to a surgical arm such that the attachment interface **4310** is distal to a patient during the surgical procedure. In this configuration, hereinafter referred to as “back-mount configuration,” the surgical tool is secured to the IDM **4300** on a side distal to the patient. A surgical tool for use with the back-mount configuration is structured such that the elongated body of the surgical tool extends from the attachment interface of the surgical tool. This configuration increases patient safety during tool removal from the IDM **4300**. As a surgical tool is removed from the IDM **4300** in a back-mount configuration, the surgical tool will be removed in a distal direction from the patient.

[0358] In a third configuration, the IDM **4300** may be removably or fixedly attached to a surgical arm such that at least a portion of the surgical tool is positioned above the IDM **4300**. In this configuration, hereinafter referred to as a “top” or “through” configuration, a shaft of the surgical tool extends downwardly through the IDM **4300**.

[0359] Certain configurations of a surgical tool may be structured such that the surgical tool can be used with an IDM in either a front-mount configuration or a back-mount configuration. In these configurations, the surgical tool includes an attachment interface on both ends of the surgical tool. For some surgical procedures, the physician may decide the configuration of the IDM depending on the type of surgical procedure being performed. For instance, the back-mount configuration may be beneficial for laparoscopic procedures wherein laparoscopic tools may be especially long relative to other surgical tools. As a surgical arm moves about during a surgical procedure, such as when a physician directs a distal end of the surgical tool to a remote location of a patient (e.g., a lung or blood vessel), the increased length of laparoscopic tools causes the surgical arm to swing about a larger arc. Beneficially, the back-mount configuration decreases the effective tool length of the surgical tool by receiving a portion of the elongated body through the passage **4312** and thereby decreases the arc of motion required by the surgical arm to position the surgical tool.

[0360] FIGS. **33-34** illustrate perspective exploded views of an example surgical tool **4500** secured to the instrument device manipulator **4300** of FIG. **31**, according to one embodiment. The surgical tool **4500** includes a housing **4502**, an elongated body **4504**, and a plurality of instrument inputs **4600**. As previously described, the elongated body **4504** may be a laparoscope, an endoscope, or other surgical tool having end-effectors. As illustrated, the plurality of torque couplers **4314** protrude outwards from the attachment interface **4310** to engage with the instrument inputs **4600** of the surgical tool. The structure of the instrument inputs **4600** can be seen in FIG. **34**, wherein the instrument inputs **4600** have corresponding geometry to the torque couplers **4314** to ensure secure surgical tool engagement.

[0361] During a surgical procedure, a surgical drape may be used to maintain a sterile boundary

between the IDM **4300** and an outside environment (i.e., an operating room). In the embodiments of FIGS. **33-34**, the surgical drape comprises a sterile adapter **4506**, a first protrusion **4508**, and a second protrusion **4510**. While not shown in FIGS. **33-34**, a sterile sheet is connected to the sterile adapter and the second protrusion and drapes around the IDM **4300** to create the sterile boundary. [0362] The sterile adapter **4506** is configured to create a sterile interface between the IDM **4300** and the surgical tool **4500** when secured to the IDM **4300**. In the embodiment of FIGS. **33-34**, the sterile adapter **4506** has a disk-like geometry that covers the attachment interface **4310** of the IDM **4300**. The sterile adapter **4506** comprises a central hole **4508** that is configured to receive the elongated body **4504** of the surgical tool **4500**. In this configuration, the sterile adapter **4506** is positioned between the attachment interface **4310** and the surgical tool **4500** when the surgical tool **4500** is secured to the IDM **4300**, creating the sterile boundary between the surgical tool **4500** and the IDM **4300** and allowing the elongated body **4504** to pass through the passage **4312**. In certain embodiments, the sterile adapter **4506** may be capable of rotating with the surgical tool holder **4308**, transmitting the rotational torque from the plurality of torque couplers **4314** to the surgical tool **4500**, passing electrical signals between the IDM **4300** and the surgical tool **4500**, or some combination thereof.

[0363] In the embodiment of FIGS. **33-34**, the sterile adapter **4506** further comprises a plurality of couplers **4512**. A first side of a coupler **4512** is configured to engage with a respective torque coupler **4314** while a second side of a coupler **4512** is configured to engage with a respective instrument input **4600**.

[0364] Similar to the structure of the plurality of torque couplers **4314**, each coupler **4512** is structured as a cylindrical protrusion including a plurality of notches. Each side of the coupler **4512** has complementary geometry to fully engage with the respective torque coupler **4314** and the respective instrument input **4600**. In some embodiments, the one or more instrument inputs **4600** are referred to as mechanical inputs. Each coupler **4512** is configured to rotate in a clockwise or counter-clockwise direction with the respective torque coupler **4314**. This configuration allows each coupler **4512** to transfer rotational torque from the plurality of torque couplers **4314** of the IDM **4300** to the plurality of instrument inputs **4600** of the surgical tool **4500**, and thus control the end-effectors of the surgical tool **4500**.

[0365] The first protrusion **4508** and the second protrusion **4510** are configured to pass through the passage **4312** of the IDM **4300** and mate with each other inside the passage **4312**. Each protrusion **4508**, **4510** is structured to allow the elongated body **4504** to pass through the protrusion and thus the passage **4312**. The connection of the first protrusion **4508** and the second protrusion **4510** creates the sterile boundary between the IDM **4300** and the outside environment (i.e., an operating room).

[0366] FIG. **35** illustrates a zoomed-in, perspective view of an actuation mechanism for engagement and disengagement of a surgical tool **4500** from a sterile adapter **4506** of a surgical drape, according to one embodiment. Due to the configuration of the IDM **4300** as described with regards to FIG. **31**, the axis of surgical tool insertion into the patient during a surgical procedure is the same as the axis of surgical tool removal. To ensure patient safety during surgical tool removal, the surgical tool **4500** can be de-articulated from the sterile adapter **4506** and the ID M **4300** before removing the surgical tool **4500**. In the embodiment of FIG. **35**, the plurality of couplers **4512** are configured to translate in an axial direction, i.e., protract away from and retract towards the sterile adapter **4506**. The translation of the plurality of couplers **4512** is actuated by the actuation mechanism which ensures de-articulation of the surgical tool **4500** by disengaging the plurality of couplers **4512** from the respective instrument inputs **4600**. The actuation mechanism includes a wedge **4702** and a pusher plate **4704**.

[0367] The wedge **4702** is a structural component that activates the pusher plate **4704** during the process of surgical tool disengagement. In the embodiment of FIG. **35**, the wedge **4702** is located within the housing **4502** of the surgical tool **4500** along the outer perimeter of the housing **4502**. As

illustrated, the wedge **4702** is oriented such that contact with the pusher plate **4704** causes the pusher plate **4704** to depress into the sterile adapter **4506** if the housing **4502** of the surgical tool **4500** is rotated clockwise relative to the sterile adapter **4506**. In alternate embodiments, the wedge **4702** may be configured such that the housing **4502** of the surgical tool **4500** is rotated counter-clockwise rather than clockwise. Geometries other than a wedge may be employed, such as an arch-shaped ramp, given that the structure is able to depress the pusher plate when rotating. [0368] The pusher plate **4704** is an actuator that disengages the plurality of couplers **4512** from the surgical tool **4500**. Similar to the plurality of torque couplers **4314**, each of the couplers **4512** may be coupled to one or more springs that bias each coupler **4512** to spring outwards away from the sterile adapter **4506**. The plurality of couplers **4512** are further configured to translate in an axial direction, i.e., protract away from and retract into the sterile adapter **4506**. The pusher plate **4704** actuates the translational movement of the couplers **4512**. As the pusher plate **4704** is depressed by the wedge **4702**, the pusher plate **4704** causes the spring or plurality of springs coupled to each coupler **4512** to compress, resulting in the couplers **4512** retracting into the sterile adapter **4506**. In the embodiment of FIG. 35, the pusher plate **4704** is configured to cause simultaneous retraction of the plurality of couplers **4512**. Alternate embodiments may retract the couplers **4512** in a specific sequence or a random order. In the embodiment of FIG. 35, the pusher plate **4704** causes the plurality of couplers **4512** to partially retract into the sterile adapter **4506**. This configuration allows a surgical tool **4500** to be de-articulated from the sterile adapter **4506** before the surgical tool **4500** is removed. This configuration also allows a user to de-articulate the surgical tool **4500** from the sterile adapter **4506** at any desired time without removing the surgical tool **4500**. Alternate embodiments may fully retract the plurality of couplers **4512** into the sterile adapter **4506** such that the effective height of each coupler **4512** measured is zero. In some embodiments, the pusher plate **4704** may cause the plurality of torque couplers **4314** to retract synchronously with the plurality of respective couplers **4512**.

[0369] FIGS. 36A and 36B illustrate a process of engaging and disengaging a surgical tool from a sterile adapter, according to one embodiment. FIG. 36A illustrates a sterile adapter **4506** and a surgical tool **4500** in a secured position, such that the two components are secured together and the plurality of couplers **4512** are fully engaged with respective instrument inputs **4600** of the surgical tool **4500**. To achieve the secured position as illustrated in FIG. 36A, the elongated body **4504** (not shown) of the surgical tool **4500** is passed through the central hole **4508** (not shown) of the sterile adapter **4506** until mating surfaces of the surgical tool **4500** and the sterile adapter **4506** are in contact, and the surgical tool **4500** and the sterile adapter **4506** are secured to each other by a latching mechanism. In the embodiments of FIGS. 36A and 36B, the latching mechanism comprises a ledge **4802** and a latch **4804**.

[0370] The ledge **4802** is a structural component that secures the latch **4804** in the secured position. In the embodiment of FIG. 36A, the ledge **4802** is located within the housing **4502** of the surgical tool **4500** along the outer perimeter of the housing **4502**. As illustrated in FIG. 36A, the ledge **4802** is oriented such that it rests below a protrusion on the latch **4804**, preventing the latch **4804** and thereby the sterile adapter **4506** from pulling away from the surgical tool **4500** due to the sprung-up nature of the plurality of couplers **4512**, as described with regards to FIG. 35.

[0371] The latch **4804** is a structural component that mates with the ledge **4802** in the secured position. In the embodiment of FIG. 36A, the latch **4804** protrudes from the mating surface of the sterile adapter **4506**. The latch **4804** comprises a protrusion that is configured to rest against the ledge **4802** when the surgical tool **4500** is secured to sterile adapter **4506**. In the embodiment of FIG. 36A, the housing **4502** of the surgical tool **4500** is capable of rotating independent of the rest of the surgical tool **4500**. This configuration allows the housing **4502** to rotate relative to the sterile adapter **4506** such that the ledge **4802** is secured against the latch **4804**, thereby securing the surgical tool **4500** to the sterile adapter **4502**. In the embodiment of FIG. 36A, the housing **4502** is rotated counter-clockwise to achieve the secured position, but other embodiments may be

configured for clockwise rotation. In alternate embodiments, the ledge **4802** and the latch **4804** may have various geometries that lock the sterile adapter **4506** and the surgical tool **4500** in the secured position.

[0372] FIG. **36B** illustrates the sterile adapter **4506** and the surgical tool **4500** in an unsecured position, in which the surgical tool **4500** may be removed from the sterile adapter **4506**. As previously described, the housing **4502** of the surgical tool **4500** is capable of rotating independent of the rest of the surgical tool **4500**. This configuration allows the housing **4502** to rotate even while the plurality of couplers **4512** are engaged with the instrument inputs **4600** of the surgical tool **4500**. To transition from the secured position to the unsecured position, a user rotates the housing **4502** of the surgical tool **4500** clockwise relative to the sterile adapter **4506**. During this rotation, the wedge **4702** contacts the pusher plate **4704** and progressively depresses the pusher plate **4704** as it slides against the angled plane of the wedge **4702**, thereby causing the plurality of couplers **4512** to retract into the sterile adapter **4506** and disengage from the plurality of instrument inputs **4600**. Further rotation causes the latch **4804** to contact an axial cam **4806**, which is structured similar to wedge **4702**. As the latch **4804** contacts the axial cam **4806** during rotation, the axial cam **4806** causes the latch **4804** to flex outwards away from the surgical tool **4500** such that the latch **4804** is displaced from the ledge **4802**. In this unsecured position, the plurality of couplers **4512** are retracted, and the surgical tool **4500** can be removed from the sterile adapter **4506**, in the embodiment of FIG. **36B**. In other embodiments, the axial cam **4806** may have various geometries such that rotation causes the latch **4804** to flex outwards.

[0373] In alternate embodiments, the direction of rotation of the housing **4502** of the surgical tool **4500** may be configured as counter-clockwise rotation to unsecure the latch **4804** from the ledge **4802**. Additionally, alternate embodiments may include similar components but the location of the components may be switched between the sterile adapter **4506** and the surgical tool **4500**. For example, the ledge **4802** may be located on the sterile adapter **4506** while the latch **4804** may be located on the surgical tool **4500**. In other embodiments, an outer portion of the sterile adapter **4506** may be rotatable relative to the plurality of couplers **4512** rather than the housing **4502** of the surgical tool **4500**. Alternate embodiments may also include a feature to lock the rotation of the housing **4502** of the surgical tool **4500** when the housing **4502** is fully rotated relative to the instrument inputs **4600**. This configuration prevents rotation of the surgical tool if the instrument inputs **4600** have been de-articulated from the couplers **4512**. In some embodiments, the retraction and protraction of the couplers **4512** may be coupled with a respective retraction and protraction of the torque couplers **4314**, such that a coupler **4512** engaged with a torque coupler **4314** will translate together.

[0374] FIGS. **37A** and **37B** illustrate a process of surgical tool engagement and disengagement of a surgical tool from a sterile adapter, according to another embodiment. In the embodiment of FIGS. **37A** and **37B**, a sterile adapter **4900** may include an outer band **4902** that secures the surgical tool **4904** to the sterile adapter **4900**. As illustrated in FIGS. **37A** and **37B**, the surgical tool **4904** comprises a ramp **4906** on the outer surface of the housing **4908**. The ramp **4906** includes a notch **4910** that is configured to receive a circular protrusion **4912**, which is positioned on an inner surface of the outer band **4902** of the sterile adapter **4900**. The outer band **4902** is capable of rotating independent of and relative to the sterile adapter **4900** and the surgical tool **4904**. As the outer band **4902** rotates in a first direction, the circular protrusion **4912** glides up the surface of the ramp **4906** until the circular protrusion **4912** is nested within the notch **4910**, thereby securing the sterile adapter **4900** and the surgical tool **4904** together. Rotation of the outer band **4902** in a second direction causes the sterile adapter **4900** and the surgical tool **4904** to unsecure from each other. In certain embodiments, this mechanism may be coupled with a de-articulation of the plurality of couplers **4914** on the sterile adapter **4900**, as described with regards to FIGS. **35-36**.

[0375] Alternative embodiments of surgical tool disengagement may include additional features, such as an impedance mode. With an impedance mode, the surgical robotics system may control

whether the surgical tool can be removed from the sterile adapter by a user. The user may initiate the disengagement mechanism by rotating the outer housing of the surgical tool and unsecuring the surgical tool from the sterile adapter, but the surgical robotics system may not release the couplers from the instrument inputs. Only once the surgical robotics system has transitioned into the impedance mode are the couplers released and the user can remove the surgical tool. An advantage of keeping the surgical tool engaged is that the surgical robotics system can control the end-effectors of the surgical tool and position them for tool removal before the surgical tool is removed to minimize damage to the surgical tool. To activate an impedance mode, the pusher plate **4704** may have a hard-stop such that the pusher plate can be depressed up to a certain distance. In some embodiments, the hard-stop of the pusher plate may be adjustable such that the hard-stop coincides with the maximum amount of rotation of the housing of the surgical tool. Thus, once the full rotation is reached, the hard-stop is also met by the pusher plate. A plurality of sensors may detect these events and trigger the impedance mode.

[0376] Certain situations may require emergency tool removal during a surgical procedure in which the impedance mode may not be desirable. In some embodiments, the hard-stop of the pusher plate may have compliance, such that the hard-stop may yield in an emergency. The hard-stop of the pusher plate may be coupled to a spring, allowing the hard-stop to yield in response to additional force. In other embodiments, the hard-stop of the pusher plate may be rigid such that emergency tool removal occurs by removing the latch that secures the surgical tool to the sterile adapter.

[0377] FIG. **38A** illustrates a perspective view of a mechanism for rolling a surgical tool holder **4308** within an instrument device manipulator **4300**, according to one embodiment. As illustrated in FIG. **38A**, the attachment interface **4310** is removed to expose the roll mechanism. This mechanism allows the surgical tool holder **4308** to continuously rotate or “roll” about the rotational axis **4316** in either direction. The roll mechanism comprises a stator gear **5002** and a rotor gear **5004**.

[0378] The stator gear **5002** is a stationary gear configured to mate with the rotor gear **5004**. In the embodiment of FIG. **38A**, the stator gear **5002** is a ring-shaped gear comprising gear teeth along the inner circumference of the ring. The stator gear **5002** is fixedly attached to the outer housing **4306** behind the attachment interface **4310**. The stator gear **5002** has the same pitch as the rotor gear **5004**, such that the gear teeth of the stator gear **5002** are configured to mate with the gear teeth of the rotor gear **5004**. The stator gear **5002** may be composed of rigid materials (e.g., metals or hard plastics).

[0379] The rotor gear **5004** is a rotating gear configured to induce rotation of the surgical tool holder **4308**. As illustrated in FIG. **38A**, the rotor gear **5004** is a circular gear comprising gear teeth along its outer circumference. The rotor gear **5004** is positioned behind the attachment interface **4310** and within the inner circumference of the stator gear **5002** such that the gear teeth of the rotor gear **5004** mate with the gear teeth of the stator gear. As previously described, the rotor gear **5004** and the stator gear **5002** have the same pitch. In the embodiment of FIG. **38A**, the rotor gear **5004** is coupled to a drive mechanism (e.g., a motor) that causes the rotor gear **5004** to rotate in a clockwise or counter-clockwise direction. The drive mechanism may receive signals from an integrated controller within the surgical tool holder assembly **4304**. As the drive mechanism causes the rotor gear **5004** to rotate, the rotor gear **5004** travels along the gear teeth of the stator gear **5002**, thereby causing the surgical tool holder **4308** to rotate. In this configuration, the rotor gear **5004** is capable of continuously rotating in either direction and thus allows the surgical tool holder **4308** to achieve infinite roll about the rotational axis **4316**. Alternate embodiments may use similar mechanisms to allow for infinite roll, such as a configuration of a ring gear and a pinion gear.

[0380] FIG. **38B** illustrates a cross-sectional view of an instrument device manipulator **4300**, according to one embodiment. As illustrated in FIG. **38B**, the roll mechanism is coupled with a plurality of bearing **5006**. A bearing is a mechanical component that reduces friction between moving parts and facilitates rotation around a fixed axis. One bearing alone can support the radial

or torsional loading as the surgical tool holder **4308** rotates within the outer housing **4306**. In the embodiment of FIG. **38B**, the IDM **4300** includes two bearings **5006a**, **5006b** fixedly attached to the surgical tool holder **4308** such that a plurality of components (such as balls or cylinders) within the bearings **5006** contacts the outer housing **4306**. A first bearing **5006a** is secured at a first end behind the attachment interface **4310** and a second bearing **5006b** is secured at a second end. This configuration improves rigidity and support between the first end and the second end of the surgical tool holder **4308** as the surgical tool holder **4308** rotates within the outer housing **4306**. Alternate embodiments may include additional bearings that provide additional support along the length of the surgical tool holder.

[0381] FIG. **38B** also illustrates sealing components within the IDM **4300**, according to one embodiment. The IDM **4300** comprises a plurality of O-rings **5008** and a plurality of gaskets **5010** which are configured to seal a junction between two surfaces to prevent fluids from entering the junction. In the embodiment of FIG. **38B**, the IDM includes O-rings **5008a**, **5008b**, **5008c**, **5008d**, **5008e** between junctions of the outer housing and gaskets **5010a**, **5010b** between junctions within the surgical tool holder **4308**. This configuration helps to maintain sterility of the components within the IDM **4300** during a surgical procedure. Gaskets and O-rings are typically composed of strong elastomeric materials (e.g., rubber).

[0382] FIG. **38C** illustrates a partially exploded, perspective view of the internal components of an instrument device manipulator and certain electrical components thereof, according to one embodiment. The internal components of the surgical tool holder **4308** include a plurality of actuators **5102**, a motor, a gearhead (not shown), a torque sensor (not shown), a torque sensor amplifier **5110**, a slip ring **5112**, a plurality of encoder boards **5114**, a plurality of motor power boards **5116**, and an integrated controller **5118**.

[0383] The plurality of actuators **5102** drive the rotation of each of the plurality of torque couplers **4314**. In the embodiment of FIG. **38C**, an actuator, such as **5102a** or **5102b**, is coupled to a torque coupler **4314** via a motor shaft. The motor shaft may be a keyed shaft such that it includes a plurality of grooves to allow the motor shaft to securely mate to a torque coupler **4314**. The actuator **5102** causes the motor shaft to rotate in a clockwise or counter-clockwise direction, thereby causing the respective torque coupler **4314** to rotate in that direction. In some embodiments, the motor shaft may be torsionally rigid but spring compliant, allowing the motor shaft and thus the torque coupler **4314** to rotate and to translate in an axial direction. This configuration may allow the plurality of torque couplers **4314** to retract and protract within the surgical tool holder **4308**. Each actuator **5102** may receive electrical signals from the integrated controller **5118** indicating the direction and amount to rotate the motor shaft. In the embodiment of FIG. **38C**, the surgical tool holder **4308** includes five torque couplers **4314** and thus five actuators **5102**.

[0384] The motor drives the rotation of the surgical tool holder **4308** within the outer housing **4306**. The motor may be structurally equivalent to one of the actuators, except that it is coupled to the rotor gear **5004** and stator gear **5002** (see FIG. **38A**) for rotating the surgical tool holder **4308** relative to the outer housing **4306**. The motor causes the rotor gear **5004** to rotate in a clockwise or counter-clockwise direction, thereby causing the rotor gear **5004** to travel about the gear teeth of the stator gear **5002**. This configuration allows the surgical tool holder **4308** to continuously roll or rotate without being hindered by potential wind-up of cables or pull-wires. The motor may receive electrical signals from the integrated controller **5118** indicating the direction and amount to rotate the motor shaft.

[0385] The gearhead controls the amount of torque delivered to the surgical tool **4500**. For example, the gearhead may increase the amount of torque delivered to the instrument inputs **4600** of the surgical tool **4500**. Alternate embodiments may be configured such that the gearhead decreases the amount of torque delivered to the instrument inputs **4600**.

[0386] The torque sensor measures the amount of torque produced on the rotating surgical tool

holder **4308**. In the embodiment shown in FIG. **38C**, the torque sensor is capable of measuring torque in the clockwise and the counter-clockwise direction. The torque measurements may be used to maintain a specific amount of tension in a plurality of pull-wires of a surgical tool. For instance, some embodiments of the surgical robotics system may have an auto-tensioning feature, wherein, upon powering on the surgical robotics system or engaging a surgical tool with an ID M, the tension on the pull-wires of the surgical tool will be pre-loaded. The amount of tension on each pull-wire may reach a threshold amount such that the pull-wires are tensioned just enough to be taut. The torque sensor amplifier **5110** comprises circuitry for amplifying the signal that measures the amount of torque produced on the rotating surgical tool holder **4308**. In some embodiments, the torque sensor is mounted to the motor.

[0387] The slip ring **5112** enables the transfer of electrical power and signals from a stationary structure to a rotating structure. In the embodiment of FIG. **38C**, the slip ring **5112** is structured as a ring including a central hole that is configured to align with the passage **4312** of the surgical tool holder **4308**, as is also shown in an additional perspective view of the slip ring **5112** in FIG. **38D**. A first side of the slip ring **5112** includes a plurality of concentric grooves **5120** while a second side of the slip ring **5112** includes a plurality of electrical components for the electrical connections provided from the surgical arm and the base **4302**, as described with regards to FIG. **31**. The slip ring **5112** is secured to the outer housing **4306** of the surgical tool holder **4308** at a specific distance from the outer housing **4306** to allocate space for these electrical connections. The plurality of concentric grooves **5120** are configured to mate with a plurality of brushes **5122** attached to the integrated controller. The contact between the grooves **5120** and the brushes **5122** enables the transfer of electrical power and signals from the surgical arm and base to the surgical tool holder.

[0388] The plurality of encoder boards **5114** read and process the signals received through the slip ring from the surgical robotic system. Signals received from the surgical robotic system may include signals indicating the amount and direction of rotation of the surgical tool, signals indicating the amount and direction of rotation of the surgical tool's end-effectors and/or wrist, signals operating a light source on the surgical tool, signals operating a video or imaging device on the surgical tool, and other signals operating various functionalities of the surgical tool. The configuration of the encoder boards **5114** allows the entire signal processing to be performed completely in the surgical tool holder **4308**. The plurality of motor power boards **5116** each comprises circuitry for providing power to the motors.

[0389] The integrated controller **5118** is the computing device within the surgical tool holder **4308**. In the embodiment of FIG. **38C**, the integrated controller **5118** is structured as a ring including a central hole that is configured to align with the passage **4312** of the surgical tool holder **4308**. The integrated controller **5118** includes a plurality of brushes **5122** on a first side of the integrated controller **5118**. The brushes **5122** contact the slip ring **5112** and receive signals that are delivered from the surgical robotics system through the surgical arm, the base **4302**, and finally through the slip ring **5112** to the integrated controller **5118**. As a result of the received signals, the integrated controller **5118** is configured to send various signals to respective components within the surgical tool holder **4308**. In some embodiments, the functions of the encoder boards **5114** and the integrated controller **5118** may be distributed in a different manner than is described here, such that the encoder boards **5114** and the integrated controller **5118** may perform the same functions or some combination thereof.

[0390] FIG. **38D** illustrates a partially exploded, perspective view of the internal components of an instrument device manipulator and certain electrical components thereof, according to one embodiment. The embodiment of FIG. **38D** includes two encoder boards **5114a** and **5114b**, a torque sensor amplifier **5110**, and three motor power boards **5116a**, **5116b**, and **5116c**. These components are secured to the integrated controller **5118** and protrude outwards, extending perpendicularly from the integrated controller **5118**. This configuration provides room for the plurality of actuators **5102** and motor to be positioned within the electrical boards.

[0391] As discussed with regards to FIG. 38C, the slip ring 5112 is secured at a specific distance from the outer housing 4306. To ensure correct space allocation between the slip ring 5112 and the outer housing 4306 for the electrical connections from the surgical arm and base 4302 to the slip ring 5112, in the embodiment of FIG. 38D, the slip ring 5112 is supported by a plurality of alignment pins, a plurality of coil springs, and a shim. The slip ring 5112 includes a hole 5124 on each side of the center hole of the slip ring 5112 that is configured to accept a first side of an alignment pin while a second side of the alignment pin is inserted into a respective hole in the outer housing 4306. The alignment pins may be composed of rigid materials (e.g., metal or hard plastics). The plurality of coil springs is secured around the center of the slip ring 5112 and configured to bridge the space and maintain contact between the slip ring 5112 and the outer housing 4306. The coil springs may beneficially absorb any impact to the IDM 4300. The shim is ring-shaped spacer that is positioned around the center hole of the slip ring 5112 to add further support between the slip ring 5112 and the outer housing 4306. In addition, these components provide stability to the slip ring 5112 as the plurality of brushes 5122 on the integrated controller 5118 contact and rotate against the plurality of concentric grooves 5120. In alternate embodiments, the number of alignment pins, coil springs, and shims may vary until the desired support between the slip ring 5112 and the outer housing 4306 is achieved.

[0392] FIG. 38E illustrates a zoomed-in, perspective view of electrical components of an instrument device manipulator 4300 for roll indexing the surgical tool holder 4308, according to one embodiment. Roll indexing monitors the position of the surgical tool holder 4308 relative to the outer housing 4306 such that the position and orientation of the surgical tool 4500 is continuously known by the surgical robotics system. The embodiment of FIG. 38E includes a micro switch 5202 and a boss 5204. The micro switch 5202 and the boss 5204 are secured within the surgical tool holder 4308. The boss 5204 is a structure on the outer housing 4306 that is configured to contact the micro switch 5202 as the surgical tool holder 4308 rotates, thus activating the micro switch each time there is contact with the boss 5204. In the embodiment of FIG. 38E, there is one boss 5204 that serves as a single reference point for the micro switch 5202.

[0393] Various tools or instruments can attach to the IDM 4300, including instruments used for laparoscopic, endoscopic and endoluminal surgery. The instruments described herein are particularly novel, as they include instrument based insertion architectures that reduce the reliance on robotic arms for insertion. In other words, insertion of an instrument (e.g., towards a surgical site) can be facilitated by the design and architecture of the instrument. For example, in some embodiments, wherein an instrument comprises an elongated shaft and a handle, the architecture of the instrument enables the elongated shaft to translate relative to the handle along an axis of insertion.

[0394] The instruments described herein incorporate instrument based insertion architectures that alleviate many issues. Instruments that do not incorporate an instrument based insertion architecture rely on a robotic arm and its IDM for insertion. In this arrangement, to achieve instrument insertion, the IDM may need to be moved in and out, therefore requiring additional motor power and arm link size for moving the additional mass in a controlled manner. In addition, the larger volume creates a much larger swept volume that can result in collisions during operation. By incorporating instrument based insertion architectures, the instruments described herein typically have a reduced swung mass, as the instrument itself (e.g., its shaft) moves along an insertion axis with less reliance on the robotic arm.

[0395] Some embodiments of the instruments described herein may have novel instrument based insertion architectures that not only allow for insertion of the instrument, but also allow an end effector of the instrument to actuate without interference. For example, in some embodiments, an instrument comprises a first actuation mechanism for actuating an end effector and a second actuation mechanism for causing translation of a portion of the instrument (e.g., a shaft) along an axis of insertion. The first actuation mechanism is advantageously decoupled from the second

actuation mechanism such that the actuation of the end effector is not affected by the insertion of the instrument, and vice versa.

[0396] FIG. 39 illustrates a side view of an instrument having an instrument based insertion architecture, according to one embodiment. The design and architecture of the instrument 5200 enables the instrument (e.g., its shaft) to translate along an insertion axis with less reliance on movement of a robotic arm for insertion.

[0397] The instrument 5200 comprises an elongated shaft 5202, an end effector 5212 connected to the shaft 5202, and a handle 5220 coupled to the shaft 5202. The elongated shaft 5202 comprises a tubular member having a proximal portion 5204 and a distal portion 5206. The elongated shaft 5202 comprises one or more channels or grooves 5208 along its outer surface. The grooves 5208, which are most visible in the cross-sectional view of the shaft 5202, are configured to receive one or more wires or cables 5230 therethrough. One or more cables 5230 thus run along an outer surface of the elongated shaft 5202. In other embodiments, cables 5230 can also run through the shaft 5202, as shown in the schematic drawing in FIG. 49. In some embodiments, cables 5230 that run through the shaft 5202 are not exposed. In some embodiments, manipulation of the one or more of these cables 5230 (e.g., via the IDM 4300) results in actuation of the end effector 5212.

[0398] The end effector 5212 comprises one or more laparoscopic, endoscopic or endoluminal components designed to provide an effect to a surgical site. For example, the end effector 5212 can comprise a wrist, grasper, tines, forceps, scissors, or clamp. In the present embodiment shown in FIG. 39, one or more of the cables 5230 that extend along the grooves 5208 on the outer surface of the shaft 5202 actuate the end effector 5212. The one or more cables 5230 extend from a proximal portion 5204 of the shaft 5202, through the handle 5220 and toward a distal portion 5206 of the shaft 5202, where they actuate the end effector 5212.

[0399] The instrument handle 5220, which may also be referred to as an instrument base, may generally comprise an attachment interface 5222 having one or more mechanical inputs 5224, e.g., receptacles, pulleys or spools, that are designed to be reciprocally mated with one or more torque couplers 4314 on an attachment interface 4310 of the IDM 4300 (shown in FIG. 31). The attachment interface 5222 is capable of attaching to an IDM 4300 via front-mount, back-mount and/or top mount. When physically connected, latched, and/or coupled, the mated mechanical inputs 5224 of the instrument handle 5220 may share axes of rotation with the torque couplers 4314 of the IDM 4300, thereby allowing the transfer of torque from the IDM 4300 to the instrument handle 5220. In some embodiments, the torque couplers 4314 may comprise splines that are designed to mate with receptacles on the mechanical inputs. Cables 5230 that actuate the end effector 5212 engage the receptacles, pulleys or spools of the handle 5220, such that the transfer of torque from the IDM 4300 to the instrument handle 5220 results in actuation of the end effector.

[0400] Some embodiments of the instrument 5200 comprise a first actuation mechanism that controls actuation of the end effector 5212. An embodiment of such a first actuation mechanism is schematically illustrated in FIG. 40. In addition, the instrument 5200 includes a second actuation mechanism that enables the shaft 5202 to translate relative to the handle 5220 along an axis of insertion. An embodiment of such a second actuation mechanism is shown in FIG. 45.

Advantageously, the first actuation mechanism is decoupled from the second actuation mechanism, such that actuation of the end effector 5212 is not affected by the translation of the shaft 5202, and vice versa. Embodiments of the first and second actuation mechanisms that can be incorporated into a tool or instrument 5200 are described in more detail below with respect to FIGS. 40-48.

[0401] FIG. 40 illustrates a schematic diagram showing a first actuation mechanism for actuating an end effector, according to one embodiment. In some embodiments, the first actuation mechanism provides N+1 wrist motion, wherein N is the number of degrees of freedom provided by N+1 cables. The first actuation mechanism for actuating the end effector 5212 comprises at least one cable or cable segment 5230a that extends through at least one set of pulleys 5250. In the present embodiment, a first cable or cable segment 5230a extends through pulley members 5250a,

5250b, 5250c, while a second cable or cable segment 5230a extends through pulley members 5250d, 5250e, 5250f. The at least one cable 5230a is grounded at or near the proximal end 5205 of the shaft 5202, then extends through the at least one set of pulleys 5250 (which are located within the handle 5220), before terminating at the end effector 5212. Cable total path length is kept constant by grounding each cable 5230a at or near the proximal end 5205 of the shaft 5202, and relative length changes are made by moving pulleys (e.g., pulley members 5250b and 5250e) relative to each other (see arrows), thereby enabling actuation of the end effector 5212. In some embodiments, the pulleys can be moved via linear or rotary motion of corresponding mechanical inputs 5224. This first actuation mechanism advantageously permits free movement of the instrument shaft 5202 relative to the actuation pulleys 5250 (which will be accomplished by a second actuation mechanism described below), thereby allowing an additional cable to be included to permit insertion and retraction of the instrument shaft 5202 at the same time as end effector 5212 actuation.

[0402] FIG. 41 illustrates a zoomed-in side view of a first actuation mechanism of the instrument of FIG. 39, according to one embodiment. The first actuation mechanism corresponds with the schematic diagram shown in FIG. 40 and is designed to cause actuation of the end effector 5212, while permitting a separate second actuation mechanism to translate the shaft 5202 relative to the handle 5220. As shown in FIG. 41, the handle 5220 includes a set of bearings, spools, pulleys or pulley members 5250a, 5250b, 5250c, 5250d, 5250e (wherein pulleys 5250a, 5250b, 5250c correspond to the same set of pulleys in FIG. 40). A cable 5230a extends through the pulleys 5250a, 5250d, 5250b, 5250e, 5250c. Manipulation of a mechanical input (identified as 5224' in FIG. 41) causes rotary motion of the pulleys 5250d, 5250b, 5250e. The rotary motion of the pulleys 5250d, 5250b, 5250e changes the amount of cable 5230 that is received in the handle 5220, thereby actuating the end effector. The effect of the rotary motion of the pulleys on the cable 5230a is shown in FIGS. 43 and 44. Depending on the direction of the rotary motion, the pulleys 5250d, 5250e can either wound or “take up” cable 5230 in the handle 5220, or can unwound and “give out” cable 5230a in the handle 5220. Either way, the length of the cable 5230a changes within the handle 5220, thereby causing actuation of the end effector 5212. While the embodiment in FIG. 41 depicts a pulley system that is modified by rotary motion, in other embodiments, the pulley system can be modified by linear and/or rotary motion. In addition, one skilled in the art will appreciate that a change in length in the amount of cable 5230a in the handle 5220 can also change cable tension.

[0403] FIG. 42 illustrates a zoomed-in perspective view of a first actuation mechanism of the instrument of FIG. 39, according to one embodiment. From this view, one can see different details of the pulleys 5250a-e including the spools of the pulleys 5250a, 5250c.

[0404] FIGS. 43 and 44 illustrate a front view of a pulley member 5250e and cable of the instrument of FIG. 39, before and after actuation of the pulley member, according to one embodiment. Applying torque on the mechanical input 5224' rotates pulleys 5250e, 5250b and 5250d. As shown in FIG. 43, before actuation of the pulley 5250e, cable 5230a can run along one side of the pulley 5250e. As shown in FIG. 44, after actuation of the pulley 5250e, the cable 5230a is then wound and taken up by the pulley, thereby increasing the amount of cable 5230a within the handle 5220 to cause actuation of an end effector.

[0405] While embodiments in FIGS. 39-44 disclose one or more pulleys mounted on a rotary axis to change relative cable length, in other embodiments, mounting a pulley on a lever, gear or track based system to adjust location are additional options. In addition, ball spline rotary shafts that travel down a length of a tool could also be used to transmit forces in a mechanically remote way.

[0406] FIG. 45 illustrates a side view of a second actuation mechanism including a spool for shaft translation, according to one embodiment. The second actuation mechanism is designed to translate the shaft 5202 relative to the handle 5220 along an axis of insertion. Like the first actuation mechanism that actuates the end effector 5212, the second actuation mechanism can also be

incorporated within the handle **5220**.

[0407] The second actuation mechanism comprises a cable or cable segment **5230b** that engages a set of spools **5270a**, **5270b**, **5270c**, **5270d**. One end of the cable **5230b** can be attached at or near a proximal end **5205** of the shaft **5202**, while the other end of the cable **5230b** can be attached at or near a distal end **5207** of the shaft **5202**. The cable **5230b** extends through the set of spools **5270a**, **5270b**, **5270c**, of which spool **5270b** is a capstan. Rotating a mechanical input of the handle **5220** causes rotation of the capstan, thereby driving cable **5230b** in and out of the capstan. As cable **5230b** is driven in and out of the capstan, this causes the shaft **5202** to translate relative to the handle **5220**. Advantageously, by applying adequate pre-tension to the cable **5230b** that is attached at both the proximal and distal end of the shaft **5202**, frictional force can be used to drive the cable **5230b** in and out, thereby moving the shaft **5202** relative to the handle **5220** without slipping.

[0408] In the present embodiment, the capstan **5270b** comprises a zero-walk capstan. In other embodiments, such as shown in FIGS. **46** and **47**, a capstan can be incorporated into the handle **5220** that can allow for cable walk. The zero-walk capstan architecture helps to manage multiple wraps of cable **5230b** around the capstan **5270b** without a helix angle on the groove to prevent the cable walk across the capstan **5270b**, which could affect overall path length and change tension in the cable. By placing an additional pulley **5270d** on an incline next to the capstan **5270b**, a redirect to a parallel path on the capstan **5270b** can be achieved, resulting in no walking action of the cable **5230b** on the capstan **5270b**.

[0409] FIGS. **46** and **47** present alternative embodiments to the zero-walk capstan shown in FIG. **45**. In these embodiments, the capstan that drives shaft insertion is an enlarged capstan **5270e** that can be incorporated into the architecture of the second actuation mechanism. With a large enough drive capstan **5270e** and a small enough insertion stroke, the number of rotations of the capstan is small. For example, with a 22 mm drive capstan **5270e** and a 350 mm insertion stroke, the number of rotations of the capstan **5270e** for full insertion range is 5 rotations. If the distance that the cable goes to is large enough compared to the cable walk range of the capstan **5270e**, the amount of fleet angle on the cable and path length change during insertion is small enough to be negligible. In some embodiments, the fleet angle can be between ± 2 degrees.

[0410] FIG. **46** illustrates a perspective view of an alternative spool using a single cable for shaft translation, according to one embodiment. The alternative spool comprises an enlarged capstan **5270e** which is engaged by a single cable **5230b**. In this embodiment, to actuate drive shaft insertion, the single cable **5230b** has a large enough wrap angle to have enough capstan friction to drive. In some embodiments, the single cable **5230b** is continuous and wraps around the capstan **5270e** multiple times (e.g., 3, 4 or more times) to have a large enough wrap angle to drive the capstan and insertion.

[0411] FIG. **47** illustrates a perspective view of an alternative spool using more than one cable for shaft translation, according to one embodiment. The alternative spool comprises an enlarged capstan **5270e** which is engaged by two separate segments **5230b'**, **5230b''** of a single cable **5230b**. Each of the segments **5230b'**, **5230b''** terminates on the capstan **5270e**. Unlike the embodiment in FIG. **46**, the present embodiment does not rely on capstan friction to drive shaft insertion. In this embodiment, the cable **5230b** is helixed to the outsides and then terminated to the spool at both the top and bottom. An advantage of the double termination approach shown in FIG. **47** is that it is resilient to loss of cable tension. As the double termination approach relies on a positive engagement rather than friction, slip cannot happen.

[0412] FIG. **48** illustrates a front view of a handle including the spool of FIG. **46**, according to one embodiment. From this view, one can see one possible position of the spool (e.g., the capstan **5270e**) within the handle **5220**. Advantageously, additional spools and pulleys can be provided within the handle **5220** to actuate the end effector **5212**. For example, a pulley system for end effector actuation as represented in FIG. **40** can be incorporated into the handle in FIG. **48**.

Accordingly, the handle **5220** can incorporate multiple mechanisms for both end effector actuation

and/or drive insertion. As shown in FIG. 48, the one or more pulleys guiding the cable 5230 onto the capstan 5270e are situated across the handle to increase cable distance. If the distance that the cable goes to is large enough compared to the cable walk range of the capstan 5270e, the amount of fleet tangle on the cable and path length change during insertion is small enough to be negligible. In some embodiments, it is possible to have a traditional helix capstan and keep the length change and fleet angle to a minimum.

[0413] FIG. 49 illustrates a schematic diagram showing an alternative architecture for actuating an end effector and shaft insertion, according to one embodiment. The architecture incorporates a first actuation mechanism for actuating an end effector and a second actuation mechanism for shaft insertion. Like prior embodiments, the first actuation mechanism and the second actuation mechanism are decoupled, such that actuation of the end effector does not impact shaft insertion, and vice versa. However, in the present embodiment, the first actuation mechanism comprises one or more cables for actuating an end effector that terminate at an insertion spool (which is also used as part of the second actuation mechanism for shaft insertion), rather than terminating on the proximal and distal portions of the shaft as in the embodiment in FIG. 40. As a result of this architecture, during shaft insertion via a second actuation mechanism, one or more cables that are wound by the insertion spool are substantially counterbalanced by a length of one or more cables (used in a first actuation mechanism to actuate an end effector) that are unwound by the insertion spool. During end effector actuation via a first actuation mechanism, one is trading off the path lengths of the cables coming off of the insertion spool.

[0414] As shown in FIG. 49, the alternative architecture for end effector actuation and shaft insertion comprises a shaft 5502 having a proximal portion 5304 and a distal portion 5306 where an end effector is located. One or more spools 5370a, 5370b, 5370c, 5370d, 5370e (which are part of a handle) are positioned about the shaft 5502. Spool 5370c comprises an insertion spool. Rotation of the insertion spool 5370c in a first direction causes shaft translation relative to the handle in a first direction (e.g., in a direction of insertion), while rotation of the insertion spool 5370c in a second direction causes shaft translation relative to the handle in a second direction (e.g., in a direction of retraction). One or more cables or cable segments 5330a terminate to an end effector (e.g., a wrist) on one end and an insertion spool on the other. One or more additional cables or cable segments 5330b also begin at the insertion spool 5370c before terminating at, near or towards a distal portion 5306 of the shaft 5502.

[0415] In the present embodiment, a first actuation mechanism is provided wherein manipulation of one or more spools (e.g., spools 5370a, 5370d) via linear or rotary movement causes a change of length of the one or more cables 5330a within the handle. In some embodiments, the change of length of the one or more cables 5330a within the handle can include a change of the path length of one or more cables or cable segments within the handle. In this first actuation mechanism, the one or more cables 5330a can be considered “end effector” cables. Any change in length of the one or more cables 5330a in the handle that causes actuation of the end effector is counterbalanced by a length of the one or more cables 5330b.

[0416] In the present embodiment, a second actuation mechanism is provided wherein manipulation of the insertion spool 5370c via linear or rotary movement causes a change of length of the one or more cables 5330b within the handle. In this second actuation mechanism, the one or more cables 5330b can be considered “insertion” cables. Any change in length of the one or more cables 5330b in the handle that causes shaft insertion or retraction is counterbalanced by a length of the one or more cables 5330a. Under insertion and retraction, tension is maintained because equal amounts of the one or more end effector cables 5330a are being paid out as the one or more insertion cables 5330b are being taken up. The relative path length of the one or more end effector cables 5330a remains unchanged, so the end effector does not move under insertion.

[0417] FIG. 50A illustrates a zoomed-in front view of an instrument incorporating the alternative architecture for actuating an end effector and shaft insertion of FIG. 49, according to one

embodiment. FIG. 50B illustrates a top perspective view of the instrument incorporating the alternative architecture for actuating an end effector and shaft insertion of FIG. 49. The instrument 5300 incorporates the first and second actuation mechanism shown in FIG. 49, and includes a handle 5320 comprising one or more mechanical inputs 5324, each corresponding to one or more spools 5370a-e, wherein at least one of the spools (5370c) comprises an insertion spool. One or more cables or cable segments 5330a', 5330a'', 5330a''' and 5330a''', each corresponding to a separate mechanical input 5324, terminate at the drive spool 5370c. Each of these cables 5330a', 5330a'', 5330a''' and 5330a'''' can engage with one or more spools akin to the one or more cables 5330a (shown in the schematic in FIG. 49). In a first actuation mechanism, these cables can serve as end effector cables, such that manipulation of their corresponding mechanical inputs 5324 causes a change of length of the cables within the handle. In some embodiments, the change of length of the one or more cables within the handle can include a change of the path length of one or more cables or cable segments within the handle. In some embodiments, a path length of the cables within the handle is changed. In some instances, the change of length in the one or more cables 5330a', 5330a'', 5330a''', 5330a'''' within the handle 5320 that actuate the end effector is counterbalanced by a length of cable 5330b, which is akin to the similarly reference cable 5330b in FIG. 49. In other instances, under pure end effector actuation, the length of the cable 5330b in the handle is not changing. In a second actuation mechanism, the cable 5330b can serve as an insertion cable, such that manipulation of its corresponding mechanical input 5324 causes cable 5330b to be wound around the insertion spool 5370c. The amount of cable 5330b that is wound around the insertion spool 5370c that causes shaft insertion is counterbalanced by a length of the one or more cables 5330a', 5330a'', 5330a''', 5330a'''' being unwound.

[0418] FIG. 51 illustrates a top perspective view of a handle and shaft of an instrument, according to one embodiment. The shaft 5202 is translatable relative to the handle 5220. From this view, one can see the one or more mechanical inputs 5224, which upon rotation, actuate the end effector. In addition, one can see the one or more mechanical inputs 5324, which upon rotate, allow for translation of the shaft 5202 relative to the handle 5220 along an axis of insertion. The attachment interface 5222 includes the one or more mechanical inputs 5224, 5324 e.g., receptacles, pulleys or spools, that are designed to reciprocally mate with one or more torque couplers 4314 on an attachment interface 4310 of the IDM 4300 (shown in FIG. 31).

[0419] FIG. 52A illustrates a schematic view of a cross-section of an instrument shaft utilizing the insertion architecture shown in FIG. 40, while FIG. 52B illustrates a schematic view of a cross-section of an instrument shaft utilizing the alternative insertion architecture shown in FIG. 49. While not visible, each of the cross-sections in FIGS. 52A and 52B include openings or lumens that extend therethrough. As shown in FIG. 52A, the insertion architecture of FIG. 40 results in one or more cables 5230 that extend through grooves or channels 5208 that extend along an outer surface of the shaft 5202. In contrast, as shown in FIG. 52B, the insertion architecture of FIG. 49 results in one or more cables 5330b that extend through less grooves or channels 1308 (here a single channel) along an outer surface of the shaft 5202. This is because in the alternative architecture of FIG. 49, cables are more inclined to extend within the body of the shaft 5502. For example, there are no end effector cables on the outside of the shaft 5502. With less cables extending on the outside of the shaft 5502, the architecture in FIG. 49 can result in an overall smoother shaft surface with less grooves or channels extending on an outer surface.

[0420] The architectures described above (e.g., shown in FIGS. 40 and 49) can be used to actuate an end effector and accommodate instrument insertion. In addition, these architectures can be incorporated into specific types of instruments to assist in surgical procedures.

[0421] One such instrument is a vessel sealer. With a vessel sealer, a knife or cutter can be driven through to cut tissue. In some embodiments, motion of the knife is rotational. In other embodiments, motion of the knife is translational. FIGS. 53-55 show different architectures that can be incorporated into a vessel sealer instrument to drive a knife through a vessel sealer. The

architectures shown in these figures are like the architecture and related mechanisms shown in FIG. 40, but in other embodiments, the architectures can be like the architecture and related mechanisms shown in FIG. 49.

[0422] FIGS. 53-55 illustrate schematic diagrams showing different architectures for driving a knife in a vessel sealer. The architectures create a differential in path length amongst cables, and turns this differential path length change into linear motion of the knife. In the embodiments in FIGS. 53 and 54, two cables 5430a, 5430b are placed in counter tension, while in the embodiment in FIG. 55, a single cable 5430 and spring 5490 is used for counter tension. In the embodiments where two cables are placed in counter tension, linear motion of the knife is achieved by having both differentials on the same input axis, but in opposite directions (e.g., one is unwrapping cable while the other is wrapping cable). The dual, opposing cable approach also utilizes a redirect pulley to close the tension loop, and this can be mounted at or near a proximal end or at or near a distal end of a shaft (shown respectively in FIGS. 53 and 54). Once you have cable that is being pulled in and out, the knife can be coupled to a section of cable to create an in and out motion of the knife.

[0423] FIG. 53 illustrates a schematic diagram showing an architecture for driving a knife 5482 in a vessel sealer 5480. The architecture comprises a first cable 5430a and a second cable 5430b, wherein the first cable 5430a and second cable 5430b are in counter tension. The architecture further comprises one or more spools or pulley members 5470a, 5470b, 5470c that are engaged by the first cable 5430a, and one or more spools or pulley members 5470d, 5470e, 5470f that are engaged by the second cable 5430b, and a redirect spool or pulley 5470g that closes the tension loop. The redirect pulley 5470g is positioned at or near a proximal portion of the shaft. With the first cable 5430a and second cable 5430b in counter tension to one another, the knife 5482 can be coupled to a section of cable (e.g., first cable 5430a) via a connector such as elongate member 5484, thereby creating an in and out motion of the knife 5482 relative to the vessel sealer 5480. In some embodiments, elongate member 5484 comprises a push rod. In other embodiments, elongate member 5484 withstands the driving compression forces without buckling.

[0424] FIG. 54 illustrates a schematic diagram showing an alternative architecture for driving a knife in a vessel sealer. The architecture is similar to that shown in FIG. 53; however, in the present embodiment, the redirect pulley is positioned at or near a distal portion of the shaft.

[0425] FIG. 55 illustrates a schematic diagram showing yet another alternative architecture for driving a knife in a vessel sealer. Unlike the prior embodiments in FIGS. 53 and 54, the architecture in the present embodiment utilizes a single cable 5430 that is in counter tension with a spring 5490. The architecture further comprises one or more spools or pulley members 5470a, 5470b, 5470c that are engaged by the first cable 5430a. With the cable 5430 in counter tension with the spring 5490, the knife 5482 can be coupled to a section of the cable 5430, thereby creating an in and out motion of the knife 5482 relative to the vessel sealer 5480.

[0426] Another device that can serve as an insertion instrument is a camera. The camera can be used for endoscopic surgery. The architecture can vary depending on whether the camera is a rigid camera or an articulating camera, for which actuation for articulation will have to be provided.

[0427] FIG. 56 illustrates a schematic diagram showing an architecture for making a rigid camera an insertion instrument. The camera 5500 comprises a distal image payload connected by a shaft 5502 to a camera handle 5530 which has interface buttons and a cable coming out of it. The cable 5530 is received in a channel or groove formed on the outside of the shaft 5502, while the insertion handle 5520 is positioned around the shaft 5502. This in effect adds a second handle to the endoscope which enables insertion capability. The cable 5530 extends through one or more spools 5570a, 5570b, 5570c. In the present embodiment, spool 5570b can be a capstan. In some embodiments, the capstan can comprise a zero-walk capstan (as shown in FIG. 45), while in other embodiments, the capstan can allow cable walk (as shown in FIGS. 46 and 47). Via the capstan mechanism, the camera is capable of translation along an axis of insertion. In some embodiments, the core payload maintains the same sealing architecture as a rigid scope, so it can be expected to

be sterilized with the same methods. For a rigid scope, this means it can be autoclaved. The additional insertion handle **5520** may also look like an instrument from a sterilization perspective and can be autoclaved as well.

[0428] While FIG. **56** shows an architecture for making a rigid camera an insertion instrument, articulating cameras present additional complexity, as mechanisms would be added to the camera to provide for articulation. For the articulating camera, one or more cables (e.g., actuation or wrist cables) can be provided to accommodate articulating movement. The camera can also be housed in a sealed area, such that if one is to run the one or more cables on the outside, one can also create a sealed compartment for the camera that excludes the one or more cables. With this architecture, it may be possible that some particles and debris get into small spaces within the sealed area. In some embodiments, to prevent the contamination, one solution may be to add two articulation motors within the sealed camera area rather than relying on the IDM for articulation motion. This greatly simplifies the cleaning and sealing of the camera components by taking the cables from the outside of the tube and putting them in the sealed inside. Another benefit of adding the two articulation motors within the sealed camera is that articulation of the camera can be controlled as soon as the camera is plugged into a vision box. This enables features like keeping the camera straight during installation or removal and being able to articulate the camera from the camera handle to look around during off-robot use. This then makes the articulation camera look a lot like the rigid camera from a sterilization perspective such that it is possible to be autoclaved.

[0429] If a camera is not able to be autoclaved, then the sealed camera core and the insertion section may need to be separated for cleaning and insertion. This is because it is desirable to autoclave an insertion handle to achieve reliable sterilization. FIG. **57** shows a first insertion architecture that allows a camera to be separated from an insertion handle, while FIGS. **58** and **59** show a second insertion architecture that allows a camera to be separated from an insertion handle, thereby allowing for better sterilization.

[0430] FIG. **57** shows a first insertion architecture that allows a camera to be separated from an insertion handle. The architecture has an autoclavable insertion handle **5620** that latches onto an IDM and is separable from the camera core **1600**. The camera core **1600** comprises a shaft **5602** that extends through the handle **5620**. The handle **5620** comprises one or more wires **5630a**, **5630b** that extend through spools **5670a**, **5670b**, **5670c**, **5670d**. In the present embodiment, spool **5670b** comprises a capstan. In some embodiments, the spool **5670b** comprises a leadscrew. In some embodiments, the capstan is a zero-walk capstan (as shown in FIG. **45**), while in other embodiments, the capstan allows cable walk. The insertion handle **5620** can be removably attached to the camera core **5600** via a connector **5640**. In some embodiments, the connector **5640** comprises a bracket. In other embodiments, the connector **5640** comprises a vertical plate that the camera latches to. As the insertion handle **5620** is removably attached to the camera core **1600**, each is capable of separation for cleaning.

[0431] FIGS. **58** and **59** show a second architecture that allows a camera to be separated from an insertion handle. In the present embodiment, an overtube **5780** is provided that has an insertion cable **5730** attached to it and through which a camera **5700** can be loaded for a procedure. FIG. **60** shows the camera **5700** detached and separated from the overtube **5780**, while FIG. **61** shows the camera **5700** loaded into the overtube **5780**. To load the camera **5700** into the overtube, a distal tip **5706** and shaft **5702** of the camera **5700** passes through the overtube **5780**. The overtube **5780** is connected to a handle **5720** which houses a spool **5770** in the form of a capstan. This architecture has the benefit of keeping the camera **5700** separate from an insertion handle **5720** if desired, so that both components can be easily cleaned. Furthermore, the camera **5700** is kept low profile in use, as it is to be fit into the overtube **5780**. As the insertion handle **5720** is removably attached to the camera core **5700**, each is capable of separation for cleaning.

[0432] FIG. **60** illustrates a diagram showing an alternative architecture for shaft translation, according to another embodiment. In the present embodiment, the instrument comprises a shaft

5902 having a proximal portion **5904** and a distal portion **5906**. Insertion of the shaft **5902** can be driven by a rack gear **5912** and pinion **5914**, wherein rotation of the pinion **5914** results in translation of the rack gear **5912** and the shaft **5902** that is coupled to the rack gear **5912**. In some embodiments, the rack gear **5912** is positioned on the instrument shaft **5902**, while the pinion **5914** is positioned within the housing of the instrument handle. A motor driver can be used to translate the shaft **5902** relative to the handle. In some embodiments, a spur gear can be used, in addition to a cycloid pin rack profile. In some embodiments, the rack gear **5912** and pinion **5914** can be used on its own to cause insertion or translation of the shaft **5902**. In other embodiments, the rack gear **5912** and pinion **5914** can accompany and complement any of the insertion mechanisms described above. The rack gear **5912** and pinion **5914** can be used with any of the types of instruments described above to provide linear insertion of the instrument shaft relative to the handle.

[0433] When performing surgical procedures, such as laparoscopic procedures, surgeons use insufflation. This means that cannulas inserted into a patient are sealed against the surgical tool shafts to maintain positive pressure inside a patient's body. Seals can be coupled to the surgical tool shafts to prevent air from leaking from a patient's body. These seals are often designed to accommodate tools having round cross-sections. It can be difficult to apply the same seals to tools having non-circular shapes and concave features on the outer surfaces of the shaft, as passages formed by these surfaces can allow the release of air pressure at the tool seal. For example, instruments having instrument based insertion architectures can have cross-sections (as shown in FIG. 52A) with grooves **5208** where air can leak from a patient.

[0434] To address this challenge, a system including multiple seals can be provided to prevent air leakage in a patient. In particular, a novel seal can be provided that works with a cannula seal having a circular outer shape, which is customary with instruments having circular cross-sections. The novel seal can pass through the circular cannula seal, thereby providing a consistent rotary seal. The novel seal would advantageously discretize any rotary and linear motion to create two boundaries at which a seal is created. The discretization is achieved by having an intermediate tool seal piece.

[0435] FIG. 61 shows a side cross-sectional view of an instrument having multiple seals to prevent air leakage from a patient. FIG. 62 shows a front cross-sectional view of the instrument having the multiple seals. The instrument **5200** is inserted into a cannula **5050**, and is akin to the instrument shown in FIG. 39 having an instrument based insertion architecture. The instrument can include a shaft **5202** translatable relative to a handle **5220**. The shaft **5202** can have one or more channels or grooves **5208** extending along an outer surface thereof, thereby creating passages that could allow air to leak from a patient.

[0436] To prevent air leakage, a multi-seal system advantageously couples to the instrument. In some embodiments, the multi-seal system comprises a first seal **5810** and a second seal **5820** that can work in conjunction to reduce the risk of air leakage. In some embodiments, the first seal **5810** and second seal **5820** are coaxial. As shown in FIG. 60, the second seal **5820** can be received in an interior of the first seal **5810**. The first seal **5810** can have a cross-section having a round outer perimeter and round inner perimeter, while the second seal **5820** can have a cross-section having a round outer perimeter and an inner perimeter with inner protrusions, tabs or nubs **5822**, as shown in FIG. 62. The advantage of having a second seal **5820** with the inner protrusions is that the inner protrusions can fill in voids, such as grooves **5208**, that may extend along an outside of the instrument shaft **5202**, thereby reducing the risk of air leakage from a patient during surgery.

[0437] The multi-seal advantageously discretizes rotary and linear motion to create two boundaries at which a seal is created. The second seal **5820**, with its inner protrusions **5822**, can slide down the outer grooves of the instrument shaft **5202**, thereby creating a sliding linear seal for instrument shaft motion. One skilled in the art will appreciate that while the second seal **5820** is shown with a plurality of inner protrusions that are rounded and spaced substantially symmetrically around an inner perimeter, the inner portion of the second seal **5820** can assume other shapes as well, so long

as the molding process substantially matches the interior of the second seal 5820 to the outer surface of the instrument shaft 5202. When received in the grooves 5208 of the instrument 5200, each of the inner nubs 5822 of the second seal 5820 creates a rotary seal point 5824. These rotary seal points allow the instrument 5200 and second seal 5820 to rotationally lock and rotate together upon rotation of the instrument shaft 5202. While the present embodiment shows a multi-seal having dual seals, in other embodiments, three, four, or more seals can work together to reduce the risk of air leakage from a patient during surgery.

XV. Software

[0438] In some embodiments, one or more aspects of a system including adjustable arm supports and corresponding robotic arms can be controlled via software. For example, the system can be designed so that all actuations are robotically controlled by the system, and the system knows the position of all end effectors relative to the tabletop. This may provide a unique advantage that existing robotic surgery systems do not have. Further, this may allow for advantageous workflows including: adjusting the table top intraoperatively (e.g., tilt, Trendelenburg, height, flexure, etc.) while arms and arm positioning platforms move in sync; moving the robotic arms can move away from the operative field for draping or patient loading; after a clinician tells the system the type of procedure, the robotic arms can move to approximate positions near where ports are typically placed (Surgeons could modify and set port selection “presets” for how they like to do surgery); and performing “last mile” docking with cameras on the end effectors and vision targets on cannulas (other non-optical sensors around the end effector could provide similar functionality).

[0439] Further, some incarnations of robotic arm joints may require applying high forces to the arm to back-drive the motors and transmissions. This can be reduced with torque sensors in arm joints or a force sensor or joystick at the end effector to allow the robot to know where the clinician is trying to push it and move accordingly (admittance control) to lower back-drive forces felt at the output. Such back-drive regulation can be accomplished in software in some embodiments.

XVI. Additional Considerations

[0440] Upon reading this disclosure, those of skill in the art will appreciate still additional alternative structural and functional designs through the disclosed principles herein. Thus, while particular embodiments and applications have been illustrated and described, it is to be understood that the disclosed embodiments are not limited to the precise construction and components disclosed herein. Various modifications, changes and variations, which will be apparent to those skilled in the art, may be made in the arrangement, operation and details of the method and apparatus disclosed herein without departing from the spirit and scope defined in the appended claims.

[0441] As used herein any reference to “one embodiment” or “an embodiment” means that a particular element, feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

[0442] Some embodiments may be described using the expression “coupled” and “connected” along with their derivatives. For example, some embodiments may be described using the term “coupled” to indicate that two or more elements are in direct physical or electrical contact. The term “coupled,” however, may also mean that two or more elements are not in direct contact with each other, but yet still co-operate or interact with each other. The embodiments are not limited in this context unless otherwise explicitly stated.

[0443] As used herein, the terms “comprises,” “comprising,” “includes,” “including,” “has,” “having” or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, method, article, or apparatus that comprises a list of elements is not necessarily limited to only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. Further, unless expressly stated to the contrary, “or” refers to an inclusive or and not to an exclusive or. For example, a condition A or B is satisfied by

any one of the following: A is true (or present) and B is false (or not present), A is false (or not present) and B is true (or present), and both A and B are true (or present).

[0444] In addition, use of the “a” or “an” are employed to describe elements and components of the embodiments herein. This is done merely for convenience and to give a general sense of the invention. This description should be read to include one or at least one and the singular also includes the plural unless it is obvious that it is meant otherwise.

Claims

1. A system, comprising: a table; a table support below the table; an arm support coupled to at least one of the table or table support; a first robotic arm coupled to the arm support; an insertion axis body coupled to a distal link of the first robotic arm via a joint, the insertion axis body extending along an axis, the joint permitting adjustment of an angle between the axis of the insertion axis body and a longitudinal axis of the distal link; and first and second instrument drivers translatable coupled to the insertion axis body, the first instrument driver configured to receive a first surgical instrument and the second instrument driver configured to receive a second surgical instrument, the first instrument driver configured to translate along the insertion axis body to insert or retract the first surgical instrument along a first insertion axis parallel to the axis of the insertion axis body, the second instrument driver configured to translate along the insertion axis body to insert or retract the second surgical instrument along a second insertion axis parallel to the axis of the insertion axis body.
2. The system of claim 1, wherein the first instrument driver is configured to insert or retract the first surgical instrument within a channel of the second surgical instrument.
3. The system of claim 1, wherein the first and second instrument drivers are configured to drive the first and second surgical instruments, respectively, independently of each other.
4. The system of claim 1, wherein the first and second insertion axes are coaxial.
5. The system of claim 1, wherein the first and second instrument drivers are removable from the robotic arm.
6. The system of claim 1, wherein the first instrument driver is rotatably coupled to the insertion axis body, the first instrument driver configured to rotate about the first insertion axis to roll the first surgical instrument about the first insertion axis.
7. The system of claim 1, further comprising the first and second surgical instruments, the first surgical instrument having a first housing and a first shaft extending from the first housing, the first instrument driver being configured to translate the first housing along the insertion axis body to insert or retract the first shaft along the first insertion axis, the second surgical instrument having a second housing and a second shaft extending from the second housing, the second instrument driver being configured to translate the second housing along the insertion axis body to insert or retract the second shaft along the second insertion axis.
8. The system of claim 1, wherein the insertion axis body is movable between a deployed configuration and a stowed configuration, wherein, in the deployed configuration, the insertion axis body and the first and second instrument drivers are elevated above the table, and, in the stowed configuration, the insertion axis body and the first and second instrument drivers are positioned below the table with the angle between the axis of the insertion axis body and the longitudinal axis of the distal link reduced relative to the deployed configuration so that the stowed configuration is more compact than the deployed configuration.
9. The system of claim 1, wherein the joint is a wrist joint that permits adjustment of pitch and adjustment of yaw between the insertion axis body and the distal link.
10. The system of claim 1, further comprising the first and second surgical instruments, wherein the first surgical instrument is an endoscope and the second surgical instrument is a sheath that surrounds the endoscope.

11. A system, comprising: a table; a table support below the table; an arm support coupled to at least one of the table or table support; a first robotic arm coupled to the arm support; an insertion axis body coupled to a link of the first robotic arm via a wrist joint, the insertion axis body extending along an axis, the wrist joint permitting adjustment of an angle between the axis of the insertion axis body and a longitudinal axis of the link; a first instrument driver translatably coupled to the insertion axis body, the first instrument driver configured to receive a first housing of a first surgical instrument, the first instrument driver configured to translate along the axis of the insertion axis body to move the first housing of the first surgical instrument along a first insertion axis parallel to the axis of the insertion axis body, the first instrument driver comprising a first plurality of torque couplers configured to engage a first plurality of mechanical inputs of the first housing; and a second instrument driver translatably coupled to the insertion axis body, the second instrument driver configured to receive a second housing of a second surgical instrument, the second instrument driver configured to translate along the longitudinal axis of the insertion axis body to move the second housing of the second surgical instrument along a second insertion axis parallel to the axis of the insertion axis body, the second instrument driver comprising a second plurality of torque couplers configured to engage a second plurality of mechanical inputs of the second housing.

12. The system of claim 11, wherein the first instrument driver is configured to insert or retract a shaft of the first surgical instrument within a channel of the second surgical instrument in a telescoping configuration.

13. The system of claim 11, wherein the first and second instrument drivers are configured to drive the first and second surgical instruments, respectively, independently of each other, wherein the first instrument driver is configured to apply torque to the first plurality of torque couplers to thereby actuate the first surgical instrument via the first plurality of mechanical inputs, wherein the second instrument driver is configured to apply torque to the second plurality of torque couplers to thereby actuate the second surgical instrument via the second plurality of mechanical inputs.

14. The system of claim 11, wherein the first and second insertion axes are coaxial.

15. The system of claim 9, wherein the first and second instrument drivers are removable from the robotic arm.

16. A system, comprising: a table; a table support below the table; an arm support coupled to at least one of the table or table support; a first robotic arm coupled to the arm support; an insertion axis body coupled to a distal link of the first robotic arm via a joint, the insertion axis body extending along an axis, the joint permitting adjustment of an angle between the axis of the insertion axis body and a longitudinal axis of the distal link; and first and second instrument drivers translatably coupled to the insertion axis body, the first and second instrument drivers axially aligned and configured to receive first and second instruments, the first instrument driver configured to translate along the axis of the insertion axis body to insert or retract the first instrument along a first insertion axis parallel to the axis of the insertion axis body, the second instrument driver configured to translate along the insertion axis body to insert or retract the second instrument along a second insertion axis coaxial with the first insertion axis, the insertion axis body movable between a deployed configuration and a stowed configuration, wherein, in the deployed configuration, the insertion axis body and the first and second instrument drivers are elevated above the table, and, in the stowed configuration, the insertion axis body and the first and second instrument drivers are positioned below the table with the angle between the axis of the insertion axis body and the longitudinal axis of the distal link reduced relative to the deployed configuration so that the stowed configuration is more compact than the deployed configuration.

17. The system of claim 16, wherein the first and second instrument drivers are configured to translate along the insertion axis body independently of each other.

18. The system of claim 16, wherein the first and second instrument drivers are configured to drive the first and second instruments, respectively, independently of each other.

- 19.** The system of claim 16, further comprising the first and second instruments, wherein the first instrument is an endoscope and the second instrument is a sheath that surrounds the endoscope.
- 20.** The system of claim 16, wherein the first instrument driver is configured to insert or retract a shaft of the first instrument within a shaft of the second instrument in a telescoping configuration.
-