

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250267200

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Gaetje; Clay

---

### LOCALIZED WEATHER APPLICATION

---

#### Abstract

Systems and methods are provided herein for supplying localized weather information to a user. This may be accomplished by a system receiving a request to generate a weather report for a location. The system may identify weather information sources within a threshold distance of the location, wherein one or more of the weather information sources is a mobile weather information source. The device may generate a weather report for the location based on the weather information received from the weather information sources.

---

**Inventors:** Gaetje; Clay (Fullerton, CA)

**Applicant:** Adeia Guides Inc. (San Jose, CA)

**Family ID:** 1000008586898

**Appl. No.:** 19/202353

**Filed:** May 08, 2025

#### Related U.S. Application Data

parent US continuation 18644713 20240424 parent-grant-document US 12328371 child US 19202353

parent US continuation 18142252 20230502 parent-grant-document US 11997174 child US 18644713

parent US continuation 16950416 20201117 parent-grant-document US 11683388 child US 18142252

---

#### Publication Classification

**Int. Cl.:** H04L67/52 (20220101); G01W1/10 (20060101); H04W4/029 (20180101)

**U.S. Cl.:**

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/644,713, filed Apr. 24, 2024, which is a continuation of U.S. patent application Ser. No. 18/142,252, now U.S. Pat. No. 11,997,174, filed May 2, 2023, which is a continuation of U.S. patent application Ser. No. 16/950,416, now U.S. Pat. No. 11,683,388, filed Nov. 17, 2020. The disclosures of which are hereby incorporated by reference herein in their entities.

### BACKGROUND

[0002] The present disclosure relates to computer-implemented techniques for determining weather information, in particular to techniques for supplying localized weather information to a user.

### SUMMARY

[0003] Electronic devices (e.g., smartphones, laptops, tablets, personal computers, etc.) provide various types of information to users throughout the day. One type of information that many users have grown to rely on is information related to weather conditions. Information related to weather conditions can include temperature, humidity, cloud cover, precipitation, wind speed, barometric pressure, and similar such information. This information is particularly important for users when planning out their daily lives. For example, when temperatures are cold, a user may decide to incorporate a jacket into their wardrobe, and if temperatures are hot, a user may decide to go to the pool. Current weather applications rely on data received from weather collection stations to generate information related to weather conditions. However, there are many situations where current weather applications are wholly inadequate. For example, due to the limited number of weather collection stations, current weather applications lack granularity, and most weather applications are only able to provide weather conditions down to a city level. This is problematic as many cities, such as Los Angeles, span very large areas where weather conditions can vary drastically in different parts of the cities. In some situations, there may be thunderstorms on one side of the city and sunny weather conditions on the other side of the city twenty miles away. This results in users receiving inaccurate information, causing disruptions throughout their day. In view of these deficiencies, there exists a need for improved systems and methods for supplying localized weather information to a user.

[0004] Accordingly, techniques are disclosed herein for improved systems and methods for supplying localized weather information to a user. Various embodiments disclosed herein provide for a weather application to determine a location of a user associated with a first device. After determining the location of the user using the first device, the weather application identifies vehicles that are within a threshold distance of the user's location. For example, the weather application may identify all vehicles that are within five miles of the location of the user. To identify these vehicles, the weather application may access a database containing locations of vehicles and select vehicles that are within a threshold distance of the user's location. After the weather application determines the vehicles that are close to the user, the weather application then receives weather information from said vehicles. The weather information can correspond to any information used to generate a weather report. For example, most vehicles comprise a thermometer, photoelectric sensor, and/or a precipitation sensor. These instruments can be used to generate weather information (e.g., the thermometer can be used to indicate the current temperature). The weather application receives the weather information generated by the vehicles and uses this information to generate a weather report for the user. Utilizing vehicles instead of solely relying on weather stations provides improved systems and methods that result in a weather report for users

that is more accurate and more granular.

[0005] In some embodiments, when determining vehicles that are within a threshold distance of the user, the weather application dynamically updates the threshold distance based on the number of vehicles within the threshold distance. For example, the weather application may require weather information from at least five vehicles within the threshold distance in order to generate a weather report. If the starting threshold distance is one mile from the user and the weather application determines that there are only three vehicles within the one-mile threshold distance, then the weather application will incrementally update the threshold distance until the minimum number of vehicles are within the threshold distance. For example, when the weather application increases the threshold distance to two miles, the weather application may determine that eight vehicles are located within the threshold distance. The weather application will use the new threshold distance of two miles to generate the weather report because the two-mile threshold distance comprises the necessary number of vehicles. After determining vehicles that are within the threshold distance of the user, the weather application may receive a plurality of data points wherein each data point is associated with one of the vehicles that are within the threshold distance. The plurality of data points corresponds to the weather information collected by the one or more instruments onboard the vehicles that are within the threshold distance. For example, a first vehicle within the threshold distance may send a first data point that indicates the temperature determined by the thermometer onboard the first vehicle. In other examples, the first vehicle may send additional data points where the data points correspond to different weather information. For example, the other data points may correspond to brightness determined by a photoelectric sensor onboard the first vehicle and/or precipitation determined by one or more sensors onboard the first vehicle.

[0006] In some embodiments, the weather application receives the plurality of data points from each of the vehicles that are within the threshold distance of the user. For example, each vehicle within the threshold distance of the user submits data points corresponding to the temperature recorded by its onboard thermometers to a database. The vehicles may submit data points when requested or may automatically submit data points periodically (e.g., every 30 seconds). The data points may be accompanied by location data to ensure the vehicles that submitted the data points, are still within the threshold distance of the user. The weather application uses the data points submitted by the vehicles that are within the threshold distance of the user and generates the weather report. When generating the weather report the weather application may use a weighted average where each received data point is weighted depending on a number of factors. For example, data points received from vehicles that are closer to the user will be weighted higher than data points received from vehicles that are farther away from the user. In another example, data points associated with moving vehicles may be weighted differently than data points associated with stationary vehicles. Data points received from newer vehicles with newer onboard instruments may be weighted differently than data points received from older vehicles.

[0007] In some embodiments, the weather application processes the received data points to generate a weather report for the user. For example, if ten vehicles within the threshold distance of the user each submit a data point indicating the temperature recorded by their respective onboard thermometers, the weather application can take the average of the ten data points to determine a current local temperature that is included in the weather report for the user. Using data processing methods, the weather application can determine if any of the received data points should be ignored when generating the weather report. For example, if nine data points indicate temperatures that are within five degrees of each other, but a tenth data point indicates a temperature that is fifteen degrees different from any of the other nine data points, then the weather application will identify the tenth data point as an abnormality. This abnormality may be the result of the vehicle being exposed to some variant (e.g., shade, wind, excessive sunlight, etc.), faulty instruments onboard the vehicle, or some other irregularity. In some embodiments, the weather application will ignore data points that are categorized as abnormal when generating the weather report for the user. In some

embodiments, the weather application can utilize weather information collected by other sources (e.g., weather collection stations, home weather stations, etc.) to further refine the accuracy of the generated weather reports.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The below and other objects and advantages of the disclosure will be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

[0009] FIG. 1 shows an illustrative diagram of a system for providing localized weather information, in accordance with some embodiments of the disclosure;

[0010] FIG. 2 shows a diagram of an illustrative table for providing localized weather information, in accordance with some embodiments of the disclosure;

[0011] FIGS. 3A and 3B show illustrative diagrams of user devices generating weather reports, in accordance with some embodiments of the disclosure;

[0012] FIG. 4 shows an illustrative block diagram of a system for generating weather reports, in accordance with some embodiments of the disclosure;

[0013] FIG. 5 shows an illustrative block diagram of a user equipment (UE) device system, in accordance with some embodiments of the disclosure;

[0014] FIG. 6 is an illustrative flowchart of a process for providing localized weather information, in accordance with some embodiments of the disclosure.

[0015] FIG. 7 is an illustrative flowchart of a process for providing localized weather information, in accordance with some embodiments of the disclosure;

[0016] FIG. 8 is an illustrative flowchart of a process for determining a threshold distance when providing localized weather information, in accordance with some embodiments of the disclosure; and

[0017] FIG. 9 is an illustrative flowchart of a process for generating a localized weather report, in accordance with some embodiments of the disclosure.

### DETAILED DESCRIPTION

[0018] FIG. 1 shows an illustrative diagram **100** of a system for providing localized weather information, in accordance with some embodiments of the disclosure. System **100** includes a user **102** with a user equipment device. System **100** also includes weather information sources **112A-B**, **114A-C**, **116A-E**, and **118**. Weather information sources can be any source that can supply information related to weather conditions (e.g., temperatures, humidity, sun conditions, cloud cover, precipitation, wind speed, barometric pressure, and similar such information). In some embodiments, weather information sources **112A-B**, **114A-C**, **116A-E**, and **118** comprise one or more instruments for collection of weather information. Weather information sources **112A-B**, **114A-C**, and **116A-E** are mobile weather information sources such as vehicles with instruments for collecting weather information. For example, most vehicles comprise a thermometer, photoelectric sensor, and/or a precipitation sensor. These instruments can be used to generate weather information (e.g., the thermometer can be used to indicate the current temperature). Weather information source **118** is a stationary weather information source such as weather collection station or a home weather station.

[0019] In some embodiments, a user **102** with a user equipment device requests a local weather report by launching a weather application on the user equipment device. The weather application determines the location of the user **102** by using a global positioning system. In some embodiments, the weather application determines the location of the user **102** using cell tower data, Wi-Fi hotspot information, user profile information, or similar such information. After determining

the location of the user equipment device, the weather application identifies weather information sources that are within a threshold distance of the user's location. To identify the relevant weather information sources, the weather application can access a database containing locations of weather information sources and select weather information sources that are within a threshold distance of the user's location. In some embodiments, the desired location for the weather report is the destination of the user rather than the current location of the user. The destination of the user can be inputted by the user, determined using a calendar, determined from a mapping or navigation application and/or determined using some other method.

[0020] In some embodiments, the weather application selects a first area **104** as the threshold distance and identifies all weather information sources that are within the first area **104**. In some embodiments, the weather application determines the first area **104** based on predetermined criteria (e.g., circle with a radius of one mile from the determined location). Although circles are shown, any shape, pattern, and/or zone can be used for the threshold distance. In this embodiment, there are no weather information sources in the first area **104**, so the weather application determines that it must change its threshold distance to a second area **106**. In some embodiments, the second area **106** covers a larger area than the first area **104**. The second area **106** can overlap with the first area **104** or, as in this embodiment, can encompass the entire first area **104**. In some embodiments, the first area **104** is a first annulus and the second area **106** is second non-overlapping annulus. The weather application can determine the second area **106** to be used as the threshold distance based on predetermined zones, incremental increases, or similar such parameters.

[0021] In some embodiments, the weather application selects the second area **106** as the threshold distance and identifies all weather information sources that are within the second area **106**. As shown, there are two weather information sources **112A** and **112B** in the second area **106**. The weather application can determine the approximate location of weather information sources using global positioning systems, cell tower data, Wi-Fi hotspot information, user profile information, or similar such information. The weather application receives weather information from the two weather information sources **112A** and **112B** in the second area **106**. In some embodiments, the weather information sources **112A** and **112B** comprise instruments to generate weather information. For example, weather information sources **112A** and **112B** comprise thermometers and submit temperature data to the weather application. The weather application receives the temperature data and generates a weather report for the user **102**.

[0022] In some embodiments, the weather application requires weather information from a minimum number of weather information sources in order to generate a weather report. For example, if the weather application requires a minimum of five weather information sources, the weather application determines that the second area **106** does not include the minimum number of weather information sources. In some embodiments, the weather application selects a third area **108** and identifies all weather information sources that are within the third area **108**. As shown, there are five weather information sources **112A**, **112B**, **114A**, **114B**, and **114C** in the third area **108**, satisfying the minimum number of weather information sources required by the weather application. In some embodiments, the weather information sources **112A**, **112B**, **114A**, **114B**, and **114C** in the third area **108** comprise thermometers and submit temperature data to the weather application. The weather application receives the temperature data and generates a weather report for the user **102**. In some embodiments, the weather application averages all the temperature data received from the weather information sources to generate the weather report. In some embodiments, the temperature data is weighted corresponding to the proximity of the weather information source to the user **102**. For example, the temperature data submitted by weather information sources **112A** and **112B** is weighted higher than the temperature data submitted by weather information sources **114A**, **114B**, and **114C** because weather information sources **112A** and **112B** are closer to the user than weather information sources **114A**, **114B**, and **114C**.

[0023] In some embodiments, the weather application requires a minimum of ten weather

information sources, and the weather application determines that the third area **108** does not include the minimum number of weather information sources. In some embodiments, the weather application selects a fourth area **110** and identifies all weather information sources that are within the fourth area **110**. As shown, there are eleven weather information sources **112A-B**, **114A-C**, **116A-E**, and **118** in the fourth area **110**, satisfying the minimum number of weather information sources required by the weather application. In some embodiments, the weather information sources **112A-B**, **114A-C**, **116A-E** and **118** in the fourth area **110** comprise thermometers and submit temperature data to the weather application. The weather application receives the temperature data and generates a weather report for the user **102**. In some embodiments, weather information source **118** is a weather collection station or a home weather station.

[0024] In some embodiments, the weather application weights weather information (e.g., temperature data) received from different sources differently. For example, temperature data submitted by weather information source **118** may be weighted differently than temperature data submitted by weather information sources **116A-E**. In some embodiments, temperature data submitted by a newer weather information source is weighted differently than temperature data submitted by an older weather information source. In some embodiments, weather information sources have confidence values associated with their submitted weather information. The confidence values may be generated by the weather information sources that generate the temperature data and/or the weather application. In some embodiments, the confidence values are based on the accuracy of previously submitted weather information.

[0025] FIG. 2 shows a diagram of an illustrative table **200** for providing localized weather information, in accordance with some embodiments of the disclosure. In particular, table **200** can illustrate a table of entries contained in a database accessible by the user equipment device of user **102**. In some embodiments, table **200** reflects system **100** from FIG. 1.

[0026] Table **200** comprises eleven entries corresponding to different identifiers (**112A-B**, **114A-C**, **116A-E**, and **118**) where each identifier is associated with a different weather information source. For each identifier, table **200** indicates whether the identifier is within the threshold distance of the user equipment device of user **102**. In the shown embodiment, the weather application selects a threshold distance (e.g., third area **108**) and identifies all weather information sources that are within the threshold distance. Table **200** indicates that weather information sources **112A**, **112B**, **114A**, **114B**, and **114C** are all within the threshold distance. The threshold distance can be determined and/or updated using the techniques described herein. For example, if the weather application requires weather information from a minimum of ten weather information sources, the weather application can determine that the threshold distance needs to be updated to satisfy the condition. In an embodiment, table **200** is changed to reflect an updated threshold distance by indicating that identifiers **116A**, **116B**, **116C**, **116D**, **116E** and **118** are within the threshold distance.

[0027] For each identifier, table **200** indicates one or more categories (Temperature, Precipitation, and Brightness) of data points associated with the identifier. The categories correspond to weather information collected by one or more instruments onboard a weather information source. For example, the temperature measurement may be determined by a thermometer onboard a weather information source. In some embodiments, the precipitation measurement may be determined by one or more sensors onboard the weather information source (e.g., vehicles with rain-sensing windshield wipers). In some embodiments, the brightness measurement may be determined by one or more photoelectric sensors onboard the weather information source. Table **200** displays that weather information source **112A** submitted a temperature of 78 degrees Fahrenheit, precipitation at 0%, and a brightness of 5,050 lux. Table **200** is just one embodiment; any variation of organization, categories, measurements, and units can be used without departing from the systems and methods described herein.

[0028] The weather application processes the data points from the weather information sources within the threshold distance to generate a weather report for the user. As shown, five weather

information sources **112A**, **112B**, **114A**, **114B**, and **114C** are all within the threshold distance. In some embodiments, the weather application generates a weather report by averaging all the data points received from the weather information sources within the threshold distance. For example, to determine the local temperature, the weather application averages the five temperature data points from the weather information sources within the threshold distance. Any number of data processing techniques may be used to process data received from the weather information sources. In some embodiments, data received from the weather information sources may go through smoothing operations (e.g., moving averages, splines, etc.) to correct for variance.

[0029] Using data processing methods, the weather application may determine that some of the received data points should be ignored when generating the weather report. For example, the five temperature data points received from the weather information sources within the threshold distance are 78, 89, 76, 76, and 77. Four of the temperature data points from **112A**, **114A**, **114B**, and **114C** are all within two degrees of each other, while the fifth temperature data point from **112B** is more than ten degrees different than any of the other data points. In an embodiment, the weather application identifies the data point received from **112B** as an abnormality. This abnormality may be the result of weather information source **112B** being exposed to some variant (e.g., excessive sunlight), faulty instruments onboard weather information source **112B**, or some other irregularity. In some embodiments, the weather application ignores data points categorized as abnormal when generating weather reports. In another example, the weather information sources within the threshold distance submit four precipitation data points. Three of the data points from **112A**, **112B**, and **114B** indicate a 0% precipitation and one data point from **114C** indicates a 50% precipitation. In an embodiment, the weather application identifies the data point received from **114C** as an abnormality. This abnormality may be the result of weather information source **114C** being exposed to some variant (e.g., weather information source **114C** going through a puddle, or having the windshield washer turned on, etc.), faulty instruments onboard weather information source **114C**, or some other irregularity. In some embodiments, the weather application ignores data points categorized as abnormal when generating weather reports.

[0030] In some embodiments, when a weather information source is associated with an abnormal data point, the weather application will flag the weather information source that submitted the abnormal data point. For example, weather information source **112B** submitted the temperature data point of 89 degrees, which was determined to be abnormal. Weather information source **112B** also recorded precipitation and brightness data points. When the weather application averages the precipitation and/or brightness data points received from the weather information sources within the threshold distance to generate a weather report, the weather application weights the precipitation and brightness data points received from weather information source **112B** lower because it submitted a temperature data point that was determined to be abnormal. In some embodiments, all data points received from weather information source **112B** will be determined to be abnormal. In some embodiments, a flagged weather information source may have to submit a certain number of non-abnormal data points in order to not be flagged as abnormal. In some embodiments, once a flagged information source is flagged as abnormal, the weather application sends a message to check and/or repair the weather information source. In some embodiments, if a group of weather information sources share an attribute (e.g., the same model of vehicle) and they consistently submit data points in a similar abnormal manner (e.g., all submit abnormally high temperatures), the weather application flags other weather information sources that share that attribute without having to receive a first data point from the other weather information sources. In some embodiments, once a group of weather information sources that share an attribute (e.g., group of vehicles of the same model) are flagged, the weather application sends a message to indicate a possible manufacturing defect. In some embodiments, a weather information source that is flagged as abnormal cannot be used to satisfy minimum conditions required to generate a weather report. For example, if the weather application requires temperature data points from a minimum of five

weather information sources and one of the five information sources is flagged as abnormal, the weather application will determine that the minimum conditions to generate the weather report are not met. In some embodiments, the weather application updates the threshold distance to include at least five weather information sources that are not flagged as abnormal.

[0031] In some embodiments, some data points are not available as indicated by “N/A,” meaning “not applicable.” For example, weather information source **114A**'s precipitation and brightness data points are N/A. This may be because weather information source **114A** does not have instruments to measure these values or the instruments are damaged. In some embodiments, data points are indicated as N/A when the data points are stale. For example, the weather application can require data points to expire after a certain amount of time (e.g., one minute, five minutes, etc.) to ensure accurate data. The weather information sources may submit data points when requested or may automatically submit data points periodically (e.g., every 30 seconds). In some embodiments, a weather information source submits location data along with weather information. For example, if a mobile weather information source is a vehicle on the freeway, it may be in the threshold distance one minute and then be miles away in the next few minutes. In some embodiments, certain requirements (e.g., location data accompanying data points, data point refresh rate, etc.) are applied to all weather information sources, types of weather information sources, and/or to certain weather information sources. For example, stationary weather information sources may not be required to refresh their submitted weather information as often as mobile weather information sources. These requirements can be user selected, pre-programmed, and/or learned over time using a machine-learning algorithm.

[0032] In some embodiments, to generate the weather report, the weather application weights the data points in table **200** according to one or more factors. In some embodiments, a factor is the proximity of the weather information source to the location associated with the weather report. For example, the data submitted by weather information sources **112A** and **112B** may be weighted higher than the data submitted by weather information sources **114A**, **114B**, and **114C** if weather information sources **112A** and **112B** are closer to the location associated with the weather report than weather information sources **114A**, **114B**, and **114C**. In some embodiments, a factor affecting the weighting of data points is the type of weather information source. For example, data submitted by stationary weather information source **118** may be weighted differently than data submitted by a mobile weather information source **116A**. In some embodiments, data submitted by newer weather information sources may be weighted differently than temperature data submitted by older weather information sources. In some embodiments, weather information sources have confidence values associated with their submitted weather information. The confidence values may be generated by the weather information sources that generate the weather information and/or the weather application. In some embodiments, the confidence values are based on the accuracy of previously submitted weather information.

[0033] FIG. **3A** shows an illustrative diagram **300** of a user equipment device **302** generating a weather report, in accordance with some embodiments of the disclosure. Although a smartphone is used in this example, a user equipment device **302** may be any device or devices capable of displaying a weather report, such as televisions, laptops, tablets, smartphones, or similar such devices. In some embodiments, a user launches the weather application, and the weather application displays the weather report corresponding to the user's location **316**. The user's location may be determined using a global positioning system, cell tower data, Wi-Fi hotspot information, user profile information, or similar such information. The weather report displays the local temperature **304**, precipitation **306**, and conditions **308**. These values may be generated using the information in table **200** from FIG. **2** and may reflect system **100** from FIG. **1**.

[0034] In some embodiments, the user equipment device **302** displays an “Other Information” option **310**. A user can select the other information option **310** to view other weather-related information (e.g., windspeed, humidity, barometric pressure, and similar such information). In



some embodiments, the user equipment device **302** displays an “Adjust Threshold” option **312**. The user can select the adjust threshold option **312** to change the threshold distance used to generate the weather report. In some embodiments, the user can select the adjust threshold option **312** to change the location being used to generate the weather report. For example, the user can change from having a weather report based on the user's location to a weather report based on a different location. In some embodiments, the user equipment device **302** displays an “Update” option **314**. The user can select the update option **314** to cause the weather application to generate a fresh weather report. In some embodiments, the weather report is updated periodically (e.g., every 30 seconds) without the user's input.

[0035] FIG. **3B** shows an illustrative diagram **350** of a user equipment device **352** generating a weather report, in accordance with some embodiments of the disclosure. In some embodiments, a user launches the weather application on the user equipment device **352** and types in a location **366**, and the weather application displays the weather report corresponding to the location **366**. The weather report displays the temperature **354**, precipitation **356**, and conditions **358** associated with the location **366**. In some embodiments, the weather application makes recommendations (e.g., activities, clothing, etc.) based on the weather report. For example, when it is cold the weather application may recommend that the user “Bring a sweater.” In another example, when it is rainy the weather application may recommend to “Leave the baseball mitt at home and bring an umbrella.” In some embodiments, the weather application generates the weather report for a location and makes recommendations based on event and/or attraction information associated with the location, wherein the event and/or attraction information is received from a database. For example, the weather application recommends going to a baseball game based on the generated weather report indicating sunny weather conditions and event information indicating that a baseball game is occurring near the location **366**.

[0036] In some embodiments, the user equipment device **352** has access to a database comprising a calendar with scheduled events associated with the user, wherein one or more of the scheduled events is associated with a location. In some embodiments, the user equipment device **352** can generate a notification **368** related to the weather report. For example, if the user has a picnic scheduled in their calendar at a location **366** and the weather application determines that the weather conditions are not suitable for the scheduled activity, the notification **368** will ask if the user wants to reschedule. In some embodiments, the weather application generates the notification **368** at a predetermined time (e.g., 30 minutes) before the scheduled event. In some embodiments, the weather application generates the notification **368** when the weather application determines that weather conditions are changing or have changed. For example, if the weather application determines that weather conditions have changed from sunny to rainy at a location **366** near the time of a scheduled event (e.g., picnic), the weather application will generate the notification **368** that asks if the user wants to reschedule. In some embodiments, a user can input notifications to be triggered when certain weather conditions are met. For example, a user may request the weather application to generate a notification when the current temperature exceeds a threshold. In another example, the user may request the weather application to generate a notification when the weather is no longer rainy.

[0037] In some embodiments, the weather application will use a weather forecast in addition to the generated local weather report. For example, if the user has a picnic scheduled for 11:00 a.m. at a location **366** and the weather application, using the generated local weather report, determines that the weather conditions are not suitable (e.g., rainy) for the scheduled activity, the weather application can use the weather forecast to suggest a different time. In some embodiments, the weather forecast indicates that the non-suitable weather conditions (e.g., rain) will change at 2:00 p.m. The weather application can generate the notification **368** to ask if the user wants to reschedule the event and provides a recommended time (e.g., 2:00 p.m.) to reschedule using the weather forecast.

[0038] FIGS. 4-5 describe exemplary devices, systems, servers, and related hardware for providing localized weather information, in accordance with one embodiment. In the system **400**, there can be more than one user equipment device **402** but only one is shown in FIG. 4 to avoid overcomplicating the drawing. In addition, a user may utilize more than one type of user equipment device and more than one of each type of user equipment device. In an embodiment there may be paths between user equipment devices, so that the devices may communicate directly with each other via communications paths, as well as other short-range point-to-point communications paths, such as USB cables, IEEE 1394 cables, wireless paths (e.g., Bluetooth, infrared, IEEE 802-11x, etc.), or other short-range communication via wired or wireless paths. BLUETOOTH is a certification mark owned by Bluetooth SIG, INC. In an embodiment, the user equipment devices may also communicate with each other directly through an indirect path via the communications network **406**.

[0039] The user equipment devices may be coupled to communications network **406**. Namely, the user equipment device **402** is coupled to the communications network **406** via communications path **404**. The communications network **406** may be one or more networks including the Internet, a mobile phone network, mobile voice or data network (e.g., a 4G, 5G, or LTE network), cable network, public switched telephone network, or other types of communications network or combinations of communications networks. The path **404** may separately or in together with other paths include one or more communications paths, such as, a satellite path, a fiber-optic path, a cable path, a path that supports Internet communications (e.g., IPTV), free-space connections (e.g., for broadcast or other wireless signals), or any other suitable wired or wireless communications path or combination of such paths. In one embodiment path **404** can be a wireless path. Communication with the user equipment device may be provided by one or more communications paths but is shown as a single path in FIG. 4 to avoid overcomplicating the drawing.

[0040] The system **400** also includes weather information sources **412**, and server **414**, which can be coupled to any number of databases providing information to the user equipment devices. The weather information sources **412** represent any computer-accessible sources of weather information, such as weather-measuring devices, storage for weather information, or, similar such information. The server **414** may store and execute various software modules for providing localized weather information functionality. In some embodiments, the user equipment device **402**, weather information sources **412**, and server **414** may store metadata associated with weather information and/or weather information requests.

[0041] FIG. 5 shows a generalized embodiment of a user equipment device **500**, in accordance with one embodiment. In an embodiment, the user equipment device **500**, is the same user equipment device **402** of FIG. 4. The user equipment device **500** may receive content and data via input/output (I/O) path **502**. The I/O path **502** may provide audio content (e.g., broadcast programming, on-demand programming, Internet content, content available over a local area network (LAN) or wide area network (WAN), and/or other content) and data to control circuitry **504**, which includes processing circuitry **506** and a storage **508**. The control circuitry **504** may be used to send and receive commands, requests, and other suitable data using the I/O path **502**. The I/O path **502** may connect the control circuitry **504** (and specifically the processing circuitry **506**) to one or more communications paths. I/O functions may be provided by one or more of these communications paths but are shown as a single path in FIG. 5 to avoid overcomplicating the drawing.

[0042] The control circuitry **504** may be based on any suitable processing circuitry such as the processing circuitry **506**. As referred to herein, processing circuitry should be understood to mean circuitry based on one or more microprocessors, microcontrollers, digital signal processors, programmable logic devices, field-programmable gate arrays (FPGA s), application-specific integrated circuits (ASICs), etc., and may include a multi-core processor (e.g., dual-core, quad-core, hexa-core, or any suitable number of cores) or supercomputer. In some embodiments, processing circuitry may be distributed across multiple separate processors or processing units, for

example, multiple of the same type of processing units (e.g., two Intel Core i7 processors) or multiple different processors (e.g., an Intel Core i5 processor and an Intel Core i7 processor). The providing of weather information functionality can be at least partially implemented using the control circuitry **504**. The providing of weather information functionality described herein may be implemented in or supported by any suitable software, hardware, or combination thereof. The providing of weather information can be implemented on user equipment, on remote servers, or across both.

[0043] In client-server-based embodiments, the control circuitry **504** may include communications circuitry suitable for communicating with one or more servers that may at least implement the described providing of localized weather information. The instructions for carrying out the above-mentioned functionality may be stored on the one or more servers. Communications circuitry may include a cable modem, an integrated service digital network (ISDN) modem, a digital subscriber line (DSL) modem, a telephone modem, Ethernet card, or a wireless modem for communications with other equipment, or any other suitable communications circuitry. Such communications may involve the Internet or any other suitable communications networks or paths. In addition, communications circuitry may include circuitry that enables peer-to-peer communication of user equipment devices, or communication of user equipment devices in locations remote from each other (described in more detail below).

[0044] Memory may be an electronic storage device provided as the storage **508** that is part of the control circuitry **504**. As referred to herein, the phrase “electronic storage device” or “storage device” should be understood to mean any device for storing electronic data, computer software, or firmware, such as random-access memory, read-only memory, hard drives, optical drives, digital video disc (DVD) recorders, compact disc (CD) recorders, BLU-RAY disc (BD) recorders, BLU-RAY 3D disc recorders, digital video recorders (DVR, sometimes called a personal video recorder, or PVR), solid-state devices, quantum storage devices, gaming consoles, gaming media, or any other suitable fixed or removable storage devices, and/or any combination of the same. The storage **508** may be used to store various types of content described herein. Nonvolatile memory may also be used (e.g., to launch a boot-up routine and other instructions). Cloud-based storage, described in relation to FIG. **4**, may be used to supplement the storage **508** or instead of the storage **508**.

[0045] The control circuitry **504** may include audio generating circuitry and tuning circuitry, such as one or more analog tuners, audio generation circuitry, filters or any other suitable tuning or audio circuits or combinations of such circuits. The control circuitry **504** may also include scaler circuitry for upconverting and down converting content into the preferred output format of the user equipment device **500**. The control circuitry **504** may also include digital-to-analog converter circuitry and analog-to-digital converter circuitry for converting between digital and analog signals. The tuning and encoding circuitry may be used by the user equipment device **500** to receive and to display, to play, or to record content. The circuitry described herein, including, for example, the tuning, audio generating, encoding, decoding, encrypting, decrypting, scaler, and analog/digital circuitry, may be implemented using software running on one or more general purpose or specialized processors. If the storage **508** is provided as a separate device from the user equipment device **500**, the tuning and encoding circuitry (including multiple tuners) may be associated with the storage **508**.

[0046] The user may utter instructions to the control circuitry **504**, which are received by the microphone **516**. The microphone **516** may be any microphone (or microphones) capable of detecting human speech. The microphone **516** is connected to the processing circuitry **506** to transmit detected voice commands and other speech thereto for processing. In some embodiments, voice assistants (e.g., Siri, Alexa, Google Home and similar such voice assistants) receive and process the voice commands and other speech.

[0047] The user equipment device **500** may optionally include an interface **510**. The interface **510** may be any suitable user interface, such as a remote control, mouse, trackball, keypad, keyboard,

touch screen, touchpad, stylus input, joystick, or other user input interfaces. A display **512** may be provided as a stand-alone device or integrated with other elements of the user equipment device **500**. For example, the display **512** may be a touchscreen or touch-sensitive display. In such circumstances, the interface **510** may be integrated with or combined with the microphone **516**. When the interface **510** is configured with a screen, such a screen may be one or more of a monitor, a television, a liquid crystal display (LCD) for a mobile device, active matrix display, cathode ray tube display, light-emitting diode display, organic light-emitting diode display, quantum dot display, or any other suitable equipment for displaying visual images. In some embodiments, the interface **510** may be HDTV-capable. In some embodiments, the display **512** may be a 3D display. The speaker (or speakers) **514** may be provided as integrated with other elements of user equipment device **500** or may be a stand-alone unit. In some embodiments, the display **512** may be outputted through speaker **514**.

[0048] The user equipment device **500** of FIG. **5** can be implemented in system **400** of FIG. **4** as user equipment device **402**, but any other type of user equipment suitable for providing localized weather information may be used. For example, user equipment devices such as television equipment, computer equipment, wireless user communication devices, or similar such devices may be used. User equipment devices may be part of a network of devices. Various network configurations of devices may be implemented and are discussed in more detail below.

[0049] FIG. **6** is an illustrative flowchart of a process **600** for providing localized weather information, in accordance with some embodiments of the disclosure. Process **600**, and any of the following processes, may be executed by control circuitry **504** on a user equipment device **500**. In some embodiments, control circuitry **504** may be part of a remote server separated from the user equipment device **500** by way of a communications network or distributed over a combination of both. In some embodiments, instructions for executing process **600** may be encoded onto a non-transitory storage medium (e.g., the storage **508**) as a set of instructions to be decoded and executed by processing circuitry (e.g., the processing circuitry **506**). Processing circuitry may, in turn, provide instructions to other sub-circuits contained within control circuitry **504**, such as the encoding, decoding, encrypting, decrypting, scaling, analog/digital conversion circuitry, and the like. It should be noted that any of the process, or any step thereof, could be performed on, or provided by, any of the devices shown in FIGS. **1-5**. Although the processes are illustrated and described as a sequence of steps, it is contemplated that various embodiments of the processes may be performed in any order or combination and need not include all the illustrated steps.

[0050] At **602**, the user equipment device **500**, by control circuitry **504**, determines a location that is used to generate a weather report. In some embodiments, the location is the location of the user equipment device **500**. The location of the user equipment device **500** can be determined using a global positioning system, cell tower data, Wi-Fi hotspot information, user profile information, or similar such information. In some embodiments, a location is inputted by a user, where the inputted location is different than the current location of the user equipment device. For example, a user in Los Angeles can select the location “1234 Fifth Ave NE, Seattle WA,” and the user equipment device **500** displays the weather report corresponding to that location. In some embodiments, the user equipment device **500** provides selectable locations. In some embodiments, the user equipment device **500** infers a location based on user behavior and/or information in a database.

[0051] At **604**, the user equipment device **500**, by control circuitry **504**, identifies a plurality of weather information sources within a threshold distance of the location determined in step **602**. In some embodiments, when determining vehicles that are within a threshold distance of the location, the user equipment device **500** first determines the threshold distance. In some embodiments, the user equipment device **500** uses a standard threshold distance (e.g., within one mile from the location) for identifying a plurality of weather information sources. To identify the weather information sources within the threshold distance, the user equipment device **500** can access a database containing locations of weather information sources and select weather information

sources that are within a threshold distance of the determined location. In some embodiments, the user equipment device **500** submits the determined location to a database and the database determines a threshold distance and identifies weather information sources within the threshold distance.

[0052] In some embodiments, the user equipment device **500** determines the threshold distance based on the number of weather information sources required to generate a weather report. For example, the user equipment device **500** may require weather information from at least five weather information sources within the threshold distance to generate a weather report. If a first threshold distance (e.g., within one mile from the location) is used and the user equipment device **500** determines that there are only three vehicles within the one-mile threshold distance, then the user equipment device **500** will incrementally update the threshold distance until a minimum number of vehicles are within the threshold distance. For example, the user equipment device **500** increases the threshold distance from one mile to two miles and determines that eight vehicles are located within the new threshold distance. The user equipment device **500** uses the new threshold distance of two miles because the two-mile threshold distance comprises the necessary number of weather information sources.

[0053] At **606**, the user equipment device **500**, by control circuitry **504**, receives weather information from the plurality of weather information sources. In some embodiments, the user equipment device **500** receives weather information (e.g., a plurality of data points) from each of the weather information sources identified in step **604**. For example, each weather information source within the threshold distance submits weather information to the user equipment device **500**. In some embodiments, each weather information source within the threshold distance submits weather information to a database, and the user equipment device **500** receives weather information from the weather information sources using the database. In some embodiments, the weather information sources submit weather information when requested or may automatically submit weather information periodically (e.g., every 30 seconds).

[0054] At **608**, the user equipment device **500**, by control circuitry **504**, generates a weather report using the weather information received in step **606**. In some embodiments, the weather information includes a plurality of data points, where the data points correspond to weather information collected by the weather information sources using one or more instruments. For example, a first weather information source within the threshold distance may send a first data point that indicates the temperature determined by the thermometer onboard the weather information source. In some embodiments, data points may correspond to brightness determined by a photoelectric sensor onboard a weather information source and/or precipitation determined by one or more sensors onboard a weather information source. Data points can correspond to any information related to weather conditions such as temperatures, humidity, cloud cover, precipitation, wind speed, barometric pressure, and similar such information.

[0055] In some embodiments, when generating the weather report the user equipment device **500** uses weighted averages where each data point is weighted depending on a number of factors. For example, data points received from weather information sources that are closer to the user will be weighted higher than data points received from weather information sources that are farther away from the user. In some embodiments, the user equipment device **500** identifies abnormalities in the data received from the weather information sources before generating the weather report. In some embodiments, data received from the weather information sources may go through smoothing operations (e.g., moving averages, splines, etc.) to correct for variance. In some embodiments, after generating one or more weather reports, the user equipment device **500** can determine weather trends and weather regions (e.g., isothermal lines). The user equipment device **500** can use the weather trends and weather regions to generate more accurate weather reports in the future. In some embodiments, the user equipment device **500** determines that weather trends and weather regions depend on time of day, time of year, and/or similar such temporal categories. In some

embodiments, the one or more weather reports may be used in and/or generated by fleet management systems.

[0056] In some embodiments, the user equipment device **500** displays the weather report for the user. In some embodiments, displaying the weather report to the user is done visually and/or audibly. In some embodiments, the user equipment device **500** uses the weather report to generate one or more notifications for the user. For example, if the user has a picnic scheduled in their calendar at the determined location and the user equipment device **500** determines, using the weather report, that the weather conditions are not suitable for the scheduled activity, the user equipment device **500** will generate a notification suggesting that the user reschedule the event. In another example, the user equipment device **500** determines, using the weather report, that the weather conditions are rainy and generates a notification to the user recommending the user to bring an umbrella.

[0057] FIG. **7** is an illustrative flowchart of a process **700** for providing localized weather information, in accordance with some embodiments of the disclosure.

[0058] At **702**, the user equipment device **500**, by control circuitry **504**, receives an input to generate a weather report. In some embodiments, a user generates an input when the user selects an application on the user equipment device **500**. In some embodiments, a user generates an input when a user inputs a search. For example, a user may input “find a nearby beach where it is sunny, but the temperature is below 85 degrees,” and the user equipment device **500** generates weather reports and determines which weather report correlates to the user's input. In some embodiments, the input is generated in response to a scheduled event. For example, if the user has an event scheduled for 2:00 p.m. the user equipment device **500** receives an input to generate a weather report at 2:00 p.m. In another example, user equipment device **500** receives an input to generate a weather report at some predetermined time (e.g., 30 minutes) before the scheduled event. In some embodiments, the user equipment device **500** predicts inputs from users. For example, the user equipment device **500** can access a database and determine that a baseball game is scheduled for 7:00 p.m. and can further determine that many users will request weather reports for the baseball game. The user equipment device **500** can generate a weather report for the location of the baseball game before any user requests a weather report. In some embodiments, an input is generated periodically. For example, the user equipment device **500** may receive an input to generate a weather report every hour.

[0059] At **704**, the user equipment device **500**, by control circuitry **504**, determines a location for the weather report. In some embodiments, the location is the location of the user equipment device **500**. The location of the user equipment device **500** can be determined using a global positioning system, cell tower data, Wi-Fi hotspot information, user profile information, or similar such information. In some embodiments, the location is a location inputted by a user, where the inputted location is different than the current location of the user. In some embodiments, the user equipment device **500** provides selectable locations. In some embodiments, the user equipment device **500** infers a location based on user behavior and/or information in a database.

[0060] At **706**, the user equipment device **500**, by control circuitry **504**, determines a threshold distance for the weather report. In some embodiments, the user equipment device **500** uses a standard threshold distance (e.g., within one mile from the location). In some embodiments, the user equipment device **500** determines the threshold distance based on the number of weather information sources in an area. In some embodiments, the user equipment device **500** submits the determined location to a database and the database determines a threshold distance. In some embodiments, the user equipment device **500** determines the threshold distance based on the number of weather information sources required to generate a weather report. For example, the user equipment device **500** may require weather information from at least five weather information sources within the threshold distance to generate a weather report. If a first threshold distance (e.g., within one mile from the location) is used and the user equipment device **500** determines that there

are only three vehicles within the one-mile threshold distance, then the user equipment device **500** will incrementally update the threshold distance until a minimum number of vehicles are within the threshold distance. For example, the user equipment device **500** increases the threshold distance to two miles and determines that eight vehicles are located within the new threshold distance. The user equipment device **500** uses the new threshold distance of two miles because the two-mile threshold distance comprises the necessary number of weather information sources.

[0061] At **708**, the user equipment device **500**, by control circuitry **504**, identifies a plurality of weather information sources within the threshold distance determined in step **706**. To identify the weather information sources within the threshold distance, the user equipment device **500** can access a database containing locations of weather information sources and select weather information sources that are within the threshold distance of the location. In some embodiments, the user equipment device **500** submits the determined location and the determined threshold distance to a database and the database identifies weather information sources within the threshold distance.

[0062] At **710**, the user equipment device **500**, by control circuitry **504**, receives weather information from the plurality of weather information sources. In some embodiments, the user equipment device **500** receives weather information from each of the weather information sources identified in step **708**. For example, each weather information source within the threshold distance submits weather information to the user equipment device **500**. In some embodiments, each weather information source within the threshold distance submits weather information to a database, and the user equipment device **500** receives weather information from the weather information sources using the database. In some embodiments, the weather information sources submit weather information when requested or may automatically submit weather information periodically (e.g., every 30 seconds).

[0063] At **712**, the user equipment device **500**, by control circuitry **504**, processes the weather information received from the weather information sources in step **710**. In some embodiments, the user equipment device **500** translates weather information received from weather information sources into one or more data points. In some embodiments, the user equipment device **500** categorizes the one or more data points. For example, data points related to temperature are categorized as temperature data, while data points relating to precipitation are categorized as precipitation data. In some embodiments, the user equipment device **500** may assign different weights to each data point where the weight depends on a number of factors. For example, data points received from weather information sources that are closer to the location determined in step **704** will be weighted higher than data points received from weather information sources that are farther away from the location determined in step **704**. In some embodiments, the user equipment device **500** identifies abnormal data points received from the weather information sources. In some embodiments, data received from the weather information sources goes through smoothing operations (e.g., moving averages, splines, etc.) to correct for variance.

[0064] At **714**, the user equipment device **500**, by control circuitry **504**, generates a weather report using the weather information processed in step **712**. In some embodiments, when generating the weather report the user equipment device **500** uses the weights assigned to the data points in step **712**. In some embodiments, when generating the weather report the user equipment device **500** ignores data points that were identified as abnormal in step **712**. In some embodiments, the user equipment device **500** displays the generated weather report for the user. In some embodiments, displaying the weather report to the user is done visually and/or audibly. In some embodiments, the user equipment device **500** generates multiple weather reports for multiple locations where the multiple weather reports are used for searches and/or route planning. For example, if a user has to go to multiple locations (e.g., to make deliveries) then the user equipment device **500** generates multiple weather reports for the multiple locations and recommends an optimal route. In one example, if the weather reports indicate that some of the locations have rain and some of the

locations do not have rain, then a device can recommend a route that begins with the locations that do not have rain and leaves the locations with rain for the end, in case the rain stops. In another example, if a user makes temperature-sensitive deliveries (e.g., food, flowers, and/or similar such products) to multiple locations, the user equipment device **500** generates multiple weather reports for the multiple locations and recommends an optimal route.

[0065] FIG. **8** is an illustrative flowchart of a process **800** for determining a threshold distance when providing localized weather information, in accordance with some embodiments of the disclosure.

[0066] At **802**, the user equipment device **500**, by control circuitry **504**, determines a location. In some embodiments, the location is the location of the user equipment device **500**. The location of the user equipment device **500** can be determined using a global positioning system, cell tower data, Wi-Fi hotspot information, user profile information, or similar such information. In some embodiments, the location is the location inputted by a user, where the inputted location is different than the current location of the user. In some embodiments, the user equipment device **500** provides selectable locations. In some embodiments, the user equipment device **500** infers a location based on user behavior and/or information in a database.

[0067] At **804**, the user equipment device **500**, by control circuitry **504**, selects a threshold. In some embodiments, the user equipment device **500** uses a standard threshold distance (e.g., within one mile from the location). A threshold distance or threshold can be any shape, pattern, and/or zone used to categories weather information sources. In some embodiments, the threshold distance is based on a number of factors.

[0068] In some embodiments, the determined location is a factor affecting the threshold distance. For example, in populated areas, the starting threshold distance is smaller than in rural areas, because there are more weather information sources in populated areas compared to rural areas. In some embodiments, the climate of the determined location is a factor affecting the threshold distance. For example, some locations are known to have microclimates where weather can vary dramatically between two sublocations despite the two sublocations being relatively close to each other. In this example, the starting threshold distance will be smaller in a location with microclimates because increased granularity is required. In another example, locations with weather affecting driving conditions will have a larger starting threshold distance because fewer vehicles will be on the road. The larger starting threshold distance helps ensure there is enough data to generate an accurate weather report.

[0069] In some embodiments, the time of day, season, and/or year are factors affecting the threshold distance. For example, some locations have increased microclimates depending on the time of day, season, and/or year. In some embodiments, the number of weather information sources is affected by the time of day, season, and/or year. For example, during rush hour there may be more vehicles on the road in a given location, so the starting threshold distance can be smaller because there is plenty of data from the weather information sources (e.g., vehicles). In some embodiments, fewer people drive in a given location during night hours so there are fewer weather information sources. Accordingly, the starting threshold distance must be larger to ensure there is enough data to generate an accurate weather report.

[0070] In some embodiments, user conditions are a factor affecting the threshold distance. For example, if the user equipment device **500** determines that the user is moving, then the starting threshold will be larger compared to if the user is stationary. A user driving in a car may require a larger starting threshold because a hyper granular weather report will not be helpful to the user. For example, a weather report indicating the weather conditions within one mile of a user is unnecessary if the user is driving seventy miles per hour on the freeway. In some embodiments, the user equipment device **500** determines the direction the user is moving to refine the weather report. For example, after determining that the user is moving north, the user equipment device **500** determines the starting threshold distance to only include areas to the north of the user.



[0071] At **806**, the user equipment device **500**, by control circuitry **504**, identifies weather information sources within the threshold distance. To identify the weather information sources within the threshold distance, the user equipment device **500** can access a database containing locations of weather information sources and select weather information sources that are within the threshold distance of the location. In some embodiments, the user equipment device **500** submits the determined location and the determined threshold distance to a database, and the database identifies weather information sources within the threshold distance.

[0072] At **808**, the user equipment device **500**, by control circuitry **504**, determines if there are a minimum number of weather information sources within the determined threshold distance. In some embodiments, there is a minimum number (e.g., five) of weather information sources required to generate a weather report. If the user equipment device **500** determines that there are a minimum number of weather information sources, then the process **800** continues to step **810**. If the user equipment device **500** determines that there are not the minimum number of weather information sources, then the process continues to step **812**. In some embodiments, the user equipment device **500** determines the minimum number of weather information sources using the same or similar factors to the factors affecting threshold distance described above in step **804**. For example, the user equipment device **500** can determine that fewer weather information sources are required at nighttime when there are fewer users driving vehicles. In some embodiments, there is no minimum number of weather information sources, and the process **800** continues to step **810**.

[0073] At **812**, the user equipment device **500**, by control circuitry **504**, updates the threshold determined in step **804**. In some embodiments, the user equipment device **500** incrementally updates the threshold distance. For example, if the starting threshold distance is one mile from the determined location, the user equipment device **500** can increase the distance to two miles from the determined location. In some embodiments, the updated threshold distance covers a larger area than the original threshold distance. In some embodiments, the updated threshold distance overlaps with the area covered by the original threshold distance. In some embodiments, the updated threshold distance encompasses the entire area covered by the original threshold distance. In some embodiments, the user equipment device **500** updates the threshold distance based on predetermined zones, incremental increases, or similar such parameters. After the threshold distance is updated, the process **800** proceeds to step **806**.

[0074] In some embodiments, the user equipment device **500** updates the threshold distance using one or more factors. In some embodiments, a factor is a predefined multiplier, where the area covered by the original threshold distance is multiplied by the multiplier (e.g., doubled, tripled, etc.). In some embodiments, the one or more factors used to determine the updated threshold are similar or the same as the factors affecting the selecting of the original threshold distance as described above in step **804**. For example, at rush hour, a user equipment device **500** updates a first threshold distance from a one-mile radius to a two-mile radius. During night hours, the user equipment device **500** will update the first threshold distance from a one-mile radius to a four-mile radius, because there are fewer users driving vehicles so there are fewer weather information sources.

[0075] In some embodiments, the user equipment device **500** uses the number of identified weather information sources to update the threshold. For example, if the user equipment device **500** identifies, using a database, that a minimum number of vehicles are located within a second threshold distance, where the second threshold distance is different than the threshold distance determined in step **804**, the user equipment device **500** updates the threshold distance to be the second threshold distance. In another example, if the user equipment device **500** identifies very few or zero weather information sources in the original threshold distance, then the user equipment device may **500** increase the first threshold distance from a one-mile radius to a five-mile radius. If the equipment device **500** identifies a significant number (e.g., 95% of the minimum number of weather information sources required to generate a weather report) of weather information sources

in the original threshold distance, then the user equipment device may **500** increase the first threshold distance from a one-mile radius to a one and a half-mile radius.

[0076] At **810**, the user equipment device **500**, by control circuitry **504**, receives weather information from the identified weather information sources. In some embodiments, the user equipment device **500** receives weather information (e.g., a plurality of data points) from each of the weather information sources identified in step **806**. For example, each weather information source within the threshold distance submits weather information to the user equipment device **500**. In some embodiments, each weather information source within the threshold distance submits weather information to a database, and the user equipment device **500** receives weather information from the weather information sources using the database. In some embodiments, the weather information sources submit weather information when requested or may automatically submit weather information periodically (e.g., every 30 seconds).

[0077] FIG. **9** is an illustrative flowchart of a process **900** for generating a localized weather report, in accordance with some embodiments of the disclosure.

[0078] At **902**, the user equipment device **500**, by control circuitry **504**, receives weather information from weather information sources within a threshold distance. In some embodiments, each weather information source within the threshold distance submits weather information to the user equipment device **500**. In some embodiments, each weather information source within the threshold distance submits weather information to a database, and the user equipment device **500** receives weather information from the weather information sources using the database. In some embodiments, the weather information sources submit weather information when requested or may automatically submit weather information periodically (e.g., every 30 seconds).

[0079] At **904**, the user equipment device **500**, by control circuitry **504**, determines data points from the received weather information. In some embodiments, the user equipment device **500** translates weather information received from the weather information sources into one or more data points. In some embodiments, the user equipment device **500** categorizes the one or more data points. For example, data points related to temperature are categorized as temperature data, while data points relating to precipitation are categorized as precipitation data. In some embodiments, the user equipment device **500** translates different types of data points into a standard format. For example, different weather information stations (e.g., vehicles) may have different formats used for reporting weather information. The user equipment device **500** translates the different types of weather information formats into a standard format, which is used to generate the weather report.

[0080] At **906**, the user equipment device **500**, by control circuitry **504**, identifies abnormal data points from the data points determined in step **904**. In some embodiments, the user equipment device **500**, using data processing methods, determines if any of the data points received from the weather information sources are abnormal. For example, the user equipment device **500** receives five temperature data points from the weather information sources within the threshold distance. Four of the temperature data points are all within an acceptable range of one another (e.g., two degrees) while the fifth temperature data point is more than ten degrees different than any of the other data points. The user equipment device **500** identifies the fifth data point as abnormal. In some embodiments, this abnormality may be the result of the weather information source that submitted the data point being exposed to some variant (e.g., excessive sunlight), faulty instruments, and/or some other irregularity. In some embodiments, the user equipment device **500** does not use data points categorized as abnormal when generating weather reports. In some embodiments, the user equipment device **500** requests the weather information source to submit a new data point and checks if the new data point is within an acceptable range.

[0081] In some embodiments, when a weather information source is associated with an abnormal data point, the user equipment device **500** flags the weather information source that submitted the abnormal data point. In some embodiments, data points submitted by a flagged weather information source are not used when generating a weather report. For example, if the flagged

weather information source also submits data points for other categories (e.g., precipitation, brightness, etc.) these data points are also flagged as abnormal and are not used when generating a weather report. In some embodiments, data points submitted by a flagged weather information source are weighted differently in step **908**. In some embodiments, a flagged weather information source must submit a certain number of non-abnormal data points in order to no longer be flagged as abnormal. In some embodiments, a weather information source that is flagged as abnormal cannot be used to satisfy minimum conditions required to generate a weather report. For example, if the user equipment device **500** requires temperature data points from a minimum of five weather information sources and one of the five information sources is flagged as abnormal, the user equipment device **500** will determine that the minimum conditions to generate the weather report are not met.

[0082] At **908**, the user equipment device **500**, by control circuitry **504**, assigns weights to the data points determined in step **904**. In some embodiments, to generate the weather report, the user equipment device **500** weights the data points according to one or more factors. In some embodiments, a factor is the proximity of the weather information source to the location associated with the weather report. For example, data submitted by weather information sources closer to the location associated with the weather report are weighted higher than data submitted by weather information sources that are farther away from the location associated with the weather report. In some embodiments, a factor affecting the weighting of data points is the type of weather information source. For example, temperature data submitted by a stationary weather information source is weighted differently than temperature data submitted by a mobile weather information source. In some embodiments, data submitted by newer weather information sources are weighted differently than data submitted by older weather information sources. In some embodiments, data submitted by flagged weather information sources are weighted differently than data submitted by non-flagged weather information sources. In some embodiments, weather information sources have confidence values associated with their submitted weather information. The confidence values may be generated by the weather information source that generates the weather information and/or by the user equipment device **500**. In some embodiments, the confidence values are based on the accuracy of previously submitted weather information.

[0083] In some embodiments, the user equipment device **500** uses a feedback loop for training and/or calibrating the weighting of data points. For example, the weather report generated at step **910** may indicate that temperature at the location is likely to be 75 degrees. The user equipment device **500** can determine the actual temperature at the location using a trusted weather information source (e.g., the vehicle the user drove to the location). If the user equipment device **500** determines that the actual temperature is higher or lower than 75 degrees, the user equipment device **500** adjusts the weights for either particular weather information sources or locations of weather information sources (e.g., weather information sources to the south are more accurate than weather information sources to the north) used to generate the weather report.

[0084] At **910**, the user equipment device **500**, by control circuitry **504**, generates the weather report using the data points weighted in step **908**. In some embodiments, when generating the weather report the user equipment device **500** ignores data points that were identified as abnormal in step **906**. In some embodiments, the user equipment device **500** uses a weighted average to generate the weather report for the user. In some embodiments, the user equipment device **500** displays the generated weather report for the user. In some embodiments, displaying the weather report to the user is done visually and/or audibly.

[0085] It is contemplated that some suitable steps or suitable descriptions of FIGS. **6-9** may be used with other suitable embodiments of this disclosure. In addition, some suitable steps and descriptions described in relation to FIGS. **6-9** may be implemented in alternative orders or in parallel to further the purposes of this disclosure. For example, some suitable steps may be performed in any order or in parallel or substantially simultaneously to reduce lag or increase the

speed of the system or method. Some suitable steps may also be skipped or omitted from the process. Furthermore, it should be noted that some suitable devices or equipment discussed in relation to FIGS. 1-5 could be used to perform one or more of the steps in FIGS. 6-9.

[0086] The processes discussed above are intended to be illustrative and not limiting. One skilled in the art would appreciate that the steps of the processes discussed herein may be omitted, modified, combined, and/or rearranged, and any additional steps may be performed without departing from the scope of the invention. More generally, the above disclosure is meant to be exemplary and not limiting. Only the claims that follow are meant to set bounds as to what the present invention includes. Furthermore, it should be noted that the features and limitations described in any one embodiment may be applied to any other embodiment herein, and flowcharts or examples relating to one embodiment may be combined with any other embodiment in a suitable manner, done in different orders, or done in parallel. In addition, the systems and methods described herein may be performed in real time. It should also be noted that the systems and/or methods described above may be applied to, or used in accordance with, other systems and/or methods.

## Claims

1. A method comprising: receiving an event associated with a user profile, wherein the event corresponds to a first location and a first time period; receiving a plurality of data points, wherein each data point of the plurality of data points corresponds to at least one weather information source of a plurality of weather information sources; generating a weather report, wherein: the plurality of data points are used to generate the weather report; and the weather report comprises a weather condition; and generating for display a notification on a device associated with the user profile based, at least in part, on receiving the event and generating the weather report, wherein the notification indicates the weather condition.
2. The method of claim 1, wherein the weather condition comprises at least one of a temperature indicator, a humidity indicator, a cloud cover indicator, a precipitation indicator, a wind speed indicator, and a barometric pressure indicator.
3. The method of claim 2, further comprising: determining a characteristic associated with the event; and determining that the weather condition is not suitable for the event based, at least in part, on the characteristic associated with the first event, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition is not suitable for the event.
4. The method of claim 2, further comprising: receiving a trigger related to the event; and determining that the weather condition satisfies the trigger related to the event, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition satisfies the trigger related to the event.
5. The method of claim 2, wherein the notification is generated for display at a predetermined time before the first time period.
6. The method of claim 5, further comprising determining, at the predetermined time, that the weather report is the most recent weather report.
7. The method of claim 6, further comprising receiving the predetermined time from the device associated with the user profile.
8. The method of claim 2, further comprising: receiving a weather forecast related to the first location for the first time period; and determining that the weather condition of the weather report is different than one or more weather conditions of the weather forecast, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition of

the weather report is different than one or more weather conditions of the weather forecast.

**9.** The method of claim 2, further comprising: accessing a previous weather report, wherein the previous weather report comprises a previous weather condition; and determining that the weather condition of the weather report is different than the previous weather condition of the previous weather report, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition of the weather report is different than the previous weather condition of the previous weather report.

**10.** The method of claim 2, further comprising determining that the weather condition of the weather report exceeds a threshold, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition of the weather report exceeds the threshold.

**11.** The method of claim 10, further comprising receiving the threshold from the device associated with the user profile.

**12.** The method of claim 1, wherein the notification suggests rescheduling the event.

**13.** An apparatus comprising: control circuitry; and at least one memory including computer program code for one or more programs, the at least one memory and the computer program code configured to, with the control circuitry, cause the apparatus to perform at least the following: receive an event associated with a user profile, wherein the event corresponds to a first location and a first time period; receive a plurality of data points, wherein each data point of the plurality of data points corresponds to at least one weather information source of a plurality of weather information sources; generate a weather report, wherein: the plurality of data points are used to generate the weather report; and the weather report comprises a weather condition; and generate for display on a device a notification associated with the user profile based, at least in part, on receiving the event and generating the weather report, wherein the notification indicates the weather condition.

**14.** The apparatus of claim 13, wherein the apparatus is further caused to: determine a characteristic associated with the event; and determine that the weather condition is not suitable for the event based, at least in part, on the characteristic associated with the first event, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition is not suitable for the event.

**15.** The apparatus of claim 13, wherein the apparatus is further caused to: receive a trigger related to the event; and determine that the weather condition satisfies the trigger related to the event, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition satisfies the trigger related to the event.

**16.** The apparatus of claim 15, wherein the apparatus is further caused to: receive a predetermined time before the first time period from the device associated with the user profile; and determine, at the predetermined time, that the weather report is the most recent weather report, wherein the notification is generated for display at the predetermined time.

**17.** The apparatus of claim 13, wherein the apparatus is further caused to: receive a weather forecast related to the first location for the first time period; and determine that the weather condition of the weather report is different than one or more weather conditions of the weather forecast, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition of the weather report is different than one or more weather conditions of the weather forecast.

**18.** The apparatus of claim 13, wherein the apparatus is further caused to access a previous weather report, wherein the previous weather report comprises a previous weather condition; and determine

that the weather condition of the weather report is different than the previous weather condition of the previous weather report, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition of the weather report is different than the previous weather condition of the previous weather report.

**19.** The apparatus of claim 13, wherein the apparatus is further caused to determine that the weather condition of the weather report exceeds a threshold, wherein the notification is generated for display on the device associated with the user profile based, at least in part, on receiving the event, generating the weather report, and determining that the weather condition of the weather report exceeds the threshold.

**20.** A non-transitory computer-readable medium having instructions encoded thereon that, when executed by control circuitry, cause the control circuitry to: receive an event associated with a user profile, wherein the event corresponds to a first location and a first time period; receive a plurality of data points, wherein each data point of the plurality of data points corresponds to at least one weather information source of a plurality of weather information sources; generate a weather report, wherein: the plurality of data points are used to generate the weather report; and the weather report comprises a weather condition; and generate for display on a device a notification associated with the user profile based, at least in part, on receiving the event and generating the weather report, wherein the notification indicates the weather condition.

---