

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250267206

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

PARK; Chanhyeok

---

### DISPLAY MODULE AND DISPLAY DEVICE

---

#### Abstract

A display module and a display device which can improve a heat-dissipation performance and a shock absorption function while reducing a bezel area, and in particular, reduce an impact applied to an edge of a cushion plate, and reduce deterioration in the shock absorption function due to moisture. A chamfer is formed along an edge of a metal foam included in the cushion plate to implement the improvement. Thus, a spacing between the edge of the cushion plate and a frame is maximized such that the impact applied to the edge of the cushion plate can be reduced as much as possible. Further, a rear face of a body and a chamfer of the metal foam can be covered with a water-proof layer, such that moisture invasion into the cushion plate can be reduced as much as possible.

---

**Inventors:** PARK; Chanhyeok (Paju-si, KR)

**Applicant:** LG Display Co., Ltd. (Seoul, KR)

**Family ID:** 1000008578369

**Assignee:** LG Display Co., Ltd. (Seoul, KR)

**Appl. No.:** 19/196142

**Filed:** May 01, 2025

#### Foreign Application Priority Data

KR 10-2020-0183760

Dec. 24, 2020

#### Related U.S. Application Data

parent US continuation 18316777 20230512 parent-grant-document US 12317429 child US 19196142

parent US continuation 17530845 20211119 parent-grant-document US 11690182 child US 18316777

---

## Publication Classification

**Int. Cl.:** H04M1/02 (20060101); H05K5/03 (20060101)

**U.S. Cl.:**

**CPC** H04M1/0266 (20130101); H05K5/03 (20130101);

---

## Background/Summary

### CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims a benefit under 35 U.S.C. § 119 (a) of Korean Patent Application No. 10-2020-0183760 filed on Dec. 24, 2020, in the Korean Intellectual Property Office, the entire disclosure of which is incorporated herein by reference for all purposes.

### BACKGROUND

#### Technical Field

[0002] The present disclosure relates to a display module and a display device, and more specifically, a display module and a display device capable of improving heat-dissipation performance and shock absorption function while reducing a bezel area.

#### Description of the Related Art

[0003] A display device is implemented in a wide variety of forms as in televisions, monitors, smart phones, tablet PCs, notebook computers, and wearable devices.

[0004] In general, the display device includes a display area displaying a image and a non-display area along an outer periphery of the display area.

[0005] The display device includes various additional components such as a driving integrated circuit or a circuit board in addition to a display panel to display the screen.

[0006] In the non-display area, the additional components can be disposed, or various connection parts such as a flexible circuit board for connecting the additional components to each other can be disposed.

[0007] In the display device, the non-display area is also referred to a bezel area. When the bezel area is thick, a user's gaze is wide. However, when the bezel area is thinner, the user's gaze is fixed on the screen of the display area such that user immersion increases.

[0008] In other words, when the bezel area becomes thinner, an entire size of the display device can be reduced while increasing the user immersion. Accordingly, demand from the user for the display device that can reduce the bezel area as much as possible is increasing.

### BRIEF SUMMARY

[0009] In the display device, not only a pad of the display panel but also various additional components such as the driving integrated circuit and the circuit board can be disposed on a rear face (or a rear surface) of the display panel in order to secure the display area as large as possible and to ensure the minimum bezel area.

[0010] In this case, the various additional components can be mounted on or connected to a connection component such as a flexible circuit board and can be disposed on the rear face of the display panel.

[0011] For example, the flexible circuit board connected to one distal end of the display panel can be bent in a direction from the bezel area to the rear face of the display panel.

[0012] Alternatively, as one distal end of the display panel is bent toward the rear face of the display panel, the various additional components can be disposed on the rear face of the display panel.

[0013] In this case, when a radius of curvature of the bending distal end increases, the flexible circuit board or display panel can be bent more stably and easily. However, as the bending radius of curvature increases, the bezel area increases, and a total width of the display device increases.

[0014] A cushion plate for heat-dissipation and shock absorption can be disposed on the rear face of the display panel.

[0015] In one example, the cushion plate has a laminated structure in which a plurality of layers having various functions such as a heat-dissipation layer having a heat-dissipation function, a cushion layer capable of absorbing shock, an adhesive layer for bonding the heat-dissipation layer and the cushion layer to each other, etc., are laminated one on top of another.

[0016] In this case, when a thickness of each of the heat-dissipation layer and the cushion layer is as thick as possible, the heat-dissipation function and shock absorption function can increase. However, as the thickness thereof increases, a total thickness of the display device increases, resulting in an increase in the bezel area.

[0017] Otherwise, when the thickness of each of the heat-dissipation layer and the cushion layer is thin to reduce the total thickness of the display device, the heat-dissipation function and the shock absorbing function can decrease.

[0018] Further, the heat-dissipation layer and cushion layer having different functions can be formed of different materials suitable for the functions thereof. In this connection, interlayer separation or adhesion deterioration between the various layers formed of different materials can occur.

[0019] In particular, in order to fix or connect each layer, a separate adhesive layer must be added between the layers. This can lead to an increase in a thickness, and a limitation in selection of a type of the adhesive layer depending on a material to be bonded and an increase in a cost of the device.

[0020] Further, because the cushion plate is formed in a multi-layered structure, change in a shape of the cushion plate can be limited.

[0021] Moreover, a sudden impact is applied to the display device. In this connection, because an edge portion (or a periphery portion) is generally most vulnerable to the impact, considerable damage can occur at the edge portion (or a periphery portion) of the display device.

[0022] The cushion plate disposed on the rear face of the display panel can be disposed close to a frame that houses the display module. In particular, an edge portion of the cushion plate can be disposed very close to an edge portion (or a periphery portion) of the frame.

[0023] Therefore, when the sudden impact is applied to the edge portion of the display device, the impact can be directly transmitted to the edge portion of the cushion plate, and then, the impact can be transmitted to the display panel.

[0024] Even though the cushion plate has the shock absorbing function, the shock absorbing function of the cushion plate may not work effectively when the sudden shock is applied through the edge (or the periphery) that is vulnerable to the shock.

[0025] Further, when moisture invades into the cushion plate, the shock absorbing function of the cushion plate can be deteriorated.

[0026] For example, when the display device is used in a very humid environment or falls into water, moisture can invade into an interior of the display device. In this case, when the moisture invades into the cushion layer of the cushion plate, the shock absorption function thereof can be greatly degraded.

[0027] Accordingly, the inventors of the present disclosure have invented a display module and a display device which can improve a heat-dissipation performance and a shock absorption function while reducing the bezel area, and in particular, reduce the impact applied to the edge of the cushion plate, and reduce the deterioration in the shock absorption function due to the moisture.

[0028] A purpose to be achieved according to an embodiment of the present disclosure is to provide a display module and a display device capable of reducing an impact applied to an edge (or a

periphery) of a cushion plate.

[0029] A purpose to be achieved according to an embodiment of the present disclosure is to provide a display module and a display device capable of reducing moisture invasion into a cushion plate.

[0030] A purpose to be achieved according to an embodiment of the present disclosure is to provide a display module and a display device capable of improving a heat-dissipation performance and a shock absorption function while reducing the bezel area.

[0031] A purpose to be achieved according to an embodiment of the present disclosure is to provide a display module and a display device capable of minimizing interlayer separation or adhesion deterioration between layers constituting a cushion plate.

[0032] A purpose to be achieved according to an embodiment of the present disclosure is to provide a display module and a display device including a cushion plate have a higher freedom in a shape change thereof.

[0033] Purposes to be achieved according to an embodiment of the present disclosure are not limited to the purpose as mentioned above. Other purposes that are not mentioned can be clearly understood by those skilled in the art based on following descriptions.

[0034] A display module according to an embodiment of the present disclosure includes a cover member, a display panel disposed on a rear face (or a rear surface) of the cover member, and a cushion plate disposed on a rear face (or a rear surface) of the display panel and including a metal foam and a water-proof layer.

[0035] In this case, the metal foam includes a body and a chamfer along an edge (or a periphery) of the body, and the water-proof layer is disposed on a rear face (or a rear surface) of the metal foam, and covers a rear face (or a rear surface) of the body, and the chamfer.

[0036] The chamfer is disposed on the rear face of the body, and is formed by removing at least a portion of a rear face (or a rear surface) and at least a portion of a side face (or a side surface) of the metal foam.

[0037] The chamfer includes at least one of an inclined face (or an inclined surface), a right angled face (or a right angled surface), and a curved face (or a curved surface), and extends along an entire perimeter of the body.

[0038] The water-proof layer includes an organic material, and the water-proof layer additionally covers a side face of the body.

[0039] A display device according to an embodiment of the present disclosure includes a cover member, a display module according to an embodiment of the present disclosure coupled to a rear face (or a rear surface) of the cover member, and a frame disposed on a rear face (or a rear surface) of the display module to support the cover member.

[0040] In accordance with the present disclosure, the chamfer can be formed along the edge (or the periphery) of the metal foam included in the cushion plate, such that a spacing between an edge (or a periphery) of the cushion plate and the frame can be maximized, and thus the impact applied to the edge of the cushion plate can be reduced as much as possible.

[0041] Further, in accordance with the present disclosure, the water-proof layer can cover the rear face (or the rear surface) of the body of the metal foam included in the cushion plate, and the chamfer thereof, thereby minimizing a moisture invading path and thus reducing moisture invasion into the cushion plate as much as possible.

[0042] In particular, because the chamfer is formed by removing at least a portion of the rear face (or the rear surface) as well as at least a portion of the side face (or the side surface) of the metal foam, the water-proof layer can cover the side face (or the side surface) of the metal foam, thereby more effectively reducing the moisture invasion into the side face (or the side surface) of the cushion plate.

[0043] Further, the cushion plate according to the present disclosure includes the metal foam having both a heat-dissipation function and a cushion function. Thus, the cushion plate can have an effective heat-dissipation function and an effective cushion function at the same time only using the

metal foam without a separate heat-dissipation layer or a separate cushion layer.

[0044] In particular, the metal foam has a very good heat-dissipation function and a very good cushioning function even when the metal foam is thin. Thus, a total thickness of the cushion plate can be greatly reduced, such that the bezel area can be reduced.

[0045] Further, the cushion plate according to the present disclosure can realize both the heat-dissipation function and the cushion function only using the metal foam. Thus, it is not necessary to stack separate layers formed of different materials having a heat-dissipation function and a cushion function, respectively, thereby minimizing the interlayer separation or adhesion deterioration.

[0046] In addition, because there is no need to add a separate adhesive layer configured to fix or connect each of layers, an increase in thickness due to the adhesive layer or an increase in a manufacturing cost of the display device due to the addition of various layers may not occur.

[0047] Further, because the cushion plate according to the present disclosure includes the metal foam having a higher freedom in the change shape, the shape of the cushion plate can be freely and easily changed in response to a design change of the display module.

[0048] Effects of the present disclosure are not limited to the above-mentioned effects, and other effects as not mentioned will be clearly understood by those skilled in the art from following descriptions.

---

## Description

### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0049] FIGS. 1A and 1B respectively show a front face and a rear face of a display device according to an embodiment of the present disclosure.

[0050] FIG. 2 is a cross-sectional view taken along an I-I' direction of a display module according to an embodiment of the present disclosure.

[0051] FIG. 3A and FIG. 3B are enlarged cross-sectional views when an external force is applied to edges (or peripheries) of display device according to Comparative Example, and an embodiment of the present disclosure, respectively.

[0052] FIG. 4 is a perspective view of a cushion plate according to an embodiment of the present disclosure.

[0053] FIGS. 5A to 5D are cross-sectional views of cushion plates according to various embodiments of the present disclosure, respectively.

[0054] FIGS. 6A to 6C are cross-sectional views of metal foams according to various embodiments of the present disclosure, respectively.

[0055] FIG. 7A and FIG. 7B are cross-sectional views showing waterproofing effects of cushion plates according to Comparative Example, and an embodiment of the present disclosure, respectively.

[0056] FIG. 8A and FIG. 8B are SEM photographs of cross sections of cushion plates according to Comparative Example, and an embodiment of the present disclosure, respectively.

[0057] FIG. 9A and FIG. 9B are SEM photographs showing moisture invasion into cushion plates according to Comparative Example, and an embodiment of the present disclosure, respectively.

[0058] FIG. 10A and FIG. 10B are comparative cross-sectional views of laminated structures of cushion plates according to Comparative Example, and an embodiment of the present disclosure, respectively.

### DETAILED DESCRIPTIONS

[0059] Advantages and features of the present disclosure, and a method of achieving the Advantages and features will become apparent with reference to embodiments described later in detail together with the accompanying drawings. However, the present disclosure is not limited to the embodiments as disclosed below, but can be implemented in various different forms. Thus,

these embodiments are set forth only to make the present disclosure complete, and to completely inform the scope of the disclosure to those of ordinary skill in the technical field to which the present disclosure belongs.

[0060] A shape, a size, a ratio, an angle, a number, etc., disclosed in the drawings for describing the embodiments of the present disclosure are exemplary, and the present disclosure is not limited thereto. The same reference numerals refer to the same elements herein. Further, descriptions and details of well-known steps and elements are omitted for simplicity of the description. Furthermore, in the following detailed description of the present disclosure, numerous specific details are set forth in order to provide a thorough understanding of the present disclosure. However, it will be understood that the present disclosure can be practiced without these specific details. In other instances, well-known methods, procedures, components, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the present disclosure.

[0061] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the present disclosure. As used herein, the singular forms “a” and “an” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes,” and “including” when used in this specification, specify the presence of the stated features, integers, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, operations, elements, components, and/or portions thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. Expression such as “at least one of” when preceding a list of elements can modify the entire list of elements and may not modify the individual elements of the list. In interpretation of numerical values, an error or tolerance therein can occur even when there is no explicit description thereof.

[0062] In addition, it will also be understood that when a first element or layer is referred to as being present “on” a second element or layer, the first element can be disposed directly on the second element or can be disposed indirectly on the second element with a third element or layer being disposed between the first and second elements or layers. It will be understood that when an element or layer is referred to as being “connected to,” or “coupled to” another element or layer, it can be directly on, connected to, or coupled to the other element or layer, or one or more intervening elements or layers can be present. In addition, it will also be understood that when an element or layer is referred to as being “between” two elements or layers, it can be the only element or layer between the two elements or layers, or one or more intervening elements or layers can also be present.

[0063] In descriptions of temporal relationships, for example, temporal precedent relationships between two events such as “after,” “subsequent to,” “before,” etc., another event can occur therebetween unless “directly after,” “directly subsequent” or “directly before” is not indicated.

[0064] It will be understood that, although the terms “first,” “second,” “third,” and so on can be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Thus, a first element, component, region, layer or section described below could be termed a second element, component, region, layer or section, without departing from the spirit and scope of the present disclosure.

[0065] The features of the various embodiments of the present disclosure can be partially or entirely combined with each other, and can be technically associated with each other or operate with each other. The embodiments can be implemented independently of each other and can be implemented together in an association relationship.

[0066] Hereinafter, various configurations of a display module and a display device that can improve a heat-dissipation performance and a shock absorption function while reducing a bezel

area, and in particular, can reduce an impact applied to an edge (or a periphery) of a cushion plate and reduce deterioration of the shock absorbing function due to moisture will be described in detail. [0067] FIG. 1A briefly shows a front face (or a front surface) of a display device **1** on which an image is displayed, and FIG. 1B briefly shows a rear face (or a rear surface) of display device **1**. [0068] FIG. 2 is a cross-sectional view taken along an I-I' direction of a display module **10** according to an embodiment of the present disclosure.

[0069] The display device **1** includes a cover member **20**, a display module **10** coupled to a rear face (or a rear surface) of cover member **20**, and a frame **30** disposed on a rear face (or a rear surface) of display module **10** to support the cover member **20**.

[0070] The display module **10** can include a display panel **100** and include various layers such as a functional film **120**, a back plate **110**, and a cushion plate **200**, and can be bonded or attached to the cover member **20** via a module fixing member (or a connection member) **130**.

[0071] The cover member **20** can be disposed to cover a front face (or a front surface) of the display module **10**, and thus can protect the display module **10** from external shocks.

[0072] An edge (or a periphery) of the cover member **20** can have a round shape in which the edge thereof is curved toward a rear face (or a rear surface) thereof on which the display module **10** is disposed.

[0073] The display device **1** displays an image through a front face (or a front surface) of the cover member **20**, and is configured such that a non-display area NAA is formed around a display area AA.

[0074] In other words, the front face (or the front surface) of the cover member **20** can be divided into the display area AA and the non-display area NAA as an area other than the display area AA. The non-display area NAA can be formed along an edge (or a periphery) of the display area AA, and the non-display area NAA can be defined as a bezel area BZA.

[0075] The cover member **20** includes the display area AA that displays a screen, and thus can be formed of a transparent material such as a cover glass to display the screen. For example, the cover member **20** can be formed of a transparent plastic material, a glass material, or a reinforced glass material.

[0076] The frame **30** can be disposed on the rear face (or the rear surface) of display module **10** and therein accommodate the display module **10** and contact the cover member **20** to support the cover member **20**.

[0077] The frame **30** serves as a housing that defines a rear face (or a rear surface) of the display device **1**, and can be formed of various materials such as plastic, metal, or glass.

[0078] In this case, the frame **30** can function as a casing defining an outermost portion of display device **1**. However, the present disclosure is not limited thereto.

[0079] For example, the frame **30** can function as a middle frame that serves as a housing that protects the rear face (or the rear surface) of display module **10**, and there can be an additional casing on the rear face (or the rear surface) of the frame **30**.

[0080] Hereinafter, the display device **1** and the display module **10** according to an embodiment of the present disclosure will be described in more detail with reference to FIG. 2.

[0081] The display module **10** includes the display panel **100** disposed on the rear face (or a rear surface) of cover member **20**.

[0082] The display module **10** can be defined as including the display panel **100** attached to the rear face (or the rear surface) of cover member **20**, and additional components related to the display panel **100** except the cover member **20** in a narrow sense. The display module **10** can be defined as including the cover member **20** in a broad sense.

[0083] The display module **10** can additionally include various layers such as the functional film **120**, the back plate **110**, and the cushion plate **200**.

[0084] The display module **10** can be bonded or attached to the cover member **20** via the module fixing member (or a connection member) **130**.

[0085] First, specifically, the module fixing member **130** that fixes or connects the display panel **100** to the cover member **20** is disposed on the rear face (or the rear surface) of the cover member **20**.

[0086] Since the module fixing member **130** can be disposed to overlap the display area AA, the module fixing member **130** can be embodied as a transparent adhesive member. For example, the module fixing member **130** can be formed of or include a material such as OCA (Optical Clear Adhesive), OCR (Optical Clear Resin), or PSA (Pressure Sensitive Adhesive).

[0087] The functional film **120** can be additionally disposed between the module fixing member **130** and the display panel **100**. The functional film **120** can have a structure in which one or more functional layers are stacked one on top of another, but is not particularly limited.

[0088] In one example, the functional film **120** can include an antireflection layer such as a polarizing film that prevents reflection of external light to improve an outdoor visibility and a contrast ratio for an image displayed on the display panel **100**.

[0089] In addition, in one example, the functional film **120** can further include a barrier layer for preventing moisture or oxygen invasion. The barrier layer can be formed of a material having low moisture permeability, such as a polymer material.

[0090] The display panel **100** can include a display substrate, a pixel array disposed on the display substrate, and an encapsulation portion disposed to cover the pixel array.

[0091] The display substrate can serve as a base substrate of the display panel **100**. The display substrate can be formed of a flexible plastic material and thus can act as a flexible display substrate.

[0092] In one example, the display substrate can be formed of polyimide as a plastic material having flexibility, or can be formed of a thin-type glass material having flexibility.

[0093] The pixel array can correspond to an area configured to display the image toward the front face (or the front surface) of the cover member **20**, and thus can correspond to the display area AA.

[0094] Therefore, the area corresponding to the pixel array in the cover member **20** can be the display area AA, and the area other than the display area AA can be the bezel area.

[0095] The pixel array can be implemented using various elements that display an image, and may not be particularly limited.

[0096] The pixel array can include a plurality of pixels that are arranged in a pixel area defined by signal lines on the display substrate, and display an image according to signals supplied to the signal lines. The signal lines can include a gate line, a data line, and a pixel driving power line.

[0097] Each of the plurality of pixels can include a thin film transistor in the pixel area, an anode electrically connected to the thin film transistor, a light-emissive element layer formed on the anode, and a cathode electrically connected to the light-emissive element layer.

[0098] The thin film transistor can include a gate electrode, a semiconductor layer, a source electrode, a drain electrode, and the like. The semiconductor layer of the thin film transistor can include silicon such as a-Si, poly-Si, or low-temperature poly-Si, or an oxide such as IGZO (Indium-Gallium-Zinc-Oxide).

[0099] The anode can be disposed in each pixel in a corresponding manner to an opening area defined according to a pattern shape of a pixel, and can be electrically connected to the thin film transistor.

[0100] In one example, the light-emissive element layer can include an organic light-emissive element formed on the anode. The organic light-emissive element can be implemented to emit light of the same color such as white light across the pixels or can be implemented to emit light beams of different colors such as red, green, and blue light beams across the pixels.

[0101] In another example, the light-emissive element layer can include a micro light-emissive diode element electrically connected to each of the anode and the cathode. The micro light-emissive diode element refers to a light-emissive diode implemented in a form of an integrated circuit (IC) or a chip, and can include a first terminal electrically connected to the anode and a second terminal electrically connected to the cathode.



[0102] The cathode can be commonly connected to a light-emissive element of a light-emissive element layer disposed in each pixel area.

[0103] The encapsulation portion is formed on the display substrate to cover the pixel array, such that oxygen, moisture, or foreign substances can be prevented from invading into the light-emissive element layer of the pixel array. In one example, the encapsulation portion can be formed in a multilayer structure in which organic material layers and inorganic material layers are alternately stacked one on top of another.

[0104] The back plate **110** can be disposed under the display panel **100**.

[0105] The back plate **110** can be disposed under the display substrate to complement a rigidity of the display substrate, and can be formed to have a certain strength and a certain thickness to complement the rigidity of the display substrate.

[0106] The cushion plate **200** can be disposed under the back plate **110**.

[0107] An embossed layer **230**, a metal foam **220** and a water-proof layer **210** of the cushion plate **200** can be sequentially stacked vertically in a direction toward the rear face (or the rear surface) of the display panel **100**.

[0108] Hereinafter, the cushion plate **200** will be described in detail with reference to FIG. 5A to FIG. 5D showing various embodiments of the cushion plate **200**, and FIGS. 6A to 6D showing various embodiments of the metal foam **220**, together with FIG. 4 showing a perspective view of the cushion plate **200** according to an embodiment.

[0109] The cushion plate **200** includes the embossed layer **230**, the metal foam **220** and the water-proof layer **210**.

[0110] First, the embossed layer **230** can refer to a layer that directly contacts the back plate **110** to fix or connect the cushion plate **200** to the back plate **110**, and thus can function as an adhesive layer including an adhesive component.

[0111] The embossed layer **230** can be formed of or include a material such as OCA (Optical Clear Adhesive), OCR (Optical Clear Resin), or PSA (Pressure Sensitive Adhesive).

[0112] Specifically, the embossed layer **230** can include a base substrate **231**, and a first adhesive layer **233a** and a second adhesive layer **233b** disposed on both opposite faces (or both opposite surfaces) of the base substrate **231**, respectively.

[0113] In this case, the second adhesive layer **233b** can contact the metal foam **220** to bond (or attach) and fix (or connect) the metal foam **220** to the embossed layer **230**.

[0114] The first adhesive layer **233a** of the embossed layer **230** can have a plurality of embossed patterns **233e** such as an uneven structure.

[0115] The first adhesive layer **233a** of the embossed layer **230** can act as a face (or a surface) in contact with the back plate **110**. The first adhesive layer **233a** has the embossed patterns **233e**, thereby preventing production of air bubbles between the back plate **110** and the cushion plate **200**, such that a degassing process for removing air bubbles can be omitted.

[0116] The base substrate **231** of the embossed layer **230** can serve to hold a shape of the embossed layer **230**, and can be formed of a material such as PET.

[0117] In order to have an effective anti-bubble effect, the embossed layer **230** preferably has a thickness of at least 40  $\mu\text{m}$ .

[0118] The metal foam **220** is disposed on one face (or one surface) of the embossed layer **230**.

[0119] The metal foam **220** can refer to a porous metal structure including metal as a main component, and the metal foam **220** can have a multiple of pores **225** therein.

[0120] That is, the metal foam **220** can refer to a porous metal structure having a multiple of pores **225** therein.

[0121] The metal foam **220** can be formed using a following manufacturing method by way of example. However, the present disclosure is not limited thereto.

[0122] The metal foam **220** can be formed by sintering a metal foam precursor including metal powders.

[0123] The metal foam precursor refers to a structure before proceeding with a process performed to form the metal foam **220** such as the sintering process.

[0124] For example, the metal foam precursor can be formed using a slurry including metal powders, dispersant, and binder.

[0125] The metal powder can be embodied as mixture metal powders or alloy powders between at least two among copper powder, nickel powder, iron powder, SUS powder, molybdenum powder, silver powder, platinum powder, gold powder, aluminum powder, chromium powder, indium powder, tin powder, magnesium powder, phosphorous powder, zinc powder, and manganese powder. However, the present disclosure is not limited thereto.

[0126] In one example, alcohol can be used as the dispersant. However, the present disclosure is not limited thereto.

[0127] In this case, the alcohol can include monohydric alcohol having 1 to 20 carbon atoms such as methanol, ethanol, propanol, pentanol, octanol, ethylene glycol, propylene glycol, pentanol, 2-methoxyethanol, 2-ethoxyethanol, 2-butoxyethanol, glycerol, texanol or terpeneol, or a dihydric alcohol having 1 to 20 carbon atoms such as ethylene glycol, propylene glycol, hexanediol, octanediol or pentanediol, or polyhydric alcohols other than dihydric alcohol. However, the present disclosure is not limited thereto.

[0128] A type of the binder is not particularly limited and can be appropriately adjusted according to a type of a metal component or the dispersant used in preparation of the slurry.

[0129] For example, the binder can include an alkyl cellulose having an alkyl group having 1 to 8 carbon atoms such as methyl cellulose or ethyl cellulose, polyalkylene carbonate having an alkylene unit having 1 to 8 carbon atoms such as polypropylene carbonate or polyethylene carbonate, or a polyvinyl alcohol-based binder such as polyvinyl alcohol or polyvinyl acetate. However, the present disclosure is not limited thereto.

[0130] After producing the slurry including the metal powder, the dispersant, and the binder as described above, the slurry can be injected into a frame having a predefined shape or coating (or forming) the slurry on the substrate, thereby forming the metal foam precursor.

[0131] The metal foam precursor as thus formed can be changed into the metal foam **220** via the sintering process.

[0132] In this case, a condition of the sintering process is not particularly limited as long as the process proceeds at a temperature and for a time duration to allow solvent included in the slurry to be removed at a desired amount.

[0133] In one example, the sintering temperature can be in a range of about 50° C. to 250° C. and the sintering time duration can be predefined. However, the present disclosure is not limited thereto.

[0134] According to an embodiment of the present disclosure, after forming the metal foam precursor on the embossed layer **230**, the sintering process can be performed to form the metal foam **220**, thereby forming the cushion plate **200** including the embossed layer **230** and the metal foam **220**.

[0135] Alternatively, after forming the metal foam **220** separately from the embossed layer **230**, the embossed layer **230** and the metal foam **220** can be bonded or attached to each other, thereby forming the cushion plate **200** including the embossed layer **230** and the metal foam **220**. Thus, the manufacturing method of the cushion plate **200** is not particularly limited.

[0136] In the cushion plate **200** including the embossed layer **230** and the metal foam **220**, the metal foam **220** as a metal structure having a multiple of pores **225** therein can have a heat-dissipation function and a cushion function at the same time.

[0137] The metal foam **220** is formed of metal with a high thermal conductivity, such that the metal foam **220** itself exhibits excellent heat-dissipation function. Since the metal foam has the metal structure having a multiple of pores **225** therein, the metal foam can also realize excellent cushioning function.

[0138] In particular, because the metal foam **220** has a metal structure having a multiple of pores **225** therein, an overall surface area thereof can increase, and thus, the metal foam **220** itself can realize the excellent heat-dissipation function.

[0139] Therefore, the cushion plate **200** according to an embodiment of the present disclosure has both of an effective heat-dissipation function and an effective cushion functions at the same time using only the metal foam **220** without having a heat-dissipation layer for a heat-dissipation function and a cushion layer for a cushion function as separate layers.

[0140] In this regard, referring to FIGS. **10A** and **10B**, FIG. **10A** shows Comparative Example of a cushion plate **200** having a four-layers laminated structure. FIG. **10B** shows a cross-sectional view of a cushion plate **200** having a two-layers laminated structure including the metal foam **220** according to an embodiment of the present disclosure.

[0141] As shown in FIG. **10A**, the cushion plate according to Comparative Example has a structure in which four layers are laminated by sequentially stacking a cushion layer, a base layer, and a heat-dissipation layer on an embossed layer.

[0142] The embossed layer can include a base substrate formed of PET, and a first adhesive layer PSA and a second adhesive layer PSA on both opposing faces (or both opposing surfaces) of the base substrate, respectively, wherein the second adhesive layer can be embodied as an embossed adhesive layer Embo PSA.

[0143] In this case, the base substrate of the embossed layer can have a thickness of about 12  $\mu\text{m}$ , and each of the first adhesive layer and the second adhesive layer can have a thickness of about 24  $\mu\text{m}$ .

[0144] A cushion layer as a foam pad can be formed on the embossed layer to impart a cushion function to the cushion plate.

[0145] In this case, the cushion layer should have a thickness of at least 100  $\mu\text{m}$  in order to provide minimum effective cushioning function using only the foam pad.

[0146] The heat-dissipation layer is formed on the cushion layer, and the base layer must be added between the cushion layer and the heat-dissipation layer.

[0147] The heat-dissipation layer is directly bonded or attached to the cushion layer. In this case, when the cushion plate is bent in a bent area of the display module **10** and then a time lapses, the cushion layer and the heat-dissipation layer formed of different materials from each other are not completely adhered to each other, and are separated from each other.

[0148] Accordingly, the base layer can be added between the cushion layer and the heat-dissipation layer to minimize the separation between the cushion layer and the heat-dissipation layer and to realize flexibility in the bent area.

[0149] The base layer can be formed by disposing an adhesive layer PSA on a flexible base formed of polyimide (PI).

[0150] In this case, in order for the base layer to achieve minimum effective separation-suppressing and support functions, the base formed of the polyimide should have a thickness of at least 25  $\mu\text{m}$ , and a thickness of the adhesive layer PSA included in the base layer should be at least 15  $\mu\text{m}$ .

[0151] The heat-dissipation layer is disposed on the base layer to impart a heat-dissipation function to the cushion plate.

[0152] The heat-dissipation layer can be formed by disposing an adhesive layer PSA on a metal layer formed of a material having good thermal conductivity such as copper.

[0153] In this case, in order for the heat-dissipation layer to achieve minimum effective heat-dissipation function, the metal layer must have a thickness of at least 18  $\mu\text{m}$ , and a thickness of the adhesive layer PSA included in the heat-dissipation layer should be at least 12  $\mu\text{m}$ .

[0154] In other words, the cushion plate according to Comparative Example can have a structure in which the four layers are laminated, that is, the layers having separate functions must be stacked one on top of another in order to provide both of the heat-dissipation function and the cushion function. Thus, the number of process steps can increase, thus leading to an increase in a

manufacturing cost of the display device.

[0155] In particular, the layers having different functions are formed of different materials. Thus, additional adhesive layers must be disposed between the layers in order to bond or attach the layers to each other. Thus, a total thickness of the cushion plate can be further increased.

[0156] To the contrary, as shown in FIG. 10B, the cushion plate **200** according to an embodiment of the present disclosure can achieve both of an effective heat-dissipation function and an effective cushion function only using a double-layer laminated structure in which the metal foam **220** and the embossed layer **230** are stacked one on top of the other.

[0157] That is, because the cushion plate **200** according to an embodiment of the present disclosure can realize both the heat-dissipation function and the cushion function using only the metal foam **220**, there is no need to stack separate layers formed of different materials having a heat-dissipation function and a cushion function, respectively, so that separation between the layers, and adhesion deterioration therebetween can be minimized.

[0158] In addition, there is no need to add a separate adhesive layer configured to fix or connect the layers to each other. Thus, the increase in the manufacturing cost of the display device due to the increase in the thickness due to the adhesive layer or the addition of various layers may not occur.

[0159] In this case, a thickness of the metal foam **220** can be in a range of 20  $\mu\text{m}$  to 200  $\mu\text{m}$ , and a thickness of the cushion plate **200** can be in a range of 80  $\mu\text{m}$  to 260  $\mu\text{m}$ .

[0160] In particular, even when the metal foam **220** of the cushion plate **200** according to an embodiment of the present disclosure has a minimum thickness of 20  $\mu\text{m}$ , the metal foam **220** can have both a heat-dissipation function and a cushion function. Thus, a total thickness of the cushion plate **200** can be reduced.

[0161] The minimum and maximum thicknesses of each of the metal foam **220** and the cushion plate **200** can be appropriately adjusted according to a shape change of the display module **10**.

[0162] As described above, the cushion plate **200** according to an embodiment of the present disclosure includes the metal foam **220** having a higher freedom in the shape change. Thus, in response to the design change of the display module **10**, the shape of the cushion plate **200** can be freely and easily changed.

[0163] The embossed layer **230** is disposed on one face (or one surface) of the metal foam **220**, and the water-proof layer **210** is disposed on the opposite face (or the opposite surface) of the metal foam **220**.

[0164] In other words, the embossed layer **230** and the water-proof layer **210** are opposite to each other around the metal foam **220**.

[0165] The metal foam **220** having the higher freedom in the shape change includes a body **221** and a chamfer **223** along an edge (or a periphery) of the body **221**.

[0166] The chamfer **223** is formed on an opposite face (or an opposite surface) of the metal foam **220** where the water-proof layer **210** is disposed, and is not formed on one face (or one surface) of the metal foam **220** where the embossed layer **230** is disposed.

[0167] When describing based on FIGS. 5A to 5D, one face (or one surface) of the metal foam **220** can be defined as a top face (or a top surface or an upper surface) of the metal foam **220**, and the opposite face of the metal foam **220** can be defined as a bottom face (or a bottom surface or a lower surface) of the metal foam **220**.

[0168] Further, one face (or one surface) and the opposite face (or the opposite surface) thereto of the metal foam **220** can connect to a side face (or a side surface) of the metal foam **220**.

[0169] Therefore, the water-proof layer **210** can be disposed on the opposite face (or the opposite surface) of the metal foam **220** to cover the opposite face (or the opposite surface) of the body **221** where the chamfer **223** is formed, and the chamfer **223**.

[0170] In this case, the chamfer **223** of the metal foam **220** can be formed along an entire edge (or an entire periphery) of the body **221**.

[0171] In one example, the chamfer **223** can be formed by removing a portion of an edge area (or a

periphery area) of the body **221** so as to have an inclined face (or an inclined surface) as shown in FIG. 5A and FIG. 5B.

[0172] Specifically, at least a portion of a top face (or a top surface or an upper surface) and at least a portion of a side face (or a side surface) of the body **221** can be removed. A partial area of the body **221** can be removed so that the removed outer face (or outer surface) of the body **221** is inclined.

[0173] Accordingly, the side face (or the side surface) of the body **221** can be divided into a first side face (or a first side surface) **221a** formed as an inclined face (or an inclined surface) of the chamfer **223**, and a second side face (or a second side surface) **221b** free of the chamfer **223**.

[0174] The water-proof layer **210** disposed on one face (or one surface) of the body **221** can cover one face (or one surface) of the body **221** and the inclined face (or the inclined surface) of the chamfer **223**.

[0175] In other words, the water-proof layer **210** can cover the top face (or the top surface or the upper surface) of the body **221** and the first side face (or the first side surface) **221a** of the body **221** as shown in FIG. 5A.

[0176] The water-proof layer **210** can include an organic material.

[0177] In general, the organic material has a high waterproof effect.

[0178] The organic material can include an acrylic organic material or a polyurethane-based organic material, but is not limited thereto. The organic material can include other organic material components.

[0179] Therefore, the water-proof layer **210** can be formed by depositing the organic material on one face (or one surface) of the metal foam **220**.

[0180] However, when the water-proof layer **210** includes the organic material, it can be difficult to form the water-proof layer **210** so as to cover a right angled side face (or a right angled side surface) such as the second side face (or the second side surface) **221b** in terms of a process.

[0181] However, because the first side face (or the first side surface) **221a** of the body **221** is inclined, the water-proof layer **210** can cover the first side face (or the first side surface) **221a** of the body **221** in terms of the process regardless of a type of a material of the water-proof layer **210**.

[0182] Accordingly, the water-proof layer **210** covering one face (or one surface) of the body **221** and the chamfer **223** can cover the top face (or the top surface or the upper surface) of the body **221** and a portion of the side face (or the side surface) of the body **221**.

[0183] Further, the water-proof layer **210** can cover the top face (or the top surface or the upper surface) of the body **221** and the first side face (or the first side surface) **221a** and the second side face (or the second side surface) **221b** of the body **221** as shown in FIG. 5B.

[0184] In other words, the water-proof layer **210** can be formed to cover the top face (or the top surface or the upper surface) of the body **221** and an entire side face (or an entire side surface) of the body **221**.

[0185] In this case, the water-proof layer **210** can include a material which can allow the process to easily form the water-proof layer **210** to cover the right angled side face (or the right angled side surface) such as the second side face (or the second side surface) **221b**.

[0186] Accordingly, the water-proof layer **210** covering one face (or one surface) of the body **221** and the chamfer **223** thereof can cover the top face (or the top surface or the upper surface) of the body **221** and the entire side face (or the entire side surface) of the body **221**.

[0187] A thickness  $W_{sub.2}$  of the chamfer **223** can be  $\frac{2}{3}$  or smaller of a thickness  $W_{sub.1}$  of the body **221**.

[0188] The metal foam **220** has a shock absorbing function to absorb external shocks. Thus, when a size of the body **221** is greatly reduced, the shock absorbing function can be reduced accordingly.

[0189] Therefore, when the thickness  $W_{sub.2}$  of the chamfer **223** formed by removing the edge portion (or the periphery portion) of the body **221** increases, overall shock absorbing function of the metal foam **220** can be reduced. Thus, when the thickness  $W_{sub.2}$  of the chamfer **223** is

smaller than or equal to  $\frac{2}{3}$  of the thickness W.sub.1 of the body **221**, the deterioration in the shock absorbing function of the metal foam **220** can be minimized.

[0190] Further, in another example, the chamfer **223** can be obtained by removing a portion of the edge area (or the periphery area) of the body **221** so as to have a right angled face (or the right angled surface) as shown FIG. 5C.

[0191] Specifically, at least a portion of the top face and at least a portion of the side face (or the side surface) of the body **221** can be removed. In this connection, a partial area of the body **221** can be removed to have a right angled face.

[0192] In this case, the edge (or the periphery) of the body **221** can have a step due to the chamfer **223** having the right angled face.

[0193] Accordingly, the top face of the body **221** can include a first top face **221c** on which the chamfer **223** is not formed, and a second top face **221d** defining a horizontal face of the chamfer **223**.

[0194] Further, the side face of the body **221** can be divided into the first side face **221a** defining a right angled face of the chamfer **223** and the second side face **221b** free of the chamfer **223**.

[0195] The first top face **221c** of the body **221** can be connected to the first side face **221a** thereof, the first side face **221a** thereof can be connected to the second top face **221d** thereof, and the second top face **221d** thereof can be connected to the second side face **221b** thereof.

[0196] The water-proof layer **210** disposed on one face of the body **221** can cover one face of the body **221** and the right angled face of the chamfer **223**.

[0197] In other words, the water-proof layer **210** can cover the top face of the body **221** including the first top face **221c** and the second top face **221d** of the body **221** and the first side face **221a** of the body **221** as shown in FIG. 5C.

[0198] In FIG. 5C, unlike the second side face **221b**, the first side face **221a** constitutes the side face of the step connecting to the second top face **221d**. Thus, even when the metal foam **220** is covered with the water-proof layer **210** formed of the organic material, the water-proof layer **210** can cover both the top face of the body **221** and the chamfer **223** without any difficulties in the process.

[0199] Further, in another example, the chamfer **223** can be obtained by removing a portion of the edge area (or the periphery area) of the body **221** so as to have a curved face as shown in FIG. 5D.

[0200] Specifically, at least a portion of the top face and at least a portion of the side face of the body **221** can be removed. In this connection, a partial area of the body **221** can be removed to have a curved face.

[0201] Accordingly, the side face of the body **221** can be divided into the first side face **221a** as the curved face of the chamfer **223** and the second side face **221b** free of the chamfer **223**.

[0202] In this case, the curved face can be formed to have a concave shape, and can have a shape approximate to a step shape.

[0203] The water-proof layer **210** disposed on one face of the body **221** can cover one face of body **221** and the curved face of the chamfer **223**.

[0204] That is, the water-proof layer **210** can cover the top face of the body **221** and the first side face **221a** of the body **221** as shown in FIG. 5D.

[0205] In FIG. 5D, unlike the second side face **221b**, the first side face **221a** defines the curved side face having a shape approximate to a step shape. Even when the metal foam **220** is covered with the water-proof layer **210** including the organic material, the water-proof layer **210** can cover both the top face of the body **221** and the chamfer **223** without any difficulties in the process.

[0206] As shown in FIG. 2, each of the cushion plates **200** having the stacked structures according to various embodiments is disposed on the rear face of the display panel **100** when being applied to the display module **10** of the display device **1**. In this connection, the embossed layer **230**, the metal foam **220** and the water-proof layer **210** of the cushion plate **200** are stacked in this order in a direction toward the rear face of the display panel **100**.

[0207] The front face of the metal foam **220** of the cushion plate **200** contacts the embossed layer **230**, while the rear face of the metal foam **220** thereof contacts the water-proof layer **210**.

[0208] Therefore, the chamfer **223** obtained by removing at least a portion of the rear face and at least a portion of the side face of the metal foam **220** along the edge (or the periphery) of the metal foam **220** is disposed on the rear face of the body **221**.

[0209] The water-proof layer **210** is disposed on the rear face of the metal foam **220** to cover the rear face of the body **221** and the chamfer **223**.

[0210] Because the water-proof layer **210** is disposed to cover the chamfer **223** obtained by removing at least a portion of the rear face and at least a portion of the side face of the metal foam **220**, the water-proof layer **210** can cover the rear face of the metal foam **220** free of the chamfer **223** and at least a portion of the side face of the metal foam **220** having the chamfer **223**.

[0211] The display module **10** as described above is coupled to the rear face of the cover member **20**, and the frame **30** is disposed on the display module **10** to support the cover member **20**.

[0212] FIGS. **3A** and **3B** are enlarged cross-sectional views when an external force is applied to an edge (or a periphery) of a display device according to Comparative Example and an edge (or a periphery) of the display device **1** according to the embodiment, respectively.

[0213] Comparative Example according to FIG. **3A** has the same stack structure as that of the embodiment according to FIG. **3B** in that the cushion plate **200** is formed by sequentially stacking the embossed layer **230**, the metal foam **220**, and the water-proof layer **210** in a direction toward the rear face of the display panel **100**.

[0214] However, Comparative Example shown in FIG. **3A** differs from the embodiment shown in FIG. **3B** in that the chamfer **223** is formed along the edge (or the periphery) of the metal foam **220** in FIG. **3B** while the chamfer **223** is not formed along the edge (or the periphery) of the metal foam **220** in FIG. **3A**.

[0215] The edge portion (or the periphery portion) of the display device **1** is most vulnerable to an impact resulting from the external force.

[0216] Therefore, when a sudden impact is applied to the display device **1**, the edge portion (or the periphery portion) is most vulnerable to the impact, such that considerable damage occurs at the edge portion (or the periphery portion) of the display device **1**.

[0217] When an external force is applied to the display device **1**, the impact can be first applied to the frame **30** which constitutes an exterior appearance of the display device **1**.

[0218] When the impact applied to the frame **30** is transmitted to the internal display panel **100**, the display panel **100** can be damaged by the external force or by the impact.

[0219] In this case, as shown in FIG. **3A**, the cushion plate **200** disposed on the rear face of the display panel **100** is disposed closer to the frame **30** that houses the display module **10**. In particular, an edge portion (or a periphery portion) of the cushion plate **200** is very closer to an edge portion (or a periphery portion) of the frame **30**.

[0220] Therefore, when a sudden impact is applied to the edge portion (or the periphery portion) of the display device **1**, the impact can be directly transmitted to the edge portion (or the periphery portion) of the cushion plate **200**, and then, the impact can be transmitted to the display panel **100**.

[0221] When a spacing d.sub.1 between the edge (or the periphery) of the cushion plate **200** and the frame **30** is as large as possible so that the impact applied to the frame **30** is not transmitted to the edge of the cushion plate **200**, the total thickness of the display device **1** increases.

[0222] On the contrary, in the embodiment of the present disclosure as shown in FIG. **3B**, the chamfer **223** is formed along the edge (or the periphery) of the metal foam **220** included in the cushion plate **200**, such that a spacing d.sub.2 between the edge of the cushion plate **200** and the frame **30** is maximized.

[0223] In particular, the spacing d.sub.2 between the edge of the cushion plate **200** most vulnerable to the impact and the frame **30** can be maximized without changing a general spacing between the cushion plate **200** and the frame **30**.

[0224] Therefore, according to an embodiment of the present disclosure, the impact applied to the edge of the cushion plate **200** can be reduced as much as possible without increasing the total thickness of the display device **1**.

[0225] On the other hand, in Comparative Example shown in FIG. 3A, there is no change in the shape of the metal foam **220**, so that the water-proof layer **210** does not cover the side face of the metal foam **220** but covers the rear face of the metal foam **220**.

[0226] In contrast, in the embodiment shown in FIG. 3B, the chamfer **223** is formed along the edge (or the periphery) of the metal foam **220**, such that the water-proof layer **210** is disposed to cover the rear face and at least a portion of the side face of the metal foam **220**.

[0227] This will be described in detail with referring to FIGS. 7 to 9.

[0228] FIG. 7A and FIG. 8A show a cross-sectional view and a scanning electron microscope (SEM) photograph of the cushion plate **200** according to Comparative Example, respectively.

[0229] FIG. 7B and FIG. 8B show a cross-sectional view and a SEM photograph of the cushion plate **200** according to the embodiment of the present disclosure, respectively.

[0230] FIGS. 9A and 9B are SEM photographs identifying whether moisture invades into the pores **225** of the metal foam **220** after exposing the cushion plates **200** according to Comparative Example and according to the embodiment of the present disclosure to the same moisture environment, respectively.

[0231] As shown in FIG. 7A, in the Comparative Example, the water-proof layer **210** covers the top face of the metal foam **220** but does not cover the side face of the metal foam, the moisture may not invade into the metal foam **220** through the top face thereof but can invade into the metal foam **220** through the side face thereof.

[0232] In this case, because the metal foam **220** has a porous metal structure including a multiple of pores **225**, the moisture can invade into the multiple of pores **225**.

[0233] In this regard, referring to FIG. 9A, it can be identified that a large amount of moisture has invaded into the pores **225** of the metal foam **220** according to the Comparative Example.

[0234] The cushion plate **200** includes the metal foam **220** including a multiple of pores **225**, and can have a shock absorbing function that absorbs external shocks while a porosity thereof is maintained at a level above a certain level.

[0235] However, when the porosity of the metal foam **220** is reduced due to the invasion of the external moisture into the pores **225** of the metal foam **220**, the shock absorption function of the cushion plate **200** is greatly reduced.

[0236] Therefore, the cushion plate **200** having the same structure as in Comparative Example may not prevent the moisture from invasion into the side face of the metal foam **220**, such that the shock absorbing function of the cushion plate **200** decreases due to the moisture invasion.

[0237] On the contrary, as shown in FIG. 7B, in the embodiment of the present disclosure, the water-proof layer **210** is disposed to cover not only the top face of the metal foam **220**, but also at least a portion of the side face thereof, thereby effectively preventing the moisture from invading not only into the top face but also the side face of the metal foam **220**.

[0238] In this regard, referring to FIG. 9B, it can be identified that the moisture may not invade into the pores **225** of the metal foam **220** according to the embodiment.

[0239] That is, according to the embodiment of the present disclosure, when covering the rear face of the body **221** of the metal foam **220** included in the cushion plate **200** and the chamfer **223** of the metal foam **220** with the water-proof layer **210**, the moisture can invade into the cushion plate **200** at a minimum level.

[0240] In particular, because the chamfer **223** is formed by removing at least a portion of the rear face of the metal foam **220** as well as at least a portion of the side face of the metal foam, the water-proof layer **210** can cover the side face of the metal foam **220**, such that the moisture invasion into the side face of the cushion plate **200** can be more effectively reduced.

[0241] In one example, FIGS. 6A to 6C show metal foams **220** according to various embodiments



of the present disclosure, respectively.

[0242] As described above, the metal foam **220** according to FIG. **6A** has a porous metal structure including a multiple of pores **225** therein.

[0243] In this case, the metal foam **220** can have a shock absorbing function due to the pores **225** included in the metal foam **220**. Thus, it is desirable to maintain a porosity in a range above a certain value in order to maintain the impact absorption function of the metal foam **220** effectively.

[0244] In one example, the metal foam **220** according to FIG. **6B** shows another embodiment in which a heat-dissipation material **227** is included in some of the pores **225**.

[0245] When the metal foam **220** includes a multiple of pores **225**, a density of a metal component decreases accordingly. Thus, the shock absorption function can increase, but the heat-dissipation function can decrease to some extent.

[0246] Accordingly, the metal foam **220** according to another embodiment of FIG. **6B** can further include the heat-dissipation material **227** included in some of the inner pores **225**.

[0247] In one example, the heat-dissipation material **227** can include a mixture of ceramic powders, or a separate cooling material. However, the present disclosure is not limited thereto.

[0248] The ceramic powder can include at least one among boron nitride (BN), aluminum oxide (Al.sub.2O.sub.3), silicon carbide (SiC), magnesium oxide (MgO), aluminum hydroxide (Al(OH).sub.3), and magnesium hydroxide (Mg(OH).sub.2). However, the present disclosure is not limited thereto.

[0249] The cooling material can include a gel-type silicone resin. However, the present disclosure is not limited thereto.

[0250] Further, the metal foam **220** according to FIG. **6C** shows another embodiment in which some of the inner pores **225** are waterproof-coated with a waterproof material **229**.

[0251] As described above, in one embodiment of the present disclosure, the top face and a portion of the side face of the metal foam **220** are covered with the water-proof layer **210**, such that the moisture invasion into the metal foam **220** is prevented as much as possible.

[0252] In order to further increase the waterproof performance, water repellency can be additionally imparted to the metal foam by coating the inner pores **225** of the metal foam **220** with a waterproof material such as an organic material.

[0253] In this case, when a percentage of the organic material coating inside the metal foam **220** is set to around 2%, the internal water-repellent function of the metal foam **220** can be maximized while minimizing the deterioration in the shock absorbing function of the metal foam **220**.

[0254] In one example, in this case, when it is desirable to maximize the inner waterproof function of the metal foam **220**, the inner pores **225** of the metal foam **220** can be fully filled with the waterproof material.

[0255] The waterproof material can include an organic material. The organic material can include an acrylic organic material or a polyurethane organic material. However, the present disclosure is not limited thereto.

[0256] Various additional components for operating the display panel **100** can be disposed under the cushion plate **200**.

[0257] The various additional components can be mounted on or connected to a connecting part such as a flexible circuit board and can be disposed on the rear face of the display panel **100**.

[0258] For example, the flexible circuit board connected to one distal end of the display panel **100** can be bent from one edge area (or one periphery area) of the display device **1** toward the rear face of the display panel **100**.

[0259] Alternatively, one distal end of the display panel **100** can be bent toward the rear face of the display panel **100**, so that various additional components can be disposed on the rear face of the display panel **100**.

[0260] A driving integrated circuit can be disposed under the cushion plate **200**.

[0261] For example, the driving integrated circuit can be mounted on the display substrate in a

COP (Chip On Plastic) manner. However, the present disclosure is not limited thereto.

[0262] The driving integrated circuit generates a data signal and a gate control signal based on image data and a timing synchronization signal supplied from an external host driving system. Further, the driving integrated circuit can supply the data signal to the data line of each pixel through the display pad, and can supply the gate control signal to the gate driving circuitry through the display pad.

[0263] That is, the driving integrated circuit can be mounted on a chip mounted area defined on the display substrate and can be electrically connected to the display pad, and can be connected to a signal line of each of a gate driving circuitry and a pixel array disposed on the display substrate.

[0264] The display pad can be disposed at a distal end of the display substrate on which the driving integrated circuit is mounted. A plurality of display pads can be formed.

[0265] The display pad can be disposed on the rear face of the display substrate and can be electrically connected to the flexible circuit board on which a circuit board is mounted.

[0266] The flexible circuit board can be electrically connected to the display pad disposed at the distal end of the display substrate via a film attaching process using a conductive adhesive layer, and thus can be disposed on the rear face of the display panel.

[0267] In this case, the conductive adhesive layer can include ACF (Anisotropic Conductive Film) by way of example.

[0268] The circuit board can supply the image data and the timing synchronization signal supplied from the host driving system to the driving integrated circuit, and can respectively supply voltages for driving the pixel array, the gate driving circuitry, and the driving integrated circuit thereto.

[0269] The display module according to an embodiment of the present disclosure as described above can include the display panel, and the cushion plate disposed on the rear face of the display panel, and the cushion plate can include the metal foam and the water-proof layer.

[0270] In this case, the metal foam can include the body and the chamfer along the edge (or the periphery) of the body, and the water-proof layer can be disposed on the rear face of the metal foam to cover the rear face of the body and the chamfer.

[0271] The chamfer can be disposed on the rear face of the body.

[0272] The chamfer can be formed by removing at least a portion of the rear face and at least a portion of the side face of the metal foam.

[0273] The chamfer can include at least one of an inclined face, a right angled face, and a curved face.

[0274] The chamfer can be formed along an entire circumference of the body.

[0275] A thickness of the chamfer can be smaller than or equal to two third ( $\frac{2}{3}$ ) of a thickness of the body.

[0276] The water-proof layer can include an organic material and can cover an entire side face of the body.

[0277] A side face (or A side surface) of the body can be divided into a first side face (or a first side surface) comprising the chamfer of the metal foam and a second side face (or a second side surface) free of the chamfer, the water-proof layer of the cushion plate can cover only the rear face (or the rear surface) of the metal foam and the first side face (or the first side surface), but may not cover the second side face (or the second side surface).

[0278] The cushion plate can include an embossed layer. The embossed layer, the metal foam, and the water-proof layer can be sequentially stacked in this order toward the rear face of the display panel.

[0279] The embossed layer can include a base substrate and a first adhesive layer and a second adhesive layer can be respectively disposed on both opposing faces of the base substrate, The first adhesive layer can have an embossed pattern, and the second adhesive layer can be coupled to the metal foam.

[0280] The metal foam can have a porous metal structure having a plurality of pores.

[0281] The metal foam can further include a heat-dissipation material therein.

[0282] At least some of the pores can be coated with a waterproof material, and the waterproof material includes an organic material.

[0283] The plurality of pores of the metal foam can be fully filled with the waterproof material.

[0284] The embossed layer can have a thickness of at least 40  $\mu\text{m}$ .

[0285] A thickness of the metal foam can be in a range of 20  $\mu\text{m}$  to 200  $\mu\text{m}$ , and a thickness of the cushion plate is in a range of 80  $\mu\text{m}$  to 260  $\mu\text{m}$ .

[0286] The display device according to an embodiment of the present disclosure includes the cover member, the display module according to an embodiment of the present disclosure coupled to the rear face of the cover member, and the frame disposed on the rear face of the display module to support the cover member.

[0287] Although the embodiments of the present disclosure have been described in more detail with reference to the accompanying drawings, the present disclosure is not necessarily limited to these embodiments. The present disclosure can be implemented in various modified manners within the scope not departing from the technical idea of the present disclosure. Accordingly, the embodiments disclosed in the present disclosure are not intended to limit the technical idea of the present disclosure, but to describe the present disclosure. The scope of the technical idea of the present disclosure is not limited by the embodiments. Therefore, it should be understood that the embodiments as described above are illustrative and non-limiting in all respects. The scope of protection of the present disclosure should be interpreted by the claims, and all technical ideas within the scope of the present disclosure should be interpreted as being included in the scope of the present disclosure.

## Claims

1. A display device, comprising: a display panel including a transistor, the transistor comprising an oxide semiconductor; a frame disposed on a rear face of the display panel; and a cushion plate disposed on a rear face of the display panel, wherein the cushion plate is disposed between the display panel and the frame, wherein the cushion plate includes a first side face disposed on at least one edge of the cushion plate, and a second side face extending from the first side face toward the display panel, wherein a first distance between the first side face and the frame, and a second distance between the second side face and the frame are different from each other.
2. The display device of claim 1, wherein the cushion plate includes a first face disposed on the rear face of the display panel, and a second face opposite to the first face, and wherein the first face and the second face of the cushion plate are disposed between the first side face and the second side face of the cushion plate.
3. The display device of claim 1, wherein the second distance is greater than the first distance.
4. The display device of claim 1, wherein the second side face extends in a direction perpendicular to the display panel.
5. The display device of claim 2, wherein a distance between the second face and the first side face of the cushion plate is less than a distance between the first face and the second face of the cushion plate.
6. The display device of claim 2, wherein a shape of a corner of the first face of the cushion plate is different from a shape of the first side face of the cushion plate.
7. The display device of claim 2, wherein the first face of the cushion plate is a flat surface from one corner to an opposite corner of the cushion plate.
8. The display device of claim 1, further comprising: an embossed layer disposed between the display panel and the cushion plate.
9. The display device of claim 8, wherein the embossed layer includes an adhesive component.
10. The display device of claim 1, wherein the first side face is disposed at least at a corner of the

cushion plate.

**11.** The display device of claim 1, wherein the cushion plate includes metal.

**12.** The display device of claim 1, wherein the cushion plate includes a porous structure having a plurality of pores.

**13.** The display device of claim 1, wherein the first side face includes at least one of an inclined surface inclined relative to the second side face, a right angled surface, and a curved surface.

**14.** The display device of claim 1, further comprising: a cover member disposed on the display panel, wherein a width of the display panel is less than a width of the cover member, and a width of the cushion plate is less than the width of the display panel.

**15.** The display device of claim 1, further comprising: a cover member disposed on the display panel, wherein the cover member includes an upper surface and a lower surface opposite to the upper surface, the lower surface of the cover member facing the display panel, and wherein an edge of the upper surface and an edge of the lower surface of the cover member have different curvature shapes or different angle of curvatures, respectively.

**16.** The display device of claim 1, further comprising: an anode electrically connected to the transistor; a light emission layer disposed on the anode; and a cathode electrically connected to the light emission layer.

**17.** The display device of claim 16, wherein the light emission layer includes an organic light-emissive element, wherein the organic light-emissive element is configured to emit light of white color from a plurality of pixels, or configured to emit light of different colors from each pixel of the plurality of pixels, and wherein the anode is disposed on an opening area according to a pattern shape of the plurality of pixels.

---