

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12390253
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Baker; Charles R. et al.

Variable angle locking implant

Abstract

A variable angle locking implant includes a bone plate having a lower surface, an upper surface, and at least one opening extending from the lower surface to the upper surface along an axis. The opening has a plurality of fins oriented along a plane. The axis is non-perpendicular to a tangent of a projection of the lower surface across the opening, the tangent defined at the intersection between the axis and the projected lower surface, and/or the plane is non-parallel to the tangent. The implant includes at least one fastener, and the plurality of fins are deflectable relative to a head portion of the fastener such that the fastener can be inserted and retained at any one of a plurality of angles.

Inventors: Baker; Charles R. (Lakeland, TN), Stevenson; Ryan (Southaven, MS), Gerlach; Darin S. (Germantown, TN)

Applicant: Smith & Nephew, Inc. (Memphis, TN)

Family ID: 1000008763742

Assignee: Smith & Nephew, Inc. (Memphis, TN)

Appl. No.: 17/734002

Filed: April 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220265329 A1	Aug. 25, 2022

Related U.S. Application Data

continuation parent-doc US 16569204 20190912 ABANDONED child-doc US 17734002
continuation parent-doc US 15970747 20180503 US 10448980 20191022 child-doc US 16569204
continuation parent-doc US 13524506 20120615 ABANDONED child-doc US 15970747
us-provisional-application US 61497180 20110615

Publication Classification

Int. Cl.: **A61B17/80** (20060101)

U.S. Cl.:

CPC **A61B17/8052** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
300146	12/1883	Sinnett	N/A	N/A
351751	12/1885	Douglas	N/A	N/A
382670	12/1887	Trovillion	N/A	N/A
544606	12/1894	Balsley	N/A	N/A
545331	12/1894	Balsley	N/A	N/A
565808	12/1895	Staples	N/A	N/A
575631	12/1896	Brooks	N/A	N/A
583158	12/1896	Upham	N/A	N/A
637990	12/1898	Hoepner	N/A	N/A
651949	12/1899	Lillie	N/A	N/A
689722	12/1900	Hoover	N/A	N/A
766270	12/1903	Lapham	N/A	N/A
775427	12/1903	Lusted, Sr.	N/A	N/A
902040	12/1907	Wyckoff	N/A	N/A
1025008	12/1911	Miner	N/A	N/A
1105105	12/1913	Sherman	N/A	N/A
1275810	12/1917	White	N/A	N/A
1575149	12/1925	Craig et al.	N/A	N/A
1755588	12/1929	Bronk	N/A	N/A
1925385	12/1932	Humes et al.	N/A	N/A
2010913	12/1934	Bruce et al.	N/A	N/A
2133859	12/1937	Hawley	N/A	N/A
2152977	12/1938	John	N/A	N/A
2501978	12/1949	Heins	N/A	N/A
2524167	12/1949	Frank	N/A	N/A
2560912	12/1950	George	N/A	N/A
2667194	12/1953	Fischer et al.	N/A	N/A
2756791	12/1955	Benjamin	N/A	N/A
3056441	12/1961	Helms	N/A	N/A
3279510	12/1965	Dreyer et al.	N/A	N/A
3347293	12/1966	Clark	N/A	N/A
3409058	12/1967	La	N/A	N/A
3547114	12/1969	Haboush	N/A	N/A

3552389	12/1970	Allgower et al.	N/A	N/A
3630261	12/1970	Gley	N/A	N/A
3662797	12/1971	Healis	N/A	N/A
3668972	12/1971	Allgower et al.	N/A	N/A
3716050	12/1972	Johnston	N/A	N/A
3739825	12/1972	Knox	N/A	N/A
3741205	12/1972	Markolf et al.	N/A	N/A
3744488	12/1972	Cox	N/A	N/A
3779240	12/1972	Kondo	N/A	N/A
3782432	12/1973	Allen	N/A	N/A
3866607	12/1974	Forsythe et al.	N/A	N/A
3906550	12/1974	Rostoker et al.	N/A	N/A
3935762	12/1975	Tudisco	N/A	N/A
RE28841	12/1975	Allgower et al.	N/A	N/A
4059102	12/1976	Devas	N/A	N/A
4060114	12/1976	Matsushima	N/A	N/A
4096896	12/1977	Engel	N/A	N/A
4219015	12/1979	Steinemann	N/A	N/A
4246811	12/1980	Bondhus et al.	N/A	N/A
4263904	12/1980	Judet	N/A	N/A
4338926	12/1981	Kummer et al.	N/A	N/A
4364382	12/1981	Mennen	N/A	N/A
4388921	12/1982	Sutter et al.	N/A	N/A
4408601	12/1982	Wenk	N/A	N/A
RE31628	12/1983	Allgower et al.	N/A	N/A
4484570	12/1983	Sutter et al.	N/A	N/A
4493317	12/1984	Klaue	N/A	N/A
4513744	12/1984	Klaue	N/A	N/A
4535658	12/1984	Molinari	N/A	N/A
4564007	12/1985	Coombs et al.	N/A	N/A
4565193	12/1985	Streli	N/A	N/A
4573458	12/1985	Lower	N/A	N/A
4683878	12/1986	Carter	N/A	N/A
4704929	12/1986	Osada	N/A	N/A
4791918	12/1987	Von	N/A	N/A
4797948	12/1988	Milliorn et al.	N/A	N/A
4838252	12/1988	Klaue	N/A	N/A
4927421	12/1989	Goble et al.	N/A	N/A
4978349	12/1989	Frigg	N/A	N/A
4988350	12/1990	Herzberg	N/A	N/A
5002544	12/1990	Klaue et al.	N/A	N/A
5006120	12/1990	Carter	N/A	N/A
5041114	12/1990	Chapman et al.	N/A	N/A
5053036	12/1990	Perren et al.	N/A	N/A
5085660	12/1991	Lin	N/A	N/A
5129901	12/1991	Decoste	N/A	N/A
5151103	12/1991	Tepic et al.	N/A	N/A
5190544	12/1992	Chapman et al.	N/A	N/A
5192281	12/1992	de la Caffiniere	N/A	N/A
5197966	12/1992	Sommerkamp	N/A	N/A

5198308	12/1992	Shelly et al.	N/A	N/A
5237893	12/1992	Ryder et al.	N/A	N/A
5259398	12/1992	Vrespa	N/A	N/A
5269784	12/1992	Mast	N/A	N/A
5275601	12/1993	Gogolewski et al.	N/A	N/A
5304180	12/1993	Slocum	N/A	N/A
5312410	12/1993	Miller et al.	N/A	N/A
5324290	12/1993	Zdeblick et al.	N/A	N/A
5324291	12/1993	Ries et al.	N/A	N/A
5356410	12/1993	Pennig	N/A	N/A
5360452	12/1993	Engelhardt et al.	N/A	N/A
5364398	12/1993	Chapman et al.	N/A	N/A
5364399	12/1993	Lowery et al.	N/A	N/A
5395374	12/1994	Miller et al.	N/A	N/A
5415658	12/1994	Kilpela et al.	N/A	N/A
5423820	12/1994	Miller et al.	N/A	N/A
5423826	12/1994	Coates et al.	N/A	N/A
5429641	12/1994	Golfried	N/A	N/A
5431659	12/1994	Ross et al.	N/A	N/A
5470333	12/1994	Ray	N/A	N/A
5474553	12/1994	Baumgart	N/A	N/A
5487743	12/1995	Laurain et al.	N/A	N/A
5514138	12/1995	McCarthy	N/A	N/A
5520690	12/1995	Errico et al.	N/A	N/A
5522902	12/1995	Yuan et al.	N/A	N/A
5527310	12/1995	Cole et al.	N/A	N/A
5531143	12/1995	Habermehl et al.	N/A	N/A
5531746	12/1995	Errico et al.	N/A	N/A
5531748	12/1995	de la Caffiniere	N/A	N/A
5534932	12/1995	Van et al.	N/A	N/A
5536127	12/1995	Pennig	N/A	N/A
5569253	12/1995	Farris et al.	N/A	N/A
5578034	12/1995	Estes	N/A	N/A
5591168	12/1996	Jude et al.	N/A	N/A
5601553	12/1996	Trebing et al.	N/A	N/A
5607426	12/1996	Ralph et al.	N/A	N/A
5607428	12/1996	Lin	N/A	N/A
5643265	12/1996	Errico et al.	N/A	N/A
5647873	12/1996	Errico et al.	N/A	N/A
5665088	12/1996	Gil et al.	N/A	N/A
5665089	12/1996	Dall et al.	N/A	N/A
5676667	12/1996	Hausman	N/A	N/A
5702399	12/1996	Kilpela et al.	N/A	N/A
5709686	12/1997	Talos et al.	N/A	N/A
5713900	12/1997	Benzel et al.	N/A	N/A
5725588	12/1997	Errico et al.	N/A	N/A
5733287	12/1997	Tepic et al.	N/A	N/A
5735853	12/1997	Olerud	N/A	N/A
5741258	12/1997	Klaue et al.	N/A	N/A
5749872	12/1997	Kyle et al.	N/A	N/A

5769850	12/1997	Chin	N/A	N/A
5772662	12/1997	Chapman et al.	N/A	N/A
5776196	12/1997	Matsuzaki et al.	N/A	N/A
5788697	12/1997	Kilpela et al.	N/A	N/A
5797912	12/1997	Runciman et al.	N/A	N/A
5810823	12/1997	Klaue et al.	N/A	N/A
5824247	12/1997	Tunc	N/A	N/A
5876402	12/1998	Errico et al.	N/A	N/A
5888204	12/1998	Ralph et al.	N/A	N/A
5893856	12/1998	Jacob et al.	N/A	N/A
5902305	12/1998	Beger et al.	N/A	N/A
5904683	12/1998	Pohndorf et al.	N/A	N/A
5904684	12/1998	Rooks	N/A	N/A
5925047	12/1998	Errico et al.	N/A	N/A
5935130	12/1998	Kilpela et al.	N/A	N/A
5935133	12/1998	Wagner et al.	N/A	N/A
5938664	12/1998	Winqvist et al.	N/A	N/A
5954722	12/1998	Bono	N/A	N/A
5960681	12/1998	Anderson et al.	N/A	N/A
5961524	12/1998	Crombie	N/A	N/A
5964769	12/1998	Wagner et al.	N/A	N/A
5968046	12/1998	Castleman	N/A	N/A
5968047	12/1998	Reed	N/A	N/A
5976141	12/1998	Haag et al.	N/A	N/A
6016727	12/1999	Morgan	N/A	N/A
6019762	12/1999	Cole	N/A	N/A
6022352	12/1999	Vandewalle	N/A	N/A
6053921	12/1999	Wagner et al.	N/A	N/A
6096040	12/1999	Esser	N/A	N/A
6102951	12/1999	Sutter et al.	N/A	N/A
6129730	12/1999	Bono et al.	N/A	N/A
6176861	12/2000	Bernstein et al.	N/A	N/A
6183475	12/2000	Lester et al.	N/A	N/A
6193721	12/2000	Michelson	N/A	N/A
6206881	12/2000	Frigg et al.	N/A	N/A
6214049	12/2000	Gayer et al.	N/A	N/A
6228085	12/2000	Theken et al.	N/A	N/A
6235033	12/2000	Brace et al.	N/A	N/A
RE37249	12/2000	Leibinger et al.	N/A	N/A
6258092	12/2000	Dall	N/A	N/A
6273889	12/2000	Richelsoph	N/A	N/A
6302001	12/2000	Karle	N/A	N/A
6302883	12/2000	Bono	N/A	N/A
6306136	12/2000	Baccelli	N/A	N/A
6306140	12/2000	Siddiqui	N/A	N/A
6309393	12/2000	Tepic et al.	N/A	N/A
6322562	12/2000	Wolter	N/A	N/A
6342055	12/2001	Eisermann et al.	N/A	N/A
6355041	12/2001	Martin	N/A	N/A
6355043	12/2001	Adam	N/A	N/A

6358250	12/2001	Orbay	N/A	N/A
6361537	12/2001	Anderson	N/A	N/A
6364885	12/2001	Kilpela et al.	N/A	N/A
6370091	12/2001	Kuroda	N/A	N/A
6379359	12/2001	Dahners	N/A	N/A
6386808	12/2001	Fujii et al.	N/A	N/A
6391030	12/2001	Wagner et al.	N/A	N/A
6413259	12/2001	Lyons et al.	N/A	N/A
6428542	12/2001	Michelson	N/A	N/A
6436100	12/2001	Berger	N/A	N/A
6440135	12/2001	Orbay et al.	N/A	N/A
6454769	12/2001	Wagner et al.	N/A	N/A
6454770	12/2001	Klaue	N/A	N/A
6468278	12/2001	Muckter	N/A	N/A
6475218	12/2001	Gournay et al.	N/A	N/A
6506191	12/2002	Joos	N/A	N/A
6520965	12/2002	Chervitz et al.	N/A	N/A
6524238	12/2002	Velikaris et al.	N/A	N/A
6527776	12/2002	Michelson	N/A	N/A
6558387	12/2002	Errico et al.	N/A	N/A
6575975	12/2002	Brace et al.	N/A	N/A
6595993	12/2002	Donno et al.	N/A	N/A
6595994	12/2002	Kilpela et al.	N/A	N/A
6605090	12/2002	Trieu et al.	N/A	N/A
6623486	12/2002	Weaver et al.	N/A	N/A
6669700	12/2002	Farris et al.	N/A	N/A
6669701	12/2002	Steiner et al.	N/A	N/A
6682531	12/2003	Winquist et al.	N/A	N/A
6682533	12/2003	Dinsdale et al.	N/A	N/A
6684741	12/2003	Blackston	N/A	N/A
6689133	12/2003	Morrison et al.	N/A	N/A
6692498	12/2003	Niiranen et al.	N/A	N/A
6692581	12/2003	Tong et al.	N/A	N/A
6719759	12/2003	Wagner et al.	N/A	N/A
6730091	12/2003	Pfefferle et al.	N/A	N/A
6755829	12/2003	Bono et al.	N/A	N/A
6767351	12/2003	Orbay et al.	N/A	N/A
6780186	12/2003	Errico et al.	N/A	N/A
6821278	12/2003	Frigg et al.	N/A	N/A
6866665	12/2004	Orbay	N/A	N/A
6893443	12/2004	Frigg et al.	N/A	N/A
6893444	12/2004	Orbay	N/A	N/A
6916320	12/2004	Michelson	N/A	N/A
6945975	12/2004	Dalton	N/A	N/A
6955677	12/2004	Dahners	N/A	N/A
6960213	12/2004	Chervitz et al.	N/A	N/A
6969390	12/2004	Michelson	N/A	N/A
6973860	12/2004	Nish	N/A	N/A
6974461	12/2004	Wolter	N/A	N/A
6979334	12/2004	Dalton	N/A	N/A

7073415	12/2005	Casutt et al.	N/A	N/A
7074221	12/2005	Michelson	N/A	N/A
7128744	12/2005	Weaver et al.	N/A	N/A
7172593	12/2006	Trieu et al.	N/A	N/A
7179260	12/2006	Gerlach et al.	N/A	N/A
7230039	12/2006	Trieu et al.	N/A	N/A
7250053	12/2006	Orbay	N/A	N/A
7250054	12/2006	Allen et al.	N/A	N/A
7255701	12/2006	Allen et al.	N/A	N/A
7282053	12/2006	Orbay	N/A	N/A
7294130	12/2006	Orbay	N/A	N/A
7341589	12/2007	Weaver et al.	N/A	N/A
7419714	12/2007	Magerl et al.	N/A	N/A
7637928	12/2008	Fernandez	N/A	N/A
7695472	12/2009	Young	N/A	N/A
7722653	12/2009	Young et al.	N/A	N/A
7766948	12/2009	Leung	N/A	N/A
8105367	12/2011	Austin et al.	N/A	N/A
8992581	12/2014	Austin et al.	N/A	N/A
2001/0037112	12/2000	Brace et al.	N/A	N/A
2001/0047174	12/2000	Donno et al.	N/A	N/A
2002/0013587	12/2001	Winquist et al.	N/A	N/A
2002/0045901	12/2001	Wagner et al.	N/A	N/A
2002/0058940	12/2001	Frigg et al.	N/A	N/A
2002/0058943	12/2001	Kilpela et al.	N/A	N/A
2002/0115742	12/2001	Trieu et al.	N/A	N/A
2002/0143338	12/2001	Orbay et al.	N/A	N/A
2002/0161370	12/2001	Frigg et al.	N/A	N/A
2003/0040749	12/2002	Grabowski et al.	N/A	N/A
2003/0057590	12/2002	Loher et al.	N/A	N/A
2003/0060827	12/2002	Coughln	N/A	N/A
2003/0105462	12/2002	Haider	N/A	N/A
2003/0183335	12/2002	Winniczek et al.	N/A	N/A
2004/0010257	12/2003	Cachia et al.	N/A	N/A
2004/0030342	12/2003	Trieu et al.	N/A	N/A
2004/0044345	12/2003	DeMoss et al.	N/A	N/A
2004/0059334	12/2003	Weaver et al.	N/A	N/A
2004/0059335	12/2003	Weaver et al.	N/A	N/A
2004/0073218	12/2003	Dahners	N/A	N/A
2004/0087954	12/2003	Allen et al.	N/A	N/A
2004/0097942	12/2003	Allen et al.	N/A	N/A
2004/0138666	12/2003	Molz et al.	N/A	N/A
2004/0181228	12/2003	Wagner et al.	N/A	N/A
2004/0186477	12/2003	Winquist et al.	N/A	N/A
2004/0199169	12/2003	Koons et al.	N/A	N/A
2004/0213645	12/2003	Kovac	N/A	N/A
2004/0215195	12/2003	Shipp et al.	N/A	N/A
2004/0220570	12/2003	Frigg	N/A	N/A
2004/0236332	12/2003	Frigg	N/A	N/A

2004/0254579	12/2003	Buhren	606/71	A61B 17/8033
2004/0260306	12/2003	Fallin et al.	N/A	N/A
2005/0010220	12/2004	Casutt et al.	N/A	N/A
2005/0010226	12/2004	Grady et al.	N/A	N/A
2005/0027298	12/2004	Michelson	N/A	N/A
2005/0043736	12/2004	Mathieu et al.	N/A	N/A
2005/0049593	12/2004	Duong et al.	N/A	N/A
2005/0049594	12/2004	Wack et al.	N/A	N/A
2005/0070904	12/2004	Gerlach et al.	N/A	N/A
2005/0080421	12/2004	Weaver et al.	N/A	N/A
2005/0107796	12/2004	Gerlach et al.	N/A	N/A
2005/0137597	12/2004	Butler et al.	N/A	N/A
2005/0149026	12/2004	Buller et al.	N/A	N/A
2005/0165400	12/2004	Fernandez	N/A	N/A
2005/0192580	12/2004	Dalton	N/A	N/A
2005/0222570	12/2004	Jackson	N/A	N/A
2005/0234457	12/2004	James et al.	N/A	N/A
2005/0261688	12/2004	Grady et al.	N/A	N/A
2005/0277937	12/2004	Leung et al.	N/A	N/A
2005/0283154	12/2004	Orbay et al.	N/A	N/A
2006/0004361	12/2005	Hayeck et al.	N/A	N/A
2006/0009770	12/2005	Speirs et al.	N/A	N/A
2006/0009771	12/2005	Orbay et al.	N/A	N/A
2006/0095040	12/2005	Schlienger et al.	N/A	N/A
2006/0116678	12/2005	Impellizzeri	N/A	N/A
2006/0122602	12/2005	Konieczynski et al.	N/A	N/A
2006/0129148	12/2005	Simmons et al.	N/A	N/A
2006/0129151	12/2005	Allen et al.	N/A	N/A
2006/0149265	12/2005	James et al.	N/A	N/A
2006/0165400	12/2005	Spencer	N/A	N/A
2006/0167464	12/2005	Allen et al.	N/A	N/A
2006/0200147	12/2005	Ensign et al.	N/A	N/A
2006/0235400	12/2005	Schneider	N/A	N/A
2006/0235410	12/2005	Ralph et al.	N/A	N/A
2006/0259039	12/2005	Pitkanen et al.	N/A	N/A
2007/0010817	12/2006	de Coninck	N/A	N/A
2007/0043366	12/2006	Pfefferle et al.	N/A	N/A
2007/0093836	12/2006	Derouet	N/A	N/A
2007/0142921	12/2006	Lewis et al.	N/A	N/A
2007/0161995	12/2006	Trautwein et al.	N/A	N/A
2007/0162016	12/2006	Matityahu	N/A	N/A
2007/0162020	12/2006	Gerlach et al.	N/A	N/A
2007/0185488	12/2006	Pohjonen et al.	N/A	N/A
2007/0213828	12/2006	Trieu et al.	N/A	N/A
2007/0233106	12/2006	Horan et al.	N/A	N/A
2007/0260244	12/2006	Wolter	N/A	N/A
2007/0270691	12/2006	Bailey et al.	N/A	N/A
2007/0270832	12/2006	Moore	N/A	N/A

2007/0270833	12/2006	Bonutti et al.	N/A	N/A
2007/0276383	12/2006	Rayhack	N/A	N/A
2008/0021474	12/2007	Bonutti et al.	N/A	N/A
2008/0039845	12/2007	Bonutti et al.	N/A	N/A
2008/0086129	12/2007	Lindemann et al.	N/A	N/A
2008/0140130	12/2007	Chan et al.	N/A	N/A
2008/0154367	12/2007	Justis et al.	N/A	N/A
2008/0154368	12/2007	Justis et al.	N/A	N/A
2008/0154373	12/2007	Protosaltis et al.	N/A	N/A
2008/0167717	12/2007	Trieu et al.	N/A	N/A
2008/0200955	12/2007	Tepic	N/A	N/A
2008/0208259	12/2007	Gilbert et al.	N/A	N/A
2008/0234677	12/2007	Dahners et al.	N/A	N/A
2008/0234748	12/2007	Wallenstein et al.	N/A	N/A
2008/0234751	12/2007	McClintock	N/A	N/A
2008/0300637	12/2007	Austin et al.	N/A	N/A
2009/0024161	12/2008	Bonutti et al.	N/A	N/A
2009/0076553	12/2008	Wolter	N/A	N/A
2009/0088807	12/2008	Castaneda et al.	N/A	N/A
2009/0143824	12/2008	Austin et al.	N/A	N/A
2009/0149888	12/2008	Abdelgany	N/A	N/A
2009/0192549	12/2008	Sanders et al.	N/A	N/A
2009/0312803	12/2008	Austin	606/86R	A61B 17/8014
2010/0057138	12/2009	Murner	606/108	A61B 17/1728
2010/0256686	12/2009	Fisher et al.	N/A	N/A
2010/0312286	12/2009	Dell'Oca	N/A	N/A
2011/0015681	12/2010	Elsbury	N/A	N/A
2012/0059425	12/2011	Biedermann	N/A	N/A
2012/0083847	12/2011	Huebner et al.	N/A	N/A
2012/0136396	12/2011	Baker et al.	N/A	N/A
2012/0143193	12/2011	Hulliger	N/A	N/A
2012/0265253	12/2011	Conley et al.	N/A	N/A
2013/0165977	12/2012	Biedermann et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2047521	12/1991	CA	N/A
2408327	12/2000	CA	N/A
2536960	12/2004	CA	N/A
611147	12/1978	CH	N/A
1380043	12/2001	CN	N/A
2602900	12/1978	DE	N/A
3513600	12/1985	DE	N/A
3804749	12/1988	DE	N/A
3832343	12/1989	DE	N/A
4341980	12/1994	DE	N/A
4343117	12/1994	DE	N/A

4438261	12/1994	DE	N/A
4438264	12/1995	DE	N/A
19629011	12/1997	DE	N/A
102005015496	12/2005	DE	N/A
102005042766	12/2006	DE	N/A
19858889	12/2007	DE	N/A
0201024	12/1985	EP	N/A
0207884	12/1986	EP	N/A
0274713	12/1987	EP	N/A
0355035	12/1989	EP	N/A
0468192	12/1991	EP	N/A
0486762	12/1994	EP	N/A
0530585	12/1995	EP	N/A
0760632	12/1996	EP	N/A
0799124	12/2000	EP	N/A
1813292	12/2006	EP	N/A
1857073	12/2006	EP	N/A
2667913	12/1991	FR	N/A
2698261	12/1994	FR	N/A
2739151	12/1996	FR	N/A
2757370	12/1997	FR	N/A
2963396	12/2011	FR	N/A
580571	12/1945	GB	N/A
2521346	12/2014	GB	N/A
2003509107	12/2002	JP	N/A
2234878	12/2003	RU	N/A
1279626	12/1985	SU	N/A
477687	12/2001	TW	N/A
WO1989004150	12/1988	WO	N/A
WO1990007304	12/1989	WO	N/A
WO1996009014	12/1995	WO	N/A
WO1996019336	12/1995	WO	N/A
WO1996025892	12/1995	WO	N/A
WO1996029948	12/1995	WO	N/A
WO1997009000	12/1996	WO	N/A
WO1998034553	12/1997	WO	N/A
WO1998034556	12/1997	WO	N/A
WO1999005968	12/1998	WO	N/A
WO1999025266	12/1998	WO	N/A
WO1999061081	12/1998	WO	N/A
WO2000018309	12/1999	WO	N/A
WO2000019264	12/1999	WO	N/A
WO2000036984	12/1999	WO	N/A
WO2000053110	12/1999	WO	N/A
WO2000053111	12/1999	WO	N/A
WO2000066012	12/1999	WO	N/A
WO2001019267	12/2000	WO	N/A
WO2001019268	12/2000	WO	N/A
WO2001019264	12/2000	WO	N/A
WO2001078615	12/2000	WO	N/A

WO2001091660	12/2000	WO	N/A
WO2002000127	12/2001	WO	N/A
WO2002058574	12/2001	WO	N/A
WO2002068009	12/2001	WO	N/A
WO2002034159	12/2001	WO	N/A
WO2002096309	12/2001	WO	N/A
WO2003006210	12/2002	WO	N/A
WO2003106110	12/2002	WO	N/A
WO2004032726	12/2003	WO	N/A
WO2004032751	12/2003	WO	N/A
WO2004086990	12/2003	WO	N/A
WO2004089233	12/2003	WO	N/A
2004/107957	12/2003	WO	N/A
WO2005018471	12/2004	WO	N/A
WO2005018472	12/2004	WO	N/A
WO2005032386	12/2004	WO	N/A
WO2005034722	12/2004	WO	N/A
WO2005079685	12/2004	WO	N/A
WO2005062902	12/2004	WO	N/A
WO2006007965	12/2005	WO	N/A
WO2006039636	12/2005	WO	N/A
WO2006068775	12/2005	WO	N/A
WO2007014279	12/2006	WO	N/A
WO2007025520	12/2006	WO	N/A
WO2007041686	12/2006	WO	N/A
WO2007014192	12/2006	WO	N/A
WO2007092869	12/2006	WO	N/A
WO2007130840	12/2006	WO	N/A
WO200802213	12/2007	WO	N/A
WO2008033742	12/2007	WO	N/A
WO2008077137	12/2007	WO	N/A
WO2008079846	12/2007	WO	N/A
WO2008079864	12/2007	WO	N/A
WO2008116203	12/2007	WO	N/A
WO2009029908	12/2008	WO	N/A
WO2013/059090	12/2012	WO	N/A

OTHER PUBLICATIONS

Decision of Rejection for Japanese Application No. 2014-516034, mailed Mar. 27, 2017. cited by applicant

Office Action for U.S. Appl. No. 14/605,651, mailed Oct. 6, 2016. cited by applicant

Office Action for U.S. Appl. No. 14/535,573, mailed Oct. 24, 2016. cited by applicant

Patent Examination Report No. 2 for Australian Application No. 2012271441, issued Sep. 28, 2016. cited by applicant

Office Action for Russian Application No. 2013158111/14(090494), mailed May 17, 2016, with English-language synopsis. cited by applicant

Office Action for U.S. Appl. No. 14/671,499, mailed Jun. 2, 2016. cited by applicant

Office Action for U.S. Appl. No. 14/535,573, mailed Mar. 31, 2016. cited by applicant

Office Action for U.S. Appl. No. 14/605,651, mailed Mar. 14, 2016. cited by applicant

Notice of Reasons for Rejection for Japanese Application No. 2014-516034 mailed Jun. 6, 2016.

cited by applicant

Office Action for Chinese Application No. 201280039748.1, mailed Mar. 17, 2016. cited by applicant

Office Action for U.S. Appl. No. 14/535,573, mailed Oct. 1, 2015. cited by applicant

Notice of Reasons for Rejection for Japanese Application No. 2013-037623, mailed Jan. 26, 2015. cited by applicant

Notice of Reasons for Rejection for Japanese Application No. 2013-037623, mailed Mar. 3, 2014. cited by applicant

Wolter, D., et al., "Universal Internal Titanium Fixation Device," Trauma Berufskrankh (1999) 1:307-309, Springer-Verlag 1999, Certified English Translation Thereof. cited by applicant

Bohmer, G., et al., "Ti Fix® Angularly Stable Condylar Plate," Trauma Berufskrankh (1999) 1 :351-355, Springer-Verlag 1999, Certified English Translation Thereof. cited by applicant

Kranz, H.-W., et al., "Internal Titanium Fixation of Tibial Pseudarthrosis, Malalignment, and Fractures," Trauma Berufskrankh (1999) 1 :356-360, Springer-Verlag 1999, Certified English Translation Thereof. cited by applicant

Fuchs, S., et al., "Clinical Experiences with a New Internal Titanium Fixator for Ventral Spondylodesis of the Cervical Spine," Trauma Berufskrankh (1999) 1 :382-386, Springer-Verlag 1999, Certified English Translation Thereof. cited by applicant

Jurgens, C., et al., "Special Indications for the Application of the Fixed Angle Internal Fixation in Femur Fractures," Trauma Berufskrankh (1999) 1 :387,391, Springer-Verlag 1999, Certified English Translation Thereof. cited by applicant

Wolter, D., et al., "Titanium Internal Fixator for the Tibia," Trauma Berufskrankh, Mar. 2001 (Supp 2): S156-S161, Springer-Verlag 2001, Certified English Translation Thereof. cited by applicant

Fuchs, S., et al., "Titanium Fixative Plate System with Multidirectional Angular Stability in the Lower Leg and Foot," Trauma Berufskrankh, Mar. 2001 (Suppl 4): S447-S453, Springer-Verlag 2001, Certified English Translation Thereof. cited by applicant

Office Action for U.S. Appl. No. 13/774,721, mailed Aug. 22, 2013. cited by applicant

Australian Office Action in Application No. 2013202741, issued Feb. 3, 2014, 4 pages. cited by applicant

Examiner's First Report on Australian Application No. 2006272646, mailed Mar. 21, 2011, 4 pages. cited by applicant

Smith & Nephew Brochure entitled 'Surgical Technique PERI-LOC VLP Variable-Angle Locked Plating System,' pp. 1-32 (Nov. 2007). cited by applicant

Smith & Nephew Brochure entitled 'PERI-LOC VLP Variable-Angle Locked Plating System Distal Tibia Locking Plates,' 04 pages (Oct. 2007). cited by applicant

Smith & Nephew Brochure entitled 'PERI-LOC VLP Variable-Angle Locked Plating System Distal Fibula Locking Plates,' 04 pages (Oct. 2007). cited by applicant

Smith & Nephew Brochure entitled 'PERI-LOC VLP Variable-Angle Locked Plating System Proximal Tibia Locking Plates,' 04 pages (Oct. 2007). cited by applicant

Smith & Nephew Brochure entitled 'PERI-LOC VLP Variable-Angle Locked Plating System Proximal Tibia Variable-Angle Locking Plates,' 04 pages (Nov. 2007). cited by applicant

Smith & Nephew Brochure entitled 'PERI-LOC VLP Variable-Angle Locked Plating System Improved Torsional Fatigue Properties with Thin Locked Versus Non-Locked Plate Constructs for Fixation of Simulated Osteoporotic Distal Fibula Fractures,' 04 pages (Nov. 2007). cited by applicant

Winkelstabilität, Litos Unidirectional locking screw technology, Jan. 15, 2008, 5 pages

http://www.litos.com/pages/winkelstabilitaet_e.html. cited by applicant

"SMARTLock Locking Screw Technology," http://www.stryker.com/microimplants/products/cmf_smartlock.phn, Mar. 14, 2004. cited by applicant

International Search Report for PCT /US2006/028778, dated Apr. 19, 2007. cited by applicant

“Fracture and Dislocation Compendium,” Orthopaedic Trauma Association Committee for Coding and Classification, Journal of Orthopaedic Trauma, vol. 10, Suppl.,jp, v=ix, 1996. cited by applicant

English Abstract of JP 2002532185, Published Oct. 2, 2002. cited by applicant

English Abstract of ZA 200200992, Published Dec. 18, 2002, Applicant: Synthes AG. cited by applicant

NCB® Proximal Humerus Plating System, Surgical Technique, Zimmer, Inc. 2005. cited by applicant

Zimmer® NCB® Plating System, Zimmer, Inc. 2006. cited by applicant

NCB® Distal Femoral Plating System, Surgical Technique, Zimmer, Inc. 2005. cited by applicant

Office Action for Japanese Application No. 2008-0524048 mailed Oct. 25, 2011, 6 pages. cited by applicant

Office Action for U.S. Appl. No. 12/069,331 mailed Aug. 23, 2011, 12 pages. cited by applicant

International Preliminary Report on Patentability for International Application No. PCT/US2006/028778, mailed Jan. 29, 2008, 9 pages. cited by applicant

Office Action for U.S. Appl. No. 12/484,527, mailed May 18, 2011, 10 pages. cited by applicant

Office Action for U.S. Appl. No. 12/484,527, mailed Jan. 20, 2011, 9 pages. cited by applicant

DePuy brochure entitled “Every Surgeon has His or Her Own View,” Stryker Numelock II® Polyaxial Locking System, Operative Technique, Gtrauma Application, 6 pages (undated). cited by applicant

“Polyax Wide Angle Freedom Surgical Technique Distal Femoral Locked Playing System,” DePuy International Ltd., <http://www/rcsed.ac.uk/fellows/Ivanrensburg/classification/surgicaltech/depuy> (2005). cited by applicant

DePuy Orthopaedics, Inc., “Surgical Technique Distal Femoral Locked Plating System,” Polyax Wide Angle Freedom (2005). cited by applicant

Machine Translation of EP 1649819. cited by applicant

Final Office Action for U.S. Appl. No. 12/069,331, mailed Apr. 9, 2012. cited by applicant

Office Action for U.S. Appl. No. 11/996,795, mailed Mar. 23, 2012. cited by applicant

Decision of Rejection for Japanese Application No. 2008-0524048, mailed Oct. 30, 2011. cited by applicant

Office Action for U.S. Appl. No. 11/996,795, mailed Nov. 21, 2012. cited by applicant

Office Action for Canadian Patent Application No. 2,839,423, mailed Dec. 6, 2018. cited by applicant

Final Office Action for Japanese Application No. 2017-145326, mailed Jan. 28, 2019. cited by applicant

Office Action for Japanese Patent Application No. 2017-145326, mailed Nov. 5, 2019. cited by applicant

Examination Report for Indian Patent Application No. 10688/DELNP/2013, mailed Jan. 17, 2020. cited by applicant

Primary Examiner: Sipp; Amy R

Attorney, Agent or Firm: KDW Firm PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of U.S. patent application Ser. No. 16/569,204, filed Sep. 12, 2019, entitled “Variable

Angle Locking Implant”, which is a continuation application of U.S. patent application Ser. No. 15/970,747, filed May 3, 2018, now U.S. Pat. No. 10,448,980, entitled “Variable Angle Locking Implant”, which is a continuation application of U.S. patent application Ser. No. 13/524,506, filed Jun. 15, 2012, entitled “Variable Angle Locking Implant”, which application claims priority to and the full benefit of U.S. Provisional Application Ser. No. 61/497,180 filed Jun. 15, 2011, and entitled “Variable Angle Locking Implant,” the entire contents of each application incorporated herein by reference.

TECHNICAL FIELD

(1) This invention relates to a variable angle locking implant.

BACKGROUND

(2) Variable angle locking implants for repairing bone fractures have been described, for example, in U.S. patent application Ser. No. 12/484,527, filed Jun. 15, 2009, published as U.S. Publication No. 2009/0312803, hereby incorporated herein by reference in its entirety. In particular, U.S. Publication No. 2009/0312803 describes an implant having fastener receiving holes with fins that permit a fastener to be positioned off-axis within the hole.

(3) Implants such as bone plates have been provided with threaded holes (that may receive either locking screws or non-locking screws), non-threaded holes (for non-locking screws), partially threaded slots to allow either non-locking or locking screws to be used together, and combinations of the above.

SUMMARY

(4) The variable angle locking implant provides a stable connection between a bone and a bone plate using a fastener that permits different angles to be obtained between the bone plate and the fastener, while the fastener also locks into the bone plate. This allows the surgeon to reach denser areas of bone or capture random bone fragments that are in irregular positions, for example, in cases of severe fractures with highly fragmented bones. The fastener and plate system advantageously allows the surgeon to choose the angle at which the screw is inserted through, and rigidly affixed in, an opening of the plate.

(5) The variable angle locking implant allows a surgeon to direct the fastener toward bone fragments that are not necessarily located along the axis of the opening in the plate. It also provides flexibility in the placement of the plate in relation to the bone fracture. Allowing surgeons to choose the angle at which the fastener is inserted into the plate leads to better tailoring of the system to the specific nature of the bone fracture to be treated, and allows surgeons to adjust their strategy as necessary after the surgical site has been accessed, but prior to insertion of the fastener into bone material.

(6) According to one aspect, a variable angle locking implant includes a bone plate having a lower surface, an upper surface, and at least one opening extending from the lower surface to the upper surface along an axis. The opening has an inner surface with a plurality of fins oriented along a plane. The axis is non-perpendicular to a tangent of a projection of the lower surface across the opening, the tangent defined at the intersection between the axis and the projected lower surface, and/or the plane is non-parallel to the tangent.

(7) Implementations of this aspect may include one or more of the following features.

(8) For example, the lower surface includes a bone conforming arcuate surface. The lower surface is adapted to contact a distal femur, a proximal femur, a distal tibia, a proximal tibia, a proximal humerus, a distal humerus, a clavicle, a fibula, an ulna, a radius, a distal radius, a rib, pelvis, a vertebra, bones of the foot, or bones of the hand, shaft fractures on long bones, or any of the aforementioned adjacent bones in the case of a joint fusion plate.

(9) The fins are positioned within the opening. The axis is perpendicular to the tangent and the plane is non-parallel to the tangent. Alternatively, the axis is non-perpendicular to the tangent and the plane is non-parallel to the tangent, for example, the plane is perpendicular to the axis.

- (10) The fins are integrally connected to, and protruding from, the inner surface. The opening has a radius between the inner surface and the top of the fins, and each fin tapers in thickness from the inner surface towards its terminal end. The opening has a jagged circumference formed by protruding fins at the lower surface. The protruding fins form a concave portion of the inner surface. The protruding fins have bases that meet the inner surface along the plane. The fins have a tapered shape or a straight shape. The fins are provided in more than one layer. The fins are trapezoidally-shaped, rounded, oval, rectangular, curved, rhomboid, diamond-shaped, or triangular. The edges of the fins taper inwardly, outwardly, or are about parallel with one another. There are at least 3, but no more than 10, fins integrally connected to, and protruding from, the inner surface. The fins are provided as a series of concavely indented, inwardly protruding fins that are adapted to secure a threaded head of a fastener in place at varying angles.
- (11) The bone plate includes one or more of the following openings: a threaded opening; a non-threaded opening; an opening adapted to receive locking or non-locking fasteners; an opening with fins; a provisional fixation opening; a combination slot; or any combination thereof.
- (12) The implant includes at least one fastener. The fastener is at least partially threaded and has a head portion and a shaft portion. The opening is adapted to receive the fastener without being tapped by the fastener. The plurality of fins are deflectable relative to the head portion of the fastener when the fastener is inserted into the opening such that the fastener can be inserted and retained at any one of a plurality of angles relative to the opening. The fins are deflectable so that the fins are interposed between the threads of the fastener. The inner surface includes threads located above or below the fins.
- (13) According to another aspect, a method for securing a bone plate to a bone includes placing a lower surface of the bone plate against the bone; inserting a fastener into an opening in the bone plate, the opening having an axis that is non-perpendicular to a tangent of a projection of the lower surface across the opening, the tangent defined at the intersection between the axis and the projected lower surface, selecting a trajectory of the fastener into the bone, the trajectory being up to about 15 degrees off the hole axis; and inserting the fastener into the bone.
- (14) Implementations of this aspect may include one or more of the following features.
- (15) For example, either a locking screw or a non-locking screw is inserted in the opening. The fastener is removed and re-inserted into the opening of the bone plate at any one of a plurality of angles. Inserting the fastener into the bone includes drawing a bone fragment into alignment with an intact bone segment.
- (16) The details of one or more implementations of the invention are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an illustration of a variable angle locking implant positioned on a bone.
- (2) FIG. 2 is a cross-sectional view of the variable angle locking implant taken along line 2-2 of FIG. 1.
- (3) FIG. 3 is a perspective view of a bone plate and fastener of the variable angle locking implant.
- (4) FIG. 4 is a perspective view of a bone plate of the variable angle locking implant having a finned opening.
- (5) FIGS. 5A-5E are cross-sectional views of various implementations of the finned opening.

DETAILED DESCRIPTION

- (6) Referring to FIGS. 1 and 2, a variable angle locking implant 2 for repairing fractures in bone 4 includes a bone plate 40 and one or more fasteners 90. A fastener 90 is shown engaged in a finned

opening **50** that extends between an upper surface **44** and a lower, bone contacting surface **42** of the bone plate **40**. The fastener **90** can be positioned in the opening **50** and fixed in the plate **40** at various insertion angles to capture “renegade” or random bone fragments that have split from the bone during fracture and secure the bone fragments to the plate **40**.

(7) The fastener **90** shows a new trajectory achieved by increasing the range of angles as compared to the screw **90a**. For example, the central axis **96** of fastener **90** has an approximate 15 degree offset from the central axis **52** and approximately 30 degree offset from perpendicular to the lower surface **42** of the bone plate **40**. The alternative placement of a screw **90a** in a hole having an axis **52** perpendicular to the lower surface **42** of the plate **40** and a plane **59** that is parallel to the bottom lower surface **42** illustrates approximately a 15 degree offset from the central axis **52** and a corresponding approximately 15 degree offset from perpendicular to the lower surface **42** of the bone plate **40**, thus illustrating the greater range of the insertion angle of the fastener **90**.

(8) The locking implant **2** also includes a provisional pin opening **102** as well as a combination slot **104**.

(9) Referring also to FIGS. **3** and **4**, the plate **40** has an inner surface **54** that defines the opening **50** and a series of concavely indented, inwardly protruding fins **56** that extend toward a central axis **52** of the opening **50**. Each fin **56** has a base **58** and the bases **58** form concave portions **60**. The bases **58** of the fins **56** all meet, for example, in substantially the same plane **59a-59d** (FIGS. **5A-5D**) and then angle downwardly and inwardly at a similar angle or slope. As discussed further below, the central axis **52** can be oriented non-perpendicular to the lower surface **42** and/or the planes **59a-59d** can be oriented non-parallel to the lower surface **42** to increase the range of possible insertion angles.

(10) The concave portions **60** are smooth and non-threaded, and as illustrated, the entire inner surface **54** of the finned opening **50** can be devoid of threads. The lack of threads helps ease the manufacturing of the plate **40**, and allows the plate **40** to be manufactured as thinly as desired. The bases **58** can extend from the inner surface **54** at or near an upper circumference **62** of the inner surface, at a middle region of the inner surface, or at or near a lower circumference of the inner surface. With the fins **56** located adjacent a lower circumference at the lower, bone contacting surface **42** of plate **40**, the lower circumference appears jagged due to the presence of the fins, while the upper circumference **62** is smooth.

(11) As the fins **56** extend toward central axis **52**, they taper to form tapered sides **64**. The fins **56** end at rounded tips **66**, although tips **66** can be pointed, square, rectangular, or any other appropriate configuration. For example, as described in U.S. Patent Application Publication No. 2009/0312803, which is incorporated herein by reference in its entirety, the fins **56** can have straight edges or sides and straight ends such that the fins are partially rectangular-shaped with slit-shaped openings between the fins. Alternatively, the fins can be more triangular in shape having sides that taper inwardly and end edges that are flat and small. Other example fin shapes include trapezoidal, square, round, circular, triangular (with a pointed tip).

(12) The dimensions of fins **56** are typically dependent at least in part upon the pitch and threads of the fastener **90**. For example, a larger plate **40** for use with a larger fastener **90** (for example, for use on a femur bone) will likely be thicker and will have larger and thicker fins **56** than a smaller plate **40** (for example, for use on a smaller bone). In specific implementations, the fins **56** are particularly thin so that they can be moved up or down and deformed under pressure. In some implementations, the fins **56** may be pressed toward the edges of the finned opening **50**. A non-limiting exemplary range of thicknesses for the fins **56** is from about 0.15 mm to about 5 mm, although larger and smaller sizes are possible. The fins **56** are intended to fit between threads **98** on the thread form of fastener **90**, as shown in FIG. **3**.

(13) Providing a non-threaded inner surface **54** also allows the fastener **90** to be inserted into the finned opening **50** at any desired insertion angle, that is the angle defined between a longitudinal axis **96** (FIG. **2**) of the fastener **90** and the central axis **52** (FIG. **4**) of the finned opening **50**. The

central axis **52** and the longitudinal axis **96** can be co-linear so that the insertion angle is zero, or the central axis **52** and the longitudinal axis **96** (FIG. 1) can be non-co-linear with an insertion angle of up to about ± 15 degrees. Varying the insertion angle is possible because there are not any threads in the finned opening **50** to interfere with the desired insertion angle. The fins **56** are intended to slightly bend or deform in order to secure the fastener **90** in place in the finned opening **50**. The fins **56** engage the threads **98** or other surface of the fastener **90**.

(14) The fastener **90** has a head **94** and a shaft **92**. The shaft **92** may be threaded or non-threaded. The head **94** of the fastener **90** has at least one set of threads **98** and a bore **18** for receiving a driver in order to drive the fastener **90** through the plate **40** and into bone. The threads **98** are typically any standard-type thread.

(15) Referring to FIGS. 5A and 5B, the central axis **52a**, **52b** of the opening **50** can be oriented non-perpendicular to the lower surface **42** of the plate **40**, for example, at an angle, Θ , in the range between 0 and 90 degrees. In FIG. 5A, two rows of fins **56** are illustrated that each lie in a plane **59a** that is parallel to the lower surface **42** of the plate **40**. In FIG. 5B, the fins **56** lie in a plane **59b** that is oriented non-parallel to the lower surface **42** of the plate **40**, for example, the plane **59b** is perpendicular or nearly perpendicular to the axis **52b**. In FIG. 5C, the fins **56** are illustrated lying in a plane **59c** that is oriented non-parallel to the lower surface **42** of the plate **40** and the plane **59c** is non-perpendicular to the axis **52c**. The fins **56** of FIGS. 5B and 5C are positioned within the opening **50**, that is, between the upper surface **44** and lower surface **42** of the plate **40**.

(16) The non-perpendicular orientation of the central axis **52a**, **52b**, **52d** and/or the non-parallel orientation of the plane **59b-d** increases the useful range of possible insertion angles as compared to a bone plate **40** having the central axis **52** perpendicular to the lower surface **42** and the plane **59** parallel to the lower surface **42**. For example, referring to FIG. 5B, assuming Θ is 15 degrees, a fastener **90** could be inserted with the fastener axis **96** aligned with axis **52b**, and thus 15 degrees off from perpendicular to the lower surface **42**, or the fastener axis **96** could be tilted up to, for example, ± 15 degrees, such that the fastener axis **96** is perpendicular to the lower surface **42** or up to 30 degrees off from perpendicular to reach bone fragments. Increasing the range of angles allows the surgeon to target new fastener trajectories in the bone as shown in FIG. 2.

(17) The screw **90** (FIG. 2) shows a new trajectory achieved by increasing the range of angles as compared to the screw **90a**. The fastener **90** is shown positioned in the hole of FIG. 5B and having a 15 degree offset from the central axis **52** and 30 degree offset from perpendicular to the lower surface **42** of the bone plate **40**. The alternative placement of a screw **90a** in a hole having an axis **52** perpendicular to the lower surface **42** of the plate **40** and a plane **59** that is parallel to the lower surface **42** illustrates a 15 degree offset from the central axis **52** and only a corresponding 15 degree offset from perpendicular to the lower surface **42** of the bone plate **40**, thus illustrating the greater range of the insertion angle of the fastener **90**. Angling the screw greater than 15 degrees from the central axis **52** of an opening having an axis **52** perpendicular to the lower surface **42** of the plate **40** and a plane **59** that is parallel to the lower surface **42** produces inconsistent failure loads. Therefore, to achieve a screw trajectory greater than 15 degrees from the lower surface **42** of the plate **40** while maintaining the ability to capture and secure bone fragments, the angle of the central axis **52** is offset from perpendicular to the lower surface **42** and the screw axis **96** tilted to reach a maximum of 30 degrees offset.

(18) Referring to FIG. 5D, the range of insertion angles can also be increased by orienting the axis **52d** of the opening **50** perpendicular to the lower surface **42** of the plate **40**, while the fins **56** lie in a plane **59d** that is non-parallel to the lower surface, for example, at an angle, α , in the range between 0 and 90 degrees.

(19) The finned opening **50** can include about five to eight fins **56**, as illustrated, two or three fins **56**, or ten or twenty or more fins **56**, depending upon the plate **40** for which the finned opening **50** is intended for use. The finned holes can optionally include threads **112** (FIG. 5B) formed above or below the fins in the inner surface of the hole. The region of the opening above the fins can taper

inwardly from the upper surface of the plate, for example, at an angle of about 5 to 15 degrees, and the region of the opening below the fins can taper outwardly toward the lower surface of the plate, for example, at an angle of about 40 to 50 degrees. The finned opening **50** can optionally be a slot hole or combination hole with half or more of the length of the opening can be finned with the remainder of the opening being non-threaded for sliding compression.

(20) The primary purpose of fins **56** is to grasp one or more threads **98** of the fastener **90** in order to secure the fastener **90** in place in the bone plate **40** at any desired insertion angle. Fasteners **90** received in different finned openings **50** can be inserted at the same or different insertion angles. As a fastener **90** is inserted, its threads **98** start to engage the fins **56**, as shown in FIG. 3. As discussed above, the fins **56** can be very thin so that as the threads **98** start to grab the fins **56**, the fins **56** can move up or down as appropriate to engage the threads **98** and secure the fastener **90** in the finned opening **50**. The threads **98** engage the fins **56** so that the fins **56** fit between the threads **98**. The movement of fins **56** can be a permanent deformation, so that the fins **56** cannot flex back and allow the fastener **90** to work its way out.

(21) The finned openings **50** can be provided on all types of bone plates **40** and can be combined with other types of openings. As illustrated in FIG. 1, there can be finned openings **50**, a threaded opening **30**, and a provisional pin opening **102**. Other options are holes that can be used with either a threaded or non-threaded fastener, as well as combination slots **104**. For example, a slot having fins mounted on either or both ends of the slot for static locking and no threads or fins in the middle portion of the slot for dynamic locking. These various types of openings may be used on any type of bone plate, in any combination and in any size. The inclusion of a plurality of finned openings **50** in the bone plate **40** can help achieve better fixation of a fractured bone, for example, where numerous fragments have shattered in various directions, because the fasteners **90** can be inserted at various angles to capture “renegade” or random bone fragments that have split from the bone during fracture, but still secure the bone fragments to the plate **40**.

(22) The threads **98** on fastener **90** can be any type of standard or non-standard thread. For example, the threads **98** can be a continuous ridge or a non-continuous ridge. The threads **98** can form a portion of a revolution, one complete revolution, multiple revolutions, a single lead, or multiple leads, or any other threads known in the art. Additionally or alternatively, the head **94** of fastener **90** can include any other surface that will engage with and seat within the fins **56** of the finned opening **50**. For example, the head **94** can have a series of dimples, ridges, bumps, textured areas, or any other surface that can secure fastener **90**.

(23) The fastener **90** may be any typical fastener, made out of any appropriate material. The fastener **90** typically has a bore **18** for receiving a driver in order to drive the fastener **90** through the plate **40** and into bone. The bore **18** may be any size and shape, for example, it may have a hexagonal configuration to receive a corresponding hexagonal driver, a Phillips screw head, a flat-head, a star configuration, Torx, or any other appropriate configuration that can cooperate with a driver to drive the fastener **90** into the plate **40**.

(24) The shaft **92** may be fully threaded, partially threaded, or a helical blade, and/or may include one or more tacks, deployable talons, expandable elements, or any feature that allows shaft **92** to engage bone. It is also possible that shaft **92** is not threaded, so that fastener **90** takes the form of a peg or a pin. This alternative implementation may be preferred in certain procedures where, for instance, the main goal is to prevent tilting of a bone segment or in procedures where there is no concern of fastener **90** pulling out from the bone and hence no need for shaft **92** to be threaded or otherwise configured to engage bone. The end of shaft **92** may be a self-tapping or self-drilling tip.

(25) The bone plate **40** may be adapted to contact one or more of a distal femur, a proximal femur, a distal tibia, a proximal tibia, a proximal humerus, a distal humerus, a clavicle, a fibula, an ulna, a radius, a distal radius, a rib, pelvis, a vertebra, bones of the foot, or bones of the hand, shaft fractures on long bones, or any of the aforementioned adjacent bones in the case of a joint fusion plate. The bone plate **40** may be curved, contoured, straight, or flat. The lower, bone contacting

surface **42** can have an arcuate shape that conforms to the bone. For example, referring to FIG. 5E, the bone plate **40** is shown with a bone contacting surface **42** having an arcuate or curved shape. In the implementation shown, the central axis **52** of the opening **50** can be oriented non-perpendicular to a tangent line or tangent plane T-T of the projected arcuate bone contacting surface **42** that intersects the central axis **52** at a point P along the projected bone contacting surface **42**, for example, at an angle, Θ , in the range of between 0 and 90 degrees. In FIG. 5E, a row of fins **56** is illustrated that each lie in a plane **59e** that is oriented non-parallel to the tangent line or plane T-T. The fins **56** can alternatively be located at the lower surface **42** and also have an arcuate shape that conforms to the bone. The plate can be a periarticular plate or a straight plate. The plate may have a head portion that is contoured to conform to a particular bone surface, such as a metaphysis or diaphysis, that flares out from the shaft portion, that forms an L-shape, T-shape, Y-shape, with the shaft portion, or that forms any other appropriate shape to fit the bone to be treated.

(26) The bone plate **40** can be made from metal, a resorbable or non-resorbable plastic, ceramic, or composite materials. Suitable materials may include, for example, titanium, stainless steel, cobalt chrome, polyetheretherketone (PEEK), polyethylene, ultra high molecular weight polyethylene (UHMWPE), resorbable polylactic acid (PLA), polyglycolic acid (PGA), combinations or alloys of such materials or any other appropriate material that has sufficient strength to be secured to and hold bone, while also having sufficient biocompatibility to be implanted into a body.

(27) Turning now to the methods of implantation, the surgeon accesses the surgical site of interest, which can be an internal site at which a bone fracture is located that requires stabilization to ensure proper healing. The fracture may be reduced with conventional forceps and guides (which are known to those in the art), and a bone plate **40** of appropriate size and shape is placed over the fracture site. In some instances, the bone plate **40** may be temporarily secured to the bone **4** using provisional fixation pins. The provisional fixation pins may be used through either the provisional pin openings **102**, or any other opening in the plate **40**. Provisional fixation provides for temporarily securing the bone plate **40** to the bone **4** before placing fixation screws through the bone plate **40**, so that one can be certain the bone plate **40** is properly positioned before placing bone screws for permanent fixation of the bone plate **40** to the bone **4**. Moreover, with provisional fixation, x-rays can be taken of the bone plate/construct without excess instruments in the field of view.

(28) Once the plate **40** is secured at a desired location in relation to the fracture (typically using one or more provisional fixation pins, although any other appropriate method may be used), the surgeon then identifies an insertion angle at which the fastener **90** is to be inserted through a selected opening **50** and driven into bone material **4**. If the bone plate **40** includes more than one opening **50**, the surgeon also selects the specific opening **50** to be used. After selecting the desired insertion angle and the opening **50**, the surgeon inserts the shaft **92** of the fastener **90** through the opening **50** until the tip contacts bone material **4**. In some cases, a hole may need to be drilled or tapped into the bone **4** along the insertion angle to facilitate the initial tapping or insertion of the fastener **90**. The surgeon then uses an appropriate driving tool in the bore **18** of the head **94** to manipulate the fastener **90** into place.

(29) Because the fastener **90** can be inserted at angles up to about 60 degrees from perpendicular to the lower surface of the plate, the fastener **90** can be used to grab and/or secure bone fragments that are out of line with the traditional angle at which a locking screw would normally be inserted. The surgeon may need to toggle or maneuver the fastener **90** in order to secure and draw in displaced bone fragments.

(30) Once the bone fragment is secured, the fastener **90** is ready to be secured to the plate **40**. As the fastener **90** is driven further into bone **4**, it is also drawn further into the plate **40**. As the threads **98** of the fastener head **94** begin to contact the fins **56**, the fins **56** engage within the threads **98** to hold the fastener **90** in place at the desired insertion angle. The action of engagement between the fins **56** and the threads **98** rigidly affixes the fastener **90** to the bone plate **40** at the desired insertion

angle.

(31) The surgeon may then use traditional locking and/or non-locking screws in other openings on the plate **40**. This can help further secure the bone plate **40** to the bone fracture if needed.

(32) Once all the fasteners and/or screws are placed, the surgeon may place covers over the unused openings, particularly if there are any unused openings that cross the fracture, to strengthen the plate **40**. Additionally or alternatively, the surgeon may use bone graft material, bone cement, bone void filler, and any other material to help heal the bone.

(33) In practice, a first screw is initially inserted through a bone plate **40** and into a bone **4** on one side of a fracture and then a second screw is inserted through the bone plate **40** on the opposite side of the fracture. In particular, after the first screw is in place, an axial compression screw is inserted through a hole in the bone plate **40** on a side of the fracture opposite the side of the first screw. The compression screw may be inserted through the hole and into the bone **4** such that as the compression screw is fully inserted, the bone plate **40** is drawn over to a desired position. By moving the bone plate **40**, the tissue is pulled together to reduce the fracture. Once the compression screw has been used to move the bone plate **40** into the desired position, the compression screw may be removed from the bone **4** and bone plate **40** and a locking screw may be inserted through the opening **50** in the bone plate **40** and in the bone **4** in the space formerly occupied by the compression screw. The locking screw can then be tightened to lock the plate **40** into position. The replacement of the compression screw with the locking screw is not required, but a locking screw may provide more stability and rigid fixation than leaving the compression screw in place. In some modes of operation, a locking screw is placed directly in a locking hole without first inserting a compression screw in the hole.

(34) A number of implementations of the invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the invention. Accordingly, other implementations are within the scope of the following claims. For example, locking screws, non-locking screws, or other fasteners may be used. One or more openings having a non-perpendicular orientation of the central axis **52** and/or the non-parallel orientation of the plane **59** can be employed to receive a fastener in implants other than plates, such as in an acetabular cup or glenoid base component, to increase the useful range of possible insertion angles of the fastener. According to another implementation, the head of the screw **94** can include the fins **56** and the opening **50** can be threaded, with the opening having a non-perpendicular orientation of its central axis **52** and/or the plane **59** defined by the fins **56** having a non-parallel orientation.

Claims

1. An implant comprising: a first surface; a second surface; and at least one opening extending from the first surface to the second surface, the at least one opening including: a central axis; an inner surface including a plurality of fins defining a circumferential edge to contact a head of a bone fastener in use; and a plurality of threads formed on the inner surface; wherein the at least one opening is configured to secure the bone fastener with respect to the implant.
2. The implant of claim 1, wherein the central axis is non-perpendicular to a tangent of a projection of the first surface across the opening, the tangent defined at an intersection between the central axis and the projected first surface.
3. The implant of claim 2, wherein the plurality of fins are oriented along a plane, wherein each of the fins has a base and a tip, wherein each of the fins extends through the plane from the base to the tip, and wherein the tip of each fin has a rounded, convex curve that lies in the plane.
4. The implant of claim 3, wherein the plane along which the plurality of fins is oriented is nonparallel to the tangent.
5. The implant of claim 4, wherein the plane is perpendicular to the central axis.

6. The implant of claim 1, wherein the plurality of fins are adapted and configured to deform in order to secure a position of the head of the bone fastener inserted into the at least one opening.
 7. The implant of claim 1, wherein the implant is a bone plate, the first surface is a bone contacting surface, and the plurality of threads are positioned closer to the bone contacting surface than the plurality of fins.
 8. The implant of claim 7, wherein the bone contacting surface is adapted to contact a distal femur, a proximal femur, a distal tibia, a proximal tibia, a proximal humerus, a distal humerus, a clavicle, a fibula, an ulna, a radius, a distal radius, a rib, pelvis, a vertebra, bones of a foot, or bones of a hand.
 9. The implant of claim 7, wherein the central axis is non-perpendicular to the bone contacting surface, the plurality of fins are oriented along a plane, wherein the plane is oriented nonparallel to the bone contacting surface.
 10. The implant of claim 9, wherein the central axis is orientated an angle relative to the bone contacting surface, the angle being fifteen degrees.
 11. The implant of claim 1, wherein each of the plurality of fins includes a tip having a rounded, convex curve, each of the plurality of fins extends toward the central axis of the opening from a base to the rounded, convex curve, and each of the plurality of fins has a width in the plane that decreases from the base to the tip in a direction toward the central axis of the opening.
 12. The implant of claim 1, wherein the implant has at least 3, but no more than 10, fins integrally connected to, and protruding from, the inner surface.
 13. The implant of claim 1, wherein the plurality of fins are provided as a series of inwardly protruding fins that are adapted to secure the head of the bone fastener in place at varying angles, wherein the head is threaded, wherein adjacent fins in the series of inwardly protruding fins cooperate to form a curved, concave indentation along the plane.
 14. The implant of claim 1, wherein the opening is adapted to receive the bone fastener without being tapped by the bone fastener, wherein the plurality of fins are deflectable relative to the head of the bone fastener when the bone fastener is inserted into the opening such that the bone fastener can be inserted and retained at any one of a plurality of angles relative to the opening.
 15. The implant of claim 14, wherein the plurality of fins are deflectable so that the plurality fins are interposed between threads of the bone fastener.
 16. A variable angle locking implant comprising: a bone plate having: an end portion; a shaft portion that extends along a longitudinal axis; a lower bone contacting surface; an upper surface; and an opening including: a central axis, the opening extending along the central axis from the lower bone contacting surface to the upper surface; an inner surface including a plurality of fins oriented along a plane, wherein each of the fins has a base and a tip, wherein each of the fins extends through the plane from the base to the tip, the tips of the plurality of fins collectively defining a circumferential edge to contact a head of a bone fastener in use; and a plurality of threads formed on the inner surface.
 17. The variable angle locking implant of claim 16, wherein the central axis is non-perpendicular to the lower bone contacting surface and the plane is oriented nonparallel to the lower bone contacting surface.
 18. The variable angle locking implant of claim 16, wherein the plurality of threads are positioned closer to the lower bone contacting surface than the plurality of fins.
-