



US012383411B2

(12) **United States Patent**
Spann

(10) **Patent No.:** **US 12,383,411 B2**

(45) **Date of Patent:** **Aug. 12, 2025**

(54) **SPINAL SURGERY METHODS AND DEVICES**

(71) Applicant: **Pantheon Spinal, LLC**, Austin, TX (US)

(72) Inventor: **Scott Spann**, Austin, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/990,254**

(22) Filed: **Nov. 18, 2022**

(65) **Prior Publication Data**

US 2023/0081748 A1 Mar. 16, 2023

Related U.S. Application Data

(63) Continuation of application No. 17/209,874, filed on Mar. 23, 2021, now Pat. No. 11,969,359, which is a continuation of application No. 16/149,108, filed on Oct. 1, 2018, now Pat. No. 10,959,860, which is a continuation of application No. 15/235,957, filed on Aug. 12, 2016, now Pat. No. 10,085,854, which is a continuation of application No. 13/239,014, filed on (Continued)

(51) **Int. Cl.**

A61F 2/44 (2006.01)

A61B 17/02 (2006.01)

A61F 2/46 (2006.01)

A61F 2/30 (2006.01)

(52) **U.S. Cl.**

CPC **A61F 2/4611** (2013.01); **A61B 17/02** (2013.01); **A61F 2/44** (2013.01); **A61F 2/4455** (2013.01); **A61F 2/446** (2013.01); **A61F 2/4465** (2013.01); **A61F 2/447** (2013.01); **A61F 2/4684** (2013.01); **A61F 2002/30538** (2013.01); **A61F 2002/30593** (2013.01); **A61F**

2002/30772 (2013.01); **A61F 2002/30777** (2013.01); **A61F 2002/30784** (2013.01); **A61F 2002/30843** (2013.01); **A61F 2002/4627** (2013.01); **A61F 2002/4629** (2013.01); **A61F 2250/0006** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,706,500 A 3/1929 Smith
D245,789 S 9/1977 Shea et al.
(Continued)

FOREIGN PATENT DOCUMENTS

DE 299 08 259 7/1999
DE 10048790 4/2002
(Continued)

OTHER PUBLICATIONS

"MetRx System MicroEndoscopic Discectomy: An Evolution in Minimally Invasive Spine Surgery," *Sofamor Danek*, 1999, 6 pages.
(Continued)


Primary Examiner — Jan Christopher L Merene

(74) *Attorney, Agent, or Firm* — Avantech Law, LLP

(57) **ABSTRACT**

Disclosed methods, devices and systems are suitable for performing a minimally-invasive procedure for accessing the intervertebral space along an oblique pathway with an insertion instrument that holds a disc implant, and reorienting the angular relationship between instrument and implant while the implant is inside the body (for example at or within the disc space).

23 Claims, 22 Drawing Sheets



Related U.S. Application Data

Sep. 21, 2011, now Pat. No. 9,451,940, which is a continuation of application No. 13/133,909, filed as application No. PCT/US2009/069476 on Dec. 23, 2009, now abandoned.

- (60) Provisional application No. 61/178,315, filed on May 14, 2009, provisional application No. 61/140,926, filed on Dec. 26, 2008.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,512,351 A	4/1985	Pohndorf	5,375,067 A	12/1994	Berchin
4,515,168 A	5/1985	Chester et al.	5,375,594 A	12/1994	Cueva
4,519,403 A	5/1985	Dickhudt	5,383,876 A	1/1995	Nardella
4,545,374 A	10/1985	Jacobson	5,395,317 A	3/1995	Kambin
4,561,445 A	12/1985	Berke et al.	5,450,845 A	9/1995	Alexgaard
4,562,832 A	1/1986	Wilder et al.	5,472,426 A	12/1995	Bonati et al.
4,573,448 A	3/1986	Kambin	5,474,057 A	12/1995	Makower et al.
4,592,369 A	6/1986	Davis et al.	5,474,558 A	12/1995	Neubardt
4,595,013 A	6/1986	Jones et al.	5,480,440 A	1/1996	Kambin
4,595,018 A	6/1986	Rantala	5,482,038 A	1/1996	Ruff
4,611,597 A	9/1986	Kraus	5,484,437 A	1/1996	Michelson
4,616,635 A	10/1986	Caspar et al.	5,487,739 A	1/1996	Aebischer et al.
4,633,889 A	1/1987	Talalla	5,509,893 A	4/1996	Pracas
4,658,835 A	4/1987	Pohndorf	5,514,153 A	5/1996	Bonutti
D295,445 S	4/1988	Freeman	5,514,180 A	5/1996	Heggeness et al.
4,744,371 A	5/1988	Harris	5,540,235 A	7/1996	Wilson
4,753,223 A	6/1988	Bremer	5,549,656 A	8/1996	Reiss
4,759,377 A	7/1988	Dykstra	5,560,372 A	10/1996	Cory
4,784,150 A	11/1988	Voorhies et al.	5,566,678 A	10/1996	Cadwell
4,807,642 A	2/1989	Brown	5,569,290 A	10/1996	McAfee
D300,561 S	4/1989	Asa et al.	5,571,149 A	11/1996	Liss et al.
4,892,105 A	1/1990	Prass	5,579,781 A	12/1996	Cooke
4,913,134 A	4/1990	Luque	5,593,429 A	1/1997	Ruff
4,917,274 A	4/1990	Asa et al.	5,599,279 A	2/1997	Slotman et al.
4,917,704 A	4/1990	Frey et al.	5,609,635 A	3/1997	Michelson
4,926,865 A	5/1990	Oman	5,630,813 A	5/1997	Kieturakis
4,934,352 A	6/1990	Sullivan	5,667,508 A	9/1997	Errico et al.
4,950,257 A	8/1990	Hibbs et al.	5,671,752 A	9/1997	Sinderby et al.
4,962,766 A	10/1990	Herzon	5,681,265 A	10/1997	Maeda et al.
4,964,411 A	10/1990	Johnson et al.	5,688,223 A	11/1997	Rosendahl
5,007,902 A	4/1991	Witt	5,707,359 A	1/1998	Bufalini
5,015,247 A	5/1991	Michelson	5,711,307 A	1/1998	Smits
5,045,054 A	9/1991	Hood et al.	5,728,046 A	3/1998	Mayer et al.
5,052,373 A	10/1991	Michelson	5,741,253 A	4/1998	Michelson
5,058,602 A	10/1991	Brody	5,741,261 A	4/1998	Moskovitz et al.
5,081,990 A	1/1992	Deletis	5,759,159 A	6/1998	Masreliez
5,092,344 A	3/1992	Lee	5,762,629 A	6/1998	Kambin
5,127,403 A	7/1992	Brownlee	5,772,661 A	6/1998	Michelson
5,161,533 A	11/1992	Prass et al.	5,775,331 A	7/1998	Raymond et al.
5,171,279 A	12/1992	Mathews	5,776,144 A	7/1998	Leysieffer et al.
5,192,327 A	3/1993	Brantigan	5,776,199 A	7/1998	Michelson
5,195,541 A	3/1993	Obenchain	5,779,642 A	7/1998	Nightengale
5,196,015 A	3/1993	Neubardt	5,785,658 A	7/1998	Benaron
5,215,100 A	6/1993	Spitz et al.	5,792,044 A	8/1998	Foley et al.
RE34,390 E	9/1993	Culver	5,797,854 A	8/1998	Hedgecock
D340,521 S	10/1993	Heinzelman et al.	5,797,909 A	8/1998	Michelson
5,255,691 A	10/1993	Otten	5,814,073 A	9/1998	Bonutti
5,282,468 A	2/1994	Klepinski	5,830,151 A	11/1998	Hadzic et al.
5,284,153 A	2/1994	Raymond et al.	5,851,191 A	12/1998	Gozani
5,284,154 A	2/1994	Raymond et al.	5,853,373 A	12/1998	Griffith et al.
5,295,994 A	3/1994	Bonutti	5,860,973 A	1/1999	Michelson
5,297,538 A	3/1994	Daniel	5,862,314 A	1/1999	Jeddeloh
5,299,563 A	4/1994	Seton	5,872,314 A	2/1999	Clinton
5,312,417 A	5/1994	Wilk	5,885,210 A	3/1999	Cox
5,313,956 A	5/1994	Knutsson et al.	5,885,219 A	3/1999	Nightengale
5,313,962 A	5/1994	Obenchain	5,888,196 A	3/1999	Bonutti
5,327,902 A	7/1994	Lemmen	5,888,227 A *	3/1999	Cottle
5,331,975 A	7/1994	Bonutti	5,891,147 A	4/1999	Moskovitz et al.
5,333,618 A	8/1994	Lekhtman et al.	5,895,352 A	4/1999	Kleiner
5,337,736 A	8/1994	Reddy	5,902,231 A	5/1999	Foley et al.
5,342,384 A	8/1994	Sugarbaker	5,928,139 A	7/1999	Koros et al.
5,352,219 A	10/1994	Reddy	5,928,158 A	7/1999	Aristides
5,357,983 A	10/1994	Mathews	5,931,777 A	8/1999	Sava
			5,935,131 A	8/1999	Bonutti et al.
			5,938,688 A	8/1999	Schiff
			5,944,658 A	8/1999	Koros et al.
			5,976,094 A	11/1999	Gozani et al.
			5,984,922 A	11/1999	McKay
			6,004,262 A	12/1999	Putz et al.
			6,004,312 A	12/1999	Finneran
			6,007,487 A	12/1999	Foley et al.
			6,010,520 A	1/2000	Pattison
			6,024,696 A	2/2000	Hoftman et al.
			6,024,697 A	2/2000	Pisarik
			6,027,456 A	2/2000	Feler et al.
			6,030,401 A	2/2000	Marino
			6,038,469 A	3/2000	Karlsson et al.
			6,038,477 A	3/2000	Kayyali

A61F 2/4455
623/17.16

(56)

References Cited

U.S. PATENT DOCUMENTS

6,042,540 A	3/2000	Johnson et al.	6,535,759 B1	3/2003	Epstein et al.
6,050,992 A	4/2000	Nichols	6,540,747 B1	4/2003	Marino
6,074,343 A	6/2000	Nathanson et al.	6,564,078 B1	5/2003	Marino et al.
6,080,105 A	6/2000	Spears	6,579,244 B2	6/2003	Goodwin
6,080,155 A	6/2000	Michelson	6,599,294 B2	7/2003	Fuss et al.
6,083,154 A	7/2000	Liu et al.	6,620,157 B1	9/2003	Dabney et al.
6,095,987 A	8/2000	Schmulewitz	6,645,194 B2	11/2003	Briscoe et al.
6,096,026 A	8/2000	Schultz	6,679,833 B2	1/2004	Smith et al.
6,104,957 A	8/2000	Alo et al.	6,719,692 B2	4/2004	Kleffner et al.
6,104,960 A	8/2000	Duysens et al.	6,723,043 B2	4/2004	Kleeman et al.
6,120,503 A	9/2000	Michelson	6,760,616 B2	7/2004	Hoey et al.
6,126,660 A	10/2000	Dietz	6,764,452 B1	7/2004	Gillespie et al.
6,132,386 A	10/2000	Gozani et al.	6,770,074 B2	8/2004	Michelson
6,132,387 A	10/2000	Gozani et al.	6,796,985 B2	9/2004	Bolger et al.
6,135,965 A	10/2000	Tumer et al.	6,802,844 B2	10/2004	Ferree
6,139,493 A	10/2000	Koros et al.	6,810,281 B2	10/2004	Brock et al.
6,142,931 A	11/2000	Kaji	6,819,956 B2	11/2004	DiLorenzo
6,143,032 A	11/2000	Schafer et al.	6,829,508 B2	12/2004	Schulman et al.
6,146,335 A	11/2000	Gozani	6,847,849 B2	1/2005	Mamo et al.
6,152,871 A	11/2000	Foley et al.	6,849,047 B2	2/2005	Goodwin
6,159,179 A	12/2000	Simonson	6,852,126 B2	2/2005	Ahlgren
6,159,215 A	12/2000	Urbahns et al.	6,855,105 B2	2/2005	Jackson, III et al.
6,161,047 A	12/2000	King et al.	6,902,569 B2	2/2005	Parmer et al.
6,174,311 B1	1/2001	Branch et al.	6,869,398 B2	3/2005	Obenchain
6,181,961 B1	1/2001	Prass	6,871,099 B1	3/2005	Whitehurst et al.
6,183,517 B1	2/2001	Suddaby	6,887,248 B2	5/2005	McKinley et al.
6,196,969 B1	3/2001	Bester et al.	6,916,330 B2	7/2005	Simonson
6,206,826 B1	3/2001	Mathews et al.	6,923,814 B1	8/2005	Hildebrand et al.
6,217,509 B1	4/2001	Foley et al.	6,926,728 B2	8/2005	Zucherman et al.
6,221,082 B1	4/2001	Marino et al.	6,929,606 B2	8/2005	Ritland
6,224,545 B1	5/2001	Cocchia et al.	6,945,933 B2	9/2005	Branch
6,224,549 B1	5/2001	Drongelen	6,945,973 B2	9/2005	Bray
6,224,603 B1	5/2001	Marino	6,951,538 B2	10/2005	Ritland
6,245,082 B1	6/2001	Gellman et al.	6,964,674 B1	11/2005	Matsuura et al.
6,245,108 B1	6/2001	Biscup	7,025,769 B1	4/2006	Ferree
6,251,140 B1	6/2001	Marino et al.	7,047,082 B1	5/2006	Schrom et al.
6,259,945 B1	7/2001	Epstein et al.	7,050,848 B2	5/2006	Hoey et al.
6,264,651 B1	7/2001	Underwood et al.	7,079,883 B2	7/2006	Marino et al.
6,266,394 B1	7/2001	Marino	7,089,059 B1	8/2006	Pless
6,266,558 B1	7/2001	Gozani et al.	7,115,132 B2	10/2006	Errico et al.
6,273,905 B1	8/2001	Streeter	7,125,380 B2	10/2006	Yager
6,280,447 B1	8/2001	Marino et al.	7,156,875 B2	1/2007	Michelson
6,290,724 B1	9/2001	Marino	7,162,850 B2	1/2007	Marino et al.
6,292,701 B1	9/2001	Prass et al.	7,166,113 B2	1/2007	Arambula et al.
6,306,100 B1	10/2001	Prass	7,169,182 B2	1/2007	Errico et al.
6,308,712 B1	10/2001	Shaw	7,177,677 B2	2/2007	Kaula et al.
6,312,392 B1	11/2001	Herzon	7,198,598 B2	4/2007	Smith et al.
6,312,443 B1	11/2001	Stone	7,207,949 B2	4/2007	Miles et al.
6,325,764 B1	12/2001	Griffith et al.	7,207,991 B2	4/2007	Michelson
6,334,068 B1	12/2001	Hacker	7,226,451 B2	6/2007	Shluzas et al.
6,348,058 B1	2/2002	Melkent et al.	7,235,081 B2	6/2007	Errico et al.
6,360,750 B1	3/2002	Gerber et al.	7,235,082 B2	6/2007	Bartish et al.
6,368,325 B1	4/2002	McKinley et al.	7,261,688 B2	8/2007	Smith et al.
6,371,968 B1	4/2002	Kogasaka et al.	7,288,093 B2	10/2007	Michelson
6,387,070 B1	5/2002	Marino et al.	7,320,688 B2	1/2008	Foley et al.
6,387,130 B1	5/2002	Stone et al.	7,326,216 B2	2/2008	Bertagnoli et al.
6,395,007 B1	5/2002	Bhatnagar et al.	7,341,587 B2	3/2008	Molz et al.
6,416,465 B2	7/2002	Brau	7,341,590 B2	3/2008	Ferree
6,425,859 B1	7/2002	Foley et al.	7,361,193 B2	4/2008	Frey et al.
6,425,887 B1	7/2002	McGuckin et al.	7,452,359 B1	11/2008	Michelson
6,425,901 B1	7/2002	Zhu et al.	7,455,692 B2	11/2008	Michelson
6,450,952 B1	9/2002	Rioux et al.	7,462,195 B1	12/2008	Michelson
6,451,015 B1	9/2002	Rittman, III et al.	7,470,236 B1	12/2008	Kelleher et al.
6,466,817 B1	10/2002	Kaula et al.	7,473,222 B2	1/2009	Dewey et al.
6,468,205 B1	10/2002	Mollenauer et al.	7,476,252 B2	1/2009	Foley
6,468,207 B1	10/2002	Fowler, Jr.	7,481,766 B2	1/2009	Lee et al.
6,478,805 B1	11/2002	Marino et al.	7,481,812 B2	1/2009	Frey et al.
6,485,518 B1	11/2002	Cornwall et al.	7,485,146 B1	2/2009	Crook et al.
6,491,626 B1	12/2002	Stone et al.	7,491,205 B1	2/2009	Michelson
6,500,116 B1	12/2002	Knapp	7,503,933 B2	3/2009	Michelson
6,500,128 B2	12/2002	Marino	7,513,869 B2	4/2009	Branch et al.
6,519,319 B1	2/2003	Marino et al.	7,522,953 B2	4/2009	Kaula et al.
6,520,907 B1	2/2003	Foley et al.	7,524,285 B2	4/2009	Branch et al.
6,524,320 B2	2/2003	DiPoto	7,527,649 B1	5/2009	Blain
6,533,797 B1	3/2003	Stone et al.	7,556,601 B2	7/2009	Branch et al.
			7,582,058 B1	9/2009	Miles et al.
			7,643,884 B2	1/2010	Pond et al.
			7,691,057 B2	4/2010	Miles et al.
			7,693,562 B2	4/2010	Marino et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,717,959	B2	5/2010	William et al.	2006/0224078	A1	10/2006	Hoey et al.
7,819,801	B2	10/2010	Miles et al.	2006/0229627	A1	10/2006	Hunt et al.
7,935,051	B2	5/2011	Miles et al.	2006/0235426	A1	10/2006	Lim et al.
8,000,782	B2	8/2011	Gharib et al.	2007/0016097	A1	1/2007	Farquhar et al.
8,005,535	B2	8/2011	Gharib et al.	2007/0055109	A1	3/2007	Bass et al.
8,021,430	B2	9/2011	Michelson	2007/0093850	A1	4/2007	Harris et al.
8,133,173	B2	3/2012	Miles et al.	2007/0100212	A1	5/2007	Pimenta et al.
8,182,423	B2	5/2012	Miles et al.	2007/0156026	A1	7/2007	Frasier et al.
8,192,356	B2	6/2012	Miles et al.	2007/0173941	A1	7/2007	Allard
8,251,997	B2	8/2012	Michelson	2007/0179611	A1	8/2007	DePoto et al.
8,303,458	B2	11/2012	Fukano et al.	2007/0198062	A1	8/2007	Miles et al.
8,343,046	B2	1/2013	Miles et al.	2007/0203580	A1	8/2007	Yeh
8,343,224	B2	1/2013	Lynn et al.	2007/0208227	A1	9/2007	Smith et al.
8,388,527	B2	3/2013	Miles	2007/0213826	A1	9/2007	Smith et al.
8,394,144	B2	3/2013	Zehavi et al.	2007/0225726	A1	9/2007	Dye et al.
8,409,290	B2	4/2013	Zamani et al.	2007/0225808	A1	9/2007	Warnick
8,506,629	B2	8/2013	Weiland	2007/0255415	A1	11/2007	Edie et al.
8,562,521	B2	10/2013	Miles	2007/0282449	A1	12/2007	de Villiers
8,602,982	B2	12/2013	Miles	2007/0293782	A1	12/2007	Marino
8,740,783	B2	6/2014	Gharib et al.	2008/0009880	A1*	1/2008	Warnick A61F 2/4455
9,028,553	B2*	5/2015	Lindenmann A61F 2/4684				623/17.16
9,345,587	B2	5/2016	Mitchell	2008/0021285	A1	1/2008	Drzyzga et al.
9,451,940	B2	9/2016	Spann	2008/0058606	A1	3/2008	Miles et al.
10,478,313	B1	11/2019	Sweeney, III	2008/0058838	A1	3/2008	Steinberg
2001/0034535	A1	6/2001	Schultz	2008/0064976	A1	3/2008	Kelleher et al.
2001/0039949	A1	11/2001	Loubser	2008/0064977	A1	3/2008	Kelleher et al.
2001/0056280	A1	12/2001	Underwood et al.	2008/0065082	A1	3/2008	Chang et al.
2002/0007129	A1	1/2002	Marino	2008/0065144	A1	3/2008	Marino et al.
2002/0010392	A1	1/2002	Desai	2008/0065178	A1	3/2008	Kelleher et al.
2002/0013514	A1	1/2002	Brau	2008/0065219	A1	3/2008	Dye
2002/0065481	A1	5/2002	Cory	2008/0071191	A1	3/2008	Kelleher et al.
2002/0072686	A1	6/2002	Hoey et al.	2008/0077241	A1	3/2008	Nguyen
2002/0077632	A1	6/2002	Tsou	2008/0077247	A1	3/2008	Murillo et al.
2002/0120336	A1	8/2002	Santilli	2008/0091211	A1	4/2008	Gately
2002/0123744	A1	9/2002	Reynard	2008/0097164	A1	4/2008	Miles et al.
2002/0123780	A1	9/2002	Grill et al.	2008/0119851	A1	5/2008	Shelokov
2002/0143400	A1*	10/2002	Biscup A61F 2/4455	2008/0140085	A1	6/2008	Gately et al.
			623/17.11	2008/0183046	A1	7/2008	Boucher et al.
2002/0161415	A1	10/2002	Cohen et al.	2008/0215153	A1	9/2008	Butterman et al.
2002/0165612	A1	11/2002	Gerber et al.	2008/0221694	A1	9/2008	Warnick et al.
2002/0193843	A1	12/2002	Hill et al.	2008/0300465	A1	12/2008	Feigenwinter et al.
2003/0032966	A1	2/2003	Foley et al.	2008/0300688	A1	12/2008	Cannon et al.
2003/0060687	A1	3/2003	Kleeman et al.	2009/0030423	A1	1/2009	Puno
2003/0070682	A1	4/2003	Wilson et al.	2009/0043345	A1	2/2009	Matthews
2003/0083688	A1	5/2003	Simonson	2009/0099660	A1	4/2009	Scifert et al.
2003/0105503	A1	6/2003	Marino	2009/0124860	A1	5/2009	Miles et al.
2003/0139648	A1	7/2003	Foley et al.	2009/0138050	A1	5/2009	Ferree
2003/0149341	A1	8/2003	Clifton	2009/0192403	A1	7/2009	Gharib et al.
2003/0225405	A1	12/2003	Weiner	2009/0204016	A1	8/2009	Gharib et al.
2003/0233147	A1	12/2003	Nicholson et al.	2009/0259108	A1	10/2009	Miles et al.
2003/0236544	A1	12/2003	Lunsford et al.	2009/0276049	A1*	11/2009	Weiland A61F 2/30771
2004/0024291	A1	2/2004	Zinkel				623/17.16
2004/0106927	A1	6/2004	Ruffner et al.	2010/0069783	A1	3/2010	Miles et al.
2004/0117020	A1	6/2004	Frey et al.	2010/0094422	A1	4/2010	Hansell et al.
2004/0176665	A1	9/2004	Branch et al.	2010/0130827	A1	5/2010	Pimenta et al.
2004/0199084	A1	10/2004	Kelleher et al.	2010/0152603	A1	6/2010	Miles et al.
2004/0225228	A1	11/2004	Ferree	2010/0160738	A1	6/2010	Miles et al.
2005/0004593	A1	1/2005	Simonson	2010/0174146	A1	7/2010	Miles
2005/0004623	A1	1/2005	Miles et al.	2010/0174148	A1	7/2010	Miles et al.
2005/0033380	A1	2/2005	Tanner et al.	2011/0276142	A1*	11/2011	Niemiec A61F 2/4465
2005/0043796	A1	2/2005	Grant et al.				623/17.16
2005/0071009	A1	3/2005	Muhanna et al.	2011/0313530	A1	12/2011	Gharib et al.
2005/0075578	A1	4/2005	Gharib et al.	2012/0010472	A1	1/2012	Spann
2005/0080320	A1	4/2005	Lee et al.	2012/0010715	A1	1/2012	Spann
2005/0096745	A1*	5/2005	Andre A61F 2/4611	2012/0010716	A1	1/2012	Spann
			623/17.11	2012/0010717	A1	1/2012	Spann
2005/0149035	A1	7/2005	Pimenta et al.	2012/0035730	A1	2/2012	Spann
2005/0182454	A1	8/2005	Gharib et al.	2012/0130429	A1	5/2012	Mitchell et al.
2005/0192575	A1	9/2005	Pacheco	2012/0238822	A1	9/2012	Miles
2006/0025703	A1	2/2006	Miles et al.	2012/0238893	A1	9/2012	Farquhar et al.
2006/0052828	A1	3/2006	Kim et al.	2017/0112635	A1	4/2017	Ty et al.
2006/0069315	A1	3/2006	Miles et al.				
2006/0195017	A1	8/2006	Shluzas et al.				
2006/0224044	A1	10/2006	Marchek et al.				

FOREIGN PATENT DOCUMENTS

EP	0334116	9/1989
EP	0567424	10/1993
EP	0972538	1/2000
EP	1002500	5/2000
EP	2795624	1/2001

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	793186	5/1990	
JP	10-14928	3/1996	
KR	3019990007098	11/1999	
WO	WO 199428824	12/1994	
WO	WO 199700702	1/1997	
WO	WO 199823324	6/1998	
WO	WO 199952446	10/1999	
WO	WO 200027291	5/2000	
WO	WO 200038574	7/2000	
WO	WO 200044288	8/2000	
WO	WO 200066217	11/2000	
WO	WO 200067645	11/2000	
WO	WO 200108563	2/2001	
WO	WO 200137728	5/2001	
WO	WO 200160263	8/2001	
WO	WO 2002054960	7/2002	
WO	WO 2002058780	8/2002	
WO	WO 200271953	9/2002	
WO	WO 200287678	11/2002	
WO	WO 2003005887	1/2003	
WO	WO 2003026482	4/2003	
WO	WO 2003037170	5/2003	
WO	WO 2005013805	2/2005	
WO	WO 2005030318	4/2005	
WO	WO 2006042241	4/2006	
WO	WO 2006066217	6/2006	
WO	WO-2006079356	8/2006	A1 *
WO	WO 2007016247	2/2007	A61F 2/28
WO	WO 2010075555	1/2010	

OTHER PUBLICATIONS

"Sofamor Danek MED Microendoscopic Discectomy System Brochure" including Rapp "New endoscopic lumbar technique improves access preserves tissue" Reprinted with permission from: *Orthopedics Today*, 1998, 18(1): 2 pages.

Baulot et al., Adjuvant Anterior Spinal Fusion via Thoracoscopy, *Lyon Chirurgial*, 1994, 90(5): 347-351 (13 pages with English Translation and Certificate of Translation.

Bergey et al., "Endoscopic Lateral Transpsoas Approach to the Lumbar Spine," *Spine*, 2004, 29(15):1681-1688.

Brau, "Chapter 22: Anterior Retroperitoneal Muscle-Sparing approach to L2-S1 of the Lumbar Spine," *Surgical Approaches to the Spine*. Robert G. Watkins, MD. (ed) 2003. pp. 165-181.

Co-Pending U.S. Appl. No. 13/169,919 by Spann entitled "MINIMALLY-Invasive Retroperitoneal Lateral Approach for Spinal Surgery" filed Jun. 27, 2011.

Crock, H.V. Md., "Anterior Lumbar Interbody Fusion," *Clinical Orthopaedics and Related Research*, Number One Hundred Sixty Five, 1982, pp. 157-163, 13 pages.

De Peretti et al., "New possibilities in L2-L5 lumbar arthrodesis using a lateral retroperitoneal approach assisted by laparoscopy: preliminary results," *Eur Spine J.* 1996, 5: 210-216.

Dezawa et al., "Retroperitoneal Laparoscopic Lateral Approach to the Lumbar Spine: A New Approach, Technique, and Clinical Trial," *Journal of Spinal Disorders*, 2000, 13(2): 138-143.

Dirksmeier et al., "Microendoscopic and Open Laminotomy and Discectomy in Lumbar Disc Disease" *Seminars in Spine Surgery*, 1999, 11(2): 138-146.

Extended European Search Report for European Patent Application No. EP09835860, date of completion: Feb. 7, 2013 (6 pages).

Foley and Smith, "Microendoscopic Discectomy," *Techniques in Neurosurgery*, 1997, 3(4):301-307.

Friedman, "Percutaneous discectomy: An alternative to chemonucleolysis," *Neurosurgery*, 1983, 13(5): 542-547.

Gardocki, "Tubular discectomy minimizes collateral damage: A logical progression moves spine surgery forward," *AAOS Now*, 2009, 5 pages.

Gumbs et al., "Open Anterior Approaches for Lumbar Spine Procedures," *The American Journal of Surgery* 194:98-102, 2007.

Gumbs et al., "The Open Anterior Paramedian Retroperitoneal Approach for Spine Procedures," *Arch Surg* 140:339-343, Apr. 2005.

Hovorka et al., "Five years' experience of retroperitoneal lumbar and thoracolumbar surgery," *Eur Spine J.*, 2000, 9(1): S30-S34.

International Search Report and Written Opinion for PCT/US2009/069476, mailed Aug. 17, 2010. (5 pages).

Kossman et al., "The use of a retractor system (SynFrame) for open, minimal invasive reconstruction of the anterior column of the thoracic and lumbar spine," *Eur Spine J.* 2001, 10: 396-402.

Kossmann et al., "Minimally Invasive Vertebral Replacement with Cages in Thoracic and Lumbar Spine," *European Journal of Trauma*, 2001, 27: 292-300.

Mathews et al., "Laparoscopic Discectomy with Anterior Lumbar Interbody Fusion," *SPINE*, 1995, 20(16): 1797-1802.

Mayer and Brock, "Percutaneous endoscopic discectomy: surgical technique and preliminary results compared to microsurgical discectomy," *J. Neurosurg*, 1993, 78: 216-225.

Mayer and Wiechert, "Microsurgical Anterior Approaches to the Lumbar Spine for Interbody Fusion and Total Disc Replacement," *Neurosurgery*, 2002, 51(2): 159-165.

Mayer H. M., "Minimally Invasive Spine Surgery: A Surgical Manual", Springer, 262 pages, 2000.

Mayer, "A New Microsurgical Technique for Minimally Invasive Anterior Lumbar Interbody Fusion," *Spine*, 1997, 22(6): 691-699.

Mayer, "The ALIF Concept," *Eur Spine J.*, 2000, 9(1): S35-S43.

McAfee et al., "Minimally Invasive Anterior Retroperitoneal Approach to the Lumbar Spine: Emphasis on the Lateral BAK," *Spine*, 1998, 23(13): 1476-1484.

Medtronic Sofamor Danek "METRx System Surgical Technique," 2004, 22 pages.

Medtronic Sofamor Danek "METRxTM MicroDiscectomy System," *Medtronic Sofamor Danek USA*, 2000, 21 pgs.

Patent Examination Report No. 1 for Australian Patent Application No. 2009329873, date of issue: Mar. 7, 2014. (4 pages).

Pimenta et al., "Implante de protese de nucleo pulposo: analise inicial," *Journal Brasileiro de Neurocirurgia*, 2001, 12(2): 93-96 *English Abstract.

Pimenta et al., "The Lateral Endoscopic Transpsoas Retroperitoneal Approach (Letra) for Implants in the Lumbar Spine," *World Spine II—Second Interdisciplinary Congress on Spine Care*, Aug. 2003, 2 pages.

Pimenta, "Initial Clinical Results of Direct Lateral, Minimally Invasive Access to the Lumbar Spine for Disc Nucleus Replacement Using a Novel Neurophysiological Monitoring System." *The 9th IMAST*, May, 2002, 1 page.

Rao, et al., "Dynamic retraction of the psoas muscle to expose the lumbar spine using the retroperitoneal approach," *J. Neurosurg Spine*, 2006, 5: 468-470.

Schaffer and Kambin, "Percutaneous Posterolateral Lumbar Discectomy and Decompression with a 6.9-Millimeter Cannula," *The Journal of Bone and Joint Surgery*, 1991, 73A(6): 822-831.

Schick et al., "Microendoscopic lumbar discectomy versus open surgery: an intraoperative EMG study," *Eur Spine J.* 2002, 11: 20-26.

Smith and Foley "MetRx System MicroEndoscopic Discectomy: Surgical Technique" *Medtronic Sofamor Danek*, 2000, 24 pages.

USPTO Advisory Action for U.S. Appl. No. 13/133,909, mailed Jul. 2, 2013.

USPTO Advisory Action for U.S. Appl. No. 13/239,042, mailed Feb. 6, 2014.

USPTO Advisory Action for U.S. Appl. No. 13/239,053, mailed Feb. 13, 2014.

USPTO Final Office Action for U.S. Appl. No. 13/133,909, mailed Mar. 20, 2013.

USPTO Final Office Action for U.S. Appl. No. 13/239,014, mailed Sep. 14, 2015.

USPTO Final Office Action for U.S. Appl. No. 13/239,024, mailed Jun. 17, 2014.

USPTO Final Office Action for U.S. Appl. No. 13/239,014, mailed Oct. 30, 2013.

USPTO Final Office Action for U.S. Appl. No. 13/239,024, mailed Jul. 19, 2013.

(56)

References Cited

OTHER PUBLICATIONS

USPTO Final Office Action for U.S. Appl. No. 13/239,042, mailed Oct. 30, 2013.
 USPTO Final Office Action for U.S. Appl. No. 13/239,053, mailed Oct. 18, 2013.
 USPTO Interview Summary for U.S. Appl. No. 13/133,909, mailed Dec. 26, 2013.
 USPTO Interview Summary for U.S. Appl. No. 13/239,014, mailed Dec. 24, 2013.
 USPTO Interview Summary for U.S. Appl. No. 13/239,014, mailed Dec. 31, 2015.
 USPTO Interview Summary for U.S. Appl. No. 13/239,014, mailed May 6, 2015.
 USPTO Interview Summary for U.S. Appl. No. 13/239,024, mailed Dec. 30, 2013.
 USPTO Interview Summary for U.S. Appl. No. 13/239,042, mailed Dec. 27, 2013.
 USPTO Interview Summary for U.S. Appl. No. 13/239,053, mailed Dec. 26, 2013.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/133,909, mailed Jul. 13, 2012.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/133,909, mailed Sep. 10, 2014.

USPTO Non-Final Office Action for U.S. Appl. No. 13/239,014, mailed Dec. 4, 2014.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/239,014, mailed Feb. 21, 2013.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/239,024, mailed Dec. 20, 2012.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/239,024, mailed Jan. 28, 2014.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/239,024, mailed Nov. 28, 2014.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/239,042, mailed Dec. 4, 2014.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/239,042, mailed Mar. 6, 2013.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/239,053, mailed Nov. 6, 2014.
 USPTO Non-Final Office Action for U.S. Appl. No. 13/239,053, mailed Jan. 29, 2013.
 USPTO Requirement for Restriction/Election for U.S. Appl. No. 13/239,053, mailed Nov. 2, 2012.
 Wolfla et al., "Retroperitoneal lateral lumbar interbody fusion with titanium threaded fusion cages," *J. Neurosurg (Spine 1)*, 2002, 96: 50-55.
 Zdeblick, Thomas A. (ed.). Anterior Approaches to the Spine, 1999, Chapters 11, 13, and 14, 43 pages.

* cited by examiner




FIG.1A




FIG. 1C







FIG. 1B

FIG.2A








FIG.3A











FIG.3B














FIG. 11A




FIG. 11B












FIG. 11C














FIG. 18A




FIG. 18B










FIG. 18C












FIG. 23A




FIG. 23B




FIG. 23C

1

SPINAL SURGERY METHODS AND DEVICES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/209,874 (now U.S. Pat. No. 11,969,359) filed on Mar. 23, 2021, which is a divisional application of U.S. patent application Ser. No. 16/149,108 (now U.S. Pat. No. 10,959,860) filed on Oct. 1, 2018, which is a continuation of U.S. patent application Ser. No. 15/235,957 (now U.S. Pat. No. 10,085,854) filed on Aug. 12, 2016, which is a continuation of U.S. patent application Ser. No. 13/239,014 (now U.S. Pat. No. 9,451,940) filed on Sep. 21, 2011, which is a continuation of U.S. patent application Ser. No. 13/133,909 having a 371(c) date of Sep. 23, 2011, which is a Rule 371 U.S. National Stage of International Patent Application No. PCT/US2009/069476 filed on Dec. 23, 2009, which claims priority to U.S. Provisional Patent Application No. 61/178,315, filed on May 14, 2009, and U.S. Provisional Patent Application No. 61/140,926, filed on Dec. 26, 2008, all of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

Spinal surgery methods and devices are disclosed for repairing damaged or deteriorated vertebrae at the lower lumbar levels, such as in the L5-S1 intervertebral space.

2. Description of the Relevant Art

The vertebral column is the central pillar of the body. It is a generally flexible column that bears tensile and compressive loads, permits bending motions, and provides an attachment site for ribs, muscles and other structures. The vertebral column includes irregular bones called vertebrae that are separated by fibrocartilaginous structures known as intervertebral discs. There are seven vertebral, twelve thoracic, five lumbar, five sacral, and four coccygeal vertebrae. A typical vertebra consists of a rounded anterior body and a posterior vertebral arch that together form a protective structure around the vertebral canal that contains the spinal cord.

The intervertebral discs can be damaged or undergo degeneration, which often results in painful and sometimes debilitating nerve impingement syndromes. It is sometimes necessary to surgically replace the native disc with prosthetic disc implants to relieve the pain, restore the functional mechanics of the vertebral column, and promote fusion between adjacent vertebral bodies. Procedures such as total disc arthroplasty (disc replacement) have used a direct anterior approach orthogonal to the midline of the vertebral body, but such procedures require unfettered anterior spinal exposure for precise midline placement of the prosthetic disc. The major vascular structures that run along the anterior spine must be mobilized to achieve this exposure, which typically requires the assistance of a vascular surgeon. The procedure also causes significant surgical disruption of the anterior annular element around the disc.

Bertagnoli has described an anterolateral transposiotic approach (ALPA) for implantation of prosthetic disc replacement devices. The patient is positioned in a supine position on the operating table, with the arms in abduction.

2

The target disc level is localized through bi-planar fluoroscopy, and an inflatable bladder is placed beneath the level of interest to permit additional lordosis. An anterolateral incision is made on the left side for access to lumbar intervertebral spaces, while the incision is made on the right side for access to L5-S1. The fascia of the external oblique muscle is opened along the direction of its fibers and the muscle is split. The retroperitoneal space is entered and the peritoneal sac mobilized away from the overlying fascia to develop an operative pathway along the anterior aspect of the psoas muscle to the lateral aspect of the intervertebral space. The target zone for annulotomy is from the one o'clock to three o'clock position above the L5-S1 level, which leaves the anterior longitudinal ligament intact and avoids mobilizing the iliac vessels. At the L5-S1 level the target annulotomy zone is from the eight o'clock to ten o'clock position with mobilization of the iliac vessel toward the midline. Injury to the left iliac vessel is an unfortunate complication of such procedures. Additional information about anterolateral approaches to spinal surgery at the L4-L5 level is found in Bertagnoli et al, U.S. Pat. No. 7,326,216.

A minimally invasive procedure promoted by Nuvasive, Inc. uses a direct lateral, retroperitoneal approach to access the intervertebral discs above the L5-S1 level with minimal muscular disruption. The patient is placed in a lateral decubitus position and the direct lateral incision is made in the axillary line. Another incision is made posterior to the lateral border of the erector spinae muscle, and finger dissection is conducted through this opening to the retroperitoneal space. The index finger of the surgeon sweeps the peritoneum anteriorly and palpates the psoas muscle. A dilator instrument is then introduced through the direct lateral incision and the index finger then guides the dilator instrument to the psoas muscle. The fibers of the psoas muscle are then split using blunt dissection and EMG monitoring to minimize damage to the nerves of the lumbar plexus that run through the posterior psoas muscle. A tissue distraction and tissue retraction assembly are then used to help establish an operative corridor to the direct lateral aspect of the intervertebral space at about the 3 o'clock position, as shown in U.S. Pat. No. 7,207,949. The direct lateral retroperitoneal approach to the L5-S1 space has not been possible because the anterior superior iliac spine obstructs a direct lateral approach to the L5-S1 intervertebral space. Hence approaches to the L5-S1 space typically use a standard anterior approach. For a laterally positioned patient, an extremely large sigmoidal incision has been required, with subsequent reflection of all the overlying musculature to expose the L5-S1 space.

It would therefore be useful to provide a minimally invasive approach to the L5-S1 space that minimizes injury to the blood vessels and nerves around the vertebral bodies. It would also be helpful to perform such a procedure in a manner that minimizes retroperitoneal scarring and damage to other body structures. Minimally invasive surgical approaches to the intervertebral spaces in the past have also been limited by the need to insert the prosthetic disc implant either into the front portion, posterior portion, or the side of the disc space to achieve stable placement of the prosthetic implant. It would therefore be useful to have a procedure that could avoid such a limitation at any vertebral level.

SUMMARY OF THE INVENTION

The inventor has found it is advantageous to provide a method, device and system that permit an angle between a disc implant and insertion instrument to be altered without

removing the implant from the intervertebral space. This new surgical approach also removes the native disc contents from a generally lateral direction, which permits the peritoneal contents to fall out of the surgical field, while also taking advantage of the mechanics of anterior interbody surgery.

Disclosed methods, devices and systems are suitable for performing a minimally-invasive procedure for accessing the intervertebral space along an oblique pathway with an insertion instrument that holds a disc implant, and reorienting the angular relationship between instrument and implant while the implant is inside the body (for example at or within the disc space). In some disclosed embodiments, a prosthetic disc implant is inserted diagonally within the disc space, and the implant is then pivoted to a medial-lateral orientation within the disc space. The invention is particularly useful for accessing the L5-S1 intervertebral space along an anterolateral pathway to the anterior aspect of the spine, placing a prosthetic disc implant diagonally within the intervertebral space, and pivoting the implant within the disc space. However the method can also be used at other vertebral levels. In one embodiment, the oblique pathway has a caudal or cephalad-directed component, and the implant can be repositioned into a transverse anatomic plane through the intervertebral space.

In one embodiment, an implant is positioned in the intervertebral disc space of a laterally positioned subject by accessing the anterior face of the spinal disc intervertebral space, between the L5 and S1 vertebrae, from an anterolateral retroperitoneal approach. An oblique operative corridor is then established to the anterior face of the spinal disc space by introducing a retractor instrument anterolaterally to the spinal disc space, for example anterior to the anterior superior iliac spine, and in some instances between the level of the anterior superior iliac spine and the anterior inferior iliac spine. The spinal disc contents are removed from the intervertebral space through the operative corridor, and an elongated implant is introduced through the operative corridor into the intervertebral space diagonally (at an angle). The elongated implant is then pivoted within the intervertebral space to eventually position the implant substantially medial-laterally within the intervertebral space and achieve midline symmetric distribution of the mechanical load on the implant. The ability to pivot the implant within the intervertebral space permits the elongated implant to be generally aligned with the insertion instrument and advanced into the body through a relatively narrow operative corridor, then turned to its final position within the intervertebral space.

In a disclosed embodiment, the retractor instrument includes a proximal handle portion and a distal retractor blade portion that carries opposing ipsilateral and contralateral vascular retractor blades that are placed between the right and left iliac vessels and moved apart from one another to retract the right and left iliac vessels away from the anterior face of the spinal disc intervertebral space. A particular example of the retractor instrument has an ipsilateral arm on which the ipsilateral blade is mounted and a contralateral arm on which the contralateral blade is mounted. The retractor blades are placed between the right and left iliac vessels to move them away from one another to expose the anterior surface of the spine as the ipsilateral and contralateral arms of the retractor instrument move the retractor blades apart. For example, the blades of the retractor instrument are positioned at the anterior face of the vertebral body adjacent the anterior longitudinal ligament,

and the retractor blades are spread to expose an area from about the 10 o'clock to 2 o'clock position of the vertebral body.

The elongated implant may be advanced into the intervertebral space through the operative corridor defined by the arms of the retractor instrument by securing the implant to a distal end of an elongated rigid introducer instrument and advancing the implant on the introducer instrument through the operative corridor to the anterior face of the intervertebral space at an oblique angle so that the implant enters the disc space diagonally. The angle between the implant and the introducer is then selectively changed to pivot the implant in one or more subsequent steps into the medial-lateral position for symmetric midline placement within the intervertebral space. In some embodiments the introducer instrument has a distal docking element that selectively docks with an interface element of the implant in a series of preselected positions to alter the angle between the implant and the introducer instrument. For example, the docking element is a plurality of docking pins on the tip of the introducer element, and the interface element is a corresponding series of docking holes that cooperatively mate to hold the implant in preselected angular orientations to the introducer instrument.

In some disclosed embodiments, the implant is an elongated elastomeric member that has a top bearing face, a bottom bearing face, a front face, a rear face, an ipsilateral face and a contralateral face. The rear face of the implant may be substantially flat. The contralateral face of the implant may be rounded (particularly at its corners that adjoin the front and rear faces) to minimize trauma induced by advancing the implant diagonally into the intervertebral space at the oblique angle, and using the ipsilateral face to function as an impact hinge or pivot point as the implant is moved in one or more realignments from the oblique to medial-lateral orientation. The ipsilateral end of the implant may have a pivot axis and an interface element, such as multiple pairs of spaced docking holes arranged on a curved surface that extends partially circumferentially around the pivot axis. The selected pairs of spaced docking holes are positioned to mate with the docking element of the introducer instrument, such as a pair of docking pins that extend from a distal tip of the introducer instrument.

In some embodiments the implant tapers in height from its front face to rear face, and/or medially to laterally, and it may be a partially hollow member in which the top face and bottom face are substantially open and separated by an internal divider wall that extends from the front face to the rear face to form a contralateral and ipsilateral window through the implant to promote the growth of bone within the implant. In some disclosed embodiments, the implant is a slightly compressible member in which the front face is convex and the ipsilateral face includes the interface element that mates with the docking element. The external surfaces of the implant (such as the top and bottom faces of the implant) have protuberances that help frictionally engage the implant to adjoining vertebral bodies, and also promote bone growth into the implant. The protuberances may have a variety of shapes, such as grooves or corrugations, but a frustopyramidal protuberance is believed to be particularly suitable. The retractor instrument may also take a variety of forms, but certain disclosed embodiments have an ipsilateral arm that is shorter than the contralateral arm. A retractor blade on the ipsilateral arm therefore extends a shorter distance from the handle than the retractor blade on the contralateral arm. This asymmetric arrangement permits the retractor instrument to be advanced diagonally through the

5

body from an anterolateral entrance point through the abdominal wall to the anterior aspect of the vertebral body. Since the contralateral arm is longer than the ipsilateral arm, the retractor blades at the anterior vertebral body span the anterior face of the vertebral body, for example from the 10 o'clock to 2 o'clock positions. The retractor blades may be curved outwardly from a longitudinal axis of the retractor instrument to help minimize damage to the blood vessels as they are retracted. A thin shim with a tapered tip may be inserted into the intervertebral space and mounted to the ipsilateral blade to retain the instrument in its desired angular orientation and distract adjacent vertebral bodies (such as L5 and S1) apart from one another during the procedure. The shim curves inwardly into the disc space, toward the midline of the body, away from the ipsilateral retractor blade, and toward a longitudinal axis of the retractor instrument. The shim has a height sufficient to maintain the adjacent vertebral bodies spaced from one another while a trial spacer and subsequent disc implant are pivoted into place within the disc space. The present disclosure also includes a system for positioning an implant in an intervertebral space of a subject. In certain disclosed embodiments, the system includes the retractor instrument for establishing an operative corridor to the anterior face of the intervertebral space. The retractor instrument has a proximal handle portion and a distal retractor blade portion that includes opposing ipsilateral and contralateral arms that are movable toward and away from one another to define a portion of the operative corridor therebetween. In certain embodiments, the ipsilateral retractor blade is carried by the ipsilateral arm, and a contralateral vascular retractor blade is carried by the contralateral arm. The contralateral arm and blade are longer than the ipsilateral arm and blade so that the retractor instrument can be introduced at an oblique angle with the two retractor blades spaced apart on the anterior aspect of the vertebral body.

The system also includes the introducer instrument for advancing an elongated prosthetic spinal disc implant between the arms and blades of the retractor instrument to the intervertebral space at an oblique angle so that the implant enters the intervertebral space diagonally. The introducer instrument is capable of pivoting the implant in the intervertebral space, for example by connecting docking pins on a tip of the introducer instrument to different sets of corresponding docking holes on the implant. The docking pins selectively mate with the different sets of docking holes on the implant to maintain the implant at different fixed angles to the introducer instrument. By mating the docking pins with different docking holes, the implant can be pivoted within the intervertebral space to move it from its initial diagonal orientation to a medial-lateral orientation generally symmetric with respect to the axis of the vertebral column. In certain embodiments, the system also includes the implant which has a top bearing face, a bottom bearing face, a front face, a rear face, an ipsilateral face and a contralateral face. The implant's contralateral face may be rounded to minimize trauma induced by advancing the implant diagonally into the intervertebral space and pivoting it around a pivot axis within the intervertebral space. The implant has an interface element for coupling with the introducer instrument and pivoting the implant within the disc space. For example, the interface element includes multiple pairs of spaced docking holes arranged on a curved surface that extends partially circumferentially around the pivot axis, and selected pairs of spaced docking holes are positioned to mate with the docking element of the introducer instrument. In certain disclosed embodiments, the implant tapers in

6

height from the front face to the rear face. The implant may also be a partially hollow member in which the top face and bottom face are substantially open and may be separated by an internal divider wall that extends from the front face to the rear face to define the ipsilateral and contralateral windows therebetween for promoting tissue growth within the implant.

Another aspect of the invention is the prosthetic implant itself, the retractor itself, and the introducer element itself.

BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of the present invention will become apparent to those skilled in the art with the benefit of the following detailed description of embodiments and upon reference to the accompanying drawings in which:

FIG. 1A illustrates a patient positioned in a right lateral decubitus position for minimally-invasive spinal surgery using a retroperitoneal approach;

FIG. 1B is a schematic top view illustrating the anatomy of the L5 vertebra;

FIG. 1C is a schematic perspective view of the human body illustrating several anatomic reference planes;

FIG. 2A is a schematic cross-sectional view of the abdomen at the level of the L5-S1 intervertebral space illustrating the left anterolateral displacement of the peritoneum and the right anterolateral introduction of a dilator through an incision toward the L5-S1 space under the guidance of a surgeon's finger introduced through a lateral incision;

FIG. 2B is an isolated perspective view illustrating the components and use of an initial distraction assembly that includes a K-wire, an initial dilating cannula with handle, and a split-dilator housed within the initial dilating cannula;

FIG. 2C is an isolated perspective view illustrating the K-wire and split-dilator of the initial distraction assembly with the initial dilating cannula and handle removed;

FIG. 3A is a view similar to FIG. 2A, but showing introduction of a minimally invasive retractor instrument through the right anterolateral incision, and its positioning at the L5-S1 intervertebral space with the right and left iliac vessels retracted away from the anterior spine;

FIG. 3B is an isolated schematic end view of the retractor blades on the retraction instrument, illustrating the greater curvature of the shorter retraction blade;

FIG. 4A is a front elevation view of a shim for placement on the ipsilateral blade of the retractor instrument;

FIG. 4B is a side view of the shim of FIG. 4A;

FIG. 4C is a top view of the shim of FIGS. 4A and 4B;

FIG. 5A is a perspective fragmentary view of the pelvis and the sacro-lumbar segment of the spinal column illustrating the bifurcation of the iliac vasculature along the anterior aspect of the spinal column;

FIG. 5B is a front view of FIG. 5A with the iliac vessels retracted to expose the L5-S1 disc space;

FIG. 6 is a perspective view of an introducer instrument for guiding an implant to a spinal disc space, showing the implant connected to the introducer instrument for movement about a pivot axis;

FIG. 7 is an isolated perspective view of the introducer instrument;

FIG. 8 is an enlarged, fragmentary view of the tip of the introducer instrument of FIG. 7 illustrating the instrument interface of the implant, and showing the pins on the distal tip of the instrument for connection to positioning holes on the implant;

FIG. 9 is an enlarged, fragmentary view of the implant held in a fixed angular position relative to the introducer

element by the pins of the instrument interface locked into a preselected set of positioning holes on the implant;

FIG. 10A is a perspective view of a first embodiment of the implant, showing the implant interface surface in which pairs of pin receiving holes are arranged at different angles around the interface surface to hold the implant at variable fixed angles relative to the longitudinal axis of the introducer instrument;

FIG. 10B is an end view of the implant of FIG. 10A, illustrating a tapered height of the implant;

FIG. 11A is a top view of an embodiment of an implant;

FIG. 11B is a side view of an embodiment of the implant of FIG. 11A;

FIG. 11C is an end view of an embodiment of the implant of FIG. 11A;

FIG. 12 is a perspective view of a second embodiment of the implant;

FIG. 13 is a schematic top perspective view of the pelvis with a retractor instrument introduced obliquely into the subject's body along an anterolateral operative trajectory, and with the introducer instrument advanced through the operative corridor defined by the retractor instrument. A trial spacer is attached to the distal end of the introducer instrument for introduction diagonally into the L5-S1 intervertebral space;

FIG. 14A is an enlarged top view of the L5-S1 disc space shown in FIG. 13, illustrating the rounded contralateral face of the trial spacer impacting the far lateral aspect of the apophyseal ring;

FIG. 14B is a view similar to FIG. 14A, but illustrating adjustment of the angle between the introducer instrument and the body of the trial spacer by repositioning the pins on the tip of the instrument in a different set of pin receiving holes on the trial spacer;

FIG. 14C is a view similar to FIG. 14A, but illustrating progressive reorientation of the trial spacer in a generally medial-lateral orientation within the intervertebral space;

FIG. 15 is a view similar to FIG. 13, but showing a subsequent step of the procedure in which the introducer instrument has advanced an implant to the disc space;

FIGS. 16A, 16B and 16C are top views of the L5-S1 disc space, illustrating progressive reorientation of the implant within the disc space by repositioning of the pins on the tip of the introducer instrument in different sets of pin receiving holes on the implant;

FIG. 17 is an enlarged top view of the L5-S1 disc space illustrating the implant in position within the disc space;

FIG. 18A is a front elevation view of a shim for placement on the ipsilateral blade of the retractor instrument;

FIG. 18B is a side view of the shim of FIG. 18A;

FIG. 18C is a top view of the shim of FIGS. 18A and 18B;

FIG. 19A is a perspective view of an embodiment of an implant;

FIG. 19B is a side view of an embodiment of the implant of FIG. 19A;

FIG. 19C is an end view of an embodiment of the implant of FIG. 19A;

FIG. 20 is a top view of the L5-S1 disc space, illustrating orientation of the implant of FIG. 11A within a disc space;

FIG. 21 is a perspective view of a portion of a retraction instrument with a pair of blades provided at a distal end;

FIG. 22 is a top view of the retraction instrument of FIG. 21, showing a mechanism for moving the retractor blades;

FIG. 23A is a perspective view of a blade for use with a retraction instrument;

FIG. 23B is a rear view of the blade of FIG. 23A; and

FIG. 23C is a top view of the blade of FIG. 23A.

While the invention may be susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. The drawings may not be to scale. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but to the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

DETAILED DESCRIPTION OF THE EMBODIMENTS

It is to be understood the present invention is not limited to particular devices or methods, which may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting. As used in this specification and the appended claims, the singular forms "a", "an", and "the" include singular and plural referents unless the content clearly dictates otherwise. Furthermore, the word "may" is used throughout this application in a permissive sense (i.e., having the potential to, being able to), not in a mandatory sense (i.e., must). The term "include," and derivations thereof, mean "including, but not limited to." The term "coupled" means directly or indirectly connected.

Embodiments of the invention are disclosed herein for accessing an intervertebral space, such as the L5-S1 space, and implanting a prosthetic disc implant within that space. The disclosed devices, methods and systems are suitable for use in a minimally invasive procedure for repairing degenerated or otherwise injured intervertebral discs.

General Overview of the Surgical Procedure

The method generally includes initially accessing the intervertebral space using a retroperitoneal lateral approach. Then, with a finger-directed dilator or other suitable instrument, the distal retroperitoneum is swept anteriorly to expose an eventual channel to a direct approach to L5-S1. In most people, the direct approach to L5-S1 is anterior to the anterior superior iliac spine, or between the anterior superior iliac spine and the anterior inferior iliac spine. An incision is then made to open this channel, and blunt dilators are directed in an oblique direction directly to the mid-anterior aspect of L5-S1, for example between the 10 o'clock and 2 o'clock position. Fluoroscopic guidance may be used in accordance with known techniques to assist in advancing and positioning the dilators.

A retractor is then advanced over the dilators. In certain embodiments, the blades of the retractor are translucent so that the retracted contents can be seen through the blades. In contrast to existing retractors used in minimally invasive spinal surgery, the blades are shaped so that the curvature of the retractor blades conforms to the unique shape of the anatomy for the approach described herein, and is particularly suitable for use in this portion of the spine. For example, the ipsilateral blade may be shorter than the contralateral blade, and the ipsilateral blade may be more arcuate with a steeper curve as compared to the less curved, straighter contralateral blade. In one embodiment, the blades can accommodate a xenon light source for visualization in the cavity.

Once the retraction blades are advanced to the anterior aspect of the spine (for example between the 10 o'clock and 2 o'clock positions at the L5-S1 intervertebral space), the retractor blades are positioned below the iliac bifurcation between the right and left iliac vessels. The retractor blades

are moved apart to increase exposure of the anterior vertebral column. A docking shim that is angled away from the ipsilateral blade and toward the disk space is placed in the intervertebral space to secure the retractor in position and maintain distraction of the vertebral bodies. If the small middle sacral artery is viewable in the midline, the surgeon may choose to ligate or electrocauterize this small vessel.

The procedure provides a relatively large window within which a discectomy and reconstruction can be carried out. The tools used for the discectomy may be slightly angled (relative to tools used for existing techniques) to maximize disc removal from an oblique direction. Trial spacers and final disc implants have a unique design suited to the trajectory of the implantation, as described in greater detail below. Radiopaque markers may be included on the trial spacers and implants (for example at its corners) to enable the structures to be visualized under fluoroscopy.

One or more trial spacers are then introduced into the evacuated disc space to help select an appropriate size implant. During introduction of the trial spacer or final implant, the initial insertion trajectory is oblique, resulting in diagonal entry of the trial spacer into disc space with impaction of the contralateral face of the implant or trial spacer to the far lateral aspect of the apophyseal rings (for example of L5-S1). The angle of impaction is then reoriented so that the portion of the trial spacer or implant that is present in the more anterior portion of the intervertebral space is impacted posteriorly on the apophyseal ring by using the contralateral side as a swivel point. Under fluoroscopic control, final seating of the implant or trial spacer is achieved. Once the final implant is in place, retraction is slowly released by allowing the retraction blades to move toward one another to check for any residual bleeding. The retractor is then slowly removed so that the skin closure of the percutaneous incision can be carried out.

This general summary of the procedure is illustrated in more detail in the following sections of this specification. Positioning the Patient and Relevant Spinal Anatomy

As shown in FIG. 1A, a patient 20 is placed in a direct right lateral decubitus position with the patient's right side down on an operating table 22 and the left side up. A bolster pillow 24 is placed at the waist of patient 20 to bend the body at that point, which elevates and tilts the pelvis 26 of patient 20. Pelvis 26 is schematically shown in FIGS. 1, SA and SB to include an ileum 28, with an iliac crest 30, anterior superior iliac spine 32, and anterior inferior iliac spine 34. A notch 36 (FIGS. SA and SB) is formed between the superior and inferior iliac spines 32, 34. The spinal anatomy is schematically illustrated in FIG. 1A, wherein the sacrum 38 is shown connected to the L5 vertebra 40. Higher levels of lumbar and thoracic vertebrae are shown superior to the L5 disc. The anatomy of the L5 vertebra is illustrated in more detail in FIG. 1B, wherein the vertebra includes an anterior vertebral body 42 and a posterior vertebral arch 44 that cooperatively define spinal foramen 46. Vertebral body 42 includes a circumferential apophyseal ring 48, while vertebral arch 44 includes a spinous process 50, right transverse process 52 and left transverse process 54. Positions around vertebral body 42 can be designated arbitrarily by hours of the clock, with anterior-most position 56 designated the twelve o'clock position. Hence an anterior face of vertebral body 42 is designated herein as the face 58 that extends from about the ten o'clock position 60 to the two o'clock position 62. The axis of the vertebral column is located generally at the center of vertebral body 42.

To clarify some of the terms in this specification, the anatomic planes of the body in the standard anatomical

position are shown in FIG. 1C. In general anatomic terminology, "superior" means closer to the head, "posterior" means closer to the posterior surface of the body, "anterior" means closer to the anterior surface of the body, "cephalad" means toward the head, "caudad" means toward the feet. The anatomic reference planes in FIG. 1C are the "coronal plane" that separates the body into anterior and posterior halves, and the "median plane" that separates the body into right and left parts. A transverse plane is shown, which is any plane that is perpendicular to the coronal and median planes; multiple transverse planes exist at different levels of the body. With reference to the coordinate planes of FIG. 1C, the "noon" position is on the front of the body along the A-P (anterior-posterior) line at which the median plane intersects a transverse plane. The three and six o'clock positions are along the L-M (lateral-medial) line at the intersection of the transverse and coronal planes.

An "oblique plane" is any plane that is at an angle (not within or parallel) to any one of the coronal, median or transverse planes. Hence an operative corridor is "oblique" if it is an oblique plane. An oblique angle can lie in one of the illustrated coronal, median or transverse planes, be parallel to one or two of those planes, or be outside of (and not parallel) to all three of them. For instance, an oblique pathway P1 to an intervertebral space can extend in a transverse plane at a non-zero angle to the median plane. Alternatively, an oblique pathway P2 can extend at a non-zero angle to the transverse, coronal and median planes.

Additional pertinent anatomy at the anterior aspect of the spine is illustrated in FIGS. 5A and 5B, which shows the aortic bifurcation 64 into the right and left common iliac arteries 66, 68, each of which divides into an external iliac artery 66a, 68a and an internal iliac artery 66b, 68b. Accompanying common iliac veins 67, 69 are also shown in FIG. 5A. The descending aortic artery, bifurcation 64, and the bifurcated iliac vessels are at the anterior face of the vertebral bodies, and have complicated surgical approaches that attempt to access the anterior vertebral body to repair a damaged spinal disc. The L5-S1 intervertebral space 70 is shown in FIG. 5A without retraction of the iliac vessels, and in FIG. 5B with retraction of the iliac vessels to expose L5-S1 intervertebral space 70.

Additional pertinent perispinal anatomy is shown in FIGS. 2A and 3A, wherein right and left common iliac arteries 66, 68 and veins 67, 69 are shown in their normal anatomic position on the anterior aspect of the spine. The nucleus pulposus 72 of the L5-S1 intervertebral disc is illustrated, as are the right and left psoas muscles 74, 76, the right and left erector spinae muscles 78, 80 and the right and left transversospinalis muscles 82, 84. The peritoneum 86, which is normally adjacent and adherent to the retroperitoneal structures, is shown in FIGS. 2A and 3A after it has been moved anteriorly and separated from the retroperitoneal structures on the right side of the body to clear an operative pathway to the L5-S1 intervertebral space.

Access to Retroperitoneal Space and Establishing Operative Corridor to Intervertebral Space

The surgeon palpates the subject to locate the position of the anterior superior iliac spine 32, and an initial incision 90 (FIG. 1) is made at this point in the mid-axillary line, as in a standard retroperitoneal approach. As shown in FIG. 2A, blunt finger dissection is directed caudally in the retroperitoneal plane to connect to a point that is parallel the L5-S1 disc space, just anterior to ileum 28. The surgeon's finger 94 sweeps peritoneum 86 anteriorly, moving it away from the ileum 28 and the retroperitoneal structures in the right side of the abdominal cavity. A second skin incision 92 (FIGS.

11

1A and 2A) is then made inferior to first incision 90. Second incision 92 is anterior to first incision 90, between the anterior axially line and the sheath of the rectus abdominis muscle, and is approximately 3-5 cm in length. Second incision 92 is made at the level of the L5-S1 disc space, which is determined fluoroscopically prior to making the incision. FIG. 2B illustrates an initial access assembly 100 for accessing the targeted intervertebral space, such as the L5-S1 intervertebral space. Although a particular device and method are described for accessing the L5-S1 intervertebral space, the disclosed invention is not limited to use of this particular device and method. The term "accessing" the intervertebral space or its face is meant to broadly include any device and/or method for establishing a pathway from a surface incision to the disc space or its face. Illustrated access assembly 100 includes a K-wire 102, an initial dilating cannula 104 with handle 106, and a split-dilator 108 housed within the initial dilating cannula 104. The entire assembly 100 is advanced under fluoroscopic guidance through the tissue towards the surgical target site (i.e., annulus). This may be accomplished using a nerve detection and/or direction device as described in U.S. Pat. No. 7,207,949, although the nerve detection capability is not necessary. Initial dilating assembly 100 is advanced until the distal ends of split-dilator 108 and initial dilator 104 are positioned within the disc space. The initial dilator 104 and handle 106 are then removed (FIG. 2C) to leave split-dilator 108 and K-wire 102 in place. Split-dilator 108 is thereafter split such that the respective halves 108a, 108b are separated from one another to distract tissue in a generally cephalad-caudal fashion relative to the target site as described in more detail in U.S. Pat. No. 7,207,949. Split dilator 108 may thereafter be relaxed (allowing the dilator halves 108a, 108b to come together) and rotated approximately 90 degrees such that the dilator halves 108a, 108b are disposed in a transverse anatomic plane. Once rotated in this manner, the dilator halves 108a, 108b are again separated to distract tissue in the transverse plane. Each dilator half 108a, 108b may be provided with one or more electrodes (preferably at their distal regions) equipped for use with a nerve surveillance system, such as, by way of example, the Neuro Vision System, although the nerve monitors are optional.

Progressively larger dilators (not shown) may be used to further establish the operative pathway. The dilators are labeled with depth markings to help assure insertion of the successive dilators to the appropriate depth. The dilators are introduced obliquely into the body along a diagonal pathway from incision 92 to the anterior aspect of the spine to enter the intervertebral space between the twelve o'clock and two o'clock positions. The particularly illustrated pathway is generally in a transverse plane at the level of L5-S1, but at an angle to (and between) the coronal and median planes (for example in the direction of the pathway P1 in FIG. 1C). However, the pathway can also be at an angle to the transverse plane as well (for example, at the same angle as pathway P2 in FIG. 1C). The dilator pathway helps determine the eventual operative corridor that is established by placement of retraction instrument 110. However, in some embodiments, the retraction instrument 110 can itself establish the operative corridor without the initial use of the dilators.

In the illustrated embodiment, one of more of the dilators is left in place to serve as a guide for insertion of a retractor instrument 110 (FIG. 3A). Retraction instrument 110 includes a proximal handle portion 112 and a distal retractor blade portion 114 that includes opposing contralateral retraction arm 116 and ipsilateral retraction arm 118, which

12

respectively carry a terminal contralateral retraction blade 120 and ipsilateral retraction blade 122. Each of blades 120, 122 is curved longitudinally away from the axis of elongated retractor instrument 110 (FIG. 3A), and is additionally curved radially (FIG. 3B). As shown in FIGS. 3A and 3B, ipsilateral retraction blade 122 is shorter and has a greater cross-sectional (radial) curvature than contralateral retraction blade 120. In addition, ipsilateral blade 122 has a greater longitudinal curvature than contralateral blade 120.

A pair of angled extension members 117, 119 can extend from handle portion 112 to improve the access angle provided by the retractor instrument. Conventional retraction instruments are not well suited for approaches that are not directly lateral to an implantation site. The increased distance from the handle to the blades and the change in angle provided by extension members 117, 119 improve access to the implantation sites for the methods described herein.

In particular, extension members 117, 119 can extend from handle portion 112 such that they are substantially parallel to one another and form an angle of between about 45 and 80 degrees from a plane formed by a surface of handle portion 112 to which extension members abut and from which extension members extend. As shown in FIG. 22, extension member 119 is preferably shorter than extension member 117. If desired, a central angled extension member 121 can be provided between extension members 117, 119 to receive another blade member. Arms 116, 118 (FIG. 3A) are coupled to extension members 117, 119, respectively.

Arms 116, 118 and their respective retraction blades 120, 122 can be moved toward and away from one another by the movement of handles 124, 126, generally as shown in U.S. Pat. No. 7,207,949. Preferably, handles 124, 126 are coupled to a gear mechanism that converts the movement of the handles toward each other into linear movement of retraction arms 116, 118 away from one another to widen the distance between those arms without rotating them. The distance between handles 124, 126 can be adjusted and fixed by rotation of knobs 134, 136.

The retraction instrument 110 is placed in cannulated fashion over the dilators with the shorter ipsilateral arm/retraction blade on the ipsilateral side of the operative corridor.

Retraction instrument 110 is slightly opened by moving handles 124, 126 toward one another so that opposing retraction arms 116, 118 move farther apart without rotation of the retraction arms. A standard xenon light source is carried by the instrument, and it is used for visualization of the anatomy at the distal tip of the instrument to position the retractor blades between the bifurcation of the right and left common iliac arteries and veins. The foot of ipsilateral blade 122 is placed beneath the ipsilateral vasculature (the right side for the approach illustrated in FIG. 3A) and the foot of contralateral blade 120 is placed under the contralateral vasculature (the left side for the approach illustrated in FIG. 3A). Handles 124, 126 are then moved closer together and fixed in position to move retraction arms 116, 118 away from one another and create surgical exposure of the anterior spine by moving ipsilateral vessels 66, 67 posteriorly and laterally with ipsilateral blade 122, and by moving contralateral vessels 68, 69 anteriorly and laterally with contralateral blade 120. Handles 124, 126 can be moved and fixed in different positions by rotation of knobs 134, 136.

FIGS. 5A and 5B illustrate retraction of the iliac vasculature to expose the L5-S1 intervertebral space; FIG. 5B also shows the trajectory along which retraction instrument 110 may be advanced. FIG. 5A shows the iliac vasculature

13

running along the anterior spine near the front of the L5-S1 intervertebral space 70. FIG. 5B illustrates the iliac vessels retracted away from the anterior face of the spine by the retractor instrument 110 (not shown). A trajectory along which retractor instrument 110 may be introduced is shown by arrow 128 in FIG. 5B. The illustrated trajectory is from anterolateral incision 92 through the region of notch 36 between interior superior iliac spine 32 and anterior inferior iliac spine 34. This trajectory contrasts with trajectory 130 (dotted line in FIG. 5B) taken by prior minimally invasive direct lateral surgeries for the L4-L5 disc space from the axillary line.

According to one aspect of the invention, once satisfactory ipsilateral vascular retraction is achieved, a shim 132 (FIGS. 3A and 4A, 4B, 4C) is inserted along the ipsilateral blade and advanced to position shim 132 within the anterolateral region of the L5-S1 disc space. Referring to FIGS. 22 and 23A-23C, blades 120, 122 can each be provided with a slot 133 for receiving a shim 132. FIG. 22 illustrates blade 122 with a shim 132 in slot 133, while blade 120 of FIG. 22 is shown without a shim or other structure positioned within its respective slot 133.

Shim 132 is an elongated plate with a substantially planar proximal portion 130a and a curved distal portion 130b. The curved distal portion 130b also tapers to a pointed distal tip 131 that is designed for introduction into an intervertebral space. The substantially planar proximal portion of shim 132 has a height h greater than its thickness t to minimize obstruction of access to the disc space when the shim is in place, and the height of the shim narrows anteriorly to pointed distal tip 131. Shim 132 further has a reversed curvature, in that its distal portion 130b is curved away from ipsilateral retraction blade 122 and toward contralateral retraction blade 120.

The curvature of the distal portion of shim 132 is relatively slight, being only 5-15 degrees out of the plane of the planar proximal portion 130a of shim 130. Alternatively, as shown in FIGS. 18A, 18B, and 18C, shim 132 can be substantially straight along its entire length. Shim 132 is attached to ipsilateral blade 120 to help lock retractor instrument 110 in position until removal of the instrument is desired, and distracts the adjacent vertebral bodies (such as L5 and S1) to restore disc height. Shim 132 can be coupled to ipsilateral blade 120 and/or contralateral blade 122 in a variety of manners. In a preferred embodiment, shim 132 comprises a projecting portion 135 that projects outward from a surface of shim 132. Projecting portion 135 can be a spring-loaded member that is biased outward from the surface of shim 132.

In use, shim 132 can be positioned in a slot 133 and secured thereto to the respective blade (e.g., blade 122 in FIG. 23C).

As shown in FIGS. 21 and 23B, a plurality of spaced detents or openings 137 can extend along the length of a rear side 139 of blade 122 to receive projecting portion 135 and secure shim 132 to blade 122. When projecting portion 135 is in a locked position (i.e., with projecting portion 135 extending at least partially through a detent 137), shim 132 is restricted from moving relative to blade 122. To adjust the position of shim 132 relative to blade 122, projecting portion 135 can be pushed inward towards the surface of shim 132, moving projecting portion 135 out of detent 137 and releasing shim 132 from blade 122. Once projecting portion 135 is released from detent 137, shim 132 can be moved into another position along blade 122 by pushing or otherwise directing shim 132 downward along the length of blade 122.

14

This process can be repeated until shim 132 is secured to blade 122 in a desired position.

Shim 132 also rigidly couples ipsilateral retractor blade 122 in fixed relation relative to the vertebral bodies, and helps ensure that surgical instruments employed within the operative corridor are not advanced outside the operative corridor, thereby avoiding inadvertent contact with the exiting nerve roots and vasculature during the surgery. Once the operative corridor is established, any of a variety of surgical instruments, devices, or implants may be passed through and/or manipulated within the operative corridor depending upon the given surgical procedure.

Superior and inferior soft tissue retractors (not shown) may also be placed as needed for retraction for any creeping retroperitoneal contents to allow creation of a box-type approach to the L5-S1 disc space. Discectomy is then carried out in a conventional fashion to evacuate as much of the disc and interspace contents as possible. The handle portion 112 may be coupled to any number of mechanisms for rigidly registering it in fixed relation to the operative site, such as through the use of an articulating arm mounted to the operating table 22.

Introducer Instrument

Once the discectomy has been completed, trial implants are introduced into the L5-S1 disc space 70 to select an appropriate size final implant, and a final implant is then introduced into the disc space.

FIGS. 6-9 illustrate an introducer instrument 140 for introducing implants into the disc space. Instrument 140 includes a rigid sheath 142 (FIGS. 6-7) that is sufficiently long to reach the L5-S1 disc space 70. A longitudinal axis 144 of sheath 142 is illustrated by a dashed line. Instrument 140 is provided with a proximal handle 146 that is coupled to a rotatable shaft 147 (FIG. 8) inside a ridged collar 148 (FIG. 7) so that shaft 147 can be rotated within sheath 142 by rotating handle 146 as collar 148 is grasped by the surgeon's hand to maintain collar 148 stationary. As shown in FIG. 7, an externally threaded rod 150 projects from a cylindrical distal tip 152 of sheath 142 along longitudinal axis 144 on sheath 142. A pair of small coupling pins 154, 156, which are smaller than threaded rod 150, project from distal tip 152 on either side of rod 150 in a fixed spaced alignment generally along a common plane that bisects shaft 142 along its axis 144. Coupling pins 154, 156 are substantially shorter and of much smaller diameter than the threaded rod 150. For example, coupling pins are less than 25% or even 10% of the diameter and length of threaded rod 150 projecting from the tip 152 of instrument 140.

As shown best in FIG. 8, threaded rod 150 is connected to rotatable shaft 147 by a reduced diameter step-down extension 158 that projects out of distal tip 152 of sheath 142 to provide a gap between threaded rod 150 and the face 160 of distal tip 152. Distal tip 152 (and pins 154, 156 that it carries) can be selectively advanced toward and retracted from implant 172 in a pathway generally parallel to longitudinal axis 144 by rotating handle 146. As handle 146 rotates counterclockwise, it drives shaft 147 to turn threaded rod 150 and loosen the connection between rod 150 and a threaded opening in the implant. Since pins 154, 156 have a much shorter axial length than threaded rod 150, only slight loosening of the threaded rod is required to disengage pins 154, 156 from the implant. Once pins 154, 156 are disengaged from the implant, they can be repositioned in another set of openings on the implant to change the angle between instrument 140 and the implant. Handle 146 is then rotated

15

clockwise to tighten the pins in their new openings to fix the new angular relationship between instrument 140 and the implant.

Threaded rod 150 and coupling pins 154, 156 form an example of a docking element of introducer instrument 140. The docking element selectively docks with an interface element 170 of an implant 172, as shown in FIG. 9. The docking element docks at a plurality of positions with interface element 170 to selectively alter an angle between implant 172 and introducer instrument 140. Implant 172 has a pivot axis 174 around which implant 172 may be pivoted relative to longitudinal axis 144 of instrument 140.

An example of an implant 172 is shown in greater detail in FIGS. 10A and 10B, where implant 172 has a top bearing face 176, a bottom bearing face 178, a front face 180, a rear face 182, an ipsilateral face 184 and a contralateral face 186. A rotation pin 188 extends between top and bottom faces 176, 178 and rotates relative to implant 172; pivot axis 174 of implant 172 extends along the axis of rotation pin 188. Interface element 170 (FIGS. 9 and 10A) has a recessed slot 190 between top and bottom faces 176, 178 that provides access to the side of rotation pin 188 in which an internally threaded opening 191 is provided which has threads that are complementary to the external threads of rod 150 of introducer instrument 140. An upper arcuate lip 192 and lower arcuate lip 194 form slot 190 cooperatively therebetween. Lips 192, 194 are spaced from and generally parallel to the outer walls of rotation pin 188. Lips 192, 194 of interface element 170 each have a series of spaced docking holes that form paired upper and lower sets of spaced holes arranged on the curved surfaces of the lips. These docking holes extend partially circumferentially around pivot axis 174, and selected pairs of spaced docking holes are positioned to mate with the docking element of introducer instrument 140. This docking is illustrated in greater detail in FIG. 9 wherein face 160 of distal tip 152 is curved to fit in register with the curved faces of lips 192, 194 with pin 154 in an upper member of a docking pair of holes on upper lip 192 and pin 156 (not shown in FIG. 9) in a corresponding aligned lower member of the docking pair of holes on lower lip 194. Interface element 170 therefore includes spaced docking holes that extend partially circumferentially around pivot axis 174 so that selected pairs of docking holes are positioned to mate with the docking element of introducer instrument 140.

In use, introducer instrument 140 is secured to an implant 172 by threading rod 150 into opening 191 of rotation pin 188 by rotating handle 146 to turn shaft 147 within sheath 142. Handle 146 is rotated until implant 172 is tightly secured to distal tip 152 and pins 154, 156 are aligned with and inserted within a pair of the upper and lower aligned docking holes. The angular relationship between instrument 140 and implant 172 can be altered by slightly unscrewing threaded rod 150 from threaded opening 191. This action moves face 160 of distal tip 152 sufficiently out of engagement with interface element 170 to disengage pins 154, 156 from a first set of docking holes without completely disconnecting instrument 140 from implant 172. The implant 172 and instrument 140 can then pivot relative to one another until sheath 142 is again advanced to engage coupling pins 152, 154 with a new pair of docking holes by rotating handle 146 to once again securely engage instrument 140 to implant 172, so that the implant is fixed at a new angular relationship with the instrument.

Although a particular embodiment of the device is illustrated in which the angular relationship between instrument 140 and implant 172 can be selectively altered, many other

16

means for varying this angular relationship to pivot the implant are contemplated. For example, rotation of handle 146 can actuate a gear that pivots implant 172, or handle rotation can actuate a cam that selectively moves pins 154, 156 to selectively engage and disengage them from interface element 170. Alternatively the tip of instrument 140 can fit into a slot within implant 172 to pivot the implant as instrument 140 is moved from the contralateral to the ipsilateral arm of the retractor instrument. In other embodiments, a universal joint is provided between the instrument 140 and implant 172 to selectively pivot the implant relative to the instrument. Different numbers and arrangements of the pins can also be provided. Electronic devices can also be used that rotate the implant in the plane of the disc space while maintaining the instrument within the operative pathway defined between the retraction blades of instrument 140.

The Implant

Additional features of implant 172 are shown in detail in FIGS. 10 and 11 to illustrate details that make the implant particularly suitable for insertion and progressive pivoting of the implant within the L5-S1 disc space, as described in greater detail below. The implant tapers in height from the height h1 of front face 180 to height h2 of rear face 182, and is elongated in a direction transverse to the direction of tapering height. Hence front face 180 and rear face 182 are longer than ipsilateral and contralateral faces 184, 186. The implant material is made of a generally compressible or elastomeric material. Front face 180 is generally convex, ipsilateral face 184 includes interface element 170, rear face 176 is generally flat, and contralateral face 186 is rounded at its front and rear edges to minimize impact damage to spinal structures as the implant is introduced into the disc space and pivoted into position. Implant 172 is also partially hollow and may have ipsilateral and contralateral windows 200, 202 extending between top and bottom faces 176, 178. The windows are formed by an internal divider wall 204 that extends from the front to rear of implant 172 and substantially bisects the implant into ipsilateral and contralateral halves. However, ipsilateral window 200 is smaller than contralateral window 202 because a portion of the ipsilateral half of implant 172 is occupied by rotation pin 188 and the structure that supports it. The windows 200, 202 provide communication between the open bottom and top faces of the implant to promote ingrowth of tissue within and through implant 172.

Top and bottom faces 176, 178 are provided with protuberances 206 that also help promote bone growth into implant 172. The protuberances may take a variety of shapes, but the illustrated frustopyramidal protuberances 206 are believed to be particularly suitable for this purpose.

In addition to the implant, trial spacers are also provided to help assess the size of the disc space once the disc space contents have been evacuated but before the final implant is advanced into the disc space.

FIGS. 11A, 11B, and 11C illustrate another embodiment of an implant 272. To facilitate comparison to implant 172, FIGS. 11A-C use reference numbers with the same two final digits for elements that are generally similar to elements identified in FIGS. 10A and 10B. Thus, implant 272 has a top bearing face 276, a bottom bearing face 278, a front face 280, a rear face 282, an ipsilateral face 284 and a contralateral face 286. A rotation pin 288 extends between top and bottom faces 276, 278 and rotates relative to implant 272. Pivot axis 274 of implant 272 extends along the axis of rotation pin 288.

An interface element 270 (FIGS. 11B and 11C) has a recessed slot 290 between top and bottom faces 276, 278 that provides access to the side of rotation pin 288 in which an internally threaded opening 291 is provided which has threads that are complementary to the external threads of rod 150 of introducer instrument 140. An upper arcuate lip 292 and lower arcuate lip 294 form slot 290 cooperatively therebetween. For clarity, FIG. 11B is shown without pin 288 fitted or received in implant 272.

Lips 292, 294 of interface element 270 can have a series of spaced docking holes such as that shown in FIGS. 10A and 10B. Alternatively, as shown in FIGS. 11B and 11C, lips 292, 294 can be formed without such docking holes. Instead, the introducer instrument can be shaped to contact a portion of the upper and/or lower curved faces of lips 292, 294, thereby forming a frictional fit between the convex face of implant 272 and a concave face 160 of the introducer instrument 140. Thus, in use, introducer instrument 140 can be secured to implant 272 by threading rod 150 into opening 291 of rotation pin 288 by rotating handle 146 to turn shaft 147 within sheath 142. When handle 146 is rotated a sufficient amount, implant 272 will be tightly secured to face 160 of distal tip 152. The angular relationship between instrument 140 and implant 272 can be altered by slightly unscrewing threaded rod 150 from threaded opening 291. This action moves face 160 of distal tip 152 sufficiently out of engagement of the frictional fit with interface element 270 (or other contacting portion of a surface of implant 272). Implant 272 and instrument 140 can then pivot relative to one another until sheath 142 is again advanced to engage the instrument 140 and implant 272 in a frictional fit that is tight enough to restrict relative movement of the instrument 140 and implant 272.

As shown in FIGS. 11B and 11C, implant 272 can be constructed so that it is substantially the same thickness (height) along its length (FIG. 11B), while at the same time varying in thickness (height) along its width (FIG. 11C). In particular, as shown in FIG. 11C, the thickness (height) of implant 272 can vary from a first larger height to a second smaller height to facilitate the implantation of the device in the patient.

Like implant 172, implant 272 can be provided with protuberances 306 that help promote bone growth into implant 172. As noted above, such protuberances can take a variety of shapes.

Also like implant 172, implant 272 can be at least partially hollow and can have one or more windows (e.g., windows 300, 302). Windows 300, 302 can provide the same benefits as windows 200, 202 in the previous embodiment, which is to provide communication between the open bottom and top faces of the implant to promote ingrowth of tissue within and through implant 272. Implant 272 can also have one or more openings 303 that extend through a side wall of the implant to further promote ingrowth of tissue and to facilitate access to internal areas of implant 272 (e.g., access to one or both of windows 300, 302) when implant 272 is implanted in the body.

Windows 300, 302 can extend between top and bottom faces 276, 278 as shown in FIG. 11A. The windows can be formed by an internal divider wall 304 that substantially bisect the implant into two halves. Unlike divider wall 204 shown in FIG. 10A, however, divider wall 304 preferably extends diagonally across implant 272 from an area adjacent or near the pin 288 to an area at or near contralateral face 286. By extending generally diagonally across implant 272 as shown in FIG. 11A, diagonal wall 304 can provide structural strength to the implant in the general direction of

the force that will be applied to implant 272 during implantation. For example, as shown in FIG. 20, divider wall 304 is located substantially in-line with the instrument 140.

FIG. 12 illustrates another version of an implant 220. This implant is similar to that shown in FIGS. 10-11, except it is substantially rectangular in shape instead of polygonal, and it has a rotation pin 222 with a pivot axis 224 that extends between a front and rear face of implant 220. Rotation pin 222 includes an opening 226 (e.g., a threaded opening) for receiving a threaded distal end of introducer instrument 140. As described above with respect to implant 172, implant 220 can be secured to threading rod 150 by positioning rod 150 into opening 226 and rotating handle 146 to turn shaft 147 and tighten the distal end of the instrument (e.g., face 160) to a facing surface of implant 220.

Because rotation pin 222 is positioned horizontally (FIG. 12) rather than vertically (FIG. 10A), implant 220 is therefore suitable for pivoting up and down with respect to introducer instrument 140 instead of from side-to-side as with implant 172. It may also have varied dimensions medial to lateral as described for implant 172, although other embodiments do not taper and are of uniform height. The embodiment of the implant shown in FIG. 12 is generally used in surgeries superior to the L5-S1 space, for example in the L4-L5 space or the L3-L4 space. By providing an implant that can pivot vertically, such as implant 220, the implantation site can be more easily accessed from an incision point superior or inferior to the implantation site. For example, in use, the implant can be delivered to the implantation site from a location superior to iliac crest 30 and pivoted vertically into the desired position at the implantation site.

As with the other implants described herein, implant 220 can be provided with one or more windows 228, 230 and a plurality of protrusions 232 to promote the ingrowth of tissue. Implant 220 can also be provided with a plurality of docking holes 234 to help lock or secure implant 220 to a distal end of instrument 140. Alternatively, implant 220 can be secured to the instrument 140 via a frictional fit or other similar mechanism. FIGS. 19A, 19B, and 19C illustrate another embodiment of an implant that can pivot up and down (e.g., vertically), in a manner similar to that shown in FIG. 12. Implant 320 is configured to receive a rotation pin (not shown) in a recess 322 between a top surface 324 and a bottom surface 326 of implant 320. As described in other embodiments, implant 320 can include a plurality of windows 330, 332 separated by a divider wall 334. In addition, openings 336 can be formed in the side of the implant as shown in FIGS. 19A and 19B.

Introducing the Trial Spacer and Disc Implant

Once the operative corridor has been established by retraction instrument 110 and the operative field has been exposed, a trial spacer 210 is attached to introducer instrument 140 and advanced into the L5-S1 disc space as shown in FIG. 13. The trial spacer is generally similar to implant 174, except it does not have the protuberances projecting from its top and bottom faces. For the initial introduction of trial spacer 210, the spacer is directly laterally attached to instrument 110. The direct lateral attachment is shown in FIG. 13, wherein the longitudinal axis of sheath 142 is generally parallel to flat rear face 182 of implant 210. Because of the anterolateral operative pathway to the disc space, trial implant 210 moves along a generally oblique or diagonal pathway into the disc space. The "oblique" pathway is one that travels diagonally within the body, for example in an oblique anatomic plane. The oblique pathway may be a diagonal pathway, for example between 15 and 45

or 60 degrees to a coronal plane of the body. In FIG. 13, the oblique pathway is shown at an angle of about 30 degrees to coronal plane 212 (FIG. 13). The oblique pathway may be either in a transverse plane of the body, or above or below a transverse plane (for example between 15 and 45 or 60 degrees to a transverse plane of the body). However, in a particular disclosed embodiment of the method, fluoroscopy is used to detect the level of the target disc space (such as L5-S1) so that the instrument, spacer and implant can be introduced diagonally in the body, but generally in the plane of the L5-S1 disc space.

As trial spacer 210 enters the illustrated L5-S1 disc space (FIGS. 13 and 14A), contralateral face 186 impacts the posterior contralateral aspect of the disc space. The rounded edges of contralateral face 186 help avoid damage to the structures which the contralateral face 186 of the trial spacer encounters. The trial spacer is then progressively reoriented from its diagonal orientation in the disc space (FIG. 14A) to a generally medial-lateral orientation (FIG. 14C) by successively retracting sheath 142, pivoting the trial spacer on rotation pin 188 by forcing contralateral face of trial spacer 210 against the postero lateral apophyseal ring and moving introducer instrument 140 toward ipsilateral retractor arm 118, and repositioning coupling pins in a new set of docking holes that maintain the trial spacer in an intermediate position shown in FIG. 14B. Sheath 142 is then retracted again, and the trial spacer pivoted on rotation pin 188 to the generally medial-lateral orientation (FIG. 14C). As the trial spacer 210 moves from its initial diagonal to final medial-lateral orientation (with its flat rear face generally parallel to a coronal plane of the body), sheath 142 moves from a first position abutting contralateral retractor blade 120 (FIG. 14A) to a second position abutting ipsilateral blade 122 (FIG. 14C).

Trial spacers of different sizes may be introduced into the disc space and pivoted from the diagonal to the medial-lateral orientation until a trial spacer of the appropriate size and height is found. Introducer instrument 140 is detached from trial spacer 210 by rotating handle to unscrew threaded 150 from the internally threaded opening of trial spacer 210 to secure different trial spacers until the correct one is found. The trial spacer is then withdrawn from the disc space and detached from introducer instrument 140, and the final implant 172 is directly laterally attached to distal tip 152 of introducer instrument 140 (as illustrated in FIG. 15) by rotating handle 146 to screw the threaded rod at the tip of instrument 140 into the internally threaded hole on the implant. With the implant 172 directly laterally attached to instrument 141, the elongated implant 172 can be introduced through a relatively narrow operative pathway between the arms of retractor instrument 110. FIG. 16A illustrates the diagonal introduction of implant 172 into the disc space along the same pathway already described for trial spacer 210. The implant enters the disc space with its flat rear face 182 at an angle of about 15-45 degrees (for example 30 degrees) to a coronal plane of the body. The implant is then progressively reoriented by retracting sheath 142, pivoting implant 172 within the disc space, and advancing sheath 142 to reengage coupling pins 154, 156 within a new set of docking holes to hold implant 172 in the intermediate orientation shown in FIG. 16B wherein the implant is at an angle of about 15 degrees to a coronal plane of the body. Implant 172 can then be further reoriented in this fashion until sheath 142 contacts ipsilateral arm 118 of retractor instrument 110 (FIG. 16C). Once implant 172 cannot be reoriented any further using the instrument, handle 146 is

rotated to completely disengage introducer instrument 140 from implant 172. Instrument 140 is then withdrawn from retractor instrument 110.

Additional positioning of implant 172 can be achieved by pushing it with the tip of instrument 140, or with other elongated instruments introduced through retractor instrument 110. Retractor instrument 110 can then be removed from the body by moving arms 116, 118 toward one another to reduce the width of instrument 110 then withdrawing it from the body. Normal closure of the surgical incisions on the body surface is then carried out.

FIG. 20 illustrates implant 272 secured to instrument 140 and being delivered to an implantation site. The method of delivering implant 272 is substantially the same as the method of delivering implant 172, which is described above and shown in FIGS. 15-17.

Implant 272 is desirably secured to the distal end of instrument 140 so that divider wall 304 is generally in-line with axis 350 of instrument 140. In this manner, implant 272 can exhibit increased strength to ensure that it can withstand the impaction force, which is generally applied along the axis 350 to deliver implant 272 to the desired location in the body.

The implants described herein can be coated with and/or impregnated with various elements to promote bone in-growth. In a preferred embodiment, stem cells can be delivered along with the implant (either delivered into openings in the implant or coated thereon) to improve and facilitate bone in-growth. In view of the many possible embodiments to which the principles of the disclosed invention may be applied, it should be recognized that the illustrated embodiments are only preferred examples of the invention and should not be taken as limiting the scope of the invention. Rather, the scope of the invention is defined by the following claims. We therefore claim as our invention all that comes within the scope and spirit of these claims.

What is claimed is:

1. A spinal implant system advanceable along an oblique anterolateral retroperitoneal operative corridor to an intervertebral disc space, the spinal implant system comprising:

a spinal implant sized and shaped to be introduced into the intervertebral disc space via the oblique anterolateral retroperitoneal operative corridor, the spinal implant further sized and shaped to be repositionable within and to substantially occupy the intervertebral disc space, the spinal implant including:

an implant body including:

- a top bearing face having upper bone engagement protuberances;
- a bottom bearing face located opposite the top bearing face, the bottom bearing face having lower bone engagement protuberances;
- an anterior face extending between the top bearing face and the bottom bearing face;
- a posterior face located opposite the anterior face, the posterior face extending between the top bearing face and the bottom bearing face;
- an ipsilateral face located between the anterior face and the posterior face, the ipsilateral face extending between the top bearing face and the bottom bearing face, the ipsilateral face including an upper arcuate lip and a lower arcuate lip;
- a contralateral face located between the anterior face and the posterior face opposite the ipsilateral face, the contralateral face extending between the top bearing face and the bottom bearing face; and

21

a recessed slot formed along the ipsilateral face and located within the implant body between the top bearing face and the bottom bearing face; and
 a pin extending between the top bearing face and the bottom bearing face, the pin pivotable about a vertical pivot axis between a plurality of angular positions relative to the implant body, the pin including an internally threaded opening having a central axis oriented transverse to the vertical pivot axis, the internally threaded opening accessible via the recessed slot; and
 an introducer instrument configured to introduce the spinal implant into the intervertebral disc space via the oblique anterolateral retroperitoneal operative corridor, the introducer instrument further configured to reposition the spinal implant within the intervertebral disc space from an initial oblique orientation to a lateral orientation in which the posterior face of the spinal implant is substantially parallel to a coronal plane of the intervertebral disc space, the introducer instrument including:
 a sheath including a distal tip having a plurality of fixation protuberances, the sheath defining a longitudinal axis; and
 a rotatable shaft extending through the sheath, the rotatable shaft including an externally threaded end projecting externally from the distal tip past the fixation protuberances, wherein the externally threaded end of the rotatable shaft of the introducer instrument is configured to threadedly mate with the internally threaded opening of the pin of the spinal implant while the externally threaded end is positioned within the recessed slot of the implant body of the spinal implant, wherein rotation of the rotatable shaft in a first rotational direction about the longitudinal axis while the externally threaded end is threadedly coupled to the internally threaded opening and the pin is positioned at a first angular position from among the plurality of angular positions advances the externally threaded end along the internally threaded opening, the advancement causing at least a first one of the plurality of fixation protuberances of the introducer instrument to engage the upper arcuate lip of the ipsilateral face of the spinal implant and at least a second one of the plurality of fixation protuberances of the introducer instrument to engage the lower arcuate lip of the ipsilateral face of the spinal implant in a manner that fixes the pin of the spinal implant relative to the implant body of the spinal implant at the first angular position and also fixes the introducer instrument relative to the spinal implant at the first angular position, wherein rotation of the rotatable shaft in a second rotational direction about the longitudinal axis opposite the first rotational direction while the pin and the introducer instrument are fixed at the first angular position retracts the externally threaded end along the internally threaded opening, the retraction causing the at least a first one of the plurality of fixation protuberances of the introducer instrument to disengage from the upper arcuate lip of the ipsilateral face of the spinal implant and the at least a second one of the plurality of fixation protuberances of the introducer instrument to disengage from the lower arcuate lip of the ipsilateral face of the spinal implant in a manner that releases the pin and the introducer instrument from the first angular position while the externally

22

threaded end remains threadedly coupled to the internally threaded opening, wherein the pin can subsequently be pivoted relative to the implant body of the spinal implant via the introducer instrument from the first angular position to a second angular position from among the plurality of angular positions, the second angular position differing from the first angular position, wherein rotation of the rotatable shaft in the first rotational direction about the longitudinal axis while the externally threaded end remains threadedly coupled to the internally threaded opening and the pin is positioned at the second angular position fixes the pin of the spinal implant relative to the implant body of the spinal implant at the second angular position and also fixes the introducer instrument relative to the spinal implant at the second angular position.

2. The spinal implant system of claim 1, wherein the pin of the spinal implant is exposed along the ipsilateral face of the implant body through the recessed slot.

3. The spinal implant system of claim 1, further comprising a multi-blade retractor having at least first and second retractor blades that are sized to establish the oblique anterolateral retroperitoneal operative corridor to the intervertebral disc space.

4. The spinal implant system of claim 3, wherein the first retractor blade has a different tip shape than the second retractor blade such that the first retractor blade is configured to lateralize a left common iliac vein and a left common iliac artery, and the second retractor blade is configured to lateralize a right common iliac vein and a right common iliac artery.

5. The spinal implant system of claim 1, wherein the implant body has a longitudinal length that extends from the ipsilateral face to the contralateral face and that is configured to be arranged parallel to the coronal plane of the intervertebral disc space, wherein the implant body has a maximum width that extends from the posterior face to the anterior face and that is configured to be arranged parallel to a medial plane of the intervertebral disc space.

6. The spinal implant system of claim 1, wherein the vertical pivot axis is located between the anterior face and the posterior face and between the ipsilateral face and the contralateral face.

7. The spinal implant system of claim 1, wherein the recessed slot is located between the upper arcuate lip and the lower arcuate lip.

8. The spinal implant system of claim 1, wherein an outer surface of the upper arcuate lip and an outer surface of the lower arcuate lip are spaced apart from and extend generally parallel to an outer wall of the pin of the spinal implant that is exposed through the recessed slot of the implant body.

9. The spinal implant system of claim 1, wherein the rotatable shaft is rotatable relative to the sheath.

10. The spinal implant system of claim 1, wherein the ipsilateral face of the implant body is parallel to the vertical pivot axis.

11. The spinal implant system of claim 1, wherein the posterior face of the implant body is flat.

12. The spinal implant system of claim 1, wherein the anterior face of the implant body has a front maximum height and the posterior face of the implant body has a rear maximum height, wherein the rear maximum height is less than the front maximum height.

23

13. The spinal implant system of claim 12, wherein the implant body tapers in height from the front maximum height of the anterior face to the rear maximum height of the posterior face.

14. A spinal implant system advanceable along an oblique anterolateral retroperitoneal operative corridor to an intervertebral disc space, the spinal implant system comprising:

a spinal implant sized and shaped to be introduced into the intervertebral disc space via the oblique anterolateral retroperitoneal operative corridor, the spinal implant further sized and shaped to be repositionable within and to substantially occupy the intervertebral disc space, the spinal implant including:

an implant body including:

a top bearing face having upper bone engagement protuberances;

a bottom bearing face located opposite the top bearing face, the bottom bearing face having lower bone engagement protuberances;

an anterior face extending between the top bearing face and the bottom bearing face;

a posterior face located opposite the anterior face, the posterior face extending between the top bearing face and the bottom bearing face;

an ipsilateral face located between the anterior face and the posterior face, the ipsilateral face extending between the top bearing face and the bottom bearing face, the ipsilateral face including an upper arcuate lip and a lower arcuate lip;

a contralateral face located between the anterior face and the posterior face opposite the ipsilateral face, the contralateral face extending between the top bearing face and the bottom bearing face;

a recessed slot formed along the ipsilateral face and located within the implant body between the top bearing face and the bottom bearing face; and

a tissue ingrowth window extending through the top bearing face and the bottom bearing face, the tissue ingrowth window located between the anterior face and the posterior face and between the contralateral face and the ipsilateral face; and

a pin extending between the top bearing face and the bottom bearing face, the pin exposed along the ipsilateral face through the recessed slot, the pin pivotable about a vertical pivot axis between a plurality of angular positions relative to the implant body, the vertical pivot axis located between the anterior face and the posterior face and between the ipsilateral face and the contralateral face, the vertical pivot axis being parallel to the ipsilateral face, the pin including an internally threaded opening having a central axis oriented transverse to the vertical pivot axis, the internally threaded opening accessible via the recessed slot; and

an introducer instrument configured to introduce the spinal implant into the intervertebral disc space via the oblique anterolateral retroperitoneal operative corridor, the introducer instrument further configured to reposition the spinal implant within the intervertebral disc space from an initial oblique orientation to a lateral orientation in which the posterior face of the spinal implant is substantially parallel to a coronal plane of the intervertebral disc space, the introducer instrument including:

24

a sheath including a distal tip having a plurality of fixation protuberances, the sheath defining a longitudinal axis; and

a rotatable shaft extending through the sheath, the rotatable shaft including an externally threaded end projecting externally from the distal tip past the fixation protuberances, wherein the externally threaded end of the rotatable shaft of the introducer instrument is configured to threadedly mate with the internally threaded opening of the pin of the spinal implant while the externally threaded end is positioned within the recessed slot of the implant body of the spinal implant, wherein rotation of the rotatable shaft in a first rotational direction about the longitudinal axis while the externally threaded end is threadedly coupled to the internally threaded opening and the pin is positioned at a first angular position from among the plurality of angular positions advances the externally threaded end along the internally threaded opening, the advancement causing at least a first one of the plurality of fixation protuberances of the introducer instrument to engage the upper arcuate lip of the ipsilateral face of the spinal implant and at least a second one of the plurality of fixation protuberances of the introducer instrument to engage the lower arcuate lip of the ipsilateral face of the spinal implant in a manner that fixes the pin of the spinal implant relative to the implant body of the spinal implant at the first angular position and also fixes the introducer instrument relative to the spinal implant at the first angular position, wherein rotation of the rotatable shaft in a second rotational direction about the longitudinal axis opposite the first rotational direction while the pin and the introducer instrument are fixed at the first angular position retracts the externally threaded end along the internally threaded opening, the retraction causing the at least a first one of the plurality of fixation protuberances of the introducer instrument to disengage from the upper arcuate lip of the ipsilateral face of the spinal implant and the at least a second one of the plurality of fixation protuberances of the introducer instrument to disengage from the lower arcuate lip of the ipsilateral face of the spinal implant in a manner that releases the pin and the introducer instrument from the first angular position while the externally threaded end remains threadedly coupled to the internally threaded opening, wherein the pin can subsequently be pivoted relative to the implant body of the spinal implant via the introducer instrument from the first angular position to a second angular position from among the plurality of angular positions, the second angular position differing from the first angular position, wherein rotation of the rotatable shaft in the first rotational direction about the longitudinal axis while the externally threaded end remains threadedly coupled to the internally threaded opening and the pin is positioned at the second angular position fixes the pin of the spinal implant relative to the implant body of the spinal implant at the second angular position and also fixes the introducer instrument relative to the spinal implant at the second angular position.

15. The spinal implant system of claim 14, wherein the recessed slot is located between the upper arcuate lip and the lower arcuate lip.

25

16. The spinal implant system of claim 14, wherein an outer surface of the upper arcuate lip and an outer surface of the lower arcuate lip are spaced apart from and extend generally parallel to an outer wall of the pin of the spinal implant that is exposed through the recessed slot of the implant body.

17. The spinal implant system of claim 14, wherein the rotatable shaft is rotatable relative to the sheath.

18. The spinal implant system of claim 14, wherein the anterior face of the implant body has a front maximum height and the posterior face of the implant body has a rear maximum height, wherein the rear maximum height is less than the front maximum height.

19. The spinal implant system of claim 18, wherein the implant body tapers in height from the front maximum height of the anterior face to the rear maximum height of the posterior face.

20. A spinal implant system advanceable along an oblique anterolateral retroperitoneal operative corridor to an intervertebral disc space, the spinal implant system comprising:

a spinal implant sized and shaped to be introduced into the intervertebral disc space via the oblique anterolateral retroperitoneal operative corridor, the spinal implant further sized and shaped to be repositionable within the intervertebral disc space, the spinal implant including: an implant body including:

a top bearing face having upper bone engagement protuberances;

a bottom bearing face located opposite the top bearing face, the bottom bearing face having lower bone engagement protuberances;

an anterior face extending between the top bearing face and the bottom bearing face;

a posterior face located opposite the anterior face, the posterior face extending between the top bearing face and the bottom bearing face, the posterior face being flat;

an ipsilateral face located between the anterior face and the posterior face, the ipsilateral face extending between the top bearing face and the bottom bearing face, the ipsilateral face including an upper arcuate lip and a lower arcuate lip;

a contralateral face located between the anterior face and the posterior face opposite the ipsilateral face, the contralateral face extending between the top bearing face and the bottom bearing face;

a recessed slot formed along the ipsilateral face between the upper arcuate lip and the lower arcuate lip, the recessed slot located within the implant body between the top bearing face and the bottom bearing face; and

a tissue ingrowth window extending through the top bearing face and the bottom bearing face, the tissue ingrowth window located between the anterior face and the posterior face and between the contralateral face and the ipsilateral face; and

a pin extending between the top bearing face and the bottom bearing face, the pin exposed along the ipsilateral face through the recessed slot, the pin pivotable about a vertical pivot axis between a plurality of angular positions relative to the implant body, the vertical pivot axis positioned between the anterior face and the posterior face and between the ipsilateral face and the contralateral face, the vertical pivot axis being parallel to the ipsilateral face, the pin including an internally threaded opening having

26

a central axis oriented transverse to the vertical pivot axis, the internally threaded opening accessible via the recessed slot, wherein an outer surface of the upper arcuate lip and an outer surface of the lower arcuate lip are spaced apart from and extend generally parallel to an outer wall of the pin; and

an introducer instrument configured to introduce the spinal implant into the intervertebral disc space via the oblique anterolateral retroperitoneal operative corridor, the introducer instrument further configured to reposition the spinal implant within the intervertebral disc space from an initial oblique orientation to a lateral orientation in which the posterior face of the spinal implant is substantially parallel to a coronal plane of the intervertebral disc space, the introducer instrument including:

a sheath including a distal tip having a plurality of fixation protuberances, the sheath defining a longitudinal axis; and

a rotatable shaft extending through the sheath, the rotatable shaft including an externally threaded end projecting externally from the distal tip past the fixation protuberances, wherein the externally threaded end of the rotatable shaft of the introducer instrument is configured to threadedly mate with the internally threaded opening of the pin of the spinal implant while the externally threaded end is positioned within the recessed slot of the implant body of the spinal implant, wherein rotation of the rotatable shaft in a first rotational direction about the longitudinal axis while the externally threaded end is threadedly coupled to the internally threaded opening and the pin is positioned at a first angular position from among the plurality of angular positions advances the externally threaded end along the internally threaded opening, the advancement causing at least a first one of the plurality of fixation protuberances of the introducer instrument to engage the upper arcuate lip of the ipsilateral face of the spinal implant and at least a second one of the plurality of fixation protuberances of the introducer instrument to engage the lower arcuate lip of the ipsilateral face of the spinal implant in a manner that fixes the pin of the spinal implant relative to the implant body of the spinal implant at the first angular position and also fixes the introducer instrument relative to the spinal implant at the first angular position, wherein rotation of the rotatable shaft in a second rotational direction about the longitudinal axis opposite the first rotational direction while the pin and the introducer instrument are fixed at the first angular position retracts the externally threaded end along the internally threaded opening, the retraction causing the at least a first one of the plurality of fixation protuberances of the introducer instrument to disengage from the upper arcuate lip of the ipsilateral face of the spinal implant and the at least a second one of the plurality of fixation protuberances of the introducer instrument to disengage from the lower arcuate lip of the ipsilateral face of the spinal implant in a manner that releases the pin and the introducer instrument from the first angular position while the externally threaded end remains threadedly coupled to the internally threaded opening, wherein the pin can subsequently be pivoted relative to the implant body of the spinal implant via the introducer instrument from the first angular position to a second angular

27

position from among the plurality of angular positions, the second angular position differing from the first angular position, wherein rotation of the rotatable shaft in the first rotational direction about the longitudinal axis while the externally threaded end 5 remains threadedly coupled to the internally threaded opening and the pin is positioned at the second angular position fixes the pin of the spinal implant relative to the implant body of the spinal implant at the second angular position and also fixes 10 the introducer instrument relative to the spinal implant at the second angular position that differs from the corresponding first angular position.

21. The spinal implant system of claim **20**, wherein the rotatable shaft is rotatable relative to the sheath. 15

22. The spinal implant system of claim **20**, wherein the anterior face of the implant body has a front maximum height and the posterior face of the implant body has a rear maximum height, wherein the rear maximum height is less than the front maximum height. 20

23. The spinal implant system of claim **22**, wherein the implant body tapers in height from the front maximum height of the anterior face to the rear maximum height of the posterior face.

* * * * *

25

28