

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383921
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Fritz; Hans-Georg et al.

Coating device and corresponding coating process

Abstract

The disclosure concerns a coating device and a corresponding coating process for coating components, in particular motor vehicle body components, with a coating agent (e.g. paint), with a coating robot with a first printhead which is mounted on the coating robot. The disclosure provides that the first printhead is exchangeably mounted on the coating robot and can be exchanged for a second printhead during a color change. Another variant of the disclosure, on the other hand, provides for a second printhead to be mounted on the coating robot in addition to the first printhead, the two printheads each applying a specific coating agent in order to enable a color change without changing the printhead.

Inventors: Fritz; Hans-Georg (Ostfildern, DE), Wöhr; Benjamin (Eibensbach, DE), Kleiner; Marcus (Besigheim, DE), Bubek; Moritz (Ludwigsburg, DE), Beyl; Timo (Besigheim, DE), Herre; Frank (Oberriexingen, DE), Sotzny; Steffen (Oberstenfeld, DE)

Applicant: Dürr Systems AG (Bietigheim-Bissingen, DE)

Family ID: 60582577

Appl. No.: 18/402832

Filed: January 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240139768 A1	May. 02, 2024

Foreign Application Priority Data

DE	10 2016 014 955.8	Dec. 14, 2016
----	-------------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **B05B15/58** (20180101); **B05B1/14** (20060101); **B05B1/16** (20060101); **B05B12/14** (20060101); **B05B15/531** (20180101); **B05B15/55** (20180101); **B05B15/555** (20180101); **B05D1/02** (20060101); **B25J11/00** (20060101); **B41J3/407** (20060101); **B41J3/54** (20060101); B05B13/04 (20060101)

U.S. Cl.:

CPC **B05B15/58** (20180201); **B05B1/14** (20130101); **B05B1/16** (20130101); **B05B12/14** (20130101); **B05B12/149** (20130101); **B05B15/531** (20180201); **B05B15/55** (20180201); **B05B15/555** (20180201); **B05D1/02** (20130101); **B25J11/0075** (20130101); **B41J3/4073** (20130101); **B41J3/543** (20130101); B05B13/0452 (20130101)

Field of Classification Search

CPC: B05B (15/555); B05B (15/531); B05B (1/14); B05D (1/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3421694	12/1968	Muller	N/A	N/A
3717306	12/1972	Hushon et al.	N/A	N/A
3981320	12/1975	Wiggins	N/A	N/A
4141231	12/1978	Kudlich	N/A	N/A
4375865	12/1982	Springer	N/A	N/A
4383264	12/1982	Lewis	N/A	N/A
4423999	12/1983	Choly	N/A	N/A
4430010	12/1983	Zrenner et al.	N/A	N/A
4435719	12/1983	Snaper	N/A	N/A
4478241	12/1983	Cardenas-Franco	N/A	N/A
4555719	12/1984	Arway et al.	N/A	N/A
4593360	12/1985	Cocks	N/A	N/A
4668948	12/1986	Merkel	N/A	N/A
4714044	12/1986	Kikuchi	N/A	N/A
4734711	12/1987	Piatt et al.	N/A	N/A
4826135	12/1988	Mielke	N/A	N/A
4894252	12/1989	Bongen et al.	N/A	N/A
4941778	12/1989	Lehmann	N/A	N/A
4974780	12/1989	Nakamura et al.	N/A	N/A
4985715	12/1990	Cyphert et al.	N/A	N/A
5050533	12/1990	Zaber	N/A	N/A
5072881	12/1990	Taube, III	N/A	N/A

5429682	12/1994	Harlow, Jr	N/A	N/A
5435884	12/1994	Simmons et al.	N/A	N/A
5538221	12/1995	Joswig	N/A	N/A
5556466	12/1995	Martin et al.	N/A	N/A
5602575	12/1996	Pauly	N/A	N/A
5636795	12/1996	Sedgwick et al.	N/A	N/A
5647542	12/1996	Diana	N/A	N/A
5659347	12/1996	Taylor	N/A	N/A
5681619	12/1996	Ogasawara	N/A	N/A
5740967	12/1997	Simmons et al.	N/A	N/A
5843515	12/1997	Crum et al.	N/A	N/A
5951882	12/1998	Simmons et al.	N/A	N/A
5964407	12/1998	Sandkleiva	N/A	N/A
5976343	12/1998	Schlaak	N/A	N/A
6164746	12/1999	Akahira et al.	N/A	N/A
6179217	12/2000	Yoshida et al.	N/A	N/A
6325302	12/2000	Guzowski	N/A	N/A
6540835	12/2002	Kim et al.	N/A	N/A
6607145	12/2002	Boriani et al.	N/A	N/A
6641667	12/2002	Ochiai et al.	N/A	N/A
6712285	12/2003	Provenaz et al.	N/A	N/A
6777032	12/2003	Ogasahara et al.	N/A	N/A
6811807	12/2003	Zimmermann et al.	N/A	N/A
6849684	12/2004	Poppe et al.	N/A	N/A
7160105	12/2006	Edwards	N/A	N/A
7178742	12/2006	Nellentine et al.	N/A	N/A
7182815	12/2006	Katagami et al.	N/A	N/A
7244310	12/2006	Edwards	N/A	N/A
7270712	12/2006	Edwards	N/A	N/A
7357959	12/2007	Bauer	N/A	N/A
7387071	12/2007	Heinke et al.	N/A	N/A
7449070	12/2007	Fellingham	N/A	N/A
7604333	12/2008	Horsnell	N/A	N/A
7757632	12/2009	Edwards	N/A	N/A
7837071	12/2009	Achrainer	N/A	N/A
7901741	12/2010	Katagami et al.	N/A	N/A
8028651	12/2010	Rademacher et al.	N/A	N/A
8118385	12/2011	Van De Wynckel et al.	N/A	N/A
8449087	12/2012	Kataoka et al.	N/A	N/A
8545943	12/2012	Frankenberger et al.	N/A	N/A
8652581	12/2013	Merchant	N/A	N/A
8678535	12/2013	Beier et al.	N/A	N/A
8875655	12/2013	Pettersson et al.	N/A	N/A
8882242	12/2013	Beier et al.	N/A	N/A
9010899	12/2014	Harjee et al.	N/A	N/A
9108424	12/2014	Wallsten et al.	N/A	N/A
9140247	12/2014	Herre et al.	N/A	N/A
9156054	12/2014	Ikushima	N/A	N/A
9266353	12/2015	Beier et al.	N/A	N/A

9393787	12/2015	Ikushima	N/A	N/A
9464573	12/2015	Remy et al.	N/A	N/A
9592524	12/2016	Fritz et al.	N/A	N/A
9701143	12/2016	Ikushima	N/A	N/A
9707585	12/2016	Reimert et al.	N/A	N/A
9844792	12/2016	Pettersson et al.	N/A	N/A
9901945	12/2017	Fehr et al.	N/A	N/A
9914150	12/2017	Pettersson et al.	N/A	N/A
10016977	12/2017	Stefani et al.	N/A	N/A
10105946	12/2017	Nakamura et al.	N/A	N/A
10150304	12/2017	Herre et al.	N/A	N/A
10252552	12/2018	Pitz et al.	N/A	N/A
10272677	12/2018	Stefani et al.	N/A	N/A
10464095	12/2018	Fritz	N/A	N/A
10532569	12/2019	Wallsten et al.	N/A	N/A
10814643	12/2019	Herre	N/A	N/A
11504735	12/2021	Fritz	N/A	N/A
2001/0006392	12/2000	Otsuki	N/A	N/A
2001/0017085	12/2000	Kubo et al.	N/A	N/A
2001/0019340	12/2000	Kubo et al.	N/A	N/A
2002/0024544	12/2001	Codos	N/A	N/A
2002/0043280	12/2001	Ochiai et al.	N/A	N/A
2002/0043567	12/2001	Provenaz et al.	N/A	N/A
2002/0105688	12/2001	Katagami et al.	N/A	N/A
2002/0109741	12/2001	Okabe et al.	N/A	N/A
2002/0128371	12/2001	Poppe et al.	N/A	N/A
2003/0020783	12/2002	Sanada	N/A	N/A
2003/0041884	12/2002	Bahr	N/A	N/A
2003/0049383	12/2002	Ogasahara et al.	N/A	N/A
2003/0063154	12/2002	Goto	N/A	N/A
2004/0028830	12/2003	Bauer	N/A	N/A
2004/0089234	12/2003	Hagglund et al.	N/A	N/A
2004/0107900	12/2003	Clifford et al.	N/A	N/A
2004/0123159	12/2003	Kerstens	N/A	N/A
2004/0173144	12/2003	Edwards	N/A	N/A
2004/0221804	12/2003	Zimmermann et al.	N/A	N/A
2004/0231594	12/2003	Edwards	N/A	N/A
2004/0238522	12/2003	Edwards	N/A	N/A
2004/0256501	12/2003	Mellentine et al.	N/A	N/A
2004/0261700	12/2003	Edwards	N/A	N/A
2005/0000422	12/2004	Edwards	N/A	N/A
2005/0015050	12/2004	Mowery et al.	N/A	N/A
2005/0016451	12/2004	Edwards	N/A	N/A
2005/0023367	12/2004	Reighard et al.	N/A	N/A
2005/0156963	12/2004	Song et al.	N/A	N/A
2005/0243112	12/2004	Kobayashi et al.	N/A	N/A
2006/0061613	12/2005	Fienup et al.	N/A	N/A
2006/0068109	12/2005	Frankenberger et al.	N/A	N/A
2006/0146379	12/2005	Katagami et al.	N/A	N/A
2006/0238587	12/2005	Horsnell	N/A	N/A

2006/0251796	12/2005	Fellingham	N/A	N/A
2007/0062383	12/2006	Gazeau	N/A	N/A
2007/0292626	12/2006	Larsson et al.	N/A	N/A
2008/0271674	12/2007	Rademarcher	N/A	N/A
2008/0309698	12/2007	Nakano et al.	N/A	N/A
2009/0027433	12/2008	Van De Wynckel et al.	N/A	N/A
2009/0029069	12/2008	Edwards	N/A	N/A
2009/0117283	12/2008	Herre	N/A	N/A
2009/0181182	12/2008	Sloan	N/A	N/A
2009/0244216	12/2008	Niimi	N/A	N/A
2010/0132612	12/2009	Achrainer	N/A	N/A
2010/0156970	12/2009	Ikushima	N/A	N/A
2010/0170918	12/2009	Achrainer	N/A	N/A
2010/0225685	12/2009	Kwon et al.	N/A	N/A
2010/0279013	12/2009	Frankenberger et al.	N/A	N/A
2010/0282283	12/2009	Bauer	N/A	N/A
2010/0321448	12/2009	Buestgens et al.	N/A	N/A
2011/0014371	12/2010	Herre et al.	N/A	N/A
2011/0084150	12/2010	Merchant	N/A	N/A
2011/0248046	12/2010	Simion	N/A	N/A
2011/0262622	12/2010	Herre	N/A	N/A
2012/0085842	12/2011	Ciardella	N/A	N/A
2012/0105522	12/2011	Wallsten	N/A	N/A
2012/0114849	12/2011	Melcher	N/A	N/A
2012/0162331	12/2011	Kataoka	N/A	N/A
2012/0186518	12/2011	Herre	N/A	N/A
2012/0219699	12/2011	Pettersson et al.	N/A	N/A
2012/0249679	12/2011	Beier	347/40	B41J 3/543
2012/0282405	12/2011	Herre	N/A	N/A
2013/0201243	12/2012	Yoshida	N/A	N/A
2013/0215203	12/2012	Chen	N/A	N/A
2013/0257984	12/2012	Beier et al.	N/A	N/A
2013/0284833	12/2012	Fritz et al.	N/A	N/A
2014/0076985	12/2013	Pettersson et al.	N/A	N/A
2014/0120457	12/2013	Choi	N/A	N/A
2014/0184683	12/2013	Harjee et al.	N/A	N/A
2014/0242285	12/2013	Pettersson et al.	N/A	N/A
2014/0329001	12/2013	Rouaud et al.	N/A	N/A
2015/0009254	12/2014	Kaiba et al.	N/A	N/A
2015/0042716	12/2014	Beier et al.	N/A	N/A
2015/0086723	12/2014	Bustgens	N/A	N/A
2015/0098028	12/2014	Ohnishi	N/A	N/A
2015/0328654	12/2014	Scwab	N/A	N/A
2015/0375258	12/2014	Fritz et al.	N/A	N/A
2015/0375507	12/2014	Ikushima	N/A	N/A
2016/0001322	12/2015	Fritz et al.	N/A	N/A
2016/0052312	12/2015	Pitz et al.	N/A	N/A
2016/0074822	12/2015	Han	N/A	N/A
2016/0288552	12/2015	Ikushima	N/A	N/A

2016/0306364	12/2015	Ikushima et al.	N/A	N/A
2017/0087837	12/2016	Stefani et al.	N/A	N/A
2017/0106393	12/2016	Hamspon et al.	N/A	N/A
2017/0128962	12/2016	Kashiyama	N/A	N/A
2017/0136481	12/2016	Fritz et al.	N/A	N/A
2017/0252765	12/2016	Medard et al.	N/A	N/A
2017/0267002	12/2016	Pitz et al.	N/A	N/A
2017/0299088	12/2016	Rau	N/A	N/A
2017/0361346	12/2016	Lahidjanian et al.	N/A	N/A
2018/0022105	12/2017	Nakamura et al.	N/A	N/A
2018/0056670	12/2017	Kerr	N/A	N/A
2018/0093491	12/2017	Murayama et al.	N/A	N/A
2018/0178505	12/2017	Stefani et al.	N/A	N/A
2018/0222186	12/2017	Stefani et al.	N/A	N/A
2018/0250955	12/2017	Herre	N/A	N/A
2019/0091712	12/2018	Medard et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2287527	12/1997	CN	N/A
1331661	12/2001	CN	N/A
1411914	12/2002	CN	N/A
1438942	12/2002	CN	N/A
1512919	12/2003	CN	N/A
1176815	12/2003	CN	N/A
1668386	12/2004	CN	N/A
1761530	12/2005	CN	N/A
101264698	12/2007	CN	N/A
101309755	12/2007	CN	N/A
101657264	12/2009	CN	N/A
101784348	12/2009	CN	N/A
102177002	12/2010	CN	N/A
102198434	12/2010	CN	N/A
102971080	12/2012	CN	N/A
103153483	12/2012	CN	N/A
103909743	12/2013	CN	N/A
104613205	12/2014	CN	N/A
104994966	12/2014	CN	N/A
105358259	12/2015	CN	N/A
205042649	12/2015	CN	N/A
106414081	12/2016	CN	N/A
1284250	12/1967	DE	N/A
7710895	12/1976	DE	N/A
3045401	12/1981	DE	N/A
3221327	12/1982	DE	N/A
3225554	12/1983	DE	N/A
3634747	12/1986	DE	N/A
3804092	12/1987	DE	N/A
4013322	12/1990	DE	N/A
4115111	12/1990	DE	N/A

4138491	12/1992	DE	N/A
9405600	12/1993	DE	N/A
68924202	12/1995	DE	N/A
19606716	12/1996	DE	N/A
19630290	12/1997	DE	N/A
19731829	12/1998	DE	N/A
19743804	12/1998	DE	N/A
9422327	12/1999	DE	N/A
19852079	12/1999	DE	N/A
19936790	12/2000	DE	N/A
20017629	12/2000	DE	N/A
10048749	12/2001	DE	N/A
69429354	12/2001	DE	N/A
69622407	12/2002	DE	N/A
10307719	12/2002	DE	N/A
60001898	12/2003	DE	N/A
102004021223	12/2003	DE	N/A
10331206	12/2004	DE	N/A
102004034270	12/2005	DE	N/A
102004044655	12/2005	DE	N/A
102004049471	12/2005	DE	N/A
60212523	12/2006	DE	N/A
69836128	12/2006	DE	N/A
60125369	12/2006	DE	N/A
102006021623	12/2006	DE	N/A
102006056051	12/2007	DE	N/A
102007018877	12/2007	DE	N/A
60132100	12/2007	DE	N/A
102007037663	12/2008	DE	N/A
10 2008 018 881	12/2008	DE	N/A
102008053178	12/2009	DE	N/A
102009029946	12/2009	DE	N/A
102009038462	12/2010	DE	N/A
102010004496	12/2010	DE	N/A
102010019612	12/2010	DE	N/A
102012006371	12/2011	DE	N/A
102012005087	12/2011	DE	N/A
102012005650	12/2012	DE	N/A
102012212469	12/2013	DE	N/A
102012109123	12/2013	DE	N/A
202013101134	12/2013	DE	N/A
102013002412	12/2013	DE	N/A
102013011107	12/2013	DE	N/A
102013205171	12/2013	DE	N/A
102014006991	12/2013	DE	N/A
102014007523	12/2014	DE	N/A
102014008183	12/2014	DE	N/A
10 2014 217 892	12/2015	DE	N/A
102014012705	12/2015	DE	N/A
102014013158	12/2015	DE	N/A

10 2016 014 952	12/2017	DE	N/A
0138322	12/1984	EP	N/A
0297309	12/1988	EP	N/A
0665106	12/1994	EP	N/A
1120258	12/2000	EP	N/A
1270086	12/2002	EP	N/A
1764226	12/2006	EP	N/A
1852733	12/2006	EP	N/A
1884365	12/2007	EP	N/A
1946846	12/2007	EP	N/A
2002898	12/2007	EP	N/A
2133154	12/2008	EP	N/A
2151282	12/2009	EP	N/A
2196267	12/2009	EP	N/A
2380744	12/2010	EP	N/A
2433716	12/2011	EP	N/A
2468512	12/2011	EP	N/A
2641661	12/2012	EP	N/A
2644392	12/2012	EP	N/A
2777938	12/2013	EP	N/A
2799150	12/2013	EP	N/A
2842753	12/2014	EP	N/A
3002128	12/2015	EP	N/A
3156138	12/2016	EP	N/A
3213823	12/2016	EP	N/A
3257590	12/2016	EP	N/A
3272669	12/2017	EP	N/A
3068626	12/2018	EP	N/A
3010918	12/2014	FR	N/A
2200433	12/1987	GB	N/A
2367771	12/2001	GB	N/A
2507069	12/2013	GB	N/A
S5722070	12/1981	JP	N/A
S62116442	12/1986	JP	N/A
H04-106669	12/1991	JP	N/A
H0798171	12/1994	JP	N/A
H09192583	12/1996	JP	N/A
2011206958	12/1999	JP	N/A
2000317354	12/1999	JP	N/A
2001129456	12/2000	JP	N/A
2001157863	12/2000	JP	N/A
2001239652	12/2000	JP	N/A
2001300404	12/2000	JP	N/A
2005501745	12/2001	JP	N/A
2002361863	12/2001	JP	N/A
2003506210	12/2002	JP	N/A
2003136030	12/2002	JP	N/A
2003164780	12/2002	JP	N/A
2004142382	12/2003	JP	N/A
2004528956	12/2003	JP	N/A

2004337710	12/2003	JP	N/A
2000158670	12/2004	JP	N/A
2005526234	12/2004	JP	N/A
2007021760	12/2006	JP	N/A
2007152666	12/2006	JP	N/A
2007520340	12/2006	JP	N/A
2007245633	12/2006	JP	N/A
2007289848	12/2006	JP	N/A
2008110332	12/2007	JP	N/A
2009006324	12/2008	JP	N/A
2010528852	12/2009	JP	N/A
2010531213	12/2009	JP	N/A
2010531729	12/2009	JP	N/A
2010241003	12/2009	JP	N/A
2012011310	12/2011	JP	N/A
2012506305	12/2011	JP	N/A
2012135925	12/2011	JP	N/A
2012206116	12/2011	JP	N/A
2012228643	12/2011	JP	N/A
2012228660	12/2011	JP	N/A
2013067179	12/2012	JP	N/A
2013530816	12/2012	JP	N/A
2013188706	12/2012	JP	N/A
2014019140	12/2013	JP	N/A
2014050832	12/2013	JP	N/A
2014111307	12/2013	JP	N/A
2015-009222	12/2014	JP	N/A
2015027636	12/2014	JP	N/A
2015096322	12/2014	JP	N/A
2015520011	12/2014	JP	N/A
2015193129	12/2014	JP	N/A
2015535735	12/2014	JP	N/A
2016507372	12/2015	JP	N/A
2016526910	12/2015	JP	N/A
2016175077	12/2015	JP	N/A
2016175662	12/2015	JP	N/A
2018012065	12/2017	JP	N/A
2020513311	12/2019	JP	N/A
2020513314	12/2019	JP	N/A
8601775	12/1985	WO	N/A
9856585	12/1997	WO	N/A
02098576	12/2001	WO	N/A
2003021519	12/2002	WO	N/A
2003062129	12/2002	WO	N/A
2004048112	12/2003	WO	N/A
2004085738	12/2003	WO	N/A
2005016556	12/2004	WO	N/A
2005075170	12/2004	WO	N/A
2006022217	12/2005	WO	N/A
2007121905	12/2006	WO	N/A

2009019036	12/2008	WO	N/A
2010046064	12/2009	WO	N/A
2010146473	12/2009	WO	N/A
2011044491	12/2010	WO	N/A
2011128439	12/2010	WO	N/A
2011138048	12/2010	WO	N/A
2013121565	12/2012	WO	N/A
2014121916	12/2013	WO	N/A
2014121927	12/2013	WO	N/A
2015071270	12/2014	WO	N/A
2015096322	12/2014	WO	N/A
2015186014	12/2014	WO	N/A
2016-087016	12/2015	WO	N/A
2016142510	12/2015	WO	N/A
2016145000	12/2015	WO	N/A
2017006245	12/2016	WO	N/A
2017006246	12/2016	WO	N/A
2018102846	12/2017	WO	N/A
2018108565	12/2017	WO	N/A

OTHER PUBLICATIONS

USPTO Final Office Action mailed Mar. 19, 2024 in related U.S. Appl. No. 16/468,699 (24 pages). cited by applicant

Final Office Action mailed Jun. 11, 2021 for U.S. Appl. No. 16/468,701 (64 pages). cited by applicant

Chinese Office Action for Application No. CN20178007017.9 mailed on Aug. 31, 2020 (8 pages; with English translation). cited by applicant

Non Final Office Action for USPA No. U.S. Appl. No. 16/468,697 mailed Oct. 22, 2020 (78 pages). cited by applicant

Non Final Office Action for USPA No. 16468696 mailed Nov. 2, 2020 (58 pages). cited by applicant

Non Final Office Action for USPA No. 16468689 mailed Oct. 15, 2020 (77 pages). cited by applicant

Chinese Office Action for CN201780077476.7 mailed Sep. 23, 2020 (12 pages; English translation not available). cited by applicant

Non Final Office Action for USPA No. U.S. Appl. No. 16/468,700 mailed Dec. 1, 2020 (73 pages). cited by applicant

Final Office Action mailed Mar. 19, 2021 for U.S. Appl. No. 16/468,696 (45 pages). cited by applicant

Non-Final Office Action mailed Nov. 23, 2021 for U.S. Appl. No. 16/468,694 (25 pages). cited by applicant

Non-Final Office Action for related U.S. Appl. No. 16/468,699 mailed Mar. 9, 2022 (180 pages). cited by applicant

JPO Decision to Grant in related application No. JP2019-532030 mailed Feb. 1, 2022 (6 pages; English machine translation provided). cited by applicant

Non-Final Office Action mailed Dec. 24, 2021 for related U.S. Appl. No. 16/468,693 (19 pages). cited by applicant

Non-Final Office Action mailed Jan. 6, 2022 for related U.S. Appl. No. 16/468,701 (36 pages). cited by applicant

JPO Decision to Grant in related application JP2019-532012 mailed Jan. 25, 2022 (6 pages; with

English machine translation). cited by applicant
Chinese Office Action in related application No. CN201780077045.0 mailed Jan. 29, 2022 (17 pages; English machine translation provided). cited by applicant
Final Office Action mailed Aug. 17, 2022 for USPA No. 16468699 (26 pages). cited by applicant
EPO Notification of Objection mailed May 18, 2022 for Patent No. EP3718643, related to related application no. USPA No. 16468693 (55 pages; with English machine translation). cited by applicant
Huo Lijiang, "Packaging Printing Technology", 1st edition, pp. 321-323, Printing Industry Press, Sep. 30, 2011 (10 pages; with English machine translation). cited by applicant
Chinese Patent Office - Office Action for Application No. CN202211512023.1 mailed Aug. 16, 2023 (26 pages; with English machine translation). cited by applicant
USPTO Non-Final Office Action mailed Jun. 23, 2023 for related application No. U.S. Appl. No. 17/740,537 (107 pages). cited by applicant
USPTO Non-Final Office Action in related application No. U.S. Appl. No. 17/532,411 mailed Jan. 13, 2023 (127 pages). cited by applicant
USPTO Non-Final Office Action mailed Dec. 13, 2022 in related application on. U.S. Appl. No. 16/468,699 (21 pages). cited by applicant
Ghasem, G. et al; "Chapter 2 Background on Sprays and Their Production", Industrial Sprays and Atomization: Design, Analysis and Applications, Jan. 1, 2002, Springer, London, pp. 7-33, XP009195118, ISBN: 978-1-4471-3816-7. cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081141 mailed Feb. 26, 2018 (17 pages; with English translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081114 mailed May 15, 2018 (33 pages; with English translation). cited by applicant
Anonymous: "Roboterkalibrierung—Wikipedia", Nov. 7, 2016, XP055471615, Gefunden im Internet: URL: <https://de.wikipedia.org/w/index.php?title=Roboterkalibrierung&oldid=159460756> [gefunden am Apr. 30, 2018] das ganze dOCUMENT (8 pages; with English translation). cited by applicant
Beyer, Lukas: "Genauigkeitssteigerung von Industrierobotern", Forschungsberichte Aus Dem Laboratorium Fertigungstechnik/Helmut-Schmidt-Universitat, Universitat Der Bundeswehr Hamburg, Dec. 31, 2005, Seiten 1-4, XP009505118; ISSN: 1860-2886; ISBN: 978-3-8322-3681-6 (13 pages; with English machine translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081108 mailed Feb. 28, 2018 (with English translation; 18 pages). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081099 mailed Feb. 26, 2018 (21 pages; with English translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081102 mailed Mar. 14, 2018 (16 pages; with English translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081105 mailed Feb. 26, 2018 (19 pages; with English translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081152 mailed May 15, 2018 (25 pages; with English translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081098 mailed May 14, 2018 (26 pages; with English translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081101 mailed Feb. 28, 2018 (14 pages; with English translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081121 mailed Feb. 26, 2018 (20 pages; with English translation). cited by applicant
International Search Report and Written Opinion for PCT/EP2017/081117 mailed Mar. 12, 2018 (27 pages; with English translation). cited by applicant

International Search Report and Written Opinion for PCT/EP2017/081123 mailed on Feb. 26, 2018 (20 pages; with English translation). cited by applicant

JPO Submission for JP2019-531096; submitted Dec. 21, 2020 (32 pages; with English translation). cited by applicant

JPO Submission for JP2019-531957; submitted Dec. 21, 2020 (21 pages; with English translation). cited by applicant

Japanese Patent Office Notice of Reasons of Refusal for Application No. JP 2019-531967 mailed Jun. 8, 2021 (8 pages; with English machine translation). cited by applicant

Notification of Reasons for Refusal for Application No. JP2019-532012 mailed Jun. 22, 2021 (6 pages; with English machine translation). cited by applicant

Notification of Reasons for Refusal for Application No. JP2019-527330 mailed Jun. 22, 2021 (10 pages; with English machine translation). cited by applicant

Chinese Office Action mailed Jun. 2, 2021 for Application No. CN201780077017.9 (17 pages; with English machine translation). cited by applicant

Japanese Notification of Reasons for Rejection mailed Jun. 1, 2021 for Application No. JP2019-531944 (14 pages; with English machine translation). cited by applicant

Japanese Notification of Reasons for Rejection mailed Jun. 8, 2021 for Application No. JP2019-531957 (13 pages; with English machine translation). cited by applicant

Supplemental Notice of Allowability mailed Jul. 8, 2021 for U.S. Appl. No. 16/468,696 (11 pages). cited by applicant

Liptak, Bela. (2006). Instrument Engineers' Handbook (4th Edition)—Process Control and Optimization, vol. 2—2.1.3.5 Process Time Constant, (pp. 99-102). Taylor & Francis. Retrieved from <https://app.knovel.com/hotlink/pdf/id:kt00CC7HL1/instrument-engineers/process-time-constant> (Year: 2006). cited by applicant

JPO Office Action for Application No. JP2019-531097 mailed Jun. 29, 2021 (10 pages; with English machine translation). cited by applicant

JPO Office Action for Application No. 2019-531096 mailed Jul. 6, 2021 (9 pages; with English machine translation). cited by applicant

JPO Office Action for Application No. 2019-531098 mailed Jul. 6, 2021 (5 pages; English translation only). cited by applicant

JPO Office Action for Application No. 2019-531459 mailed Jul. 6, 2021 (8 pages; with English machine translation). cited by applicant

JPO Office Action mailed Jul. 13, 2021 for Application No. JP2019-532024 (12 pages; with English machine translation). cited by applicant

Non-Final Office Action mailed Aug. 27, 2021 for USPA No. U.S. Appl. No. 16/468,695 (149 pages). cited by applicant

JPO Notification of Reasons for Rejection for Application No. JP2019-532030 mailed May 18, 2021 (6 pages; with English translation). cited by applicant

CIPO Office Action for Application No. CN201780077474.8 mailed Apr. 26, 2021 (17 pages; with English translation). cited by applicant

Notice of Allowance mailed in USPA No. 16468689 on Jun. 2, 2021 (38 pages). cited by applicant

Non-Final Office Action mailed Feb. 5, 2021 for U.S. Appl. No. 16/468,701 (80 pages). cited by applicant

Non-Final Office Action mailed Feb. 18, 2021 for U.S. Appl. No. 16/468,692 (97 pages). cited by applicant

Final Office Action mailed May 13, 2021 for USPA No. U.S. Appl. No. 16/468,691 (70 pages). cited by applicant

JPO Decision to Grant mailed Oct. 5, 2021 for Application No. JP2019-532113 (7 pages; with English machine translation). cited by applicant

Final Office Action mailed Oct. 7, 2021 for U.S. Appl. No. 16/468,693 (58 pages). cited by

applicant

Non-Final Office Action for U.S. Appl. No. 16/468,691 mailed Jan. 7, 2021 (79 pages). cited by applicant

China National Intellectual Property Administration Office Action and Search Report for CN Application No. 201780077018.3 mailed Aug. 27, 2020 (11 pages; Search Report in English). cited by applicant

Chinese Office Action and Search Report for CN201780077603.3 mailed Oct. 12, 2020 (15 pages; English translation not available). cited by applicant

European Search Report for EP20170638.9 mailed Sep. 14, 2020 (4 pages—English translation not available). cited by applicant

European Search Report for EP20170021.8 mailed Sep. 8, 2020 (11 pages—English translation not available). cited by applicant

European Search Report for EP20170025.9 mailed Sep. 9, 2020 (4 pages—English translation not available). cited by applicant

European Search Report for EP20170016.8 mailed Sep. 7, 2020 (4 pages—English translation not available). cited by applicant

EPO Examination Report for Application No. 201702818.1 mailed Dec. 18, 2020 (with English machine translation; 6 pages). cited by applicant

EPO Official Notification of Opposition for Application No. 17821803.8 mailed Feb. 10, 2021 (64 pages; with English machine translation). cited by applicant

Non-Final Office Action mailed on Apr. 28, 2021 for U.S. Appl. No. 16/468,693 (109 pages). cited by applicant

Final Office Action mailed on Apr. 19, 2021 for U.S. Appl. No. 16/468,700 (62 pages). cited by applicant

Chinese Office Action for application No. 201780077045.0 mailed Apr. 29, 2025 (20 pages; English translation unavailable). cited by applicant

Primary Examiner: Leong; Nathan T

Attorney, Agent or Firm: Taft Stettinius & Hollister LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional of, and claims priority to, U.S. patent application Ser. No. 17/965,062, filed on Oct. 13, 2022, which application is a divisional of, and claims priority to, U.S. patent application Ser. No. 16/468,691, filed on Jun. 12, 2019 (issued as U.S. Pat. No. 11,504,735 on Nov. 22, 2022), which application is a national stage of, and claims priority to, Patent Cooperation Treaty Application No. PCT/EP2017/081108, filed on Dec. 1, 2017, which application claims priority to German Application No. DE 10 2016 014 955.8, filed on Dec. 14, 2016, which applications are hereby incorporated herein by reference in their entireties.

BACKGROUND

(1) The disclosure concerns a coating device for coating components with a coating agent, in particular for painting vehicle body components with a paint. Furthermore, the disclosure concerns a corresponding operating method.

(2) For the serial painting of car body components, rotary atomizers are usually used as application devices, which however have the disadvantage of a limited application efficiency, i.e. only a part of the applied paint is deposited on the components to be coated, while the rest of the applied paint

must be disposed of as so-called overspray.

(3) A newer development line, on the other hand, provides for so-called printheads as application devices, as known for example from DE 10 2013 002 412 A1, U.S. Pat. No. 9,108,424 B2 and DE 10 2010 019 612 A1. In contrast to the known rotary atomizers, such printheads do not emit a spray of the paint to be applied, but a narrowly confined jet of paint, which is almost completely deposited on the component to be painted, so that almost no overspray occurs.

(4) However, the known printheads are not designed for a color change and are therefore only suitable to a very limited extent for the series painting of motor vehicle body components in a paint shop.

(5) In addition, the coating in the printhead can become dry or dry out during coating breaks, which in the worst case can lead to a loss of function of the printhead.

(6) Furthermore, regarding the general technical background of the disclosure, reference is made to DE 601 25 369 T2, DE 10 2010 019 612 A1, WO 2005/016556 A1, DE 698 36 128 T2, DE 10 2004 044 655 A1, DE 10 2013 205 171 A1, DE 600 01 898 T2, EP 1 946 846 A2, DE 10 2013 002 412 A1 and DE 689 24 202 T2.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 a schematic, highly simplified representation of a coating device according to the disclosure with a painting robot with a printhead and a wet deposit device for deposition of the disassembled printhead,

(2) FIG. 2A is a modification of FIG. 1, in which a cleaning device is additionally provided to clean the deposited printhead from the outside and material circulation through the deposited printhead is possible,

(3) FIG. 2B a flowchart to illustrate a color change process with a storage of the old printhead and a pick-up of a new printhead,

(4) FIG. 3A a modification of FIG. 1 according to the second disclosure variant with two printheads on the coating robot,

(5) FIG. 3B a highly simplified fluid-technical equivalent circuit diagram of the coating device according to FIG. 3A with an A/B color changer,

(6) FIG. 3C a flow chart to illustrate the A/B operation of the coating device according to FIGS. 3A and 3B,

(7) FIG. 3D a modification of the fluid-technical equivalent circuit diagram according to FIG. 3B with two separate color changers for the two printheads, and

(8) FIG. 4A-4D various illustrations to explain the various flushing options.

DETAILED DESCRIPTION

(9) The disclosure includes two examples, according to which the printhead is replaceably mounted on the coating robot or several printheads are mounted on the coating robot, each of which applies only one specific coating agent.

(10) The coating device in accordance with the disclosure is preferably used to paint vehicle body components with a paint and is designed accordingly.

(11) However, the disclosure also offers the alternative of coating other types of components.

(12) Furthermore, the applied coating does not necessarily have to be paint (e.g. water-based paint, solvent-based paint, clear coat, basecoat, etc.). Rather, the disclosure-based coating device can also be designed for the application of other coating agents, such as adhesives, insulating materials, sealants, primers, etc., to name just a few examples.

(13) In accordance with the state of the art, the coating device according to the disclosure initially has at least one multi-axis coating robot, which preferably has serial robot kinematics, at least six

or seven movable robot axes and one multi-axis robot hand axis. Such coating robots are known from the state of the art and therefore do not need to be described in detail.

(14) In addition, in accordance with the state of the art, the coating device according to the disclosure has at least one first printhead to apply the coating agent to the surface of the component to be coated. The printhead has at least one nozzle to deliver a coating agent jet of the coating agent onto the surface of the component to be coated. The term “printhead” used in the disclosure must therefore be distinguished from the atomizers usually used as application devices, which do not emit a spatially limited jet of coating agent but a spray of the coating agent. Otherwise, the term “printhead” used in the context of the disclosure is to be understood generally, so that different construction principles of known printheads can be used. Preferably, however, the printhead is similar to the printheads described in DE 10 2013 002 412 A1, U.S. Pat. No. 9,108,424 B2 and DE 10 2010 019 612 A1.

(15) It should also be noted that the printhead has at least one printhead valve to control the release of coating agent through the nozzle. For example, this printhead valve may have an electrically actuated solenoid actuator to adjust the valve position, but the design and operation of such a printhead valve are state of the art and therefore do not need to be described in more detail.

(16) The printhead is mounted on the coating robot and is program-controlled by the coating robot over the surface of the component to be coated, which is also known from the state of the art.

(17) In the first example of the disclosure, the first printhead is mounted on the coating robot and can be exchanged for a second printhead during a color change, so that the printheads themselves do not have to undergo a color change, but can simply be exchanged by another printhead.

(18) In the second example at least a second printhead is mounted on the coating robot in addition to the first printhead, whereby the two printheads each apply a specific coating agent in order to enable a color change without changing the printhead. The first printhead can then apply black paint, for example, while the second printhead can apply silver paint, for example.

(19) In the first example described briefly above, a deposit device is preferably provided to deposit the first printhead disassembled by the coating robot in the deposit device and to pick up the second printhead from the deposit device instead of the deposited first printhead.

(20) The deposit device is preferably arranged stationary in the coating device and can be reached by the coating robot, so that the coating robot can deposit the currently mounted printhead in the deposit device and pick up the other printhead previously located in the deposit device from the deposit device. In the case of a color change, the coating robot places the mounted printhead in the deposit device and picks up a new printhead from the deposit device so that the new color can then be applied with this new printhead.

(21) The deposit device may be a wet deposit device or wet holding device in which the nozzles of the deposited printhead are kept moist to prevent the liquid coating from drying during storage.

(22) The wet deposit device can also be realized in connection with a permanently mounted printhead, i.e. with a printhead that is not exchangeably mounted on the coating robot. The coating robot can then place the printhead in the wet deposit device during coating breaks (e.g. in shift pauses or during maintenance pauses) so that the coating in the printhead does not dry up.

(23) In an example of such a wet deposit device, a liquid bath can be provided which is filled with a liquid (e.g. rinsing agent, thinner) and into which the printhead is at least partially immersed during deposition, whereby the liquid prevents the liquid coating agent from drying on the outside of the printhead during deposition. When immersing the printhead in the liquid bath, at least the printhead nozzles should be immersed in the liquid bath, as the nozzles have a very small nozzle cross section and can therefore clog relatively easily.

(24) In another example, the wet deposit device allows fluid circulation through the deposited printhead. For this purpose, the printhead has an inlet and an outlet in addition to the nozzles so that a liquid (e.g. coating agent, rinsing agent) can circulate through the printhead. The wet deposit device then has a docking device that allows docking with circulation ports to the inlet and outlet of

the deposited printhead so that the Wet Dispenser then circulates a liquid (e.g., coating or rinsing agent) through the deposited printhead. When the printhead is placed by the coating robot in the wet deposit device, the printhead is separated from the coating robot and the printhead is connected to the docking device in the wet deposit device.

(25) The fluid circulation through the deposited printhead can be done with the previously used paint, so that the printhead is then ready to be picked up again by the coating robot for application with the same paint.

(26) Alternatively, it is also possible to clean the deposited printhead with a rinsing agent and then pre-fill (i.e. fill) it with a different paint so that the printhead is ready for application with the new paint.

(27) In the second example at least two printheads are mounted on the coating robot, which can be operated alternately. This also enables a so-called A/B operation, in which printhead A applies coating agent, while the other printhead B is rinsed with a rinsing agent and, if necessary, pre-filled with a different colored coating agent. Then coating agent is applied with the printhead B, while the printhead A is rinsed with rinsing agent and, if necessary, pre-filled with a coating agent of a different color. This A/B operation enables an uninterrupted coating during a color change, since you can switch from printhead A to printhead B or vice versa without a pause. The time required for rinsing and pre-filling the printhead does not interrupt the coating operation.

(28) Furthermore, with the second example it is possible that the at least two printheads on the coating robot can each be supplied with coating agent by a separate coating agent circuit. In this example and in contrast to the A/B operation described above, no separate A/B valve or corresponding valve arrangement is required. However, the two coating circuits must then be routed through the coating robot to the two printheads.

(29) It has already been mentioned briefly above that the second example has at least two printheads mounted on the coating robot, which can be operated selectively. Here one coating agent flows through each printhead. The number of printheads mounted on the coating robot is therefore preferably greater than 2, and smaller than 6. The individual printheads are then preferably connected to a separate coating agent supply line, so that the coating agent supply lines are only passed through by the associated coating agent.

(30) With this second example there is also the possibility that some printheads are intended for frequently used coating agents ("high runner") and then only the associated frequently used coating agent flows through them without a color change being provided for these printheads. Another part of the printheads or even only one printhead is intended for the application of rarely used coating agents ("low runner") and allows a color change between the different rarely used coating agents. This allows the frequently used coating agents to avoid color change at all with corresponding losses. When applying the rarely used coating agents, a color change with corresponding losses is necessary, but this is of little importance, since the rare coating agents associated with color change losses are only rarely used.

(31) In addition, the coating device according to the disclosure can have a time control to rinse the printheads time-controlled. For example, the time control can trigger a rinsing process after a specified rinse interval, for example after a rinse interval of 1 h, 2 h, or 4 h. In addition, there is the possibility that the time control triggers a rinsing process after a specified downtime of a conveyor conveying the components to be coated has elapsed, for example after a downtime of more than 10 minutes, 20 minutes, 30 minutes or 1 hour. These two variants of a time control can be used alone or in combination with each other.

(32) In addition, the coating device according to the disclosure preferably includes a cleaning device to clean the mounted or dismounted printheads. State-of-the-art atomizer cleaning devices are known, into which the coating robot introduces the mounted rotary atomizer, whereby the rotary atomizer is then sprayed inside the cleaning device with a cleaning liquid (e.g. thinner) in order to clean the rotary atomizer from the outside. The cleaning device according to the disclosure

can be constructed similarly, whereby the cleaning device is naturally adapted to the different outer contour of the printhead and to missing functions like e.g. shaping air.

(33) The cleaning device may be located separately from the coating robot, but the cleaning device is located within the working area of the coating robot so that the coating robot can insert the printhead into the cleaning device.

(34) In an example of the disclosure, the cleaning device and the deposit device form a uniform component. This means that the deposit device is not only used for depositing, picking up and temporarily storing the printheads, but also for cleaning the printheads in the deposited state and/or in the mounted state on the coating robot.

(35) The disclosure preferably enables a very short color change time, which is preferably shorter than 1 h, 20 min, 10 min, 1 min, 30 s, 10 s or even shorter than 5 s.

(36) In the case of stop-and-go conveying of the motor vehicle body components through the paint shop, the color change time is preferably shorter than the change time between two successive motor vehicle body components, i.e. shorter than the conveying time of the motor vehicle body components between two positions.

(37) In the case of continuous line tracking conveying of the motor vehicle body components through the paint shop, however, the color change time is preferably shorter than the time interval between two successive motor vehicle body components. In A/B mode, the color change time can be extended to the duration of a car body cycle.

(38) Another advantage is the low loss of coating agent during a color change, whereby the loss of coating agent is preferably less than 5 l, 2 l, 200 ml, 20 ml, 10 ml, 5 ml or even less than 2 ml.

(39) In addition, a color change preferably results in a very low rinsing agent requirement, which is preferably less than 300 ml, 250 ml, 200 ml, 100 ml, 50 ml, 20 ml or even less than 10 ml.

(40) In general it should be noted that the printheads preferably emit a narrowly limited jet of coating agent as opposed to a spray mist as is the case with conventional atomizers (e.g. rotary atomizers).

(41) In a variant of the disclosure, the printheads each emit a droplet jet consisting of several droplets separated from each other in the longitudinal direction of the jet, as opposed to a jet of coating agent being continuous in the longitudinal direction of the jet.

(42) Alternatively, it is also possible for the printheads to emit a continuous jet of coating agent in the longitudinal direction of the jet, as opposed to the droplet jet mentioned above.

(43) In the case of the coating device in accordance with the disclosure, the coating agent pressure is preferably controlled with a very small fluctuation range, whereby the fluctuation range of the coating agent pressure is preferably smaller than 500 mbar, 200 mbar, 100 mbar or 50 mbar.

(44) It should also be mentioned that the printheads preferably have a very high application efficiency of at least 80%, 90%, 95% or 99%, so that substantially all of the applied coating agent is completely deposited on the component without overspray. The printheads are therefore essentially overspray-free within the scope of the disclosure.

(45) In addition, it should be noted that the printheads preferably have a sufficiently high surface coating performance to paint vehicle body components, for example. The surface coating performance is therefore preferably at least 0.5 m.sup.2/min, 1 m.sup.2/min, 2 m.sup.2/min or even 3 m.sup.2/min.

(46) It should also be noted that the volume flow of the applied coating agent and thus the exit velocity of the coating agent are preferably adjusted so that the coating agent does not bounce off the component when it hits it. Furthermore, the impact velocity of the coating agent jet should be designed in such a way that the coating agent does not penetrate the underlying paint layer, but the coating agent lies on it (layers). The exit velocity of the coating agent is therefore preferably in the range of 5 m/s to 30 m/s. The coating agent is applied to the substrate at a speed of 5 m/s to 30 m/s. The coating agent is then applied to the substrate. The application distance is preferably in the range of 4 mm to 200 mm.

(47) Finally, it should be mentioned that the control of the at least one printhead valve is preferably done by an electrically controllable actuator, for example by a magnetic actuator or a piezo actuator, whereby such actuators are known from the state of the art and therefore do not need to be described in detail.

(48) It should also be mentioned that the disclosure does not only claim protection for the coating device described above. Rather, the disclosure also claims protection for a corresponding coating process, whereby most of the method steps already result from the above description, so that a separate description of the individual method steps can be dispensed with.

(49) In addition, however, it should be mentioned that during a color change from a solvent-based paint to a water-based paint, it is preferable to first use a solvent-based rinsing agent, then optionally a release agent (e.g. alcohol) and then a water-based rinsing agent. If the change from a water-based to a solvent-based coating is reversed, this sequence must of course be reversed.

(50) The disclosure also offers the possibility of sequential rinsing with different rinsing agents, for example with an increasing content of organic solvents.

(51) It is also possible to use a universal rinsing agent for rinsing, which is used both for rinsing out water-based paint and for rinsing out solvent-based paint.

(52) In addition, rinsing can be assisted by introducing pulsed air and/or an aerosol of compressed air and rinsing agent into the printhead and/or cleaning device.

(53) It should also be mentioned that the rinsing agent can also be a VOC-free (VOC: Volatile Organic Compound).

(54) In addition, it is advantageous if the residual liquids (e.g. old coating agent, rinsing agent residues, etc.) are collected and disposed of during a rinsing process in order to avoid contamination of the coating device.

(55) The above applies both to flushing the media-carrying areas inside the printhead or printhead supply lines and to cleaning or flushing the printhead in the cleaning device.

(56) In addition, it is advantageous if the printhead is prefilled with the new coating agent after a rinsing process so that it is immediately available for application. When this is done, it is preferable to squeeze a defined amount of the new coating agent out of the printhead nozzles, whereby the squeezed out amount of coating agent is then preferably collected and disposed of. In practice, the pressure is probably applied only before application.

(57) It has already been mentioned above that the printhead valve can be controlled by a solenoid actuator. Such solenoid actuators usually have an electric coil wound onto a coil tube, with an armature movably arranged in the coil tube and displaced depending on the current applied to the coil to close or open the nozzle. Here there is the possibility that coating agent can enter the coil tube. The coil tube of the magnetic actuator is therefore also preferably flushed during a rinsing process. Here it is possible that the rinsing agent is led through the coil tube through a separate rinsing connection in the direction of the nozzle. Conversely, it is also possible for the rinsing agent to flow in the opposite direction through the coil tube, i.e. to a separate flushing outlet. In addition, these two types of flushing can also be combined alternately.

(58) Furthermore, the printhead can be flushed with rinsing agent through the return, i.e. the rinsing agent is introduced into the inlet of the printhead and then enters the return through the outlet of the printhead, whereby the nozzles are then preferably closed.

(59) In addition, it is also possible for the rinsing agent to be introduced into the printhead through the inlet and then to exit through the nozzles when the printhead valves are open in order to flush the nozzle channels.

(60) Furthermore, the disclosure also offers the possibility that the rinsing agent may remain at least partially as a barrier medium in the coil tube after a color change in order to prevent coating agent from entering the coil tube at all.

(61) The second example involves designing the printhead in such a way that a color change is possible during coating operation. This is achieved by the fact that the printhead can be rinsed with

a rinsing agent during a color change in order to rinse out coating agent residues from the printhead.

(62) In accordance with the state of the art, the printhead according to the disclosure has a coating agent supply in order to supply the coating agent to be applied to the printhead. In addition, the disclosure printhead preferably also has a separate rinsing agent supply to supply a rinsing agent. It should be mentioned here that the coating agent supply is preferably separated from the rinsing agent supply, so that the printhead preferably has separate inlets for the supply of the coating agent on the one hand and for the supply of the rinsing agent on the other hand.

(63) For a few colors, one color hose (coating agent supply) per color could be connected to the applicator (printhead) (Integrated Color Changer technology). Then there is a rinsing agent connection and a pulse air connection in or on the applicator. These are then used for rinsing.

(64) In addition, the printhead according to the disclosure also preferentially has a recirculation system in order to return coating agents and/or rinsing agents, either to a ring line or to disposal. In addition to the separate connections for the supply of the coating agent and the rinsing agent, the printhead according to the disclosure also has a separate connection for returning the coating agent or the rinsing agent.

(65) The recirculation flow to the recirculation is preferably controlled by a controllable recirculation valve, which can be either a self-actuated recirculation valve or a proportional valve. Such valve types are known from the state of the art and therefore do not need to be described in detail.

(66) In an example of the disclosure, the printhead has several nozzles for dispensing the coating. A control valve is preferably assigned to each individual nozzle in order to control the release of the coating agent through the respective nozzle. The above mentioned rinsing agent supply then may have branch lines leading to the individual control valves so that all control valves of the pressure head can be flushed simultaneously with the rinsing agent.

(67) The individual branch lines of the rinsing agent supply are preferably designed in such a way that the rinsing agent supplied is distributed evenly over the branch lines to the control valves so that the individual control valves are flushed essentially with the same amount of rinsing agent.

(68) In an example of the disclosure, the printhead has at least one nozzle for dispensing the coating agent and an associated control valve for controlling the dispensing of the coating agent through the nozzle, as explained briefly above. The control valve can have an electric coil, which can be wound onto a coil tube, as in the case of the known design described above. It was already explained at the beginning about the state of the art that coating residues can be deposited in this coil tube, which on the one hand can impair the functionality of the control valve and on the other hand can prevent the color change capability. In the case of the printhead according to the disclosure, the rinsing agent supply line therefore preferably flows into the coil tube in order to flush the inside of the coil tube.

(69) It should be mentioned here that the coil tube—as in the conventional control valve described above—preferably has a circular internal cross-section and contains a coil core. Here it can be advantageous if the coil core has a profile cross-section which does not completely fill the internal cross-section of the coil tube in order to leave space for the rinsing agent between the coil tube and the coil core so that the rinsing agent can flow through in the axial direction. For example, the coil core may have a star-shaped profile cross-section with radially projecting ribs running in the axial direction, so that the flushing medium can flow between the ribs of the coil core in the axial direction.

(70) Alternatively, it is possible for the coil core to have a flushing groove in its circumferential surface that can run axially, in the circumferential direction or spirally, for example.

(71) In addition, axial flushing channels can also be arranged in the coil core.

(72) Another example shows that the profile cross-section of the coil core is grid-shaped and can be flowed through by the rinsing agent.

(73) It should also be mentioned that the coil core is preferably sealed against the coil tube with a seal, in particular with a pressure resistance of more than 2 bar, 4 bar or 6 bar.

(74) It has already been briefly mentioned above that the printhead may have several control valves, all of which can be flushed. The individual control valves usually have one coil tube each, whereby the rinsing agent supply then flows into all coil tubes in order to flush all coil tubes.

(75) It should also be mentioned that the control valve usually has a movable armature, as in the known control valve described at the beginning, which is moved depending on the current supplied to the coil and closes or releases the nozzle depending on its position.

(76) This armature may run coaxially on part of its length in the coil tube and preferably has an axially permeable profile cross-section so that flushing fluid can flow between the armature and the inner wall of the coil tube. For this purpose, the armature preferably has a non-circular profile cross-section which does not completely fill the circular internal cross-section of the coil tube and therefore permits an axial flow of rinsing agent. For example, the profile cross-section of the armature can be star-shaped or cross-shaped.

(77) In an example, the rinsing agent supply flows axially between the armature and the coil core into the coil tube.

(78) In another example the rinsing agent supply opens in the axial direction in the area of the coil core into the coil tube, in particular at the end of the nozzle tube remote from the movable armature.

(79) In another example, the movable armature is arranged in a guide cage permeable to flushing medium, in particular in a slotted cylinder. This offers the advantage that the movable armature can be flushed during a rinsing process, thus avoiding coating deposits on the armature.

(80) In another example, the sliding anchor has a central guide hole with a guide pin projecting into the guide hole. This results in a linear guide, which can also be flushed.

(81) In another example, a flexible diaphragm is provided which separates the control valve from the coating agent supply so that the control valve is protected by the diaphragm against contact with a coating agent. This means that the control valve itself does not have to be flushed at all, as the control valve itself does not come into contact with the respective coating agent at all. Rather, only the smooth surface of the diaphragm on the coating side should be rinsed, which is, however, very easy and efficient since the smooth diaphragm surface hardly forms any starting points for paint deposits.

(82) The printhead according to the disclosure preferably enables a fast color change within a color change time of less than 1 h, 20 min, 10 min, 30 s, 10 s or even less than 5 s.

(83) The aim is to achieve the lowest possible paint change losses, which are preferably smaller than 5 l, 2 l, 200 ml, 20 ml, 10 ml, 5 ml or even smaller than 2 ml with the printhead according to the disclosure.

(84) This also leads advantageously to a very lower rinsing agent consumption with a color change, whereby the rinsing agent consumption is preferably smaller than 10 l, 5 l, 2 l, 200 ml, 100 ml, 50 ml, 20 ml or even smaller than 10 ml.

(85) The disclosure also allows the printhead to be equipped with several separate rinsing agent supplies to supply different rinsing agents, which can be adapted to the respective coating agent, for example.

(86) It should also be mentioned that the printhead with its media-carrying parts is preferably designed in such a way that the media-carrying parts are free of dead space and/or undercuts in order to improve rinsability.

(87) To improve rinsability, it is also possible for the printhead to be coated with an easy-to-clean coating on the surfaces that come into contact with the coating.

(88) Furthermore, it should be noted that the disclosure does not only claim protection for the printhead according to the disclosure as described above as a single component or as a replacement part. Rather, the disclosure also claims protection for a complete coating device with such a

printhead.

(89) In addition, the coating device according to the disclosure preferably also includes a color changer, such as a linear color changer, a rotary color changer, a color changer integrated in the printhead or an A/B color changer. These types of color changers are known from the state of the art and therefore do not need to be described further.

(90) Finally, the disclosure also includes a corresponding operating method for such a printhead, whereby the individual method steps already result from the above description and therefore do not need to be described in more detail.

(91) However, it should be mentioned that the rinsing agent can be a universal rinsing agent that is suitable for both water-based and solvent-based coatings. In addition, the rinsing agent can be a VOC-free (VOC: volatile organic compounds) rinsing agent.

(92) During the rinsing process, the printhead can also be rinsed together with the rinsing agent or alternately with pulsed air.

(93) It is also possible to supply the printhead with an aerosol for rinsing.

(94) The disclosure also offers the possibility of supplying the printhead with different rinsing agents one after the other.

(95) In a variant of the operating method according to the disclosure, a solvent-based paint is first supplied and applied. The printhead is then rinsed with a solvent-based rinsing agent to rinse out residues of the solvent-based paint. An optional release agent can then be added, such as alcohol. In the next step, a water-based paint is added and applied. Finally, the printhead is rinsed with a water-based rinsing agent to rinse out any residues of the water-based paint.

(96) The above description explains a change from a solvent-based coating to a water-based coating. Of course, it is also possible to switch from a water-based to a solvent-based coating, which requires a corresponding change in the sequence of the method steps described above.

(97) After a color change, the printhead is preferably pre-filled with the new coating, i.e. filled. A defined amount of coating is preferably applied through the nozzle of the printhead.

(98) When operating the printhead according to the disclosure, it is also possible that all fluids (coating agent and rinsing agent) released during a rinsing process are collected for disposal.

(99) It is also possible for the outer surface of the nozzle head to be rinsed during the color change in order to remove any coating agent residues adhering to it.

(100) It should also be mentioned that the rinsing agent can be discharged one after the other or alternately into the recirculation system or through the nozzle. In addition, there is also the option of rinsing with a mixture of rinsing agent and pulsed air.

(101) FIG. 1 shows a very simplified, schematic representation of an painting installation according to the disclosure for painting vehicle body components **1**, which are conveyed by a conveyor **2** at right angles to the drawing plane along a painting line through the painting installation, whereby the conveying can take place either in stop-and-go operation or in line tracking operation, which is known per se from the state of the art and therefore does not need to be described in more detail.

(102) Next to the conveyor **2**, a painting robot **3** is simplified, whereby the painting robot **3** has a robot base **4**, a rotatable robot member **5**, a proximal robot arm **6** ("arm **1**"), a distal robot arm **7** ("arm **2**") and a multi-axis robot hand axis **8**, which is known from the state of the art. The robot base **4** can either be fixed here or moved along an unrepresented traversing rail at right angles to the drawing plane.

(103) The rotatable robot member **5** can be rotated about a vertical axis of rotation relative to the robot base **4**.

(104) The proximal robot arm **6**, on the other hand, can be swivelled about a horizontal swivel axis relative to the rotatable robot member **5**.

(105) The distal robot arm **7** can also be swivelled about a horizontal swivel axis relative to the proximal robot arm **6**.

(106) The robot hand axis **8** has a mounting flange on which a printhead **9** is mounted. The

printhead **9** has a large number of nozzles to emit a jet of coating agent onto the surface of the motor vehicle body part **1**.

(107) In addition, the coating device shown has a wet deposit device **10** which is filled with a liquid bath **11**, whereby the liquid may, for example, be a thinner. The liquid bath **11** may also contain a soaked pad or sponge as an alternative to moistening printhead **9**.

(108) During a color change, the coating robot **3** places the printhead **9** in the liquid bath **11** and takes another printhead from the wet deposit device **10**, so that another paint can then be applied with the new printhead (not shown).

(109) In addition, the coating robot **3** positions the printhead **9** in the liquid bath **11** during longer coating pauses to prevent the coating from drying in the nozzles of the printhead **9**.

(110) It should be mentioned that the drawing only shows a simplified schematic representation of this example.

(111) FIG. 2A shows a modification of the example according to FIG. 1, so that in order to avoid repetitions, reference is made to the above description, whereby the same reference signs are used for the corresponding details.

(112) A feature of this example is that the wet deposit device **10** is also designed as a cleaning device and contains cleaning nozzles **12** for spraying the deposited printhead **13** from the outside with a cleaning liquid (e.g. thinner).

(113) Another feature of this example is that the wet deposit device **10** contains a docking device **14** which can establish a flow connection with the deposited printhead **13**. Thus the printhead **13** has an inlet in order to be able to introduce liquid (e.g. paint, rinsing agent) into the printhead **13**. In addition, the printhead **13** has an outlet for discharging the liquid (e.g. paint, rinsing agent) from the printhead **13**. The docking device **14** can now dock to the inlet and outlet of the deposited printhead **13** so that fluid can circulate through the deposited printhead **13** via circulation lines **15**, **16**.

(114) For example, the same paint that was previously applied by the printhead **13** can then flow through the deposited printhead **13** via the circulation lines **15**, **16**.

(115) Alternatively, it is possible to carry out a color change using the docking device **14**. In this case, the deposited printhead **13** is first rinsed with a rinsing agent via the circulation lines **15**, **16** in order to clean the printhead **13**. Then the deposited printhead **13** can be pre-filled with the new paint, so that the printhead **13** is immediately available for application with the new paint.

(116) FIG. 2B shows the operating mode of the coating device according to FIG. 2A in a flowchart.

(117) In a step S1, the coating is first carried out with a printhead A, which is mounted on the painting robot **3**.

(118) If it is determined in a step S2 that a color change is required, the mounted printhead A is then first deposited in a step S3 in the wet deposit device **10**.

(119) In a step S4, a printhead B from the wet deposit device **10** is then picked up by the painting robot **3**.

(120) The deposited printhead A is then cleaned in a step S5 in the wet deposit device **10** and rinsed in one step S6.

(121) In step S7, the deposited printhead A is then pre-filled with a new paint.

(122) Meanwhile, in a step S8, the new printhead B can already be coated with the new paint.

(123) FIGS. 3A-3C are used to explain a variation of the example in FIGS. 2A and 2B so that to avoid repetition, reference is made to the above description, using the same reference signs for corresponding details.

(124) A feature of this embodiment is that two printheads A, B are mounted on the painting robot **3**, which enables a so-called A/B operation by means of an A/B color changer **17**. The A/B color changer **17** is connected via two parallel color lines **18**, **19** to the two printheads A, B, which can return the unneeded paint or rinsing agent residue to a return line RA or RB respectively.

(125) FIG. 3C shows the function of the so-called A/B operation with the coating device according to FIGS. 3A and 3B.

(126) In a first step **S1**, it is initially painted with the printhead A.

(127) If it is then determined in step **S2** that a color change is to take place, step **S3** switches over to the other printhead B.

(128) Then, in step **S4**, printhead A is rinsed and then pre-filled in step **S5** with the desired new paint.

(129) At the same time, a new coating can be applied without interruption with printhead B in step **S6**. Steps **S4** and **S5** therefore do not delay the color change, so that the coating can be applied almost without interruption during a color change.

(130) If in step **S7** it is then determined again that a new color change is to take place, then in step **S8** it is switched to the printhead A again and the printhead B is rinsed at step **S9** and pre-filled in step **S10** with a new paint.

(131) FIG. 3D shows a modification of the fluid equivalent schematic as shown in FIG. 3B, so that to avoid repetitions, reference is made to the above description, using the same reference signs for corresponding details.

(132) A feature of this embodiment is that two separate color changers **17.1**, **17.2** are provided instead of the A/B color changer **17**.

(133) FIGS. 4A-4D show a schematic diagram of a printhead with multiple printhead valves **20** to control coating delivery. The shown printhead has a nozzle plate **21** with numerous nozzles **22** which can be closed or opened by the individual printhead valves **20**.

(134) The individual printhead valves **20** are electrically controlled and operate magnetically. The printhead valves **20** each have a coil **23** wound onto a coil tube **24**, the coil tube **24** having a coil core **25** and a movable armature **26**. The armature **26** can be moved vertically in the drawing and is pressed by a return spring **27** into the closed position shown in the drawings, in which a seal **28** at the lower end of the armature **26** closes the nozzle **22**.

(135) To open the printhead valve **20**, the coil **23** is energized in such a way that the armature **26** is pushed upwards in the drawing, so that the seal **28** releases the nozzle **22**.

(136) In addition, the individual printhead valves **20** each have a rinse ports **29** at the top end.

(137) The printhead itself has an inlet **30** for supplying paint or rinsing agent and an outlet **31** for dispensing paint or rinsing agent.

(138) As for the drawings in FIGS. 4A-4D, it should be noted that in the drawings all printhead valves **20** are shown in the closed state and the nozzles **22** then close. In fact, however, the individual printhead valves **20** must open or close in order to perform the rinsing operations described below.

(139) It should also be mentioned that the drawings show the flow path of the rinsing agent in the various rinsing processes by means of a large arrow.

(140) In FIG. 4A, the flushing fluid is introduced into the printhead through the inlet **30** and then leaves the printhead through the outlet **31** into the return, with all printhead valves **20** being closed.

(141) In the flushing procedure shown in FIG. 4B, the flushing fluid is also fed into the printhead through the inlet **30** and then leaves the printhead through the nozzles **22**. In this flushing procedure, the individual printhead valves **20** are opened which is different from the drawing.

(142) In the rinse operation shown in FIG. 4C, however, the rinsing agent is fed through rinse ports **29** of each printhead valve **20** and then leaves the printhead through nozzles **22**. Again, each printhead valve **20** release nozzle **22** differently from the drawing.

(143) In the flushing procedure shown in FIG. 4D, however, the rinsing agent is introduced in the reverse direction through the open nozzles **22** and then leaves the printhead via the rinse ports **29** of the individual printhead valves **20** and/or (not shown) via the return. Thus, within the scope of the disclosure, there is the possibility that the coil tubes **24** of the individual printhead valves **20** can be flowed through bidirectionally by flushing medium in order to achieve a good flushing effect.

(144) The disclosure is not limited to the preferred embodiments described above. Rather, a large number of variants and modifications are possible which also make use of the disclosure and

therefore fall within the scope of protection. In particular, the disclosure also claims protection for the subject-matter and the features of the dependent claims independently of the claims referred to in each case and in particular also without the features of the main claim. The disclosure thus comprises a large number of different aspects which enjoy protection independently of each other.

LIST OF REFERENCE SIGNS

(145) **1** Motor vehicle body component **2** Conveyors **3** Painting robots **4** Robot base **5** Rotatable robot link **6** Proximal robot arm ("Arm 1") **7** Distal robot arm ("Arm 2") **8** Robot hand axis **9** Printhead **10** Wet deposit device **11** Liquid bath **12** Cleaning nozzles in the wet deposit device **13** Deposited printhead in the wet deposit device **14** Docking device in the wet deposit device **15** Circulation line in the wet deposit device **16** Circulation line in the wet deposit device **17** A/B color changer **17.1** Color changer **17.2** Color changer **18** Color lines **19** Color lines **20** Printhead valves **21** Nozzle plate **22** Nozzles **23** Coil **24** Coil tube **25** Coil core **26** Armature **27** Return spring **28** Seal **29** Rinse ports **30** Printhead inlet **31** Printhead outlet A, B Printheads **F1-F6** Color lines **PL** Pulse air line **V** Thinner line **RA, RB** Return lines

Claims

1. A coating process for coating components with a coating agent, the coating process comprising the following steps: a) moving a first printhead with at least one nozzle and an associated printhead valve by means of a multi-axis coating robot over a surface of the component to be coated, and b) discharging a coating agent jet of a first coating agent through the nozzle of the first printhead onto the surface of the component to be coated, c) a color change with the following step: exchanging the first printhead by a second printhead for the subsequent delivery of a coating agent jet of a second coating agent through the second printhead onto the surface of the component to be coated, including depositing the first printhead from the coating robot in a deposit device and taking-up the second printhead by the coating robot, d) circulating coating agent and/or rinsing agent through the deposited first and second printheads, respectively, in the deposit device to prevent the coating agent from drying in the deposited first and second printheads.

2. The coating process according to claim 1, further comprising the following step: bathing or at least partially immersing the deposited first or second printhead in a liquid bath in the deposit device in order to prevent the coating agent from drying in the deposited first or second printhead.

3. The coating process according to claim 1, further comprising the following step: moistening the deposited first or second printhead on a moistening fleece in the deposit device in order to prevent the coating agent from drying in the deposited first or second printhead.

4. A coating process for coating components with a coating agent, the coating process comprising the following steps: a) moving a first printhead with at least one nozzle and an associated printhead valve by means of a multi-axis coating robot over a surface of the component to be coated, and b) discharging a coating agent jet of a first coating agent through the nozzle of the first printhead onto the surface of the component to be coated, c) a color change with the following steps: switching coating agent delivery from said first printhead to a second printhead mounted on the same coating robot for subsequent delivery of a coating agent jet of a second coating agent through said second printhead, inserting the first or second printhead into a cleaning device, cleaning the first or second printhead in the cleaning device, collecting and disposing of the liquids applied in the cleaning device, and pre-filling with a new coating agent in the cleaning device.

5. The coating process according to claim 4, further comprising the following steps: a) Application of said coating agent by said first printhead while said second printhead is rinsed with a rinsing agent, and b) Application of said coating agent by the second printhead while the first printhead is rinsed with a rinsing agent.

6. The coating process according to claim 4, further comprising the following steps: a) applying said first coating agent through said first printhead while circulating said second coating agent

through said second printhead with closed printhead valves of said second printhead; and b) applying the second coating agent through the second printhead while the first coating agent circulates through the first printhead with the printhead valves of the first printhead being closed.

7. The coating process according to claim 4, further comprising the following steps during a color change from a solvent-based paint to a water-based paint: a) rinsing the first or second printhead with a solvent rinsing agent, b) rinsing the first or second printhead with a solvent, c) rinsing said first or second printhead with a water-based rinsing agent.

8. Coating process according to claim 4, further comprising the following steps during a color change: a) Sequential rinsing of the first or second printhead with different rinsing agents, and b) rinsing the first or second printhead with a universal rinsing agent both for rinsing out water-based paint and for rinsing out solvent-based paint, and c) rinsing the first or second printhead with a mixture of pulsed air, rinsing agent and/or aerosol, and d) rinsing the first or second printhead with a VOC-free rinsing agent.

9. A coating process for coating components with a coating agent, the coating process comprising the following steps: a) moving a first printhead with at least one nozzle and an associated printhead valve by a multi-axis coating robot over a surface of the component to be coated, and b) discharging a coating agent jet of a first coating agent through the nozzle of the first printhead onto the surface of the component to be coated, c) a color change with the following step: exchanging the first printhead by a second printhead for the subsequent delivery of a coating agent jet of a second coating agent through the second printhead onto the surface of the component to be coated, including depositing the first printhead from the coating robot in a deposit device and taking-up the second printhead by the coating robot, and d) bathing or at least partially immersing the deposited first or second printhead in a liquid bath in the deposit device in order to prevent the coating agent from drying in the deposited first or second printhead.
