

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12392689
B2
August 19, 2025
Nagai; Yusuke et al.

Online sampling system

Abstract

It is an object to enable a sample of a sample source to be injected into a LC while a pressure state of the sample source is maintained. There are provided an injector (2) including a first sample loop (18) and an injection valve (20), a sample supply channel (26), a pump part (4), a second sample loop (12), a sample source channel (52), and a path construction part. The path construction part is configured to be capable of selectively constructing a sampling path and a sample supply path. The sampling path is configured so that the sample source channel (52) and the pump part (4) are fluidly connected to each other in a closed system with the second sample loop (12) interposed therebetween and the sample is drawn from the sample source to the second sample loop (12) using the pump part (4), and the sample supply path is configured so that the second sample loop (12) is separated from the sample source channel (52) while maintaining a closed system state of the sample source channel (52) and the pump part (4) or another pump (40) different from the pump part and the sample supply channel (26) are fluidly connected to each other with the second sample loop (12) interposed therebetween and the sample held in the second sample loop (12) is supplied to the injector (2) through the sample supply channel (26) using the pump part (4) or the other pump (40).

Inventors: Nagai; Yusuke (Kyoto, JP), Iwata; Yosuke (Kyoto, JP), Yamazaki; Tomoyuki (Kyoto, JP)

Applicant: SHIMADZU CORPORATION (Kyoto, JP)

Family ID: 1000008765198

Assignee: SHIMADZU CORPORATION (Kyoto, JP)

Appl. No.: 18/132371

Filed: April 08, 2023

Prior Publication Data

Document Identifier
US 20230324261 A1

Publication Date
Oct. 12, 2023

Foreign Application Priority Data

JP 2022-064942 Apr. 11, 2022

Publication Classification

Int. Cl.: G01N30/20 (20060101); G01N1/14 (20060101); G01N1/20 (20060101)

U.S. Cl.:

CPC G01N1/2035 (20130101); G01N1/14 (20130101); G01N2001/205 (20130101)

Field of Classification Search

CPC: G01N (1/2035); G01N (1/14); G01N (2001/205); G01N (30/24); G01N (2001/002); G01N (2001/105); G01N (2030/202); G01N (30/20); G01N (2030/201); G01N (30/22); G01N (2030/207)

USPC: 73/61.52; 73/61.55; 73/61.56; 73/61.59; 73/64.56; 73/863.86; 73/864.21; 73/864.22; 73/864.81; 134/22.11; 134/22.12; 210/656; 210/198.2; 422/70

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4057997	12/1976	Chandler	73/864.83	G01N 30/06
2016/0195564	12/2015	Hewitson	422/63	G01N 30/06
2019/0101513	12/2018	Phoebe	N/A	G01N 30/8696

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
S6219758	12/1986	JP	N/A
2021063835	12/2020	JP	N/A
WO-2020168156	12/2019	WO	B01D 15/14

Primary Examiner: Raevis; Robert R

Attorney, Agent or Firm: Renner, Otto, Boisselle & Sklar, LLP

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to an online sampling system that takes a sample from a sample source and injects it online during a mobile phase in a liquid chromatograph (referred to below as an LC).

2. Description of the Related Art

(2) LC is an analysis technique that is not only used in various fields such as pharmaceutical

production, food production, and chemistry, but also widely used from upstream (research and development) to downstream (manufacturing and quality control) processes. The LC is used in adoption of process analytical technology (PAT) and use of the PAT is promoted in manufacturing and quality control processes to check whether required product quality is ensured by monitoring a manufacturing process automatically and continuously as much as possible. Introduction of the PAT not only enhances reliability and robustness of a manufacturing process, but also achieves cost reduction effect. Thus, introduction of the PAT has progressed in the petroleum and chemical industries, and the pharmaceutical and electronic industries also have studied introduction of the PAT.

(3) An online monitoring system using an LC, in which a flow vial is used, is known (see JP 2021-063835 A). The system using the flow vial is configured such that the flow vial is disposed in an autosampler of the LC, and the autosampler injects a sample supplied to the flow vial from a sample source into the LC.

SUMMARY OF THE INVENTION

(4) When a system using a flow vial starts to monitor a manufacturing process under high pressure, a sample source under high pressure is to be fluidly connected to the flow vial to increase pressure in the flow vial. However, a needle of the autosampler penetrates a septum of the flow vial when the sample supplied to the flow vial is injected into the LC, so that the system from the sample source to the flow vial cannot be said to be a completely closed system. As a result, the sample source is less likely to be maintained in a required high pressure state, so that reaction of the sample in the manufacturing process may be affected.

(5) The present invention is made in view of the above problems, and an object thereof is to enable a sample of a sample source to be injected into an LC while a pressure state of the sample source is maintained.

(6) An online sampling system according to the present invention is configured to collect a sample from a sample source and to inject the sample into a mobile phase flowing through an analysis channel of an LC, the online sampling system including: an injector including a first sample loop for temporarily holding a sample and an injection valve for switching between a state in which the first sample loop is incorporated in the analysis channel and a state in which the first sample loop is separated from the analysis channel; a sample supply channel fluidly connected to the injector and configured to supply the sample to the injector; a pump part configured to suck and discharge a liquid; a second sample loop provided separately from the first sample loop; a sample source channel communicating with the sample source; a path construction part including one or more switching valves, the path construction part being configured to selectively build multiple fluid flow paths in the online sampling system by switching the one or more switching valves.

(7) The path construction part is configured to be capable of selectively constructing a sampling path and a sample supply path, the sampling path is configured so that the sample source channel and the pump part are fluidly connected to each other in a closed system with the second sample loop interposed therebetween to draw a sample from the sample source to the second sample loop using the pump part, and the sample supply path is configured so that the second sample loop is separated from the sample source channel while maintaining a closed system state of the sample source channel and the pump part or another pump different from the pump part and the sample supply channel are fluidly connected to each other with the second sample loop interposed therebetween and the sample held in the second sample loop is supplied to the injector through the sample supply channel using the pump part or the other pump.

(8) Here, the term, “closed system”, means a system including no place through which a fluid can flow between the inside and the outside of the system, and an internal space formed to be completely closed. The phrase, “maintaining the closed system state of the sample source channel”, means that the closed system state in the system including the sample source channel is always maintained before and after a connection destination of the sample source channel is switched.

(9) The online sampling system according to the present invention enables supplying a sample of the sample source to the injector to inject the sample into the LC while maintaining a pressure state of the sample source because of including the second sample loop separately from the first sample loop provided in the injector configured to inject a sample into the LC, and capable of selectively constructing the sampling path being a closed system configured to draw a sample from the sample source to the second sample loop through the sample source channel, and the sample supply path configured to separate the second sample loop from the sample source channel and fluidly connect the second sample loop to the injector while maintaining the closed system state of the sample source channel, thereby feeding the sample held in the second sample loop to the injector.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a channel configuration diagram illustrating an example of an online sampling system;
- (2) FIG. 2 is a diagram illustrating an example of a channel configuration when a sampling path is constructed in the example;
- (3) FIG. 3 is a diagram illustrating an example of a channel configuration when a sample supply path is constructed in the example;
- (4) FIG. 4 is a diagram illustrating an example of a channel configuration when a diluted sample is drawn into a first sample loop in the example;
- (5) FIG. 5 is a diagram illustrating an example of a channel configuration when a cleaning liquid is fed from a pump part to clean the inside of a channel;
- (6) FIG. 6 is a diagram illustrating an example of a channel configuration when a sample held in a first sample loop is injected into a mobile phase of an LC;
- (7) FIG. 7 is a diagram illustrating an example of a channel configuration when a pretreatment part cleaning path is constructed in the example;
- (8) FIG. 8 is a diagram illustrating another example of a channel configuration when a pretreatment part cleaning path is constructed in the example;
- (9) FIG. 9 is a diagram illustrating an example of a channel configuration when the inside of a channel is cleaned with a solvent supplied by a liquid feed pump in the example;
- (10) FIG. 10 is a flowchart for illustrating an example of a sampling operation of injecting a sample of a sample source into a mobile phase of an LC in the example;
- (11) FIG. 11 is a channel configuration diagram illustrating another example of an online sampling system;
- (12) FIG. 12 is a diagram illustrating an example of a channel configuration when a sampling path is constructed in the other example;
- (13) FIG. 13 is a diagram illustrating an example of a channel configuration when a sample supply path is constructed in the other example;
- (14) FIG. 14 is a channel configuration diagram illustrating yet another example of an online sampling system;
- (15) FIG. 15 is a diagram illustrating an example of a channel configuration when a sampling path is constructed in the yet other example;
- (16) FIG. 16 is a diagram illustrating an example of a channel configuration when a sample supply path is constructed in the yet other example;
- (17) FIG. 17 is a channel configuration diagram illustrating still another example of an online sampling system;
- (18) FIG. 18 is a diagram illustrating an example of a channel configuration when a sampling path is constructed in the still other example; and
- (19) FIG. 19 is a diagram illustrating an example of a channel configuration when a sample supply

path is constructed in the still other example.

DETAILED DESCRIPTION OF THE INVENTION

(20) Hereinafter, an embodiment of an online sampling system according to the present invention will be described with reference to the drawings.

(21) An online sampling system **1** of the present example includes an injector **2**, a pump part **4**, switching valves **6**, **8**, and **10**, a sample loop **12** (second sample loop), a container part **14**, a drain port **16**, and a controller **17**.

(22) The injector **2** is for injecting a sample into a mobile phase flowing through an analysis channel **100** of an LC including a separation column **102**, a detector **104**, and the like. The injector **2** includes a sample loop **18** (first sample loop) for temporarily holding a sample, an injection valve **20** for switching between a state in which the sample loop **18** is incorporated in the analysis channel **100** and a state in which the sample loop is separated from the analysis channel **100**, and a sampling channel **24** provided at its tip with a needle **22** that three-dimensionally moves. The injection valve **20** is a two-position valve in which six ports **1** to **6** are arranged counterclockwise. The ports **1** and **2** adjacent to each other of the injection valve **20** are fluidly connected to an upstream channel and a downstream channel of the analysis channel **100**, respectively. The ports **3** and **6** of the injection valve **20** are fluidly connected to one end and the other end of the sample loop **18**, respectively. The port **4** of the injection valve **20** is fluidly connected to the sampling channel **24**, and the port **5** adjacent to the port **4** is connected to one end of a sample supply channel **26**. The other end of the sample supply channel **26** is fluidly connected to a port **6** of a switching valve **6**. The sample supply channel **26** is for supplying a sample to the injector **2**.

(23) The pump part **4** is fluidly connected to a port **1** of the switching valve **6** via a pump channel **36**. The pump part **4** includes two syringe pumps **28** and **30**, and two 3-port valves **32** and **34**. The syringe pumps **28** and **30** are different in cylinder capacity from each other. The pump part **4** allows one of the syringe pumps **28** and **30** to be fluidly connected to the pump channel **36** using the 3-port valves **32** and **34**. The pump part **4** also can supply a cleaning liquid from any one of the syringe pumps **28** and **30** through the pump channel **36**. The pump part **4** does not necessarily include two syringe pumps, and may include only one syringe pump.

(24) The container part **14** is configured to allow multiple containers **54** to be set. Examples of a container **54** set in the container part **14** include an empty container that can be used for diluting a sample, and a sample container that stores a sample. The drain port **16** allows access of the needle **22** to discharge a liquid ejected from the needle **22** to a drain. The needle **22** of the injector **2** is accessible to any container **54** set in the container part **14** and the drain port **16**.

(25) Each of the switching valves **6**, **8** and **10** is a two-position valve including six ports **1** to **6** counterclockwise.

(26) The port **2** of the switching valve **6** is fluidly connected to the port **3** of the switching valve **8** via a channel **38**, the port **4** of the switching valve **6** is fluidly connected to the port **1** of the switching valve **8** via a channel **44**, and the port **5** of the switching valve **6** is fluidly connected to the port **6** of the switching valve **8** via a channel **46**. The port **3** of the switching valve **6** is connected to a solvent supply channel **42** including a liquid feed pump **40** provided separately from the pump part **4**. The liquid feed pump **40** can supply a solvent through the solvent supply channel **42**.

(27) The ports **2** and **5** of the switching valve **8** are fluidly connected one end and the other end of the sample loop **12**, respectively. The port **4** of the switching valve **8** is fluidly connected to a port **4** of a switching valve **10** via a pretreatment channel **48**. The pretreatment channel **48** is provided with a pretreatment part **50**. The pretreatment part **50** is configured to apply pretreatment to a sample drawn into the sample loop **12** from a sample source. Examples of the pretreatment part **50** include a filter for removing unnecessary substances in a sample, a remelting device for remelting a sample precipitated in a channel, and the like. Conceivable examples of the remelting device include a device that generates ultrasonic waves, low-frequency vibrations, heat, an electric field,

or a magnetic field.

(28) The switching valve **10** includes ports **1**, **2**, and **6** that are each a closed port. The switching valve **10** includes a port **3** that is fluidly connected to a sample source channel **52** communicating with the sample source.

(29) The switching valves **6**, **8**, and **10** constitute a path construction part for constructing various fluid flow paths in the online sampling system **1**. The fluid flow path constructed by the path construction part including the switching valves **6**, **8**, and **10** will be described below.

(30) As illustrated in FIG. **2**, the pump part **4** and the sample source channel **52** are fluidly connected to each other in a closed system with the sample loop **12** interposed therebetween in states as follows: the switching valve **6** includes the ports **1** and **2** fluidly communicating with each other; the switching valve **8** includes the ports **2** and **3** fluidly communicating with each other, and the ports **4** and **5** fluidly communicating with each other; and the switching valve **10** includes the ports **3** and **4** fluidly communicating with each other. When any syringe pump (syringe pump **28** in the drawing) of the pump part **4** is driven to perform sucking in these states, a sample of the sample source is drawn into the sample loop **12** through the sample source channel **52** and the pretreatment channel **48**. That is, bringing the switching valves **6**, **8**, and **10** into the state of FIG. **2** constructs a sampling path for drawing the sample of the sample source into the sample loop **12** with the pump part **4**. When the sampling path is constructed, the sample source channel **52** to the pump part **4** are in a closed system. Thus, pressure in the sample source **52** can be maintained with no reduction.

(31) As illustrated in FIG. **3**, the solvent supply channel **42** and the sample supply channel **26** are fluidly connected to each other with the sample loop **12** interposed therebetween in states as follows: the switching valve **6** includes the ports **3** and **4** fluidly communicating with each other and the ports **5** and **6** fluidly communicating with each other; and the switching valve **8** includes the ports **1** and **2** fluidly communicating with each other, and the ports **5** and **6** fluidly communicating with each other. Feeding a solvent with the liquid feed pump **40** in these states causes the sample held in the sample loop **12** to be supplied to the injector **2** together with the solvent from the liquid feed pump **40**. That is, bringing the switching valves **6**, **8**, and **10** into the state of FIG. **3** constructs a sample supply path for supplying the sample held in the sample loop **12** to the injector **2** with the liquid feed pump **40**. At this time, the ports **4** and **5** of the injection valve **20** of the injector **2** is caused to fluidly communicate with each other and the needle **22** is caused to access the container **54** being empty set in the container **14**, so that the sample and the solvent supplied to the injector **2** through the sample supply channel **26** can be stored in the container **54**, and the sample can be diluted in the container **54**. The sample has a dilution rate that can be adjusted by a liquid feed flow rate of the liquid feed pump **40**.

(32) FIG. **3** illustrates a state in which the port **3** of the switching valve **10**, which is fluidly connected to the sample source channel **52**, fluidly communicates with the closed port **2** when the sample supply path is constructed, the state causing a closed system state to be maintained even after the sample source channel **52** is disconnected from the sample loop **12**. Even when the ports **3** and **4** of the switching valve **10** fluidly communicate with each other in a state where the sample supply path is constructed, the closed system state in the system including the sample source can be maintained.

(33) When the ports **1** and **6** of the switching valve **6** are caused to fluidly communicate with each other as illustrated in FIG. **4**, the pump part **4** is fluidly connected to the sampling channel **24**, and thus constructing a sucking and discharging path for sucking and discharging a fluid with the pump part **4** via the needle **22**. FIG. **4** illustrates an example in which the needle **22** is caused to access the drain port **16**. When any of the syringe pumps (syringe pump **30** in the drawing) of the pump part **4** supplies a cleaning liquid in this state, the inside of a channel from the pump part **4** to the needle **22** can be cleaned.

(34) When the injection valve **20** of the injector **2** is caused to allow the ports **3** and **4** to fluidly communicate with each other, and the ports **5** and **6** to fluidly communicate with each other, as

illustrated in FIG. 5, the sample loop **18** can be incorporated in the sucking and discharging path. When the needle **22** is caused to access the container **54** storing the diluted sample, and any syringe pump (the syringe pump **30** in the drawing) of the pump part **4** is driven to perform sucking, in this state, the sample in the container **54** can be drawn into the sample loop **18**.

(35) When the injection valve **20** of the injector **2** is caused to allow the ports **1** and **6** to fluidly communicate with each other, and the ports **2** and **3** to fluidly communicate with each other to incorporate the sample loop **18** into the analysis channel **100** after the sample is drawn into the sample loop **18**, as illustrated in FIG. 6, the sample held in the sample loop **18** can be injected into the mobile phase of the LC.

(36) Besides the above, the path construction part including the switching valves **6**, **8**, and **10** can construct various cleaning paths.

(37) As illustrated in FIG. 7, a pretreatment part cleaning path is constructed in which the solvent supply channel **42**, the pretreatment channel **48**, and the drain are fluidly connected in series when the ports **2** and **3** of the switching valve **6** are caused to fluidly communicate with each other, the ports **3** and **4** of the switching valve **8** are caused to fluidly communicate with each other, and the ports **4** and **5** of the switching valve **10** are caused to fluidly communicate with each other. Construction of such a pretreatment part cleaning path enables the pretreatment part **50** on the pretreatment channel **48** to be cleaned with the solvent from the liquid feed pump **40**.

(38) As illustrated in FIG. 8, a pretreatment part cleaning path is constructed in which the solvent supply channel **42**, the sample loop **12**, the pretreatment channel **48**, and the drain are fluidly connected in series when the ports **2** and **3** of the switching valve **6** are caused to fluidly communicate with each other, the ports **2** and **3** of the switching valve **8**, and the ports **4** and **5** thereof are caused to fluidly communicate with each other, and the ports **4** and **5** of the switching valve **10** are caused to fluidly communicate with each other. The pretreatment part cleaning path of FIG. 8 enables the pretreatment channel **48** and the inside of the sample loop **12** to be cleaned with the solvent from the liquid feed pump **40**.

(39) The pretreatment part cleaning path as illustrated in FIGS. 7 and 8 enables the solvent to flow in a direction opposite to a flow of the sample when the sample is drawn from the sample source to the sample loop **12** in the pretreatment part **50**, so that a high cleaning effect of the pretreatment part **50** can be obtained.

(40) As illustrated in FIG. 9, a path for supplying the solvent from the liquid feed pump **40** to the injector **2** through the channels **44** and **46**, and the sample supply channel **26** is constructed when the ports **3** and **4** of the switching valve **6**, and the ports **5** and **6** thereof, are caused to fluidly communicate with each other, and the ports **1** and **6** of the switching valve **8** are caused to fluidly communicate with each other. When the needle **22** of the injector **2** is caused to access the drain port **16** and the liquid feed pump **40** supplies the solvent to the injector **2** in this state, not only the channels **44** and **46**, and the sample supply channel **26**, but also the sample loop **18** and the sampling channel **24** of the injector **2**, can be cleaned.

(41) Operations of the injector **2**, the pump part **4**, the switching valves **6**, **8**, and **10**, and the liquid feed pump **40** are controlled by the controller **17** (see FIG. 1). The controller **17** is a function implemented by executing a computer program in a computer device including a central processing part (CPU) and an information storage device. The controller **17** is configured to control the operations of the injector **2**, the pump part **4**, the switching valves **6**, **8**, and **10**, and the liquid feed pump **40** to collect a sample from the sample source and supply the sample to the injector **2**, perform pretreatment such as dilution of the sample as necessary, and then execute a sampling operation of injecting the sample into a mobile phase flowing through the analysis channel **100**.

(42) FIG. 10 illustrates an example of the sampling operation.

(43) The controller **17** causes the switching valves **6**, **8**, and **10** to construct the sampling path illustrated in FIG. 2 (step **101**), and causes the sample of the sample source to be drawn into the sample loop **12** (second sample loop) by connecting any one of the syringe pumps **28** and **30** of the

pump part 4 to the pump channel 36 and driving the pump to perform sucking (step 102).

(44) Next, the controller 17 causes the switching valves 6, 8, and 10 to construct the sample supply path illustrated in FIG. 3 (step 103), and causes the liquid feed pump 40 to feed the solvent to supply the sample held in the sample loop 12 together with the solvent to the injector 2 through the sample supply channel 26 (step 104). At this time, the needle 22 of the injector 2 is caused to access the container 54 being empty of the container part 14 to temporarily store the sample and the solvent supplied to the injector 2 through the sample supply channel 26 in the empty container 54, and then the sample is diluted in the container 54.

(45) After the sample and the solvent are stored in the container 54, an operation of stirring inside the container 54 can be performed as necessary. The stirring inside the container 54 can be performed by causing the ports 1 and 6 of the switching valve 6 to fluidly communicate with each other with the needle 22 having accessed the container 54, fluidly connecting any one of the syringe pumps 28 and 30 of the pump part 4 to the sampling channel 24, and causing the syringe pump 28 or 30 to repeatedly perform a sucking operation and a discharging operation. After that, when the needle 22 is caused to access the drain port 16 and a cleaning liquid is supplied from the pump part 4, the sample supply channel 26 and the sampling channel 24 can be cleaned (see FIG. 4).

(46) After the sample and the solvent are stored in the container 54 and cleaning of the channels, for example, is performed as necessary, the controller 17 causes the sucking and discharging path with the sample loop 18 interposed between the pump part 4 and the sampling channel 24 to be constructed with the needle 22 having accessed the stored container 54, and then causes any one of the syringe pumps 28 and 30 of the pump part 4 to perform the sucking operation to draw the sample into the sample loop 18 (see FIG. 5). After that, the controller 17 injects the sample into the mobile phase of the LC by switching the injection port 20 to incorporate the sample loop 18 into the analysis channel 100 (step 105). After the sample is injected into the mobile phase of the LC, the controller 17 causes a cleaning path as illustrated in FIGS. 7 to 9 to be constructed as necessary to perform cleaning of the inside of each channel of the system 1 (step 106). Cleaning of the pretreatment part 50 using the pretreatment part cleaning path illustrated in FIGS. 7 and 8 can be performed at any time after the sample is supplied to the injector 2.

(47) Although various fluid flow paths can be constructed by the path construction part including the three switching valves 6, 8, and 10 in the above example, the present invention is not limited thereto. That is, the online sampling system may be configured to enable constructing at least a sampling path capable of collecting a sample from the sample source to the sample loop 12 and a sample supply path capable of supplying a sample from the sample loop 12 to the injector 2 while a system including the sample source is always maintained as a closed system.

(48) FIG. 11 is a configuration diagram illustrating another example of the online sampling system. The example described below denotes the same components as those of the online sampling system 1 described with reference to FIGS. 1 to 10 with the same reference numerals as those of FIGS. 1 to 10, and does not describe a detailed duplicated description thereof.

(49) An online sampling system 1' of the present example includes a path construction part for constructing various fluid flow paths that is implemented by two switching valves 56 and 58.

(50) Each of the switching valves 56 and 58 is a two-position valve including six ports 1 to 6 counterclockwise. The port 1 of the switching valve 56 is fluidly connected to a sample supply channel 26 communicating with an injector 2, and the port 2 of the switching valve 56 is fluidly connected to a pump channel 36 communicating with a pump part 4. The port 3 of the switching valve 56 fluidly communicates with the port 1 of the switching valve 58 via a channel 60, and the port 6 of the switching valve 56 fluidly communicates with the port 5 of the switching valve 58 via a channel 62. The ports 4 and 5 of the switching valve 56 are closed.

(51) The port 2 of the switching valve 58 is fluidly connected to a sample source channel 52 communicating with a sample source. The sample source channel 52 is provided with a

pretreatment part **50**. The ports **3** and **6** of the switching valve **58** are fluidly connected to one end and the other end of a sample loop **12**, respectively. The port **4** of the switching valve **58** is fluidly connected to a solvent supply channel **42** including a liquid feed pump **40**.

(52) As illustrated in FIG. **12**, the online sampling system **1'** includes a sampling path in which the pump part **4** fluidly communicate with the sample source channel **52** with the sample loop **12** interposed therebetween, the sampling path being constructed by causing the ports **2** and **3** of the switching valve **56** to fluidly communicate with each other, and the ports **1** and **2** of the switching valve **58**, and the ports **2** and **3** thereof, to fluidly communicate with each other. When any one of syringe pumps **28** and **30** of the pump part **4** is driven to perform sucking in this state, a sample of the sample source can be drawn into the sample loop **12**.

(53) When the ports **1** and **6** of the switching valve **56** are caused to fluidly communicate with each other, and the ports **3** and **4** of the switching valve **58**, and the ports **5** and **6** thereof, are caused to fluidly communicate with each other, as illustrated in FIG. **13**, a sample supply path is constructed in which a solvent feed channel **42** fluidly communicate with the sample supply channel **26** with the sample loop **12** interposed therebetween. Feeding a solvent with the liquid feed pump **40** in these states enables the sample held in the sample loop **12** to be supplied to the injector **2** together with the solvent. At this time, the ports **4** and **5** of the injection valve **20** of the injector **2** is caused to fluidly communicate with each other and the needle **22** is caused to access the container **54** being empty set in the container **14**, so that the sample and the solvent supplied to the injector **2** through the sample supply channel **26** can be stored in the container **54**, and the sample can be diluted in the container **54**. The sample has a dilution rate that can be adjusted by a liquid feed flow rate of the liquid feed pump **40**. As another dilution method, the dilution rate can be adjusted during liquid feeding by changing pipe capacity of a channel. For example, in comparison between a pipe having a pipe capacity of 100 mL and a pipe having a pipe capacity of 50 mL, the sample is more diluted by using a pipe having the pipe capacity of 100 mL. That is, using a pipe having a pipe capacity corresponding to a target dilution rate for a channel enables further dilution than when a liquid feed flow rate of the liquid feed pump **40** is adjusted.

(54) Although not illustrated in the drawing, the pump part **4** can fluidly communicate with a sampling channel **24** by causing the ports **1** and **2** of the switching valve **56** to fluidly communicate with each other, so that the sample stored in the container **54** can be drawn into the sample loop **18**, or a cleaning liquid can be supplied from the pump part **4** toward the sampling channel **24** to clean the channel.

(55) FIG. **14** is a configuration diagram illustrating yet another example of the online sampling system. The example described below also denotes the same components as those of the online sampling system **1** described with reference to FIGS. **1** to **10** with the same reference numerals as those of FIGS. **1** to **10**, and does not describe a detailed duplicated description thereof.

(56) An online sampling system **1''** of the present example includes a path construction part for constructing various fluid flow paths that is implemented by two switching valves **64** and **66**.

(57) The switching valve **64** is a two-position valve in which ports **1** to **6** are arranged counterclockwise. The switching valve **66** is a seven-port valve that is provided at its center with a common port and that includes the ports **1** to **6** arranged counterclockwise around the common port, and is configured to selectively causes the central port to fluidly communicate with any one of the ports **1** to **6**.

(58) The port **1** of the switching valve **64** is fluidly connected to a pump channel **36** communicating with a pump part **4**, and the ports **3** and **6** of the switching valve **64** are fluidly connected to one end and the other end of a sample loop **12**, respectively. The port **2** of the switching valve **64** fluidly communicates with the common port of the switching valve **66** via a channel **68**. The ports **4** and **5** of the switching valve **64** are closed.

(59) The port **2** of the switching valve **66** is fluidly connected to a sample supply channel **26** communicating with an injector **2**, and the port **4** of the switching valve **66** is fluidly connected to a

sample source channel **52**. The sample source channel **52** is provided with a pretreatment part **50**. The port **5** of the switching valve **66** communicates with a drain, and the port **6** communicates with a container for storing a cleaning liquid. The ports **1** and **3** of the switching valve **66** are closed.

(60) As illustrated in FIG. **15**, the online sampling system **1''** includes a sampling path in which the pump part **4** fluidly communicate with the sample source channel **52** with the sample loop **12** interposed therebetween, the sampling path being constructed by causing the ports **1** and **6** of the switching valve **64**, and the ports **2** and **3** thereof, to fluidly communicate with each other, and the common port and the port **4** of the switching valve **66** to fluidly communicate with each other. When any one of syringe pumps **28** and **30** of the pump part **4** is driven to perform sucking in this state, a sample of the sample source can be drawn into the sample loop **12**.

(61) When the ports **1** and **6** of the switching valve **64**, and the ports **2** and **3** thereof, are caused to fluidly communicate with each other, and the common port and the port **2** of the switching valve **66** are caused to fluidly communicate with each other, as illustrated in FIG. **16**, a sample supply path is constructed in which the pump part **4** fluidly communicate with the sample supply channel **26** with the sample loop **12** interposed therebetween. When the pump part **4** is driven to push out the sample drawn into the sample loop **12** toward the sample supply channel **26** in this state, the sample held by the sample loop **12** can be supplied to the injector **2**. At this time, the ports **3** and **4** of an injection valve **20** of the injector **2**, and the ports **5** and **6** thereof, are caused to fluidly communicate with each other, and a needle **22** is caused to access a drain port **16**, so that the sample supplied to the injector **2** through the sample supply channel **26** can be fed into a sample loop **18**.

(62) FIG. **17** is a configuration diagram illustrating still another example of the online sampling system. The example described below also denotes the same components as those of the online sampling system **1** described with reference to FIGS. **1** to **10** with the same reference numerals as those of FIGS. **1** to **10**, and does not describe a detailed duplicated description thereof.

(63) An online sampling system **1'''** of the present example includes a path construction part for constructing various fluid flow paths that is implemented by only one switching valve **70**.

(64) The switching valve **70** is a seven-port valve that is provided at its center with a common port and that includes ports **1** to **6** arranged counterclockwise around the common port, and is configured to selectively causes the central port to fluidly communicate with any one of the ports **1** to **6**.

(65) The common port of the switching valve **70** is fluidly connected to a pump channel **36** communicating with a pump part **4**. The pump channel **36** is provided with a sample loop **12**. The port **2** of the switching valve **70** is fluidly connected to a sample supply channel **26** communicating with an injector **2**, and the port **4** of the switching valve **70** is fluidly connected to a sample source channel **52**. The sample source channel **52** is provided with a pretreatment part **50**, and pretreatment such as filtering is performed on a sample flowing through the sample source channel **52**. The port **5** of the switching valve **70** communicates with a drain, and the port **6** communicates with a container for storing a cleaning liquid. The ports **1** and **3** of the switching valve **70** are closed.

(66) As illustrated in FIG. **18**, the online sampling system **1'''** includes a sampling path in which the pump part **4** fluidly communicate with the sample source channel **52** with the sample loop **12** interposed therebetween, the sampling path being constructed by causing the common port and the port **4** of the switching valve **70** to fluidly communicate with each other. When any one of syringe pumps **28** and **30** of the pump part **4** is driven to perform sucking in this state, a sample of the sample source can be drawn into the sample loop **12**.

(67) When the common port and the port **2** of the switching valve **70** are caused to fluidly communicate with each other as illustrated in FIG. **19**, a sample supply path is constructed in which the pump part **4** fluidly communicate with the sample supply channel **26** with the sample loop **12** interposed therebetween. When the pump part **4** is driven to push out the sample drawn

into the sample loop 12 toward the sample supply channel 26 in this state, the sample held by the sample loop 12 can be supplied to the injector 2. At this time, the ports 3 and 4 of an injection valve 20 of the injector 2, and the ports 5 and 6 thereof, are caused to fluidly communicate with each other, and a needle 22 is caused to access a drain port 16, so that the sample supplied to the injector 2 through the sample supply channel 26 can be fed into a sample loop 18.

(68) The examples described above are merely examples of embodiments of the online sampling system according to the present invention. The embodiments of the online sampling system according to the present invention are as follows.

(69) An online sampling system according to an embodiment of the present invention is configured to collect a sample from a sample source and to inject the sample into a mobile phase flowing through an analysis channel of a liquid chromatograph, the online sampling system including: an injector including a first sample loop for temporarily holding a sample and an injection valve for switching between a state in which the first sample loop is incorporated in the analysis channel and a state in which the first sample loop is separated from the analysis channel; a sample supply channel fluidly connected to the injector and configured to supply the sample to the injector; a pump part configured to suck and discharge a liquid; a second sample loop provided separately from the first sample loop; a sample source channel communicating with the sample source; a path construction part including one or more switching valves, the path construction part being configured to selectively build multiple fluid flow paths in the online sampling system by switching the one or more switching valves.

(70) The path construction part is configured to be capable of selectively constructing paths a sampling path and a sample supply path, the sampling path is configured so that the sample source channel and the pump part are fluidly connected to each other in a closed system with the second sample loop interposed therebetween and the sample is drawn from the sample source to the second sample loop using the pump part, and the sample supply path is configured so that the second sample loop is separated from the sample source channel while maintaining a closed system state of the sample source channel and the pump part or another pump different from the pump part and the sample supply channel are fluidly connected to each other with the second sample loop interposed therebetween and the sample held in the second sample loop is supplied to the injector through the sample supply channel using the pump part or the other pump.

(71) The embodiment includes a first aspect in which the one or more switching valves include one switching valve having a first port and a second port, the sample supply channel is provided to fluidly connect the first port of the one switching valve and one port of the injection valve, and the pump part is fluidly connected to the second port of the one switching valve.

(72) The embodiment includes a second aspect configured such that the other pump is provided to feed a solvent, and the online sampling system is configured so that the other pump and the sample supply channel are fluidly connected to each other with the second sample loop interposed therebetween when the path construction part constructs the sample supply path, and thereby, the sample held in the second sample loop is supplied to the injector together with the solvent fed by the other pump.

(73) The second aspect includes a specific aspect in which the online sampling system further includes a container part in which a container for containing a sample is set, the injector includes a sampling channel having a tip provided with a needle for accessing the container set in the container part to suck a liquid from the container and discharging the liquid to the container, and the injector is configured so that the sample supply channel and the sampling channel may be connected to each other, thereby, it can be achieved that the sample and the solvent supplied through the sample supply channel are stored in the container by fluidly connecting the sample supply channel to the container when the path construction part constructs the sample supply path. Such an aspect enables a sample collected from the sample source to be automatically diluted.

(74) The above specific aspect that enables a sample to be automatically diluted is configured such

that the sample supply channel and the sampling channel always fluidly communicate with each other via the injection valve, and the first sample loop is interposed between the sample supply channel and the sampling channel when the first sample loop is disconnected from the analysis channel, and the path construction part is configured so that selectively construct a sucking and discharging path, which is for the pump part to suck and discharge a liquid through the needle, may be selectively constructed by fluidly connecting the pump part to the sample supply channel. Such an aspect enables a sample to be sucked from the container via the needle using the pump part and drawn into the first sample loop. As a result, all of a series of sampling operations such as collecting a sample from the sample source, diluting the collected sample, and injecting the diluted sample into the LC, can be performed online.

(75) The embodiment includes a third aspect in which a pretreatment channel is provided, including a pretreatment part that performs pretreatment on a sample drawn from the sample source toward the second sample loop, the pretreatment channel being interposed between the second sample loop and the sample source channel when the sampling path is constructed, and the path construction part is configured to selectively construct a pretreatment part cleaning path for supplying the solvent to the pretreatment part using the other pump by fluidly connecting the liquid feed pump and the pretreatment channel while disconnecting the pretreatment channel from the sample source channel and connecting the pretreatment channel to a drain. Such an aspect enables the pretreatment part to be cleaned with the pretreatment channel separated from the sample source channel.

(76) Examples of the pretreatment part include a filter for removing substances unnecessary for analysis from a sample, and a remelting device for remelting a sample precipitated in a channel.

(77) The third aspect may be configured such that the path construction part is configured to allow the second sample loop to be interposed between the liquid feed pump and the pretreatment channel when the pretreatment part cleaning path is constructed. This configuration enables the second sample loop to be cleaned simultaneously with the pretreatment part.

(78) The embodiment includes a fourth aspect that further includes a controller configured to control operations of the injector, the pump part, and the path construction part, and also control an operation of the other pump when the other pump is provided, the controller being configured to perform the following: a sampling step of constructing the sampling path and drawing a sample of the sample source into the second sample loop to hold the sample; a sample supply step of constructing the sample supply path after the sampling step is completed to supply the sample held in the second sample loop to the injector using the pump part or the other pump; and an injection step of injecting the sample into the mobile phase by incorporating the first sample loop holding the sample into the analysis channel after the sample supply step is completed.

(79) The embodiment includes a fifth aspect that further includes a controller configured to control operations of the injector, the pump part, the other pump, and the path construction part, the controller being configured to perform the following: a sampling step of constructing the sampling path and drawing a sample of the sample source into the second sample loop to hold the sample; a sample dilution step of constructing the sample supply path after the sampling step is completed, causing the sample supply channel and the sampling channel to fluidly communicate with each other and the needle to access the container being empty, and supplying the sample held in the second sample loop using the other pump to the container together with the solvent to dilute the sample in the container; a sample sucking step of constructing the sucking and discharging path by fluidly connecting the pump part to the sample supply channel while interposing the first sample loop between the sample supply channel and the sampling channel after the sample dilution step is completed, and drawing the sample diluted in the container into the first sample loop using the pump part; and an injection step of injecting the sample into the mobile phase by incorporating the first sample loop holding the sample into the analysis channel after the sample sucking step is completed.

(80) 1, 1', 1'', 1''' online sampling system 2 injector 4 pump part 6, 8, 10, 32, 34, 56, 58, 64, 66, 70 switching valve 12 sample loop (second sample loop) 14 container part 16 drain port 18 sample loop (first sample loop) 20 injection port 22 needle 24 sampling channel 26 sample supply channel 28, 30 syringe pump 36 pump channel 38, 44, 46, 60, 62, 68 channel 40 liquid feed pump 42 solvent supply channel 48 pretreatment channel 50 pretreatment part 52 sample source channel 54 container

Claims

1. An online sampling system configured to collect a sample from a sample source and to inject the sample into a mobile phase flowing through an analysis channel of a liquid chromatograph, the online sampling system comprising: an injector including a first sample loop for temporarily holding a sample and an injection valve for switching between a state in which the first sample loop is incorporated in the analysis channel and a state in which the first sample loop is separated from the analysis channel; a sample supply channel fluidly connected to the injector and configured to supply the sample to the injector; a pump part configured to suck and discharge a liquid; a second sample loop provided separately from the first sample loop; a sample source channel communicating with the sample source; a path construction part including one or more switching valves, the path construction part being configured to selectively build multiple fluid flow paths in the online sampling system by switching the one or more switching valves, wherein the path construction part being configured to be capable of selectively constructing a sampling path and a sample supply path, the sampling path is configured so that the sample source channel and the pump part are fluidly connected to each other in a closed system with the second sample loop interposed therebetween and the sample is drawn from the sample source to the second sample loop using the pump part, and the sample supply path is configured so that the second sample loop is separated from the sample source channel while maintaining a closed system state of the sample source channel and the pump part or another pump different from the pump part and the sample supply channel are fluidly connected to each other with the second sample loop interposed therebetween and the sample held in the second sample loop is supplied to the injector through the sample supply channel using the pump part or the other pump.

2. The online sampling system according to claim 1, wherein the one or more switching valves includes one switching valve having a first port and a second port, the sample supply channel is provided to fluidly connect the first port of the one switching valve and one port of the injection valve, and the pump part is fluidly connected to the second port of the one switching valve.

3. The online sampling system according to claim 1, wherein the other pump is provided to feed a solvent, and the online sampling system is configured so that the other pump and the sample supply channel are fluidly connected to each other with the second sample loop interposed therebetween when the path construction part constructs the sample supply path, and thereby, the sample held in the second sample loop is supplied to the injector together with the solvent fed by the other pump.

4. The online sampling system according to claim 3, further comprising: a container part in which a container for containing a sample is set, wherein the injector includes a sampling channel having a tip provided with a needle for accessing the container set in the container part to suck a liquid from the container and discharging the liquid to the container, and the injector is configured so that the sample supply channel and the sampling channel may be connected to each other, thereby, it can be achieved that the sample and the solvent supplied through the sample supply channel are stored in the container by fluidly connecting the sample supply channel to the container when the path construction part constructs the sample supply path.

5. The online sampling system according to claim 4, further comprising: a controller configured to control operations of the injector, the pump part, the other pump, and the path construction part, the

controller being configured to perform the following: a sampling step of constructing the sampling path and drawing a sample of the sample source into the second sample loop to hold the sample; a sample dilution step of constructing the sample supply path after the sampling step is completed, causing the sample supply channel and the sampling channel to fluidly communicate with each other and the needle to access the container being empty, and supplying the sample held in the second sample loop using the other pump to the container together with the solvent to dilute the sample in the container; a sample sucking step of constructing the sucking and discharging path by fluidly connecting the pump part to the sample supply channel while interposing the first sample loop between the sample supply channel and the sampling channel after the sample dilution step is completed, and drawing the sample diluted in the container into the first sample loop using the pump part; and an injection step of injecting the sample into the mobile phase by incorporating the first sample loop holding the sample into the analysis channel after the sample sucking step is completed.

6. The online sampling system according to claim 4, wherein the sample supply channel and the sampling channel always fluidly communicate with each other via the injection valve, and the first sample loop is interposed between the sample supply channel and the sampling channel when the first sample loop is disconnected from the analysis channel, and the path construction part is configured so that a sucking and discharging path, which is for the pump part to suck and discharge a liquid through the needle, may be selectively constructed by fluidly connecting the pump part to the sample supply channel.

7. The online sampling system according to claim 1, further comprising: a pretreatment channel including a pretreatment part that performs pretreatment on a sample drawn from the sample source toward the second sample loop, the pretreatment channel being interposed between the second sample loop and the sample source channel when the sampling path is constructed, wherein the path construction part is configured to selectively construct a pretreatment part cleaning path for supplying the solvent to the pretreatment part using the other pump by fluidly connecting the liquid feed pump and the pretreatment channel while disconnecting the pretreatment channel from the sample source channel and connecting the pretreatment channel to a drain.

8. The online sampling system according to claim 7, wherein the pretreatment part is a filter for removing substances unnecessary for analysis from a sample, or a remelting device for remelting a sample precipitated in a channel.

9. The online sampling system according to claim 7, wherein the path construction part is configured to allow the second sample loop to be interposed between the liquid feed pump and the pretreatment channel when the pretreatment part cleaning path is constructed.

10. The online sampling system according to claim 1, further comprising: a controller configured to control operations of the injector, the pump part, and the path construction part, and also control an operation of the other pump when the other pump is provided, the controller being configured to perform the following: a sampling step of constructing the sampling path and drawing a sample of the sample source into the second sample loop to hold the sample; a sample supply step of constructing the sample supply path after the sampling step is completed to supply the sample held in the second sample loop to the injector using the pump part or the other pump; and an injection step of injecting the sample into the mobile phase by incorporating the first sample loop holding the sample into the analysis channel after the sample supply step is completed.
