

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12390294
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Heiliger; Zachary S.

---

### Robotic surgical assemblies including surgical instruments having articulatable wrist assemblies

---

#### Abstract

A surgical instrument for use in a robotic surgical system includes an end effector, a housing configured to be operably coupled to an instrument drive unit, a shaft extending distally from the housing, a wrist assembly coupled to a distal end portion of the shaft, articulation cables that adjust the pitch and yaw of the end effector relative to the shaft, and a differential gear mechanism that transfers an input rotation to the articulation cables.

---

<b>Inventors:</b>	<b>Heiliger; Zachary S. (Nederland, CO)</b>
<b>Applicant:</b>	<b>Covidien LP (Mansfield, MA)</b>
<b>Family ID:</b>	<b>1000008766257</b>
<b>Assignee:</b>	<b>Covidien LP (Mansfield, MA)</b>
<b>Appl. No.:</b>	<b>17/979105</b>
<b>Filed:</b>	<b>November 02, 2022</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230181274 A1	Jun. 15, 2023

#### Related U.S. Application Data

us-provisional-application US 63289361 20211214

---

#### Publication Classification

**Int. Cl.:** A61B34/30 (20160101); A61B34/00 (20160101)

## U.S. Cl.:

CPC      **A61B34/71** (20160201); **A61B34/70** (20160201); A61B34/30 (20160201)

## Field of Classification Search

**CPC:**    A61B (34/71); A61B (34/70); A61B (34/30); A61B (2034/302); A61B (2034/303); A61B (2034/305); A61B (17/068); A61B (17/28); A61B (17/2804); A61B (17/29); A61B (17/00234); A61B (2017/0046); A61B (2017/00464); A61B (2017/00473); A61B (2017/00367); A61B (2017/00477)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6132368	12/1999	Cooper	N/A	N/A
6206903	12/2000	Ramans	N/A	N/A
6246200	12/2000	Blumenkranz et al.	N/A	N/A
6312435	12/2000	Wallace et al.	N/A	N/A
6331181	12/2000	Tierney et al.	N/A	N/A
6394998	12/2001	Wallace et al.	N/A	N/A
6424885	12/2001	Niemeyer et al.	N/A	N/A
6441577	12/2001	Blumenkranz et al.	N/A	N/A
6459926	12/2001	Nowlin et al.	N/A	N/A
6491691	12/2001	Morley et al.	N/A	N/A
6491701	12/2001	Tierney et al.	N/A	N/A
6493608	12/2001	Niemeyer	N/A	N/A
6565554	12/2002	Niemeyer	N/A	N/A
6645196	12/2002	Nixon et al.	N/A	N/A
6659939	12/2002	Moll	N/A	N/A
6671581	12/2002	Niemeyer et al.	N/A	N/A
6676684	12/2003	Morley et al.	N/A	N/A
6685698	12/2003	Morley et al.	N/A	N/A
6699235	12/2003	Wallace et al.	N/A	N/A
6714839	12/2003	Salisbury, Jr. et al.	N/A	N/A
6716233	12/2003	Whitman	N/A	N/A
6728599	12/2003	Wang et al.	N/A	N/A
6746443	12/2003	Morley et al.	N/A	N/A
6766204	12/2003	Niemeyer et al.	N/A	N/A
6770081	12/2003	Cooper et al.	N/A	N/A
6772053	12/2003	Niemeyer	N/A	N/A
6783524	12/2003	Anderson et al.	N/A	N/A
6793652	12/2003	Whitman et al.	N/A	N/A
6793653	12/2003	Sanchez et al.	N/A	N/A
6799065	12/2003	Niemeyer	N/A	N/A
6837883	12/2004	Moll et al.	N/A	N/A
6839612	12/2004	Sanchez et al.	N/A	N/A
6840938	12/2004	Morley et al.	N/A	N/A
6843403	12/2004	Whitman	N/A	N/A

6846309	12/2004	Whitman et al.	N/A	N/A
6866671	12/2004	Tierney et al.	N/A	N/A
6871117	12/2004	Wang et al.	N/A	N/A
6879880	12/2004	Nowlin et al.	N/A	N/A
6899705	12/2004	Niemeyer	N/A	N/A
6902560	12/2004	Morley et al.	N/A	N/A
6936042	12/2004	Wallace et al.	N/A	N/A
6951535	12/2004	Ghodoussi et al.	N/A	N/A
6974449	12/2004	Niemeyer	N/A	N/A
6991627	12/2005	Madhani et al.	N/A	N/A
6994708	12/2005	Manzo	N/A	N/A
7048745	12/2005	Tierney et al.	N/A	N/A
7066926	12/2005	Wallace et al.	N/A	N/A
7118582	12/2005	Wang et al.	N/A	N/A
7125403	12/2005	Julian et al.	N/A	N/A
7155315	12/2005	Niemeyer et al.	N/A	N/A
7239940	12/2006	Wang et al.	N/A	N/A
7306597	12/2006	Manzo	N/A	N/A
7357774	12/2007	Cooper	N/A	N/A
7373219	12/2007	Nowlin et al.	N/A	N/A
7379790	12/2007	Toth et al.	N/A	N/A
7386365	12/2007	Nixon	N/A	N/A
7391173	12/2007	Schena	N/A	N/A
7398707	12/2007	Morley et al.	N/A	N/A
7413565	12/2007	Wang et al.	N/A	N/A
7453227	12/2007	Prisco et al.	N/A	N/A
7524320	12/2008	Tierney et al.	N/A	N/A
7574250	12/2008	Niemeyer	N/A	N/A
7594912	12/2008	Cooper et al.	N/A	N/A
7607440	12/2008	Coste-Maniere et al.	N/A	N/A
7666191	12/2009	Orban, III et al.	N/A	N/A
7682357	12/2009	Ghodoussi et al.	N/A	N/A
7689320	12/2009	Prisco et al.	N/A	N/A
7695481	12/2009	Wang et al.	N/A	N/A
7695485	12/2009	Whitman et al.	N/A	N/A
7699855	12/2009	Anderson et al.	N/A	N/A
7713263	12/2009	Niemeyer	N/A	N/A
7725214	12/2009	Diolaiti	N/A	N/A
7727244	12/2009	Orban, III et al.	N/A	N/A
7741802	12/2009	Prisco	N/A	N/A
7756036	12/2009	Druke et al.	N/A	N/A
7757028	12/2009	Druke et al.	N/A	N/A
7762825	12/2009	Burbank et al.	N/A	N/A
7778733	12/2009	Nowlin et al.	N/A	N/A
7803151	12/2009	Whitman	N/A	N/A
7806891	12/2009	Nowlin et al.	N/A	N/A
7819859	12/2009	Prisco et al.	N/A	N/A
7819885	12/2009	Cooper	N/A	N/A
7824401	12/2009	Manzo et al.	N/A	N/A
7835823	12/2009	Sillman et al.	N/A	N/A

7843158	12/2009	Prisco	N/A	N/A
7865266	12/2010	Moll et al.	N/A	N/A
7865269	12/2010	Prisco et al.	N/A	N/A
7886743	12/2010	Cooper et al.	N/A	N/A
7899578	12/2010	Prisco et al.	N/A	N/A
7907166	12/2010	Lamprecht et al.	N/A	N/A
7935130	12/2010	Williams	N/A	N/A
7963913	12/2010	Devengenzo et al.	N/A	N/A
7983793	12/2010	Toth et al.	N/A	N/A
8002767	12/2010	Sanchez	N/A	N/A
8004229	12/2010	Nowlin et al.	N/A	N/A
8012170	12/2010	Whitman et al.	N/A	N/A
8054752	12/2010	Druke et al.	N/A	N/A
8062288	12/2010	Cooper et al.	N/A	N/A
8079950	12/2010	Stern et al.	N/A	N/A
8100133	12/2011	Mintz et al.	N/A	N/A
8108072	12/2011	Zhao et al.	N/A	N/A
8120301	12/2011	Goldberg et al.	N/A	N/A
8142447	12/2011	Cooper et al.	N/A	N/A
8147503	12/2011	Zhao et al.	N/A	N/A
8151661	12/2011	Schena et al.	N/A	N/A
8155479	12/2011	Hoffman et al.	N/A	N/A
8182469	12/2011	Anderson et al.	N/A	N/A
8202278	12/2011	Orban, III et al.	N/A	N/A
8206406	12/2011	Orban, III	N/A	N/A
8210413	12/2011	Whitman et al.	N/A	N/A
8216250	12/2011	Orban, III et al.	N/A	N/A
8220468	12/2011	Cooper et al.	N/A	N/A
8256319	12/2011	Cooper et al.	N/A	N/A
8285517	12/2011	Sillman et al.	N/A	N/A
8315720	12/2011	Mohr et al.	N/A	N/A
8335590	12/2011	Costa et al.	N/A	N/A
8347757	12/2012	Duval	N/A	N/A
8374723	12/2012	Zhao et al.	N/A	N/A
8418073	12/2012	Mohr et al.	N/A	N/A
8419717	12/2012	Diolaiti et al.	N/A	N/A
8423182	12/2012	Robinson et al.	N/A	N/A
8452447	12/2012	Nixon	N/A	N/A
8454585	12/2012	Whitman	N/A	N/A
8499992	12/2012	Whitman et al.	N/A	N/A
8508173	12/2012	Goldberg et al.	N/A	N/A
8528440	12/2012	Morley et al.	N/A	N/A
8529582	12/2012	Devengenzo et al.	N/A	N/A
8540748	12/2012	Murphy et al.	N/A	N/A
8551116	12/2012	Julian et al.	N/A	N/A
8562594	12/2012	Cooper et al.	N/A	N/A
8594841	12/2012	Zhao et al.	N/A	N/A
8597182	12/2012	Stein et al.	N/A	N/A
8597280	12/2012	Cooper et al.	N/A	N/A
8600551	12/2012	Itkowitz et al.	N/A	N/A

8608773	12/2012	Tierney et al.	N/A	N/A
8620473	12/2012	Diolaiti et al.	N/A	N/A
8624537	12/2013	Nowlin et al.	N/A	N/A
8634957	12/2013	Toth et al.	N/A	N/A
8638056	12/2013	Goldberg et al.	N/A	N/A
8638057	12/2013	Goldberg et al.	N/A	N/A
8644988	12/2013	Prisco et al.	N/A	N/A
8666544	12/2013	Moll et al.	N/A	N/A
8668638	12/2013	Donhowe et al.	N/A	N/A
8746252	12/2013	McGrogan et al.	N/A	N/A
8749189	12/2013	Nowlin et al.	N/A	N/A
8749190	12/2013	Nowlin et al.	N/A	N/A
8758352	12/2013	Cooper et al.	N/A	N/A
8761930	12/2013	Nixon	N/A	N/A
8768516	12/2013	Diolaiti et al.	N/A	N/A
8786241	12/2013	Nowlin et al.	N/A	N/A
8790243	12/2013	Cooper et al.	N/A	N/A
8808164	12/2013	Hoffman et al.	N/A	N/A
8816628	12/2013	Nowlin et al.	N/A	N/A
8821480	12/2013	Burbank	N/A	N/A
8823308	12/2013	Nowlin et al.	N/A	N/A
8827989	12/2013	Niemeyer	N/A	N/A
8838270	12/2013	Druke et al.	N/A	N/A
8852174	12/2013	Burbank	N/A	N/A
8858547	12/2013	Brogna	N/A	N/A
8862268	12/2013	Robinson et al.	N/A	N/A
8864751	12/2013	Prisco et al.	N/A	N/A
8864752	12/2013	Diolaiti et al.	N/A	N/A
8903546	12/2013	Diolaiti et al.	N/A	N/A
8903549	12/2013	Itkowitz et al.	N/A	N/A
8911428	12/2013	Cooper et al.	N/A	N/A
8912746	12/2013	Reid et al.	N/A	N/A
8944070	12/2014	Guthart	N/A	N/A
8989903	12/2014	Weir et al.	N/A	N/A
9002518	12/2014	Manzo	N/A	N/A
9014856	12/2014	Manzo et al.	N/A	N/A
9016540	12/2014	Whitman et al.	N/A	N/A
9019345	12/2014	O'Grady et al.	N/A	N/A
9043027	12/2014	Durant et al.	N/A	N/A
9050120	12/2014	Swarup et al.	N/A	N/A
9055961	12/2014	Manzo et al.	N/A	N/A
9068628	12/2014	Solomon et al.	N/A	N/A
9078684	12/2014	Williams	N/A	N/A
9084623	12/2014	Gomez et al.	N/A	N/A
9095362	12/2014	Dachs, II et al.	N/A	N/A
9096033	12/2014	Holop et al.	N/A	N/A
9101381	12/2014	Burbank et al.	N/A	N/A
9113877	12/2014	Whitman et al.	N/A	N/A
9138284	12/2014	Krom et al.	N/A	N/A
9144456	12/2014	Rosa et al.	N/A	N/A

9198730	12/2014	Prisco et al.	N/A	N/A
9204923	12/2014	Manzo et al.	N/A	N/A
9226648	12/2015	Saadat et al.	N/A	N/A
9226750	12/2015	Weir et al.	N/A	N/A
9226761	12/2015	Burbank	N/A	N/A
9232984	12/2015	Guthart et al.	N/A	N/A
9241766	12/2015	Duque et al.	N/A	N/A
9241767	12/2015	Prisco et al.	N/A	N/A
9241769	12/2015	Larkin et al.	N/A	N/A
9259275	12/2015	Burbank	N/A	N/A
9259277	12/2015	Rogers et al.	N/A	N/A
9259281	12/2015	Griffiths et al.	N/A	N/A
9259282	12/2015	Azizian et al.	N/A	N/A
9261172	12/2015	Solomon et al.	N/A	N/A
9265567	12/2015	Orban, III et al.	N/A	N/A
9265584	12/2015	Itkowitz et al.	N/A	N/A
9283049	12/2015	Diolaiti et al.	N/A	N/A
9301811	12/2015	Goldberg et al.	N/A	N/A
9314307	12/2015	Richmond et al.	N/A	N/A
9317651	12/2015	Nixon	N/A	N/A
9345546	12/2015	Toth et al.	N/A	N/A
9393017	12/2015	Flanagan et al.	N/A	N/A
9402689	12/2015	Prisco et al.	N/A	N/A
9417621	12/2015	Diolaiti	N/A	N/A
9424303	12/2015	Hoffman et al.	N/A	N/A
9433418	12/2015	Whitman et al.	N/A	N/A
9446517	12/2015	Burns et al.	N/A	N/A
9452020	12/2015	Griffiths et al.	N/A	N/A
9474569	12/2015	Manzo et al.	N/A	N/A
9480533	12/2015	Devengenzo et al.	N/A	N/A
9503713	12/2015	Zhao et al.	N/A	N/A
9550300	12/2016	Danitz et al.	N/A	N/A
9554859	12/2016	Nowlin et al.	N/A	N/A
9566124	12/2016	Prisco et al.	N/A	N/A
9579164	12/2016	Itkowitz et al.	N/A	N/A
9585641	12/2016	Cooper et al.	N/A	N/A
9615883	12/2016	Schena et al.	N/A	N/A
9623563	12/2016	Nixon	N/A	N/A
9623902	12/2016	Griffiths et al.	N/A	N/A
9629520	12/2016	Diolaiti	N/A	N/A
9662177	12/2016	Weir et al.	N/A	N/A
9664262	12/2016	Donlon et al.	N/A	N/A
9675354	12/2016	Weir et al.	N/A	N/A
9687312	12/2016	Dachs et al.	N/A	N/A
9700334	12/2016	Hinman et al.	N/A	N/A
9718190	12/2016	Larkin et al.	N/A	N/A
9730719	12/2016	Brisson et al.	N/A	N/A
9737199	12/2016	Pistor et al.	N/A	N/A
9795446	12/2016	DiMaio et al.	N/A	N/A
9797484	12/2016	Solomon et al.	N/A	N/A

9801690	12/2016	Larkin et al.	N/A	N/A
9814530	12/2016	Weir et al.	N/A	N/A
9814536	12/2016	Goldberg et al.	N/A	N/A
9814537	12/2016	Itkowitz et al.	N/A	N/A
9820823	12/2016	Richmond et al.	N/A	N/A
9827059	12/2016	Robinson et al.	N/A	N/A
9830371	12/2016	Hoffman et al.	N/A	N/A
9839481	12/2016	Blumenkranz et al.	N/A	N/A
9839487	12/2016	Dachs, II	N/A	N/A
9850994	12/2016	Schena	N/A	N/A
9855102	12/2017	Blumenkranz	N/A	N/A
9855107	12/2017	Labonville et al.	N/A	N/A
9872737	12/2017	Nixon	N/A	N/A
9877718	12/2017	Weir et al.	N/A	N/A
9883920	12/2017	Blumenkranz	N/A	N/A
9888974	12/2017	Niemeyer	N/A	N/A
9895813	12/2017	Blumenkranz et al.	N/A	N/A
9901408	12/2017	Larkin	N/A	N/A
9918800	12/2017	Itkowitz et al.	N/A	N/A
9943375	12/2017	Blumenkranz et al.	N/A	N/A
9948852	12/2017	Lilagan et al.	N/A	N/A
9949798	12/2017	Weir	N/A	N/A
9949802	12/2017	Cooper	N/A	N/A
9952107	12/2017	Blumenkranz et al.	N/A	N/A
9956044	12/2017	Gomez et al.	N/A	N/A
9980778	12/2017	Ohline et al.	N/A	N/A
10008017	12/2017	Itkowitz et al.	N/A	N/A
10028793	12/2017	Griffiths et al.	N/A	N/A
10033308	12/2017	Chaghajerdi et al.	N/A	N/A
10034719	12/2017	Richmond et al.	N/A	N/A
10052167	12/2017	Au et al.	N/A	N/A
10085811	12/2017	Weir et al.	N/A	N/A
10092344	12/2017	Mohr et al.	N/A	N/A
10123844	12/2017	Nowlin	N/A	N/A
10188471	12/2018	Brisson	N/A	N/A
10201390	12/2018	Swarup et al.	N/A	N/A
10213202	12/2018	Flanagan et al.	N/A	N/A
10258416	12/2018	Mintz et al.	N/A	N/A
10278782	12/2018	Jarc et al.	N/A	N/A
10278783	12/2018	Itkowitz et al.	N/A	N/A
10282881	12/2018	Itkowitz et al.	N/A	N/A
10335242	12/2018	Devengenzo et al.	N/A	N/A
10405934	12/2018	Prisco et al.	N/A	N/A
10433922	12/2018	Itkowitz et al.	N/A	N/A
10464219	12/2018	Robinson et al.	N/A	N/A
10485621	12/2018	Morrisette et al.	N/A	N/A
10500004	12/2018	Hanuschik et al.	N/A	N/A
10500005	12/2018	Weir et al.	N/A	N/A
10500007	12/2018	Richmond et al.	N/A	N/A
10507066	12/2018	DiMaio et al.	N/A	N/A

10510267	12/2018	Jarc et al.	N/A	N/A
10524871	12/2019	Liao	N/A	N/A
10548459	12/2019	Itkowitz et al.	N/A	N/A
10575909	12/2019	Robinson et al.	N/A	N/A
10592529	12/2019	Hoffman et al.	N/A	N/A
10595946	12/2019	Nixon	N/A	N/A
10881469	12/2020	Robinson	N/A	N/A
10881473	12/2020	Itkowitz et al.	N/A	N/A
10898188	12/2020	Burbank	N/A	N/A
10898189	12/2020	McDonald	N/A	N/A
10905506	12/2020	Itkowitz et al.	N/A	N/A
10912544	12/2020	Brisson et al.	N/A	N/A
10912619	12/2020	Jarc et al.	N/A	N/A
10918387	12/2020	Duque et al.	N/A	N/A
10918449	12/2020	Solomon et al.	N/A	N/A
10932873	12/2020	Griffiths et al.	N/A	N/A
10932877	12/2020	Devengenzo et al.	N/A	N/A
10939969	12/2020	Swarup et al.	N/A	N/A
10939973	12/2020	DiMaio et al.	N/A	N/A
10952801	12/2020	Miller et al.	N/A	N/A
10965933	12/2020	Jarc	N/A	N/A
10966742	12/2020	Rosa et al.	N/A	N/A
10973517	12/2020	Wixey	N/A	N/A
10973519	12/2020	Weir et al.	N/A	N/A
10984567	12/2020	Itkowitz et al.	N/A	N/A
10993773	12/2020	Cooper et al.	N/A	N/A
10993775	12/2020	Cooper et al.	N/A	N/A
11000331	12/2020	Krom et al.	N/A	N/A
11013567	12/2020	Wu et al.	N/A	N/A
11020138	12/2020	Ragosta	N/A	N/A
11020191	12/2020	Piolaiti et al.	N/A	N/A
11020193	12/2020	Wixey et al.	N/A	N/A
11026755	12/2020	Weir et al.	N/A	N/A
11026759	12/2020	Donlon et al.	N/A	N/A
11040189	12/2020	Vaders et al.	N/A	N/A
11045077	12/2020	Stern et al.	N/A	N/A
11045274	12/2020	Dachs, II et al.	N/A	N/A
11058501	12/2020	Tokarchuk et al.	N/A	N/A
11076925	12/2020	DiMaio et al.	N/A	N/A
11090119	12/2020	Burbank	N/A	N/A
11096687	12/2020	Flanagan et al.	N/A	N/A
11098803	12/2020	Duque et al.	N/A	N/A
11109925	12/2020	Cooper et al.	N/A	N/A
11116578	12/2020	Hoffman et al.	N/A	N/A
11129683	12/2020	Steger et al.	N/A	N/A
11135029	12/2020	Suresh et al.	N/A	N/A
11147552	12/2020	Burbank et al.	N/A	N/A
11147640	12/2020	Jarc et al.	N/A	N/A
11154373	12/2020	Abbott et al.	N/A	N/A
11154374	12/2020	Hanuschik et al.	N/A	N/A



11160622	12/2020	Goldberg et al.	N/A	N/A
11160625	12/2020	Wixey et al.	N/A	N/A
11161243	12/2020	Rabindran et al.	N/A	N/A
11166758	12/2020	Mohr et al.	N/A	N/A
11166770	12/2020	DiMaio et al.	N/A	N/A
11166773	12/2020	Ragosta et al.	N/A	N/A
11173597	12/2020	Rabindran et al.	N/A	N/A
11185378	12/2020	Weir et al.	N/A	N/A
11191596	12/2020	Thompson et al.	N/A	N/A
11197729	12/2020	Thompson et al.	N/A	N/A
11213360	12/2021	Hourtash et al.	N/A	N/A
11221863	12/2021	Azizian et al.	N/A	N/A
11234700	12/2021	Ragosta et al.	N/A	N/A
11241274	12/2021	Vaders et al.	N/A	N/A
11241290	12/2021	Waterbury et al.	N/A	N/A
11259870	12/2021	DiMaio et al.	N/A	N/A
11259884	12/2021	Burbank	N/A	N/A
11272993	12/2021	Gomez et al.	N/A	N/A
11272994	12/2021	Saraliev et al.	N/A	N/A
11291442	12/2021	Wixey et al.	N/A	N/A
11291513	12/2021	Manzo et al.	N/A	N/A
2014/0318288	12/2013	Lee	N/A	N/A
2018/0055589	12/2017	Joseph et al.	N/A	N/A
2019/0357989	12/2018	Brisson et al.	N/A	N/A
2020/0038128	12/2019	Joseph et al.	N/A	N/A
2020/0229833	12/2019	Vakharia et al.	N/A	N/A
2020/0237455	12/2019	Anglese	N/A	A61B 34/30
2020/0261166	12/2019	Anglese	N/A	A61B 18/1442
2020/0261167	12/2019	Anglese	N/A	A61B 34/71
2023/0181274	12/2022	Heiliger	606/130	A61B 34/71

## OTHER PUBLICATIONS

Extended European Search Report dated May 3, 2023 for EP Applicaion No. 22213048.6, 12 pages. cited by applicant

---

*Primary Examiner:* Dornbusch; Dianne

*Attorney, Agent or Firm:* Carter, DeLuca & Farrell LLP

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims the benefit of and priority to U.S. Provisional Patent Application No. 63/289,361, filed Dec. 14, 2021, the entire contents of which are incorporated by reference herein.

## BACKGROUND

(1) Some surgical robotic systems include a console supporting a surgical robotic arm and a surgical instrument or at least one end effector (e.g., forceps or a grasping tool) mounted to the robotic arm. The robotic arm provides mechanical power to the surgical instrument for its operation

and movement. Each robotic arm may include an instrument drive unit operatively connected to the surgical instrument and coupled to the robotic arm via a rail. In operation, the robotic arm is moved to a position over a patient and then guides the surgical instrument into a small incision via a surgical trocar or a natural orifice of a patient to position the end effector at a work site within the patient's body. The instrument drive unit drives a rotation of each corresponding driven member of the attached surgical instrument to perform a surgical treatment. The instrument drive unit may be configured to articulate the end effector in a plurality of directions to adjust its pitch and/or yaw within a surgical site, to open/close jaw members, and/or to fire features thereof.

## SUMMARY

(2) In accordance with an aspect of the disclosure, a surgical instrument of a surgical robotic system is provided and includes a housing, a first transmission disposed within the housing, a shaft extending distally from the housing, an end effector pivotably coupled to a distal end portion of the shaft, and first and second articulation cables. The first transmission includes a rotatable first input shaft, first and second output shafts configured to rotate in response to a rotation of the first input shaft, and a first differential gear mechanism operably coupling the first input shaft to the first and second output shafts and the first and second output shafts to one another. Each of the first and second articulation cables has a proximal end portion operably coupled to the respective first and second output shafts, and a distal end portion secured to the end effector. The first and second articulation cables move axially in opposing directions at a different rate from one another to articulate the end effector relative to the shaft in response to the rotation of the first input shaft.

(3) In aspects, the first transmission may further include first and second articulation nuts operably coupled to the respective first and second output shafts. The articulation nuts may be configured to translate along the respective first and second output shafts in response to a rotation of the first and second output shafts. The articulation cables may be axially fixed to the respective first and second articulation nuts.

(4) In aspects, the first differential gear mechanism may include a ring gear, first and second spider gears coupled to the ring gear, and first and second side axles. The ring gear may be operably coupled to the first input shaft such that the ring gear is configured to be rotated by the first input shaft. The first and second spider gears may be configured to rotate about a respective axis thereof relative to the ring gear and with the ring gear around a rotation axis of the ring gear. The first side axle may be operably coupled to the first output shaft and the first and second spider gears, and the second side axle may be operably coupled to the second output shaft and the first and second spider gears.

(5) In aspects, the first side axle may have opposing first and second gears. The first gear may be operably coupled to the first and second spider gears and the second gear may be operably coupled to the first output shaft.

(6) In aspects, the second side axle may have opposing first and second gears. The first gear of the second side axle may be operably coupled to the first and second spider gears and the second gear of the second side axle may be operably coupled to the second output shaft.

(7) In aspects, the first input shaft may have a pinion gear non-rotationally fixed to a distal end portion thereof. The pinion gear may be in meshing engagement with the ring gear.

(8) In aspects, the ring gear may rotate about an axis that is perpendicular to a rotation axis of the first input shaft.

(9) In aspects, the surgical instrument may further include a second transmission nested with or positioned adjacent the first transmission and supported in the housing. The second transmission may include a rotatable second input shaft, third and fourth output shafts configured to rotate in response to a rotation of the second input shaft, and a second differential gear mechanism operably coupling the second input shaft to the third and fourth output shafts and the third and fourth output shafts to one another.

(10) In aspects, the surgical instrument may further include third and fourth articulation cables each

having a proximal end portion operably coupled to the respective third and fourth output shafts, and a distal end portion secured to the end effector, such that the third and fourth articulation cables move axially in opposing directions at a different rate from one another to articulate the end effector relative to the shaft in response to the rotation of the second input shaft.

(11) In aspects, the surgical instrument may further include a wrist assembly movably coupling the end effector to the distal end portion of the shaft. The wrist assembly may be configured to allow the end effector to articulate relative to the distal end portion of the shaft to adjust both a pitch and yaw of the end effector.

(12) In aspects, the first transmission may be configured to change the pitch of the end effector, and the second transmission may be configured to change the yaw of the end effector.

(13) In accordance with another aspect of the disclosure, a surgical robotic system is provided that includes a surgical robotic arm, an instrument drive unit configured to be supported on the surgical robotic arm, and a surgical instrument configured to be coupled to and driven by the instrument drive unit. The surgical instrument includes a housing configured to be attached to the instrument drive unit, a first transmission disposed within the housing, a shaft extending distally from the housing, an end effector pivotably coupled to a distal end portion of the shaft, and first and second articulation cables. The first transmission includes a rotatable first input shaft drivingly coupled to a corresponding drive shaft of the instrument drive unit, first and second output shafts configured to rotate in response to a rotation of the first input shaft, and a first differential gear mechanism operably coupling the first input shaft to the first and second output shafts and the first and second output shafts to one another. Each of the first and second articulation cables has a proximal end portion operably coupled to the respective first and second output shafts, and a distal end portion secured to the end effector, such that the first and second articulation cables move axially in opposing directions at a different rate from one another to adjust a pitch or a yaw of the end effector relative to the shaft in response to the rotation of the first input shaft.

(14) In aspects, the surgical instrument may further include a second transmission nested with or positioned adjacent the first transmission and supported in the housing. The second transmission may further include a rotatable second input shaft, third and fourth output shafts configured to rotate in response to a rotation of the second input shaft, and a second differential gear mechanism operably coupling the second input shaft to the third and fourth output shafts and the third and fourth output shafts to one another. The surgical instrument may further include third and fourth articulation cables each having a proximal end portion operably coupled to the respective third and fourth output shafts, and a distal end portion secured to the end effector, such that the third and fourth articulation cables move axially in opposing directions at a different rate from one another to articulate the end effector relative to the shaft in response to the rotation of the second input shaft.

(15) In aspects, the surgical instrument may further include a wrist assembly movably coupling the end effector to the distal end portion of the shaft. The wrist assembly may be configured to allow the end effector to articulate relative to the distal end portion of the shaft to adjust both the pitch and yaw of the end effector.

(16) In aspects, the first transmission may be configured to change the pitch of the end effector, and the second transmission may be configured to change the yaw of the end effector.

(17) In aspects, the first transmission may further include first and second articulation nuts operably coupled to the respective first and second output shafts and configured to translate therealong in response to a rotation of the respective first and second output shafts. The first and second articulation cables may be axially fixed to the respective first and second articulation nuts.

(18) In accordance with further aspects of the disclosure, a surgical instrument of a surgical robotic system is provided that includes a housing, a first transmission disposed within the housing, a shaft extending distally from the housing, an end effector pivotably coupled to a distal end portion of the shaft, and first and second articulation cables. The first transmission includes a rotatable first input shaft, first and second outputs configured to rotate in response to a rotation of the first input shaft,

and a first differential gear mechanism operably coupling the first input shaft to the first and second outputs and the first and second outputs to one another. The first and second articulation cables each have a proximal end portion operably coupled to the respective first and second outputs, and a distal end portion secured to the end effector. The first and second articulation cables move axially in opposing directions at a different rate from one another to change the pitch or yaw of the end effector relative to the shaft in response to the rotation of the first input shaft.

(19) In aspects, each of the first and second outputs may include an articulation wheel configured to rotate via the first differential gear mechanism. The first and second articulation cables may be attached to the respective articulation wheels, such that the rotation of the articulation wheels axially moves the first and second articulation cables in the opposing directions.

(20) In aspects, the first output may include a left-handed lead screw and the second output may include a right-handed lead screw.

(21) In aspects, the first transmission may further include first and second articulation nuts operably coupled to the respective left-handed and right-handed lead screws. The articulation nuts may be configured to translate along the left-handed and right-handed lead screws in response to the rotation of the respective lead screws. The articulation cables may be axially fixed to the respective first and second articulation nuts.

(22) In aspects, the surgical instrument may further include a second transmission nested with or positioned adjacent the first transmission and supported in the housing. The second transmission may include a rotatable second input shaft, third and fourth outputs configured to rotate in response to a rotation of the second input shaft, and a second differential gear mechanism operably coupling the second input shaft to the third and fourth outputs and the third and fourth outputs to one another. The surgical instrument may further include third and fourth articulation cables each having a proximal end portion operably coupled to the respective third and fourth output shafts, and a distal end portion secured to the end effector, such that the third and fourth articulation cables move axially in opposing directions at a different rate from one another to articulate the end effector relative to the shaft in response to the rotation of the second input shaft.

(23) Further details and aspects of exemplary embodiments of the disclosure are described in more detail below with reference to the appended figures.

(24) As used herein, the terms parallel and perpendicular are understood to include relative configurations that are substantially parallel and substantially perpendicular up to about + or -10 degrees from true parallel and true perpendicular.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments of the disclosure are described herein with reference to the accompanying drawings, wherein:

(2) FIG. 1 is a schematic illustration of a robotic surgical system in accordance with the disclosure;

(3) FIG. 2 is a perspective view of a surgical robotic arm of the robotic surgical system of FIG. 1 illustrating a surgical instrument and an instrument drive unit being coupled to the surgical robotic arm;

(4) FIG. 3 is a perspective view, with parts shown schematically, of the surgical instrument of FIG. 2;

(5) FIG. 4 is an enlarged, perspective view of a wrist assembly of the surgical instrument shown in FIG. 3;

(6) FIG. 5A is a perspective view illustrating a first transmission of the surgical instrument of FIG. 2;

(7) FIG. 5B is a perspective view illustrating a second transmission of the surgical instrument of

FIG. 2; and

(8) FIG. 6 is a perspective view illustrating a third transmission of the surgical instrument of the robotic surgical system of FIG. 2.

#### DETAILED DESCRIPTION

(9) Embodiments of the disclosed robotic surgical system and methods thereof are described in detail with reference to the drawings, in which like reference numerals designate identical or corresponding elements in each of the several views. As used herein the term “distal” refers to that portion of the robotic surgical system or component thereof that is further from the user, while the term “proximal” refers to that portion of the robotic surgical system or component thereof that is closer to the user.

(10) Articulation in a wristed robotic instrument is not linear. Stated differently, the wrist imposes a non-linear curve into the system. Consequently, an inside articulation cable is pulled back further than an outside articulation cable, therefore covering a greater axial distance in the same amount of time. Thus, because the two articulation cables are not driven the same distance during the same amount of time, the disclosure provides a differential. The differential converts rotational motion of an input shaft to rotational motion of two output axles. An open differential system allows for torque to be applied regardless of rotational differences between the output axles, covering variable distances in the same amount of time.

(11) Referring initially to FIGS. 1 and 2, a robotic surgical system 1 is shown and generally includes a plurality of surgical robotic arms 2, 3 each having a surgical instrument 10 (e.g., an electrosurgical instrument, a surgical stapling instrument, a surgical forceps, or the like) removably coupled thereto; a control device 4 (e.g., a computer); and an operating console 5 coupled with the control device 4.

(12) With continued reference to FIG. 1, the operating console 5 includes a display device 6, which is set up to display two-dimensional and three-dimensional images; and manual input devices 7, 8 that serve to enable a user (e.g., a surgeon) to telemanipulate robotic arms 2, 3, as known in principle to a person skilled in the art. Each of the robotic arms 2, 3 may include a plurality of members that are interconnected by joints. The robotic arms 2, 3 may be driven by electric drives (not shown) that are connected to the control device 4. The control device 4 is set up to execute a computer program to activate the electric drives in such a way that the robotic arms 2, 3, their instrument drive units 20, and thus the surgical instrument 10 execute a movement in accordance with a movement of the manual input devices 7, 8. The control device 4 may also be set up in such a way that it regulates the movement of the robotic arms 2, 3 and/or of the electric drives.

(13) The robotic surgical system 1 is configured for minimally invasive treatment of a patient “P” lying on a surgical table “ST” using a surgical instrument (e.g., surgical instrument 10) coupled to the robotic surgical system 1. In some embodiments of the disclosure, the robotic surgical system 1 may include more than two robotic arms that are likewise coupled to the control device 4 and telemanipulatable by the operating console 5. A surgical instrument (e.g., surgical instrument 10) may also be attached to the additional robotic arm(s).

(14) The surgical instrument 10 includes an end effector 40 (FIG. 2) for grasping and, in aspects, treating tissue. The control device 4 may control a plurality of motors (Motor 1 . . . n) with each motor configured to drive a relative rotation of drive members of a transmission assembly 100 (FIG. 3) of the surgical instrument 10 to effect operation and/or movement of the end effector 40 of the surgical instrument 10. It is contemplated that the control device 4 coordinates the activation of the various motors (Motor 1 . . . n) to coordinate a clockwise or counter-clockwise rotation of drive members (not shown) of the instrument drive unit 20 in order to coordinate an operation and/or movement of the end effector 40. In embodiments, each motor can be configured to actuate a drive rod or a lever arm to effect operation and/or movement of the end effector 40 of the surgical instrument 10.

(15) With specific reference to FIG. 2, the robotic surgical system 1 includes a surgical assembly

**12**, which includes the robotic arm **2**, the surgical instrument **10** coupled to the robotic arm **2**, and the instrument drive unit **20** configured to operably couple to the surgical instrument **10**. The instrument drive unit **20** is configured for powering the surgical instrument **10**. The instrument drive unit **20** transfers power and actuation forces from its motors (not shown) to the transmission assembly **100** (FIG. 3) of the surgical instrument **10** to ultimately drive movement of components of the end effector **40**, for example, a movement of a knife blade (not explicitly shown) for cutting tissue and a closing and opening of jaw members of the end effector **40** for grasping tissue, and/or drive an articulation of the end effector **40**.

(16) With reference to FIGS. 2 and 3, the surgical instrument **10** generally includes a housing **102**, a shaft **120** extending distally from the housing **102**, and a wrist assembly **30** pivotably coupling the end effector **40** to the shaft **120**. The housing **102** is configured to hook, latch, or otherwise attach to a surface of the robotic arm **2**, e.g., the distal end **2a** of the robotic arm **2**, to secure the surgical instrument **10** to the robotic arm **2**. In embodiments, the housing **102** may be attached to the surgical robotic arm **2** via various fastening engagements, such as, for example, clips, latches, friction fit engagement, buttons, a variety of fasteners, and/or a bayonet-type connection. The housing **102** houses the transmission assembly **100** that interfaces with the instrument drive unit **20**. The transmission assembly **100** translates the motion and torques of the motors of the instrument drive unit **20** into the motion necessary to articulate the wrist assembly **30** of the surgical instrument **10**, open and close the jaw members of the end effector **40**, and deploy and retract a knife blade to cut tissue grasped between the jaw members of the end effector **40**.

(17) With brief reference to FIG. 4, the wrist assembly **30** of the surgical instrument **10** operably couples the end effector **40** to a distal end portion **122** (FIG. 3) of the shaft **120**. More specifically, the wrist assembly **30** has a proximal body **32** immovably attached to the distal end portion **122** of the shaft **120**, a proximal pivot member **34** pivotably coupled to the proximal body **32**, and a distal pivot member **36** pivotably coupled to the proximal pivot member **34**. The proximal pivot member **34** is pivotable about a first articulation axis relative to the proximal body **32** to adjust a pitch of the end effector **40**, and the distal pivot member **36** is pivotable relative to the proximal pivot member **34** about a second articulation axis to adjust a yaw of the end effector **40**. The wrist assembly **30** is configured to affect the pivoting motion of the end effector **40** relative to the shaft **120** to adjust the yaw and/or pitch of the end effector **40** utilizing a series of translatable cables driven by the motors of the instrument drive unit **20**. One set of articulation cables “C1,” “C2” for adjusting the yaw of the end effector **40** are routed through the wrist assembly **30** and fixed to the distal pivot member **36** of the wrist assembly **30** or a proximal end of the end effector **40**. Accordingly, translation of selected cables pivots the end effector **40** in one of a plurality of directions, as will be described further below. The cables “C3,” “C4” for effecting the change in pitch of the end effector **40** are shown in FIG. 5B.

(18) Details about the transmission assembly **100** of the surgical instrument **10** will now be described with reference to FIGS. 3-5B. The transmission assembly **100** includes a first transmission **100a** (FIG. 5A) and a second transmission **100b** (FIG. 5B) each disposed within the housing **102** and nested with one another, or located in axial alignment with one another (e.g., first transmission **100a** being located distal of second transmission **100b** or first transmission **100a** being located proximal of second transmission **100b**).

(19) The first transmission **100a** includes a rotatable first input shaft **104**, first and second output shafts **106**, **108** each configured to rotate in response to a rotation of the first input shaft **104**, and a first differential gear mechanism **110** operably coupling the first input shaft **104** to the first and second output shafts **106**, **108** and the first and second output shafts **106**, **108** to one another. The first input shaft **104** has a proximal end portion **104a** configured to be drivingly coupled to a corresponding drive member or shaft (not shown) of the instrument drive unit **20** (FIG. 2), and a distal end portion having a pinion gear **104b** non-rotationally fixed thereto. The pinion gear **104b** is in meshing engagement with a ring gear **112** of the first differential gear mechanism **110** such that

the ring gear **112** is rotatable by the pinion gear **104b** of the first input shaft **104**. The ring gear **112** rotates about an axis that is perpendicular to a rotation axis of the first input shaft **104**. In aspects, the ring gear **112** may be a crown wheel.

(20) In addition to the first differential gear mechanism **110** having the ring gear **112**, the first differential gear mechanism **110** further includes first and second spider gears **114a**, **114b** coupled to the ring gear **112**, and first and second side axles **116**, **118** coupled to the respective spider gears **114a**, **114b** and the respective output shafts **106**, **108**. The spider gears **114a**, **114b** are rotatably supported on respective posts **120a**, **120b** that are fixed to the ring gear **112** and rotatable therewith about the rotation axis of the ring gear **112**. As such, the first and second spider gears **114a**, **114b** are configured to rotate about their respective axes relative to the ring gear **112** and with the ring gear **112** around the rotation axis of the ring gear **112**.

(21) The first and second side axles **116**, **118** of the first differential gear mechanism **110** each include opposing first and second gears **116a**, **116b**, **118a**, **118b**, such as, for example, bevel gears or crown gears. The first gear **116a** of the first side axle **116** is in meshing engagement with both the first and second spider gears **114a**, **114b** and the second gear **116b** of the first side axle **116** is in meshing engagement with a gear **124** (e.g., a bevel gear) of the first output shaft **106**. The second side axle **118** extends through a central opening of the ring gear **112**. The first gear **118a** of the second side axle **118** is in meshing engagement with both the first and second spider gears **114a**, **114b** and the second gear **118b** of the second side axle **118** is in meshing engagement with a gear **126** (e.g., a bevel gear) of the second output shaft **106**. Due to the function of the first differential gear mechanism **110**, the average of the rotational speed of the first and second output shafts **106**, **108** is equal to the input rotational speed of the input drive shaft **104** such that an increase in the speed of one of the output shafts **106** or **108** results in a proportional decrease in the speed of the other of the output shafts **106**, **108**, the benefit of which will be described in further detail below.

(22) With continued reference to FIG. 5A, the first transmission **100a** further includes first and second articulation nuts **128**, **130** operably coupled to the respective first and second output shafts **106**, **108**. The first output shaft **106** may be a left-handed lead screw and the second output shaft **108** may be a right-handed lead screw such that rotation of the output shafts **106**, **108** in the same rotational direction is configured to translate the respective articulation nuts **128**, **130** therealong in opposing axial directions. For example, as the output shafts **106**, **108** rotate in a clockwise direction, the first articulation nut **128** may translate proximally whereas the second articulation nut **130** may translate distally. The first and second articulation cables “C 1,” “C2” each have a proximal end portion **140**, **142** operably coupled to the respective first and second output shafts **106**, **108**, and a distal end portion **144**, **146** (FIG. 4) secured to the end effector **40**, such that the first and second articulation cables “C1,” “C2” move axially in opposing directions at a different rate from one another to articulate the end effector **40** relative to the shaft **120** to adjust a yaw of the end effector **40**.

(23) As illustrated in Table 1 below, it has been discovered that the degree of articulation of the end effector **40** is not linear to the degree of axial movement of the cables “C1-C4”; rather, articulation of the wrist assembly **30** imposes a non-linear curve into the system and to the degree of axial movement of the cables “C1-C4”. Consequently, the inside articulation cable (e.g., articulation cable “C1”) is translated proximally a greater distance than the outside articulation cable (e.g., articulation cable “C2”) is translated distally. That is, the inside articulation cable “C1” traverses a greater axial distance in the same amount of time than does the outside articulation cable “C2”. The differential gear mechanism **110** compensates for this difference to allow for the inside articulation cable “C1” to traverse the greater axial distance in the same amount of time thereby reducing stress and strain on the inside articulation cable “C2”. Therefore, use of the transmission assembly **100** of this disclosure will result in the articulation cables having a longer lifespan, and articulation of the end effector **40** will be more precise.

(24) TABLE-US-00001 TABLE 1 Joint Inside Outside Average Angle (deg) Cable (mm) Cable

(mm) Length (mm) % Change 0 7.21313 7.21313 7.21313 0 15.5 6.52968 7.85589 7.192785  
-0.282852887 31 5.74358 8.63665 7.190115 -0.320092238 46.5 4.88954 9.46854 7.17904  
-0.474854577 62 4.05633 10.3072 7.181765 -0.436731082

(25) With reference to FIG. 5B, the second transmission **100b** (FIG. 5B) of the transmission assembly **100** is substantially similar or identical to the first transmission **100a** but is configured to effect a change in pitch of the end effector **40** via translation of a second set of articulation cables “C3,” “C4.” The second transmission **100b** is disposed within the housing **102** (FIG. 3) and may be orientated generally perpendicular to and nested with the first transmission **100a**. In aspects, instead of nesting or overlapping the first and second transmissions **100a**, **100b**, the first and second transmissions **100a**, **100b** may be positioned in side-by-side relation to one another, or, as mentioned above, may be positioned distal/proximal to one another.

(26) The second transmission **100b** includes a rotatable first input shaft **154**, first and second output shafts **156**, **158** each configured to rotate in response to a rotation of the first input shaft **154**, and a second differential gear mechanism **160** operably coupling the first input shaft **154** to the first and second output shafts **156**, **158** and the first and second output shafts **156**, **158** to one another. The first input shaft **154** has a proximal end portion **154a** configured to be drivingly coupled to a corresponding drive member or shaft (not shown) of the instrument drive unit **20** (FIG. 2), and a distal end portion **154b** operably coupled to the second differential gear mechanism **160**. Since the second differential gear mechanism **160** is substantially similar or identical to the first differential gear mechanism **110**, details of the second differential gear mechanism **160** are not provided herein.

(27) The second transmission **100b** further includes third and fourth articulation nuts **168**, **170** operably coupled to the respective first and second output shafts **156**, **158**. The first output shaft **156** may be a left-handed lead screw and the second output shaft **158** may be a right-handed lead screw such that rotation of the output shafts **156**, **158** in the same rotational direction is configured to translate the respective articulation nuts **168**, **170** therealong in opposing axial directions. The articulation cables “C3,” “C4” each have a proximal end portion **172**, **174** operably coupled to the respective first and second output shafts **156**, **158**, and a distal end portion (not explicitly shown) secured to the end effector **40**, such that the articulation cables “C3,” “C4” move axially in opposing directions at a different rate from one another to articulate the end effector **40** relative to the shaft **120** to adjust a pitch of the end effector **40**.

(28) With reference to FIG. 6, another type of transmission **100c** is illustrated that can be used in place of or in addition to one or both of the first and second transmissions **100a**, **100b**. Since the transmission **100c** is substantially similar to transmissions **100a**, **100b**, only those details about the transmission **100c** necessary to appreciate the differences from transmissions **100a**, **100b** will be provided.

(29) The transmission **100c** includes a rotatable first input shaft **180**, first and second outputs **182**, **184** each configured to rotate in response to a rotation of the first input shaft **180**, and a third differential gear mechanism **186** operably coupling the first input shaft **180** to the first and second outputs **182**, **184** and the first and second outputs **182**, **184** to one another. The first input shaft **180** has a proximal end portion **188** configured to be drivingly coupled to a corresponding drive member or shaft (not shown) of the instrument drive unit **20** (FIG. 2), and a distal end portion **190** operably coupled to the third differential gear mechanism **186**. Since the third differential gear mechanism **186** is substantially similar or identical to the first and second differential gear mechanisms **110**, **160** described above, details of the third differential gear mechanism **180** are not provided herein.

(30) The first and second outputs **182**, **184** of the third transmission **100c** may be an articulation wheel rotatably supported in the housing **102** and configured to rotate via the third differential gear mechanism **186**. Articulation cables “C5,” “C6” are fixed to the respective articulation wheels **182**, **184** such that the rotation of the articulation wheels **182**, **184** axially moves the first and second articulation cables “C5,” “C6” in the opposing directions. For example, the articulation cables



“C5,” “C6” may be secured to the wheels **182, 184** by being wrapped about the wheels **182, 184** in opposing circumferential directions from one another such that rotation of the wheels **182, 184** in the same rotational direction results in the translation of the cables “C5,” “C6” in opposing axial directions. In aspects, the outputs **182, 184** may be configured similarly to a capstan or a windlass. (31) It will be understood that various modifications may be made to the embodiments disclosed herein. Therefore, the above description should not be construed as limiting, but merely as exemplifications of various embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended thereto.

## Claims

1. A surgical instrument of a surgical robotic system, the surgical instrument comprising: a housing; a first transmission disposed within the housing and including: a rotatable first input shaft; first and second output shafts configured to rotate in response to a rotation of the first input shaft; and a first differential gear mechanism operably coupling the first input shaft to the first and second output shafts and the first and second output shafts to one another; a shaft extending distally from the housing; an end effector pivotably coupled to a distal end portion of the shaft; and first and second articulation cables each having a proximal end portion operably coupled to the respective first and second output shafts, and a distal end portion secured to the end effector, such that the first and second articulation cables move axially in opposing directions at a different rate from one another to articulate the end effector relative to the shaft in response to the rotation of the first input shaft.
2. The surgical instrument according to claim 1, wherein the first transmission further includes first and second articulation nuts operably coupled to the respective first and second output shafts and configured to translate therealong in response to a rotation of the respective first and second output shafts, the first and second articulation cables being axially fixed to the respective first and second articulation nuts.
3. The surgical instrument according to claim 1, wherein the first differential gear mechanism includes: a ring gear operably coupled to the first input shaft such that the ring gear is configured to be rotated by the first input shaft; first and second spider gears coupled to the ring gear such that the first and second spider gears are configured to rotate about a respective axis thereof relative to the ring gear and with the ring gear around a rotation axis of the ring gear; and first and second side axles, the first side axle operably coupled to the first output shaft and the first and second spider gears, and the second side axle operably coupled to the second output shaft and the first and second spider gears.
4. The surgical instrument according to claim 3, wherein the first side axle has opposing first and second gears, the first gear is operably coupled to the first and second spider gears and the second gear is operably coupled to the first output shaft.
5. The surgical instrument according to claim 4, wherein the second side axle has opposing first and second gears, the first gear of the second side axle is operably coupled to the first and second spider gears and the second gear of the second side axle is operably coupled to the second output shaft.
6. The surgical instrument according to claim 3, wherein the first input shaft has a pinion gear non-rotationally fixed to a distal end portion thereof, the pinion gear being in meshing engagement with the ring gear.
7. The surgical instrument according to claim 3, wherein the ring gear rotates about an axis that is perpendicular to a rotation axis of the first input shaft.
8. The surgical instrument according to claim 1, further comprising: a second transmission nested with or positioned adjacent the first transmission and supported in the housing, wherein the second transmission includes: a rotatable second input shaft; third and fourth output shafts configured to rotate in response to a rotation of the second input shaft; and a second differential gear mechanism

operably coupling the second input shaft to the third and fourth output shafts and the third and fourth output shafts to one another; and third and fourth articulation cables each having a proximal end portion operably coupled to the respective third and fourth output shafts, and a distal end portion secured to the end effector, such that the third and fourth articulation cables move axially in opposing directions at a different rate from one another to articulate the end effector relative to the shaft in response to the rotation of the second input shaft.

9. The surgical instrument according to claim 8, further comprising a wrist assembly movably coupling the end effector to the distal end portion of the shaft, wherein the wrist assembly is configured to allow the end effector to articulate relative to the distal end portion of the shaft to adjust both a pitch and yaw of the end effector.

10. The surgical instrument according to claim 9, wherein the first transmission is configured to change the pitch of the end effector, and the second transmission is configured to change the yaw of the end effector.

11. A surgical robotic system, comprising: a surgical robotic arm; an instrument drive unit configured to be supported on the surgical robotic arm; and a surgical instrument configured to be coupled to and driven by the instrument drive unit, the surgical instrument including: a housing configured to be attached to the instrument drive unit; a first transmission disposed within the housing and including: a rotatable first input shaft drivingly coupled to a corresponding drive shaft of the instrument drive unit; first and second output shafts configured to rotate in response to a rotation of the first input shaft; and a first differential gear mechanism operably coupling the first input shaft to the first and second output shafts and the first and second output shafts to one another; a shaft extending distally from the housing; an end effector pivotably coupled to a distal end portion of the shaft; and first and second articulation cables each having a proximal end portion operably coupled to the respective first and second output shafts, and a distal end portion secured to the end effector, such that the first and second articulation cables move axially in opposing directions at a different rate from one another to adjust a pitch or a yaw of the end effector relative to the shaft in response to the rotation of the first input shaft.

12. The surgical robotic system according to claim 11, wherein the surgical instrument further includes: a second transmission nested with or positioned adjacent the first transmission and supported in the housing, wherein the second transmission includes: a rotatable second input shaft; third and fourth output shafts configured to rotate in response to a rotation of the second input shaft; and a second differential gear mechanism operably coupling the second input shaft to the third and fourth output shafts and the third and fourth output shafts to one another; and third and fourth articulation cables each having a proximal end portion operably coupled to the respective third and fourth output shafts, and a distal end portion secured to the end effector, such that the third and fourth articulation cables move axially in opposing directions at a different rate from one another to articulate the end effector relative to the shaft in response to the rotation of the second input shaft.

13. The surgical robotic system according to claim 12, wherein the surgical instrument further includes a wrist assembly movably coupling the end effector to the distal end portion of the shaft, wherein the wrist assembly is configured to allow the end effector to articulate relative to the distal end portion of the shaft to adjust both the pitch and yaw of the end effector.

14. The surgical robotic system according to claim 12, wherein the first transmission is configured to change the pitch of the end effector, and the second transmission is configured to change the yaw of the end effector.

15. The surgical robotic system according to claim 11, wherein the first transmission further includes first and second articulation nuts operably coupled to the respective first and second output shafts and configured to translate therealong in response to a rotation of the respective first and second output shafts, the first and second articulation cables being axially fixed to the respective first and second articulation nuts.

16. A surgical instrument of a surgical robotic system, the surgical instrument comprising: a housing; a first transmission disposed within the housing and including: a rotatable first input shaft; first and second outputs configured to rotate in response to a rotation of the first input shaft; and a first differential gear mechanism operably coupling the first input shaft to the first and second outputs and the first and second outputs to one another; a shaft extending distally from the housing; an end effector pivotably coupled to a distal end portion of the shaft; and first and second articulation cables each having a proximal end portion operably coupled to the respective first and second outputs, and a distal end portion secured to the end effector, such that the first and second articulation cables move axially in opposing directions at a different rate from one another to change the pitch or yaw of the end effector relative to the shaft in response to the rotation of the first input shaft.

17. The surgical instrument according to claim 16, wherein each of the first and second outputs includes an articulation wheel configured to rotate via the first differential gear mechanism, the first and second articulation cables being attached to the respective articulation wheels, such that the rotation of the articulation wheels axially moves the first and second articulation cables in the opposing directions.

18. The surgical instrument according to claim 16, wherein the first output includes a left-handed lead screw and the second output includes a right-handed lead screw.

19. The surgical instrument according to claim 18, wherein the first transmission further includes first and second articulation nuts operably coupled to the respective left-handed and right-handed lead screws and configured to translate therealong in response to the rotation of the respective left-handed and right-handed lead screws, the first and second articulation cables being axially fixed to the respective first and second articulation nuts.

20. The surgical instrument according to claim 16, further comprising: a second transmission nested with or positioned adjacent the first transmission and supported in the housing, wherein the second transmission includes: a rotatable second input shaft; third and fourth outputs configured to rotate in response to a rotation of the second input shaft; and a second differential gear mechanism operably coupling the second input shaft to the third and fourth outputs and the third and fourth outputs to one another; and third and fourth articulation cables each having a proximal end portion operably coupled to the respective third and fourth outputs, and a distal end portion secured to the end effector, such that the third and fourth articulation cables move axially in opposing directions at a different rate from one another to articulate the end effector relative to the shaft in response to the rotation of the second input shaft.

---