

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385395
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Smith; Russell P. et al.

Cutter head for mining machine

Abstract

A cutter head includes a first member, a cutting bit, and a second member. The first member includes a first end and a second end and includes a first mass. The cutting bit is coupled to the first member proximate the second end. The cutting bit includes a cutting edge rotatable about the axis. The second member is rotatable about the axis and includes a second mass eccentrically positioned with respect to the axis. Rotation of the second mass causes the first member and the cutting bit to oscillate.

Inventors: Smith; Russell P. (New South Wales, AU), Hunter; Andrew D (New South Wales, AU), Lugg; Peter A. (Queensland, AU), Schirmer; Ian B. (Queensland, AU), Keech; Geoffrey W (Queensland, AU), Coates; Christopher (Queensland, AU), Neilson; Bradley M. (New South Wales, AU)

Applicant: Joy Global Underground Mining LLC (Warrendale, PA)

Family ID: 50273716

Assignee: Joy Global Underground Mining LLC (Warrendale, PA)

Appl. No.: 18/349574

Filed: July 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240125232 A1	Apr. 18, 2024

Related U.S. Application Data

continuation parent-doc US 16678656 20191108 US 11371346 20220628 child-doc US 17745561
continuation parent-doc US 15266386 20160915 US 10472961 20191112 child-doc US 16678656
continuation parent-doc US 14028511 20130916 US 9470087 20161018 child-doc US 15266386

Publication Classification

Int. Cl.: E21C35/23 (20060101); E21C25/06 (20060101); E21C25/16 (20060101); E21C27/16 (20060101); E21C31/02 (20060101); E21C35/00 (20060101); E21C35/24 (20060101); E21C41/16 (20060101); E21D9/10 (20060101)

U.S. Cl.:

CPC E21C35/23 (20130101); E21C25/06 (20130101); E21C25/16 (20130101); E21C27/16 (20130101); E21C31/02 (20130101); E21C35/00 (20130101); E21C35/24 (20130101); E21C41/16 (20130101); E21D9/102 (20130101)

Field of Classification Search

CPC: E21C (35/23)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1093787	12/1913	Kuhn et al.	N/A	N/A
1304352	12/1918	Morgan	N/A	N/A
1340731	12/1919	Morgan	N/A	N/A
1510628	12/1923	Morgan	N/A	N/A
1735583	12/1928	Morgan	N/A	N/A
1953326	12/1933	Morgan	N/A	N/A
2336335	12/1942	Zublin	N/A	N/A
2336337	12/1942	Zublin	N/A	N/A
2466709	12/1948	Karr	N/A	N/A
2511267	12/1949	Jacob	N/A	N/A
2517267	12/1949	Watson	N/A	N/A
2619338	12/1951	Lindgren	N/A	N/A
2619339	12/1951	Cartlidge	N/A	N/A
2654586	12/1952	Berry	N/A	N/A
2659565	12/1952	Johnson et al.	N/A	N/A
2659585	12/1952	Mccallum	N/A	N/A
2745651	12/1955	Herrmann	N/A	N/A
2756039	12/1955	Barrett	N/A	N/A
2776823	12/1956	Barrett	N/A	N/A
3115588	12/1962	Hueter	N/A	N/A
3157437	12/1963	Gonski	N/A	N/A
3197256	12/1964	Hlinsky	N/A	N/A
3302974	12/1966	Hlinsky	N/A	N/A
3306663	12/1966	Webster	N/A	N/A
3353871	12/1966	Arentzen	N/A	N/A
3355215	12/1966	Haspert et al.	N/A	N/A

3374033	12/1967	Arentzen	239/97	E21C 35/23
3408109	12/1967	Lockwood	N/A	N/A
3412816	12/1967	Lautsch	N/A	N/A
3446535	12/1968	Ernst	N/A	N/A
3554604	12/1970	Sugden	N/A	N/A
3647263	12/1971	Lauber et al.	N/A	N/A
3663054	12/1971	Dubois	N/A	N/A
3719404	12/1972	Sterner	N/A	N/A
3729056	12/1972	Paurat	N/A	N/A
3840271	12/1973	Sugden	N/A	N/A
3860292	12/1974	Bechem	N/A	N/A
3922017	12/1974	Cobb	N/A	N/A
3929378	12/1974	Frenyo et al.	N/A	N/A
3972571	12/1975	Benkowski	N/A	N/A
3995907	12/1975	Dubois	N/A	N/A
4005905	12/1976	Dubois	N/A	N/A
4087131	12/1977	Peterson et al.	N/A	N/A
4096917	12/1977	Harris	N/A	N/A
4108494	12/1977	Kogler	N/A	N/A
4230372	12/1979	Marten	N/A	N/A
4239290	12/1979	Goris	299/17	E21C 25/60
4248481	12/1980	Stoltefuss	N/A	N/A
4273383	12/1980	Grisebach	N/A	N/A
4302054	12/1980	Haskew et al.	N/A	N/A
4372403	12/1982	Beeman	N/A	N/A
4377311	12/1982	Seller	N/A	N/A
4470635	12/1983	Paurat et al.	N/A	N/A
4516807	12/1984	Eagles	N/A	N/A
4548442	12/1984	Sugden et al.	N/A	N/A
4589701	12/1985	Beckmann et al.	N/A	N/A
4643483	12/1986	Brooks et al.	N/A	N/A
4647112	12/1986	Demoulin et al.	N/A	N/A
4662684	12/1986	Marten	N/A	N/A
4682819	12/1986	Masse	N/A	N/A
4741577	12/1987	Sato et al.	N/A	N/A
4750513	12/1987	Griffin et al.	N/A	N/A
4755002	12/1987	Parrott	N/A	N/A
4760513	12/1987	Edwards	N/A	N/A
4796713	12/1988	Bechem et al.	N/A	N/A
4838614	12/1988	Pentith et al.	N/A	N/A
4838615	12/1988	Gerald	N/A	N/A
4848486	12/1988	Bodine	N/A	N/A
4878714	12/1988	Franz et al.	N/A	N/A
4946227	12/1989	Paul	37/189	E02F 5/287
4968098	12/1989	Hirsch et al.	N/A	N/A
5028092	12/1990	Coski	N/A	N/A
5050934	12/1990	Brandl et al.	N/A	N/A
5087102	12/1991	Kiefer	N/A	N/A
5112111	12/1991	Addington et al.	N/A	N/A
5114213	12/1991	Kornecki	299/17	E21C 35/23

5190353	12/1992	Bechem	N/A	N/A
5205612	12/1992	Sugden et al.	N/A	N/A
5210997	12/1992	Mountcastle, Jr.	N/A	N/A
5234257	12/1992	Sugden et al.	N/A	N/A
5601153	12/1996	Ensminger et al.	N/A	N/A
5676125	12/1996	Kelly et al.	N/A	N/A
5697733	12/1996	Marsh, Jr.	N/A	N/A
5938288	12/1998	Saint-Pierre et al.	N/A	N/A
6086257	12/1999	Lee	N/A	N/A
6364418	12/2001	Schwoebel	299/60	E21B 7/18
6561590	12/2002	Sugden	N/A	N/A
6857706	12/2004	Hames et al.	N/A	N/A
6938702	12/2004	Saha et al.	N/A	N/A
7182407	12/2006	Peach et al.	N/A	N/A
7325882	12/2007	Sugden et al.	N/A	N/A
7384104	12/2007	Sugden	N/A	N/A
7431402	12/2007	Peach et al.	N/A	N/A
7490911	12/2008	Steinberg et al.	N/A	N/A
7695071	12/2009	Jackson et al.	N/A	N/A
7731298	12/2009	Merten et al.	N/A	N/A
7934776	12/2010	De Andrade et al.	N/A	N/A
7954735	12/2010	Belotserkovsky	N/A	N/A
8079647	12/2010	Yao et al.	N/A	N/A
8276991	12/2011	Thomson	N/A	N/A
8328292	12/2011	De Andrade et al.	N/A	N/A
8636324	12/2013	Skea	N/A	N/A
8690262	12/2013	Ebner et al.	N/A	N/A
8727450	12/2013	De Andrade et al.	N/A	N/A
9470087	12/2015	Smith et al.	N/A	N/A
2002/0001009	12/2001	Gasvoda et al.	N/A	N/A
2002/0093239	12/2001	Sugden	N/A	N/A
2005/0200192	12/2004	Sugden et al.	N/A	N/A
2007/0000578	12/2006	Matschullat et al.	N/A	N/A
2007/0001009	12/2006	Miyake et al.	N/A	N/A
2007/0193810	12/2006	Steinberg et al.	N/A	N/A
2008/0015653	12/2007	Siejko et al.	N/A	N/A
2008/0156531	12/2007	Boone et al.	N/A	N/A
2009/0058172	12/2008	De Andrade et al.	N/A	N/A
2009/0066148	12/2008	Willison	N/A	N/A
2009/0127918	12/2008	Yao et al.	N/A	N/A
2010/0019563	12/2009	Thomson	N/A	N/A
2010/0260563	12/2009	Conroy et al.	N/A	N/A
2011/0062768	12/2010	Van Zyl et al.	N/A	N/A
2011/0181097	12/2010	Skea	N/A	N/A
2012/0098325	12/2011	Junker et al.	N/A	N/A
2013/0057044	12/2012	De Andrade et al.	N/A	N/A
2013/0315063	12/2012	Rcz et al.	N/A	N/A
2014/0077578	12/2013	Smith et al.	N/A	N/A
2014/0091612	12/2013	Rowher et al.	N/A	N/A
2014/0178155	12/2013	Feasey	N/A	N/A

2015/0152728	12/2014	Hartwig et al.	N/A	N/A
2017/0204666	12/2016	Galler et al.	N/A	N/A
2017/0211383	12/2016	Lugg et al.	N/A	N/A
2017/0342829	12/2016	De Sousa et al.	N/A	N/A
2018/0051561	12/2017	Daher et al.	N/A	N/A
2018/0051562	12/2017	Daher et al.	N/A	N/A
2018/0087379	12/2017	Lugg et al.	N/A	N/A
2018/0203820	12/2017	Missoni et al.	N/A	N/A
2019/0001190	12/2018	Robinson	N/A	N/A
2020/0002400	12/2019	Li et al.	N/A	N/A
2020/0347723	12/2019	Daher et al.	N/A	N/A
2021/0102463	12/2020	Daher et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
466244	12/1971	AU	N/A
466244	12/1971	AU	N/A
2018203820	12/2017	AU	N/A
2018203820	12/2019	AU	N/A
2141984	12/1995	CA	N/A
2141984	12/2001	CA	N/A
2884641	12/2013	CA	N/A
2884641	12/2020	CA	N/A
2015000627	12/2014	CL	N/A
101778998	12/2009	CN	N/A
101828004	12/2009	CN	N/A
102061914	12/2010	CN	N/A
102305067	12/2011	CN	N/A
102513998	12/2011	CN	N/A
102587911	12/2011	CN	N/A
102606154	12/2011	CN	N/A
102704927	12/2011	CN	N/A
102733803	12/2011	CN	N/A
202500560	12/2011	CN	N/A
101778998	12/2011	CN	N/A
101828004	12/2012	CN	N/A
202991028	12/2012	CN	N/A
103206213	12/2012	CN	N/A
102606154	12/2013	CN	N/A
103498671	12/2013	CN	N/A
102587911	12/2013	CN	N/A
104047603	12/2013	CN	N/A
102704927	12/2013	CN	N/A
102061914	12/2014	CN	N/A
104500086	12/2014	CN	N/A
204283458	12/2014	CN	N/A
104500086	12/2016	CN	N/A
103498671	12/2017	CN	N/A
1440261	12/1935	DE	N/A
1440261	12/1969	DE	N/A

4123307	12/1991	DE	N/A
4440261	12/1995	DE	N/A
4440261	12/1996	DE	N/A
19900906	12/1999	DE	N/A
176234	12/1985	EP	N/A
176235	12/1985	EP	N/A
176235	12/1987	EP	N/A
329915	12/1988	EP	N/A
329915	12/1992	EP	N/A
2214963	12/1988	GB	N/A
2214963	12/1991	GB	N/A
55040058	12/1979	JP	N/A
55040058	12/1979	JP	N/A
55040058	12/1979	JP	N/A
55040058	12/1979	JP	N/A
02147793	12/1989	JP	N/A
02147793	12/1989	JP	N/A
5540058	12/2013	JP	N/A
2044125	12/1994	RU	N/A
2142561	12/1998	RU	N/A
2187640	12/2001	RU	N/A
2209979	12/2002	RU	N/A
2209979	12/2002	RU	N/A
2276728	12/2005	RU	N/A
2441155	12/2011	RU	N/A
323552	12/1971	SU	N/A
514097	12/1975	SU	N/A
519117	12/1975	SU	N/A
581263	12/1976	SU	N/A
619117	12/1977	SU	N/A
750061	12/1979	SU	N/A
804832	12/1980	SU	N/A
962626	12/1981	SU	N/A
1328521	12/1986	SU	N/A
1712599	12/1991	SU	N/A
1731946	12/1991	SU	N/A
1744249	12/1991	SU	N/A
9722424	12/1996	WO	N/A
0043637	12/1999	WO	N/A
0046486	12/1999	WO	N/A
0201045	12/2001	WO	N/A
02066793	12/2001	WO	N/A
03062587	12/2002	WO	N/A
03089761	12/2002	WO	N/A
2006075910	12/2005	WO	N/A
2012156843	12/2011	WO	N/A
2012156843	12/2012	WO	N/A
2016055087	12/2015	WO	N/A
2020043637	12/2019	WO	N/A
2020046486	12/2019	WO	N/A

OTHER PUBLICATIONS

Peruvian Patent Office Technical Report for Application No. 2001-2019 dated Mar. 19, 2024 (5 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2013/060017 dated Apr. 15, 2014. cited by applicant

PCT/US2013/060017 International Search Report and Written Opinion dated Apr. 15, 2014 (18 Pages). cited by applicant

Chilean Office Action for Application No. 2015-000627 dated Oct. 7, 2017. cited by applicant

International Mining, ““DynaCut Technology Achieving Breakthroughs,”” web page accessed Nov. 22, 2019. cited by applicant

Peruvian Office Action for Application No. 000367-2015 dated Jul. 19, 2019 (19 pages including English translation). cited by applicant

Second Office Action with English translation from the State Intellectual Property Office of the People's Republic of China for Application No. 201380053676.0 dated Nov. 2, 2016 (20 pages). cited by applicant

Supplementary European Search Report from the European Patent Office for Application No. 13837734.6 dated Jul. 16, 2016 (1 page). cited by applicant

Second Australian Examination Report for Application No. 2013315063 dated Nov. 9, 2017 (3 pages). cited by applicant

Fourth Office Action of the People's Republic of China for Application No. 201380053676.0 dated Jan. 3, 2018. cited by applicant

European Extended Search Report for Application No. 17201425.0 dated Mar. 1, 2018 (7 pages). cited by applicant

European Extended Search Report for Application No. 17201428.40 dated Jun. 18, 2018 (10 pages). cited by applicant

European Partial Search Report for Application No. 17201428.4 dated Mar. 8, 2018 (12 pages). cited by applicant

Australian Patent Office Examination Report No. 1 for Application No. 2018203820 dated Aug. 12, 2019 (4 pages). cited by applicant

Mining3 Mining, “CRCMining Joy Global Oscillating Disc Cutter {ODC} Hard Rock Culling Machine,” <https://www.youtube.com/watch?v=anyPQWkH4rM> web page accessed Oct. 24, 2019. cited by applicant

Brazilian Patent Office Action for Application No. 122020010678 dated May 27, 2020 (58 pages including statement of relevance). cited by applicant

Chilean Patent Office Search Report and Examiner's Report for Application No. 201901190 dated Mar. 11, 2020 (18 pages including statement of relevance). cited by applicant

Chinese Patent Office Action for Application No. 201910052648.6 dated May 6, 2020 (13 pages including English Translation). cited by applicant

Examination Report No. 2 issued by the Australian Government for Application No. 2018203820 dated Aug. 5, 2020 (3 pages). cited by applicant

Extended European Search Report for Application No. 19218632.8 dated Apr. 7, 2020 (7 pages). cited by applicant

Extended European Search Report for Application No. 19218675.7 dated Apr. 3, 2020 (7 pages). cited by applicant

Extended European Search Report for Application No. 19218676.5 dated Apr. 2, 2020 (5 pages). cited by applicant

Chilean Patent Office Action and Search Report for Application No. 202002400 dated Jun. 26, 2021 (14 pages Including statement of relevance). cited by applicant

Chinese Patent Office Second Office Action for Application No. 201910052648.6 dated Mar. 4,

2021 (6 pages Including English summary). cited by applicant
Canadian Patent Office Action for Application No. 3115588 dated Sep. 7, 2022 (4 pages). cited by applicant
European Patent Office Action for Related Application No. 19218675.7 dated Jan. 20, 2023 (5 pages). cited by applicant
Australian Examination Report for Application No. 2023200238 dated May 6, 2024 (4 pages). cited by applicant

Primary Examiner: Kreck; Janine M

Attorney, Agent or Firm: Husch Blackwell LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a divisional of prior-filed, co-pending U.S. patent application Ser. No. 17/745,561, filed May 16, 2022, which is a continuation of U.S. patent application Ser. No. 16/678,656, filed Nov. 8, 2019, which is a continuation of U.S. patent application Ser. No. 15/266,386, filed Sep. 15, 2016, which is a continuation of U.S. patent application Ser. No. 14/028,511, filed Sep. 16, 2013, which claims the benefit of and priority to U.S. Provisional Patent Application No. 61/701,256, filed Sep. 14, 2012. The entire contents of these applications are incorporated by reference herein.

BACKGROUND

- (1) The present invention relates to underground mining machines, and in particular to a cutter head for an underground mining machine.
- (2) A hard rock continuous miner includes a cutter head having an oscillating cutting disc. The oscillating disc cutter transmits all of the dynamic cutting forces through the bearings, and the life of the bearings are limited due to the high loads and high speed of the cutting discs. In addition, the oscillating discs require large face seal surface areas in the primary cutting area, while the cutting discs oscillate at frequencies typically around 50 Hz. It is difficult to seal a large area with a high surface velocity, and this is further complicated due to the fact that the cutting operation generates a large amount of highly abrasive rock particles. The combination of the contaminated environment and high surface velocity accelerates wear on the seals and decreases the working life of the seals. Furthermore, the deficiencies in the seals and the highly loaded bearings can combine to even further increase maintenance and replacement of the disc cutter assembly. These factors also limit the frequency and the eccentricity of oscillation of the cutting discs, thereby limiting the total power available for rock cutting
- (3) In addition, oscillating disc cutter systems typically lack a means for directly monitoring the behavior of the disc cutter at the cutting surface. As a result, it is difficult to sense a change in the cutting conditions (e.g., when the hardness of the rock changes). Thus, the operator is unable to control the disc cutter to optimize the cutting performance.

SUMMARY

- (4) In some aspects the invention provides a cutter head for a mining machine including a frame and a boom movably coupled to the frame. The cutter head includes a first member, a cutting bit, and a second member. The first member includes a first end and a second end and includes a first mass. The cutting bit is coupled to the first member proximate the second end and includes a cutting edge. The second member is rotatable about an axis and includes a second mass eccentrically positioned with respect to the axis. The second mass and the first mass at least partially define a combined center of mass. Rotation of the second mass causes the first member

and the cutting bit to oscillate about the combined center of mass along a closed path.

(5) In other aspects the invention provides a mining machine including a frame for supporting the machine on a support surface, a boom, and a cutter head. The boom includes a first end coupled to the frame and a second end positioned away from the frame. The cutter head a cutter head coupled to the second end of the boom, the cutter head includes a first member, a cutting bit, and a second member. The first member defines a first end and a second end and includes a first mass and a coupling member supporting the first mass on the second end of the boom. The cutting bit is coupled to the first member proximate the second end and includes a cutting edge. The first member and the cutting bit at least partially define a first mass center. The second member is rotatable about an axis and includes a second mass eccentrically positioned with respect to the axis. The second mass defines a second mass center. The first mass center and the second mass center define a combined center of mass. Rotation of the second mass about the axis causing the first member and the cutting bit to oscillate about the combined center of mass along a closed path.

(6) In still other aspects the invention provides a mining machine including a frame for supporting the machine on a support surface, a boom, a cutter head, and a coupling member. The boom includes a first end coupled to the frame and a second end positioned away from the frame; the second end includes a bracket. The cutter head includes a first member and a cutting bit. The first member includes a first end coupled to the bracket and a second end. The cutting bit is coupled to the first member proximate the second end. The coupling member supporting the first member on the second end of the boom to facilitate oscillation of the cutter head relative to the boom.

(7) In still other aspects the invention provides a cutter head for a mining machine including a frame and a boom movably coupled to the frame. The cutter head includes a first member, a cutting bit, a fluid conduit, and a plurality of nozzles. The first member includes a first end and a second end and is movable relative to the second end. The cutting bit is coupled to the first member proximate the second end. The fluid conduit extends through the first member and is configured to be in fluid communication with a fluid source. The nozzles are positioned on the cutting edge, the nozzles in fluid communication with the fluid conduit.

(8) In still other aspects, the invention provides a method for removing material from a rock wall. The method includes moving a cutting edge through the rock wall to create a first slot in the rock wall; moving the cutting edge through the rock wall to create a second slot in the rock wall, the second slot being separated from the first slot by an uncut portion, the uncut portion defining a base surface attached to the wall; cutting a notch into the base surface of the uncut portion; and applying a force on the uncut portion to break the uncut portion away from the wall.

(9) In still other aspects, the invention provides a method for controlling a mining machine. The method includes sensing a value of an indicator of a cutting efficiency of a cutter head; comparing the sensed value with a desired value; modifying an operating parameter in a first direction from an initial value to a second value; detecting the change in the indicator of cutting efficiency; and when the change in the indicator of the cutting efficiency represents an improvement, modifying the operating parameter further in the first direction to a third value.

(10) In still other aspects, the invention provides a method for controlling a mining machine. The method includes sensing a first value of an indicator of a cutting efficiency of a first cutter; sensing a second value of an indicator of cutting efficiency of a second cutter; comparing the first value with the second value to detect whether the first value is less than the second value; when the first value is less than the second value, modifying an operating parameter of the second cutter so that the second value matches the first value.

(11) Other aspects of the invention will become apparent by consideration of the detailed description and accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of a mining machine engaging a mine wall.
- (2) FIG. 2 is a front perspective view of the mining machine of FIG. 1.
- (3) FIG. 3 is a perspective view of a cutter head.
- (4) FIG. 3A is a side perspective view of the cutter head of FIG. 3.
- (5) FIG. 4 is an exploded front perspective view of the cutter head of FIG. 3.
- (6) FIG. 5 is an exploded rear perspective view of the cutter head of FIG. 3.
- (7) FIG. 6 is a section view of the cutter head of FIG. 3 taken along the line 6-6.
- (8) FIG. 7 is a side view of a cutter head engaging a mine wall.
- (9) FIG. 8 is an enlarged side view of a cutter head engaging a mine wall.
- (10) FIG. 9 is a perspective view of a cutter head according to another embodiment.
- (11) FIG. 9A is a side perspective view of the cutter head of FIG. 9.
- (12) FIG. 10 is an exploded perspective view of a cutter head according to another embodiment.
- (13) FIG. 11 is a section view of the cutter head of FIG. 10 taken along the line 11-11.
- (14) FIG. 12 is a section view of a cutter head according to another embodiment.
- (15) FIG. 13 is a section view of the cutter head of FIG. 12 showing a fluid flow path.
- (16) FIG. 14 is a perspective view of a cutting bit.
- (17) Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising” or “having” and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. The terms “mounted,” “connected” and “coupled” are used broadly and encompass both direct and indirect mounting, connecting and coupling. Further, “connected” and “coupled” are not restricted to physical or mechanical connections or couplings, and can include electrical or hydraulic connections or couplings, whether direct or indirect. Also, electronic communications and notifications may be performed using any known means including direct connections, wireless connections, etc.

DETAILED DESCRIPTION

- (18) As shown in FIGS. 1 and 2, a mining machine 10 includes a frame 14, a boom 18, and a cutter head 22 supported on the boom 18 for engaging a mine wall 26. The frame 14 includes tracks 30 for moving the frame 14 over a support surface or mine floor (not shown). The frame 14 further includes a gathering head 32 positioned adjacent the mine floor proximate the cutter head 22. The gathering head 32 includes a deck 34 and rotating fingers 38 that urge cut material onto a conveyor (not shown). The frame 14 also includes a pair of arms 42 pivotably coupled to the frame 14. The arms 42 can be extended to a position forward of the gathering head 32 in order to direct cut material onto the deck 34.
- (19) The boom 18 is pivotably coupled to the frame 14 at one end, and operation of one or more first actuators 46 pivot, extend, and retract the boom 18 relative to the frame 14. In the illustrated embodiment, the first actuators 46 are hydraulic cylinders. Also, in the illustrated embodiment, the boom 18 pivotably supports the cutter head 22 on an end of the boom 18 opposite the frame 14. A second actuator 50 (FIG. 2) pivots the cutter head 22 relative to the boom 18. The cutter head 22 is positioned such that the cutter head 22 engages the mine wall 26 with a controlled force. Operation of the first actuators 46 moves the boom 18 relative to the frame 14, thereby moving the cutter head 22 over the mine wall 26 to produce a desired cutting profile. The angle between the cutter head 22 and the boom 18 is continuously monitored. Sensor data for the angle is provided to a control system for controlling the position of the boom 18. The speed of movement of the boom 18 can be

adjusted to match the excavation rate, or the energy delivered to the mine wall **26**.

(20) As shown in FIG. 3, a coupling member or mounting bracket **58** supports the cutter head **22** for pivoting movement relative to the boom **18** (FIG. 2). In the embodiment of FIG. 3, the cutter head **22** includes a first end **62**, a second end **66**, and a support plate **70** proximate the first end **62**. In the illustrated embodiment the cutter head **22** includes a coupling member or arm **60** for supporting the cutter head **22** on the mounting bracket **58**. Multiple pins **74** are positioned around the perimeter of the support plate **70** and extend through the support plate **70** and the arm **60**. Each pin **74** supports a spring **78**, which reacts to the forces exerted on the cutter head **22** by the mine wall **26**. The springs **78** also isolate the boom **18** against transmission of vibrational forces from the cutter head **22**. In some embodiments, each pin **74** also supports a damper. Referring to FIG. 3A, the geometry and the mass of the cutter head **22** defines a combined center of mass **80** that is generally positioned between the first end **62** and the cutting bit **86**. The size, shape, and density of the components of the cutter head **22** may be modified to adjust the position of the center of mass **80** relative to the cutting bit **86**.

(21) In other embodiments, a different type of cutter head (including a cutter head having a conventional oscillating disc cutter) may be coupled to the arm **60** by the pins **74** and springs **78**. In still other embodiments, a plate spring or hinge is coupled between the support plate **70** and the boom **18**. The plate spring is made from a fatigue-resistant material such as a carbon-fiber composite. The plate spring eliminates the need for mechanical pivots and reduces wear on the coupling, thereby improving the working life.

(22) The cutter head **22** is shown in FIGS. 4-6. The cutter head **22** includes a cutting bit **86** proximate the second end **66**, a first or inertial member **90** coupled to the cutting bit **86**, and a second or exciter member **94**. In the illustrated embodiment, the cutting bit **86** is formed as a ring or disc that is secured to the inertial member **90** to move with the inertial member **90**. The cutting bit **86** includes a cutting edge **88** (FIG. 6). The cutter head **22** further includes a first motor **102**, a second motor **106**, a slew plate or bearing **110** coupled to the inertial member **90**, and a support plate **114** for supporting the first motor **102** and the second motor **106**. The slew bearing **110** includes a ring gear **118** that is driven by the second motor **106**. As best shown in FIG. 6, the first motor **102** drives a first shaft **126** (FIG. 6) to rotate the exciter member **94** about an axis of rotation **98**. In one embodiment, the second motor **106** rotates the ring gear **118** and the inertial member **90** about the axis **98**.

(23) In the embodiment of FIGS. 4-6, the inertial member **90** has a generally frusto-conical shape and tapers in a direction from the first end **62** toward the second end **66**. More particularly, the inertial member **90** includes a main body **130**, a housing **133** positioned proximate a narrow end of the main body **130**, and a sleeve **138** that is positioned within the body **130** and is coupled to the housing **133**. The housing **133** supports the cutting bit **86** proximate the second end **66** of the cutter head **22**. In other embodiments, the inertial member **90** may have another construction.

(24) The tapered shape provides clearance for the cutting bit **86** to engage the mine wall **26** while still permitting the boom **18** to position the cutter head **22** and produce an optimum cutting profile. The position and shape of the inertial member **90** are inter-related design factors, and the tapered shape allows a minimum amount of mass to provide a relatively high “equivalent” mass or moment of inertia. In addition, the tapered shape facilitates cutting along tight corners and performing cut-and-break mining as described in more detail below. It is understood that the cutter head **22** could be used for cutting a mine wall according to other methods (i.e., the cutter head **22** is not limited to cut-and-break mining methods). In general, the tapered shape provides a versatile cutter head **22** that permits a variety of cutting profiles while positioning the inertial member **90** as close to the cutting bit **86** as practicable to improve the efficiency of the cutting operation.

(25) In other embodiments, the inertial member **90** may have a different shape or position, depending on the tunnel dimensions, the geometry of the boom, and the optimum effective mass. The inertial member **90** may include other configurations, such as a rotating overhung mass **142**

(illustrated in FIG. 2) that allows clearance in the cutting process, or a plate shaped mass.

(26) Referring to FIG. 6, the exciter member **94** is positioned within body **130** and particularly within the sleeve **138** of the inertial member **90**. The exciter member **94** is supported for rotation relative to the inertial member **90** by high-speed bearings **144**. The exciter member **94** is elongated and coupled to the first shaft **126** for rotation about the axis of rotation **98**. The exciter member **94** is a non-contact eccentric and includes at least one lobe **134** that is eccentrically positioned with respect to the axis of rotation **98**.

(27) The exciter member **94** is rotated by the first motor **102**, and the rotation of the exciter member **94** “excites” the inertial member **90** and the connected cutting bit **86** and induces a desired oscillation in the inertial member **90** and cutting bit **86**. As shown in FIG. 3A, the inertial member **90** defines a first mass center **132** that oscillates or orbits about the combined center of mass **80** at a first effective radius. The exciter member **94** defines a second mass center **136** that oscillates or orbits about the combined center of mass **80** at a second effective radius. As shown, movement of the exciter member **94** causes the second mass center **136** to orbit about the combined center of mass **80**, thereby causing the first mass center **132** to orbit about the combined center of mass **80**. In the illustrated embodiment, the second mass center **136** has a larger effective radius than the first mass center **132**. The cutter head **22** moves in circular movement about a point **140**. Stated another way, a reference line **146** extending between the cutting bit **86** and point **140** traces a conical shape as the first mass center **132** oscillates, and the cutting bit **86** moves in a closed path **148** having a dimension that is proportional to the eccentricity of the oscillating motion induced on the inertial member **90**. In the illustrated embodiment, the path **148** is circular. The reference line **146** defines a radius of the cutting bit **86** from the point **140**, and the point **140** defines the apex of the conical shape while the cutting bit **86** moves along the base of the conical shape.

(28) More specifically, the dimension of the path **148** is proportional to the mass of the exciter member **94** and the eccentricity (i.e., axial offset) of the exciter member **94**. The dimension is also inversely proportional to the mass of the inertial member **90**. For example, in one embodiment the inertial member **90** has an effective mass of 1000 kg at the cutter, while the exciter member **94** has an effective eccentric mass of 40 kg at the cutter and an eccentricity (i.e., an amplitude of eccentric oscillation) of 50 mm. The resultant oscillation of the inertial member **90** is proportional to the product of the mass and eccentricity of the exciter member **94** divided by the mass of the inertial member **90**; therefore the excitation causes the inertial member of 1000 kg to oscillate or vibrate with an amplitude of ± 2 mm (i.e., the radius of the path **148** of the cutting bit **86** is 2 mm). In other embodiments, the relative masses of the inertial member **90** and the exciter member **94** as well as the eccentricity of the exciter member **94** can be modified to produce a desired oscillation response in the inertial member **90**.

(29) When the cutting bit **86** contacts mine wall, the wall exerts a reaction force on the cutting bit **86** that resists the oscillating motion of the inertial member **90**. To compensate, the feed force is exerted on the cutter head **22** by the boom **18** to urge the cutting bit **86** towards the wall. The oscillation of the inertial member **90** and the exciter member **94** is controlled so that the inertial member **90** has a maximum velocity in the direction of the cut when the cutting bit **86** engages the mine wall.

(30) The cutter head **22** directly secures together the inertial member **90** and the cutting bit **86**. Unlike conventional oscillating disc cutters in which all of the dynamic cutting forces are transmitted from a cutting bit and through a bearing arrangement into an inertial mass, the cutter head **22** provides a direct connection between the cutting bit **86** and the inertial member **90**. This direct connection permits the inertial member **90** to absorb a significant amount of the dynamic cutting force before the load is transmitted to the bearings **110**, **144**, thereby reducing the load on the bearings **110**, **144**. In one embodiment, the high-speed bearing **144** is subject to approximately 5% of the total dynamic cutting forces. The bearings **110**, **144** are also sealed from the rock cutting zone. Furthermore, the cutter head **22** eliminates dynamic seals in the primary rock cutting zone

operating at high speed over large areas. As a result, it is possible to increase both the frequency and the eccentricity of cutter head **22** while also improving the working life of the cutter head **22**. Therefore, the cutter head **22** improves the efficiency of the cutting operation. The increased frequency and eccentricity permit the cutting bit **86** to exert more dynamic power on the wall to break rock without requiring larger cutter components.

(31) In one embodiment, the frequency (i.e., rotational speed) and the mass of the inertial member **90** as well as the feed force provided by the boom **18** are generally the same as that of a conventional oscillating disc cutter, but the mass and eccentric radius of the exciter member **94** are increased. The increased excitation increases inertial member **90** travel (i.e., oscillation amplitude) and results in greater impact energy for the rock cutting process. In one embodiment, the impact energy is three to four times more than the impact energy provided by a conventional oscillating disc cutter.

(32) Alternatively, a smaller cutter head **22** can be used to generate the same cutting forces as a conventional cutter head, permitting a lower cost machine that can access and operate in tightly constrained areas of the underground mine. For example, in one embodiment, the inertial member **90** is sized with the same mass and oscillates at the same frequency as a conventional oscillating disc cutter, but only requires half of the feed force (i.e., the external force applied to the cutter head by the boom **18**) to impart the same amount of energy into the rock.

(33) FIGS. **1**, **7**, and **8** illustrate a method for cutting rock from the mine wall **26**. Although the method described below refers to the cutter head **22**, it is understood that the method may be performed using a cutter head having a different shape or disc cutter configuration, such as a conventional oscillating disc cutter. In one embodiment, the perimeter of the mine wall **26** is first cut (i.e., a wall relief cut) to define a profile **150** (FIG. **1**) of the mine wall **26**. The profile **150** may be cut by multiple passes of the cutter head **22** in order to increase the depth to a desired level, such as the maximum practical cutting depth of the cutter head **22**. In one embodiment, the depth of the cut is in the range of approximately 200 mm to approximately 400 mm. After the profile **150** is formed, the cutter head **22** subsequently cuts multiple slots **154** into the mine wall **26**, leaving uncut rock sections **158** adjacent the slots **154**. Cutting the slots **154** may require multiple passes in order to cut the slots **154** to the desired depth. In the illustrated embodiment, the slots **154** are cut in a generally horizontal direction. In other embodiments, the slots **154** may be cut vertically or at an angle across the mine wall **26** in order to facilitate fracturing. Also, the terms “tall”, “high”, and “height” as used herein to describe this method generally refer to a vertical dimension of the slots **154** and the uncut sections **158** as shown in the embodiment of FIGS. **1**, **7** and **8**. Although the embodiment illustrated in these figures shows the slots **154** and uncut sections **158** in a substantially horizontal orientation, it is understood that the slots **154** and uncut sections **158** could be formed in a different orientation, in which case other terms may be used to refer to the transverse dimension of these features.

(34) As the cutter head **22** makes a final cutting pass through a slot **154**, (e.g., as the cutter head **22** cuts the slot **154** to a desired depth), the protruding (i.e., uncut) rock sections **158** above and below the slot **154** are undercut and overcut, respectively, to a maximum allowable depth of the cutting bit **86**. That is, a base of each side of the rock section **158** is notched to create a fracture line adjacent the mine wall **26** (FIG. **7**). The ends of the protruding rock section **158** are similarly relieved during the perimeter cut. After forming the initial notch **160**, the cutter head **22** contacts the protruding rock section **158**. The force exerted on the cutter head **22** by the boom **18** and/or the vibration of the inertial member **90** causes the protruding rock section **158** to break away from the wall **26**. Alternatively, the mining machine **10** may include a breaker attachment (for example, mounted on a separate boom from the cutter head) that is applied against the rock section **158** to break the rock section **158** along the fracture line.

(35) Unlike conventional methods that require cutting virtually all of the rock on the mine wall **26**, the method described above permits the operator to selectively cut rock in such a way to maximize

the potential for rock fracturing, and subsequently breaking uncut rock sections **158**. Depending on the type of rock, the presence of shear planes, and the size of the mine wall **26**, the “cut-and-break” method described above can mine the rock such that the ratio between the amount of rock that is broken from the wall **26** to the amount of rock that is cut from the wall **26** exceeds 1:1. That is, the method requires cutting less than half of the rock that is removed from the wall **26**. The method substantially reduces cutting time and energy consumption, and also reduces the wear on the cutting bit **86** and other components of the cutter head **22**. In some embodiments, the method described above more than doubles the productivity in underground entry development, when compared with conventional rock cutting processes.

(36) In one embodiment, the cutting bit **86** has a diameter of 400 mm and cuts a slot **154** that is nominally 400 mm tall and 250 mm deep, leaving uncut protruding rock sections **158** that are 200 mm tall and 250 mm deep. The cutter velocity is approximately 100 mm per second and cuts a depth of 50 mm per pass. The mine wall **26** is generally about 5 m wide by 4.8 m tall. The protruding sections **158** are broken from the mine wall **26** as described above. The cutting method according to this embodiment requires cutting at least 25% less rock than conventional hard rock cutting methods. This configuration (i.e., a wide cutting bit diameter and narrower uncut rock sections **158**) may be particularly useful for mining extremely hard, competent rock (i.e., rock into which unsupported openings may be cut).

(37) In another embodiment, the cutting bit has a diameter of 250 mm and cuts a slot **154** that is nominally 250 mm tall and 250 mm deep, leaving protruding uncut rock sections **158** that are generally 400 mm tall and 250 mm deep. The protruding sections **158** are then broken as described above. The cutting method according to this embodiment requires cutting less than half of the rock than would be cut using conventional hard rock cutting methods. This configuration (i.e., a narrower cutting bit diameter and relatively wide uncut rock sections **158**) may be particularly useful for mining hard rock with shear planes and fractures, or rock that has medium strength.

(38) Furthermore, the cut-and-break method provides cuts or slots **154** that are separated by uncut rock sections **158**, permitting a mining machine **10** to incorporate additional cutter heads **22** supported on additional booms **18** and operating simultaneously, effectively doubling the cutting rate. In addition, each of the cutter heads **22** in a multiple cutter head arrangement can operate toward one another, effectively counteracting the majority of cutting-induced boom forces that are typically transmitted through the machine **10** and into mine floor or the surrounding rock mass. Also, an embodiment including two cutter heads **22** supported on separate booms **18** can impart much larger forces on the protruding rock sections **158**, thereby increasing the allowable height of the protruding rock section **158** to be broken. Each boom **18** can simultaneously impart loads from an undercut and an overcut position. By maintaining separation between the centers of the booms **18**, the cutter heads **22** apply a torque on the rock in addition to exerting a direct force and dynamic cutting action.

(39) FIG. **9** illustrates another embodiment in which the cutter head **22** includes an arm **60** coupled to the mounting bracket **58** and supported by multiple hydraulic cylinders **72**. The illustrated embodiment includes four hydraulic cylinders **72a** positioned at approximately 90 degree intervals around the perimeter of the cutter head **22**. The arm **60** includes a fifth cylinder **72b** extending from the center of the support plate **70** to the mounting bracket **58**, and the cutter head **22** oscillates about a point **140** at the joint between the cylinder **72b** and the mounting bracket **58**. Other embodiments may include fewer or more hydraulic cylinders. The cylinders **72** are coupled to one or more hydraulic accumulators (not shown) such that the cylinders **72** behave similar to the springs **78** to react to the forces exerted on and by the cutter head **22**. In addition, the hydraulic cylinders **72a** can be actuated to pivot the cutter head **22** relative to the mounting bracket **58**, and the center cylinder **72b** extends the cutter head **22** relative to the mounting bracket **58**.

(40) The operation of the cylinders **72** provides omni-directional control of the cutter head **22** in order to maintain a desired orientation of the cutter head **22** relative to the mine wall **26** (i.e., the

angle of attack). In addition, the cylinders **72** can more accurately sense the force feedback from the cutter head **22**, providing accurate measurement of the cutting force exerted by the cutter head **22** and permitting the operator to more precisely control the cutting force. An automated system controls the cutting force based on various factors, such as oscillation frequency or speed, mass of the inertial member, and eccentricity of the exciter member. In other embodiments, a different type of cutter head (including a cutter head that does not include the exciter mass) may be coupled to the mounting bracket **58** by the cylinders **72**.

(41) FIGS. **10** and **11** illustrate a cutter head **222** according to another embodiment. The cutter head **22** is generally similar to the cutter head **22** described above with respect to FIGS. **4-6**, and similar features are identified by similar reference numbers, plus 200.

(42) As shown in FIGS. **10** and **11**, the cutter head **222** includes a cutting bit **286**, an inertial member **290**, an exciter member **294**, and a motor **302** for driving the exciter member **294**. The inertial member includes a body **330** and a cap **332** coupled to an end of the body **330**. The cutting bit **286** generally has a ring or annular shape and includes a cutting edge **288**. The cutting bit **286** is coupled to an end of the cap **332** by a retaining ring **336** (FIG. **10**). A radial and thrust bearing plate **340** (FIG. **10**) is positioned between the cutting bit **286** and the end of the cap **332** to support the cutting bit **286** for rotation relative to the cap **332**. The bearing plate **340** supports the cutting bit **286** against radial and axial loads. The exciter member **294** includes an eccentric mass **334** coupled to a shaft **326**. In the illustrated embodiment, the mass **334** has two lobes **334a**, **334b** that are eccentrically positioned with respect to the axis of rotation **298**. The shaft **326** is driven about the axis **298** by the motor **302**. The motor **302** is coupled to a support plate **270** of the cutter head **222**.

(43) In the embodiment of FIGS. **10** and **11**, only the exciter member **294** is driven by the motor **302**; the cutter head **222** does not include an external motor to directly drive the inertial member **290**. However, the inertial member **290** is rotatably coupled to the support plate **270** by a bearing **308**, and therefore the inertial member **290** is freely rotatable. In addition, the cutting bit **286** is freely rotatable relative to the inertial member **290** due to the bearing plate **340**. The inertial member **290** rotates about the axis **298** due to oscillation induced by the rotation of the exciter member **294**. The cutting bit **286** rotates at a relatively low speed due to the reaction forces exerted on the cutting bit **286** by the rock of the mine wall. In one embodiment, the cutting bit has a diameter of 400 mm and rotates at a speed of approximately 30 RPM.

(44) In another embodiment, shown in FIG. **12**, the lobes **334a**, **334b** of the exciter member **294** rotate independently of one another. The first motor **302** engages a first gear **316** that is coupled to a first or outer shaft **326a**. The first lobe **334a** is coupled to the outer shaft **326a**, and operation of the first motor **302** drives the first lobe **334a** to rotate about the axis **298**. The cutter head **222** also includes a second motor **304** engaging a second gear **320** that is coupled to a second or inner shaft **326b**. The second lobe **334b** is coupled to the inner shaft **326b**, and operation of the second motor **306** drives the second lobe **334b** to rotate about the axis **298**. The relationship between the lobes **334a**, **334b** can be tuned to provide a desired moment of inertia. For example, the lobes **334a**, **334b** can be moved to diametrically opposed positions (i.e., the angle between the lobes **334a**, **334b** is 180 degrees). If the lobes **334a**, **334b** have the same mass, this configuration effectively cancels or “turns off” the excitation. When the lobes **334a**, **334b** are positioned in the same relative position about the shaft **326**, the maximum power is delivered to the inertial member **290**.

(45) In other embodiments, the lobes **334a**, **334b** are counter-rotating such that the lobe **334a** rotates about the axis **298** in a first direction while the other lobe **334b** rotates about the axis **298** in an opposite second direction. When the counter-rotating lobes **334a**, **334b** have the same mass, the cutter head **222** produces a jackhammer-like action on the cutting edge of the cutting bit. Due to the configuration of the cutting bit **286**, the jackhammer effect acts at a 90 degree angle. Alternatively, if the lobes **334a**, **334b** have different masses, the counter-rotating exciter member **294** will drive the edge of the cutting bit **286** along a path **148** (FIG. **3A**) having an elliptical shape.

(46) As shown in FIGS. **13** and **14**, the cutter head **222** includes an internal fluid flow path **370** for

a cutting clearance system. The flow path **370** is in fluid communication with a fluid source, such as a pump (not shown). The flow path **370** includes a first passage **374** extending through the shaft **326** of the exciter member **294** and multiple second passages **378** extending through the cutting bit **286**. In the illustrated embodiment, the first passage **374** extends into a ring carrier of the cutting bit **286** and is in fluid communication with the second passage **378**. The second passages **378** extend radially (i.e., in a direction that is non-parallel to the axis **298**) from the first passage **374** through the cutting bit **286** to nozzles **382** positioned along the perimeter of the cutting bit **286** between the cutting tips **386** (FIG. **14**). The clearance fluid (e.g., water) is pumped through the first passage **374** and through the second passage **378** before being discharged through the nozzles **382**. The fluid discharge path is aligned with the primary cutting direction.

(47) The cutting clearance system eliminates hoses or other fluid conduit near the cutting interface. Furthermore, the cutting clearance system does not require additional moving parts inside the cutter head **222**, since the first passage **374** is fixed and statically sealed to the cutting bit **286**. In addition, embedding the nozzles **382** in the cutting bit **286** reduces the potential for damage to the fluid circuit or blockage caused by cuttings or debris.

(48) Unlike conventional oscillating disc cutter systems that merely allow for adjusting the motion or speed of the disc cutter, the mining machine **10** monitors certain characteristics of the cutter head **22** and incorporates feedback from the cutting interface to adjust certain parameters. The mining machine **10** detects changes in conditions of the cutting operation (e.g., a change in rock hardness or density) and incorporates the sensed information into a feedback control loop to modify the operating parameters of the cutter head **22** and optimize cutting performance. Such operating parameters may include the depth of cut, the angle of attack of the cutting bit **86** relative to the mine wall, the eccentricity of the exciter member **94**, the oscillation frequency of the exciter member **94**. Other factors (such as the diameter of the cutting bit **86**, the geometry of the cutting edge and cutting tips, and the cutting clearance) may be modified through manual adjustments.

(49) The cutting effectiveness of the cutter head **22** at least partially depends on the velocity of the inertial member **90** in the direction of cutting at the moment the cutting bit **86** impacts the mine wall, and on the frequency of the impacts between the cutting bit **86** and the mine wall. The velocity and frequency are controlled to optimize the velocity and the frequency of the impact of the cutter head **22** with the mine wall. The velocity and frequency can be controlled through various parameters, such as the effective mass of the exciter member **94**, operating frequency of the exciter member **94**, the stiffness of the cutter head **22** coupling member, the feed force from the boom, etc.

(50) Referring to FIG. **9A**, as the cutter head **22** oscillates around the center of mass, the cutting bit **86** moves in a generally circular or elliptical motion to engage the mine wall. The control system synchronizes the oscillation of the inertial member **90** with the motion of the cutting bit **86** such that the cutting bit **86** engages the mine wall when the momentum of the inertial member **90** is directed substantially into the mine wall. This timing between the cutting bit's engagement in the wall and the motion of the inertial member **90** maximizes the velocity of the inertial member **90** in the direction of the wall, thereby maximizing the kinetic energy imparted to the wall by the cutter head **22**. In other embodiments, the cutting bit **86** may trace a different shaped path, the bit **86** may engage the wall at a different position along the path **148**, and/or the oscillation of the inertial member **90** may be synchronized to deliver maximum velocity at a different position along the path **148**.

(51) In one embodiment, the control system adjusts the force exerted by the boom **18** and varies the oscillation frequency of the exciter member **94** in order to increase or decrease cutting energy. These modifications optimize productivity by increasing cutting velocity when possible. In addition, the condition of the tool may be monitored to detect changes in productivity and feed force as the cutting bit becomes blunt.

(52) In another embodiment, the cutter head **22** is controlled by directly sensing an indicator of the

force exerted by the cutting bit **86** on the mine wall **26** in real-time. For example, the control system may include a load cell (e.g., a multi-axis strain gauge; not shown) positioned on the cutting bit **86** to detect the stress on the cutting bit. The cutting force is calculated based on the measured stress. In addition, the control system may include sensors, such as infrared sensors, for monitoring the temperature at the cutting interface. The load sensor and thermal sensor provide accurate measurements of the performance of the cutter head **22**, permitting accurate adjustment of certain parameters (such as cutting speed or feed force) in order to optimize the closed loop control and optimize the power provided at the cutting interface. In another embodiment, the control system includes measuring a cutting speed of the cutting bit **86** with non-contact sensors and varying a feed rate of the cutter head **22** to optimize a cutting rate. Other embodiments can incorporate other adaptive features to optimize performance of the cutter head **22**.

(53) In general, increasing the power delivered by a cutter head **22** to the mine wall **26** generally results in a larger amount of rock cut from the wall **26**. The power delivered by the cutter head **22** varies depending on the rotation speed of the cutting bit **86**, the eccentricity of the cutting bit **86**, the mass of the inertial member **90** and the exciter member **94**, and the cutting feed force. In one embodiment, one or more of these parameters remain fixed due to the inherent characteristics of the mining machine **10** and the remaining parameters are dynamically controlled to continuously monitor and optimize the power output of the cutter head **22**. For example, a selected parameter may be varied slightly and the system detects whether the variation increases the cutting rate. If so, the selected parameter is adjusted further in the same direction. Otherwise, the parameter is adjusted in the opposite direction and any change in the cutting rate is monitored. The process is frequently repeated to ensure that the machine is generating maximum power output.

(54) In another embodiment, the control system provides automated position and force control of the boom **18**. The cutter head consistently operates at maximum capacity and at an optimum setting. In addition, the magnitude and direction of a load on the machine is known and controlled. The cutting force is the same for different applications, conditions, rock types etc., but the production rate varies depending on these parameters. Because the system is optimally tuned for substantially all conditions, it is not necessary to change the parameters if the mine conditions change (e.g., if the rock density changes). The cutting operation can be slowed down if required by reducing the oscillation speed of the cutting bit **86** and/or the exciter mass **94**.

(55) In other embodiments, the mining machine includes multiple cutter heads **22** coupled to a common boom **18**. Each cutter head **22** is force-controlled as described above, while the common boom **18** is position-controlled. Each cutter head **22** constitutes a single cutter system with the position-controlled common boom **18** as described above; however, each cutter system is linked via the common boom **18**. The multiple cutter system is controlled to progress through the mine wall **26** at a rate that is determined by the least productive individual cutter head **22** (i.e., the master cutter head). The more productive cutter head systems (i.e., slave cutter heads) are de-tuned to match the rate of the master cutter head in order to prevent the more productive systems from overrunning the position-controlled boom **18**. In one embodiment, the slave cutter(s) are de-tuned by altering one of the operating parameters, (e.g., the rotation speed of the cutting bit). For example, a master cutter head operates at nominal speed, while the slave cutter heads operate at speeds slower than the rated value. If a slave cutter head begins to lag, its speed is increased until its cutting performance matches the master cutter. The parameter(s) of the master cutter head are continuously varied to maximize its power output as described above with respect to the single cutter head system.

(56) If the speed of one of the slave cutter heads is adjusted to exceed the nominal cutting speed due to, for example, a change in cutting conditions, the slave cutter is automatically designated the master cutter head and the previous master cutter head becomes a slave. Therefore, the poorest performing cutter head is continuously adjusted to achieve its maximum possible performance and the other cutter heads are controlled to match this performance, thereby achieving maximum

performance of the combined cutter head assembly. In one embodiment, a significant discrepancy in the relative performance of the cutter heads indicates either differing rock characteristics or cutter condition problems.

(57) Thus, the invention provides, among other things, a cutter head for a mining machine. Although the invention has been described in detail with reference to certain preferred embodiments, variations and modifications exist within the scope and spirit of one or more independent aspects of the invention as described. Various features and advantages of the invention are set forth in the following claims.

Claims

1. A cutter head for a mining machine, the mining machine including a frame and a boom movably coupled to the frame, the cutter head comprising: a first member including a first end and a second end; a cutting bit coupled to the first member proximate the second end, the cutting bit having a cutting edge and configured to engage a rock surface; a second member supported for rotation relative to the first member in an eccentric manner, rotation of the second member inducing an oscillating motion of the cutting bit; a fluid conduit extending through the first member and configured to be in fluid communication with a fluid source; and a plurality of nozzles positioned on the cutting edge, the nozzles in fluid communication with the fluid conduit.
 2. The cutter head of claim 1, wherein the fluid conduit includes first conduit and a second conduit, the first conduit extending through the first member in a direction generally parallel to the axis, the second conduit extending through the cutting bit and providing fluid communication between the first conduit and the nozzles, the second conduit extending in a direction that is angled with respect to the axis.
 3. The cutter head of claim 1, further comprising a motor, wherein the second member is supported on a shaft, the motor driving the shaft to rotate about the axis, the fluid conduit extending through the shaft.
 4. The cutter head of claim 1, wherein the cutting edge has a generally circular perimeter and includes a plurality of cutting tips positioned at regular intervals around the perimeter, and wherein each nozzle is positioned between adjacent cutting tips.
-