

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12393817
Kind Code	B1
Date of Patent	August 19, 2025
Inventor(s)	Hopkins; Casey et al.

---

### Housings for tracking devices

---

#### Abstract

Housings (10) for tracking devices (12) comprise a housing body (16) and a seal (22). The housing body (16) has an internal volume (18) that is configured to selectively receive and retain the tracking device (12) in a close-fit relationship. The seal (22) is positioned within the internal volume (18) to engage both the housing body (16) and the tracking device (12). An outermost seal dimension (24) of the seal (22) is less than a width (20) of the internal volume (18) of the housing body (16).

---

<b>Inventors:</b>	<b>Hopkins; Casey (Portland, OR), Hull; Jacob (Portland, OR)</b>
<b>Applicant:</b>	<b>Elevation Lab, Inc. (Portland, OR)</b>
<b>Family ID:</b>	<b>1000008409346</b>
<b>Assignee:</b>	<b>Elevation Lab, Inc. (Portland, OR)</b>
<b>Appl. No.:</b>	<b>19/012635</b>
<b>Filed:</b>	<b>January 07, 2025</b>

---

#### Publication Classification

<b>Int. Cl.:</b>	<b>G06K19/077 (20060101)</b>
<b>U.S. Cl.:</b>	
<b>CPC</b>	<b>G06K19/07758 (20130101);</b>

#### Field of Classification Search

<b>CPC:</b>	<b>G06K (19/07758)</b>
<b>USPC:</b>	<b>235/492</b>

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
675213	12/1900	Harris	N/A	N/A
714538	12/1901	Walter	N/A	N/A
1785186	12/1929	Day	N/A	N/A
2013485	12/1934	Bary et al.	N/A	N/A
2491166	12/1948	Stiso	N/A	N/A
2515551	12/1949	Cohen	N/A	N/A
3312255	12/1966	Ellison	N/A	N/A
3608685	12/1970	Childress	N/A	N/A
3953722	12/1975	Stick	N/A	N/A
4531310	12/1984	Acson et al.	N/A	N/A
4597206	12/1985	Benson	N/A	N/A
D375695	12/1995	Narai	N/A	N/A
5585867	12/1995	Ooya	N/A	N/A
5748087	12/1997	Ingargiola et al.	N/A	N/A
D402805	12/1997	Nagano et al.	N/A	N/A
5878698	12/1998	Lyell	N/A	N/A
D407985	12/1998	Pimentel	N/A	N/A
D414186	12/1998	Hogenbirk	N/A	N/A
D415480	12/1998	Kendall et al.	N/A	N/A
D440397	12/2000	Bardet	N/A	N/A
6243870	12/2000	Graber	N/A	N/A
D447067	12/2000	Vollenweider	N/A	N/A
D511699	12/2004	Pan	N/A	N/A
6970090	12/2004	Sciarra	N/A	N/A
D556938	12/2006	Russello et al.	N/A	N/A
D571557	12/2007	Lawler	N/A	N/A
D575649	12/2007	Scalisi et al.	N/A	N/A
D598018	12/2008	Sumii	N/A	N/A
7598869	12/2008	Kumagai et al.	N/A	N/A
D609123	12/2009	Pace	N/A	N/A
7780972	12/2009	Hurwitz	N/A	N/A
D632853	12/2010	Hardi et al.	N/A	N/A
D633644	12/2010	Sprengers	N/A	N/A
D647227	12/2010	Kaule et al.	N/A	N/A
8148701	12/2011	Yoder	N/A	N/A
D661846	12/2011	Miller et al.	N/A	N/A
8195313	12/2011	Fadell et al.	N/A	N/A
D666367	12/2011	Miller et al.	N/A	N/A
D680015	12/2012	Hauser et al.	N/A	N/A
D683251	12/2012	Dumas et al.	N/A	N/A
D703394	12/2013	Bozeman	N/A	N/A
D713103	12/2013	Sproviero et al.	N/A	N/A
D726161	12/2014	Howard et al.	N/A	N/A
D729773	12/2014	Salojarvi et al.	N/A	N/A
D735131	12/2014	Akana et al.	N/A	N/A

D750980	12/2015	Takach et al.	N/A	N/A
D752588	12/2015	Li	N/A	N/A
D757585	12/2015	H.Jmose	N/A	N/A
D757587	12/2015	Li	N/A	N/A
9526433	12/2015	Lapetina et al.	N/A	N/A
D779977	12/2016	Jacob et al.	N/A	N/A
D781572	12/2016	Duval	N/A	N/A
D783422	12/2016	Kashimoto	N/A	N/A
D790514	12/2016	Woodward et al.	N/A	N/A
D795109	12/2016	Olodort et al.	N/A	N/A
D803410	12/2016	Im et al.	N/A	N/A
D804533	12/2016	Mangum et al.	N/A	N/A
D812577	12/2017	Turksu et al.	N/A	N/A
D817332	12/2017	Yaprak et al.	N/A	N/A
D817558	12/2017	Lee et al.	N/A	N/A
D817793	12/2017	Vu et al.	N/A	N/A
D818854	12/2017	Kachar et al.	N/A	N/A
D820238	12/2017	Boshernitzan et al.	N/A	N/A
D820318	12/2017	Mullins et al.	N/A	N/A
9996996	12/2017	Siebels et al.	N/A	N/A
D822921	12/2017	Wen	N/A	N/A
D822922	12/2017	Wen	N/A	N/A
D825549	12/2017	Lebovitz	N/A	N/A
D826748	12/2017	Kim et al.	N/A	N/A
10176691	12/2018	Smoak	N/A	N/A
D843238	12/2018	Rose et al.	N/A	N/A
10271524	12/2018	Chen	N/A	N/A
10305178	12/2018	Gibson et al.	N/A	N/A
D852150	12/2018	Turksu et al.	N/A	N/A
D854950	12/2018	Seum et al.	N/A	N/A
D858904	12/2018	Zinn et al.	N/A	N/A
D865859	12/2018	Ben Avi	N/A	N/A
D867909	12/2018	Kachar	N/A	N/A
D870399	12/2018	Van Curen et al.	N/A	N/A
D883581	12/2019	Daly et al.	N/A	N/A
D890002	12/2019	Cound et al.	N/A	N/A
D890754	12/2019	Raken et al.	N/A	N/A
D895465	12/2019	Loew et al.	N/A	N/A
D896798	12/2019	Yang	N/A	N/A
D898613	12/2019	Stapleton	N/A	N/A
D900812	12/2019	Friedman et al.	N/A	N/A
D911191	12/2020	Qi	N/A	N/A
D920138	12/2020	Kuwashiro et al.	N/A	N/A
D926396	12/2020	Jia	N/A	N/A
D929051	12/2020	Li	N/A	N/A
11160335	12/2020	Eidelman et al.	N/A	N/A
D938668	12/2020	Jia	N/A	N/A
D939972	12/2021	Erbacher et al.	N/A	N/A
11224301	12/2021	Delgado Carmona	N/A	N/A
D943438	12/2021	Chen	N/A	N/A

D943845	12/2021	Li	N/A	N/A
11308744	12/2021	Exantus	N/A	N/A
D952961	12/2021	Li	N/A	N/A
D956765	12/2021	Lee et al.	N/A	N/A
11393319	12/2021	Maisano, II et al.	N/A	N/A
D960013	12/2021	Konen et al.	N/A	N/A
D960129	12/2021	Karimi et al.	N/A	N/A
D960562	12/2021	Lee et al.	N/A	N/A
D964667	12/2021	Mo	N/A	N/A
D970372	12/2021	Aneja	N/A	N/A
D977278	12/2022	Ramm et al.	N/A	N/A
D983066	12/2022	Wright et al.	N/A	N/A
D983786	12/2022	Herrmann	N/A	N/A
2002/0197960	12/2001	Lee et al.	N/A	N/A
2006/0061546	12/2005	Jong	N/A	N/A
2007/0034165	12/2006	Yang	N/A	N/A
2007/0253192	12/2006	Monteiro et al.	N/A	N/A
2008/0165056	12/2007	Bader	N/A	N/A
2008/0198585	12/2007	Tait	N/A	N/A
2009/0322480	12/2008	Benedict et al.	N/A	N/A
2010/0147854	12/2009	Fauveau	N/A	N/A
2010/0238033	12/2009	Blumel et al.	N/A	N/A
2012/0033898	12/2011	Barron	N/A	N/A
2012/0118980	12/2011	Yoder	N/A	N/A
2012/0147594	12/2011	Tait	N/A	N/A
2013/0208938	12/2012	Midha	N/A	N/A
2014/0002239	12/2013	Rayner	N/A	N/A
2014/0180019	12/2013	Martinez et al.	N/A	N/A
2014/0331942	12/2013	Sarazyn	N/A	N/A
2015/0150319	12/2014	Walmsley	N/A	N/A
2015/0297134	12/2014	Albert et al.	N/A	N/A
2015/0356861	12/2014	Daoura et al.	N/A	N/A
2015/0356862	12/2014	Daoura et al.	N/A	N/A
2015/0359127	12/2014	Daoura et al.	N/A	N/A
2016/0058149	12/2015	Dhanasekaran	N/A	N/A
2016/0071392	12/2015	Hankey et al.	N/A	N/A
2016/0247156	12/2015	Hwang et al.	N/A	N/A
2016/0247379	12/2015	Forbes	N/A	N/A
2016/0266606	12/2015	Ricci	N/A	N/A
2016/0291162	12/2015	Larkins	N/A	N/A
2017/0079336	12/2016	Hirschberg et al.	N/A	N/A
2017/0135315	12/2016	Marmen et al.	N/A	N/A
2017/0135414	12/2016	Fultz	N/A	N/A
2017/0302099	12/2016	Bolden et al.	N/A	N/A
2017/0360169	12/2016	Stein	N/A	N/A
2018/0299991	12/2017	Juhasz et al.	N/A	N/A
2018/0325426	12/2017	Shaw et al.	N/A	N/A
2019/0103012	12/2018	Daoura et al.	N/A	N/A
2020/0107522	12/2019	Kersey et al.	N/A	N/A
2020/0169848	12/2019	Daoura et al.	N/A	N/A

2020/0337162	12/2019	Perkins et al.	N/A	N/A
2020/0352300	12/2019	Sube	N/A	N/A
2021/0020020	12/2020	Rothschild et al.	N/A	N/A
2021/0274315	12/2020	Daoura et al.	N/A	N/A
2021/0274754	12/2020	Talley et al.	N/A	N/A
2021/0306807	12/2020	Kashani-Nejad et al.	N/A	N/A
2021/0307294	12/2020	Kimbel	N/A	N/A
2022/0051182	12/2021	Fox et al.	N/A	N/A
2022/0140431	12/2021	Moon	N/A	N/A
2022/0265214	12/2021	Jariwala et al.	N/A	N/A
2022/0391656	12/2021	Chen et al.	N/A	N/A
2023/0046992	12/2022	Leyva	N/A	H04L 67/75
2023/0109754	12/2022	Newton	N/A	N/A
2024/0211717	12/2023	Barovic	N/A	G06K 19/0702
2024/0239144	12/2023	Trimnell	N/A	G01S 19/16
2024/0254809	12/2023	Wright	N/A	F16M 13/04
2024/0384872	12/2023	Fraser	N/A	F23Q 2/38

## FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
306512384	12/2019	CN	N/A
306806113	12/2020	CN	N/A
306806204	12/2020	CN	N/A
306820796	12/2020	CN	N/A
307127923	12/2020	CN	N/A
307552161	12/2021	CN	N/A
3929468	12/1990	DE	N/A
008844344-0001	12/2021	EP	N/A
008869267-0006	12/2021	EP	N/A
6189757	12/2021	GB	N/A
6194869	12/2021	GB	N/A
6194870	12/2021	GB	N/A
H0544379	12/1992	JP	N/A
WO2022251483	12/2021	WO	N/A
WO2013117879	12/2022	WO	N/A

## OTHER PUBLICATIONS

Catalyst Lifestyle Limited, “Stick-It” Product Page, <https://catalystlifestyle.com/products/total-protection-airtag-stick-it-case?variant=39616587038829>, (Apr. 24, 2023). cited by applicant

EBay, “2-Pack Waterproof Airtag Sticker Mount Case for Apple Hidden Air Tag Adhesive,” <https://ebay.com/itm/195579903589>, (Apr. 24, 2023). cited by applicant

Amazon, “New IPX8 Waterproof AirTag Holder/Case,” <https://www.amazon.com/Waterproof-Adhesive-Sticker-Compatible-Luggage/dp/B0BM L9S KPX>, (Nov. 16, 2022). cited by applicant

Amazon, “[Upgrade] I PX8 Waterproof Airtag Sticker Mount,” <https://www.amazon.ca/Upgrade-Waterproof-Adhesive-Protective-Shockproof/dp/B0BRMG PWVK?th=1>, (Jan. 12, 2023). cited by applicant

## Background/Summary

### FIELD

(1) The present disclosure relates to housings for tracking devices.

### BACKGROUND

(2) In recent years, wireless tracking devices have become popular amongst consumers. Typically, wireless tracking devices are small and require additional hardware to be physically mounted or coupled to an object that a user desires to track. Consumers often use wireless tracking devices for keys, sports equipment, pets, electronic equipment, etc. In some applications, keeping dirt, debris, and water away from the wireless tracking device is important, as is providing a housing for a tracking device that is rugged and withstands impacts. Examples of housings for tracking devices are disclosed in U.S. Pat. Nos. 11,694,058; 11,910,888; 11,931,643; 11,934,902; and 12,014,236, the disclosures of which are incorporated herein by reference.

### SUMMARY

(3) Housings for securing tracking devices to articles comprise a housing body and a seal. the housing body has an internal volume that is configured to selectively receive and retain a tracking device in a close-fit relationship. The seal is positioned within the internal volume to engage both the housing body and the tracking device, and an outermost seal dimension of the seal is less than a width of the internal volume of the housing body.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic illustration representing housings for tracking devices according to the present disclosure.

(2) FIG. 2 is an isometric view of an example housing according to the present disclosure, shown secured to a pet collar.

(3) FIG. 3 is a front view of the example housing and pet collar of FIG. 2.

(4) FIG. 4 is a cross-sectional view of the example housing of FIG. 2 with an Apple AirTag™ device, taken along line 4-4 in FIG. 3.

(5) FIG. 5 is an isometric view of another example housing according to the present disclosure, shown secured to a key ring.

(6) FIG. 6 is a front view of the example housing of FIG. 5.

(7) FIG. 7 is a cross-sectional view of the example housing of FIG. 5 with an Apple AirTag™ device, taken along line 7-7 in FIG. 6.

(8) FIG. 8 is an isometric view of another example housing according to the present disclosure with an Apple AirTag™ device.

(9) FIG. 9 is a front view of the example housing and Apple AirTag™ device of FIG. 8.

(10) FIG. 10 is a cross-sectional view of the example housing and Apple AirTag™ device of FIG. 8, taken along line 10-10 in FIG. 9.

(11) FIG. 11 is a cross-sectional view of the example housing and Apple AirTag™ device of FIG. 8, taken along line 11-11 in FIG. 9.

(12) FIG. 12 is an isometric view of another example housing according to the present disclosure

with an Apple AirTag™ device.

(13) FIG. 13 is a front view of the example housing and Apple AirTag™ device of FIG. 12.

(14) FIG. 14 is a cross-sectional view of the example housing and Apple AirTag™ device of FIG. 12, taken along line 14-14 in FIG. 13.

(15) FIG. 15 is a cross-sectional view of the example housing and Apple AirTag™ device of FIG. 12, taken along line 15-15 in FIG. 13.

(16) FIG. 16 is an isometric view of another example housing according to the present disclosure.

(17) FIG. 17 is a front view of the example housing of FIG. 16.

(18) FIG. 18 is a cross-sectional view of the example housing of FIG. 16 with an Apple AirTag™ device, taken along line 18-18 in FIG. 17.

## DESCRIPTION

(19) Housings 10 for securing tracking devices 12 to articles 14 are disclosed herein. Examples of tracking devices 12 include wireless (e.g., WiFi, Bluetooth™, GPS) tracking devices (e.g., Apple AirTag™, Tile™, Samsung Galaxy SmartTag™, Chipolo One™, CubePro™, Orbit™, and Baseus™ branded tracking devices); and examples of articles 14 include sports equipment, snowboards, skis, skateboards, surfboards, paddle boards, stand-up paddle boards, wake boards, water skis, bicycles, hard-sided articles, land vehicles, trailers, All-Terrain-Vehicles (ATVs), motorcycles, watercraft, power tools, cases, luggage, camera gear, coolers, camping equipment, apparel, pet collars, etc. Functionally, a housing 10 may be used to secure a tracking device 12 to an article 14 that a user desires to keep track of.

(20) FIG. 1 schematically illustrates housings 10 according to the present disclosure. Generally, in FIG. 1, elements that are likely to be included in a given example are illustrated in solid lines, while elements that are optional to a given example or that correspond to one or more specific examples are illustrated in broken lines. However, elements that are illustrated in solid lines are not essential to all examples of the present disclosure, and an element shown in solid lines may be omitted from a particular example without departing from the scope of the present disclosure.

(21) As schematically represented in FIG. 1, housings 10 generally comprise at least a housing body 16 and a seal 22.

(22) The housing body 16 has an internal volume 18 that is configured to selectively receive and retain the tracking device 12 in a close-fit relationship. For example, the size and shape of the internal volume 18 may be only slightly larger than (e.g., less than 1% by volume) the size and shape of the tracking device 12, such that the housing body 16 generally contacts a significant portion (e.g., greater than 50%) of the external surface of the tracking device 12 and restricts the tracking device 12 from moving relative to the housing body 16. As schematically indicated in FIG. 1, the internal volume 18 may be described as having a central axis 70, a width 20 (i.e., a maximum width) that is transverse to the central axis 70, and a height 21 (i.e., a maximum height) that is aligned with the central axis 70. In some examples the height 21 is less than the width 20. In some examples, the housing 10 is substantially radially symmetrical about the central axis 70. By “substantially radially symmetrical,” it is meant that the housing 10 is at least 75% radially symmetrical, such as being at least 75% round.

(23) The seal 22 is either positioned within the internal volume 18 or is configured to be positioned within the internal volume 18 (e.g., if sold or distributed in an unassembled state) to engage both the housing body 16 and the tracking device 12 when the tracking device 12 is operatively received in the internal volume 18. Accordingly, when the tracking device 12 is operatively received in the internal volume 18, the seal 22 effectively restricts fluids or debris from passing between the tracking device 12 and the housing body 16 at the location of the seal 22. As schematically indicated in FIG. 1, the seal 22 may be described as having an outermost (i.e., maximum) seal dimension 24 that is less than the width 20 of the internal volume 18.

(24) In some examples, the seal 22 has an enclosed shape, such that when the tracking device 12 is operatively received in the internal volume 18, a region of the internal volume 18 is completely

sealed off from the remainder of the internal volume **18**. In other examples, the seal **22** defines an expanse, with an opening thereof, and is configured to engage an expanse of the tracking device **12**. (25) As schematically represented in FIG. **1**, in some examples, the housing body **16** defines a seal channel **72**, within which the seal **22** is positioned or is configured to be positioned. In some such examples, the housing body **16** comprises one or more ribs **74** that at least partially define the seal channel **72**.

(26) In some examples, the seal **22** is an O-ring and/or a gasket. In some example, the seal **22** is fixed to the housing body **16**. For example, the seal **22** may be adhered to the housing body **16** and/or may be overmolded to the housing body **16**. In other examples, the seal **22** may be removable from the internal volume **18**.

(27) In some examples, the seal **22** is positioned within the internal volume **18** or is configured to be positioned within the internal volume **18** to protect less than an entirety of the tracking device **12** from environment that is external to the housing **10** when the tracking device **12** is operatively received in the internal volume **18**. For example, depending on the configuration of the tracking device **12**, portions of the tracking device **12** may be susceptible to damage when exposed to environment, such as a battery or electronics compartment that has the potential to be penetrated by moisture, while other portions of the tracking device **12** may be subject to moisture without issue. Such a configuration of housing **10** may provide for a more compact envelope, or overall volume, of the housing **10**, thus utilizing less material for the construction of the housing **10** and for fitting into tighter spaces for securement of a tracking device **12** to an article **14**.

(28) As an example and as schematically represented in FIG. **1**, in some examples, the tracking device **12** defines a battery compartment **26** and a device opening **28** to the battery compartment **26**. In some such examples, the device opening **28** has an outermost opening dimension **30** that is less than the outermost seal dimension **24**, and the seal **22** extends around the device opening **28** when the tracking device **12** is operatively received within the internal volume **18**. Accordingly, the seal **22** protects the battery compartment **26** from moisture, but not necessarily others portions of the tracking device **12**. In some such examples, the tracking device **12** comprises a device body **32** and a device cover **34** that is removably coupled to the device body **32** to close the device opening **28**. The device body **32** defines the device opening **28**, and the seal **22** engages the device body **32** around the device cover **34** when the tracking device **12** is operatively received within the internal volume **18**. In some such examples, the seal **22** further engages the device cover **34** when the tracking device **12** is operatively received within the internal volume **18**.

(29) In some examples, the device body **32** comprises a circular planar surface **56** that extends around the device opening **28**, and the seal **22** engages the circular planar surface **56** when the tracking device **12** is operatively received within the internal volume **18**.

(30) With continued reference to FIG. **1** in some examples of housings **10**, the housing body **16** comprises a first body portion **36** and a second body portion **38** that collectively define the internal volume **18**. In some such examples, the second body portion **38** is removably coupled to the first body portion **36** to permit placement and removal of the tracking device **12** in and from the internal volume **18**. In such examples, the first body portion **36** and the second body portion **38** may be described as a base and a cover, respectively, or vice versa.

(31) As schematically represented in FIG. **1**, in some examples, the first body portion **36** and the second body portion **38** collectively define thread structure **40**. In other words, relative rotation of the first body portion **36** relative to the second body portion **38** may effectively decouple and recouple the first body portion **36** and the second body portion **38**. In some such examples, the thread structure **40** is configured to require less than 180-degrees of rotation, such as about 90-degrees of rotation, of the first body portion **36** relative to the second body portion **38** for operatively coupling and decoupling of the first body portion **36** and the second body portion **38**. Such examples of thread structure **40** may be described as having a quarter-turn configuration.

(32) In other examples, the first body portion **36** and the second body portion **38** have a snap-fit



arrangement or a friction-fit arrangement.

(33) In yet other examples as schematically illustrated in FIG. 1, the housing body **16** comprises a hinge **42**, and second body portion **38** is hinged to the first body portion **36**. In such examples, the first body portion **36** and the second body portion **38** also may have a snap-fit arrangement or a friction-fit arrangement to permit effective opening and closing of the housing body **16** about the hinge **42**, and thus permit and restrict access to the internal volume **18** for placement and removal of the tracking device **12**. Additionally or alternatively in hinged examples, housings **10** may further comprise a fastener **44** that selectively permits the opening and closing of the housing body **16** about the hinge **42**.

(34) In some examples of housings **10**, the seal **22** engages only one of the first body portion **36** or the second body portion **38** when the first body portion **36** and the second body portion **38** are operatively coupled together. Stated differently, in such examples, the seal **22** is not positioned at an interface between the first body portion **36** and the second body portion **38**.

(35) As discussed above, housings **10** may be configured for being secured to various articles **14**. As an example, the article **14** may be a flat flexible material **48**, as schematically represented in FIG. 1. For example, the flat flexible material **48** may be a strap or webbing material, such as a pet collar, a backpack strap, or another type of strap. In such examples and as schematically illustrated in FIG. 1, housings **10** may further comprise at least one fastener **44** that is (e.g., two or more fasteners **44** that are) configured to extend through the flat flexible material **48**, with the housing body **16** defining at least one fastener bore **46** that is (e.g., two or more fastener bores **46** that are) configured to operatively receive (i.e., mate with) the fastener(s) **44**. In some such examples as schematically illustrated in FIG. 1, the fastener(s) **44** are configured to pierce the flat flexible material **48**. That is, the fastener(s) **44** may have pointed or sharp ends and be configured to pierce between fibers, webbing, or the like. Accordingly, such housings **10** may be secured to a flat flexible material **48** without first needing to make a hole or holes in the flat flexible material **48**.

(36) Some housings **10** further comprise a backing plate **50** that is configured to be positioned opposite the housing body **16** relative to the flat flexible material **48**, and the fastener(s) **44** are configured to extend through the backing plate **50**. In some such examples of housings **10** with a housing body **16** that comprises a first body portion **36** and a second body portion **38**, the fastener bore(s) **46** extend through the first body portion **36** and the second body portion **38**. Accordingly, when the fastener(s) **44** extend through the flat flexible material **48** and are operatively received in the fastener bore(s) **46**, the fastener(s) **44** serve to secure the housing **10** to the flat flexible material **48** and to couple the first body portion **36** to the second body portion **38** to restrict access to the internal volume **18**. That is, in such examples, the fastener(s) **44** serve two functions: securing the housing **10** to the flat flexible material **48** and closing the housing body **16** to retain the tracking device **12** therein. Accordingly, separate fasteners need not be provided for these distinct functions, resulting in fewer parts and a smaller overall possible envelope, or volume, of the housing **10**. Accordingly, such housings **10** may fit into tighter spaces for securing a tracking device **12** to an article **14**.

(37) With continued reference to FIG. 1, in some examples, the housing body **16** defines a through-hole **52** that is configured to receive at least a portion of an article **14**. For example, the article **14** may be a key ring **54**, a carabiner, or other such structure that is sized to extend through the through-hole **52**. In some such examples in which the housing body **16** comprises a first body portion **36** and a second body portion **38**, the through-hole **52** extends through both of the first body portion **36** and the second body portion **38**. Accordingly, when the article **14**, such as a key ring **54**, operatively extends through the through-hole **52**, the internal volume **18** is restricted from being fully accessed to receive the tracking device **12** in the internal volume **18** or to release the tracking device **12** from the internal volume **18**. That is, the article **14** extending through the through-hole **52** may restrict the housing body **16** from being fully opened, thereby preventing the tracking device **12** from inadvertently being released from the housing **10**, even if the coupling

mechanism (e.g., threads, snap-fit arrangement, friction-fit arrangement, etc.) between the first body portion **36** and the second body portion **38** fails.

(38) Additionally or alternatively, as also schematically illustrated in FIG. **1**, some housings **10** further comprise an elongate retainer **58** that extends from the housing body **16**. The elongate retainer **58** and the housing body **16** collectively define a passage **60** that is configured to receive at least a portion of an article **14**, such as a key ring, a carabiner, a luggage handle, a belt loop, or other such structure. In some examples, the elongate retainer **58** is removably coupled to the housing body **16**, thus permitting for the selective placement of a portion of an article through the passage **60**. In other examples, the housing **10** may be configured to restrict opening of the passage **60**, such that an article **14** has to be configured to selectively extend through the passage **60** for securement to the housing **10**, such as with a key ring **54**, a carabiner, or other structure that can be selectively opened by a user.

(39) In some examples, the elongate retainer **58** is rigid, such as similar to a shackle on a padlock. In other examples, the elongate retainer **58** is flexible, such as being constructed of a braided metal wire or a plastic-coated braided metal wire.

(40) With continued reference to FIG. **1**, in some examples, the elongate retainer **58** comprises end regions **62** that are positioned within the housing body **16**, and the housing body **16** is configured to restrict removal of the end regions **62** from within the housing body **16**. In some such examples, each end region **62** defines a circumferential channel **64**, and the housing body **16** comprises at least one protrusion **66** that extends into each circumferential channel **64**. For example, the protrusion(s) **66** may be a rib that extends substantially around or even fully around the circumferential channel **64** of the end regions **62**. In some such examples of housing **10** where the housing body **16** comprises a first body portion **36** and a second body portion **38**, the first body portion **36** and the second body portion **38** collectively define the protrusion(s) **66** that extends into each circumferential channel **64**. In other examples, only one of the first body portion **36** or the second body portion **38** may define the protrusion(s) **66**. Accordingly, when the first body portion **36** and the second body portion **38** are operatively coupled together, the end regions **62** are restricted from being removed from the housing body **16**, and when the first body portion **36** and the second body portion **38** are operatively separated, the end regions **62** are permitted to be removed from the housing body **16**. Accordingly in such examples, when the housing body **16** is opened to permit access to the internal volume **18** for placement or removal of a tracking device **12**, the end regions **62** may be removed from the housing body **16** for selective extension around a portion of an article **14** by a user.

(41) As schematically illustrated in FIG. **1**, some housings **10** may further comprise a coupler **68** that is attached to the housing body **16** and that is configured to be operatively attached to an article **14**. As an example, the coupler **68** may comprise a double-sided adhesive, such as a double-sided foam tape. Additionally or alternatively, the coupler **68** may comprise a magnet.

(42) Turning now to FIGS. **2-17**, illustrative non-exclusive examples of housings **10** configured for use with tracking devices **12** in the form of Apple AirTag™ devices are illustrated. Where appropriate, the reference numerals from the schematic illustration of FIG. **1** are used to designate corresponding parts of the housings of FIGS. **2-17**; however, the examples of FIGS. **2-17** are non-exclusive and do not limit housings **10** to the illustrated embodiments of FIGS. **2-17**. That is, housings **10** may incorporate any number of the various aspects, configurations, characteristics, properties, etc. of housings **10** that are illustrated in and discussed with reference to the schematic representations of FIG. **1** and/or the embodiments of FIGS. **2-17**, as well as variations thereof, without requiring the inclusion of all such aspects, configurations, characteristics, properties, etc. For the purpose of brevity, each previously discussed component, part, portion, aspect, region, etc., or variants thereof may not be discussed, illustrated, and/or labeled again with respect to the embodiments of FIGS. **2-17**.

(43) FIGS. **2-4** illustrate example housing **100** operatively secured to a flat flexible material **48** in

the form of a pet collar. In particular, as seen in FIG. 4, housing **100** is an example of a housing **10** whose housing body **16** comprises a first body portion **36** and a second body portion **38** and that comprises two fasteners **44** that are configured to pierce the flat flexible material **48** and to operatively coupled together the first body portion **36** and the second body portion **38**. Moreover, the first body portion **36** and the second body portion **38** collectively define thread structure **40**. In particular the thread structure **40** of assembly **100** has a quarter-turn configuration. Accordingly, when the two fasteners **44** extend through the flat flexible material **48** and are operatively received in the fastener bores **46** of the housing body **16**, as depicted in FIG. 4, the fasteners not only secure the housing **100** to the flat flexible material **48**, but also prevent the internal volume **18** from being accessed.

(44) As seen in FIG. 4, the Apple AirTag device has a circular planar surface **56** extending around the device cover **34** (i.e., the battery cover of the Apple AirTag™ device). The seal **22**, which is in the form of an O-ring, engages the circular planar surface **56** and extends around the battery cover of the Apple AirTag™ device. As a result of the placement of the seal **22**, moisture may be able to ingress into the internal volume **18** of the housing body **16** from the interface between the first body portion **36** and the second body portion **38**; however, the seal **22** will restrict any such moisture from traveling to the battery compartment of the Apple AirTag™ device.

(45) FIGS. 5-7 illustrate example housing **200**. Housing **200** is configured for use with an article **14**, such as a key ring **54**, as seen in FIG. 5. Housing **200** is an example of a housing **10** that comprises a first body portion **36** and a second body portion **38** that collectively define a through-hole **52** and thread structure **40** having a quarter-turn configuration. The through-hole **52** is sized such that when an article **14**, such as a key ring **54**, extends through the through-hole **52**, the thread structure **40** will not fully disengage to permit access to the internal volume **18**. Accordingly, the key ring **54** will have to be removed from the through-hole **52** for full access to the internal volume **18**, and thus for placement and removal of an Apple AirTag™ device.

(46) As best seen in FIG. 7, as with housing **100**, the seal **22** of housing **200** is in the form of an O-ring that engages the circular planar surface **56**, and that extends around the battery cover of, the Apple AirTag™ device.

(47) FIGS. 8-11 illustrate example housing **300**. Housing **300** is an example of a housing **10** that comprises a first body portion **36** and a second body portion **38** that collectively define a hinge **42**. Housing **300** comprises a single fastener **44**, which, as best seen in FIG. 10, maintains the housing body **16** in a closed configuration to restrict removal of the Apple AirTag™ device.

(48) As best seen in the FIG. 10, as with housing **100**, the seal **22** of housing **300** is in the form of an O-ring that engages the circular planar surface **56** and extends around the battery cover of the Apple AirTag™ device.

(49) Housing **300** is an example of a housing **10** that also comprises a rigid elongate retainer **58** that extends from the housing body **16**. In particular, with reference to FIG. 11, the elongate retainer **58** of housing **300** comprises end regions **62** that each define a circumferential channel **64**, and the second body portion **38** comprises protrusions **66** that extend into each circumferential channel **64** when the first body portion **36** and the second body portion **38** are hinged closed. Accordingly, when the fastener **44** operatively maintains the first body portion **36** and the second body portion **38** in a closed configuration, the rigid elongate retainer **58** is restricted from being removed from the housing body **16**.

(50) The first body portion **36** of the housing body **16** of housing **300** defines a window **76** that provides visual and physical access to the Apple AirTag™ device, but which restricts removal of the Apple AirTag™ device via the window **76**.

(51) FIGS. 12-15 illustrate example housing **400**. Housing **400** is constructed identically to housing **300**, but for inclusion of an elongate retainer **58** that is flexible and longer than the rigid elongate retainer of housing **300**.

(52) FIGS. 16-18 illustrate example housing **500**. Housing **500** is an example of a housing **10** that

comprises a first body portion **36** and a second body portion **38** that are threadingly coupled together via thread structure **40**. Housing **500** comprises a coupler **68** in the form of a double-sided foam tape. As seen in the FIG. **18**, as with housing **100**, the seal **22** of housing **500** is in the form of an O-ring that engages the circular planar surface **56** and extends around the battery cover of the Apple AirTag™ device.

(53) Illustrative, non-exclusive examples of inventive subject matter according to the present disclosure are described in the following enumerated paragraphs:

(54) A. A housing (**10**) for a tracking device (**12**), the housing (**10**) comprising: a housing body (**16**) having an internal volume (**18**) configured to selectively receive and retain the tracking device (**12**) in a close-fit relationship, wherein the internal volume (**18**) has a width (**20**) and a height (**21**); and a seal (**22**) positioned within the internal volume (**18**) or configured to be positioned within the internal volume (**18**) to engage both the housing body (**16**) and the tracking device (**12**) when the tracking device (**12**) is operatively received in the internal volume (**18**), wherein the seal (**22**) has an outermost seal dimension (**24**) that is less than the width (**20**) of the internal volume (**18**); wherein the housing (**10**) is configured to be secured to an article (**14**).

(55) A1. The housing (**10**) of paragraph A, wherein the seal (**22**) has an enclosed shape.

(56) A2. The housing (**10**) of any of paragraphs A-A1, wherein the seal (**22**) is fixed to the housing body (**16**).

(57) A2.1. The housing (**10**) of paragraph A2, wherein the seal (**22**) is adhered to the housing body (**16**).

(58) A2.2. The housing (**10**) of any of paragraphs A2-A2.1, wherein the seal (**22**) is overmolded to the housing body (**16**).

(59) A3. The housing (**10**) of any of paragraphs A-A2.2, wherein the seal (**22**) is an O-ring or a gasket.

(60) A4. The housing (**10**) of any of paragraphs A-A3, wherein the tracking device (**12**) is an Apple AirTag™ device.

(61) A5. The housing (**10**) of any of paragraphs A-A4, wherein the seal (**22**) is positioned within the internal volume (**18**) or is configured to be positioned within the internal volume (**18**) to protect less than an entirety of the tracking device (**12**) from environment external to the housing (**10**) when the tracking device (**12**) is operatively received in the internal volume (**18**).

(62) A6. The housing (**10**) of any of paragraphs A-A5, wherein the tracking device (**12**) defines a battery compartment (**26**) and a device opening (**28**) to the battery compartment (**26**); wherein the device opening (**28**) has an outermost opening dimension (**30**) that is less than the outermost seal dimension (**24**); and wherein the seal (**22**) extends around the device opening (**28**) when the tracking device (**12**) is operatively received within the internal volume (**18**).

(63) A6.1. The housing (**10**) of paragraph A6, wherein the tracking device (**12**) comprises a device body (**32**) and a device cover (**34**) removably coupled to the device body (**32**) to close the device opening (**28**); wherein the device body (**32**) defines the device opening (**28**); wherein the seal (**22**) engages the device body (**32**) around the device cover (**34**) when the tracking device (**12**) is operatively received within the internal volume (**18**).

(64) A6.1.1. The housing (**10**) of paragraph A6.1, wherein the seal (**22**) further engages the device cover (**34**) when the tracking device (**12**) is operatively received within the internal volume (**18**).

(65) A6.1.2. The housing (**10**) of any of paragraphs A6.1-A6.1.1, wherein the device body (**32**) comprises a circular planar surface (**56**) extending around the device opening (**28**); and wherein the seal (**22**) engages the circular planar surface (**56**) when the tracking device (**12**) is operatively received within the internal volume (**18**).

(66) A7. The housing (**10**) of any of paragraphs A-A6.1.2, further comprising the tracking device (**12**).

(67) A7.1. The housing (**10**) of paragraph A7, wherein the tracking device (**12**) is operatively received in the internal volume (**18**).

(68) A8. The housing (10) of any of paragraphs A-A7.1, wherein the housing body (16) comprises a first body portion (36) and a second body portion (38) that collectively define the internal volume (18).

(69) A8.1. The housing (10) of paragraph A8, wherein the second body portion (38) is removably coupled to the first body portion (36) to permit placement and removal of the tracking device (12) in and from the internal volume (18).

(70) A8.1.1. The housing (10) of paragraph A8.1, wherein the first body portion (36) and the second body portion (38) collectively define a thread structure (40).

(71) A8.1.1.1. The housing (10) of paragraph A8.1, wherein the thread structure (40) is configured to require less than 180-degrees of rotation of the first body portion (36) relative to the second body portion (38) for operatively coupling and decoupling of the first body portion (36) and the second body portion (38).

(72) A8.1.2. The housing (10) of paragraph A8.1, wherein the first body portion (36) and the second body portion (38) have a snap-fit arrangement or a friction-fit arrangement.

(73) A8.2. The housing (10) of paragraph A8, wherein the housing body (16) comprises a hinge (42), and wherein second body portion (38) is hinged to the first body portion (36).

(74) A8.3. The housing (10) of any of paragraphs A8-A8.2, wherein the seal (22) engages only one of the first body portion (36) or the second body portion (38) when the first body portion (36) and the second body portion (38) are operatively coupled together.

(75) A9. The housing (10) of any of paragraphs A-A8.3, wherein the article (14) is a flat flexible material (48).

(76) A9.1. The housing (10) of paragraph A9, further comprising: at least one fastener (44) configured to extend through the flat flexible material (48); wherein the housing body (16) defines at least one fastener bore (46) configured to operatively receive the at least one fastener (44).

(77) A9.1.1. The housing (10) of paragraph A9.1, wherein the at least one fastener (44) is configured to pierce the flat flexible material (48).

(78) A9.1.2. The housing (10) of any of paragraphs A9.1-A9.1.1, further comprising: a backing plate (50) configured to be positioned opposite the housing body (16) relative to the flat flexible material (48); wherein the at least one fastener (44) is configured to extend through the backing plate (50).

(79) A9.1.3. The housing (10) of any of paragraphs A9.1-A9.1.2 when depending from paragraph A8, wherein the at least one fastener bore (46) extends into the first body portion (36) and the second body portion (38); and wherein, when the at least one fastener (44) extends through the flat flexible material (48) and is operatively received in the at least one fastener bore (46), the at least one fastener (44) serves to secure the housing (10) to the flat flexible material (48) and to couple the first body portion (36) to the second body portion (38) to restrict access to the internal volume (18).

(80) A9.1.4. The housing (10) of any of paragraphs A9.1-A9.1.3, wherein the at least one fastener (44) comprises two fasteners (44).

(81) A10. The housing (10) of any of paragraphs A-A9.1.4, wherein the housing body (16) defines a through-hole (52) configured to receive at least a portion of the article (14).

(82) A10.1. The housing (10) of paragraph A10, wherein the article (14) is a key ring (54).

(83) A10.1.1. The housing (10) of paragraph A10.1, further comprising the key ring (54).

(84) A10.1.1.1. The housing (10) of paragraph A10.1.1, wherein the key ring (54) extends through the through-hole (52).

(85) A10.2. The housing (10) of any of paragraphs A10-A10.1.1.1 when depending from paragraph A8, wherein the through-hole (52) extends through the first body portion (36) and the second body portion (38); and wherein, when the article (14) operatively extends through the through-hole (52), the internal volume (18) is restricted from being fully accessed to receive the tracking device (12) in the internal volume (18) or to release the tracking device (12) from the internal volume (18).

(86) A10.2.1. The housing (10) of paragraph A10.2 when depending from paragraph A8.1.1, wherein, when the article (14) operatively extends through the through-hole (52), the article (14) restricts the thread structure (40) from fully separating the first body portion (36) from the second body portion (38).

(87) A11. The housing (10) of any of paragraphs A-A10.2.1, further comprising: an elongate retainer (58) extending from the housing body (16), wherein the elongate retainer (58) and the housing body (16) collectively define a passage (60) configured to receive at least a portion of the article (14).

(88) A11.1. The housing (10) of paragraph A11, wherein the elongate retainer (58) is removably coupled to the housing body (16).

(89) A11.2. The housing (10) of any of paragraphs A11-A11.1, wherein the elongate retainer (58) is rigid.

(90) A11.3. The housing (10) of any of paragraphs A11-A11.1, wherein the elongate retainer (58) is flexible.

(91) A11.4. The housing (10) of any of paragraphs A11-A11.3, wherein the elongate retainer (58) comprises end regions (62) positioned within the housing body (16); and wherein the housing body (16) is configured to restrict removal of the end regions (62) from within the housing body (16).

(92) A11.4.1. The housing (10) of paragraph A11.4, wherein each end region (62) of the end regions (62) defines a circumferential channel (64); and wherein the housing body (16) comprises a protrusion (66) that extends into each circumferential channel (64).

(93) A11.4.1.1. The housing (10) of paragraph A11.4.1 when depending from paragraph A8, wherein the first body portion (36) and the second body portion (38) collectively define the protrusion (66) that extends into each circumferential channel (64); wherein, when the first body portion (36) and the second body portion (38) are operatively coupled together, the end regions (62) are restricted from being removed from the housing body (16); and wherein, when the first body portion (36) and the second body portion (38) are operatively separated, the end regions (62) are permitted to be removed from the housing body (16).

(94) A12. The housing (10) of any of paragraphs A-A11.4.1.1, further comprising: a coupler (68) attached to the housing body (16) and configured to be operatively attached to the article (14).

(95) A12.1. The housing (10) of paragraph A12, wherein the coupler (68) comprises a double-sided adhesive.

(96) A12.2. The housing (10) of any of paragraphs A12-A12.1, wherein the coupler (68) comprises a double-sided foam tape.

(97) A12.3. The housing (10) of any of paragraphs A12-A12.2, wherein the coupler (68) comprises a magnet.

(98) A13. The housing (10) of any of paragraphs A-A12.3, wherein the housing (10) defines a central axis (70), and wherein the housing (10) is substantially radially symmetrical about the central axis (70).

(99) B. A housing (10) for a tracking device (12), the housing (10) comprising: a housing body (16) having an internal volume (18) configured to selectively receive and retain the tracking device (12); and an elongate retainer (58) extending from the housing body (16), wherein the elongate retainer (58) and the housing body (16) collectively define a passage (60) configured to receive at least a portion of an article (14), and wherein the elongate retainer (58) is rigid.

(100) B1. The housing (10) of paragraph B, wherein the elongate retainer (58) is removably coupled to the housing body (16).

(101) B2. The housing (10) of any of paragraphs B-B1, wherein the elongate retainer (58) comprises end regions (62) positioned within the housing body (16); and wherein the housing body (16) is configured to restrict removal of the end regions (62) from within the housing body (16).

(102) B2.1. The housing (10) of paragraph B2, wherein each end region (62) of the end regions (62) defines a circumferential channel (64); and wherein the housing body (16) comprises a

protrusion (66) that extends into each circumferential channel (64).

(103) B2.1.1. The housing (10) of paragraph B2.1, wherein the housing body (16) comprises a first body portion (36) and a second body portion (38) that collectively define the internal volume (18); wherein the first body portion (36) and the second body portion (38) collectively define the protrusion (66) that extends into each circumferential channel (64); wherein, when the first body portion (36) and the second body portion (38) are operatively coupled together, the end regions (62) are restricted from being removed from the housing body (16); and wherein, when the first body portion (36) and the second body portion (38) are operatively separated, at least one of the end regions (62) is permitted to be removed from the housing body (16).

(104) B3. The housing (10) of any of paragraphs B-B2.1.1, further comprising the subject matter of any of paragraphs A-A13.

(105) As used herein, the terms “adapted” and “configured” mean that the element, component, or other subject matter is designed and/or intended to perform a given function. Thus, the use of the terms “adapted” and “configured” should not be construed to mean that a given element, component, or other subject matter is simply “capable of” performing a given function but that the element, component, and/or other subject matter is specifically selected, created, implemented, utilized, programmed, and/or designed for the purpose of performing the function. It is also within the scope of the present disclosure that elements, components, and/or other recited subject matter that is recited as being adapted to perform a particular function may additionally or alternatively be described as being configured to perform that function, and vice versa. Similarly, subject matter that is recited as being configured to perform a particular function may additionally or alternatively be described as being operative to perform that function.

(106) As used herein, the term “and/or” placed between a first entity and a second entity means one of (1) the first entity, (2) the second entity, and (3) the first entity and the second entity. Multiple entries listed with “and/or” should be construed in the same manner, i.e., “one or more” of the entities so conjoined. Other entities optionally may be present other than the entities specifically identified by the “and/or” clause, whether related or unrelated to those entities specifically identified. Thus, as a non-limiting example, a reference to “A and/or B,” when used in conjunction with open-ended language such as “comprising,” may refer, in one example, to A only (optionally including entities other than B); in another example, to B only (optionally including entities other than A); in yet another example, to both A and B (optionally including other entities). These entities may refer to elements, actions, structures, steps, operations, values, and the like.

(107) The various disclosed elements of apparatuses and steps of methods disclosed herein are not required to all apparatuses and methods according to the present disclosure, and the present disclosure includes all novel and non-obvious combinations and subcombinations of the various elements and steps disclosed herein. Moreover, one or more of the various elements and steps disclosed herein may define independent inventive subject matter that is separate and apart from the whole of a disclosed apparatus or method. Accordingly, such inventive subject matter is not required to be associated with the specific apparatuses and methods that are expressly disclosed herein, and such inventive subject matter may find utility in apparatuses and/or methods that are not expressly disclosed herein.

## Claims

1. A housing (10) for a tracking device (12), the housing (10) comprising: a housing body (16) having an internal volume (18) configured to selectively receive and retain the tracking device (12) in a close-fit relationship, wherein the internal volume (18) has a width (20) and a height (21), and wherein the housing body (16) comprises a first body portion (36) and a second body portion (38) that collectively define the internal volume (18); and a seal (22) positioned within the internal volume (18) or configured to be positioned within the internal volume (18) to engage both the

housing body (16) and the tracking device (12) when the tracking device (12) is operatively received in the internal volume (18), wherein the seal (22) has an outermost seal dimension (24) that is less than the width (20) of the internal volume (18), wherein the seal (22) engages only one of the first body portion (36) or the second body portion (38) when the first body portion (36) and the second body portion (38) are operatively coupled together, and wherein the seal (22) is positioned to engage a device body (32) of the tracking device (12) around a device cover (34) of the tracking device (12) when the tracking device (12) is operatively received within the internal volume (18).

2. The housing (10) of claim 1, wherein the housing (10) is configured to be secured to a flat flexible material (48); wherein the second body portion (38) is removably coupled to the first body portion (36) to permit placement and removal of the tracking device (12) in and from the internal volume (18); wherein the housing (10) further comprises at least one fastener (44) configured to pierce and extend through the flat flexible material (48); wherein the housing body (16) defines at least one fastener bore (46) configured to operatively receive the at least one fastener (44); wherein the at least one fastener bore (46) extends into the first body portion (36) and the second body portion (38); and wherein, when the at least one fastener (44) extends through the flat flexible material (48) and is operatively received in the at least one fastener bore (46), the at least one fastener (44) serves to secure the housing (10) to the flat flexible material (48) and to couple the first body portion (36) to the second body portion (38) to restrict access to the internal volume (18).

3. The housing (10) of claim 1, wherein the first body portion (36) and the second body portion (38) collectively define a thread structure (40); wherein the first body portion (36) and the second body portion (38) collectively define a through-hole (52) configured to receive a key ring (54); and wherein, when the key ring (54) operatively extends through the through-hole (52), the key ring (54) restricts the thread structure (40) from fully separating the first body portion (36) from the second body portion (38).

4. The housing (10) of claim 1, wherein the housing body (16) comprises a hinge (42), and wherein the second body portion (38) is hinged to the first body portion (36); wherein the housing (10) further comprises at least one fastener (44); wherein the housing body (16) defines at least one fastener bore (46) configured to operatively receive the at least one fastener (44); wherein the at least one fastener bore (46) extends into the first body portion (36) and the second body portion (38); wherein the housing (10) further comprises an elongate retainer (58) extending from the housing body (16); wherein the elongate retainer (58) and the housing body (16) collectively define a passage (60) configured to receive at least a portion of an article (14); wherein the elongate retainer (58) is removably coupled to the housing body (16); wherein the elongate retainer (58) comprises end regions (62) positioned within the housing body (16); wherein the housing body (16) is configured to restrict removal of the end regions (62) from within the housing body (16); wherein each end region (62) of the end regions (62) defines a circumferential channel (64); and wherein the housing body (16) comprises a protrusion (66) that extends into each circumferential channel (64); and wherein, when the first body portion (36) and the second body portion (38) are operatively coupled together with the at least one fastener (44), the end regions (62) are restricted from being removed from the housing body (16); and wherein, when the first body portion (36) and the second body portion (38) are operatively separated, the end regions (62) are permitted to be removed from the housing body (16).

5. The housing (10) of claim 1, wherein the housing (10) further comprise a coupler (68) attached to the housing body (16) and configured to be operatively attached to an article (14); wherein the coupler (68) comprises a double-sided adhesive and/or a magnet; wherein the housing (10) defines a central axis (70); and wherein the housing (10) is substantially radially symmetrical about the central axis (70).

6. A housing (10) for a tracking device (12), the housing (10) comprising: a housing body (16) having an internal volume (18) configured to selectively receive and retain the tracking device (12)



in a close-fit relationship, wherein the internal volume (18) has a width (20) and a height (21); and a seal (22) positioned within the internal volume (18) or configured to be positioned within the internal volume (18) to engage both the housing body (16) and the tracking device (12) when the tracking device (12) is operatively received in the internal volume (18), wherein the seal (22) has an outermost seal dimension (24) that is less than the width (20) of the internal volume (18); wherein the housing (10) is configured to be secured to an article (14); wherein the tracking device (12) defines a battery compartment (26) and a device opening (28) to the battery compartment (26); wherein the device opening (28) has an outermost opening dimension (30) that is less than the outermost seal dimension (24); wherein the tracking device (12) comprises a device body (32) and a device cover (34) removably coupled to the device body (32) to close the device opening (28); wherein the device body (32) defines the device opening (28); wherein the seal (22) engages the device body (32) around the device cover (34) when the tracking device (12) is operatively received within the internal volume (18).

7. The housing (10) of claim 6, wherein the seal (22) is positioned within the internal volume (18) or is configured to be positioned within the internal volume (18) to protect less than an entirety of the tracking device (12) from environment external to the housing (10) when the tracking device (12) is operatively received in the internal volume (18).

8. The housing (10) of claim 6, wherein the device body (32) comprises a circular planar surface (56) extending around the device opening (28); and wherein the seal (22) engages the circular planar surface (56) when the tracking device (12) is operatively received within the internal volume (18).

9. The housing (10) of claim 6, further comprising the tracking device (12), wherein the tracking device (12) is operatively received in the internal volume (18).

10. The housing (10) of claim 6, wherein the housing body (16) comprises a first body portion (36) and a second body portion (38) that collectively define the internal volume (18); and wherein the second body portion (38) is removably coupled to the first body portion (36) to permit placement and removal of the tracking device (12) in and from the internal volume (18).

11. The housing (10) of claim 10, wherein the first body portion (36) and the second body portion (38) collectively define a thread structure (40).

12. The housing (10) of claim 10, wherein the first body portion (36) and the second body portion (38) have a snap-fit arrangement or a friction-fit arrangement.

13. The housing (10) of claim 6, wherein the housing body (16) comprises a first body portion (36) and a second body portion (38) that collectively define the internal volume (18); and wherein the housing body (16) comprises a hinge (42), and wherein the second body portion (38) is hinged to the first body portion (36).

14. The housing (10) of claim 13, wherein the seal (22) engages only one of the first body portion (36) or the second body portion (38) when the first body portion (36) and the second body portion (38) are operatively coupled together.

15. The housing (10) claim 6, wherein the article (14) is a flat flexible material (48); wherein the housing (10) further comprises at least one fastener (44) configured to pierce and extend through the flat flexible material (48); wherein the housing body (16) defines at least one fastener bore (46) configured to operatively receive the at least one fastener (44); wherein the housing body (16) comprises a first body portion (36) and a second body portion (38) that collectively define the internal volume (18); wherein the at least one fastener bore (46) extends into the first body portion (36) and the second body portion (38); and wherein, when the at least one fastener (44) extends through the flat flexible material (48) and is operatively received in the at least one fastener bore (46), the at least one fastener (44) serves to secure the housing (10) to the flat flexible material (48) and to couple the first body portion (36) to the second body portion (38) to restrict access to the internal volume (18).

16. The housing (10) of claim 6, wherein the housing body (16) comprises a first body portion (36)

and a second body portion (38) that collectively define the internal volume (18); wherein the second body portion (38) is removably coupled to the first body portion (36) to permit placement and removal of the tracking device (12) in and from the internal volume (18); wherein the first body portion (36) and the second body portion (38) collectively define a thread structure (40); wherein the first body portion (36) and the second body portion (38) collectively define a through-hole (52) configured to receive at least a portion of the article (14); and wherein, when the article (14) operatively extends through the through-hole (52), the internal volume (18) is restricted from being fully accessed to receive the tracking device (12) in the internal volume (18) or to release the tracking device (12) from the internal volume (18).

17. The housing (10) of claim 6, wherein the housing body (16) comprises a first body portion (36) and a second body portion (38) that collectively define the internal volume (18); wherein the housing body (16) comprises a hinge (42), and wherein the second body portion (38) is hinged to the first body portion (36); wherein the housing (10) further comprises at least one fastener (44); wherein the housing body (16) defines at least one fastener bore (46) configured to operatively receive the at least one fastener (44); wherein the at least one fastener bore (46) extends into the first body portion (36) and the second body portion (38); wherein the housing (10) further comprises an elongate retainer (58) extending from the housing body (16); wherein the elongate retainer (58) and the housing body (16) collectively define a passage (60) configured to receive at least a portion of the article (14); wherein the elongate retainer (58) is removably coupled to the housing body (16); wherein the elongate retainer (58) comprises end regions (62) positioned within the housing body (16); wherein the housing body (16) is configured to restrict removal of the end regions (62) from within the housing body (16); wherein each end region (62) of the end regions (62) defines a circumferential channel (64); and wherein the housing body (16) comprises a protrusion (66) that extends into each circumferential channel (64); and wherein, when the first body portion (36) and the second body portion (38) are operatively coupled together with the at least one fastener (44), the end regions (62) are restricted from being removed from the housing body (16); and wherein, when the first body portion (36) and the second body portion (38) are operatively separated, the end regions (62) are permitted to be removed from the housing body (16).

18. The housing (10) of claim 6, wherein the housing (10) further comprise a coupler (68) attached to the housing body (16) and configured to be operatively attached to the article (14); and wherein the coupler (68) comprises a double-sided adhesive and/or a magnet.

19. The housing (10) of claim 18, wherein the housing (10) defines a central axis (70); and wherein the housing (10) is substantially radially symmetrical about the central axis (70).

20. The housing (10) of claim 17, wherein the elongate retainer (58) is rigid.

---