

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12390865
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Farniok; Craig Martin et al.

---

### Tool alignment system and method

---

#### Abstract

A system and a method include a fixture template configured to be secured to a component. The fixture template includes a plurality of insert holes. A plurality of guide inserts have channels. Each of the channels has an orientation. The orientation of at least two of the plurality of guide inserts differs. Each of the plurality of guide inserts is removably secured within a respective one of the plurality of insert holes to position and orient the channels in relation to a pattern of openings to be formed in relation to the component. Each of the channels is configured to receive an operative member of a tool that is configured to form the pattern of openings in relation to the component.

---

**Inventors:** Farniok; Craig Martin (Godfrey, IL), Roffo; Todd Jeremy (San Antonio, TX), Brown; Thomas A. (Moncks, SC)

**Applicant:** THE BOEING COMPANY (Chicago, IL)

**Family ID:** 1000008767790

**Assignee:** The Boeing Company (Chicago, IL)

**Appl. No.:** 17/650091

**Filed:** February 07, 2022

#### Prior Publication Data

Document Identifier	Publication Date
US 20230249265 A1	Aug. 10, 2023

---

#### Publication Classification

**Int. Cl.:** B23B49/02 (20060101); B23B47/28 (20060101)

**U.S. Cl.:**

CPC     **B23B49/023** (20130101); **B23B47/28** (20130101); B23B2215/04 (20130101);  
B23B2247/10 (20130101); B23B2260/026 (20130101); Y10T408/03 (20150115);  
Y10T408/568 (20150115); Y10T408/569 (20150115)

## Field of Classification Search

**CPC:**     B23B (2247/08); B23B (2247/10); B23B (2247/00); B23B (2260/026); B23B (2260/104);  
B23B (2260/004); B23B (2270/58); B23B (2215/04); B23B (49/023); B23B (49/02);  
B23B (49/00); B23B (47/28); B23B (51/0054); B23B (11/00); B23B (39/025); B23B  
(47/287); B23Q (39/025); Y10T (408/567); Y10T (408/568); Y10T (408/569)

**USPC:**    408/115R; 408/115B; 408/72B

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2209433	12/1939	Ulrich	408/72R	B23B 47/28
2265616	12/1940	Ulrich	92/236	F16J 1/06
2548197	12/1950	Conner	33/562	B23B 47/287
4586846	12/1985	Kellison	404/6	B28D 1/14
4793747	12/1987	Reitz	408/72R	B23B 47/28
4922573	12/1989	Miller	156/92	F16B 37/122
5056965	12/1990	Tsui	408/241B	B23B 49/023
5318394	12/1993	Pierce	408/241B	B23B 47/287
5947656	12/1998	Simson	408/241B	B23B 47/28
7073991	12/2005	Thomas	408/103	B23B 47/287
7112014	12/2005	Thomas	408/1R	E05B 17/06
9108250	12/2014	Bui	N/A	B23B 47/28
10183340	12/2018	Lentz	N/A	B23B 49/023
2003/0157457	12/2002	Blacklock	433/76	A61B 17/176
2016/0199922	12/2015	Andersson	700/160	G05B 19/4015
2023/0405690	12/2022	Nelson	N/A	F16B 15/00

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106825688	12/2016	CN	B23B 47/287
4227975	12/1992	DE	B23B 47/287
2063730	12/1980	GB	B23B 49/02
2346573	12/1999	GB	B23B 47/28
2001059297	12/2000	JP	B23B 47/287
2001259912	12/2000	JP	B23B 49/02
WO-2004076106	12/2003	WO	A61C 1/084

---

*Primary Examiner:* Singh; Sunil K

*Assistant Examiner:* Vitale; Michael

*Attorney, Agent or Firm:* The small Patent LAw Group LLC

---

## Background/Summary

### FIELD OF THE DISCLOSURE

(1) Examples of the present disclosure generally relate to tool alignment systems and methods, such as are used to align an operative portion of a tool in relation to a component that is configured to be modified by the tool.

### BACKGROUND OF THE DISCLOSURE

(2) Various components are operated on by tools. For example, a tool can be used to drill holes into a component, such as a panel, sheet, block, or the like. As another example, a saw can be used to cut portions of components. A tool includes an operative member, such as a drill bit, blade, laser emitter, and/or the like.

(3) Various systems include components that may be replaced. For example, portions of a fuselage of an aircraft can be replaced. As a further example, a first outer skin portion of an aircraft can be replaced with a second outer skin portion. A tool, such as a drill, can be used to form holes in the skin portions that receive fasteners, such as bolts, which secure the skin portions to another portion of the fuselage. When the first outer skin portion is removed, a hole pattern of the second outer skin portion typically needs to match that of the replaced portion, and/or is configured to secure in a different pattern. In either case, however, the hole pattern is precisely positioned and oriented in order to securely and properly couple the replacement portion to another portion to which the replacement portion secures.

(4) Currently, a variety of non-efficient methods are utilized to transfer hole locations from an initial part to a replacement part. As an example, when a skin on an aircraft is replaced, it can be difficult to transfer the locations of the openings on the old skin to the new skin due to accessibility.

(5) In general, manually laying out a pattern of holes for drilling is labor and time intensive, and typically relies upon highly skilled craftsmen for measurement, layout, and drilling.

### SUMMARY OF THE DISCLOSURE

(6) A need exists for a system and a method for efficiently and effectively forming a pattern of holes in a component. Further, a need exists for a system and a method for efficiently and effectively replacing portions of a component, such as skin portions of a fuselage of an aircraft.

(7) With those needs in mind, certain examples of the present disclosure provide a system including a fixture template configured to be secured to a component. The fixture template includes a plurality of insert holes. A plurality of guide inserts has guiding features, such as channels. Each of the channels has an orientation. The orientation of at least two of the plurality of guide inserts differs. Each of the plurality of guide inserts is removably secured within a respective one of the plurality of insert holes to position and orient the channels in relation to a pattern of openings to be formed in relation to the component. Each of the channels is configured to receive an operative member of a tool that is configured to form the pattern of openings in relation to the component.

(8) In at least one example, the tool is a drill. In at least one example, the component is a portion of an aircraft.

(9) In at least one example, the fixture template further includes index slots connected to the plurality of insert holes (for example, slotted apertures that extend from the holes). The plurality of guide inserts include keys that are configured to be removably secured within the index slots.

(10) In at least one example, the orientation of each of and all of the plurality of guide inserts differs.

(11) In at least one example, each of the plurality of guide inserts includes a plug and a collar. The channels are formed through the plug and collar. The plug is configured to be received and retained by one of the plurality of insert holes.

(12) In at least one example, outer dimensions of the plug and the collar for each of the plurality of

guide inserts are common.

(13) The orientation includes a length, an axial angle, and a radial angle. In at least one example, the orientation of at least two of the plurality of guide inserts differs with respect to one or more of the length, the axial angle, or the radial angle.

(14) In at least one example, the fixture template further includes a different fixture identifier proximate to each of the plurality of insert holes. Each of the plurality of guide inserts includes a different insert identifier. Each of the different insert identifiers corresponds to one of the different fixture identifiers to ensure proper location of the plurality of guide inserts within the plurality of insert holes.

(15) Certain examples of the present disclosure provide a method including securing a fixture template to a component, the fixture template including a plurality of insert holes; removably securing each of a plurality of guide inserts within a respective one of the plurality of insert holes to position and orient channels of the plurality of guide inserts in relation to a pattern of openings to be formed in relation to the component, wherein each of the channels has an orientation, wherein the orientation of at least two of the plurality of guide inserts differs; and receiving, by each of the channels, an operative member of a tool that is configured to form the pattern of openings in relation to the component.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a schematic block diagram of a system for aligning a tool in relation to a component, according to an example of the present disclosure.

(2) FIG. 2 illustrates an isometric top view of a fixture template, according to an example of the present disclosure.

(3) FIG. 3 illustrates an isometric top view of guide inserts, according to an example of the present disclosure.

(4) FIG. 4 illustrates a top view of a guide insert, according to an example of the present disclosure.

(5) FIG. 5A illustrates an axial cross section of a guide insert through line 5-5 of FIG. 4, according to an example of the present disclosure.

(6) FIG. 5B illustrates an axial cross section of a guide insert through line 5-5 of FIG. 4, according to an example of the present disclosure.

(7) FIG. 5C illustrates an axial cross section of a guide insert through line 5-5 of FIG. 4, according to an example of the present disclosure.

(8) FIG. 6 illustrates an isometric top view of the system, according to an example of the present disclosure.

(9) FIG. 7 illustrates a flow chart of a method for aligning a tool in relation to a component, according to an example of the present disclosure.

(10) FIG. 8 illustrates a perspective front view of an aircraft, according to an example of the present disclosure.

### DETAILED DESCRIPTION OF THE DISCLOSURE

(11) The foregoing summary, as well as the following detailed description of certain examples will be better understood when read in conjunction with the appended drawings. As used herein, an element or step recited in the singular and preceded by the word “a” or “an” should be understood as not necessarily excluding the plural of the elements or steps. Further, references to “one example” are not intended to be interpreted as excluding the existence of additional examples that also incorporate the recited features. Moreover, unless explicitly stated to the contrary, examples “comprising” or “having” an element or a plurality of elements having a particular condition can include additional elements not having that condition.

(12) Certain examples of the present disclosure provide adaptable drill fixture devices that include modular and removable drill guide bushings with indexing features for positive location within receiving holes contained in a drill fixture or template. Replication of existing hole patterns can be achieved by incorporating each unique hole location and orientation from actual, measured holes within the modular drill guide bushing and relying upon placement of each individual hole by known locations of receiving holes in the drill fixture. Three dimensional measurement data of holes is utilized to fabricate unique bushings (which could be three-dimensionally printed) for each hole, which serve as guides for drilling holes to replicate hole patterns. Examples of the present disclosure provide accurately replicated hole patterns for mating parts, and reduce occurrence of oversized holes for replicated hole patterns.

(13) In at least one example, the system and method provide an adaptable drill fixture device and drill guides which can be utilized within a standardized drill fixture for replication of hole patterns in which hole location and orientation variation is anticipated. Examples of the present disclosure ensure that accurate hole locations are drilled for mating hole patterns.

(14) Certain examples of the present disclosure provide a system that includes a fixture template and a plurality of guide inserts or bushings to be installed in the fixture template. Each guide insert has an opening extending therethrough that has a position and orientation. The position and orientation of the guide insert opening corresponds to a position and orientation of an opening extending through a receiving structure. Each guide insert is configured to be installed in a particular location and orientation within the fixture template. In at least one example, each guide bushing includes an identifier, such as a label, which enables an operator to install the guide bushing in the correct location within the fixture template. Additionally, each guide bushing includes a key or keying feature, such as an indexing pin, that mates with an index slot formed within the opening in the fixture template. In this manner, the guide bushing is properly oriented within the opening, which ensures that the location and orientation of the opening extending through the guide bushing matches the location and orientation of the opening extending through the receiving structure.

(15) FIG. 1 illustrates a schematic block diagram of a system **100** for aligning a tool **102** in relation to a component **104**, according to an example of the present disclosure. The tool **102** is configured to operate on the component **104**. The tool **102** can be a drill, for example. As such, the tool **102** has an operative member **106**, such as a drill bit, that is configured to form holes on, in, and/or through the component **104**. As another example, the tool **102** can be a saw. In this example, the operative member **106** can be a blade, for example, which is configured to cut the component **104**, and/or form incisions on, in, and/or through the component **104**. As another example, the tool **102** can be a laser cutting tool. As another example, the tool **102** can be a fastener driving tool, such as a screw driver.

(16) The component **104** can be any type of structure that is to be operated on by the tool **102**. For example, the component **104** can be a panel, sheet, block, and/or the like. In at least one example, the component **104** is a portion of a fuselage of an aircraft, such as an outer skin portion. In at least one example, the component **104** is a replacement skin that is to be secured to another portion of an aircraft, such as to a frame, stringer, and/or the like. The tool **102** is configured to form a pattern of openings **103** in relation to (such as on, in, and/or through) the component **104**. In at least one example, the pattern of openings **103** are configured to receive fasteners, such as bolts or screws that are configured to secure the component **104** to another structure.

(17) The system **100** includes a fixture template **108** and a plurality of guide inserts **110** that are configured to align the operative member **106** of the tool **102** to efficiently, effectively, and accurately form the pattern of openings **103** in relation to the component **104**. The fixture template **108** includes a plurality of insert holes **112** and index slots **114**. The insert holes **112** correspond to a number of the guide inserts **110**. For example, if a pattern of openings **103** include five openings, the fixture template **108** includes five insert holes **112** that are configured to receive and retain five

respective guide inserts **110**. The shape of the fixture template **108**, the number of insert holes **112**, the number of guide inserts **110** depends on a desired pattern of openings **103** to be formed. The number of insert holes **112** and guide inserts **110** can be any number, depending on the desired pattern of openings **103** to be formed in relation to the component **104**. The system **100** can include two or more insert holes **112** and two or more guide inserts **110**. For example, the system **100** can include five, six, seven, or more insert holes **112** and respective guide inserts **110**.

(18) Each guide insert **110** includes a guiding feature, such as a channel **116**, and a key **118**. The channel **116** is configured to receive the operative member **106** of the tool **102**. The key **118** is configured to be removably secured within, such as received and retained by, a respective index slot **114** of the fixture template **108**. For example, the key **118** can be a protuberance, such as a fin, tab, pin, or the like extending from an outer surface of the guide insert **110**. The key **118** is configured to fit into a respective index slot **114** of the fixture template **108** to secure the guide insert **110** in the fixture template **108** at a particular position, so that the channel **116** is at a desired orientation.

(19) In operation, the fixture template **108** is secured to the component **104** at a desired position to align the operative member **106** of the tool **102** to form the pattern of openings **103**, which is predetermined. For example, the fixture template **108** can be clamped to the component **104**. As another example, the fixture template **108** can be secured to the component **104** through adhesives, fasteners, and/or the like. The fixture template **108** is configured to receive and retain the guide inserts **110** within respective insert holes **112**.

(20) In at least one example, the channels **116** of the guide inserts **110** are at different orientations. Each guide insert **110** is inserted into a respective insert hole **112** of the fixture template at a particular position in relation to the component **104**. The orientations of at least two of the channels **116** of the guide inserts **110** that are inserted into the fixture template **108** differ from one another. In at least one example, when the guide inserts **110** are inserted into the insert holes **112** of the fixture template **108** at respective positions (which differ from another), the orientations of all of the channels **116** differ from one another.

(21) After the guide inserts **110** are disposed within the insert holes **112**, the tool **102** can be used in conjunction with the fixture template **108** and the guide inserts **110** to form the pattern of openings **103**. For example, the channels **116** are sized and shaped to receive and constrain the operative member **106** of the tool **102**. As an example, the diameter of each channel **116** can be sized and shaped to receive the operative member **106**, such as a drill bit, to ensure that the operative member is axially constrained and allowed to operatively rotate to form an opening in the component **104**. The fixture template **108** secures the guide inserts **110** at desired positions, and the guide inserts **110** have the channels **116** at desired orientations to ensure that the tool **102** forms the pattern of openings **103** in relation to the component **104**, as desired.

(22) As described herein, the system **100** includes the fixture template **108** configured to be secured to the component **104**. The fixture template **108** includes the plurality of insert holes **112**. The plurality of guide inserts **110** have channels **116**. Each of the channels **116** has an orientation. The orientation of at least two of the plurality of guide inserts **110** differs. Each of the plurality of guide inserts **110** is removably secured within a respective one of the plurality of insert holes **112** to position (at different locations of the fixture template **108**) and orient the channels **116** in relation to the pattern of openings **103** to be formed in relation to the component **104**. Each of the channels **116** is configured to receive the operative member **106** of the tool **102** that is configured to form the pattern of openings **103** in relation to the component **104**.

(23) FIG. 2 illustrates an isometric top view of a fixture template **108**, according to an example of the present disclosure. The fixture template **108** includes a main body **120**, such as a frame. The main body **120** includes a first surface **122**, such as a top surface, opposite from a second surface **124**, such as a bottom surface. The second surface **124** is configured to abut against a surface of the component **104** (shown in FIG. 1). The insert holes **112** are formed through the main body **120**,

such as between and through the first surface **122** and the second surface **124**. Index slots **114** connect to (for example, extend from) the insert holes **112**. That is, an index slot **114** connects to each insert hole **112**.

(24) The fixture template **108** can be sized and shaped differently than shown. Further, the fixture template **108** can include more or less insert holes **112** and index slots **114** than shown.

(25) FIG. 3 illustrates an isometric top view of guide inserts **110**, according to an example of the present disclosure. In at least one example, the guide inserts **110** are bushings that are configured to be received and retained within the insert holes **112** of the fixture template (shown in FIGS. 1 and 2).

(26) Each guide insert **110** includes a plug **130** connected to a collar **132**. Outer portions of the plugs **130** and the collars **132** can be the same for each of the guide inserts **110**. That is, each of the guide inserts **110** can have common (for example, the same) outer dimensions for the plugs **130** and the collars **132**.

(27) Referring to FIGS. 1-3, the plugs **130** are sized and shaped to fit within the insert holes **112** of the fixture template **108**. In particular, the plugs **130** have an outer perimeter that is slightly smaller than an outer perimeter of the insert holes **112**, so that the plugs **130** can be received and retained within the insert holes **112**. The collars **132** have larger perimeters than the plugs **130** and the insert holes **112**, thereby ensuring that the guide inserts **110** do not fall through the insert holes **112**. As shown, the plugs **130** and the collars **132** can have circular axial cross-sections. Optionally, the plugs **130** and the collars **132** can have different axial cross-sections, which correspond to the axial cross-sections of the insert holes **112**.

(28) Each guide insert **110** further includes a key **118** outwardly extending from an outer surface of a plug **130** and/or a collar **132**. For example, the key **118** can be a fin, pin, tab, or the like. The key **118** is sized and shaped to fit into a respective index slot **114** of the fixture template **108**. The key **118** ensures that the guide insert **110** is properly positioned and oriented within the fixture template. Further, the key **118** retained within the index slot **114** ensures that the guide insert **110** is axially and rotationally constrained, thereby ensuring that the guide insert **110** remains properly positioned and oriented when the operative member **106** is disposed within the channel **116**.

(29) The channel **116** for each guide insert **110** extends therethrough, such as between and through the collar **132** and the plug **130**. In at least one example, the channel **116** is oriented differently for at least two of the guide inserts **110**. In at least one example, the channel **116** for each of the guide inserts **110** is at a different orientation.

(30) In at least one example, a diameter **140** of each channel **116** is the same. For example, the diameter **140** is sized and shaped to receive and axially constrain the operative member **106** of the tool **102** (shown in FIG. 1). Each of the channels **116** has an orientation within the guide inserts **110**. The orientation includes a length and at least one angle. The orientation for the channels **116** of the guide inserts **110** can differ in relation to one or both of the length and/or the angle.

(31) FIG. 4 illustrates a top view of a guide insert **110**, according to an example of the present disclosure. The channel **116** extends through the guide insert **110**. The channel **116** is sized and shaped to receive and axially constrain the operative member **106** of the tool **102**. For example, the channel **116** is sized and shaped to receive and axially constrain a drill bit of a drilling tool.

(32) FIG. 5A illustrates an axial cross section of a guide insert **110a** through line 5-5 of FIG. 4, according to an example of the present disclosure. As shown, the channel **116** of the guide insert **110a** can be coaxial with the plug **130** and the collar **132**. The channel **116** has a first length **150**. The channel **116** has an axis **117** having a first axial angle in relation to the key **118**. For example, the axis **117** is parallel with a longitudinal axis **119** of the key **118**. Referring to FIGS. 4 and 5A, the axis **117** also has a first radial angle  $\beta$  in relation to the key **118**. The first radial angle  $\beta$  can be zero degrees, for example. Optionally, the first radial angle  $\beta$  can be greater than zero degrees. The first radial angle  $\beta$  can be range from zero and three hundred and sixty degrees.

(33) FIG. 5B illustrates an axial cross section of a guide insert **110b** through line 5-5 of FIG. 4,

according to an example of the present disclosure. As shown, the channel **116** of the guide insert **110b** is not coaxial with the plug **130** and the collar **132**. The channel **116** has a second length **152**, which is longer than the first length **150** shown in FIG. 5A. The channel **116** has an axis **117** having a second axial angle  $\theta$  in relation to the key **118**. For example, the axis **117** is at the angle  $\theta$  in relation to the longitudinal axis **119** of the key **118**. The second axial angle  $\theta$  differs from the first axial angle of FIG. 5A. Referring to FIGS. 4 and 5B, the axis **117** also has a second radial angle in relation to the key **118**. The second radial angle  $\theta$  can differ from the first radial angle  $\beta$  of the guide insert **110a**. Optionally, the first radial angle  $\beta$  and the second radial angle  $\beta$  can be the same.

(34) FIG. 5C illustrates an axial cross section of a guide insert **110c** through line 5-5 of FIG. 4, according to an example of the present disclosure. As shown, the channel **116** of the guide insert **110b** is not coaxial with the plug **130** and the collar **132**. The channel **116** has a third length **154**, which can be different than the first length **150** shown in FIG. 5A and/or the second length **152** shown in FIG. 5B. The channel **116** has an axis **117** having a third axial angle  $\theta$  in relation to the key **118**. For example, the axis **117** is at the angle  $\theta$  in relation to the longitudinal axis **119** of the key **118**. The third axial angle  $\theta$  differs from the first axial angle of FIG. 5A, and the second axial angle of FIG. 5B. Referring to FIGS. 4 and 5B, the axis **117** also has a third radial angle in relation to the key **118**. The third radial angle  $\beta$  can differ from the first radial angle  $\beta$  of the guide insert **110a** and/or the second radial angle  $\beta$  of the guide insert **110b**. Optionally, the third radial angle  $\beta$  can be the same as one or both of the first radial angle  $\beta$  and/or the second radial angle  $\beta$ .

(35) Referring to FIGS. 4-5C, examples of guide inserts **110a-110c** are shown. The channels **116** of the guide inserts **110** have different orientations. The orientations differ with respect to one or more of length, axial angle, and/or radial angle. The orientations of the channels **116** shown in FIGS. 5A-5C are merely exemplary, and can be different than shown. In at least one example, orientations of at least two of the channels **116** of the guide inserts **110** shown in FIGS. 1 and 3 can be different, while orientations of at least two channels **116** of other guide inserts **110** can be the same.

(36) Referring again to FIGS. 1-3, mating between the keys **118** and the index slots **114** ensures that the guide inserts **110** are securely positioned within the fixture template **108** at respective positions of the fixture template **108**. The mating between the keys **118** and the index slots **114** also constrains the guide inserts **110** within the insert holes **112** to ensure that the orientations of the channels **116** are maintained when the operative member **106** of the tool **102** is disposed within the channels **116**.

(37) In at least one example, the fixture template **108** also includes a fixture identifier **160** proximate to (such as directly below, to a lower left, or the like of) each insert hole **112**. The fixture identifier **160** can be a number, letter, text, or the like. Similarly, each guide insert **110** includes an insert identifier **162**, such as on an outer surface of a plug **130**. The insert identifier **162** can be a number, letter, text, or the like. The fixture identifier **160** corresponds to the insert identifier **162** of a corresponding guide insert **110** to be disposed within a particular insert hole **112**. In this manner, the fixture identifiers **160** and the insert identifiers **162** cooperate to ensure that a particular guide insert **110** having a desired orientation is disposed within the appropriate insert hole **112**. That is, the insert identifier **162** of a guide insert **110** is to match the fixture identifier **160** proximate to a corresponding insert hole **112** to ensure proper positioning of the guide inserts **110** within the fixture template **108**. Alternatively, the fixture template **108** may not include fixture identifiers, and the guide inserts **110** may not include insert identifiers.

(38) FIG. 6 illustrates an isometric top view of the system **100**, according to an example of the present disclosure. Referring to FIGS. 1-6, as shown, the fixture template **108** secures each of the guide inserts **110** at a different position. That is, each guide insert **110** is secured within a respective insert hole **112** of the fixture template **108**. The channels **116** of the guide inserts **110** are oriented differently, thereby providing different operative paths **180** (both in terms of a different position, and a different orientation) for the operative member **106** of the tool **102**.

(39) In at least one example, the locations of the insert holes **112**, the orientation of the index slots



**114**, and the orientations of the channels **116** are predetermined, and are used to fabricate the fixture template **108** and the guide inserts **110**, in order to replicate hole locations for the pattern of openings **103**.

(40) As described herein, certain examples of the present disclosure provide the system **100**, which can be an adaptable drill fixture device. The system **100** includes modular and removable guide inserts **110**, such as drill guide bushings, having indexing features (such as the keys **118**) for positive location within the insert holes **112** of the fixture template **108**. Replication of existing hole patterns (such as a desired pattern of openings **103**) can be achieved by incorporating each unique hole location and orientation from the channels **116** of the guide inserts **110**. Three dimensional measurement data of holes is utilized to fabricate the guide inserts **110** for each hole of the pattern of openings **103**.

(41) FIG. 7 illustrates a flow chart of a method for aligning a tool in relation to a component, according to an example of the present disclosure. Referring to FIGS. 1 and 7, the method begins at **200**, at which the fixture template **108** is secured to the component **104** at a location to form a desired pattern of openings **103** in relation to the component **104**. At **202**, the guide inserts **110** are inserted into corresponding insert holes **112** of the fixture template **108**. At **204**, the operative member **106** of the tool **102** is inserted into the channels **116** of the guide inserts **110** (and the tool **102** operated accordingly) to form the pattern of the openings **103**.

(42) FIG. 8 illustrates a perspective front view of an aircraft **300**, according to an example of the present disclosure. The aircraft **300** includes a propulsion system **312** that includes engines **314**, for example. Optionally, the propulsion system **312** may include more engines **314** than shown. The engines **314** are carried by wings **316** of the aircraft **300**. In other examples, the engines **314** may be carried by a fuselage **318** and/or an empennage **320**. The empennage **320** may also support horizontal stabilizers **322** and a vertical stabilizer **324**. The fuselage **318** of the aircraft **300** defines an internal cabin **330**, which includes a flight deck or cockpit, one or more work sections (for example, galleys, personnel carry-on baggage areas, and the like), one or more passenger sections (for example, first class, business class, and coach sections), one or more lavatories, and/or the like.

(43) Examples of the present disclosure can be used to form a pattern of openings on various components of the aircraft **300**, for example. For example, the systems and methods described herein can be used to form patterns of openings in various replacement components, such as replacement skin panels, of the aircraft **300**. FIG. 8 shows an example of an aircraft **300**. It is to be understood that the aircraft **300** can be sized, shaped, and configured differently than shown in FIG. 8.

(44) Further, the disclosure comprises examples according to the following clauses:

(45) Clause 1. A system comprising: a fixture template configured to be secured to a component, the fixture template including a plurality of insert holes; and a plurality of guide inserts having channels, wherein each of the channels has an orientation, wherein the orientation of at least two of the plurality of guide inserts differs, wherein each of the plurality of guide inserts is removably secured within a respective one of the plurality of inserts holes to position and orient the channels in relation to a pattern of openings to be formed in relation to the component, and wherein each of the channels is configured to receive an operative member of a tool that is configured to form the pattern of openings in relation to the component.

(46) Clause 2. The system of Clause 1, wherein the tool is a drill.

(47) Clause 3. The system of Clauses 1 or 2, wherein the component is a portion of an aircraft.

(48) Clause 4. The system of any of Clauses 1-3, wherein the fixture template further comprises index slots connected to the plurality of insert holes, and wherein the plurality of guide inserts comprise keys that are configured to be removably secured within the index slots.

(49) Clause 5. The system of any of Clauses 1-4, wherein the orientation of each of and all of the plurality of guide inserts differs.

(50) Clause 6. The system of any of Clauses 1-5, wherein each of the plurality of guide inserts

comprises a plug and a collar, wherein the channels are formed through the plug and collar, and wherein the plug is configured to be received and retained by one of the plurality of insert holes.

(51) Clause 7. The system of any of Clauses 1-6, wherein outer dimensions of the plug and the collar for each of the plurality of guide inserts are common.

(52) Clause 8. The system of any of Clauses 1-7, wherein the orientation comprises a length, an axial angle, and a radial angle, wherein the orientation of at least two of the plurality of guide inserts differs with respect to one or more of the length, the axial angle, or the radial angle.

(53) Clause 9. The system of any of Clauses 1-8, wherein the fixture template further comprises a different fixture identifier proximate to each of the plurality of insert holes, wherein each of the plurality of guide inserts comprises a different insert identifier, and wherein each of the different insert identifiers corresponds to one of the different fixture identifiers to ensure proper location of the plurality of guide inserts within the plurality of insert holes.

(54) Clause 10. A method comprising: securing a fixture template to a component, the fixture template including a plurality of insert holes; removably securing each of a plurality of guide inserts within a respective one of the plurality of inserts holes to position and orient channels of the plurality of guide inserts in relation to a pattern of openings to be formed in relation to the component, wherein each of the channels has an orientation, wherein the orientation of at least two of the plurality of guide inserts differs; and receiving, by each of the channels, an operative member of a tool that is configured to form the pattern of openings in relation to the component.

(55) Clause 11. The method of Clause 10, wherein the tool is a drill.

(56) Clause 12. The method of Clauses 10 or 11, wherein the component is a portion of an aircraft.

(57) Clause 13. The method of any of Clauses 10-12, further comprising removably securing keys of the plurality of guide inserts within index slots connected to the plurality of insert holes.

(58) Clause 14. The method of any of Clauses 10-13, wherein the orientation of each of and all of the plurality of guide inserts differs.

(59) Clause 15. The method of any of Clauses 10-14, wherein each of the plurality of guide inserts comprises a plug and a collar, wherein the channels are formed through the plug and collar, and wherein the plug is configured to be received and retained by one of the plurality of insert holes.

(60) Clause 16. The method of Clause 15, wherein outer dimensions of the plug and the collar for each of the plurality of guide inserts are common.

(61) Clause 17. The method of any of Clauses 10-16, wherein the orientation comprises a length, an axial angle, and a radial angle, wherein the orientation of at least two of the plurality of guide inserts differs with respect to one or more of the length, the axial angle, or the radial angle.

(62) Clause 18. The method of any of Clauses 10-17, wherein the fixture template further comprises a different fixture identifier proximate to each of the plurality of insert holes, wherein each of the plurality of guide inserts comprises a different insert identifier, and wherein each of the different insert identifiers corresponds to one of the different fixture identifiers to ensure proper location of the plurality of guide inserts within the plurality of insert holes.

(63) Clause 19. A system comprising: a fixture template configured to be secured to a component, the fixture template including a plurality of insert holes and index slots connected to the plurality of insert holes; and a plurality of guide inserts having channels and a key that is configured to be removably secured within one of the index slots, wherein each of the channels comprises an orientation and, wherein the orientation of at least two of the plurality of guide inserts differs, wherein the orientation comprises a length, an axial angle, and a radial angle, wherein the orientation of at least two of the plurality of guide inserts differs with respect to one or more of the length, the axial angle, or the radial angle, wherein each of the plurality of guide inserts is removably secured within a respective one of the plurality of insert holes to position and orient the channels in relation to a pattern of openings to be formed in relation to the component, and wherein each of the channels is configured to receive an operative member of a drill that is configured to form the pattern of openings in relation to the component.

(64) Clause 20. The system of Clause 19, wherein each of the plurality of guide inserts comprises a plug and a collar, wherein the channels are formed through the plug and collar, wherein the plug is configured to be received and retained by one of the plurality of insert holes, and wherein outer dimensions of the plug and the collar for each of the plurality of guide inserts are common, wherein the fixture template further comprises a different fixture identifier proximate to each of the plurality of insert holes, wherein each of the plurality of guide inserts comprises a different insert identifier, and wherein each of the different insert identifiers corresponds to one of the different fixture identifiers to ensure proper location of the plurality of guide inserts within the plurality of insert holes.

(65) As described herein, examples of the present disclosure provide a system and a method for efficiently and effectively forming a pattern of holes in a component. Further, examples of the present disclosure provide a system and a method for efficiently and effectively replacing portions of a component, such as skin portions of a fuselage of an aircraft.

(66) While various spatial and directional terms, such as top, bottom, lower, mid, lateral, horizontal, vertical, front and the like can be used to describe examples of the present disclosure, it is understood that such terms are merely used with respect to the orientations shown in the drawings. The orientations can be inverted, rotated, or otherwise changed, such that an upper portion is a lower portion, and vice versa, horizontal becomes vertical, and the like.

(67) As used herein, a structure, limitation, or element that is “configured to” perform a task or operation is particularly structurally formed, constructed, or adapted in a manner corresponding to the task or operation. For purposes of clarity and the avoidance of doubt, an object that is merely capable of being modified to perform the task or operation is not “configured to” perform the task or operation as used herein.

(68) It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described examples (and/or aspects thereof) can be used in combination with each other. In addition, many modifications can be made to adapt a particular situation or material to the teachings of the various examples of the disclosure without departing from their scope. While the dimensions and types of materials described herein are intended to define the parameters of the various examples of the disclosure, the examples are by no means limiting and are exemplary examples. Many other examples will be apparent to those of skill in the art upon reviewing the above description. The scope of the various examples of the disclosure should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims and the detailed description herein, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Moreover, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects. Further, the limitations of the following claims are not written in means-plus-function format and are not intended to be interpreted based on 35 U.S.C. § 112(f), unless and until such claim limitations expressly use the phrase “means for” followed by a statement of function void of further structure.

(69) This written description uses examples to disclose the various examples of the disclosure, including the best mode, and also to enable any person skilled in the art to practice the various examples of the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the various examples of the disclosure is defined by the claims, and can include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if the examples have structural elements that do not differ from the literal language of the claims, or if the examples include equivalent structural elements with insubstantial differences from the literal language of the claims.

## Claims

1. A system comprising: a fixture template configured to be secured to a component, the fixture template including a plurality of insert holes; and a plurality of guide inserts, wherein each of the plurality of guide inserts comprises: a respective plug; a respective collar; and a respective channel formed through the plug and the collar corresponding thereto, and wherein the respective plug of each of the plurality of guide inserts is configured to be received and retained by one of the plurality of insert holes of the fixture template, wherein the respective channel formed through the plug and the collar corresponding thereto has a longitudinal axis, and the respective channel extends a length that spans an entirety of said plug and an entirety of said collar, wherein, when each of the plurality of guide inserts is received and is retained by one of the plurality of insert holes of the fixture template, the respective longitudinal axis for each respective channel has an oblique orientation with respect to a vertical extending longitudinal axis of a corresponding key of each of the plurality of guide inserts, wherein outer dimensions of the respective plug and the respective collar for each of the plurality of guide inserts are the same, and wherein the oblique orientation of the respective channel of at least two of the plurality of guide inserts differs, wherein each of the plurality of guide inserts is removably secured within a respective one of the plurality of insert holes to position and orient the respective channel of each of the plurality of guide inserts in relation to a pattern of openings to be formed in the component, and wherein the respective channel of each of the plurality of guide inserts is configured to receive an operative member of a tool that is configured to form the pattern of openings in the component.
2. The system of claim 1, wherein the tool is a drill.
3. The system of claim 1, wherein the component is a portion of an aircraft.
4. The system of claim 1, wherein the fixture template further comprises a plurality of index slots, wherein each one of the plurality of index slots is connected to a corresponding one of the plurality of insert holes, and wherein each of the plurality of guide inserts comprises a respective key that is configured to be removably secured within a corresponding one of the plurality of index slots.
5. The system of claim 1, wherein the oblique orientation of each of and all of the plurality of guide inserts differs.
6. The system of claim 1, wherein, for at least two of the plurality of guide inserts, a respective length, a respective axial angle, and a respective radial angle of the corresponding channel differs for each of the at least two of the plurality of guide inserts.
7. The system of claim 1, wherein the fixture template further comprises a different fixture identifier proximate to each of the plurality of insert holes, wherein each of the plurality of guide inserts comprises a different insert identifier, and wherein each of the different insert identifiers corresponds to one of the different fixture identifiers to ensure proper location of the plurality of guide inserts within the plurality of insert holes.
8. The system of claim 1, wherein the plurality of insert holes includes four or more insert holes, and the plurality of guide inserts includes four or more guide inserts.
9. The system of claim 1, wherein the fixture template comprises a main body having a first surface and a second surface opposite from the first surface, wherein each of the plurality of insert holes is formed through the main body between and through the first surface and the second surface.
10. A system comprising: a fixture template configured to be secured to a component, the fixture template including a plurality of insert holes and a plurality of index slots, wherein each one of the plurality of index slots is connected to a corresponding one of the plurality of insert holes; and a plurality of guide inserts, wherein each of the plurality of guide inserts comprises: a respective plug; a respective collar; a respective key that is configured to be removably secured within a corresponding one of the plurality of index slots, and a respective channel formed through the plug and the collar corresponding thereto, and wherein the respective plug of each of the plurality of

guide inserts is configured to be received and retained by one of the plurality of insert holes of the fixture template, wherein the respective channel formed through the plug and the collar corresponding thereto has a longitudinal axis, and the respective channel extends a length that spans an entirety of said plug and an entirety of said collar, and wherein, when each of the plurality of guide inserts is received and is retained by one of the plurality of insert holes of the fixture template, the respective longitudinal axis for each respective channel has an oblique orientation with respect to a vertical extending longitudinal axis of the corresponding key of each of the plurality of guide inserts, wherein the oblique orientation of the respective channel of at least two of the plurality of guide inserts differs, and wherein outer dimensions of the respective plug and the respective collar for each of the plurality of guide inserts are the same, wherein each of the plurality of guide inserts is removably secured within a respective one of the plurality of insert holes to position and orient the respective channel of each of the plurality of guide inserts in relation to a pattern of openings to be formed in the component, and wherein the respective channel of each of the plurality of guide inserts is configured to receive an operative member of a drill that is configured to form the pattern of openings in the component.

11. The system of claim 10, wherein the fixture template further comprises a different fixture identifier proximate to each of the plurality of insert holes, wherein each of the plurality of guide inserts comprises a different insert identifier, and wherein each of the different insert identifiers corresponds to one of the different fixture identifiers to ensure proper location of the plurality of guide inserts within the plurality of insert holes.

12. A method of operating the system according to claim 1, the method comprising: providing the system of claim 1; securing the fixture template to a component; removably securing each of the plurality of guide inserts within a respective one of the plurality of insert holes of the fixture template so as to position and orient the respective channel of each of the plurality of guide inserts in relation to the pattern of openings that is to be formed in the component; and inserting, in the respective channel of each of the plurality of guide inserts, the operative member of the tool which is configured to form the pattern of openings in the component.

13. The method of claim 12, wherein the tool is a drill.

14. The method of claim 12, wherein the component is a portion of an aircraft.

15. The method of claim 12, further comprising removably securing a respective key of each of the plurality of guide inserts within a corresponding one of a plurality of index slots, wherein each of the plurality of index slots is connected to a corresponding one of the plurality of insert holes.

16. The method of claim 12, wherein the oblique orientation of each of and all of the plurality of guide inserts differs.

17. The method of claim 12, wherein, for at least two of the plurality of guide inserts, a respective length, a respective axial angle, and a respective radial angle of the corresponding channel differs for each of the at least two of the plurality of guide inserts.

18. The method of claim 12, wherein the fixture template further comprises a different fixture identifier proximate to each of the plurality of insert holes, wherein each of the plurality of guide inserts comprises a different insert identifier, and wherein each of the different insert identifiers corresponds to one of the different fixture identifiers to ensure proper location of the plurality of guide inserts within the plurality of insert holes.

19. The method of claim 12, wherein the plurality of insert holes includes four or more insert holes, and the plurality of guide inserts includes four or more guide inserts.

20. The method of claim 12, wherein the fixture template comprises a main body having a first surface and a second surface opposite from the first surface, wherein each of the plurality of insert holes is formed through the main body between and through the first surface and the second surface.

---