

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395947
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Arvapally; RadhaKrishna et al.

System and method to configure O-RAN fronthaul to support 2nd-generation (2G), 3rd-generation (3G) and NB-IOT

Abstract

There is provided, an open radio access network distributed unit (O-DU) having an electronic module that performs an FS-8 Radio Access Technology (RAT) functionality.

Inventors: Arvapally; RadhaKrishna (Bangalore, IN), Guchhait; Atanu (Bangalore, IN), Mudaraddi; Somashekar (Bangalore, IN), Unnikrishnan; Brijesh (Bangalore, IN), Ahmed; Wessam Afifi (Plano, TX), Piercy; Neil Philip (Royston, GB)

Applicant: Mavenir Systems, Inc. (Richardson, TX)

Family ID: 1000008764588

Assignee: MAVENIR SYSTEMS, INC. (Richardson, TX)

Appl. No.: 17/848772

Filed: June 24, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230052205 A1	Feb. 16, 2023

Foreign Application Priority Data

IN	202121028461	Jun. 24, 2021
----	--------------	---------------

Publication Classification

Int. Cl.: H04W52/52 (20090101); H04W72/0446 (20230101); H04W74/08 (20090101); H04W74/0833 (20240101)

U.S. Cl.:

CPC **H04W52/52** (20130101); **H04W72/0446** (20130101); **H04W74/0833** (20130101);
H04W74/0866 (20130101);

Field of Classification Search

CPC: H04W (52/52); H04W (72/0446); H04W (74/0833); H04W (74/0866)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10791507	12/2019	Mukherjee	N/A	H04W 4/029
2020/0128414	12/2019	Mishra et al.	N/A	N/A
2021/0045193	12/2020	Mishra et al.	N/A	N/A
2021/0126760	12/2020	Lee	N/A	H04B 7/0617
2024/0259084	12/2023	Astrom	N/A	H04B 7/0697
2024/0292344	12/2023	Guo	N/A	H04W 52/367

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019217391	12/2018	WO	N/A

OTHER PUBLICATIONS

O-RAN Alliance Working Group 4 CUS.0-v06.00 “Control Use and Synchronization Plane Specification” O-Ran Alliance, Mar. 11, 2021. cited by applicant

O-RAN Alliance Working Group 4 MP.0-v06.00 “Management Plane Specification” O-Ran Alliance, Mar. 22, 2021. cited by applicant

O-RAN Fronthaul Working Group 4 CUS.0-v02.00 “Control Use and Synchronization Plane Specification” O-Ran Alliance, Aug. 2, 2019. cited by applicant

Umesh et al. “Overview of O-RAN Fronthaul Specifications (Special Articles on Standardization Trends Toward Open en Intelligent Radio Access Networks)” NTT Docomo Technical Journal, vol. 21, No. 1, Apr. 1, 2019 pp. 46-59. cited by applicant

Extended European Search Report and Written Opinion for corresponding European application EP22181111.0, 10 pages, dated Nov. 28, 2022. cited by applicant

Primary Examiner: Cai; Wayne H

Attorney, Agent or Firm: Ruggiero McAllister & McMahon LLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application claims foreign priority to Indian Patent Application No. 202121028461, filed on Jun. 24, 2021, the entirety of which is incorporated herein by reference.

COPYRIGHT NOTICE

(2) A portion of the disclosure of this patent document contains material that is subject to copyright

protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent files or records, but otherwise reserves all copyright rights whatsoever.

BACKGROUND OF THE DISCLOSURE

1. Field of the Disclosure

(3) The present document is directed to a system for functional split-8 (FS-8) Radio Access Technologies (RATs), referred to herein as FS-8 RAT, e.g., second generation (2G) and third generation (3G), to generate/receive Open Radio Access Network (O-RAN) fronthaul (FH) compatible messaging in an open distributed unit (O-DU). The acronyms O-DU and DU are used herein, interchangeably. For references to an Open RAN Radio Unit, the acronyms O-RU and RU are used herein, interchangeably. In embodiments, described are: Multi-RAT DUs supporting 2G, 3G, 4G and 5G along with NB-IOT vDUs supporting 2G and/or 3G along with NB-IOT Multi-RAT RUs supporting 2G, 3G, 4G and 5G along with NB-IOT RUs supporting 2G and/or 3G along with NB-IOT

(4) O-RAN compliant distributed units (O-DUs) and O-RAN compliant radio units (O-RUs).

(5) O-RAN compliant combined central unit (O-CU) and O-DU communicating via the O-RAN fronthaul interface to O-RUs.

(6) O-RAN compliant Service Management and Orchestration (SMO) communicating to O-CUs, O-DUs and O-RUs.

(7) The invention also supports any existing/future wireless system that is O-RAN compliant.

2. Description of the Related Art

(8) The approaches described in this section are approaches that could be pursued, but not necessarily approaches that have been previously conceived or pursued. Therefore, the approaches described in this section may not be prior art to the claims in this application and are not admitted to be prior art by inclusion in this section.

(9) The present document, near its end, includes a list of acronyms and a list of definitions.

(10) Open Radio Access Network (O-RAN) standard has gained huge attention from wireless infrastructure manufacturers and operators across the globe. O-RAN fronthaul (FH) specification allows interoperability and standardization of RAN components primarily Open Distributed Unit (O-DU) and Open Radio Unit (O-RU) using a unified interconnection standard over a packet-based transport interface such as Enhanced Common Public Radio Interface (eCPRI) and Radio over Ethernet (RoE). This has enabled seamless integration of white-box hardware and open-source software elements from different component vendors for O-DUs and O-RUs.

(11) O-RAN standard in its current specifications covers support for the control, user, and synchronization planes (CUS-plane) (O-RAN Control, User and Synchronization Plane Specification 6.01, O-RAN.WG4.CUS.0-v06) and management plane (M-plane) (O-RAN Management Plane Specification v06, O-RAN.WG4.MP.0-v06.) for only radio access technologies (RAT). As of the present disclosure, the O-RAN standard supports only 4G and 5G radio access technologies (RAT) through functional split 7.2x (FS-7.2x) interconnect where frequency domain data IQ samples, beamforming weights and related control, management and synchronization information are carried over a fronthaul interface (FH). This architecture allowed FS-7.2x RAT base-station systems to be designed and deployed more flexibly, cost effectively and efficiently, thus reducing system CAPEX and OPEX significantly.

(12) Accordingly, in the current O-RAN specification, packet-based FH interface standard O-RAN supports only FS-7.2x RAT operations, thus defines frequency-domain IQ data transfer mechanism over FH using O-RAN specified CUS and M-plane standards. 2G and 3G radio access technologies traditionally use streaming interface-based FH connections to carry time-domain IQ samples to or from the RU. The O-RAN standard in its current form, however, does not support RATs with functional split-8 (FS-8), which do not have any frequency-domain operations defined in their respective RAT standard specifications. As such, the O-RAN standard in its current form does not

provide any support to carry FS-8 RAT time domain IQ data, control, and related management information over the FH interface. Enhancements in multiple aspects are needed in O-RAN standard for seamless integration of 2G and 3G RATs supporting functional split FS-8 with newer RATs (4G and NR) supporting FS-7.2x.

SUMMARY OF THE DISCLOSURE

(13) Described are implementations of O-RAN FH interfaces to FS-8 RATs to carry time domain IQ samples over the FH without impacting the existing access network operations.

(14) In implementations, described are a set of additions to the current O-RAN standard from the M-Plane perspective to enable FS-8 RATs transport over the FH.

(15) Implementations described herein do not change with hybrid and hierarchical M-Plane architectures as they do not impact existing M-Plane procedures. The disclosed parameters can be transported as part of existing user plane configuration as defined in the standard for hybrid and hierarchical models.

(16) Existing O-RAN fronthaul interfaces do not support transport of FS-8 RAT traffic. Thus FS-8 RATs were transported to/from RU using non-O-RAN FH standards like CPRI or eCPRI.

(17) In an implementation, disclosed is an open radio access network distributed unit (O-DU) comprising an electronic module that configured with structures to execute parameters to perform FS-8 Radio Access Technology (RAT), the parameters comprising: FS-8 frame structure parameters; Narrow Band-Internet of Things (NB-IOT) parameters; and automatic gain control (AGC) parameters.

(18) In an implementation, the O-DU can be further configured to send AGC parameters for a random access channel (RACH) AGC configuration to a 2G network radio unit (O-RU), the AGC parameters comprising: a Frame number where the RACH is expected; a Slot Number or Slot Numbers on the corresponding Frame number; and a Target dynamic Gain Range of the AGC. The 2G radio unit can determine one or more of the AGC parameters based on the AGC parameter values. The 2G O-RU can be configured to determine where the RACH is expected on a frame and apply gain control based on the AGC parameter values.

(19) In an implementation, the FS-8 frame structure can comprise a maximum symbol size per millisecond capability for the O-RU. The FS-8 frame structure can further comprises extended symbol length parameter, a normal symbol length parameter, a sampling rate parameter, or a combination thereof. The FS-8 frame structure can further comprise an AGC-2G parameter, a 2G/3G RU frame format parameter, or both. The sampling rate $SR_{sub.bandwidth}$ (in Msps) for occupied bandwidth can be used to determine a symbol length $N_{sub.symb}$ and a cyclic prefix length $CP_{sub.bandwidth}$ of fronthaul symbols. The FH symbols can be expressed as:

$$N_{sub.symb} = T_{sub.symb} \times SR_{sub.bandwidth}$$

$$CP_{sub.bandwidth} = (T_{sub.symb} - 66.66 \times e_{sup.6}) \times SR_{sub.bandwidth} \text{ where } T_{sub.symb} \text{ is in seconds.}$$

(20) In an implementation, the AGC parameters can comprise a parameter structure configured for the O-DU to inform an O-RU of AGC parameters other than RACH slots, the parameters comprising: a target dynamic range of the AGC, and AGC parameter sets. The AGC parameter sets can comprise an AGC integral gain parameter, an AGC proportional gain parameter, and a derivative gain parameter.

(21) In an implementation, the O-DU can be configured to support a 2G and 3G NB-IOT. The O-DU can be configured with a supported technology parameter configured for supporting GSM, UMTS and an NB-IOT, the supported technology parameter comprising a downlink parameter set, and uplink parameter set, or both. The O-DU can be configured to support 2G and 3G NB-IOT in a U-plane configuration, wherein the O-DU is configured with carrier parameters. The carrier parameters can comprise: tx-array carrier parameters, rx array carrier parameters, or both.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a block diagram of a system of a single RAT radio access solution where an O-DU communicates with an O-RU over an O-RAN FH in an O-RAN.

(2) FIG. 2 shows a 4G LTE subframe and slot structure.

(3) FIG. 3 shows a 4G LTE subframe and slot structure.

DESCRIPTION OF THE DISCLOSURE

(4) The system disclosed herein will allow FS-8 RATs (2G and 3G) to interface to O-RAN FH, and in general, any packet-based FH transport network standard. Reference is made to Third Generation Partnership Project (3GPP), the O-RAN Alliance, and the Internet Engineering Task Force (IETF) in accordance with embodiments of the present disclosure

(5) FIG. 1 is a block diagram of a system **100** of a single RAT radio access solution where an O-DU **105** communicates with an O-RU **115** over an O-RAN FH **110** in an O-RAN **120**. System **100** includes a 2G RAT **125** and a 3G RAT **130**, which, in practice, are connected directly to O-DU **105**.

(6) System **100** can be configured for single carrier or multi-carrier systems. For example, for multi-carrier systems, the system can be configured to map the 2G signal to the any LTE bandwidth equivalent analog stream such as 5/10/15/20 MHz. Thus, system **100** allows an available 2G spectrum to be split across different antennas in multiples of LTE-equivalent bandwidths by using different RF frequencies for each of the antenna.

(7) Implementations as described in this section with respect to a RAT system diagram in FIG. 1 where, O-RU system implement the C&M server **117**. O-RU declares its capability and works with the C&M client **107** located in O-DU **105**. M-Plane standard based message/information exchange **112** are carried out between O-RU and O-DU (between C&M server **117** and C&M client **105**) over the FH **110** to handshake required non-real time system configuration and management for desired system operation.

(8) Each of O-DU **105** and O-RU **115** includes electronic circuitry that performs operations to execute methods or processes described herein. The circuitry may be implemented with any or all of (a) discrete electronic components, (b) firmware, or (c) a programmable circuit that includes a processor and a memory. Such a processor is an electronic device configured of logic circuitry that responds to and executes instructions. Such a memory is a tangible, non-transitory, computer-readable storage device encoded with a computer program. In this regard, the memory stores data and instructions, i.e., program code, that are readable and executable by the processor for controlling operations of the processor. The memory may be implemented in a random-access memory (RAM), a hard drive, a read only memory (ROM), or a combination thereof.

(9) Additionally, the program code may be configured on a storage device for subsequent loading into the memory. Such a storage device is a tangible, non-transitory, computer-readable storage device, and examples include (a) a compact disk, (b) a magnetic tape, (c) a read only memory, (d) an optical storage medium, (e) a hard drive, (f) a memory unit consisting of multiple parallel hard drives, (g) a universal serial bus (USB) flash drive, (h) a random-access memory, and (i) an electronic storage device coupled the components of system **100** via a network, e.g., the Internet.

(10) The program code may be configured in one or more modules. The term “module” is used herein to denote a functional operation that may be embodied either as a stand-alone component or as an integrated configuration of a plurality of subordinate components. Thus, a module may be implemented as a single module or as a plurality of sub-ordinate modules that operate in cooperation with one another.

(11) In an implementation, described is an O-RAN M-Plane Data-Structure Enhancement for 2G, 3G, NB-IoT RAT:

(12) In an implementation, described is a YANG parameter structure for a DU to inform an RU of

AGC parameters for a RACH Slot. AGC is a conditional feature, which can be implemented as a function of whether the O-RU supports 2G or not. The parameter is applicable for single carrier 2G or synchronized multi carrier 2G systems.

(13) In an implementation, a 2G O-DU **107** sends following parameters to 2G O-RU for RACH AGC configuration: a Frame number where a RACH is expected; a Slot Number(s) on the corresponding Frame number; a Target dynamic Gain Range of the AGC; and AGC parameter sets (e.g.: agc-rach-nframe, agc-rach-slot, agc-rach-proportional-gain, agc-rach-integral-gain and agc-rach-differential-gainfactors). An implementation of an exemplary 2G PARCH AGC optional parameter structure includes: +—rw agc-configuration—rach {AGC-2G} +—agc-rach-nframe? unit 8 +—agc-rach-rach-slot? unit 8 +—agc-rach-proportional-gain? decimal64 +—agc-rach-integral-gain? decimal64 +—agc-rach-differential-gain? decimal64 +—rw agc-configuration—tch {AGC-2G} +—agc-tch-gain-range? decimal64 +—agc-tch-integral-gain? decimal64 +—agc-tch-differential-gain? decimal64 +—agc-tch-proportional-gain? decimal64 =

(14) The 2G PARCH AGC optional parameter structure can be implemented under the O-RAR U-Plane configuration for rx array carriers (o-ran-uplane-conf.yang.fwdarw.rx-array-carriers).

(15) Based on the parameter values, a 2G RU can be configured to determine the slots where the RACH is expected on each frame and can thus apply gain control.

(16) In an implementation, described is a subframe and slot structure supporting multiple symbols in a frame. Over the FH multicarrier 2G and 3G radio access technology, IQ data flows can have following two alternative frame structures.

(17) Option 1: Maintain 4G LTE subframe and slot structures and the corresponding 14 symbols per subframe as shown in the FIG. 2. Differences with 4G are total number of IQ data sample content per symbol is equal to the full size of the corresponding LTE symbol size for the corresponding bandwidth of operation. For example, for slot #0 or #7, a Symbol Size is the number of IQ samples $T_{\text{symb}}=71.9 \mu\text{s}$ at a sample rate corresponding to the system bandwidth e.g., Symbol Size=1104 Samples for a 10 MHz bandwidth multicarrier 2G/3G System. For slot #1, a Symbol Size is the number of IQ samples $T_{\text{symb}}=71.3 \mu\text{s}$ at a sample rate corresponding to the system bandwidth e.g., Symbol Size=1096 Samples for a 10 MHz bandwidth multicarrier 2G/3G System

(18) Option 2: Maintain 4G LTE Subframe and slot structure and the corresponding 15 symbols per subframe as shown in FIG. 3. The difference for a 4G system is the number of IQ data sample content per symbol is equal to the full size of the corresponding LTE symbol size for the corresponding bandwidth of operation. For example, all slots have a Symbol Size that is the number of IQ samples $T_{\text{symb}}=66.67 \mu\text{s}$ at a sample rate corresponding to the system bandwidth e.g., Symbol Size=1024 Samples for a 10 MHz bandwidth multicarrier 2G/3G System.

(19) To support the above symbols in one millisecond, the O-RU can be configured to indicate the capability in YANG model under RU capability (e.g.: max-symbols-per-ms).

(20) In an implementation, described is a FH sampling rate and symbol length structure and process. The O-DU can be configured to indicate the fronthaul sampling rate to O-RU. The sampling rate $SR_{\text{sub.bandwidth}}$ (in Msps,) which is a function of occupied bandwidth, can be configured to determine the symbol length $N_{\text{sub.symb}}$ and cyclic prefix length $CP_{\text{sub.bandwidth}}$ of the fronthaul symbols. They could be expressed as following:

$$N_{\text{sub.symb}} = T_{\text{sub.symb}} \times SR_{\text{sub.bandwidth}}$$

$$CP_{\text{sub.bandwidth}} = (T_{\text{sub.symb}} - 66.66 \times e^{\text{sup.6}}) \times SR_{\text{sub.bandwidth}}$$
 Where $T_{\text{sub.symb}}$ is in unit seconds.

(21) An example of an implementation of FS-8 frame format parameters is shown below. Three additional parameters, “extended-symbol-length”, “normal-symbol-length” and “sampling-rate”, can be added under an O-RAN U-Plane configuration (o-ran-uplane-conf.yang), for example as follows: +—rw fs8-frame-structure {FS8-Frame-Format}? +—rw max-symbols-per-ms +—rw extended-symbol-length +—rw normal-symbol-length +—rw sampling-rate

These parameters can be pushed from O-DU to O-RU via the M-plane as part of user plane

configuration for 2G RUs **125** or 3G RUs **130**. Optional features as shown in Table 1 can also be added.

(22) TABLE-US-00001 TABLE 1 No Optional Feature Namespace Feature name 1 AGC for 2G RUs “urn:o-ran:uplane- AGC-2G conf:x.y” 2 Frame Format for “urn:o-ran:uplane- FS8-FRAME-FORMAT 2G/3G RUs conf:x.y”

(23) In an implementation, described is a Yang parameter structure for an O-DU to inform an O-RU of AGC parameters for slots other than RACH slots. A 2G O-DU sends following parameters to 2G O-RU for AGC configuration for TCH and other slots: a Target dynamic Gain Range of the AGC and the AGC parameter sets {agc-tch-integral-gain, agc-tch-differential-gain, and agc-tch-proportional-gain} (proportional, integral and derivative parameters).

(24) The 2G TCH slots (except RACH) AGC parameter structures are implemented under and an O-RAN U-Plane configuration for rx array carriers (o-ran-uplane-conf.yang.fwdarw.rx-array-carriers). Based on the above-referenced values, the 2G Radio unit can apply gain control for slots other than RACH slots.

(25) In an implementation, a module is configured for a YANG model to support 2G, 3G and NB-IOT. The O-RU can be configured to report as a part of its capabilities whether it supports 2G, 3G, or NB-IOT. For example, an enhanced definition is added to the following two parameters in YANG model under RU capability:

(26) TABLE-US-00002 .circle-solid. supportedtechnology-dl ☐ enum range of type enhanced to support GSM, UMTS, NB IoT leaf-list supported-technology-dl { type enumeration{ enum LTE { description “LTE is supported in DL path.”; } enum NR { description “NR is supported in DL path.”; } enum DSS_LTE_NR { if-feature DSS_LTE_NR; description “DSS is supported in the DL, which implicitly means LTE and NR are also BOTH supported in the DL.”; } enum GSM { description “GSM is supported in DL path.”; } enum UMTS { description “UMTS is supported in DL path.”; } enum NBIOT { description “NBIOT StandAlone mode supported by RU”; } enum NBIOT-LTE { description “NBIOT inband/guard band mode over LTE carrier supported by RU”; } enum NBIOT-NR { description “NBIOT inband/guard band mode over NR carrier supported by RU”; } } .circle-solid. supportedtechnology-ul ☐ enum range of type enhanced to support GSM, UMTS, NB IoT leaf-list supported-technology-ul { type enumeration{ enum LTE { description “LTE is supported in UL path.”; } enum NR { description “NR is supported in UL path.”; } enum DSS_LTE_NR { if-feature DSS_LTE_NR; description “DSS is supported in the UL, which implicitly means LTE and NR are also BOTH supported in the UL.”; } enum GSM { description “GSM is supported in UL path.”; } enum UMTS { description “UMTS is supported in UL path.”; } enum NBIOT { description “NBIOT StandAlone mode supported by RU”; } enum NBIOT-LTE { description “NBIOT inband/guard band mode over LTE carrier supported by RU”; } enum NBIOT-NR { description “NBIOT inband/guard band mode over NR carrier supported by RU”; } } }

(27) In an implementation, to support 2nd-Generation (2G), 3rd-Generation (3G) and NB-IoT in U-plane configurations, enum values for the parameter “type” are added under tx-array-carriers and rx-array-carriers present in the O-RAN U-Plane configuration (o-ran-uplane-conf.yang).

(28) The present disclosure employs abbreviations, terms and technology defined in accord with Third Generation Partnership Project (3GPP) and/or Internet Engineering Task Force (IETF) technology standards and papers, including the following standards and definitions. 3GPP and IETF technical specifications (TS), standards (including proposed standards, technical reports (TR) and other papers are incorporated by reference in their entirety hereby, define the related terms and


```

mode”;           }           enum GSM {           description “GSM technology.”;
           }           enum UMTS {           description “UMTS technology.”;
           }           enum NB-IOT {           description “NB-IOT StandAlone mode
supported by RU”;           }           enum NB-IOT-LTE {           description
“NB-IOT inband/guard band mode over LTE           carrier supported by RU”;           }
           enum NB-IOT-NR {           description “NB-IOT inband/guard band mode over
NR           carrier supported by RU”;           }           }           description
“Type of carrier. Indicates array-carrier technology.; In an implementation, these
additional value options are added to existing values of LTE, NR or DSS-LTE-N.

```

(32) The techniques described herein are exemplary, and should not be construed as implying any particular limitation on the present disclosure. Various alternatives, combinations and modifications could be devised by those skilled in the art. For example, operations associated with the processes described herein can be performed in any order, unless otherwise specified or dictated by the operations themselves. The present disclosure is intended to embrace all such alternatives, modifications and variances that fall within the scope of the appended claims.

(33) The term “comprises” or “comprising” are to be interpreted as specifying the presence of the stated features, integers, operations or components, but not precluding the presence of one or more other features, integers, operations or components or groups thereof. The terms “a” and “an” are indefinite articles, and as such, do not preclude embodiments having pluralities of articles.

Claims

1. An open radio access network distributed unit (O-DU) comprising an electronic module that configured with structures to execute parameters to perform FS-8 Radio Access Technology (RAT), the parameters comprising: functional split 8 (FS-8) frame structure parameters; Narrow Band-Internet of Things (NB-IOT) parameters; and automatic gain control (AGC) parameters, wherein the O-DU is configured to send the AGC parameters for a random access channel (RACH) AGC configuration to a 2G network radio unit (O-RU), the AGC parameters comprising: a Frame number where the RACH is expected; a Slot Number or Slot Numbers on the corresponding Frame number; and a Target dynamic Gain Range of the AGC.
2. The O-DU of claim 1, wherein the 2G radio unit can determine one or more of the AGC parameters based on the AGC parameter values.
3. The O-DU of claim 2, wherein the 2G O-RU is configured to determine where the RACH is expected on a frame and apply gain control based on the AGC parameter values.
4. The O-DU of claim 1, wherein the FS-8 frame structures comprise a maximum symbol size per millisecond capability for the O-RU.
5. The O-DU of claim 4, wherein the FS-8 frame structure further comprises extended symbol length parameter, a normal symbol length parameter, a sampling rate parameter, or a combination thereof.
6. The O-DU of claim 5, wherein the FS-8 frame structure further comprises an AGC-2G parameter, a 2G/3G RU frame format parameter, or both.
7. The O-DU of claim 1, wherein the O-DU is configured to support a 2G and 3G NB-IOT.
8. The O-DU of claim 7, wherein the O-DU is configured with a supported technology parameter configured for supporting GSM, UMTS and an NB-IOT, the supported technology parameter comprising a downlink parameter set, and uplink parameter set, or both.
9. The O-DU of claim 7, wherein the O-DU is configured to support 2G and 3G NB-IOT in a U-plane configuration, wherein the O-DU is configured with carrier parameters.
10. The O-DU of claim 9, wherein the carrier parameters comprise: tx-array carrier parameters, rx array carrier parameters, or both.
11. An open radio access network distributed unit (O-DU) comprising an electronic module that

configured with structures to execute parameters to perform FS-8 Radio Access Technology (RAT), the parameters comprising: functional split 8 (FS-8) frame structure parameters comprising: a maximum symbol size per millisecond capability for the O-RU; and an extended symbol length parameter, a normal symbol length parameter, or a sampling rate parameter, or a combination thereof; Narrow Band-Internet of Things (NB-IOT) parameters; and automatic gain control (AGC) parameters, wherein a sampling rate SR_{sub} (in Msps) for occupied bandwidth is used to determine a symbol length N_{sub} and a cyclic prefix length CP_{sub} of fronthaul symbols.

12. The O-DU of claim 11, where the FH symbols are expressed as:

$$N_{sub} = T_{sub} \times SR_{sub}$$

$$CP_{sub} = (T_{sub} - 66.66 \times 10^{-6}) \times SR_{sub}$$

where T_{sub} is in seconds.

13. An open radio access network distributed unit (O-DU) comprising an electronic module that configured with structures to execute parameters to perform FS-8 Radio Access Technology (RAT), the parameters comprising: functional split 8 (FS-8) frame structure parameters; Narrow Band-Internet of Things (NB-IOT) parameters; and automatic gain control (AGC) parameters comprising a parameter structure configured for the O-DU to inform an O-RU of AGC parameters other than RACH slots, the AGC parameters comprising: a target dynamic range of the AGC, and AGC parameter sets.

14. The O-DU of claim 13, wherein the AGC parameter sets comprise: an AGC integral gain parameter, an AGC proportional gain parameter and a derivative gain parameter.
