

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392170
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Yamada; Tsuyoshi et al.

Lock mechanism of a storage box

Abstract

A lock mechanism of a storage box can secure and release a lock pin of a lid member with a rotational operation of a cam member, and includes a cam support member for supporting the cam member, and a rotation lock plate for restricting the rotational movement of the cam member, in which the rotation lock plate is configured to restrict the rotational movement of the cam member in a case that the rotation lock plate is at a position along a contact part provided on the cam support member.

Inventors:	Yamada; Tsuyoshi (Tokyo, JP), Kikuchi; Takehiko (Tokyo, JP)
Applicant:	HONDA MOTOR CO., LTD. (Tokyo, JP)
Family ID:	1000008764398
Assignee:	HONDA MOTOR CO., LTD. (Tokyo, JP)
Appl. No.:	17/951452
Filed:	September 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230100618 A1	Mar. 30, 2023

Foreign Application Priority Data

JP	2021-162264	Sep. 30, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: E05B65/52 (20060101); E05B83/16 (20140101)

U.S. Cl.:

Field of Classification Search

CPC: E05B (65/52); E05B (77/08); E05B (83/24); E05B (83/243); E05B (83/28); E05B (83/16); E05B (83/18); E05B (83/22); E05B (83/30); E05B (83/32)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
107422	12/1869	Steinmetz	70/66	E05B 65/52
325017	12/1884	Schmidt	70/66	E05B 65/52
1623318	12/1926	Rasmussen	292/259R	E05B 65/467
2399812	12/1945	Ledin	70/84	E05B 65/52
3016968	12/1961	Roberts, Jr.	292/201	E05B 81/10
3062033	12/1961	Schmalfeldt	292/DIG.43	E05B 83/16
3113447	12/1962	Oishei	292/201	E05B 81/52
3401968	12/1967	Testa	70/70	E05B 63/248
RE27390	12/1971	Allen	292/216	E05B 83/16
3868836	12/1974	La Roche	70/370	E05B 83/16
3985381	12/1975	Kobayashi	292/216	E05B 83/16
4073170	12/1977	Miyabayashi	292/216	E05B 83/16
4194377	12/1979	Maeda	292/216	E05B 85/243
4492101	12/1984	Tanaka	70/451	E05B 77/44
4907428	12/1989	Nakashima	70/279.1	B62J 9/40
5071179	12/1990	Brackmann	292/DIG.60	E05B 79/06
5445326	12/1994	Ferro	292/DIG.43	E05B 83/26
5894749	12/1998	Tomaszewski	292/DIG.43	E05B 83/16
6014876	12/1999	Taylor	70/451	B60R 25/04
6135514	12/1999	Kowalewski	292/216	E05B 79/20
6192725	12/2000	Watson	292/DIG.43	E05B 85/18
6223468	12/2000	Kobayashi	292/201	E05B 81/20
6247732	12/2000	Alton	292/216	E05B 79/20
6369395	12/2001	Roessler	250/462.1	B60Q 3/30
6378920	12/2001	Ostrowski	292/216	E05B 83/16
6581987	12/2002	Gentile	292/216	E05B 83/24
6973810	12/2004	Chen	292/216	E05C 3/24
7195090	12/2006	Parks	180/271	E05B 77/08
7455333	12/2007	Ookawara	292/34	E05B 83/30
9074389	12/2014	Shimizu	N/A	E05D 1/04
10287806	12/2018	Mizuno	N/A	E05B 79/10
11555339	12/2022	Tamura	N/A	E05B 83/26
11746573	12/2022	Lim	292/92	E05B 79/20
2002/0027497	12/2001	Sumada	340/425.5	B62J 9/23
2003/0081995	12/2002	Acciacca	403/353	E05B 83/16
2003/0173796	12/2002	Harima	296/146.7	B60J 5/101
2003/0227177	12/2002	Matsuda	292/216	E05B 81/16
2006/0027003	12/2005	Mizukura	70/252	E05B 17/16

2006/0202485	12/2005	Yamamoto	292/201	E05B 81/20
2007/0163310	12/2006	Ookawara	70/208	E05C 1/145
2011/0140461	12/2010	Murray	292/216	E05B 79/20
2012/0274457	12/2011	Burns	70/91	E05B 85/18
2013/0219974	12/2012	Lange	70/91	E05B 81/14
2016/0194907	12/2015	Kikuchi et al.	N/A	N/A
2016/0201362	12/2015	Mizuno et al.	N/A	N/A
2017/0036642	12/2016	Nomura	N/A	N/A
2018/0276921	12/2017	Haber	N/A	G07C 5/0858
2019/0218834	12/2018	Komatsu	N/A	E05B 77/44
2019/0351952	12/2018	Hunt	N/A	B62D 33/037
2021/0317690	12/2020	Nakasone	N/A	E05C 9/043

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1990331	12/2006	CN	N/A
104937199	12/2014	CN	N/A
105781279	12/2015	CN	N/A
105829172	12/2015	CN	N/A
10034523	12/2001	DE	B60R 21/38
1172507	12/2001	EP	E05B 77/02
1 808 366	12/2006	EP	N/A
S62-146379	12/1986	JP	N/A
2007-176239	12/2006	JP	N/A
2012-201356	12/2011	JP	N/A
2014-134093	12/2013	JP	N/A
2015-123774	12/2014	JP	N/A

OTHER PUBLICATIONS

Japanese Office Action dated Jul. 11, 2023, Application No. JP 2021-162264, English translation included, 7 pages. cited by applicant

Chinese Office Action Corresponding to CN Application No. 20221117962.1A, dated May 22, 2025, 13 pages. cited by applicant

Primary Examiner: Mills; Christine M

Assistant Examiner: Ahmad; Faria F

Attorney, Agent or Firm: Rankin, Hill & Clark LLP

Background/Summary

INCORPORATION BY REFERENCE

(1) The present application claims priority under 35 U.S.C. § 119 to Japanese Patent Application No. 2021-162264 filed on Sep. 30, 2021. The content of the application is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

Field of the Invention

(2) The present invention relates to a lock mechanism of a storage box.

Description of the Related Art

(3) Conventionally, a storage box apparatus is known that includes a lock mechanism capable of securing and releasing a lock pin of a lid member with a rotational operation of a cam member (see, e.g., Japanese Patent Laid-Open No. 62-146379). A storage box apparatus of this type includes a link mechanism that enables a rotational movement of a cam member and releasing the engagement of the link mechanism disables the rotational movement of the cam member and locks the storage box apparatus.

(4) However, there is a problem in the related art in that the number of parts of the link mechanism is large, which leads to a complex movement of the link mechanism.

SUMMARY OF THE INVENTION

(5) A lock mechanism of a storage box is capable of securing and releasing a lock pin of a lid member with a rotational operation of a cam member, and includes a cam support member for supporting the cam member, and a rotation lock plate for restricting a rotational movement of the cam member. In the lock mechanism, the rotation lock plate is configured to restrict the rotational movement of the cam member in a case that the rotation lock plate is at a position along a contact part provided on the cam support member.

(6) To restrict the rotational movement of the cam member, it is just needed to move the rotation lock plate to a position where the rotation lock plate contacts the cam member. Therefore, the link mechanism is not needed, the number of parts is reduced, and the structure is simplified.

(7) Also, even in a case that a large load is applied to the cam member, a rotational movement of the cam member is restricted by a cooperation between the rotation lock plate and the contact part of the cam support member, and thus strength of the rotation lock plate is reinforced.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a side view of a saddle-ride vehicle according to an embodiment;

(2) FIG. 2 is a perspective view of a storage box according to the embodiment;

(3) FIG. 3 is a vertical cross-sectional view in a front-rear direction of the storage box according to the embodiment;

(4) FIG. 4 is a perspective view of a lock mechanism according to the embodiment;

(5) FIG. 5 is a perspective view seen from the rear of the lock mechanism according to the embodiment;

(6) FIG. 6 is a cross-sectional view illustrating a cam member in a state where the lock mechanism is locked according to the embodiment;

(7) FIG. 7 is a cross-sectional view illustrating the cam member in a state where the lock mechanism is unlocked according to the embodiment; and

(8) FIG. 8 is a cross-sectional view illustrating a cam member at the time when the lock mechanism is being unlocked according to the embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(9) An embodiment of the present invention will be described below with reference to the drawings. Unless otherwise mentioned, directions including front-rear, left-right, and up-down mentioned in the description are the same as those directions relative to a vehicle body. Reference signs FR, UP, and LH shown in the drawings indicate a vehicle body front side, a vehicle body upper side, and a vehicle body left side, respectively.

Embodiment

(10) FIG. 1 is a side view of a saddle-ride vehicle **10** according to an embodiment of the present invention.

(11) The saddle-ride vehicle **10** is a vehicle including a vehicle body frame **11**, a power unit **12**

supported on the vehicle body frame **11**, a front fork **14** that supports a front wheel **13** in a steerable manner, a swing arm **16** that supports a rear wheel **15**, and a seat **17** for a rider.

(12) The saddle-ride vehicle **10** is a vehicle on which the rider sits astride the seat **17**. The seat **17** is provided above a rear part of the vehicle body frame **11**.

(13) The vehicle body frame **11** includes a head pipe **18** provided at a front end portion of the vehicle body frame **11**, a front frame **19** located on a rear side of the head pipe **18**, and a rear frame **20** located on a rear side of the front frame **19**. A front end portion of the front frame **19** is connected to the head pipe **18**.

(14) The seat **17** is supported on the rear frame **20**.

(15) The front fork **14** is supported on the head pipe **18** in such a manner that it can be steered left and right. The front wheel **13** is supported on an axle **13a** provided at a lower end portion of the front fork **14**. A handle **21** for steering that the rider grasps is mounted at an upper end portion of the front fork **14**.

(16) The swing arm **16** is supported on a pivot shaft **22** that is supported on the vehicle body frame **11**. The pivot shaft **22** is a shaft extending horizontally in a vehicle width direction. The pivot shaft **22** is passed through a front end portion of the swing arm **16**. The swing arm **16** swings up and down around the pivot shaft **22**.

(17) The rear wheel **15** is supported on an axle **15a** provided at a rear end portion of the swing arm **16**.

(18) The power unit **12** is disposed between the front wheel **13** and the rear wheel **15** and supported on the vehicle body frame **11**.

(19) The power unit **12** is an internal combustion engine. The power unit **12** includes a crankcase **23** and a cylinder **24** that houses a reciprocating piston. An exhaust device **25** is connected to an exhaust port of the cylinder **24**.

(20) An output of the power unit **12** is transmitted to the rear wheel **15** through a drive power transmission member that connects the power unit **12** and the rear wheel **15** to each other.

(21) The saddle-ride vehicle **10** further includes a front fender **26** that covers the front wheel **13** from above, a rear fender **27** that covers the rear wheel **15** from above, footrests **28** on which the rider places his or her feet, and a fuel tank **29** that stores fuel to be used by the power unit **12**.

(22) The front fender **26** is mounted on the front fork **14**. The rear fender **27** and the footrests **28** are provided on a lower side relative to the seat **17**. The fuel tank **29** is supported on the vehicle body frame **11**.

(23) The saddle-ride vehicle **10** includes a storage box **30** on a rear side of the vehicle.

(24) FIG. 2 is a perspective view of the storage box **30**, and FIG. 3 is a vertical cross-sectional view in a front-rear direction of the storage box **30**.

(25) A pair of storage boxes **30** are attached to left and right sides of the vehicle body frame **11** via a pipe-shaped attachment member **31**.

(26) Because the left and right storage boxes **30** have the same structures, the storage box **30** attached to the right side is described below, and regarding the storage box **30** attached to the left side, the same reference numbers are added to the same parts and the description is omitted.

(27) The storage box **30** includes a lid member **40** and a box-shaped housing **51** having an opening at its top part. As illustrated in FIG. 3, the lid member **40** is connected to a front part of the housing **51** via a hinge **33**, and the lid member **40** is opened by lifting up a rear part **40a** of the lid member **40**. The hinge **33** is covered by a cover **35** from a rear side. The movable range of the lid member **40** is limited by the cover **35** so that the lid member **40** does not open too much.

(28) A lock mechanism **50** is provided at the rear side of the housing **51**. As illustrated in FIG. 2, the lock mechanism **50** includes, outside the housing **51**, a key cylinder **53** and an operation member **55**. And as illustrated in FIG. 3, the lock mechanism **50** includes, inside the housing **51**, a tabular, cam support member **60** and a cam mechanism **70** attached to the cam support member **60**.

(29) The operation member **55**, in response to being pushed down, tilts a lever **59** to move the cam

mechanism **70**, which releases the lock between the rear part **40a** of the lid member **40** and a rear part of the housing **51**. Thus, opening and closing of the lid member **40** is enabled.

(30) A key **54** can be inserted into the key cylinder **53** to rotate. In a case that the key **54** is rotated to a lock position, a rotation lock plate **57** attached to the key cylinder **53** is rotated to lock the lock mechanism **50** so that a lock between the lid member **40** and the housing **51** cannot be released even if the operation member **55** is pushed down. While the lock mechanism **50** is locked, the rotation lock plate **57** is at a position illustrated with solid lines in FIG. **3** and, while the lock mechanism **50** is not locked, the rotation lock plate **57** is at a position illustrated with dashed lines in FIG. **3**.

(31) In the present embodiment, the operation member **55** is a button that can be pushed down, an application of the present invention is not limited to the button-type operation member **55**. For example, the operation may be carried out with a handle-type operation member or a cable which can be pulled to release a lock between the rear part **40a** of the lid member **40** and the rear part of the housing **51**.

(32) FIG. **4** is a perspective view of a lock mechanism **50**, and FIG. **5** is a perspective view seen from the rear of the lock mechanism **50**.

(33) The lid member **40** includes, as illustrated in FIG. **4**, a pin fixing member **41** and a lock pin **43**.

(34) The pin fixing member **41** is fixed to the lid member **40** at its top part. The pin fixing member **41** includes two protruding members **41a** at its bottom part, which are formed to sandwich the cam support member **60** and a first cam **80** between the two protruding members **41a** arranged in a front-rear direction. The lock pin **43** is fixed between the two protruding members **41a**.

(35) As illustrated in FIG. **5**, according to the present embodiment, the key cylinder **53** is provided at a position between the operation member **55** and the cam mechanism **70**, which allows for a compact arrangement of the lock mechanism.

(36) The cam support member **60** is attached to the rear part of the housing **51** with a fixture **69**. The cam mechanism **70** includes the first cam **80** and a second cam **90**. The first cam **80** and the second cam **90** are rotatably attached to the cam support member **60** via a first cam support shaft **81** and a second cam support shaft **91**, respectively.

(37) The lever **59** connected to the operation member **55** is arranged at a position where the lever **59**, in response to a tilt around a lever support shaft **52**, pushes up a lever receiving part **92** provided on the second cam **90**. The lever **59** is configured to be supported by an elastic member (not illustrated) such as a spring so that the lever **59** goes back to its home position.

(38) As illustrated in FIGS. **4** and **5**, a tension spring **71** is provided in a tensioned state between a first spring connection part **89** of the first cam **80** and a second spring connection part **99** of the second cam.

(39) The first cam **80** is, with tension of the tension spring **71**, constantly urged in a counterclockwise direction in FIG. **5** around the first cam support shaft **81**, and the second cam **90** is constantly urged in a clockwise direction in FIG. **5** around the second cam support shaft **91**.

(40) FIG. **6** is a cross-sectional view in a cross-section including the first cam **80** and the second cam **90**. In FIG. **6**, the lock mechanism **50** is in a locked state, and the tension spring **71** is illustrated with dashed lines for convenience of explanation.

(41) The first cam **80** includes a first concave part **83** into which the lock pin **43** is inserted, and a first engaging part **85** that contacts the second cam **90**. The first cam **80** also includes a first engaging protrusion (a part of the cam member) **87** that is inserted into a first guide part (a guide part) **65** of the cam support member **60**, and a first curved part **82** that contacts the lock pin **43** when the lid member **40** is being closed.

(42) The first guide part **65** is a hole that is formed in a shape of a circular arc centered around the first cam support shaft **81**, suppresses rattling of the first cam **80**, by sliding the first engaging protrusion **87** therein, and also limits a rotation angle of the first cam **80**.

(43) The second cam **90** includes a second protruding part **93** that contacts the rotation lock plate

57, and a second engaging part 95 that contacts the first engaging part 85 of the first cam 80.

(44) The second cam 90 also includes a second engaging protrusion (a part of the cam member) 97 that is inserted into the second guide part (a guide part) 67 of the cam support member 60.

(45) The second guide part 67 is a hole that is formed in a shape of a circular arc centered around the second cam support shaft 91, suppresses rattling of the second cam 90, by sliding the second engaging protrusion 97 therein, and also limits a rotation angle of the second cam 90.

(46) The cam support member 60 includes a plate-receiving concave part 61 into which the rotation lock plate 57 is inserted, a contact part 62 provided on the plate-receiving concave part 61, and a pin-receiving concave part 63 into which the lock pin 43 is inserted when the lid member 40 is closed.

(47) In the present embodiment, the rotation lock plate 57 is inserted into the plate-receiving concave part 61, and, while the rotation lock plate 57 is at a position along the contact part 62, interferes with the second protruding part 93 to restrict the rotational (or pivotal) movement of the second cam 90.

(48) In a case that the second cam 90 is rotated counterclockwise by an action of an excessive force, in a state where the rotation of the second cam 90 is restricted, the rotation lock plate 57 contacts the contact part 62 of the plate-receiving concave part 61, and the rotation of the second cam 90 in a counterclockwise direction is restricted by the contact part 62.

(49) The contact part 62, instead of being provided on the plate-receiving concave part 61, may be provided on the cam support member 60, as long as it is in a rotation range of the second cam 90, and at a plane or a side of the cam support member 60 facing against a rotational direction of the second cam 90 moved by the lever 59. For example, even though the contact part 62 is provided on a protrusion formed on the cam support member 60, the rotation of the second cam 90 due to the action of the excessive force can be restricted by the contact part 62.

(50) Regarding the lock mechanism of the storage box 30 of the above-described configuration, its operation is described below with reference to FIGS. 6 through 8.

(51) (In a State where the Lid Member 40 is Opened)

(52) In this state, as illustrated in FIG. 7, the rotation lock plate 57 is out of the plate-receiving concave part 61 formed in the cam support member 60.

(53) The first cam 80 is urged in a counterclockwise direction in FIG. 7, by a spring force of the tension spring 71, and the first engaging protrusion 87 contacts an end wall 65a of the first guide part 65. The second cam 90 is urged in a clockwise direction in FIG. 7, by a spring force of the tension spring 71, and the second engaging protrusion 97 contacts an end wall 67a of the second guide part 67.

(54) (Operation for Closing the Lid Member 40)

(55) While the lid member 40 is being closed, the lock pin 43 provided at the lid member 40 is first inserted into the pin-receiving concave part 63 formed in the cam support member 60, and then contacts the first curved part 82 of the first cam 80 and pushes the first curved part 82.

(56) When the lid member 40 is being closed further, the lock pin 43 makes the first cam 80 start to rotate clockwise in FIG. 7 against a spring force of the tension spring 71, and is inserted into the first concave part 83 of the first cam 80.

(57) In a case that the first cam 80 is rotated, the first engaging part 85 of the first cam 80 engages with the second engaging part 95 of the second cam 90 and rotates the second cam 90 in a counterclockwise direction against a spring force of the tension spring 71. In a case that the first engaging part 85 climbs over the second engaging part 95, the second cam 90 moves back by a spring force of the tension spring 71 to rotate clockwise, and the first engaging part 85 and the second engaging part 95 are engaged with each other as illustrated in FIG. 6.

(58) In a case that the lid member 40 is completely closed, the lock pin 43 is bound in a substantially rectangular-shaped region S (see FIG. 6) surrounded by the first concave part 83 and the pin-receiving concave part 63.

(59) (Operation for Opening the Lid Member **40**)

(60) While the lid member **40** is closed, the lock pin **43** is bound in the region S as illustrated in FIG. **6**. In a case that the lock mechanism **50** is not locked, such as in a situation immediately after the lid member **40** has been closed as described above, the rotation lock plate **57** in FIG. **6** is retracted and is out of the plate-receiving concave part **61**.

(61) In this state, if the operation member **55** is pushed down, the lever **59** is tilted around the lever support shaft **52** and lifts the lever receiving part **92** up. In a case that the lever receiving part **92** is lifted up, the second cam **90** rotates counterclockwise as illustrated in FIG. **8** and the second engaging part **95** detaches from the first engaging part **85** of the first cam **80**. By the detachment, the restriction of the rotation of the first cam **80** is released, and the first cam **80** starts to rotate counterclockwise by the tension spring **71**.

(62) By the rotation of the first cam **80**, the lock pin **43** escapes from the first concave part **83** and the pin-receiving concave part **63** and the lid member **40** is opened.

(63) (Operation for Locking the Lock Mechanism **50**)

(64) On the other hand, after the lid member **40** is completely closed, as illustrated in FIG. **4**, the key **54** can be inserted into the key cylinder **53** and the key **54** can be rotated to a lock position. By the operation of the key, the rotation lock plate **57** is, as illustrated in FIG. **6**, inserted into the plate-receiving concave part **61** and rotates to a position along the contact part **62**, and the lock mechanism **50** is locked.

(65) The rotation lock plate **57** does not need to be provided at the key cylinder **53**. For example, the rotation lock plate **57** may be rotated by an electronically controlled device. The rotation lock plate **57** does not need to be rotated, as long as it is able to lock the lock mechanism **50** by being positioned along the contact part **62** and is provided movable to a position where it does not lock the lock mechanism **50**.

(66) (Function of the Lock Mechanism **50** in a Locked State)

(67) While the lock mechanism **50** is in a locked state, if the operation member **55** is pushed down, the lever **59** of the operation member **55** lifts up the lever receiving part **92**. In a case that the lever receiving part **92** is lifted up, the second cam **90** is rotated counterclockwise in FIG. **7**. However, in this case, the second protruding part **93** of the second cam **90** contacts the rotation lock plate **57** and the rotation of the second cam **90** is restricted.

(68) In a case that the rotation of the second cam **90** is restricted, because the second engaging part **95** continues contacting the first engaging part **85** of the first cam **80**, a state where the rotation of the first cam **80** is restricted can be maintained even though the operation member **55** is pushed down. Therefore, because a state where the lock pin **43** is surrounded all around by the first concave part **83** and the pin-receiving concave part **63** is maintained, the lid member **40** is kept unopened.

(69) In this state, the second protruding part **93** contacts the rotation lock plate **57** to restrict the rotation of the second cam **90**, so that a movable range of the lever receiving part **92** is also limited. Therefore, in a state where the lock mechanism **50** is locked, a range of a pushing operation on the operation member **55** is also limited.

(70) As described above, in a case that the lock mechanism **50** is locked, the pushing operation on the operation member **55** itself is restricted, the operator pushing the operation member **55** can determine that the lock mechanism **50** is locked, with a touch feel when the operation member **55** is pushed down.

(71) Also, while the lock mechanism **50** is locked, the operation member **55** can be pushed down with a large load by any reason.

(72) In such a situation, the second protruding part **93** can be strongly pushed to the rotation lock plate **57**. This can bend or deform the rotation lock plate **57** in a rotational direction of the second cam **90**.

(73) In the present embodiment, the rotation lock plate **57** that is bent or deformed at a certain

amount or more is pushed to the contact part **62** of the plate-receiving concave part **61**. This makes the rotation lock plate **57** reinforced by the contact part **62**, and reduces possibility of disengagement of the rotation lock plate **57** from the second protruding part **93** of the second cam **90** due to the bending or deformation of the rotation lock plate **57**.

(74) Therefore, even in a case that the operation member **55** is pushed down with a large load, the rotation lock plate **57** makes it easier to continue restricting the rotation of the second protruding part **93**, thus the lock state of the lock mechanism **50** is maintained more easily.

(75) As described above, according to the embodiment of the present invention, the lock mechanism **50** of the storage box **30** can secure and release the lock pin **43** of the lid member **40** with the rotational operation of the first cam **80** and the second cam **90**. The lock mechanism **50** of the storage box **30** includes the cam support member **60** that supports the first cam **80** and the second cam **90**, and a rotation lock plate **57** that restricts the rotational movement of the first cam **80** and the second cam **90**. The rotation lock plate **57** restricts the rotational movement of the first cam **80** and the second cam **90** while the rotation lock plate **57** is at a position along the contact part **62** provided on the cam support member **60**.

(76) According to this configuration, the rotation lock plate **57** that restricts the rotation of the first cam **80** and the second cam **90**, is reinforced by the contact part **62** provided on the cam support member **60**. Therefore, in a case that the rotation lock plate **57** is at a position along the contact part **62**, it is difficult to release the lock of the lock mechanism **50** even though a large force is applied to the rotation lock plate **57**.

(77) The second cam **90** is rotated by the movement of the operation member **55** activated by a user's operation and the rotational movement of the second cam **90** is restricted by the rotation lock plate **57**.

(78) According to this configuration, the rotation movement of the second cam **90** interlocked with the operation member **55** is restricted by the rotation lock plate **57**, and a movable range of the operation member **55** itself is also limited. Thus, the operator can confirm whether the lock mechanism **50** is locked, by a touch feel when the operator operates the operation member **55**.

(79) The cam support member **60** includes the first guide part **65** in which the first engaging protrusion **87** of the first cam **80** slides, and the second guide part **67** in which the second engaging protrusion **97** of the second cam **90** slides.

(80) According to this configuration, the first guide part **65** and the second guide part **67** guide rotation of the first cam **80** and the second cam **90**, respectively, and thus rattling of the first cam **80** and the second cam **90** can be suppressed. Also, the rotation ranges of the first cam **80** and the second cam **90** are limited, and thus the rotation of the first cam **80** and the second cam **90** to an unexpected angle can be restricted.

(81) The rotation lock plate **57** is operated to be rotated by the rotation of the key cylinder **53**, and the key cylinder **53** is arranged between the operation member **55** and the cam mechanism **70** including the first cam **80** and the second cam **90**.

(82) According to this configuration, the lock mechanism **50** provided with the storage box **30** can be arranged compactly.

(83) [Configurations Supported by the Above-Described Embodiment]

(84) The above-described embodiment supports configurations described below.

(85) (Configuration 1)

(86) A lock mechanism of a storage box, the lock mechanism being capable of securing and releasing a lock pin of a lid member with a rotational operation of a cam member, the lock mechanism including a cam support member for supporting the cam member, and a rotation lock plate for restricting a rotational movement of the cam member, in which the rotation lock plate is configured to restrict the rotational movement of the cam member in a case that the rotation lock plate is at a position along a contact part provided on the cam support member.

(87) According to this configuration, the rotation lock plate that restricts the rotational movement

of the cam member, is reinforced by the contact part provided on the cam support member. Thus, it is difficult to release the lock between the housing and the lid even though a large force is applied to the rotation lock plate.

(88) (Configuration 2)

(89) The lock mechanism of the storage box of Configuration 1, in which the cam member comprises a first cam and a second cam, and the second cam is rotated by a movement of an operation member activated by an operation of a user and the rotational movement of the second cam is restricted by the rotation lock plate.

(90) According to this configuration, the rotation of the second cam interlocked with the operation member is restricted by the rotation lock plate, and a movable range of the operation member is also limited. Thus, the user can confirm whether the lock mechanism is locked, by a touch feel when the user operates the operation member.

(91) (Configuration 3)

(92) The lock mechanism of the storage box of Configuration 1 or 2, in which the cam support member comprises a guide part for guiding a sliding movement of a part of the cam member.

(93) According to this configuration, the guide part guides rotation of the cam member, which can suppress rattling of the cam member. Also, a rotation range of the cam member is limited, which can restrict rotation of the cam member to an unexpected angle.

(94) (Configuration 4)

(95) The lock mechanism of the storage box of Configuration 2, in which the rotation lock plate is operated to be rotated by a rotation of a key cylinder, and the key cylinder is arranged between the operation member and a cam mechanism including the cam member.

(96) According to this configuration, the lock mechanism can be arranged compactly.

REFERENCE SIGNS LIST

(97) **10** saddle-ride vehicle **30** storage box **40** lid member **43** lock pin **50** lock mechanism **53** key cylinder **55** operation member **57** rotation lock plate **60** cam support member **62** contact part **65** first guide part (guide part) **67** second guide part (guide part) **70** cam mechanism **80** first cam (cam member) **83** first concave part **87** first engaging protrusion (part of cam member) **90** second cam (cam member) **93** second protruding part **97** second engaging protrusion (part of cam member)

Claims

1. A lock mechanism of a storage box comprising a housing having an opening at a top part thereof and a lid member that is connected to the housing and movable so as to open and close, the lock mechanism being capable of securing and releasing a lock pin of the lid member with a rotational operation of a first cam member and a second cam member, wherein the housing includes a cam support member for supporting the first cam member and the second cam member that are rotatable in opposite directions to each other, and a rotation lock plate for restricting rotational movements of the first cam member and the second cam member, the second cam member includes a second protruding part that contacts the rotation lock plate, the cam support member includes a contact part provided in a rotation range of the second protruding part and at a plane or a side of the cam support member facing against a rotational direction of the second cam member, the lock pin is inserted into a first concave portion of the first cam member while the lid member is being closed, a first engaging part of the first cam member engages with a second engaging part of the second cam member so as to lock the lid member, the second cam member rotates, in a direction in which an engagement between the first engaging part and the second engaging part is released, while being pushed down by a lever of an operation member, and when the operation member is operated in a state where the lock mechanism is locked, the second protruding part comes into contact with the rotation lock plate and the rotation lock plate comes into contact with the contact part so as to restrict the rotational movement of the second cam member.

2. The lock mechanism of the storage box of claim 1, wherein the second cam member is rotated by a movement of the operation member activated by an operation of a user and the rotational movement of the second cam member is restricted by the rotation lock plate.
 3. The lock mechanism of the storage box of claim 1, wherein the cam support member comprises a guide part for guiding a sliding movement of at least one of the first and second cam members.
 4. The lock mechanism of the storage box of claim 2, wherein the rotation lock plate is operated to be rotated by a rotation of a key cylinder, and the key cylinder is arranged between the operation member and a cam mechanism including the first and second cam members.
 5. The lock mechanism of the storage box of claim 1, wherein the rotation lock plate is configured to restrict the rotational movement of the second cam member in a case that the rotation lock plate is at a position along a contact part provided on the cam support member.
 6. The lock mechanism of the storage box of claim 1, wherein the contact part is provided on a plate-receiving concave part of the cam support member, and wherein the rotation lock plate is inserted into the plate-receiving concave part.
-