

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250263788

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Combs; David Howard et al.

APPARATUS FOR APPLYING THERMAL ENERGY TO A RECEPTACLE AND DETECTING AN EMISSION SIGNAL FROM THE RECEPTACLE

Abstract

A method for determining the presence of a target nucleic acid in a sample includes transporting multiple receptacles to each of a plurality of corresponding receptacle wells of a thermally-conductive receptacle holder, each of the receptacles containing a reaction mixture, wherein the receptacle holder is in thermal communication with a support, and wherein the support is in thermal communication with a heat sink, pre-heating the heat sink to a temperature above ambient temperature, cycling the temperature of the receptacle holder, establishing optical communication between each of the receptacle wells and an excitation signal source and an emission signal detector, and determining whether an emission signal is emitted from any of the receptacles as an indication of the presence of a target nucleic acid.

Inventors: Combs; David Howard (San Diego, CA), OPALSKY; David (San Diego, CA)

Applicant: Gen-Probe Incorporated (San Diego, CA)

Family ID: 1000008586709

Assignee: Gen-Probe Incorporated (San Diego, CA)

Appl. No.: 19/027025

Filed: January 17, 2025

Related U.S. Application Data

parent US continuation 18386976 20231103 PENDING child US 19027025

parent US continuation 17028367 20200922 parent-grant-document US 11840727 child US 18386976

parent US continuation 17025735 20200918 parent-grant-document US 11230733 child US 17028367

parent US continuation 16434910 20190607 parent-grant-document US 10961572 child US

17025735

parent US continuation 13956022 20130731 parent-grant-document US 10494668 child US 16434910

us-provisional-application US 61783952 20130314

us-provisional-application US 61677976 20120731

Publication Classification

Int. Cl.: **C12Q1/686** (20180101); **B01L7/00** (20060101); **B01L9/06** (20060101); **G01N21/64** (20060101)

U.S. Cl.:

CPC **C12Q1/686** (20130101); **B01L7/52** (20130101); **G01N21/6452** (20130101); **B01L9/06** (20130101); **B01L2200/141** (20130101); **B01L2200/142** (20130101); **B01L2300/042** (20130101); **B01L2300/0654** (20130101); **B01L2300/0829** (20130101); **B01L2300/0851** (20130101); **B01L2300/1822** (20130101); **G01N2021/6482** (20130101); **G01N2021/6484** (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This is a continuation of U.S. application Ser. No. 18/386,976, filed Nov. 3, 2023, which is a continuation of U.S. application Ser. No. 17/028,367 filed Sep. 22, 2020, now U.S. Pat. No. 11,840,727, which is a continuation of U.S. application Ser. No. 17/025,735 filed Sep. 18, 2020, now U.S. Pat. No. 11,230,733, which is a continuation of U.S. application Ser. No. 16/434,910 filed Jun. 7, 2019, now U.S. Pat. No. 10,961,572, which is a continuation of U.S. application Ser. No. 13/956,022 filed Jul. 31, 2013, now U.S. Pat. No. 10,494,668, which claims the benefit under 35 U.S.C. § 119 (e) of the filing date of provisional patent application Ser. Nos. 61/677,976, filed Jul. 31, 2012, and 61/783,952, filed Mar. 14, 2013, the respective disclosures of which are incorporated herein by reference.

BACKGROUND

[0002] The present disclosure relates generally to a system and apparatus for automated heating and/or cooling of samples.

BACKGROUND INFORMATION

[0003] Automated molecular assay instrumentation offers numerous advantages, however most automated instruments suffer from a limited set of assay capabilities. These limited capabilities complicate or inhibit parallel processing of multiple assays and, as a result, reduce sample throughput and flexibility in assay choices. This is particularly true for assays requiring incubation of some sort, such as the temperature cycling necessary for polymerase chain reaction (PCR) based assays. In PCR instruments a thermocycler is included that is capable of cycling the temperature of many samples, such as a batch of samples held within a 96-well microtiter plate. This assay format requires the preparation of the entire batch of samples prior to subjecting them to an initial temperature cycle. For example, the first sample that is fully prepared for temperature cycling must wait until the last sample is prepared prior to temperature cycling. In the case of a 96-well plate, this wait time can be substantial, thus slowing the throughput of the instrument. In addition, since all samples are subject to the same temperature profile and cycling parameters, the types of assays that can be run in parallel are limited. Different assays often must be run in completely different thermocycler units or await availability of the thermocycler from a prior batch of samples. This too

inhibits the ability to provide rapid assay results.

[0004] The present disclosure addresses these and other needs in the art.

[0005] All documents referred to herein, or the indicated portions, are hereby incorporated by reference herein. No document, however, is admitted to be prior art to the claimed subject matter.

SUMMARY

[0006] The present disclosure relates to a system and apparatus for altering the temperature of at least one receptacle holder that is adapted for use in an automated instrument capable of performing biochemical assays.

[0007] In an aspect of the present disclosure, there is provided an apparatus that includes one or more receptacle holders made of a heat-conducting material. Each receptacle holder includes a plurality of receptacle wells, each receptacle well being configured to receive a receptacle therein; a plurality of through-holes, each through-hole extending from an inner surface of one of the receptacle wells to an outer surface of the receptacle holder; a plurality of optical fibers, each optical fiber having first and second ends, wherein the first end is in optical communication with one of the receptacle wells, and the second end is in optical communication with at least one of an excitation signal source and an emission signal detector, the first end of each optical fiber being disposed outside, within, or extending through, a corresponding through-hole in each receptacle well, and wherein the first end of each optical fiber is moveable or fixedly disposed within one of the through-holes relative to the surface of the receptacle well; and one or more thermal elements positioned proximal to the receptacle holder for altering a temperature or temperatures of the receptacle holder. In certain embodiments, the apparatus includes a cover movable between an opened position and a closed position relative to the receptacle holder, wherein one or more receptacles disposed within one or more of the receptacle wells are seated or secured into the receptacle well by the cover when the cover is moved into the closed position. In an exemplary embodiment, the first end of each optical fiber moves within its corresponding through-hole when (1) the cover is moved to the closed and/or opened position, or (2) a receptacle is present in the receptacle well and the cover is moved to the closed and/or open position. In a variety of these embodiments, the apparatus does not include a cover. Also, in a variety of these embodiments, when these apparatuses are comprised in a system, one or more of these apparatuses do/does not include a cover. One or more receptacle transport mechanism(s) are often included in such systems to transport receptacles to the receptacles wells, deposit the receptacles in the receptacles wells, optionally ensure each receptacle is securely seated in its respective receptacle well by using, for example, physical contact, and removing each receptacle from its respective receptacle well. More than one receptacle transport mechanism may be utilized in such embodiments to effect one or more of these steps.

[0008] In various embodiments, the thermal element is positioned proximal to a side surface of the receptacle holder and provides thermal energy through the receptacle holder to each of the plurality of receptacle wells. The thermal energy may be uniform. In frequent embodiments, the apparatus further includes one or more support(s), each positioned proximal to a side surface of one or more of the receptacle holders, and the thermal element is positioned between the support and the receptacle holder. One or more thermistors may be disposed in contact with the receptacle holder. In a variety of embodiments, the one or more thermistors and/or associated wiring thereof are disposed within a channel formed in the receptacle holder. In certain embodiments, the apparatus further includes one or more closed-ended channels formed on opposing sides of a receptacle well of the receptacle holder, each having one of the thermistors disposed therein.

[0009] In certain embodiments the apparatus further includes one or more cross-braces positioned to provide compressive force between the receptacle holder and the support. In other embodiments, the apparatus further includes one or more bodies having a low thermal conductivity, each connected directly or indirectly with a linker, positioned to provide compressive force between the receptacle holder and the support. In various embodiments, the support of the apparatus is a heat

sink or the support is provided in thermal communication with a heat sink. The apparatus may include a first controller electrically connected to the thermal element to cycle the temperature of the thermal element and may include one or more motors electrically connected to the first controller disposed in moveable communication with the cover, if present. In various embodiments, if present, the cover may include a rigid element and one or more flexible extensions, wherein the flexible extensions are attached to, and extend laterally away from, the rigid element to apply a force when the cover is in the closed position to at least a portion of one or more receptacles when present within the receptacle wells.

[0010] In exemplary embodiments, the apparatus further includes a stripper plate in movable association with the receptacle holder for removing a receptacle from a receptacle transport mechanism that delivers a receptacle to the receptacle holder. The stripper plate may be moveable relative to the receptacle well into unlocked and locked positions, wherein the unlocked position permits access of a receptacle to the receptacle well, and wherein the locked position inhibits removal of the receptacle from the receptacle well without inhibiting access to the receptacle by the receptacle transport mechanism.

[0011] In another aspect, the disclosure provides a system that includes one or more apparatus of the present disclosure. In various embodiments, each of the one or more apparatus is in independent thermal communication with a single heat sink. The thermal element corresponding to each receptacle holder within the system may be independently controllable to only alter the temperature of its corresponding receptacle holder. In frequent embodiments, the system includes one or more controllers electrically connected to the thermal elements, and to one or more motors disposed in moveable communication with a cover corresponding to each receptacle holder. In various embodiments, the system does not include a cover. The system may include at least ten receptacle wells and at least ten corresponding optical fibers, wherein the second ends of all of the optical fibers are in optical communication with one or more excitation signal sources and/or one or more emission signal detectors. In frequent embodiments, the system is disposed in a single housing.

[0012] In another aspect, the disclosure provides a method of conducting an automated, random-access incubation process. In one exemplary embodiment, the method includes the automated steps of transferring a first set of receptacles to a first receptacle holder and subjecting the contents of the first set of receptacles to a first incubation process, and during the first incubation process, transferring a second set of receptacles to a second receptacle holder and subjecting the contents of the second set of receptacles to a second incubation process. In another exemplary embodiment, the first and second receptacle holders are components of the apparatus as disclosed herein. Each of the first and second sets of receptacles may be sealed to prevent contamination and/or evaporation. In various exemplary embodiments, the first and second receptacle holders are each in thermal communication with a single temperature cycling apparatus, as described herein.

[0013] In frequent embodiments, the method further includes, during the second incubation process, beginning a third of three or more independent processes comprising: transferring a third or higher set of receptacles to a third or higher receptacle holder and subjecting the contents of the third or higher set of receptacles to a third or higher incubation process, wherein the transfer of each successive set of receptacles is begun prior to completion of the incubation process for each immediately preceding set of receptacles. The transfer of the first and second sets of receptacles may be effected by a receptacle transport mechanism. As described herein, each set of receptacles may be removed from its respective receptacle holder prior to completion of the next successive incubation process.

[0014] In another aspect, the disclosure provides a method of establishing optical communication between a receptacle and an excitation signal source and/or an emission signal detector within a housing of an apparatus. The method includes the automated steps of providing a receptacle to a well of a receptacle holder comprised of a heat-conducting material, applying a first force to the

receptacle, thereby seating the receptacle within the well, and either of (1) while the force is being applied to the receptacle, effecting movement of an end of an optical fiber toward and into contact with the seated receptacle, or (2) while the force is being applied to the receptacle, the receptacle applies a second force to an end of an optical fiber disposed within the well such that the end of the optical fiber moves within the well in a direction opposite from the direction of the applied second force.

[0015] In various embodiments, the receptacle is in contact with the optical fiber during or after step (a), and while the force is being applied to the receptacle, the receptacle contacts and applies force to the end of the optical fiber disposed within the well such that the end of the optical fiber moves within the well in a direction opposite from the direction of the applied force. The end of or an area proximal to the end of the optical fiber may be connected, directly or indirectly, with a resilient element to the receptacle holder such that the resilient element compresses when force is applied to the receptacle.

[0016] In yet another exemplary aspect, the disclosure provides an apparatus that includes a housing, a plurality of receptacle holders contained within the housing, each comprised of a heat-conducting material, wherein each receptacle holder comprises a plurality of receptacle wells, one or more thermal elements positioned proximal to each receptacle holder for altering a temperature or temperatures of the plurality of receptacle wells. In various embodiments, the apparatus further includes a plurality of covers, each disposed in moveable association with a receptacle holder, wherein a first controller controls movement of each cover between an opened and a closed position. When at least one receptacle is present in the plurality of receptacle wells it is secured within the receptacle wells by the cover when in the closed position. When the cover is in the opened position, a receptacle transport mechanism can access the plurality of receptacle wells to introduce or remove a receptacle. In addition, each cover can move between the opened and closed positions together with, or independently of, one or more other covers. In other various embodiments, the apparatus does not include a cover.

[0017] In various embodiments, the apparatus further includes an optical fiber associated with each receptacle well such that optical communication is established between an interior of each receptacle well and an excitation signal source and/or an emission signal detector. The apparatus may further include one or more receptacles in the plurality of receptacle wells, and optical communication is established between each receptacle and the excitation signal source and/or the emission signal detector by the optical fibers. In frequent embodiments, the apparatus further includes a stripper plate in moveable association with each receptacle holder for removing a receptacle from the receptacle transport mechanism.

[0018] In various embodiments, the support of the apparatus is a heat sink or the support is provided in thermal communication with a heat sink. The apparatus may include a first controller electrically connected to the thermal element to cycle the temperature of the thermal element and may include one or more motors electrically connected to the first controller disposed in moveable communication with the cover, if present. In various embodiments, if present, the cover may include a rigid element and one or more flexible extensions, wherein the flexible extensions are attached to, and extend laterally away from, the rigid element to apply a force when the cover is in the closed position to at least a portion of one or more receptacles when present within the receptacle wells.

[0019] In yet another exemplary aspect, the disclosure provides an apparatus that includes a housing, a plurality of receptacle holders contained within the housing, each comprised of a heat-conducting material, wherein each receptacle holder comprising a plurality of receptacle wells, and one or more thermal elements electrically connected to a first controller, and positioned proximal to each receptacle holder for altering a temperature or temperatures of the plurality of receptacle wells. In various embodiments, the apparatus may further include a plurality of covers, each being movable between a first non-engagement position and a second engagement position with respect

to a receptacle holder, wherein each cover comprises a series of flexible extensions, wherein each individual flexible extension is associated with a single receptacle well within the receptacle holder, and wherein the movement of each cover between the first non-engagement position and second engagement position is controlled by a second controller. When at least one receptacle is present in the plurality of receptacle wells it is secured within the receptacle well by the cover when in the second position. When the cover is in the first position, a receptacle transport mechanism can access the plurality of receptacle wells to introduce or remove a receptacle. In addition, each cover can move between the first and second positions together with, or independently of, one or more other covers. The first controller and the second controller may be the same unit. In other various embodiments, the apparatus does not include a cover or a plurality of covers.

[0020] In various embodiments, the support of the apparatus is a heat sink or the support is provided in thermal communication with a heat sink. The apparatus may include a first controller electrically connected to the thermal element to cycle the temperature of the thermal element and may include one or more motors electrically connected to the first controller disposed in moveable communication with the cover, if present. In various embodiments, if present, the cover may include a rigid element and one or more flexible extensions, wherein the flexible extensions are attached to, and extend laterally away from, the rigid element to apply a force when the cover is in the closed position to at least a portion of one or more receptacles when present within the receptacle wells.

[0021] In yet another exemplary aspect, the disclosure provides an apparatus that includes one or more receptacle holders made of a heat-conducting material. Each receptacle holder includes a plurality of receptacle wells, each receptacle well being configured to receive a receptacle therein; a plurality of through-holes, each through-hole extending from an inner surface of one of the receptacle wells to an outer surface of the receptacle holder; and a plurality of optical fibers, each optical fiber having first and second ends, wherein the first end is in optical communication with one of the receptacle wells, and the second end is in optical communication with at least one of an excitation signal source and/or an emission signal detector, the first end of each optical fiber being disposed outside, within, or extending through, a corresponding through-hole in each receptacle well, one or more thermal elements positioned proximal to the receptacle holder for altering a temperature or temperatures of the receptacle holder. In various embodiments, the apparatus does not have a cover. In various embodiments, the apparatus further includes a primary cover fixedly positioned over the receptacle holder and having one or more securing arms in alignment with and disposed in a surrounding arrangement with each receptacle well of the receptacle holder, wherein one or more receptacles disposed within one or more of the receptacle wells are seated or secured into the receptacle well by the securing arms; and a secondary cover fixedly positioned over the primary cover and having one or more releasing arms in alignment with and in sliding contact with the securing arms of the primary cover. In an exemplary embodiment, application of a force onto the releasing arms urges the securing arms to flex in a radial outward direction relative to an axial center of the receptacle well, thereby releasing the receptacle disposed within the receptacle well. One, two, three, four, or more securing arms are contemplated. In other various embodiments, the apparatus does not include a primary or secondary cover. In a variety of embodiments, the one or more thermistors and/or associated wiring thereof are disposed within a channel formed in the receptacle holder. In certain embodiments, the apparatus further includes one or more closed-ended channels formed on opposing sides of a receptacle well of the receptacle holder, each having one of the thermistors disposed therein.

[0022] In yet another exemplary aspect, the disclosure provides an apparatus that includes one or more receptacle holders made of a heat-conducting material. Each receptacle holder includes a plurality of receptacle wells, each receptacle well being configured to receive a receptacle therein; a plurality of through-holes, each through-hole extending from an inner surface of one of the

receptacle wells to an outer surface of the receptacle holder; a plurality of optical fibers, each optical fiber having first and second ends, wherein the first end is in optical communication with one of the receptacle wells, and the second end is in optical communication with at least one of an excitation signal source and an emission signal detector, the first end of each optical fiber being disposed outside, within, or extending through, a corresponding through-hole in each receptacle well, and wherein the first end of each optical fiber is moveable within one of the through-holes relative to the surface of the receptacle well; and one or more thermal elements positioned proximal to the receptacle holder for altering a temperature or temperatures of the receptacle holder. In various embodiments, the apparatus may further include a cover movable between an opened position and a closed position relative to the receptacle holder. When present, one or more receptacles disposed within one or more of the receptacle wells are securely seated to maximize contact with the inner surfaces of the receptacle wells without the need for contact with the cover. In certain embodiments, the apparatus may not include a cover. In a variety of embodiments, the one or more thermistors and/or associated wiring thereof are disposed within a channel formed in the receptacle holder. In certain embodiments, the apparatus further includes one or more closed-ended channels formed on opposing sides of a receptacle well of the receptacle holder, each having one of the thermistors disposed therein.

[0023] In other embodiments, the present disclosure provides methods of introducing and removing a receptacle from a receptacle holder utilizing a fluid transfer apparatus, wherein the fluid transfer apparatus is configured to fixedly introduce the receptacle to the receptacle holder and to release the receptacle from a securing mechanism disposed within the receptacle holder that fixedly holds the receptacle within the receptacle holder.

[0024] In yet another exemplary aspect, the disclosure provides a system that includes one or more apparatus of the present disclosure. In various embodiments, the system also includes a receptacle transport mechanism, which may be a modified pipettor. The receptacle transport mechanism includes a body having a plunger slidingly disposed therein, and one or more limbs hingedly attached to the body and positioned in sliding communication with a knob fixedly attached to the plunger. When the plunger is in a first position, a lower portion of the one or more limbs are proximal to the body, and when the plunger is in a second position, the lower portion of the one or more limbs are extended in a radial outward direction relative to the body.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] FIG. 1 is a pictorial diagram showing an apparatus of the present disclosure.

[0026] FIG. 2 is a pictorial diagram showing an apparatus of the present disclosure mounted in a housing.

[0027] FIGS. 3A-3C are pictorial diagrams showing a receptacle holder of the present disclosure.

[0028] FIG. 4 is a pictorial diagram showing the top view of an apparatus of the present disclosure mounted in a housing.

[0029] FIGS. 5A-5C are pictorial diagrams showing a receptacle holder mounted in sliding engagement with a support. The support is mounted in thermal communication with a heat sink (FIG. 5A). A cross-brace may be mounted to the support to exert a force onto a front surface of the receptacle holder (FIG. 5B). A detailed view of the support is shown in FIG. 5C.

[0030] FIGS. 5D and 5E are pictorial diagrams showing an exemplary receptacle holder. The receptacle holder may include a channel through which the wiring and/or electrical connections for one or more thermistors may be disposed (FIG. 5D). The receptacle holder may also include one or more bulges formed corresponding to closed through-holes disposed within the channel for containing the one or more thermistors (FIG. 5E).

[0031] FIGS. 6A and 6B are pictorial diagrams showing a receptacle holder mounted in sliding engagement with a support.

[0032] FIGS. 7A and 7B are pictorial diagrams showing multiple rows of receptacle holders disposed in an apparatus of the present disclosure (FIG. 7A), and that cartridge heaters may be disposed within the heat sink of the apparatus (FIG. 7B).

[0033] FIGS. 8A-8E are pictorial diagrams showing exemplary covers and stripper plates disposed within the apparatus of the present disclosure.

[0034] FIGS. 9A-9C are pictorial diagrams showing movement of the optical fibers of the apparatus of the present disclosure and the forces associated therewith prior to and after seating receptacles within the receptacle wells of a receptacle holder.

[0035] FIG. 10 is a pictorial diagram showing an apparatus in optical communication with an excitation signal source and/or an emission signal detector within a housing of an instrument for performing a biochemical assay.

[0036] FIGS. 11A and 11B are flow charts showing exemplary steps involved in a method for establishing optical communication between a receptacle and an excitation signal source and/or an emission signal detector within a housing of the apparatus while allowing maximal contact between the surface of the receptacle well and the receptacle.

[0037] FIGS. 12A-12D are pictorial diagrams showing exemplary steps involved in loading receptacles into the receptacle wells of a receptacle holder of an apparatus of the present disclosure.

[0038] FIG. 13 is a flow chart showing exemplary steps involved in a method of conducting automated, random-access temperature cycling processes.

[0039] FIGS. 14A-14D are pictorial diagrams showing a second exemplary embodiment of an apparatus of the present disclosure.

[0040] FIGS. 15A-15C are pictorial diagrams showing a modified pipettor for use as a receptacle transport mechanism within a system of the present disclosure.

[0041] FIG. 16 is a pictorial diagram showing a perspective view of an alternative exemplary embodiment of the cover mechanism of the apparatus.

DETAILED DESCRIPTION

[0042] The present disclosure relates to a system, apparatus, and method for incubating at least one receptacle holder that is adapted for use in an automated instrument capable of performing nucleic acid-based amplification assays. Also provided are methods for conducting automated, random-access temperature cycling processes using the same.

[0043] Before the present systems, methods, and apparatuses are described, it is to be understood that this disclosure is not limited to particular methods and experimental conditions described, as such methods and conditions may vary. It is also to be understood that the terminology used herein is for purposes of describing particular embodiments only, and is not intended to be limiting, since the scope of the present disclosure will be limited only in the appended claims.

[0044] As used in this specification and the appended claims, the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise. Thus, for example, references to “the method” includes one or more methods, and/or steps of the type described herein which will become apparent to those persons skilled in the art upon reading this disclosure and so forth.

[0045] The term “comprising,” which is used interchangeably with “including,” “containing,” “having,” or “characterized by,” is inclusive or open-ended language and does not exclude additional, unrecited elements or method steps. The phrase “consisting of” excludes any element, step, or ingredient not specified in the claim. The phrase “consisting essentially of” limits the scope of a claim to the specified materials or steps and those that do not materially affect the basic and novel characteristics of the disclosed subject matter. The present disclosure contemplates exemplary embodiments of an apparatus and methods of use thereof corresponding to the scope of each of these phrases. Thus, an apparatus or method comprising recited elements or steps

contemplates particular embodiments in which the apparatus or method consists essentially of or consists of those elements or steps.

[0046] Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. Although any methods and materials similar or equivalent to those described herein can be used in the practice or testing disclosed herein, the preferred methods and materials are now described.

[0047] As used herein, a “reaction mixture” refers to a volume of fluid comprising one or more of a buffer for a nucleic acid amplification reaction, one or more nucleotides, an enzyme, and a sample containing or suspected of containing a nucleic acid.

[0048] As used herein, a “sample” or a “test sample” refers to any substance suspected of containing a target organism or biological molecule, such as nucleic acid. The substance may be, for example, an unprocessed clinical specimen, a buffered medium containing the specimen, a medium containing the specimen and lytic agents for releasing nucleic acid belonging to the target organism, or a medium containing nucleic acid derived from a target organism which has been isolated and/or purified in a reaction receptacle or on a reaction material or device. In some instances, a sample or test sample may comprise a product of a biological specimen, such as an amplified nucleic acid to be detected.

[0049] As used herein, “analyte” refers to a substance, such as a nucleic acid or protein, that is detected or measured in an analytical procedure. The analyte may be contained in a sample undergoing testing.

[0050] As used herein, “polynucleotide” refers to either RNA, DNA, or a chimeric molecule containing both RNA and DNA.

[0051] As used herein, “nucleic acid” refers to a multimeric compound comprising nucleosides or nucleoside analogs which have nitrogenous heterocyclic bases, or base analogs, which are linked by phosphodiester bonds or other linkages to form a polynucleotide. Nucleic acids include RNA, DNA, or chimeric DNA-RNA polymers, and analogs thereof. A nucleic acid “backbone” may be made up of a variety of linkages, including one or more of sugar-phosphodiester linkages, peptide-nucleic acid (PNA) bonds (PCT No. WO 95/32305), phosphorothioate linkages, methylphosphonate linkages, or combinations thereof. Sugar moieties of the nucleic acid may be either ribose or deoxyribose, or similar compounds having known substitutions, such as 2' methoxy substitutions and 2' halide substitutions (e.g., 2'-F). Nitrogenous bases may be conventional bases (A, G, C, T, U), analogs thereof (e.g., inosine), derivatives of purine or pyrimidine bases, such as N.sup.4-methyl deoxyguanosine, deaza- or aza-purines, deaza- or aza-pyrimidines, pyrimidine bases having substituent groups at the 5 or 6 position, purine bases having an altered or replacement substituent at the 2, 6 and/or 8 position, such as 2-amino-6-methylaminopurine, O.sup.6-methylguanine, 4-thio-pyrimidines, 4-amino-pyrimidines, 4-dimethylhydrazine-pyrimidines, and O.sup.4-alkyl-pyrimidines, and pyrazolo-compounds, such as unsubstituted or 3-substituted pyrazolo[3,4-d]pyrimidine (U.S. Pat. Nos. 5,378,825, 6,949,367 and PCT No. WO 93/13121). Nucleic acids may include “abasic” positions in which the backbone does not include a nitrogenous base for one or more residues (see U.S. Pat. No. 5,585,481). Nucleic acids also include “locked nucleic acids” (LNA), an analog containing one or more LNA nucleotide monomers with a bicyclic furanose unit locked in an RNA mimicking sugar conformation (Vester et al., 2004, *Biochemistry* 43(42):13233-41). A nucleic acid may comprise only conventional sugars, bases, and linkages as found in RNA and DNA, or may include conventional components and substitutions (e.g., conventional bases linked by a 2' methoxy backbone, or a nucleic acid including a mixture of conventional bases and one or more base analogs). Methods for synthesizing nucleic acids in vitro are well known in the art.

[0052] As used herein “oligonucleotide” or “oligomer” refers to a polymer made up of two or more nucleoside subunits or nucleobase subunits coupled together. Oligonucleotides preferably have a

length in the range of from 10-100 nucleotides, more preferably 10-80 nucleotides, and still more preferably from 15-60 nucleotides. The oligonucleotide may be DNA and/or RNA and analogs thereof. The sugar groups of the nucleoside subunits may be ribose, deoxyribose and analogs thereof, including, for example, ribonucleosides having a 2'-O-methylsubstitution to the ribofuranosyl moiety. Oligonucleotides including nucleoside subunits having 2' substitutions and which are useful as detection probes, capture oligos and/or amplification oligonucleotides are disclosed in U.S. Pat. No. 6,130,038. The nucleoside subunits may be joined by linkages such as phosphodiester linkages, modified linkages, or by non-nucleotide moieties, which do not prevent hybridization of the oligonucleotide to its complementary target nucleic acid sequence. Modified linkages include those linkages in which a standard phosphodiester linkage is replaced with a different linkage, such as a phosphorothioate linkage or a methylphosphonate linkage. The nucleobase subunits may be joined, for example, by replacing the natural deoxyribose phosphate backbone of DNA with a pseudo-peptide backbone, such as a 2-aminoethylglycine backbone which couples the nucleobase subunits by means of a carboxymethyl linker to the central secondary amine. (DNA analogs having a pseudo-peptide backbone are commonly referred to as "peptide nucleic acids" or "PNA," and are disclosed in U.S. Pat. No. 5,539,082). Other non-limiting examples of oligonucleotides or oligomers contemplated by the present disclosure include nucleic acid analogs containing bicyclic and tricyclic nucleoside and nucleotide analogs referred to as "Locked Nucleic Acids," "Locked Nucleoside Analogues" or "LNA." (see, e.g., U.S. Pat. Nos. 6,083,482; 6,268,490; and 6,670,461). Any nucleic acid analog is contemplated by the present disclosure, provided that the modified oligonucleotide can hybridize to a target nucleic acid under either stringent hybridization conditions or amplification reaction conditions.

[0053] As used herein, the term "biochemical assay" refers to a scientific investigative procedure for qualitatively assessing or quantitatively measuring the presence or amount or the functional activity of a target entity, such as, but not limited to, a biochemical substance, a cell, organic sample, or target nucleic acid sequence. Included in the term "biochemical assay" are nucleic acid amplification and heat denaturation (i.e., melting). Nucleic acid melting typically involves precise warming of a double stranded nucleic acid molecule to a temperature at which the two strands separate or "melt" apart. The melting process typically occurs at a temperature of about 50° C. to about 95° C.

[0054] As used herein, a "target nucleic acid sequence" or "target sequence" refers to a strand of nucleic acid molecules that is to be assayed. Thus, when used in the context of an amplification assay, a target sequence refers to a sequence of nucleotides or a portion of a nucleic acid molecule that is intended to be copied.

[0055] As used herein, "amplification" or "amplifying" refers to an in vitro procedure for obtaining multiple copies of a target nucleic acid sequence, its complement or fragments thereof. For example, an in vitro amplification reaction is an enzyme-catalyzed reaction that results in the synthesis of multiple copies of a target nucleic acid sequence, its complement or fragments thereof. Examples of amplification methods that can be used for preparing in vitro amplification reactions are given below. Preferred in vitro amplification reactions synthesize amplicons in an exponential fashion, meaning that one amplicon serves as the template for production of new amplicons. As used herein, the term "amplicon" or "amplification product" refers to a nucleic acid molecule generated in a nucleic acid amplification reaction. An amplicon or amplification product contains a target nucleic acid sequence that may be of the same or opposite sense as the target nucleic acid.

[0056] Target nucleic acid amplification involves the use of amplification oligonucleotides (e.g., primer sequences) and enzymes (e.g., polymerases) to synthesize nucleic acid amplification products (copies) containing a sequence that is either complementary or homologous to the template nucleic acid sequence being amplified. As used herein, an "amplification oligonucleotide" refers to a strand of nucleic acid that serves as a starting point for the production of amplification products. The amplification products may be either extension products or transcripts generated in a

transcription-based amplification procedure. The amplification oligonucleotides may be provided to a reaction mixture free in solution or one or more of the amplification oligonucleotides may be immobilized on a solid support, including the inner surface of a chamber or chambers within a receptacle. See, e.g., U.S. Pat. Nos. 5,641,658 and 7,582,470. Examples of nucleic acid amplification procedures practiced in the art include, but are not limited to, the polymerase chain reaction (PCR), strand displacement amplification (SDA), helicase dependent amplification (HDA), loop-mediated isothermal amplification (LAMP), and a variety of transcription-based amplification procedures, including transcription-mediated amplification (TMA), nucleic acid sequence based amplification (NASBA), and self-sustained sequence replication (3SR). See, e.g., Mullis, "Process for Amplifying, Detecting, and/or Cloning Nucleic Acid Sequences," U.S. Pat. No. 4,683,195; Walker, "Strand Displacement Amplification," U.S. Pat. No. 5,455,166; Kong et al., "Helicase Dependent Amplification of Nucleic Acids," U.S. Pat. No. 7,282,328, Notomi et al., "Process for Synthesizing Nucleic Acid," U.S. Pat. No. 6,410,278; Kacian et al., "Nucleic Acid Sequence Amplification Methods," U.S. Pat. No. 5,399,491; Becker et al., "Single-Primer Nucleic Acid Amplification Methods," U.S. Pat. No. 7,374,885; Malek et al., "Enhanced Nucleic Acid Amplification Process," U.S. Pat. No. 5,130,238; and Lizardi et al. (1988) *BioTechnology* 6:1197. With some procedures, the formation of detectable amplification products depends on an initial antibody/antigen interaction. See, e.g., Cashman, "Blocked-Polymerase Polynucleotide Immunoassay Method and Kit," U.S. Pat. No. 5,849,478. Nucleic acid amplification is especially beneficial when the amount of analyte (e.g., targeted nucleic acid, antigen or antibody) present in a sample is very low. By amplifying a target sequence associated with the analyte and detecting the synthesized amplification product, the sensitivity of an assay can be vastly improved, since less analyte is needed at the beginning of the assay to ensure detection of the analyte.

[0057] As used herein, the term "incubate," "incubation," "incubation process" and all variants thereof, refer collectively to altering the temperature of an object in a controlled manner such that conditions are sufficient for conducting the desired biochemical assay. Thus, it is envisioned that the terms encompass heating a receptacle to a desired temperature and maintaining such temperature for a fixed time interval. Also included in the terms is the act of subjecting a receptacle to one or more heating and cooling cycles (i.e., "temperature cycling"). While temperature cycling typically occurs at relatively high rates of change in temperature, the term is not limited thereto, and may encompass any rate of change in temperature.

[0058] As used herein, a "detectable label," or simply "label," refers to a chemical moiety that can be detected or can lead to a detectable response. Detectable labels in accordance with the present disclosure can be linked to probes, such as hybridization probes, either directly or indirectly. Examples of detectable labels include, but are not limited to, radioisotopes, enzymes, haptens, chromophores such as dyes or particles that impart a detectable color (e.g., latex beads or metal particles), luminescent compounds (e.g., bioluminescent, phosphorescent or chemiluminescent moieties) and fluorescent compounds.

Receptacle Holder

[0059] The conditions of a nucleic acid amplification reaction may be substantially isothermal or they may require periodic temperature changes, as with PCR thermal cycling. The apparatus described herein may be used to heat and maintain a nucleic acid containing sample to a constant or ambient temperature or it may be used to fluctuate the temperature thereof. Target nucleic acid amplification reactions may be either "real-time" or "end-point" assays. Accordingly, in an exemplary aspect, there is provided an apparatus to perform the heating (i.e., isothermal or temperature cycling) necessary for a nucleic acid amplification assay. As shown in FIG. 1, the apparatus **100** includes one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, or any whole number between 1 and 20, or more) receptacle holders **110** (see also FIG. 3). In an exemplary embodiment, the apparatus **100** includes two or more receptacle holders **110**. Such an apparatus may include a housing **50** (see FIGS. 2 and 4) within which the one or more receptacle holders **110** are located.

The housing **50** may be made from any suitable structural material such as, for example, plastic or metal.

[0060] When multiple receptacle holders **110** are provided in an apparatus described herein, each receptacle holder **110** disposed within the apparatus may be disposed in alignment with one another to facilitate the automated processing steps involved in nucleic acid amplification assays. It should be understood that any alignment may be used in accordance with the size and shape of the apparatus. In an exemplary embodiment, the receptacle holders are disposed within the apparatus in one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) rows of two receptacle holders per row, as shown in FIG. **4**. Thus, two receptacle holders may be disposed in a row either in thermal connection with, or thermally separated from, one another. In an exemplary embodiment, the apparatus **100** includes six rows of two receptacle holders per row.

[0061] As shown in FIGS. **3A-3C**, the receptacle holder **110** includes a plurality (i.e., two or more) of receptacle wells **120** that are configured to receive a receptacle **130** optionally containing a sample or reaction mixture **140**. For purposes of explanation, the surface of the receptacle holder into which the receptacles **130** are inserted will be referred to as the “top surface” **150** thereof. Likewise, the surface of the receptacle holder opposite to the surface into which the receptacles **130** are inserted will be referred to as the “bottom surface” **160**. In an exemplary embodiment, each receptacle holder **110** includes five or more (i.e., 5, 6, 7, 8, 9, 10, or any whole integer between 1 and 10, or more) receptacle wells **120**. In another exemplary embodiment, each receptacle holder **110** includes one to ten receptacle wells. In another exemplary embodiment, each receptacle holder includes three to six receptacle wells. In yet another exemplary embodiment, each receptacle holder includes five receptacle wells. Each of the plurality of receptacle wells within a respective receptacle holder may be disposed in alignment with one another. In an exemplary embodiment, the receptacle wells **120** are disposed in a row extending along the length of the top surface **150** of the receptacle holder **110**.

[0062] Exemplary materials from which a receptacle holder may be made include, but are not limited to, aluminum, titanium, copper, steel, magnesium, metal composites, metal alloys, ceramics, plastics, plastic composites, or any suitable thermally-conductive material.

[0063] As used herein, a receptacle well of the receptacle holder that is “configured to receive” a particular size or shape of receptacle refers to a receptacle well whose dimensions are substantially similar to the size and shape of a receptacle **130** (i.e., a sample tube) such that the receptacle **130** fits snugly within the receptacle well **120**, thereby maximizing contact between the surface of the receptacle well **120** and the receptacle **130**. In certain embodiments, this maximal contact refers to physical contact of the receptacle well **120** with at least a portion of the receptacle **130**. In various embodiments, receptacles **130** in accordance with the present disclosure are individual reaction vessels made from suitable rigid or flexible materials, and shaped and dimensioned to fit within the receptacle wells of the apparatus described herein. In other embodiments, two or more (i.e., 2, 3, 4, 5, or more) receptacles may be manufactured as a single unit configured to fit within a receptacle holder. Each receptacle **130** may be closed or sealed to prevent contamination of and/or evaporation of the contents therein, and/or to facilitate handling or transport of each receptacle. Such seals may be permanent or semi-permanent and may be fluid-tight. In certain embodiments the seal comprises a cap or lid **135**.

[0064] Within each receptacle well **120** is at least one through-hole **170**, which extends from an inner surface **180** of the receptacle well to an outer surface of the receptacle holder. In an exemplary embodiment, the through-hole **170** of a particular receptacle well **120** extends from the bottom-center of inner surface **180** of the receptacle well **120** and extends to the surface of the receptacle holder **110** that is opposite to the surface of the receptacle holder within which the receptacles **130** are inserted (i.e., in this embodiment, the through-hole extends from the bottom of the receptacle well **120** to the bottom surface **160** of the receptacle holder **110**). In certain embodiments the diameter of the through-hole **170** is the same as that of the bottom **190** of the

inner surface **180** of receptacle well **120**. In other embodiments, the through-hole **170** comprises a hole or opening having dimensions smaller than the bottom **190** of the inner surface **180** of receptacle well **120**. In other embodiments, the through-hole **170** comprises a hole or opening having dimensions the same size as, or larger than, the bottom **190** of the inner surface **180** of receptacle well **120**. The exact dimensions of the through-hole **170** may vary, provided that the presence of the through-hole **170** does not detrimentally affect the ability of the receptacle holder **110** to efficiently transfer heat to and from a receptacle **130** held within the receptacle well **120**.

Thermal Element

[0065] As shown in FIGS. 5A and 5B, positioned proximal to the receptacle holder is one or more thermal elements **200** for altering a temperature or temperatures of the receptacle holder **110**. As used herein, the term “thermal element” may include any known heating element for heating and cooling applications. In one embodiment, the thermal element is a resistive heating element, such as a thin metal film that is applied to the receptacle holder **110** by using well-known methods such as sputtering or controlled vapor deposition. The heating element also can be provided as a molded or machined insert (e.g., such as a cartridge) for incorporation into the receptacle holder **110**.

[0066] In an exemplary embodiment, the thermal element **200** is a thermoelectric device, such as a “Peltier device,” which is generally constructed from electron-doped n-p semiconductor pairs that act as miniature heat pumps. When current is applied to the semiconductor pairs, a temperature difference is established whereas one side becomes hot and the other cold. If the current direction is reversed, the hot and cold faces will be reversed. Usually an electrically nonconductive material layer, such as aluminum nitride or polyimide, is disposed over the substrate faces of the thermoelectric modules so as to allow for proper isolation of the semiconductor element arrays.

[0067] As used herein, “altered temperature or temperatures” of the receptacle holder refers to the increase or decrease of the temperature of the receptacle holder **110**. Often, the increase or decrease of the temperature is determined relative to the ambient temperature. Included in the term is the ability to individually adjust the temperature of one or more receptacle wells **120**, while separately adjusting the temperature of other receptacle wells within the same receptacle holder. Thus, the term may refer to uniformly raising/lowering the temperature of all receptacle wells **120** within a receptacle holder **110** or may refer to altering a subset of the receptacle wells **120** within a single receptacle holder **110**. As used herein, “ambient temperature” refers to the temperature of a surrounding environment, which may include a fluid (e.g., air or liquid) or solid structure.

[0068] The thermal element **200** may be electrically connected to a controllable power source **210** for applying a current across the element to alter the temperature thereof. Control of the power source **210** can be carried out by an appropriately programmed controller **220** (such as a computer) which receives signals from one or more thermal sensors **610** (see FIG. 6A) in thermal communication with the receptacle holder **110**, as discussed below, and/or signals from another processor **750** that controls the automated process steps involved with temperature cycling processes.

[0069] The thermal element **200** may be held in contact with a side surface **115** (see FIG. 3A) of the receptacle holder **110** by one or more supports **240** (see FIG. 5C), which may be positioned in sliding engagement with the receptacle holder **110**. As used herein, being positioned “in sliding engagement” refers to a non-fixed contact between adjacent surfaces of different parts of the apparatus described herein. Thus, when the apparatus **100** includes two or more receptacle holders **110**, each of the two or more receptacle holders are configured in sliding engagement with a support **240**. As used herein, the term “support” refers to a rigid structure, which can be thermally-conductive. Exemplary materials from which a support may be made include, but are not limited to, aluminum, titanium, copper, steel, magnesium, metal composites, metal alloys, ceramics, plastics, plastic composites, or any suitable rigid thermally-conductive material. Supports may also comprise a structure formed of, or from, a combination of materials, for example, plastic, metal (including alloys and composites), ceramic, or a combination of different types of one or more of

these materials.

[0070] As is known in the art, thermal elements may require a specific force to achieve adequate thermal contact with a component that is to be heated. For example, certain Peltier devices require a mounting force of approximately 150-300 psi to effectively transfer thermal energy to a device. With reference to FIG. 5B, the apparatus may include one or more cross-braces **248** mounted to a support **240**, and which exert a force **F1** onto a front surface **117** (see FIG. 3A) of a receptacle holder **110**. Force **F1** is sufficient to effect thermal transfer of energy from thermal element **200** to receptacle holder **200**. In certain embodiments, the apparatus includes one cross-brace **248** for each receptacle holder **110**. In other embodiments, the apparatus includes one cross-brace **248** per row of receptacle holders **110**. In such embodiments, the cross-brace generally incorporates a portion or layer having low thermal conductivity as the portion that directly contacts the receptacle holder **110**. As discussed below, in other embodiments, a body **300** (see FIGS. 6A, 6B, 7A) having low thermal conductivity is used to exert the force required for thermal transfer of energy to the receptacle holder **110**.

Support

[0071] As shown in FIG. 5C, the support **240** may be formed in a shape suitable for use in the apparatus described herein. In an exemplary embodiment, the support is a solid member having a base portion **245** and an upright portion **247**. In certain embodiments, the base portion **245** and upright portion **247** comprise a single contiguous material. The upright portion **247** may intersect the base portion at a right angle or may intersect the base portion **245** at an angle greater or less than 90°. Disposed within the base portion is a plurality of through-holes **242**, which are preferably in alignment with the through-holes **170** of the bottom surface **160** of the receptacle holder **110** that will be positioned in sliding engagement therewith. Each of the through-holes **242** of the base portion **245** of the support **240** form a channel through which optical fibers **400** (see FIGS. 5A, 7A) and/or associated components such as a fixed or moveable ferrule **450**, for example, may pass, thereby providing optical communication between each receptacle well **120** and an excitation signal source and/or an emission signal detector, as discussed below.

[0072] The upright portion **247** of the support **240** includes a first side **243** and second side **244**. The first side **243** is configured to be positioned proximal to a side surface **115** of the receptacle holder **110**, with the thermal element **200** being positioned between the first side **243** of the support **240** and the receptacle holder **110**. The second side **244** of the upright portion **247** of the support **240** provides a solid surface to which at least one body **300** having low thermal conductivity may be disposed (see FIGS. 6A, 6B, and 7A).

Body & Linker

[0073] As shown in FIGS. 6A, 6B, and 7A, when the apparatus **100** includes multiple supports **240** that are oriented in rows, as discussed above, the apparatus may include one or more bodies **300** having low thermal conductivity, each associated with a respective receptacle well **120** of a receptacle holder **110**. In certain embodiments, the apparatus will include a linker for exerting force **F1** through the body **300** onto the receptacle holder **110**.

[0074] As used herein, the term “linker” refers to any device that can exert a force in the direction that extends away from the surface upon which it is mounted. Exemplary linkers useful in the apparatus include, but are not limited to, springs, spacers, linear expanders, materials formed of elastic or rubbery material, piezoelectric devices, levers, screws, etc. As such, in an exemplary embodiment, a first end **312** of a linker **310** (e.g., spring) is mounted to the second side **243** of the upright portion **247** of a support **240**, while a second end **314** contacts and exerts a force **F1** onto a body **300** having lower thermal conductivity (e.g., a glass or plastic bead, cap, or insert). Each body **300** then transfers the force **F1** exerted upon it by the linker **310** onto the front surface **117** of the receptacle holder **110** opposite to the side surface **115** of the receptacle holder **110** that is in contact with the thermal element **200**, thereby ensuring maximal contact between the thermal element **200** and the receptacle holder **110**. In one embodiment, the apparatus **100** includes one to ten linkers

310 per support **240**, depending on the number of receptacle holders **110** positioned in sliding engagement therewith. In another embodiment, the apparatus **100** includes one linker **310** per receptacle well **120**. In yet another embodiment, the apparatus **100** includes two linkers **310** per support **240**. In yet another embodiment, the apparatus **100** includes five linkers **310** per support **240**.

[0075] It is noted that the body **300** should have a lower thermal conductivity than the receptacle holder **110** in order to prevent thermal energy from transferring from the receptacle holder **110** to the body **300** and/or support **240**. Exemplary bodies for use in the apparatus include, but are not limited to, glass or plastic beads that are connected, either directly or indirectly, to the receptacle holder by a linker **310** located between the support **240** and the body **300**.

[0076] Thus, as shown in FIG. 7A, a support **240** of a row of receptacle holders **110** may be provided as a solid surface by which body **300** and linker **310** exert a force **F1** to the receptacle holder **110** positioned in sliding engagement with the support **240** located in the row immediately subsequent thereto. For example, the body **300** of a first support **240** positioned in a first row **101** of receptacle holders **110** exerts a force **F1** onto the front surface **117** of a receptacle holder **110** positioned in sliding engagement with a second row **102**, wherein the first **101** and second **102** rows are adjacent to one another within the apparatus **100**, as described herein.

[0077] In certain embodiments, the apparatus may include a single support **240** in sliding engagement with all receptacle holders **110**, or may include a single support **240** in sliding engagement with each row (e.g., **101-106** in FIGS. 4 and 7A) of receptacle holders **110**, or may include a single support **240** in sliding engagement each individual receptacle holder **110**.

Thermistors

[0078] In various embodiments, the apparatus may further include one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) thermal sensors **610** to monitor the temperature of the receptacle holder **110**. A wide variety of microsensors are available for determining temperatures, including, e.g., thermocouples having a bimetallic junction which produces a temperature dependent electromotive force (EMF), resistance thermometers which include material having an electrical resistance proportional to the temperature of the material, thermistors, IC temperature sensors, quartz thermometers and the like. See, e.g., Horowitz and Hill, The Art of Electronics, Cambridge University Press 1994 (2nd Ed. 1994). As used herein, the term “thermistor” refers to a type of resistor whose resistance varies significantly with temperature. Such thermistors **610** may be disposed in direct or indirect contact with the receptacle holder **110**. In one embodiment, two or more thermistors **610** are disposed in contact with a receptacle holder **110**. In another embodiment, one or more thermistors **610** are disposed in contact with each of the receptacle wells **120** of a single receptacle holder **110** to enable monitoring of the temperatures of each of the individual receptacle wells **120**.

[0079] As shown in FIG. 5D, in an exemplary embodiment, receptacle holder **110** may include a channel **612** disposed within the side surface **115**. In various embodiments, the channel extends from an edge of the side surface **115** to a location corresponding to a center-most receptacle well **120** of the receptacle holder **110**. For example, in embodiments wherein the receptacle holder **110** includes five receptacle wells **120**, the channel **612** frequently extends to a location that corresponds with the third/central receptacle well **120**. The channel **612** is configured to accept therein wires and/or electrical connections for the thermistors **610** of the receptacle block.

Disposing the wires and/or electrical connections of the thermistors **610** within the channel **612** shields the thermistors and associated wiring thereof from the heat-depleting effects of ambient temperatures, thereby ensuring accurate monitoring of the temperature of the receptacle holder **110**. Provided at the end of the channel **612** corresponding with the center-most receptacle well **120** may be one or more closed through-holes **614** through which the thermistors may be provided such that the thermistors are in contact with the center-most receptacle well **120**. In certain embodiments, two through-holes **614** are provided within the channel **612** such that two thermistors may be

disposed therein to monitor the temperature of the receptacle holder **110** on opposing sides of the center-most receptacle wells **120**. Although not shown, channel **612** may extend the length of the receptacle holder **110**, and two closed through-holes **614** corresponding to each of the receptacle wells **120** may be provided therein.

[0080] As shown in FIG. 5E, to accommodate the thermistors inserted through through-holes **614**, the receptacle holder **110** may be formed to include one or more bulges **616** disposed on opposing sides of the center-most receptacle holder **120**. The bulges **616** provide a closed-ended channel surrounding a portion of the receptacle well **120** that extend from the side surface **115** of the receptacle holder **110** and terminating at the front surface **117** opposite to the side surface **115** of the receptacle holder **110**. Thus, when two thermistors **610** are provided to monitor the temperature of the receptacle holder **110**, one thermistor **610** is provided in each bulge **616** thereof. Although not shown, when channel **612** extends the length of the receptacle holder **110**, and two through-holes **614** are provided corresponding to each of the receptacle wells **120**, receptacle holder **110** may include one bulge **616** per through-hole **614** to accommodate individual thermistors therein. It is contemplated that additional through-holes **614** may be provided, corresponding to two or more of the receptacle wells, including one or more through-holes **614** for each receptacle well.

Heat Sink

[0081] In an exemplary embodiment, each support **240** is a heat sink or is in thermal communication with an individual heat sink **330**. As used herein, the term “heat sink” refers to a component that transfers thermal energy from a higher temperature to a lower temperature fluid medium. The fluid medium is frequently air but can also be water or in the case of heat exchangers, refrigerants and oil. A variety of suitable heat sink configurations and related materials are well known in the art. As used herein, the term “thermal communication” refers to the ability to transfer thermal energy from one body to another or from one body to a fluid medium.

[0082] As shown in FIG. 7A, in certain embodiments, each support **240** is provided in thermal communication with a single heat sink **330**. Each heat sink **330** positioned in thermal communication with one or more supports **240** of the apparatus **100**, may further include a plurality of through-holes **332** (see FIG. 7B) disposed in a surface thereof. Each through-hole **332** may be in direct alignment with the through-holes **242** of the support and/or the through-holes **170** at the bottom surface **160** of the receptacle holders **110** that are positioned in sliding engagement therewith. Such through-holes **332** form a channel through which optical fibers and/or associated components, for example, may pass thereby providing optical communication between each receptacle well **120** and an excitation signal source and/or an emission signal detector, as discussed below.

[0083] In certain embodiments, disposed within heat sink **330** may be one or more thermal devices separate from those used to heat the receptacle holders to pre-heat the heat sink prior to the amplification assay. Pre-heating of the heat sink may be desirable to reduce the temperature difference between the receptacle holder **110** undergoing heating and the heat sink, thereby avoiding sapping of the thermal energy being transferred to the receptacle holder **110** by the thermal element **200**. It has been found that pre-heating the heat sink, among other things, improves temperature cycling rates and reduces the electric and thermal strain on the thermal element, thus reducing power consumption and increasing the lifespan of the thermal element. The heat sink may be pre-heated to a temperature above ambient temperature, but at or below a nucleic acid annealing temperature, e.g., at or below about 50° C.-64° C., but above about 20° C.-22° C. In another embodiment, the heat sink may be pre-heated to a temperature between an annealing temperature and an elongation/extension temperature, e.g., between about 50° C.-64° C. and about 72° C.-80° C. In another embodiment, the heat sink may be pre-heated to a temperature between an elongation/extension temperature and a melting/denaturation temperature, e.g., between about 72° C.-80° C. to about 94° C.-98° C. In another embodiment, the heat sink may be pre-heated to a temperature between an annealing temperature and a melting/denaturation temperature, e.g.,

between about 50° C.-64° C. and about 94° C.-98° C. Exemplary thermal devices used for pre-heating the heat sink **330** include, but are not limited to, cartridge heaters **334**. In various embodiments, the one or more cartridge heaters **334** pre-heat the heat sink **330** to about 45° C.-50° C., for example, prior to the amplification assay. As should be understood, additional thermistors may be provided in thermal contact with one or more portions of the heat sink to monitor the temperature thereof to avoid sapping of the thermal energy being transferred to the receptacle holder **110** by the thermal element **200**.

Cover

[0084] As shown in FIGS. **1**, **2**, **8**, and **12**, the apparatus **100** may also include a cover **350** that is positioned in movable association with the receptacle holder **110**. As can be expected, the cover **350** is movable between an opened position (FIG. **8B**) and a closed position (FIG. **8C**) relative to the receptacle holder **110** and may be moved to any position between opened and closed, as necessary. In the opened position, the cover **350** does not obstruct access to the receptacle wells **120** within the receptacle holder **110** (see FIG. **8A**). When in the closed position, the cover **350** will block and/or obstruct access to the receptacle wells **120**. In addition, when closed, the cover **350** may exert a force **F2** onto any receptacle within a receptacle well **120** to seat or secure the receptacle **130** into the receptacle well **120** (see FIG. **8C**). As discussed above, because the receptacle well **120** is configured to receive a receptacle **130**, the force **F2** exerted by the cover **350** serves to ensure that the receptacle **130** fits snugly within the receptacle well **120**, thereby allowing maximal contact between the inner surface **180** of the receptacle well **120** and the receptacle **130**.

[0085] The cover **350** may be made from any rigid or semi-rigid material suitable for exerting downward pressure onto a receptacle disposed within a receptacle well. Exemplary materials from which the cover may be made include, but are not limited to, beryllium copper, spring steel, chrome vanadium, chrome silicon, phosphor bronze, stainless steel, aluminum, titanium, tungsten, metal alloys, metal composites, plastic, or any suitable rigid or semi-rigid material.

[0086] The cover **350** may be movable by any suitable mechanical element included in the apparatus. In one embodiment, the cover **350** is hingedly attached to the apparatus **100** so as to enable movement between the open and closed positions. Attachment points include but are not limited to any of the one or more supports of the apparatus or any suitable location within a housing containing the apparatus. As shown in FIG. **1**, the cover **350** may be fixedly attached to a rigid rotatable member **352**, which is in movable communication with one or more electric motors **355**. The rotatable member may be rotatably mounted to opposing sides of the housing **50** of the apparatus or opposing sides of additional support members thereof, and span a length of the apparatus parallel to the orientation of one or more receptacle holders such that actuation of the rotatable member **352** results in the cover **350** being moved into the opened or closed position relative to the one or more receptacle holders **110**. In an exemplary embodiment, the rotatable member **352** is a cylindrical rod having a circular cross-section and an axis of rotation at the center thereof, as shown in FIG. **8E**, which is a sectional view taken along A'-A' in FIG. **8D**. Exemplary materials from which the rigid rotatable member may be made include, but are not limited to, steel, titanium, aluminum, or any suitable rigid material. As used herein, the term "rotatably mounted" refers to any mounting orientation that allows the rotatable member to rotate about its center axis.

[0087] The cover **350** may comprise one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) flexible extensions **360** attached to and extending laterally away from, the rigid rotatable member **352**. Such flexible extensions **360** are configured to make contact with at least a portion of a receptacle **130** disposed within the receptacle holder **110** when the cover is in, approaching, or for a short distance after leaving, the closed position. As contact is made between the flexible extensions **360** and at least a portion of the receptacle **130**, the flexible extensions **360** flex while applying force **F2** directly to at least a portion of the receptacle **130**. In an exemplary embodiment, the cover **350** includes two or more (i.e., 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) flexible extensions **360** extending in the same direction away from the rigid rotatable member **352**. In certain embodiments, the flexible

extensions **360** extend laterally away from the hinged attachment of the cover **350** to the apparatus **100**. In frequent embodiments, the cover **350** includes one flexible extension **360** per receptacle well **120** of a receptacle holder **110**. Also, in frequent embodiments, one flexible extension **360** of the cover **350** may contact at least a portion of more than one receptacle **130** disposed within the receptacle holder **110**. Likewise, more than one flexible extension **360** may contact at least a portion of more than one receptacle **130** disposed within the receptacle holder **110**.

[0088] The cover **350** of the present disclosure often comprises multiple components, such as flexible extensions **360**, a rotatable member **352**, or other elements, as a single molded cover unit, or in multiple elements comprising the entire cover unit. For example, the flexible extensions **360** may be attached to the rotatable member **352**, or a single material may comprise the rotatable member **352** and the flexible extensions **360**.

[0089] The apparatus **100** may include a single cover **350** in moveable association with all receptacle holders **110** (not shown), or it may include a single cover **350** for each row of receptacle holders **110**, or it may include a single cover **350** for each individual respective receptacle holder **110**. Movement of each cover **350** may be actuated by an electric motor **355** disposed either within the apparatus **100** or within the housing **50** in which the apparatus is located. When the apparatus **100** includes more than one cover **350**, each cover **350** may be actuated by its own motor **355**, or more than one cover **350** may be actuated by the same motor **355**. As such, when the apparatus **100** includes more than one cover **350**, each cover **350** may move independently of the next and/or more than one cover **350** may be moved simultaneously. One of skill in the art would appreciate that independent movement of multiple covers utilizing a single motor may be provided through, for example, appropriate camming of its connection to each cover. The electric motor **355** is electrically connected to a controllable power source **210** for applying a current thereto. Control of the power source **210** can be carried out by an appropriately programmed controller **370** (such as a computer) which may receive signals from another processor **750** that controls the automated process steps involved with temperature cycling processes.

[0090] Though several embodiments of the apparatuses and methods of the present disclosure include a cover, a cover is not required, and often not included or desired. For example, in particularly frequent embodiments, the receptacle holder does not have a cover in operable orientation therewith. In such embodiments, receptacles are often held in place in the receptacle holder, for example, by gravity, friction, and/or another mode. When the apparatus is provided without a cover for the receptacles, it will frequently comprise any of the configurations of the apparatus described herein, but lacking the cover, including all associated instrumentation and mechanical and/or electrical elements associated therewith. Frequently, in such embodiments, a pipettor or receptacle transport mechanism will have uninhibited access to the receptacle holder to introduce or remove receptacles at will. An example of an apparatus without a cover is depicted in FIG. **14B**. Such an apparatus could be readily attached to a heat sink, in communication with a detection system, and a power source and be fully operational. In frequent embodiments multiple of these apparatuses are incorporated on a single heat sink.

Optical Fibers

[0091] With reference now to FIGS. **9A-9C**, the apparatus **100** further includes a plurality of (i.e., more than one) optical fibers **400** to provide optical communication of a receptacle well with at least one of an excitation signal source **500** and an emission signal detector **510** (see FIG. **10**). In one embodiment, the apparatus **100** includes one optical fiber **400** per receptacle well **120**. Thus, when the apparatus **100** includes ten receptacles wells **120**, at least ten optical fibers **400** will be provided to establish optical communication between the receptacle well **120** and one or more excitation signal sources **500** and/or one or more emission signal detectors **510**.

[0092] As used herein, an “optical fiber” refers to a flexible, transparent fiber made of glass or plastic that functions as a waveguide to transmit light between the two ends (i.e., the first end and the second end) of the fiber. Typically, optical fibers include a transparent core surrounded by an

opaque cladding material with a lower index of refraction and low to no autofluorescence characteristics. It should be understood that an optical pathway or assembly comprising the optical fiber may optionally include one or more filters, lenses, aspheres, etc., to modify and/or focus and excitation or emission signals passing therethrough. Optionally, the apparatus **100** may include an optical interface **440** between the first end **410** of each optical fiber **400** and the receptacle **130** (see FIG. **9C**). Such optical interface **440** may include a filter, lens, asphere, nose, cap, or any other element having desired optical properties. However, it should be understood that in various embodiments, the interface **440** is not, and/or does not function as a lens. Exemplary interfaces **440** useful in the apparatus include, but are not limited to, glass or plastic balls, noses or caps covering the first end **410** of the optical fiber **400**, or any suitable optically clear material.

[0093] The first end **410** of each of the plurality of optical fibers **400** is disposed outside, within, or extending through a through-hole **170** of the receptacle well **120**, thereby providing optical communication with a receptacle well **120**, and/or a receptacle **130** disposed within the receptacle well **120**. When disposed within the receptacle well **120**, as shown in FIG. **9A**, the first end **410** of the optical fiber **400** may be moveable within the through-hole **170** of the receptacle well **120** relative to the inner surface **180** thereof. A variety of means of movement of the first end **410** of the optical fiber **400** within the through-hole **170** are contemplated. For example, the first end **410** of the optical fiber **400** may extend into the receptacle well **120**, and when a receptacle **130** is placed within the well **120**, the receptacle **130** contacts the first end **410** of the optical fiber **400**, thereby providing optical communication between the receptacle **130** and the optical fiber **400**. In an exemplary embodiment, the presence of a receptacle **130** within the receptacle well **120** will cause the optical fiber **400** to move within the through-hole **170** (e.g., through the application of a direct force) in a direction opposite from the inner surface **180** of the receptacle well **120** such that the receptacle **130** can make maximal contact with the inner surface **180** of the receptacle well **120** while maintaining optical communication with the optical fiber **400**, as shown in FIG. **9B**. In another embodiment, the downward force **F2** exerted by the cover **350** and/or the flexible extensions **360** of the cover **350** onto at least a portion of a receptacle **130** disposed within a receptacle well **120** causes the optical fiber **400** to move within the through-hole **170** when the receptacle **130** contacts the optical fiber **400**. In such embodiments, the receptacle **130** may apply a force **F3** to the first end **410** of optical fiber **400** in substantially the same direction as the force **F2** being applied to the receptacle, which is disposed within the well such that the end **410** of the optical fiber **400** moves within the well **120**.

[0094] As is known in the art, optical fibers are rigid members, thereby having a certain amount of inherent resilience to movement. Thus, one of skill in the art would understand that optical fibers useful in the apparatus **100** should have sufficient rigidity to resist bending or otherwise deforming within the receptacle holder **120** upon application of force **F3** onto the first end **410** thereof. Alternatively, a flexible optical fiber **400** may be utilized, but the first end **410** of the optical fiber **410** may be surrounded or protected by a rigid ferrule **450**, for example, that optionally moves within the through-hole in response to the application or release of force **F3**.

[0095] Often, the first end **410** of each of the plurality of optical fibers **400**, or an area **420** proximal to the first end **410** of each of the plurality of optical fibers **400**, is connected, directly or indirectly, to a respective through-hole **170** of a receptacle well **120** with a resilient element **600**. The resilient element **600** thereby compresses and/or deforms as the optical fiber **400** moves within the through-hole **170** and returns to its uncompressed and/or original form when the optical fiber **400** returns to its rest position to thereby moderate movement of optical fiber **400**. As used herein, the “rest position” of an optical fiber refers to the position of the first end **410** thereof when no receptacle is present within the receptacle well and/or when no downward force **F2** is exerted by the cover **350** onto at least a portion of a receptacle **130** disposed within the receptacle well **120**. Exemplary resilient elements include, but are not limited to springs, plastics, opened- or closed-cell foams, rubbers, dampers, pneumatic elements, hydraulic elements, electromagnetic elements, or

combinations thereof.

[0096] One of skill in the art would understand that the inherent resilience/rigidity of the optical fiber **400** should be taken into consideration when selecting a resilient element **600** for use in the apparatus **100** to avoid having the optical fiber's inherent rigidity interfere with the ability of its movement within the through-hole **170**. Thus, in frequent embodiments, each optical fiber **400** in the apparatus **100** has one or more dedicated resilient element(s) **600**. Also, in frequent embodiments, two or more optical fibers **400** are in contact with a single resilient element **600** that permits individual or coordinated movement of the two or more optical fibers **400**.

[0097] In yet another exemplary embodiment, the movement of the optical fiber **400** within the through-hole **170** of the receptacle well **120** is associated with the movement of the cover **350** of the apparatus **100**. For example, in such embodiments the optical fiber **400** may be disposed outside, within, or extending through a through-hole **170** of the receptacle well **120** (as shown in FIG. 9A). Here the optical fiber **400** may, for example, be in moveable connection with the motor **355** that actuates the cover **350** such that the same motor **355** actuates movement of the optical fiber **400** within the through-hole **170**. Alternatively, the optical fiber **400** may, for example, be in moveable connection with a motor (not shown) that is different than the motor **355** that actuates the cover **350**, but the action of the motors on the cover **350** and optical fiber **400** may be coordinated such that the optical fiber **400** moves within the through-hole **170** in a time period that corresponds to the movement of the cover **350**. This corresponding time period may comprise an overlapping time period or distinct, but associated, time periods. For example, the fiber **400** may move at the same time as the cover **350**, the fiber **400** may move during only a portion of the time the cover **350** is moving, or the fiber **400** may move during a time that is before or after movement of the cover **350**. In frequent, non-overlapping time period embodiments, before the cover **350** begins to move toward the closed position, the first end **410** of the optical fiber **400** may move within the through-hole **170** toward the inner surface **180** of the receptacle well **120**. Alternatively, in other frequent, non-overlapping time period embodiments, before the first end **410** of the optical fiber **400** begins to move toward the inner surface **180** of the receptacle well **120**, the cover **350** moves toward the closed position. Often, however, the movement of the optical fiber **400** and the cover **350** is coordinated such that the first end **410** of the optical fiber **400** moves toward the inner surface **180** of the receptacle well **120** after the cover **350** has begun to move and is approaching a closed position. In such embodiments, the first end **410** of the optical fiber **400** can be actuated to move towards the interior of the receptacle well **120** at the beginning of the movement of the cover **350** away from the closed position, or at another time period.

[0098] In another exemplary embodiment, the rest position of the first end **410** of the optical fiber **400** is below the inner surface **180** of the receptacle well **120**. In other words, the first end **410** of the optical fiber **400** is at rest within the through-hole **170** of the receptacle holder **110**. In such an embodiment, the first end **410** of the optical fiber **400** is therefore moved towards the interior of the receptacle well prior to, during, or after the cover **350** is moved to a closed position in order to bring the first end **410** into contact with at least a portion of the receptacle **130** disposed within a receptacle well **120**, or otherwise positioned close to, but not in direct contact with, a portion of the receptacle **130** in order to establish optical communication therewith. As discussed above, the optical fiber **400** may, for example, be in moveable connection with the motor **355** that actuates the cover **350** such that the same motor **355** actuates movement of the optical fiber **400** within the through-hole **170**. Alternatively, the optical fiber **400** may, for example, be in moveable connection with a motor (not shown) that is different than the motor **355** that actuates the cover **350**, but the action of the motors on the cover **350** and optical fiber **400** may be coordinated such that the optical fiber **400** moves within the through-hole **170** in a time period that corresponds to the movement of the cover **350**.

[0099] In yet another exemplary embodiment, movement of the optical fiber **400** within through-hole **170** (either into or out of the interior of receptacle well **120**) may be actuated through a

mechanical connection to the rigid rotatable member **352** of the cover **350**. For example, a geared or cammed mechanical connection (not shown) with the rigid rotatable member **352** may be used to coordinate movement of the first end **410** of the optical fiber **400** into and away from the interior of the receptacle well **120** as the cover **350** is moved into the opened or closed position. As such, the optical fiber **400** of the apparatus **100** may move into and out of the receptacle well **120** in conjunction with the opening and closing of the cover **350** of the apparatus **100**.

[0100] In certain embodiments, placement of a receptacle **130** within the receptacle well **120** generally will not cause the optical fiber **400** to move within the through-hole **170**. However, as discussed above, the force **F2** exerted by the cover **350** onto at least a portion of the receptacle **130** will prevent movement of the receptacle **130** within the receptacle well **120**, and allow for optical communication between the receptacle **130** and the optical fiber **400**, while maintaining maximal contact between the receptacle **130** and the inner surface **180** of the receptacle well **120**. In embodiments wherein the rest position of the optical fiber **400** results in the first end **410** thereof being disposed below the inner surface **180** of the receptacle well **120**, force **F2** maintains receptacle **130** in the seated position within receptacle well **120** even after the actuated movement of the optical fiber **400** into the interior of the receptacle well **120**. As should be understood, actuation of optical fiber **400** into contact with receptacle **130** often exerts a force **F4** (FIG. 9C) onto the closed bottom end **138** of the receptacle **130**. In the absence of force **F2** exerted by the cover **350** onto at least a portion of the receptacle **130**, force **F4** may dislodge or otherwise impair optimal contact of the receptacle **130** with the inner surface **180** of the receptacle well **120**. Therefore, in such embodiments, force **F4** generally has the same magnitude, or has a magnitude smaller than, force **F2** or force **F3**.

Methods of Establishing Optical Communication

[0101] In another aspect, disclosed herein is provided a method for establishing optical communication between a receptacle and an excitation signal source and/or an emission signal detector within a housing of the apparatus while allowing maximal contact between the surface of the receptacle well and the receptacle (FIG. 11A). As discussed in detail above, the method includes providing a receptacle **130** to a receptacle well **120** of a receptacle holder **110** (step **S110**). Thereafter, a force **F2** is applied to the receptacle **130** or at least a portion of the receptacle **130**, such that the receptacle **130** fits snugly within the receptacle well **120**, thereby allowing maximal contact between the inner surface **180** of the receptacle well **120** and the receptacle **130** (step **S120**). While force **F2** is being applied to at least a portion of the receptacle **130**, movement of a first end **410** of an optical fiber **400** is effected toward the inner surface **180** of the receptacle well **120** (step **S130**). In such embodiments, the receptacle **130** may apply a force **F3** to the optical fiber **400** in substantially the same direction as the force **F2** being applied to the receptacle **130**, to the first end **410** of the optical fiber **400**, which is disposed within the receptacle well **120** such that optical communication is established between the bottom **138** of the receptacle **130** and the first end **410** of the optical fiber **400** (step **S140**). As discussed above, movement of the first end **410** of the optical fiber **400** is coordinated with movement of cover **350** into the closed position. As such, the method may further include movement of the cover **350** in coordination with the movement of the first end **410** of the optical fiber **400**.

[0102] Another exemplary embodiment of the method for establishing optical communication between a receptacle and an excitation signal source and/or an emission signal detector within a housing of the apparatus while allowing maximal contact between the surface of the receptacle well and the receptacle is shown in FIG. 11B. In this embodiment, the method includes providing a receptacle **130** to a receptacle well **120** of a receptacle holder **110** (step **S210**). Thereafter, a cover **350** is moved into the closed position (step **S220**), thereby exerting a force **F2** onto the receptacle **130** or at least a portion of the receptacle **130**, such that the receptacle **130** fits snugly within the receptacle well **120**, thereby allowing maximal contact between the inner surface **180** of the receptacle well **120** and the receptacle **130** (step **S230**). Prior to, during, or after movement of the

cover **350** into the closed position, movement of a first end **410** of an optical fiber **400** is effected toward and into contact with the seated receptacle **130** (step **S240**). Upon contact of the first end **410** of the optical fiber **400** with the closed end **138** of the receptacle **130**, force **F4** is exerted by the first end **410** onto the receptacle **130**. In such embodiments, the receptacle **130** may apply a force **F3**, which is greater than force **F4**, onto the first end **410** of the optical fiber **400** in substantially the same direction as the force **F2**. As such, optical communication is established between the first end **410** of the optical fiber and the receptacle **130**, while ensuring maximal contact between the receptacle **130** and the inner wall **180** of the receptacle well **120** (step **S250**). As discussed above, movement of the first end **410** of the optical fiber **400** is coordinated with movement of cover **350** into the closed position.

[0103] Often, the first end **410** of each of the plurality of optical fibers **400**, or an area **420** proximal to the first end **410** of each of the plurality of optical fibers **400**, is connected, directly or indirectly, to a respective through-hole **170** of a receptacle well **120** with a resilient element **600**, as discussed above. The resilient element **600** thereby compresses and/or deforms as the optical fiber **400** moves within the through-hole **170** and returns to its uncompressed and/or original form when the optical fiber **400** returns to its rest position.

Stripper Plate

[0104] With reference now to FIGS. **12A-12D**, the apparatus **100** may further include one or more stripper plates **650** mounted in moveable association with the receptacle holder **110**. Like the cover **350**, the stripper plate **350** is movable between an opened and closed position, which in reference to the stripper plate **650**, will be referred to as the “unlocked position” and the “locked position.” When in the unlocked position (FIG. **12B**), the stripper plate **650** permits transfer to and removal of a receptacle **130** into or out of a receptacle well **120**. When in the locked position (FIG. **12C**), the stripper plate **650** inhibits removal of a receptacle **130** disposed within a receptacle well **120**, thereby permitting a receptacle transport mechanism **700**, such as a pipettor or pick-and-place robot, to withdraw from receptacle **130** (FIG. **12D**). It should be understood that when in the locked position, the stripper plate **650** does not inhibit access to the top of the receptacle **130** by a receptacle transport mechanism **700** used to deliver to and/or remove receptacles **130** but will prevent removal of the receptacle **130**. Thus, removal of the receptacle **130** may only occur, if the stripper plate **650** is present, when the stripper plate **650** is in the unlocked position.

[0105] When present, the stripper plate **650** may be made from any rigid material suitable for removing a receptacle **130** from a receptacle transport mechanism **700**. Exemplary materials from which the stripper plate may be made include, but are not limited to, beryllium copper, spring steel, aluminum, titanium, plastic, or any suitable rigid material.

[0106] In various embodiments, the apparatus **100** may include a single stripper plate **650** in moveable association with all receptacle holders **110**, or it may include a single stripper plate **650** for each row of receptacle holders **110**, or it may include a single stripper plate **650** for each individual receptacle holder **110**. Movement of the stripper plate **650** may be actuated by an electric motor **660** disposed either within the apparatus **100** or within the housing **50** in which the apparatus is located. When more than one stripper plate **650** is provided in the apparatus, each stripper plate **650** may be actuated by its own motor **660**, or more than one stripper plate **650** may be actuated by the same motor **660**. As such, when the apparatus **100** includes more than one stripper plate **650**, each stripper plate **650** may move independently of the next and/or more than one stripper plate **650** may be moved simultaneously. The electric motors **660** effecting movement of the one or more stripper plates **650** are electrically connected to a controllable power source **210** for applying a current thereto. Control of the power source **210** can be carried out by an appropriately programmed processor **670** (such as a computer) which may receive signals from another processor that controls the automated process steps involved with thermal cycling processes.

[0107] As with movement of the optical fibers **400** discussed above, movement of the stripper plate **650** between the locked and unlocked positions may be associated with the movement of the cover

350 of the apparatus **100**. For example, in such embodiments the stripper plate **650** may be disposed in moveable connection with the motor **355** that actuates the cover **350** such that the same motor **355** actuates movement of the stripper plate **650** as necessary. Thus, the action of the motors on the cover **350** and stripper plate **650** may be coordinated such that the stripper plate **650** moves in a time period that corresponds to the movement of the cover **350**. This corresponding time period may comprise an overlapping time period or distinct, but associated, time periods. For example, the stripper plate **650** may move at the same time as the cover **350**, the stripper plate **650** may move during only a portion of the time the cover **350** is moving, or the stripper plate **650** may move during a time that is before or after movement of the cover **350**. However, movement of the stripper plate must be timed such that the receptacle transport mechanism **700** may withdraw from receptacle **130** without interfering with the movement of the cover **350**.

[0108] In other exemplary embodiments, the stripper plate **650** may be movable between the locked and unlocked positions by any suitable mechanical element included in the apparatus. In an exemplary embodiment, the stripper plate **650** is hingedly attached to the apparatus **100** so as to enable movement between the locked and unlocked positions. Attachment points include, but are not limited to, any of the one or more supports of the apparatus or any suitable location within a housing **50** containing the apparatus **100**. In another embodiment, the stripper plate **650** is slidingly attached to opposing sides of a support of the apparatus **100**. For example, the stripper plate **650** may laterally slide in a direction perpendicular to the orientation of the rows (**101-106**) of receptacle holders **110**. While a stripper plate may be utilized in certain embodiments described herein, it is often not incorporated as a feature when the receptacle transport mechanism **700** is provided with a receptacle release such as a tip stripper, ejection mechanism, or other receptacle release mechanism known in the art.

Second Exemplary Embodiment of the Apparatus

[0109] With reference now to FIGS. **14A-14D** and **16**, there is provided a second exemplary embodiment of the apparatus **800** described herein. The description will be provided based on the differences from the first exemplary embodiment discussed above. As such any reference to like elements should be understood as described above.

[0110] As in the previous exemplary embodiment, the apparatus **800** includes one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, or any whole number between 1 and 20, or more) receptacle holders **110** (see also FIG. **3**). When multiple receptacle holders **110** are provided in an apparatus described herein, each receptacle holder **110** disposed within the apparatus may be disposed in alignment with one another to facilitate the automated processing steps involved in nucleic acid amplification assays. Such an apparatus **800** may include a housing **50** (see FIGS. **2** and **4**) within which the one or more receptacle holders **110** are located. The housing **50** may be made from any suitable structural material such as, for example, plastic or metal.

[0111] As shown in FIG. **14A**, the upright portion **247** of the support **240** includes a mount **810** projecting from a third side thereof, for attachment to a controller board **820** shown in FIG. **14B**. Attachment of the controller board **820** to the mount **810** of the support **240** may be accomplished by any means known in the art. For example, the controller board **820** may be fixedly attached by rivets or screws **825**. Often, the attachment is by way of a mechanism that permits independent lateral movement between the support **240** and the controller board **820**. Such an attachment may be by way of the use of shoulder screws or machining of the attachment points in the support **240** such that the controller board can move laterally over them regardless of the type of securing means that is utilized, including standard-threaded screws. Such lateral movement of the controller board **820** facilitates the mounting of the support **240**/controller board **820** unit to the heat sink **330**, and allows for proper alignment of through-holes **242** of the support **240** with through-holes **332** of the heat sink **330**, thereby providing optimal positioning of optical fibers **400** for examination of the contents of a receptacle well **120**.

[0112] The controller board **820** may include logic and control circuitry for performing one or more

of the motorization and temperature control functions described above. In various embodiments, the controller board **820** includes at least one electronic connection point **830** for electrical connection to a second controller board **835** (see FIG. **16**) disposed on the apparatus **800**. In frequent embodiments, the entire unit (or apparatus), including the circuitry on the controller board **820**, depicted in FIG. **14B** represents an independently calibrated unit that can be utilized when plugged into a power source and oriented in communication with a detection system, such as an optical system or another detection system. In such embodiments, the controller board **820** has been configured to operate with the installed elements identified in FIGS. **14A-14D**, with or without the primary or secondary cover **840/850**, or any other cover means. In essence, the unit exemplified in FIG. **14B** may be operated and utilized as a “plug-and-play” type of apparatus, whereby it can be installed, removed, or replaced with a different unit, at will, without the need for independent calibration of the overall detection system after installation. As discussed above, disposed between the receptacle holder **110** and the upright portion **247** of the support **240** is a thermal element **200**, such as a “Peltier device.” A compressive housing **855** having a top surface **857** is configured for securable attachment over the receptacle holder **110**. Disposed in the top surface **857** of the compressive housing **855** are a plurality of through-holes, each corresponding to and in alignment with a receptacle well **120** of the receptacle holder **110**. One or more cross-braces **248** are mounted to the support **240** and exert a force **F1** (FIG. **5B**) onto a side surface of the compressive housing **855**, which in turn exerts the force **F1** onto the receptacle holder **110**. The support **240** and compressive housing **855** may each be formed from a material having low thermal conductivity such as plastic. In certain embodiments, the material from which the support **240** and compressive housing **855** are formed may be the same material or may be different materials. [0113] FIG. **14D** depicts a top view of a portion of the apparatus **800** provided in FIGS. **14A-14C**. In various embodiments, the compressive housing **855** has a side wall **864** with sloped ends **859** that are oriented toward the receptacle holder **110**. The sloped ends **859** enhance the uniformity of the compressive force of the compressive housing **855** on the receptacle holder **110**, while simplifying the compressive connection, installation case, and serviceability of the unit. In this embodiment, screws **827** may be threaded through the upright portion **247** and into the cross-brace **248**. When the screws **827** are tightened, the cross-brace **248** exerts a force on the outer surface of the side wall **864** (i.e., the surface facing away from the receptacle holder **110**), and the outer ends **249** of the cross-brace **248** are pulled toward the upright portion **247**, resulting in a bowed curvature (not shown) of the cross-brace **248** around the compressive housing **855**. The sloping ends **859** permit cross-brace **248** bowing while enhancing the overall uniformity of the applied compressive force **F1**. The compressive housing **855** illustrated in FIG. **14D** further includes a plurality of ribs, including end ribs **861** and intermediate ribs **862**, extending from the inner surface of side wall **864** (i.e., the surface facing the receptacle holder **110**) and contacting the front surface **117** of the receptacle holder **110** adjacent the receptacle wells **120**. The end ribs **861** in the illustrated embodiment contact the receptacle holder **110** at locations outside the endmost receptacle wells **120**, and the intermediate ribs contact the receptacle holder **110** between adjacent pairs of receptacle wells **120**. One of skill in the art would appreciate that additional orientations and configurations of the cross-brace **248**/compressive housing **855** connection could be provided without departing from the scope of the present disclosure.

[0114] With reference now to FIG. **16**, each support **240** may be a heat sink, may be in thermal communication with an individual heat sink **330**, or may be in thermal communication with a single heat sink **330**. Each heat sink **330** positioned in thermal communication with one or more supports **240** of the apparatus **800**, may further include a plurality of through-holes **332** (see FIG. **7B**) disposed in a surface thereof. Each through-hole **332** may be in direct alignment with the through-holes **242** of the support and/or the through-holes **170** at the bottom surface **160** of the receptacle holders **110** that are positioned in engagement therewith. Such through-holes **332** form a channel through which optical fibers and/or associated components, for example, may pass thereby

providing optical communication between each receptacle well **120** and an excitation signal source and/or an emission signal detector, as discussed above.

[0115] As shown in FIG. **14C**, the apparatus **800** may also include a primary cover **840** that is fixedly positioned over the receptacle holder **110**. The primary cover **840** may be formed with one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) securing arms **845** in direct alignment with and circumscribing each receptacle well **120** of the receptacle holder **110**. In certain embodiments, the primary cover **840** is formed with four securing arms **845** in direct alignment with and disposed in a surrounding arrangement with each receptacle well **120** of the receptacle holder **110**. The securing arms **845** are configured for securable attachment to at least a portion of the receptacle or cap **135** that is attached to a receptacle **130**. Such securable attachment is analogous to the force **F2** exerted by the cover **350**, as discussed above, for ensuring that the receptacle **130** fits snugly within the receptacle well **120**, thereby allowing maximal contact between the inner surface **180** of the receptacle well **120** and the receptacle **130**. The securing arms can be made of any suitable material, including plastic, metal, or a metal composite.

[0116] The apparatus **800** may further include a secondary cover **850** fixedly positioned over the primary cover **840**. The secondary cover **850** may be formed with one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) releasing arms **856**, each in direct alignment and in sliding contact with the securing arms **845** of the primary cover. In various embodiments, the securing arms **845** of the primary cover include an angled surface **847** upon which the corresponding releasing arm **856** of the secondary cover **850** may slide when actuated during an automated process. The secondary cover **850** may further include one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) actuators **860** that are fixedly connected to the releasing arms **856**, and are positioned such that when a force is applied thereon, the force is transferred from the actuator **860** to the releasing arms **856**, which in turn, press onto the angled surface **847** of the primary cover **840** and release the securable attachment to the cap **135** that is attached to a receptacle **130**.

[0117] It is therefore contemplated that the housing **50** within which the apparatus **800** is located will include at least one modified pipettor **900**, as shown in FIGS. **15A** and **15B**. As shown in FIG. **15A**, the modified pipettor **900** is modified such that a plunger **910** is slidably coupled to one or more limbs **915**, which are hingedly attached to a body **920** of the modified pipettor **900**. Thus, when the modified pipettor **900** causes the plunger **910** to be in a first position (as shown in FIG. **15A**), the one or more limbs **915** are in a retracted position such that a lower portion **917** thereof are positioned in close proximity to the body **920**. When the modified pipettor **900** causes the plunger **910** to be in a lowered second position (as shown in FIG. **15B**), the one or more limbs **915** are then moved into an extended position such that the lower portions **917** thereof are moved away from the body **920**.

[0118] This modified pipettor **900** is useful for engaging the secondary cover **850** and pressing on the secondary cover **850** in a downward movement that actuates the release of the securing arms **845** by the physical action of the releasing arms **856**. When the releasing arms **856** are depressed in this manner, the securing arms **845** are pulled axially away from the receptacle **130** and cap **135**, permitting its unencumbered release and lifting out by the pipettor. In such circumstances it is advantageous that the releasing arms **856** maintain contact with, and depress in a radially outward manner, the securing arms **845** for the time period required for the pipettor plunger **910** to frictionally engage the receptacle cap and to lift the receptacle and cap vertically clear of the securing arms **845**.

[0119] FIG. **16** depicts an alternate embodiment of a cover mechanism **824** that is actuated by an automated pipettor or a modified pipettor **900**, as described above. In this embodiment the end or plunger **910** of a pipettor **900** contacts and depresses a cover release mechanism **852**, which opens the cover **822**, permitting access of the receptacle **130** to the well **120**. Once the receptacle **130** is placed in the well **120**, the pipettor end or plunger is utilized to depress a cover securing mechanism **854**, which causes a force to be exerted on the cap **135** and/or receptacle **130** which

then is securely seated in the well **120**. The force is analogous to the force **F2** exerted by the cover **350**, as discussed above, for ensuring that the receptacle **130** fits snugly within the receptacle well **120**, thereby allowing maximal contact between the inner surface **180** of the receptacle well **120** and the receptacle **130**. The cover **822** may be motor-actuated, as discussed above, may be actuated through one or more torsion springs disposed on the rigid rotatable member **352** (FIG. **8B**) to which the cover **822** is fixedly attached, or may be actuated by a spring mechanism that causes the cover **822** to move vertically with respect to the receptacle holder **110**. In various embodiments, the spring-loaded cover **822** may include a push-lock fastener, which may lock the spring-loaded cover **822** into the locked position. The push-lock mechanism may be directly or indirectly associated with the cover release mechanism **852** and/or the cover securing mechanism **854**.

[0120] In certain embodiments, any of the apparatuses described herein will not include a cover or a mechanism to exert force **F2** onto the capped receptacle **130**. In such embodiments, the receptacle **130** fits snugly within the receptacle well **120**, thereby allowing maximal contact between the inner surface **180** of the receptacle well **120** and the receptacle **130** without the need for a force **F2**.

[0121] In certain embodiments, any of the apparatuses described herein may include a cover but will not include a mechanism to exert force **F2** onto the capped receptacle **130**. In such embodiments, the cover does not contact the capped receptacle, as the receptacle **130** fits snugly within the receptacle well **120**, thereby allowing maximal contact between the inner surface **180** of the receptacle well **120** and the receptacle **130** without the need for a force **F2**.

Use of the Apparatus in a Biochemical Assay

[0122] Use of the apparatus described herein is envisioned as, but is not limited to, being part of an automated process for performing a biochemical assay, such as nucleic acid amplification. Thus, in another aspect, there is provided a method of conducting automated, random-access temperature cycling processes (see FIG. **13**). A reaction mixture is prepared by first providing oil to a first receptacle **130** or first set of receptacles (step **S310**), reconstituting a PCR master mix (step **S320**) and providing the reconstituted PCR master mix to the receptacle **130** (step **S330**). The sample to be assayed is thereafter inserted into the receptacle **130** containing the PCR master mix (step **S340**), thereby forming a reaction mixture **140**, and the receptacle **130** is capped (step **S350**). The first receptacle **130** or first set of receptacles, each containing a reaction mixture **140** is transferred by a receptacle transport mechanism **700** to a first receptacle holder **110** of the apparatus **100** (step **S360**). The steps of preparing a reaction mixture may optionally be repeated to fill a particular receptacle holder **110** and/or a particular row (step **S370**).

[0123] If a cover **350** and/or stripper plate **650** associated with the particular receptacle holder **110** is present and in the closed and/or locked position, the cover and/or stripper plate is moved to the opened and/or unlocked position to receive the first receptacle **130** or first set of receptacles. Alternatively, if the apparatus includes an alternative embodiment of the cover **824**, the receptacle transport mechanism **700**, a didi (i.e., end of a pipettor), or a modified pipettor **900**, may depress a cover releasing mechanism **852**, thereby causing the cover **822** to be moved to the opened position. Yet in another alternative embodiment, if no cover is present, then any step involving movement of the cover is unnecessary and therefore may be omitted. Once the cover **350** and/or stripper plate **650** associated with the receptacle holder **110** is in the opened and/or unlocked position, the receptacle transport mechanism **700** places the first receptacle **130** or first set of receptacles into one or more receptacle wells **120** of the first receptacle holder **110** (step **S360**). Prior to withdrawal of the receptacle transport mechanism **700**, if present, the stripper plate **650** is moved into the locked position to prevent removal of the transferred first receptacle **130**, or set thereof, from the first receptacle holder **110** (not shown). In alternative embodiments the receptacle transport mechanism **700** is provided with a mechanism to remove receptacles without utilizing a stripper plate (see, e.g., U.S. Pub. No. 2010/0179687; U.S. Pub. No. 2005/0244303; U.S. Pat. Nos. 6,869,571; 6,824,024; and 6,431,015), thus rendering the use of a stripper plate **650** or equivalent mechanism on the apparatus optional. The transferred receptacle **130** or set thereof may then be

released from the receptacle transport mechanism **700** upon contact with the stripper plate **650** as the receptacle transport mechanism **700** withdraws therefrom. After the area surrounding the first receptacle holder is clear of the receptacle transport mechanism, the cover **350** is moved into the closed position (step **S380**). If the alternative embodiment of the cover mechanism **824** is present in the apparatus, the receptacle transport mechanism **700**, the didi, or the modified pipettor **900** depresses a cover securing mechanism **854**, thereby causing the cover **822** to be moved to the closed position. As discussed above, once in the closed position, the cover may exert a force **F2** onto at least a portion of the receptacle **130** or a set of receptacles. However, in certain embodiments, the cover does not exert force **F2** onto the receptacle **130**.

[0124] As used herein, a “set” of receptacles refers to one or more receptacle(s) **130** held within a receptacle holder **110**. For example, a “set” of receptacles **130** refers to the number of receptacles **130** required to at least partially, or to completely, fill a particular receptacle holder **110**. Thus, a set of receptacles **130** may refer to a single receptacle **130** being processed by the apparatus **100**, or it may refer to any whole number of receptacles **130** up to and including the maximum number of receptacle wells **120** within a particular receptacle holder **110**.

[0125] The first receptacle holder **110** is then subjected to a first incubation process (step **S390**), which includes applying a voltage to a first thermal element **200** of the apparatus **100** to alter the temperature of the first receptacle holder **110**. By altering the temperature or temperatures of the first receptacle holder **110**, the first set of receptacles **130** within the first receptacle holder **110**, including the reaction mixture(s) **140** contained in each receptacle **130**, is brought to a predetermined temperature and optionally sustained at the temperature for a predetermined time.

[0126] During the first incubation process, a second set of receptacles **130**, each containing a reaction mixture **140**, is optionally transferred by the receptacle transport mechanism **700** to a second receptacle holder **110** of the apparatus **100** (step **S400**). As with the first set of receptacles, if a cover **350** and/or stripper plate **650** associated with the second receptacle holder **110** is present and in the closed and/or locked position, the cover and/or stripper plate is moved to the opened position and/or unlocked position to receive the second set of receptacles. Once the cover **350** and/or stripper plate **650** associated with the second receptacle holder **110** is in the open position and/or unlocked position, the receptacle transport mechanism **700** places the second set of receptacles into the receptacle wells **120** of the second receptacle holder **110**. If a stripper plate **650** is utilized, prior to withdrawal of the receptacle transport mechanism **700**, the stripper plate **650** is moved into the locked position to prevent removal of the transferred second set of receptacles from the second receptacle holder **110**. The transferred second set of receptacles **130** may then be released from the receptacle transport mechanism **700** upon contact with the stripper plate **650** as the receptacle transport mechanism **700** withdraws therefrom. When the area surrounding the second receptacle holder **110** is clear of the receptacle transport mechanism **700**, the cover **350** associated therewith is moved into the closed position. As discussed above, once in the closed position, the cover **350** exerts a force **F2** onto at least a portion of the respective set of receptacles.

[0127] The second receptacle holder **110** is then subject to a second incubation process, which may be the same as or different—in terms of temperature and duration thereof—than the first incubation process. It should be understood that the first and second incubation processes may occur simultaneously or subsequent to one another. It should be further understood that a third or higher (i.e., third, fourth, fifth, sixth, seventh, eighth, ninth, tenth, eleventh, twelfth, or higher) set of receptacles **130** may be transferred to the apparatus **100**, which may thereafter, subject the third or higher set of receptacles **130** to a third or higher (i.e., third, fourth, fifth, sixth, seventh, eighth, ninth, tenth, eleventh, twelfth, or higher) incubation process. Such additional sets of receptacles **130** may be transferred and/or subject to the additional incubation processes either simultaneously or sequentially, as necessary. The transfer of each subsequent set of receptacles **130** may be begun prior to completion of the incubation process for each immediately preceding set of receptacles **130**.

[0128] In one exemplary embodiment, the first set of receptacles **130** is removed (step S410 of FIG. **13**) from the first receptacle holder **110** immediately following placement of the last of the second, or subsequent, set of receptacles **130** within the second receptacle holder **110**. In a related exemplary embodiment, the second set of receptacles **130** is removed from the second receptacle holder **110** immediately following placement of the last of the third, or subsequent, set of receptacles **130** within the second receptacle holder **110**, and so forth. It will be appreciated by those of skill in the art that the terms “first,” “second,” “third,” and higher terms are relative terms, and are therefore not limited to the positioning or orientation of the receptacle holders **110** within the apparatus **100**. Similarly, it will be appreciated by those of skill in the art that the terms “first,” “second,” “third,” and higher terms are not limited to the timing of the incubation process relative to the timing that the apparatus **100** is set up. These terms are merely intended to be relative to the timing of placement and incubation of any particular set of receptacles **130** within each respective receptacle holder **110**. For example, the 50.sup.th set of receptacles may be considered to be the first set of receptacles relative to the 51.sup.st set of receptacles.

[0129] Use of the second exemplary embodiment of the apparatus **800** described herein, like the first exemplary apparatus, is also envisioned as, but is not limited to, being part of an automated process for performing a biochemical assay, such as nucleic acid amplification. As above, if no cover, primary cover, or secondary cover is present, then any step involving movement of the covers is unnecessary and therefore may be omitted. As above, a reaction mixture is prepared by first providing oil to a first receptacle **130** or first set of receptacles (step S310), reconstituting a PCR master mix (step S320) and providing the reconstituted PCR master mix to the receptacle **130** (step S330). The sample to be assayed is thereafter inserted into the receptacle **130** containing the PCR master mix (step S340), thereby forming a reaction mixture **140**, and the receptacle **130** is capped (step S350). The first receptacle **130** or first set of receptacles, each containing a reaction mixture **140** is transferred by a receptacle transport mechanism **700** to a first receptacle holder **110** of the apparatus **100** (step S360). The steps of preparing a reaction mixture may optionally be repeated to fill a particular receptacle holder **110** and/or a particular row (step S370). Transferring of the first receptacle **130** or first set of receptacles is accomplished by first performing an automated motion of moving the plunger **910** of a modified pipettor **900** into the raised position (as shown in FIG. **15A**), thereby causing the knob **912** to slidingly contact the one or more limbs **915** and move the limbs **915** into a retracted position such that a lower portions **917** thereof are placed in close proximity to the body **920** of the pipettor **900**. The pipettor **900**, having a capped first receptacle **130** or first set of receptacles frictionally attached thereto, places the first receptacle **130** or first set of receptacles into one or more receptacle wells **120** of the first receptacle holder **110** (step S360). As the first receptacle **130** or first set of receptacles is lowered into the receptacle well **120**, the first receptacle **130** or first set of receptacles contacts at least a portion of the securing arms **845** of the primary cover **840**. The downward force applied by receptacle to the securing arms **845** cause the securing arms **845** to flex in a radial outward direction in relation to the axial center of the receptacle well **120** such that the lower portion of the cap clears the securing arms **845**. Once the lower portion of the cap **135** clears the securing arms **845**, the securing arms return to their rest position, thereby securably contacting at least a portion of the cap **135**, ensuring that the capped receptacle fits snugly within the receptacle well **120**, thereby allowing maximal contact between the inner surface **180** of the receptacle well **120** and the receptacle **130**.

[0130] The first receptacle holder **110** is then subjected to a first incubation process (step S390), which includes applying a voltage to a first thermal element **200** of the apparatus **100** to alter the temperature of the first receptacle holder **110**. By altering the temperature or temperatures of the first receptacle holder **110**, the first set of receptacles **130** within the first receptacle holder **110**, including the reaction mixture(s) **140** contained in each receptacle **130**, is brought to a predetermined temperature and optionally sustained at the temperature for a predetermined time or fluctuated between a series of temperatures.

[0131] As above, during the first incubation process, a second set of receptacles **130**, each containing a reaction mixture **140**, is optionally transferred by the receptacle transport mechanism **700** to a second receptacle holder **110** of the apparatus **100** (step **S400**).

[0132] Upon completion of the incubation process, removal of the first receptacle **130** or set of receptacles from the second exemplary embodiment of the apparatus **800** is accomplished by performing an automated motion of moving the plunger **910** of a modified pipettor **900** into the lowered position (as shown in FIG. **15B**), thereby causing the knob **912** to slidably contact the one or more limbs **915** and move the limbs **915** into an extended position such that a lower portions **917** thereof are moved away from the body **920**. Thereafter, the modified pipettor **900** is lowered into the open end of the cap **135** of the first receptacle **130** or set of receptacles. As shown in FIG. **15C**, upon lowering of the modified pipettor **900**, the extended lower portions **917** of the limbs **915** contact the actuators **860** of the secondary cover **850** and apply a downward force thereto. The downward force causes the releasing arms **856** to slidably contact the securing arms **845** of the primary cover **840**, causing the securing arms **845** to flex in a radial outward direction relative to the axial center of the receptacle well **120**, as the modified pipettor **900** frictionally engages the open end of the cap **135**. The flexing of the securing arms **845** releases the capped receptacle **130/135** or set of receptacles, allowing the capped receptacle to be removed from the receptacle well **120** as the modified pipettor **900** is raised therefrom.

[0133] In certain embodiments, it is desirable to preheat the heat sink **330** of the apparatus **100** prior to or during the incubation process. In those embodiments, prior to, during, or after the first receptacle **130** or first set of receptacles, each containing a reaction mixture **140** is transferred by a receptacle transport mechanism **700** to a first receptacle holder **110** of the apparatus **100**, a voltage is applied to a thermal element **334** that is in thermal communication with the heat sink **330**. As discussed above, the heat sink may be warmed to about 45-50° C., for example, prior to the biochemical assay. The transferred receptacle **130** or set thereof may then be released from the receptacle transport mechanism **700** upon contact with the stripper plate **650** as the receptacle transport mechanism **700** withdraws therefrom. After the area surrounding the first receptacle holder is clear of the receptacle transport mechanism, the cover **350** is moved into the closed position. As discussed above, once in the closed position, the cover exerts a force **F2** onto at least a portion of the receptacle **130** or a set of receptacles. Thereafter, the first receptacle holder **110** is then subjected to a first incubation process, which includes applying a voltage to a first thermal element **200** of the apparatus **100** to alter the temperature of the first receptacle holder **110**. By altering the temperature or temperatures of the first receptacle holder **110**, the first set of receptacles **130** within the first receptacle holder **110**, including the reaction mixture(s) **140** contained in each receptacle **130**, is brought to a predetermined temperature and optionally sustained at the temperature for a predetermined time.

[0134] In various embodiments, the temperature of the receptacle holder **110** will be above ambient temperature as a result of a prior incubation process performed on a previous receptacle **130** or set thereof, or due to pre-heating of the heat sink **330**. In these embodiments, pre-heating or additional heating of the heat sink **330** may or may not be desired due to a lessened risk of heat sap, as discussed above.

[0135] Each of the first and second sets of receptacles **130** (and/or any additional sets of receptacles) may be transferred to the apparatus **100** by a single receptacle transport mechanism **700** or may be transferred by more than one receptacle transport mechanism **700**, depending on the configuration of the apparatus **100**, system, or biochemical instrument.

[0136] Each set of receptacles **130** may undergo a single incubation process or a plurality of incubation processes prior to completion of the biochemical assay. Alternatively, or in conjunction, each set of receptacles **130** may undergo a single temperature ramp for purposes of, for example, a melt curve analysis. If a set of receptacles **130** undergoes multiple temperature cycles, each subsequent temperature cycle may be the same as or different from the temperature cycle

immediately preceding it. During the single or plurality of incubation processes, during the temperature ramp, or upon completion of a predetermined number of incubation processes, an excitation signal source **500** transmits an excitation signal via optical fibers **400** of the apparatus **100** to the set of receptacles **130**. Any emission signals resulting therefrom are thereafter transmitted via the optical fibers **400** to one or more emission signal detectors **510**. Though FIG. **10** depicts separate optical fibers branching out to the excitation signal source **500** and emission signal detector **510**, various embodiments of the present disclosure utilize a single optical fiber (i.e., a light pipe) between the excitation signal source **500** and its corresponding emission signal detector **510**. One of skill in the art will appreciate that a collection of mirrors, dichroics, and/or filters can be utilized to split the excitation and emission signals travelling through the single optical fiber between the excitation signal source **500** and its corresponding emission signal detector **510**. In these embodiments, one end of the single optical fiber terminates in or at a single receptacle well, and the other end of the single optical fiber terminates at location in optical communication with the excitation signal source **500** and its corresponding emission signal detector **510**. Often, in such a configuration, every receptacle well in the apparatus will be outfitted with a similar optical fiber arrangement.

[0137] Following completion of all incubation processes and/or detection steps, the respective set of receptacles **130** is removed from the respective receptacle holder **110** of the apparatus **100**. Removal of a set of receptacles **130** often proceeds as follows. The cover **350**, if present, that is associated with the receptacle holder **110** in which the assayed receptacles **130** are seated is moved to the opened position. Either simultaneously or shortly thereafter, the stripper plate **650**, if present and in the locked position, is moved to the unlocked position. The receptacle transport mechanism **700** is moved into position and lowered toward the receptacle holder **110** to contact the tops of each of the receptacles **130** seated therein. In frequent embodiments, the receptacle transport mechanism **700** contacts a single receptacle **130** at any particular time. In certain embodiments the receptacle transport mechanism **700** is capable of contacting and removing a set of receptacles **130**. Upon withdrawal of the receptacle transport mechanism **700**, any receptacles contacted therewith are removed from the receptacle holder **110**. It should be understood that assayed receptacles **130** or sets thereof, may be removed prior to, during, or after completion of the temperature cycling process of any previous or subsequent sets of receptacles.

[0138] Thus, a first set of receptacles may be removed from the first receptacle holder **110** prior to completion of the second incubation process of the second set of receptacles **130** within the second receptacle holder **110**. Likewise, a second set of receptacles **130** may be removed from the second receptacle holder **110** prior to completion of a third or higher incubation process of a third or higher set of receptacles **130** within the third or higher receptacle holder **110**.

[0139] Because the present apparatus **100, 800** is capable of simultaneously conducting a variety of different assays, it is also envisioned that due to the requirements of a particular assay, sample, reagents, or any other reason, a second set of receptacles **130** may be subjected to a shorter incubation process than a first set of receptacles **130** such that the second or subsequent set of receptacles may be removed prior to removal of the first set of receptacles.

[0140] Accordingly, the apparatus **100, 800** described herein provides the ability to automate incubation processes, simultaneously involving the same or different biochemical assays. In an exemplary embodiment, the apparatus includes six rows (**101-106**) of receptacle holders **110** with two receptacle holders **110** per row and five receptacle wells **120** per receptacle holder **110**. As such, the apparatus of the exemplary embodiment is capable of simultaneously incubating up to sixty receptacles **130** at any given time. Assuming an incubation time of sixty minutes for each set of receptacles **130** within each receptacle holder, and population of each receptacle holder **110** (containing five receptacle wells **120**) with a set of receptacles **130** every five minutes, the first set of receptacles will complete the incubation, about sixty five minutes after the first receptacle **130** is placed in a receptacle well **120**. Thereafter, every five minutes another set of five receptacles will

complete its incubation period. When each set of receptacles has completed its incubation, the set is removed from the receptacle holder and replaced with a fresh set of receptacles for another incubation period. Thus, when an apparatus **100, 800** is used in conjunction with an automated instrument for performing a biochemical assay, such as PCR, the apparatus increases instrument throughput productivity within a typical 8-hour shift.

System for Automated Random-Access Incubation

[0141] In another aspect, the present disclosure provides a system for automated random-access incubation for nucleic acid amplification assays. The system includes one or more of the apparatus **100, 800** and allows for simultaneous or individualized assays to be performed. The system includes a housing **50** into which the one or more apparatuses **100, 800** are located. As discussed above, the thermal element **200** corresponding to each receptacle holder **110** may be independently controllable to only alter the temperature of its corresponding receptacle holder **110**. Thus, the system may include more than one controller **220**, each of which is electrically connected to a single thermal element **200** and one or more thermistors **610** of an individual receptacle holder **110**, and/or connected to a controllable power source **212** connected to a motor **355** effecting movement to a cover **350**, if present, and/or a motor **660** effecting movement of a stripper plate **650**, if present, of the individual receptacle holder **110**. It should be understood that any one or more controllers (**220, 370, 670**) may be combined to effect independent control of more than one thermal element **200** and/or controllable power source **212** connected to an electric motor (**355, 660**). Thus, the system may include a single controller electrically connected to each of the thermal elements **200** and to one or more motors **355** disposed in moveable communication with the cover **350** and/or stripper plate **650** corresponding to each receptacle holder **110**. Likewise, the system may include an appropriately programmed processor **750** (such as a computer) which is electrically connected to each controller (**220, 370, 670**) to send and/or receive signals/commands for performing an incubation process. In certain embodiments, the controller (**220, 370, 670**) and the processor **750** will be configured in the same unit, thereby reducing the number of components within the system. [0142] As discussed above, the system will include at least one heat sink **330**. Thus, each of the one or more apparatuses **100, 800** within the system may be disposed in independent thermal communication with a single heat sink **330** (i.e., one heat sink per apparatus), or every apparatus **100, 800** may be in thermal communication with a single heat sink **330**. In certain embodiments, each receptacle holder **110** of each apparatus **100, 800** of the system will be disposed in independent thermal communication with a dedicated heat sink **330** (i.e., one heat sink per receptacle holder), as discussed above.

[0143] As shown in FIG. **10**, the system may further include one or more excitation signal sources **500** and one or more emission signal detectors **510** to which the second ends **430** of the optical fibers **400** of the apparatus **100, 800** included therein are in optical communication. Excitation signal sources **500** and emission signal detectors **510** contemplated by the present disclosure include, but are not limited to, fluorometers, luminometers, spectrophotometers, infrared detectors and charged-coupled devices. Each of these types of optical detection systems can be positioned within the housing of the apparatus **100, 800**, within the housing of the system, or within the overall housing of the biochemical analysis instrument, as appropriate. Multiple types of signal sources **500** and signal detectors **510** may be movably mounted on a platform to facilitate different detection methods for different processes. The system may also include multiple detectors of the same or different types for detecting signals emitted from different receptacles **130** simultaneously. As discussed above, though FIG. **10** depicts separate optical fibers branching out to the excitation signal source **500** and emission signal detector **510**, certain embodiments of the present disclosure utilize a single optical fiber (e.g., a light pipe) between the excitation signal source **500** and its corresponding emission signal detector **510**.

[0144] The system may further include a receptacle transport mechanism **700** (e.g., a pick-and-place mechanism, a pipettor, or a modified pipettor) that is positioned within the housing of the

system or within the overall housing of the instrument. The receptacle transport mechanism **700** is configured to transfer and/or remove one or more receptacles **130**, either individually or as a set, from a receptacle holder **110** of the apparatus **100**. In various embodiments, the modified pipettor **900** includes a body having a plunger slidably disposed therein, and one or more limbs hingedly attached to the body and positioned in sliding communication with a knob fixedly attached to the plunger. When the plunger is in a first position, a lower portion of the one or more limbs are proximal to the body, and when the plunger is in a second position, the lower portion of the one or more limbs are extended in a radial outward direction relative to the body. In certain embodiments, the receptacle transport mechanism **700** is configured to additionally dispense into and/or remove liquids from individual receptacles **130**.

[0145] Although the present disclosure has been described with reference to the above example, it will be understood that modifications and variations are encompassed within the spirit and scope of the disclosed subject matter. Accordingly, the present disclosure is limited only by the following claims.

Claims

1. (canceled)
2. An apparatus for incubating a plurality of receptacles, the apparatus comprising: one or more thermally-conductive receptacle holders, each of the receptacle holders having opposed front and back sides, wherein each of the receptacle holders comprises a plurality of receptacle wells, each of the receptacle wells being configured to receive a receptacle; a support associated with each of the receptacle holders, wherein each of the receptacle holders is held in a fixed position with respect to the associated support; a thermal element associated with each of the receptacle holders and its associated support, wherein each thermal element is positioned between a portion of the associated support and the back side of the associated receptacle holder; at least one body associated with each receptacle holder and in contact with the front side of the associated receptacle holder; and a linker disposed between each body and a second support separate from the associated support with respect to which the receptacle holder is fixed and configured to provide a compressive force to the body and the front side of the associated receptacle holder in a direction toward the thermal element positioned between the associated support and the back side of the associated receptacle holder.
3. The apparatus of claim 2, wherein the support is thermally conductive.
4. The apparatus of claim 2, wherein the receptacle holder is in sliding engagement with respect to the support.
5. The apparatus of claim 2, wherein each body has lower thermally conductivity than the associated receptacle holder.
6. The apparatus of claim 5, wherein each body comprises a glass or plastic bead, cap, or insert.
7. The apparatus of claim 2, wherein each linker comprises at least one of a spring, a spacer, a linear expander, an elastic body, a piezoelectric device, a lever, and a screw.
8. The apparatus of claim 2, wherein the thermal element comprises a thermoelectric module.
9. The apparatus of claim 2, wherein each associated support comprises: a base portion; and an upright portion extending from the base portion, wherein the thermal element is positioned between the upright portion of the associated support and the back side of the associated receptacle holder.
10. The apparatus of claim 2, wherein the at least one body comprises one body associated with each receptacle well of each receptacle holder.
11. The apparatus of claim 2, wherein the at least one body comprises two bodies associated each receptacle holder.
12. The apparatus of claim 2, wherein the at least one body comprises five bodies associated with each receptacle holder.

13. The apparatus of claim 3, further comprising a heat sink in thermal communication with each support.

14. The apparatus of claim 9, further comprising a heat sink, wherein the support is thermally conductive, and wherein the base portion of each associated support is attached to the heat sink.

15. The apparatus of claim 2, further comprising one or more thermal sensors in thermal communication with the receptacle holder and configured to monitor a temperature of the receptacle holder.

16. The apparatus of claim 2, further comprising a plurality of optical fibers, wherein a first end of each optical fiber is in optical communication with one of the receptacle wells and a second end of each optical fiber is in optical communication with at least one of an excitation signal source and an emission signal detector.

17. The apparatus of claim 16, wherein each receptacle holder includes a through hole extending from an inner surface of each receptacle well to an outer surface of the receptacle holder, and wherein the first end of each optical fiber is disposed outside, is disposed within, or extends through the through-hole of one of the receptacle wells.

18. The apparatus of claim 17, wherein each associated support comprises: a base portion; and an upright portion extending from the base portion, wherein the thermal element is positioned between the upright portion of the associated support and the back side of the associated receptacle holder, and wherein the associated support includes a plurality of through-holes formed through the base portion, each of the through-holes of the associated support being aligned with a corresponding one of the through-holes extending from the inner surface of each of the receptacle wells to the outer surface of the receptacle holder.

19. The apparatus of claim 18, wherein each of the through-holes of each associated support forms a channel supporting a fixed or moveable ferrule and through which a corresponding one of the optical fibers passes.

20. The apparatus of claim 19, further comprising a spring biased against each ferrule, wherein each ferrule is movably supported in the channel so that the spring urges the first end of the corresponding optical fiber into the associated receptacle well.
