

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250265580

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Perullo; Jerry

---

### MULTI-SIGNATURE VERIFICATION NETWORK

---

#### Abstract

Systems and methods for authorizing a blockchain transaction. A verification network receives a transaction request for the blockchain transaction from a payer device including a first signature generated by a first private key associated with a payer. The verification network broadcasts a verification request to verification system(s) which assess pre-agreed threshold parameters. If the parameter(s) are satisfied, at least one verification system perfects the transaction by generating a second signature using a second private key, and broadcasts the transaction to the blockchain network. If the parameter(s) are not satisfied, verification offer(s) from among the verification system(s) including the second signature(s) are used to prompt the payer device to confirm the blockchain transaction by selecting at least one of the offer(s). The verification network receives selected offer(s) from the payer device and broadcasts the transaction to the blockchain network, in accordance with the selected offer(s) and the transaction request.

---

**Inventors:** Perullo; Jerry (Atlanta, GA)

**Applicant:** Intercontinental Exchange Holdings, Inc. (Atlanta, GA)

**Family ID:** 1000008575138

**Assignee:** Intercontinental Exchange Holdings, Inc. (Atlanta, GA)

**Appl. No.:** 19/199644

**Filed:** May 06, 2025

#### Related U.S. Application Data

parent US continuation 18829661 20240910 parent-grant-document US 12327242 child US 19199644

parent US continuation 18435321 20240207 parent-grant-document US 12125026 child US 18829661

parent US continuation 18110011 20230215 parent-grant-document US 11928673 child US 18435321

parent US continuation 17752251 20220524 parent-grant-document US 11615408 child US 18110011  
parent US continuation 17400236 20210812 parent-grant-document US 11386423 child US 17752251  
parent US continuation 17226142 20210409 parent-grant-document US 11120435 child US 17400236  
parent US continuation 17003044 20200826 parent-grant-document US 11004068 child US 17226142  
parent US continuation 16808127 20200303 parent-grant-document US 10922685 child US 17003044  
parent US continuation 16561295 20190905 parent-grant-document US 10621579 child US 16808127  
us-provisional-application US 62727824 20180906

---

## Publication Classification

**Int. Cl.:** **G06Q20/38** (20120101); **G06F3/0482** (20130101); **G06Q20/40** (20120101); **H04L9/00** (20220101); **H04L9/06** (20060101); **H04L9/32** (20060101)

## U.S. Cl.:

**CPC** **G06Q20/3825** (20130101); **G06Q20/4016** (20130101); **H04L9/0637** (20130101); **H04L9/3247** (20130101); **G06F3/0482** (20130101); **H04L9/50** (20220501)

---

## Background/Summary

### FIELD OF THE DISCLOSURE

[0001] The present disclosure generally relates to systems and methods for authorizing blockchain-based transactions of digital assets, and more specifically, to a multi-signature authorization system including a multi-signature verification network that leverages a pool of trusted verification institutions to generate at least one signature and at least one verification offer together with a payer signature, in order to authorize blockchain-based transactions.

### BACKGROUND

[0002] The use of blockchain technology for transactions involving digital assets such as cryptocurrencies has become increasingly popular due to the decentralized nature of transactions, the use of a mathematically verifiable ledger, near-immediate settlement, and isolation from operational, technical, or geo-political concentration risks. Although blockchain technology presents these advantages, managing cryptographic keys is burdensome and dangerous, exposing users to the dual threats of electronic theft and accidental loss of assets. Further, with near-immediate settlement comes a lack of “claw-back” reversibility of transactions, increasing the impact of fraud. Accordingly, there is a need to provide the security, safety, and reversibility of traditional centralized payment systems without reinstating concentration risks posed by relying on any single service provider.

### SUMMARY

[0003] Aspects of the present disclosure relate to systems, methods and non-transitory computer readable media for authorizing a blockchain transaction. In some examples, system may include a verification network in communication with at least a payer computing device associated with a payer, a verification pool that includes one or more independent third-party verification computing

systems (e.g., verification providers or verification institutions), and a blockchain network. In some examples, the verification network includes a computing system having a processor and a memory having programming instructions stored thereon, where the programming instructions, when executed by the processor, cause the system to perform an operation for authorizing the blockchain transaction. The operation of the verification network includes receiving, from the payer computing device, a partially-signed blockchain transaction (e.g., a transaction request). The transaction may include a first signature, where the first signature may be generated by a first private key created and managed by the payer (e.g., a first private key associated with the payer). In one example, the first signature may be the only signature included in the (partially-signed) transaction. In some examples, the partially-signed transaction may be enriched by the verification network with situational details such as (without being limited to) time, value, geolocation, merchant statistics and/or any suitable information that may be useful to a verification provider in analyzing the likelihood of attempted fraud. Since, in an exemplary embodiment, the payer private key must be protected by the payer, the nature of the present disclosure significantly mitigates the impact of unauthorized access to this payer private key, thereby significantly increasing the attractiveness of existing backup solutions.

[0004] The operation of the verification network further includes broadcasting the partially-signed transaction and details relating to one or more pre-agreed threshold parameters (e.g., risk assessment details) to the one or more verification providers. The operation may further include assessing, by at least one verification provider from among the verification pool, the one or more pre-agreed threshold parameters associated with the partially-signed transaction. The assessing may be a part of a broader risk analysis procedure and the threshold parameters may comprise one or more pre-agreed risk parameters. If the pre-agreed threshold parameters are satisfied, the (at least one) verification provider may immediately perfect (e.g., “bless”) the transaction request and broadcast the now-perfected blockchain transaction to the blockchain network. Perfecting the transaction request may include generating a second signature using a second private key (e.g., created and maintained by the verification provider) and optionally imposing a pre-agreed surcharge.

[0005] In the absence of pre-agreed threshold parameters, or if the pre-agreed threshold parameters are not satisfied during the assessment, the operation may further include generating, by at least one of the one or more verification providers, one or more verification offers including a respective one or more second signatures and, optionally, in some examples, one or more risk-related surcharges. Each of the one or more second signatures may be generated by a respective one of the one or more verification providers using a second private key (e.g., created and maintained by the verification provider). In some embodiments, the one or more verification providers may transmit one or more denials, rather than verification offers.

[0006] In an example operation of the present disclosure, the first verification provider to assess the risk and perfect the transaction may prevail and capture a previously-agreed fee. In the event that the risk analysis performed by the verification provider determines that a risk surcharge is needed to offset risk, the operation may include transmitting the one or more verification offers to the payer client device and prompting the payer computing device to confirm the blockchain transaction by selecting at least one of the one or more verification offers and receiving, from the payer client device, a selection of at least one offer of the one or more verification offers (thereby providing a perfected blockchain transaction). The operation may conclude with broadcasting the perfected blockchain transaction to the blockchain network.

[0007] In some examples, systems and methods of the present disclosure may leverage the breakthroughs in real-time risk assessment that have been created via high-frequency trading to allow verification providers to compete for individual transaction fees, while isolating the payer from reliance on any single provider.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1A is a block diagram illustrating a computing environment for authorizing blockchain transactions, according to an exemplary embodiment.

[0009] FIG. 1B is a block diagram visually depicting one or more parties to a blockchain transaction, according to an exemplary embodiment.

[0010] FIG. 2 is a block diagram illustrating a computing environment for authorizing blockchain transactions including a verification network, according to an exemplary embodiment.

[0011] FIG. 3 is a flow diagram illustrating a method of authorizing a blockchain transaction using a verification network, according to one or more exemplary embodiments.

[0012] FIG. 4 is a flow diagram illustrating communication among one or more computing components for authorizing a blockchain transaction using a verification network, according to one or more exemplary embodiments.

[0013] FIG. 5A is a block diagram illustrating one or more screenshots of a client computing device, according to one or more exemplary embodiments.

[0014] FIG. 5B is a block diagram illustrating one or more screenshots of a client computing device, according to one or more exemplary embodiments.

[0015] FIG. 6 is a block diagram illustrating a computing environment, according to one or more exemplary embodiments.

### DETAILED DESCRIPTION

[0016] Aspects of the present disclosure relate to systems, methods and non-transitory computer readable media for authorizing a blockchain transaction. In some examples, system may include a verification network in communication with at least a payer computing device associated with a payer, a verification pool that includes one or more independent third-party verification computing systems (e.g., verification providers or verification institutions), and a blockchain network. In some examples, the verification network includes a computing system having a processor and a memory having programming instructions stored thereon, where the programming instructions, when executed by the processor, cause the system to perform an operation for authorizing the blockchain transaction. The operation includes receiving, from the payer computing device, a partially-signed blockchain transaction (e.g., a transaction request). The transaction may include a first signature, where the first signature may be generated by a first private key created and managed by the payer (e.g., a first private key associated with the payer). In one example, the first signature may be the only signature included in the (partially-signed) transaction. In some examples, the partially-signed transaction may be enriched by the verification network with situational details such as (without being limited to) time, value, geolocation, merchant statistics and/or any suitable information that may be useful to a verification provider in analyzing the likelihood of attempted fraud. Since, in an exemplary embodiment of the present disclosure, the payer private key must be protected by the payer, the nature of the present disclosure significantly mitigates the impact of unauthorized access to this payer private key, thereby significantly increasing the attractiveness of existing backup solutions.

[0017] The operation of the verification network further includes broadcasting the partially-signed transaction and details relating to one or more pre-agreed threshold parameters (e.g., risk assessment details) to the one or more verification providers. The operation may further include assessing, by at least one verification provider from among the verification pool, the one or more pre-agreed threshold parameters associated with the partially-signed transaction. The assessing may be a part of a broader risk analysis procedure and the threshold parameters may comprise one or more pre-agreed risk parameters. If the pre-agreed threshold parameters are satisfied, the (at least one) verification provider may immediately perfect (e.g., “bless”) the transaction request and

broadcast the now-perfected blockchain transaction to the blockchain network. Perfecting the transaction request may include generating a second signature using a second private key (e.g., created and maintained by the verification provider) and optionally imposing a pre-agreed surcharge.

[0018] In the absence of pre-agreed threshold parameters, or if the pre-agreed threshold parameters are not satisfied during the assessment, the operation may further include generating, by at least one of the one or more verification providers, one or more verification offers including a respective one or more second signatures and, optionally, in some examples, one or more risk-related surcharges. Each of the one or more second signatures may be generated by a respective one of the one or more verification providers using a second private key (e.g., created and maintained by the verification provider). In some embodiments, the one or more verification providers may transmit one or more denials, rather than verification offers.

[0019] In an example operation of the present disclosure, the first verification provider to assess the risk and perfect the transaction may prevail and capture a previously-agreed fee. In the event that the risk analysis performed by the verification provider determines that a risk surcharge is needed to offset risk, the operation may include transmitting the one or more verification offers to the payer client device and prompting the payer computing device to confirm the blockchain transaction by selecting at least one of the one or more verification offers and receiving, from the payer client device, a selection of at least one offer of the one or more verification offers (thereby providing a perfected blockchain transaction). The operation may conclude with broadcasting the perfected blockchain transaction to the blockchain network.

[0020] In some examples, systems and methods of the present disclosure may leverage the breakthroughs in real-time risk assessment that have been created via high-frequency trading to allow verification providers to compete for individual transaction fees, while isolating the payer from reliance on any single provider.

[0021] In conventional blockchain transaction systems, two parties may directly transact with one another. For example, a payee may share a public address (e.g., public key) to which a payer is to transmit an amount of cryptocurrency. The payer may then initiate a transaction that has one or more inputs and one or more outputs. The one or more inputs may correspond to a public key of the payer (e.g., an address from which the cryptocurrency originates) and a signature that was generated using a private key of the payer. The one or more outputs may correspond to the public address of the payee. The transaction may be transmitted to a blockchain network for verification (e.g., to verify that the payer actually has the amount of digital assets, e.g., cryptocurrency, that the payer alleges to have, and that the payer has not transmitted these digital assets).

[0022] Such conventional systems, however, suffer from one or more limitations. For example, should a user's private key become compromised (e.g., stolen), the fraudulent party that obtained the user's private key has necessarily stolen all cryptocurrency associated therewith. Further, should a user lose their private key, all cryptocurrency associated therewith is effectively lost.

[0023] One or more systems currently exist to combat the limitations of a single signature transaction. For example, one or more systems may provide a multi-signature service. A multi-signature transaction requires that two or more signatures be generated for each transaction. With conventional multi-signature systems, each system functions to provide the additional signature that may be necessary to perfect a transaction. In other words, in a conventional multi-signature service, a signature from the payer and a signature from the multi-signature service is needed for any given transaction.

[0024] The one or more techniques disclosed herein provide a verification network that improves upon conventional multi-signature services. For example, the verification network described herein acts as a middleman between parties to a transaction and one or more trusted verification institutions. Upon receiving a transaction request from a payer, the verification network may broadcast a verification request to a pool of pre-defined verification institutions. Each verification

institution may be a trusted entity that can “bless” or verify the transaction. At least one signature is needed from the pool of verification institutions to perfect (i.e., “bless”) the respective transaction. Accordingly, the system of the present disclosure eliminates dependency on a single entity, as currently required by conventional multi-signature services, and instead relies on a pool, or network, of verification institutions that may verify the transaction. Moreover, the system of the present disclosure also eliminates control over a payer's digital assets that may result from two or more parties colluding to release or take control of the digital assets.

[0025] The term “user” as used herein includes, for example, a person or entity that owns a computing device (which may include a wireless device); a person or entity that operates or utilizes a computing device; or a person or entity that is otherwise associated with a computing device (which may include a wireless device). It is contemplated that the term “user” is not intended to be limiting and may include various examples beyond those described.

[0026] Moreover, examples of the present disclosure described below refer to blockchain-based transactions involving digital assets such as, for example (but not limited to), cryptocurrency. In general, systems and methods of the present disclosure may be configured to authorize transactions involving any suitable digital asset that may be tokenized, including security tokens, tokenized real estate, and one or more cryptocurrencies (e.g., digital or virtual currency that may use cryptography for security). In general, cryptocurrency may include, without being limited to, Bitcoin, Litecoin, Ether, etc. In fact, for purposes of this disclosure, the term cryptocurrency should be understood to include any digital or virtual asset or currency.

[0027] In some examples, transactions with respect to the present disclosure are referred to as blockchain transactions. In other examples, transactions are referred to as cryptocurrency transactions. As used herein, both blockchain transactions and cryptocurrency transactions refer to transactions of cryptocurrency (or any suitable digital asset) that uses a blockchain network.

[0028] FIG. 1A is a block diagram illustrating a computing environment **100** for authorizing blockchain transactions, according to an example embodiment. Computing environment **100** may include at least client device **102**, client device **104**, verification pool **106**, verification network **105** and blockchain network **108**. Communication among client device **102**, client device **104**, verification pool **106** and blockchain network **108** may be performed via verification network **105**. Although one client device **102** and one client device **104** are shown in FIG. 1A, it is understood that environment **100** may include any number of client devices **102** and/or any number of client devices **104**.

[0029] In the examples described herein, client device **102** may be operated by a user representing a payer. For example, client device **102** may be a mobile device, a tablet, a desktop computer, or any computing system having the capabilities described herein.

[0030] In the examples described herein, client device **104** may be operated by a user representing a payee. For example, client device **104** may be a mobile device, a tablet, a desktop computer, or any computing system having the capabilities described herein.

[0031] Client device **102** and client device **104** may communicate with verification network **105**. Verification network **105** may be representative of a service that supports multi-signature functionality. In general, multi-signature functionality is a service that requires two or more signatures (e.g., two or more private keys) to authorize a cryptocurrency transaction. Verification network **105** may be configured to store one or more private keys associated with each user or subscriber. For example, verification network **105** may be configured to store one or more private keys associated with at least the payer to a transaction (e.g., client device **102**).

[0032] Unlike conventional multi-signature services, verification network **105** does not perform the verification of cryptocurrency transactions between parties to a transaction. Rather, verification network **105** may be configured to facilitate the verification thereof by broadcasting a proposed transaction to verification pool **106**.

[0033] Verification pool **106** may be representative of one or more trusted financial institutions

(e.g., verification providers) that may verify a cryptocurrency transaction. In other words, verification pool **106** may include one or more financial institutions that are required to act as a second party to a multi-signature transaction. Verification pool **106** may include one or more verification institutions **110.sub.1**, **110.sub.2**, . . . , **110.sub.n** (generally “verification institution **110**”, where n is an integer greater than or equal to 1). In some embodiments, each verification institution **110** may be pre-approved with verification network **105**. When a transaction request is received from client device **102** at verification network **105**, verification network **105** may broadcast a verification request to each verification institution **110**. Each verification institution **110** may then assess a risk associated with verifying the transaction. Based on this assessment, each verification institution **110** may generate a verification offer (described further below) to be transmitted to client device **102**. In some embodiments, one or more verification institutions **110** may prompt client device **102** to authenticate with verification institution **110**. For example, a verification institution **110** may request verification network **105** to transmit an identification request to the payer (e.g., client device **102**) to confirm the identity of the payer for risk analysis purposes. Because each verification institution **110** is competing with one or more other verification institutions **110**, each verification institution **110** may race to assess the risk associated with a transaction and generate an offer that competes with other offers. Accordingly, those skilled in the art may readily understand that verification institutions **110** may balance the trade-off between quickly generating a verification offer and accurately assessing a risk associated with the verification offer.

[0034] When each verification institution **110** generates a verification offer, verification institution **110** may access a private key associated with the payer (e.g., created and/or managed by the payer) via verification network **105**. Each verification institution **110** may then generate a second signature for the transaction, using the private key hosted by verification network **105**. The second signature for the transaction may be transmitted by verification institution **110** to verification network **105** with the verification offer. In some examples, the second signature may represent a private key created and/or maintained by verification institution **110** (a verification provider) and/or provided via verification network **105**. Accordingly, verification network **105** receives at least two signatures (e.g., a first signature from client device **102** and a second signature from each verification institution **110**) which are required for the transaction.

[0035] In some embodiments, each verification institution **110** may have a pre-established relationship with a user (or subscriber) of verification network **105**. For example, each verification institution **110** may prompt the user to submit a verification application, such that each verification institution **110** may vet the user similar to a credit card application process. Accordingly, for each user, each verification institution **110** may set one or more pre-arranged limits, parameters, or contractual duties for each transaction. For example, for a given user, verification institution **110** may set a transaction limit of Bitcoin, Litecoin, Ether, etc. to a transaction. In another example, a verification institution **110** may attempt to limit its liability to a transaction, by contractually agreeing with each user that verification institution **110** is only liable for up to 50% of the transaction amount. Accordingly, when selecting a verification offer, a user may base the decision on, for example, which verification institution **110** offers the best refund policy.

[0036] Verification network **105** may receive the one or more verification offers from the one or more verification institutions **110** (i.e., verification instate **110.sub.1**, **110.sub.2**, . . . , **110.sub.n**). Verification network **105** may transmit the one or more verification offers to client device **102** and prompt client device **102** to select an offer among the verification offer(s). Verification network **105** may receive from client device **102** an indication of a selection of a particular verification offer. Verification network **105** may then broadcast the transaction to blockchain network **108** (responsive to the selected offer) for posting. Blockchain network **108** may include one or more computing devices for processing a blockchain transaction, by generating a block that is added to a blockchain that includes a record for the transaction. The blockchain represents a decentralized, public ledger

of all transactions of a blockchain-based currency.

[0037] The role played by verification institution **110** is similar to a verifier of a transaction. For example, verification institution **110** may be responsible for verifying that the payer (e.g., client device **102**) is indeed the payer and that the payer has the alleged amount of cryptocurrency for the transaction.

[0038] In conventional blockchain systems, transactions between a payer and payee are irreversible, because once a payer relinquishes control of the amount of cryptocurrency, the payer can only be made whole if the payee agrees to refund the payer. The present system addresses this limitation by providing an intermediary verification network **105** and verification pool **106**. When one or more verification institutions **110** assess a risk associated with a particular transaction, proposes a verification offer, and receives an acceptance of that verification offer, the respective verification institution **110** has taken responsibility for the transaction. In other words, if a fraudulent third party gained access to the payer's account, verification institution **110** is responsible for making the payer whole (i.e., refunding the payer the amount transferred to the payee). In this manner, verification institution **110** (e.g., a verification provider) may “eat the charges” for any risk miscalculations, thereby reducing the impact of fraud on the payer. Moreover, because various verification institutions **110** (e.g., verification providers) of verification pool **106** may compete to perfect a transaction through one or more verification offers, environment **100** may spread out any risk miscalculations among the verification providers of verification pool **106**, thereby reducing any concentration risk that is conventionally posed by relying on a single verification service provider.

[0039] Further, because verification network **105** supports multi-signature functionality, for each transaction, two or more signatures are necessary to perfect the transaction. In conventional multi-signature systems (e.g., two-signature system), any individual party that has access to at least two of the payer's private keys may take control of the payer's cryptocurrency. Similarly, in conventional systems, any two actors may collude to release or take control of an individual's cryptocurrency by gaining access to at least two private keys of the individual. The present disclosure addresses these limitations of conventional systems by anticipating the possibility that, when the proposed transaction is broadcast to verification pool **106**, two or more verification institutions **110** may collude to release the payer's funds. To address this, the computing device associated with the payer (e.g., client device **102**) is a mandatory party to the transaction. In other words, even though one or more verification institutions **110** in verification pool **106** may collude and provide the necessary number of signatures required for a specific multi-signature transaction, verification network **105** will not perfect the transaction without receiving a signature from the payer.

[0040] Examples of client device **102**, verification network **105** and verification institution **110.sub.n** are described further below with respect to FIG. 2.

[0041] FIG. 1B is a block diagram **150** visually depicting one or more parties to a cryptocurrency transaction, according to example embodiments. As shown, block diagram **150** includes verification institution **110.sub.1**, verification institution **110.sub.2**, and verification institution **110.sub.n** as the one or more verification institutions **110**. For this transaction, at least two signatures are needed to perfect the transaction from payer to payee.

[0042] As illustrated, the verification offers **122-1** and **122-2** submitted by institution **110.sub.1** and institution **110.sub.2**, respectively, have been selected by payer (e.g., client device **102**). In conventional systems, because a minimum of two signature are required, the signature (2/2) generated by verification institution **110.sub.1** and the signature (2/2) generated by verification institution **110.sub.2** would be sufficient to perfect the transaction. Those skilled in the art may readily understand that, if verification network **105** were compromised, and two or more private keys associated with client device **102** were accessed, verification institution **110.sub.1** and verification institution **110.sub.2** could collude to release or gain access to the payer's



cryptocurrency. However, such signatures would not be sufficient to perfect the transaction in computing environment **100** because client device **102** (including signature **120** generated by client device **102**) is a mandatory party to the transaction. Accordingly, at least one of the at least two required signatures must be generated by client device **102** (or more generally, the payer). Thus, in the example shown in FIG. **1B**, signatures **124** to perfect the transaction (e.g., for payment) includes signatures (2/3) (i.e., signature **120** of client device **102** and signatures (2/2) of respective verification institutions **110.sub.1.110.sub.2**).

[0043] FIG. **2** is a block diagram illustrating computing environment **200** for authorizing blockchain transactions, according to one or more exemplary embodiments. As illustrated, computing environment **200** includes at least client device **102**, at least one verification institution **110**, and verification network **105**. Client device **102**, verification institution **110** and verification network **105** may communicate via at least one network **205**.

[0044] Network **205** may be of any suitable type, including individual connections via the Internet, such as cellular or Wi-Fi networks. In some embodiments, network **205** may connect terminals, services, and mobile devices using direct connections, such as, without being limited to, radio frequency identification (RFID), near-field communication (NFC), Bluetooth™, low-energy Bluetooth™ (BLE), Wi-Fi™, ZigBee™, ambient backscatter communication (ABC) protocols, universal serial bus (USB), wide area network (WAN), or local area network (LAN). Because the information transmitted may be personal or confidential, security concerns may dictate one or more of these types of connections be encrypted or otherwise secured. In some embodiments, however, the information being transmitted may be less personal, and therefore, the network connections may be selected for convenience over security.

[0045] Network **205** may include any type of computer networking arrangement used to exchange data. For example, network **205** may be the Internet, a private data network, a virtual private network using a public network and/or other suitable connection(s) that enables components in computing environment **200** to send and receive information therebetween.

[0046] Client device **102** may include application **252** and wallet **254**. Application **252** may be representative of a web browser that allows access to a website or a stand-alone application. Client device **102** may access application **252** to access functionality of verification network **105**. Client device **102** may communicate over network **205** to request a webpage, for example, from web client application server **206** of verification network **105**. For example, client device **102** may be configured to execute application **252** to access one or more functionalities of verification network **105**. The content that is displayed to client device **102** may be transmitted from web client application server **206** to client device **102**, and subsequently processed by application **252** for display through an interactive graphical user interface (GUI) rendered by client device **102**.

[0047] Wallet **254** may be representative of a digital storage location on client device **102**. Wallet **254** may be configured to store one or more key pairs **255** associated with a user's blockchain account (e.g., account **212**). As illustrated, each key pair **255** may include a private key **256** and a corresponding public key **258**.

[0048] Each private key **256** may be an alphanumeric string that allows a user of client device **102** to transmit (e.g., spend) one or more cryptocurrencies to another individual or entity (i.e., another cryptocurrency address). Private key **256** may be used to sign each cryptocurrency transaction. For example, a user may input private key **256** into a signature algorithm which outputs a signature that may be verified by verification network **105**. Any individual or entity that has access to private key **256** may be able to access the one or more cryptocurrencies corresponding to private key **256**.

[0049] Each public key **258** may correspond to a respective private key **256**. In some embodiments, public key **258** may be derived from its respective private key **256**. Public key **258** may be an alphanumeric string that corresponds to a public address of an individual or entity. For example, when a payer or transmitter attempts to transmit an amount of cryptocurrency to a user of client device **102**, the payer or transmitter directs the transmittal to the address defined by public key **258**.

Public key **258** may be public because, although derived from a respective private key **256**, it is near impossible to reverse engineer private key **256**.

[0050] Verification network **105** may include management system **202** and database **204**.

Management system **202** may be representative of a computing system. Management system **202** may include web client application server **206**, account handler **208**, transaction agent **209**, and verification agent **210**.

[0051] Each of account handler **208**, transaction agent **209**, and verification agent **210** may be comprised of one or more software modules. The one or more software modules may be collections of code or instructions stored on a media (e.g., memory of management system **202**) that represent a series of machine instructions (e.g., program code) that implements one or more algorithmic steps. Such machine instructions may be the actual computer code that a processor of management system **202** interprets to implement the instructions or, alternatively, may be a higher level of coding of the instructions that is interpreted to obtain the actual computer code. The one or more software modules may also include one or more hardware components. One or more aspects of the algorithm may be performed by the hardware components (e.g., circuitry) itself, rather than as a result of an instruction.

[0052] Account handler **208** may be configured to manage one or more accounts **212** associated with one or more users. For example, account handler **208** may communicate with database **204**. As illustrated, database **204** may include one or more accounts **212**. Each account **212** may include one or more key pairs **215** and one or more transactions **218**. Each key pair **215** may include a private key **214** and a corresponding public key **216**. Account handler **208** may generate one or more key pairs **215** upon a user registering with verification network **105**. In some embodiments, account handler **208** may generate one or more key pairs **255** stored on client device **102**.

[0053] Each private key **214** may be an alphanumeric string that allows one or more verification institutions **110** to verify a particular transaction request. Private key **214** may be used to sign each cryptocurrency transaction. For example, a verification institution **110** may access a private key **214** from verification network **105**, and input private key **214** into a signature algorithm which outputs a signature that may be verified by verification network **105**. Any individual or entity that has access to private key **214** may be able to access the one or more cryptocurrencies corresponding the private key **214**.

[0054] Each public key **216** may correspond to a respective private key **214**. In some embodiments, public key **216** may be derived from its respective private key **214**. Public key **216** may be an alphanumeric string that corresponds to a public address associated with an individual or entity. For example, when a verification institution **110** assesses a risk associated with a transaction request, verification institution **110** may identify a payer using public key **216**. Public key **216** may be public because, although derived from a respective private key **214**, it is near impossible to reverse engineer private key **214**.

[0055] Transaction agent **209** may be configured to manage one or more transactions **218** associated with each account **212**. For example, transaction agent **209** may act as a “middle-man” between client device **102** and one or more verification institutions **110**. In operation, for example, transaction agent **209** may transmit a transaction request to one or more verification institutions **110**. Each of the one or more verification institutions **110** may race to assess the risk associated with verifying the transaction, and provide an offer to the payer for verifying the transaction. For example, each of the one or more verification institutions **110** may transmit to verification network **105** a willingness to verify the transaction along with a fee for their verification (e.g., a verification offer). The verification offer may, in turn, be transmitted from verification network **105** to client device **102** for display. Upon receiving input from client device **102** that corresponds to a selection of a verification offer, verification network **105** may transmit the offer acceptance to the respective verification institution **110**.

[0056] After a transaction is finalized between a payer (e.g., client device **102**) and a payee (e.g.,

client device **104**), transaction agent **209** may record the transaction in database **204**. For example, transaction agent **209** may record the payer to the transaction and the payee to the transaction, along with the transaction amount, in one or more transactions **218**. Accordingly, if, for example, the transaction was later deemed fraudulent, transaction agent **209** may notify the verification institution **110** that verified the transaction, such that verification institution **110** can reimburse the payer to the transaction.

[0057] Verification agent **210** may be configured to verify one or more transactions between a payer (e.g., client device **102**) and a payee (e.g., client device **104**). Verification agent **210** may, for example, verify a first signature transmitted from client device **102** to verification network **105** that signals the initiation of the transaction. The first signature may correspond to a first signature needed for a multi-signature transaction. Verification agent **210** may further be configured to verify a second signature transmitted from a verification institution **110**, in response to generation of a verification offer from verification institution **110**. The second signature may correspond to a second signature (or additional signature) needed for a multi-signature transaction.

[0058] Upon receiving the necessary number of signatures required for the multi-signature transaction (e.g., two or more signatures), verification institution **110** may communicate with transaction agent **209** to complete the transaction. Transaction agent **209** may broadcast the completed transaction to blockchain network **108**, such that the transaction may be posted thereto.

[0059] Verification institution **110** may be representative of a computing system associated with any suitable entity such as, for example, a particular financial institution or other trusted entity. Verification institution **110** may include computing device **260**. Computing device **260** may be a mobile device, a tablet, a desktop computer, or any computing system having the capabilities described herein. Computing device **260** may include application **262** and risk analyzer **264**.

[0060] Application **262** may be representative of a web browser that allows access to a website or a stand-alone application. Computing device **260** may access application **262** to access functionality of verification network **105**. Computing device **260** may communicate over network **205** to request a webpage, for example, from web client application server **206** of verification network **105**. For example, computing system **260** may be configured to execute application **262** to access one or more functionalities of verification network **105**. The content that is displayed to computing device **260** may be transmitted from web client application server **206** to computing device **260**, and subsequently processed by application **262** and, in some examples, may be displayed through a GUI rendered by computing system **260**.

[0061] Risk analyzer **264** may be comprised of one or more software modules. The one or more software modules may be collections of code or instructions stored on a media (e.g., memory of computing device **260**) that represent a series of machine instructions (e.g., program code) that implements one or more algorithmic steps. Such machine instructions may be the actual computer code a processor of computing device **260** interprets to implement the instructions or, alternatively, may be a higher level of coding of the instructions that is interpreted to obtain the actual computer code. The one or more software modules may also include one or more hardware components. One or more aspects of the algorithm may be performed by the hardware components (e.g., circuitry) itself, rather than as a result of an instruction.

[0062] Risk analyzer **264** may be configured to assess a risk associated with verifying a cryptocurrency transaction between the payer (e.g., client device **102**) and the payee (e.g., client device **104**). In some embodiments, risk analyzer **264** may assess the risk associated with verifying the cryptocurrency transaction by taking in account one or more parameters that include, but are not limited to, a current location of client device **102** (e.g., at a location associated with the user), an amount of cryptocurrency to be transmitted, a frequency of transactions between the payer (e.g., client device **102**) and the payee (e.g., client device **104**), the identity of the payee (e.g., a merchant), the time of day of the transaction, a purchase history of the payer, and the like. In some examples, risk analysis by risk analyzer **264** may include contacting the payer (e.g., via a call or

text) to confirm the transaction. Based on the risk assessment performed by risk analyzer **264**, verification institution **110** may generate a verification offer to be transmitted to client device **102**. [0063] Because, however, verifying the transaction may subject verification institution **110** to financial risk (e.g., if the transfer from client device **102** to client device **104** was fraudulent), verification institution **110** may charge the payer a fee for their verification service. For example, when risk analyzer **264** determines that there is minimal risk associated with verifying the transaction, verification institution **110** may propose a minimal fee to client device **102** in the verification offer. In another example, when risk analyzer **264** determines that there is a higher risk associated with verifying the transaction, verification institution **110** may propose a higher fee to client device **102** in the verification offer. Further, in some embodiments, verification institution **110** may propose a surge fee to a transaction. For example, in those embodiments in which verification network **105** broadcasts a higher volume of verification requests, verification institution **110** may propose a surge fee for its services.

[0064] FIG. **3** is a flow diagram illustrating a method **300** of authorizing a blockchain transaction using verification network **105**, according to one or more exemplary embodiments. Method **300** may begin at step **302**.

[0065] At step **302**, verification network **105** may receive a transaction request from client device **102** (e.g., via a payment card, an application, a mobile phone, online, etc.). The transaction request may include at least a designation of the payer (e.g., client device **102**), the payee (e.g., client device **104**), and the amount of cryptocurrency specified in the transaction. For example, the transaction request may include a public address (e.g., public key **258**) corresponding to client device **102**, a signature generated by client device **102** using private key **256**, a public address corresponding to client device **104**, and the amount specified in the transaction. Further, in some embodiments, the transaction request may also specify a number of signatures required for the multi-signature authorization. For example, in some embodiments, the transaction request may specify that at least one verification institution **110** is necessary for verification. In another example, the transaction request may specify that at least two of the verification institutions **110** are necessary for verification. In some examples, the transaction request may represent a partially-signed blockchain transaction, that may include a first signature generated by the client device **102** using private key **256**, but may not include any second signatures needed to perfect the blockchain transaction.

[0066] At step **304**, verification network **105** may broadcast a verification request to verification pool **106**. The verification request may include one or more parameters associated with the transaction request. Such parameters may include, but are not limited to, the public address (e.g., public key **258**) corresponding to client device **102**, a public address associated with client device **104**, and the amount specified in the transaction. In some examples, verification network **105** may determine and include situational details associated with the partially-signed transaction that may be useful (to verification pool **106**) in analyzing a likelihood of attempted fraud. Non-limiting examples of situational details may include a time of the transaction, a value of the transaction, a geolocation of client device **102**, any merchant statistics, etc. In some examples, the verification request broadcast by verification network **105** may include the partially-signed transaction (from client device **102**) and any additional information and/or risk assessment details (e.g., parameters, situational details, etc.) provided by verification network **105**. Thus, in some examples, the partially-signed transaction may be enriched by the information provided by verification network **105**. In some embodiments, the one or more parameters may further include a number of additional signatures needed from verification pool **106** to complete the multi-signature transaction.

[0067] At step **306**, verification network **105** may receive one or more verification offers based on a risk analysis of the transaction request. For example, verification network **105** may receive one or more verification offers from one or more verification institutions **110** to be transmitted to client device **102**. Each verification offer may be generated by a verification institution **110** based on a

determined risk with verifying the transaction. Each verification offer may include a verification charge associated therewith.

[0068] At step **308**, verification network **105** may prompt the payer to select a verification offer from a respective verification institution **110**. Verification network **105** may transmit the one or more verification offers to client device **102** for display. Client device **102** may, in turn, push the one or more verification offers to client device **102**, prompting the payer to select from among the one or more verification offers.

[0069] At step **310**, verification network **105** may receive, from client device **102**, an indication of a selection of at least one verification offer. For example, client device **102** may receive input via a GUI displayed thereon, which corresponds to a selection of a verification offer from a particular verification institution **110**. Client device **102** may translate the input to a message that is transmitted to verification network **105**. The message may indicate the verification offer selected by the payer.

[0070] At step **312**, verification network **105** may broadcast the transaction between client device **102** and client device **104** to blockchain network **108**. For example, upon determining that the necessary number of signatures required by the transaction request is met, verification network **105** may transmit the transaction between payer and payee to blockchain network **108** for posting to the blockchain. In some examples, the transaction may also take into account any surcharge fee associated with the selected verification offer(s).

[0071] In some examples, the verification request (step **304**) may include the partially-signed transaction (e.g., the transaction request) and details relating to one or more pre-agreed threshold parameters (e.g., risk assessment details). Responsive to the broadcasted verification request (step **304**), at least one verification institution **110** (e.g., verification institution **110.sub.2**) among verification pool **106** may assess the pre-agreed threshold parameter(s) associated with the partially-signed transaction. The assessing may be a part of a broader risk analysis procedure and the threshold parameter(s) may comprise one or more pre-agreed risk parameters. If the pre-agreed threshold parameter(s) are satisfied, the (at least one) verification institution **110** (e.g., verification institution **110.sub.2**) may immediately perfect (e.g., “bless”) the transaction request and broadcast the now-perfected blockchain transaction to blockchain network **108** (e.g., bypassing steps **306-310**). Perfecting the transaction request may include generating a second signature using a second private key (e.g., created and maintained by the verification provider) and optionally imposing a pre-agreed surcharge. In some examples, verification institution **110** (e.g., verification institution **110.sub.2**) may broadcast the perfected transaction directly to blockchain network **108** and/or via verification network **105**. In some examples, a first verification institution **110** (e.g., verification institution **110.sub.2**) to assess the risk, perfect the transaction (according to the previously-agreed upon fee) and broadcast the perfected transaction (e.g., the now fully-signed transaction including the first signature from client device **102** and the second signature from verification institution **110.sub.2**) may prevail and capture the previously-agreed fee.

[0072] In the absence of pre-agreed threshold parameter(s), or if the pre-agreed threshold parameter(s) are not satisfied during the assessment, the operation may further include generating, by at least one of verification institutions **110**, a respective one or more verification offer(s) including a respective one or more second signatures and, optionally, in some examples, one or more risk-related surcharges. Each of the second signature(s) may be generated by a respective one of verification institutions **110** using a respective second private key (e.g., created and maintained by a respective verification institution **110**). The verification offer(s) may be transmitted to and received by verification network **105** (step **306**) and step **306** may proceed to steps **308-310** (as discussed above). In some embodiments, verification institution(s) **110** may transmit one or more denials, rather than verification offers. Thus, in some examples, when verification institution(s) **110** determine, from the risk analysis, that a risk surcharge is needed to offset risk, the verification offer(s) may include the requested surcharge and an indication to prompt client device **102** to select

a verification offer. Based on the indication to prompt the payer, verification network **105** may prompt client device **102** to select a verification offer and may receive a selection from client device **102** (as described above at steps **308-310**). Responsive to the selection from client device **102**, verification network **105** may then broadcast the now perfected transaction (e.g., including the first signature from client device **102** and the second signature in the selected verification offer) to blockchain network **108** (step **312**). In this manner, verification network **105** may cause the payer (via client device **102**) to confirm the blockchain transaction.

[0073] FIG. **4** is a flow diagram illustrating a method **400** of communication among one or more computing components for authorizing a blockchain transaction using verification network **105**, according to one or more exemplary embodiments. Method **400** may begin at step **402**.

[0074] At step **402**, client device **102** may transmit a transaction request to verification network **105**. The transaction request may include at least a designation of the payer (e.g., client device **102**), the payee (e.g., client device **104**), and the amount of cryptocurrency specified in the transaction. For example, the transaction request may include a public address (e.g., public key **258**) corresponding to client device **102**, a signature generated by client device **102** using private key **256**), a public address corresponding to client device **104**, and the amount specified in the transaction. Further, in some embodiments, the transaction request may also specify a number of signatures required for the multi-signature authorization. For example, in some embodiments, the transaction request may specify that at least one verification institution **110** is necessary for verification. In another example, the transaction request may specify that at least two of the verification institutions **110** is necessary for verification.

[0075] At step **404**, verification network **105** may receive the transaction request from client device **102**. In some embodiments, upon receiving the transaction request from client device **102**, verification network **105** may verify that the payer has indeed signed the transaction. For example, verification network **105** may verify that client device **102** transmitted the signature for the transaction.

[0076] At step **406**, verification network **105** may broadcast a verification request to verification pool **106**. The verification request may include one or more parameters associated with the transaction request. Such parameters may include, but are not limited to, the public address (e.g., public key **258**) corresponding to client device **102**, a public address associated with client device **104**, and the amount specified in the transaction. In some embodiments, the one or more parameters may further include a number of additional signatures needed from verification pool **106** to complete the multi-signature transaction.

[0077] At step **408**, verification institution **110** may receive the broadcasted verification request from verification network **105**. Although the below operations are discussed generally with respect to one or more verification institutions **110**, those skilled in the art may readily understand that it is not required for all verification institutions **110** in verification pool **106** to perform all of the operations described below.

[0078] At step **410**, verification institution **110** may assess a risk associated with verifying the transaction request. For example, risk analyzer **264** may be configured to assess a risk associated with verifying the cryptocurrency transaction between the payer (e.g., client device **102**) and the payee (e.g., client device **104**). In some embodiments, risk analyzer **264** may assess the risk associated with verifying the cryptocurrency transaction by taking in account one or more parameters that include, but are not limited to, a current location of client device **102** (e.g., at a location associated with the user), an amount of cryptocurrency to be transmitted, a frequency of transactions between the payer (e.g., client device **102**) and the payee (e.g., client device **104**), and the like. Based on the risk assessment performed by risk analyzer **264**, verification institution **110** may generate a verification offer to be transmitted to client device **102**.

[0079] At step **412**, verification institution **110** may assign a verification fee to the verification offer based on the risk assessment analysis. For example, verification institution **110** may assign a fee to

their verification service based on the risk associated with verifying a particular transaction. For example, if risk analyzer **264** determines that there is minimal risk associated with verifying the transaction, verification institution **110** may propose a minimal fee to client device **102** in the verification offer. In another example, if risk analyzer **264** determines that there is a higher risk associated with verifying the transaction, verification institution **110** may propose a higher fee to client device **102** in the verification offer.

[0080] At step **414**, verification institution **110** may access a private key associated with the payer. For example, upon generating a verification offer, verification institution **110** may request from verification network **105** a private key (e.g., private key **214**) that is hosted by verification network **105** and associated with the payer (e.g., client device **102**).

[0081] At step **416**, verification institution **110** may generate a signature using the accessed private key. For example, verification institution **110** may generate a second (or third, fourth, etc.) signature for the transaction using private key **214**. By generating a second signature prior to transmitting the verification offer to client device **102**, the transaction may be completed as soon as the payer selects a verification offer.

[0082] At step **418**, verification institution **110** may transmit the verification offer and the second (or additional) signature to verification network **105**. At step **420**, verification network **105** may receive the verification offer and the second signature from verification institution **110**.

[0083] At step **422**, verification network **105** may prompt the payer to select a verification offer from a respective verification institution **110**. Verification network **105** may transmit the one or more verification offers to client device **102** for display. The verification offer may include the verification fee associated therewith.

[0084] At step **424**, client device **102** may receive the prompt from verification network **105**. For example, client device **102** may receive the one or more verification offers from verification network **105** via application **252** executing thereon.

[0085] At step **426**, client device **102** may generate a GUI displaying the one or more verification offers. The GUI generated by client device **102** may be displayed to the payer via a display associated with client device **102**. For example, the GUI may be displayed via an external display device (e.g., a monitor) associated with client device **102**. In another embodiment, the GUI may be displayed via a touchscreen associated with client device **102**. The GUI may include the one or more verification offers and the one or more verification fees associated therewith.

[0086] At step **428**, client device **102** may receive an input that corresponds to a selection among the verification offer(s). For example, client device **102** may receive an input, via the GUI, a selection of a verification offer. At step **430**, client device **102** may transmit a verification offer acceptance to verification network **105**.

[0087] At step **430**, verification network **105** may receive the selection of the verification offer acceptance from client device **102**. At step **432**, verification network **105** may notify a respective verification institution **110** of the verification offer acceptance. For example, verification network **105** may transmit a message to a respective verification institution **110** associated with the verification offer.

[0088] At step **434**, verification network **105** may record the transaction details in database **204**. For example, verification network **105** may record the transaction date, the transaction amount, the payer public address, the payee public address, any verification fees and one or more verification institutions **110** associated with one or more accepted verification offers in database **204**. By recording the transaction details in database **204**, should the transaction later be deemed fraudulent (e.g., a fraudulent third party obtained the payer's private key (e.g., private key **256**), the transaction may be reversible. For example, the one or more verification institutions **110** whose verification offers were accepted are now liable for refunding the payer the transaction amount.

[0089] At step **436**, verification network **105** may broadcast/post the transaction between client device **102** and client device **104** to blockchain network **108**. For example, upon determining that

the necessary number of signatures required by the transaction request is met, verification network **105** may transmit the transaction between payer and payee to blockchain network **108** for posting to the blockchain. In some examples, the transaction may also reflect any verification fees.

[0090] Although not shown in FIG. **4**, as discussed above, in some examples, after step **408** (e.g., at step **410**), verification institution(s) **110** may assess pre-agreed threshold parameter(s) associated with the transaction request and determine whether the pre-agreed threshold parameter(s) have been satisfied. If at least one of verification institutions **110** determine that the pre-agreed threshold parameter(s) are satisfied, the at least one verification institution **110** may perfect the blockchain transaction (as discussed above) and broadcast the perfected blockchain transaction to blockchain network **108** (thereby bypassing, for example, steps **412-434**). If the pre-agreed threshold parameter(s) are not satisfied, the process may proceed according to steps **412-436**.

[0091] FIG. **5A** is a block diagram **500** illustrating one or more screenshots of client computing device **502**, according to one or more exemplary embodiments. As illustrated, client device **502** may be a mobile device associated with a payer. For example, client device **502** may be associated with client device **102** (explained in detail above). Client device **502** may include display **504**. Display **504** may be currently displaying screenshot **505**. Screenshot **505** may illustrate an example GUI that may be generated and displayed to the payer upon receiving one or more verification offers from verification network **105**.

[0092] As shown, screenshot **505** includes one or more verification offers **503.sub.1**, **503.sub.2**, and **503.sub.3** (generally “verification offer **503**”). Verification offer **503.sub.1** may include a graphic **508.sub.1** associated with a verification institution **110.sub.1** and verification fee **506.sub.1** associated therewith. Verification offer **503.sub.2** may include a graphic **508.sub.2** associated with a verification institution **110.sub.2** and verification fee **506.sub.2** associated therewith. Verification offer **503.sub.3** may include a graphic **508.sub.3** associated with a verification institution **110.sub.3** and verification fee **506.sub.3** associated therewith. Each verification offer **503** may be selectable by the payer.

[0093] FIG. **5B** is a block diagram **550** illustrating one or more screenshots of client computing device **502**, according to one or more exemplary embodiments. As illustrated, display **504** of client device **502** may be currently displaying screenshot **555**. Screenshot **555** may illustrate an example GUI that may be generated and displayed to the payer upon the payer providing input accepting or rejection a verification offer.

[0094] As shown, when a payer provides a select and drag input (e.g., swipe right) the display may update to reveal screenshot **555**. The payer may be prompted with one or more options for each verification offer **503**. For example, verification offer **503.sub.1** may include a graphic **552.sub.1** associated with a rejection of the verification offer (e.g. “deny”) and graphic **554.sub.1** associated with an approval of the verification offer (e.g. “approve”). Verification offer **503.sub.2** may include a graphic **552.sub.2** associated with a rejection of the verification offer (e.g. “deny”) and graphic **554.sub.2** associated with an approval of the verification offer (e.g. “approve”). Verification offer **503.sub.3** may include a graphic **552.sub.3** associated with a rejection of the verification offer (e.g. “deny”) and graphic **554.sub.3** associated with an approval of the verification offer (e.g. “approve”).

[0095] Upon receiving an input via graphic **552** or graphic **554**, client device **102** may transmit to verification network **105** a rejection or approval of each verification offer.

[0096] It is understood that FIGS. **5A** and **5B** illustrate an example arrangement, presentation and selection operations of verification offers **503** on display **504** of client device **502**. It is understood that verification offers **503** may be arranged and presented in any suitable manner on display **504**, and that verification offers **503** may be selected by one or more suitable input operations including operations other than a select and drag input (e.g., swipe right).

[0097] FIG. **6** is a block diagram illustrating an exemplary computing environment **600**, according to one or more embodiments. Computing environment **600** may include computing system **602** and



computing system **652**. Computing system **602** may be representative of client device **102**. Computing system **652** may be representative of management system **202** or verification network **105**.

[0098] Computing system **602** may include processor **604**, memory **606**, storage **608**, and network interface **610**. In some embodiments, computing system **602** may be coupled to one or more I/O device(s) **612** (e.g., keyboard, mouse, etc.).

[0099] Processor **604** may retrieve and execute program code **618** (i.e., programming instructions) stored in memory **606**, as well as store and retrieve application data. Processor **604** may be included to be representative of a single processor, multiple processors, a single processor having multiple processing cores, and the like. Network interface **610** may be any type of network communications allowing computing system **602** to communicate externally via computing network **605**. For example, network interface **610** may be configured to enable external communication with computing system **652**.

[0100] Storage **608** may be, for example, a disk storage device. Although shown as a single unit, storage **608** may be a combination of fixed and/or removable storage devices, such as fixed disk drives, removable memory cards, optical storage, network attached storage (NAS), storage area network (SAN), and the like. Storage **608** may include wallet **620**. Wallet **620** may be configured to store one or more key pairs associated with a user's blockchain account. Each key pair may include a private key and a corresponding public key.

[0101] Memory **606** may include application **614**, operating system **616** and program code **618**. In some examples, memory **606** may include a geolocation agent (not shown). Program code **618** may be accessed by processor **604** for processing (i.e., executing program instructions). Program code **618** may include, for example, executable instructions for communicating with computing system **652** to display one or more pages of website **662**. Application **614** may enable a user of computing system **602** to access a functionality of computing system **652**. For example, application **614** may access content managed by computing system **652**, such as website **662**. The content that is displayed to a user of computing system **602** may be transmitted from computing system **652** to computing system **602**, and subsequently processed by application **614** for display through a GUI of computing system **602**.

[0102] Computing system **652** may include processor **654**, memory **656**, storage **658**, and network interface **660**. In some embodiments, computing system **652** may be coupled to one or more I/O device(s) **674**. In some embodiments, computing system **652** may be in communication with database **204**.

[0103] Processor **654** may retrieve and execute program code **666** (i.e., programming instructions) stored in memory **656**, as well as store and retrieve application data. Processor **654** is included to be representative of a single processor, multiple processors, a single processor having multiple processing cores, and the like. Network interface **660** may be any type of network communications enabling computing system **652** to communicate externally via computing network **605**. For example, network interface **660** may allow computing system **652** to communicate with computer system **602**.

[0104] Storage **658** may be, for example, a disk storage device. Although shown as a single unit, storage **658** may be a combination of fixed and/or removable storage devices, such as fixed disk drives, removable memory cards, optical storage, network attached storage (NAS), storage area network (SAN), and the like.

[0105] Memory **656** may include website **662**, operating system **664**, program code **666**, account handler **668**, verification agent **670**, and transaction agent **672**. Program code **666** may be accessed by processor **654** for processing (i.e., executing program instructions). Program code **666** may include, for example, executable instructions configured to perform steps discussed above in conjunction with FIGS. 3-4. As an example, processor **654** may access program code **666** to perform operations for verifying a cryptocurrency transaction. Website **662** may be accessed by

computing system **602**. For example, website **662** may include content accessed by computing system **602** via a web browser or application.

[0106] Account handler **668** may be configured to manage one or more accounts associated with one or more users. For example, account handler **668** may communicate with database **204** that stores one or more key pairs **215** (FIG. 2). Account handler **668** may generate one or more key pairs upon a user registering with verification network **105**. In some embodiments, account handler **668** may generate one or more key pairs stored on computing system **602**.

[0107] Transaction agent **672** may be configured to manage one or more transactions associated with each account. For example, transaction agent **672** may act as a “middle-man” between computing system **602** and one or more verification institutions **110**. In operation, for example, transaction agent **672** may transmit the transaction request to one or more verification institutions **110**. Upon receiving input from computing system **602** that corresponds to a selection of a verification offer, transaction agent **672** may transmit the offer acceptance to the respective verification institution **110**.

[0108] Verification agent **670** may be configured to verify one or more transactions between a payer and a payee. Verification agent **670** may, for example, verify a first signature transmitted from client device **602** to verification network **105** that signals the initiation of the transaction. The first signature may correspond to a first signature needed for a multi-signature transaction. Verification agent **670** may further be configured to verify a second signature transmitted from a verification institution, in response to generation of a verification offer from verification institution **110**. The second signature may correspond to a second signature (or additional signature) needed for a multi-signature transaction.

[0109] Although not shown in FIG. 6, each verification institution **110** may also include one or more of the components shown in computing system **652**. For example, verification institution **110** may include a processor similar to processor **654**, memory similar to memory **656**, storage similar to storage **658**, a network interface similar to network interface **660** and, in some examples, one or more I/O devices similar to I/O device(s) **674**. Similar to memory **656** of computing system **652**, the memory of verification institution **110** may also include an operating system similar to operating system **664** and program code similar to program code **666**. In contrast to memory **656** of computing system **652**, the memory of verification institution **110** may store application **262** (FIG. 2) and risk analyzer **264** (FIG. 2), and the program code of verification institution **110** may include program instructions relating to application **260** and risk analyzer **264**.

[0110] It is understood that aspects of the present disclosure may be implemented in hardware or software or a combination of hardware and software. In one example, aspects of the present disclosure may be implemented as a program product for use with a computer system. The program(s) of the program product define functions of the embodiments (including the methods described herein) and can be contained on a variety of computer-readable storage media.

Illustrative computer-readable storage media include, but are not limited to: (i) non-writable storage media (e.g., read-only memory (ROM) devices within a computer, such as compact disk-ROM (CD-ROM) disks readable by a CD-ROM drive, flash memory, ROM chips, or any type of solid-state non-volatile memory) on which information is permanently stored; and (ii) writable storage media (e.g., floppy disks within a diskette drive or hard-disk drive or any type of solid state random-access memory (RAM)) on which alterable information is stored. Such computer-readable storage media, when carrying computer-readable instructions that direct the functions of the present disclosure, are embodiments of the present disclosure.

[0111] While the present disclosure has been discussed in terms of certain embodiments, it should be appreciated that the present disclosure is not so limited. The embodiments are explained herein by way of example, and there are numerous modifications, variations and other embodiments that may be employed that would still be within the scope of the present disclosure.

## Claims

- 1.** A system comprising: one or more verification computing systems; and a verification network comprising a computing system having a processor and a memory storing programming instructions, the verification network configured to: receive a proposed blockchain transaction generated by at least one payer device, and broadcast a verification request for the proposed blockchain transaction to the one or more verification computing systems, the verification request including one or more situational detail parameters associated with the proposed blockchain transaction, the one or more verification computing systems configured to determine whether the proposed blockchain transaction includes one or more pre-agreed threshold parameters, responsive to the verification request, when the proposed blockchain transaction includes the one or more pre-agreed threshold parameters, the one or more verification computing systems are configured to: directly perfect the proposed blockchain transaction to create a perfected blockchain transaction, and broadcast the perfected blockchain transaction directly to a blockchain network, and when the proposed blockchain transaction fails to include the one or more pre-agreed threshold parameters: the one or more verification computing systems are configured to perfect the proposed blockchain transaction via prompting authorization from the at least one payer device, and the verification network is configured to broadcast the perfected blockchain transaction to the blockchain network, responsive to receiving said authorization from the at least one payer device.
- 2.** The system of claim 1, wherein the proposed blockchain transaction comprises a first signature that is generated using a first private key.
- 3.** The system of claim 2, wherein the first private key is generated and maintained by the at least one payer device.
- 4.** The system of claim 3, wherein the perfecting of the proposed blockchain transaction comprises generating one or more additional signatures using a second private key.
- 5.** The system of claim 4, wherein the second private key is generated and maintained by the one or more verification computing systems.
- 6.** The system of claim 1, wherein when the proposed blockchain transaction fails to include the one or more pre-agreed threshold parameters: the one or more verification computing systems are configured to perfect the proposed blockchain transaction by generating and transmitting one or more verification offers to the at least one payer device, responsive to receiving the one or more verification offers, the at least one payer device is configured to transmit a selection of at least one offer from among the one or more verification offers to the verification network, the selection indicating the authorization of the proposed blockchain transaction, and upon receiving said selection, the verification network is configured to broadcast the perfected blockchain transaction to the blockchain network.
- 7.** The system of claim 6, wherein the at least one payer device is configured to display the one or more verification offers via a graphical user interface of the at least one payer device.
- 8.** The system of claim 6, wherein the one or more verification computing systems are configured to generate the one or more verification offers based on a risk analysis of the proposed blockchain transaction.
- 9.** The system of claim 8, wherein the one or more verification offers comprise one or more of an indication of a transaction risk based on the risk analysis, a verification charge based on the risk analysis, and a surge charge based on a volume of verifications requests received by the one or more verification computing systems.
- 10.** The system of claim 8, wherein the one or more verification computing systems are configured to assess a risk associated with verifying the proposed blockchain transaction.
- 11.** The system of claim 10, wherein the risk is based on one or more of a location of the at least one payer device, a transaction amount, a frequency of transactions between a payer associated

with the at least one payer device and a payee, an identity of the payee, a time of the proposed blockchain transaction, and a purchase history of the payer.

**12.** The system of claim 6, wherein the verification network further comprises an account handler, a transaction agent, a verification agent, and a database, wherein: the account handler is configured to generate one or more key pairs, each key pair comprising a public key and a private key, and each key pair associated with a particular user, and to store said one or more key pairs in the database, the transaction agent is configured to perform one or more of: broadcasting the verification request to the one or more verification computing systems, recording the perfected blockchain transaction in the database, and broadcasting the perfected blockchain transaction to the blockchain network, and the verification agent is configured to verify at least one of a first signature and one or more additional signatures.

**13.** The system of claim 12, wherein: the account handler is configured to grant access to at least one private key among the one or more key pairs to the one or more verification computing systems, and the one or more verification computing systems are configured to generate one or more additional signatures using said at least one private key.

**14.** The system of claim 1, wherein the proposed blockchain transaction comprises one or more of a public key associated with the at least one payer device, payee address information associated with a payee, a public key associated with the payee, a transaction amount and a specification of two or more additional signatures to perfect the proposed blockchain transaction.

**15.** The system of claim 1, wherein the one or more verification computing systems are configured to: prompt the at least one payer device to authenticate with the one or more verification computing systems, confirm an identity of a payer associated with the at least one payer device, and verify that an account associated with the payer includes a transaction amount.

**16.** The system of claim 1, wherein the verification network is configured to incorporate the one or more situational detail parameters into the proposed blockchain transaction.

**17.** The system of claim 1, wherein the one or more situational detail parameters comprise one or more of transaction information, geolocation data, and merchant data.

**18.** The system of claim 17, wherein the transaction information comprises one or more of a time and a value, and the merchant data comprises merchant statistics data.

**19.** The system of claim 1, wherein the one or more verification computing systems are configured to analyze the one or more situational detail parameters in the verification request to determine a likelihood of fraud associated with the proposed blockchain transaction.

**20.** The system of claim 19, wherein the one or more verification computing systems are configured to perfect the proposed blockchain transaction responsive to said analyzing of the one or more situational detail parameters and said determining of whether the proposed blockchain transaction includes the one or more pre-agreed threshold parameters.

**21.** The system of claim 19, wherein the one or more verification computing systems are configured to reverse the perfected blockchain transaction responsive to determining that the proposed blockchain transaction is fraudulent.

---