

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250256875

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

FOLEY; Kevin et al.

---

### **METHOD FOR PROVIDING AT LEAST ONE UTENSIL WRAPPED IN A NAPKIN, APPARATUS FOR WRAPPING A NAPKIN AROUND AT LEAST ONE UTENSIL, UTENSIL PICKER AND MAGAZINE FOR STORING UTENSILS**

---

#### **Abstract**

A method for providing at least one utensil wrapped in a napkin is provided. The method includes placing the napkin on a wrapping assembly having first, second and third rollers and an endless belt wrapped around the rollers, in an initial configuration, placing the at least one utensil on the napkin, moving the second roller toward the first roller, turning the endless belt around rollers, stopping to turn the endless belt, and returning the wrapping assembly to the initial configuration. An apparatus for wrapping a napkin around at least one utensil, a utensil picker for picking up at least one utensil from at least one utensil magazine storing a plurality of utensils, an apparatus having the utensil picker, a magazine for storing a plurality of utensils and an apparatus having the magazine are also disclosed.

---

**Inventors:** FOLEY; Kevin (Encinitas, CA), FOLEY; Michael D. (Cambridge, MA), HEILNER; Esko (Portland, ME)

**Applicant:** LEFT FIELD PRODUCTS LLC (Encinitas, CA)

**Family ID:** 81600836

**Appl. No.:** 19/193221

**Filed:** April 29, 2025

#### **Related U.S. Application Data**

parent US continuation 18252663 20230511 parent-grant-document US 12312111 WO  
continuation PCT/IB2021/060469 20211111 child US 19193221  
us-provisional-application US 63112392 20201111

---

## Publication Classification

**Int. Cl.:** **B65B11/56** (20060101); **B65B11/04** (20060101); **B65B35/16** (20060101); **B65B35/36** (20060101); **B65B41/06** (20060101); **B65B67/10** (20060101)

**U.S. Cl.:**

**CPC** **B65B11/56** (20130101); **B65B11/04** (20130101); **B65B35/16** (20130101); **B65B41/06** (20130101); **B65B67/10** (20130101); **B65B35/36** (20130101); **B65B2220/14** (20130101)

---

## Background/Summary

CROSS-REFERENCE [0001] The present application is a continuation of U.S. patent application Ser. No. 18/252,663, filed May 11, 2023, which is a National Stage Entry of International Application No. PCT/IB2021/060469, filed Nov. 11, 2021, which claims priority to U.S. Provisional Patent Application No. 63/112,392 filed Nov. 11, 2020, the entire contents of each of which are incorporated by reference herein in their entirety.

### TECHNOLOGICAL FIELD

[0002] The present technology relates to a method for providing at least one utensil wrapped in a napkin, an apparatus for wrapping a napkin around at least one utensil, a utensil picker for picking up at least one utensil from at least one utensil magazine storing a plurality of utensils, and a magazine for storing utensils. #

### BACKGROUND

[0003] Many establishments where food is served such as restaurants, cruise lines, and hospitals provide utensils that are wrapped in a napkin. Wrapping utensils in napkins can help accelerate the distribution of utensils and can help reduce contamination thereof.

[0004] Typically, utensils are manually wrapped in a napkin. This manual process can be time consuming, and when performed in commercial settings, can increase operational costs. In addition, the utensils being wrapped could be contaminated by the person manually wrapping them.

[0005] Therefore, there is a desire for an apparatus and associated components that can wrap utensils in napkins.

### SUMMARY

[0006] It is an object of the present technology to ameliorate at least some of the inconveniences present in the prior art.

[0007] According to one aspect of the present technology, there is provided a method for providing at least one utensil wrapped in a napkin. The method includes placing the napkin on a wrapping assembly in an initial configuration. The wrapping assembly includes a frame first roller, a second roller, a third roller being vertically lower than the first and second roller; and an endless belt wrapped around the first, second and third rollers. The first, second and third roller are mounted to the frame. In the initial configuration, the first roller is generally vertically aligned with the second roller, and the endless belt is in tension about the first, second and third rollers. The napkin is placed on a portion of the endless belt extending between the first and second rollers. After placing the napkin on the wrapping assembly, the method includes placing the at least one utensil on the napkin. After placing the at least one utensil on the napkin, the method includes moving the second roller toward the first roller, thereby causing the endless belt to sag between the first and second rollers, and causing the napkin and the at least one utensil to be received in a resulting sag. After moving the second roller toward the first roller, the method includes turning the endless belt around the first, second and third rollers thereby wrapping the napkin around the at least one utensil. Once

the at least one utensil is wrapped in the napkin, the method including stopping to turn the endless belt, and after stopping to turn the endless belt, returning the wrapping assembly to the initial configuration by moving the second roller away from the first roller, thereby causing the at least one utensil wrapped in the napkin to be disposed on the portion of the endless belt extending between the first and second roller.

[0008] In some embodiments, placing the at least one utensil on the napkin includes placing a plurality of utensils on the napkin.

[0009] In some embodiments, turning the endless belt around the first, second and third rollers includes rotating the third roller to drive the endless belt.

[0010] In some embodiments, the second roller is moved toward and away from the first roller about an arcuate path.

[0011] In some embodiments, the method further includes, after placing the at least one utensil on the napkin and before turning the endless belt around the first, second and third rollers, lifting the third roller thereby also causing the endless belt to sag between the first and second rollers, and also causing the napkin and the at least one utensil to be received in the resulting sag. The method also includes lowering the third roller when returning the wrapping assembly to the initial configuration.

[0012] In some embodiments, the method further includes, after moving the second roller toward the first roller and before turning the endless belt around the first, second and third rollers, lowering the third roller to increase tension in the endless belt.

[0013] In some embodiments, the third roller is lifted and lowered about an arcuate path.

[0014] In some embodiments, the second roller is moved toward and away from the first roller about a rectilinear path.

[0015] In some embodiments, the method further includes picking up the napkin from a stack of napkins.

[0016] In some embodiments, picking up the napkin from the stack of napkins includes picking up the napkin using a fan.

[0017] In some embodiments, the method further includes picking up the at least one utensil from at least one magazine storing a plurality of utensils.

[0018] In some embodiments, picking up the at least one utensil includes picking up the at least one utensil using a utensil picker.

[0019] In some embodiments, placing the at least one utensil on the napkin includes dropping the at least one utensil on a chute disposed above the wrapping assembly.

[0020] In some embodiments, the first roller rotates about an axis of rotation that is fixed relative to the frame.

[0021] According to another aspect of the present technology, there is provided an apparatus for wrapping a napkin around at least one utensil. The apparatus includes a frame, a first roller, a second roller, a third roller, an actuator, a motor and an endless belt. The first roller is rotationally connected to the frame. The second roller is rotationally connected to the frame, and is movable between a first position and a second position. In the first position, the second roller is generally vertically aligned with the first roller. The second roller is closer to the first roller in the second position than in the first position in a horizontal direction. The actuator is operatively connected to the second roller for moving the second roller between the first position and the second position. The third roller is rotationally connected to the frame and is disposed vertically lower than the first and second rollers. The motor is operatively connected to one of the first, second and third rollers for rotating the one of the first, second and third rollers. The endless belt is wrapped around the first, second and third rollers. In an initial configuration of the first, second and third rollers, the second roller is in the first position, the endless belt is in tension about the first, second, and third rollers, and a portion of the endless belt extending between the first and second rollers defines a flat surface for receiving a napkin and the at least one utensil thereon. In a wrapping configuration of

the first, second and third rollers, the second roller is in the second position, and the portion of the endless belt extending between the first and second rollers extends generally downward from the first roller to a low point and extends generally upward from the low point to the second roller for receiving the napkin and the at least one utensil at the low point such that rotation of the one of the first, second and third rollers by the motor causes the endless belt to turn around the first, second and third rollers thereby wrapping the napkin around the at least one utensil.

[0022] In some embodiments, the motor is operatively connected to the third roller for rotating the third roller.

[0023] In some embodiments, the second roller is movable between the first and second positions along a rectilinear path.

[0024] In some embodiments, the apparatus further includes a controller in communication with the motor and the actuator for controlling the motor and the actuator.

[0025] In some embodiments, the controller is programmed for consecutively controlling the actuator for placing the first, second and third rollers in the initial configuration, controlling the actuator for placing the first, second and third rollers in the wrapping configuration, controlling the motor to rotate the one of the first, second and third rollers for turning the endless belt around the first, second and third rollers, controlling the motor to stop rotating the first roller, and controlling the actuator for placing the first, second and third rollers in the initial configuration.

[0026] In some embodiments, the actuator is a first actuator. The third roller is movable between a third position, a fourth position and a fifth position where the third roller is closer to the first roller in the fourth position than in the third position in a vertical direction, and the fifth position of the third roller is intermediate the third and fourth positions of the third roller. The apparatus further includes a second actuator operatively connected to the third roller for moving the third roller between the third position, the fourth position and the fifth position. In the initial configuration of the first, second and third rollers, the third roller is in the third position. In a folding configuration of the first, second and third rollers, the second roller is in the first position, the third roller is in the fourth position, and the portion of the endless belt extending between the first and second rollers defines a V-shape for receiving the napkin and the at least one utensil at a bottom of the V-shape. In a wrapping configuration of the first, second and third rollers, the third roller is in the fifth position.

[0027] In some embodiments, the apparatus further includes a controller in communication with the motor, the first actuator and the second actuator for controlling the motor, the first actuator and the second actuator.

[0028] In some embodiments, the controller is programmed for consecutively controlling the first and second actuators for placing the first, second and third rollers in the initial configuration, controlling the first and second actuators for placing the first, second and third rollers in the folding configuration, controlling the first and second actuators for placing the first, second and third rollers in the wrapping configuration, controlling the motor to rotate the first roller for turning the endless belt around the first, second and third rollers, controlling the motor to stop rotating the first roller; and controlling the first and second actuators for placing the first, second and third rollers in the initial configuration.

[0029] In some embodiments, the second roller is pivotable between the first and second positions; and the third roller is pivotable between the third, fourth and fifth positions.

[0030] In some embodiments, the apparatus further includes at least one first pivotable arm operatively connected to the first actuator, the second roller being connected to the at least one first pivotable arm, and at least one second pivotable arm operatively connected to the second actuator, the third roller being connected to the at least one second arm.

[0031] In some embodiments, the motor is a first motor, and the actuator is a second motor.

[0032] In some embodiments, the apparatus further includes a napkin delivery assembly for delivering the napkin to the endless belt.

[0033] In some embodiments, the napkin delivery assembly includes a fan for picking up the

napkin from a stack of napkins and is movable between the stack of napkins and the endless belt.

[0034] In some embodiments, the apparatus further includes a utensil delivery assembly for delivering the at least one utensil to the endless belt.

[0035] In some embodiments, the utensil delivery assembly includes at least one magazine for storing a plurality of utensils, and a utensil picker for picking up at least one utensil from the at least one magazine and delivering the at least one utensil to the endless belt.

[0036] In some embodiments, the first roller rotates about an axis of rotation that is fixed relative to the frame.

[0037] According to another aspect of the present technology, there is provided a utensil picker for picking up at least one utensil from at least one utensil magazine storing a plurality of utensils. The utensil picker includes at least one movable arm, at least one base connected to the at least one movable arm, and at least two fingers connected to each base of the at least one base. Each finger of the at least two fingers has a fingertip operatively connected to the base and an attachment. The fingertip is configured to move vertically with respect to the base, and the attachment is provided at an end of the fingertip for attaching one utensil of the at least one utensil to the finger.

[0038] In some embodiments, the attachment is a permanent magnet.

[0039] In some embodiments, the utensil picker further includes at least one track, the at least one movable arm being movable along the at least one track.

[0040] In some embodiments, the at least two fingers are connected under the base.

[0041] In some embodiments, each base includes an upper portion connected to the at least one movable arm, a lower portion connected to the upper portion, and a hinge connecting the upper portion to the lower portion.

[0042] In some embodiments, each finger of the at least two fingers further includes a spring connected to the base. The spring biases the fingertip away from the base.

[0043] In some embodiments, each finger of the at least two fingers further includes a housing connected to the base; and for each finger, the spring is housed in the housing.

[0044] In some embodiments, for each finger, the fingertip is slidable in the housing.

[0045] In some embodiments, the at least two fingers are five fingers arranged in a line.

[0046] According to another aspect of the present technology, there is provided an apparatus for wrapping a napkin around at least one utensil. The apparatus includes at least one magazine for storing the at least one utensil, a wrapping assembly for wrapping the napkin around the at least one utensil, and the utensil picker according to at least one of the above aspects or according to at least one of the above aspects and one or more of the above embodiments for picking up the at least one utensil from the at least one magazine and for bringing the at least one utensil from the at least one magazine to the wrapping assembly.

[0047] In some embodiments, each magazine of the at least one magazine has a corresponding at least two fingers of the at least two fingers, and for each magazine the corresponding at least two fingers are configured to pick up at least one utensil at a time from the magazine.

[0048] In some embodiments, for each magazine the corresponding at least two fingers are configured to pick up a single utensil at a time from the magazine.

[0049] In some embodiments, the apparatus further includes a comb having upwardly extending teeth, the comb being disposed above the wrapping assembly, and the at least one movable arm is configured to move the at least two fingers through spaces defined between teeth of the comb, thereby causing the comb to detach the at least one utensil picked up by the utensil picker from the at least two fingers and, as a result, cause the at least one utensil to fall toward the wrapping assembly.

[0050] In some embodiments, the apparatus further includes a chute disposed at least in part vertically between the comb and the wrapping apparatus such that the at least one utensil detached from the utensil picker by the comb falls on the chute and then falls from the chute on the wrapping assembly.

[0051] In some embodiments, the apparatus further includes a chute disposed above the wrapping assembly, and the at least one movable arm is configured to move above the chute such that the at least one utensil picked up by the utensil picker can be dropped from the utensil picker onto the chute and then fall from the chute on the wrapping assembly.

[0052] In some embodiments, the apparatus further includes a napkin delivery assembly for delivering the napkin to the wrapping assembly.

[0053] In some embodiments, the napkin delivery assembly includes a fan for picking up the napkin from a stack of napkins and is movable between the stack of napkins and the wrapping assembly.

[0054] According to another aspect of the present technology, there is provided a magazine for storing a plurality of utensils. The magazine has a receptacle and at least one set of dividers. The receptacle has a first side defining a first opening, a second side opposite the first side, a third side extending between the first and second sides, the third side defining a second opening, a fourth extending between the first and second sides, the fourth side being opposite the third side, a fifth side; and a sixth side opposite the fifth side. The first, second, third and fourth sides extend between the fifth and sixth sides. The at least one set of dividers is disposed in the receptacle. The dividers are spaced apart from each other between the third side to the fourth side. The at least one set of dividers is movable between a first position and a second position. In the first position, the dividers extend at least partially across the receptacle toward one of the fifth side and the sixth side such that utensils can be inserted via the first opening between the dividers and the dividers keep the utensils apart from each other. In the second position, the dividers extend toward one of the first side and the second side such that moving the at least one set of dividers from the first position to the second position with the receptacle lying on its fourth side causes utensils inserted between the dividers to fall in a stack on the fourth side, and the utensils can be removed from the stack via the second opening.

[0055] In some embodiments, the magazine further includes a lid for selectively closing the first opening.

[0056] In some embodiments, the lid is hinged to the receptacle.

[0057] In some embodiments, the magazine further includes at least one shaft extending in the receptacle. The at least one set of dividers is connected to the at least one shaft, and the at least one shaft is rotatable to move the at least one set of dividers between the first position and the second position.

[0058] In some embodiments, the dividers are generally perpendicular to the at least one shaft.

[0059] In some embodiments, the at least one shaft passes through the second opening and protrudes from the receptacle.

[0060] In some embodiments, the at least one set of dividers includes a first set of dividers and a second set of dividers, and the first set of dividers is disposed between the first side and the second set of dividers.

[0061] In some embodiments, in the second position, the dividers of the first set of dividers extend toward the second side, and in the second position, the dividers of the second set of dividers extend toward the first side.

[0062] In some embodiments, the at least one set of dividers includes a first set of dividers and a second set of dividers. The first set of dividers is disposed next to the fifth side, the second set of dividers is disposed next to the sixth side and the first and second sets of dividers are at a same distance from the first side. In the first position, the dividers of the first set of dividers extend toward the sixth side; and in the first position, the dividers of the second set of dividers extend toward the fifth side.

[0063] In some embodiments, with the first set of dividers in the first position and with the second set of dividers in the first position, each divider of the first set of dividers is coaxial with a corresponding divider of the second set of dividers.

[0064] In some embodiments, the at least one set of dividers further includes a third set of dividers and a fourth set of dividers. The first and second sets of dividers are disposed between the first side and the third and fourth set of dividers. The third set of dividers is disposed next to the fifth side, the fourth set of dividers is disposed next to the sixth side and the third and fourth sets of dividers are at a same distance from the first side. In the first position, the dividers of the third set of dividers extend toward the sixth side; and in the first position, the dividers of the fourth set of dividers extend toward the fifth side.

[0065] In some embodiments, in their second positions, the dividers of the first and second sets of dividers extend toward the second side; and in their second positions, the dividers of the third and fourth sets of dividers extend toward the first side.

[0066] In some embodiments, with the third set of dividers in the first position and with the fourth set of dividers in the first position, each divider of the third set of dividers is coaxial with a corresponding divider of the fourth set of dividers.

[0067] In some embodiments, the dividers are spacers.

[0068] According to another aspect of the present technology, there is provided an apparatus for wrapping a napkin around at least one utensil. The apparatus includes at least one magazine according to at least one of the above aspects or according to at least one of the above aspects and one or more of the above embodiments for storing the at least one utensil, a wrapping assembly for wrapping the napkin around the at least one utensil, and a utensil picker for picking up the at least one utensil from the at least one magazine via the second opening and for bringing the at least one utensil from the at least one magazine to the wrapping assembly.

[0069] In some embodiments, the second opening of the at least one magazine faces up.

[0070] In some embodiments, the at least one magazine is a plurality of magazines disposed next to each other.

[0071] In some embodiments, the apparatus further includes a napkin delivery assembly for delivering the napkin to the wrapping assembly.

[0072] In some embodiments, the napkin delivery assembly includes a fan for picking up the napkin from a stack of napkins and is movable between the stack of napkins and the wrapping assembly.

[0073] Implementations of the present technology each have at least one of the above-mentioned object and/or aspects, but do not necessarily have all of them. It should be understood that some aspects of the present technology that have resulted from attempting to attain the above-mentioned object may not satisfy this object and/or may satisfy other objects not specifically recited herein.

[0074] Additional and/or alternative features, aspects, and advantages of implementations of the present technology will become apparent from the following description, the accompanying drawings, and the appended claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0075] For a better understanding of the present technology, as well as other aspects and further features thereof, reference is made to the following description which is to be used in conjunction with the accompanying drawings, where:

[0076] FIG. 1 is a perspective view taken from a front, top, right side of an apparatus for wrapping a napkin around utensils;

[0077] FIG. 2 is a perspective view taken from a front, top, right side of a portion of the apparatus of FIG. 1, with a napkin delivery assembly of the apparatus of FIG. 1 having picked up a napkin and a utensil picker of the apparatus picking up utensils from magazines;

[0078] FIG. 3 is a perspective view taken from a front, top, right side of a portion of the apparatus

of FIG. 1, with the napkin delivery assembly being above a wrapping assembly of the apparatus of FIG. 1;

[0079] FIG. 4 is a perspective view taken from a front, top, left side of a portion of the apparatus of FIG. 1, in the configuration shown in FIG. 3;

[0080] FIG. 5 is a perspective view taken from a front, top, right side of the apparatus of FIG. 1 with the napkin being disposed on the wrapping assembly, and the utensil picker being above the wrapping assembly, and interacting with a comb of the apparatus of FIG. 1;

[0081] FIG. 6 is a perspective view taken from a front, top, right side of the apparatus of FIG. 1, with the napkin and a fork being disposed on the wrapping assembly;

[0082] FIG. 7 is a perspective view taken from a front, top, right side of the wrapping assembly of the apparatus of FIG. 1 with the napkin and utensils being disposed thereon;

[0083] FIG. 8 is a perspective view taken from a front, top, right side of the wrapping assembly of FIG. 7 in an initial configuration, with a frame shown in transparency;

[0084] FIG. 9 is a perspective view taken from a front, top, right side of the wrapping assembly of FIG. 7 in a folding configuration;

[0085] FIG. 10 is a perspective view taken from a front, top, right side of the wrapping assembly of FIG. 7 in a wrapping configuration;

[0086] FIG. 11 is a perspective view taken from a front, top, right side of the wrapping assembly of FIG. 7 back in the initial configuration, and the utensils being wrapped in the napkin;

[0087] FIG. 12 is a schematic illustration of connections between a controller, motor and actuators of the wrapping assembly of the apparatus of FIG. 1;

[0088] FIG. 13 is a perspective view taken from a rear, top, left side of one of the magazines of the apparatus of FIG. 1;

[0089] FIG. 14 is a perspective view of the magazine of FIG. 13 and utensils, with the magazine standing upright on its front side, and with portions of the magazine shown in transparency;

[0090] FIG. 15 is a perspective view taken from a front, top, right side of the magazine of FIG. 13 and utensils, with sets of dividers of the magazine being in a holding position and with portions of the magazine shown in transparency;

[0091] FIG. 16 is a perspective view taken from a front, top, right side of the magazine of FIG. 13 and utensils, with the sets of dividers of the magazine being in a retracted position and with portions of the magazine shown in transparency;

[0092] FIG. 17 is an exploded, perspective view, taken from a rear, top, right side of a portion of a base and fingers of the utensil picker of the apparatus of FIG. 1;

[0093] FIG. 18 is a left side view of the base and fingers of the utensil picker of the apparatus of FIG. 1;

[0094] FIG. 19 is a perspective view taken from a front, top, right side of the magazine of FIG. 13, utensils and the base and fingers of the utensil picker of FIG. 18, portions of the magazine and of the utensil picker being shown in transparency;

[0095] FIG. 20 is a left side elevation view of the base and fingers of the utensil picker of FIG. 18 with a fork connected thereto;

[0096] FIG. 21 is a right side elevation view of a comb of the apparatus of FIG. 1;

[0097] FIG. 22 is a perspective view taken from a front, top, left side of an alternative embodiment of an apparatus for wrapping a napkin around utensils;

[0098] FIG. 23 is a perspective view taken from a front, top, right side of a wrapping assembly of the apparatus of FIG. 22 with a napkin and utensils being disposed thereon and the wrapping assembly being in an initial configuration;

[0099] FIG. 24 is a perspective view taken from a front, top, right side of the wrapping assembly of FIG. 23 in a configuration intermediate to the initial configuration and a wrapping configuration;

[0100] FIG. 25 is a perspective view taken from a front, top, right side of the wrapping assembly of FIG. 23 in the wrapping configuration, and with a front portion of a frame of the wrapping



assembly being omitted; and

[0101] FIG. **26** is a perspective view taken from a front, top, right side of the wrapping assembly of FIG. **23** back in the initial configuration, and the utensils being wrapped in the napkin.

#### DETAILED DESCRIPTION

[0102] The present detailed description is intended to be a description of illustrative examples of the present technology.

[0103] The present technology relates to an apparatus **50** for wrapping a napkin **60** around utensils. In the present embodiment, the apparatus **50** includes a wrapping assembly **100**, a napkin delivery assembly **200** and a utensil delivery assembly **300**. The napkin delivery assembly **200** is configured to deliver a napkin **60** to the wrapping assembly **100**. The utensil delivery assembly **300** is configured to deliver utensils to the wrapping assembly **100** on the napkin **60** delivered by the napkin delivery assembly **200**. The wrapping assembly **100** is configured to wrap the napkin **60** around the utensils.

[0104] Referring to FIGS. **1** to **6**, the apparatus **50** will be described. In the present embodiment, the wrapping assembly **100** has a frame **110**. A driven roller **120**, an upper idler roller **130** and a lower idler roller **140** (best seen in FIG. **8**) are rotationally connected to the frame **110**. An endless belt **150** is wrapped around the driven roller **120**, the upper idler roller **130**, and the lower idler roller **140**. In the present embodiment, the napkin delivery assembly **200** includes a fan **210** that is movable. The utensil delivery assembly **300** includes three magazines **302**, **304**, **306** and a utensil picker **400**.

[0105] Referring to FIGS. **7** to **11**, the wrapping assembly **100** will be described in greater detail. As mentioned above, the wrapping assembly **100** has the driven roller **120**, the upper idler roller **130** and the lower idler roller **140**. A motor **122** (schematically shown in FIG. **12** and shown in FIGS. **22** to **26** with reference to a wrapping assembly **1100**) is operatively connected to the driven roller **120**. When the motor **122** is operated, the driven roller **120** rotates about a driven roller axis **124**. In some embodiments, the motor **122** is a stepper motor **122**, but other types of motors are contemplated.

[0106] The upper idler roller **130** is disposed inside the frame **110**, and is connected to the frame **110** via a pair of pivotable arms **132** that is disposed outside the frame **110**. The pair of pivotable arms **132** connects to the upper idler roller **130** through a pair of slots **112** that is defined in the frame **110**. The pair of pivotable arms **132** is further pivotally connected to the frame **110**, and pivots about a pivot axis **134**. Thus, the pair of slots **112** is arcuate to accommodate for the pivotal movement of the upper idler roller **130** and the pair of pivotable arms **132**. It is contemplated that in some embodiments, the pair of slots **112** could be linear. It is also contemplated that in some embodiments, only a single arm **132** could be provided. Two actuators **136** are connected to the pair of pivotable arms **132**, such that when the actuators **136** are actuated, the pair of pivotable arms **132** pivots about the pivot axis **134**, resulting in the movement of the upper idler roller **130**. It is contemplated that there could be more or less than two actuators. In the present embodiment, the actuators **136** are stepper motors. It is also contemplated that in some embodiments, the actuators **136** could be other types of motor or other types of actuators, such as pneumatic or hydraulic cylinders for example.

[0107] The upper idler roller **130** is movable between an initial position and a wrapping position. It is contemplated that in some embodiments, the upper idler roller **130** could be moved to positions intermediate these two positions. In the initial position, the upper idler roller **130** is generally vertically aligned with the driven roller **120**. In the wrapping position (shown in FIG. **10**), the upper idler roller **130** is horizontally closer to the driven roller **120** than when the upper idler roller **130** is in the initial position. The upper idler roller **130** is pivotable between the initial position and the wrapping position about the pivot axis **134**, in an arcuate path, but it is contemplated that in some embodiments, the upper idler roller **130** could move in a linear path. Thus, upon actuation of the actuator **136**, the upper idler roller **130** pivots from the initial position to the wrapping position, or

vice-versa.

[0108] The lower idler roller **140** is disposed inside the frame **110**, and is connected to the frame **110** via a pair of pivotable arms **142** that is disposed outside the frame **110**. The pair of pivotable arms **142** connects to lower idler roller **140** through a pair of slots **114** that are defined in the frame **110**. The pair of pivotable arms **142** is further pivotally connected to the frame **110**, and pivots about a pivot axis **144**. Thus, the pair of slots **114** is arcuate to accommodate for the pivotal movement of the lower idler roller **140** and the pair of pivotable arms **142**. It is contemplated that in some embodiments, the pair of slots **114** could be linear. It is also contemplated that in some embodiments, only a single arm **132** could be provided. The lower idler roller **140** is disposed vertically lower than the driven roller **120** and the upper idler roller **130**. Two actuators **146** are connected to the pair of pivotable arms **142**, such that when the actuators **146** are actuated, the pair of pivotable arms **142** pivots about the pivot axis **144**, resulting in the movement of the lower idler roller **140**. It is contemplated that there could be more or less than two actuators **146**. In the present embodiment, the actuators **146** are stepper motors. It is also contemplated that in some embodiments, the actuators **146** could be other types of motor or other types of actuators, such as pneumatic or hydraulic cylinders for example.

[0109] The lower idler roller **140** is movable between an initial position, a folding position and a wrapping position. It is contemplated that in some embodiments, the lower idler roller **140** could be moved to positions intermediate these three positions. In the initial position (shown in FIG. **8**), the lower idler roller **140** is vertically furthest to the driven roller **120**. In the folding position (shown in FIG. **9**), the lower idler roller **140** is closer to the driven roller **120** than in the initial position in a vertical direction. In the wrapping position (shown in FIG. **10**), the lower idler roller **140** is intermediate to the initial position and the folding position. In any one of the initial, folding and wrapping position, the lower idler roller **140** remains vertically lower than the driven roller **120** and the upper idler roller **130**. In the present embodiment, the lower idler roller **140** is pivotable between the initial position, the folding position and the wrapping position about the pivot axis **144**, in an arcuate path, but it is contemplated that in some embodiments, the lower idler roller **140** could be movable in a linear path. Thus, upon actuation of the actuator **146**, the lower idler roller **140** pivots from the initial position to the wrapping position and/or to the folding position.

[0110] As mentioned above, the endless belt **150** is wrapped around the driven roller **120**, the upper idler roller **130** and the lower idler roller **140**. In the present embodiment, the endless belt **150** is made from a textile material, though it is contemplated that other suitable materials could be used. As will be described in greater detail below, when the motor **122** is actuated, the endless belt **150** turns around the driven roller **120**, the upper idler roller **130** and the lower idler roller **140**, and when the motor **122** is stopped, the endless belt **150** stops turning.

[0111] Referring to FIGS. **8** to **11**, the various configurations of the wrapping assembly **100** will now be described in greater detail. In the present embodiment, the wrapping assembly **100** has an initial configuration, a folding configuration and a wrapping configuration. It is contemplated that in other embodiments, there could be more than three configurations.

[0112] In the initial configuration (seen in FIG. **8**), the upper idler roller **130** and the lower idler roller **140** are in their initial positions. In this configuration, the endless belt **150** is in tension about the driven roller **120**, the upper idler roller **130** and the lower idler roller **140**. In the initial configuration, a portion **152** of the endless belt **150** extending between the driven roller **120** and the upper idler roller **130** defines a flat surface. As will be described in greater detail below, the flat surface is adapted to receive the napkin **60** and utensils thereon.

[0113] In the folding configuration (seen in FIG. **9**), the upper idler roller **130** is in the initial position, while the lower idler roller **140** is in the folding position. The positioning of the upper idler roller **130** and the lower idler roller **140** result in the endless belt **150** not being in tension between the driven roller **120** and the upper idler roller **130**. The portion **152** of the endless belt extending between the driven roller **120** and the upper idler roller **130** droops to define a V-shape.

As will be described in greater detail below, the napkin **60** and the utensils are received at a bottom of the V-shape.

[0114] In the wrapping configuration (seen in FIG. **10**), the upper idler roller **130** and the lower idler roller **140** are in their wrapping positions. The position of the upper idler roller **130** and the lower idler roller **140** result in the portion **152** of the endless belt **150** extending generally downward from the driven roller **120** to a low point, and generally upward from the low point to the upper idler roller **130**. Thus, the endless belt **150** is taut compared to when the endless belt **150** was in the folding configuration. As will be described in greater detail below, the portion **152** receives the napkin and the utensil at the low point, such that when the motor **122** is operated, and the driven roller **120** rotates, the rotation causes the endless belt **150** to turn around the driven roller **120**, the upper idler roller **130** and the lower idler roller **140**, which thereby results in the napkin wrapping around the utensils, yielding the wrapped utensil, shown in FIG. **11**.

[0115] Referring to FIG. **12**, in the present embodiment, the apparatus **50** also includes a controller **70**. The controller **70** is in communication with the fan **210**, a motor **229**, a motor **239**, a motor **418** and a motor **419**, the motor **122**, the actuators **136** and the actuators **146** such that the controller **70** controls the fan **210**, the motor **229**, the motor **239**, the motor **418**, the motor **419**, the motor **122**, the actuators **136** and the actuators **146**. It is contemplated that in some embodiments, the controller **70** could be omitted.

[0116] In the present embodiment, the controller **70** is programmed to control the actuators **136** and the actuators **146** to consecutively position the wrapping assembly **100** in the initial configuration, in the folding configuration and then in the wrapping configuration. The controller **70** then controls the motor **122** to rotate the driven roller **120**, which turns the endless belt **150** around the driven roller **120**, the upper idler roller **130** and the lower idler roller **140**. The controller **70** then controls the motor **122** to stop the rotation of the driven roller **120**. The controller **70** then finally controls the actuators **136** and the actuators **146** to position the wrapping assembly **100** back in the initial configuration. The controller **70** thus automates the wrapping of the napkin **60** around the utensils. As will be described in greater detail below, the controller **70** also automates the delivery of a napkin to the endless belt **150**, and the delivery of utensils to the endless belt **150**.

[0117] Turning back to FIGS. **1** to **6**, the napkin delivery assembly **200** adapted for delivering a napkin to the endless belt **150** will now be described in more detail. In the present embodiment, the napkin delivery assembly **200** includes a fan **210**. The fan **210** has fan blades **212** and a grill (not shown). In the present embodiment, when the fan **210** is turned on, the fan **210** suctions air through a bottom thereof. The grill prevents the napkin from being suctioned into the fan blades **212**. In the present embodiment, the fan **210** is vertically and horizontally movable, as the fan **210** is operatively connected to arms **220**, **230**. In the present embodiment, the arms **220**, **230** are T-tracks. The arm **220** has an upper track **222** and a lower track **224**. The lower track **224** is connected to the upper track **222** via a pair of T-slot wheels **226** and a bracket **228**. More precisely, the pair of T-slot wheels **226** is connected to the bracket **228**, and to the lower track **224**. The bracket **228** is fixedly connected to the upper track **222**. Thus, when the pair of T-slot wheels **226** is actuated by the motor **229**, the pair of T-slot wheels **226** roll on the lower track **224**, such that the lower track **224** moves in the vertical direction. In the present embodiment, the motor **229** is a stepper motor. The upper track **222** is connected to the two arms **230** by two pairs of T-slot wheels **236** and two brackets **238**. More precisely, each of the two pairs of T-slot wheels **236** is connected to one of the brackets **238**, and to the arm **230**. The brackets **238** is fixedly connected to the upper track **222**. Thus, when the pair of T-slot wheels **236** that is connected to the motor **239**, is actuated by the motor **239**, the two pairs of T-slot wheels **236** roll along the arm **230**, such that the upper track **222** moves along the arms **230**. In the present embodiment, the motor **239** is a stepper motor. It is contemplated that in other embodiments, the fan **210** could be movable by other mechanisms. For instance, it is contemplated that the fan **210** could move from one position to another by a mechanical arm. In the present embodiment, the fan **210** is movable from a stack of napkins **62** to the endless belt **150**. To

deliver a napkin to the endless belt **150**, the fan **210** is moved above the stack of napkins **62**. The fan **210** is then moved down until a top of the stack of napkins **62** is reached. The fan **210** is then turned on, and air begins to be suctioned, which results in the fan **210** picking up a napkin **60**. The fan **210**, and thus the napkin **60**, is then moved to a position above the endless belt **150**. When in position, the fan **210** is turned off, which releases the napkin **60** onto the endless belt **150**. These steps are repeated for other napkins. In the present embodiment, the controller **70** turns the fan **210** on and off, and controls the movement of the fan **210** via the arms **220**, **230**.

[0118] The utensil delivery assembly **300** adapted for delivering utensils to the endless belt **150** will now be described in more detail. In the present embodiment, the utensil delivery assembly **300** includes the three magazines **302**, **304**, **306** and the utensil picker **400**. The utensil picker **400** is adapted to pick up utensils from each of the three magazines **302**, **304**, **306** and deliver the utensils to the endless belt **150** on top of a napkin **60**. In the present embodiment, the magazine **302** holds forks, the magazine **304** holds spoons, and the magazine **306** holds knives.

[0119] Referring to FIGS. **13** to **16**, the magazines **302**, **304**, **306** will be described in greater detail. The magazines **302**, **304**, **306** are disposed next to each other, and are adapted for storing utensils therein. The magazines **302**, **304**, **306** also defines apertures (shown in FIGS. **1**, **2**, **3**, **5** and **6**) to permit water and/or soap to flow through the magazines **302**, **304**, **306**. It is contemplated that in other embodiments, there could be more or less than three magazines. As the magazines **302**, **304**, **306** are identical, only the magazine **302** will be described in detail herein.

[0120] The magazine **302** has a receptacle **310**. In the present embodiment, the receptacle **310** has a front side **311**, a rear side **312**, a top side **316**, a bottom side **318**, a left side **319** and right side **320**. It is contemplated that in other embodiments, the receptacle **310** could have another shape. The rear side **312** is opposite to the front side **311**. The top side **316** extends between the front side **311** and the rear side **312**. The bottom side **318** is opposite to the top side **316**, and also extends between the front side **311** and the rear side **312**. The right side **320** is opposite to the left side **319**. The front, rear, top and bottom sides **311**, **312**, **316**, **318** extend between the left and right sides **319**, **320**. In the present embodiment, the rear side **312** defines an opening **313** (FIG. **14**), and the top side **316** defines an opening **317**, which faces up when the magazine **302** rests on its bottom side **318**.

[0121] The magazine **302** has a lid **324** that is hinged to the lower, rear corner of the receptacle **310**. It is contemplated that in other embodiments, the lid **324** could be hinged elsewhere, or could be removable. The lid **324** selectively closes the opening **313**. It is contemplated that the lid **324** could be omitted. It is also contemplated that the lid **324** could be another type of lid, such as a slidable lid.

[0122] The magazine **302** has four sets of dividers **330**, **332**, **334**, **336** disposed in the receptacle **310**. It is contemplated that in other embodiments, there could be more or less than four sets of dividers.

[0123] In the present embodiment, the set of dividers **330** is disposed next to the right side **320**, and the set of dividers **332** is disposed next to the left side **319**. The sets of dividers **330**, **332** are disposed at a same distance from the front side **311**. Likewise, the set of dividers **334** is disposed next to the right side **320**, and the set of dividers **336** is disposed next to the left side **319**. The sets of dividers **334**, **336** are disposed at a same distance from the front side **311**. In the present embodiment, the set of dividers **330**, **332** are disposed between the front side **311** and the set of dividers **334**, **336**.

[0124] It is contemplated that in some embodiments there could only be two sets of dividers, where the two sets of dividers are disposed next to the left side **319**, and one of the two sets of dividers is closer to the rear side **312**, such that one of the sets of dividers is between the rear side **312** and the other set of dividers.

[0125] In the present embodiment, the set of dividers **330** has dividers **350** that are connected perpendicularly to a shaft **340** and has a knob **360** that is on a top end thereof, the set of dividers **332** has dividers **352** that are connected perpendicularly to a shaft **342** and has a knob **362** that is on

a top end thereof, the set of dividers **334** has dividers **354** that are connected perpendicularly to a shaft **344** and has a knob **364** that is on a top end thereof and the set of dividers **336** has dividers **356** that connected perpendicularly to a shaft **346** and has a knob **366** that is on a top end thereof. [0126] As the sets of dividers **330**, **332**, **334**, **336** are identical, only the set of dividers **330** will be described in detail herein. The set of dividers **330** has eleven dividers **350**. It is contemplated that there could be more or less than eleven dividers **350**. In the present embodiment, the dividers **350** are spacers. In the present embodiment, the eleven dividers **350** are generally perpendicular to the shaft **340**, though it is contemplated that in some embodiments, the dividers **350** could be slanted with respect to the shaft **340**. The dividers **350** are spaced apart from each other between the top and bottom sides **316**, **318**. In other words, the dividers **350** are vertically spaced. The shaft **340** extends in the receptacle **310**, and protrudes therefrom such that the shaft **340** passes through the opening **317**. The knob **360** is on the top end of the shaft **340** that protrudes from the receptacle **310**. It is contemplated that in some embodiments, the shaft **340** could be omitted, while the set of dividers **330** remains. The set of dividers **330** is movable between a holding position and a retracted position. The set of dividers **330** can be moved between the holding position and the retracted position by manually rotating the knob **360**, which rotates the shaft **340**. It is contemplated that in some embodiments, the set of dividers **330** could be movable between the holding position and the retracted position without the help of the shaft **340** and/or the knob **360**. In some embodiments, the knob **360** and/or the shaft **340** could be rotated by an actuator.

[0127] It is contemplated that in some embodiments, turning the knob **360** could simultaneously rotate the shafts **340**, **342**, such that the sets of dividers **330**, **332** are both moved from the holding position to the retracted position upon rotation of the knob **360**. It is also contemplated that in some embodiments, turning the knob **360** could simultaneously rotate the shafts **340**, **342**, **344**, **346**, such that the sets of dividers **330**, **332**, **334**, **336** all move from the holding position to the retracted position upon rotation of the knob **360**. It is contemplated that any of the knobs **360**, **362**, **364**, **366** could be rotated to reach this effect. In such embodiments, the magazine **302** has gears, belts and/or pulleys connecting the shafts **340**, **342**, **344**, **346**.

[0128] Referring to FIGS. **14** and **15**, the sets of dividers **330**, **332**, **334**, **336** when they are in the holding position will now be described.

[0129] In the holding position, the dividers **350** of the set of dividers **330** extend about halfway across the receptacle **310** toward the left side **319**, whereas the dividers **352** of the set of dividers **332** extend about halfway across the receptacle **310** toward the right side **320**. In the holding position, each divider **350** is coaxial with a corresponding divider **352**. Likewise, the dividers **354** of the set of dividers **334** extend about halfway across the receptacle **310** toward the left side **319**, whereas the dividers **356** of the set of dividers **336** extend about halfway across the receptacle **310** toward the right side **320**. In this position, each divider **354** is coaxial with a corresponding divider **356**. It is contemplated that in some embodiments, the dividers **350**, **352**, **354**, **356** could extend more or less than about half-way across the receptacle **310**.

[0130] It is contemplated that in some embodiments, there could be only two sets of dividers, where one of the two sets of dividers is disposed next to the left side **319** and the other set of dividers is disposed next to the right side **320**. In such embodiments, the two sets of dividers are at a same distance from the front side **311**, and in the holding position, the dividers of one of the sets of dividers extend to the right side **320**, and the dividers of the other set of dividers extend to the left side **319**.

[0131] When the sets of dividers **330**, **332**, **334**, **336** are in the holding position, as shown in FIG. **15**, utensils can be inserted in the magazine **302**, from the opening **313**, between the dividers **350**. To do so, the magazine **302** is placed upright on the front side **311**, such that the opening **313** and the lid **324** are oriented in the upward direction. The lid **324** is then opened. A utensil is then put inside each space defined by the sets of dividers **330**, **332**, **334**, **336**, until the magazine **302** is fully loaded. The lid **324** is then closed. The dividers **350**, **352**, **354**, **356** keep the utensils apart from

each other, such that placing the magazine **302** in a dishwasher would permit adequate cleaning of the utensils.

[0132] Referring now to FIG. **16**, the sets of dividers **330**, **332**, **334**, **336** when they are in the retracted position will now be described.

[0133] In the retracted position, the dividers **350** of the set of dividers **330** and the dividers **352** of the set of dividers **332** extend toward the front side **311**. It is contemplated that in some embodiments, the dividers **350**, **352** could extend toward the rear side **312** in the retracted position. It is also contemplated that in some embodiments, the dividers **350** could extend toward the rear side **312**, whereas the dividers **352** could extend toward the front side **311** or vice-versa. Similarly, the dividers **354** of the set of dividers **334** and the dividers **356** of the set of dividers **336** extend toward the rear side **312**. It is contemplated that in some embodiments, the dividers **354**, **356** could extend toward the front side **311** in the retracted position. It is also contemplated that in some embodiments, the dividers **354** could extend toward the rear side **312**, whereas the dividers **356** could extend toward the front side **311** or vice-versa.

[0134] It is contemplated that in some embodiments there could only be two sets of dividers, where one of the sets of dividers is disposed next to the left side **319** and the other set of dividers is disposed next to the right side **320**. In such embodiments, one of the sets of dividers is between the front side **311** and the other set of dividers, and in the retracted position, the dividers of one of the sets of dividers extend toward the rear side **312**, and the dividers of the other set of dividers extend toward the front side **311**.

[0135] When the sets of dividers **330**, **332**, **334**, **336** are moved from the holding position to the retracted position while the magazine **302** is storing utensils, and the receptacle **310** is lying on its bottom side **318**, as shown in FIG. **16**, the utensils that were inserted between the dividers **350**, **352**, **354**, **356** and kept apart from each other, fall in a stack on the bottom side **318**. The utensils can be removed from the stack by the opening **317**.

[0136] Referring to FIGS. **1**, **2** and **17** to **20**, the utensil picker **400** will now be described in greater detail. In the present embodiment, the utensil picker **400** is adapted to pick up one utensil from each of the magazines **302**, **304**, **306**. It is contemplated that in other embodiments, the utensil picker **400** could pick up more or less utensils from more or less magazines.

[0137] The utensil picker **400** has two movable arms **410** that are spaced from one another. In the present embodiment, the utensil picker **400** also has two arms **415**, to which the two movable arms **410** are connected. In the present embodiment, the movable arms **410** are movable in the horizontal and vertical directions, along the two arms **415**. It is contemplated that in some embodiments, the utensil picker **400** could have more or less than two movable arms **410** and/or could have more or less than two arms **415**. In the present embodiment, the arms **410** and **415** are T-tracks. Each arm **410** made of an upper track **411** and a lower track **412**.

[0138] As the two arms **410** are similar, only one arm **410** and the connections thereof will be described. The lower track **412** is connected to the upper track **411** via a pair of T-slot wheels **413** and a bracket **414**. More precisely, the pair of T-slot wheels **413** is connected to the bracket **414**, and to the upper track **411**. The bracket **414** is fixedly connected to the lower track **412**. Thus, when the pair of T-slot wheels **413** is actuated by a motor **418**, the pair of T-slot wheels **413** climb the upper track **411** such that the lower track **412** can move up or down the upper track **411**. In the present embodiment, the motor **418** is a stepper motor. The upper track **411** is connected to the arm **415** by a pair of T-slot wheels **416** and a bracket **417**. More precisely, the pair of T-slot wheels **416** is connected to the bracket **417**, and to the arm **415**. The bracket **417** is fixedly connected to the upper track **411**. Thus, when the pair of T-slot wheels **416** is actuated by a motor **419**, the pair of T-slot wheels **416** roll across the arm **415** such that upper track **411** moves along the arms **415**. In the present embodiment, the motor **419** is a stepper motor. In the present embodiment, the motors **418**, **419** are controlled by the controller **70**.

[0139] The utensil picker **400** also has three bases **420**, **422**, **424** that are connected to the two

movable arms **410**. It is contemplated that in other embodiments, there could be more or less than three bases depending on the number of magazines being used. As the three bases **420**, **422**, **424** and the features connected thereto are identical, only the base **420** and the features connected thereto will be described in detail herein.

[0140] In the present embodiment, the base **420** has an upper portion **430** and a lower portion **432**. The upper portion **430** is connected to the two movable arms **410**. Two hinges **434** connect the upper portion **430** to the lower portion **432**.

[0141] In the present embodiment, the utensil picker **400** has five fingers **450** that are arranged in a line and connected under the base **420**, to the lower portion **432**. It is contemplated that in some embodiments, there could be two, three, four or more fingers connected to the base **420**. It is contemplated that in some embodiments, the fingers **450** could be arranged in a shape other than a line.

[0142] Each one of the fingers **450** has a housing **460** that is connected to the lower portion **432** of the base **420**. Each one of the fingers **450** also includes a spring **452** which is housed in the housing **460**. In the present embodiment, the springs **452** can be inserted in their respective housings **460** by pivoting the upper portion **430** relative to the lower portion **432** using the hinges **434**, thereby revealing the upper open ends of the housings **460**. It is contemplated that in some embodiments, the springs **452** could be other resiliently deformable members. In other embodiments, the springs **452** could be omitted.

[0143] Each one of the fingers **450** also includes a fingertip **454** that is connected to a lower end of the spring **452** and that is opposite to the base **420** (i.e., fingertip **454** is below the corresponding base **420**). Each one of the fingertips **454** is movable in a vertical direction with respect to the base **420**, and is biased away from the base **420** by the spring **452**. In the present embodiment, each one of the fingertips **454** is also slidable in the corresponding housing **460**. As will be described in greater detail below, the fingers **450** are adapted to pick up utensils of various shapes.

[0144] Each one of the fingers **450** also includes a permanent magnet **456** provided at a lower end of the fingertip **454**. It is contemplated that in some embodiments, the permanent magnet **456** could be another type of attachment such as, for instance, an electro-magnet, a suction cup and/or a nozzle that suctions air. As will be described in greater detail below, the permanent magnet **456** is adapted for attaching a utensil to the fingers **450**.

[0145] In some embodiments, as mentioned above, the springs **452** could be omitted. In such embodiments, a weight of the fingertips **454** and a weight of the corresponding permanent magnets **456** can result in the fingertips **454** being pulled down away from the base **420**.

[0146] Referring to FIGS. **4** to **6**, **19** and **20**, the utensil picker **400** as it picks up a utensil from the magazines **302**, **304**, **306**, where the sets of dividers **330**, **332**, **334**, **336** are in the retracted position, will now be described. The two movable arms **410** move the utensil picker **400** such that fingers **450** of each of the bases **420**, **422**, **424** are respectively aligned with a corresponding one of the magazines **302**, **304**, **306**. As such, when the utensil picker **400** moves vertically down, as shown in FIG. **4**, the fingers **450** of the bases **420**, **422**, **424** are respectively received in the magazines **302**, **304**, **306**. In the present embodiment, the fingers **450** of the base **420** are configured to pick up a single fork, at a time from the magazine **302**, the fingers **450** of the base **422** are configured to pick up a single spoon at a time from the magazine **304** and the fingers **450** of the base **424** are configured to pick up a single knife at a time from the magazine **306**. It is contemplated that in some embodiments, the fingers **450** of one of the bases **420**, **422**, **424** could be configured to pick up more than one utensil at a time.

[0147] Focusing now on the base **420** and the features connected thereto, as mentioned above, the fingers **450** can pick up utensils of various shapes. When the utensil being picked up is not flat, the fingertips **454** can move in their housings **460** to partially conform to the shape of the utensil. As such, when the utensil has a portion extending toward the fingers **450**, the fingertips **454** can slide inwards.

[0148] For instance, referring to FIG. 20, where the fork **80** has a curved handle **92**, the fingertip **454** retract in the housings **460** toward the base **420** to conform to the shape of the handle **92**. More specifically, as can be seen for this shape of handle **92**, the outer fingertips **454** are more retracted in their respective housings **460** than the three central fingertips **454**. This allows the fingers **450** to connect to the utensil at multiple points and helps ensure that the utensil will be picked up by the utensil picker **400**. As mentioned above, the utensil picker **400** can pick up utensils of various shapes.

[0149] Referring to FIGS. 1 to 6 and 21, in the present embodiment, the apparatus **50** also has a comb **500** and a chute **550** which will now be described in greater detail. The comb **500** is disposed above the wrapping assembly **100**, while the chute **550** is disposed vertically between the comb **500** and the wrapping assembly **100**. It is contemplated that in some embodiments, the comb **500** and/or the chute **550** could be omitted.

[0150] The comb **500**, which in the present embodiment is connected to the frame **110**, has six upwardly extending teeth **502** that define five spaces **504** (best seen in FIG. 21). It is contemplated that in some embodiments, the number of teeth and spaces could be different than illustrated. The five spaces **504** are adapted for each receiving one of the five fingers **450** therethrough.

[0151] The chute **550**, which in the present embodiment is also connected to the frame, is curved. It is contemplated that in other embodiments, the chute **550** could be a flat surface. The chute **550** is oriented such that the utensils falling thereon are guided to fall on the wrapping assembly **100**.

[0152] As will be described in greater detail below, in the present embodiment, when the utensil picker **400** has picked up utensils, and the movable arms **410** move the fingers **450** through the spaces **504** in the comb **500**, the teeth **502** of the comb **500** separate the utensils from the ends of the fingers **450** as the fingers **450** pass through the comb **500** and the utensils fall toward the chute **550**. The chute **550** then slows the fall of the utensils and directs them onto the wrapping assembly **100**. It is contemplated that in embodiments where the comb **500** is omitted, the movable arms **410** would move the utensil picker **400** until it is aligned with the chute **550**, and drop the utensils thereon via some other mechanism.

[0153] Referring back to FIGS. 1 to 11, a method for providing three utensils **80**, **82**, **84** wrapped in the napkin **60** will be described.

[0154] Referring to FIGS. 1 to 3, the method includes placing the napkin **60** on the wrapping assembly **100**, with the wrapping assembly **100** in the initial configuration. This includes picking up a napkin **60** from the stack of napkins **62** with the fan **210**, by turning the fan **210** on when the fan **210** is above the stack of napkins **62**. The fan **210**, and thus the napkin **60**, then moves from the stack of napkin **62**, until the fan **210** is above the wrapping assembly **100**. The napkin **60** is then placed on the portion **152** of the wrapping assembly **100** by turning off the fan **210**. The fan **210** is then returned to the stack of napkins **62**.

[0155] Referring to FIGS. 4 to 6, then the three utensils: a fork **80**, a spoon **82** and a knife **84** are to be placed on the napkin **60**. In the present embodiment, this includes picking up the three utensils **80**, **82**, **84** with the utensil picker **400** from the magazines **302**, **304**, **306**. It is contemplated that in some embodiments, the utensil picker **400** could pick more or less than the three utensils **80**, **82**, **84**. More precisely, in the present embodiment, the movable arms **410** move the utensil picker **400** such that the fingers **450** of the bases **420**, **422**, **424** are aligned with the magazines **302**, **304**, **306**. The movable arms **410** then move the utensil picker **400** downwardly such that the fingers **450** are received into the magazines **302**, **304**, **306**. In the present embodiment, the permanent magnets **456** of the fingers **450** of the base **420** that are received in the magazine **302** connect to the fork **80**, the permanent magnets **456** of the fingers **450** of the base **422** that are received in the magazine **304** connect to the spoon **82** and the permanent magnets **456** of the fingers **450** of the base **424** that are received in the magazine **306** connect to the knife **84**. The movable arms **410** then move upwardly until the fingers **450** are vertically aligned with the spaces **504** of the comb **500**. The movable arms **410** then move toward the comb **500**.



[0156] The fork **80**, spoon **82** and knife **84** are then dropped on the chute **550** that is disposed above the wrapping assembly **100**. The fork **80**, the spoon **82** and the knife **84** are dropped from the utensil picker **400** onto the chute **550**, as the fingers **450** pass through the spaces **504**, and the fork **80**, the spoon **82** and the knife **84** encounter the comb **500** which separates them from the fingers **450**. It is contemplated that there could be more or less than three utensils being placed on the napkin **60**.

[0157] Once the utensils **80**, **82**, **84** are on the napkin **60**, the wrapping assembly **100** is configured in the folding configuration, as shown in FIG. **9**, by lifting the lower idler roller **140** in an arcuate path, as described above. This causes the endless belt **150** to sag between the driven roller **120** and the upper idler roller **130**, and thereby causes the napkin **60** and the utensils **80**, **82**, **84** to be received in the sag.

[0158] The wrapping assembly **100** is then configured in the wrapping configuration, as shown in FIG. **10**, by moving the upper idler roller **130** toward the driven roller **120** in an arcuate path, and by lowering the lower idler roller **140** in an arcuate path to increase the tension in the endless belt **150** as described above.

[0159] The endless belt **150** is then turned around the driven roller **120**, the upper idler roller **130** and the lower idler roller **140** by the motor **122** rotating the driven roller **120**, thereby wrapping the napkin **60** around the fork **80**, the spoon **82** and the knife **84**. Once the endless belt **150** has moved sufficiently to properly wrap the napkin **60** around the fork **80**, the spoon **82** and the knife **84**, the motor **122** is stopped, thereby stopping to turn the endless belt **150**. This could be determined by a predetermined amount of time by which the motor **122** is to be operated or by a predetermined number of rotation of the driven roller or by some other factor.

[0160] The wrapping assembly **100** is then returned to the initial configuration by moving the upper idler roller **130** away from the driven roller **120** in an arcuate path, and by lowering the lower idler roller **140**. This causes the fork **80**, the spoon **82** and the knife **84** that are wrapped in the napkin **60** to be disposed on the flat horizontal portion **152** of the endless belt **150**. It is contemplated that a taping apparatus could be added to apply tape, or a band of paper with adhesive, around the napkin **60** to secure the napkin **60** around the utensils **80**, **82**, **84**. The wrapped utensils are then removed manually from the wrapping assembly **100**. It is contemplated that an automated mechanism could be used to pick up the wrapped utensils from the wrapping assembly **100**. It is also contemplated that the motor **122** of the wrapping assembly **100** could be turned on to move the wrapped utensils off the endless belt **150** into a basket or some other receptacle.

[0161] It is contemplated that in some embodiments, some of the steps of the methods could be done simultaneously, so long as the napkins are delivered to the endless belt **150** before the utensils

[0162] In the present embodiment, the method described above is automated by the controller **70**.

[0163] It is contemplated that the wrapping assembly **100** could be used without the napkin delivery assembly **200** or without the utensil delivery assembly **300** or without both. It is also contemplated that in some embodiments, the apparatus **50** could have one or two of the wrapping assembly **100**, the napkin delivery assembly **200** and the utensil delivery assembly **300**, but with one or two of a wrapping assembly, a napkin delivery assembly and a utensil delivery assembly that is/are different from the ones described above. Similarly, it is contemplated that in some embodiments the magazines **302**, **304**, **306** could be used with a different type of utensil picker and that the utensil picker **400** could be used with a different type of magazines.

[0164] Referring now to FIGS. **22** to **26**, an alternative embodiment of the apparatus **50**, namely apparatus **1050**, includes a wrapping assembly **1100**, a napkin delivery assembly **1200**, a utensil delivery assembly **1300** and the comb **500**. Similarly to the apparatus **50**, the napkin delivery assembly **1200** is configured to deliver the napkin **60** to the wrapping assembly **1100**. The utensil delivery assembly **1300** along with the comb **500** are configured to deliver the utensils **80**, **82**, **84** to the wrapping assembly **1100** on the napkin **60** delivered by the napkin delivery assembly **1200**. In the present embodiment, the chute **550** is omitted, such that when the utensils **80**, **82**, **84** picked up

by the utensil delivery assembly **1300** encounter the comb **500** and are dropped, the utensils **80, 82, 84** fall directly on the wrapping assembly **1100**, rather than falling on the chute **550** and then falling on the wrapping assembly **1100**. The wrapping assembly **1100** is configured to wrap the napkin **60** around the utensils **80, 82, 84**.

[0165] Features of the apparatus **1050**, the wrapping assembly **1100**, the napkin delivery assembly **1200** and the utensil delivery assembly **1300** that are, respectively, generally similar to those of the apparatus **50**, the wrapping assembly **100**, the napkin delivery assembly **200** and the utensil delivery assembly **300** described above have been labeled with the same reference numerals and will not be described again in detail. That being said, the configuration of the apparatus **1050** differs slightly from the configuration of the apparatus **50**. For instance, the configuration of the arms **220, 230** of the napkin delivery assembly **1200** are different from the configuration of the arms **220, 230** of the napkin delivery assembly **200** and the configuration of the arms **410, 415** of the utensil delivery assembly **1300** are different from the configuration of the arms **410, 415** of the utensil delivery assembly **300**. Additionally, the motors **229, 239** of the napkin delivery assembly **1200**, and the motors **418, 419** of the utensil delivery assembly **1300** have been replaced by motorized lead screw actuators. Actuation of the motorized lead screw actuators **229, 239, 418, 419** result in the movement of the napkin delivery assembly **1200** and the utensil delivery assembly **1300**. Limit switches (not shown) control the motorized lead screw actuators **229, 239, 418, 419** to limit movement of the napkin delivery assembly **1200** and the utensil delivery assembly **1300**.

[0166] Turning to FIGS. **23** to **26**, the wrapping assembly **1100** has a driven roller **1120**, an idler roller **1130** and an idler roller **1140**, all three of which are rotationally connected to the frame **110**. An endless belt **150** is wrapped around the driven roller **1120** and the idler rollers **1130, 1140**.

[0167] In the present embodiment, the driven roller **1120**, which is operatively connected to the motor **122**, is vertically below the idler rollers **1130, 1140**, whereas the idler rollers **1130, 1140** are generally vertically aligned with one another. It is contemplated that in some embodiments, the motor **122** could be connected to another one of the rollers. For instance, in other embodiments, the idler roller **1130** could be configured to be the driven roller.

[0168] The idler roller **1130** is disposed inside the frame **110**, and is rotationally connected thereto about a rotation axis **1131**, which is fixed relative to the frame **110**.

[0169] The idler roller **1140** is disposed inside the frame **110**, and is connected to the frame **110** via a movable member **1142** (best seen in FIG. **25**) that is also disposed inside the frame **110**. Ends of a shaft of the idler roller **1140** extends out through a pair of rectilinear slots **1114** that are defined in the frame **110**. The movable member **1142** is configured to move along a rectilinear path in the slots **1114** with respect to the frame **110**. An actuator **1146** is operatively connected to the movable member **1142**. In the present embodiment, the actuator **1146** is a motorized lead screw actuator, though it is contemplated that other types of actuators **1146** could be used. The actuator **1146** is operatively connected to limit switches **1147** which are configured to control the actuator **1146**. Upon actuation of the actuator **1146**, the movable member **1142** moves in a rectilinear path, guided by the slots **1114**, which results in the movement of the idler roller **1140**.

[0170] The idler roller **1140** is movable between an initial position a wrapping position. It is contemplated that in some embodiments, the idler roller **1140** could be moved to positions intermediate these two positions. In the initial position (shown in FIG. **23**), the idler roller **1140** is furthest to the driven roller **1120** and to the idler roller **1130**. As the idler roller **1140** moves from the initial position toward the wrapping position, the idler roller **1140** gets closer to the driven roller **1120** and to the idler roller **1130**. In the wrapping position (shown in FIG. **25**), the idler roller **1140** is closest to the driven roller **1120** and to the idler roller **1130**. Thus, upon actuation of the actuator **1146**, the idler roller **1140** moves from the initial position toward the wrapping position or vice-versa. In some embodiments, the idler roller **1140** could be configured to stop at a position intermediate to the initial and wrapping positions. The limit switches **1147** are configured to determine when the idler roller **1140** reaches the initial and wrapping positions, and to control the

actuator **1146** to stop the actuator **1146** once the initial or wrapping positions are reached.

[0171] In the initial configuration (seen in FIG. 23), the idler roller **1140** is in its initial position. In this configuration, the endless belt **150** is in tension about the driven roller **1120** and the idler rollers **1130**, **1140**. In the initial configuration, the portion **152** of the endless belt **150** extending between the idler rollers **1130**, **1140** defines a generally flat surface.

[0172] Intermediate to the initial and wrapping configurations, (seen in FIG. 24), the positioning of the idler roller **1140** results in the endless belt **150** not being in tension between the idler rollers **1130**, **1140**. The portion **152** of the endless belt extending between the idler rollers **1130**, **1140** droops to define a V-shape where the napkin **60** and the utensils **80**, **82**, **84** are configured to be received at a bottom of the V-shape.

[0173] In the wrapping configuration (seen in FIG. 25), the idler roller **1140** is in its wrapping position. The position of the idler roller **1140** results in the portion **152** of the endless belt **150** extending generally downward from the idler roller **1130** to a low point, and generally upward from the low point to the idler roller **1140**. The endless belt **150** is configured to be taut compared to when the wrapping apparatus **1050** is intermediate to the initial and wrapping configurations, in part due to the weight of the utensils **80**, **82**, **84**.

[0174] The apparatus **1050** is configured to, by using the napkin delivery assembly **1200** and the utensil delivery assembly **1300**, place a napkin and utensils on the wrapping assembly **1100**. As the method for accomplishing this is similar to the method for apparatus **50**, it will not be re-described in detail herewith.

[0175] Once utensils **80**, **82**, **84** are placed on the napkin **60**, as shown in FIG. 24, the idler roller **1140** is moved toward the idler roller **1130**, as described above. This causes the endless belt **150** to sag between the idler rollers **1130**, **1140**, and thereby causes the napkin **60** and the utensils **80**, **82**, **84** to be received in the sag.

[0176] Eventually, when the idler roller **1140** reaches the wrapping position, the wrapping assembly **1100** is in the wrapping configuration, as shown in FIG. 25.

[0177] The endless belt **150** is then turned around the driven roller **1120** and the idler rollers **1130**, **1140** by the motor **122** rotating the driven roller **1120**, thereby wrapping the napkin **60** around the utensils **80**, **82**, **84**. Once the endless belt **150** has moved sufficiently to properly wrap the napkin **60** around the utensils **80**, **82**, **84**, the motor **122** is stopped, thereby stopping to turn the endless belt **150**.

[0178] The wrapping assembly **100** is then returned to the initial configuration by moving the idler roller **1140** away from the driven roller **1120** and the idler roller **1130**, toward the initial position. This causes the utensils **80**, **82**, **84** that are wrapped in the napkin **60** to be disposed on the generally flat horizontal portion **152** of the endless belt **150** as shown in FIG. 26.

[0179] Similarly to the apparatus **50**, the method described hereabove with reference to the apparatus **1050** is automated by the controller **70**.

[0180] Modifications and improvements to the above-described embodiments of the present technology may become apparent to those skilled in the art. The foregoing description is intended to be exemplary rather than limiting. The scope of the present technology is therefore intended to be limited solely by the appended claims.

## Claims

1. A utensil picker for picking up at least one utensil from at least one utensil magazine storing a plurality of utensils, the utensil picker comprising: at least one movable arm; at least one base connected to the at least one movable arm; and at least two fingers connected to each base of the at least one base, each finger of the at least two fingers comprising: a fingertip operatively connected to the at least one base, the fingertip being configured to move vertically with respect to the at least one base; and an attachment provided at an end of the fingertip for attaching one utensil of the at

- least one utensil to the finger.
2. The utensil picker of claim 1, wherein the attachment is a permanent magnet.
3. The utensil picker of claim 1, wherein the attachment is an electro-magnet.
4. The utensil picker of claim 1, further comprising at least one track, the at least one movable arm being movable along the at least one track.
5. The utensil picker of claim 1, wherein the at least two fingers are connected under the at least one base.
6. The utensil picker of claim 1, wherein each base of the at least one base comprises: an upper portion connected to the at least one movable arm; a lower portion connected to the upper portion; and a hinge connecting the upper portion to the lower portion.
7. The utensil picker of claim 1, wherein each finger of the at least two fingers further comprises a spring connected to the at least one base, the spring biasing the fingertip away from the at least one base.
8. The utensil picker of claim 1, wherein: each finger of the at least two fingers further comprises a housing connected to the at least one base; and for each finger, the fingertip is at least partially housed in the housing.
9. The utensil picker of claim 8, wherein each housing has an open end for receiving the fingertip.
10. The utensil picker of claim 8, wherein for each finger, the fingertip is slidable in the housing.
11. The utensil picker of claim 1, wherein the at least two fingers are at least three fingers arranged in a line.
12. The utensil picker of claim 11, wherein the at least three fingers are three or four fingers.
13. An apparatus for wrapping a napkin around at least one utensil comprising: at least one magazine for storing the at least one utensil; a wrapping assembly for wrapping the napkin around the at least one utensil; and the utensil picker of claim 1 for picking up the at least one utensil from the at least one magazine and for bringing the at least one utensil from the at least one magazine to the wrapping assembly.
14. The apparatus of claim 13, wherein: each magazine of the at least one magazine has a corresponding at least two fingers of the at least two fingers; and for each magazine the corresponding at least two fingers are configured to pick up at least one utensil at a time from the magazine.
15. The apparatus of claim 14, wherein for each magazine the corresponding at least two fingers are configured to pick up a single utensil at a time from the magazine.
16. The apparatus of claim 13, further comprising a comb having upwardly extending teeth, the comb being disposed above the wrapping assembly; and wherein the at least one movable arm is configured to move the at least two fingers through spaces defined between teeth of the comb, thereby causing the comb to detach the at least one utensil picked up by the utensil picker from the at least two fingers and, as a result, cause the at least one utensil to fall toward the wrapping assembly.
17. The apparatus of claim 16, further comprising a chute disposed at least in part vertically between the comb and the wrapping assembly such that the at least one utensil detached from the utensil picker by the comb falls on the chute and then falls from the chute on the wrapping assembly.
18. The apparatus of claim 16, further comprising a chute disposed above the wrapping assembly; and wherein the at least one movable arm is configured to move above the chute such that the at least one utensil picked up by the utensil picker can be dropped from the utensil picker onto the chute and then fall from the chute on the wrapping assembly.
19. The apparatus of claim 13, further comprising a napkin delivery assembly for delivering the napkin to the wrapping assembly.
20. The apparatus of claim 19, wherein the napkin delivery assembly comprises a fan for picking

up the napkin from a stack of napkins and being movable between the stack of napkins and the wrapping assembly.

---