

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250264688

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Sharma; Shashank et al.

---

### Camera Actuator for Lens and Sensor Shifting

---

#### Abstract

Some embodiments include a camera voice coil motor (VCM) actuator configured to shift a lens and/or an image sensor along multiple axes. The VCM actuator may include a bottom flexure and a top flexure that connect one or more dynamic members to one or more static members. The VCM actuator may include stationary magnets and coils held by dynamic members. In some cases, the VCM actuator may be configured to move the image sensor along an optical axis, to move the image sensor in directions orthogonal to the optical axis, and/or to tilt the image sensor relative to the orthogonal axis. In some examples, the VCM actuator may be configured to move the image sensor in directions orthogonal to the optical axis, to move the lens along the optical axis, and/or to tilt the lens relative to the optical axis.

---

**Inventors:** Sharma; Shashank (San Francisco, CA), Brodie; Douglas S. (Los Gatos, CA), Miller; Scott W. (Los Gatos, CA)

**Applicant:** Apple Inc. (Cupertino, CA)

**Family ID:** 1000008589797

**Assignee:** Apple Inc. (Cupertino, CA)

**Appl. No.:** 19/202919

**Filed:** May 08, 2025

#### Related U.S. Application Data

parent US continuation 18438264 20240209 parent-grant-document US 12326613 child US 19202919

parent US continuation 18189973 20230324 parent-grant-document US 11982867 child US 18438264

parent US continuation 17145100 20210108 parent-grant-document US 11614597 child US 18189973

parent US continuation 15940661 20180329 parent-grant-document US 10890734 child US

## Publication Classification

**Int. Cl.:** **G02B7/09** (20210101); **H02P25/034** (20160101); **H04N23/54** (20230101); **H04N23/55** (20230101); **H04N23/67** (20230101)

**U.S. Cl.:**

**CPC** **G02B7/09** (20130101); **H02P25/034** (20160201); **H04N23/54** (20230101); **H04N23/55** (20230101); **H04N23/67** (20230101);

---

## Background/Summary

### SUMMARY OF EMBODIMENTS

[0001] Some embodiments include a camera. The camera may include a lens, an image sensor, and a VCM actuator. In various embodiments, the VCM actuator may include a magnet, coils, a sensor shift platform, a first set of one or more flexures, and a second set of one or more flexures. The sensor shift platform may be coupled to the image sensor such that the image sensor moves together with the sensor shift platform.

[0002] In some embodiments, the first set of flexures may be configured to mechanically connect the sensor shift platform to a first static member of the camera. For instance, the first static member may be configured to be static relative to the sensor shift platform. The second set of flexures may be configured to mechanically connect a coil holder to a second static member of the camera. For instance, the second static member may be configured to be static relative to the sensor shift platform. The coil holder may be configured to support one or more of the coils. In some cases, the coil holder may be further configured to hold the lens. That is, the coil holder may also be considered a lens holder in some embodiments.

[0003] In various embodiments, the VCM actuator may be configured to move the image sensor in a plurality of directions orthogonal to the optical axis, e.g., to provide OIS functionality to the camera. Additionally, or alternatively, the VCM actuator may be configured to move the image sensor and/or the lens along the optical axis, e.g., to provide autofocus functionality to the camera. Additionally, or alternatively, the VCM actuator may be configured to tilt the image sensor and/or the lens relative to the optical axis.

[0004] Some embodiments include a voice coil motor (VCM) actuator. The VCM actuator may include a magnet, coils, a dynamic platform, a first static member, a second static member, a bottom flexure, and a top flexure. The dynamic platform may be configured to be coupled to an image sensor of a camera such that the image sensor moves together with the dynamic platform. Each of the first static member and the second static member may be configured to be static, e.g., relative to the dynamic platform. In various embodiments, the magnet and the coils may be configured to magnetically interact to move the image sensor in directions orthogonal to an optical axis of the camera, e.g., to provide optical image stabilization (OIS) functionality. Additionally, or alternatively, the magnet and the coils may be configured to magnetically interact to move the image sensor and/or the lens along the optical axis, e.g., to provide autofocus functionality. Additionally, or alternatively, the magnet and the coils may be configured to magnetically interact to tilt the image sensor and/or the lens relative to the optical axis.

[0005] In some embodiments, a device (e.g., a mobile multifunction device) may include one or

more camera modules, a display, and/or one or more processors. For instance, a camera module may include a lens that defines an optical axis, an image sensor, and a voice coil motor (VCM) actuator. The image sensor may be configured to capture light passing through the lens and convert the captured light into image signals.

[0006] In various examples, the VCM actuator may include a sensor shift platform, a bottom flexure, and a top flexure. The sensor shift platform may be configured to be coupled to the image sensor such that the image sensor moves together with the sensor shift platform. The bottom flexure may be configured to mechanically connect the sensor shift platform to a first static member of the camera. The first static member may be configured to be static, e.g., relative to the sensor shift platform. The top flexure may be configured to mechanically connect a coil holder to a second static member of the camera. The second static member may be configured to be static, e.g., relative to the sensor shift platform. The coil holder may be configured to support one or more actuator coils. In some cases, the coil holder may be further configured to hold the lens.

[0007] In some embodiments, the processors may be configured to cause the VCM actuator to move the image sensor in directions orthogonal to the optical axis. Additionally, or alternatively, the processors may be configured to cause the VCM actuator to move the image sensor and/or the lens along the optical axis. Additionally, or alternatively, the processors may be configured to cause the VCM actuator to tilt the image sensor and/or the lens relative to the optical axis.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 illustrates an example camera module that includes a voice coil motor (VCM) actuator for shifting a lens and/or an image sensor along multiple axes, in accordance with some embodiments. FIG. 1 includes a perspective view of an example exterior of the camera module and a block diagram of example camera module components.

[0009] FIG. 2A illustrates a cross-sectional view of an example camera module that includes a voice coil motor (VCM) actuator for shifting an image sensor along multiple axes, in accordance with some embodiments.

[0010] FIG. 2B illustrates a top view of an example magnet and coil arrangement of the VCM actuator in the camera module of FIG. 2A, in accordance with some embodiments.

[0011] FIGS. 3A and 3B each illustrate a respective cross-sectional view of another example camera module that includes a voice coil motor (VCM) actuator for shifting an image sensor along multiple axis, in accordance with some embodiments.

[0012] FIG. 3C illustrates a top view of an example magnet and coil arrangement of the VCM actuator in the camera module of FIGS. 3A and 3B, in accordance with some embodiments.

[0013] FIGS. 4A and 4B each illustrate a respective cross-sectional view of an example camera module that includes a voice coil motor (VCM) actuator for shifting a lens and an image sensor along multiple axis, in accordance with some embodiments.

[0014] FIG. 4C illustrates a top view of an example magnet and coil arrangement of the VCM actuator in the camera module of FIGS. 4A and 4B, in accordance with some embodiments.

[0015] FIG. 5 is a flowchart of an example method of conveying signals (e.g., image signals) from a sensor shift platform of a voice coil motor (VCM) actuator to a flex circuit board, where the signals are conveyed in part via one or more flexures that include electrical traces, in accordance with some embodiments.

[0016] FIG. 6 is a flowchart of an example method of conveying current to one or more coils (e.g., autofocus and/or optical image stabilization coils) of a voice coil motor (VCM) actuator, where the current is conveyed in part via one or more flexures that include electrical traces, in accordance with some embodiments.

[0017] FIG. 7 is a flowchart of an example method of conveying current to one or more autofocus coils of a voice coil motor (VCM) actuator, where the current is conveyed in part via one or more flexures that include electrical traces, in accordance with some embodiments.

[0018] FIG. 8 is a flowchart of an example method of conveying current to one or more optical image stabilization (OIS) coils of a voice coil motor (VCM) actuator, where the current is conveyed in part via one or more flexures that include electrical traces, in accordance with some embodiments.

[0019] FIG. 9 illustrates a block diagram of a portable multifunction device with a camera, in accordance with some embodiments.

[0020] FIG. 10 depicts a portable multifunction device having a camera, in accordance with some embodiments.

[0021] FIG. 11 illustrates an example computer system that may include a camera, in accordance with some embodiments.

[0022] This specification includes references to “one embodiment” or “an embodiment.” The appearances of the phrases “in one embodiment” or “in an embodiment” do not necessarily refer to the same embodiment. Particular features, structures, or characteristics may be combined in any suitable manner consistent with this disclosure.

[0023] “Comprising.” This term is open-ended. As used in the appended claims, this term does not foreclose additional structure or steps. Consider a claim that recites: “An apparatus comprising one or more processor units . . .” Such a claim does not foreclose the apparatus from including additional components (e.g., a network interface unit, graphics circuitry, etc.).

[0024] “Configured To.” Various units, circuits, or other components may be described or claimed as “configured to” perform a task or tasks. In such contexts, “configured to” is used to connote structure by indicating that the units/circuits/components include structure (e.g., circuitry) that performs those task or tasks during operation. As such, the unit/circuit/component can be said to be configured to perform the task even when the specified unit/circuit/component is not currently operational (e.g., is not on). The units/circuits/components used with the “configured to” language include hardware—for example, circuits, memory storing program instructions executable to implement the operation, etc. Reciting that a unit/circuit/component is “configured to” perform one or more tasks is expressly intended not to invoke 35 U.S.C. § 112, sixth paragraph, for that unit/circuit/component. Additionally, “configured to” can include generic structure (e.g., generic circuitry) that is manipulated by software and/or firmware (e.g., an FPGA or a general-purpose processor executing software) to operate in manner that is capable of performing the task(s) at issue. “Configure to” may also include adapting a manufacturing process (e.g., a semiconductor fabrication facility) to fabricate devices (e.g., integrated circuits) that are adapted to implement or perform one or more tasks.

[0025] “First,” “Second,” etc. As used herein, these terms are used as labels for nouns that they precede, and do not imply any type of ordering (e.g., spatial, temporal, logical, etc.). For example, a buffer circuit may be described herein as performing write operations for “first” and “second” values. The terms “first” and “second” do not necessarily imply that the first value must be written before the second value.

[0026] “Based On.” As used herein, this term is used to describe one or more factors that affect a determination. This term does not foreclose additional factors that may affect a determination. That is, a determination may be solely based on those factors or based, at least in part, on those factors. Consider the phrase “determine A based on B.” While in this case, B is a factor that affects the determination of A, such a phrase does not foreclose the determination of A from also being based on C. In other instances, A may be determined based solely on B.

#### DETAILED DESCRIPTION

[0027] Some embodiments include camera equipment outfitted with controls, magnets, and voice coil motors to improve the effectiveness of a miniature actuation mechanism for a compact camera

module. More specifically, in some embodiments, compact camera modules include actuators to deliver functions such as autofocus (AF), optical image stabilization (OIS), and/or tilt. One approach to delivering a very compact actuator for OIS is to use a voice coil motor (VCM) arrangement.

[0028] In some embodiments, a camera may include a lens, an image sensor, and a VCM actuator. The lens may define an optical axis. The image sensor may be configured to capture light passing through the lens and convert the captured light into image signals. In various embodiments, the VCM actuator may include a magnet, coils, a sensor shift platform, a first set of one or more flexures, and a second set of one or more flexures. The sensor shift platform may be coupled to the image sensor such that the image sensor moves together with the sensor shift platform.

[0029] In some embodiments, the first set of flexures may be configured to mechanically connect the sensor shift platform to a first static member of the camera. For instance, the first static member may be configured to be static relative to the sensor shift platform. The second set of flexures may be configured to mechanically connect a coil holder to a second static member of the camera. For instance, the second static member may be configured to be static relative to the sensor shift platform. The coil holder may be configured to support one or more of the coils. In some cases, the coil holder may be further configured to hold the lens.

[0030] In various embodiments, the VCM actuator may be configured to move the image sensor in a plurality of directions orthogonal to the optical axis, e.g., to provide OIS functionality to the camera. Additionally, or alternatively, the VCM actuator may be configured to move the image sensor and/or the lens along the optical axis, e.g., to provide autofocus functionality to the camera. Additionally, or alternatively, the VCM actuator may be configured to tilt the image sensor and/or the lens relative to the optical axis.

[0031] In some embodiments, the first set of flexures may be configured to provide compliance for movement (e.g., of the image sensor) in directions orthogonal to the optical axis and along the optical axis. The second set of flexures may be configured to provide compliance for movement (e.g., of the image sensor and/or the lens) in directions orthogonal to the optical axis and along the optical axis. In some cases, the second set of flexures may also be configured to support the coil holder and to provide stiffness to counteract tilt (e.g., of the image sensor and/or the lens) relative to the optical axis.

[0032] In some examples, the coils may include a first OIS coil and a second OIS coil. The first OIS coil may be held, by the coil holder, proximate a first side (e.g., a top side) of the magnet. The second OIS coil may be held, by the coil holder, proximate a second side (e.g., a bottom side) of the magnet that is opposite the first side. To move the image sensor in directions orthogonal to the optical axis, the VCM actuator may be configured to cause the first OIS coil and/or the second OIS coil to magnetically interact with the magnet.

[0033] According to some embodiments, the magnet may be a single pole magnet. Furthermore, the magnet may be configured to be static, e.g., relative to the coil holder. In some cases, the coils may include an autofocus coil disposed between the magnet and the coil holder. The autofocus coil may extend around the lens, e.g., along a plane that is orthogonal to the optical axis. To move the image sensor along the optical axis, the VCM actuator may be configured to cause the autofocus coil to magnetically interact with the magnet.

[0034] In some embodiments, the magnet may be a dual pole magnet. Furthermore, the magnet may be configured to be static, e.g., relative to the coil holder. In some cases, the coils may further include an autofocus coil disposed between the magnet and the coil holder. To move the image sensor along the optical axis and/or to tilt the image sensor relative to the optical axis, the VCM actuator may be configured to cause the autofocus coil to magnetically interact with the magnet.

[0035] By using stationary magnets, reliability and power efficiency may be improved compared to VCM actuators that use moving magnets, as magnets tend to be among the heaviest objects in VCM actuators. Furthermore, embodiments described herein that include stationary magnets may

be used in multi-aperture systems (e.g., side-by-side cameras) as two such VCM actuators being located next to each other will have minimal interaction due the magnets being stationary.

[0036] In some cases, the magnet may be part of a magnet arrangement that includes a first magnet, a second magnet, a third magnet, and a fourth magnet. The first magnet may be located to a first side of the lens. The second magnet maybe located to a second side of the lens and opposite the first magnet relative to the lens. The third magnet may be located to a third side of the lens. The fourth magnet may be located to a fourth side of the lens and opposite the third magnet relative to the lens. In some examples, a first axis may traverse the first magnet, the lens, and the second magnet. A second axis may traverse the third magnet, the lens, and the fourth magnet. The second axis may be orthogonal to the first axis. In some embodiments, the coils may include a first set of coils proximate the first magnet, a second set of coils proximate the second magnet, a third set of coils proximate the third magnet, and a fourth set of coils proximate the fourth magnet. Each set of coils may include a respective set of OIS coils and a respective autofocus coil.

[0037] In various embodiments, the coils may include an autofocus coil and an OIS coil. The autofocus coil may be held by the coil holder. The OIS coil may be located on the sensor shift platform. For instance, the OIS coil may be a flat race track coil that is etched on the sensor shift platform. The VCM actuator may be configured to move the image sensor in directions orthogonal to the optical axis, move the lens along the optical axis, and/or tilt the lens relative to the optical axis. To move the image sensor in directions orthogonal to the optical axis, the VCM actuator may be configured to cause the OIS coil to magnetically interact with the magnet. To move the lens along the optical axis and/or to tilt the lens relative to the optical axis, the VCM actuator may be configured to cause the autofocus coil to magnetically interact with the magnet.

[0038] According to some examples, the first set of flexures may be a part of a sensor shift arrangement of the VCM actuator. For instance, the sensor shift arrangement may be configured to provide compliance for movement of the image sensor in directions orthogonal to the optical axis. In some cases, the sensor shift arrangement may further include the sensor shift platform, an OIS coil on the sensor shift platform, and/or the image sensor. Furthermore, in some embodiments, the second set of flexures may be configured to mechanically connect the coil holder to the second static member. The second set of flexures may be part of a lens shift arrangement of the VCM actuator. For instance, the lens shift arrangement may be configured to provide compliance for movement of the lens along the optical axis and/or for tilt of the lens relative to the optical axis. In some cases, the lens shift arrangement may further include the lens, the coil holder (which may be further configured to hold the lens), an autofocus coil held by the coil holder, and/or a third set of one or more flexures configured to mechanically connect the coil holder to the first static member, the second static member, and/or a third static member.

[0039] In some embodiments, a voice coil motor (VCM) actuator may include a magnet, coils, a dynamic platform, a first static member, a second static member, a bottom flexure, and a top flexure. The dynamic platform may be configured to be coupled to an image sensor of a camera such that the image sensor moves together with the dynamic platform. Each of the first static member and the second static member may be configured to be static, e.g., relative to the dynamic platform. In various embodiments, the magnet and the coils may be configured to magnetically interact to move the image sensor in directions orthogonal to an optical axis of the camera, e.g., to provide optical image stabilization (OIS) functionality. Additionally, or alternatively, the magnet and the coils may be configured to magnetically interact to move the image sensor and/or the lens along the optical axis, e.g., to provide autofocus functionality. Additionally, or alternatively, the magnet and the coils may be configured to magnetically interact to tilt the image sensor and/or the lens relative to the optical axis.

[0040] In some embodiments, the bottom flexure may be configured to mechanically connect the dynamic platform to the first static member. The top flexure may be configured to mechanically connect a coil holder of the camera to the second static member. The coil holder may be configured

to support one or more of the coils. In some cases, the coil holder may be further configured to hold a lens of the camera that defines the optical axis.

[0041] In some examples, the bottom flexure may extend, along a first plane that is orthogonal to the optical axis, from the dynamic platform to the first static member. Furthermore, the second flexure may extend, along a second plane that is orthogonal to the optical axis, from the coil holder to the second static member. In some cases, the first plane may be closer to the image sensor than the second plane. That is, a first distance between the first plane and the image sensor may be less than a second distance between the second plane and the image sensor. Additionally, or alternatively, the first plane may be closer to the image sensor than to the second plane. That is, the first distance between the first plane and the image sensor may be less than a third distance between the first plane and the second plane.

[0042] In some cases, the top flexure may be configured to mechanically connect the coil holder to the second static member. Furthermore, the coils may include a first OIS coil and a second OIS coil. The first OIS coil may be held, by the coil holder, proximate a first side (e.g., a top side) of the magnet. The second OIS coil may be held, by the coil holder, proximate a second side (e.g., a bottom side) of the magnet that is opposite the first side. In some examples, each of the first OIS coil and the second OIS coil may be a flat race track coil that is etched on the coil holder. To move the image sensor in directions orthogonal to the optical axis, the VCM actuator may be configured to cause the first OIS coil and/or the second OIS coil to magnetically interact with the magnet.

[0043] In some embodiments, the magnet may be a single pole magnet that is configured to be static relative to the coil holder. Furthermore, the coils may include an autofocus coil disposed between the magnet and the coil holder. The autofocus coil may extend around the lens along a plane that is orthogonal to the optical axis. To move the image sensor along the optical axis, the VCM actuator may be configured to cause the autofocus coil to magnetically interact with the magnet.

[0044] In some embodiments, the magnet may be a dual pole magnet that is configured to be static relative to the coil holder. Furthermore, the coils may include an autofocus coil held, by the coil holder, proximate a third side of the magnet that is adjacent to the first and second sides of the magnet. To move the image sensor along the optical axis and/or to tilt the image sensor relative to the optical axis, the VCM actuator may be configured to cause the autofocus coil to magnetically interact with the magnet.

[0045] According to some embodiments, the magnet may be a single pole magnet. Furthermore, the coils may include an autofocus coil and an OIS coil. The autofocus coil may be held by the coil holder. The OIS coil may be a flat race track coil that is etched on the dynamic platform. To move the image sensor in directions orthogonal to the optical axis, the VCM actuator may be configured to cause the OIS coil to magnetically interact with the magnet. To move the lens along the optical axis and/or to tilt the lens relative to the optical axis, the VCM actuator may be configured to cause the autofocus coil to magnetically interact with the magnet.

[0046] In some embodiments, a device (e.g., a mobile multifunction device) may include one or more camera modules, a display, and/or one or more processors. For instance, a camera module may include a lens that defines an optical axis, an image sensor, and a voice coil motor (VCM) actuator. The image sensor may be configured to capture light passing through the lens and convert the captured light into image signals.

[0047] In various examples, the VCM actuator may include a sensor shift platform, a bottom flexure, and a top flexure. The sensor shift platform may be configured to be coupled to the image sensor such that the image sensor moves together with the sensor shift platform. The bottom flexure may be configured to mechanically connect the sensor shift platform to a first static member of the camera. The first static member may be configured to be static, e.g., relative to the sensor shift platform. The top flexure may be configured to mechanically connect a coil holder to a second static member of the camera. The second static member may be configured to be static, e.g.,

relative to the sensor shift platform. The coil holder may be configured to support one or more actuator coils. In some cases, the coil holder may be further configured to hold the lens.

[0048] In some embodiments, the processors may be configured to cause the VCM actuator to move the image sensor in directions orthogonal to the optical axis. Additionally, or alternatively, the processors may be configured to cause the VCM actuator to move the image sensor and/or the lens along the optical axis. Additionally, or alternatively, the processors may be configured to cause the VCM actuator to tilt the image sensor and/or the lens relative to the optical axis.

[0049] In some cases, the processors may be configured to cause the display to present an image based at least in part on one or more of the image signals from the image sensor. For instance, the image sensor may be in electrical contact with the sensor shift platform. The bottom flexure may include one or more electrical traces configured to convey the image signals from the sensor shift platform to the first static member. Furthermore, the first static member may be in electrical contact with a flex circuit board of the device such that the first static member conveys the image signals to the flex circuit board. The processors may be configured to receive the image signals at least partly via the flex circuit board.

[0050] Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present disclosure. However, it will be apparent to one of ordinary skill in the art that some embodiments may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

[0051] It will also be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first contact could be termed a second contact, and, similarly, a second contact could be termed a first contact, without departing from the intended scope. The first contact and the second contact are both contacts, but they are not the same contact.

[0052] The terminology used in the description herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description and the appended claims, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0053] As used herein, the term “if” may be construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” may be construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

[0054] FIG. 1 illustrates an example camera module **100** that includes a voice coil motor (VCM) actuator for shifting a lens and/or an image sensor along multiple axes, in accordance with some embodiments. FIG. 1 includes a perspective view of an example exterior **102** of the camera module **100** and a block diagram of example camera module components **104** of the camera module **100**. In some embodiments, the camera module **100** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. 2A-11.

[0055] In some embodiments, the camera module components **104** may include a lens **106**, an



image sensor **108**, and a VCM actuator **110**. The lens **106** may define an optical axis **112**. The image sensor **108** may be configured to capture light passing through the lens **106** and convert the captured light into image signals. In various embodiments, the VCM actuator **110** may include magnets **114**, coils **116**, one or more coil holding components **118**, one or more bottom flexures **120**, and one or more top flexures **122**.

[0056] The magnets **114** and the coils **116** may be configured to magnetically interact, e.g., to produce Lorentz forces that cause one or more of the coil holding components **118** to shift along multiple axes. For instance, the coil holding component(s) may move in directions orthogonal to the optical axis **112** (e.g., along the x-y plane). Additionally, or alternatively, the coil holding component(s) **118** may move along the optical axis (e.g., along the z axis). Additionally, or alternatively, the coil holding component(s) **118** may tilt relative to the optical axis (e.g., along the x- and y-axes). In various examples, the lens **106** and/or the image sensor **108** may be configured to shift together with, and in a similar or same manner as, one or more of the coil holding components.

[0057] The coils **116** may include autofocus (AF) coils **124** and/or optical image stabilization (OIS) coils **126**. In some cases, the autofocus coils **124** and the optical image stabilization coils **126** may be held by a same coil holding component **118**. In other cases, the autofocus coils **124** and the optical image stabilization coils **126** may be held by different coil holding components **118**.

[0058] In some embodiments, the coil holding components **118** may include a coil holder **128** that is configured to hold at least one AF coil **124** and at least one OIS coil **126**. The coil holder **128** may be coupled to the sensor shift platform **130** such that the sensor shift platform **130** shifts together with the coil holder **128**. Furthermore, the sensor shift platform **130** may be coupled to the image sensor **108** such that the image sensor **108** shifts together with the sensor shift platform **130**. In some cases, the coil holder **128** may also be configured to hold the lens **106** and may thus be referred to herein as a “lens holder” (e.g., lens holder **136**).

[0059] The bottom flexures **120** may be configured to mechanically connect the sensor shift platform **130** to a static member **132** (e.g., a base). The bottom flexures **120** may also be configured to provide compliance for movement of the sensor shift platform **130**. Furthermore, the bottom flexures **120** may be configured to support, at least in part, the sensor shift platform **130**.

[0060] The top flexures **122** may be configured to mechanically connect the coil holder **128** to another static member **134** (e.g., a case that at least partially encompasses an interior of the camera module **100**). The top flexures **122** may also be configured to provide compliance for movement of the coil holder **128**. Furthermore, the top flexures **122** may be configured to support the coil holder **128** and/or to provide stiffness to counteract tilt of the coil holder **128** relative to the optical axis.

[0061] The AF coil(s) **124** and the OIS coil(s) **126** may receive a current and magnetically interact with the magnet(s) **114** to produce forces that cause the coil holder **128** to shift. For instance, interaction between the AF coil(s) **124** and the magnet(s) **114** may produce forces that cause the coil holder **128** to move along the optical axis **112** and/or to tilt relative to the optical axis **112**. Interaction between the OIS coil(s) **116** and the magnet(s) **114** may produce forces that cause the coil holder **128** to move in directions orthogonal to the optical axis **112**. In some embodiments, the sensor shift platform **130** may be suspended from, or otherwise coupled to, the coil holder **128**. Accordingly, the sensor shift platform **130** may shift together with, and in a similar or same manner as, the coil holder **128**. Furthermore, the image sensor **108** may be suspended from, or otherwise coupled to, the sensor shift platform **130**. Accordingly, the image sensor **108** may shift together with, and in a similar or same manner as, the sensor shift platform **130**.

[0062] In some embodiments, the coil holding components **118** may include the sensor shift platform **130** and a lens holder **136** (also referred to herein as a “coil holder”). For instance, the sensor shift platform **130** may be configured to hold at least one OIS coil **126**, and the lens holder **136** may be configured to hold at least one autofocus coil **124**. The sensor shift platform **130** may be coupled to the image sensor **108** such that the image sensor **108** shifts together with the sensor

shift platform **130**. Furthermore, the lens holder **136** may be coupled to the lens **106** such that the lens **106** shifts together with the lens holder **136**.

[0063] The bottom flexures **120** may be configured to mechanically connect the sensor shift platform **130** to the static member **132**. The bottom flexures **120** may also be configured to provide compliance for movement of the sensor shift platform **130**. Furthermore, the bottom flexures **120** may be configured to support, at least in part, the sensor shift platform **130**. For example, the sensor shift platform **130** may be suspended from the bottom flexures **120**.

[0064] The top flexures **122** may be configured to mechanically connect the lens holder **136** to the static member **134**. The top flexures **122** may also be configured to provide compliance for movement of the lens holder **136**. Furthermore, the top flexures **122** may be configured to support, at least in part, the lens holder **136**. For example, the lens holder **136** may be suspended from the top flexures **122**. As will be discussed in further detail below with reference to FIGS. **4A** and **4B**, one or more additional flexures may be used to mechanically connect the lens holder **136** and/or the sensor shift platform **130** to a static member.

[0065] The AF coil(s) **124** may receive a current and magnetically interact with the magnet(s) **114** to produce forces that cause the lens holder **136** to shift. For instance, interaction between the AF coil(s) **124** and the magnet(s) **114** may produce forces that cause the lens holder **136** to move along the optical axis **112** and/or to tilt relative to the optical axis **112**. The lens **106** may shift together with, and in a similar or same manner as, the lens holder **136**.

[0066] Furthermore, the OIS coil(s) **126** may receive a current and magnetically interact with the magnet(s) **114** to produce forces that cause the sensor shift platform **130** to shift. For instance, interaction between the OIS coil(s) **126** and the magnet(s) **114** may produce forces that cause the sensor shift platform **130** to move in directions orthogonal to the optical axis **112**. The image sensor **108** may shift together with, and in a similar or same manner as, the sensor shift platform **130**.

[0067] FIG. **2A** illustrates a cross-sectional view of an example camera module **200a** that includes a voice coil motor (VCM) actuator for shifting an image sensor along multiple axes, in accordance with some embodiments. In some embodiments, the camera module **200** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. **1** and **2B-11**.

[0068] In some embodiments, the camera module **200a** may include a lens **202**, an image sensor **204**, and a VCM actuator module **206**. The lens **202** may define an optical axis **208**. In some examples, the lens **202** may be a fixed lens. The image sensor **204** may be configured to capture light passing through the lens **202** and convert the captured light into image signals. In some cases, the VCM actuator module **206** may be one of multiple VCM actuator modules of the camera module **200a**. For instance, the camera module **200a** may include four such VCM actuator modules **206**, such as two pairs of VCM actuator modules **206** that oppose one another relative to the lens **202**. As discussed in further detail below, the VCM actuator module(s) **206** may be configured to shift the image sensor **204** along three axes in some embodiments. For instance, the VCM actuator module(s) **206** may shift the image sensor **204** along the optical axis **208** (e.g., to provide autofocus (AF) functionality) and/or in directions orthogonal to the optical axis **208** (e.g., to provide optical image stabilization (OIS) functionality).

[0069] In various embodiments, the VCM actuator module **206** may include a stationary single pole magnet **210**, a top OIS coil **212**, a bottom OIS coil **214**, and an AF coil **216**. Furthermore, the VCM actuator module **206** may include a coil holder **218**, a sensor shift platform **220**, a top flexure **222**, and a bottom flexure **224**.

[0070] In some embodiments, the coil holder **218** may hold, or otherwise support, the top OIS coil **212**, the bottom OIS coil **214**, and the AF coil **216**. The coil holder **218** may be coupled to the sensor shift platform **220** such that the sensor shift platform **220** shifts together with the coil holder **218**. Furthermore, the sensor shift platform **220** may be coupled to the image sensor **204** such that the image sensor **204** shifts together with the sensor shift platform **220**.

[0071] The bottom flexure **224** may be configured to mechanically connect the sensor shift platform **220** to a base **226** of the VCM actuator module(s) **206** and/or of the camera module **200a**. The bottom flexure **224** may also be configured to provide compliance for movement of the sensor shift platform **220** along the optical axis **208** and in directions orthogonal to the optical axis **208**. Furthermore, the bottom flexure **224** may be configured to support, at least in part, the sensor shift platform **220**. In some cases, the sensor shift platform **220** may be suspended from the bottom flexure **224** and the coil holder **218**. The base **226** may be a static member that is static relative to one or more moving components (e.g., the sensor shift platform **220**). In other embodiments, the bottom flexure **224** may additionally, or alternatively, be connected to a different static member.

[0072] The top flexure **222** may be configured to mechanically connect the coil holder **218** to a case **228** of the VCM actuator module(s) and/or of the camera module **200a**. The top flexure **222** may also be configured to provide compliance for movement of the coil holder **218** along the optical axis **208** and in directions orthogonal to the optical axis **208**. Furthermore, the top flexure **222** may be configured to support the coil holder **218** and/or to provide stiffness to counteract tilt of the coil holder **218** relative to the optical axis **208**. The case **228** may encompass, at least in part, an interior of the camera module **200a**. The case **228** may be a static member that is static relative to one or more moving components (e.g., the sensor shift platform **220**). In other embodiments, the top flexure **222** may additionally, or alternatively, be connected to a different static member.

[0073] In some embodiments, the stationary single pole magnet **210** may be fixed to a static member (e.g., the case **228**). The coil holder **218** may be configured to at least partially encompass an outer perimeter of the single pole magnet **210**. As illustrated in FIG. 2A, the top OIS coil **212** may be held, by the coil holder **218**, proximate a top side of the single pole magnet **210**. Furthermore, the bottom OIS coil **214** may be held, by the coil holder **218**, proximate a bottom side of the single pole magnet **210**. In some examples, each of the top OIS coil **212** and the bottom OIS coil **214** may be a flat race track coil that is etched on the coil holder **218**. In some embodiments, the top OIS coil **212** and the bottom OIS coil **214** are formed using a semi-additive manufacturing process in which conductors are grown on metal substrates. The metal substrates may be formed into different shapes based on the particular design of the VCM actuator module **206**. In some instances, current flow through the top OIS coil **212** may be in a direction that is opposite the current flow through the bottom OIS coil **214**. Furthermore, each of the top OIS coil **212** and the bottom OIS coil **214** may be oriented such that current flows through the respective coil **212**, **214** along a respective plane that is orthogonal to the optical axis **208**.

[0074] In some embodiments, the VCM actuator module **206** may include one of the top OIS coil **212** or the bottom OIS coil **214** instead of including both. By including both, however, as one moves away from the single pole magnet **210** (e.g., due to magnetic interaction between the AF coil **216** and the single pole magnet **210**), the other moves closer to the single pole magnet **210**. That is, at least one of the top OIS coil **212** or the bottom OIS coil **214** will be capable of effectively interacting with the single pole magnet **210** at all times.

[0075] The AF coil **216** may be held by the coil holder **218** such that the AF coil **216** is disposed between the single pole magnet **210** and the coil holder **218**. In various embodiments, the AF coil **216** may extend around the lens **202**, e.g., along a plane that is orthogonal to the optical axis **208**.

[0076] Interaction between the AF coil **216** and the single pole magnet **210** may produce forces that cause the coil holder **218** to move along the optical axis **208**. Interaction between the single pole magnet **210** and the top OIS coil **212** and/or the bottom OIS coil **214** may produce forces that cause the coil holder **218** to move in directions orthogonal to the optical axis **208**. The sensor shift platform **220** may shift together with, and in a similar or same manner as, the coil holder **218**. Furthermore, the image sensor **204** may shift together with, and in a similar or same manner as, the sensor shift platform **220**.

[0077] In various embodiments, electrical contacts/connections may allow for image signals to be conveyed from the image sensor **204** to a flex circuit board **230**. For instance, the image sensor **204**

may be in electrical contact with the sensor shift platform **220** via one or more contacts **232**, and thus the image signals may be conveyed from the image sensor **204** to the sensor shift platform **220**. The image signals may be conveyed from the sensor shift platform **220** to the base **226** via bottom flexure **224**. For instance, the bottom flexure **224** may include electrical traces **234** that allow for the image signals to be conveyed from the sensor shift platform **220** to the base **226**. The base **226** may be in electrical contact with the flex circuit board **230** via one or more contacts **236**, and thus the image signals may be conveyed from the base **226** to the flex circuit board **230**.

[0078] According to various examples, electrical contacts/connections may allow for current to be conveyed from the flex circuit board **230** to the coil holder **218** to drive one or more of the coils **212**, **214**, **216**. For instance, the flex circuit board **230** may convey the current to the base **226** via the contact(s) **236**. The current may be conveyed from the base **226** to the image sensor platform **220** via the electrical traces **234** of the bottom flexure **224**. The image sensor platform **220** may be in electrical contact with the coil holder **218** via one or more contacts **238**, and thus the current may be conveyed from the image sensor platform **220** to the coil holder **218**. The coil holder **218** may convey the current to one or more of the coils **212**, **214**, **216**.

[0079] In some embodiments, the VCM actuator module **206** and/or the camera module **200a** may include a position sensor **240** (e.g., a Hall sensor) for position detection based on movement of the bottom OIS coil **214** and/or the top OIS coil **212** in directions orthogonal to the optical axis **208**. For example, the position sensor **240** may be located on the base **226** or otherwise proximate the bottom OIS coil **214** and/or the top OIS coil **212**.

[0080] Although the coil holder **218** and the sensor shift platform **220** are shown in FIG. 2A as two separate pieces, it is understood that the coil holder **218** and the sensor shift platform **220** may be a single piece in some embodiments.

[0081] FIG. 2B illustrates a top view of an example magnet and coil arrangement **200b** of the VCM actuator in the camera module **200a** of FIG. 2A, in accordance with some embodiments. In some embodiments, the magnet and coil arrangement **200b** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. 1, 2A, and 3A-11.

[0082] The magnet arrangement may include a first single pole magnet **210**, a second single pole magnet **242**, a third single pole magnet **244**, and a fourth single pole magnet **246**. In some embodiments, each of the magnets may be stationary magnets. For instance, each of the magnets may be fixed to the case **228**. The polarities of the magnets are indicated in FIG. 2B by the solid arrows. As shown, each of the polarities may point inwards. In other embodiments, each of the polarities may point outwards.

[0083] The coil arrangement may include the autofocus coil **216**, a first bottom OIS coil **214** below the first single pole magnet **210**, a second bottom OIS coil **248** below the second single pole magnet **242**, a third bottom OIS coil **250** below the third single pole magnet **244**, and a fourth bottom OIS coil **252** below the fourth single pole magnet **246**. Although not shown in FIG. 2B, the coil arrangement may include a set of top OIS coils that are arranged like the bottom OIS coils, but that are instead located above a respective one of the single pole magnets. The direction of current flow of the coils are indicated in FIG. 2B by the dashed arrows.

[0084] FIGS. 3A and 3B each illustrate a respective cross-sectional view of another example camera module **300** that includes a voice coil motor (VCM) actuator for shifting an image sensor along multiple axis, in accordance with some embodiments. In some embodiments, the camera module **300** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. 1 and 2B and 3C-11.

[0085] In some embodiments, the camera module **300** may include several of the same structural elements as the camera module **200a** described above with reference to FIG. 2A. However, as discussed in further detail below, the coil holder **304** of the VCM actuator module **302** of the camera module **300** may have a different coil arrangement than that of the VCM actuator module

**206** in the camera module **200a**. Furthermore, the VCM actuator module **302** may include a dual pole magnet **306** instead of the single pole magnet **210** of the VCM actuator module **206** in the camera module **200a**. In some cases, the VCM actuator module **302** may be one of multiple VCM actuator modules of the camera module **300**. For instance, the camera module **300** may include four such VCM actuator modules **302**, such as two pairs of VCM actuator modules **302** that oppose one another relative to the lens **202**. The VCM actuator module(s) **302** may be configured to shift the image sensor **204** along five axes in some embodiments. For instance, the VCM actuator module(s) **302** may move the image sensor **204** along the optical axis **208** (e.g., to provide autofocus (AF) functionality), move the image sensor **204** in directions orthogonal to the optical axis **208** (e.g., to provide optical image stabilization (OIS) functionality), and/or tilt the image sensor **204** relative to the optical axis **208**.

[0086] In some embodiments, the dual pole magnet **306** may be fixed to a static member (e.g., the case **228**). The coil holder **304** may be configured to at least partially encompass an outer perimeter of the dual pole magnet **306**. As illustrated in FIGS. 3A and 3B, the top OIS coil **308** may be held, by the coil holder **304**, proximate a top side of the dual pole magnet **306**. Furthermore, the bottom OIS coil **310** may be held, by the coil holder **304**, proximate a bottom side of the dual pole magnet **306**.

[0087] The coil holder **304** may be configured to hold the AF coil **312** proximate a side of the dual pole magnet **306** that is adjacent to the top side and the bottom side of the dual pole magnet **306**. Instead of having a single AF coil that extends around the lens and that is shared by multiple VCM actuator modules, such as the AF coil **216** described above with reference to FIG. 2A, each VCM actuator module **302** in the camera module **300** may include a separate AF coil **312**.

[0088] Interaction between the AF coil **312** and the dual pole magnet **306** may produce forces that cause the coil holder **304** to move along the optical axis **208**. Because each VCM actuator **302** in the camera module **300** may include a separate AF coil **312**, interaction between the AF coil **312** and the dual pole magnet **306** may also produce forces that cause the coil holder **304** to tilt relative to the optical axis **208**, as indicated by  $M_{\text{sub},\theta,x}$  in FIG. 3B. Furthermore, interaction between the dual pole magnet **306** and the top OIS coil **308** and/or the bottom OIS coil **310** may produce forces that cause the coil holder **304** to move in directions orthogonal to the optical axis **208**. The sensor shift platform **220** may shift together with, and in a similar or same manner as, the coil holder **304**. Furthermore, the image sensor **204** may shift together with, and in a similar or same manner as, the sensor shift platform **220**.

[0089] FIG. 3C illustrates a top view of an example magnet and coil arrangement **300c** of the VCM actuator in the camera module **300** of FIGS. 3A and 3B, in accordance with some embodiments. In some embodiments, the magnet and coil arrangement **300c** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. 1-3B and 4A-11.

[0090] The magnet arrangement may include a first dual pole magnet **306**, a second dual pole magnet **314**, a third dual pole magnet **316**, and a fourth dual pole magnet **318**. In some embodiments, each of the magnets may be stationary magnets. For instance, each of the magnets may be fixed to the case **228**. The polarities of the magnets are indicated in FIG. 3C by the solid arrows.

[0091] The coil arrangement may include a first bottom OIS coil **310** below the first dual pole magnet **306**, a second bottom OIS coil **320** below the second dual pole magnet **314**, a third bottom OIS coil **322** below the third dual pole magnet **316**, and a fourth bottom OIS coil **324** below the fourth dual pole magnet **318**. Although not shown in FIG. 3C, the coil arrangement may include a set of top OIS coils that are arranged like the bottom OIS coils, but that are instead located above a respective one of the single pole magnets. Furthermore, the coil arrangement may include a first AF coil **312** proximate a side of the first dual pole magnet **306**, a second AF coil **326** proximate a side of the second dual pole magnet **314**, a third AF coil **328** proximate a side of the third dual pole

magnet **316**, and a fourth AF coil **330** proximate a side of the fourth dual pole magnet **318**. The direction of current flow of the coils are indicated in FIG. **3C** by the dashed arrows.

[0092] FIGS. **4A** and **4B** each illustrate a respective cross-sectional view of an example camera module **400** that includes a voice coil motor (VCM) actuator for shifting a lens and an image sensor along multiple axis, in accordance with some embodiments. In some embodiments, the camera module **400** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. **1-3C** and **4C-11**.

[0093] In some embodiments, the camera module **400** may include a lens **402**, an image sensor **404**, and a VCM actuator module **406**. The lens **402** may define an optical axis **408**. The image sensor **404** may be configured to capture light passing through the lens **402** and convert the captured light into image signals. In some cases, the VCM actuator module **406** may be one of multiple VCM actuator modules of the camera module **400**. For instance, the camera module **400** may include four such VCM actuator modules **406**, such as two pairs of VCM actuator modules **206** that oppose one another relative to the lens **402**. As discussed in further detail below, the VCM actuator module(s) **406** may be configured to move the lens **402** along the optical axis **408** (e.g., to provide autofocus (AF) functionality) and/or tilt the lens **402** relative to the optical axis **408**. Furthermore, the VCM actuator module(s) **406** may be configured to move the image sensor **404** in directions orthogonal to the optical axis **408** (e.g., to provide optical image stabilization (OIS) functionality).

[0094] In various embodiments, the VCM actuator module **406** may include a stationary single pole magnet **410**, a lens holder **412**, a sensor shift platform **414**, a top flexure **416**, an intermediate flexure **418**, and a bottom flexure **420**. Furthermore, the VCM actuator module **406** may include an autofocus coil **422** and a bottom OIS coil **424**.

[0095] In some embodiments, the lens holder **412** may hold, or otherwise support, the AF coil **422** proximate a side of the single pole magnet **410**. The lens holder **412** may be coupled to the lens **402** such that the lens **402** shifts together with the lens holder **412**.

[0096] In some embodiments, the sensor shift platform **414** may hold, or otherwise support, the bottom OIS coil **424** proximate a bottom side of the single pole magnet **410**. The sensor shift platform **414** may be coupled to the image sensor **404** such that the image sensor **404** shifts together with the sensor shift platform **414**.

[0097] The bottom flexure **420** may be configured to mechanically connect the sensor shift platform **414** to a base **426** of the VCM actuator module(s) **406** and/or of the camera module **400**. The bottom flexure **420** may also be configured to provide compliance for movement of the sensor shift platform **414** in directions orthogonal to the optical axis **408**. Furthermore, the bottom flexure **420** may be configured to support, at least in part, the sensor shift platform **414**. In some cases, the sensor shift platform **414** may be suspended from the bottom flexure **420**. The base **426** may be a static member that is static relative to one or more moving components (e.g., the sensor shift platform **414**). In other embodiments, the bottom flexure **420** may additionally, or alternatively, be connected to a different static member.

[0098] The intermediate flexure **418** and the top flexure **416** may be configured to mechanically connect the lens holder **412** the base **426** and a case **428**, respectively. For instance, the intermediate flexure **418** may be configured to connect a bottom portion of the lens holder **412** to the base **426**, and the top flexure may be configured to connect a top portion of the lens holder **412** to the case **428**. The intermediate flexure **418** and the top flexure **416** may also be configured to provide compliance for movement of the lens holder **412** along the optical axis **408** and for tilt of the lens holder **412** relative to the optical axis **408**. The case **428** may encompass, at least in part, an interior of the camera module **400**. The case **428** may be a static member that is static relative to one or more moving components (e.g., the lens holder **412**). In other embodiments, the intermediate flexure **418** and/or the top flexure **416** may additionally, or alternatively, be connected to a different static member.

[0099] In some embodiments, the stationary single pole magnet **410** may be fixed to a static member (e.g., the case **428**). In some examples, each of the AF coil **422** and the bottom OIS coil **424** may be a race track coil. In some embodiments, the bottom OIS coil may be a flat race track coil that is etched on the sensor shift platform **414**.

[0100] As indicated in FIG. **4B**, interaction between the AF coil **422** and the single pole magnet **410** may produce forces that cause the lens holder **412** to move along the optical axis **408** and/or to tilt relative to the optical axis **408**. Interaction between the single pole magnet **410** and the bottom OIS coil **424** may produce forces that cause the sensor shift platform **414** to move in directions orthogonal to the optical axis **408**. The lens **402** may shift together with, and in a similar or same manner as, the lens holder **412**. Furthermore, the image sensor **404** may shift together with, and in a similar or same manner as, the sensor shift platform **414**.

[0101] In various embodiments, electrical contacts/connections may allow for image signals to be conveyed from the image sensor **404** to a flex circuit board **430**. For instance, the image sensor **404** may be in electrical contact with the sensor shift platform **414** via one or more contacts **432**, and thus the image signals may be conveyed from the image sensor **404** to the sensor shift platform **414**. The image signals may be conveyed from the sensor shift platform **414** to the base **426** via the bottom flexure **420**. For instance, the bottom flexure **420** may include electrical traces that allow for the image signals to be conveyed from the sensor shift platform **414** to the base **426**. The base **426** may be in electrical contact with the flex circuit board **430** via one or more contacts **434**, and thus the image signals may be conveyed from the base **426** to the flex circuit board **430**.

[0102] According to various examples, electrical contacts/connections may allow for current to be conveyed from the flex circuit board **430** to the sensor shift platform **414** to drive the bottom OIS coil **424**. Furthermore, current may be conveyed from the flex circuit board **430** to the lens holder **412** to drive the AF coil **422**. For instance, the flex circuit board **430** may convey the current to the base **426** via the contact(s) **434**. The current may be conveyed from the base **426** to the sensor shift platform **414** via the electrical traces of the bottom flexure **420**. The sensor shift platform **414** may convey the current to the bottom OIS coil **424**. Furthermore, the base **426** may convey the current to the lens holder **412** via the intermediate flexure **418**. For instance, the intermediate flexure **418** may include electrical traces that allow for the current to be conveyed from the base **426** to the lens holder **412**. The lens holder **412** may convey the current to the AF coil **422**.

[0103] In some embodiments, the VCM actuator module **406** and/or the camera module **400** may include a position sensor **436** (e.g., a Hall sensor) for position detection based on movement of the bottom OIS coil **424** in directions orthogonal to the optical axis **408**. For example, the position sensor **436** may be located on the base **426** or otherwise proximate the bottom OIS coil **424**.

[0104] FIG. **4C** illustrates a top view of an example magnet and coil arrangement **400c** of the VCM actuator in the camera module **400** of FIGS. **4A** and **4B**, in accordance with some embodiments. In some embodiments, the magnet and coil arrangement **400c** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. **1-4B** and **5-11**.

[0105] The magnet arrangement may include a first single pole magnet **410**, a second single pole magnet **438**, a third single pole magnet **440**, and a fourth single pole magnet **442**. In some embodiments, each of the magnets may be stationary magnets. For instance, each of the magnets may be fixed to the case **428**. The polarities of the magnets are indicated in FIG. **4C** by the solid arrows.

[0106] The coil arrangement may include a first bottom OIS coil **424** below the first single pole magnet **410**, a second bottom OIS coil **444** below the second single pole magnet **438**, a third bottom OIS coil **446** below the third single pole magnet **440**, and a fourth bottom OIS coil **448** below the fourth single pole magnet **442**. Furthermore, the coil arrangement may include a first AF coil **422** proximate a side of the first single pole magnet **410**, a second AF coil **450** proximate a side of the second single pole magnet **438**, a third AF coil **452** proximate a side of the third single pole

magnet **440**, and a fourth AF coil **454** proximate a side of the fourth single pole magnet **442**. The direction of current flow of the coils are indicated in FIG. **4C** by the dashed arrows.

[0107] FIG. **5** is a flowchart of an example method **500** of conveying signals (e.g., image signals) from a sensor shift platform of a voice coil motor (VCM) actuator (e.g., a VCM actuator of a camera module) to a flex circuit board, where the signals are conveyed in part via one or more flexures that include electrical traces, in accordance with some embodiments. In some embodiments, the method **500** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. **1-4C** and **6-11**.

[0108] At **502**, the method **500** may include generating signals. For instance, an image sensor of the camera module may generate image signals. At **504**, the method **500** may include conveying the image signals from the image sensor to the sensor shift platform of the VCM actuator. At **506**, the method **500** may include conveying the image signals from the sensor shift platform to a base of the VCM actuator (e.g., a VCM actuator of a camera module). In some examples, one or more flexures of the VCM actuator may be configured to mechanically connect the sensor shift platform to the base. The flexures may include electrical traces that allow the image signals to be conveyed from the sensor shift platform to base via the flexures. At **508**, the method **500** may include conveying the image signals from the base to a flex circuit board. The base may be in electrical contact with the flex circuit board. The flex circuit board may be configured to route the image signals (or other signals) from the camera module to one or more other components in a device and/or system. For instance, the flex circuit board may route signals from the camera module to one or more processors of a device in which the camera module resides.

[0109] FIG. **6** is a flowchart of an example method **600** of conveying current to one or more coils (e.g., autofocus and/or optical image stabilization coils) of a voice coil motor (VCM) actuator (e.g., a VCM actuator of a camera module), where the current is conveyed in part via one or more flexures that include electrical traces, in accordance with some embodiments. In some embodiments, the method **500** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. **1-5** and **7-11**.

[0110] At **602**, the method **600** may include providing current for driving one or more coils of the VCM actuator. At **604**, the method **600** may include conveying the current to a base of the VCM actuator. For instance, the current may be conveyed to the base via a flex circuit board. The flex circuit board may be in electrical contact with the base. At **606**, the method **600** may include conveying the current from the base to a coil holder of the VCM actuator. In some examples, one or more flexures of the VCM actuator may be configured to mechanically connect the coil holder to the base. The flexures may include electrical traces that allow the image signals to be conveyed from the base to the coil holder. At **608**, the method **600** may include conveying the current from the coil holder to the coil(s).

[0111] FIG. **7** is a flowchart of an example method **700** of conveying current to one or more autofocus coils of a voice coil motor (VCM) actuator (e.g., a VCM actuator of a camera module), where the current is conveyed in part via one or more flexures that include electrical traces, in accordance with some embodiments. In some embodiments, the method **500** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. **1-6** and **8-11**.

[0112] At **702**, the method **700** may include providing current for driving one or more autofocus coils of the VCM actuator. The autofocus coil(s) may be held by a lens holder of the VCM actuator. The lens holder may also hold the lens of the camera module such that the lens moves together with the lens holder. At **704**, the method **700** may include conveying the current to a base of the VCM actuator. For instance, the current may be conveyed to the base via a flex circuit board. The flex circuit board may be in electrical contact with the base. At **706**, the method **700** may include conveying the current from the base to the lens holder. In some examples, one or more flexures of the VCM actuator may be configured to mechanically connect the lens holder to the base. The



flexures may include electrical traces that allow the image signals to be conveyed from the base to the lens holder. At **708**, the method **700** may include conveying the current from the lens holder to the AF coil(s).

[0113] FIG. **8** is a flowchart of an example method **800** of conveying current to one or more optical image stabilization (OIS) coils of a voice coil motor (VCM) actuator (e.g., a VCM actuator of a camera module), where the current is conveyed in part via one or more flexures that include electrical traces, in accordance with some embodiments. In some embodiments, the method **800** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. **1-7** and **9-11**.

[0114] At **802**, the method **800** may include providing current for driving one or more OIS coils of the VCM actuator. The OIS coil(s) may be held by a sensor shift platform of the VCM actuator. The lens holder may also hold the image sensor of the camera module such that the image sensor moves together with the lens holder. At **804**, the method **800** may include conveying the current to a base of the VCM actuator. For instance, the current may be conveyed to the base via a flex circuit board. The flex circuit board may be in electrical contact with the base. At **806**, the method **800** may include conveying the current from the base to the sensor shift platform. In some examples, one or more flexures of the VCM actuator may be configured to mechanically connect the sensor shift platform to the base. The flexures may include electrical traces that allow the image signals to be conveyed from the base to the sensor shift platform.

#### Multifunction Device Examples

[0115] FIG. **9** illustrates a block diagram of a portable multifunction device **900**, in accordance with some embodiments. In some embodiments, the portable multifunction device **900** may include one or multiple features, components, and/or implement functionality of embodiments described herein with reference to FIGS. **1-8**, **10**, and **11**.

[0116] In some embodiments, the device **900** is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA, camera, video capture and/or playback, and/or music player functions. Example embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California. Other portable electronic devices, such as laptops, cell phones, smartphones, pad or tablet computers with touch-sensitive surfaces (e.g., touch screen displays and/or touch pads), may also be used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a touch-sensitive surface (e.g., a touch screen display and/or a touch pad). In some embodiments, the device is a gaming computer with orientation sensors (e.g., orientation sensors in a gaming controller). In other embodiments, the device is not a portable communications device, but is a camera and/or video camera.

[0117] In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device may include one or more other physical user-interface devices, such as a physical keyboard, a mouse and/or a joystick.

[0118] The device **900** typically supports a variety of applications, such as one or more of the following: a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, a streaming video application, and/or a digital video player application.

[0119] The various applications that may be executed on the device **900** may use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device may be adjusted and/or varied from one application to the next and/or within a respective application. In

this way, a common physical architecture (such as the touch-sensitive surface) of the device may support the variety of applications with user interfaces that are intuitive and transparent to the user. [0120] Device **900** may include memory **902** (which may include one or more computer readable storage mediums), memory controller **922**, one or more processing units (CPU's) **920**, peripherals interface **918**, RF circuitry **908**, audio circuitry **910**, speaker **911**, touch-sensitive display system **912**, microphone **913**, input/output (I/O) subsystem **906**, other input control devices **916**, and external port **924**. Device **900** may include one or more optical sensors or cameras **964** (e.g., one or more embodiments of the cameras described herein). These components may communicate over one or more communication buses or signal lines **903**.

[0121] It should be appreciated that device **900** is only one example of a portable multifunction device, and that device **900** may have more or fewer components than shown, may combine two or more components, or may have a different configuration or arrangement of the components. The various components shown in FIG. **9** may be implemented in hardware, software, or a combination of hardware and software, including one or more signal processing and/or application specific integrated circuits.

[0122] Memory **902** may include high-speed random access memory and may also include non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory **902** by other components of device **900**, such as CPU **920** and the peripherals interface **918**, may be controlled by memory controller **922**.

[0123] Peripherals interface **918** can be used to couple input and output peripherals of the device to CPU **920** and memory **902**. The one or more processors **920** run or execute various software programs and/or sets of instructions stored in memory **902** to perform various functions for device **900** and to process data.

[0124] In some embodiments, peripherals interface **918**, CPU **920**, and memory controller **922** may be implemented on a single chip, such as chip **904**. In some other embodiments, they may be implemented on separate chips.

[0125] RF (radio frequency) circuitry **908** receives and sends RF signals, also called electromagnetic signals. RF circuitry **908** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **908** may include well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a coder/decoder (codec) chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **908** may communicate with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The wireless communication may use any of a variety of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

[0126] Audio circuitry **910**, speaker **911**, and microphone **913** provide an audio interface between a user and device **900**. Audio circuitry **910** receives audio data from peripherals interface **918**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **911**. Speaker **911** converts the electrical signal to audible sound waves. Audio circuitry **910** also receives electrical signals converted by microphone **913** from sound waves. Audio circuitry **910** converts the electrical signal to audio data and transmits the audio data to peripherals interface **918** for processing. Audio data may be retrieved from and/or transmitted to memory **902** and/or RF circuitry **908** by peripherals interface **918**. In some embodiments, audio circuitry **910** also includes a headset jack. The headset jack provides an interface between audio circuitry **910** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

[0127] I/O subsystem **906** couples input/output peripherals on device **900**, such as touch screen **912** and other input control devices **916**, to peripherals interface **918**. I/O subsystem **906** may include display controller **956** and one or more input controllers **960** for other input control devices **916**. The one or more input controllers **960** receive/send electrical signals from/to other input control devices **916**. The other input control devices **916** may include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternative embodiments, input controller(s) **960** may be coupled to any (or none) of the following: a keyboard, infrared port, USB port, and a pointer device such as a mouse. The one or more buttons may include an up/down button for volume control of speaker **911** and/or microphone **913**. The one or more buttons may include a push button.

[0128] Touch-sensitive display **912** provides an input interface and an output interface between the device and a user. Display controller **956** receives and/or sends electrical signals from/to touch screen **912**. Touch screen **912** displays visual output to the user. The visual output may include graphics, text, icons, video, and any combination thereof (collectively termed “graphics”). In some embodiments, some or all of the visual output may correspond to user-interface objects.

[0129] Touch screen **912** has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **912** and display controller **956** (along with any associated modules and/or sets of instructions in memory **902**) detect contact (and any movement or breaking of the contact) on touch screen **912** and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on touch screen **912**. In an example embodiment, a point of contact between touch screen **912** and the user corresponds to a finger of the user.

[0130] Touch screen **912** may use LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies may be used in other embodiments. Touch screen **912** and display controller **956** may detect contact and any movement or breaking thereof using any of a variety of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **912**. In an example embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone®, iPod Touch®, and iPad® from Apple Inc. of Cupertino, California.

[0131] Touch screen **912** may have a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user may make contact with touch screen **912** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

[0132] In some embodiments, in addition to the touch screen **912**, device **900** may include a

touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad may be a touch-sensitive surface that is separate from touch screen **912** or an extension of the touch-sensitive surface formed by the touch screen.

[0133] Device **900** also includes power system **962** for powering the various components. Power system **962** may include a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

[0134] Device **900** may also include one or more optical sensors or cameras **964**. FIG. **9** shows an optical sensor coupled to optical sensor controller **958** in I/O subsystem **906**. Optical sensor **964** may, for example, include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors or photosensors. Optical sensor **964** receives light from the environment, projected through one or more lenses, and converts the light to data representing an image. In conjunction with imaging module **943** (also called a camera module), optical sensor **964** may capture still images and/or video sequences. In some embodiments, at least one optical sensor may be located on the back of device **900**, opposite touch screen display **912** on the front of the device. In some embodiments, the touch screen display may be used as a viewfinder for still and/or video image acquisition. In some embodiments, at least one optical sensor may instead or also be located on the front of the device.

[0135] Device **900** may also include one or more proximity sensors **966**. FIG. **9** shows proximity sensor **966** coupled to peripherals interface **918**. Alternatively, proximity sensor **966** may be coupled to input controller **960** in I/O subsystem **906**. In some embodiments, the proximity sensor turns off and disables touch screen **912** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

[0136] Device **900** may also include one or more orientation sensors **968**. In some embodiments, the one or more orientation sensors include one or more accelerometers (e.g., one or more linear accelerometers and/or one or more rotational accelerometers). In some embodiments, the one or more orientation sensors include one or more gyroscopes. In some embodiments, the one or more orientation sensors include one or more magnetometers. In some embodiments, the one or more orientation sensors include one or more of global positioning system (GPS), Global Navigation Satellite System (GLONASS), and/or other global navigation system receivers. The GPS, GLONASS, and/or other global navigation system receivers may be used for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **900**. In some embodiments, the one or more orientation sensors include any combination of orientation/rotation sensors. FIG. **9** shows the one or more orientation sensors **968** coupled to peripherals interface **918**. Alternatively, the one or more orientation sensors **968** may be coupled to an input controller **960** in I/O subsystem **906**. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more orientation sensors.

[0137] In some embodiments, device **900** may also include one or more other sensors (not shown) including but not limited to ambient light sensors and motion detectors. These sensors may be coupled to peripherals interface **918** or, alternatively, may be coupled to an input controller **960** in I/O subsystem **906**. For example, in some embodiments, device **900** may include at least one forward-facing (away from the user) and at least one backward-facing (towards the user) light sensors that may be used to collect ambient lighting metrics from the environment of the device **900** for use in video and image capture, processing, and display applications.

[0138] In some embodiments, the software components stored in memory **902** include operating system **926**, communication module **928**, contact/motion module (or set of instructions) **930**, graphics module **932**, text input module **934**, Global Positioning System (GPS) module **935**, and

applications **936**. Furthermore, in some embodiments memory **902** stores device/global internal state **957**. Device/global internal state **957** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **912**; sensor state, including information obtained from the device's various sensors and input control devices **916**; and location information concerning the device's location and/or attitude.

[0139] Operating system **926** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

[0140] Communication module **928** facilitates communication with other devices over one or more external ports **924** and also includes various software components for handling data received by RF circuitry **908** and/or external port **924**. External port **924** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with the 30-pin connector used on iPod (trademark of Apple Inc.) devices.

[0141] Contact/motion module **930** may detect contact with touch screen **912** (in conjunction with display controller **956**) and other touch sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **930** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **930** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, may include determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations may be applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., “multi-touch”/multiple finger contacts). In some embodiments, contact/motion module **930** and display controller **956** detect contact on a touchpad.

[0142] Contact/motion module **930** may detect a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns. Thus, a gesture may be detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (lift off) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (lift off) event.

[0143] Graphics module **932** includes various software components for rendering and displaying graphics on touch screen **912** or other display, including components for changing the intensity of graphics that are displayed. As used herein, the term “graphics” includes any object that can be displayed to a user, including without limitation text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations and the like.

[0144] In some embodiments, graphics module **932** stores data representing graphics to be used. Each graphic may be assigned a corresponding code. Graphics module **932** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **956**.

[0145] Text input module **934**, which may be a component of graphics module **932**, provides soft keyboards for entering text in various applications that need text input.

[0146] GPS module **935** determines the location of the device and provides this information for use in various applications (e.g., to telephone module **938** for use in location-based dialing, to camera module **943** as picture/video metadata, and to applications that provide location-based services such as map/navigation applications).

[0147] Applications **936** may include one or more of, but are not limited to, the following modules (or sets of instructions), or a subset or superset thereof: [0148] telephone module **938**; [0149] video conferencing module **939**; [0150] camera module **943** for still and/or video imaging; [0151] image management module **944**; [0152] browser module **947**; [0153] search module **951**; [0154] video and music player module **952**, which may be made up of a video player module and a music player module; and/or [0155] online video module **955**. [0156] one or more other modules not shown, such as a gaming module.

[0157] Examples of other applications **936** that may be stored in memory **902** include but are not limited to other word processing applications, other image editing applications, drawing applications, presentation applications, communication/social media applications, map applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

[0158] In conjunction with RF circuitry **908**, audio circuitry **910**, speaker **911**, microphone **913**, touch screen **912**, display controller **956**, contact module **930**, graphics module **932**, and text input module **934**, telephone module **938** may be used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in an address book, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation and disconnect or hang up when the conversation is completed. As noted above, the wireless communication may use any of a variety of communications standards, protocols and technologies.

[0159] In conjunction with RF circuitry **908**, audio circuitry **910**, speaker **911**, microphone **913**, touch screen **912**, display controller **956**, optical sensor **964**, optical sensor controller **958**, contact/motion module **930**, graphics module **932**, text input module **934**, and telephone module **938**, videoconferencing module **939** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

[0160] In conjunction with touch screen **912**, display controller **956**, optical sensor(s) **964**, optical sensor controller **958**, contact/motion module **930**, graphics module **932**, and image management module **944**, camera module **943** includes executable instructions to capture still images or video (including a video stream) and store them into memory **902**, modify characteristics of a still image or video, or delete a still image or video from memory **902**.

[0161] In conjunction with touch screen **912**, display controller **956**, contact/motion module **930**, graphics module **932**, text input module **934**, and camera module **943**, image management module **944** includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

[0162] In conjunction with RF circuitry **908**, touch screen **912**, display system controller **956**, contact/motion module **930**, graphics module **932**, and text input module **934**, browser module **947** includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

[0163] In conjunction with touch screen **912**, display system controller **956**, contact/motion module **930**, graphics module **932**, and text input module **934**, search module **951** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **902** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

[0164] In conjunction with touch screen **912**, display system controller **956**, contact/motion module **930**, graphics module **932**, audio circuitry **910**, speaker **911**, RF circuitry **908**, and browser module **947**, video and music player module **952** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present or otherwise play back videos (e.g., on touch screen **912** or on an external, connected display via external port **924**). In some embodiments, device **900** may include the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

[0165] In conjunction with touch screen **912**, display system controller **956**, contact/motion module **930**, graphics module **932**, audio circuitry **910**, speaker **911**, RF circuitry **908**, text input module **934**, and browser module **947**, online video module **955** includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port **924**), and otherwise manage online videos in one or more video formats, such as the H.264/AVC format or the H.265/HEVC format.

[0166] Each of the above identified modules and applications correspond to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules may be combined or otherwise rearranged in various embodiments. In some embodiments, memory **902** may store a subset of the modules and data structures identified above. Furthermore, memory **902** may store additional modules and data structures not described above.

[0167] In some embodiments, device **900** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **900**, the number of physical input control devices (such as push buttons, dials, and the like) on device **900** may be reduced.

[0168] The predefined set of functions that may be performed exclusively through a touch screen and/or a touchpad include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **900** to a main, home, or root menu from any user interface that may be displayed on device **900**. In such embodiments, the touchpad may be referred to as a “menu button.” In some other embodiments, the menu button may be a physical push button or other physical input control device instead of a touchpad.

[0169] FIG. **10** depicts illustrates an example portable multifunction device **900** that may include one or more cameras, in accordance with some embodiments. In some embodiments, the portable multifunction device **900** may include one or multiple features, components, and/or functionality of embodiments described herein with reference to FIGS. **1-9** and **11**.

[0170] The device **900** may have a touch screen **912**. The touch screen **912** may display one or more graphics within user interface (UI) **1000**. In this embodiment, as well as others described below, a user may select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **1002** (not drawn to scale in the figure) or one or more styluses **1003** (not drawn to scale in the figure).

[0171] Device **900** may also include one or more physical buttons, such as “home” or menu button **1004**. As described previously, menu button **1004** may be used to navigate to any application **936** in a set of applications that may be executed on device **900**. Alternatively, in some embodiments, the menu button **1004** is implemented as a soft key in a GUI displayed on touch screen **912**.

[0172] In one embodiment, device **900** includes touch screen **912**, menu button **1004**, push button **1006** for powering the device on/off and locking the device, volume adjustment button(s) **1008**, Subscriber Identity Module (SIM) card slot **1010**, head set jack **1012**, and docking/charging external port **924**. Push button **1006** may be used to turn the power on/off on the device by

depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device **900** also may accept verbal input for activation or deactivation of some functions through microphone **913**.

[0173] It should be noted that, although many of the examples herein are given with reference to optical sensor(s)/camera(s) **964** (on the front of a device), one or more rear-facing cameras or optical sensors that are pointed opposite from the display may be used instead of, or in addition to, an optical sensor(s)/camera(s) **964** on the front of a device.

#### Example Computer System

[0174] FIG. **11** illustrates an example computer system **1100** that may include one or more cameras, in accordance with some embodiments. In some embodiments, the computer system **1100** may include one or multiple features, components, and/or implement functionality of embodiments described herein with reference to FIGS. **1-10**.

[0175] The computer system **1100** may be configured to execute any or all of the embodiments described above. In different embodiments, computer system **1100** may be any of various types of devices, including, but not limited to, a personal computer system, desktop computer, laptop, notebook, tablet, slate, pad, or netbook computer, mainframe computer system, handheld computer, workstation, network computer, a camera, a set top box, a mobile device, a consumer device, video game console, handheld video game device, application server, storage device, a television, a video recording device, a peripheral device such as a switch, modem, router, or in general any type of computing or electronic device.

[0176] Various embodiments of a camera motion control system as described herein, including embodiments of magnetic position sensing, as described herein may be executed in one or more computer systems **1100**, which may interact with various other devices. Note that any component, action, or functionality described above with respect to FIGS. **1-10** may be implemented on one or more computers configured as computer system **1100** of FIG. **11**, according to various embodiments. In the illustrated embodiment, computer system **1100** includes one or more processors **1110** coupled to a system memory **1120** via an input/output (I/O) interface **1130**.

Computer system **1100** further includes a network interface **1140** coupled to I/O interface **1130**, and one or more input/output devices **1150**, such as cursor control device **1160**, keyboard **1170**, and display(s) **1180**. In some cases, it is contemplated that embodiments may be implemented using a single instance of computer system **1100**, while in other embodiments multiple such systems, or multiple nodes making up computer system **1100**, may be configured to host different portions or instances of embodiments. For example, in one embodiment some elements may be implemented via one or more nodes of computer system **1100** that are distinct from those nodes implementing other elements.

[0177] In various embodiments, computer system **1100** may be a uniprocessor system including one processor **1110**, or a multiprocessor system including several processors **1110** (e.g., two, four, eight, or another suitable number). Processors **1110** may be any suitable processor capable of executing instructions. For example, in various embodiments processors **1110** may be general-purpose or embedded processors implementing any of a variety of instruction set architectures (ISAs), such as the x86, PowerPC, SPARC, or MIPS ISAs, or any other suitable ISA. In multiprocessor systems, each of processors **1110** may commonly, but not necessarily, implement the same ISA.

[0178] System memory **1120** may be configured to store program instructions **1122** accessible by processor **1110**. In various embodiments, system memory **1120** may be implemented using any suitable memory technology, such as static random access memory (SRAM), synchronous dynamic RAM (SDRAM), nonvolatile/Flash-type memory, or any other type of memory. Additionally, existing camera control data **1132** of memory **1120** may include any of the information or data structures described above. In some embodiments, program instructions and/or data may be



received, sent or stored upon different types of computer-accessible media or on similar media separate from system memory **1120** or computer system **1100**. While computer system **1100** is described as implementing the functionality of functional blocks of previous figures, any of the functionality described herein may be implemented via such a computer system.

[0179] In one embodiment, I/O interface **1130** may be configured to coordinate I/O traffic between processor **1110**, system memory **1120**, and any peripheral devices in the device, including network interface **1140** or other peripheral interfaces, such as input/output devices **1150**. In some embodiments, I/O interface **1130** may perform any necessary protocol, timing or other data transformations to convert data signals from one component (e.g., system memory **1120**) into a format suitable for use by another component (e.g., processor **1110**). In some embodiments, I/O interface **1130** may include support for devices attached through various types of peripheral buses, such as a variant of the Peripheral Component Interconnect (PCI) bus standard or the Universal Serial Bus (USB) standard, for example. In some embodiments, the function of I/O interface **1130** may be split into two or more separate components, such as a north bridge and a south bridge, for example. Also, in some embodiments some or all of the functionality of I/O interface **1130**, such as an interface to system memory **1120**, may be incorporated directly into processor **1110**.

[0180] Network interface **1140** may be configured to allow data to be exchanged between computer system **1100** and other devices attached to a network **1185** (e.g., carrier or agent devices) or between nodes of computer system **1100**. Network **1185** may in various embodiments include one or more networks including but not limited to Local Area Networks (LANs) (e.g., an Ethernet or corporate network), Wide Area Networks (WANs) (e.g., the Internet), wireless data networks, some other electronic data network, or some combination thereof. In various embodiments, network interface **1140** may support communication via wired or wireless general data networks, such as any suitable type of Ethernet network, for example; via telecommunications/telephony networks such as analog voice networks or digital fiber communications networks; via storage area networks such as Fibre Channel SANs, or via any other suitable type of network and/or protocol.

[0181] Input/output devices **1150** may, in some embodiments, include one or more display terminals, keyboards, keypads, touchpads, scanning devices, voice or optical recognition devices, or any other devices suitable for entering or accessing data by one or more computer systems **1100**. Multiple input/output devices **1150** may be present in computer system **1100** or may be distributed on various nodes of computer system **1100**. In some embodiments, similar input/output devices may be separate from computer system **1100** and may interact with one or more nodes of computer system **1100** through a wired or wireless connection, such as over network interface **1140**.

[0182] As shown in FIG. **11**, memory **1120** may include program instructions **1122**, which may be processor-executable to implement any element or action described above. In one embodiment, the program instructions may implement the methods described above. In other embodiments, different elements and data may be included. Note that data may include any data or information described above.

[0183] Those skilled in the art will appreciate that computer system **1100** is merely illustrative and is not intended to limit the scope of embodiments. In particular, the computer system and devices may include any combination of hardware or software that can perform the indicated functions, including computers, network devices, Internet appliances, PDAs, wireless phones, pagers, etc. Computer system **1100** may also be connected to other devices that are not illustrated, or instead may operate as a stand-alone system. In addition, the functionality provided by the illustrated components may in some embodiments be combined in fewer components or distributed in additional components. Similarly, in some embodiments, the functionality of some of the illustrated components may not be provided and/or other additional functionality may be available.

[0184] Those skilled in the art will also appreciate that, while various items are illustrated as being stored in memory or on storage while being used, these items or portions of them may be transferred between memory and other storage devices for purposes of memory management and

data integrity. Alternatively, in other embodiments some or all of the software components may execute in memory on another device and communicate with the illustrated computer system via inter-computer communication. Some or all of the system components or data structures may also be stored (e.g., as instructions or structured data) on a computer-accessible medium or a portable article to be read by an appropriate drive, various examples of which are described above. In some embodiments, instructions stored on a computer-accessible medium separate from computer system **1100** may be transmitted to computer system **1100** via transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as a network and/or a wireless link. Various embodiments may further include receiving, sending or storing instructions and/or data implemented in accordance with the foregoing description upon a computer-accessible medium. Generally speaking, a computer-accessible medium may include a non-transitory, computer-readable storage medium or memory medium such as magnetic or optical media, e.g., disk or DVD/CD-ROM, volatile or non-volatile media such as RAM (e.g. SDRAM, DDR, RDRAM, SRAM, etc.), ROM, etc. In some embodiments, a computer-accessible medium may include transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as network and/or a wireless link.

[0185] The methods described herein may be implemented in software, hardware, or a combination thereof, in different embodiments. In addition, the order of the blocks of the methods may be changed, and various elements may be added, reordered, combined, omitted, modified, etc. Various modifications and changes may be made as would be obvious to a person skilled in the art having the benefit of this disclosure. The various embodiments described herein are meant to be illustrative and not limiting. Many variations, modifications, additions, and improvements are possible. Accordingly, plural instances may be provided for components described herein as a single instance. Boundaries between various components, operations and data stores are somewhat arbitrary, and particular operations are illustrated in the context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within the scope of claims that follow. Finally, structures and functionality presented as discrete components in the example configurations may be implemented as a combined structure or component. These and other variations, modifications, additions, and improvements may fall within the scope of embodiments as defined in the claims that follow.

## Claims

**1.-20.** (canceled)

**21.** A camera, comprising: a lens that defines an optical axis; an image sensor configured to capture light passing through the lens and convert captured light into image signals; a voice coil motor (VCM) actuator, comprising: a magnet; and a plurality of coils; a sensor shift platform coupled to the image sensor such that the image sensor is moveable together with the sensor shift platform; a coil holder configured to support one or more coils of the plurality of coils; a set of one or more flexures configured to: electrically connect, via one or more electrical traces, a static member of the camera to the sensor shift platform and the coil holder, and mechanically connect the static member of the camera to the sensor shift platform and the coil holder; wherein the VCM actuator is configured to cause at least one of optical image stabilization (OIS) movement of the image sensor, autofocus (AF) movement of one of the image sensor or the lens, or tilt movement of one of the image sensor or the lens.

**22.** The camera of claim 21, wherein to tilt the image sensor or the lens, the VCM actuator is configured to cause a first coil of the plurality of coils to magnetically interact with the magnet independently relative to a second coil of the plurality of coils.

**23.** The camera of claim 21, wherein the plurality of coils further comprises: an optical image stabilization (OIS) coil, wherein the OIS coil is attached to the coil holder and positioned proximate

the magnet; wherein the VCM actuator is configured to cause the OIS coil to magnetically interact with the magnet to move the image sensor in a direction orthogonal to the optical axis.

**24.** The camera of claim 21, wherein the lens is a stationary lens.

**25.** The camera of claim 21, wherein the one or more flexures comprise: a bottom flexure that extends along a first plane orthogonal to the optical axis; and a top flexure that extends along a second plane orthogonal to the optical axis.

**26.** The camera of claim 21, wherein the camera is configured to convey current to drive at least one of the plurality of coils via the one or more electrical traces of the one or more flexures.

**27.** The camera of claim 21, wherein the VCM actuator is configured to cause at least one coil of the plurality of coils to magnetically interact with the magnet to tilt the image sensor, and the coil holder is attached to the sensor shift platform.

**28.** The camera of claim 27, wherein the at least one coil of the plurality of coils is also configured to move the sensor shift platform and the image sensor in directions parallel to the optical axis for autofocus (AF).

**29.** The camera of claim 21, wherein the lens is configured to move in directions along the optical axis for autofocus (AF).

**30.** The camera of claim 29, wherein the VCM actuator is configured to cause at least one coil of the plurality of coils to magnetically interact with the magnet to tilt the lens, and the coil holder is fixedly attached to the lens and moves independently of the sensor shift platform and the image sensor.

**31.** The camera of claim 29, wherein the plurality of coils further comprises: an optical image stabilization (OIS) coil, wherein the OIS coil is attached to the sensor shift platform and positioned proximate the magnet; wherein the VCM actuator is configured to cause the OIS coil to magnetically interact with the magnet to move the image sensor in a direction orthogonal to the optical axis independently of the coil holder.

**32.** A device, comprising: one or more processors; memory storing program instructions that are executable by the one or more processors to control operation of a camera; and the camera, comprising: a lens that defines an optical axis; an image sensor configured to capture light passing through the lens and convert captured light into image signals; a voice coil motor (VCM) actuator, comprising: a magnet; and a plurality of coils; a sensor shift platform coupled to the image sensor such that the image sensor is moveable together with the sensor shift platform; a coil holder configured to support one or more coils of the plurality of coils; a set of one or more flexures configured to: electrically connect, via one or more electrical traces, a static member of the camera to the sensor shift platform and the coil holder, and mechanically connect the static member of the camera to the sensor shift platform and the coil holder; wherein the VCM actuator is configured to cause at least one of optical image stabilization (OIS) movement of the image sensor, autofocus (AF) movement of one of the image sensor or the lens, or tilt movement of one of the image sensor or the lens.

**33.** The device of claim 32, wherein the VCM actuator is configured to cause at least one coil of the plurality of coils to magnetically interact with the magnet to tilt the image sensor, and the coil holder is attached to the sensor shift platform.

**34.** The device of claim 33, wherein at least one coils of the plurality of coils is also configured to move the sensor shift platform and the image sensor in directions parallel to the optical axis for autofocus (AF).

**35.** The device of claim 32, wherein the lens is configured to move in directions along the optical axis for autofocus (AF).

**36.** The device of claim 35, wherein the VCM actuator is configured to cause at least one coil of the plurality of coils to magnetically interact with the magnet to tilt the lens, and the coil holder is fixedly attached to the lens and moves independently of the sensor shift platform and the image sensor.

**37.** The device of claim 35, wherein the plurality of coils further comprises: an optical image stabilization (OIS) coil, wherein the OIS coil is attached to the sensor shift platform and positioned proximate the magnet; wherein the VCM actuator is configured to cause the OIS coil to magnetically interact with the magnet to move the image sensor in a direction orthogonal to the optical axis independently of the coil holder.

**38.** A system, comprising: a voice coil motor (VCM) actuator, comprising: a magnet; and a plurality of coils; a sensor shift platform coupled to the image sensor such that the image sensor is moveable together with the sensor shift platform; a coil holder configured to support one or more coils of the plurality of coils; a set of one or more flexures configured to: electrically connect, via one or more electrical traces, a static member of the camera to the sensor shift platform and the coil holder, and mechanically connect the static member of the camera to the sensor shift platform and the coil holder; wherein the VCM actuator is configured to cause at least one of optical image stabilization (OIS) movement of the image sensor, autofocus (AF) movement of one of the image sensor or the lens, or tilt movement of one of the image sensor or the lens.

**39.** The system of claim 38, wherein the VCM actuator is configured to cause at least one coil of the plurality of coils to magnetically interact with the magnet to tilt the image sensor, and the coil holder is attached to an upper surface of the sensor shift platform.

**40.** The system of claim 38, wherein the VCM actuator is configured to cause at least one coil of the plurality of coils to magnetically interact with the magnet to tilt the lens, and the coil holder is fixedly attached to the lens and moves independently of the sensor shift platform and the image sensor.

---