

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395289
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Takeda; Kazuki et al.

Reference signal configuration for secondary cell activation

Abstract

Methods, systems, and devices for wireless communications are described, in which temporary reference signals may be configured for use in secondary cell (SCell) activation. A user equipment (UE) may perform wireless communications with a first serving cell supported by a base station, and may receive an indication that a SCell is to be activated. As a result of activation of the SCell, the UE may perform one or more measurements on a reference signal of the SCell that is being activated. The one or more measurements may be performed on a temporary reference signal of the SCell that has one or more parameters that are indicated to the UE with the SCell activation information. The one or more parameter may be indicated by downlink control information (DCI), one or more medium access control (MAC) control elements, implicit signaling, or any combinations thereof.

Inventors: Takeda; Kazuki (Tokyo, JP), Rico Alvarino; Alberto (San Diego, CA), Gaal; Peter (San Diego, CA), Montojo; Juan (San Diego, CA), Chen; Wanshi (San Diego, CA), Luo; Tao (San Diego, CA), Purkayastha; Punyaslok (San Diego, CA)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 1000008762883

Assignee: QUALCOMM Incorporated (San Diego, CA)

Appl. No.: 17/507049

Filed: October 21, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220131669 A1	Apr. 28, 2022

Related U.S. Application Data

Publication Classification

Int. Cl.: H04W56/00 (20090101); H04L5/00 (20060101); H04W24/08 (20090101); H04W72/23 (20230101)

U.S. Cl.:

CPC H04L5/0048 (20130101); H04W24/08 (20130101); H04W72/23 (20230101);

Field of Classification Search

CPC: H04L (5/0048); H04L (72/23); H04L (24/08)

USPC: 370/252

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11456830	12/2021	Lee et al.	N/A	N/A
2011/0268087	12/2010	Kwon et al.	N/A	N/A
2019/0207662	12/2018	Zhou	N/A	H04W 72/0446
2019/0215136	12/2018	Zhou et al.	N/A	N/A
2019/0356444	12/2018	Noh et al.	N/A	N/A
2021/0377876	12/2020	Jeon	N/A	H04W 24/08
2024/0155595	12/2023	Cirik	N/A	H04W 72/046

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110149178	12/2018	CN	N/A
111385078	12/2019	CN	N/A
3897046	12/2020	EP	N/A
2019159296	12/2018	JP	N/A
2019139769	12/2018	WO	N/A
2020034889	12/2019	WO	N/A
WO-2020135341	12/2019	WO	N/A

OTHER PUBLICATIONS

“Li, A Signalling Processing, Sending Method, Device And Storage Medium, Nov. 13, 2020, CN 111934837” (Year: 2020). cited by examiner

“Zhang et al., Communication Method and Apparatus for Activating Secondary Cell, Apr. 1, 2021, WO 2021056334” (Year: 2019). cited by examiner

International Search Report and Written Opinion—PCT/US2021/056234—ISA/EPO—Apr. 4, 2022. cited by applicant

Vivo: “Discussion on Efficient Activation/De-Activation Mechanism for Scells”, 3GPP TSG-RAN WG1 meeting #102-e, 3GPP Draft, R1-2005411, 3rd Generation Partnership Project (3GPP),

Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1, No. e-Meeting, Aug. 17, 2020-Aug. 28, 2020, 10 Pages, Aug. 8, 2020 (Aug. 8, 2020), XP051917436, Retrieved from the Internet: URL:

https://ftp.3gpp.org/tsg_ran/WG1_RL1/TSGR1_102-e/Docs/R1-2005411.zip R1-2005411

Discussion on efficient activation/de-activation mechanism for SCells.docx [retrieved on Aug. 8, 2020] Sections 1-3. cited by applicant

CATT: “Discussion on Efficient Activation and De-Activation Mechanism for SCell in NR CA”, 3GPP Draft, R1-2005698, Vo1. RAN WG1, No. e-Meeting, Aug. 17, 2020-Aug. 28, 2020, Aug. 8, 2020 (Aug. 8, 2020), XP051917673, Retrieved from the Internet:

URL:https://ftp.3gpp.org/tsg_ran/WG1_RL1/TSGR1_102-e/Docs/R1-2005698.zip R1-2005698.docx [retrieved on Aug. 8, 2020] Sections 1-3. cited by applicant

Partial International Search Report—PCT/US2021/056234—ISA/EPO—Feb. 10, 2022. cited by applicant

VIVO: “Discussion on Efficient Activation/de-activation Mechanism for SCells”, R1-2005411, 3GPP TSG-RAN WG1 Meeting #102-e e-Meeting, August 17-28, Aug. 8, 2020, 10 Pages. cited by applicant

Mediatek Inc: “Efficient and Low Latency SCell Data Transmission for NR CA”, 3GPP TSG RAN WG1 Meeting RAN1 #99, R1-1912101, Reno, U.S.A., Nov. 18-22, 2019, XP051823194, 15 pages. cited by applicant

Qualcomm Incorporated: “Discussion on fast SCell Activation Based on Aperiodic TRS (A-TRS)”, R2-1914381, 3GPP TSG RAN WG2 Meeting #108 Reno, Nevada, US, Nov. 18-22, 2019, Nov. 8, 2019, pp. 1-7. cited by applicant

Primary Examiner: Mesfin; Yemane

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary

CROSS REFERENCE (1) The present application for patent claims the benefit of U.S. Provisional Patent Application No. 63/094,996 by TAKEDA et al., entitled “REFERENCE SIGNAL CONFIGURATION FOR SECONDARY CELL ACTIVATION,” filed Oct. 22, 2020, assigned to the assignee hereof, and expressly incorporated by reference herein.

TECHNICAL FIELD

(1) The following relates to wireless communications, including reference signal configuration for secondary cell activation.

BACKGROUND

(2) Wireless communications systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on. These systems may be capable of supporting communication with multiple users by sharing the available system resources (e.g., time, frequency, and power). Examples of such multiple-access systems include fourth generation (4G) systems such as Long Term Evolution (LTE) systems, LTE-Advanced (LTE-A) systems, or LTE-A Pro systems, and fifth generation (5G) systems which may be referred to as New Radio (NR) systems. These systems may employ technologies such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal frequency division multiple access (OFDMA), or discrete Fourier transform spread orthogonal frequency division multiplexing (DFT-S-OFDM). A wireless multiple-access communications system may include one or more base stations or one or more

network access nodes, each simultaneously supporting communication for multiple communication devices, which may be otherwise known as user equipment (UE).

(3) In some wireless communications systems, the base station may communicate with a UE via one or more serving cells, such as a primary cell (PCell) and one or more secondary cells (SCells). A base station may activate additional serving cells (e.g., SCells) at the UE to increase data throughput, to alleviate network congestion, or both. Conversely, the network may also deactivate serving cells which were previously activated. Efficient techniques for activating serving cells may help enhance the efficiency and reliability of a wireless communications system.

SUMMARY

(4) The described techniques relate to improved methods, systems, devices, and apparatuses that support reference signal configuration for secondary cell activation. Various described techniques are directed to the use of reference signals (e.g., temporary reference signals, which may be referred to as aperiodic reference signals herein) on serving cells which are transmitted in order to decrease a time duration for activation of a serving cells at a user equipment (UE). In some aspects, a UE may perform wireless communications with a first serving cell supported by a base station (e.g., a primary cell (PCell)), and may receive an indication that a secondary cell (SCell) supported by the base station (or a different base station) is to be activated. As a result of activation of the SCell, the UE may perform one or more measurements on a reference signal of the SCell that is being activated, in order to perform automatic gain control (AGC), time tracking, frequency tracking, or any combinations thereof, for the SCell. In order to shorten the activation time for the SCell, a temporary reference signal may be transmitted on the SCell in advance of one or more other reference signals transmitted by the SCell (e.g., a reference signal transmitted with a synchronization signal block (SSB) that may have a relatively long periodicity). By receiving the temporary reference signal, the activation time for the SCell may be reduced, allowing for data communications relatively quickly after SCell activation.

(5) In some cases, the SCell activation message may indicate one or more parameters for the temporary reference signal, such as a carrier for the temporary reference signal, a slot location of the temporary reference signal, a reference signal configuration, a beam configuration for the temporary signal, or any combinations thereof. In some cases, a downlink control information (DCI) communication from the base station that activates the SCell may provide the one or more parameters for the temporary reference signal. In other cases, a medium access control (MAC) control element (CE) may provide the one or more parameters for the temporary reference signal. Additionally or alternatively, one or more parameters for the temporary reference signal may implicitly signaled by the base station.

(6) A method of wireless communication at a UE is described. The method may include receiving, from a base station, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell, identifying, based on the secondary cell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and measuring one or more characteristics of the secondary cell based on the aperiodic reference signal.

(7) An apparatus for wireless communication at a UE is described. The apparatus may include a processor, memory coupled (e.g., operatively, communicatively, functionally, electronically, and/or electrically) with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to receive, from a base station, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell, identify, based on the secondary cell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters

include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and measure one or more characteristics of the secondary cell based on the aperiodic reference signal.

(8) Another apparatus for wireless communication at a UE is described. The apparatus may include means for receiving, from a base station, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell, identifying, based on the secondary cell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and measuring one or more characteristics of the secondary cell based on the aperiodic reference signal.

(9) A non-transitory computer-readable medium storing code for wireless communication at a UE is described. The code may include instructions executable by a processor to receive, from a base station, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell, identify, based on the secondary cell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and measure one or more characteristics of the secondary cell based on the aperiodic reference signal.

(10) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the identifying may include operations, features, means, or instructions for receiving, from the base station, one or more of DCI or a MAC-CE that includes information associated with the aperiodic reference signal, and determining, based on the DCI, the MAC-CE, implicit signaling, or combinations thereof, the one or more parameters for the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal include one or more of the carrier for the aperiodic reference signal, the slot location of the aperiodic reference signal, a mapping of resources of the aperiodic reference signal, a power offset of the aperiodic reference signal relative to a downlink shared channel or SSB transmission, a quasi-co-location (QCL) assumption for a beam of the aperiodic reference signal, a transmission configuration indicator (TCI) state of the aperiodic reference signal, or any combinations thereof.

(11) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the aperiodic reference signal may be transmitted after a time gap associated with the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the time gap corresponds to a first predetermined time period after an acknowledgment of the secondary cell activation message by the UE, a second predetermined time period after a downlink control channel communication that provides the DCI, or a third predetermined time period after an acknowledgment of the DCI by the UE.

(12) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, from the base station, DCI that indicates the one or more parameters for the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the DCI schedules a shared channel communication that provides the secondary cell activation message and indicates the one or more parameters for the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be provided in

an information field in the DCI, and where the information field may have a same format as a channel state information (CSI) request field that may be transmitted in DCI.

(13) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the DCI may be a separate DCI from a scheduling DCI that schedules a shared channel communication that provides the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the separate DCI includes other scheduling information for downlink shared channel communications with the UE, and the one or more parameters for the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the separate DCI may be included with a downlink control channel communication that does not provide scheduling information for shared channel communications. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be provided in one or more fields in the separate DCI that may be otherwise used for the scheduling information for shared channel communications.

(14) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be provided in an information field having a same format as a CSI request field in an uplink grant. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, a number of bits in the information field may be configured by radio resource control (RRC) signaling or may be determined based on a number of available tracking reference signal (TRS) states. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the information field may be mapped to one or more of a TRS timing or slot, a TRS resource, a TRS power offset, or any combinations thereof, for one or multiple serving cells. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be provided in one or more of a frequency domain resource assignment (FDRA) field, a time domain resource assignment (TDRA) field, or any combinations thereof. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the DCI may have a fallback DCI format or a non-fallback DCI format.

(15) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the DCI indicates that the UE is not to measure the aperiodic reference signal, and where the measuring of the one or more characteristics the secondary cell may be based on one or more channel measurements of a SSB associated with the secondary cell.

(16) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, measurements of the aperiodic reference signal may be triggered by the DCI having a preconfigured DCI format. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the preconfigured DCI format may be configured by RRC signaling.

(17) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein measurements of the aperiodic reference signal may be triggered by the DCI located in a preconfigured DCI search space set. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, one or more preconfigured DCI search space sets that can contain DCI that triggers measurement of the aperiodic reference signal may be configured by RRC signaling.

(18) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, from the base station, a MAC-CE that indicates the one or more parameters for the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the MAC-CE that provides the one or more parameters for the aperiodic

reference signal also provides the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, a first MAC-CE provides the one or more parameters for the aperiodic reference signal and a second MAC-CE provides the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the first MAC-CE and the second MAC-CE may be in a same downlink shared channel communication, or may be in different downlink shared channel communications, from the base station.

(19) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the MAC-CE includes a first field that indicates the secondary cell that is to be activated and a second field that indicates the one or more parameters for the aperiodic reference signal for the secondary cell that is to be activated. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the MAC-CE includes a field that carries an indication of the one or more parameters for the aperiodic reference signal for two or more secondary cells. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the MAC-CE includes a first field that indicates a carrier of the aperiodic reference signal, and a second field that indicates one or more other parameters for the aperiodic reference signal.

(20) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, subsequent to receiving the MAC-CE, a DCI transmission from the base station that disables the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a preconfigured DCI format. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the preconfigured DCI format may be configured by RRC signaling. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a DCI transmission in a DCI search space set that is configured by RRC signaling.

(21) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be implicitly indicated by a MAC-CE that carries the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be preconfigured at the UE by higher layer signaling.

(22) A method of wireless communication at a base station is described. The method may include transmitting, to a UE, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell, identifying, based on the secondary cell activation message, one or more parameters for an aperiodic reference signal of the secondary cell, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and transmitting the aperiodic reference signal to the UE based on the identifying.

(23) An apparatus for wireless communication at a base station is described. The apparatus may include a processor, memory coupled (e.g., operatively, communicatively, functionally, electronically, and/or electrically) with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to transmit, to a UE, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell, identify, based on the secondary cell activation message, one or more parameters for an aperiodic reference signal of the secondary cell, where the one or more

parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and transmit the aperiodic reference signal to the UE based on the identifying.

(24) Another apparatus for wireless communication at a base station is described. The apparatus may include means for transmitting, to a UE, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell, identifying, based on the secondary cell activation message, one or more parameters for an aperiodic reference signal of the secondary cell, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and transmitting the aperiodic reference signal to the UE based on the identifying.

(25) A non-transitory computer-readable medium storing code for wireless communication at a base station is described. The code may include instructions executable by a processor to transmit, to a UE, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell, identify, based on the secondary cell activation message, one or more parameters for an aperiodic reference signal of the secondary cell, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and transmit the aperiodic reference signal to the UE based on the identifying.

(26) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the UE, one or more of DCI or a MAC-CE that includes information associated with the aperiodic reference signal, and where the one or more parameters for the aperiodic reference signal may be indicated by the DCI, the MAC-CE, an implicit indication, or any combinations thereof. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal include one or more of the carrier for the aperiodic reference signal, the slot location of the aperiodic reference signal, a mapping of resources of the aperiodic reference signal, a power offset of the aperiodic reference signal relative to a downlink shared channel or SSB transmission, a QCL assumption for a beam of the aperiodic reference signal, a TCI state of the aperiodic reference signal, or any combinations thereof.

(27) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the aperiodic reference signal may be transmitted after a time gap associated with the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the time gap corresponds to a first predetermined time period after an acknowledgment of the secondary cell activation message by the UE, a second predetermined time period after a downlink control channel communication that provides the DCI, or a third predetermined time period after an acknowledgment of the DCI by the UE.

(28) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the UE, DCI that indicates the one or more parameters for the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the DCI schedules a shared channel communication that provides the secondary cell activation message and indicates the one or more parameters for the aperiodic reference signal.

(29) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be provided in

an information field in the DCI, and where the information field may have a same format as a CSI request field that may be transmitted in DCI. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the DCI may be a separate DCI from a scheduling DCI that schedules a shared channel communication that provides the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the separate DCI includes other scheduling information for downlink shared channel communications with the UE, and the one or more parameters for the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the separate DCI may be included with a downlink control channel communication that does not provide scheduling information for shared channel communications. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be provided in one or more fields in the separate DCI that may be otherwise used for the scheduling information for shared channel communications.

(30) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be provided in an information field having a same format as a CSI request field in an uplink grant. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, a number of bits in the information field may be configured by RRC signaling or may be determined based on a number of available TRS states. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the information field may be mapped to one or more of a TRS timing or slot, a TRS resource, a TRS power offset, or any combinations thereof, for one or multiple serving cells. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be provided in one or more of a FDRA field, a TDRA field, or any combinations thereof. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the DCI may have a fallback DCI format or a non-fallback DCI format.

(31) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the DCI indicates that the UE is not to measure the aperiodic reference signal, and where the UE measures one or more characteristics of the secondary cell based on one or more channel measurements of a SSB associated with the secondary cell.

(32) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein measurements of the aperiodic reference signal is triggered by the DCI having a preconfigured DCI format. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the preconfigured DCI format may be configured by RRC signaling.

(33) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein measurements of the aperiodic reference signal is triggered by the DCI located in a preconfigured DCI search space set. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, one or more preconfigured DCI search space sets that can contain DCI that triggers measurement of the aperiodic reference signal may be configured by RRC signaling.

(34) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the UE, a MAC-CE that indicates the one or more parameters for the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the MAC-CE that provides the one or more parameters for the aperiodic reference signal also provides the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, a first MAC-CE

provides the one or more parameters for the aperiodic reference signal and a second MAC-CE provides the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the first MAC-CE and the second MAC-CE may be in a same downlink shared channel communication, or may be in different downlink shared channel communications, from the base station.

(35) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the MAC-CE includes a first field that indicates the secondary cell that is to be activated and a second field that indicates the one or more parameters for the aperiodic reference signal for the secondary cell that is to be activated. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the MAC-CE includes a field that carries an indication of the one or more parameters for the aperiodic reference signal for two or more secondary cells. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the MAC-CE includes a first field that indicates a carrier of the aperiodic reference signal, and a second field that indicates one or more other parameters for the aperiodic reference signal.

(36) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, subsequent to transmitting the MAC-CE, a DCI transmission to the UE that disables the aperiodic reference signal. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a preconfigured DCI format. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the preconfigured DCI format may be configured by RRC signaling. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a DCI transmission in a DCI search space set that is configured by RRC signaling.

(37) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be implicitly indicated by a MAC-CE that carries the secondary cell activation message. In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more parameters for the aperiodic reference signal may be preconfigured at the UE by higher layer signaling.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example of a system for wireless communications that supports reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (2) FIG. 2 illustrates an example of a portion of a wireless communications system that supports reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (3) FIGS. 3 through 8 illustrate examples of resource allocation schemes that support reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (4) FIG. 9 illustrates examples of reference signal activation fields that support reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (5) FIG. 10 illustrates an example of a process flow that supports reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.

- (6) FIGS. 11 and 12 show block diagrams of devices that support reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (7) FIG. 13 shows a block diagram of a communications manager that supports reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (8) FIG. 14 shows a diagram of a system including a device that supports reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (9) FIGS. 15 and 16 show block diagrams of devices that support reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (10) FIG. 17 shows a block diagram of a communications manager that supports reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (11) FIG. 18 shows a diagram of a system including a device that supports reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.
- (12) FIGS. 19 through 27 show flowcharts illustrating methods that support reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure.

DETAILED DESCRIPTION

(13) In some wireless communications systems, the base station may communicate with a user equipment (UE) via one or more serving cells (e.g., a primary cell (PCell) and one or more secondary cells (SCells)). The network may activate one or more SCells, in addition to a PCell, at the UE to increase data throughput, to alleviate network congestion, or both. However, the process of activating a SCell may in some cases take a relatively long duration of time. For example, in some 5G NR systems, each cell may transmit relatively few reference signals and in some cases prior to activating the SCell the UE may measure one or more reference signals to obtain measurements associated with the SCell (e.g., automatic gain control (AGC) measurements, time tracking measurements, and/or frequency tracking measurements). In some cases, such UE measurements for SCell activation may be made using periodic synchronization signal block (SSB) transmissions of the SCell, which may occur at a relatively long periodicity. In order to reduce the time for activating the SCell, in some cases, a temporary reference signal may be transmitted by the SCell to allow for the UE measurements and faster activation of the SCell. Such a temporary reference signal may be an example of an aperiodic reference signal.

(14) In accordance with some aspects of the present disclosure, an SCell activation message may indicate one or more parameters for the temporary reference signal, such as a carrier for the temporary reference signal, a slot location of the temporary reference signal, a reference signal configuration, a beam configuration for the temporary signal, or any combinations thereof. In some cases, a downlink control information (DCI) communication from the base station that activates the SCell may provide the one or more parameters for the temporary reference signal. In other cases, a medium access control (MAC) control element (CE) may provide the one or more parameters for the temporary reference signal. Additionally or alternatively, one or more parameters for the temporary reference signal may be implicitly signaled by the base station.

(15) By reducing interruption periods on active serving cells which are attributable to activation/deactivation of additional serving cells, techniques described herein may enable more reliable, efficient wireless communications and improve overall user experience.

(16) Particular implementations of the subject matter described in this disclosure can be implemented to realize one or more of the following potential advantages. In some implementations, the described techniques may provide for improved wireless communications by reducing durations of activation times for SCells. In particular, by receiving reference signals (e.g., temporary reference signals) based on reference signal parameters associated with an activation command, a UE may activate an SCell with a reduced activation time relative to cases where the UE would use other periodically transmitted reference signals (e.g., in a SSB). By reducing activation time durations of SCells at the UE, techniques described herein may improve the efficiency and reliability of wireless communications, provide higher throughput, greater system

capacity, and lower latency, among other benefits.

(17) Aspects of the disclosure are initially described in the context of wireless communications systems. Additional aspects of the disclosure are described in the context of example resource allocation schemes, reference signal activation fields, and an example process flow. Aspects of the disclosure are further illustrated by and described with reference to apparatus diagrams, system diagrams, and flowcharts that relate to reference signal configuration for secondary cell activation.

(18) FIG. 1 illustrates an example of a wireless communications system **100** that supports reference signal configuration for secondary cell activation in accordance with aspects of the present disclosure. The wireless communications system **100** may include one or more base stations **105**, one or more UEs **115**, and a core network **130**. In some examples, the wireless communications system **100** may be a Long Term Evolution (LTE) network, an LTE-Advanced (LTE-A) network, an LTE-A Pro network, or a New Radio (NR) network. In some examples, the wireless communications system **100** may support enhanced broadband communications, ultra-reliable (e.g., mission critical) communications, low latency communications, communications with low-cost and low-complexity devices, or any combination thereof.

(19) The base stations **105** may be dispersed throughout a geographic area to form the wireless communications system **100** and may be devices in different forms or having different capabilities. The base stations **105** and the UEs **115** may wirelessly communicate via one or more communication links **125**. Each base station **105** may provide a coverage area **110** over which the UEs **115** and the base station **105** may establish one or more communication links **125**. The coverage area **110** may be an example of a geographic area over which a base station **105** and a UE **115** may support the communication of signals according to one or more radio access technologies.

(20) The UEs **115** may be dispersed throughout a coverage area **110** of the wireless communications system **100**, and each UE **115** may be stationary, or mobile, or both at different times. The UEs **115** may be devices in different forms or having different capabilities. Some example UEs **115** are illustrated in FIG. 1. The UEs **115** described herein may be able to communicate with various types of devices, such as other UEs **115**, the base stations **105**, or network equipment (e.g., core network nodes, relay devices, integrated access and backhaul (IAB) nodes, or other network equipment), as shown in FIG. 1.

(21) The base stations **105** may communicate with the core network **130**, or with one another, or both. For example, the base stations **105** may interface with the core network **130** through one or more backhaul links **120** (e.g., via an S1, N2, N3, or other interface). The base stations **105** may communicate with one another over the backhaul links **120** (e.g., via an X2, Xn, or other interface) either directly (e.g., directly between base stations **105**), or indirectly (e.g., via core network **130**), or both. In some examples, the backhaul links **120** may be or include one or more wireless links.

(22) One or more of the base stations **105** described herein may include or may be referred to by a person having ordinary skill in the art as a base transceiver station, a radio base station, an access point, a radio transceiver, a NodeB, an eNodeB (eNB), a next-generation NodeB or a giga-NodeB (either of which may be referred to as a gNB), a Home NodeB, a Home eNodeB, or other suitable terminology.

(23) A UE **115** may include or may be referred to as a mobile device, a wireless device, a remote device, a handheld device, or a subscriber device, or some other suitable terminology, where the “device” may also be referred to as a unit, a station, a terminal, or a client, among other examples. A UE **115** may also include or may be referred to as a personal electronic device such as a cellular phone, a personal digital assistant (PDA), a tablet computer, a laptop computer, or a personal computer. In some examples, a UE **115** may include or be referred to as a wireless local loop (WLL) station, an Internet of Things (IoT) device, an Internet of Everything (IoE) device, or a machine type communications (MTC) device, among other examples, which may be implemented in various objects such as appliances, or vehicles, meters, among other examples.

(24) The UEs **115** described herein may be able to communicate with various types of devices,

such as other UEs **115** that may sometimes act as relays as well as the base stations **105** and the network equipment including macro eNBs or gNBs, small cell eNBs or gNBs, or relay base stations, among other examples, as shown in FIG. **1**.

(25) The UEs **115** and the base stations **105** may wirelessly communicate with one another via one or more communication links **125** over one or more carriers. The term “carrier” may refer to a set of radio frequency spectrum resources having a defined physical layer structure for supporting the communication links **125**. For example, a carrier used for a communication link **125** may include a portion of a radio frequency spectrum band (e.g., a bandwidth part (BWP)) that is operated according to one or more physical layer channels for a given radio access technology (e.g., LTE, LTE-A, LTE-A Pro, NR). Each physical layer channel may carry acquisition signaling (e.g., synchronization signals, system information), control signaling that coordinates operation for the carrier, user data, or other signaling. The wireless communications system **100** may support communication with a UE **115** using carrier aggregation or multi-carrier operation. A UE **115** may be configured with multiple downlink component carriers and one or more uplink component carriers according to a carrier aggregation configuration. Carrier aggregation may be used with both frequency division duplexing (FDD) and time division duplexing (TDD) component carriers.

(26) In some examples (e.g., in a carrier aggregation configuration), a carrier may also have acquisition signaling or control signaling that coordinates operations for other carriers. A carrier may be associated with a frequency channel (e.g., an evolved universal mobile telecommunication system terrestrial radio access (E-UTRA) absolute radio frequency channel number (EARFCN)) and may be positioned according to a channel raster for discovery by the UEs **115**. A carrier may be operated in a standalone mode where initial acquisition and connection may be conducted by the UEs **115** via the carrier, or the carrier may be operated in a non-standalone mode where a connection is anchored using a different carrier (e.g., of the same or a different radio access technology).

(27) The communication links **125** shown in the wireless communications system **100** may include uplink transmissions from a UE **115** to a base station **105**, or downlink transmissions from a base station **105** to a UE **115**. Carriers may carry downlink or uplink communications (e.g., in an FDD mode) or may be configured to carry downlink and uplink communications (e.g., in a TDD mode).

(28) A carrier may be associated with a particular bandwidth of the radio frequency spectrum, and in some examples the carrier bandwidth may be referred to as a “system bandwidth” of the carrier or the wireless communications system **100**. For example, the carrier bandwidth may be one of a number of determined bandwidths for carriers of a particular radio access technology (e.g., 1.4, 3, 5, 10, 15, 20, 40, or 80 megahertz (MHz)). Devices of the wireless communications system **100** (e.g., the base stations **105**, the UEs **115**, or both) may have hardware configurations that support communications over a particular carrier bandwidth or may be configurable to support communications over one of a set of carrier bandwidths. In some examples, the wireless communications system **100** may include base stations **105** or UEs **115** that support simultaneous communications via carriers associated with multiple carrier bandwidths. In some examples, each served UE **115** may be configured for operating over portions (e.g., a sub-band, a BWP) or all of a carrier bandwidth.

(29) Signal waveforms transmitted over a carrier may be made up of multiple subcarriers (e.g., using multi-carrier modulation (MCM) techniques such as orthogonal frequency division multiplexing (OFDM) or discrete Fourier transform spread OFDM (DFT-S-OFDM)). In a system employing MCM techniques, a resource element may consist of one symbol period (e.g., a duration of one modulation symbol) and one subcarrier, where the symbol period and subcarrier spacing are inversely related. The number of bits carried by each resource element may depend on the modulation scheme (e.g., the order of the modulation scheme, the coding rate of the modulation scheme, or both). Thus, the more resource elements that a UE **115** receives and the higher the order of the modulation scheme, the higher the data rate may be for the UE **115**. A wireless

communications resource may refer to a combination of a radio frequency spectrum resource, a time resource, and a spatial resource (e.g., spatial layers or beams), and the use of multiple spatial layers may further increase the data rate or data integrity for communications with a UE **115**.

(30) One or more numerologies for a carrier may be supported, where a numerology may include a subcarrier spacing (Δf) and a cyclic prefix. A carrier may be divided into one or more BWPs having the same or different numerologies. In some examples, a UE **115** may be configured with multiple BWPs. In some examples, a single BWP for a carrier may be active at a given time and communications for the UE **115** may be restricted to one or more active BWPs.

(31) The time intervals for the base stations **105** or the UEs **115** may be expressed in multiples of a basic time unit which may, for example, refer to a sampling period of $T_{\text{sub.s}} = 1/(\Delta f_{\text{sub.max}} \cdot N_{\text{sub.f}})$ seconds, where $\Delta f_{\text{sub.max}}$ may represent the maximum supported subcarrier spacing, and $\Delta f_{\text{sub.f}}$ may represent the maximum supported discrete Fourier transform (DFT) size. Time intervals of a communications resource may be organized according to radio frames each having a specified duration (e.g., 10 milliseconds (ms)). Each radio frame may be identified by a system frame number (SFN) (e.g., ranging from 0 to 1023).

(32) Each frame may include multiple consecutively numbered subframes or slots, and each subframe or slot may have the same duration. In some examples, a frame may be divided (e.g., in the time domain) into subframes, and each subframe may be further divided into a number of slots. Alternatively, each frame may include a variable number of slots, and the number of slots may depend on subcarrier spacing. Each slot may include a number of symbol periods (e.g., depending on the length of the cyclic prefix prepended to each symbol period). In some wireless communications systems **100**, a slot may further be divided into multiple mini-slots containing one or more symbols. Excluding the cyclic prefix, each symbol period may contain one or more (e.g., $N_{\text{sub.f}}$) sampling periods. The duration of a symbol period may depend on the subcarrier spacing or frequency band of operation.

(33) A subframe, a slot, a mini-slot, or a symbol may be the smallest scheduling unit (e.g., in the time domain) of the wireless communications system **100** and may be referred to as a transmission time interval (TTI). In some examples, the TTI duration (e.g., the number of symbol periods in a TTI) may be variable. Additionally or alternatively, the smallest scheduling unit of the wireless communications system **100** may be dynamically selected (e.g., in bursts of shortened TTIs (sTTIs)).

(34) Physical channels may be multiplexed on a carrier according to various techniques. A physical control channel and a physical data channel may be multiplexed on a downlink carrier, for example, using one or more of time division multiplexing (TDM) techniques, frequency division multiplexing (FDM) techniques, or hybrid TDM-FDM techniques. A control region (e.g., a control resource set (CORESET)) for a physical control channel may be defined by a number of symbol periods and may extend across the system bandwidth or a subset of the system bandwidth of the carrier. One or more control regions (e.g., CORESETs) may be configured for a set of the UEs **115**. For example, one or more of the UEs **115** may monitor or search control regions for control information according to one or more search space sets, and each search space set may include one or multiple control channel candidates in one or more aggregation levels arranged in a cascaded manner. An aggregation level for a control channel candidate may refer to a number of control channel resources (e.g., control channel elements (CCEs)) associated with encoded information for a control information format having a given payload size. Search space sets may include common search space sets configured for sending control information to multiple UEs **115** and UE-specific search space sets for sending control information to a specific UE **115**.

(35) Each base station **105** may provide communication coverage via one or more cells, for example a macro cell, a small cell, a hot spot, or other types of cells, or any combination thereof. The term “cell” may refer to a logical communication entity used for communication with a base station **105** (e.g., over a carrier) and may be associated with an identifier for distinguishing

neighboring cells (e.g., a physical cell identifier (PCID), a virtual cell identifier (VCID), or others). In some examples, a cell may also refer to a geographic coverage area **110** or a portion of a geographic coverage area **110** (e.g., a sector) over which the logical communication entity operates. Such cells may range from smaller areas (e.g., a structure, a subset of structure) to larger areas depending on various factors such as the capabilities of the base station **105**. For example, a cell may be or include a building, a subset of a building, or exterior spaces between or overlapping with geographic coverage areas **110**, among other examples.

(36) A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by the UEs **115** with service subscriptions with the network provider supporting the macro cell. A small cell may be associated with a lower-powered base station **105**, as compared with a macro cell, and a small cell may operate in the same or different (e.g., licensed, unlicensed) frequency bands as macro cells. Small cells may provide unrestricted access to the UEs **115** with service subscriptions with the network provider or may provide restricted access to the UEs **115** having an association with the small cell (e.g., the UEs **115** in a closed subscriber group (CSG), the UEs **115** associated with users in a home or office). A base station **105** may support one or multiple cells and may also support communications over the one or more cells using one or multiple component carriers.

(37) In some examples, a carrier may support multiple cells, and different cells may be configured according to different protocol types (e.g., MTC, narrowband IoT (NB-IoT), enhanced mobile broadband (eMBB)) that may provide access for different types of devices.

(38) In some examples, a base station **105** may be movable and therefore provide communication coverage for a moving geographic coverage area **110**. In some examples, different geographic coverage areas **110** associated with different technologies may overlap, but the different geographic coverage areas **110** may be supported by the same base station **105**. In other examples, the overlapping geographic coverage areas **110** associated with different technologies may be supported by different base stations **105**. The wireless communications system **100** may include, for example, a heterogeneous network in which different types of the base stations **105** provide coverage for various geographic coverage areas **110** using the same or different radio access technologies.

(39) The wireless communications system **100** may be configured to support ultra-reliable communications or low-latency communications, or various combinations thereof. For example, the wireless communications system **100** may be configured to support ultra-reliable low-latency communications (URLLC) or mission critical communications. The UEs **115** may be designed to support ultra-reliable, low-latency, or critical functions (e.g., mission critical functions). Ultra-reliable communications may include private communication or group communication and may be supported by one or more mission critical services such as mission critical push-to-talk (MCPTT), mission critical video (MCVideo), or mission critical data (MCData). Support for mission critical functions may include prioritization of services, and mission critical services may be used for public safety or general commercial applications. The terms ultra-reliable, low-latency, mission critical, and ultra-reliable low-latency may be used interchangeably herein.

(40) In some examples, a UE **115** may also be able to communicate directly with other UEs **115** over a device-to-device (D2D) communication link **135** (e.g., using a peer-to-peer (P2P) or D2D protocol). One or more UEs **115** utilizing D2D communications may be within the geographic coverage area **110** of a base station **105**. Other UEs **115** in such a group may be outside the geographic coverage area **110** of a base station **105** or be otherwise unable to receive transmissions from a base station **105**. In some examples, groups of the UEs **115** communicating via D2D communications may utilize a one-to-many (1:M) system in which each UE **115** transmits to every other UE **115** in the group. In some examples, a base station **105** facilitates the scheduling of resources for D2D communications. In other cases, D2D communications are carried out between the UEs **115** without the involvement of a base station **105**.

(41) The core network **130** may provide user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. The core network **130** may be an evolved packet core (EPC) or 5G core (5GC), which may include at least one control plane entity that manages access and mobility (e.g., a mobility management entity (MME), an access and mobility management function (AMF)) and at least one user plane entity that routes packets or interconnects to external networks (e.g., a serving gateway (S-GW), a Packet Data Network (PDN) gateway (P-GW), or a user plane function (UPF)). The control plane entity may manage non-access stratum (NAS) functions such as mobility, authentication, and bearer management for the UEs **115** served by the base stations **105** associated with the core network **130**. User IP packets may be transferred through the user plane entity, which may provide IP address allocation as well as other functions. The user plane entity may be connected to IP services **150** for one or more network operators. The IP services **150** may include access to the Internet, Intranet(s), an IP Multimedia Subsystem (IMS), or a Packet-Switched Streaming Service.

(42) Some of the network devices, such as a base station **105**, may include subcomponents such as an access network entity **140**, which may be an example of an access node controller (ANC). Each access network entity **140** may communicate with the UEs **115** through one or more other access network transmission entities **145**, which may be referred to as radio heads, smart radio heads, or transmission/reception points (TRPs). Each access network transmission entity **145** may include one or more antenna panels. In some configurations, various functions of each access network entity **140** or base station **105** may be distributed across various network devices (e.g., radio heads and ANCs) or consolidated into a single network device (e.g., a base station **105**).

(43) The wireless communications system **100** may operate using one or more frequency bands, typically in the range of 300 megahertz (MHz) to 300 gigahertz (GHz). Generally, the region from 300 MHz to 3 GHz is known as the ultra-high frequency (UHF) region or decimeter band because the wavelengths range from approximately one decimeter to one meter in length. The UHF waves may be blocked or redirected by buildings and environmental features, but the waves may penetrate structures sufficiently for a macro cell to provide service to the UEs **115** located indoors. The transmission of UHF waves may be associated with smaller antennas and shorter ranges (e.g., less than 100 kilometers) compared to transmission using the smaller frequencies and longer waves of the high frequency (HF) or very high frequency (VHF) portion of the spectrum below 300 MHz.

(44) The wireless communications system **100** may utilize both licensed and unlicensed radio frequency spectrum bands. For example, the wireless communications system **100** may employ License Assisted Access (LAA), LTE-Unlicensed (LTE-U) radio access technology, or NR technology in an unlicensed band such as the 5 GHz industrial, scientific, and medical (ISM) band. When operating in unlicensed radio frequency spectrum bands, devices such as the base stations **105** and the UEs **115** may employ carrier sensing for collision detection and avoidance. In some examples, operations in unlicensed bands may be based on a carrier aggregation configuration in conjunction with component carriers operating in a licensed band (e.g., LAA). Operations in unlicensed spectrum may include downlink transmissions, uplink transmissions, P2P transmissions, or D2D transmissions, among other examples.

(45) A base station **105** or a UE **115** may be equipped with multiple antennas, which may be used to employ techniques such as transmit diversity, receive diversity, multiple-input multiple-output (MIMO) communications, or beamforming. The antennas of a base station **105** or a UE **115** may be located within one or more antenna arrays or antenna panels, which may support MIMO operations or transmit or receive beamforming. For example, one or more base station antennas or antenna arrays may be co-located at an antenna assembly, such as an antenna tower. In some examples, antennas or antenna arrays associated with a base station **105** may be located in diverse geographic locations. A base station **105** may have an antenna array with a number of rows and columns of antenna ports that the base station **105** may use to support beamforming of communications with a UE **115**. Likewise, a UE **115** may have one or more antenna arrays that may support various MIMO

or beamforming operations. Additionally or alternatively, an antenna panel may support radio frequency beamforming for a signal transmitted via an antenna port.

(46) The base stations **105** or the UEs **115** may use MIMO communications to exploit multipath signal propagation and increase the spectral efficiency by transmitting or receiving multiple signals via different spatial layers. Such techniques may be referred to as spatial multiplexing. The multiple signals may, for example, be transmitted by the transmitting device via different antennas or different combinations of antennas. Likewise, the multiple signals may be received by the receiving device via different antennas or different combinations of antennas. Each of the multiple signals may be referred to as a separate spatial stream and may carry bits associated with the same data stream (e.g., the same codeword) or different data streams (e.g., different codewords). Different spatial layers may be associated with different antenna ports used for channel measurement and reporting. MIMO techniques include single-user MIMO (SU-MIMO), where multiple spatial layers are transmitted to the same receiving device, and multiple-user MIMO (MU-MIMO), where multiple spatial layers are transmitted to multiple devices.

(47) Beamforming, which may also be referred to as spatial filtering, directional transmission, or directional reception, is a signal processing technique that may be used at a transmitting device or a receiving device (e.g., a base station **105**, a UE **115**) to shape or steer an antenna beam (e.g., a transmit beam, a receive beam) along a spatial path between the transmitting device and the receiving device. Beamforming may be achieved by combining the signals communicated via antenna elements of an antenna array such that some signals propagating at particular orientations with respect to an antenna array experience constructive interference while others experience destructive interference. The adjustment of signals communicated via the antenna elements may include a transmitting device or a receiving device applying amplitude offsets, phase offsets, or both to signals carried via the antenna elements associated with the device. The adjustments associated with each of the antenna elements may be defined by a beamforming weight set associated with a particular orientation (e.g., with respect to the antenna array of the transmitting device or receiving device, or with respect to some other orientation).

(48) A base station **105** or a UE **115** may use beam sweeping techniques as part of beam forming operations. For example, a base station **105** may use multiple antennas or antenna arrays (e.g., antenna panels) to conduct beamforming operations for directional communications with a UE **115**. Some signals (e.g., synchronization signals, reference signals, beam selection signals, or other control signals) may be transmitted by a base station **105** multiple times in different directions. For example, the base station **105** may transmit a signal according to different beamforming weight sets associated with different directions of transmission. Transmissions in different beam directions may be used to identify (e.g., by a transmitting device, such as a base station **105**, or by a receiving device, such as a UE **115**) a beam direction for later transmission or reception by the base station **105**.

(49) Some signals, such as data signals associated with a particular receiving device, may be transmitted by a base station **105** in a single beam direction (e.g., a direction associated with the receiving device, such as a UE **115**). In some examples, the beam direction associated with transmissions along a single beam direction may be determined based on a signal that was transmitted in one or more beam directions. For example, a UE **115** may receive one or more of the signals transmitted by the base station **105** in different directions and may report to the base station **105** an indication of the signal that the UE **115** received with a highest signal quality or an otherwise acceptable signal quality.

(50) In some examples, transmissions by a device (e.g., by a base station **105** or a UE **115**) may be performed using multiple beam directions, and the device may use a combination of digital precoding or radio frequency beamforming to generate a combined beam for transmission (e.g., from a base station **105** to a UE **115**). The UE **115** may report feedback that indicates precoding weights for one or more beam directions, and the feedback may correspond to a configured number

of beams across a system bandwidth or one or more sub-bands. The base station **105** may transmit a reference signal (e.g., a cell-specific reference signal (CRS), a channel state information reference signal (CSI-RS)), which may be precoded or unprecoded. The UE **115** may provide feedback for beam selection, which may be a precoding matrix indicator (PMI) or codebook-based feedback (e.g., a multi-panel type codebook, a linear combination type codebook, a port selection type codebook). Although these techniques are described with reference to signals transmitted in one or more directions by a base station **105**, a UE **115** may employ similar techniques for transmitting signals multiple times in different directions (e.g., for identifying a beam direction for subsequent transmission or reception by the UE **115**) or for transmitting a signal in a single direction (e.g., for transmitting data to a receiving device).

(51) A receiving device (e.g., a UE **115**) may try multiple receive configurations (e.g., directional listening) when receiving various signals from the base station **105**, such as synchronization signals, reference signals, beam selection signals, or other control signals. For example, a receiving device may try multiple receive directions by receiving via different antenna subarrays, by processing received signals according to different antenna subarrays, by receiving according to different receive beamforming weight sets (e.g., different directional listening weight sets) applied to signals received at multiple antenna elements of an antenna array, or by processing received signals according to different receive beamforming weight sets applied to signals received at multiple antenna elements of an antenna array, any of which may be referred to as “listening” according to different receive configurations or receive directions. In some examples, a receiving device may use a single receive configuration to receive along a single beam direction (e.g., when receiving a data signal). The single receive configuration may be aligned in a beam direction determined based on listening according to different receive configuration directions (e.g., a beam direction determined to have a highest signal strength, highest signal-to-noise ratio (SNR), or otherwise acceptable signal quality based on listening according to multiple beam directions).

(52) The wireless communications system **100** may be a packet-based network that operates according to a layered protocol stack. In the user plane, communications at the bearer or Packet Data Convergence Protocol (PDCP) layer may be IP-based. A Radio Link Control (RLC) layer may perform packet segmentation and reassembly to communicate over logical channels. A Medium Access Control (MAC) layer may perform priority handling and multiplexing of logical channels into transport channels. The MAC layer may also use error detection techniques, error correction techniques, or both to support retransmissions at the MAC layer to improve link efficiency. In the control plane, the Radio Resource Control (RRC) protocol layer may provide establishment, configuration, and maintenance of an RRC connection between a UE **115** and a base station **105** or a core network **130** supporting radio bearers for user plane data. At the physical layer, transport channels may be mapped to physical channels.

(53) The UEs **115** and the base stations **105** may support retransmissions of data to increase the likelihood that data is received successfully. Hybrid automatic repeat request (HARQ) feedback is one technique for increasing the likelihood that data is received correctly over a communication link **125**. HARQ may include a combination of error detection (e.g., using a cyclic redundancy check (CRC)), forward error correction (FEC), and retransmission (e.g., automatic repeat request (ARQ)). HARQ may improve throughput at the MAC layer in poor radio conditions (e.g., low signal-to-noise conditions). In some examples, a device may support same-slot HARQ feedback, where the device may provide HARQ feedback in a specific slot for data received in a previous symbol in the slot. In other cases, the device may provide HARQ feedback in a subsequent slot, or according to some other time interval.

(54) In some cases, the UEs **115** and the base stations **105** of the wireless communications system **100** may support techniques for temporary reference signal configuration for SCell activation. In particular, a UE **115** of the wireless communications system **100** may be configured to receive an aperiodic reference signal (e.g., temporary reference signal) on a SCell (e.g., a SCell that is by a

same or different base station **105** that provides a PCell) in order to reduce an activation time of the SCell. For example, a UE **115** of the wireless communications system **100** may perform wireless communications with a first serving cell (e.g., PCell) supported by a base station **105**. In this example, the base station **105** may transmit, to the UE **115**, an indication that a second serving cell (e.g., SCell) supported by the base station **105** is to be activated at the UE **115**. The base station **105** may activate the SCell at the UE **115** to increase data throughput, to alleviate network congestion, or both. In some cases, the UE **115** may receive a temporary reference signal on the SCell in order to reduce a duration of the activation time of the SCell. For example, the UE **115** may determine AGC associated with the SCell, time/frequency tracking associated with the SCell, or both, based on the received temporary reference signal, thereby enabling the UE **115** to initiate communications with the SCell relatively quickly, compared to a time duration for such activation using reference signals that have a relatively long periodicity, such reference signals transmitted with an SSB.

(55) In some cases, the activation message that activates the SCell may provide an indication of one or more parameters of the temporary reference signal in DCI that is transmitted to the UE **115**. In some cases, a same DCI that schedules a MAC-CE that carries the activation command may be used to provide the one or more parameters of the temporary reference signal. In other cases, a separate DCI may be transmitted that indicates the one or more parameters of the temporary reference signal. In further cases, a MAC-CE may indicate the one or more parameters of the temporary reference signal. Such a MAC-CE may be a same MAC-CE that provides the SCell activation command, or a different MAC-CE. Additionally or alternatively, one or more of the temporary reference signal parameters may be implicitly signaled by the activation command. For example, one or more reference signal parameters may be configured by RRC signaling, and used at the UE **115** upon receipt of the SCell activation command.

(56) The techniques described herein may provide for improved wireless communications by reducing durations of SCell activation periods. In particular, by receiving reference signals (e.g., temporary reference signals, tracking reference signals, non-zero power CSI-RS with higher layer parameters such as trs-Info) on an activated SCell, a UE **115** may be able to determine information (e.g., AGC, time/frequency tracking) associated with the SCell, and this information determined based on the reference signals may thereby reduce a duration of the time for activation of the SCell compared to using periodic SSBs to determine the information. By reducing the activation time durations for SCell activation at the UE **115**, techniques described herein may improve the efficiency and reliability of wireless communications, and improve overall user experience.

(57) FIG. 2 illustrates an example of a wireless communications system **200** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some examples, wireless communications system **200** may implement aspects of wireless communications system **100**. The wireless communications system **200** may include a UE **115-a** and a base station **105-a**, which may be examples of UEs **115** and base stations **105**, as described with reference to FIG. 1.

(58) The wireless communications system **200** may support wireless communications with wireless devices (e.g., UE **115-a**) via one or more serving cells **205** of the wireless communications system **200**. In particular, each serving cell **205** may be supported by one or more base stations **105** of the wireless communications system **200**. For example, as shown in FIG. 2, the wireless communications system **200** may include a first serving cell **205-a** (e.g., a PCell) supported by the base station **105-a**, and a second serving cell **205-b** (e.g., a SCell) supported by the base station **105-a**. The serving cells **205** may also be primary-secondary cells (PSCells) of a secondary cell group (SCG), or any combinations of PCells, SCells, or PSCells of a SCG. The wireless communications system **200** may include any quantity of serving cells **205** supported by any quantity of base stations **105**. For example, in additional or alternative cases, the first cell **205-a** may be supported by the base station **105-a**, and the second cell **205-b** may be supported by a second base station which is different from the base station **105-a**.

(59) In some cases, the first serving cell **205-a** and the second serving cell **205-b** may be associated with the same frequency band (e.g., intra-band carrier aggregation). In some cases, the first serving cell **205-a**, the second serving cell **205-b**, or both, may include a PCell, an SCell, a PSCell of an SCG, or any combination thereof. For example, in cases where the first serving cell **205-a** includes a PCell, the second serving cell **205-b** may include an SCell. By way of another example, in cases where the first serving cell **205-a** includes an SCell, the second serving cell **205-b** may include an additional SCell. Moreover, in cases where the first serving cell **205-a** includes a PSCell of an SCG, the second serving cell **205-b** may include an SCell of the SCG.

(60) In some cases, the first serving cell **205-a**, the second serving cell **205-b**, or both, may be associated with a given radio access technology, such as a 5G radio access technology, an NR access technology, a 4G radio access technology, an LTE radio access technology, or any combination thereof. In some cases, techniques described herein may be implemented in the context of dual connectivity scenarios. In this regard, the second serving cell **205-b** may be associated with the same or different radio access technology as the radio access technology associated with the first serving cell **205-a**. For example, in cases where the first serving cell **205-a** is associated with a 5G or NR access technology, the second serving cell **205-b** may be associated with a 4G radio access technology, an LTE radio access technology, or both. Moreover, in some cases, the first serving cell **205-a** and the second serving cell **205-b** may be associated with different frequency bands associated with a common radio access technology. For example, in some cases, both the first and second serving cells **205-a** and **205-b** may be associated with an NR access technology, where the first serving cell **205-a** is associated with a frequency range one (FR1) frequency band of the NR access technology and the second serving cell **205-b** is associated with an FR2 frequency band of the NR access technology.

(61) In some cases, the UE **115-a** may communicate with the base station **105-a** using one or more beams, one or more carriers, one or more communications links, or any combination thereof. For example, each serving cell **205** may be associated with a different frequency range, separate beams, separate component carriers, and/or communications links to facilitate wireless communications between the UE **115-a** and the respective serving cells **205**. For example, the UE **115-a** may communicate with the base station **105-a** via a communication link **210**, where the communication link **210** includes a first component carrier **215-a** and a second component carrier **215-b**. In some cases, the first component carrier **215-a** may be associated with the first serving cell **205-a**, and the second component carrier **215-b** may be associated with the second serving cell **205-b**. In some cases, the communication link **210** may include an example of an access link (e.g., a Uu link). The communication link **210** may include a bi-directional link that can include both uplink and downlink communication. For example, the UE **115-a** may transmit uplink transmissions, such as uplink control signals or uplink data signals, to the base station **105-a** using the communication link **210**, and the base station **105-a** may transmit downlink transmissions, such as downlink control signals or downlink data signals, to the UE **115-a** using the communication link **210**.

(62) In some cases, the UE **115-a** and the base station **105-a** of the wireless communications system **200** may support techniques for SCell activation using temporary reference signals, in which temporary reference signal configuration may be indicated by a downlink communication associated with an activation command for the SCell. In particular, the UE **115-a** of the wireless communications system **200** may be configured to receive a reference signal (e.g., temporary reference signal) on the second serving cell **205-b** supported by the base station **105-a** in order to reduce an activation time for wireless communications on the second serving cell **205-b** which is attributable to the activation of the second serving cell **205-b** supported by the base station **105-a**.

(63) For example, the UE **115-a** may establish wireless communications with the first serving cell **205-a**. In some cases, the UE **115-a** may establish the wireless communications with the first serving cell **205-a** by initiating or otherwise performing a setup procedure with the first serving cell **205-a**. In some cases, the UE **115-a** may receive a control message **220** from the base station **105-a**

via the first serving cell **205-a** (e.g., via the first component carrier **215-a**). In some cases, the control message **220** may include configuration information that indicates whether temporary reference signals are enabled, activation information for such temporary reference signals, one or more parameters for a temporary reference signal, or any combinations thereof. The control message **220** may include an RRC message, a system information block (SIB) message, an SSB message, or any combination thereof. In some aspects, the UE **115-a** may receive the control message **220** based on establishing the wireless communications with the first serving cell **205-a**.

(64) In some aspects, the UE **115-a** may receive, from the base station **105-a** via the first serving cell **205-a**, a DCI message **225** scheduling a downlink transmission (e.g., physical downlink shared channel (PDSCH) transmission and/or a MAC-CE message **230**) from the base station **105-a** to the UE **115-a**. For example, as shown in FIG. 2, the UE **115-a** may receive the DCI message **225** from the base station **105-a** via the first serving cell **205-a** (e.g., via the first component carrier **215-a**). The DCI message **225** may be transmitted via physical downlink control channel (PDCCH) resources. In some cases, the UE **115-a** may receive the DCI message **225** based on establishing the wireless communications with the first serving cell **205-a**, receiving the control message **220** (e.g., RRC message, SIB message, SSB message), or any combination thereof. In some cases, the DCI message **225** may include an indication that the reference signal **240** (e.g., temporary reference signals) associated with the second serving cell **205-b**, have been activated (e.g., triggered, initiated). In this regard, the UE **115-a** may be configured to determine that it may monitor for the reference signal **240** on the second serving cell **205-b**, based on the indication in the DCI message **225**.

(65) In some cases, the UE **115-a** may receive, from the base station **105-a** via the first serving cell **205-a**, an indication to activate the second serving cell **205-b**. For example, as shown in FIG. 2, the UE **115-b** may receive a MAC-CE message **230** from the base station **105-a** via the first serving cell **205-a** (e.g., via the first component carrier **215-a**). In this example, the MAC-CE message **230** may include an indication to activate the second serving cell **205-b**. In some cases, the base station **105-a** may transmit, and the UE **115-a** may receive, the indication to activate the second serving cell **205-b** (e.g., an SCell activation message in the MAC-CE message **230**) based on the DCI message **225**. For example, the DCI message **225** may schedule a PDSCH transmission (e.g., MAC-CE message **230**), where the PDSCH transmission includes the indication to activate the second serving cell **205-b**.

(66) In some aspects, based on the activation message, the UE **115-a** may determine a set of resources which are usable by the UE **115-a** to receive a reference signal **240** (e.g., temporary reference signal) from the base station **105-a** via the second serving cell **205-b** (e.g., via a second component carrier **215-b**). The set of resources may include a set of time resources (e.g. a slot where the reference signal **240** is located), a set of frequency resources (e.g., a carrier where the reference signal **240** is located), resource mapping of the reference signal **240**, a power offset (e.g., a power difference between the reference signal **240** and one or more other communications on the second component carrier **215-b** such as data or SSB transmissions), a quasi-co-location (QCL) assumption of the reference signal **240**, a transmission configuration indicator (TCI) state of the reference signal, a set of spatial resources, or any combinations thereof.

(67) In some cases, a same DCI message **225** that schedules a MAC-CE message **230** that carries the activation command may be used to provide the one or more parameters of the reference signal **240**. In other cases, a separate DCI, such as discussed with reference to the examples of FIGS. 5-6, may be transmitted that indicates the one or more parameters of the reference signal **240**. In some cases, the DCI message **225** may have a fallback DCI format or a non-fallback DCI format. In some cases, the non-fallback DCI format is a DCI format 1_1 or a DCI format 1_2, and fallback DCI format is a DCI format 1_0. In some cases, DCI 1_1 or 1_2 may include the triggering indication for the reference signal **240** on the second serving cell **205-b**.

(68) In further cases, the MAC-CE message **230** may indicate the one or more parameters of the

reference signal **240** (e.g., the same MAC-CE message **230** that provides the SCell activation command). In other cases, a different MAC-CE may indicate the one or more parameters of the reference signal **240**, such as discussed with reference to the examples of FIGS. 7-8. Additionally, or alternatively, one or more of the reference signal **240** parameters may be implicitly signaled by the activation command. For example, one or more reference signal parameters may be configured by the control message **220** (e.g., via RRC signaling), and used at the UE **115-a** upon receipt of the SCell activation command.

(69) In some cases, the reference signal **240** (e.g., temporary reference signal) may be triggered on the second serving cell **205-b** to-be-activated without an explicit triggering indication provided by the DCI message **225** or MAC-CE message **230**. In some cases, the reference signal **240** may be is triggered on the SCell to-be-activated and already active cell(s) in the same band without an explicit triggering indication. In some cases, one or more of the following may be identified without explicit triggering signaling: the carrier where the temporary reference signal is transmitted (e.g., the reference signal **240** may be activated on the carrier of the SCell to-be-activated or the SCell to-be-activated and any already active cell(s) in the same band); the slot where the temporary reference signal is transmitted (e.g., the slot may be higher-layer configured with timing relative to the timing of feedback message **235** for PDSCH carrying MAC-CE message **230** for SCell activation command or relative to the start of a radio frame); a configuration of the temporary reference signal (e.g., a resource mapping and/or power offset to data/SSB, for the reference signal **240**, which may be configured by higher-layer signaling); the QCL assumption for the temporary reference signal, or a TCI-state for the temporary reference signal (e.g., QCL or TCI-state may be configured by higher-layer signaling).

(70) In some cases, the UE **115-a** may transmit feedback message **235** to the base station **105** via the first serving cell **205-a**, the second serving cell **205-b**, or both. For example, in cases where the MAC-CE message **230** is received via the first serving cell **205-a**, the UE **115-a** may transmit the feedback message **235** via the first serving cell **205-a**. In some cases, the UE **115-a** may transmit the feedback message **235** to the base station **105-a** based on (e.g., in response to) receiving the indication to activate the second serving cell **205-b**. The feedback message **235** may include an acknowledgement (ACK) message, a negative acknowledgement (NACK) message, or both. For example, in cases where the indication within the MAC-CE message **230** includes an activation of the second serving cell **205-b**, the UE **115-a** may transmit an ACK message in response to the activation of the second serving cell **205-b**. In some cases, the UE **115-a** may determine and/or adjust AGC associated with the second serving cell **205-b**, tracking (e.g., time tracking, frequency tracking) associated with the second serving cell **205-b**, or any combination thereof.

(71) FIG. 3 illustrates an example of a resource allocation scheme **300** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some examples, resource allocation scheme **300** may implement aspects of wireless communications system **100** or **200**. The resource allocation scheme **300** in this example illustrates activation of a serving cell using a periodic reference signal for one or more cell measurements, rather than a temporary reference signal.

(72) The resource allocation scheme **300** may include a first serving cell, namely PCell **305**, and an SCell **310** that is to be activated at a UE. In some cases, the base station serving the SCell **310** (which may be a same base station as serving the PCell **305** or a different base station) may be configured to transmit SSB **315** to the UE via the SCell **310** according to an SSB periodicity **320**. For example, in the context of an NR access technology, the base station may transmit an SSB **315** according to a 10 ms SSB periodicity **320**, a 20 ms SSB periodicity **320**, or another duration.

(73) The UE may receive, via the PCell **305**, a DCI **325** which schedules a PDSCH transmission (e.g., that includes MAC-CE message having an activation command **330** for the SCell **310**) from the base station to the UE. Subsequently, the UE may receive the PDSCH transmission (e.g., MAC-CE message) based on the DCI **325**. The UE may transmit, to the base station via the PCell **305**, a

feedback message **335** (e.g., ACK message) in response to successfully receiving the indication to activate the SCell **310** via the PDSCH transmission.

(74) In this example, an SCell activation time may be based on an activation time **345**, a timing of the feedback message **335**, the SSB periodicity **320**, and a timing for a channel state information (CSI) report. In some cases, the time for SCell activation may be determined as:

(75) SCell activation delay = $\{T_{HARQ} + T_{\text{activation time}} + T_{\text{CSI reporting}}\} / \text{NR slot length}$ where T.sub.HARQ is the timeline **340** from the activation command **330** until the feedback message **335** (e.g., HARQ ACK) is transmitted, T.sub.activation time is an activation time **345** corresponding to a first SSB **315-c** (T.sub.FirstSSB) plus 5 ms, where T.sub.FirstSSB is the time to first SSB **315-c** indicated by the SSB measurement timing configuration (SMTC) after slot n (with PDSCH)+T.sub.HARQ+3 ms, and where T.sub.CSI reporting is a delay time **350** until a first available CSI report, including uncertainties of CSI-RS resource and CSI report.

(76) Accordingly, in cases where a temporary reference signal is not transmitted on the SCell **310**, the UE may use signals provided with SSBs **315** to perform measurements and activate the SCell **310**. In some cases, the base station may not trigger a temporary reference signal, and thus the timing as illustrated in FIG. 3 may be used for SCell **310** activation. For example, in cases where the PDSCH resources used to transmit the PDSCH transmission are relatively close to a measurable SSB **315** occasion, the base station may determine not to trigger a temporary reference signal. In other cases, the base station may trigger a temporary reference signal (e.g., in a MAC-CE), but after the transport block with the MAC-CE is formatted, the base station may determine that the temporary reference signal is not to be transmitted, and may indicate in a DCI that the temporary reference signal is canceled, in which case the timing of the SCell **310** activation may be as illustrated in FIG. 3. Examples of a base station cancelling a temporary reference signal trigger are discussed in more detail with reference to the example of FIG. 8.

(77) FIG. 4 illustrates another example of a resource allocation scheme **400** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some examples, resource allocation scheme **400** may implement aspects of wireless communications system **100** or **200**. The resource allocation scheme **400** in this example illustrates activation of a serving cell using a temporary reference signal **455** for one or more cell measurements, rather than a periodic reference signal.

(78) Similarly as above, the resource allocation scheme **400** may include a first serving cell, namely PCell **405**, and an SCell **410** that is to be activated at a UE. In some cases, the base station serving the SCell **410** (which may be a same base station as serving the PCell **405** or a different base station) may be configured to transmit SSB messages **415** to the UE via the SCell **410** according to an SSB periodicity **420**. The UE may receive, via the PCell **405**, DCI **425** which schedules a PDSCH transmission **430** (e.g., that includes MAC-CE message having an activation command for the SCell **410**) from the base station to the UE. Subsequently, the UE may receive the PDSCH transmission **430** (e.g., MAC-CE message) based on the DCI **425**. The UE may transmit, to the base station via the PCell **405**, a feedback message **435** (e.g., ACK message) in response to successfully receiving the indication to activate the SCell **410** via the PDSCH transmission **430**.

(79) In some aspects, the PDSCH transmission **430** (e.g., MAC-CE message) may trigger the UE to measure temporary reference signal **455**. In this example, the temporary reference signal **455** may be transmitted on the SCell **410** and may allow for UE measurements in advance of when such measurements could otherwise be made using reference signals provided with SSB messages **415**, such as discussed with reference to FIG. 3. In this example, an SCell activation delay may again be determined as:

(80) SCell activation delay = $\{T_{HARQ} + T_{\text{activation time}} + T_{\text{CSI reporting}}\} / \text{NR slot length}$ where T.sub.HARQ is the timeline **340** from the activation command **330** until the feedback message **435** (e.g., HARQ ACK) is transmitted. In this case, however, T.sub.activation time **445** is reduced relative to the example of FIG. 3, and corresponds to a temporary reference signal **455**

time (T.sub.temp RS) plus 5 ms, where T temp RS is the time to the temporary reference signal **455** after slot n (with PDSCH)+T.sub.HARQ+3 ms. The value of T.sub.CSI reporting is the delay time **450** until the first available CSI report, including uncertainties of CSI-RS resource and CSI report. (81) Thus, in this example, the SCell activation delay is reduced relative to that discussed in the example of FIG. 3, which may result in faster SCell **410** activation, higher throughput, reduced latency, and other benefits. In accordance with various aspects discussed herein, one or more parameters of the temporary reference signals **455** may be indicated by the DCI **425**, the MAC-CE in the PDSCH transmission **430**, a different DCI or MAC-CE, or combinations thereof, several examples of which are discussed herein. Additionally, or alternatively, the UE may be configured to implicitly determine that the temporary reference signal **455** on the SCell **410** has been activated and one or more parameters associated therewith, as discussed herein.

(82) In some cases, the one or more parameters associated with the temporary reference signal **455** may include, for example, a carrier where the temporary reference signal **455** is transmitted. In some cases, the temporary reference signal **455** may be an aperiodic transmission of a tracking reference signal (TRS). In some cases, for aperiodic TRS transmissions, carrier may be informed by one or multiple carriers of the corresponding CSI-ReportConfig associated with CSI-AssociatedReportConfigInfo (e.g., that provides information for a TRS as a non-zero power (NZP) channel state information reference signal (CSI-RS)), and in some examples some aspects of a CSI request field may be reused for triggering the temporary reference signal **455**, and to provide carrier information. The one or more parameters of the temporary reference signal **455** may also include a slot where the temporary reference signal **455** is transmitted. In cases where a TRS is used, the slot may be informed by an aperiodicTriggeringOffset in the NZP-CSI-RS-ResourceSet in the CSI-ResourceConfig, where aperiodicTriggeringOffset tells the number of slots from the aperiodic TRS triggering DCI to the aperiodic TRS transmission, and such signaling may be reused in cases where the CSI request field is reused to trigger the temporary reference signal **455**.

(83) The one or more parameters of the temporary reference signal **455** may also include a configuration of the temporary reference signal **455**, such as resource mapping or power offset to data/SSB. In cases where TRS is used, the configuration may be informed by NZP-CSI-RS-ResourceSet, which is configured to an entry of aperiodicTriggeringOffset of CSI-AperiodicTriggerStateList, and such signaling may be reused in cases where the CSI request field is reused to trigger the temporary reference signal **455**. The one or more parameters of the temporary reference signal **455** may also include a QCL assumption or TCI-state for the temporary reference signal **455**. In cases where TRS is used as the temporary reference signal **455**, the TRS may be QCLed with periodic TRS in the same carrier, which may be used to determine the QCL assumption or TCI-state for the temporary reference signal **455**. While TRS is used as the temporary reference signal **455** in some cases, in other cases other reference signals may be used in addition to or alternatively to TRS. For example, the temporary reference signal **455** may be an aperiodic CSI-RS, a periodic or semi-persistent CSI RS (P/SP-CSI-RS), a sounding reference signal (SRS), a reference signal based on a secondary synchronization signal (SSS) or primary synchronization signal (PSS), or combinations thereof.

(84) FIG. 5 illustrates another example of a resource allocation scheme **500** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some examples, resource allocation scheme **500** may implement aspects of wireless communications system **100** or **200**. The resource allocation scheme **500** in this example illustrates activation of a serving cell using a temporary reference signal **555** for one or more cell measurements.

(85) Similarly as above, the resource allocation scheme **500** may include a first serving cell, namely PCell **505**, and an SCell **510** that is to be activated at a UE. In some cases, the base station serving the SCell **510** (which may be a same base station as serving the PCell **505** or a different base station) may be configured to transmit SSB messages **515** to the UE via the SCell **510**

according to an SSB periodicity **520**. The UE may receive, via the PCell **505**, DCI **525** which schedules a PDSCH transmission **530** (e.g., that includes MAC-CE message having an activation command for the SCell **510**) from the base station to the UE. Subsequently, the UE may receive the PDSCH transmission **530** (e.g., MAC-CE message) based on the DCI **525**. The UE may transmit, to the base station via the PCell **505**, a feedback message **535** (e.g., ACK message) in response to successfully receiving the indication to activate the SCell **510** via the PDSCH transmission **530**.

(86) In this example, the DCI **525** may be used to provide one or more parameters associated with the temporary reference signal **555**. In some cases, a DCI format of the DCI **525** may inform the UE of one or more of the carrier where the temporary reference signal **555** is transmitted, a slot where the temporary reference signal **555** is transmitted, a configuration of the temporary reference signal **555** (e.g., resource mapping, power offset to data/SSB), or the QCL assumption or TCI-state for the temporary reference signal **555**. In some cases, the DCI format of the DCI **525** that schedules the PDSCH transmission **530** carrying the SCell activation command MAC-CE tells the UE of the temporary reference signal information. The DCI format may include PDSCH scheduling information for the scheduled cell (e.g., SCell **510**), and temporary reference signal **555** triggering information for the SCell **510** to-be-activated. In some cases, the temporary reference signal **555** triggering information may include a defined request field in the DCI format with parameters for the temporary reference signal **555** (e.g., the DCI may reuse a CSI request field from an uplink grant that is defined for the downlink DCI format). In some cases, the temporary reference signal **555** is triggered at least a predetermined time period (e.g., 3 ms) after the feedback message **535** transmission for the PDSCH transmission **530**.

(87) FIG. **6** illustrates an example of a resource allocation scheme **600** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some examples, resource allocation scheme **600** may implement aspects of wireless communications system **100** or **200**. The resource allocation scheme **600** in this example illustrates activation of a serving cell using a temporary reference signal **655** for one or more cell measurements.

(88) Similarly as above, the resource allocation scheme **600** may include a first serving cell, namely PCell **605**, and an SCell **610** that is to be activated at a UE. In some cases, the base station serving the SCell **610** (which may be a same base station as serving the PCell **605** or a different base station) may be configured to transmit SSB messages **615** to the UE via the SCell **610** according to an SSB periodicity **620**. The UE may receive, via the PCell **605**, DCI **625** which schedules a PDSCH transmission **630** (e.g., that includes MAC-CE message having an activation command for the SCell **610**) from the base station to the UE. Subsequently, the UE may receive the PDSCH transmission **630** (e.g., MAC-CE message) based on the DCI **625**. The UE may transmit, to the base station via the PCell **605**, a feedback message **635** (e.g., ACK message) in response to successfully receiving the indication to activate the SCell **610** via the PDSCH transmission **630**.

(89) In this example, a second DCI **660** may be used to provide one or more parameters associated with the temporary reference signal **655**. In some cases, a DCI format of the second DCI **660** may be different than a DCI format of DCI **625** that schedules the PDSCH transmission **630** carrying the SCell activation command MAC-CE. In some cases, the second DCI format includes PDSCH scheduling information for the scheduled cell (e.g., PCell **605**), and temporary reference signal **655** triggering information for the SCell **610** to-be-activated. In some cases, the temporary reference signal **655** triggering information may include a defined request field that indicates one or more reference signal parameters (e.g., the request field may reuse of CSI request field from an uplink grant, similarly as discussed with reference to FIG. **5**). In some cases, the temporary reference signal **655** may be triggered at least a predetermined time period (e.g., 3 ms) after the ACK/NACK transmission (e.g., feedback message **635**) for the PDSCH transmission **630**.

(90) In other cases, the second DCI format does not include PDSCH scheduling information for any cell, but includes temporary reference signal **655** triggering information for the SCell **610** to-

be-activated. The temporary reference signal **655** triggering information may again be provided in a request field, and in some cases, may be a reuse of PDSCH scheduling information fields (e.g., a frequency domain resource assignment (FDRA) field). In some cases, the temporary reference signal **655** may be triggered at least a predetermined time period (e.g., 3 ms) after the second DCI **660** with the temporary reference signal **655** triggering, or at least a predetermined time period (e.g., 3 ms) after a second ACK/NACK transmission **665** transmission for the second DCI **660** (if HARQ feedback for the associated PDCCH is reception is enabled).

(91) As discussed, in some cases a DCI from the base station may include a field that provides an indication of the one or more temporary reference signal **655** parameters. In some cases, the DCI may reuse a CSI request field from an uplink grant to indicate the temporary reference signal **655** parameters, in which a number of bits in the field is either configured by RRC signaling or is determined by a number of TRS triggering states. In some cases, a TRS triggering field is linked to {TRS timing/slot, TRS configuration (resource and/or power offset)} for one or multiple serving cells. In other cases, the DCI may reuse one or more PDSCH scheduling information fields in a downlink DCI format that triggers the temporary reference signal **655**. For example, the time/frequency resources that the temporary reference signal **655** is mapped to may be indicated by FDRA/TDRA fields that may be present for PDSCH scheduling.

(92) In some cases, the temporary reference signal **655** triggering by a DCI is supported for both a fallback DCI format (e.g., DCI format 1_0) and a non-fallback DCI format (e.g., DCI format 1_1). In some cases, the temporary reference signal triggering field may indicate no transmission of the temporary reference signal **655**, in which case the UE utilizes the SSB for activation in a similar manner as discussed with reference to the example of FIG. 3. In some cases, the temporary reference signal **655** triggering by a DCI is supported only for particular DCI formats. For example one particular DCI format may be a non-fallback DCI format (e.g., DCI format 1_1), and if the PDSCH carrying MAC-CE for SCell **610** activation is scheduled by a fallback DCI format (e.g., DCI format 1_0), then the DCI format may not have a temporary reference signal triggering field, and a temporary reference signal is assumed to be not transmitted, in which case the UE may utilize the SSB for activation in a similar manner as discussed with reference to the example of FIG. 3. In some cases, the particular DCI format is explicitly configured by the base station via RRC signaling. In further cases, the temporary reference signal **655** triggering by a DCI may be supported only for a DCI format in a particular search space set (or sets). For example, the particular search space set may be a UE-specific search space set, and if the PDSCH carrying the MAC-CE for SCell **610** activation is scheduled by a DCI format in a common search space (CSS) set, then the DCI format may not have a temporary reference signal triggering field, and a temporary reference signal is assumed to be not transmitted (e.g., similarly as discussed with reference to FIG. 3). In some cases, the particular search space set is explicitly configured by the base station via RRC signaling.

(93) FIG. 7 illustrates an example of a resource allocation scheme **700** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some examples, resource allocation scheme **700** may implement aspects of wireless communications system **100** or **200**. The resource allocation scheme **700** in this example illustrates activation of a serving cell using a temporary reference signal **755** for one or more cell measurements.

(94) Similarly as above, the resource allocation scheme **700** may include a first serving cell, namely PCell **705**, and an SCell **710** that is to be activated at a UE. In some cases, the base station serving the SCell **710** (which may be a same base station as serving the PCell **705** or a different base station) may be configured to transmit SSB messages **715** to the UE via the SCell **710** according to an SSB periodicity **720**. The UE may receive, via the PCell **705**, DCI **725** which schedules a PDSCH transmission **730** (e.g., that includes MAC-CE message having an activation command for the SCell **710**) from the base station to the UE. Subsequently, the UE may receive the

PDSCH transmission **730** (e.g., MAC-CE message) based on the DCI **725**. The UE may transmit, to the base station via the PCell **705**, a feedback message **735** (e.g., ACK message) in response to successfully receiving the indication to activate the SCell **710** via the PDSCH transmission **730**. (95) In this example, a MAC-CE in the PDSCH transmission **730** may be used to provide one or more parameters associated with the temporary reference signal **755**. For example, such a MAC-CE may provide an indication of one or more of a carrier where the temporary reference signal **755** is transmitted, a slot where the temporary reference signal **755** is transmitted, a configuration of the temporary reference signal **755** (e.g., resource mapping or power offset to data/SSB), or a QCL assumption or TCI-state for the temporary reference signal. In some cases, the PDSCH transmission **730** carrying the MAC-CE for the SCell **710** activation also carries the MAC-CE for the temporary reference signal **755** trigger. The PDSCH transmission **730** carrying the MAC-CE of SCell **710** activation command, in this example, also carries the MAC-CE of temporary reference signal **755** triggering on the SCell **710** to-be-activated.

(96) In some cases, a same MAC-CE may jointly indicate SCell **710** activation and temporary reference signal **755** triggering. In other cases, a first MAC-CE indicates SCell **710** activation and another MAC-CE indicates temporary reference signal **755** triggering. In some cases, the temporary reference signal **755** may triggered at least a predetermined time period (e.g., 3 ms) after the feedback message **735** transmission for the PDSCH transmission **730**.

(97) FIG. **8** illustrates an example of a resource allocation scheme **800** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some examples, resource allocation scheme **800** may implement aspects of wireless communications system **100** or **200**. The resource allocation scheme **800** in this example illustrates activation of a serving cell using a temporary reference signal **855** for one or more cell measurements.

(98) Similarly as above, the resource allocation scheme **800** may include a first serving cell, namely PCell **805**, and an SCell **810** that is to be activated at a UE. In some cases, the base station serving the SCell **810** (which may be a same base station as serving the PCell **805** or a different base station) may be configured to transmit SSB messages **815** to the UE via the SCell **810** according to an SSB periodicity **820**. The UE may receive, via the PCell **805**, a first DCI **825** which schedules a first PDSCH transmission **830** (e.g., that includes MAC-CE message having an activation command for the SCell **810**) from the base station to the UE. Subsequently, the UE may receive the first PDSCH transmission **830** (e.g., MAC-CE message) based on the first DCI **825**. The UE may transmit, to the base station via the PCell **805**, a feedback message **835** (e.g., ACK/NACK message) in response to successfully receiving the indication to activate the SCell **810** via the first PDSCH transmission **830**.

(99) In this example, a second DCI **870** may schedule a second PDSCH transmission **875** that includes a second MAC-CE that may be used to provide one or more parameters associated with the temporary reference signal **855**. For example, such a second MAC-CE may provide an indication of one or more of a carrier where the temporary reference signal **855** is transmitted, a slot where the temporary reference signal **855** is transmitted, a configuration of the temporary reference signal **855** (e.g., resource mapping or power offset to data/SSB), or a QCL assumption or TCI-state for the temporary reference signal. Thus, the first PDSCH transmission **830** indicates SCell **810** activation and a second MAC-CE in the second PDSCH transmission **875** indicates temporary reference signal triggering and associated parameters. In some case, the temporary reference signal **855** may be triggered at least a predetermined time period (e.g., 3 ms) after an ACK/NACK transmission **880** of the second PDSCH transmission **875**.

(100) With reference to the examples of FIGS. **7** and **8**, in some cases, the MAC-CE contents cannot be changed once the transport block is generated. In such cases, once temporary reference signal triggering is indicated by a MAC-CE carried by a PDSCH, that indication is kept in the initial transmission and any re-transmission of the transport block. Thus, if the base station wants to

trigger a temporary reference signal for SCell activation at a certain timing, if the PDSCH decoding is failed and the PDSCH is re-transmitted, then the base station may no longer want to trigger temporary reference signal for SCell activation. For example, for a re-transmission, an SSB on the SCell to-be-activated may be expected to be available right after ACK+3 ms for the PDSCH carrying MAC-CE SCell activation command, and a temporary reference signal is not needed. Accordingly, for a re-transmission, PDSCHs for other UEs may be scheduled at the timing where the temporary reference signal for the concerned UE is supposed to be transmitted, in which case the base station may want to prioritize PDSCH scheduling for other UEs, rather than using resources for a temporary reference signal for the SCell activation of this concerned UE.

(101) In order to allow the base station to cancel a transmission of a temporary reference signal, in some cases, the base station may enable turning off the temporary reference signal indication provided in the MAC-CE through a DCI indication. In some cases, the temporary reference signal triggering by a MAC-CE is enabled only if the PDSCH carrying the MAC-CE is scheduled by a particular DCI format. For example, the particular DCI format may be a non-fallback DCI format (e.g., DCI format 1_1), and if the PDSCH carrying MAC-CE with a SCell activation command is scheduled by a fallback DCI format (e.g., DCI format 1_0), then the DCI format may not have a temporary reference signal triggering field, and a temporary reference signal is assumed to be not transmitted, in which case the UE utilizes the SSB for activation in a manner similar as discussed with reference to FIG. 3. Otherwise, if a non-fallback DCI format is used, the temporary reference signal is transmitted. In some cases, the particular DCI format may be explicitly configured by the base station via RRC signaling. In other cases, the temporary reference signal triggering by a MAC-CE is enabled only if the PDSCH carrying the MAC-CE is scheduled by particular search space set. For example, the particular search space set may be a UE-specific search space set. Thus, if the PDSCH carrying MAC-CE for an SCell activation command is scheduled by a DCI format in a common search space (CSS) set, then the DCI format may not have a temporary reference signal triggering field, and a temporary reference signal is assumed to be not transmitted. The particular search space set may be explicitly configured by the base station via RRC signaling.

(102) FIG. 9 illustrates examples of reference signal activation fields **900** that support reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some examples, reference signal activation fields **900** may implement aspects of wireless communications system **100** or **200**. As discussed with reference to FIGS. 7 and 8, a MAC-CE may be used to provide temporary reference signal triggering and one or more associated parameters.

(103) The MAC-CE may trigger the temporary reference signal through one or more activation or triggering fields in the MAC-CE. In a first example **905**, a MAC-CE jointly indicates SCell activation and temporary reference signal triggering. In this example **905**, a SCell activation field **910** may contain a Ci field which indicates the SCell to be activated, and a TRS triggering field **915** that indicates temporary reference signal details $\{T_{i,j}\}$ with $j=0, 1, \dots$, that carries indication of temporary reference signal for the cell having index i, or for the i-th cell amongst the SCells to-be-activated by this MAC-CE.

(104) In a second example **920**, the PDSCH carrying the MAC-CE for the SCell activation may be different than the PDSCH carrying the MAC-CE for the temporary reference signal trigger. In this example **920**, the MAC-CE for SCell activation may be unchanged from traditional MAC-CEs, and the MAC-CE for the temporary reference signal may have TRS triggering field **925** with $\{T_{i,j}\}$ with $j=0, 1, \dots$, which carries an indication of temporary reference signal for the cell having index i. In a third example **930**, a MAC-CE may have a carrier indication field **935** with $\{C_i\}$ with $i=0, 1, \dots$, which indicates which carrier the temporary reference signal is triggered, and a TRS triggering field **940** with $\{T_{i,j}\}$ with $j=0, 1, \dots$, that carries an indication of the temporary reference signal for the serving cell corresponding to C_i .

(105) FIG. 10 illustrates an example of a process flow **1000** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. In some

examples, process flow **1000** may implement aspects of wireless communications system **100** or **200**, may implement resource allocation schemes of FIGS. **3** through **8**, or any combination thereof. For example, the process flow **1000** may illustrate a UE **115-b** receiving an indication from a first serving cell **205-c** that a SCell **205-d** has been activated (thus becoming a new serving cell of the UE **115-b**), receiving a reference signal on the SCell, and activating the SCell **205-d**, as described with reference to FIGS. **1-9**, among other aspects.

(106) The process flow **1000** may include a UE **115-b**, a first serving cell **205-c** (e.g. a PCell), and a SCell **205-d**, which may be examples of UEs **115** and serving cells **205** as described with reference to FIGS. **1** and **2**. In particular, the first serving cell **205-c** may include an example of a serving cell **205** at the UE **115-b** which is to remain active, and the SCell **205-d** may include an example of a serving cell **205** which is to be activated. In some aspects, the first serving cell **205-c** and the SCell **205-d** may be associated with (e.g., supported by) a single base station **105** of a wireless communications system (e.g., base station **105-a** illustrated in FIG. **2**). Additionally, or alternatively, the first serving cell **205-c** and the SCell **205-d** may be associated with (e.g., supported by) different base stations **105**.

(107) In some examples, the operations illustrated in process flow **1000** may be performed by hardware (e.g., including circuitry, processing blocks, logic components, and other components), code (e.g., software) executed by a processor, or any combination thereof. Alternative examples of the following may be implemented, where some steps are performed in a different order than described or are not performed at all. In some cases, steps may include additional features not mentioned below, or further steps may be added.

(108) At **1005**, the UE **115-b** may establish wireless communications with the first serving cell **205-c**. In some aspects, the UE **115-b** may establish the wireless communications with the first serving cell **205-c** by initiating or otherwise performing a setup procedure with the first serving cell **205-c**. In some aspects, the first serving cell **205-c** and the SCell **205-d** may be associated with the same frequency band (e.g., intra-band carrier aggregation), or a different frequency band (e.g., inter-band carrier aggregation). In some cases, the first serving cell **205-c**, the SCell **205-d**, or both, may be associated with a given radio access technology, such as a 5G radio access technology, an NR access technology, a 4G radio access technology, an LTE radio access technology, or any combination thereof. In some cases, the first serving cell **205-c** may be associated with the same or different radio access technology as the radio access technology associated with the SCell **205-d**. Moreover, in some cases, the first serving cell **205-c** and the SCell **205-d** may be associated with different frequency bands associated with a common radio access technology. For example, in some cases, both the cells may be associated with an NR access technology, where the first serving cell **205-c** is associated an FR1 frequency band of the NR access technology and the SCell **205-d** is associated an FR2 frequency band of the NR access technology.

(109) At **1010**, the UE **115-b** may receive a DCI message via the first serving cell **205-c**. In some aspects, the DCI may include an indication of PDSCH resources usable by the UE **115-b** to receive a MAC-CE that activates the SCell **205-d**. The DCI message may be transmitted via PDCCH resources. In some aspects, the UE **115-b** may receive the DCI message at **1010** based on establishing the wireless communications with the first serving cell **205-c** at **1005**, receiving a control or configuration message (e.g., RRC message, SIB message, SSB message), or any combination thereof.

(110) In some aspects, the DCI message may include an indication that the reference signals (e.g., temporary reference signals) associated with the SCell **205-d** have been activated (e.g., triggered, initiated). In this regard, the UE **115-b** may be configured to determine that it may monitor for the reference signals on the SCell **205-d** based on the indication in the DCI message.

(111) At **1015**, the UE **115-b** may receive, from the base station via the first serving cell **205-c**, an indication to activate the SCell **205-d**. In some aspects, the indication to activate the SCell **205-d** may be indicated via a MAC-CE message. In some aspects, the base station may transmit, and the

UE **115-b** may receive, the indication to activate the SCell **205-d** based on the DCI message. For example, the DCI message may schedule a PDSCH transmission (e.g., MAC-CE message), where the PDSCH transmission includes the indication to activate the SCell **205-d**. In cases where the indication to activate the SCell **205-d** is conveyed via a MAC-CE message, the MAC-CE message may include an indication that the reference signals (e.g., temporary reference signals) associated with the SCell **205-d** have been activated (e.g., triggered, initiated).

(112) At **1020**, the UE **115-b** may transmit a feedback message to the base station via the first serving cell **205-c**. In some aspects, the UE **115-b** may transmit the feedback message to the base station based on (e.g., in response to) receiving the indication to activate the SCell **205-d**. The feedback message may include an ACK message, a NACK message, or both. For example, in cases where the indication includes an activation of the SCell **205-d**, the UE **115-b** may transmit an ACK message in response to the activation of the SCell **205-d**.

(113) At **1025**, the UE **115-b** may determine one or more temporary reference signal parameters for the SCell **205-d**. The determination of the temporary reference signal parameters may be made in accordance with various techniques as discussed herein. In some aspects, the UE **115-b** may determine that the temporary reference signal has been activated based on an implicit determination, based on explicit signaling received from the base station, or both. In particular, the UE **115-b** may be configured to determine that the reference signals associated with the SCell **205-d** have been activated based on receiving the DCI message, receiving the indication to activate the SCell (e.g., MAC-CE message), or both.

(114) At **1030**, the UE **115-b** may receive a reference signal from the base station via the SCell **205-d**. In some aspects, the UE **115-a** may receive the reference signal in accordance with techniques as discussed herein. The reference signal may include, but is not limited to, a temporary reference signal. For example, the temporary reference signal may include a tracking reference signal, a non-zero power CSI-RS configured as a tracking reference signal, one or more other reference signals, or combinations thereof.

(115) At **1035**, the UE **115-b** may determine and/or adjust AGC associated with the SCell **205-d**, tracking (e.g., time tracking, frequency tracking) associated with the SCell **205-d**, or any combination thereof. For example, the reference signals may include an indication of AGC and/or tracking associated with the SCell **205-d**.

(116) At **1040**, the UE **115-b** may conduct the wireless communications with the first serving cell **205-c** and the SCell **205-d**. For example, such communications may be based at least in part on the determined and/or adjusted AGC associated with the SCell **205-d**, tracking (e.g., time tracking, frequency tracking) associated with the SCell **205-d**, or any combination thereof.

(117) FIG. **11** shows a block diagram **1100** of a device **1105** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The device **1105** may be an example of aspects of a UE **115** as described herein. The device **1105** may include a receiver **1110**, a communications manager **1115**, and a transmitter **1120**. The device **1105** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(118) The receiver **1110** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to reference signal configuration for SCell activation). Information may be passed on to other components of the device **1105**. The receiver **1110** may be an example of aspects of the transceiver **1420** described with reference to FIG. **14**. The receiver **1110** may utilize a single antenna or a set of antennas.

(119) The communications manager **1115** may receive, from a base station, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell, identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic

reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and measure one or more characteristics of the SCell based on the aperiodic reference signal. The communications manager **1115** may be an example of aspects of the communications manager **1410** described herein.

(120) The communications manager **1115**, or its sub-components, may be implemented in hardware, code (e.g., software) executed by a processor, or any combination thereof. If implemented in code executed by a processor, the functions of the communications manager **1115**, or its sub-components may be executed by a general-purpose processor, a central processing unit (CPU), a graphics processing unit (GPU), a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described in the present disclosure.

(121) The communications manager **1115**, or its sub-components, may be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations by one or more physical components. In some examples, the communications manager **1115**, or its sub-components, may be a separate and distinct component in accordance with various aspects of the present disclosure. In some examples, the communications manager **1115**, or its sub-components, may be combined with one or more other hardware components, including but not limited to an input/output (I/O) component, a transceiver, a network server, another computing device, one or more other components described in the present disclosure, or a combination thereof in accordance with various aspects of the present disclosure.

(122) The transmitter **1120** may transmit signals generated by other components of the device **1105**. In some examples, the transmitter **1120** may be collocated with a receiver **1110** in a transceiver module. For example, the transmitter **1120** may be an example of aspects of the transceiver **1420** described with reference to FIG. **14**. The transmitter **1120** may utilize a single antenna or a set of antennas.

(123) FIG. **12** shows a block diagram **1200** of a device **1205** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The device **1205** may be an example of aspects of a device **1105**, or a UE **115** as described herein. The device **1205** may include a receiver **1210**, a communications manager **1215**, and a transmitter **1235**. The device **1205** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(124) The receiver **1210** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to reference signal configuration for SCell activation). Information may be passed on to other components of the device **1205**. The receiver **1210** may be an example of aspects of the transceiver **1420** described with reference to FIG. **14**. The receiver **1210** may utilize a single antenna or a set of antennas.

(125) The communications manager **1215** may be an example of aspects of the communications manager **1115** as described herein. The communications manager **1215** may include a SCell activation manager **1220**, a temporary reference signal manager **1225**, and a measurement manager **1230**. The communications manager **1215** may be an example of aspects of the communications manager **1410** described herein.

(126) The SCell activation manager **1220** may receive, from a base station, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell.

(127) The temporary reference signal manager **1225** may identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference

signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof.

(128) The measurement manager **1230** may measure one or more characteristics of the SCell based on the aperiodic reference signal.

(129) The transmitter **1235** may transmit signals generated by other components of the device **1205**. In some examples, the transmitter **1235** may be collocated with a receiver **1210** in a transceiver module. For example, the transmitter **1235** may be an example of aspects of the transceiver **1420** described with reference to FIG. **14**. The transmitter **1235** may utilize a single antenna or a set of antennas.

(130) FIG. **13** shows a block diagram **1300** of a communications manager **1305** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The communications manager **1305** may be an example of aspects of a communications manager **1115**, a communications manager **1215**, or a communications manager **1410** described herein. The communications manager **1305** may include a SCell activation manager **1310**, a temporary reference signal manager **1315**, a measurement manager **1320**, and a configuration manager **1325**. Each of these modules may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(131) The SCell activation manager **1310** may receive, from a base station, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. In some examples, the SCell activation manager **1310** may receive, from the base station, DCI that indicates the one or more parameters for the aperiodic reference signal. In some examples, the SCell activation manager **1310** may receive, subsequent to receiving the MAC-CE, a DCI transmission from the base station that disables the aperiodic reference signal.

(132) In some cases, the DCI schedules a shared channel communication that provides the SCell activation message and indicates the one or more parameters for the aperiodic reference signal. In some cases, the DCI is a separate DCI from a scheduling DCI that schedules a shared channel communication that provides the SCell activation message. In some cases, the separate DCI includes other scheduling information for downlink shared channel communications with the UE, and the one or more parameters for the aperiodic reference signal. In some cases, the DCI has a fallback DCI format or a non-fallback DCI format.

(133) In some cases, a first MAC-CE provides the one or more parameters for the aperiodic reference signal and a second MAC-CE provides the SCell activation message. In some cases, the first MAC-CE and the second MAC-CE are in a same downlink shared channel communication, or are in different downlink shared channel communications, from the base station. In some cases, the MAC-CE includes a first field that indicates the SCell that is to be activated and a second field that indicates the one or more parameters for the aperiodic reference signal for the SCell that is to be activated. In some cases, the one or more parameters for the aperiodic reference signal are implicitly indicated by a MAC-CE that carries the SCell activation message.

(134) The temporary reference signal manager **1315** may identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof.

(135) In some examples, the temporary reference signal manager **1315** may receive, from the base station, a MAC-CE that indicates the one or more parameters for the aperiodic reference signal. In some cases, the aperiodic reference signal is transmitted after a time gap associated with the SCell activation message. In some cases, the time gap corresponds to a first predetermined time period after an acknowledgment of the SCell activation message by the UE, a second predetermined time

period after a downlink control channel communication that provides the DCI, or a third predetermined time period after an acknowledgment of the DCI by the UE.

(136) In some cases, the one or more parameters for the aperiodic reference signal are provided in an information field in the DCI, and where the information field has a same format as a CSI request field that is transmitted in DCI. In some cases, the separate DCI is included with a downlink control channel communication that does not provide scheduling information for shared channel communications. In some cases, the one or more parameters for the aperiodic reference signal are provided in one or more fields in the separate DCI that are otherwise used for the scheduling information for shared channel communications. In some cases, the one or more parameters for the aperiodic reference signal are provided in an information field having a same format as a CSI request field in an uplink grant.

(137) In some cases, a number of bits in the information field is configured by RRC signaling or is determined based on a number of available tracking reference signal (TRS) states. In some cases, the information field is mapped to one or more of a TRS timing or slot, a TRS resource, a TRS power offset, or any combinations thereof, for one or multiple serving cells. In some cases, the one or more parameters for the aperiodic reference signal are provided in one or more of a FDRA field, a TDRA field, or any combinations thereof.

(138) In some cases, the MAC-CE that provides the one or more parameters for the aperiodic reference signal also provides the SCell activation message. In some cases, the MAC-CE includes a field that carries an indication of the one or more parameters for the aperiodic reference signal for two or more SCells. In some cases, the MAC-CE includes a first field that indicates a carrier of the aperiodic reference signal, and a second field that indicates one or more other parameters for the aperiodic reference signal.

(139) In some cases, the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a preconfigured DCI format. In some cases, the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a DCI transmission in a DCI search space set that is configured by RRC signaling.

(140) The measurement manager **1320** may measure one or more characteristics of the SCell based on the aperiodic reference signal. In some examples, the measurement manager **1320** may measurements of the aperiodic reference signal are triggered by the DCI having a preconfigured DCI format. In some cases, the DCI indicates that the UE is not to measure the aperiodic reference signal, and where the measuring of the one or more characteristics the SCell is based on one or more channel measurements of a synchronization signal block (SSB) associated with the SCell.

(141) The configuration manager **1325** may receive, from the base station, one or more of DCI or a MAC-CE that includes information associated with the aperiodic reference signal. In some examples, the configuration manager **1325** may determine, based on the DCI, the MAC control element, implicit signaling, or combinations thereof, the one or more parameters for the aperiodic reference signal. In some examples, measurements of the aperiodic reference signal are triggered by the DCI located in a preconfigured DCI search space set. In some cases, the one or more parameters for the aperiodic reference signal include one or more of the carrier for the aperiodic reference signal, the slot location of the aperiodic reference signal, a mapping of resources of the aperiodic reference signal, a power offset of the aperiodic reference signal relative to a downlink shared channel or SSB transmission, a QCL assumption for a beam of the aperiodic reference signal, a TCI state of the aperiodic reference signal, or any combinations thereof. In some cases, the preconfigured DCI format is configured by RRC signaling. In some cases, one or more preconfigured DCI search space sets that can contain DCI that triggers measurement of the aperiodic reference signal are configured by RRC signaling. In some cases, the one or more parameters for the aperiodic reference signal are preconfigured at the UE by higher layer signaling.

(142) FIG. **14** shows a diagram of a system **1400** including a device **1405** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The

device **1405** may be an example of or include the components of device **1105**, device **1205**, or a UE **115** as described herein. The device **1405** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, including a communications manager **1410**, an I/O controller **1415**, a transceiver **1420**, an antenna **1425**, memory **1430**, and a processor **1440**. These components may be in electronic communication via one or more buses (e.g., bus **1445**).

(143) The communications manager **1410** may receive, from a base station, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell, identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and measure one or more characteristics of the SCell based on the aperiodic reference signal.

(144) The I/O controller **1415** may manage input and output signals for the device **1405**. The I/O controller **1415** may also manage peripherals not integrated into the device **1405**. In some cases, the I/O controller **1415** may represent a physical connection or port to an external peripheral. In some cases, the I/O controller **1415** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system. In other cases, the I/O controller **1415** may represent or interact with a modem, a keyboard, a mouse, a touchscreen, or a similar device. In some cases, the I/O controller **1415** may be implemented as part of a processor. In some cases, a user may interact with the device **1405** via the I/O controller **1415** or via hardware components controlled by the I/O controller **1415**.

(145) The transceiver **1420** may communicate bi-directionally, via one or more antennas, wired, or wireless links as described above. For example, the transceiver **1420** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **1420** may also include a modem to modulate the packets and provide the modulated packets to the antennas for transmission, and to demodulate packets received from the antennas.

(146) In some cases, the wireless device may include a single antenna **1425**. However, in some cases the device may have more than one antenna **1425**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions.

(147) The memory **1430** may include random access memory (RAM) and read-only memory (ROM). The memory **1430** may store computer-readable, computer-executable code **1435** including instructions that, when executed, cause the processor to perform various functions described herein. In some cases, the memory **1430** may contain, among other things, a basic input/output system (BIOS) which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(148) The processor **1440** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a CPU, a GPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, the processor **1440** may be configured to operate a memory array using a memory controller. In other cases, a memory controller may be integrated into the processor **1440**. The processor **1440** may be configured to execute computer-readable instructions stored in a memory (e.g., the memory **1430**) to cause the device **1405** to perform various functions (e.g., functions or tasks supporting reference signal configuration for SCell activation).

(149) The code **1435** may include instructions to implement aspects of the present disclosure, including instructions to support wireless communications. The code **1435** may be stored in a non-transitory computer-readable medium such as system memory or other type of memory. In some cases, the code **1435** may not be directly executable by the processor **1440** but may cause a computer (e.g., when compiled and executed) to perform functions described herein.

(150) FIG. 15 shows a block diagram 1500 of a device 1505 that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The device 1505 may be an example of aspects of a base station 105 as described herein. The device 1505 may include a receiver 1510, a communications manager 1515, and a transmitter 1520. The device 1505 may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(151) The receiver 1510 may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to reference signal configuration for SCell activation). Information may be passed on to other components of the device 1505. The receiver 1510 may be an example of aspects of the transceiver 1820 described with reference to FIG. 18. The receiver 1510 may utilize a single antenna or a set of antennas.

(152) The communications manager 1515 may transmit, to a UE, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell, identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal of the SCell, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and transmit the aperiodic reference signal to the UE based on the identifying. The communications manager 1515 may be an example of aspects of the communications manager 1810 described herein.

(153) The communications manager 1515, or its sub-components, may be implemented in hardware, code (e.g., software) executed by a processor, or any combination thereof. If implemented in code executed by a processor, the functions of the communications manager 1515, or its sub-components may be executed by a general-purpose processor, a DSP, an application-specific integrated circuit (ASIC), a FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described in the present disclosure.

(154) The communications manager 1515, or its sub-components, may be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations by one or more physical components. In some examples, the communications manager 1515, or its sub-components, may be a separate and distinct component in accordance with various aspects of the present disclosure. In some examples, the communications manager 1515, or its sub-components, may be combined with one or more other hardware components, including but not limited to an input/output (I/O) component, a transceiver, a network server, another computing device, one or more other components described in the present disclosure, or a combination thereof in accordance with various aspects of the present disclosure.

(155) The transmitter 1520 may transmit signals generated by other components of the device 1505. In some examples, the transmitter 1520 may be collocated with a receiver 1510 in a transceiver module. For example, the transmitter 1520 may be an example of aspects of the transceiver 1820 described with reference to FIG. 18. The transmitter 1520 may utilize a single antenna or a set of antennas.

(156) FIG. 16 shows a block diagram 1600 of a device 1605 that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The device 1605 may be an example of aspects of a device 1505, or a base station 105 as described herein. The device 1605 may include a receiver 1610, a communications manager 1615, and a transmitter 1630. The device 1605 may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(157) The receiver 1610 may receive information such as packets, user data, or control information

associated with various information channels (e.g., control channels, data channels, and information related to reference signal configuration for SCell activation). Information may be passed on to other components of the device **1605**. The receiver **1610** may be an example of aspects of the transceiver **1820** described with reference to FIG. **18**. The receiver **1610** may utilize a single antenna or a set of antennas.

(158) The communications manager **1615** may be an example of aspects of the communications manager **1515** as described herein. The communications manager **1615** may include a SCell activation manager **1620** and a temporary reference signal manager **1625**. The communications manager **1615** may be an example of aspects of the communications manager **1810** described herein.

(159) The SCell activation manager **1620** may transmit, to a UE, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell.

(160) The temporary reference signal manager **1625** may identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal of the SCell, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof and transmit the aperiodic reference signal to the UE based on the identifying.

(161) The transmitter **1630** may transmit signals generated by other components of the device **1605**. In some examples, the transmitter **1630** may be collocated with a receiver **1610** in a transceiver module. For example, the transmitter **1630** may be an example of aspects of the transceiver **1820** described with reference to FIG. **18**. The transmitter **1630** may utilize a single antenna or a set of antennas.

(162) FIG. **17** shows a block diagram **1700** of a communications manager **1705** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The communications manager **1705** may be an example of aspects of a communications manager **1515**, a communications manager **1615**, or a communications manager **1810** described herein. The communications manager **1705** may include a SCell activation manager **1710**, a temporary reference signal manager **1715**, a configuration manager **1720**, and a measurement manager **1725**. Each of these modules may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(163) The SCell activation manager **1710** may transmit, to a UE, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. In some examples, the SCell activation manager **1710** may transmit, subsequent to transmitting the MAC-CE, a DCI transmission to the UE that disables the aperiodic reference signal.

(164) In some cases, the DCI schedules a shared channel communication that provides the SCell activation message and indicates the one or more parameters for the aperiodic reference signal. In some cases, the DCI is a separate DCI from a scheduling DCI that schedules a shared channel communication that provides the SCell activation message. In some cases, the separate DCI includes other scheduling information for downlink shared channel communications with the UE, and the one or more parameters for the aperiodic reference signal. In some cases, the separate DCI is included with a downlink control channel communication that does not provide scheduling information for shared channel communications. In some cases, the one or more parameters for the aperiodic reference signal are provided in one or more fields in the separate DCI that are otherwise used for the scheduling information for shared channel communications. In some cases, the DCI has a fallback DCI format or a non-fallback DCI format.

(165) In some cases, a first MAC-CE provides the one or more parameters for the aperiodic reference signal and a second MAC-CE provides the SCell activation message. In some cases, the first MAC-CE and the second MAC-CE are in a same downlink shared channel communication, or are in different downlink shared channel communications, from the base station. In some cases, the

MAC-CE includes a first field that indicates the SCell that is to be activated and a second field that indicates the one or more parameters for the aperiodic reference signal for the SCell that is to be activated. In some cases, the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a preconfigured DCI format. In some cases, the one or more parameters for the aperiodic reference signal are implicitly indicated by a MAC-CE that carries the SCell activation message.

(166) The temporary reference signal manager **1715** may identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal of the SCell, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof. In some examples, the temporary reference signal manager **1715** may transmit the aperiodic reference signal to the UE based on the identifying.

(167) In some examples, the temporary reference signal manager **1715** may transmit, to the UE, one or more of DCI or a MAC-CE that includes information associated with the aperiodic reference signal, and where the one or more parameters for the aperiodic reference signal are indicated by the DCI, the MAC-CE, an implicit indication, or any combinations thereof. In some examples, the temporary reference signal manager **1715** may transmit, to the UE, a MAC-CE that indicates the one or more parameters for the aperiodic reference signal.

(168) In some cases, the one or more parameters for the aperiodic reference signal include one or more of the carrier for the aperiodic reference signal, the slot location of the aperiodic reference signal, a mapping of resources of the aperiodic reference signal, a power offset of the aperiodic reference signal relative to a downlink shared channel or SSB transmission, a QCL assumption for a beam of the aperiodic reference signal, a TCI state of the aperiodic reference signal, or any combinations thereof. In some cases, the aperiodic reference signal is transmitted after a time gap associated with the SCell activation message. In some cases, the time gap corresponds to a first predetermined time period after an acknowledgment of the SCell activation message by the UE, a second predetermined time period after a downlink control channel communication that provides the DCI, or a third predetermined time period after an acknowledgment of the DCI by the UE.

(169) In some cases, the one or more parameters for the aperiodic reference signal are provided in an information field in the DCI, and where the information field has a same format as a CSI request field that is transmitted in DCI. In some cases, the one or more parameters for the aperiodic reference signal are provided in one or more of a FDRA field, a TDRA field, or any combinations thereof. In some cases, the DCI indicates that the UE is not to measure the aperiodic reference signal, and where the UE measures one or more characteristics of the SCell is based on one or more channel measurements of a SSB associated with the SCell.

(170) In some cases, the MAC-CE that provides the one or more parameters for the aperiodic reference signal also provides the SCell activation message. In some cases, the MAC-CE includes a field that carries an indication of the one or more parameters for the aperiodic reference signal for two or more SCells. In some cases, the MAC-CE includes a first field that indicates a carrier of the aperiodic reference signal, and a second field that indicates one or more other parameters for the aperiodic reference signal. In some cases, the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a DCI transmission in a DCI search space set that is configured by RRC signaling.

(171) The configuration manager **1720** may transmit, to the UE, DCI that indicates the one or more parameters for the aperiodic reference signal. In some cases, the one or more parameters for the aperiodic reference signal are provided in an information field having a same format as a CSI request field in an uplink grant. In some cases, a number of bits in the information field is configured by RRC signaling or is determined based on a number of available tracking reference signal (TRS) states. In some cases, the information field is mapped to one or more of a TRS timing

or slot, a TRS resource, a TRS power offset, or any combinations thereof, for one or multiple serving cells. In some cases, the preconfigured DCI format is configured by RRC signaling. In some cases, one or more preconfigured DCI search space sets that can contain DCI that triggers measurement of the aperiodic reference signal are configured by RRC signaling. In some cases, the one or more parameters for the aperiodic reference signal are preconfigured at the UE by higher layer signaling.

(172) The measurement manager **1725** may measurements of the aperiodic reference signal are triggered by the DCI having a preconfigured DCI format. In some examples, measurements of the aperiodic reference signal are triggered by the DCI located in a preconfigured DCI search space set.

(173) FIG. **18** shows a diagram of a system **1800** including a device **1805** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The device **1805** may be an example of or include the components of device **1505**, device **1605**, or a base station **105** as described herein. The device **1805** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, including a communications manager **1810**, a network communications manager **1815**, a transceiver **1820**, an antenna **1825**, memory **1830**, a processor **1840**, and an inter-station communications manager **1845**. These components may be in electronic communication via one or more buses (e.g., bus **1850**).

(174) The communications manager **1810** may transmit, to a UE, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell, identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal of the SCell, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof, and transmit the aperiodic reference signal to the UE based on the identifying.

(175) The network communications manager **1815** may manage communications with the core network (e.g., via one or more wired backhaul links). For example, the network communications manager **1815** may manage the transfer of data communications for client devices, such as one or more UEs **115**.

(176) The transceiver **1820** may communicate bi-directionally, via one or more antennas, wired, or wireless links as described above. For example, the transceiver **1820** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **1820** may also include a modem to modulate the packets and provide the modulated packets to the antennas for transmission, and to demodulate packets received from the antennas.

(177) In some cases, the wireless device may include a single antenna **1825**. However, in some cases the device may have more than one antenna **1825**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions.

(178) The memory **1830** may include RAM, ROM, or a combination thereof. The memory **1830** may store computer-readable code **1835** including instructions that, when executed by a processor (e.g., the processor **1840**) cause the device to perform various functions described herein. In some cases, the memory **1830** may contain, among other things, a BIOS which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(179) The processor **1840** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a CPU, a GPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, the processor **1840** may be configured to operate a memory array using a memory controller. In some cases, a memory controller may be integrated into processor **1840**. The processor **1840** may be configured to execute computer-readable instructions stored in a memory (e.g., the memory **1830**) to cause the device **1805** to perform various functions (e.g., functions or tasks supporting reference signal configuration for SCell activation).

(180) The inter-station communications manager **1845** may manage communications with other base station **105**, and may include a controller or scheduler for controlling communications with UEs **115** in cooperation with other base stations **105**. For example, the inter-station communications manager **1845** may coordinate scheduling for transmissions to UEs **115** for various interference mitigation techniques such as beamforming or joint transmission. In some examples, the inter-station communications manager **1845** may provide an X2 interface within an LTE/LTE-A wireless communication network technology to provide communication between base stations **105**.

(181) The code **1835** may include instructions to implement aspects of the present disclosure, including instructions to support wireless communications. The code **1835** may be stored in a non-transitory computer-readable medium such as system memory or other type of memory. In some cases, the code **1835** may not be directly executable by the processor **1840** but may cause a computer (e.g., when compiled and executed) to perform functions described herein.

(182) FIG. **19** shows a flowchart illustrating a method **1900** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **1900** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **1900** may be performed by a communications manager as described with reference to FIGS. **11** through **14**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the functions described below. Additionally, or alternatively, a UE may perform aspects of the functions described below using special-purpose hardware.

(183) At **1905**, the UE may receive, from a base station, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **1905** may be performed according to the methods described herein. In some examples, aspects of the operations of **1905** may be performed by a SCell activation manager as described with reference to FIGS. **11** through **14**.

(184) At **1910**, the UE may identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof. The operations of **1910** may be performed according to the methods described herein. In some examples, aspects of the operations of **1910** may be performed by a temporary reference signal manager as described with reference to FIGS. **11** through **14**.

(185) At **1915**, the UE may measure one or more characteristics of the SCell based on the aperiodic reference signal. The operations of **1915** may be performed according to the methods described herein. In some examples, aspects of the operations of **1915** may be performed by a measurement manager as described with reference to FIGS. **11** through **14**.

(186) FIG. **20** shows a flowchart illustrating a method **2000** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **2000** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **2000** may be performed by a communications manager as described with reference to FIGS. **11** through **14**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the functions described below. Additionally, or alternatively, a UE may perform aspects of the functions described below using special-purpose hardware.

(187) At **2005**, the UE may receive, from a base station, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **2005** may be performed according to the methods described herein. In some examples, aspects of the operations of **2005** may be performed by a SCell activation manager as described with reference to FIGS. **11**

through **14**.

(188) At **2010**, the UE may receive, from the base station, one or more of DCI or a MAC-CE that includes information associated with an aperiodic reference signal. The operations of **2010** may be performed according to the methods described herein. In some examples, aspects of the operations of **2010** may be performed by a configuration manager as described with reference to FIGS. **11** through **14**.

(189) At **2015**, the UE may determine, based on the DCI, the MAC-CE, implicit signaling, or combinations thereof, the one or more parameters for the aperiodic reference signal. The operations of **2015** may be performed according to the methods described herein. In some examples, aspects of the operations of **2015** may be performed by a configuration manager as described with reference to FIGS. **11** through **14**. In some cases, the one or more parameters for the aperiodic reference signal include one or more of the carrier for the aperiodic reference signal, the slot location of the aperiodic reference signal, a mapping of resources of the aperiodic reference signal, a power offset of the aperiodic reference signal relative to a downlink shared channel or synchronization signal block transmission, a QCL assumption for a beam of the aperiodic reference signal, a TCI state of the aperiodic reference signal, or any combinations thereof.

(190) At **2020**, the UE may measure one or more characteristics of the SCell based on the aperiodic reference signal. The operations of **2020** may be performed according to the methods described herein. In some examples, aspects of the operations of **2020** may be performed by a measurement manager as described with reference to FIGS. **11** through **14**.

(191) FIG. **21** shows a flowchart illustrating a method **2100** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **2100** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **2100** may be performed by a communications manager as described with reference to FIGS. **11** through **14**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the functions described below. Additionally, or alternatively, a UE may perform aspects of the functions described below using special-purpose hardware.

(192) At **2105**, the UE may receive, from a base station, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **2105** may be performed according to the methods described herein. In some examples, aspects of the operations of **2105** may be performed by a SCell activation manager as described with reference to FIGS. **11** through **14**.

(193) At **2110**, the UE may receive, from the base station, DCI that indicates one or more parameters for the aperiodic reference signal. The operations of **2110** may be performed according to the methods described herein. In some examples, aspects of the operations of **2110** may be performed by a SCell activation manager as described with reference to FIGS. **11** through **14**.

(194) At **2115**, the UE may identify, based on the DCI, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof. The operations of **2115** may be performed according to the methods described herein. In some examples, aspects of the operations of **2115** may be performed by a temporary reference signal manager as described with reference to FIGS. **11** through **14**.

(195) At **2120**, the UE may measure one or more characteristics of the SCell based on the aperiodic reference signal. The operations of **2120** may be performed according to the methods described herein. In some examples, aspects of the operations of **2120** may be performed by a measurement manager as described with reference to FIGS. **11** through **14**.

(196) FIG. **22** shows a flowchart illustrating a method **2200** that supports reference signal

configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **2200** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **2200** may be performed by a communications manager as described with reference to FIGS. **11** through **14**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the functions described below. Additionally, or alternatively, a UE may perform aspects of the functions described below using special-purpose hardware.

(197) At **2205**, the UE may receive, from a base station, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **2205** may be performed according to the methods described herein. In some examples, aspects of the operations of **2205** may be performed by a SCell activation manager as described with reference to FIGS. **11** through **14**.

(198) At **2210**, the UE may receive, from the base station, a MAC-CE that indicates one or more parameters for the aperiodic reference signal. The operations of **2210** may be performed according to the methods described herein. In some examples, aspects of the operations of **2210** may be performed by a temporary reference signal manager as described with reference to FIGS. **11** through **14**.

(199) At **2215**, the UE may identify, based on the MAC-CE, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof. The operations of **2215** may be performed according to the methods described herein. In some examples, aspects of the operations of **2215** may be performed by a temporary reference signal manager as described with reference to FIGS. **11** through **14**.

(200) At **2220**, the UE may measure one or more characteristics of the SCell based on the aperiodic reference signal. The operations of **2220** may be performed according to the methods described herein. In some examples, aspects of the operations of **2220** may be performed by a measurement manager as described with reference to FIGS. **11** through **14**.

(201) FIG. **23** shows a flowchart illustrating a method **2300** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **2300** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **2300** may be performed by a communications manager as described with reference to FIGS. **11** through **14**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the functions described below. Additionally, or alternatively, a UE may perform aspects of the functions described below using special-purpose hardware.

(202) At **2305**, the UE may receive, from a base station, a MAC-CE including an SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **2305** may be performed according to the methods described herein. In some examples, aspects of the operations of **2305** may be performed by a SCell activation manager as described with reference to FIGS. **11** through **14**.

(203) At **2310**, the UE may identify, based on the MAC-CE, one or more parameters for an aperiodic reference signal for cell activation measurements, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof. The operations of **2315** may be performed according to the methods described herein. In some examples, aspects of the operations of **2315** may be performed by a temporary reference signal manager as described with reference to FIGS. **11** through **14**.

(204) At **2315**, the UE may receive, subsequent to receiving the MAC-CE, a DCI transmission from the base station that disables the aperiodic reference signal. The operations of **2320** may be performed according to the methods described herein. In some examples, aspects of the operations of **2320** may be performed by a SCell activation manager as described with reference to FIGS. **11** through **14**.

(205) FIG. **24** shows a flowchart illustrating a method **2400** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **2400** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **2400** may be performed by a communications manager as described with reference to FIGS. **15** through **18**. In some examples, a base station may execute a set of instructions to control the functional elements of the base station to perform the functions described below. Additionally, or alternatively, a base station may perform aspects of the functions described below using special-purpose hardware.

(206) At **2405**, the base station may transmit, to a UE, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **2405** may be performed according to the methods described herein. In some examples, aspects of the operations of **2405** may be performed by a SCell activation manager as described with reference to FIGS. **15** through **18**.

(207) At **2410**, the base station may identify, based on the SCell activation message, one or more parameters for an aperiodic reference signal of the SCell, where the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof. The operations of **2410** may be performed according to the methods described herein. In some examples, aspects of the operations of **2410** may be performed by a temporary reference signal manager as described with reference to FIGS. **15** through **18**.

(208) At **2415**, the base station may transmit the aperiodic reference signal to the UE based on the identifying. The operations of **2415** may be performed according to the methods described herein. In some examples, aspects of the operations of **2415** may be performed by a temporary reference signal manager as described with reference to FIGS. **15** through **18**.

(209) FIG. **25** shows a flowchart illustrating a method **2500** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **2500** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **2500** may be performed by a communications manager as described with reference to FIGS. **15** through **18**. In some examples, a base station may execute a set of instructions to control the functional elements of the base station to perform the functions described below. Additionally, or alternatively, a base station may perform aspects of the functions described below using special-purpose hardware.

(210) At **2505**, the base station may transmit, to a UE, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **2505** may be performed according to the methods described herein. In some examples, aspects of the operations of **2505** may be performed by a SCell activation manager as described with reference to FIGS. **15** through **18**.

(211) At **2510**, the base station may transmit, to the UE, one or more of DCI or a MAC-CE that includes information associated with the aperiodic reference signal, and where the one or more parameters for the aperiodic reference signal are indicated by the DCI, the MAC-CE, an implicit indication, or any combinations thereof. The operations of **2510** may be performed according to the methods described herein. In some examples, aspects of the operations of **2510** may be performed by a temporary reference signal manager as described with reference to FIGS. **15** through **18**.

(212) At **2515**, the base station may transmit the aperiodic reference signal to the UE based on the

identified one or more parameters for the aperiodic reference signal. The operations of **2515** may be performed according to the methods described herein. In some examples, aspects of the operations of **2515** may be performed by a temporary reference signal manager as described with reference to FIGS. **15** through **18**.

(213) FIG. **26** shows a flowchart illustrating a method **2600** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **2600** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **2600** may be performed by a communications manager as described with reference to FIGS. **15** through **18**. In some examples, a base station may execute a set of instructions to control the functional elements of the base station to perform the functions described below. Additionally, or alternatively, a base station may perform aspects of the functions described below using special-purpose hardware.

(214) At **2605**, the base station may transmit, to a UE, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **2605** may be performed according to the methods described herein. In some examples, aspects of the operations of **2605** may be performed by a SCell activation manager as described with reference to FIGS. **15** through **18**.

(215) At **2610**, the base station may transmit, to the UE, DCI that indicates one or more parameters for the aperiodic reference signal. The operations of **2610** may be performed according to the methods described herein. In some examples, aspects of the operations of **2610** may be performed by a configuration manager as described with reference to FIGS. **15** through **18**. In some cases, the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof.

(216) At **2615**, the base station may transmit the aperiodic reference signal to the UE based on the identified one or more parameters for the aperiodic reference signal. The operations of **2615** may be performed according to the methods described herein. In some examples, aspects of the operations of **2615** may be performed by a temporary reference signal manager as described with reference to FIGS. **15** through **18**.

(217) FIG. **27** shows a flowchart illustrating a method **2700** that supports reference signal configuration for SCell activation in accordance with aspects of the present disclosure. The operations of method **2700** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **2700** may be performed by a communications manager as described with reference to FIGS. **15** through **18**. In some examples, a base station may execute a set of instructions to control the functional elements of the base station to perform the functions described below. Additionally, or alternatively, a base station may perform aspects of the functions described below using special-purpose hardware.

(218) At **2705**, the base station may transmit, to a UE, a SCell activation message that indicates a SCell is to be activated at the UE in addition to a primary cell. The operations of **2705** may be performed according to the methods described herein. In some examples, aspects of the operations of **2705** may be performed by a SCell activation manager as described with reference to FIGS. **15** through **18**.

(219) At **2710**, the base station may transmit, to the UE, a MAC-CE that indicates one or more parameters for the aperiodic reference signal. The operations of **2710** may be performed according to the methods described herein. In some examples, aspects of the operations of **2710** may be performed by a temporary reference signal manager as described with reference to FIGS. **15** through **18**. In some cases, the one or more parameters include a carrier for the aperiodic reference signal, a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof.

(220) At **2715**, the base station may transmit the aperiodic reference signal to the UE based on the identified one or more parameters for the aperiodic reference signal. The operations of **2715** may be performed according to the methods described herein. In some examples, aspects of the operations of **2715** may be performed by a temporary reference signal manager as described with reference to FIGS. **15** through **18**.

(221) It should be noted that the methods described herein describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Further, aspects from two or more of the methods may be combined.

(222) Although aspects of an LTE, LTE-A, LTE-A Pro, or NR system may be described for purposes of example, and LTE, LTE-A, LTE-A Pro, or NR terminology may be used in much of the description, the techniques described herein are applicable beyond LTE, LTE-A, LTE-A Pro, or NR networks. For example, the described techniques may be applicable to various other wireless communications systems such as Ultra Mobile Broadband (UMB), Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM, as well as other systems and radio technologies, including future systems and radio technologies, not explicitly mentioned herein.

(223) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(224) The various illustrative blocks and components described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, a CPU, a GPU, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(225) The functions described herein may be implemented in hardware, software executed by a processor, or any combination thereof. Software shall be construed broadly to mean instructions, instruction sets, code, code segments, program code, programs, subprograms, software modules, applications, software applications, software packages, routines, subroutines, objects, executables, threads of execution, procedures, and/or functions, whether referred to as software, firmware, middleware, microcode, hardware description language, or otherwise. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described herein may be implemented using software executed by a processor, hardware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

(226) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that may be accessed by a general-purpose or special-purpose computer. By way of example, and not limitation, non-transitory computer-readable media may include RAM, ROM, electrically erasable programmable ROM (EEPROM), flash memory, compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory

medium that may be used to carry or store desired program code means in the form of instructions or data structures and that may be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of computer-readable medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers.

Combinations of the above are also included within the scope of computer-readable media.

(227) As used herein, including in the claims, “or” as used in a list of items (e.g., a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (e.g., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an example step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(228) In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label, or other subsequent reference label.

(229) The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “example” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

(230) The description herein is provided to enable a person having ordinary skill in the art to make or use the disclosure. Various modifications to the disclosure will be apparent to a person having ordinary skill in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein, but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. An apparatus for wireless communication at a user equipment (UE), comprising: one or more memories storing processor-executable code; and one or more processors coupled with the one or more memories and individually or collectively configured to execute the code to cause the UE to: receive, from a network device, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell; receive, based at least in part on the secondary cell activation message, a medium access control (MAC)-control element (CE) that indicates one or more parameters for an aperiodic reference signal for cell activation measurements, wherein a first field of the MAC-CE indicates a carrier for the aperiodic reference

signal and a second field of the MAC-CE indicates a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof; and measure one or more characteristics of the secondary cell based at least in part on the aperiodic reference signal.

2. The apparatus of claim 1, wherein the MAC-CE is a first MAC-CE that indicates the one or more parameters for the aperiodic reference signal, wherein the first MAC-CE is different from a second MAC-CE that provides the secondary cell activation message.

3. The apparatus of claim 2, wherein the first MAC-CE and the second MAC-CE are in a same downlink shared channel communication, or are in different downlink shared channel communications, from the network device.

4. The apparatus of claim 1, wherein the first field of the MAC-CE indicates the secondary cell that is to be activated and the second field of the MAC-CE indicates the one or more parameters for the aperiodic reference signal for the secondary cell that is to be activated.

5. The apparatus of claim 1, wherein the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a preconfigured downlink control information (DCI) format.

6. The apparatus of claim 5, wherein the preconfigured DCI format is configured by radio resource control (RRC) signaling.

7. The apparatus of claim 1, wherein the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a downlink control information (DCI) transmission in a DCI search space set that is configured by radio resource control (RRC) signaling.

8. An apparatus for wireless communication at a network device, comprising: one or more memories storing processor-executable code; and one or more processors coupled with the one or more memories and individually or collectively configured to execute the code to cause the network device to: transmit, to a user equipment (UE), a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell; transmit, based at least in part on the secondary cell activation message, a medium access control (MAC)-control element (CE) that indicates one or more parameters for an aperiodic reference signal for cell activation measurements, wherein a first field of the MAC-CE indicates a carrier for the aperiodic reference signal and a second field of the MAC-CE indicates a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof; and transmit the aperiodic reference signal to the UE based at least in part on the transmission of the MAC-CE.

9. The apparatus of claim 8, wherein the MAC-CE is a first MAC-CE that indicates the one or more parameters for the aperiodic reference signal, wherein the first MAC-CE is different from a second MAC-CE that provides the secondary cell activation message.

10. The apparatus of claim 9, wherein the first MAC-CE and the second MAC-CE are in a same downlink shared channel communication, or are in different downlink shared channel communications, from the network device.

11. The apparatus of claim 8, wherein the first field of the MAC-CE indicates the secondary cell that is to be activated and the second field of the MAC-CE indicates the one or more parameters for the aperiodic reference signal for the secondary cell that is to be activated.

12. The apparatus of claim 8, wherein the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a preconfigured downlink control information (DCI) format.

13. The apparatus of claim 12, wherein the preconfigured DCI format is configured by radio resource control (RRC) signaling.

14. The apparatus of claim 8, wherein the aperiodic reference signal is enabled if a shared channel communication carrying the MAC-CE is scheduled by a downlink control information (DCI)

transmission in a DCI search space set that is configured by radio resource control (RRC) signaling.

15. A method for wireless communication at a user equipment (UE), comprising: receiving, from a network device, a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell; receiving, based at least in part on the secondary cell activation message, a medium access control (MAC)-control element (CE) that indicates one or more parameters for an aperiodic reference signal for cell activation measurements, wherein a first field of the MAC-CE indicates a carrier for the aperiodic reference signal and a second field of the MAC-CE indicates a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof; and measuring one or more characteristics of the secondary cell based at least in part on the aperiodic reference signal.

16. A method for wireless communication at a network device, comprising: transmitting, to a user equipment (UE), a secondary cell activation message that indicates a secondary cell is to be activated at the UE in addition to a primary cell; transmitting, based at least in part on the secondary cell activation message, a medium access control (MAC)-control element (CE) that indicates one or more parameters for an aperiodic reference signal for cell activation measurements, wherein a first field of the MAC-CE indicates a carrier for the aperiodic reference signal and a second field of the MAC-CE indicates a slot location of the aperiodic reference signal, a reference signal configuration of the aperiodic reference signal, a beam configuration for the aperiodic reference signal, or any combinations thereof; and transmitting the aperiodic reference signal to the UE based at least in part on the transmission of the MAC-CE.
