



US 20250264781A1

(19) **United States**
(12) **Patent Application Publication** (10) **Pub. No.: US 2025/0264781 A1**
Shabtay et al. (43) **Pub. Date: Aug. 21, 2025**

(54) **POP-OUT ZOOM CAMERA** *G02B 15/14* (2006.01)
(71) Applicant: **Corephotonics Ltd.**, Tel Aviv (IL) *G03B 5/02* (2021.01)
(72) Inventors: **Gal Shabtay**, Tel Aviv (IL); **Ephraim Goldenberg**, Tel Aviv (IL); **Itay Yedid**, Tel Aviv (IL); **Roy Rudnick**, Tel Aviv (IL); **Michael Dror**, Tel Aviv (IL); **Michael Scherer**, Tel Aviv (IL); **Ziv Shemesh**, Tel Aviv (IL); **Nadav Goulinski**, Tel Aviv (IL) *G03B 13/36* (2021.01)
(21) Appl. No.: **19/178,909** *G03B 30/00* (2021.01)
(22) Filed: **Apr. 15, 2025** *H04N 23/68* (2023.01)
(52) **U.S. Cl.**
CPC *G03B 17/04* (2013.01); *G02B 13/009* (2013.01); *G02B 15/142* (2019.08); *G03B 5/02* (2013.01); *G03B 13/36* (2013.01); *G03B 30/00* (2021.01); *H04N 23/687* (2023.01); *G02B 13/0045* (2013.01); *G03B 2205/0046* (2013.01)

Related U.S. Application Data

(63) Continuation of application No. 18/808,132, filed on Aug. 19, 2024, now Pat. No. 12,298,651, which is a continuation of application No. 18/607,844, filed on Mar. 18, 2024, now Pat. No. 12,111,561, which is a continuation of application No. 17/915,148, filed on Sep. 28, 2022, filed as application No. PCT/IB2021/057311 on Aug. 9, 2021, now Pat. No. 11,966,147.
(60) Provisional application No. 63/173,446, filed on Apr. 11, 2021, provisional application No. 63/080,047, filed on Sep. 18, 2020.


Publication Classification

(51) **Int. Cl.**
G03B 17/04 (2021.01)
G02B 13/00 (2006.01)

(57) **ABSTRACT**

Cameras with OIS capable of performing multi zoom super macro photography and handheld electronic devices comprising such cameras. A camera may include a lens comprising N lens elements L_1 - L_N divided into two or more lens groups arranged along a lens optical axis starting with L_1 on an object side and ending with L_N on an image side, adjacent lens groups separated by a respective air-gap d_i along the lens optical axis; an image sensor with a sensor diagonal S_D between 7 and 20 mm separated from lens element L_N by an air-gap d_2 along the lens optical axis; and an actuator for controlling air-gaps d_1 and d_2 to switch the camera between $M \geq 1$ operative pop-out states and a collapsed state and to focus the camera on an object at an object-lens distance of less than 30 cm.

850






FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 2A






FIG. 2B






FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B

5cm

5 mm




FIG. 12A




FIG. 12B

5 mm




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17B




FIG. 18A




FIG. 18B




FIG. 19A




FIG. 19B




FIG. 20A




FIG. 20B




FIG. 21A




FIG. 21B

POP-OUT ZOOM CAMERA

CROSS REFERENCE TO EXISTING APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 18/808,132 filed Aug. 19, 2024 (now allowed), which was a continuation application of U.S. patent application Ser. No. 18/607,844 filed Mar. 18, 2024 (issued as U.S. Pat. No. 12,111,561), which was a continuation application of U.S. patent application Ser. No. 17/915,148 filed Sep. 28, 2022 (issued as U.S. Pat. No. 11,966,147), which was a 371 application from international patent application PCT/IB2021/057311 filed Aug. 9, 2021, which claims priority from U.S. Provisional Patent Applications No. 63/080,047 filed Sep. 18, 2020 and 63/173,446 filed Apr. 11, 2021, which are incorporated herein by reference in their entirety.

FIELD

[0002] The presently disclosed subject matter is generally related to the field of digital cameras, and in particular to zoom compact multi-aperture cameras.

BACKGROUND

[0003] Compact multi-cameras and their incorporation in handheld electronic devices (also referred to herein as “devices”) such as tablets and mobile phones (the latter referred to hereinafter generically as “smartphones”) are known. These cameras provide advanced imaging capabilities such as zoom, see e.g. co-owned PCT patent application No. PCT/IB2063/060356. A typical triple-camera system exemplarily includes an ultra-wide-angle (or “Ultra-Wide” or “UW”) camera, wide-angle (or “Wide” or “W”) camera and a telephoto (or “Tele” or “T”) camera, wherein their fields of view (FOVs) fulfill $FOV_{UW} > FOV_W > FOV_T$.

[0004] First smartphone models that provide Macro-photography capabilities by enabling very close focusing with a UW camera, which has a relatively short focal length (e.g. 2.5 mm), have entered the consumer market. Drawbacks of UW Macro cameras include a need for small object-lens distances (“u”), and small object-to-image magnifications (“M”). For example, when a 2.5 mm UW lens is focused to an object at 5 cm (lens-object distance), the UW camera will have object-to-image a M of about 19:1.

[0005] Challenges with zoom cameras relates to camera height or length (correlated e.g. with a total track length or “TTL”), to the effective focal length (EFL) and to the size of the image sensor of camera (“Sensor Diagonal” or “SD”). FIG. 1A illustrates schematically the definition of various entities such as TTL, EFL and back focal length (“BFL”). TTL is defined as the maximal distance between the object-side surface of a first lens element facing the object and a camera image sensor plane. BFL is defined as the minimal distance between the image-side surface of a last lens element facing the image sensor and a camera image sensor plane.

[0006] FIG. 1B shows an exemplary camera system having a lens with a FOV, an EFL, and an image sensor with a sensor width W and height H. SD connects to a sensor width W and a height H via $SD = \sqrt{W^2 + H^2}$. For fixed width/height ratios of a (normally rectangular) image sensor, the sensor

diagonal is proportional to the sensor width and height. The diagonal field of view (FOV) relates to EFL and SD as follows:

$$\tan\left(\frac{FOV}{2}\right) = SD/2/EFL \quad (\text{Eq. 1})$$

This shows that a camera with a larger SD but same FOV requires a larger EFL.

[0007] A Tele camera enables optical zoom. The TTL of a Tele lens is smaller than its EFL, typically satisfying $0.7 < TTL/EFL < 1.0$. Typical Tele EFL values in vertical Tele cameras range from 6 mm to 10 mm (without applying 35 mm equivalence conversion). In folded Tele cameras, they range and from 10 mm to 40 mm. Larger EFL is desirable for enhancing the optical zoom effect, but this results in larger TTL, which is undesirable.

[0008] In a continuous attempt to improve the obtained image quality, there is a need to incorporate larger image sensors into Tele cameras. Larger sensors allow for improved low-light performance and larger number of pixels, hence improving spatial resolution as well. Other image quality characteristics, such as noise characteristics, dynamic range and color fidelity may also improve as the sensor size increases. In most Tele cameras, the SD of the sensor pixel array ranges from about 4.5 mm (typically referred to as 1/4" sensor) to 7 mm (typically referred to 1/2.5" sensor).

[0009] It would be beneficial to have a Tele camera design which both supports large EFL for

[0010] large optical zoom effect;

[0011] incorporation of large sensors (e.g. $SD > 10$ mm or 1/1.7" sensor);

[0012] large M (e.g. 2:1-10:1) at lens-object distances of 5-15 cm,

while still having small TTL for slim design. This can be achieved by a “pop-out camera”, i.e. a camera having two or more lens states. In a first (“pop-out”) lens state the camera is operative and has a large height H_O . A second lens state is a collapsed lens state where the camera is not operative and has a height $H_{N-O} < H_O$. Such design is presented for example in co-owned international patent application No. PCT/IB2020/058697.

[0013] Modern multi-cameras usually further include optical image stabilization (OIS). OIS is required to mitigate undesired camera host device motion (“hand motion” or “hand-shake”). For OIS, the lens or the image sensor or the entire camera can be linearly moved in two directions that are perpendicular to the camera’s optical axis (see FIG. 14A).

[0014] Undesired host device motions shift the camera in 6 degrees of freedom, namely linear movements in X-Y-Z (coordinates given with reference to the coordinate system shown in FIG. 6A), roll (“tilt about” or “tilt around”) the Y axis, yaw (tilt around the Y axis) and pitch (tilt around the X axis), wherein mainly yaw and pitch are accountable for significant image deterioration. As undesired linear motion in X-Y-Z affects the image quality only negligibly for lens-object distances of 1 m or more, most known premium smartphones include OIS that corrects for yaw and pitch only. In contrast, for Macro photography with a Tele camera allowing for large M of 10:1 or larger, undesired linear motion in X-Y may significantly affect the image quality. It

would thus be beneficial to have an OIS mechanism that corrects for undesired linear motion during Macro capture.

SUMMARY

[0015] In various embodiments, there are provided cameras, comprising: a lens comprising N lens elements L_1 - L_N arranged along a lens optical axis starting with L_1 on an object side and ending with L_N on an image side, wherein N is ≥ 5 , wherein the lens elements are divided into two or more lens groups and wherein two adjacent lens groups are separated by a respective air-gap d_1 along the lens optical axis; an image sensor separated from lens element L_N by an air-gap d_2 along the lens optical axis, image sensor having a sensor diagonal S_D between 7 and 20 mm; and an actuator for controlling air-gaps d_1 and d_2 to switch the camera between $M \geq 1$ operative pop-out states and a collapsed state and to focus the camera on an object at an object-lens distance of less than 30 cm, wherein in each operative pop-out state $m \in \{1, 2, \dots, M\}$ the lens has a respective effective focal length EFL_m and a total track length TTL_m , wherein in the collapsed state the lens has a total track length c-TTL, wherein a minimal EFL in the set of m EFLs is equal to or greater than 7 mm, wherein c-TTL < 0.7 EFL.

[0016] In some embodiments, $M=2$ or 3 or 4.

[0017] In some embodiments, the operative state is continuous such that the EFL changes continuously from EFL_1 to EFL_M .

[0018] In some embodiments, for a minimal EFL in the set of m EFLs, c-TTL < 0.65 EFL.

[0019] In some embodiments, a camera can focus the lens to an object at a distance of less than 25 cm.

[0020] In some embodiments, a camera can focus the lens to an object at a distance of less than 15 cm.

[0021] In some embodiments, the actuator comprises a spring.

[0022] In some embodiments, d_1 is larger than $TTL_M/6$.

[0023] In some embodiments, d_1 is larger than $TTL_M/5$.

[0024] In various embodiments, there are provided camera systems comprising a camera as above or below (referred to now as “first camera”) together with a second camera comprising a second lens system having at least one air-gap, wherein in the collapsed state the second lens has a total track length c-TTL₂, wherein the actuator is operative to control the at least one air-gap of the second camera for simultaneously switching the first camera and the second camera between $M \geq 1$ operative pop-out states and a collapsed state. In some embodiments, cTTL₂=CTTL $\pm 10\%$. The cameras or a camera system as above or below may be incorporated in a handheld electronic device. The handheld electronic device may have a device exterior surface, wherein in an operative state any of the cameras extends beyond the device exterior surface by 2 mm-10 mm and in a non-operative state any of the cameras of any of the claims **1-11** and **13** extends beyond the device exterior surface by less than 2 mm.

[0025] In various embodiments, there are provided handheld electronic devices, comprising: a Tele camera having a camera optical axis and comprising an image sensor and a lens having a lens axis substantially parallel to the camera optical axis, the Tele camera having an $EFL \geq 9$ mm; a motion sensor for sensing an undesired linear motion of the handheld electronic device; a depth estimator for estimating the distance between the Tele camera and an object; and an actuator for moving the Tele camera or a component of the

Tele camera to compensate for the handheld electronic device's undesired linear motion, wherein the compensation depends on the handheld electronic device's undesired linear motion and on the distance between the Tele camera and an object, wherein the distance between the Tele camera and the object is smaller than 50 cm.

[0026] In some embodiments, a handheld device further comprises an Ultra-Wide camera having a field of view FOV_{UW} larger than a field of view FOV_T of the Tele camera.

[0027] In some embodiments, a handheld device further comprises a Wide camera having a field of view FOV_W larger than a field of view FOV_T of the Tele camera.

[0028] In some embodiments, the estimating the distance between the Tele camera and an object is based on Phase detection auto focus (PDAF).

[0029] In some embodiments, the estimating the distance between the Tele camera and an object is based on the Wide camera and the Tele camera or based on the Ultra-Wide camera and the Tele camera.

[0030] In some embodiments, the sensing the linear motion includes measuring the linear motion in one or more directions.

[0031] In some embodiments, the sensing the linear motion includes measuring the linear motion in two or more directions.

[0032] In some embodiments, the moving component is the lens. An amount of lens movement d_{Lens} is calculated

$$d_{Lens} = d_0 \frac{EFL}{u},$$

as wherein d_0 is an undesired linear motion of device, EFL is the effective focal length and u is an object-lens distance.

[0033] In some embodiments, the moving component is the image sensor. An amount of image sensor movement d_{sensor} is calculated as

$$d_{sensor} = d_0 \frac{EFL}{u - EFL}$$

wherein d_0 is an undesired linear motion of device and u is an object-lens distance.

[0034] In some embodiments, the motion sensor includes an inertial measurement unit (IMU).

BRIEF DESCRIPTION OF THE DRAWINGS

[0035] Non-limiting embodiments of the presently disclosed subject matter are described below with reference to figures attached hereto that are listed following this paragraph. Identical structures, elements or parts that appear in more than one figure may be labeled with the same numeral in the figures in which they appear. The drawings and descriptions are meant to illuminate and clarify embodiments disclosed herein, and should not be considered limiting in any way.

[0036] FIG. 1A illustrates schematically the definition of various entities in a camera;

[0037] FIG. 1B illustrates schematically an exemplary camera system having a lens with a FOV, an EFL and an image sensor with a sensor width W;

[0038] FIG. 1C shows schematically in cross-section an exemplary Tele camera lens system disclosed herein in a collapsed, non-operative state;

[0039] FIG. 1D shows the camera of FIG. 1C in a first operative Tele lens state;

[0040] FIG. 1E shows the camera of FIG. 1C in a second operative Tele lens state;

[0041] FIG. 1F shows the camera of FIG. 1C in an operative Macro lens state;

[0042] FIG. 2A shows a cross-sectional view of a of a pop-out Tele camera disclosed herein in an extended state and incorporated in a camera hosting handheld electronic device;

[0043] FIG. 2B shows a cross-sectional view of pop-out mechanism of the camera of FIG. 2A in a pop-out state;

[0044] FIG. 3A shows the pop-out camera of FIG. 2A in a collapsed or non-operative state;

[0045] FIG. 3B shows the pop-out mechanism in the camera of FIG. 3A in the respective collapsed state;

[0046] FIG. 4A shows in cross-sectional view an optics module in a pop-out state;

[0047] FIG. 4B shows the optics module of FIG. 4A in a collapsed state with a collapsed c-TTL;

[0048] FIG. 4C shows schematically in cross-sectional view a lens system in a pop-out state;

[0049] FIG. 4D shows schematically in cross-sectional view the lens system of FIG. 4C in a first collapsed state;

[0050] FIG. 5A shows in cross-sectional another optics module in a pop-out state;

[0051] FIG. 5B shows the optics module of FIG. 5A in a collapsed state;

[0052] FIG. 5C shows schematically in cross-sectional view another lens system in a collapsed state;

[0053] FIGS. 5D and 5E show an embodiment of yet another lens system that switches between a pop-out state and a collapsed state;

[0054] FIG. 6A shows an embodiment of a handheld electronic device with a camera system comprising an upright Wide camera and a pop-out Tele camera in a pop-out state;

[0055] FIG. 6B shows the device of FIG. 6A with the pop-out Tele camera in a collapsed state;

[0056] FIG. 7A shows another embodiment of a handheld electronic device with a camera system comprising an upright Wide camera and a pop-out Tele camera in a pop-out state;

[0057] FIG. 7B shows the device of FIG. 7A with the pop-out Tele camera in a collapsed state;

[0058] FIG. 8A shows an embodiment of a lens system disclosed herein;

[0059] FIG. 8B shows an embodiment of another lens system disclosed herein;

[0060] FIG. 9 shows yet another lens system disclosed herein in a pop-out lens state;

[0061] FIG. 10 shows yet another lens system disclosed herein in a pop-out lens state;

[0062] FIG. 11A shows yet another lens system disclosed herein in a first pop-out lens state;

[0063] FIG. 11B shows the lens system of FIG. 11A in a second, Macro pop-out lens state;

[0064] FIG. 12A shows yet another lens system disclosed herein in a first pop-out lens state;

[0065] FIG. 12B shows the lens system of FIG. 12A in a second, Macro pop-out lens state;

[0066] FIG. 13A shows yet another lens system disclosed herein in a first pop-out lens state;

[0067] FIG. 13B shows the lens system of FIG. 13A in a second, Macro pop-out lens state;

[0068] FIG. 14A shows a known sensor shift setup;

[0069] FIG. 14B shows a sensor shift setup disclosed herein;

[0070] FIG. 15A shows an exemplary optical system at an initial time, e.g. when starting image sensor exposure for image capture;

[0071] FIG. 15B shows the optical system of FIG. 15A at a later time during exposure of its image sensor for image capture and after the camera hosting handheld device underwent an undesired linear motion in the negative Y direction by a distance Δy relative to an object at rest;

[0072] FIG. 16A shows schematically in a block diagram a handheld electronic device operative to perform OIS for correcting undesired linear motion in X and Y directions as described herein;

[0073] FIG. 16B shows schematically in a block diagram another handheld electronic device operative to perform OIS for correcting undesired linear motion in X and Y directions as described herein;

[0074] FIG. 17A shows an example of a pop-out optical lens system disclosed herein in a pop-out state;

[0075] FIG. 17B shows the pop-out optical lens system of FIG. 17A in a collapsed state;

[0076] FIG. 18A shows another embodiment of a pop-out optical lens system disclosed herein in a pop-out state;

[0077] FIG. 18B shows the pop-out optical lens system of FIG. 18A in a collapsed state;

[0078] FIG. 19A shows yet another embodiment of a pop-out optical lens system disclosed herein in a pop-out state;

[0079] FIG. 19B shows the pop-out optical lens system of FIG. 19A in a collapsed state;

[0080] FIG. 20A shows yet another embodiment of a pop-out optical lens system disclosed herein in a pop-out state;

[0081] FIG. 20B shows the pop-out optical lens system of FIG. 20A in a collapsed state;

[0082] FIG. 21A shows yet another embodiment of a pop-out optical lens system disclosed herein in a pop-out state;

[0083] FIG. 21B shows the pop-out optical lens system of FIG. 21A in a collapsed state.

DETAILED DESCRIPTION

[0084] FIGS. 1C-F show schematically an embodiment of a Tele camera lens system (or simply “lens system”) numbered **100** disclosed herein in a cross-sectional view. FIG. 1C shows lens system **100** in a collapsed, non-operative state. FIG. 1D shows lens system **100** in a first operative Tele lens state (or “Tele state”). FIG. 1E shows lens system **100** in a second operative Tele state. FIG. 1F shows lens system **100** in an operative Macro lens state (or “Macro state”). Lens system **100** comprises a lens (with lens elements), an optional optical window, and an image sensor.

[0085] Lens system **100** may be included in a pop-out Tele camera such as camera **200**, an optics module such as an optics module **240** (see FIGS. 4A-B) or **500** (see FIG. 5A-B) wherein the optics module may be included in a pop-out mechanism such as pop-out mechanism **210** (see FIG. 2A-B, FIG. 3A-B and FIG. 4A-B) to form a pop-out camera. If not

stated otherwise, a “Tele state” refers to a state in which the lens system that can focus to objects in the range from infinity to about 50 cm, while a “Macro state” refers to a state in which the lens system that can focus to objects in the range from about 50 cm to about 5 cm or less. Tele states enable Tele photography, while Macro states enable Macro photography.

[0086] Henceforth and for simplicity, the use of the term “pop-out” before various components may be skipped, with the understanding that if defined the first time as being a “pop-out” component, that component is such throughout this description.

[0087] Lens system **100** comprises two groups of lens elements, Group 1 (G1) and Group 2 (G2). G1 and G2 are movable along a common optical axis to occupy different positions that correspond to different Tele states. In some embodiments, two or three or four or five particular lens states may be supported, e.g. the four lens states shown in FIGS. 1C-E. A folded lens divided into several lens groups for realization of various lens states is described for example in PCT/IB2020/051405. FIGS. 1C-E show also the meaning of TTL, a first collapsed back focal length c-BFL, a BFL of the 1st operative Tele state (“second” back focal length) BFL₁, a third back focal length BFL₂ and a fourth back focal length BFL₃.

[0088] The pop-out design allows for a slim lens when the camera is not in use. When the camera is in use (“activated”), the lens pops out of an exterior device surface into an operative state, acting as an optical system that produces a crisp image on an image sensor. Each lens group comprises lens elements that have fixed distances to each other, but an air gap d_{G1-G2} between G1 and G2 may change between the different lens states. G1 and G2 can be moved relative to each other by an actuator such as actuator **212** see below. The actuator may move G1 and G2 by e.g. 0.05-8.5 mm with respect to each other (e.g. for modifying an air-gap such as d_{G1-G2}) or it may move G1 and G2 together relative to the image sensor for switching from one lens state to another lens state, e.g. from a Tele state to a Macro state

[0089] In some embodiments, the transition between different lens focus distances may be continuous, e.g. the pop-out camera may be capable of focusing from infinity to e.g. 5 cm continuously. In other embodiments, the transition may be discrete with ranges for continuous focusing. For example, in a Tele state, the pop-out camera may be capable of focusing continuously to object-lens distances (“u”) from infinity to e.g. 1 m, and in a Macro state the pop-out camera may be capable of focusing continuously to u from e.g. 40 cm to 5 cm. The F number (f/#) may undergo only slight changes when transitioning between the different lens states, e.g. by less than 5%, or less than 10%, or less than 30% with respect to, respectively, a lens state at infinity, at 10 cm, or at 5 cm. In yet other embodiments, only two different lens states may be provided, e.g. one collapsed lens state and one Tele lens state. The Tele lens state may be switched to a Macro lens state by changing only the BFL, i.e. by moving all lens elements.

[0090] FIG. 1C shows lens system **100** in a collapsed state. Here, a collapsed TTL (“c-TTL”) of the lens may be 4-13 mm, a collapsed BFL (“c-BFL”) may be 0.15-4 mm and a collapsed air gap “c- d_{G1-G2} ” may be 0.02-2.5 mm. In the collapsed state, the camera is not functional, i.e. the optics cannot project a scene as a crisp image onto the image sensor.

[0091] As an example (“SD-Example”) for TTL and SD, in the following we apply Eq. 1 to a Tele camera with FOV=30 degrees. We assume EFL=TTL and that an image sensor may be in a 4:3 width/height format, so that sensor width $W \sim 0.8SD$.

[0092] FIG. 1D shows lens system **100** in a first extended (or “operative” or “pop-out”) state having a first zoom factor ZF1. The lens acts as a Tele lens. Here, a first extended state TTL (TTL₁) may be 5-13 mm, a first extended state BFL (BFL₁) may be 0.25-5 mm and a first extended air gap d_{G1-G2}^1 may be 0.15-3 mm. For SD-Example with a TTL₁=12 mm, SD=8.1 mm.

[0093] FIG. 1E shows lens system **100** in a second lens state having a second zoom factor ZF2>ZF1. The lens acts as a Tele lens. Here, TTL₂ may be 6-17 mm, BFL₂ may be 0.45-6 mm and d_{G1-G2}^2 may be 0.25-5 mm. For SD-Example with a TTL₂=14 mm, SD=9.5 mm.

[0094] FIG. 1F shows lens system **100** in a third lens state having a third zoom factor ZF3>ZF2. In this state, the lens acts as a Tele lens and a Macro lens. A magnification M for Macro photography at camera-object distances of <15 cm may be 15:1-2:1. TTL₃ may be 7-20 mm, the BFL₃ may be 0.5-8 mm and d_{G1-G2}^3 may be 0.35-8 mm. For SD-Example with a TTL₃=19 mm, SD=13 mm (corresponding to a 1/1.3” sensor).

[0095] For embodiments that support a continuous lens state change, there may be continuous transitions between the lens states shown in FIGS. 1C-F. In some embodiments, G1 may include the majority of optical power Φ of the entire lens and G2 may correct for Field curvature. The “majority of optical power” refers to more than a factor of 2 between the optical power of G1 and G2, i.e. $\Phi_{G1} > 2 \cdot \Phi_{G2}$, wherein $\Phi = 1/EFL$.

[0096] FIG. 2A shows in cross-sectional view an embodiment numbered **200** of a pop-out Tele camera disclosed herein in an extended state and incorporated in a device **250**. Camera **200** comprises a pop-out optics module **240** that includes a pop-out lens **206**. Camera **200** further comprises an image sensor **208** and a pop-out mechanism **210** that includes an actuator **212** and a window frame **214** carrying a window **216**. The window covers an aperture **218** of pop-out Tele camera **200**. Optics module **240** is covered by a cover **232**.

[0097] An entrance pupil (or “aperture size”) of camera **200** may be for example 4-9 mm. For comparison, a folded Tele camera usually has an entrance pupil smaller than 4.5 mm, while a dedicated Macro camera usually has an entrance pupil smaller than 1 mm. Assuming pop-out Tele camera **200** has an aperture size of 7 mm vs. a size of 4 mm for the folded Tele camera, camera **200** will receive about 3 times more light, corresponding to a better low light signal-to-noise ratio (“SNR”). In comparison with the dedicated Macro camera with a 1 mm aperture size, camera **200** will have a 6-fold larger EFL, and a ~40 times shallower Depth of Field (DOF), translating into a ~40 times stronger optical Bokeh effect.

[0098] The lens, image sensor and (optionally) an optical window or “filter” (not shown here but shown e.g. in lens systems **800, 850, 900, 1000, 1100, 1200, 1300, 1700, 1800, 1900, 2000, 2100**) form a pop-out lens system **260**. The camera may have a Tele FOV_T of 15-50 deg.

[0099] The TTL of the lens in a pop-out Tele camera disclosed herein may be 5-35 mm. The image sensor may have a sensor diagonal SD in the range 3.5-25 mm and EFL of 6 mm to 45 mm.

[0100] FIG. 2B shows a cross-sectional view of an embodiment of pop-out mechanism 210 in a pop-out state. Pop-out mechanism 210 is essentially camera 200 without optics module 240. Camera 200 has also a collapsed (“c” or “non-operative”) state, shown in FIGS. 3A-B. FIG. 3A shows a cross-sectional view of camera 200 in the collapsed state. FIG. 3B shows a cross-sectional view of pop-out mechanism 210 in the respective collapsed state. Camera 200 switches between a pop-out state and a collapsed state according to a first method, where the gap d_{G1-G2} between G1 and G2 collapses. The BFL does not change. Lens system 800 switches according to the first method.

[0101] Pop-out optics module 240 and window frame 214 form an air-gap (or simply “gap”) 222 between lens 206 and window 216, which gap may be for example 0.15-1.2 mm. Air-gap 222 allows for a combined movement of about 0.1-1.1 mm of a first lens barrel section 202 and a second lens barrel section 204 by for performing auto-focus (AF) and OIS by moving the lens. First lens barrel section 202 includes G1. Second lens barrel section 204 includes G2. In other embodiments, air-gap 222 may be significantly larger, e.g. 6 mm. A module seal 224 prevents particles and fluids from entering the camera.

[0102] Camera 200 exceeds an exterior surface 252 of host device 250 by a significant pop-out bump height H_{P-O-B} 226. “Significant” may be for example 1.0 mm-15.0 mm. In the extended state, camera 200 increases the height of host device 250 to a “height in a pop-out state” H_{P-O} (not shown). H_{P-O} is given by adding H_{P-O-B} 226 to a device height H_O that does not include the bump, see e.g. H_0 606, $H_{P-O} = H_0 + H_{P-O-B}$. In FIG. 2A, a single spring 230 pushes first lens barrel section 202 towards window frame 214. In other embodiments, the single spring may be replaced by a plurality of springs. In the pop-out state, the spring is in an extended state (characterized by an increased gap between G1 and G2), see also FIG. 4A. A guiding pin 236 and a guiding pin 238 guide movements of first lens barrel section 202.

[0103] In general, lens 206 includes $N \geq 5$ lens elements. In some embodiments, there may be more than two lens barrel sections with one lens groups each. For example, there may be 3, 4, 5 lens barrel sections, with each lens barrel section carrying a lens group. Examples of lens systems with two lens groups are lens systems 206-1, 206-2, 206-3, 206-4, 206-6, 206-7, 206-8, 206-9, 206-10 and 206-11 shown in FIGS. 8-13 and FIGS. 17-20. Examples with lens systems with three lens groups are lens systems 206-5 and 206-12 shown in FIG. 12B and in FIG. 21A-B respectively. The lens barrel sections may be divided into fixed lens barrel sections and movable lens barrel sections. In lens 206, G1 may include lens elements $L1-L_{N-1}$ and G2 includes lens element L_N . Air-gaps of changing thickness d may be formed between lens groups according to their relative movement. In examples with more than two lens barrel sections, some or all lens barrel sections may be movable and have respective air-gaps formed between the lens groups. In some examples, all air-gaps between lens groups may collapse in a non-operative camera state. In other examples, only some

but not all of the air-gaps between lens groups may collapse in a non-operative state. The total length of such air-gaps may be 1-9.5 mm.

[0104] Lens groups may be determined by the largest air-gaps between consecutive lens elements. For example, the largest air-gap present between two consecutive lens elements may be used to divide a lens into two lens groups, the largest air-gap and the second largest air-gap present between two consecutive lens elements may be used to define three lens groups, etc. In some examples, collapsible air-gaps are formed between two consecutive lens elements. In other examples, the collapsible air-gaps are formed between a lens element and another optical component, e.g. between a lens element and an optical filter, or between a lens element and an image sensor (i.e. the air-gap is the BFL).

[0105] For examples that support two or three or four particular lens states, there may be two or three or four particular values for air-gaps. For other embodiments that support a continuous change of lens states, values for air-gaps may change continuously.

[0106] In the extended state and with reference to FIG. 2A, air-gap d_{G1-G2} may be 1-9 mm. Guiding pins 236 and 238 may guide the movement of first barrel section 202 and G1 in the X-Z plane for providing mechanical stability and repeatability in X-Z plane.

[0107] In some embodiments, a guiding and positioning mechanism such as described in PCT/IB2020/058697 may be based on a kinematic coupling mechanism.

[0108] An optical system such as camera 200 may be designed to support, e.g. by means of a guiding and positioning mechanism based on kinematic coupling mechanism, in some examples, accuracy tolerances for decenter of e.g. $\pm 20 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 10 \mu\text{m}$ in the Y direction, as well as for a tilt of $\pm 0.5^\circ$. Repeatability tolerances for decenter may be e.g. $\pm 10 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 5 \mu\text{m}$ in the Y direction, as well as for a tilt of $\pm 0.25^\circ$. In other examples, accuracy tolerances for decenter may be e.g. $\pm 10 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 5 \mu\text{m}$ in the Y direction, as well as e.g. $\pm 0.15^\circ$. Repeatability tolerances for decenter may be e.g. $\pm 5 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 2.5 \mu\text{m}$ in the Y direction, as well as for a tilt of $\pm 0.08^\circ$. In yet other examples, accuracy tolerances for decenter may be e.g. $\pm 5 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 2.5 \mu\text{m}$ in the Y direction, as well as e.g. $\pm 0.1^\circ$. Repeatability tolerances for decenter may be e.g. $\pm 1.5 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 0.8 \mu\text{m}$ in the Y direction, as well as for a tilt of $\pm 0.05^\circ$.

[0109] “Accuracy tolerances” refer here to a maximum variation of the distances between optical elements and between mechanical elements. “Repeatability tolerances” refer here to a maximum variation of the distances between optical elements and between mechanical elements in different pop-out cycles, i.e. the capability of the mechanical and optical elements to return to their prior positions after one or many pop-out (or collapse) events. Tolerances in the Y direction may be less important, as variations in Y can be compensated by optical feedback and moving the lens for auto-focus.

[0110] FIG. 3A shows pop-out camera 200 in a collapsed or non-operative state. To switch optics module 240 to the collapsed state, actuator 212 decreases air-gap d_{G1-G2} by moving window frame 214 to apply pressure to first (and here collapsible) lens barrel section 202 that translates into a movement of the collapsible lens barrel section towards

the image sensor. The TTL of the camera is now a collapsed TTL (c-TTL) and may be 4.5-12 mm. A “collapsed air-gap” $c\text{-}d_{G1-G2}$ may be 0.05-2.5 mm. Examples of lens systems for a pop-out camera with a collapsible air gap d_{G1-G2} and a non-collapsible BFL include lens systems **800**, **1200** and **1300**.

[0111] In FIG. 3A, camera **200** forms a collapsed bump (c-bump) height H_{C-B} **228** with respect to device exterior surface **252**. H_{C-B} may be 0-3 mm. In the collapsed state, the camera increases the height of host device **250** to a “height in the collapsed state” $H_C=H_0+H_{C-B}$.

[0112] A plurality of lens states such as shown in FIGS. 1C-F may be achieved by modifying air-gaps such as e.g. d_{G1-G2} . In other examples, a pop-out mechanism may have more than 2 lens states, e.g. 3 states or 4 states. The 3 lens states may include one collapsed state and two pop-out (operative) states having 2 different or identical pop-out bump heights. The 4 lens states may include one collapsed state and three pop-out (operative) states having 3 different or identical pop-out bump heights.

[0113] FIG. 4A shows in cross-sectional view optics module **240** in a pop-out state. FIG. 4B shows in cross-sectional view optics module **240** in a collapsed state with a collapsed c-TTL. The BFL does not change when switching from the pop-out to the collapsed state. Camera **240** switches between a pop-out state and a collapsed state according to the first method. FIG. 4C shows schematically in cross-sectional view a lens system **400** in a pop-out state. System **200** comprises a pop-out lens **206** and an image sensor **208**. Lens **206** includes two lens groups (G1 and G2 respectively) separated by a big gap (BG). The thickness (along an optical axis of the lens) of G1 and G2 is indicated by T_{G1} and T_{G2} respectively. FIG. 4D shows schematically in cross-sectional view lens system **400** in a first collapsed state. Camera **400** switches between a pop-out state and a collapsed state according to a second method, where the BFL collapses to a c-BFL, but the gap between G1 and G2 does not change. Lens systems **850**, **900**, **1000**, **1700** and **1800** switch between a pop-out state and a collapsed state according to the second method.

[0114] FIG. 5A shows in cross-sectional view optics module **500** in a pop-out state. FIG. 5B shows in cross-sectional view optics module **500** in a collapsed state. To form a pop-out camera, optics module **500** may be integrated into a pop-out mechanism such as **210** (not shown here) having a window **216** covering an aperture **518**. In the collapsed state, $c\text{-}d_{G1-G2}$ may be 0.05-1.5 mm and c-BFL may be 0.05-2.5 mm. Here, the BFL does change when switching from the pop-out to the collapsed state. The difference between c-TTL and TTL stems from two modified distances: a modified distance between G1 and G2, given by the difference of d_{G1-G2} and $c\text{-}d_{G1-G2}$, and a modified distance between G2 and image sensor **208**, given by the difference between BFL and c-BFL. Camera **500** switches between a pop-out state and a collapsed state according to a third method, where a gap between two lens groups collapses and additionally the BFL collapses. Lens systems **850**, **900**, **1000**, **1900** and **2000** switch between a pop-out state and a collapsed state according to the third method.

[0115] FIG. 5C shows schematically in cross-sectional view another lens system **510** in a collapsed state. In a pop-out state, camera **510** is identical with camera **400**. Camera **510** switches between a pop-out state and a collapsed state according to the third method.

[0116] FIGS. 5D-5E show an embodiment of a lens system **550** disclosed herein which switches between a pop-out state and a collapsed state according to a fourth method, where two gaps between three lens groups collapse. System **550** comprises a pop-out lens **552** and an image sensor **554**. FIG. 5D shows system **550** in a pop-out state. Lens **552** includes two lens groups G1 and G2 separated by a first big gap (BG1), and a field lens separated from G2 by a second big gap (BG2).

[0117] FIG. 5E shows lens system **550** in a collapsed state. BG1 is collapsed to a collapsed BG1 (“c-BG1”) and BG2 is collapsed to a collapsed BG2 (“c-BG2”). The BFL does not change. Lens systems **1100**, **1200**, **1300** and **2100** switch between a pop-out state and a collapsed state according to the fourth method. FIG. 6A shows an embodiment of a handheld electronic device (e.g. smartphone) **600** with a camera system comprising a regular (upright) Wide camera **602** and a pop-out Tele camera **604** in an operative pop-out state. Height H_0 **606** is the height of device **600** (not including a “camera bump”). In the pop-out state, the Tele pop-out camera extends (raises) the device’s exterior surface **252** by a camera bump **608** of height H_{P-O-B} **226**. A large image sensor such as **208** (not visible here) and a pop-out mechanism such as pop-out mechanism **210** (not fully visible here) required for switching between a collapsed and a pop-out camera state may define a minimum area of the device’s exterior surface **252** that is covered by the pop-out camera (in the X-Z plane).

[0118] FIG. 6B shows host device **600** with pop-out Tele camera **604** in a collapsed state, illustrating the small height H_{C-B} **228** of the c-bump **608'** when Tele camera **604** is in the collapsed state.

[0119] FIG. 7A shows another embodiment of a device **700** with a camera system comprising a Wide pop-out camera **702** and a Tele pop-out camera **704** as disclosed herein in an operative pop-out state. Pop-out bump **708** of height H_{P-O-B} **226** is visible. A pop-out mechanism cover **706** covers both the Tele and the Wide cameras. A pop-out mechanism like mechanism **210** (not shown) switches the Tele and the Wide camera between one or more pop-out states and a collapsed state together and simultaneously, i.e. an actuator for state switching such as actuator **212** may control one or more air-gaps of both the Tele and the Wide camera. FIG. 7B shows host device **700** with the cameras in a collapsed state, with c-bump **708'** of height H_{C-B} **228** visible. A collapsed TTL of the Wide camera, $c\text{-}TTL_W$ may be similar to the collapsed TTL of the Tele camera, $c\text{-}TTL_T$, e.g. $c\text{-}TTL_W=c\text{-}TTL_T\pm 10\%$ or $c\text{-}TTL_W=c\text{-}TTL_T\pm 20\%$.

[0120] All lens systems shown in the following may be included in a pop-out optics module such as **240** or **500** and in a pop-out camera such as **200**.

[0121] FIG. 8A shows a lens system **800** in a pop-out state. Lens system **800** comprises a first embodiment of a lens numbered **206-1**. Lens **206-1** includes eight lens elements marked L1-L8, starting with L1 on an object side facing the object and ending with L8 on an image side toward the image sensor. The lens elements are arranged in two lens groups G1 and G2. G1 includes lens elements L1-L6, and G2 includes L7 and L8. An optional window **802** may e.g. be an optical filter. The optical axis is indicated **804**. Lens **206-1** is shown in a first zoom state having ZF1 with $EFL_T=13$ mm, $F\# = 1.1-1.8$ and $TTL=19.84$ mm. Lens **206-1**

may be switched to further zoom states continuously or discretely (having particular ZF2 or ZF3) by modifying d_{G1-G2} and/or BFL.

[0122] In the pop-out state, G1 is separated from G2 by an air-gap $d_{G1-G2}=6.22$ mm (i.e. T13, the distance between S_{13}

R_{AF} may be up to 1 mm for focusing down to 1 m, and up to 7 mm for focusing down to 4 cm.

[0126] Lens system **800** is represented by Tables 1-2. Table 1 provides optical data for lens **206-1** in the pop-out state, and Table 2 provides aspheric data.

TABLE 1

Group	Lens	Surface	Type	R [mm]	T [mm]	Nd	Vd	D [mm]
Object	Stop	S ₀	Flat	Infinity	Infinity			
		S ₁	Flat	Infinity	-0.775			9.000
G1	L1	S ₂	QFORB type 1	17.302	1.786	1.5661	37.43	8.577
G1	L1	S ₃	QFORB type 1	62.771	0.725			8.652
G1	L2	S ₄	QFORB type 1	10.090	1.928	1.5449	55.91	8.557
G1	L2	S ₅	QFORB type 1	-23.147	0.689			8.086
G1	L3	S ₆	QFORB type 1	80.507	0.232	1.6991	19.44	8.073
G1	L3	S ₇	QFORB type 1	10.360	1.287			5.509
G1	L4	S ₈	QFORB type 1	-4.430	0.928	1.5449	55.91	5.543
G1	L4	S ₉	QFORB type 1	-7.104	0.144			5.555
G1	L5	S ₁₀	QFORB type 1	440.072	1.646	1.6991	19.44	6.397
G1	L5	S ₁₁	QFORB type 1	28.935	0.033			6.494
G1	L6	S ₁₂	QFORB type 1	39.391	2.010	1.5449	55.91	6.726
G1	L6	S ₁₃	QFORB type 1	-5.075	6.224			6.322
G2	L7	S ₁₄	QFORB type 1	-6.250	0.601	1.6991	19.44	6.435
G2	L7	S ₁₅	QFORB type 1	-4.314	0.033			6.292
G2	L8	S ₁₆	QFORB type 1	-4.226	0.553	1.5449	55.91	6.944
G2	L8	S ₁₇	QFORB type 1	45.368	0.510			7.179
Glass window		S ₁₈	Flat	Infinity	0.21	1.5168	64.17	7.235
		S ₁₉	Flat	Infinity	0.3			7.000
Image sensor		S ₂₀	Flat	Infinity	0			7.000

TABLE 2

Surface	Conic (k)	NR	A_2	A_2	A_3	A_4
S_2	0	4.500	1.937E-01	3.246E-02	1.318E-03	2.280E-04
S_3	0	4.500	2.594E-01	8.795E-02	5.484E-03	3.649E-03
S_4	0	4.000	-1.694E-01	7.487E-04	-3.651E-03	1.653E-03
S_5	0	4.000	-8.607E-02	-4.556E-02	9.328E-03	-1.115E-04
S_6	0	4.000	-8.318E-01	8.107E-02	-3.312E-03	1.627E-04
S_7	0	3.600	-7.475E-01	6.703E-02	-6.921E-03	5.168E-04
S_8	0	3.540	1.184E+00	-7.816E-02	6.294E-03	-5.495E-03
S_9	0	3.540	1.068E+00	-3.634E-02	4.046E-03	-3.309E-03
S_{10}	0	3.540	-7.538E-01	-8.548E-02	-3.579E-02	-4.211E-03
S_{11}	0	3.540	-3.354E-01	5.277E-03	-9.014E-03	-8.400E-04
S_{12}	0	3.540	-6.434E-02	-5.113E-04	3.479E-04	-1.573E-03
S_{13}	0	3.540	5.865E-03	1.176E-03	3.052E-03	5.638E-04
S_{14}	0	3.540	-3.496E-01	-4.291E-02	-1.806E-02	-1.974E-03
S_{15}	0	3.540	-9.519E-03	2.425E-02	-8.039E-03	-5.814E-03
S_{16}	0	3.540	2.311E-01	7.899E-02	9.116E-03	-5.414E-03
S_{17}	0	3.540	-2.319E-01	8.502E-03	-2.231E-04	-1.988E-04

and S_{14} in Table 1) and G2 is separated from window **802** by an air-gap $d_{17}=0.51$ mm (T17, the distance between S_{13} and S_{14} in Table 1). The BFL is 1.02 mm.

[0123] In a collapsed state with a collapsed c-TTL, G1 may be separated from G2 by $c-d_{G1-G2}=0.02$ -2.5 mm and G2 may be separated from image sensor **208** by $c-BFL=0.2$ -0.8 mm. The c-TTL of lens system **800** may be $c-TTL=12.6$ -16 mm, $c-TTL/EFL$ may be equal to or greater than 0.97 and $c-TTL/TTL$ may be equal to or greater than 0.64.

[0124] In other examples, when switching between a pop-out state and a collapsed state only air-gap d_{G1-G2} may be modified to $c-d_{G1-G2}$, which may be 0.2-2.5 mm. BFL may remain unchanged.

[0125] In some examples, G1+G2 are movable together relative to image sensor **208** in a range R_{AF} for focusing of camera **200** from infinity down to 1 m or even down to 4 cm.

[0127] FIG. 8B shows another lens system **850**. Lens system **850** is shown in a pop-out state. The design data is given in Tables 3-5. Lens system **850** includes a lens **206-7** having six lens elements L1-L6, optical window **802** and image sensor **208**. L1-L3 form G1, and L4-L6 form G2. The TTL is 13.5 mm and the BFL is 5.49 mm. Focal length is $EFL=15.15$ mm, F number=2.0 and the FOV=32.56 deg. Air-gap d_{G1-G2} is 1.78 mm.

[0128] In a collapsed state, a “collapsed” cTTL may be 5-11 mm. The difference between cTTL and TTL stems from a modified air-gap between L3 and L4, which is a collapsed air-gap $c-d_{G1-G2}$ and which may be 0.05-1.0 mm and a modified BFL which is a c-BFL and may be 0.1-1.5 mm. For lens system **850**, a ratio TTL/EFL is 0.89, i.e. $EFL>TTL$. The ratio $cTTL/EFL$ may be 0.35-0.75.

TABLE 3

Embodiment 850 EFL = 15.15 mm, F number = 2.0, FOV = 32.56 deg.									
Surface #	Comment	Type	Curvature Radius	Thickness	Aperture Radius (D/2)	Material	Index	Abbe #	Focal Length
1	A.S	Plano	Infinity	-1.823	3.731				
2	Lens 1	ASP	4.314	1.837	3.731	Plastic	1.54	55.91	9.50
3			21.571	0.048	3.560				
4	Lens 2	ASP	4.978	0.265	3.419	Plastic	1.67	19.44	-17.41
5			3.422	0.113	3.139				
6	Lens 3	ASP	5.764	1.473	3.113	Plastic	1.67	19.44	20.20
7			11.201	1.780	2.909				
8	Lens 4	ASP	-6.075	0.260	2.143	Plastic	1.67	19.44	-14.33
9			-17.446	1.230	2.008				
10	Lens 5	ASP	-18.298	0.688	2.264	Plastic	1.54	55.91	184.98
11			-16.202	0.040	2.468				
12	Lens 6	ASP	10.235	0.273	2.679	Plastic	1.54	55.91	-93.97
13			8.454	4.783	2.848				
14	Filter	Plano	Infinity	0.210	—	Glass	1.52	64.17	
15			Infinity	0.500	—				
16	Image	Plano	Infinity	—	—				

TABLE 4

Aspheric Coefficients					
Surface #	Conic	A4	A6	A8	A10
2	0	-4.57E-04	-5.55E-05	2.46E-05	-4.65E-06
3	0	8.55E-04	7.37E-04	-1.07E-04	9.78E-06
4	0	-1.51E-02	3.43E-03	-6.33E-04	8.54E-05
5	0	-2.21E-02	5.71E-03	-1.50E-03	2.85E-04
6	0	-3.61E-03	3.56E-03	-1.08E-03	2.29E-04
7	0	-1.74E-04	2.47E-04	5.66E-05	-3.21E-05
8	0	1.75E-02	2.27E-03	-2.24E-03	7.99E-04
9	0	1.79E-02	5.45E-03	-3.71E-03	1.37E-03
10	0	-4.37E-03	-1.59E-02	1.33E-02	-6.54E-03
11	0	-7.77E-02	4.02E-02	-1.21E-02	1.65E-03
12	0	-1.39E-01	7.50E-02	-2.44E-02	4.78E-03
13	0	-5.32E-02	1.90E-02	-4.73E-03	6.11E-04

TABLE 5

Aspheric Coefficients			
Surface #	A12	A14	A16
2	4.92E-07	-2.88E-08	5.71E-10
3	-6.44E-07	1.90E-08	-1.21E-10
4	-6.96E-06	3.18E-07	-6.61E-09
5	-3.28E-05	2.13E-06	-6.25E-08
6	-2.83E-05	1.87E-06	-5.35E-08
7	5.30E-06	-4.54E-07	1.54E-08
8	-1.70E-04	1.94E-05	-9.28E-07
9	-2.64E-04	2.29E-05	-1.78E-07
10	1.83E-03	-2.76E-04	1.73E-05
11	-8.43E-06	-2.54E-05	2.18E-06

TABLE 5-continued

Aspheric Coefficients			
Surface #	A12	A14	A16
12	-5.86E-04	4.30E-05	-1.42E-06
13	-2.86E-05	-1.51E-06	1.53E-07

[0129] FIG. 9 shows a lens system **900** in a pop-out state. Lens system **900** comprises a second embodiment of a lens numbered **206-2**. Lens **206-2** includes five lens elements marked L1-L5 arranged in G1 (L1 and L2) and G2 (L3, L4 and L5). Lens **206-2** is shown in a first zoom state having ZF1 with EFL_T=7.97 mm, F #=1.2-2.0 and TTL=7.78 mm. Lens **206-2** may be switched to further zoom states continuously or discretely (having particular ZF2 or ZF3) by modifying d_{G1-G2} and/or BFL.

[0130] In the pop-out state, G1 is separated from G2 by an air-gap d_{G1-G2}=0.974 mm (T4 in Table 3) and G2 is separated from window **802** by an air-gap d10=2.66 mm (T10). The BFL is 3.27 mm.

[0131] In a collapsed state with a collapsed c-TTL, G1 may be separated from G2 by c-d_{G1-G2}=0.02-0.75 mm and G2 may be separated from image sensor **208** by c-BFL=0.2-2.5 mm.

[0132] In other examples, when switching between a pop-out state and a collapsed state only BFL may be modified to c-BFL=0.2-2.5 mm and air-gap d_{G1-G2} may not change. The c-TTL of lens system **900** may be 3.6-7.7 mm. Ratio c-TTL/EFL may be equal to or greater than 0.45, and ratio c-TTL/TTL may be equal to or greater than 0.46.

[0133] G1+G2 are movable together relative to image sensor **208** and in a range R_{AF}.

[0134] Lens system **900** is represented by Tables 6-7.

TABLE 6

#	Type	Comments	R	T	Nd	Vd	CA/2	k
1	Evsn-asph	L ₁ S ₁	2.271	1.127	1.67	54.96	1.8	7.979E-07
2	Evsn-asph	S ₂	11.822	0.06			1.725	2.410
3	Evsn-asph	L ₂ S ₃	14.756	0.27	1.64	23.52	1.7	13.805
4	Evsn-asph	S ₄	2.728	0.974			1.45	2.902E-03
5	Evsn-asph	L ₃ S ₅	3.713	0.416	1.64	23.52	1.55	-2.868
6	Evsn-asph	S ₆	3.524	0.764			1.5	-8.486

TABLE 6-continued

#	Type	Comments	R	T	Nd	Vd	CA/2	k
7	Evn-asph	L ₄ S ₇	-5.301	0.338	1.64	23.52	1.48	2.743
8	Evn-asph	S ₈	-4.321	0.212			1.6	2.578
9	Evn-asph	L ₅ S ₉	4.327	0.352	1.53	55.66	1.68	-9.755
10	Evn-asph	S ₁₀	3.771	2.656			1.8	-6.534
11	Flat	Infinity	0.210	1.52	64.16		2.894	
12	Flat	Infinity	0.401				2.938	
13	Flat	Infinity	—				3.028	

TABLE 7

#	A1	A2	A3	A4	A5	A6	A7
1	4.421E-05	-2.009E-04	-1.152E-04	-6.051E-10			
2	6.027E-03	-1.244E-03	-5.380E-08				
3	0.020	7.012E-04	-1.081E-03	-6.297E-08			
4	0.024	0.011	4.241E-04	-9.114E-08			
5	-0.022	8.939E-03	2.200E-03	-1.002E-06			
6	-0.012	6.756E-03	-2.299E-03	1.314E-03	1.758E-04	-1.030E-05	
7	-0.017	0.053	-0.044	7.968E-03	-1.599E-03	6.117E-04	7.436E-09
8	-0.086	0.159	-0.117	0.041	-9.090E-03	1.280E-03	2.793E-07
9	-0.252	0.182	-0.084	0.016	-6.759E-04	-1.940E-06	
10	-0.175	0.095	-0.040	8.597E-03	-7.751E-04	-8.160E-07	

[0135] FIG. 10 shows a lens system **1000** in a pop-out state. Lens system **1000** comprises a third embodiment of a lens numbered **206-3**. Lens **206-3** includes five lens elements L1-L5 arranged in G1 (L1) and G2 (L2-L5) and is shown in a first zoom state having ZF1 with EFL_T=16 mm and TTL=15 mm. Lens **206-3** may be switched to further zoom states continuously or discretely (having particular ZF2 or ZF3) by modifying d_{G1-G2} and/or BFL.

[0136] In the pop-out state, G1 is separated from G2 by an air-gap d_{G1-G2}=1.547 mm (T2 in Table 5) and G2 is separated from window **802** by an air-gap d10=4.115 mm (T10). The BFL is 6.998 mm.

[0137] In a collapsed state with a collapsed c-TTL, G1 may be separated from G2 by c-d_{G1-G2}=0.02-0.75 mm and G2 may be separated from image sensor **208** by c-BFL=0.2-5 mm. In other examples, when switching between a pop-out state and a collapsed state only BFL may be modified to c-BFL=0.2-2.5 mm and air-gap d_{G1-G2} may not change. The c-TTL of lens system **1000** may be 6.2-13 mm. Ratio c-TTL/EFL may be equal to or greater than 0.39 and ratio c-TTL/TTL may be equal to or greater than 0.41.

[0138] G1+G2 are movable together relative to image sensor **208** and in a range R_{AF}. R_{AF} may be up to 0.6 mm for focusing down to 1 m, and up to 8 mm for focusing down to 0.04 m.

[0139] Lens system **1000** is represented by Tables 8-9. Table 5 provides optical data for lens **206-3** being in a pop-out state Table 6 provides aspheric data.

TABLE 8

#	R	Thickness	Material	CA/2	Conic coefficient K
0	Infinity	1.00E+06			
1	4.009	2.271	H-ZK3	2.96	0
2	18.115	1.547		2.55	0
3	-5.167	0.562	EP6000L	2.00	-2.296
4	6.968	0.162		2.00	9.483
5	4.666	1.082	K26R	1.90	-2.619
6	52.645	0.121		1.90	10.398
7	28.168	1.851	EP6000L	1.83	-367.355
8	-5.062	0.101		1.83	-10.130
9	-5.098	0.291	K26R	1.76	-10.587
10	15.000	4.115		1.76	-9.745
11	Infinity	0.210	BK7	2.44	
12	Infinity	2.673		2.47	
13	Infinity			2.94	

TABLE 9

#	A1	A2	A3	A4	A5	A6	A7
1	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0
3	7.1296E-03	-1.3791E-04	-2.8926E-05	3.7349E-06	0	0	0
4	-2.8741E-03	8.8769E-04	-1.2786E-04	2.0275E-05	0	0	0
5	-2.1504E-03	-3.1621E-04	-3.2758E-06	-2.2831E-07	0	0	0
6	4.1139E-03	-1.9087E-03	1.9639E-04	-3.2249E-05	0	0	0
7	-4.3880E-03	-7.7699E-04	1.8992E-04	-6.8854E-06	0	0	0
8	-6.5726E-03	-5.8651E-04	1.3315E-04	-2.0025E-05	0	0	0
9	-7.8205E-03	-1.1425E-03	2.7014E-04	-4.0371E-05	0	0	0
10	-5.0642E-03	3.6557E-04	-9.7321E-05	1.7319E-05	0	0	0

[0140] FIG. 11A-B show a lens system **1100** in two pop-out states. Lens system **1100** comprises a fourth embodiment of a lens numbered **206-4**. Lens **206-4** includes six lens elements L1-L6 arranged in G1 (L1-L2) and G2 (L3-L6) separated by air-gap d_{G1-G2} . Lens system **1100** may be able to focus continuously from infinity to e.g. 5 cm. FIG. 11A shows lens system **1100** in a Tele lens state focused at infinity. FIG. 11B shows lens system **1100** in a Macro lens state focused at 5 cm. For focusing lens **206-4**, d_{G1-G2} and BFL are modified, i.e. two air-gaps present in **1100** are modified. The TTL changes continuously and in dependence on u from TTL=15 mm (focus at infinity) to TTL=20.9 mm (focus at 5 cm).

[0141] In the Tele state (see FIG. 11A) having ZF1 and being focused at infinity, **206-4** has $F/\# = 1.3-1.9$, $EFL_T = 14.98$ mm and TTL=15 mm. In the Tele state, G1 is separated from G2 by an air-gap $d_{G1-G2}^T = 1.909$ mm (i.e. T5, the distance between S_5 and S_6 in Table 8) and G2 is separated from image sensor by $BFL_T = 0.586$ mm (i.e. T13 in Table 8). For the Tele state, a ratio of c-TTL/EFL may be $c-TTL/EFL \geq 0.57$, a ratio of c-TTL/TTL may be $c-TTL/EFL \geq 0.57$. **206-4** may be switched to further zoom states continuously or discretely (having particular ZF2 or ZF3) by modifying d_{G1-G2} and/or BFL.

[0142] In the Macro configuration (see FIG. 11B) with focus at 5 cm, **206-4** has $F/\# = 1.7-2.8$, $EFL_M = 14.8$ mm and TTL=20.9 mm. In the Macro state, G1 is separated from G2 by an air-gap $d_{G1-G2}^M = 1.441$ mm and G2 is separated from image sensor by $BFL_M = 6.955$ mm. According to thin lens equation (Eq. 2)

$$\frac{1}{EFL} = \frac{1}{u} + \frac{1}{v}$$

for $EFL \approx 15$ mm and $u = 50$ mm the effective lens-image distance v is $v \approx 21$ mm and a M of about 2.4:1 is achieved.

[0143] In a collapsed state with a collapsed c-TTL, G1 may be separated from G2 by e.g. $c-d_{G1-G2} = 0.02-1.4$ mm and G2 may be separated from image sensor **208** by $c-BFL = 0.2-0.8$ mm. A c-TTL of lens system **1100** may be $c-TTL = 8.5-14$ mm. For the Macro state, ratio $c-TTL/EFL$ may be equal to or greater than 0.57 and ratio $c-TTL/TTL$ may be equal to or greater than 0.41.

[0144] In some examples, another (large) air gap such as air gap d11 between L5 and L6 may be collapsed when switching to a collapsed state. For an example with a collapsible air gap d11, c-TTL of lens system **1100** may be 8.5-11 mm.

[0145] In other examples, when switching between a pop-out state and a collapsed state only $d_{G1-G2} = 0.02-1.4$ mm may be modified to $c-d_{G1-G2} = 0.02-1.4$ mm and BFL may not change. In yet other examples, when switching between a pop-out state and a collapsed state only BFL may be modified to $c-BFL = 0.2-0.8$ mm and air-gap d_{G1-G2} may not change.

[0146] Lens system **1100** is represented by Tables 10-13. Table 10 and Table 11 provide optical data for lens **206-4** being in pop-out state and (focused at infinity (left) and at 5 cm (right)). Table 12 provides aspheric data and Table 13 provides data on the focus lengths of L1-L6 as well as on G1 and G2.

TABLE 10

Group	Lens	Surface	Type	R [mm]	T [mm]	Nd	Vd	D [mm]
Object	Stop	S ₀	Flat	Infinity	See Table 11			
		S ₁	Flat	Infinity	-1.297			3.39
G1	L1	S ₂	Even Asphere	4.760	2.049	1.5348	3.40	8.577
G1	L1	S ₃	Even Asphere	-40.471	1.341		3.25	8.652
G1	L2	S ₄	Even Asphere	-208.624	0.838	1.6397	2.72	8.557
G1	L2	S ₅	Even Asphere	3.942	See table 11		2.35	8.086
G2	L3	S ₆	Even Asphere	3.675	0.703	1.5348	2.60	8.073
G2	L3	S ₇	Even Asphere	5.768	0.391		2.68	5.509
G2	L4	S ₈	Even Asphere	6.436	1.160	1.6397	2.84	5.543
G2	L4	S ₉	Even Asphere	13.466	0.330		2.51	5.555
G2	L5	S ₁₀	Even Asphere	1.745	0.270	1.5348	2.63	6.397
G2	L5	S ₁₁	Even Asphere	1.377	4.000		2.61	6.494
G2	L6	S ₁₂	Even Asphere	-8.989	0.924	1.5348	3.57	6.726
G2	L6	S ₁₃	Even Asphere	-6.006	See table 11		3.59	6.322
Glass window		S ₁₈	Flat	Infinity	0.210	1.5168	64.17	3.68
		S ₁₉	Flat	Infinity	0.290			3.69
Image sensor		S ₂₀	Flat	Infinity	0			3.71

TABLE 11

Object position		at infinity	at 50 mm
T [mm]	S ₀	Infinity	50
	S ₈	1.909	1.441
	S ₁₃	0.586	6.955

TABLE 12

Surface	Conic (k)	A ₂	A ₃	A ₄	A ₄	A ₈
S ₂	-0.630	0	4.4054E-04	1.2583E-05	-2.9783E-07	6.0963E-09
S ₃	-17.322	0	1.1175E-03	-7.2647E-05	3.0989E-06	-5.5328E-08

TABLE 12-continued

Surface	Conic (k)	A ₂	A ₃	A4	A4	A8
S ₄	10.896	0	2.8072E-04	-1.8071E-05	1.0399E-05	-5.1263E-07
S ₅	-3.542	0	4.3261E-03	-2.3939E-04	4.7495E-05	-1.4155E-06
S ₆	0.550	0	-4.6101E-03	-6.4645E-04	-5.5036E-05	-9.0004E-06
S ₇	2.038	0	-1.9132E-03	-9.1925E-04	-1.1892E-04	7.4560E-06
S ₈	-0.407	0	7.3254E-03	-9.5079E-04	1.4267E-04	-4.1002E-06
S ₉	10.906	0	9.1614E-03	-7.9578E-04	1.5907E-04	1.1780E-05
S ₁₀	-1.309	0	-5.7321E-02	7.4146E-03	-5.5742E-04	3.4068E-05
S ₁₁	-1.653	0	-4.4174E-02	7.6947E-03	-6.6729E-04	2.6326E-05
S ₁₂	-8.851	0	1.5094E-03	1.3664E-04	2.1531E-06	-1.9460E-07
S ₁₃	1.231	0	2.2125E-03	7.1788E-05	7.8923E-06	1.8970E-07

TABLE 13

Lens #	Lens or group focal length [mm]
L1	8.057
L2	-5.978
L3	16.869
L4	17.921
L5	-16.324
L6	30.404
G1	49.457
G2	12.122

[0147] FIG. 12A-B show a lens system **1200** in two pop-out states. Lens system **1200** comprises a fifth embodiment of a lens **206-5**. Lens **206-5** comprises six lens elements L1-L6 in three lens groups G1 (L1-L3), G2 (L4-L5) and G3 (L6). G1 and G2 are separated by an air-gap d_{G1-G2} and G2 and G3 are separated by an air-gap d_{G2-G3} . Lens system **1200** may be able to focus continuously from infinity to e.g. 5 cm. FIG. 12A shows lens system **1200** in a Tele lens state focused at infinity. FIG. 12B shows lens system **1200** in a Macro lens state focused at 5 cm. For focusing lens **206-5**, d_{G1-G2} and d_{G2-G3} are increased or decreased. The TTL changes continuously from TTL=15 mm (focus at infinity) to TTL=20.9 mm (focus at 5 cm).

[0148] In the Tele state (see FIG. 12A) having ZF1 and being focused at infinity, **206-5** has F/#=1.2-1.8, EFL_T=15 mm and TTL=18.7 mm. In the Tele state, $d_{G1-G2}^T=5.073$ mm (i.e. T7, the distance between S₇ and S₈ in Table 11) and G2 is separated from G3 by $d_{G2-G3}^T=4.813$ mm (i.e. T11). For the Tele state, ratio c-TTL/EFL may be equal to or greater than 0.59, and ratio c-TTL/TTL may equal to or greater than 0.48. **206-5** may be switched to further zoom

states continuously or discretely (having particular ZF2 or ZF3) by modifying d_{G1-G2} , d_{G2-G3} and/or BFL.

[0149] In the Macro configuration (see FIG. 12B) with focus at 5 cm, **206-5** has F/#=1.3-1.9, EFL_M=9.8 mm and TTL=20.9 mm. In the Macro state, $d_{G1-G2}^M=2.908$ mm and $d_{G2-G3}^M=9.175$ mm. The BFL of **206-5** is =0.95 mm and is not modified for focusing. According to eq. 2 for EFL≈10 mm and u=50 mm, the lens-image distance (“v”) is v≈12.5 mm and a M of about 4:1 is achieved.

[0150] In a collapsed state with a collapsed c-TTL, G1 may be separated from G2 by $c-d_{G1-G2}=0.02-2.5$ mm and G2 may be separated from G3 by $c-d_{G2-G3}=0.02-4.5$ mm. When switching between a pop-out state and a collapsed state two air-gaps may be modified. A c-TTL of lens system **1200** may be 8.8-15 mm. For the Macro state, ratio c-TTL/EFL may be equal to or greater than 0.89 and ratio c-TTL/TTL may be equal to or greater than 0.43.

[0151] In some examples, another (large) air gap such as air gap d9 between L4 and L5 may be collapsed when switching to a collapsed state. For an example with a collapsible air gap d9, c-TTL of lens system **1200** may be 7.6-15 mm, corresponding to a ratio c-TTL/EFL≥0.76.

[0152] In other examples, when switching between a pop-out state and a collapsed state only d_{G1-G2} may be modified to $c-d_{G1-G2}=0.02-1.4$ mm and d_{G2-G3} may not change. In yet other examples, when switching between a pop-out state and a collapsed state only d_{G2-G3} may be modified to $c-d_{G2-G3}=0.02-4.5$ mm d_{G1-G2} may not change.

[0153] Lens system **1200** is represented by Tables 14-17. Table 14 and Table 15 provide optical data for lens **206-5** being in pop-out state (focus at infinity and at 5 cm), Table 16 provides aspheric data, and Table 17 provides data on the focus lengths of each lens element and on G1, G2 and G3.

TABLE 14

Group	Lens	Surface	Type	R [mm]	T [mm]	Nd	Vd	D [mm]
Object Stop		S ₀	Flat	Infinity	See Table 15			
		S ₁	Flat	Infinity	-1.015			3.46
G1	L1	S ₂	Even Asphere	6.387	2.000	1.5449	55.913	8.577
G1	L1	S ₃	Even Asphere	-6.110	0.093			8.652
G1	L2	S ₄	Even Asphere	-5.663	0.260	1.5661	37.426	8.557
G1	L2	S ₅	Even Asphere	12.316	0.236			8.086
G1	L3	S ₆	Even Asphere	13.536	1.000	1.6397	23.529	8.073
G1	L3	S ₇	Even Asphere	16.733	See table 15			5.509
G2	L4	S ₈	Even Asphere	16.483	1.093	1.651	21.514	5.543
G2	L4	S ₉	Even Asphere	9.528	1.279			5.555
G2	L5	S ₁₀	Even Asphere	26.649	1.500	1.5449	55.913	6.397
G2	L5	S ₁₁	Even Asphere	-7.769	See table 15			6.494
G3	L6	S ₁₂	Even Asphere	-5.892	0.402	1.5449	55.913	6.726
G3	L6	S ₁₃	Even Asphere	66.620	0.450			6.322

TABLE 14-continued

Group	Lens	Surface	Type	R [mm]	T [mm]	Nd	Vd	D [mm]
Glass window		S ₁₈	Flat	Infinity	0.210	1.5168	64.17	3.62
		S ₁₉	Flat	Infinity	0.290			3.65
Image sensor		S ₂₀	Flat	Infinity	0			3.70

TABLE 15

Object position		at infinity	at 50 mm
T [mm]	S ₀	Infinity	50
	S ₇	5.073	2.908
	S ₁₁	4.813	9.175

TABLE 16

Surface	Conic (k)	A ₂	A ₃	A ₄	A ₄	A ₈
S ₂	0.677	0	-3.662E-04	1.359E-05	0.000E+00	-3.662E-04
S ₃	-4.775	0	4.898E-03	-1.397E-04	1.591E-06	4.898E-03
S ₄	-6.366	0	4.765E-03	-1.692E-04	3.254E-06	4.765E-03
S ₅	5.346	0	-3.075E-03	9.482E-05	9.656E-07	-3.075E-03
S ₆	-8.028	0	-2.837E-03	1.380E-04	-1.763E-06	-2.837E-03
S ₇	16.045	0	1.797E-04	-1.949E-05	1.044E-06	1.797E-04
S ₈	-6.134	0	-3.752E-03	-7.964E-06	-3.621E-07	-3.752E-03
S ₉	-1.248	0	-3.976E-03	2.575E-05	-3.337E-07	-3.976E-03
S ₁₀	26.732	0	-5.210E-04	-6.374E-06	5.625E-07	-5.210E-04
S ₁₁	-1.100	0	-1.300E-04	1.134E-05	9.762E-07	-1.300E-04
S ₁₂	-0.839	0	1.998E-03	-1.041E-04	2.466E-06	1.998E-03
S ₁₃	26.744	0	5.185E-04	3.489E-06	-3.179E-06	5.185E-04

TABLE 17

Lens #	Lens or group focal length [mm]
L1	6.054
L2	-6.785
L3	97.901
L4	-36.686
L5	11.176
L6	-9.882
G1	21.183
G2	15.420
G3	-9.882

[0154] FIG. 13A-B show a lens system **1300** in two pop-out states. Lens system **1300** comprises a sixth embodiment of a lens **206-6**. FIG. 13A shows lens system **1300** in a Tele lens state focused at infinity ("Config. A"). FIG. 13B shows lens system **1300** in a Macro lens state focused at 5 cm ("Config. C"). Lens **206-6** comprises two lens groups G1 (L1-L2) and G2 (L3-L6), separated by an air-gap d_{G1-G2} . Lens system **1300** may be able to focus continuously from infinity to e.g. 5 cm. For focusing lens **206-6**, d_{G1-G2} and the BFL are changed. The TTL changes continuously and depending on u from TTL=15.8 mm (focus at infinity) to TTL=20.4 mm (focus at 5 cm). I.e. for focusing, there is a relative movement of G1 and G2 and in addition a movement of G1 and G2 together (see Table 20).

[0155] In the Tele state (see FIG. 13A) having ZF1 and being focused at infinity, lens **206-6** has $F/\#$ =1.3-1.9, EFL_T =15 mm and TTL=15.8 mm. In the Tele state, d_{G1-G2}^T =2.625 mm (i.e. T5, the distance between S₅ and S₆ in Table 20) and BFL=0.844 mm. **206-6** may be switched to further zoom states continuously or discretely (having particular ZF2 or ZF3) by modifying d_{G1-G2} and/or BFL.

[0156] In the Macro configuration (see FIG. 13B) with focus at 5 cm, **206-6** has $F/\#$ =1.5-2.6, EFL_M =15 mm and TTL=20.4 mm. In the Macro state, d_{G1-G2}^M =1.303 mm and BFL=6.818 mm. AM of about 2.5:1 is achieved.

[0157] In a collapsed state with a collapsed c-TTL, G1 may be separated from G2 by e.g. $c-d_{G1-G2}$ =0.02-1.5 mm and L3 may be separated from L4 by $c-d_7$ =0.02-2.5 mm. A c-TTL of lens system **1200** may be 9.5-13.5 mm.

[0158] In other examples, when switching between a pop-out state and a collapsed state only d_7 may be modified to $c-d_7$ =0.02-2.5 mm and d_{G1-G2} may not change. In yet other examples, when switching between a pop-out state and a collapsed state only d_{G1-G2} may be modified to $c-d_{G1-G2}$ =0.02-1.5 mm d_7 may not change.

[0159] The lens system **1300** is represented by Tables 18-21. FOV is given as half FOV (HFOV). Table 18 and Table 19 provide optical data for lens **206-5** being in pop-out state. Table 20 provides aspheric data.

[0160] Table 20 shows three focus configurations of lens system **1300**: focused to infinity ("Config. A"), focused to 100 mm ("Config. B", no Figure shown) and focused to 50 mm ("Config. C"). The u which is focused on is given by Surface 0 in Table 20. Table 21 provides data on the half FOV (HFOV), M and $f/\#$. Lens system **1300** can focus continuously from Infinity to 50 mm. For changing focus of lens system **1300** continuously, the values of d_{G1-G2} and BFL change continuously.

TABLE 18

Embodiment 1300									
EFL = 15.0 mm, F number = 2.2, HFOV = 13.1 deg.									
Surface #	Comment	Type	Curvature Radius	Thickness	Aperture Radius (D/2)	Material	Index	Abbe #	Focal Length
1	A.S	Plano	Infinity	-1.138	3.394				
2	Lens 1	ASP	5.548	1.713	3.399	Plastic	1.53	55.66	10.11
3			-225.776	0.031	3.268				
4	Lens 2	ASP	4.454	1.000	3.084	Plastic	1.64	23.52	-9.96
5			2.401	2.625	2.627				
6	Lens 3	ASP	4.197	1.000	2.722	Plastic	1.53	55.66	15.25
7			7.888	4.910	2.661				
8	Lens 4	ASP	-6.881	0.435	2.717	Plastic	1.66	20.37	1841.21
9			-7.016	0.162	2.848				
10	Lens 5	ASP	2.335	0.551	2.906	Plastic	1.53	55.66	-24.20
11			1.816	1.274	3.339				
12	Lens 6	ASP	-7.488	1.251	3.393	Plastic	1.53	55.66	20.05
13			-4.675	0.344	3.546				
14	Filter	Plano	Infinity	0.210	—	Glass	1.52	64.17	
15			Infinity	0.290	—				
16	Image	Plano	Infinity	—	—				

TABLE 19

Aspheric Coefficients					
Surface #	Conic	A4	A6	A8	A10
2	-4.21E-01	6.50E-04	-1.01E-05	1.56E-06	-5.69E-08
3	-2.24E+02	2.36E-03	-1.58E-04	5.38E-06	-7.57E-08
4	-4.52E+00	-5.19E-04	5.31E-05	-6.85E-06	3.53E-07
5	-2.24E+00	2.21E-03	1.61E-05	-1.54E-06	7.95E-07
6	-8.98E-03	-7.71E-05	-5.52E-05	5.85E-06	-8.17E-07
7	6.54E-01	6.97E-04	-2.34E-05	-6.13E-07	-5.58E-07
8	-6.59E+01	4.55E-03	-1.90E-03	2.62E-05	3.32E-06
9	-4.32E-01	1.47E-02	-3.66E-03	2.57E-04	-5.76E-06
10	-4.54E+00	-2.21E-02	-1.28E-03	3.91E-04	-2.22E-05
11	-1.73E+00	-3.64E-02	4.33E-03	-2.94E-04	6.72E-06
12	-2.40E+01	1.32E-03	3.07E-04	-3.67E-05	-4.21E-07
13	-1.13E+00	6.63E-04	-3.99E-04	6.48E-05	-3.13E-06

TABLE 20

Embodiment 1300			
Variation of surface thicknesses			
Surface #	Config. A	Config. B	Config. C
0	1.00E+06	100	50
5	2.625	1.946	1.303
13	0.344	2.941	6.318

TABLE 21

Embodiment 1300			
Config. #	HFOV	Magnification	f/#
A	13.1 deg	0	1.2-1.9
B	11.3 deg	-0.17	1.3-2.2
C	9.3 deg	-0.40	1.7-2.5

[0161] The focusing range of some examples of lens systems such as **800**, **850**, **900**, **1000**, **1100**, **1200** and **1300** may be from infinity to less than 150 mm, from infinity to e.g. 1 m or 2 m, and from e.g. 350 mm to less than 150 mm,

e.g. to 50 mm. The focusing range of a lens system is defined as all u that can be focused to by means of a camera mechanism that controls the distance between lens and image sensor. That is, for each object that is located within the focus range, a focusing mechanism can set a particular v that results in maximum contrast for the object's image. Maximum contrast means that for lens-image sensor distances other than the particular lens-image sensor distance, the object's contrast will decrease. A minimal object distance (MIOD) is defined as the lower limit of the focusing range, i.e. the MIOD is the smallest u that the lens system can focus to. For example, some embodiments shown above can focus from infinity to 50 mm, i.e. MIOD is 50 mm.

[0162] FIG. 14A shows a known sensor shift setup. The sensor is shown from a viewing point on the camera's optical axis (camera not shown). Most of today's mobile devices equipped with OIS correct for undesired device motion in Yaw and Pitch directions. As indicated by arrow **1402**, for correction in Yaw direction, the sensor is moved parallel to X. As indicated by arrow **1404**, for Pitch correction, the sensor is moved parallel to Y.

[0163] FIG. 14B shows a sensor shift setup disclosed herein. The sensor is shown in the same perspective as in FIG. 14A. As shown in FIG. 14B, a correction of undesired linear motion in X (indicated by arrow **1406**) and Y direction (indicated by arrow **1408**) may be performed along the same axes used for Yaw and Pitch correction respectively. Correction for undesired linear motion in X and Y may be superposed on correction of rotational hand motion in Yaw and Pitch.

[0164] FIG. 15A shows an exemplary optical system **1500** having an optical axis **1502** parallel to X that comprises an object **1504**, a lens **1506** and an image **1508** of object **1504** formed at an image sensor **1510**. Lens **1506** may have a principal plane **1512**. FIG. 15A shows optical system **1500** at an initial time, e.g. when starting image sensor exposure for image capture. Optical system **1500** has a M of 1:1.

[0165] FIG. 15B shows optical system **1500** at a later time during exposure of image sensor **1510** for image capture and after the camera hosting device underwent an undesired linear motion in the negative Y direction by a distance do (relative to the object at rest). The undesired linear motion

results in a linear shift of an object point in the positive Y direction by a distance d_o . On image sensor **1510**, this results in a linear image shift in the negative Y direction by a distance d and eventually in image blurring. d does not only depend on the magnitude and direction of the actual undesired linear motion, but also on u : on image sensor **1510**, the actual undesired linear motion is amplified or attenuated according to

$$M = \frac{v}{u}$$

with u and v . According to eq. 2, d_{sensor} relates to d_o according to:

$$d_{\text{sensor}} = d_o \frac{EFL}{u - EFL}. \quad (\text{Eq. 3})$$

[0166] From eq. 3 we learn that for a typical image capture scenario for a Wide camera (Wide example: EFL=5 mm, $u > 10$ cm) or a Tele camera (Tele example: EFL=13 mm, $u > 100$ cm) a linear shift at the object plane d_o leads to a linear shift d_s at image sensor **1510** of $d_s \approx 0.05 \cdot d_o$ for the Wide example ($u=10$ cm) and $d_s \approx 0.01 \cdot d_o$ for the Tele example ($u=100$ cm). In general, it is assumed that $u \gg EFL$ and that an undesired linear motion such as d_o does not deteriorate image quality significantly. However, this assumption is not valid for cameras with large magnifications M such as the pop-out camera in Macro configuration described herein. Consider as an example a Tele camera having EFL=13 mm that is focused to $u=10$ cm (first Macro example: EFL=13 mm, $u=10$ cm) and $u=5$ cm object-lens distance (second Macro example: EFL=13 mm, $u=5$ cm). For the first Macro example $d_s \approx 0.15 \cdot d_o$, for the second Macro example $d_s \approx 0.35 \cdot d_o$. This shows that significant image quality deterioration caused by undesired linear motion in X and Y is expected. An undesired linear motion of a handheld device may be sensed by a motion sensor such as an inertial measurement unit (IMU). An IMU provides data on the linear acceleration which is to be integrated for determining the linear shift.

[0167] FIG. 16A shows schematically in a block diagram a device **1600** operative to perform OIS for correcting undesired linear motion in X and Y directions as described herein. Device **1600** comprises a Tele camera **1610** having FOV_T . In some examples, camera **1610** is a Macro capable (upright) pop-out camera. In other examples, camera **1610** is a Macro capable folded or upright Tele camera. Tele camera **1610** comprises of an actuator **1612** and a position sensor **1614** (e.g. a Hall sensor) for closed loop actuation and control, a lens **1616** and an image sensor **1618**. If Tele camera **1610** is a pop-out camera, lens **1616** may comprise a collapsible lens. If Tele camera **1610** is a folded camera, it may comprise an optical path folding element (OPFE, not shown) for folding an optical path, in general by 90 degrees. If Tele camera **1610** is a double-folded camera, it may comprise two OPFEs (not shown) for folding an optical path twice, in general by 90 degrees per folding. OIS may be performed as “lens shift” OIS or as “sensor shift” OIS. In a folded Tele camera, OIS may be performed as “prism OIS”, i.e. the one or two OPFEs may be rotated or moved linearly for performing OIS as described herein. For sensor shift

OIS, image sensor **1618** is moved relative to lens **1616** and to device **250**. For sensor shift OIS, a sensor shift by d_s is required for correcting an undesired linear motion by d_o as given by eq. 3. In lens shift OIS, the lens is moved relative to image sensor **1618** and to device **250**. For lens shift OIS a lens shift by d_L is required for correcting an undesired linear motion by d_o . Lens shift d_L depends on d_s (eq. 4) and d_o (eq. 5) according to:

$$d_{\text{Lens}} = d_{\text{sensor}} \frac{u}{u + v} \quad (\text{Eq. 4})$$

and

$$d_{\text{Lens}} = d_o \frac{EFL}{u} \quad (\text{Eq. 5})$$

In other examples, OIS may be performed by moving the entire Tele camera, i.e. the Tele camera's components such as lens, image sensor etc. do not move relative to each other for performing OIS, but they move together relative to device **1600**. Device **1600** comprises an application processor (AP) **1620** that includes a depth estimator **1622**, an OIS controller **1624** and a microcontroller unit (MCU, not shown). Device **1600** further comprises an IMU **1604**, at least one second camera **1630** and a memory **1640**. The MCU may be used to read and process data of IMU **1604**. In some examples, the MCU may be controlled by an OIS controller **1624** which is part of AP **1620**. Camera **1630** may e.g. be a W camera or an UW camera. FOV_W may e.g. be 60-90 degrees, FOV_{UW} may e.g. be 90-130 degrees. In other examples, **1600** may comprise additional cameras. The additional cameras may e.g. be a W camera, an UW camera, an additional Tele camera, a Time of Flight (ToF) camera. Memory **1640** may e.g. be a NVM (non-volatile memory) used to store calibration data. Calibration data may e.g. be for calibration between Tele camera **1610** and second camera **1630**. In other examples, calibration data may be stored in memory element **1640** and/or in additional memory elements (not shown). The additional memory elements may be integrated in the camera **1610** and in the second camera **1630** or only in one of the camera modules and may be EEPROMs (electrically erasable programmable read-only memory). Memory **1640** may also store image data, depth data or metadata of a specific scene, scene segment or object. Metadata may e.g. be one or more depth values.

[0168] Another example of a device numbered **1650** and operative to perform OIS for correcting undesired linear motion in X and Y direction as described herein is shown in FIG. 16B. Device **1650** includes a MCU **1630** which is configured for reading and processing motion data provided by IMU **1604** and for reading and supplying OIS control signals to the Tele camera **1610**, i.e. reading and processing of data from position sensor **1614** and supplying control signals to the driver of actuator **1612**.

[0169] For depth estimation, image data from Tele camera **1610** or from camera **1630** or from additional cameras or components is transmitted to the depth estimator **1622**. Depth estimator **1622** calculates depth as known in the art. In some examples, depth estimator **1622** calculates a depth map of the entire scene covered by FOV_T . In other examples, depth estimator **1622** calculates a depth map of the image segments of the scene that include a specific object of interest (OOI) or object of interest (ROI). In yet other examples, depth estimator **1622** calculates a single

value only, whereas the single value corresponds to a depth range of an object in focus. In yet other examples, depth information may be provided by a laser range finder (“Laser AF”) which performs a Time-of-Flight measurement. Image data transmitted to the depth estimator **1622** may e.g. be:

- [0170] Phase detection auto focus (PDAF) data from the second camera **1630**;
- [0171] PDAF data from the Tele camera **1610**;
- [0172] Stereo image data, e.g. from Tele camera **1610** and from second camera **1630**;
- [0173] Focus stacking visual image data;
- [0174] Focus stacking PDAF data;
- [0175] Visual image data from Tele camera **1610** and/or from second camera **1630** (for estimating depth from defocus);
- [0176] Visual image data from Tele camera **1610** and/or from second camera **1630** (for estimating depth from object motion);
- [0177] Depth data from second camera **1630** that may be a Time of Flight (ToF) camera.
- [0178] In some examples, visual image data from Tele camera **1610** and/or from camera **1630** may be used to estimate depth from motion, e.g. from a pre-view video stream comprising a plurality of images. Depth from motion may be estimated by turning OIS off, estimating do between two or more frames from IMU information, estimating d_s from the movement of an image point between two or more frames and estimating u according to eq. 3.
- [0179] OIS controller **1624** receives data on the linear acceleration of device **1600** from IMU **1604** and depth data on u of the object in focus (or larger segments of the scene) from depth estimator **1622**. For OIS on undesired linear motion in X and Y, OIS controller **1624** and/or a MCU such as MCU **1630** estimates do from the IMU’s data on linear acceleration and calculates d_s or d_L for sensor shift OIS or lens shift OIS respectively according to eq. 3 or eq. 5 respectively. OIS controller **1624** and/or MCU **1630** transmit control signals to actuator **1612**. Actuator **1612** may actuate an image sensor for sensor shift OIS and/or a lens for

lens shift OIS. OIS controller **1624** and/or MCU **1630** receive data on the position of lens **1616** (for lens shift OIS) or image sensor **1618** (for sensor shift OIS) from position sensors **1614** for performing closed loop control.

[0180] In all the lens examples, the EFL of the entire G1 group is marked EFL_{G1} (or “EFL(G1)”), the EFL of the entire G2 group is marked EFL_{G2} and focal lengths of individual lens elements are marked by the element number, i.e. the power of L1 is marked f_1 the focal length of L2 is marked f_2 , etc.

[0181] A mean glass thickness (“MGT”) of a lens group or an entire lens is defined by the average thickness of the single lens elements it includes. The mean glass thickness of a group, e.g. G1, is marked “MGT (G1)”, while the mean glass thickness of an entire lens is marked “MGT”.

[0182] A mean air gap (“MAG”) of a lens group or an entire lens is defined by the average thickness of the air gaps along the optical axis between the single lens elements within its lens groups G1 and G2. This means that calculating the mean air gap takes into account only intra-lens group distances but not distances between lens groups. Specifically BG, BG1, BG2 and BFL are not considered for calculating MAG. The mean air gap of a group, e.g. G1, is marked “MAG(G1)”, while the mean air gap of an entire lens is marked “MAG”.

[0183] All pop-out optical lens systems described below may be focused by moving an entire lens with respect to an image sensor.

[0184] Table 22 summarizes values and ratios thereof of various features that are included in the lens systems shown above and in the following (TTL, c-TTL, EFL, f, BG, c-BG, BFL, c-BFL, TG1, TG2, T1, T3, MGT, MAG given in mm, H-FOV given in degrees). For c-TTL, a minimum value is given. “P-O method” refers to the method used for switching the respective lens system between a pop-out and a collapsed state, wherein the number “i” refers to the i-th method embodiment (e.g. “1” refers to switching according to a 1st method embodiment, “2” refers to switching according to a 2nd method embodiment, etc.).

TABLE 22

	1700	1800	1900	2000	2100	Min. value	Max. value
TTL	12.50	10.86	12.50	12.50	12.50	10.86	12.50
c-TTL	7.78	7.08	7.80	8.13	7.50	7.08	8.13
EFL	13.90	11.94	14.60	14.70	13.90	11.94	14.70
BG	0.97	0.58	3.32	3.53	1.58	0.58	3.53
c-BG	0.97	0.58	0.75	1.00	0.20	0.20	1.00
BFL	5.52	5.00	2.88	2.60	0.85	0.85	5.52
c-BFL	0.81	1.21	0.75	0.75	0.85	0.75	1.21
TG1	3.68	2.76	3.73	3.91	3.46	2.76	3.91
TG2	2.33	2.54	2.57	2.47	2.14	2.14	2.57
H-FOV	13.40	16.80	12.80	12.70	13.50	12.70	16.80
EFL(G1)	11.71	8.57	10.29	10.31	9.95	8.57	11.71
EFL(G2)	-34.58	-16.24	-12.44	-13.01	-13.32	-34.58	-12.44
T1	2.30	1.25	2.08	2.12	1.44	1.25	2.30
T3	0.30	1.23	0.27	0.28	0.31	0.28	1.23
Lens power sequence	++----	+-----	++----	++----	++----		
MGT(G1)	1.19	0.90	1.21	0.94	1.09	0.90	1.21
MGT(G2)	0.36	0.28	0.45	0.53	0.37	0.28	0.53
MGT	0.77	0.59	0.83	0.73	0.73	0.59	0.83
MAG(G1)	0.06	0.03	0.04	0.05	0.10	0.03	0.10

TABLE 22-continued

MAG(G2)	0.63	0.47	0.60	1.42	0.52	0.47	1.42
MAG	0.34	0.25	0.32	0.73	0.31	0.25	0.73
BFL/c-BFL	6.81	4.13	3.84	3.47	1.00	1.00	6.81
EFL(G1)/EFL(G2)	-0.34	-0.53	-0.83	-0.79	-0.75	-0.83	-0.34
EFL(G1)/EFL	0.84	0.72	0.70	0.70	0.72	0.70	0.84
EFL(G2)/EFL	-2.49	-1.36	-0.85	-0.89	-0.96	-2.49	-0.85
BG/TTL	0.08	0.05	0.27	0.28	0.13	0.05	0.28
BFL/TTL	0.44	0.46	0.23	0.21	0.07	0.07	0.46
c-TTL/TTL	0.62	0.65	0.62	0.65	0.60	0.60	0.65
TG1/TTL	0.29	0.25	0.30	0.31	0.28	0.25	0.31
TTL/EFL	0.90	0.91	0.86	0.85	0.90	0.85	0.91
T1/TTL	0.18	0.12	0.17	0.17	0.12	0.12	0.18
T1/MGT	2.99	2.12	2.55	2.90	1.97	1.97	2.99
T1/T3	7.67	1.02	5.17	5.17	4.65	1.02	7.67
TG1/(TTL-BFL)	0.53	0.47	0.39	0.39	0.30	0.30	0.53
MGT(G1)/MGT	1.55	1.53	1.46	1.29	1.49	1.29	1.55
MGT(G2)/MGT	0.47	0.47	0.54	0.73	0.51	0.47	0.73
MGT(G1)/MGT(G2)	3.31	3.21	2.69	1.77	2.95	1.77	3.31
MAG/MAG(G1)	5.67	8.33	8.00	14.60	3.10	3.10	14.60
MAG/MAG(G2)	0.54	0.53	0.53	0.51	0.60	0.51	0.60
MAG(G2)/MAG(G1)	10.50	15.67	15.00	28.40	5.20	5.20	28.40
MAG/MGT	0.44	0.42	0.39	1.00	0.42	0.39	1.00
MAG(G1)/MGT(G1)	0.05	0.03	0.03	0.05	0.09	0.03	0.09
MAG(G2)/MGT(G2)	1.75	1.68	1.33	2.68	1.41	1.33	2.68
P-O method	2	2	3	3	4		

	800	850	900	1000	1100 Tele	1100 Macro	1200 Tele	1200 Macro	1300 Tele	1300 Macro	MIN	MAX
TTL	19.84	13.50	7.78	15.00	15.00	20.90	15.00	20.90	15.80	20.40	7.78	20.90
c-TTL	12.60	5.00	3.60	6.20	8.50	8.50	8.90	8.90	9.50	9.50	3.60	12.60
EFL	13.00	15.15	7.97	16.00	14.98	14.80	15.00	9.80	15.00	15.00	7.97	16.00
BG	6.22	1.78	0.97	1.55	1.91	1.44	5.07	2.91	2.63	1.30	0.97	6.22
BG2							4.81	9.18			4.81	9.18
BFL	1.02	5.49	3.27	6.99	0.59	6.96	0.95	0.95	0.84	6.82	0.59	6.99
BG/TTL	0.31	0.13	0.12	0.10	0.13	0.07	0.34	0.14	0.17	0.06	0.06	0.34
BFL/TTL	0.05	0.41	0.42	0.47	0.04	0.33	0.06	0.05	0.05	0.33	0.04	0.47
c-TTL/TTL	0.64	0.37	0.46	0.41	0.57	0.41	0.59	0.43	0.60	0.47	0.37	0.64
TTL/EFL	1.53	0.89	0.98	0.94	1.00	1.41	1.00	2.13	1.05	1.36	0.89	2.13
Number	8	6	5	5	6	6	6	6	6	6	5	8
lenses												
Number	2	2	2	2	2	2	3	3	2	2	2	3
lens groups												
Number	2	2	2	2	3	3	2	2	2	2	2	3
collapsible												
air gaps												
P-O method	1	2, 3	2, 3	2, 3	4	4	4	4	4	4		

[0185] FIG. 17A shows an example of a pop-out optical lens system disclosed herein and numbered **1700** in a pop-out state. Lens system **1700** comprises a pop-out lens **206-8** divided into two lens groups G1 and G2, an image sensor **208** and, optionally, an optical element (“window”) **802**. FIG. 17B shows pop-out optical lens system **1700** in a collapsed state.

[0186] Optical element **802** may be for example infra-red (IR) filter, and/or a glass image sensor dust cover. Optical rays pass through lens **206-8** and form an image on image sensor **208**. FIG. 17A shows 3 fields with 3 rays for each: the upper marginal-ray, the lower marginal-ray and the chief-ray. All further figures show these 3 rays as well.

[0187] Detailed optical data and surface data for pop-out lens **206-8** are given in Tables 23-26. Table 23 provides surface types, Table 24 provides aspheric coefficients, and Table 25 shows the BFL (“T”) for lens **206-8** being in a pop-out state and c-BFL for lens **206-8** being in a collapsed state. Table 26 shows the distance of a first, second and third deflection point (“DP1”, “DP2” and “DP3”) respectively from the optical axis for lens elements L_{N-1} and L_N .

[0188] The surface types are:

[0189] a) Plano: flat surfaces, no curvature

[0190] b) Q type 1 (QT1) surface sag formula:

$$z(r) = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + D_{con}(u) \quad (\text{Eq. 1})$$

$$D_{con}(u) = u^4 \sum_{n=0}^N A_n Q_n^{con}(u^2)$$

$$u = \frac{r}{r_{norm}}, x = u^2$$

$$Q_0^{con}(x) = 1 \quad Q_1^{con} = -(5-6x) \quad Q_2^{con} = 15-14x(3-2x)$$

$$Q_3^{con} = -(35-12x[14-x(21-10x)])$$

$$Q_4^{con} = 70-3x[168-5x[84-11x(8-3x)]]$$

$$Q_5^{con} = -[126-x(1260-11x[420-x[720-13x(45-14x)]])]$$

where {z, r} are the standard cylindrical polar coordinates, c is the paraxial curvature of the surface, k is the conic parameter, r_{norm} is generally one half of the surface’s clear

aperture (CA), and A_n are the aspheric coefficients shown in lens data tables. The Z axis is positive towards image. Values for CA are given as a clear aperture radius, i.e. D/2. The reference wavelength is 555.0 nm. Units are in mm except for refraction index ("Index") and Abbe #. Each lens element Li has a respective focal length f_i , and all lens elements of a group Gi together have a respective focal length f_i , both given in Table 23. The FOV is given as half FOV (HFOV). The definitions for surface types, Z axis, CA values, reference wavelength, units, focal length and HFOV are valid for all following Tables.

TABLE 23

EFL = 13.9 mm, F# = 2, HFOv = 13.4 deg, Sensor Height Full Diagonal = 6.5 mm										
Group	Lens	Surface	Type	R [mm]	T [mm]	D/2 [mm]	Nd	Vd	Focal Length [mm]	
G1	Object Stop	S ₀	Flat	Infinity	Infinity					
		S ₁	Flat	Infinity	-1.72	3.47				
		S ₂	QTYP	4.64	2.31	3.47	1.54	55.99	8.56	11.71
	L1	S ₃	QTYP	15.13	0.05	3.31				
		S ₄	QTYP	7.31	0.96	3.09	1.51	56.81	14.08	
		S ₅	QTYP	-851.44	0.06	2.96				
L3	S ₆	QTYP	-24.50	0.30	2.73	1.66	20.27	-7.31		
	S ₇	QTYP	6.11	0.97	2.25					
	G2	L4	S ₈	QTYP	4.75	0.28	2.00	1.53	56.16	-67.48
S ₉			QTYP	4.11	1.19	1.83				
S ₁₀			QTYP	-2.36	0.28	1.76	1.54	55.93	-8.83	
L5	S ₁₁	QTYP	-4.81	0.08	1.96					
	L6	S ₁₂	QTYP	4.07	0.51	1.98	1.66	20.37	10.38	
		S ₁₃	QTYP	9.40	See Table 25	2.12				
Glass window	S ₁₄	Flat	Infinity	0.11		1.52	64.17			
	S ₁₅	Flat	Infinity	0.39						
Image sensor	S ₁₆									

TABLE 25

		On State (Pop Out)	Off State (Collapsed)
T [mm]	S ₁₃	5.0156	0.2144

TABLE 26

		DP1 [mm]	DP2 [mm]	DP3 [mm]
L6	S ₁₂	0.5001	1.6672	N/A
	S ₁₃	0.5902	N/A	N/A

Table 24 shows the aspheric coefficients.

TABLE 24

Surface	Conic (k)	NR	A ₀	A ₁	A ₂	A ₃
S ₂	0.00E+00	3.74E+00	1.05E+00	-3.12E-01	1.88E-02	5.78E-02
S ₃	0.00E+00	3.34E+00	-1.17E-01	-5.93E-02	-8.16E-03	1.01E-02
S ₄	0.00E+00	3.28E+00	-9.90E-02	-2.37E-03	-1.87E-02	-1.24E-02
S ₅	0.00E+00	3.08E+00	-4.11E-02	2.68E-02	-1.53E-02	-9.81E-03
S ₆	0.00E+00	2.80E+00	3.89E-01	-1.16E-02	-7.22E-03	7.80E-03
S ₇	0.00E+00	2.18E+00	2.09E-01	3.99E-02	-1.44E-02	2.71E-03
S ₈	0.00E+00	2.19E+00	-7.23E-02	1.77E-01	-6.07E-02	-7.24E-03
S ₉	0.00E+00	2.00E+00	-3.32E-02	1.14E-01	-5.52E-02	-2.03E-02
S ₁₀	0.00E+00	1.94E+00	5.79E-01	-2.43E-01	-2.56E-02	-3.33E-02
S ₁₁	0.00E+00	2.04E+00	3.33E-01	-1.98E-01	1.11E-02	4.27E-03
S ₁₂	0.00E+00	2.25E+00	-1.23E+00	1.41E-02	-2.02E-02	3.84E-03
S ₁₃	0.00E+00	2.29E+00	-9.54E-01	2.44E-02	-1.08E-02	3.70E-03
Surface	A ₄	A ₅	A ₆	A ₇	A ₈	
S ₂	-3.56E-02	5.97E-03	4.36E-03	-3.56E-03	1.04E-03	
S ₃	-5.46E-03	2.97E-03	-1.43E-03	4.94E-04	-8.28E-05	
S ₄	-1.87E-02	2.49E-03	-2.79E-03	6.86E-05	4.79E-05	
S ₅	-2.40E-03	2.79E-03	-1.11E-03	5.21E-04	-1.37E-04	
S ₆	-3.11E-03	-2.70E-04	8.21E-04	-2.32E-04	5.68E-05	
S ₇	1.70E-03	-1.06E-03	-5.85E-05	2.45E-05	2.71E-05	
S ₈	-1.53E-02	-7.79E-03	-1.79E-03	-8.27E-04	-5.60E-05	
S ₉	-2.15E-02	-1.26E-02	-5.18E-03	-1.83E-03	-4.49E-04	
S ₁₀	-1.51E-02	-7.29E-03	-1.93E-03	-5.05E-04	5.89E-05	
S ₁₁	-3.92E-03	4.72E-04	-4.90E-04	3.78E-04	-5.23E-05	
S ₁₂	-2.17E-02	-8.24E-03	-3.14E-03	5.49E-04	-2.74E-04	
S ₁₃	-5.43E-03	-2.52E-03	-1.44E-03	-2.31E-04	-1.55E-04	

TABLE 26-continued

		DP1 [mm]	DP2 [mm]	DP3 [mm]
L7	S ₁₄	2.0629	N/A	N/A
	S ₁₅	0.1689	1.1203	2.0314

[0191] FIG. 18A shows another embodiment of a pop-out optical lens system disclosed herein and numbered **1800**. FIG. 18B shows pop-out optical lens system **1800** in a collapsed state. Lens system **1800** comprises a pop-out lens **206-9** divided into two lens groups G1 and G2, an image sensor **208** and, optionally, an optical element **802**. Table 27 provides surface types, Table 28 provides aspheric coefficients, Table 29 shows the BFL and c-BFL and Table 30 shows the deflection point distances from the optical axis.

TABLE 27

EFL = 11.94 mm, F# = 2.08, HfOV = 16.8 deg, Sensor Height Full Diagonal = 7 mm										
Group	Lens	Surface	Type	R [mm]	T [mm]	D/2 [mm]	Nd	Vd	Focal Length [mm]	
Object	Stop	S ₀	Flat	Infinity	Infinity					
		S ₁	Flat	Infinity	-1.29	2.87				
G1	L1	S ₂	QTYT	3.31	1.25	2.87	1.54	55.91	13.76	8.57
		S ₃	QTYT	5.11	0.03	2.77				
		S ₄	QTYT	3.48	0.21	2.64	1.67	19.44	-17.72	
	L2	S ₅	QTYT	2.63	0.03	2.42				
		S ₆	QTYT	2.61	1.23	2.41	1.54	55.91	9.48	
		S ₇	QTYT	4.38	0.58	2.23				
G2	L4	S ₈	QTYT	24.80	0.21	1.85	1.66	20.37	-126.21	-16.24
		S ₉	QTYT	19.09	0.58	1.64				
		S ₁₀	QTYT	-22.16	0.21	1.65	1.64	23.53	-10.42	
	L5	S ₁₁	QTYT	9.68	0.75	1.62				
		S ₁₂	QTYT	2.87	0.22	1.72	1.54	56.18	-23.25	
		S ₁₃	QTYT	2.28	0.10	1.90				
	L7	S ₁₄	QTYT	7.40	0.48	2.19	1.67	19.44	11.69	
		S ₁₅	QTYT	115.56	See Table 29	2.23				
Glass window		S ₁₆	Flat	Infinity	0.21		1.52	64.17		
		S ₁₇	Flat	Infinity	0.30					
Image sensor		S ₁₈								

TABLE 28

Surface	Conic (k)	NR	A ₀	A ₁	A ₂	A ₃
S ₂	0	2.21E+00	-4.24E-02	-7.81E-03	-8.54E-04	5.91E-05
S ₃	0	2.21E+00	-2.22E-01	3.42E-02	-2.36E-03	6.05E-05
S ₄	0	1.56E+00	-8.85E-02	5.13E-03	4.16E-04	-1.19E-04
S ₅	0	2.21E+00	-3.27E-01	4.50E-02	5.36E-03	-2.18E-03
S ₆	0	1.56E+00	-1.08E-01	2.21E-03	4.34E-04	2.13E-04
S ₇	0	1.56E+00	-5.97E-02	2.50E-03	3.62E-04	2.70E-04
S ₈	0	1.52E+00	1.22E-01	8.04E-03	-1.60E-03	8.07E-04
S ₉	0	1.52E+00	2.53E-01	2.11E-02	1.25E-03	1.53E-03
S ₁₀	0	1.63E+00	9.13E-02	1.50E-02	-6.30E-04	1.66E-03
S ₁₁	0	1.63E+00	2.11E-02	2.33E-02	-2.91E-03	1.68E-03
S ₁₂	0	1.47E+00	-5.03E-01	1.75E-02	-5.67E-04	-8.94E-04
S ₁₃	0	1.47E+00	-4.88E-01	1.82E-02	-2.08E-03	-2.28E-04
S ₁₄	0	1.49E+00	-5.09E-02	1.08E-02	-2.14E-03	4.66E-04
S ₁₅	0	1.49E+00	-4.51E-02	1.15E-02	-1.27E-03	1.12E-04
Surface	A ₄		A ₅	A ₆	A ₇	
S ₂	-3.02E-06		-1.32E-05	1.12E-06	3.76E-08	
S ₃	-2.45E-04		6.08E-05	-6.27E-06	4.05E-07	
S ₄	1.49E-05		-7.22E-07	-3.42E-09	1.07E-10	
S ₅	-2.66E-04		-3.74E-04	-1.20E-04	-7.15E-06	
S ₆	-5.64E-05		6.68E-06	-4.46E-07	-4.18E-09	
S ₇	-1.78E-04		2.85E-05	-1.67E-06	2.44E-08	
S ₈	-5.47E-04		1.41E-04	-1.73E-05	7.96E-07	
S ₉	-4.28E-04		2.76E-04	-6.70E-06	2.25E-05	
S ₁₀	3.67E-04		3.20E-04	-2.29E-05	1.37E-05	
S ₁₁	4.08E-04		3.09E-04	-3.07E-05	3.00E-05	
S ₁₂	1.82E-04		2.78E-06	4.51E-06	1.14E-06	
S ₁₃	7.63E-05		-4.39E-07	-2.13E-06	2.57E-07	
S ₁₄	-8.85E-05		1.06E-05	-6.23E-07	8.60E-09	
S ₁₅	-3.53E-05		7.82E-06	-7.35E-07	2.27E-08	

TABLE 29

		On State (Pop Out)	Off State (Collapsed)
T [mm]	S ₁₅	4.4783	0.7000

TABLE 30

		DP1 [mm]	DP2 [mm]	DP3 [mm]
L6	S ₁₂	0.5001	1.6672	N/A
	S ₁₃	0.5902	N/A	N/A

TABLE 30-continued

		DP1 [mm]	DP2 [mm]	DP3 [mm]
L7	S ₁₄ S ₁₅	2.0629 0.1689	N/A 1.1203	N/A 2.0314

[0192] FIG. 19A shows yet another embodiment of a pop-out optical lens system disclosed herein and numbered **1900** in a pop-out state. FIG. 19B shows pop-out optical lens system **1900** in a collapsed state. Lens system **1900** comprises a pop-out lens **206-10** divided into two lens groups G1 and G2, an image sensor **208** and, optionally, an optical element **802**.

[0193] Table 31 provides surface types, Table 32 provides aspheric coefficients, and Table 33 shows the BG and the BFL for the pop-out state and the c-BG and the c-BFL for the collapsed state. Table 34 shows the deflection point distances from the optical axis.

TABLE 31

EFL = 14.6 mm, F# = 2, HFoV = 12.8 deg, Sensor Height Full Diagonal = 6.5 mm										
Group	Lens	Surface	Type	R [mm]	T [mm]	D/2 [mm]	Nd	Vd	Focal Length [mm]	
G1	Object Stop	S ₀	Flat	Infinity	Infinity					
		S ₁	Flat	Infinity	-1.5744	3.6595				
	L1	S ₂	QTYP	4.4361	2.0811	3.6595	1.5333	56.1625	10.5748	10.2898
		S ₃	QTYP	17.1831	0.0371	3.4917				
		L2	S ₄	QTYP	5.6555	1.2961	3.2810	1.5109	56.7467	14.9745
	S ₅		QTYP	19.8249	0.0505	3.1251				
	L3	S ₆	QTYP	-175.7762	0.2670	2.8113	1.6604	20.2676	-11.9103	
S ₇		QTYP	8.3152	See Table 33	2.3768					
G2	L4	S ₈	QTYP	-6.5426	0.2590	1.7889	1.5339	55.8284	-11.2510	-12.4375
		S ₉	QTYP	77.3828	1.1602	1.8648				
	L5	S ₁₀	QTYP	-15.1296	0.8481	2.0658	1.6080	25.6443	13.0264	
		S ₁₁	QTYP	-5.3338	0.0451	2.2702				
	L6	S ₁₂	QTYP	-7.5609	0.2554	2.6195	1.5437	55.9556	-14.3694	
		S ₁₃	QTYP	-216.3040	See Table 33	2.7044				
	Glass window Image sensor	S ₁₄	Flat	Infinity	0.1100		1.5168	64.1673		
S ₁₅		Flat	Infinity	0.3900						
S ₁₆										

TABLE 32

Surface	Conic (k)	NR	A ₀	A ₁	A ₂	A ₃
S ₂	0	3.63E+00	-2.91E-01	-8.05E-02	-2.62E-02	-4.27E-03
S ₃	0	3.48E+00	-2.65E-01	-7.73E-02	2.94E-02	-7.70E-03
S ₄	0	3.34E+00	-3.37E-01	-8.26E-02	4.49E-02	-1.18E-02
S ₅	0	3.25E+00	-4.14E-01	1.15E-02	7.94E-04	-3.69E-03
S ₆	0	2.80E+00	1.78E-01	-5.55E-02	1.16E-02	3.08E-03
S ₇	0	2.35E+00	2.66E-01	-5.92E-02	1.10E-02	-2.21E-03
S ₈	0	2.00E+00	9.75E-02	-1.02E-02	-2.53E-03	2.44E-03
S ₉	0	1.91E+00	7.56E-02	5.35E-03	-3.61E-03	2.18E-03
S ₁₀	0	1.97E+00	-2.06E-01	-7.41E-03	1.20E-02	1.23E-02
S ₁₁	0	2.23E+00	-7.22E-02	-6.08E-03	-4.02E-03	3.52E-03
S ₁₂	0	2.53E+00	-2.88E-01	3.29E-02	-9.09E-04	-1.65E-03
S ₁₃	0	2.56E+00	-5.32E-01	2.37E-02	1.08E-03	3.36E-03
Surface	A ₄	A ₅	A ₆	A ₇	A ₈	
S ₂	-1.06E-03	6.89E-04	2.45E-04	1.36E-04	-7.34E-05	
S ₃	-2.39E-03	6.73E-03	-4.20E-03	1.24E-03	-1.28E-04	
S ₄	-7.89E-03	1.05E-02	-3.05E-03	-3.70E-04	4.94E-04	
S ₅	-6.79E-03	1.08E-02	-5.13E-03	8.77E-04	1.17E-04	
S ₆	-2.71E-03	8.88E-04	-2.85E-04	1.16E-04	-2.50E-05	
S ₇	1.85E-03	-1.35E-03	5.37E-04	-3.12E-05	-2.07E-05	
S ₈	2.31E-04	-1.22E-05	-2.13E-04	7.09E-05	-6.57E-06	

TABLE 32-continued

S ₉	-5.62E-04	3.85E-04	-2.40E-04	5.87E-05	-4.84E-06
S ₁₀	9.85E-03	6.56E-03	3.37E-03	1.23E-03	3.22E-04
S ₁₁	4.14E-03	2.69E-03	7.37E-06	-4.58E-04	-2.90E-04
S ₁₂	-3.35E-03	-1.95E-03	-8.35E-04	-2.85E-04	-3.85E-05
S ₁₃	-4.54E-04	-5.31E-04	-6.51E-04	-2.79E-04	-1.69E-04

TABLE 33

		On State (Pop Out)	Off State (Collapsed)
T [mm]	S ₉	3.3200	0.7500
	S ₁₃	2.3809	0.2500

TABLE 34

		DP1 [mm]	DP2 [mm]	DP3 [mm]
L5	S ₁₀	1.9372	N/A	N/A
	S ₁₁	2.1333	N/A	N/A
L6	S ₁₂	2.1267	N/A	N/A
	S ₁₃	2.5492	N/A	N/A

[0194] FIG. 20A shows yet another embodiment of a pop-out optical lens system disclosed herein and numbered **2000** in a pop-out state. FIG. 20B shows pop-out optical lens system **2000** in a collapsed state. Lens system **2000** comprises a pop-out lens **206-11** divided into two lens groups G1 and G2, an image sensor **208** and, optionally, an optical element **802**.

[0195] Table 35 provides surface types, Table 36 provides aspheric coefficients, and Table 37 shows the BG and the BFL for the pop-out state and the c-BG and the c-BFL for collapsed state. Table 38 shows the deflection point distances from the optical axis.

[0196] The focal length of L3+L4 together is $f_{3+4} = -17.34$.

TABLE 35

EFL = 14.7 mm, F# = 2, HFOV = 12.7 deg, Sensor Height Full Diagonal = 6.5 mm									
Lens	Surface	Type	R [mm]	T [mm]	D/2 [mm]	Nd	Vd	Focal Length [mm]	
G1	Object	S ₀	Flat	Infinity	Infinity				
	Stop	S ₁	Flat	Infinity	-1.56	3.68			
	L1	S ₂	QTYP	4.30	2.12	3.68	1.53	56.16	11.37
		S ₃	QTYP	12.20	0.05	3.55			
	L2	S ₄	QTYP	5.78	0.95	3.32	1.54	55.99	18.93
		S ₅	QTYP	12.34	0.06	3.22			
	L3	S ₆	QTYP	31.14	0.28	2.97	1.67	19.44	-13.96
		S ₇	QTYP	7.21	0.05	2.60			-17.34
	L4	S ₈	QTYP	5.77	0.41	2.55	1.51	56.81	64.80
		S ₉	QTYP	6.81	See Table 37	2.40			
G2	L5	S ₁₀	QTYP	-11.79	0.28	1.72	1.54	55.90	-7.33
		S ₁₁	QTYP	6.11	1.42	1.84			-13.01
	L6	S ₁₂	QTYP	12.04	0.77	2.34	1.61	25.64	20.17
		S ₁₃	QTYP	466.66	See Table 37	2.46			
	Glass window	S ₁₄	Flat	Infinity	0.11		1.52	64.17	
Image sensor		S ₁₅	Flat	Infinity	0.39				

TABLE 36

Surface	Conic (k)	NR	A ₀	A ₁	A ₂	A ₃
S ₂	0	3.63E+00	-2.91E-01	-8.05E-02	-2.62E-02	-4.27E-03
S ₃	0	3.48E+00	-2.65E-01	-7.73E-02	2.94E-02	-7.70E-03
S ₄	0	3.34E+00	-3.37E-01	-8.26E-02	4.49E-02	-1.18E-02
S ₅	0	3.25E+00	-4.14E-01	1.15E-02	7.94E-04	-3.69E-03
S ₆	0	2.80E+00	1.78E-01	-5.55E-02	1.16E-02	3.08E-03
S ₇	0	2.35E+00	2.66E-01	-5.92E-02	1.10E-02	-2.21E-03
S ₈	0	2.00E+00	9.75E-02	-1.02E-02	-2.53E-03	2.44E-03
S ₉	0	1.91E+00	7.56E-02	5.35E-03	-3.61E-03	2.18E-03
S ₁₀	0	1.97E+00	-2.06E-01	-7.41E-03	1.20E-02	1.23E-02
S ₁₁	0	2.23E+00	-7.22E-02	-6.08E-03	-4.02E-03	3.52E-03
S ₁₂	0	2.53E+00	-2.88E-01	3.29E-02	-9.09E-04	-1.65E-03
S ₁₃	0	2.56E+00	-5.32E-01	2.37E-02	1.08E-03	3.36E-03

TABLE 36-continued

Surface	A ₄	A ₅	A ₆	A ₇	A ₈
S ₂	-1.06E-03	6.89E-04	2.45E-04	1.36E-04	-7.34E-05
S ₃	-2.39E-03	6.73E-03	-4.20E-03	1.24E-03	-1.28E-04
S ₄	-7.89E-03	1.05E-02	-3.05E-03	-3.70E-04	4.94E-04
S ₅	-6.79E-03	1.08E-02	-5.13E-03	8.77E-04	1.17E-04
S ₆	-2.71E-03	8.88E-04	-2.85E-04	1.16E-04	-2.50E-05
S ₇	1.85E-03	-1.35E-03	5.37E-04	-3.12E-05	-2.07E-05
S ₈	2.31E-04	-1.22E-05	-2.13E-04	7.09E-05	-6.57E-06
S ₉	-5.62E-04	3.85E-04	-2.40E-04	5.87E-05	-4.84E-06
S ₁₀	9.85E-03	6.56E-03	3.37E-03	1.23E-03	3.22E-04
S ₁₁	4.14E-03	2.69E-03	7.37E-06	-4.58E-04	-2.90E-04
S ₁₂	-3.35E-03	-1.95E-03	-8.35E-04	-2.85E-04	-3.85E-05
S ₁₃	-4.54E-04	-5.31E-04	-6.51E-04	-2.79E-04	-1.69E-04

TABLE 37

		On State (Pop Out)	Off State (Collapsed)
T [mm]	S ₉	3.5280	1.0000
	S ₁₃	2.0865	0.2500

TABLE 38

		DP1 [mm]	DP2 [mm]	DP3 [mm]
L5	S ₁₀	N/A	N/A	N/A
	S ₁₁	1.7781	N/A	N/A

TABLE 38-continued

		DP1 [mm]	DP2 [mm]	DP3 [mm]
L6	S ₁₂	0.8539	2.1100	N/A
	S ₁₃	0.0957	N/A	N/A

FIG. 21A shows yet another embodiment of a pop-out optical lens system disclosed herein and numbered **2100** in a pop-out state. FIG. 21B shows pop-out optical lens system **2100** in a collapsed state. Lens system **2100** comprises a pop-out lens **206-12** which is divided into three lens groups G1, G2 and Field lens **808**, an image sensor **208** and, optionally, an optical element **802**.

[0197] Table 39 provides surface types, Table 40 provides aspheric coefficients, and Table 41 shows BG1 and BG2 for the pop-out state and c-BG1 and c-BG2 for collapsed state. Table 42 shows the deflection point distances from the optical axis.

TABLE 39

EFL = 13.9 mm, F# = 2, HFoV = 13.5 deg, Sensor Height Full Diagonal = 6.5 mm									
Group	Lens	Surface	Type	R [mm]	T [mm]	D/2 [mm]	Nd	Vd	Focal Length [mm]
	Object	S ₀	Flat	Infinity	Infinity				
		S ₁	Flat	Infinity	-1.66	3.47			
G1	L1	S ₂	QTYP	4.41	1.44	3.47	1.55	55.64	16.37
		S ₃	QTYP	7.27	0.05	3.33			9.95
	L2	S ₄	QTYP	4.32	1.51	3.23	1.51	56.81	7.82
		S ₅	QTYP	-52.11	0.15	3.05			
	L3	S ₆	QTYP	-3.92	0.31	2.82	1.67	19.44	-9.80
G2		S ₇	QTYP	-9.93	See Table 41	2.45			
		S ₈	QTYP	21.91	0.32	1.92	1.55	56.85	-27.93
	L4	S ₉	QTYP	8.97	0.99	1.76			-13.32
		S ₁₀	QTYP	-5.89	0.32	1.73	1.55	56.02	-11.76
	L5	S ₁₁	QTYP	-69.36	0.05	1.91			
	L6	S ₁₂	QTYP	3.04	0.46	1.94	1.67	19.44	19.56
		S ₁₃	QTYP	3.70	See Table 41	2.05			
	Field	S ₁₄	QTYP	15.39	0.47	3.29	1.67	19.44	-448.46
		S ₁₅	QTYP	14.47	0.54	3.30			
	Glass window	S ₁₆	Flat	Infinity	0.11		1.52	64.17	
	Image sensor	S ₁₇	Flat	Infinity	0.39				
		S ₁₈							

TABLE 40

Surface	Conic (k)	NR	A ₀	A ₁	A ₂	A ₃	A ₄
S ₂	0	3.52E+00	3.05E-01	-1.75E-01	1.08E-01	-5.69E-02	2.67E-02
S ₃	0	3.33E+00	-1.44E-01	9.96E-02	-6.22E-02	1.75E-02	-1.58E-02
S ₄	0	3.26E+00	-5.61E-01	1.16E-01	-5.80E-02	2.25E-02	-1.65E-02
S ₅	0	3.10E+00	2.25E-02	7.68E-04	-9.98E-04	-2.60E-03	-9.16E-04
S ₆	0	2.75E+00	1.38E+00	-2.15E-01	5.41E-02	-1.88E-02	6.37E-03
S ₇	0	2.32E+00	8.26E-01	-1.09E-01	2.21E-02	-8.06E-03	1.87E-03
S ₈	0	2.14E+00	3.84E-01	7.32E-02	-2.03E-02	-1.12E-03	-1.91E-03
S ₉	0	1.99E+00	2.37E-01	6.43E-02	-2.65E-02	-7.56E-03	-4.58E-03
S ₁₀	0	1.83E+00	1.22E-01	-8.70E-02	9.67E-03	-4.42E-03	2.08E-04
S ₁₁	0	1.97E+00	2.29E-01	-1.18E-01	2.15E-02	-5.51E-03	1.70E-03
S ₁₂	0	1.98E+00	-6.03E-01	1.22E-02	-1.01E-02	-1.09E-03	-1.71E-04
S ₁₃	0	2.10E+00	-6.99E-01	4.54E-02	-1.48E-02	1.08E-03	-8.96E-04
S ₁₄	0	3.30E+00	-8.94E-02	9.94E-02	-2.24E-02	-1.68E-03	-2.82E-03
S ₁₅	0	3.35E+00	-2.82E-01	1.19E-01	-3.61E-02	-4.14E-03	-5.42E-03

Surface	A ₅	A ₆	A ₇	A ₈	A ₉	A ₁₀
S ₂	-1.04E-02	4.42E-03	-2.44E-03	1.02E-03	-2.68E-04	-1.40E-07
S ₃	4.39E-03	-1.08E-03	3.34E-04	6.27E-05	—	—
S ₄	2.94E-03	-9.67E-04	3.08E-04	2.63E-04	—	—
S ₅	-5.21E-06	6.89E-04	-3.89E-04	-4.99E-06	—	—
S ₆	-2.07E-03	8.82E-04	-1.35E-04	-4.51E-05	—	—
S ₇	-2.41E-04	4.11E-05	4.76E-05	-2.17E-05	—	—
S ₈	-2.84E-04	-1.03E-04	-4.12E-06	-6.60E-06	—	—
S ₉	-1.24E-03	-3.84E-04	-6.86E-05	-2.03E-05	—	—
S ₁₀	-1.08E-04	2.49E-05	1.66E-05	4.91E-06	—	—
S ₁₁	7.12E-04	2.28E-04	1.31E-04	-1.71E-05	—	—
S ₁₂	7.13E-04	2.54E-04	1.50E-04	9.66E-06	—	—
S ₁₃	4.06E-04	-1.37E-05	5.28E-05	-1.11E-05	—	—
S ₁₄	3.35E-04	-5.87E-04	—	—	—	—
S ₁₅	5.37E-04	-8.14E-04	—	—	—	—

TABLE 41

		On State (Pop Out)	Off State (Collapsed)
T [mm]	S ₇	1.58	0.20
	S ₁₃	3.82	0.20

TABLE 42

		DP1 [mm]	DP2 [mm]	DP3 [mm]
L6	S ₁₂	0.8851	N/A	N/A
	S ₁₃	0.7231	N/A	N/A
L7	S ₁₄	3.1393	N/A	N/A
	S ₁₅	0.8056	1.8548	3.0509

While this disclosure has been described in terms of certain embodiments and generally associated methods, alterations and permutations of the embodiments and methods will be apparent to those skilled in the art. The disclosure is to be understood as not limited by the specific embodiments described herein, but only by the scope of the appended claims.

[0198] Unless otherwise stated, the use of the expression “and/or” between the last two members of a list of options for selection indicates that a selection of one or more of the listed options is appropriate and may be made.

[0199] It should be understood that where the claims or specification refer to “a” or “an” element, such reference is not to be construed as there being only one of that element.

[0200] Furthermore, for the sake of clarity the term “substantially” is used herein to imply the possibility of variations in values within an acceptable range. According to one

example, the term “substantially” used herein should be interpreted to imply possible variation of up to 5% over or under any specified value. According to another example, the term “substantially” used herein should be interpreted to imply possible variation of up to 2.5% over or under any specified value. According to a further example, the term “substantially” used herein should be interpreted to imply possible variation of up to 1% over or under any specified value.

[0201] All references mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual reference was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present disclosure.

What is claimed is:

1. A camera system, comprising:

- a camera comprising an image sensor and a lens, the camera having an effective focal length EFL in the range of 7 mm to 40 mm;
- a motion sensor for sensing an undesired linear motion of the camera system;
- a depth estimator for estimating the distance between the camera and an object; and
- an actuator operative to move the camera or a component of the camera to compensate for the undesired linear motion of the camera system, wherein the compensation depends on the undesired linear motion and on the distance between the camera and the object when the distance is smaller than 50 cm.

2. The camera system of claim 1, wherein the distance is smaller than 40 cm.

3. The camera system of claim 1, wherein the distance is smaller than 20 cm.

4. The camera system of claim 1, wherein $EFL \geq 9$ mm.

5. The camera system of claim 1, wherein $EFL \leq 30$ mm.

6. The camera system of claim 1, wherein the compensation for the undesired linear motion of the camera system is in two or more directions.

7. The camera system of claim 1, wherein the moving component is the lens.

8. The camera system of claim 1, wherein the moving component is the image sensor.

9. The camera system of claim 1, wherein the camera system is included in a mobile device.

10. The camera system of claim 9, wherein the mobile device is a smartphone.

11. A method for compensating for an undesired linear motion of a camera system, comprising:

providing a camera comprising an image sensor and a lens, the camera having an effective focal length EFL in the range of 7 mm to 40 mm;

providing a motion sensor for sensing the undesired linear motion of the camera system;

providing a depth estimator for estimating the distance between the camera and an object; and

moving the camera or a component of the camera to compensate for the undesired linear motion of the camera system, wherein the compensation depends on the undesired linear motion and on the distance between the camera and the object when the distance is smaller than 50 cm.

12. The method of claim 11, wherein the distance is smaller than 40 cm.

13. The method of claim 11, wherein the distance is smaller than 20 cm.

14. The method of claim 11, wherein $EFL \geq 9$ mm.

15. The method of claim 11, wherein $EFL \leq 30$ mm.

16. The method of claim 11, wherein the compensation for the undesired linear motion of the camera system is in two or more directions.

17. The method of claim 11, wherein the moving component is the lens.

18. The method of claim 11, wherein the moving component is the image sensor.

19. The method of claim 11, wherein the camera system is included in a mobile device.

20. The method of 19, wherein the mobile device is a smartphone.

* * * * *