

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395578
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Kang; Yitae

Electronic device comprising housing

Abstract

An electronic device is provided. The electronic device includes a display, a first plate, a side member disposed between the display and the first plate, a support member disposed inside the side member, a printed circuit board disposed between the support member and the first plate, and a second plate disposed between the first plate and the printed circuit board. The second plate includes a stacked structure including a first layer, formed at an edge portion of the second plate and extending from the second plate, and a second layer disposed on the first layer. A first protrusion portion of a first stacked structure may be at least partially inserted into a first opening of the support member, and a second protrusion portion of a second stacked structure may be at least partially inserted into a first locking groove of the support member.

Inventors:	Kang; Yitae (Suwon-si, KR)
Applicant:	Samsung Electronics Co., Ltd. (Suwon-si, KR)
Family ID:	1000008764993
Assignee:	Samsung Electronics Co., Ltd. (Suwon-si, KR)
Appl. No.:	18/169526
Filed:	February 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230199093 A1	Jun. 22, 2023

Foreign Application Priority Data

KR	10-2020-0150329	Nov. 11, 2020
----	-----------------	---------------

Related U.S. Application Data

Publication Classification**Int. Cl.:** H04M1/02 (20060101)**U.S. Cl.:****CPC** H04M1/0249 (20130101); H04M1/0266 (20130101); H04M1/0277 (20130101);**Field of Classification Search****CPC:** H04M (1/0249); H04M (1/0266); H04M (1/0277)**USPC:** 455/566

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7874534	12/2010	Kobayashi	N/A	N/A
8436256	12/2012	Kim et al.	N/A	N/A
9609099	12/2016	Lee et al.	N/A	N/A
9921367	12/2017	Jung	N/A	N/A
10034365	12/2017	Yang	N/A	N/A
10534405	12/2019	Kim	N/A	H05K 1/144
10716223	12/2019	Fordham	N/A	H05K 5/03
10971809	12/2020	Shin	N/A	H05K 1/147
11050136	12/2020	Jung	N/A	H04M 1/02
11245207	12/2021	Park	N/A	H01R 12/52
11246229	12/2021	Lee et al.	N/A	N/A
11984667	12/2023	Kim et al.	N/A	N/A
12081246	12/2023	Kim	N/A	H04B 1/40
2004/0244884	12/2003	Hideshima	148/610	C22C 38/04
2009/0165905	12/2008	Hideshima	148/621	C21D 8/0468
2017/0171960	12/2016	Yang	N/A	H05K 1/0216
2018/0299929	12/2017	Kim	N/A	G06F 1/1635
2018/0302994	12/2017	Fordham	N/A	G06F 1/1637
2020/0028241	12/2019	Jung	N/A	H01Q 1/44
2020/0225295	12/2019	Hyun	N/A	G06F 1/1656
2021/0288401	12/2020	Lee	N/A	H01Q 1/243

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004-095976	12/2003	JP	N/A
2008-103505	12/2007	JP	N/A
2008-300635	12/2007	JP	N/A
10-2004-0104939	12/2003	KR	N/A
10-0892531	12/2008	KR	N/A

10-2011-0045153	12/2010	KR	N/A
10-2012-0051169	12/2011	KR	N/A
10-2012-0115019	12/2011	KR	N/A
10-2014-0074652	12/2013	KR	N/A
10-2016-0016153	12/2015	KR	N/A
10-1633583	12/2015	KR	N/A
10-2017-0016649	12/2016	KR	N/A
10-2018-0031120	12/2017	KR	N/A
10-2019-0020971	12/2018	KR	N/A
10-2020-0015176	12/2019	KR	N/A
10-2020-0046246	12/2019	KR	N/A
10-2020-0093736	12/2019	KR	N/A
10-2020-0101018	12/2019	KR	N/A
10-2020-0101178	12/2019	KR	N/A
10-2020-0101218	12/2019	KR	N/A

OTHER PUBLICATIONS

International Search Report dated Feb. 25, 2022, issued in International Application No. PCT/KR2021/015217. cited by applicant

Korean Notice of Allowance dated Dec. 2, 2024, issued in Korean Patent Application No. 10-2020-0150329. cited by applicant

Primary Examiner: Gonzales; April G

Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No. PCT/KR2021/015217, filed on Oct. 27, 2021, which is based on and claims the benefit of a Korean patent application number 10-2020-0150329, filed on Nov. 11, 2020, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

(1) The disclosure relates to an electronic device including a housing.

2. Description of Related Art

(2) An electronic device may include a printed circuit board having various parts disposed thereon and a plate covering at least a portion of the printed circuit board.

(3) The plate may protect the printed circuit board from an external impact and may dissipate heat generated from other parts of the electronic device. Due to this, the plate may be required to be designed based on thermal conductivity for heat dissipation inside the electronic device as well as mechanical properties (e.g., stiffness) for protection of the printed circuit board.

(4) Furthermore, other parts, for example, an antenna that supports magnetic secure transmission (MST) and near field communication (NFC) may be disposed on the plate, and thus the mountability of the electronic device may be improved.

(5) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to

whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

(6) The plate may be fixed to the printed circuit board through a screw. However, there is no means for fixing the position of the plate on the printed circuit board before fastening the screw, and therefore movement of the plate may cause the screw to be loosely tightened or fastened at an inclined angle. In the case in which the screw is loosely tightened or fastened at an inclined angle, the plate may be lifted from the top of the printed circuit board. In this case, the plate cannot perform a function of protecting the printed circuit board, and a connector coupled with the printed circuit board may be pulled out. This is because the plate covers the connector coupled to the printed circuit board to prevent separation of the connector. In addition, an antenna disposed on the plate may be misaligned, and therefore the performance of the antenna may be degraded.

(7) Meanwhile, in a case in which the stiffness of the plate is insufficient, deformation, such as bending of the plate may occur. For example, a screw fastening portion of the plate subjected to a relatively large load may be vulnerable to deformation. To prevent this problem, an intermediate member, such as a washer, may be separately disposed between the screw head and the plate. Since the intermediate member is disposed in a form welded to the plate, it may cause an increase in process cost as well as material cost of the electronic device.

(8) Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide an electronic device including a housing.

(9) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(10) In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes a display that forms at least a portion of a front surface of the electronic device, a first plate that forms at least a portion of a rear surface of the electronic device, a side member that is disposed between the display and the first plate and that forms at least a portion of a side surface of the electronic device, a support member that is disposed inside the side member and that has a first opening and a first stopping recess formed therein, a printed circuit board disposed between the support member and the first plate, and a second plate that is disposed between the first plate and the printed circuit board and coupled with the support member and that covers at least a portion of the printed circuit board. The second plate includes a stacked structure that is formed on a periphery of the second plate and that includes a first layer that extends from the second plate and a second layer disposed on the first layer. The stacked structure includes a first stacked structure including a first protrusion that extends toward the display and a second stacked structure including a second protrusion that extends toward the side member. The first protrusion is at least partially inserted into the first opening of the support member, and the second protrusion is at least partially inserted into the first stopping recess of the support member.

(11) In accordance with another aspect of the disclosure, an electronic device is provided. The electronic device includes a display that forms at least a portion of a front surface of the electronic device, a first plate that forms at least a portion of a rear surface of the electronic device, a side member that is disposed between the display and the first plate and that forms at least a portion of a side surface of the electronic device, a support member that is disposed inside the side member and that has a first opening and a first stopping recess formed therein, a first printed circuit board disposed between the support member and the first plate, at least one connector disposed on the first printed circuit board, and a second plate that is disposed between the first plate and the first printed circuit board and coupled with the support member and that covers at least a portion of the first printed circuit board. The second plate includes a stacked structure that is formed on a periphery of the second plate and that includes a first layer that extends from the second plate and a second layer disposed on the first layer. The stacked structure includes a first stacked structure including a first protrusion that extends toward the display, a second stacked structure including a

second protrusion that extends toward the side member, and a third stacked structure that at least partially overlaps the at least one connector. The first protrusion is at least partially inserted into the first opening of the support member to restrict movement of the second plate in a horizontal direction, and the second protrusion is at least partially inserted into the first stopping recess of the support member to restrict movement of the second plate in a vertical direction.

(12) According to the embodiments of the disclosure, the durability of the plate may be improved by increasing the stiffness of the plate using the stacked structure.

(13) According to the embodiments of the disclosure, damage to the printed circuit board and/or separation of the connector connected to the printed circuit board may be prevented by preventing deformation of the plate using the stacked structure.

(14) According to the embodiments of the disclosure, the assembly performance of the plate may be improved by preventing movement of the plate through the protrusion of the stacked structure coupled with the support member.

(15) In addition, the disclosure may provide various effects that are directly or indirectly recognized.

(16) Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a perspective view of an electronic device as viewed in one direction according to an embodiment of the disclosure;

(3) FIG. 2 is a perspective view of an electronic device as viewed in another direction according to an embodiment of the disclosure;

(4) FIG. 3 is an exploded perspective view of an electronic device according to an embodiment of the disclosure;

(5) FIG. 4A illustrates an electronic device according to an embodiment of the disclosure;

(6) FIG. 4B illustrates an electronic device according to an embodiment of the disclosure;

(7) FIG. 4C illustrates an electronic device according to an embodiment of the disclosure;

(8) FIG. 5A illustrates a second plate and a first stacked structure of a second plate according to an embodiment of the disclosure;

(9) FIG. 5B illustrates a second plate and a first stacked structure of the second plate according to an embodiment of the disclosure;

(10) FIG. 5C is a sectional view illustrating a first stacked structure according to an embodiment of the disclosure;

(11) FIG. 6A illustrates a first stacked structure according to an embodiment of the disclosure;

(12) FIG. 6B illustrates a first stacked structure according to an embodiment of the disclosure;

(13) FIG. 6C illustrates a first stacked structure according to an embodiment of the disclosure;

(14) FIG. 7A illustrates a second plate and a second stacked structure of the second plate according to an embodiment of the disclosure;

(15) FIG. 7B illustrates a second plate and a second stacked structure of the second plate according to an embodiment of the disclosure;

(16) FIG. 7C is a sectional view illustrating a second stacked structure according to an embodiment of the disclosure;

- (17) FIG. 8 illustrates a second plate and a third stacked structure according to an embodiment of the disclosure;
- (18) FIG. 9A is a view illustrating a first stopping structure of an electronic device according to an embodiment of the disclosure;
- (19) FIG. 9B is a partial perspective view of a camera module and a second plate according to an embodiment of the disclosure;
- (20) FIG. 9C is a partial perspective view illustrating a state in which a camera module and a second plate are coupled according to an embodiment of the disclosure;
- (21) FIG. 10 illustrates a second stopping structure of an electronic device according to an embodiment of the disclosure;
- (22) FIG. 11 illustrates a third stopping structure of an electronic device according to an embodiment of the disclosure;
- (23) FIG. 12A illustrates a fourth stacked structure according to an embodiment of the disclosure;
- (24) FIG. 12B is a sectional view taken along line G-G' of FIG. 12A according to an embodiment of the disclosure; and
- (25) FIG. 13 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure.
- (26) Throughout the drawings, like reference numerals will be understood to refer to like parts, components and structures.

DETAILED DESCRIPTION

- (27) The following description with reference to accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.
- (28) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.
- (29) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.
- (30) FIG. 1 is a perspective view of an electronic device as viewed in one direction according to an embodiment of the disclosure.
- (31) FIG. 2 is a perspective view of an electronic device as viewed in another direction according to an embodiment of the disclosure.
- (32) Referring to FIGS. 1 and 2, the electronic device **100** according to an embodiment (e.g., an electronic device **1301** of FIG. 13) may include a housing **110** that includes a first surface (or, a front surface) **110A**, a second surface (or, a rear surface) **110B**, and a side surface **110C** surrounding a space between the first surface **110A** and the second surface **110B**. In another embodiment (not illustrated), the housing may refer to a structure that forms some of the first surface **110A**, the second surface **110B**, and the side surface **110C** of FIG. 1. According to an embodiment, the first surface **110A** may be formed by a front plate **102**, at least a portion of which is substantially transparent (e.g., a glass plate including various coating layers, or a polymer plate). The second surface **110B** may be formed by a back plate **111** that is substantially opaque. The back plate **111** may be formed of, for example, coated or colored glass, ceramic, a polymer, metal (e.g.,

aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the aforementioned materials. The side surface **110C** may be formed by a side bezel structure (or, a “side member”) **118** that is coupled with the front plate **102** and the back plate **111** and that includes metal and/or a polymer. In some embodiments, the back plate **111** and the side bezel structure **118** may be integrally formed with each other and may include the same material (e.g., a metallic material, such as aluminum).

(33) In the illustrated embodiment, the front plate **102** may include, at opposite long edges thereof, two first regions **110D** that curvedly and seamlessly extend from the first surface **110A** toward the back plate **111**. In the illustrated embodiment (refer to FIG. 2), the back plate **111** may include, at opposite long edges thereof, two second regions **110E** that curvedly and seamlessly extend from the second surface **110B** toward the front plate **102**. In some embodiments, the front plate **102** (or, the back plate **111**) may include only one of the first regions **110D** (or, the second regions **110E**). In another embodiment, a part of the first regions **110D** or the second regions **110E** may not be included. In the embodiments, when viewed from a side of the electronic device **100**, the side bezel structure **118** may have a first thickness (or, width) at sides not including the first regions **110D** or the second regions **110E** and may have a second thickness at sides including the first regions **110D** or the second regions **110E**, the second thickness being smaller than the first thickness.

(34) According to an embodiment, the electronic device **100** may include at least one of a display **101**, audio modules **103**, **107**, and **114**, sensor modules **104**, **116**, and **119**, camera modules **105**, **112**, and **113**, key input devices **117**, a light emitting element **106**, a pen input device **120**, or connector holes **108** and **109**. In some embodiments, the electronic device **100** may omit at least one component (e.g., the key input devices **117** or the light emitting element **106**) among the aforementioned components, or may additionally include other component(s).

(35) The display **101**, for example, may be exposed through most of the front plate **102**. In some embodiments, at least a portion of the display **101** may be exposed through the front plate **102** that forms the first surface **110A** and the first regions **110D** of the side surface **110C**. In some embodiments, the periphery of the display **101** may be formed to be substantially the same as the shape of the adjacent outside edge of the front plate **102**. In another embodiment (not illustrated), to expand the area by which the display **101** is exposed, the gap between the periphery of the display **101** and the periphery of the front plate **102** may be formed to be substantially constant.

(36) In another embodiment (not illustrated), a recess or opening may be formed in a portion of a screen display region of the display **101**, and the electronic device **100** may include at least one of the audio module **114**, the sensor module **104**, the camera module **105**, or the light emitting element **106** that is aligned with the recess or the opening. In another embodiment (not illustrated), the electronic device **100** may include, on a rear surface of the screen display region of the display **101**, at least one of the audio module **114**, the sensor module **104**, the camera module **105**, the fingerprint sensor **116**, or the light emitting element **106**. In another embodiment (not illustrated), the display **101** may be combined with, or disposed adjacent to, touch detection circuitry, a pressure sensor capable of measuring the intensity (pressure) of a touch, and/or a digitizer for detecting a stylus pen of a magnetic field type. In some embodiments, at least a part of the sensor modules **104** and **119** and/or at least a part of the key input devices **117** may be disposed in the first regions **110D** and/or the second regions **110E**.

(37) The audio modules **103**, **107**, and **114** may include the microphone hole **103** and the speaker holes **107** and **114**. A microphone for obtaining external sound may be disposed in the microphone hole **103**, and in some embodiments, a plurality of microphones may be disposed in the microphone hole **103** to detect the direction of sound. The speaker holes **107** and **114** may include the external speaker hole **107** and the receiver hole **114** for telephone call. In some embodiments, the speaker holes **107** and **114** and the microphone hole **103** may be implemented as a single hole, or without the speaker holes **107** and **114**, a speaker may be included (e.g., a piezoelectric speaker).

(38) The sensor modules **104**, **116**, and **119** may generate an electrical signal or a data value that

corresponds to an operational state inside the electronic device **100** or an environmental state external to the electronic device **100**. The sensor modules **104**, **116**, and **119** may include, for example, the first sensor module **104** (e.g., a proximity sensor) and/or the second sensor module (not illustrated) (e.g., a fingerprint sensor) that is disposed on the first surface **110A** of the housing **110**, and/or the third sensor module **119** (e.g., an HRM sensor) and/or the fourth sensor module **116** (e.g., a fingerprint sensor) that is disposed on the second surface **110B** of the housing **110**. The fingerprint sensor may be disposed not only on the first surface **110A** of the housing **110** (e.g., the display **101**) but also on the second surface **110B**. The electronic device **100** may further include a non-illustrated sensor module, for example, at least one of a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biosensor, a temperature sensor, a humidity sensor, or an illuminance sensor **104**.

(39) The camera modules **105**, **112**, and **113** may include the first camera device **105** disposed on the first surface **110A** of the electronic device **100**, and the second camera device **112** and/or the flash **113** disposed on the second surface **110B**. The camera devices **105** and **112** may include one or more lenses, an image sensor, and/or an image signal processor. The flash **113** may include, for example, a light emitting diode or a xenon lamp. In some embodiments, two or more lenses (an IR camera lens, a wide angle lens, and a telephoto lens) and image sensors may be disposed on one surface of the electronic device **100**.

(40) The key input devices **117** may be disposed on the side surface **110C** of the housing **110**. In another embodiment, the electronic device **100** may not include all or some of the aforementioned key input devices **117**, and the key input devices **117** not included may be implemented in a different form, such as a soft key, on the display **101**. In some embodiments, the key input devices may include the sensor module **116** disposed on the second surface **110B** of the housing **110**.

(41) The light emitting element **106**, for example, may be disposed on the first surface **110A** of the housing **110**. The light emitting element **106**, for example, may provide state information of the electronic device **100** in the form of light. In another embodiment, the light emitting element **106** may provide, for example, a light source that operates in conjunction with operation of the camera module **105**. The light emitting element **106** may include, for example, an LED, an IR LED, and a xenon lamp.

(42) The connector holes **108** and **109** may include the first connector hole **108** capable of accommodating a connector (e.g., a USB connector) for transmitting and receiving power and/or data with an external electronic device, and/or the second connector hole (e.g., an earphone jack) **109** capable of accommodating a connector for transmitting and receiving audio signals with an external electronic device.

(43) The pen input device **120** (e.g., a stylus pen) may be inserted into, or detached from, the housing **110** through a hole **121** formed in a side surface of the housing **110** and may include a button for facilitating the detachment. The pen input device **120** may have a separate resonance circuit embedded therein and may operate in conjunction with an electro-magnetic induction panel (e.g., a digitizer) included in the electronic device **100**. The pen input device **120** may include an electro-magnetic resonance (EMR) type, an active electrical stylus (AES) type, and an electric coupled resonance (ECR) type.

(44) FIG. 3 is an exploded perspective view of an electronic device according to an embodiment of the disclosure.

(45) Referring to FIG. 3, the electronic device **300** according to an embodiment (e.g., the electronic device **100** of FIGS. 1 and 2) may include a back plate **111** (or, a first plate **111**), a second plate **320**, a third plate **330**, at least one printed circuit board **340**, screws **390**, a first antenna **372**, a plurality of flexible printed circuit boards **345**, a battery **350**, a second antenna **376**, a side member **310** (e.g., the side bezel structure **118** of FIG. 1), a support member **311** (e.g., a bracket), a display panel **301**, and a front plate **111**.

(46) At least one of the components of the electronic device **300** may be identical or similar to at least one of the components of the electronic device **100** of FIG. **1** or FIG. **2**, and repetitive descriptions will hereinafter be omitted.

(47) In an embodiment, the second plate **320** may be disposed between the first plate **111** and the at least one printed circuit board **340**. For example, the second plate **320** may be disposed between the first plate **111** and a first printed circuit board **341**.

(48) In an embodiment, the first printed circuit board **341**, a second printed circuit board **342**, and a third printed circuit board **343** may be disposed between the first plate **111** and the support member **311**. In an embodiment, the first printed circuit board **341**, the second printed circuit board, and the third printed circuit board **343** may be electrically connected with one another. For example, the first printed circuit board **341** may be electrically connected with the second printed circuit board **342** and the third printed circuit board **343**. For example, the first printed circuit board **341** and the third printed circuit board **343** may be connected through at least one of the plurality of flexible printed circuit boards **345**. The first printed circuit board **341** and the second printed circuit board **342** may be electrically connected through a non-illustrated connecting member. For example, a structure formed to be coupled with the first printed circuit board **341** may be disposed on the second printed circuit board **342**, and by stacking the first printed circuit board **341** on the second printed circuit board **342**, the first printed circuit board **341** and the second printed circuit board **342** may be connected with each other through the structure. However, a method for electrically connecting the first printed circuit board **341**, the second printed circuit board **342**, and the third printed circuit board **343** is not limited by the above example, and various methods available to those skilled in the art may be applied.

(49) In an embodiment, various parts of the electronic device **300** may be disposed on the first printed circuit board **341** and/or the second printed circuit board **342**. For example, the first printed circuit board **341** and/or the second printed circuit board **342** may have a processor (e.g., **1320** of FIG. **13**) and/or a memory (e.g., **1330** of FIG. **13**) disposed thereon, but is not limited by the above example. For example, at least one of components of the electronic device **1301** of FIG. **13** may be disposed on the first printed circuit board **341** and/or the second printed circuit board **342**.

(50) In another embodiment, at least two of the first printed circuit board **341**, the second printed circuit board **342**, and/or the third printed circuit board **343** may be integrally formed, or one of the first printed circuit board **341**, the second printed circuit board **342**, and/or the third printed circuit board **343** may be omitted. For example, the first printed circuit board **341** and the second printed circuit board **342** may be integrally formed with each other.

(51) In an embodiment, the first antenna **372** may be disposed between the first plate **111** and the second plate **320**. In an embodiment, the first antenna **372** may be attached to the second plate **320**. In an embodiment, the first antenna **372** may include, for example, a near field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. For example, the first antenna **372** may include a loop antenna formed of a conductive coil to support short-range wireless communication and/or wireless power transmission/reception with an external device.

(52) In an embodiment, the third plate **330** may be disposed between the first plate **111** and the second printed circuit board **342**. In an embodiment, the third plate **330** may include an antenna radiator, such as a conductive pattern. In another embodiment, an antenna structure may be formed by a portion of the side member **310** together with the antenna radiator of the third plate **330**.

(53) In an embodiment, the second antenna **376** may be disposed adjacent to the side member **310**. In an embodiment, the second antenna **376** may include an array antenna including a plurality of antenna elements. In an embodiment, the second antenna **376** may be electrically connected with the first printed circuit board. In an embodiment, the second antenna **376** may support fifth-generation (5G) communication.

(54) In an embodiment, the side member **310** may be disposed between the first plate **111** and the

display panel **301**. The side member **310** may be formed to surround a space between the first plate **111** and the display panel **301**.

(55) In an embodiment, the support member **311** may be disposed inside the side member **310**. In an embodiment, the support member **311** may include, for example, a metallic material and/or a non-metallic (e.g., polymer) material.

(56) In an embodiment, the support member **311** may support several components of the electronic device **300**. For example, the support member **311** may support the second plate **320** and the at least one printed circuit board **340**. For example, the second printed circuit board **342** may be disposed on the support member **311** (e.g., the +z direction), and the first printed circuit board **341** may be disposed on the second printed circuit board **342** (e.g., the +z direction) to at least partially overlap the second printed circuit board **342**. The second plate **320** may be disposed on the first printed circuit board **341** (e.g., the +z direction) to at least partially overlap the first printed circuit board **341**. In an embodiment, the screws **390** may pass through at least one of the second plate **320**, the first printed circuit board **341**, and/or the second printed circuit board **342** and may be coupled to openings formed in the support member **311**, and thus the second plate **320**, the first printed circuit board **341**, and the second printed circuit board **342** may be coupled together and may be supported by the support member **311**.

(57) In an embodiment, the support member **311** may be integrally formed with the side member **310** and may extend from the side member **310** toward the inside of the electronic device **300**. In another embodiment, the support member **311** may be formed of a component separated from the side member **310** and may be coupled with the side member **310**.

(58) In an embodiment, the battery **350**, which is a device for supplying power to at least one component of the electronic device **300**, may include, for example, a primary cell that is not rechargeable, a secondary cell that is rechargeable, or a fuel cell. In an embodiment, the battery **350** may be at least partially accommodated in a space formed by the support member **311**.

(59) In an embodiment, the display panel **301** may be coupled with the side member **310** and/or the support member **311**.

(60) In an embodiment, the display panel **301** may include a front plate (e.g., the front plate **111** of FIG. 1), a display (e.g., the display **101** of FIG. 1) disposed on the front plate (e.g., the +z direction), and an electro-magnetic induction panel (e.g., a digitizer). In an embodiment, the electro-magnetic induction panel may be a panel for detecting an input of the pen input device (**120** of FIG. 2). In an embodiment, the electro-magnetic induction panel may include a coil and a shielding sheet. An input from the pen input device **120** may be transferred through the coil. The shielding sheet may prevent mutual interference between components due to electro-magnetic fields generated from the components (e.g., the display **101**) included in the electronic device **300**.

(61) FIG. 4A illustrates an electronic device according to an embodiment of the disclosure.

(62) FIG. 4A may be a view in which the first plate **111**, the second plate **320**, and the first antenna **372** are omitted.

(63) FIG. 4B illustrates an electronic device according to an embodiment of the disclosure.

(64) FIG. 4B may be a view in which the first plate **111** and the first antenna **372** are omitted.

(65) FIG. 4C illustrates an electronic device according to an embodiment of the disclosure.

(66) FIG. 4C may be a view in which the first plate **111** is omitted.

(67) Referring to FIG. 4A, the first printed circuit board **341** and the second printed circuit board **342** of the electronic device **300** according to an embodiment may partially overlap each other. For example, at least a portion of the first printed circuit board **341** may overlap the second printed circuit board **342**. In an embodiment, a portion of the second printed circuit board **342** may be covered by the first printed circuit board **341**, and a portion of the second printed circuit board **342** may be covered by the third plate **330**.

(68) In an embodiment, a plurality of connectors for operationally connecting various parts of the electronic device **300** may be disposed on the first printed circuit board **341**. For example, first to

seventh connectors **C1** to **C7** may be disposed on the first printed circuit board **341**.

(69) In an embodiment, signals for operating the electronic device **300** may be input and output through the first to seventh connectors **C1** to **C7**.

(70) For example, a radio frequency (RF) signal in a specified band may be transmitted and received through the first connector **C1**.

(71) For example, the second connector **C2** may be electrically connected with the battery **350**. A power management module (e.g., **1388** of FIG. **13**) disposed on the first printed circuit board **341** or the second printed circuit board **342** and the battery **350** may be electrically connected through the second connector **C2**. The power management module may provide power required for other parts of the electronic device **300** by using the battery **350**.

(72) For example, the third connector **C3** may electrically connect the first printed circuit board **341** and the third printed circuit board **343** to each other. In another example, an electrical signal related to an interface (e.g., a universal serial bus (USB)) may be input and output through the third connector **C3**.

(73) For example, the fourth connector **C4** may be electrically connected with the display **101**, and power and data (or, information) for displaying visual information using the display **101** may be provided through the fourth connector **C4**.

(74) For example, the fifth connector **C5** may be used to transmit and receive a signal related to the pen input device **120**. For example, an electrical signal for determining whether the pen input device **120** is accommodated in the electronic device **300** may be input and output through the fifth connector **C5**.

(75) For example, the sixth connector **C6** may be connected with the second antenna **376**. Through the sixth connector **C6**, power required for the second antenna **376** may be provided, a wireless signal desired to be transmitted to the second antenna **376** may be provided, or a wireless signal obtained from the second antenna **376** may be received.

(76) For example, the seventh connector **C7** may be connected with the electro-magnetic induction panel of the display panel **301**. A signal input to the electro-magnetic induction panel using the pen input device **120** may be provided through the seventh connector **C7**.

(77) However, configurations and functions of the first to seventh connectors **C1** to **C7** are not limited by the above examples, and various design changes may be possible. For example, one or more of the first to seventh connectors **C1** to **C7** may be disposed at positions different from those illustrated. In another example, one or more of the first to seventh connectors **C1** to **C7** may perform functions different from those described above. In another example, some of the first to seventh connectors **C1** to **C7** may be omitted, or other connector(s) not illustrated may be further included.

(78) Referring to FIG. **4B**, the second plate **320** according to an embodiment may be disposed on the first printed circuit board **341** by being coupled with the support member **311**. In an embodiment, the second plate **320** may be coupled with the support member **311** through at least one of the screws **390**.

(79) In an embodiment, the second plate **320** may overlap at least a portion of the first printed circuit board **341**. In an embodiment, the second plate **320** may protect the first printed circuit board **341** from an external impact by covering at least a portion of the first printed circuit board **341**.

(80) In an embodiment, the second plate **320** may be formed of a material having thermal conductivity appropriate for dissipating heat generated by various components (e.g., the second antenna **376**) of the electronic device **300**. For example, the second plate **320** may include a clad metal having copper disposed on a central portion thereof and stainless steel disposed on opposite sides of the central portion, but is not limited thereto.

(81) In an embodiment, the second plate **320** may overlap the first to seventh connectors **C1** to **C7** coupled with the first printed circuit board **341**. In an embodiment, the second plate **320** may

prevent separation of the first to seventh connectors C1 to C7 from the first printed circuit board **341**.

(82) In an embodiment, the second plate **320** may include a stacked structure **400**. In an embodiment, the stacked structure **400** may be formed on the periphery of the second plate **320**.

(83) In an embodiment, the stacked structure **400** may include a first stacked structure **410**, a second stacked structure **420**, and a third stacked structure **430**. Although not illustrated, the stacked structure **400** according to an embodiment may include a fourth stacked structure (e.g., a fourth stacked structure **440** of FIG. 12A).

(84) In an embodiment, the third stacked structure **430** may overlap at least some of the first to seventh connectors C1 to C7.

(85) In an embodiment, the positions and/or numbers of first stacked structures **410**, second stacked structure **420**, and third stacked structures **430** are not limited by the illustrated example.

(86) Referring to FIG. 4C, the first antenna **372** according to an embodiment may be disposed on the second plate **320**. In an embodiment, the first antenna **372** may include a first portion **3721** overlapping the second plate **320** and a second portion **3722** extending from the first portion **3721** to the third printed circuit board **343**. In an embodiment, the first antenna **372** may be attached to the second plate **320**. For example, the first portion **3721** of the first antenna **372** may be attached to the second plate **320** through an adhesive member, such as a double-sided tape. In an embodiment, the shape of the first portion **3721** may be substantially similar to the shape of the second plate **320**, but is not limited thereto.

(87) FIG. 5A illustrates a second plate and a first stacked structure of the second plate according to an embodiment of the disclosure.

(88) FIG. 5B illustrates a second plate and a first stacked structure of the second plate according to an embodiment of the disclosure.

(89) FIG. 5C is a sectional view illustrating a first stacked structure according to an embodiment of the disclosure. FIG. 5C may be a sectional view taken along line A-A' of FIG. 4B.

(90) Referring to FIGS. 5A, 5B, and 5C, the second plate **320** according to an embodiment may include a first surface **320A** and a second surface **320B**. The first antenna **372** may be disposed on the first surface **320A**, and the first printed circuit board **341** and the support member **311** may be disposed under the second surface **320B**. For example, the first antenna **372** may be disposed in the +z direction with respect to the second plate **320**, and the first printed circuit board **341** and the support member **311** may be disposed in the -z direction with respect to the second plate **320**.

(91) In an embodiment, the second plate **320** may include a first portion **3201** and a second portion **3202**. The first portion **3201** may be formed to be substantially flat. The second portion **3202** may be bent from the first portion **3201** and may extend from the first portion **3201** to have a height different from that of the first portion **3201**.

(92) In an embodiment, the second plate **320** may include the first stacked structure **410**. In an embodiment, the first stacked structure **410** may be formed on the periphery of the second plate **320**. For example, the first stacked structure **410** may be formed on the periphery of the second portion **3202**. In another example, unlike that illustrated, the first stacked structure **410** may be formed on the periphery of the first portion **3201**. In an embodiment, the first stacked structure **410** may be formed on the periphery of the second portion **3202** and may be located at a height different from that of the first portion **3201**. Alternatively, in another embodiment, the first stacked structure **410** may be formed on the periphery of the first portion **3201** and may be located at substantially the same height as the first portion **3201**.

(93) In an embodiment, the first stacked structure **410** may include a first layer **411**, a second layer **412**, a connecting portion **413**, and a first protrusion **415**.

(94) In an embodiment, the first layer **411** may extend from the second plate **320**. In an embodiment, the second layer **412** may be disposed on the first layer **411**. For example, the second layer **412** may be disposed on a surface of the first layer **411** that corresponds to the first surface

320A of the second plate **320**. In another example, the second layer **412** may be disposed on a surface of the first layer **411** that extends from the first surface **320A**. In another example, the second layer **412** may be disposed in the +z direction with respect to the first layer **411**.

(95) In an embodiment, the connecting portion **413** may extend from one end of the first layer **411** to one end of the second layer **412**.

(96) In an embodiment, the first protrusion **415** may extend from the second layer **412** toward the support member **311**. For example, the first protrusion **415** may extend from the second layer **412** toward the front surface of the electronic device **300** (e.g., the front surface **110A** of FIG. 1). In another example, the first protrusion **415** may extend from the second layer **412** toward the display (e.g., **101** of FIG. 1). In another example, the first protrusion **415** may extend from the second layer **412** in the -z direction.

(97) In an embodiment, the first protrusion **415** may penetrate the first layer **411** and may protrude outward from the first layer **411**. For example, the first protrusion **415** may pass through an opening **416** formed in the first layer **411** and may protrude from the first layer **411** by a specified height **h1**. In an embodiment, the first protrusion **415** may have an opening **417** formed therein into which the screw **390** is inserted.

(98) Referring to FIG. 5C, the first protrusion **415** according to an embodiment may be at least partially inserted into a first opening **592** formed in the support member **311**. In an embodiment, the screw **390** may pass through the first protrusion **415** and may be inserted into the first opening **592** of the support member **311**. As the screw **390** is fastened to a coupling portion **594** formed in the support member **311**, the second plate **320** may be coupled with the support member **311**. In an embodiment, the first opening **592** of the support member **311** may have different diameters so as to accommodate both the first protrusion **415** and the screw **390**.

(99) In an embodiment, the first protrusion **415** inserted into the first opening **592** of the support member **311** may prevent movement of the second plate **320** in a horizontal direction. For example, as the first protrusion **415** is constrained to the first opening **592**, movement of the second plate **320** in the x-y plane direction may be restricted.

(100) In an embodiment, since the position of the second plate **320** is fixed by the first protrusion **415**, an error in the position where the second plate **320** is disposed may be reduced. Accordingly, misalignment of the second plate **320** on the first printed circuit board **341** may be prevented, and defective fastening of the screw **390** may be reduced.

(101) In an embodiment, since the position of the second plate **320** is constrained by the first protrusion **415**, an error in the position of the first antenna **372** attached to the second plate **320** may be reduced. Accordingly, performance degradation of the first antenna **372** due to a position error may be reduced.

(102) In an embodiment, the first stacked structure **410** may improve the stiffness of the second plate **320**. For example, by forming a hemming structure in which the first layer **411** and the second layer **412** are superimposed on each other, the first stacked structure **410** may improve the stiffness of the second plate **320**. In an embodiment, the first stacked structure **410** may prevent the second plate **320** from being deformed by an external force depending on fastening the screw **390**. In an embodiment, even though the second plate **320** includes the clad metal having a relatively high thermal conductivity and a relatively low stiffness for heat dissipation of the electronic device **300**, the first stacked structure **410** may supplement the stiffness of the second plate **320**.

(103) In an embodiment, the first stacked structure **410** may be manufactured through a process that those skilled in the art can apply. For example, the stacked structure of the first layer **411** and the second layer **412** may be formed through bending and hamming processes, and the first protrusion **415** may be formed through piercing and drawing. A restriking process for adjusting the shape and dimensions may be performed after the piercing and drawing.

(104) FIG. 6A illustrates a first stacked structure according to an embodiment of the disclosure.

(105) FIG. 6B illustrates a first stacked structure according to an embodiment of the disclosure.

(106) FIG. 6C illustrates a first stacked structure according to an embodiment of the disclosure.

(107) Referring to FIG. 6A, the electronic device **300** according to an embodiment may include the first stacked structure **610** included in the second plate **320**. In FIG. 6A, repetitive descriptions of components having the same reference numerals as the above-described components will be omitted.

(108) In an embodiment, the first stacked structure **610** may include a first protrusion **615**. In an embodiment, the first protrusion **615** may extend from a first layer **411** toward the support member **311** (e.g., in the $-z$ direction) and may be at least partially inserted into a first opening **592** formed in the support member **311**. In an embodiment, unlike the first protrusion **415** of FIG. 5A that extends from the second layer **412**, the first protrusion **615** of the first stacked structure **610** of FIG. 6A may extend from the first layer **411**.

(109) Referring to FIG. 6B, the electronic device **300** according to an embodiment may include the first stacked structure **610-1** included in the second plate **320**. In FIG. 6B, repetitive descriptions of components having the same reference numerals as the above-described components will be omitted.

(110) In an embodiment, the first stacked structure **610-1** may not include a connecting portion (e.g., the connecting portion **413** of FIG. 4A) connected from one end of a first layer **411** to one end of a second layer **412**. In an embodiment, the first layer **411** and the second layer **412** may be bonded through laser welding. For example, referring to FIG. 6C, welding may be performed on at least one point P on an edge region of the second layer **412** to bond the first layer **411** and the second layer **412**.

(111) In an embodiment, since the connecting portion is removed, the volume of the second plate **320** may be decreased, and the mountability of the second plate **320** may be improved.

(112) In an embodiment, an edge surface **411C** of the first layer **411** and an edge surface **412C** of the second layer **412** are illustrated as being formed without a step with an edge surface **320C** of the second plate **320** by using a computer numerical control (CNC) process. However, the disclosure is not limited thereto. For example, the edge surface **411C** of the first layer **411** and/or the edge surface **412C** of the second layer **412** may protrude in the $+x$ direction, or may be recessed in the $-x$ direction, to have a step with the edge surface **320C** of the second plate **320**. The shape of the edge surface **411C** of the first layer **411** and/or the edge surface **412C** of the second layer **412** may vary depending on the interval with another part (e.g., the support member **311**) adjacent to the second plate **320**.

(113) The description of the first stacked structure **610-1** not including the connecting portion as illustrated in FIG. 6B may be substantially identically, similarly, or correspondingly applied to the first stacked structure **410** of FIG. 5A and/or the first stacked structure **610** of FIG. 6A. For example, the first stacked structure **410** of FIG. 5A and/or the first stacked structure **610** of FIG. 6A may not include the connecting portion **413**.

(114) FIG. 7A illustrates a second plate and a second stacked structure of the second plate according to an embodiment of the disclosure.

(115) FIG. 7B illustrates a second plate and a second stacked structure of the second plate according to an embodiment of the disclosure.

(116) FIG. 7C is a sectional view illustrating a second stacked structure according to an embodiment of the disclosure.

(117) FIG. 7C may be a sectional view taken along line B-B' of FIG. 4B.

(118) Referring to FIGS. 7A, 7B, and 7C, the second plate **320** according to an embodiment may include the second stacked structure **420**.

(119) In an embodiment, the second stacked structure **420** may be formed on the periphery of the second plate **320**. In an embodiment, the second stacked structure **420** may include a first layer **421**, a second layer **422**, a connecting portion **423**, and a second protrusion **425**.

(120) In an embodiment, the first layer **421** of the second stacked structure **420** may extend from

the second plate **320**. In an embodiment, the first layer **421** may include a first portion **4211** extending from the second plate **320** and a second portion **4212** extending from the first portion **4211** to the connecting portion **423**. In an embodiment, the first portion **4211** may form substantially the same layer as the second plate **320**. In an embodiment, the second portion **4212** may be bent from the first portion **4211** and may extend in a direction different from that of the first portion **4211**. For example, the first portion **4211** may extend along the x-y plane, and the second portion **4212** may extend in the -z direction substantially perpendicular to the first portion **4211**. In another example, the first portion **4211** may extend in a direction substantially parallel to the front surface (e.g., **110A** of FIG. **1**) of the electronic device **300**, and the second portion **4212** may extend toward the front surface of the electronic device **300**. In another example, the second portion **4212** may extend from the first portion **4211** toward the display (e.g., **101** of FIG. **1**). In an embodiment, one end of the second portion **4212** may be connected with the connecting portion **423**, and an opposite end of the second portion **4212** may be connected with the first portion **4211**.

(121) In an embodiment, the second layer **422** disposed on the first layer **421** may include a third portion **4221** and a fourth portion **4222**. In an embodiment, the third portion **4221** of the second layer **422** may be disposed on the first portion **4211** of the first layer **421**. In an embodiment, the fourth portion **4222** of the second layer **422** may be disposed to face the second portion **4212** of the first layer **421**.

(122) In an embodiment, the fourth portion **4222** of the second layer **422** may extend in a direction substantially parallel to the second portion **4212** of the first layer **421**. In an embodiment, one end of the fourth portion **4222** of the second layer **422** may be connected with the connecting portion **423**, and an opposite end of the fourth portion **4222** may be connected with the third portion **4221**. In an embodiment, the third portion **4221** of the second layer **422** may be bent from the fourth portion **4222** and may extend from the fourth portion **4222** in a direction substantially parallel to the first portion **4211**.

(123) In an embodiment, the first layer **421** and the second layer **422** may be at least partially brought into contact with each other. For example, the first portion **4211** of the first layer **421** may be brought into contact with the third portion **4221** of the second layer **422**, and the second portion **4212** of the first layer **421** may be spaced apart from the fourth portion **4222** of the second layer **422**. In another example, unlike that illustrated, all of the first layer **421** may be brought into contact with the second layer **422**.

(124) In an embodiment, the first layer **421** and the second layer **422** may have openings **426** and **427** formed therein into which the screw **390** is inserted.

(125) In an embodiment, the connecting portion **423** may extend from one end of the first layer **421** to one end of the second layer **422**. For example, the connecting portion **423** may extend from the second portion **4212** of the first layer **421** to the fourth portion **4222** of the second layer **422**.

(126) In an embodiment, the second protrusion **425** may extend from the second layer **422** in a direction away from the second plate **320**. In an embodiment, the second protrusion **425** may extend from the second layer **422** toward the side surface of the electronic device **300** (e.g., the side surface **110C** of FIG. **1**). In an embodiment, the second protrusion **425** may extend from the second layer **422** toward the side member (e.g., the side member **310** of FIG. **4A**). For example, the second protrusion **425** may extend from the fourth portion **4222** of the second layer **422** in a direction substantially parallel to the x-y plane. For example, the second protrusion **425** may extend from the fourth portion **4222** of the second layer **422** in the +x direction.

(127) In an embodiment, the second protrusion **425** may protrude outward from the second layer **422**. For example, the second protrusion **425** may protrude outward from the fourth portion **4222** of the second layer **422** by a specified height **h2**.

(128) Referring to FIG. **7C**, in an embodiment, the screw **390** may penetrate the first layer **421** and the second layer **422** of the second stacked structure **420**. For example, the screw **390** may be inserted into the opening **426** formed in the first portion **4211** of the first layer **421** and the opening

427 formed in the third portion **4221** of the second layer **422**. In an embodiment, the screw **390** may be inserted into a second opening **792** formed in the support member **311**. In an embodiment, as the screw **390** is fastened to a coupling portion **794** formed in the support member **311**, the second plate **320** may be coupled with the support member **311**.

(129) In an embodiment, a first stopping recess **722** and a second stopping recess **724** may be formed in the support member **311**.

(130) In an embodiment, the first stopping recess **722** may have a shape corresponding to the shape of the second protrusion **425**, and the second protrusion **425** may be at least partially inserted into the first stopping recess **722**. In an embodiment, the second protrusion **425** inserted into the first stopping recess **722** may prevent movement of the second plate **320** in a vertical direction. For example, as the second protrusion **425** is constrained by the first stopping recess **722**, movement of the second plate **320** in the z-axis direction may be restricted.

(131) In an embodiment, a portion of the second stacked structure **420** may be inserted into the second stopping recess **724**. For example, at least one of the second portion **4212**, the fourth portion **4222**, and/or the connecting portion **423** of the second stacked structure **420** may be at least partially accommodated in the second stopping recess **724**. In an embodiment, the second stacked structure **420** partially inserted into the second stopping recess **724** may prevent movement of the second plate **320** in a horizontal direction. For example, as the second stacked structure **420** is constrained by the second stopping recess **724**, movement of the second plate **320** in the x-y plane direction may be restricted.

(132) In an embodiment, since movement of the second plate **320** is restricted by the second stacked structure **420**, misalignment of the second plate **320** before or after the screw **390** is fastened may be prevented.

(133) In an embodiment, the second stacked structure **420** may improve the stiffness of the second plate **320**. For example, by forming a hemming structure in which the first layer **421** and the second layer **422** are superimposed on each other, the second stacked structure **420** may improve the stiffness of the second plate **320**. In an embodiment, the second stacked structure **420** may prevent the second plate **320** from being deformed by an external force depending on fastening the screw **390**.

(134) In an embodiment, the second stacked structure **420** may be manufactured through a process that those skilled in the art can apply. For example, the second protrusion **425** may be formed by performing piercing and drawing on the second plate **320**, and the second stacked structure **420** in which the first layer **421** and the second layer **422** are stacked on each other may be formed by performing bending and hamming on the second plate **320** having the second protrusion **425** formed thereon.

(135) FIG. **8** illustrates a second plate and a third stacked structure according to an embodiment of the disclosure.

(136) FIG. **8** may be a sectional view taken along line C-C'.

(137) Referring to FIG. **8**, the second plate **320** according to an embodiment may include the third stacked structure **430**. In an embodiment, the third stacked structure **430** may be formed on the periphery of the second plate **320**.

(138) In an embodiment, the third stacked structure **430** may include a first layer **431**, a second layer **432**, and a connecting portion **433**.

(139) In an embodiment, the first layer **431** may extend from the second plate **320**. In an embodiment, the first layer **431** may form substantially the same layer as the second plate **320**.

(140) In an embodiment, the second layer **432** may be disposed on the first layer **431** (e.g., the +z direction). For example, the second layer **432** may be disposed on a first surface **431A** of the first layer **431**. In an embodiment, the first surface **431A** of the first layer **431** may correspond to the first surface **320A** of the second plate **320**. For example, the first surface **431A** of the first layer **431** may extend from the first surface **320A** of the second plate **320**. In an embodiment, the second

layer **432** may be in contact with the first layer **431**.

(141) In an embodiment, the connecting portion **433** may extend from one end of the first layer **431** to one end of the second layer **432**.

(142) In an embodiment, the third stacked structure **430** may improve the stiffness of the second plate **320**. For example, by forming a hemming structure in which the first layer **431** and the second layer **432** are superimposed on each other, the third stacked structure **430** may improve the stiffness of the second plate **320**.

(143) In an embodiment, the third stacked structure **430** may overlap at least one of connectors of the first printed circuit board **341** (e.g., the first to seventh connectors **C1** to **C7** of FIG. **4B**). When a portion where a connector and the second plate **320** overlap each other is deformed, the connector may be separated from the first printed circuit board **341**. In an embodiment, the third stacked structure **430** that cover the connectors may prevent separation of the connectors due to deformation of the second plate **320**.

(144) In another embodiment, the second layer **432** of the third stacked structure **430** may be disposed under the first layer **431** (e.g., the $-z$ direction). For example, the second layer **432** of the third stacked structure **430** may be disposed on a second surface **431B** of the first layer **431**. In an embodiment, the second surface **431B** of the first layer **431** may correspond to the second surface **320B** of the second plate **320**. For example, the second surface **431B** of the first layer **431** may extend from the second surface **320B** of the second plate **320**.

(145) FIG. **9A** is a view illustrating a first stopping structure of an electronic device according to an embodiment of the disclosure.

(146) FIG. **9B** is a partial perspective view of a camera module and a second plate according to an embodiment of the disclosure.

(147) FIG. **9C** is a partial perspective view illustrating a state in which a camera module and a second plate are coupled according to an embodiment of the disclosure.

(148) Referring to FIGS. **9A**, **9B**, and **9C**, the electronic device **300** according to an embodiment may include the camera module **980** (e.g., a camera module **1380** of FIG. **13**) disposed in a position adjacent to the second plate **320**.

(149) In an embodiment, the second plate **320** may include the first stopping structure **940**. In an embodiment, the first stopping structure **940** may be formed on the periphery of the second plate **320**. In an embodiment, the first stopping structure **940** may be located adjacent to the camera module **980**. For example, the first stopping structure **940** may be located between the camera module **980** and the support member **311**. In another example, the first stopping structure **940** may be located between the camera module **980** and the screw **390**.

(150) In an embodiment, the first stopping structure **940** may include a first portion **9401** extending from the second plate **320** and a second portion **9402** curvedly extending from the first portion **9401** to face the first portion **9401**. The first portion **9401** may extend from the second plate **320** in a direction (e.g., the $-z$ direction) substantially perpendicular to the second plate **320**. The second portion **9402** may include a first stopping protrusion **942** protruding toward the camera module **980** (or, a housing **982**).

(151) In an embodiment, the camera module **980** may include the housing **982** and a second stopping protrusion **984** formed on the housing **982**. In an embodiment, the second stopping protrusion **984** may protrude from the housing **982** toward the first stopping structure **940** of the second plate **320**. For example, the second stopping protrusion **984** may protrude from the housing **982** in the $-y$ direction.

(152) In an embodiment, the first stopping protrusion **942** and the second stopping protrusion **984** may be brought into contact with each other to prevent movement of the second plate **320**. In an embodiment, the first stopping protrusion **942** may be located under the second stopping protrusion **984** (e.g., the $-z$ direction). In an embodiment, the second stopping protrusion **984** may form at least two inclined surfaces. For example, the second stopping protrusion **984** may include a first

inclined surface formed relatively above (e.g., the +z direction) and a second inclined surface formed relatively below (e.g., the -z direction). In an embodiment, the first stopping protrusion **942** of the first stopping structure **940** may be brought into contact with the second inclined surface of the second stopping protrusion **984**. In an embodiment, the first stopping structure **940** may be formed to have an appropriate elastic force such that the first stopping protrusion **942** and the second inclined surface remain in contact with each other. In an embodiment, the first stopping structure **940** may remain in contact with the second stopping protrusion **984** by applying the elastic force toward the camera module **980**.

(153) In an embodiment, the second inclined surface may be formed to have a steeper slope than the first inclined surface such that when the first stopping protrusion **942** is fastened to the second stopping protrusion **984**, the first stopping protrusion **942** may easily slide along the first inclined surface of the second stopping protrusion **984** and after the first stopping protrusion **942** is fastened to the second stopping protrusion **984**, the first stopping protrusion **942** is not separated from the second inclined surface.

(154) In an embodiment, the first stopping structure **940** seated on the second stopping protrusion **984** may prevent movement of the second plate **320** in a vertical direction (e.g., the z-axis direction).

(155) In an embodiment, the screw **390** may be inserted into a third opening **992** formed in the support member **311** and may be fastened to the support member **311**. In an embodiment, the second plate **320** may be coupled with the support member **311** through the screw **390**. In an embodiment, a first intermediate member **950** may be disposed between the screw **390** and the second plate **320**. In an embodiment, the first intermediate member **950** may have an annular shape having a hollow formed therein. In an embodiment, the screw **390** may pass through the hollow of the first intermediate member **950**. In an embodiment, the first intermediate member **950** may prevent the second plate **320** from being deformed by an external force that acts depending on fastening the screw **390**. In an embodiment, the first intermediate member **950** may include metal, such as stainless steel.

(156) FIG. **10** illustrates a second stopping structure of an electronic device according to an embodiment of the disclosure.

(157) Referring to FIG. **10**, the second plate **320** of the electronic device **300** according to an embodiment may include the second stopping structure **1040**.

(158) In an embodiment, the second stopping structure **1040** may be formed on the periphery of the second plate **320**. For example, the second stopping structure **1040** may be formed on the periphery of the second plate **320** that overlaps the third plate **330** when the electronic device **300** is viewed from above (e.g., in the -z direction).

(159) In an embodiment, to prevent movement of the second plate **320**, the second stopping structure **1040** may be at least partially inserted into an opening **1062** formed in the third plate **330**. For example, the second stopping structure **1040** may extend from the periphery of the second plate **320** toward the display (e.g., the display **101** of FIG. **1**). For example, the second stopping structure **1040** may include a first portion **1041** extending from the second plate **320** in a direction substantially perpendicular to the second plate **320** and a second portion **1042** curvedly extending from the first portion **1041** to face the first portion **1041**. For example, the first portion **1041** of the second stopping structure **1040** may extend in the -z direction, and the second portion **1042** may extend from the first portion **1041** in the +z direction. The first portion **1041** and the second portion **1042** may be in contact with each other.

(160) In an embodiment, the second stopping structure **1040** inserted into the opening **1062** may prevent movement of the second plate **320** in a horizontal direction (e.g., the y-axis direction).

(161) In an embodiment, the screw **390** may penetrate the second plate **320**, a second intermediate member **1050**, and the third plate **330** and may be inserted into a fourth opening **1092** formed in the support member **311**. In an embodiment, as the screw **390** is fastened to the fourth opening **1092**,

the support member **311**, the third plate **330**, the second intermediate member **1050**, and the second plate **320** may be coupled together.

(162) In an embodiment, the description of the first intermediate member **950** of FIG. **9A** may be correspondingly applied to the second intermediate member **1050**.

(163) FIG. **11** illustrates a third stopping structure of an electronic device according to an embodiment of the disclosure.

(164) Referring to FIG. **11**, the second plate **320** of the electronic device **300** according to an embodiment may include the third stopping structure **1140**.

(165) In an embodiment, the third stopping structure **1140** may be formed on the periphery of the second plate **320**. In an embodiment, the third stopping structure **1140** may at least partially overlap the third plate **330** when the electronic device **300** is viewed from above (e.g., when viewed in the $-z$ direction).

(166) In an embodiment, the third stopping structure **1140** may include a first portion **1141** extending in a direction substantially parallel to the second plate **320** and a second portion **1142** extending from the first portion **1141** to face the first portion. For example, the first portion **1141** may extend in a direction (e.g., the $+y$ direction) away from the second plate **320**, and the second portion **1142** may extend from one end of the first portion **1141** in a direction (e.g., the $-y$ direction) toward the second plate **320**.

(167) In an embodiment, to restrict movement of the second plate **320**, the third stopping structure **1140** may be at least partially accommodated in a recess **1162** formed on the third plate **330**. For example, a first portion **3301** of the third plate **330** may be located in the $+z$ direction from the third stopping structure **1140** and may overlap the third stopping structure **1140**. Movement of the third stopping structure **1140** in the $+z$ direction may be restricted by the first portion **3301**. For example, a second portion **3302** of the third plate **330** may be located in the $-z$ direction from the third stopping structure **1140** and may overlap the third stopping structure **1140**. Movement of the third stopping structure **1140** in the $-z$ direction may be restricted by the second portion **3302**.

(168) In an embodiment, the third stopping structure **1140** may be disposed between the first portion **3301** and the second portion **3302** of the third plate **330** that form the recess **1162**, and the third stopping structure **1140** accommodated in the recess **1162** may restrict movement of the second plate **320** in a vertical direction.

(169) FIG. **12A** illustrates a fourth stacked structure according to an embodiment of the disclosure.

(170) FIG. **12B** is a sectional view taken along line G-G' of FIG. **12A** according to an embodiment of the disclosure.

(171) For convenience of description, not only the second plate **320** having the fourth stacked structure **440** formed thereon but also other components coupled with the second plate **320** are illustrated together in FIG. **12B**.

(172) Referring to FIGS. **12A** and **12B**, the second plate **320** according to an embodiment may include the fourth stacked structure **440** formed on the periphery of the second plate **320**.

(173) In an embodiment, the fourth stacked structure **440** may include a first layer **441**, a second layer **442**, a connecting portion **443**, and a second protrusion **4452** formed on the second layer **442**.

(174) In an embodiment, the first layer **441**, the second layer **442**, the connecting portion **443**, and the second protrusion **4452** of the fourth stacked structure **440** may correspond to the first layer **421**, the second layer **422**, the connecting portion **423**, and the second protrusion **425** of the second stacked structure **420** of FIGS. **7A**, **7B**, and **7C**, respectively.

(175) In an embodiment, a first stopping recess **1222** and a second stopping recess **1225** formed in the support member **311** may correspond to the coupling portion **794**, the first stopping recess **722**, and the second stopping recess **725** of FIG. **7C**.

(176) In an embodiment, a third opening **1292** and a coupling portion **1294** formed in the support member **311** may correspond to the first opening **592** and the coupling portion **594** of FIG. **5C**.

(177) In an embodiment, unlike the second stacked structure **420** illustrated in FIG. **7A**, the fourth

stacked structure **440** may include a third protrusion **4451** formed on the second layer **442**. In an embodiment, the third protrusion **4451** may correspond to the first protrusion **415** of FIG. 5C or the first protrusion **615** of FIG. 6A. For example, the third protrusion **4451** according to an embodiment may extend from a third portion **4421** of the second layer **442** toward the support member **311**. In an embodiment, the third protrusion **4451** may penetrate the first layer **441** and may be at least partially inserted into the third opening **1292** formed in the support member **311**. In an embodiment, the screw **390** may penetrate the third protrusion **4451**. In an embodiment, the screw **390** may be inserted into an opening **447** formed in the third protrusion **4451** and a second opening **1291** and may be fastened to the coupling portion **1294**.

(178) In another embodiment, similarly to the first protrusion **615** of FIG. 6A, the third protrusion **4451** may extend from the first layer **441** rather than the second layer **442** toward the support member **311**.

(179) In an embodiment, the fourth stacked structure **440** may be understood as an embodiment in which the first stacked structure **410** and the second stacked structure **420** are coupled.

(180) An electronic device according to an embodiment (e.g., the electronic device **100** of FIG. 1) may include a display (e.g., the display **101** of FIG. 1) that forms at least a portion of a front surface (e.g., the front surface **110A** of FIG. 1) of the electronic device, a first plate (e.g., the first plate **111** of FIG. 2) that forms at least a portion of a rear surface (e.g., the rear surface **110B** of FIG. 2) of the electronic device, a side member (e.g., the side member **310** of FIG. 3) that is disposed between the display and the first plate and that forms at least a portion of a side surface (e.g., the side surface **110C** of FIG. 1) of the electronic device, a support member (e.g., the support member **311** of FIG. 3) that is disposed inside the side member and that has a first opening (e.g., the first opening **592** of FIG. 5C) and a first stopping recess (e.g., the first stopping recess **722** of FIG. 7C) formed therein, a printed circuit board (e.g., the at least one printed circuit board **340** of FIG. 3) disposed between the support member and the first plate, and a second plate (e.g., the second plate **320** of FIG. 4B) that is disposed between the first plate and the printed circuit board and coupled with the support member and that covers at least a portion of the printed circuit board. The second plate may include a stacked structure (e.g., at least one of the first stacked structure **410** of FIG. 5C, the first stacked structure **610** of FIG. 6A, the second stacked structure **420** of FIG. 7C, the third stacked structure **430** of FIG. 8, and/or the fourth stacked structure **440** of FIG. 12B) that is formed on a periphery of the second plate and that includes a first layer (e.g., at least one of the first layer **411** of FIG. 5C, the first layer **421** of FIG. 7C, the first layer **431** of FIG. 8, and/or the first layer **441** of FIG. 12B) that extends from the second plate and a second layer (e.g., at least one of the second layer **412** of FIG. 5C, the second layer **422** of FIG. 7C, the second layer **432** of FIG. 8, and/or the second layer **442** of FIG. 12B) disposed on the first layer. The stacked structure may include a first stacked structure (e.g., the first stacked structure **410** of FIG. 5C or the first stacked structure **610** of FIG. 6A) including a first protrusion (e.g., the first protrusion **415** of FIG. 5C or the first protrusion **615** of FIG. 6A) that extends toward the display and a second stacked structure (e.g., the second stacked structure **420** of FIG. 7C) including a second protrusion (e.g., the second protrusion **425** of FIG. 7C) that extends toward the side member. The first protrusion may be at least partially inserted into the first opening of the support member, and the second protrusion may be at least partially inserted into the first stopping recess of the support member.

(181) In an embodiment, the first protrusion may extend from the second layer of the first stacked structure and may penetrate the first layer.

(182) In an embodiment, the first protrusion may extend from the first layer of the first stacked structure.

(183) In an embodiment, the first stacked structure may include a connecting portion (e.g., the connecting portion **413** of FIG. 5C) that extends from one end of the first layer to one end of the second layer.

(184) The electronic device according to an embodiment may include a screw (e.g., the screw **390**

of FIG. 5C) that penetrates the first protrusion and that is inserted into the first opening.

(185) In an embodiment, the first layer of the second stacked structure may include a first portion (e.g., the first portion **4211** of FIG. 7C) that extends from the second plate and a second portion (e.g., the second portion **4212** of FIG. 7C) that extends from the first portion toward the display. The second layer of the second stacked structure may include a third portion (e.g., the third portion **4221** of FIG. 7C) disposed on the first portion and a fourth portion (e.g., the fourth portion **4222** of FIG. 7C) that extends from the third portion to face the second portion. The second stacked structure may include a connecting portion (e.g., the connecting portion **423** of FIG. 7C) that extends from one end of the second portion to one end of the fourth portion.

(186) In an embodiment, the second protrusion may extend from the fourth portion toward the side member.

(187) In an embodiment, a second stopping recess (e.g., the second stopping recess **725** of FIG. 7C) may be formed in the support member, and the connecting portion may be accommodated in the second stopping recess.

(188) The electronic device according to an embodiment may include a screw (e.g., the screw **390** of FIG. 7C). A second opening (e.g., the second opening **792** of FIG. 7C) may be formed in the support member, and the screw may penetrate the first portion and the third portion of the second stacked structure and may be inserted into the second opening.

(189) The electronic device according to an embodiment may include at least one connector (e.g., at least one of the first to seventh connectors **C1** to **C7** of FIG. 4B) disposed on the printed circuit board. The stacked structure may include a third stacked structure (e.g., the third stacked structure **430** of FIG. 8) that overlaps the at least one connector, and the third stacked structure may include a connecting portion (e.g., the connecting portion **433** of FIG. 8) that extends from one end of the first layer to one end of the second layer.

(190) In an embodiment, the first layer of the third stacked structure may include a first surface (e.g., the first surface **431A** of FIG. 8) that faces toward the first plate and a second surface (e.g., the second surface **431B** of FIG. 8) that faces toward the display, and the second layer may be disposed on the first surface or the second surface.

(191) In an embodiment, the electronic device may include a camera module (e.g., the camera module **980** of FIG. 9A) including a housing (e.g., the housing **982** of FIG. 9A). The second plate may include a first stopping structure (e.g., the first stopping structure **940** of FIG. 9A) formed on the periphery of the second plate. The first stopping structure may include a first stopping protrusion (e.g., the first stopping protrusion **942** of FIG. 9A) that protrudes toward the housing. The housing of the camera module may include a second stopping protrusion (e.g., the second stopping protrusion **984** of FIG. 9A) that protrudes toward the second plate and that is located over the first stopping protrusion. The first stopping protrusion and the second stopping protrusion may be brought into contact with each other to prevent movement of the second plate.

(192) The electronic device according to an embodiment may include a third plate (e.g., the third plate **330** of FIG. 10) that is disposed between the first plate and the support member and that has an opening (e.g., the opening **1062** of FIG. 10) formed therein. The second plate includes a second stopping structure (e.g., the second stopping structure **1040** of FIG. 10) that extends from the periphery of the second plate toward the display, and the second stopping structure may be at least partially inserted into the opening to prevent movement of the second plate.

(193) The electronic device according to an embodiment may include a third plate (e.g., the third plate **330** of FIG. 11) disposed between the first plate and the support member. The second plate may include a third stopping structure (e.g., the third stopping structure **1140** of FIG. 11) that extends from the periphery of the second plate in a direction substantially parallel to the second plate, and at least a portion of the third stopping structure may be accommodated in a recess (e.g., the recess **1162** of FIG. 11) formed on the third plate to prevent movement of the second plate.

(194) The electronic device according to an embodiment may further include a loop antenna (e.g.,

the first antenna **372** of FIG. **3**) disposed on the second plate.

(195) In an embodiment, the second plate may include a clad metal.

(196) An electronic device according to an embodiment (e.g., the electronic device **100** of FIG. **1**) may include a display (e.g., the display **101** of FIG. **1**) that forms at least a portion of a front surface (e.g., the front surface **110A** of FIG. **1**) of the electronic device, a first plate (e.g., the first plate **111** of FIG. **2**) that forms at least a portion of a rear surface (e.g., the rear surface **110B** of FIG. **2**) of the electronic device, a side member (e.g., the side member **310** of FIG. **3**) that is disposed between the display and the first plate and that forms at least a portion of a side surface (e.g., the side surface **110C** of FIG. **1**) of the electronic device, a support member (e.g., the support member **311** of FIG. **3**) that is disposed inside the side member and that has a first opening (e.g., the first opening **592** of FIG. **5C**) and a first stopping recess (e.g., the first stopping recess **722** of FIG. **7C**) formed therein, a first printed circuit board (e.g., the first printed circuit board **341** of FIG. **3**) disposed between the support member and the first plate, at least one connector (e.g., at least one of the first to seventh connectors **C1** to **C7** of FIG. **4B**) disposed on the first printed circuit board, and a second plate (e.g., the second plate **320** of FIG. **4B**) that is disposed between the first plate and the first printed circuit board and coupled with the support member and that covers at least a portion of the first printed circuit board. The second plate may include a stacked structure (e.g., at least one of the first stacked structure **410** of FIG. **5C**, the first stacked structure **610** of FIG. **6A**, the second stacked structure **420** of FIG. **7C**, the third stacked structure **430** of FIG. **8**, and/or the fourth stacked structure **440** of FIG. **12B**) that is formed on a periphery of the second plate and that includes a first layer (e.g., at least one of the first layer **411** of FIG. **5C**, the first layer **421** of FIG. **7C**, the first layer **431** of FIG. **8**, and/or the first layer **441** of FIG. **12B**) that extends from the second plate and a second layer (e.g., at least one of the second layer **412** of FIG. **5C**, the second layer **422** of FIG. **7C**, the second layer **432** of FIG. **8**, and/or the second layer **442** of FIG. **12B**) disposed on the first layer. The stacked structure may include a first stacked structure (e.g., the first stacked structure **410** of FIG. **5C** or the first stacked structure **610** of FIG. **6A**) including a first protrusion (e.g., the first protrusion **415** of FIG. **5C** or the first protrusion **615** of FIG. **6A**) that extends toward the display, a second stacked structure (e.g., the second stacked structure **420** of FIG. **7C**) including a second protrusion (e.g., the second protrusion **425** of FIG. **7C**) that extends toward the side member, and a third stacked structure (e.g., the third stacked structure **430** of FIG. **8**) that at least partially overlaps the at least one connector. The first protrusion may be at least partially inserted into the first opening of the support member to restrict movement of the second plate in a horizontal direction, and the second protrusion may be at least partially inserted into the first stopping recess of the support member to restrict movement of the second plate in a vertical direction.

(197) The electronic device according to an embodiment may include a screw (e.g., the screw **390** of FIG. **5C**). The first protrusion may extend from the second layer of the first stacked structure and may penetrate the first layer of the first stacked structure, and the screw may penetrate the first protrusion and may be inserted into the first opening.

(198) In an embodiment, the first layer of the second stacked structure may include a first portion (e.g., the first portion **4211** of FIG. **7C**) that extends from the second plate and a second portion (e.g., the second portion **4212** of FIG. **7C**) that extends from the first portion toward the display. The second layer of the second stacked structure may include a third portion (e.g., the third portion **4221** of FIG. **7C**) disposed on the first portion and a fourth portion (e.g., the fourth portion **4222** of FIG. **7C**) that extends from the third portion to face the second portion. The second stacked structure may include a connecting portion (e.g., the connecting portion **423** of FIG. **7C**) that extends from one end of the second portion to one end of the fourth portion.

(199) In an embodiment, the third stacked structure may include a connecting portion (e.g., the connecting portion **433** of FIG. **8**) of the third stacked structure that extends from one end of the first layer to one end of the second layer of the third stacked structure. The first layer of the third

stacked structure may include a first surface (e.g., the first surface **431A** of FIG. **8**) that faces toward the first plate and a second surface (e.g., the second surface **431B** of FIG. **8**) that faces toward the display. The second layer of the third stacked structure may be disposed on the first surface or the second surface.

(200) FIG. **13** is a block diagram illustrating an electronic device in a network environment according to an embodiment of the disclosure.

(201) Referring to FIG. **13**, an electronic device **1301** in a network environment **1300** may communicate with an external electronic device **1302** via a first network **1398** (e.g., a short-range wireless communication network), or at least one of an external electronic device **1304** or a server **1308** via a second network **1399** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **1301** may communicate with the external electronic device **1304** via the server **1308**. According to an embodiment, the electronic device **1301** may include a processor **1320**, memory **1330**, an input module **1350**, a sound output module **1355**, a display module **1360**, an audio module **1370**, a sensor module **1376**, an interface **1377**, a connecting terminal **1378**, a haptic module **1379**, a camera module **1380**, a power management module **1388**, a battery **1389**, a communication module **1390**, a subscriber identification module (SIM) **1396**, or an antenna module **1397**. In some embodiments, at least one of the components (e.g., the connecting terminal **1378**) may be omitted from the electronic device **1301**, or one or more other components may be added in the electronic device **1301**. In some embodiments, some of the components (e.g., the sensor module **1376**, the camera module **1380**, or the antenna module **1397**) may be implemented as a single component (e.g., the display module **1360**).

(202) The processor **1320** may execute, for example, software (e.g., a program **1340**) to control at least one other component (e.g., a hardware or software component) of the electronic device **1301** coupled with the processor **1320**, and may perform various data processing or computation.

According to one embodiment, as at least part of the data processing or computation, the processor **1320** may store a command or data received from another component (e.g., the sensor module **1376** or the communication module **1390**) in volatile memory **1332**, process the command or the data stored in the volatile memory **1332**, and store resulting data in a non-volatile memory **1334**.

According to an embodiment, the processor **1320** may include a main processor **1321** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **1323** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **1321**. For example, when the electronic device **1301** includes the main processor **1321** and the auxiliary processor **1323**, the auxiliary processor **1323** may be adapted to consume less power than the main processor **1321**, or to be specific to a specified function. The auxiliary processor **1323** may be implemented as separate from, or as part of the main processor **1321**.

(203) The auxiliary processor **1323** may control at least some of functions or states related to at least one component (e.g., the display module **1360**, the sensor module **1376**, or the communication module **1390**) among the components of the electronic device **1301**, instead of the main processor **1321** while the main processor **1321** is in an inactive (e.g., sleep) state, or together with the main processor **1321** while the main processor **1321** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **1323** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **1380** or the communication module **1390**) functionally related to the auxiliary processor **1323**. According to an embodiment, the auxiliary processor **1323** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **1301** where the artificial intelligence is performed or via a separate server (e.g., the server **1308**). Learning algorithms may include, but are not limited to, e.g., supervised

learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(204) The memory **1330** may store various data used by at least one component (e.g., the processor **1320** or the sensor module **1376**) of the electronic device **1301**. The various data may include, for example, software (e.g., the program **1340**) and input data or output data for a command related thereto. The memory **1330** may include the volatile memory **1332** or the non-volatile memory **1334**.

(205) The program **1340** may be stored in the memory **1330** as software, and may include, for example, an operating system (OS) **1342**, middleware **1344**, or an application **1346**.

(206) The input module **1350** may receive a command or data to be used by another component (e.g., the processor **1320**) of the electronic device **1301**, from the outside (e.g., a user) of the electronic device **1301**. The input module **1350** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(207) The sound output module **1355** may output sound signals to the outside of the electronic device **1301**. The sound output module **1355** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(208) The display module **1360** may visually provide information to the outside (e.g., a user) of the electronic device **1301**. The display module **1360** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **1360** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(209) The audio module **1370** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **1370** may obtain the sound via the input module **1350**, or output the sound via the sound output module **1355** or a headphone of an external electronic device (e.g., the external electronic device **1302**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **1301**.

(210) The sensor module **1376** may detect an operational state (e.g., power or temperature) of the electronic device **1301** or an environmental state (e.g., a state of a user) external to the electronic device **1301**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **1376** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(211) The interface **1377** may support one or more specified protocols to be used for the electronic device **1301** to be coupled with the external electronic device (e.g., the external electronic device **1302**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **1377** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(212) A connecting terminal **1378** may include a connector via which the electronic device **1301** may be physically connected with the external electronic device (e.g., the external electronic device **1302**). According to an embodiment, the connecting terminal **1378** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone

connector).

(213) The haptic module **1379** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **1379** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(214) The camera module **1380** may capture a still image or moving images. According to an embodiment, the camera module **1380** may include one or more lenses, image sensors, image signal processors, or flashes.

(215) The power management module **1388** may manage power supplied to the electronic device **1301**. According to one embodiment, the power management module **1388** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(216) The battery **1389** may supply power to at least one component of the electronic device **1301**. According to an embodiment, the battery **1389** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(217) The communication module **1390** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **1301** and the external electronic device (e.g., the external electronic device **1302**, the external electronic device **1304**, or the server **1308**) and performing communication via the established communication channel. The communication module **1390** may include one or more communication processors that are operable independently from the processor **1320** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **1390** may include a wireless communication module **1392** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **1394** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **1398** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **1399** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **1392** may identify and authenticate the electronic device **1301** in a communication network, such as the first network **1398** or the second network **1399**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **1396**.

(218) The wireless communication module **1392** may support a 5G network, after a fourth-generation (4G) network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **1392** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **1392** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **1392** may support various requirements specified in the electronic device **1301**, an external electronic device (e.g., the external electronic device **1304**), or a network system (e.g., the second network **1399**). According to an embodiment, the wireless communication module **1392** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss

coverage (e.g., 1364 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 13 ms or less) for implementing URLLC.

(219) The antenna module **1397** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **1301**. According to an embodiment, the antenna module **1397** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **1397** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **1398** or the second network **1399**, may be selected, for example, by the communication module **1390** (e.g., the wireless communication module **1392**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **1390** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **1397**.

(220) According to various embodiments, the antenna module **1397** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(221) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(222) According to an embodiment, commands or data may be transmitted or received between the electronic device **1301** and the external electronic device **1304** via the server **1308** coupled with the second network **1399**. Each of the external electronic devices **1302** or **1304** may be a device of a same type as, or a different type, from the electronic device **1301**. According to an embodiment, all or some of operations to be executed at the electronic device **1301** may be executed at one or more of the external electronic devices **1302**, **1304**, or **1308**. For example, if the electronic device **1301** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **1301**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **1301**. The electronic device **1301** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **1301** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **1304** may include an internet-of-things (IoT) device. The server **1308** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **1304** or the server **1308** may be included in the second network **1399**. The electronic device **1301** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(223) The electronic device according to various embodiments may be one of various types of

electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(224) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(225) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(226) Various embodiments as set forth herein may be implemented as software (e.g., the program **1340**) including one or more instructions that are stored in a storage medium (e.g., an internal memory **1336** or an external memory **1338**) that is readable by a machine (e.g., the electronic device **1301**). For example, a processor (e.g., the processor **1320**) of the machine (e.g., the electronic device **1301**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(227) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., a compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(228) According to various embodiments, each component (e.g., a module or a program) of the

above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added. (229) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device comprising: a display configured to form at least a portion of a front surface of the electronic device; a first plate configured to form at least a portion of a rear surface of the electronic device; a side member disposed between the display and the first plate and configured to form at least a portion of a side surface of the electronic device; a support member disposed inside the side member, the support member having a first opening and a first stopping recess formed therein; a printed circuit board disposed between the support member and the first plate; and a second plate disposed between the first plate and the printed circuit board and coupled with the support member, the second plate being configured to cover at least a portion of the printed circuit board, wherein the second plate includes a stacked structure formed on a periphery of the second plate, the stacked structure including a first layer configured to extend from the second plate and a second layer disposed on the first layer, wherein the stacked structure includes a first stacked structure including a first protrusion configured to extend toward the display and a second stacked structure including a second protrusion configured to extend toward the side member, wherein the first protrusion is at least partially inserted into the first opening of the support member, and wherein the second protrusion is at least partially inserted into the first stopping recess of the support member.
2. The electronic device of claim 1, wherein the first protrusion extends from the second layer of the first stacked structure and penetrates the first layer.
3. The electronic device of claim 1, wherein the first protrusion extends from the first layer of the first stacked structure.
4. The electronic device of claim 1, wherein the first stacked structure includes a connecting portion configured to extend from one end of the first layer to one end of the second layer.
5. The electronic device of claim 1, further comprising: a screw configured to penetrate the first protrusion and inserted into the first opening.
6. The electronic device of claim 1, wherein the first layer of the second stacked structure includes: a first portion configured to extend from the second plate; and a second portion configured to extend from the first portion toward the display, wherein the second layer of the second stacked structure includes: a third portion disposed on the first portion, and a fourth portion configured to extend from the third portion to face the second portion, and wherein the second stacked structure includes a connecting portion configured to extend from one end of the second portion to one end of the fourth portion.
7. The electronic device of claim 6, wherein the second protrusion extends from the fourth portion

toward the side member.

8. The electronic device of claim 6, wherein a second stopping recess is formed in the support member, and wherein the connecting portion is accommodated in the second stopping recess.

9. The electronic device of claim 6, further comprising: a screw, wherein a second opening is formed in the support member, and wherein the screw penetrates the first portion and the third portion of the second stacked structure and is inserted into the second opening.

10. The electronic device of claim 1, further comprising: at least one connector disposed on the printed circuit board, wherein the stacked structure includes a third stacked structure configured to overlap the at least one connector, and wherein the third stacked structure includes a connecting portion configured to extend from one end of the first layer to one end of the second layer.

11. The electronic device of claim 10, wherein the first layer of the third stacked structure includes a first surface configured to face toward the first plate and a second surface configured to face toward the display, and wherein the second layer is disposed on the first surface or the second surface.

12. The electronic device of claim 1, further comprising: a camera module including a housing, wherein the second plate includes a first stopping structure formed on the periphery of the second plate, wherein the first stopping structure includes a first stopping protrusion configured to protrude toward the housing, wherein the housing of the camera module includes a second stopping protrusion configured to protrude toward the second plate and located over the first stopping protrusion, and wherein the first stopping protrusion and the second stopping protrusion are brought into contact with each other to prevent movement of the second plate.

13. The electronic device of claim 1, further comprising: a third plate disposed between the first plate and the support member, the third plate having an opening formed therein, wherein the second plate includes a second stopping structure configured to extend from the periphery of the second plate toward the display, and wherein the second stopping structure is at least partially inserted into the opening to prevent movement of the second plate.

14. The electronic device of claim 1, further comprising: a third plate disposed between the first plate and the support member, wherein the second plate includes a third stopping structure configured to extend from the periphery of the second plate in a direction substantially parallel to the second plate, and wherein at least a portion of the third stopping structure is accommodated in a recess formed on the third plate to prevent movement of the second plate.

15. The electronic device of claim 1, further comprising: a loop antenna disposed on the second plate.

16. The electronic device of claim 1, wherein the second plate includes a clad metal.

17. An electronic device comprising: a display forming at least a portion of a front surface of the electronic device; a first plate forming at least a portion of a rear surface of the electronic device; a side member disposed between the display and the first plate, wherein the side member forms at least a portion of a side surface of the electronic device; a support member disposed inside the side member, wherein a first opening and a first stopping recess are formed in the support member; a first printed circuit board disposed between the support member and the first plate; at least one connector disposed on the first printed circuit board; and a second plate disposed between the first plate and the first printed circuit board and coupled with the support member, and that covers at least a portion of the first printed circuit board, wherein the second plate includes a stacked structure that is formed on a periphery of the second plate and that includes a first layer extending from the second plate and a second layer disposed on the first layer, wherein the stacked structure includes: a first stacked structure including a first protrusion that extends toward the display, a second stacked structure including a second protrusion that extends toward the side member, and a third stacked structure that at least partially overlaps the at least one connector, wherein the first protrusion is at least partially inserted into the first opening of the support member to restrict movement of the second plate in a horizontal direction, and wherein the second protrusion is at

least partially inserted into the first stopping recess of the support member to restrict movement of the second plate in a vertical direction.

18. The electronic device of claim 17, further comprising a screw, wherein the first protrusion extends from the second layer of the first stacked structure and penetrates the first layer of the first stacked structure, and wherein the screw penetrates the first protrusion and is inserted into the first opening.

19. The electronic device of claim 18, wherein the first layer of the second stacked structure includes: a first portion that extends from the second plate; and a second portion that extends from the first portion toward the display, wherein the second layer of the second stacked structure includes: a third portion disposed on the first portion, and a fourth portion that extends from the third portion to face the second portion, and wherein the second stacked structure includes a connecting portion that extends from one end of the second portion to one end of the fourth portion.

20. The electronic device of claim 19, wherein the third stacked structure includes a connecting portion of the third stacked structure that extends from one end of the first layer to one end of the second layer of the third stacked structure, wherein the first layer of the third stacked structure includes a first surface that faces toward the first plate and a second surface that faces toward the display, and wherein the second layer of the third stacked structure is disposed on the first surface or the second surface.
