

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250259472

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

LiVoti; John T. et al.

METHODS AND APPARATUS TO DETERMINE AN AUDIENCE COMPOSITION BASED ON VOICE RECOGNITION, THERMAL IMAGING, AND FACIAL RECOGNITION

Abstract

Methods, apparatus, systems and articles of manufacture are disclosed. An example apparatus includes an audio detector to determine a first audience count based on signatures of audio data captured in the media environment, a thermal image detector to determine a heat blob count based on a frame of thermal image data captured in the media environment, and an audience image detector to identify at least one audience member based on a comparison of a frame of audience image data with a library of reference audience images, the audience image detector to perform the comparison in response to the first audience count not matching the heat blob count.

Inventors: LiVoti; John T. (Clearwater, FL), Woodruff; Stanley Wellington (Palm Harbor, FL)

Applicant: The Nielsen Company (US), LLC (New York, NY)

Family ID: 80269615

Appl. No.: 19/038823

Filed: January 28, 2025

Related U.S. Application Data

parent US continuation 18363378 20230801 parent-grant-document US 12217527 child US 19038823

parent US continuation 16998814 20200820 parent-grant-document US 11763591 child US 18363378

Publication Classification

Int. Cl.: G06V40/10 (20220101); **G06V10/75** (20220101); **G10L25/51** (20130101); **G10L25/78** (20130101); **H04N21/442** (20110101)

U.S. Cl.:

CPC G06V40/10 (20220101); **G06V10/751** (20220101); **G10L25/51** (20130101); **G10L25/78** (20130101); **H04N21/44218** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This disclosure is a continuation of U.S. patent application Ser. No. 18/363,378, filed on Aug. 1, 2023, now issued as U.S. Pat. No. 12,217,527, which is a continuation of U.S. patent application Ser. No. 16/998,814, filed on Aug. 20, 2020, now issued as U.S. Pat. No. 11,763,591, each of which is hereby by reference in its entirety.

FIELD OF THE DISCLOSURE

[0002] This disclosure relates generally to audience monitoring, and, more particularly, to methods and apparatus to determine an audience composition based on voice recognition, thermal imaging, and facial recognition.

BACKGROUND

[0003] Media monitoring companies, also referred to as audience measurement entities, monitor user interaction with media devices, such as smartphones, tablets, laptops, smart televisions, etc. To facilitate such monitoring, monitoring companies enlist panelists and install meters at the media presentation locations of those panelists. The meters monitor media presentations and transmit media monitoring information to a central facility of the monitoring company. Such media monitoring information enables the media monitoring companies to, among other things, monitor exposure to advertisements, determine advertisement effectiveness, determine user behavior, identify purchasing behavior associated with various demographics, etc.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 illustrates an example audience measurement system having an example meter to monitor an example media presentation environment and generate exposure data for the media.

[0005] FIG. 2 illustrates a block diagram of the example meter of FIG. 1.

[0006] FIG. 3 illustrates a block diagram of an example people meter included in the example meter of FIG. 2 to determine an audience composition for audience monitoring data.

[0007] FIG. 4 illustrates a block diagram of an example audience audio detector included in the example people meter of FIG. 3 to identify audience members based on voice recognition.

[0008] FIG. 5 illustrates a block diagram of an example thermal image detector included in the example people meter of FIG. 3 to determine a heat blob count.

[0009] FIG. 6 illustrates a block diagram of an example audience image detector included in the example people meter of FIG. 3 to identify audience members based on facial recognition.

[0010] FIG. 7 illustrates a block diagram of an example people identification model controller included in the example people meter of FIG. 3 to train a model to determine an audience composition of the media presentation environment of FIG. 1.

[0011] FIG. 8 is a flowchart representative of machine readable instructions which may be executed to implement the example audience audio detector of FIGS. 3 and/or 4 to identify

audience members.

[0012] FIG. 9 is a flowchart representative of machine readable instructions which may be executed to implement the example thermal image detector of FIGS. 3 and/or 5 to determine a heat blob count.

[0013] FIG. 10 is a flowchart representative of machine readable instructions which may be executed to implement the example people meter of FIGS. 2, 3, 4, 5, 6, and 7 to verify an audience composition of the media presentation environment of FIG. 1.

[0014] FIG. 11 is a flowchart representative of machine readable instructions which may be executed to implement the example audience image detector of FIGS. 3 and/or 6 to identify audience members.

[0015] FIG. 12 is a flowchart representative of machine readable instructions which may be executed to implement the example people identification model controller of FIGS. 3 and/or 7 to train the model to determine an audience composition of the media presentation environment of FIG. 1.

[0016] FIG. 13 illustrates a block diagram of an example processing platform structured to execute the instructions of one or more of FIGS. 8-12 to implement the example people meter of FIGS. 2-7.

[0017] The figures are not to scale. In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts.

[0018] Unless specifically stated otherwise, descriptors such as “first,” “second,” “third,” etc. are used herein without imputing or otherwise indicating any meaning of priority, physical order, arrangement in a list, and/or ordering in any way, but are merely used as labels and/or arbitrary names to distinguish elements for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for identifying those elements distinctly that might, for example, otherwise share a same name.

DETAILED DESCRIPTION

[0019] At least some meters that perform media monitoring, such as the meters described above, implement media identification features and people identification features. Such features (e.g., media identification and people identification) enable the generation of media monitoring information that can be used for determining audience exposure (also referred to as user exposure) to advertisements, determining advertisement effectiveness, determining user behavior relative to media, identifying the purchasing behavior associated with various demographics, etc. The people identification features of the meter determine the audience in a media presentation environment. For example, the people identification feature may be implemented by active people meters, passive people meters, and/or a combination of active people meters and passive people meters to determine a people count.

[0020] An active people meter obtains a people count by actively prompting an audience to enter information for audience member identification. In some examples, an active people meter identifies an audience member by the audience member's assigned panelist number or visitor number. For example, the active people meter obtains the assigned panelist number or visitor number through a communication channel. In some examples, the active people meter pairs the information corresponding to the audience input with a household (e.g., a specific media environment) and with the corresponding demographic data for the people of that household. In some examples, the active people meter validates viewership (e.g., the number of audience members viewing media in the media environment) at a set interval. For example, the active people meter generates a prompting message for the audience members to verify that they are still in the audience. In this manner, the active people meter relies on audience compliance. In some examples, maintaining audience compliance is a challenge. For example, audience members may incorrectly enter the number of people viewing the media and/or they may miss the prompting messages

generated by the active people meter.

[0021] A passive people meter obtains audience information passively, usually by capturing images of the audience using a camera and then employing facial recognition to identify the individual audience members included in the audience. In some examples, image processing for facial recognition can be processor intensive. Additionally, facial recognition algorithms can take a substantial amount of time to reliably recognize people in an image.

[0022] To enable an accurate and less invasive method of determining an audience composition, example methods and apparatus disclosed herein utilize a combination of a passive people meter and an active people meter. As used herein, “audience composition” refers to the number and/or identities of audience members in the audience. An example passive people meter disclosed herein includes an example audio detection system, an example thermal imaging system, and an example facial recognition system to identify audience members in the media environment. In some examples, the audio detection system includes an audio sensor to record the media environment and record samples of audio data, the thermal imaging system includes a thermal imaging sensor (e.g., a thermal imaging camera) to scan the media environment and capture frames of thermal image data of the media environment, and the facial recognition system includes a light imaging sensor (e.g., a light imaging camera) to capture frames of audience image data that depict the audience members sensed in the thermal image data. The example passive people meter utilizes the samples of audio data, the frames of thermal image data, and/or the frames of audience image data to detect and identify audience member in the media environment.

[0023] Example methods and apparatus disclosed herein additionally utilize the active people meter to identify audience members in the media environment. An example people meter, implemented by the example active people meter and the example passive people meter as disclosed herein, includes an audience audio detector, a thermal image detector, and an audience image detector to identify audience members. In some examples, when the audience audio detector, the thermal image detector, and/or the audience image detector is unable to identify one or more audience members, the audience audio detector, the thermal image detector, and/or the audience image detector can notify the active people meter to generate a new prompting message for the audience member(s).

[0024] In some examples, the example people meter reduces (e.g., minimizes) the amount of prompting generated by the active people meter relative to prior people meters that do not employ a combination of active and passive people metering. For example, when the audience audio detector, the thermal image detector, and/or the audience image detector identifies the audience member(s), the audience composition is verified, and subsequent active prompting can be disabled for at least a given monitoring interval (e.g., 5 minutes, 15 minutes, etc.). Using audio sensing, thermal imaging, and/or light imaging, the people meter monitors the media environment over time (e.g., continuously, at sampled time intervals, etc.) to determine the number of different speech patterns, the number of human sized heat blobs, and/or the faces of audience members, validate against the number entered on the active people meter and/or previously logged, and accurately determine the audience composition.

[0025] In some examples disclosed herein, the example people meter includes a people identification model controller to train a model to learn about the corresponding household media environment. As used herein, a model is a description of an environment using mathematical concepts and language. A model is generally composed of relationships and variables, the relationships describing operators (e.g., such as algebraic operators, functions, etc.) and the variables describing monitored environment parameters of interest that can be quantified. In some examples, the model is a machine learning and/or artificial intelligence (AI) model such as a Linear Regression model, a decision tree, a support vector machine (SVM) model, a Naïve Bayes model, etc.

[0026] In some examples, the people identification model controller obtains data from the

comparator, the active people meter, and the passive people meter and generates a feature vector corresponding to the data. The example people identification model controller utilizes the feature vector to train the model. For example, the feature vector includes data representative of descriptive characteristics of a physical environment (e.g., the household media environment). In some examples, such data includes a date and time, a number and/or identification of audience members present in the media environment, a media source (e.g., radio media, television media, pay per view media, movies, Internet Protocol Television (IPTV), satellite television (TV), Internet radio, satellite radio, digital television), a media channel (e.g., broadcast channel, a domain name), and the demographics of the audience members. In this manner, the example people identification model controller can generate the model to learn who will be in the audience and at what time. Eventually, when training is complete, the model can be deployed at the meter and utilized to make informed decisions about the audience composition.

[0027] In some examples, the model can utilize the identification of audience members determined by the audience audio detector, the thermal image detector, and/or the audience image detector as a metric to determine whether the people meter is actually crediting the media exposure to the correct panelists. For example, the model could be used to determine if the audience views the same or similar media every Tuesday night at 8:00 pm, if there are usually two particular people present in the media audience, etc. In such an example, the model is used to verify the accuracy of the audience composition based on the information obtained.

[0028] FIG. 1 is an illustration of an example audience measurement system **100** having an example meter **102** to monitor an example media presentation environment **104**. In the illustrated example of FIG. 1, the media presentation environment **104** includes panelists **106**, **107**, and **108**, an example media device **110** that receives media from an example media source **112**, and the meter **102**. The meter **102** identifies the media presented by the media device **110** and reports media monitoring information to an example central facility **114** of an audience measurement entity via an example gateway **116** and an example network **118**. The example meter **102** of FIG. 1 sends media monitoring data and/or audience monitoring data to the central facility **114** periodically, a-periodically and/or upon request by the central facility **114**.

[0029] In the illustrated example of FIG. 1, the media presentation environment **104** is a room of a household (e.g., a room in a home of a panelist, such as the home of a “Nielsen family”) that has been statistically selected to develop media (e.g., television) ratings data for a population/demographic of interest. In the illustrated example of FIG. 1, the example panelists **106**, **107**, and **108** of the household have been statistically selected to develop media ratings data (e.g., television ratings data) for a population/demographic of interest. People become panelists via, for example, a user interface presented on a media device (e.g., via the media device **110**, via a website, etc.). People become panelists in additional or alternative manners such as, for example, via a telephone interview, by completing an online survey, etc. Additionally or alternatively, people may be contacted and/or enlisted using any desired methodology (e.g., random selection, statistical selection, phone solicitations, Internet advertisements, surveys, advertisements in shopping malls, product packaging, etc.). In some examples, an entire family may be enrolled as a household of panelists. That is, while a mother, a father, a son, and a daughter may each be identified as individual panelists, their viewing activities typically occur within the family's household.

[0030] In the illustrated example, one or more panelists **106**, **107**, and **108** of the household have registered with an audience measurement entity (e.g., by agreeing to be a panelist) and have provided their demographic information to the audience measurement entity as part of a registration process to enable associating demographics with media exposure activities (e.g., television exposure, radio exposure, Internet exposure, etc.). The demographic data includes, for example, age, gender, income level, educational level, marital status, geographic location, race, etc., of a panelist. While the example media presentation environment **104** is a household, the example media presentation environment **104** can additionally or alternatively be any other type(s)

of environments such as, for example, a theater, a restaurant, a tavern, a retail location, an arena, etc.

[0031] In the illustrated example of FIG. 1, the example media device **110** is a television. However, the example media device **110** can correspond to any type of audio, video, and/or multimedia presentation device capable of presenting media audibly and/or visually. In some examples, the media device **110** (e.g., a television) may communicate audio to another media presentation device (e.g., an audio/video receiver) for output by one or more speakers (e.g., surround sound speakers, a sound bar, etc.). As another example, the media device **110** can correspond to a multimedia computer system, a personal digital assistant, a cellular/mobile smartphone, a radio, a home theater system, stored audio and/or video played back from a memory such as a digital video recorder or a digital versatile disc, a webpage, and/or any other communication device capable of presenting media to an audience (e.g., the panelists **106**, **107**, and **108**).

[0032] The media source **112** may be any type of media provider(s), such as, but not limited to, a cable media service provider, a radio frequency (RF) media provider, an Internet based provider (e.g., IPTV), a satellite media service provider, etc. The media may be radio media, television media, pay per view media, movies, Internet Protocol Television (IPTV), satellite television (TV), Internet radio, satellite radio, digital television, digital radio, stored media (e.g., a compact disk (CD), a Digital Versatile Disk (DVD), a Blu-ray disk, etc.), any other type(s) of broadcast, multicast and/or unicast medium, audio and/or video media presented (e.g., streamed) via the Internet, a video game, targeted broadcast, satellite broadcast, video on demand, etc.

[0033] The example media device **110** of the illustrated example shown in FIG. 1 is a device that receives media from the media source **112** for presentation. In some examples, the media device **110** is capable of directly presenting media (e.g., via a display) while, in other examples, the media device **110** presents the media on separate media presentation equipment (e.g., speakers, a display, etc.). Thus, as used herein, “media devices” may or may not be able to present media without assistance from a second device. Media devices are typically consumer electronics. For example, the media device **110** of the illustrated example could be a personal computer such as a laptop computer, and, thus, capable of directly presenting media (e.g., via an integrated and/or connected display and speakers). In some examples, the media device **110** can correspond to a television and/or display device that supports the National Television Standards Committee (NTSC) standard, the Phase Alternating Line (PAL) standard, the Système Électronique pour Couleur avec Mémoire (SECAM) standard, a standard developed by the Advanced Television Systems Committee (ATSC), such as high definition television (HDTV), a standard developed by the Digital Video Broadcasting (DVB) Project, etc. Advertising, such as an advertisement and/or a preview of other programming that is or will be offered by the media source **112**, etc., is also typically included in the media. While a television is shown in the illustrated example, any other type(s) and/or number(s) of media device(s) may additionally or alternatively be used. For example, Internet-enabled mobile handsets (e.g., a smartphone, an iPod®, etc.), video game consoles (e.g., Xbox®, PlayStation 3, etc.), tablet computers (e.g., an iPad®, a Motorola™ Xoom™, etc.), digital media players (e.g., a Roku® media player, a Slingbox®, a Tivo®, etc.), smart televisions, desktop computers, laptop computers, servers, etc. may additionally or alternatively be used.

[0034] The example meter **102** detects exposure to media and electronically stores monitoring information (e.g., a code/watermark detected with the presented media, a signature of the presented media, an identifier of a panelist present at the time of the presentation, a timestamp of the time of the presentation) of the presented media. The stored monitoring information is then transmitted back to the central facility **114** via the gateway **116** and the network **118**. While the media monitoring information is transmitted by electronic transmission in the illustrated example of FIG. 1, the media monitoring information may additionally or alternatively be transferred in any other manner, such as, for example, by physically mailing the meter **102**, by physically mailing a memory of the meter **102**, etc.

[0035] The meter **102** of the illustrated example of FIG. 1 combines media measurement data and people metering data. For example, media measurement data is determined by monitoring media output by the media device **110** and/or other media presentation device(s), and people metering data (also referred to as demographic data, people monitoring data, etc.) is determined by monitoring people with the meter **102**. Thus, the example meter **102** provides dual functionality of a media meter to collect content media measurement data and a people meter to collect and/or associate demographic information corresponding to the collected media measurement data.

[0036] For example, the meter **102** of the illustrated example collects media identifying information and/or data (e.g., signature(s), fingerprint(s), code(s), tuned channel identification information, time of exposure information, etc.) and people data (e.g., user identifiers, demographic data associated with audience members, etc.). The media identifying information and the people data can be combined to generate, for example, media exposure data (e.g., ratings data) indicative of amount(s) and/or type(s) of people that were exposed to specific piece(s) of media distributed via the media device **110**. To extract media identification data, the meter **102** and/or the example audience measurement system **100** extracts and/or processes the collected media identifying information and/or data received by the meter **102**, which can be compared to reference data to perform source and/or content identification. Any other type(s) and/or number of media monitoring techniques can be supported by the meter **102**.

[0037] Depending on the type(s) of metering the meter **102** is to perform, the meter **102** can be physically coupled to the media device **110** or may be configured to capture signals emitted externally by the media device **110** (e.g., free field audio) such that direct physical coupling to the media device **110** is not required. For example, the meter **102** of the illustrated example may employ non-invasive monitoring not involving any physical connection to the media device **110** (e.g., via Bluetooth® connection, WIFI® connection, acoustic watermarking, etc.) and/or invasive monitoring involving one or more physical connections to the media device **110** (e.g., via USB connection, a High Definition Media Interface (HDMI) connection, an Ethernet cable connection, etc.).

[0038] In examples disclosed herein, to monitor media presented by the media device **110**, the meter **102** of the illustrated example employs audio watermarking techniques and/or signature based-metering techniques. Audio watermarking is a technique used to identify media, such as television broadcasts, radio broadcasts, advertisements (television and/or radio), downloaded media, streaming media, prepackaged media, etc. Existing audio watermarking techniques identify media by embedding one or more audio codes (e.g., one or more watermarks), such as media identifying information and/or an identifier that may be mapped to media identifying information, into an audio and/or video component of the media. In some examples, the audio or video component is selected to have a signal characteristic sufficient to hide the watermark. As used herein, the terms “code” and “watermark” are used interchangeably and are defined to mean any identification information (e.g., an identifier) that may be inserted or embedded in the audio or video of media (e.g., a program or advertisement) for the purpose of identifying the media or for another purpose such as tuning (e.g., a packet identifying header). As used herein “media” refers to audio and/or visual (still or moving) content and/or advertisements. To identify watermarked media, the watermark(s) are extracted and used to access a table of reference watermarks that are mapped to media identifying information.

[0039] Unlike media monitoring techniques based on codes and/or watermarks included with and/or embedded in the monitored media, fingerprint or signature-based media monitoring techniques generally use one or more inherent characteristics of the monitored media during a monitoring time interval to generate a substantially unique proxy for the media. Such a proxy is referred to as a signature or fingerprint, and can take any form (e.g., a series of digital values, a waveform, etc.) representative of any aspect(s) of the media signal(s) (e.g., the audio and/or video signals forming the media presentation being monitored). A signature may be a series of signatures

collected in series over a timer interval. A good signature is repeatable when processing the same media presentation, but is unique relative to other (e.g., different) presentations of other (e.g., different) media. Accordingly, the term “fingerprint” and “signature” are used interchangeably herein and are defined herein to mean a proxy for identifying media that is generated from one or more inherent characteristics of the media.

[0040] Signature-based media monitoring generally involves determining (e.g., generating and/or collecting) signature(s) representative of a media signal (e.g., an audio signal and/or a video signal) output by a monitored media device and comparing the monitored signature(s) to one or more references signatures corresponding to known (e.g., reference) media sources. Various comparison criteria, such as a cross-correlation value, a Hamming distance, etc., can be evaluated to determine whether a monitored signature matches a particular reference signature. When a match between the monitored signature and one of the reference signatures is found, the monitored media can be identified as corresponding to the particular reference media represented by the reference signature that with matched the monitored signature. Because attributes, such as an identifier of the media, a presentation time, a broadcast channel, etc., are collected for the reference signature, these attributes may then be associated with the monitored media whose monitored signature matched the reference signature. Example systems for identifying media based on codes and/or signatures are long known and were first disclosed in Thomas, U.S. Pat. No. 5,481,294, which is hereby incorporated by reference in its entirety.

[0041] For example, the meter **102** of the illustrated example senses audio (e.g., acoustic signals or ambient audio) output (e.g., emitted) by the media device **110**. For example, the meter **102** processes the signals obtained from the media device **110** to detect media and/or source identifying signals (e.g., audio watermarks) embedded in portion(s) (e.g., audio portions) of the media presented by the media device **110**. To sense ambient audio output by the media device **110**, the meter **102** of the illustrated example includes an example audio sensor **120** (e.g., a microphone). In some examples, the meter **102** may process audio signals obtained from the media device **110** via a direct cable connection to detect media and/or source identifying audio watermarks embedded in such audio signals. In some examples, the meter **102** may process audio signals and/or video signals to generate respective audio and/or video signatures from the media presented by the media device **110**.

[0042] To generate exposure data for the media, identification(s) of media to which the audience is exposed are correlated with people data (e.g., presence information) collected by the meter **102**. The meter **102** of the illustrated example collects inputs (e.g., audience monitoring data) representative of the identities of the audience member(s) (e.g., the panelists **106**, **107**, and **108**). In some examples, the meter **102** collects audience monitoring data by periodically or a-periodically prompting audience members in the monitored media presentation environment **104** to identify themselves as present in the audience (e.g., audience identification information). In some examples, the meter **102** responds to events (e.g., when the media device **110** is turned on, a channel is changed, an infrared control signal is detected, etc.) by prompting the audience member(s) to self-identify.

[0043] In some examples, the meter **102** determines an audience composition by utilizing the audio sensor **120**, an example thermal imaging sensor **124**, and/or an example light imaging sensor **125**. For example, the audio sensor **120** records samples of audio data of the media presentation environment **104** and provides the audio data to the meter **102** to detect one or more speech patterns. In some examples, the thermal imaging sensor **124** captures frames of thermal image data of the media presentation environment **104** and provides the thermal image data to the meter **102** to detect human sized blobs of heat. Additionally or alternatively, the light imaging sensor **125** captures frames of audience image data of the media presentation environment **104** and provides the audience image data to the meter **102**, which performs facial recognition and/or other image processing to identify the panelists **106**, **107**, **108** represented in the image data. In some examples,

the meter **102** responds to events (e.g., when the media device **110** is turned on, a channel is changed, an infrared control signal is detected, etc.) by prompting the audio sensor **120** to record audio samples, prompting the thermal imaging sensor **124** to capture thermal images, and/or prompting the light imaging sensor **125** to capture audience images.

[0044] The example audio sensor **120** of the illustrated example of FIG. **1** is a microphone. The example audio sensor **120** receives ambient sound (e.g., free field audio) including audible media and/or audience sounds from the audience members in the vicinity of the meter **102**. Additionally or alternatively, the example audio sensor **120** may be implemented by a line input connection. The line input connection may allow an external microphone to be used with the meter **102** and/or, in some examples, may enable the audio sensor **120** to be directly connected to an output of a media device **110** (e.g., an auxiliary output of a television, an auxiliary output of an audio/video receiver of a home entertainment system, etc.). In some examples, the meter **102** is positioned in a location such that the audio sensor **120** receives ambient audio produced by the television and/or other devices of the media presentation environment **104** (FIG. **1**) with sufficient quality to identify media presented by the media device **110** and/or other devices of the media presentation environment **104** (e.g., a surround sound speaker system). For example, in examples disclosed herein, the meter **102** may be placed on top of the television, secured to the bottom of the television, etc. In some examples, the audio sensor **120** also receives audio produced by audience members (e.g., the panelists **106**, **107**, **108**) of the media presentation environment **104** with sufficient quality to identify speech patterns of the panelists **106**, **107**, **108**. While the illustrated example of FIG. **1** includes the audio sensor **120**, examples disclosed herein can additionally or alternatively use multiple audio sensors. For example, one or more audio sensors can be positioned to receive audio from the media device, and one or more audio sensors can be positioned to receive audio from a location in which an audience is expected to be present (e.g., an expected distance corresponding to a couch, etc.). In such an example, audio sensor(s) positioned to receive audio from the media device are positioned relatively closer to the media device and the audio sensor(s) positioned to receive audio from the audience members are positioned relatively closer to the expected location of the audience members.

[0045] The example thermal imaging sensor **124** utilizes heat energy of an environment (e.g., the media presentation environment **104**) to generate thermal image data. The example thermal imaging sensor **124** records the temperature of various objects in the frame, and then assigns different shades of colors to corresponding different temperatures (e.g., to different ranges of temperatures). In some such examples, a particular shade of color indicates how much heat is radiating off an object compared to the other objects in the frame. For example, the thermal imaging sensor **124** includes measuring devices that capture infrared radiation (e.g., microbolometers) associated with each pixel in the frame. The measuring devices then record the temperature of the pixel and assign the pixel to an appropriate color. In some examples, the thermal imaging sensor **124** is configured to assign a greyscale to pixels in a frame, where white may be indicative of “hot” (e.g., the highest temperature in the frame) and dark grey/black may be indicative of “cold” (e.g., the lowest temperature in the frame). In some examples, the thermal imaging sensor **124** is configured to assign warm and cool colors (e.g., warm corresponding to red, orange, and yellow colors; cool corresponding to green, blue, and purple colors) to the pixels in a frame, where the warm colors may be indicative of relatively higher temperatures and the cool colors may be indicative of relatively lower temperatures. In some examples, a human radiates more heat (e.g., is associated with a higher temperature) than inanimate objects, such as a couch or remote control device.

[0046] The example light imaging sensor **125** captures audience image data from an environment (e.g., the media presentation environment **104**). The example light imaging sensor **125** of the illustrated example of FIG. **1** is a camera. The example light imaging sensor **125** receives light waves, such as the light waves emitting from the example media device **110** and converts them into

signals that convey information. Additionally or alternatively, the light imaging sensor **125** generates audience image data representing objects present within the field of view (FOV) of the light imaging sensor **125**. In examples disclosed herein, the FOV of the light imaging sensor **125** is based on the thermal image data generated by the thermal imaging sensor **124**. For example, the light imaging sensor **125** can control (or be controlled) to focus its FOV to correspond to locations in the thermal image frames that include audience members. For example, the meter **102** determines locations in the thermal image frames with warm colors (e.g., temperature of a human). In some examples, the thermal imaging sensor **124** collects frames of thermal data including temperatures indicative of the panelists **106** and **107**. The example meter **102** controls the light imaging sensor **125** to capture frames of audience image data corresponding to the thermal image frames indicative of humans. Thus, the FOV of the light imaging sensor **125** includes the panelists **106** and **107** but not the panelist **108**.

[0047] The audience monitoring data and the exposure data can then be compiled with the demographic data collected from audience members such as, for example, the panelists **106**, **107**, and **108** during registration to develop metrics reflecting, for example, the demographic composition of the audience. The demographic data includes, for example, age, gender, income level, educational level, marital status, geographic location, race, etc., of the panelist. In some examples, the registration of panelists includes recording samples of audio data for each panelist of the household. For example, the meter **102** records the panelists **106**, **107**, **108** saying one or more phrases. In examples disclosed herein, the recordings are used as reference samples of the panelists. In some examples, the meter **102** generates and stores reference signatures of the reference samples. That is, the reference audience signatures can be stored locally at the meter **102**, stored at the central facility **114** for signature matching, etc.

[0048] In some examples, the meter **102** may be configured to receive audience information via an example input device **122** such as, for example, a remote control, An Apple iPad®, a cell phone, etc. In such examples, the meter **102** prompts the audience members to indicate their presence by pressing an appropriate input key on the input device **122**. For example, the input device **122** may enable the audience member(s) (e.g., the panelists **106**, **107**, and **108** of FIG. 1) and/or an unregistered user (e.g., a visitor to a panelist household) to input information to the meter **102** of FIG. 1. This information includes registration data to configure the meter **102** and/or demographic data to identify the audience member(s). For example, the input device **122** may include a gender input interface, an age input interface, and a panelist identification input interface, etc. Although FIG. 1 illustrates multiple input devices **122**, the example media presentation environment **104** may include an input device **122** with multiple inputs for multiple panelists. For example, an input device **122** can be utilized as a household input device **122** where panelists of the household may each have a corresponding input assigned to them.

[0049] The example gateway **116** of the illustrated example of FIG. 1 is a router that enables the meter **102** and/or other devices in the media presentation environment (e.g., the media device **110**) to communicate with the network **118** (e.g., the Internet.)

[0050] In some examples, the example gateway **116** facilitates delivery of media from the media source **112** to the media device **110** via the Internet. In some examples, the example gateway **116** includes gateway functionality, such as modem capabilities. In some other examples, the example gateway **116** is implemented in two or more devices (e.g., a router, a modem, a switch, a firewall, etc.). The gateway **116** of the illustrated example may communicate with the network **118** via Ethernet, a digital subscriber line (DSL), a telephone line, a coaxial cable, a USB connection, a Bluetooth connection, any wireless connection, etc.

[0051] In some examples, the example gateway **116** hosts a Local Area Network (LAN) for the media presentation environment **104**. In the illustrated example, the LAN is a wireless local area network (WLAN), and allows the meter **102**, the media device **110**, etc. to transmit and/or receive data via the Internet. Alternatively, the gateway **116** may be coupled to such a LAN. In some

examples, the gateway **116** may be implemented with the example meter **102** disclosed herein. In some examples, the gateway **116** may not be provided. In some such examples, the meter **102** may communicate with the central facility **114** via cellular communication (e.g., the meter **102** may employ a built-in cellular modem).

[0052] The network **118** of the illustrated example is a wide area network (WAN) such as the Internet. However, in some examples, local networks may additionally or alternatively be used. Moreover, the example network **118** may be implemented using any type of public or private network, such as, but not limited to, the Internet, a telephone network, a local area network (LAN), a cable network, and/or a wireless network, or any combination thereof.

[0053] The central facility **114** of the illustrated example is implemented by one or more servers. The central facility **114** processes and stores data received from the meter **102**. For example, the example central facility **114** of FIG. 1 combines audience monitoring data and program identification data from multiple households to generate aggregated media monitoring information. The central facility **114** generates reports for advertisers, program producers and/or other interested parties based on the compiled statistical data. Such reports include extrapolations about the size and demographic composition of audiences of content, channels and/or advertisements based on the demographics and behavior of the monitored panelists.

[0054] As noted above, the meter **102** of the illustrated example provides a combination of media (e.g., content) metering and people metering. The example meter **102** of FIG. 1 is a stationary device that may be disposed on or near the media device **110**. The meter **102** of FIG. 1 includes its own housing, processor, memory and/or software to perform the desired audience measurement and/or people monitoring functions.

[0055] In examples disclosed herein, an audience measurement entity provides the meter **102** to the panelist **106**, **107**, and **108** (or household of panelists) such that the meter **102** may be installed by the panelist **106**, **107** and **108** by simply powering the meter **102** and placing the meter **102** in the media presentation environment **104** and/or near the media device **110** (e.g., near a television set). In some examples, more complex installation activities may be performed such as, for example, affixing the meter **102** to the media device **110**, electronically connecting the meter **102** to the media device **110**, etc.

[0056] To identify and/or confirm the presence of a panelist present in the media device **110**, the example meter **102** of the illustrated example includes an example display **132**. For example, the display **132** provides identification of the panelists **106**, **107**, **108** present in the media presentation environment **104**. For example, in the illustrated example, the meter **102** displays indicia or visual indicators (e.g., illuminated numerals **1**, **2** and **3**) identifying and/or confirming the presence of the first panelist **106**, the second panelist **107**, and the third panelist **108**.

[0057] FIG. 2 illustrates a block diagram of the example meter **102** of FIG. 1 to generate exposure data for the media. The example meter **102** of FIG. 2 is coupled to the example audio sensor **120**, the example thermal imaging sensor **124**, and the example light imaging sensor **125** of FIG. 1 to determine audience composition based on samples of audio data, frames of thermal image data, and/or frames of audience image data. The example meter **102** of FIG. 2 includes an example media identifier **204**, an example network communicator **206**, an example communication processor **208**, an example people meter **210**, an example media measurement data controller **212**, and an example data store **214**.

[0058] The example media identifier **204** of the illustrated example of FIG. 2 analyzes signals received via the light imaging sensor **125** and/or via the audio sensor **120** and identifies the media being presented. The example media identifier **204** of the illustrated example outputs an identifier of the media (e.g., media-identifying information) to the media measurement data controller **212**. In some examples, the media identifier **204** utilizes audio and/or video watermarking techniques to identify the media. Additionally or alternatively, the media identifier **204** utilizes signature-based media identification techniques. For example, the media identifier **204** generates one or more

signatures of the audio received from the audio sensor **120**. As described above, the meter **102** may include one or more audio sensors. In such an example, the media identifier **204** may generate one or more signatures of the audio received from the audio sensor that is relatively closer to the media device (e.g., the media device **110**). In some examples, the media identifier **204** outputs generated signatures of the audio data to the example people meter **210**.

[0059] The example network communicator **206** of the illustrated example of FIG. 2 is a communication interface configured to receive and/or otherwise transmit corresponding communications to and/or from the central facility **114**. In the illustrated example, the network communicator **206** facilitates wired communication via an Ethernet network hosted by the example gateway **116** of FIG. 1. In some examples, the network communicator **206** is implemented by a Wi-Fi radio that communicates via the LAN hosted by the example gateway **116**. In other examples disclosed herein, any other type of wireless transceiver may additionally or alternatively be used to implement the network communicator **206**. In examples disclosed herein, the example network communicator **206** communicates information to the communication processor **208** which performs actions based on the received information. In other examples disclosed herein, the network communicator **206** may transmit media measurement information provided by the media measurement data controller **212** (e.g., data stored in the data store **214**) to the central facility **114** of the media presentation environment **104**.

[0060] The example communication processor **208** of the illustrated example of FIG. 2 receives information from the network communicator **206** and performs actions based on that received information. For example, the communication processor **208** packages records corresponding to collected exposure data and transmits the records to the central facility **114**. In examples disclosed herein, the communication processor **208** communicates with the people meter **210** and/or a media measurement data controller **212** to transmit people count data, demographic data, etc., to the network communicator **206**.

[0061] The example people meter **210** of the illustrated example of FIG. 2 determines audience monitoring data representative of the number and/or identities of the audience member(s) (e.g., panelists) present in the media presentation environment **104**. In the illustrated example, the people meter **210** is coupled to the audio sensor **120**, the thermal imaging sensor **124**, and the light imaging sensor **125**. In some examples, the people meter **210** is coupled to the audio sensor **120**, the thermal imaging sensor **124**, and/or the light imaging sensor **125** via a direct connection (e.g., Ethernet) or indirect communication through one or more intermediary components. In some examples, the audio sensor **120**, the thermal imaging sensor **124**, and/or the light imaging sensor **125** are included in (e.g., integrated with) the meter **102**. The example people meter **210** collects data from the example audio sensor **120**, the example thermal imaging sensor **124**, the example light imaging sensor **125**, the example media identifier **204**, and data from example input device(s) **122** corresponding to audience monitoring data. In some examples, the meter **102** includes one or more audio sensors. In such examples, the people meter **210** obtains audio data from the audio sensors that are relatively closer to the expected location of audience members. The people meter **210** may then generate signatures of the audio data. In some examples, the people meter **210** and the media identifier **204** generate signatures using the same technique (e.g., generate unhashed signatures, generate hashed signatures, etc.). Additionally or alternatively, the people meter **210** and the media identifier **204** can generate signatures using different techniques. The example people meter **210** provides the audience monitoring data to the media measurement data controller **212** such that the audience monitoring data can be correlated with the media identification data to facilitate an identification of which media was presented to which audience member (e.g., exposure data). The example people meter **210** is described in further detail below in connection with FIGS. 3, 4, 5, 6, and 7.

[0062] The example media measurement data controller **212** of the illustrated example of FIG. 2 receives media identifying information (e.g., a code, a signature, etc.) from the media identifier **204**

and audience monitoring data from the people meter **210** and stores the received information in the data store **214**. The example media measurement data controller **212** periodically and/or aperiodically transmits, via the network communicator **206**, the media measurement information stored in the data store **214** to the central facility **114** for post-processing of media measurement data, aggregation and/or preparation of media monitoring reports. In some examples, the media measurement data controller **212** generates exposure data. For example, the media measurement data controller **212** correlates the media identifying information with audience monitoring data, as described above, to generate exposure data.

[0063] The example data store **214** of the illustrated example of FIG. 2 may be implemented by any device for storing data such as, for example, flash memory, magnetic media, optical media, etc. Furthermore, the data stored in the example data store **214** may be in any data format such as, for example, binary data, comma delimited data, tab delimited data, structured query language (SQL) structures, etc. In the illustrated example, the example data store **214** stores media identifying information collected by the media identifier **204** and audience monitoring data collected by the people meter **210**.

[0064] FIG. 3 illustrates a block diagram of the example people meter **210** of FIG. 2, which is to determine an audience composition for audience monitoring data in accordance with teachings of this disclosure. The example people meter **210** includes an example people meter controller **302**, an example interface **304**, an example audience audio detector **305**, an example thermal image detector **306**, an example audience image detector **307**, an example comparator **308**, an example people identification model controller **310**, and an example model database **312**.

[0065] The example people meter controller **302** of the illustrated example of FIG. 3 obtains user input from example input device(s) **122**. For example, the panelists **106**, **107**, and **108** may press a key on the respective input device(s) **122** indicating they are in the room (e.g., the media presentation environment **104**). In some examples, the panelists **106**, **107**, **108** enter a username, password, and/or other information to indicate who they are and that they are in the room viewing media. In some examples, the people meter controller **302** determines a people count based on the user input obtained from the input device(s) **122**. For example, the people meter controller **302** may determine that two people (e.g., two of the panelists **106**, **107**, **108**) have indicated their presence in the media presentation environment **104**. In some examples, the people meter controller **302** determines a people count in response to the media device **110** turning on. The example people meter controller **302** provides the people count to the example comparator **308**.

[0066] In some examples, the people meter controller **302** generates prompting messages at periodic and/or aperiodic scheduling intervals. For example, the people meter controller **302** generates a prompting message to be displayed on the media device **110** and/or a display of the meter **102**. The prompting messages can include questions and/or requests to which the panelists **106**, **107**, **108** are to respond. For example, the people meter controller **302** may generate a prompting message every **42** minutes (or at some other interval) asking the panelists **106**, **107**, **108** if they are still viewing the media. In some examples, the people meter controller **302** generates a prompting message based on one or more events, such as when the media device **110** is turned on, when the channel has changed, when the media source has changed, etc. In some examples, the people meter controller **302** receives a trigger from the audience audio detector **305**, the thermal image detector **306**, and/or the audience image detector **307** to determine whether to generate prompting messages or not generate prompting messages. The example people meter controller **302** communicates the prompting messages through the communication processor **208** of FIG. 2 to the media device **110**.

[0067] The example interface **304** of the illustrated example of FIG. 3 communicates between the example audio sensor **120** and the example audience audio detector **305**, the example thermal imaging sensor **124** and the example thermal image detector **306**, and the light imaging sensor **125** and the example audience image detector **307**. For example, the interface **304** obtains data from the

audio sensor **120** and provides the data to the example audience audio detector **305**. The interface **304** can also obtain data from the example thermal imaging sensor **124** and provide the data to the example thermal image detector **306**. Additionally or alternatively, the interface **304** obtains data from the example light imaging sensor **125** and provides the data to the example audience image detector **307**. In some examples, the interface **304** obtains requests from the example audience audio detector **305**, the example thermal image detector **306**, and/or the audience image detector **307** and passes the respective requests to the example audio sensor **120**, the example thermal imaging sensor **124**, and the example light imaging sensor **125**. For example, the interface **304** enables communication between the audio sensor **120** and the audience audio detector **305**, between the thermal imaging sensor **124** and the thermal image detector **306**, and between the light imaging sensor **125** and the audience image detector **307**. In some examples, the interface **304** enables communication between the media identifier **204** and the audience audio detector **305**. For example, the interface **304** obtains data (e.g., signatures) from the media identifier **204** and provides the data to the example audience audio detector **305**. The example interface **304** may be any type of interface, such as a network interface card (NIC), an analog-to-digital converter, a digital-to-analog converter, Universal Serial Bus (USB), GigE, FireWire, Camera Link®, etc. [0068] The example audience audio detector **305** of the illustrated example of FIG. 3 obtains audio data from the example interface **304** and determines the audience composition based on the audio data. For example, the audience audio detector **305** obtains samples of audio data from the audio sensor **120** via the interface **304** and analyzes the samples. For example, the audience audio detector can obtain audio data from the audio sensor **120** and/or the audio sensor closer to the expected location of the audience (e.g., the meter **102** includes multiple audio sensors). In some examples, the audience audio detector **305** includes a signature generator (not illustrated) to generate one or more signatures of the audio data (e.g., using the same signature generating technique as the media identifier **204** (FIG. 2), using a different signature generating technique as the media identifier **204**, etc.).

[0069] Additionally or alternatively, the audience audio detector **305** obtains signatures of the audio data from the media identifier **204** via the interface **304**. That is, in such an example, the audience audio detector **305** may not include a signature generator and instead obtains signatures generated by the media identifier **204**. In some examples, the audience audio detector **305** identifies one or more distinct speech patterns in the signatures. The example audience audio detector **305** determines a people count based on the number of distinct speech patterns. In some examples, the audience audio detector **305** analyzes the detected signatures in comparison to the reference audience signatures to identify audience member(s) (e.g., the voice(s) of the audience member(s)). The example audience audio detector **305** identifies audience members and provides the identification to the example comparator **308**, the example people identification model controller **310**, and/or the example people meter controller **302**. In response to the audience audio detector **305** identifying one or more panelists of the audience, the audience audio detector **305** can trigger the thermal image detector **306** to generate a heat blob count of the media presentation environment **104**.

[0070] In some examples, the audience audio detector **305** is unable to identify the person in the generated signature corresponding to a detected speech pattern. For example, the person corresponding to the speech pattern in the generated signature may be a visitor, a distant relative of the audience member, etc. In such an example, the audience audio detector **305** triggers the thermal image detector **306** and the audience image detector **307** to identify the person in the generated signature. The example audience audio detector **305** is described in further detail below in connection with FIG. 4.

[0071] The example thermal image detector **306** of the illustrated example of FIG. 3 obtains thermal image data from the example interface **304** and determines a heat blob count based on the thermal image data. For example, the thermal image detector **306** obtains frames of thermal image

data from the thermal imaging sensor **124** via the interface **304** and analyzes the frames. In some examples, the thermal image detector **306** determines human sized blobs of heat, or human size heat blobs, in the frames. In some examples, the thermal image detector **306** analyzes the frames of thermal image data for temperature values and particular shapes to evaluate if the blobs are indicative of humans. For example, the frames of thermal image data can include an oval shape corresponding to a temperature in the range of 92.3-98.4° F. (e.g. the body temperature of a human). Additionally or alternatively, the frames of thermal image data can include a rectangular shape corresponding to a temperature of 60° F. (e.g., representative of furniture). The example thermal image detector **306** generates a heat blob count based on the number of detected human size heat blobs and provides the count to the example comparator **308**. In some examples, the example thermal image detector **306** provides output information indicative of thermal image data analysis results to the example people identification model controller **310**. The example thermal image detector **306** is described in further detail below in connection with FIG. 5.

[0072] The example audience image detector **307** of the illustrated example of FIG. 3 obtains audience image data from the example interface **304** and identifies an audience member based on the audience image data. For example, the audience image detector **307** obtains frames of audience image data from the light imaging sensor **125** via the interface **304** and analyzes the frames. In some examples, the audience image detector **307** identifies one or more audience members in the frames using facial recognition analysis. The example audience image detector **307** provides output information indicative of audience member identification to the example people identification model controller **310**.

[0073] In some examples, the audience image detector **307** is unable to identify the person in the frame of audience image data. For example, the person in the frame of audience image data may be a visitor, a distant relative of the audience member, etc. In such an example, the audience image detector **307** triggers the people meter controller **302** to generate a prompting message for additional member logging. As used herein, member logging occurs when a given audience member logs into their respective input device **122** (or into a common input device **122** used in the environment) to indicate that they are viewing the media. The example people meter controller **302** generates the prompting message in an effort to obtain a response to verify the audience composition and generate accurate audience monitoring data. The example audience image detector **307** is described in further detail below in connection with FIG. 6.

[0074] The example comparator **308** of the illustrated example of FIG. 3 obtains the people count from the example audience audio detector **305** and the heat blob count from the example thermal image detector **306** and compares the two count values. The example comparator **308** determines if the count values are equal in value. When the comparator **308** determines the count values match, then the people count is verified. In some examples, when the people count is verified, the example comparator **308** notifies the example people meter controller **302** to reset a scheduling interval timer (e.g., a counter, clock, or other timing mechanisms) that initiate the generation of prompting messages. For example, if the people meter controller **302** is configured to generate prompting messages every 42 minutes, then a timer is set to 42 minutes. When the timer expires, a prompting message is triggered. However, if the comparator **308** verifies the number of people (e.g., the panelists **106**, **107**, **108**) in the media presentation environment **104**, a prompting message is not needed to determine whether people are still viewing the media.

[0075] In some examples, the comparator **308** determines the people count and the heat blob count values are not equal. For example, the comparator **308** may determine the people count is less than the heat blob count (e.g., the audience is undercounted). In such an example, the audience audio detector **305** did not identify a speech pattern for every person in the media presentation environment **104**. In this example, the example comparator **308** triggers the audience image detector **307** to capture a frame of audience image data to identify the people in the media presentation environment **104** via facial recognition. The example audience image detector **307**

captures a frame of audience image data in an effort to identify the people in the audience to verify the heat blob count and generate accurate audience monitoring data.

[0076] In some examples, the comparator **308** determines the people count is greater than the heat blob count (e.g., the audience is overcounted). In such an example, the audience audio detector **305** identified an incorrect number of speech patterns. For example, the audience audio detector **305** may have identified and counted a speech pattern corresponding to media content (e.g., a speaker on television). In some such examples, the comparator **308** triggers the audience image detector **307** to capture a frame of audience image data to identify the people in the media presentation environment **104** via facial recognition. The example audience image detector **307** captures a frame of audience image data in an effort to identify the people in the audience to verify the heat blob count and generate accurate audience monitoring data.

[0077] The example comparator **308** provides the heat blob count to the example people identification model controller **310**. In some examples, the comparator **308** determines a time of the comparison between the people count and the heat blob count and provides the time to the people identification model controller **310**. For example, the comparator **308** may identify 4:58 pm as the time corresponding to the comparison between the people count and the heat blob count. In some examples, the comparator **308** updates, or otherwise trains, the people identification model when the comparator **308** provides the heat blob count and the time corresponding to the comparison to the people identification model controller **310**.

[0078] The example people identification model controller **310** of the illustrated example of FIG. 3 trains a people identification model based on data obtained from the example comparator **308**, the example people meter controller **302**, the example audience audio detector **305**, the example thermal image detector **306**, and/or the example audience image detector **307**. In some examples, the people identification model controller **310** is in communication with the example media measurement data controller **212** of FIG. 2. For example, the people identification model controller **310** obtains information from the media measurement data controller **212** and provides information to the media measurement data controller **212**. In some examples, the data obtained from the media measurement data controller **212** by the people identification model controller **310** includes media identifying information. For example, the people identification model controller **310** queries the media measurement data controller **212** for media identifying information at the time corresponding to the comparison of counts and/or the time corresponding to the identification of audience members. In some examples, the media measurement data controller **212** provides the data to the people identification model controller **310** without receiving a request and/or query. In this manner, the people identification model controller **310** obtains the audience composition at, for example, 4:58 pm and obtains the broadcast channel airing on the media device **110** at 4:58 pm. In some examples, the people identification model controller **310** utilizes the data from one or more of the people meter controller **302**, the audience audio detector **305**, the thermal image detector **306**, the audience image detector **307**, the comparator **308**, and the media measurement data controller **212** to train a model to predict a verified audience composition for particular dates and times.

[0079] In some examples, the people identification model controller **310** passes the verified audience composition to the media measurement data controller **212**. For example, the people identification model controller **310** obtains the verified audience composition, packages the information, and provides the information to the media measurement data controller **212** for generation of exposure data. For example, the media measurement data controller **212** utilizes the information to correlate the verified audience composition with the media identifying information. In some examples, the people identification model controller **310** obtains demographic information from the people meter controller **302** to pass to the media measurement data controller **212**. For example, the people meter controller **302** determines the demographic information corresponding to the audience members logged into the meter **102** and/or identified by the audience audio detector **305** or the audience image detector **307**. In this manner, the example people identification model

controller **310** passes the audience composition (e.g., the people count and the demographic information of the identified audience members), and the time corresponding to the identification to the media measurement data controller **212** to generate exposure data. The example people identification model controller **310** is described in further detail below in connection with FIG. 7.

[0080] The example model database **312** of the illustrated example of FIG. 3 stores people identification models generated by the people identification model controller **310**. For example, the model database **312** may periodically or a-periodically receive new, updated, and/or trained people identification models. In some examples, the model database **312** stores one people identification model. In some examples, the model database **312** stores multiple people identification models. The example model database **312** is utilized for subsequent retrieval by the people meter controller **302**, the audience audio detector **305**, the thermal image detector **306**, the audience image detector **307**, and/or the people identification model controller **310**.

[0081] FIG. 4 is a block diagram illustrating an example implementation of the audience audio detector **305** of FIG. 3. The example audience audio detector **305** of FIG. 3 includes an example audio database **402**, an example speech pattern determination controller **404**, an example sampling controller **406**, an example speech pattern counter **408**, and an example speech pattern identifier **410**.

[0082] The example audio database **402** of the illustrated example of FIG. 4 stores samples of audio data and/or signatures obtained from the example interface **304** of FIG. 3. For example, the audio database **402** stores the samples of audio data captured by the example audio sensor **120** (e.g., one or more audio sensors) and/or signatures generated by the example media identifier **204** for current and/or subsequent use by the speech pattern determination controller **404**. In some examples, the audio database **402** stores tagged and/or analyzed samples of audio data and/or signatures.

[0083] The example speech pattern determination controller **404** of the illustrated example of FIG. 4 obtains samples of audio data and/or signatures from the example audio database **402**. The example speech pattern determination controller **404** analyzes the samples and/or signatures for speech patterns. In an example operation, the speech pattern determination controller **404** identifies portions of the audio data that warrant further attention. For example, the speech pattern determination controller **404** filters the samples for human voices. That is, the speech pattern determination controller applies a low pass filter, a high pass filter, a bandpass filter, etc. to remove frequencies incompatible with human speech (e.g., frequencies corresponding to a dog barking, a police siren, etc.).

[0084] In some examples, the speech pattern determination controller **404** does not detect speech patterns in the sample. In such an example, the speech pattern determination controller **404** may send a trigger to the sampling controller **406** to prompt the sampling controller **406** to record additional samples of audio data of the media presentation environment **104**. For example, the audience audio detector **305** may be initiated to identify speech patterns when the media device **110** is turned on. In such examples, when the media device **110** is turned on, an audience is generally present. If the example speech pattern determination controller **404** does not detect speech patterns, then a recapture of the environment is to occur. For example, an audience member may have briefly left the room after turning on the media device **110**, the audio sensor **120** may have not captured the media presentation environment **104** when the media device **110** was turned on, etc.

[0085] In some examples, the speech pattern determination controller **404** provides the evaluation results to the example people identification model controller **310** (FIG. 3). The example people identification model controller **310** utilizes the filtered output and/or evaluation results as training data for predicting a people count of the media presentation environment **104**.

[0086] The example speech pattern counter **408** of the illustrated example of FIG. 4 obtains the filtered output from the speech pattern determination controller **404** corresponding to a number, if any, of speech patterns. For example, the speech pattern determination controller **404** provides

information indicative of the evaluation of the signatures to the speech pattern counter **408**. In examples disclosed herein, the speech pattern counter **408** determines a number of distinct speech patterns detected in the filtered output. For example, the speech pattern counter **408** may analyze the filtered output to determine the number of distinct speech patterns based on one or more characteristics of the signatures. For example, the characteristics can include vocal tract length, vocal tract shape, pitch, speaking rate, etc. Additionally or alternatively, the speech pattern counter **408** can identify unique speech patterns based on a number of matches corresponding to different reference audience signatures that match the generated signature during a monitoring interval. For example, the monitoring interval can be 30 seconds. In some examples, the monitoring interval is greater than or less than 30 seconds. The example speech pattern counter **408** determines the number of different reference audience signature sets (e.g., corresponding to different audience members) during the monitoring interval. In such an example, the number of matches during the monitoring interval is the number of identified unique speech patterns (e.g., the people count). [0087] The example speech pattern counter **408** includes a counter, such as a device which stores a number of times a distinct characteristic corresponds to a speech pattern. If the example speech pattern counter **408** determines that speech patterns were detected, then the example speech pattern counter **408** increments the counter to the number of speech patterns that were detected. For example, if the speech pattern counter **408** detected five speech patterns, the speech pattern counter **408** stores a count of five speech patterns. If the example speech pattern counter **408** does not receive information indicative of a detection of speech patterns, then the example speech pattern counter **408** updates the speech pattern count with a count of zero. In some examples disclosed herein, the speech pattern count is the people count (e.g., each detected speech pattern corresponds to a person).

[0088] In some examples, the speech pattern counter **408** tags the sample of audio data and/or signatures with the people count. For example, the sample includes metadata indicative of a time the sample was recorded, the size of the sample, the device that captured the sample, etc., and further includes the people count appended by the speech pattern counter **408**. In some examples, the tagged sample is stored in the audio database **402** and/or provided to the example comparator **308** and the example people identification model controller **310**.

[0089] The example speech pattern identifier **410** of the illustrated example of FIG. 4 obtains the filtered output from the speech pattern determination controller **404** corresponding to a number, if any, of speech patterns. For example, the speech pattern determination controller **404** provides information indicative of the evaluation of the sample of audio data and/or signatures to the speech pattern identifier **410**. The example speech pattern identifier **410** includes audience data, such as reference signatures of the speech patterns of the audience members (e.g., panelists) of the household (e.g., the panelists **106**, **107**, **108** of FIG. 1). That is, the speech pattern identifier **410** includes reference speech patterns generated during panelist registration. If the example speech pattern identifier **410** determines speech patterns were detected, the example speech pattern identifier **410** compares the signatures including the detected speech patterns to the reference speech pattern signatures. For example, the speech pattern identifier **410** compares the one or more characteristics of the detected speech patterns and the reference speech patterns to determine a match. If the speech pattern identifier **410** determines a match, the speech pattern identifier **410** logs the corresponding audience member as being identified. In some examples, if the speech pattern identifier **410** determines the detected speech pattern does not match any of the stored audience speech patterns, the speech pattern identifier **410** compares the generated signature of the detected speech pattern to reference signatures stored in the example reference signature database **412** corresponding to media (e.g., television shows, movies, etc.). That is, the speech pattern identifier **410** determines whether the detected speech pattern corresponds to a speaker in a media program rather than an audience member. If the speech pattern identifier **410** determines the detected speech pattern does not match any of the stored reference speech patterns, the speech

pattern identifier **410** may add the respective speech to the audience member data. In some examples, the example speech pattern identifier **410** determines a time of the identification. For example, the speech pattern identifier **410** identifies the timestamp of when the match between the identified speech pattern and the reference speech pattern was determined.

[0090] In some examples, the speech pattern identifier **410** tags the sample of audio data and/or signatures with the audience member identity (e.g., assigned panelist number, visitor number, etc.). For example, the sample includes metadata indicative of a time the sample was recorded, the size of the sample, the device that captured the sample, etc., and further includes the one or more audience member identities identified by the speech pattern identifier **410**. In some examples, the tagged sample is stored in the audio database **402** and/or provided to the example people meter controller **302** and the example people identification model controller **310**.

[0091] In some examples, the audio database **402**, the speech pattern determination controller **404**, the sampling controller **406**, the speech pattern counter **408**, the speech pattern identifier **410** and/or otherwise the audience audio detector **305** may be coupled to the people identification model controller **310** of FIG. 3 in an effort to provide training data (e.g., people monitoring data) to the people identification model. In some examples, it is beneficial to provide training data (e.g., people monitoring data) to the people identification model controller **310** to train the people identification model to predict audience composition at particular times throughout the day

[0092] FIG. 5 is a block diagram illustrating an example implementation of the thermal image detector **306** of FIG. 3. The example thermal image detector **306** of FIG. 3 includes an example thermal image database **502**, an example heat blob determination controller **504**, an example scanning controller **506**, and an example blob counter **508**.

[0093] The example thermal image database **502** of the illustrated example of FIG. 5 stores frames of thermal image data obtained from the example interface **304** of FIG. 3. For example, the thermal image database **502** stores the frames of thermal image data captured by the example thermal imaging sensor **124** for current and/or subsequent use by the heat blob determination controller **504**. In some examples, the thermal image database **502** stores tagged and/or analyzed frames of thermal image data.

[0094] The example heat blob determination controller **504** of the illustrated example of FIG. 5 obtains a frame of the thermal image data from the example thermal image database **502**. The example heat blob determination controller **504** analyzes the frame for human sized heat blobs. In an example operation, the heat blob determination controller **504** identifies portions of the frame that warrant further attention. For example, the heat blob determination controller **504** detects warm areas of the frame that are to be analyzed further. A warm area of the frame can be determined based on the color of the pixels in that area. In some examples, the heat blob determination controller **504** includes configuration data corresponding to the color scale of the thermal image data. The example heat blob determination controller **504** utilizes the color scale to identify temperature associated with a pixel color. In some examples, the configuration data is specific to the particular thermal imaging sensor **124**. For example, the configuration data may be based on whether the thermal imaging sensor **124** includes an image processor with greyscale imaging, colored imaging, etc. For example, the configuration data for an example greyscale implementation heat blob determination controller **504** may specify that a white-colored pixel is associated with a first temperature, a lighter grey-colored pixel is associated with a second temperature lower than the first temperature, and a black-colored pixel is associated with a third temperature lower than both the first and second temperatures. Configuration data for an example color scale implementation of the heat blob determination controller **504** may specify that a red-colored pixel is associated with a first temperature, an orange-colored pixel is associated with a second temperature relatively lower than the first temperature, and a yellow-colored pixel is associated with a third temperature relatively lower than both the first and second temperatures.

[0095] In further operation, the heat blob determination controller **504** detects features of the frame

that are incompatible with the presence of a human, or a small group of humans, and discards those features. For example, the heat blob determination controller **504** identifies cool areas of the frame, areas with hard edges, etc. By discarding the incompatible features, the example heat blob determination controller **504** improves the probability and accuracy of detecting a human size heat blob.

[0096] The example heat blob determination controller **504** filters the identified areas of the frame by applying symmetry, size, and/or distance constraints. For example, the heat blob determination controller **504** utilizes convolutional filtering, where a filter (or multiple filters) indicative of a shape (e.g., a target shape of a potential heat blob), size (e.g., a target size of a potential heat blob), and/or distance (e.g., an expected distance of a potential heat blob) is convolved over the identified areas of the frame. In such an example, edge detection techniques may be utilized to identify an area of the frame that corresponds to an edge (e.g., an outline of a human head, arm, leg, etc.), where the identified area is convolved with one or more filters. For example, the heat blob determination controller **504** may implement step detection, change detection, and any other edge detection techniques to identify an area of the frame corresponding to an edge. The example heat blob determination controller **504** filters the identified areas of the frame to detect lines and features that correspond to the shape of a human. In some examples, the heat blob determination controller **504** performs multiple filtering techniques with multiple filters.

[0097] In some examples, the filters of the heat blob determination controller **504** are calibrated based on the location and/or positioning of the thermal imaging sensor **124** in the media presentation environment **104**. For example, the heat blob determination controller **504** includes positioning information of the thermal imaging sensor **124**. Such positioning information can be used to determine distance between the thermal imaging sensor **124** and an area of interest in a thermal image frame. In some examples, the filters are adjusted to accommodate for the determined distance. For example, if the heat blob determination controller **504** determines an area of interest was captured x feet away from the thermal imaging sensor **124**, then the filters are adjusted (e.g., tuned, updated, etc.) to include reduced and/or increased sized shapes (e.g., based on the value of x).

[0098] In some examples, the heat blob determination controller **504** fuses and/or otherwise connects two or more outputs of the filter detection for evaluation of the frame. For example, the connected outputs include information indicative of one or more shapes in the frame. In some examples, neural networks, adaptive boosting, and/or other types of models are used to evaluate the connected (e.g., fused) outputs of the filter detection. After evaluation, the example heat blob determination controller **504** identifies one or more human size heat blobs. In some examples, the heat blob determination controller **504** outputs the evaluation to the example blob counter **508**.

[0099] In some examples, the heat blob determination controller **504** does not detect human size heat blobs in the frame. In such an example, the heat blob determination controller **504** may send a trigger to the scanning controller **506** to prompt the scanning controller **506** to capture more frames of thermal image data of the media presentation environment **104**. For example, the thermal image detector **306** may be initiated to detect heat blobs (e.g., heat representation of the exterior temperature of an object or person) when the media device **110** is turned on. In such examples, when the media device **110** is turned on, an audience is generally present. Additionally or alternatively, the thermal image detector **306** may be initiated to detect heat blobs when the audience audio detector **305** identifies speech patterns and/or audience members. For example, when a speech pattern and/or an audience member is identified based on audio data, an audience is generally present. If the example heat blob determination controller **504** does not detect human size heat blobs, then a recapture of the environment is to occur. For example, an audience member may have briefly left the room after turning on the media device **110**, the thermal imaging sensor **124** may have not captured the media presentation environment **104** when the media device **110** was turned on, etc.

[0100] In some examples, the heat blob determination controller **504** provides the connected output and/or evaluation results to the example people identification model controller **310**. The example people identification model controller **310** utilizes the connected output and/or evaluation results as training data for predicting a people count of the media presentation environment **104**.

[0101] The example blob counter **508** of the illustrated example of FIG. 5 obtains the evaluation output from the heat blob determination controller **504** corresponding to a number, if any, of human size heat blobs. For example, the heat blob determination controller **504** provides information indicative of the evaluation of the frame of thermal image data to the blob counter **508**. The example blob counter **508** includes a counter, such as a device which stores a number of times a heat blob corresponds to a human. If the example blob counter **508** determines that human size heat blobs were detected, then the example blob counter **508** increments the counter to the number of heat blobs that were detected. For example, if the heat blob determination controller **504** detected five human size heat blobs, the blob counter **508** stores a count of five heat blobs. If the example blob counter **508** does not receive information indicative of a detection of human size heat blobs, then the example blob counter **508** updates the blob counter with a count of zero.

[0102] In some examples, the blob counter **508** tags the frame of thermal image data with the heat blob count. For example, the frame includes metadata indicative of a time the frame was captured, the size of the frame, the device that captured the frame, etc., and further includes the heat blob count appended by the blob counter **508**. In some examples, the tagged frame is stored in the thermal image database **502** and/or provided to the example comparator **308** and the example people identification model controller **310**.

[0103] In some examples, the thermal image database **502**, the heat blob determination controller **504**, the scanning controller **506**, the blob counter **508**, and/or otherwise the thermal image detector **306** may be coupled to the people identification model controller **310** of FIG. 3 in an effort to provide training data (e.g., people monitoring data) to the people identification model. In some examples, it is beneficial to provide training data (e.g., people monitoring data) to the people identification model controller **310** to train the people identification model to predict heat blob counts at particular times throughout the day.

[0104] FIG. 6 is a block diagram illustrating an example implementation of the audience image detector **307** of FIG. 3. The example audience image detector **307** of FIG. 3 includes an example audience image database **602**, an example facial feature determination controller **604**, an example scanning controller **606**, and an example audience identifier **608**.

[0105] The example audience image database **602** of the illustrated example of FIG. 6 stores frames of audience image data obtained from the example interface **304** of FIG. 3. For example, the audience image database **602** stores the frames of audience image data captured by the example light imaging sensor **125** for current and/or subsequent use by the facial feature determination controller **604**. In some examples, the audience image database **602** stores tagged and/or analyzed frames of audience image data.

[0106] The example facial feature determination controller **604** of the illustrated example of FIG. 6 obtains a frame of the audience image data from the example audience image database **602**. The example facial feature determination controller **604** analyzes the frame for audience member faces. In an example operation, the facial feature determination controller **604** identifies portions of the frame that warrant further attention. For example, the facial feature determination controller **604** detects facial features present in the frame that are to be analyzed further. For example, the facial feature determination controller **604** detects eyes, a nose, a mouth, etc. using object-class detection.

[0107] In further operation, the facial feature determination controller **604** detects features of the frame that are incompatible with the presence of a human, or a small group of humans, and discards those features. For example, the facial feature determination controller **604** identifies areas with hard edges, inanimate objects (e.g., a table, a chair, a phone, etc.), etc. By discarding the incompatible features, the example facial feature determination controller **604** improves the

probability and accuracy of detecting a human face.

[0108] The example facial feature determination controller **604** filters the identified areas of the frame by applying symmetry, size, and/or distance constraints. For example, the facial feature determination controller **604** utilizes convolutional filtering, where a filter that is indicative of a shape (e.g., a target shape of a potential human face), size (e.g., a target size of a potential human face), and/or distance (e.g., a target distance of a potential human face) is convolved over the identified areas of the frame. In such an example, edge detection techniques may be utilized to identify an area of the frame that corresponds to an edge (e.g., an outline of a human head, arm, leg, etc.), where the identified area is convolved with one or more filters. For example, the facial feature determination controller **604** may implement step detection, change detection, and any other edge detection techniques to identify an area of the frame corresponding to an edge. The example facial feature determination controller **604** filters the identified areas of the frame to detect lines and features that correspond to the shape of a human. In some examples, the facial feature determination controller **604** performs multiple filtering techniques with multiple filters.

[0109] In some examples, the filters of the facial feature determination controller **604** are calibrated based on the location and/or positioning of the light imaging sensor **125** in the media presentation environment **104**. For example, the facial feature determination controller **604** includes positioning information of the light imaging sensor **125**. Such positioning information can be used to determine distance between the light imaging sensor **125** and an area of interest in an image frame. In some examples, the filters are adjusted to accommodate for the determined distance. For example, if the facial feature determination controller **604** determines an area of interest was captured x feet away from the light imaging sensor **125**, then the filters are adjusted (e.g., tuned, updated, etc.) to include reduced and/or increased sized shapes (e.g., based on the value of x).

[0110] In some examples, the facial feature determination controller **604** fuses and/or otherwise connects two or more outputs of the filter detection for evaluation of the frame. For example, the connected outputs include information indicative of one or more shapes in the frame. In some examples, neural networks, adaptive boosting, and/or other types of models are used to evaluate the connected (e.g., fused) outputs of the filter detection. After evaluation, the example facial feature determination controller **604** identifies one or more human faces. In some examples, the facial feature determination controller **604** outputs the evaluation to the example audience identifier **608**.

[0111] In some examples, the facial feature determination controller **604** does not detect human faces in the frame. In such examples, the facial feature determination controller **604** may send a trigger to the scanning controller **606** to prompt the scanning controller **606** to capture more frames of audience image data of the media presentation environment **104**. For example, the audience image detector **307** may be initiated to detect human faces when the thermal image detector **306** detects heat blobs and/or the audience audio detector **305** did not identify one or more people in the audience. In such examples, when heat blobs are detected, an audience is generally present. If the example facial feature determination controller **604** does not detect human faces, then a recapture of the environment is to occur. For example, an audience member may have briefly left the room after turning on the media device **110**, the light imaging sensor **125** may have not captured the media presentation environment **104** when the thermal image detector **306** detected heat blobs, etc.

[0112] In some examples, the facial feature determination controller **604** provides the connected output and/or evaluation results to the example people identification model controller **310**. The example people identification model controller **310** utilizes the connected output and/or evaluation results as training data for predicting a people count of the media presentation environment **104**.

[0113] The example audience identifier **608** of the illustrated example of FIG. 6 obtains the evaluation output from the facial feature determination controller **604** corresponding to a number, if any, of human faces. For example, the facial feature determination controller **604** provides information indicative of the evaluation of the frame of audience image data to the audience identifier **608**. The example audience identifier **608** includes audience data, such as reference

audience member images (e.g., reference audience member images) of the faces of the audience members (e.g., panelists) of the household (e.g., the panelists **106**, **107**, **108** of FIG. 1). If the example audience identifier **608** determines human faces were detected, then the example audience identifier **608** compares the image frames including the human faces to the reference audience member (e.g., panelist) images. If the audience identifier **608** determines a match between the human face and a reference audience member image, the audience identifier **608** logs the audience member as being identified. If the audience identifier **608** determines the human face does not match any of the stored audience member faces in the audience data, the audience identifier **608** may add the respective frame to the audience data.

[0114] In some examples, the audience identifier **608** determines whether the number of identified audience members matches the number of heat blobs. For example, the number of audience members identified by the audience identifier **608** may be less than the number of heat blobs. In such an example, the audience identifier **608** did not identify every member in the audience. For example, the frame of audience image data may include audience members not stored in the reference audience member images (e.g., a visitor). If the audience identifier **608** determines the number of identified audience members does not match the number of heat blobs, the audience identifier **608** triggers the people meter controller **302** to generate a prompting message for additional member logging.

[0115] In some examples, the audience identifier **608** tags the frame of audience image data with the audience member's identity (e.g., assigned panelist number, visitor number, etc.). For example, the frame includes metadata indicative of a time the frame was captured, the size of the frame, the device that captured the frame, etc., and further includes the one or more audience member (e.g., panelist) identities identified by the audience identifier **608**. In some examples, the tagged frame is stored in the audience image database **602** and/or provided to example people identification model controller **310**.

[0116] In some examples, the audience image database **602**, the facial feature determination controller **604**, the scanning controller **606**, the audience identifier **608**, and/or otherwise the audience image detector **307** may be coupled to the people identification model controller **310** of FIG. 3 in an effort to provide training data (e.g., people monitoring data) to the people identification model. In some examples, it is beneficial to provide training data (e.g., people monitoring data) to the people identification model controller **310** to train the people identification model to predict audience composition at particular times throughout the day.

[0117] Turning to FIG. 7 a block diagram illustrating the example people identification model controller **310** of FIG. 3 is depicted to train a model to learn about the presence of an audience of a household media presentation environment. The example people identification model controller **310** includes an example communication controller **702**, an example feature extractor **704**, an example model trainer **706**, an example model updater **708**, and an example model generator **710**.

[0118] The example communication controller **702** of the illustrated example of FIG. 7 obtains information from the example audience audio detector **305** of FIG. 3 to pass to the example media measurement data controller **212** of FIG. 2. The example communication controller **702** is communicatively coupled to the example audience audio detector **305**, the example thermal image detector **306**, the example audience image detector **307**, the example media measurement data controller **212**, and the example feature extractor **704**. In some examples, the communication controller **702** provides the audience composition to the media measurement data controller **212**. For example, the audience audio detector **305** provides an updated and/or accurate audience composition (e.g., panelists **106**, **107**, **108**) viewing media in the media presentation environment **104**. An updated and/or accurate audience composition is a verified audience composition based on the audience member identification from the audience audio detector **305** and/or the audience image detector **307** of FIG. 3. In some examples, the communication controller **702** obtains demographic data from the people meter controller **302**, indicative of the demographics of the

people in the media presentation environment **104**, and provides the demographic data to the media measurement data controller **212**.

[0119] The example feature extractor **704** of the illustrated example of FIG. 7 extracts features from information obtained from the example audience audio detector **305** of FIG. 3, the example thermal image detector **306** of FIG. 3, the example audience image detector **307** of FIG. 3, the example people meter controller **302** of FIG. 3, and the media measurement data controller **212** of FIG. 2. For example, the feature extractor **704** obtains people monitoring data, over time, from one or more of the audience audio detector **305**, the example thermal image detector **306** of FIG. 3, the example audience image detector **307** of FIG. 3, the people meter controller **302**, and the media measurement data controller **212**, and generates a feature vector corresponding to the people monitoring data. In some examples, the feature extractor **704** obtains multiple instances of people monitoring data before generating a feature vector. For example, the feature extractor **704** obtains people monitoring data over the span of a week. The example feature extractor **704** generates or builds derived values of feature vectors (e.g., representative of features in the people monitoring data) that are to be informative and non-redundant to facilitate the training phase of the people identification model controller **310**. As used herein, a feature vector is an n-dimensional array (e.g., a vector) of features that represent some physical environment, media display, measurement parameter, etc. For example, a feature vector represents descriptive characteristics of the media presentation environment at a particular date and time.

[0120] In the illustrated example of FIG. 7, the feature vector can determine the number of people and/or the identity of the people accounted for in the media presentation environment **104** in addition to the time at which they were accounted, and the media displayed at the time for which they were accounted. The feature vector provided by the feature extractor **704** facilitates the model trainer **706** in training a people identification model to determine an audience composition for a time and a media type. For example, at time t1 on date X in the media presentation environment **104**, the feature extractor **704** extracts data indicative of media identifying information for a broadcast of “ABC the Bachelor,” as well as data indicative that three identified audience members are viewing the broadcast.

[0121] In some examples, these extracted features, by themselves, may have limited usefulness, because there is just one such feature event in a given instance of people monitoring data. However, if the feature extractor **704** extracts feature data from multiple instances of people monitoring data, the generated feature vector may be sufficient to train the people identification model. For example, the feature extractor **704** extracts feature data having date X, Y, and Z at the time t1, indicative of media identifying information for the broadcast of “ABC the Bachelor” and indicative that three identified audience members are viewing the broadcast. In such an example, the model trainer **706** can utilize the feature vector to train the people identification model to predict the audience composition for time t1.

[0122] The example model trainer **706** of the illustrated example of FIG. 7 trains the people identification model based on the output feature vector of the feature extractor **704**. The model trainer **706** operates in a training mode where it receives multiple instances of people monitoring data, generates a prediction, and outputs a people identification model based on that prediction. For the example model trainer **706** generates a people identification model, the model trainer **706** receives feature vectors corresponding to actual representations of the media presentation environment **104**. For example, during a training mode, verifications are made about the audience composition of the media presentation environment **104** so that the data they provide to the audience audio detector **305** is suitable for learning. For example, the model trainer **706** receives a feature vector indicative of the features of an actual media presentation environment and identifies a pattern in the features that maps the dates and times of the actual media presentation environment to the audience composition and outputs a model that captures these daily and/or weekly patterns. The example model trainer **706** provides the output people identification model to the example

model updater **708** to assist in generating predictions about the audience composition at subsequent dates and times.

[0123] The example model updater **708** of the illustrated example of FIG. 7 flags a people identification model received from the model trainer **706** as new and/or updated. For example, the model updater **708** can receive a people identification model from the model trainer **706** that provides a prediction algorithm to determine an audience composition of people in the media presentation environment **104**. The model updater **708** determines that a people identification model of this type is new and, therefore, tags it as new. In some examples, the model updater **708** determines that a people identification model of this type has been generated previously and, therefore, will flag the model most recently generated as updated. The example model updater **708** provides the new and/or updated model to the model generator **710**.

[0124] The example model generator **710** of the illustrated example of FIG. 7 generates a people identification model for publishing. For example, the model generator **710** may receive a notification from the model updater **708** that a new and/or updated people identification model has been trained and the model generator **710** may create a file in which the people identification model is published so that the people identification model can be saved and/or stored as the file. In some examples, the model generator **710** provides a notification to the people meter controller **302** and/or the audience audio detector **305** that a people identification model is ready to be transformed and published. In some examples, the model generator **710** stores the people identification model in the example model database **312** for subsequent retrieval by the people meter controller **302**.

[0125] In some examples, the people identification model controller **310** determines a people identification model is trained and ready for use when the prediction meets a threshold amount of error. In some examples, the people meter controller **302**, audience audio detector **305**, the example thermal image detector **306**, and/or the example audience image detector **307** implement the trained people identification model to determine an audience composition of people in a media presentation environment. In some examples, the example people meter **210** implements the people identification model. In such an example, the people identification model would obtain audio data from the audio sensor **120** to make informed decisions about audience composition, without the use of audience input data. In this manner, the people identification model may replace the people meter controller **302**, the audience audio detector **305**, the example thermal image detector **306**, the example audience image detector **307**, and the comparator **308**.

[0126] While an example manner of implementing the people meter **210** of FIG. 2 is illustrated in FIGS. 3, 4, 5, 6, and 7, one or more of the elements, processes and/or devices illustrated in FIGS. 3, 4, 5, 6, and 7 may be combined, divided, re-arranged, omitted, eliminated and/or implemented in any other way. Further, the example people meter controller **302**, the example interface **304**, the example audience audio detector **305**, the example thermal image detector **306**, the example audience image detector **307**, the example comparator **308**, the example people identification model controller **310**, the example model database **312**, the example audio database **402**, the example speech pattern determination controller **404**, the example sampling controller **406**, the example speech pattern counter **408**, the example speech pattern identifier **410**, the example reference signature database **412**, the example thermal image database **502**, the example heat blob determination controller **504**, the example scanning controller **506**, the example blob counter **508**, the example audience image database **602**, the example facial feature determination controller **604**, the example scanning controller **606**, the example audience identifier **608**, the example communication controller **702**, the example feature extractor **704**, the example model trainer **706**, the example model updater **708**, the example model generator **710** and/or, more generally, the example people meter **210** of FIG. 2 may be implemented by hardware, software, firmware and/or any combination of hardware, software and/or firmware. Thus, for example, any of the example people meter controller **302**, the example interface **304**, the example audience audio detector **305**, the example thermal image detector **306**, the example audience image detector **307**, the example

comparator **308**, the example people identification model controller **310**, the example model database **312**, the example audio database **402**, the example speech pattern determination controller **404**, the example sampling controller **406**, the example speech pattern counter **408**, the example speech pattern identifier **410**, the example reference signature database **412**, the example thermal image database **502**, the example heat blob determination controller **504**, the example scanning controller **506**, the example blob counter **508**, the example audience image database **602**, the example facial feature determination controller **604**, the example scanning controller **606**, the example audience identifier **608**, the example communication controller **702**, the example feature extractor **704**, the example model trainer **706**, the example model updater **708**, the example model generator **710** and/or, more generally, the example people meter **210** could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), programmable controller(s), graphics processing unit(s) (GPU(s)), digital signal processor(s) (DSP(s)), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)) and/or field programmable logic device(s) (FPLD(s)). When reading any of the apparatus or system claims of this patent to cover a purely software and/or firmware implementation, at least one of the example, people meter controller **302**, the example interface **304**, the example audience audio detector **305**, the example thermal image detector **306**, the example audience image detector **307**, the example comparator **308**, the example people identification model controller **310**, the example model database **312**, the example audio database **402**, the example speech pattern determination controller **404**, the example sampling controller **406**, the example speech pattern counter **408**, the example speech pattern identifier **410**, the example reference signature database **412**, the example thermal image database **502**, the example heat blob determination controller **504**, the example scanning controller **506**, the example blob counter **508**, the example audience image database **602**, the example facial feature determination controller **604**, the example scanning controller **606**, the example audience identifier **608**, the example communication controller **702**, the example feature extractor **704**, the example model trainer **706**, the example model updater **708**, and/or the example model generator **710** is/are hereby expressly defined to include a non-transitory computer readable storage device or storage disk such as a memory, a digital versatile disk (DVD), a compact disk (CD), a Blu-ray disk, etc. including the software and/or firmware. Further still, the example people meter **210** of FIG. 2 may include one or more elements, processes and/or devices in addition to, or instead of, those illustrated in FIGS. 3, 4, 5, 6, and 7, and/or may include more than one of any or all of the illustrated elements, processes and devices. As used herein, the phrase “in communication,” including variations thereof, encompasses direct communication and/or indirect communication through one or more intermediary components, and does not require direct physical (e.g., wired) communication and/or constant communication, but rather additionally includes selective communication at periodic intervals, scheduled intervals, aperiodic intervals, and/or one-time events.

[0127] A flowchart representative of example hardware logic, machine readable instructions, hardware implemented state machines, and/or any combination thereof for implementing the people meter **210** of FIG. 2 is shown in FIGS. 8-12. The machine readable instructions may be one or more executable programs or portion(s) of an executable program for execution by a computer processor and/or processor circuitry, such as the processor **1312** shown in the example processor platform **1300** discussed below in connection with FIG. 13.

[0128] The program may be embodied in software stored on a non-transitory computer readable storage medium such as a CD-ROM, a floppy disk, a hard drive, a DVD, a Blu-ray disk, or a memory associated with the processor **1312**, but the entire program and/or parts thereof could alternatively be executed by a device other than the processor **1312** and/or embodied in firmware or dedicated hardware. Further, although the example program is described with reference to the flowchart illustrated in FIGS. 8-12, many other methods of implementing the example people meter **210** may alternatively be used. For example, the order of execution of the blocks may be

changed, and/or some of the blocks described may be changed, eliminated, or combined. Additionally or alternatively, any or all of the blocks may be implemented by one or more hardware circuits (e.g., discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to perform the corresponding operation without executing software or firmware. The processor circuitry may be distributed in different network locations and/or local to one or more devices (e.g., a multi-core processor in a single machine, multiple processors distributed across a server rack, etc.).

[0129] The machine readable instructions described herein may be stored in one or more of a compressed format, an encrypted format, a fragmented format, a compiled format, an executable format, a packaged format, etc. Machine readable instructions as described herein may be stored as data or a data structure (e.g., portions of instructions, code, representations of code, etc.) that may be utilized to create, manufacture, and/or produce machine executable instructions. For example, the machine readable instructions may be fragmented and stored on one or more storage devices and/or computing devices (e.g., servers) located at the same or different locations of a network or collection of networks (e.g., in the cloud, in edge devices, etc.). The machine readable instructions may require one or more of installation, modification, adaptation, updating, combining, supplementing, configuring, decryption, decompression, unpacking, distribution, reassignment, compilation, etc. in order to make them directly readable, interpretable, and/or executable by a computing device and/or other machine. For example, the machine readable instructions may be stored in multiple parts, which are individually compressed, encrypted, and stored on separate computing devices, wherein the parts when decrypted, decompressed, and combined form a set of executable instructions that implement one or more functions that may together form a program such as that described herein.

[0130] In another example, the machine readable instructions may be stored in a state in which they may be read by processor circuitry, but require addition of a library (e.g., a dynamic link library (DLL)), a software development kit (SDK), an application programming interface (API), etc. in order to execute the instructions on a particular computing device or other device. In another example, the machine readable instructions may need to be configured (e.g., settings stored, data input, network addresses recorded, etc.) before the machine readable instructions and/or the corresponding program(s) can be executed in whole or in part. Thus, machine readable media, as used herein, may include machine readable instructions and/or program(s) regardless of the particular format or state of the machine readable instructions and/or program(s) when stored or otherwise at rest or in transit.

[0131] The machine readable instructions described herein can be represented by any past, present, or future instruction language, scripting language, programming language, etc. For example, the machine readable instructions may be represented using any of the following languages: C, C++, Java, C #, Perl, Python, JavaScript, HyperText Markup Language (HTML), Structured Query Language (SQL), Swift, etc.

[0132] As mentioned above, the example processes of FIGS. 8-12 may be implemented using executable instructions (e.g., computer and/or machine readable instructions) stored on a non-transitory computer and/or machine readable medium such as a hard disk drive, a flash memory, a read-only memory, a compact disk, a digital versatile disk, a cache, a random-access memory and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media.

[0133] “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation

of any kind, it is to be understood that additional elements, terms, etc. may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, and (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B.

[0134] As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” entity, as used herein, refers to one or more of that entity. The terms “a” (or “an”), “one or more”, and “at least one” can be used interchangeably herein. Furthermore, although individually listed, a plurality of means, elements or method actions may be implemented by, e.g., a single unit or processor. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

[0135] FIGS. **8**, **9**, **10**, **11**, and **12** illustrate programs that are executed by the example people meter **210** to determine an accurate audience composition utilizing audience input and/or audio data. FIG. **8** illustrates an example program **800** implemented by the example audience audio detector **305** of FIGS. **3** and/or **4** to determine a people count. FIG. **9** illustrates an example program **900** implemented by the example thermal image detector **306** of FIGS. **3** and/or **5** to determine a heat blob count. FIG. **10** illustrates an example program **1000** implemented by the example people meter **210** of FIGS. **2**, **3**, **4**, **5**, **6**, and **7** to determine an audience composition. FIG. **11** illustrates an example program **1012** implemented by the example audience image detector **307** of FIGS. **3** and/or **6** to determine an audience composition. FIG. **12** illustrates an example program **1200** implemented by the example people identification model controller **310** of FIGS. **3** and/or **7** to train the model to determine an audience composition of the media presentation environment.

[0136] Turning to FIG. **8**, the example program **800** begins when the example media device **110** (FIG. **1**) is on (block **802**). For example, the audio sensor **120** (FIG. **1**) may be activated and begin capturing audio data when the media device **110** is turned on, and thus the program **800** begins. The example media identifier **204** (FIG. **2**) obtains samples of audio data from the example audio sensor **120** (block **804**). For example, the audio sensor **120** captures samples of audio data corresponding to the media presentation environment **104** and the media identifier **204** generates one or more signatures based on the audio data.

[0137] The speech pattern determination controller **404** (FIG. **4**) obtains and/or generates one or more signatures from the media identifier **204** (block **806**). For example, the audio database **402** obtains a signature via the interface **304** (FIG. **3**) and the speech pattern determination controller **404** queries the audio database **402** for signatures corresponding to the media presentation environment **104**. Additionally or alternatively, the speech pattern determination controller **404**

obtains audio data via the interface **304** and generates a signature.

[0138] The example speech pattern determination controller **404** applies filters to the signature(s) corresponding to the media presentation environment **104** (block **808**). For example, the speech pattern determination controller **404** applies a low pass filter, a high pass filter, a bandpass filter, etc. to remove frequencies that are not associated with human voice (e.g., frequencies associated with animals, frequencies associated with cars, etc.). The filtered output is indicative of signature(s) of human voices detected during the filtering. In this manner, the example speech pattern determination controller **404** evaluates the filtered output (block **810**). For example, the speech pattern determination controller **404** utilizes the information in the filtered output to predict and/or otherwise determine audience member identities.

[0139] The example speech pattern determination controller **404** determines if audience member speech patterns were detected (block **812**). For example, the speech pattern determination controller **404** utilizes the evaluation of the filtered output to determine if speech patterns were detected based on one or more characteristics (e.g., vocal tract length, vocal tract shape, pitch, speaking rate, etc.). If the example speech pattern determination controller **404** determines speech patterns were not detected (e.g., block **812**=NO), then the example speech pattern determination controller **404** prompts the sampling controller **406** to sample the media environment (block **814**). For example, the speech pattern determination controller **404** may send a trigger to the sampling controller **406** to prompt the sampling controller **406** to record additional samples of audio data of the media presentation environment **104**.

[0140] If the example speech pattern determination controller **404** determines speech patterns were detected (e.g., block **812**=YES), then the example speech pattern determination controller **404** provides the filtered output to the example speech pattern counter **408**. The example speech pattern counter **408** determines the number of speech patterns in the filtered output (block **816**). That is, the speech pattern counter **408** determines the people count of the audience. For example, the speech pattern counter **408** analyzes information in the filtered output to determine the number of speech patterns that were identified based on the signatures. In some examples, the speech pattern counter **408** updates the counter with the number of speech patterns (e.g., the speech pattern counter **408** increments the counter to equal the number of speech patterns detected based on the signatures).

[0141] The example speech pattern counter **408** provides the people count to the comparator **308** (FIG. 3) (block **818**). For example, the speech pattern counter **408** is communicatively coupled to the comparator **308**, and further provides the people count to the comparator **308** for a comparison to the prompted people count and/or the previously stored people count. The program **800** ends when the example speech pattern counter **408** provides the people count to the comparator **308**. The program **800** repeats when the example sampling controller **406** (FIG. 4) initiates a new sample of audio data. For example, the sampling controller **406** may initiate the audio sensor **120** to record audio samples of the media presentation environment **104**, and thus a new and/or same audience member identification, in the media presentation environment **104**, may be detected.

[0142] Turning to FIG. 9, the example program **700** begins when the example media device **110** (FIG. 1) is on (block **902**). For example, the thermal imaging sensor **124** (FIG. 1) may be activated and begin capturing thermal image data when the media device **110** is turned on, and thus the program **900** begins. The example thermal image database **502** (FIG. 5) obtains frames of thermal image data from the example thermal imaging sensor **124** (block **904**). For example, the thermal imaging sensor **124** captures frames of thermal image data corresponding to the media presentation environment **104** and stores them in the thermal image database **502**.

[0143] The heat blob determination controller **504** (FIG. 5) obtains a frame of thermal image data from the thermal image database **502** (FIG. 5) (block **906**). For example, the heat blob determination controller **504** queries the thermal image database **502** for frames corresponding to the media presentation environment **104**.

[0144] The example heat blob determination controller **504** identifies portions of the frame that

include a high probability of a human (block **908**). For example, the heat blob determination controller **504** detects warm areas of the frame that are to be analyzed further, as described above. The example heat blob determination controller **504** detects features of the frame that are incompatible with the presence of a human (block **910**). For example, the heat blob determination controller **504** identifies cool areas of the frame, areas with hard edges, etc., as described above. The example heat blob determination controller **504** discards the incompatible features (block **912**). For example, the heat blob determination controller **504** removes any groups of pixels that were determined to be incompatible with the presence of a human in an effort to increase the probability and accuracy of detecting human size heat blob(s).

[0145] The example heat blob determination controller **504** applies filters to the identified portions of the frame (block **914**). For example, the heat blob determination controller **504** convolves filters indicative of a shape, size, and/or distance over the identified portions of the frame to detect lines and features that correspond to the shape of a human. The example the heat blob determination controller **504** connects the output(s) of the filters to form a fully connected output (block **916**).

[0146] For example, the heat blob determination controller **504** concatenates the outputs of the filters to form the fully connected output layer. The fully connected output layer is indicative of the number of human size and/or human shaped heat blobs detected during the filtering. In this manner, the example heat blob determination controller **504** evaluates the fully connected output (block **918**). For example, the heat blob determination controller **504** utilizes the information in the fully connected output to predict and/or otherwise determine if a human size heat blob was detected.

[0147] The example heat blob determination controller **504** determines if human size heat blobs were detected (block **920**). For example, the heat blob determination controller **504** utilizes the evaluation of the fully connected output to determine if human size heat blobs were detected. If the example heat blob determination controller **504** determines human size heat blobs were not detected (e.g., block **920**=NO), then the example heat blob determination controller **504** prompts the scanning controller **506** to scan the media environment (block **922**). For example, the heat blob determination controller **504** may send a trigger to the scanning controller **506** to prompt the scanning controller to capture more frames of thermal image data of the media presentation environment **104**.

[0148] If the example heat blob determination controller **504** determines human size heat blobs were detected (e.g., block **920**=YES), then the example heat blob determination controller **504** provides the fully connected output to example blob counter **508**. The example blob counter **508** determines the number of human size heat blobs in the fully connected output (block **924**). For example, the blob counter **508** analyzes information in the fully connected output to determine the number of human size heat blobs that were identified in the frame. The example blob counter **508** updates the counter with the number of heat blobs (block **926**). For example, the blob counter **508** increments the counter to equal the number of human size heat blobs detected in the image frame.

[0149] The example blob counter **508** provides the heat blob count to the comparator **308** (FIG. 3) (block **928**). For example, the blob counter **508** is communicatively coupled to the comparator **308**, and further provides the heat blob count to the comparator **308** for a comparison to the people count. The program **900** ends when the example blob counter **508** provides the heat blob count to the example comparator **308**. The heat blob count program **900** repeats when the example scanning controller **506** (FIG. 5) initiates a new capture of thermal image data. For example, the scanning controller **506** may initiate the thermal imaging sensor **124** to capture frames of the media presentation environment **104**, and thus a new and/or same number of heat blobs, in the media presentation environment **104**, may be detected.

[0150] Turning to FIG. 10, the example program **1000** begins when the example comparator **308** (FIG. 3) obtains the people count (block **1002**). For example, the comparator **308** obtains the people count from the example audience audio detector **305** (FIG. 3) and/or the people count from the prompted people count from the example people meter controller **302** (FIG. 3). Additionally,

the example comparator **308** obtains the heat blob count (block **1004**). For example, the comparator **308** obtains the heat blob count from the example thermal image detector **306** (FIG. 3).

[0151] The example comparator **308** determines whether the people count matches the heat blob count (block **1006**). For example, the comparator **308** compares the value of the people count to the value of the heat blob count and determines if the count values are equal. If the example comparator **308** determines the count values are equal in value (e.g., block **1006**=YES), the example speech pattern identifier **410** identifies one or more audience members associated with the identified speech patterns based on the signatures (block **1008**). For example, the speech pattern identifier **410** compares the detected speech patterns to one or more reference speech patterns of audience members of the household.

[0152] The example speech pattern identifier **410** determines whether the number of identified audience members matches the number of detected speech patterns (block **1010**). For example, the speech pattern identifier **410** compares the number of identified audience members to the number of detected speech patterns. If the speech pattern identifier **410** determines the number of identified audience members does not match the number of detected speech patterns (e.g., block **1010**=NO), the example audience image detector **307** obtains audience image data (block **1012**). For example, the audience image detector **307** obtains and analyzes one or more frames of audience image data. Further example instructions that may be used to implement block **1012** are described below in connection with FIG. 11.

[0153] If the example speech pattern identifier **410** determines the number of identified audience members matches the number of detected speech patterns (e.g., block **1010**=YES), the example speech pattern identifier **410** determines a time of the identification (block **1018**). For example, the speech pattern identifier **410** identifies the timestamp of when the match between the identified speech pattern and the reference speech pattern was determined.

[0154] Returning to block **1006**, if the example comparator **308** determines the count values do not match (e.g., block **1006**=NO), the example audience image detector **307** obtains audience image data. As described above, further example instructions that may be used to implement block **1012** are described below in connection with FIG. 11. The example audience identifier **608** (FIG. 6) determines whether the number of identified audience members matches the number of heat blobs (block **1014**). For example, the audience identifier **608** compares the number of identified audience members in the audience image data to the number of heat blobs determined by the thermal image detector **306**.

[0155] If the example audience identifier **608** determines the number of identified audience members does not match the number of heat blobs (e.g., block **1014**=NO), the example people meter controller **302** initiates a prompt to the audience (block **1016**). For example, the people meter controller **302** generates a prompting message. In this manner, the example people meter controller **302** generates the prompting message in an effort to obtain a response from the audience to identify the unidentified humans in the frame (e.g., the humans the example audience identifier **608** did not identify that were detected by the example thermal image detector **306**) and generate accurate audience monitoring data.

[0156] If the example audience identifier **608** the number of identified audience members matches the number of heat blobs (e.g., block **1014**=YES), the example audience identifier **608** (FIG. 6) determines a time of the identification (block **1018**). For example, the audience identifier **608** identifies the timestamp of when the frame containing the face of the identified audience member was compared to the reference image of the audience member's face.

[0157] The example facial feature determination controller **604** and/or the example speech pattern determination controller **404** provides the audience composition (e.g., the people count, the audience members in the audience, etc.) and the time to the people identification model (block **1020**). For example, the facial feature determination controller **604** and/or the example speech pattern determination controller **404** output information determined from the comparison to train

the people identification model. Further, the example audience image detector **307** and/or the example audience audio detector **305** sends a reset notification to the example people meter controller **302** (block **1022**). For example, the audience image detector **307** and/or the example audience audio detector **305** notifies the example people meter controller **302** to reset the scheduling interval timers that determine when prompting messages are to be triggered. In some examples, when the audience image detector **307** and/or the audience audio detector **305** provide the notification to the people meter controller **302**, the example program **1000** ends.

[0158] Turning to FIG. **11**, the example audience member identification program **1012** begins when the audience image database **602** (FIG. **6**) obtains frames of audience image data from the example light imaging sensor **125** (block **1102**). For example, the light imaging sensor **125** captures frames of audience image data corresponding to the media presentation environment **104** and stores them in the audience image database **602**. The example facial feature determination controller **604** obtains a frame of audience image data from the audience image database **602** (block **1104**). For example, the facial feature determination controller **604** queries the audience image database **602** for frames corresponding to the locations of the human sized heat blobs of the media presentation environment **104**.

[0159] The example facial feature determination controller **604** identifies portions of the frame that include a high probability of a human face (block **1106**). For example, the facial feature determination controller **604** detects features (e.g., eyes, mouth, etc.) of the frame that are to be analyzed further, as described above. The example facial feature determination controller **604** detects features of the frame that are incompatible with the presence of a human face (block **1108**). For example, the facial feature determination controller **604** identifies areas with hard edges, etc., as described above. The example facial feature determination controller **604** discards the incompatible features (block **1110**). For example, the facial feature determination controller **604** removes any groups of pixels that were determined to be incompatible with the presence of a human face in an effort to increase the probability and accuracy of identifying audience member(s).

[0160] The example facial feature determination controller **604** applies filters to the identified portions of the frame (block **1112**). For example, the facial feature determination controller **604** convolves filters indicative of a shape, size, and/or distance over the identified portions of the frame to detect lines and features that correspond to the shape of a human face. The example the facial feature determination controller **604** connects the output(s) of the filters to form a fully connected output (block **1114**).

[0161] For example, the facial feature determination controller **604** concatenates the outputs of the filters to form the fully connected output layer. The fully connected output layer is indicative of the human faces detected during the filtering. In this manner, the example audience identifier **608** evaluates the fully connected output (block **1116**). For example, the audience identifier **608** utilizes the information in the fully connected output to predict and/or otherwise identify audience member(s), as described above.

[0162] The example facial features determination controller **604** determines if audience member(s) were identified (block **1118**). For example, the facial feature determination controller **604** utilizes the evaluation of the fully connected output to determine if audience member(s) were identified. If the example facial feature determination controller **604** determines audience members were not detected (e.g., block **1118**=NO), then the example facial feature determination controller **604** prompts the scanning controller **606** to scan the media environment (block **1120**). For example, the facial feature determination controller **604** may send a trigger to the scanning controller **606** to prompt the scanning controller **606** to capture more frames of audience image data of the media presentation environment **104**.

[0163] If the example facial feature determination controller **604** determines audience member(s) were identified (e.g., block **1118**=YES), then the example facial feature determination controller **604** provides the audience member identification to controller(s) (block **1122**). For example, the

facial feature determination controller **604** provides the audience member identification to the people meter controller **302** (FIG. 3) and/or the people identification model controller **310** (FIG. 3). The example audience member identification program **1012** returns to block **1014** of the program **1000**.

[0164] FIG. 12 illustrates an example training program **1200** to train a people identification model to predict a verified audience composition for subsequent dates and times in the media presentation environment **104**. The example machine readable instructions **1200** may be used to implement the example people identification model controller **310** of FIG. 3. In FIG. 12, the example training program **1200** beings at block **1202**, when the example feature extractor **704** (FIG. 7) obtains comparison data from the example comparator **308** (FIG. 3). For example, the comparator **308** provides comparison results and time stamps to the example feature extractor **704**.

[0165] The example feature extractor **704** obtains data from the example people meter controller **302** (FIG. 3) (block **1204**). For example, the people meter controller **302** provides demographic data corresponding to the logged in audience members at a time they logged in. The example feature extractor **704** obtains evaluation data from the example audience audio detector **305** (FIG. 3) (block **1206**). For example, the audience audio detector **305** provides the analysis and evaluation results (e.g., people identification data) of the signatures for a particular time. Additionally, the example audience audio detector **305** provides the tagged sample (e.g., the sample tagged with a people count by the speech pattern counter **408** (FIG. 4) and/or the audience identifier by the speech pattern identifier **410** (FIG. 4)) to the example feature extractor **704**.

[0166] The example feature extractor **704** obtains evaluation data from the example thermal image detector **306** (FIG. 3) (block **1208**). For example, the thermal image detector **306** provides the analysis and evaluation results of the frame of thermal image data for a particular time.

Additionally, the example thermal image detector **306** provides the tagged frame (e.g., the frame tagged with a blob count by the blob counter **508** (FIG. 5)) to the example feature extractor **704**.

The example feature extractor **704** obtains evaluation data from the example audience image detector **307** (FIG. 3) (block **1210**). For example, the audience image detector **307** provides the analysis and evaluation results of the frame of audience image data for a particular time.

Additionally, the example audience image detector **307** provides the tagged frame (e.g., the frame tagged with audience member identifier(s) by the audience identifier **608** (FIG. 6)) to the example feature extractor **704**.

[0167] The example feature extractor **704** obtains media identifying information from the example media measurement data controller **212** (FIG. 2) (block **1212**). For example, the media measurement data controller **212** provides media identifying information to the communication controller **702** (FIG. 7) in response to receiving a people count and/or audience member identifier(s), and the communication controller **702** provides the media identifying information to the feature extractor **704**.

[0168] The example feature extractor **704** extracts features of the people monitoring information (block **1214**). As used herein, the people monitoring information corresponds to the information and data obtained from the example people meter controller **302**, the example comparator **308**, the example audience audio detector **305**, the example thermal image detector **306**, the example audience image detector **307**, and the example media measurement data controller **212**. This data can be used to determine a verified audience composition and/or represents a verified audience composition.

[0169] The example feature extractor **704** generates a feature vector corresponding to the extracted features of the people monitoring data (block **1216**). For example, the feature extractor **704** generates a feature vector that represents descriptive characteristics of a physical environment (e.g., the media presentation environment) at particular dates and times, or at a particular date and time. The example feature extractor **704** determines if there are additional people monitoring data (block **1218**). For example, the feature extractor **704** determines if another set of people monitoring data,

representative of the people count during a different time in the media presentation environment **104**, is available. If the example feature extractor **704** determines there are additional people monitoring data (block **1218**=YES), then control returns to block **1202**. In such an example, the model trainer **706** (FIG. 7) needs to receive people monitoring data of the media presentation environment **104** that is sufficient to generate a sufficiently accurate and/or precise model.

[0170] If the example feature extractor **704** determines there are not additional people monitoring data (block **1218**=NO), then the example model trainer **706** trains the people identification model based on the feature vector (block **1220**). For example, the model trainer **706** may utilize a machine learning technique to predict output probability values corresponding to the number of people and/or which audience members are in the media presentation environment **104**. The output probability values could correspond to future predictions of the audience members viewing particular media in the media presentation environment **104** or the output probability values could correspond to future predictions of the audience members in the media presentation environment **104** at a particular hour of the day or day of the week.

[0171] After the people identification model has been trained, the example model updater **708** flags the people identification model as new or updated. Further, the example model generator **710** generates the trained model (block **1222**). For example, the model generator **710** receives the new and/or updated trained people identification model from the model updater **708** and generates a file to store/save the trained people identification model for subsequent access by the people meter controller **302** (FIG. 3), the audience audio detector **305** (FIG. 3), the thermal image detector **306** (FIG. 3), and/or the audience image detector **307** (FIG. 3).

[0172] The example model generator **710** stores the trained people identification model in the example model database **312** (FIG. 3) (block **1224**). The training program **1200** ends when the trained people identification model is stored in the example model database **312**. The training program **1200** repeats when the example feature extractor **704** obtains people monitoring data.

[0173] In some examples, the trained people identification model is published by the people identification model controller **310**. When the people identification model is published, the people identification model operates in a detection phase, where the example people identification model controller **310** utilizes the trained model, in real time, to determine an accurate audience composition of the media presentation environment **104**. In some examples, the people identification model replaces the people meter controller **302**, the audience audio detector **305**, the thermal image detector **306**, the audience image detector **307**, and the comparator **308**. In such an example, the people identification model obtains input data from the audio sensor **120**, the thermal imaging sensor **124**, and/or the light imaging sensor **125** to determine an accurate audience composition of the media presentation environment **104**. Such input from the audio sensor **120**, the thermal imaging sensor **124**, and/or the light imaging sensor **125** includes samples of audio data, thermal image data, and/or audience image data. For example, the people identification model utilizes its prediction capabilities in connection with information obtained about the media presentation environment **104** to output an accurate representation of the number and/or identification of people in the media presentation environment **104**. In such an example, the people meter controller **302** no longer requires audience input, and thus compliance becomes less of an issue when determining an accurate audience composition.

[0174] FIG. 13 is a block diagram of an example processor platform **1300** structured to execute the instructions of FIGS. 8-12 to implement the people meter **210** of FIGS. 2-7. The processor platform **1300** can be, for example, a server, a personal computer, a workstation, a self-learning machine (e.g., a neural network), a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad™), a personal digital assistant (PDA), an Internet appliance, a DVD player, a CD player, a digital video recorder, a Blu-ray player, a gaming console, a personal video recorder, a set top box, a headset or other wearable device, or any other type of computing device.

[0175] The processor platform **1300** of the illustrated example includes a processor **1312**. The

processor **1312** of the illustrated example is hardware. For example, the processor **1312** can be implemented by one or more integrated circuits, logic circuits, microprocessors, GPUs, DSPs, or controllers from any desired family or manufacturer. The hardware processor may be a semiconductor based (e.g., silicon based) device. In this example, the processor implements the example people meter controller **302**, the example interface **304**, the example audience audio detector **305**, the example thermal image detector **306**, the example audience image detector **307**, the example comparator **308**, the example people identification model controller **310**, the example model database **312**, the example audio database **402**, the example speech pattern determination controller **404**, the example sampling controller **406**, the example speech pattern counter **408**, the example speech pattern identifier **410**, the example reference signature database **412**, the example thermal image database **502**, the example heat blob determination controller **504**, the example scanning controller **506**, the example blob counter **508**, the example audience image database **602**, the example facial feature determination controller **604**, the example scanning controller **606**, the example audience identifier **608**, the example communication controller **702**, the example feature extractor **704**, the example model trainer **706**, the example model updater **708**, and the example model generator **710**.

[0176] The processor **1312** of the illustrated example includes a local memory **1313** (e.g., a cache). The processor **1312** of the illustrated example is in communication with a main memory including a volatile memory **1314** and a non-volatile memory **1316** via a bus **1318**. The volatile memory **1314** may be implemented by Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS® Dynamic Random Access Memory (RDRAM®) and/or any other type of random access memory device. The non-volatile memory **1316** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **1314**, **1316** is controlled by a memory controller.

[0177] The processor platform **1300** of the illustrated example also includes an interface circuit **1320**. The interface circuit **1320** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), a Bluetooth® interface, a near field communication (NFC) interface, and/or a PCI express interface.

[0178] In the illustrated example, one or more input devices **1322** are connected to the interface circuit **1320**. The input device(s) **1322** permit(s) a user to enter data and/or commands into the processor **1312**. The input device(s) can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint and/or a voice recognition system.

[0179] One or more output devices **1324** are also connected to the interface circuit **1320** of the illustrated example. The output devices **1324** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display (LCD), a cathode ray tube display (CRT), an in-place switching (IPS) display, a touchscreen, etc.), a tactile output device, a printer and/or speaker. The interface circuit **1320** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip and/or a graphics driver processor.

[0180] The interface circuit **1320** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem, a residential gateway, a wireless access point, and/or a network interface to facilitate exchange of data with external machines (e.g., computing devices of any kind) via a network **1326**. The communication can be via, for example, an Ethernet connection, a digital subscriber line (DSL) connection, a telephone line connection, a coaxial cable system, a satellite system, a line-of-site wireless system, a cellular telephone system, etc.

[0181] The processor platform **1300** of the illustrated example also includes one or more mass storage devices **1328** for storing software and/or data. Examples of such mass storage devices **1328** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, redundant

array of independent disks (RAID) systems, and digital versatile disk (DVD) drives.

[0182] The machine executable instructions **1332** of FIGS. **8-12** may be stored in the mass storage device **1328**, in the volatile memory **1314**, in the non-volatile memory **1316**, and/or on a removable non-transitory computer readable storage medium such as a CD or DVD.

[0183] From the foregoing, it will be appreciated that example methods, apparatus and articles of manufacture have been disclosed that determine an audience composition in a media presentation environment by generating signatures from audio data, capturing frames of thermal image data, and capturing frames of audience image data. The disclosed example methods, apparatus and articles of manufacture improve the efficiency of using a computing device by using the audience input data and the evaluation of the signatures, frames of thermal image data, and frames of audience image data to train a people identification model to determine the audience composition. The people identification model, once trained, can replace the people meter and thus, improve the efficiency processing time by eliminating a need for audience input data. The disclosed example methods, apparatus and articles of manufacture improve the efficiency of using a computing device by reducing prompting messages when the speech patterns identified based on the signatures of audio data match the reference speech patterns of audience audio and/or when the faces identified in the frames of audience image data match the logged reference frames of audience member images. The disclosed methods, apparatus and articles of manufacture are accordingly directed to one or more improvement(s) in the functioning of a computer.

[0184] Example methods, apparatus, systems, and articles of manufacture to determine an audience composition in a media environment are disclosed herein. Further examples and combinations thereof include the following:

[0185] Example 1 includes an apparatus to measure an audience in a media environment, the apparatus comprising an audio detector to determine a first audience count based on signatures of audio data captured in the media environment, a thermal image detector to determine a heat blob count based on a frame of thermal image data captured in the media environment, and an audience image detector to identify at least one audience member based on a comparison of a frame of audience image data with a library of reference audience images, the audience image detector to perform the comparison in response to the first audience count not matching the heat blob count.

[0186] Example 2 includes the apparatus of example 1, further including a comparator to compare the first audience count and the heat blob count.

[0187] Example 3 includes the apparatus of example 1, further including a people meter controller to cause a people meter, which is to emit a prompt for audience identification information, to not emit the prompt for at least a first time period after the at least one audience member is identified.

[0188] Example 4 includes the apparatus of example 3, wherein the people meter

[0189] controller is to cause the people meter to emit the prompt in response to the audience image detector not identifying a number of audience members in the frame of audience image data equal to the heat blob count.

[0190] Example 5 includes the apparatus of example 1, wherein the audio detector is to

[0191] identify the at least one audience member based on a second comparison of the signatures of the audio data with a library of reference signatures, the audio detector to perform the second comparison when the first audience count matches the heat blob count.

[0192] Example 6 includes the apparatus of example 5, wherein the audience image detector is not to capture the frame of audience image data in response to the audio detector identifying the at least one audience member.

[0193] Example 7 includes the apparatus of example 1, wherein the audio detector is to identify at least one speech pattern based on the signatures of audio data.

[0194] Example 8 includes a non-transitory computer readable storage medium comprising instructions that, when executed, cause one or more processors to at least determine a first audience count based on signatures of audio data captured in a media environment, determine a heat blob

count based on a frame of thermal image data captured in the media environment, and identify at least one audience member based on a comparison of a frame of audience image data with a library of reference audience images, the comparison performed in response to the first audience count not matching the heat blob count.

[0195] Example 9 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the one or more processors to compare the first audience count and the heat blob count.

[0196] Example 10 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the one or more processors to cause a people meter, which is to emit a prompt for audience identification information, to not emit the prompt for at least a first time period after the at least one audience member is identified.

[0197] Example 11 includes the non-transitory computer readable storage medium of example 10, wherein the instructions, when executed, cause the one or more processors to cause the people meter to emit the prompt in response to not identifying a number of audience members in the frame of audience image data equal to the heat blob count.

[0198] Example 12 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the one or more processors to identify the at least one audience member based on a second comparison of the signatures of the audio data with a library of reference signatures, the second comparison performed when the first audience count matches the heat blob count.

[0199] Example 13 includes the non-transitory computer readable storage medium of example 12, wherein the instructions, when executed, cause the one or more processors not to capture the frame of audience image data in response to identifying the at least one audience member.

[0200] Example 14 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the one or more processors to identify at least one speech pattern based on the signatures of audio data.

[0201] Example 15 includes a method to measure an audience in a media environment, the method comprising determining a first audience count based on signatures of audio data captured in the media environment, determining a heat blob count based on a frame of thermal image data captured in the media environment, and identifying at least one audience member based on a comparison of a frame of audience image data with a library of reference audience images, the comparison performed in response to the first audience count not matching the heat blob count.

[0202] Example 16 includes the method of example 15, further including causing a people meter, which is to emit a prompt for audience identification information, to not emit the prompt for at least a first time period after the at least one audience member is identified.

[0203] Example 17 includes the method of example 16, further including causing the people meter to emit the prompt in response to not identifying a number of audience members in the frame of audience image data equal to the heat blob count.

[0204] Example 18 includes the method of example 15, further including identifying the at least one audience member based on a second comparison of the signatures of the audio data with a library of reference signatures, the second comparison performed when the first audience count matches the heat blob count.

[0205] Example 19 includes the method of example 18, further including not capturing the frame of audience image data in response to identifying the at least one audience member.

[0206] Example 20 includes the method of example 15, further including identifying at least one speech pattern based on the signatures of audio data.

[0207] Although certain example methods, apparatus and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

[0208] The following claims are hereby incorporated into this Detailed Description by this reference, with each claim standing on its own as a separate embodiment of the present disclosure.

Claims

1. A computing system comprising a processor and a memory, the computing system configured to perform a set of acts comprising: determining, using thermal image data acquired by a thermal imaging sensor, a heat blob count, wherein the heat blob count is indicative of a first estimated number of audience members in a media environment; determining, using samples of audio data acquired by an audio sensor, a people count, wherein the people count is indicative of a second estimated number of audience members in the media environment; determining that the people count is less than the heat blob count; based on the determining that the people count is less than the heat blob count, triggering a camera to capture audience image data; and identifying, using the audience image data, people in the media environment via facial recognition.
2. The computing system of claim 1, wherein determining the heat blob count comprises detecting multiple shapes having a temperature in an expected temperature range.
3. The computing system of claim 2, wherein detecting the multiple shapes comprises applying a size constraint or a distance constraint to area of a frame of the thermal image data.
4. The computing system of claim 2, wherein determining the people count comprises detecting one or more distinct speech patterns.
5. The computing system of claim 4, wherein detecting the one or more distinct speech patterns comprises recognizing a known speech pattern of an audience member.
6. The computing system of claim 1, wherein the set of acts further comprises: determining media monitoring data indicative of media output in the media environment; and transmitting the media monitoring data and audience monitoring data to another computing system, and wherein the audience monitoring data is indicative of the identified people.
7. The computing system of claim 6, wherein the media monitoring data is generated using the samples of audio data.
8. A method comprising: determining, using thermal image data acquired by a thermal imaging sensor, a heat blob count, wherein the heat blob count is indicative of a first estimated number of audience members in a media environment; determining, using samples of audio data acquired by an audio sensor, a people count, wherein the people count is indicative of a second estimated number of audience members in the media environment; determining that the people count is less than the heat blob count; based on the determining that the people count is less than the heat blob count, triggering a camera to capture audience image data; and identifying, using the audience image data, people in the media environment via facial recognition.
9. The method of claim 8, wherein determining the people count comprises detecting one or more distinct speech patterns.
10. The method of claim 9, wherein detecting the one or more distinct speech patterns comprises recognizing a known speech pattern of an audience member.
11. The method of claim 9, wherein determining the heat blob count comprises detecting multiple shapes having a temperature in an expected temperature range.
12. The method of claim 11, wherein detecting the multiple shapes comprises applying a size constraint or a distance constraint to area of a frame of the thermal image data.
13. The method of claim 8, further comprising: determining media monitoring data indicative of media output in the media environment; and transmitting the media monitoring data and audience monitoring data to another computing system, wherein the audience monitoring data is indicative of the identified people.
14. The method of claim 13, wherein the media monitoring data is generated using the samples of audio data.

- 15.** A non-transitory computer-readable medium having stored thereon instructions that upon executing by a computing system, cause the computing system to perform a set of acts comprising: determining, using thermal image data acquired by a thermal imaging sensor, a heat blob count, wherein the heat blob count is indicative of a first estimated number of audience members in a media environment; determining, using samples of audio data acquired by an audio sensor, a people count, wherein the people count is indicative of a second estimated number of audience members in the media environment; determining that the people count is less than the heat blob count; based on the determining that the people count is less than the heat blob count, triggering a camera to capture audience image data; and identifying, using the audience image data, people in the media environment via facial recognition.
- 16.** The non-transitory computer-readable medium of claim 15, wherein the set of acts further comprises: determining media monitoring data indicative of media output in the media environment; and transmitting the media monitoring data and audience monitoring data to another computing system, and wherein the audience monitoring data is indicative of the identified people.
- 17.** The non-transitory computer-readable medium of claim 16, wherein determining the heat blob count comprises detecting multiple shapes having a temperature in an expected temperature range.
- 18.** The non-transitory computer-readable medium of claim 17, wherein detecting the multiple shapes comprises applying a size constraint or a distance constraint to area of a frame of the thermal image data.
- 19.** The non-transitory computer-readable medium of claim 17, wherein determining the people count comprises detecting one or more distinct speech patterns.
- 20.** The non-transitory computer-readable medium of claim 19, wherein detecting the one or more distinct speech patterns comprises recognizing a known speech pattern of an audience member.
-