

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267793

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

LEE; Eon Jong et al.

FLEXIBLE PRINTED CIRCUIT BOARD, COF MODULE, AND ELECTRONIC DEVICE COMPRISING THE SAME

Abstract

A flexible printed circuit board includes: a substrate; and a circuit pattern disposed on the substrate, wherein the substrate includes a chip mounting region, and the circuit pattern includes a wiring portion and a pad portion, wherein the circuit pattern includes: a first circuit pattern including a first-first pad portion disposed inside the chip mounting region, a first-second pad portion disposed outside the chip mounting region, and a first wiring portion that connects the first-first pad portion and the first-second pad portion, and extending in a first direction based on the chip mounting region; a second circuit pattern including a second-first pad portion disposed inside the chip mounting region, a second-second pad portion disposed outside the chip mounting region, and a second wiring portion that connects the second-first pad portion and the second-second pad portion, and extending in a second direction; and a third circuit pattern including a plurality of third pad portions disposed inside the chip mounting region and including a third wiring portion connecting the third pad portion and an extension wiring portion that extends to the outside of the third pad portion, and a protective layer is disposed on the first wiring portion and the second wiring portion.

Inventors: LEE; Eon Jong (Seoul, KR), Kim; Dong Chan (Seoul, KR), Park; Ki Tae (Seoul, KR)

Applicant: LG Innotek Co., Ltd. (Seoul, KR)

Family ID: 1000008589755

Appl. No.: 19/202869

Filed: May 08, 2025

Foreign Application Priority Data

KR

10-2020-0140186

Oct. 27, 2020

Related U.S. Application Data

parent US continuation 18215469 20230628 parent-grant-document US 12328817 child US 19202869

parent US continuation 17504611 20211019 parent-grant-document US 11758659 child US 18215469

Publication Classification

Int. Cl.: **H05K1/11** (20060101); **H05K1/02** (20060101); **H05K1/18** (20060101)

U.S. Cl.:

CPC **H05K1/118** (20130101); **H05K1/028** (20130101); **H05K1/111** (20130101); **H05K1/189** (20130101); **H05K2201/10136** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a Continuation of U.S. application Ser. No. 18/215,469, filed Jun. 28, 2023, which is a Continuation of U.S. application Ser. No. 17/504,611, filed Oct. 19, 2021 (now U.S. Pat. No. 11,758,659), which claims priority under 35 U.S.C. 119 and 35 U.S.C. 365 to Korean Patent Application No. 10-2020-0140186, filed Oct. 27, 2020, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] An embodiment relates to a flexible printed circuit board, a COF module, and an electronic device including the same. In detail, the flexible printed circuit board may be a flexible printed circuit board for COF.

BACKGROUND ART

[0003] Recently, various electronic products are thin, miniaturized, and lightened. Accordingly, a research for mounting a semiconductor chip at a high density in a narrow region of an electronic device is being conducted in various ways.

[0004] Among them, since a chip on film (COF) method uses a flexible substrate, the COF method may be applied to both a flat panel display and a flexible display. That is, since the COF method may be applied to various wearable electronic devices, the COF method is attracting attention. In addition, since the COF method may realize a fine pitch, the COF method may be used to realize a high-resolution display (QHD as the number of pixel increases).

[0005] A chip on film (COF) is a method in which a semiconductor chip is mounted on a flexible printed circuit board in the form of a thin film. For example, the semiconductor chip may be an integrated circuit (IC) chip or a large scale integrated circuit (LSI) chip.

[0006] Meanwhile, chips mounted on the flexible printed circuit board may be disposed in a multiple-layer structure that performs respective roles.

[0007] Recently, a film level route (FLR) technology in which one of the chips having such a multiple-layer structure and a circuit pattern connected thereto are directly disposed on the flexible printed circuit board has been applied. That is, a layer structure of the chip may be reduced, thereby reducing manufacturing costs of the chip by disposing a routing pattern in a chip mounting region of the flexible printed circuit board.

[0008] Meanwhile, there is a problem that cracks occur in one region of the routing pattern due to tensile stress generated during a process of bonding the routing pattern and chip, and thus reliability of the COF module is deteriorated.

[0009] Therefore, a flexible printed circuit board, a COF module, and an electronic device

including the same having a new structure that can solve the above problems are required.

SUMMARY

Technical Problem

[0010] An embodiment is directed to providing a flexible printed circuit board having improved reliability, a COF module, and an electronic device including the same.

Technical Solution

[0011] A flexible printed circuit board includes: a substrate; and a circuit pattern disposed on the substrate, wherein the substrate includes a chip mounting region, and the circuit pattern includes a wiring portion and a pad portion, wherein the circuit pattern includes: a first circuit pattern including a first-first pad portion disposed inside the chip mounting region, a first-second pad portion disposed outside the chip mounting region, and a first wiring portion that connects the first-first pad portion and the first-second pad portion, and extending in a first direction based on the chip mounting region; a second circuit pattern including a second-first pad portion disposed inside the chip mounting region, a second-second pad portion disposed outside the chip mounting region, and a second wiring portion that connects the second-first pad portion and the second-second pad portion, and extending in a second direction; and a third circuit pattern including a plurality of third pad portions disposed inside the chip mounting region and including a third wiring portion connecting the third pad portion and an extension wiring portion that extends to the outside of the third pad portion, and a protective layer is disposed on the first wiring portion and the second wiring portion.

Advantageous Effects

[0012] A flexible printed circuit board according to an embodiment may include a third circuit pattern. In detail, the flexible printed circuit board according to the embodiment may include the third circuit pattern that may serve to drive one of chips having a multiple-layer structure disposed in a chip mounting region of the flexible printed circuit board.

[0013] Accordingly, it is possible to simplify a manufacturing process of the chip having the multiple-layer structure.

[0014] In addition, the third circuit pattern of the flexible printed circuit board according to the embodiment may include a bent portion.

[0015] Accordingly, it is possible to prevent the third circuit pattern from being disconnected or cracked during a bonding process due to tensile stress generated when the third circuit pattern and the chip are bonded.

[0016] Accordingly, it is possible to improve the reliability of the flexible printed circuit board according to the embodiment and the COF module including the same.

[0017] In addition, the flexible printed circuit board according to the embodiment may further include a heat dissipation circuit pattern. In detail, it is possible to effectively dissipate heat generated during driving of the COF module by further disposing the heat dissipation circuit pattern connected to the chip.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1 is a top view of a flexible printed circuit board according to an embodiment.

[0019] FIG. 2 is a cross-sectional view taken along line B-B' in FIG. 1.

[0020] FIG. 3 is a cross-sectional view taken along line C-C' in FIG. 1.

[0021] FIG. 4 is an enlarged view of region A in FIG. 1.

[0022] FIG. 5 is a cross-sectional view taken along line D-D' in FIG. 1.

[0023] FIGS. 6 to 9 are views showing various shapes of a third circuit pattern of the flexible printed circuit board according to the embodiment.

[0024] FIG. **10** is another enlarged view of region A in FIG. **1**.

[0025] FIG. **11** is a cross-sectional view taken along line E-E' in FIG. **10**.

[0026] FIG. **12** is a top view of a COF module according to an embodiment.

[0027] FIG. **13** is a cross-sectional view showing a connection relationship of the COF module including the flexible printed circuit board according to the embodiment.

[0028] FIGS. **14** to **16** are views of an electronic device including the flexible printed circuit board according to the embodiment.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0029] Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. However, the spirit and scope of the present disclosure is not limited to a part of the embodiments described, and may be implemented in various other forms, and within the spirit and scope of the present disclosure, one or more of the elements of the embodiments may be selectively combined and replaced.

[0030] In addition, unless expressly otherwise defined and described, the terms used in the embodiments of the present disclosure (including technical and scientific terms) may be construed the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs, and the terms such as those defined in commonly used dictionaries may be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art.

[0031] In addition, the terms used in the embodiments of the present disclosure are for describing the embodiments and are not intended to limit the present disclosure. In this specification, the singular forms may also include the plural forms unless specifically stated in the phrase, and may include at least one of all combinations that may be combined in A, B, and C when described in “at least one (or more) of A (and), B, and C”.

[0032] Further, in describing the elements of the embodiments of the present disclosure, the terms such as first, second, A, B, (a), and (b) may be used. These terms are only used to distinguish the elements from other elements, and the terms are not limited to the essence, order, or order of the elements.

[0033] In addition, when an element is described as being “connected”, “coupled”, or “connected” to another element, it may include not only when the element is directly “connected” to, “coupled” to, or “connected” to other elements, but also when the element is “connected”, “coupled”, or “connected” by another element between the element and other elements.

[0034] Further, when described as being formed or disposed “on (over)” or “under (below)” of each element, the “on (over)” or “under (below)” may include not only when two elements are directly connected to each other, but also when one or more other elements are formed or disposed between two elements.

[0035] Furthermore, when expressed as “on (over)” or “under (below)”, it may include not only the upper direction but also the lower direction based on one element.

[0036] Hereinafter, a flexible printed circuit board, a COF module, and an electronic device including the same according to an embodiment will be described with reference to the drawings.

[0037] FIG. **1** is a top view of a flexible printed circuit board according to an embodiment.

[0038] Referring to FIG. **1**, a flexible printed circuit board **1000** according to the embodiment may include a substrate **100** and a circuit pattern **200** disposed on the substrate **100**.

[0039] The substrate **100** may include a flexible substrate. For example, the substrate **100** may be a polyimide (PI) substrate. However, the embodiment is not limited thereto, and the substrate **100** may include a polymer material such as polyethylene terephthalate (PET), polyethylene naphthalate (PEN), or the like. Accordingly, the flexible printed circuit board including the substrate **100** may be used in various electronic devices having a curved display device. For example, the flexible printed circuit board including the substrate **100** is excellent in flexible characteristics, thereby having suitability of mounting a semiconductor chip on a wearable electronic device

[0040] The substrate **100** may have a thickness of 20 μm to 100 μm . For example, the substrate **100** may have a thickness of 25 μm to 50 μm . For example, the substrate **100** may have a thickness of 30 μm to 40 μm . When the thickness of the substrate **100** exceeds 100 μm , the overall thickness of the flexible printed circuit board may be increased, and accordingly, the flexible characteristics may be deteriorated. In addition, when the thickness of the substrate **100** is less than 20 μm , the substrate **100** may be vulnerable to heat/pressure in a process of mounting a chip.

[0041] The substrate **100** may include a first region **1A** and a second region **2A**. For example, the first region **1A** may be a central region of the substrate **100**, and the second region **2A** may be an outer region of the substrate **100**. That is, the first region **1A** may be disposed between the second regions **2A**.

[0042] The first region **1A** may include a chip mounting region **CA**. In detail, the first region **1A** may include the chip mounting region **CA** in which a chip **C** connected to the circuit pattern is mounted.

[0043] In addition, circuit patterns **210**, **220**, and **230** may be disposed on the first region **1A**. In detail, a plurality of circuit patterns that are spaced apart from each other and extend in multiple directions may be disposed in the first region **1A**.

[0044] The circuit pattern may not be disposed in the second region **2A**. That is, the first region **1A** and the second region **2A** may be divided according to the presence or absence of the arrangement of the circuit pattern.

[0045] The second region **2A** may include a plurality of holes. In detail, the second region **2A** may include a plurality of sprocket holes **H**. The flexible printed circuit board may be wound or unwound by the sprocket hole **H** in a roll-to-roll manner.

[0046] The flexible printed circuit board may be processed into the COF module and mounted on various electronic devices after cutting a boundary line **CL** between the second region **2A** in which the sprocket hole **H** is formed and the first region **1A**.

[0047] The circuit pattern may include a wiring portion and a pad portion. In addition, the plurality of circuit patterns may be disposed in the first region **1A**. In detail, a first circuit pattern **210**, a second circuit pattern **220**, and a third circuit pattern **230** may be disposed in the first region **1A**.

[0048] Referring to FIGS. **1** and **2**, the first circuit pattern **210** may include a first wiring portion **211**, a first-first pad portion **212**, and a first-second pad portion **213**. In detail, the first circuit pattern **210** may include the first-first pad portion **212** disposed inside the chip mounting region **CA**, the first-second pad portion **213** disposed outside the chip mounting region **CA**, and the first wiring portion **211** disposed between the first-first pad portion **212** and the first-second pad portion **213** and connected to the first-first pad portion **212** and the first-second pad portion **213**.

[0049] The first wiring portion **211**, the first-first pad portion **212**, and the first-second pad portion **213** may be integrally formed.

[0050] In addition, the first wiring portion **211** may be disposed to extend in a first direction **D1** based on the chip mounting region **CA**.

[0051] The first-first pad portion **212** may be electrically connected to a chip disposed in the chip mounting region. In addition, the first-second pad portion **213** may be electrically connected to a display panel. In addition, the first wiring portion **211** may transmit a signal between the chip and the display panel.

[0052] A protective layer **300** may be disposed on the first circuit pattern **210**. In detail, the protective layer **300** may be disposed on the first wiring portion **211**. The protective layer **300** may be disposed to surround the first wiring portion **211**. In addition, the protective layer **300** may not be disposed on the first-first pad portion **212** and the first-second pad portion **213**.

[0053] In addition, referring to FIGS. **1** and **3**, the second circuit pattern **220** may include a second wiring portion **221**, a second-first pad portion **222**, and a second-second pad portion **223**. In detail, the second circuit pattern **220** may include the second-first pad portion **222** disposed inside the chip mounting region **CA**, the second-second pad portion **223** disposed outside the chip mounting

region CA, and the second wiring portion **221** disposed between the second-first pad portion **222** and the second-second pad portion **223** and connected to the second-first pad portion **222** and the second-second pad portion **223**.

[0054] The second wiring portion **221**, the second-first pad portion **222**, and the second-second pad portion **223** may be integrally formed.

[0055] In addition, the second wiring portion **221** may be disposed to extend in a second direction **D2** based on the chip mounting region CA. In detail, the second wiring portion **221** may be disposed to extend in the second direction **D2** opposite to the first direction **D1**.

[0056] The second-first pad portion **222** may be electrically connected to the chip disposed in the chip mounting region. In addition, the second-second pad portion **223** may be electrically connected to a printed circuit board. In addition, the second wiring portion **211** may transmit a signal between the chip and the printed circuit board.

[0057] The protective layer **300** may be disposed on the second circuit pattern **220**. In detail, the protective layer **300** may be disposed on the second wiring portion **221**. The protective layer **300** may be disposed to surround the second wiring portion **221**. In addition, the protective layer **300** may not be disposed on the second-first pad portion **222** and the second-second pad portion **223**.

[0058] Referring to FIG. **1** and FIG. **4**, the third circuit pattern **230** may include a third wiring portion and a plurality of pad portions. In detail, the third circuit pattern **230** may include the third wiring portion and the plurality of pad portions disposed inside the chip mounting region CA. In addition, the third circuit pattern **230** may further include extension wiring portions **233a** and **233b**. In detail, the third circuit pattern **230** may include the extension wiring portions **233a** and **233b** extending outside the third pad portion. That is, the third circuit pattern **230** may include the extension wiring portions **233a** and **233b** disposed outside the chip mounting region CA.

[0059] The third circuit pattern **230** may be connected to the chip C disposed in the chip mounting region CA. In detail, the plurality of pad portions of the third circuit pattern **230** may be electrically connected to the chip C. In detail, the third circuit pattern **230** may include a plurality of third circuit patterns **230**, and each of the third circuit patterns **230** may have a plurality of pad portions, and the plurality of pad portions of each of the third circuit patterns may be electrically connected to the chip C.

[0060] The third circuit pattern **230** may be a routing pattern. That is, the third circuit pattern **230** may be a routing pattern serving as one of layers of a chip having a plurality of layers disposed in the chip mounting region CA.

[0061] As the third circuit pattern **230** is connected to the chip CA via the plurality of pad portions, the third circuit pattern **230** may receive an electronic signal transmitted from the first circuit pattern **210** to process the electronic signal, and the electronic signal transmitted from the third circuit pattern **230** through the chip C and the second circuit pattern **220** may be transmitted to the display panel.

[0062] The first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may include a metal material having excellent electrical conductivity. In detail, the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may include copper (Cu). However, the embodiment is not limited thereto, and the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may include at least one metal among copper (Cu), aluminum (Al), and chromium (Cr), nickel (Ni), silver (Ag), molybdenum (Mo), gold (Au), titanium (Ti), and an alloy thereof.

[0063] The first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may be formed in multiple layers. In detail, the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may include a first metal layer and a second metal layer.

[0064] The first metal layer may be a seed layer of the first circuit pattern **210** and the second circuit pattern **220**. The first metal layer may be formed in a single layer or in multiple layers. The first metal layer may include copper. The first metal layer may be formed through electroless

plating or sputtering after disposing a buffer layer described below on the substrate **100**.

[0065] In addition, the second metal layer may be a plating layer. In detail, the second metal layer may be a plating layer formed by electroplating using the first metal layer as a seed layer.

[0066] A thickness of the first metal layer may be smaller than a thickness of the second metal layer.

[0067] For example, the thickness of the first metal layer may be 0.7 μm to 2 μm , and the thickness of the second metal layer may be 10 μm to 25 μm .

[0068] The first metal layer and the second metal layer may include the same metal material. For example, the first metal layer and the second metal layer may include copper (Cu).

[0069] A plating layer may be further disposed on the second metal layer. The plating layer may serve as an adhesive layer capable of electrically adhering to the chip C. In detail, the plating layer may include tin (Sn).

[0070] The plating layer may be formed on the entire wiring portion and pad portion of the circuit patterns. In addition, the plating layer may be formed in one layer or two layers.

[0071] The plating layer needs to be a pure plating layer in order to serve as an adhesion to the chip C. To this end, a thickness of the plating layer on the pad portion may be formed to be 0.1 μm or more, 0.2 μm or more, 0.3 μm or more, 0.4 μm or more, 0.5 μm or more, or 10 μm or less.

[0072] When the thickness of the plating layer on the pad portion is less than 0.1 μm , when the plating layer is formed, the second metal layer of the circuit pattern, that is, copper is diffused into the plating layer, and a pure tin plating layer may not be formed, and thus an adhesive force with the chip C may be reduced.

[0073] In addition, when the thickness of the plating layer exceeds 10 μm , a thickness of the flexible circuit board may be increased.

[0074] Accordingly, the plating layer may be formed in one layer with a thickness of 0.1 μm or more, 0.2 μm or more, 0.3 μm or more, 0.4 μm or more, 0.5 μm or more, or 10 μm or less on upper and side surfaces of the circuit pattern, or 0.1 μm or less on the wiring portion of the circuit pattern and may be formed in two layers with a thickness of 0.1 μm or more, 0.2 μm or more, 0.3 μm or more, 0.4 μm or more, 0.5 μm or more, or 10 μm or less. In detail, the wiring portion of the circuit pattern may be formed thin to prevent cracks due to the plating layer when the flexible circuit board is bent, and the pad portion may be formed thick to facilitate contact with the chip C.

[0075] The first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may be disposed to have a thickness of 2 μm to 25 μm . For example, the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may be disposed to have a thickness of 5 μm to 20 μm . For example, the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may be disposed to have a thickness of 7 μm to 15 μm .

[0076] Since the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** is subjected to a process of etching the first metal layer by flash etching performed for separation of the circuit patterns during a manufacturing process, the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** to be finally manufactured may be smaller than the sum of the thicknesses of the first metal layer, the second metal layer, and the plating layer.

[0077] When the thickness of the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** is less than 2 μm , resistances of the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** may increase. When the thickness of the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** exceeds 25 μm , it may be difficult to implement a fine pattern.

[0078] Meanwhile, a buffer layer may be further disposed between the substrate **100** and the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230**. The buffer layer may improve adhesion between the substrate **100** and the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230** that are a dissimilar material.

[0079] The buffer layer may be formed in multiple layers. In detail, a first buffer layer and a second buffer layer on the first buffer layer may be disposed on the substrate **100**. Accordingly, the first buffer layer may be in contact with the substrate **100**, and the second buffer layer may be disposed in contact with the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230**.

[0080] The first buffer layer may include a material having good adhesion to the substrate **100**. For example, the first buffer layer may include nickel (Ni). In addition, the second buffer layer may include a material having good adhesion to the circuit pattern **200**. For example, the second buffer layer may include chromium (Cr).

[0081] The buffer layer including the first buffer layer and the second buffer layer may have a thin film thickness of nanometers. For example, the buffer layer may have a thickness of 20 nm or less.

[0082] Since the adhesion between the substrate **100** and the first circuit pattern **210** and the second circuit pattern **220** that are a dissimilar material may be improved by the buffer layer, it is possible to prevent delamination of a film of the first circuit pattern **210** and the second circuit pattern **220**.

[0083] Meanwhile, the protective layer **300** may be disposed on the wiring portion of the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230**. In detail, the protective layer **300** may be disposed to surround the first wiring portion **211**, the second wiring portion **221**, and the third wiring portion **231**. That is, the protective layer **300** may be disposed on the first circuit pattern **210**, the second circuit pattern **220**, and the third circuit pattern **230**

excluding the first-first pad portion, the first-second pad portion, the second-first pad portion, the second-second pad portion, and the third pad portion.

[0084] The protective layer **300** may include solder paste. For example, the protective layer **300** may include a solder paste including a thermosetting resin, a thermoplastic resin, a filler, a curing agent, or a curing accelerator.

[0085] FIG. **4** is an enlarged view of region A in FIG. **1**. That is, FIG. **4** is an enlarged view of the chip mounting region of the flexible printed circuit board.

[0086] Referring to FIG. **4**, the third circuit pattern **230** may be disposed in the chip mounting region CA. The third circuit pattern **230** may be disposed to extend in a plurality of directions. In detail, the third circuit pattern **230** may be disposed to extend in a direction corresponding to a longitudinal direction and a direction corresponding to a width direction of the chip mounting region CA.

[0087] In FIG. **4**, one third circuit pattern **230** is disposed in the chip mounting region CA, but it is only an embodiment, and a plurality of third circuit patterns **230** extending in one direction or a plurality of directions and spaced apart from each other may be disposed in the chip mounting region CA.

[0088] For example, the plurality of third circuit patterns **230** spaced apart from each other may be disposed in the chip mounting region CA. Accordingly, the number of layer structures of the chip disposed in the chip mounting region CA may be reduced, thereby reducing a chip manufacturing process.

[0089] The third circuit pattern **230** may include third wiring portions **231** and **232** and a plurality of third pad portions connected to the third wiring portions **231** and **232**. The third wiring portion may be a moving passage region for the electronic signal, and the third pad portion may be a region connected to the chip. The third pad portion may be integrally formed with the third wiring portion,

[0090] The third circuit pattern **230** may include a plurality of third wiring portions. In detail, the third circuit pattern **230** may include the plurality of third wiring portions extending in different directions. For example, the third circuit pattern **230** may include a third-first wiring portion **231** and a third-second wiring portion **232** extending in different directions.

[0091] For example, the third-second wiring portion **232** may be disposed to extend in a direction the same as or similar to those of the first direction D1 and the second direction D2. In addition, the third-first wiring portion **231** may be disposed to extend in a third direction D3 and a fourth

direction **D4** that are different from the first direction **D1** and the second direction **D2**. For example, the third-first wiring portion **231** may be disposed to extend in the third direction **D3** and the fourth direction **D4** that are perpendicular to the first direction **D1** and the second direction **D2**. [0092] Through this, the third circuit pattern may perform a role of one layer of the multiple-layer structure of the chip disposed in the chip mounting region **CA**, and a terminal of the chip connected to the third circuit pattern may be formed in the third direction and/or the fourth direction that are different directions from a terminal of the chip connected to the first circuit pattern and the second circuit pattern, so that more chip functions may be implemented on the flexible circuit board in a limited space, and a test for confirming signal transmission characteristics through the third circuit pattern may also be efficiently performed in a region other than a test region of the first circuit pattern and the second circuit pattern.

[0093] The third-second wiring portion **232** may be integrally formed with the second circuit pattern **220**. In detail, the third-second wiring portion **232** may be integrally formed with the second wiring portion **221** or the second-first pad portion **222** of the second circuit pattern **220**.

[0094] The third-first wiring portion **231** and the third-second wiring portion **232** may be connected to each other. In detail, the third-first wiring portion **231** and the third-second wiring portion **232** may be integrally formed.

[0095] In addition, the third circuit pattern **230** may include the plurality of third pad portions. For example, the third circuit pattern **230** may include two third pad portions. In detail, the third circuit pattern **230** may include a third-first pad portion **234** and a third-second pad portion **235**. In detail, the third circuit pattern **230** may be formed in plural, and each of the third circuit patterns **230** may include two or two or more third pad portions.

[0096] The third-first pad portion **234** and the third-second pad portion **235** may be connected to the third-first wiring portion **231**. That is, the third-first wiring portion **231** may be disposed between the third-first pad portion **234** and the third-second pad portion **235** and connected to the third-first pad portion **234** and the third-second pad portion **235**. The third-first pad portion **234** and the third-second pad portion **235** may be disposed to face each other in the third direction **D3** or the fourth direction **D4**.

[0097] Through this, the terminal of the chip connected to the third circuit pattern **230** may be formed in the third direction and/or the fourth direction that are different directions from the terminal of the chip connected to the first circuit pattern and the second circuit pattern, so that more chip functions may be implemented on the flexible circuit board in a limited space.

[0098] Alternatively, the third circuit pattern **230** may further include a third-third pad portion **236**. In detail, the third circuit pattern **230** may further include the third-third pad portion **236** connected to the third-second wiring portion **232**.

[0099] Alternatively, the third circuit pattern **230** may further include a third-fourth pad portion **237**. In detail, the third circuit pattern **230** may further include the third-fourth pad portion **237** disposed in an intersecting region of the third-first wiring portion **231** and the third-second wiring portion **232**.

[0100] Alternatively, the third circuit pattern **230** may further include a third-fifth pad portion **238**. In detail, the third circuit pattern **230** may further include the third-fifth pad portion **238** between the third-first pad portion **234** and the third-fourth pad portion **237**.

[0101] Alternatively, the third circuit pattern **230** may further include a third-sixth pad portion **239**. In detail, the third circuit pattern **230** may further include the third-sixth pad portion **239** between the third-second pad portion **235** and the third-fourth pad portion **237**.

[0102] Alternatively, although not shown in the drawings, the third circuit pattern **230** may include seven or more pad portions. In detail, the third circuit pattern **230** may further include an additional pad portion between the third-first pad portion **234** and the third-fourth pad portion **237** or between the third-second pad portion **235** and the third-fourth pad portion **237**.

[0103] The third-first pad portion **234**, the third-second pad portion **235**, the third-third pad portion

236, the third-fourth pad portion **237**, the third-fifth pad portion **238**, and the third-sixth pad portion **239** may be connected to the chip C disposed in the chip mounting region CA. In detail, the third-first pad portion **234**, the third-second pad portion **235**, the third-third pad portion **236**, the third-fourth pad portion **237**, the third-fifth pad portion **238**, and the third-sixth pad portion **239** may be connected to the terminal of the chip C disposed in the chip mounting region CA, whereby the third circuit pattern **230** may be electrically connected to the chip C.

[0104] The third-first wiring portion **231** may include a first-first region **1-1 A** and a first-second region **1-2 A**. In detail, the third-first wiring portion **231** may include the first-first region **1-1 A** adjacent to the third-first pad portion **234** and the first-second region **1-2 A** between the third-first pad portion **234** and the third-second pad portions **235**.

[0105] A width of the first-first region **1-1 A** and a width of the first-second region **1-2 A** may be different from each other. In detail, the width of the first-first region **1-1 A** may be smaller than the width of the first-second region **1-2 A**. That is, the width of the first-second region **1-2 A** between the third pad portions in which the third pad portion is not disposed may be greater than the width of the first-first region **1-1 A** in which the third pad portion is disposed.

[0106] That is, a width of the third-first wiring portion between the third pad portions may be greater than a width of the third-first wiring portion of a third pad portion region.

[0107] In addition, the third-second wiring portion **232** may include a first-third region **1-3 A** and a first-fourth region **1-4 A**. In detail, the third-second wiring portion **232** may include the first-third region **1-3 A** adjacent to the third-third pad portion **236** and the first-fourth region **1-4 A** between the third-third pad portion **236** and the third-fourth pad portion **237**.

[0108] Widths of the first-third region **1-3 A** and the first-fourth region **1-4 A** may be different from each other. In detail, the width of the first-third region **1-3 A** may be smaller than the width of the first-fourth region **1-4 A**. That is, the width of the first-fourth region **1-4 A** between the third pad portions in which the third pad portion is not disposed may be greater than the width of the first-third region **1-3 A** in which the third pad portion is disposed.

[0109] That is, a width of the third-second wiring portion between the third pad portions may be greater than a width of the third-second wiring portion in the third pad portion region.

[0110] By reducing a width of the third pad portion connected to the chip, more pad portions may be formed per unit area, and if necessary, a fourth circuit pattern may be further formed in the third direction of the chip mounting region and/or the fourth direction of the chip mounting region. In addition, since the third pad portion may be formed to have a width the same as or similar to that of the first pad portion and the second pad portion connected to the chip, design efficiency may be obtained when manufacturing the chip. In addition, by increasing the width of the third wiring portion, cracks that may occur in the third wiring portion having a relatively long length compared to a length of the third pad portion may be prevented.

[0111] Referring to FIG. 5, the plurality of third pad portions including the third-first pad portion **234** may be included on the third circuit pattern **230**, and the third circuit pattern **230** may be connected to the chip C via the third pad portion.

[0112] In this case, high-temperature heat may be generated in a process of bonding the third circuit pattern **230** and the chip C of the chip mounting region CA, and tensile stress may be generated in the third circuit pattern **230** due to the high-temperature heat. Accordingly, cracks or disconnection may occur in at least one region of the third circuit pattern **230** during the process of bonding the third circuit pattern **230** and the chip C.

[0113] To solve this problem, the third circuit pattern **230** may include a bent portion. In detail, the third-first wiring portion **231** and the third-second wiring portion **232** of the third circuit pattern **230** may include at least one bent portion.

[0114] In detail, the third-first wiring portion **231** may include at least one first bent portion CA1 that extends in the third direction or the fourth direction and is bent in a direction different from the third direction or the fourth direction. In addition, the third-second wiring portion **232** may include

at least one second bent portion CA2 that extends in the first direction or the second direction and is bent in a direction different from the first direction or the second direction.

[0115] The first bent portion CA1 and the second bent portion CA2 may improve reliability of the third circuit pattern 230.

[0116] That is, by disposing the first bent portion and the second bent portion on the third circuit pattern 230, it is possible to minimize cracks or disconnections of the third circuit pattern 230 due to tensile stress generated during the process of bonding the third circuit pattern 230 and the chip C.

[0117] FIGS. 6 to 9 are views for describing an example of various shapes and arrangements of the third circuit pattern.

[0118] Referring to FIGS. 6 and 7, the third circuit pattern 230 may include a bent portion CA and may extend. In detail, the third circuit pattern 230 may include a plurality of bent portions CA bent in a direction different from a longitudinal direction of the third circuit pattern 230.

[0119] As shown in FIG. 6, the third circuit pattern 230 may include a concave portion pattern P1 concave in one direction by the bent portion CA and may extend. Accordingly, when tensile stress is generated in the third circuit pattern 230, the occurrence of cracks in one region of the third circuit pattern 230 may be minimized due to the concave portion pattern.

[0120] Alternatively, as shown in FIG. 7, the third circuit pattern 230 may include the concave portion pattern P1 concave in one direction and a convex portion pattern P2 convex in the other direction by the bent portion CA and may extend. Accordingly, when the tensile stress is generated in the third circuit pattern 230, the occurrence of cracks in one region of the third circuit pattern 230 may be minimized due to the concave portion pattern and the convex portion pattern.

[0121] In addition, since the third circuit pattern 230 has both the concave portion pattern and the convex portion pattern formed by the bent portion CA and extends, even when the tensile stress is generated in a direction different from the longitudinal direction of the third circuit pattern, the occurrence of cracks in one region of the third circuit pattern 230 may be minimized.

[0122] Referring to FIGS. 8 and 9, the third circuit patterns 230 may be disposed in plural, and each of the plurality of third circuit patterns 230 may include the bent portion CA and may extend. In detail, the plurality of third circuit patterns 230 may include the plurality of bending portions CA that are bent in a direction different from the longitudinal direction of the third circuit pattern 230.

[0123] As shown in FIG. 8, the plurality of third circuit patterns 230 may include a concave pattern concave in one direction by the bent portion CA and may extend. In addition, the plurality of third circuit patterns 230 may be disposed such that the concave portion patterns P1 overlap each other.

[0124] Accordingly, when tensile stress is generated in the third circuit pattern 230, the occurrence of cracks in one region of the third circuit pattern 230 may be minimized due to the concave portion pattern.

[0125] Alternatively, as shown in FIG. 9, the plurality of third circuit patterns 230 may be disposed such that the concave portion patterns P1 overlap each other. Accordingly, when the tensile stress is generated in the third circuit pattern 230, the occurrence of cracks in one region of the third circuit pattern 230 may be minimized due to the concave portion pattern and the convex portion pattern.

[0126] Meanwhile, as an example of the plurality of pad portions described above, at least one third pad portion among the third-first pad portion 234, the third-second pad portion 235, the third-third pad portion 236, the third-fourth pad portion 237, the third-fifth pad portion 238, and the third-sixth pad portion 239 may be disposed in a bent portion of the third circuit pattern 230.

[0127] Accordingly, the tensile stress generated in the third circuit pattern 230 may be evenly distributed in a bent portion region and a non-bent portion region in the third circuit pattern to prevent the stress from concentrating in one region of the third circuit pattern 230.

[0128] Meanwhile, the third circuit pattern 230 may further include an extension wiring portion.

The extension wiring portion may be connected to at least one pad portion of the third pad portions.

[0129] The extension wiring portion may include a first extension wiring portion 233a and a

second extension wiring portion **233b**. In detail, the extension wiring portion **233** may include the first extension wiring portion **233a** that is connected to the third-first pad portion **234** to extend and the second extension wiring portions **233b** that is connected to the third-second pad portion **235** to extend.

[0130] For example, the first extension wiring portion **233a** may be integrally formed with the third-first pad portion **234**, and the second extension wiring portion **233b** may be integrally formed with the third-second pad portion **235**. One side of the first extension wiring portion **233a** may be connected to the third-first pad portion **234**, and the other end of the first extension wiring portion **233a** may be short-circuited. That is, the other side of the first extension wiring portion **233a** may not be connected to another wiring portion or pad portion while extending toward the outside of the chip mounting region CA.

[0131] Accordingly, the other side of the first extension wiring portion **233a** may be disposed while being surrounded by the protective layer **300**.

[0132] By preventing the first extension wiring portion from being exposed to the outside of the protective layer, it is possible to prevent defects due to cracks occurring in the first extension wiring portion during a process of mounting the chip in advance.

[0133] In addition, one side of the second extension wiring portion **233b** may be connected to the third-second pad portion **235**, and the other side of the second extension wiring portion **233b** may be short-circuited. That is, the other side of the second extension wiring portion **233b** may not be connected to another wiring portion or pad portion while extending toward the outside of the chip mounting region CA.

[0134] Accordingly, the other side of the second extension wiring portion **233b** may be disposed while being surrounded by the protective layer **300**.

[0135] The first extension wiring portion **233a** and the second extension wiring portion **233b** may serve as a test terminal of the third circuit pattern **230**. In detail, the first extension wiring portion **233a** and the second extension wiring portion **233b** may serve as a test terminal that may check signal transmission characteristics through the third circuit pattern **230** before disposing the chip C in the chip mounting region CA.

[0136] Meanwhile, referring to FIGS. **10** and **11**, the flexible printed circuit board according to the embodiment may further include a fourth circuit pattern **240**.

[0137] The fourth circuit pattern **240** may include a fourth wiring portion and a fourth pad portion. In detail, the fourth circuit pattern **240** may include the fourth pad portion disposed inside the chip mounting region CA and the fourth wiring portion extending outside the fourth pad portion and disposed outside the chip mounting region CA.

[0138] The fourth wiring portion may include a fourth-first wiring portion **241a** and a fourth-second wiring portion **242a**. In addition, the fourth pad portion may include a fourth-first pad portion **241b** connected to the fourth-first wiring portion **241a** and a fourth-second pad portion **242b** connected to the fourth-second wiring portion **242a**.

[0139] One side of the fourth-first wiring portion **241a** may be connected to the fourth-first pad portion **241b**, and the other side of the fourth-first wiring portion **241a** may be short-circuited. That is, the other side of the fourth-first wiring portion **241a** may not be connected to another wiring portion or pad portion while extending toward the outside of the chip mounting region CA.

[0140] Accordingly, the other side of the fourth-first wiring portion **241a** may be disposed while being surrounded by the protective layer **300**.

[0141] In addition, one side of the fourth-second wiring portion **242a** may be connected to the fourth-second pad portion **242b**, and the other side of the fourth-second wiring portion **242a** may be short-circuited. That is, the other side of the fourth-second wiring portion **242a** may not be connected to another wiring portion or pad portion while extending toward the outside of the chip mounting region CA.

[0142] Accordingly, the other side of the fourth-second wiring portion **242a** may be disposed being

surrounded by the protective layer **300**.

[0143] The fourth circuit pattern **240** may be electrically connected to the chip C disposed in the chip mounting region CA through the fourth-first pad portion and the fourth-second pad portion.

[0144] The fourth circuit pattern **240** may include a plurality of fourth circuit patterns spaced apart from each other. For example, the fourth circuit pattern **240** may include the plurality of fourth circuit patterns connected to the chip of the chip mounting region CA and spaced apart from each other.

[0145] Accordingly, the fourth circuit pattern **240** may be connected to the chip C to serve to dissipate heat generated during driving of the chip C. That is, the fourth circuit pattern **240** may be a heat dissipation circuit pattern connected to the chip.

[0146] Accordingly, the flexible printed circuit board according to the embodiment may effectively dissipate heat through the fourth circuit pattern **240**, thereby improving the reliability of the flexible printed circuit board.

[0147] The flexible printed circuit board according to the embodiment may include a third circuit pattern. In detail, the flexible printed circuit board according to the embodiment may include the third circuit pattern that may serve to drive one of the chips having the multiple-layer structure disposed in the chip mounting region of the flexible printed circuit board.

[0148] Accordingly, it is possible to simplify a manufacturing process of the chip having the multiple-layer structure.

[0149] In addition, the third circuit pattern of the flexible printed circuit board according to the embodiment may include a bent portion.

[0150] Accordingly, it is possible to prevent the third circuit pattern from being disconnected or from being cracked during a bonding process due to tensile stress generated when the third circuit pattern and the chip are bonded.

[0151] Accordingly, it is possible to improve the reliability of the flexible printed circuit board according to the embodiment and the COF module including the same.

[0152] In addition, the flexible printed circuit board according to the embodiment may further include a heat dissipation circuit pattern. In detail, it is possible to effectively dissipate the heat generated during driving of the COF module by further disposing the heat dissipation circuit pattern connected to the chip.

[0153] FIG. **12** is a view showing a top view of a COF module according to an embodiment.

[0154] Referring to FIG. **12**, the COF module according to the embodiment may include the flexible printed circuit board described above and the chip C disposed in the chip mounting region CA of the flexible printed circuit board **1000**.

[0155] In addition, the flexible printed circuit board **1000** may include the protective layer **300** described above.

[0156] Meanwhile, the COF module may be manufactured by cutting the second region **2A** of the flexible printed circuit board **1000** and then mounting the chip C. In detail, after cutting the boundary line CL between the first region **1A** and the second region **2A** of FIG. **1**, a COF module **2000** may be manufactured, in which a driving chip electrically connected to the first circuit pattern, the second circuit pattern, and the third circuit pattern and disposed in the chip mounting region of the flexible printed circuit board is mounted.

[0157] The COF module may be positioned between the display panel and the substrate to connect an electrical signal.

[0158] That is, pad portions of the first circuit pattern and the second circuit pattern that are exposed without the protective layer **300** being disposed may be connected to the display panel and the printed circuit board, and the third circuit pattern in the chip mounting region may be connected to the chip.

[0159] Referring to FIG. **13**, one end of the COF module **2000** including the flexible printed circuit board according to the embodiment may be connected to a display panel **3000**, and the other end

opposite to the one end may be connected to a printed circuit board **4000**.

[0160] For example, one end of the COF module **2000** including the flexible printed circuit board according to the embodiment may be electrically connected by being in contact with the display panel **3000**, and the other end opposite to the one end may be electrically connected by being in contact with the printed circuit board **4000**. Here, the contact may refer to a direct contact. Alternatively, it may refer to contacting with an anisotropic conductive film (ACF) interposed therebetween.

[0161] As an example, the ACF may be disposed between the COF module **2000** and the printed circuit board **4000**. The COF module **2000** and the printed circuit board **4000** may be electrically connected while being bonded by the ACF. The ACF may be a resin in which conductive particles are dispersed. Therefore, the electrical signal connected by the printed circuit board **4000** may be transmitted to the COF module **2000** through the conductive particles included in the ACF.

[0162] Since the COF module **2000** includes a flexible substrate, it may have a rigid shape or a bent shape between the display panel **3000** and the printed circuit board **4000**.

[0163] The COF module **2000** may connect between the display panel **3000** and the printed circuit board **4000** disposed opposite to each other in a bent shape, thereby reducing a thickness of the electronic device and improving the degree of freedom in design. In addition, since the COF module **2000** including the flexible substrate may not be disconnected even in the bent shape, the reliability of the electronic device including the COF module may be improved.

[0164] Since the COF module is flexible, it may be used in various electronic devices.

[0165] For example, referring to FIG. **14**, the COF module may be included in a bendable flexible touch window. Therefore, a touch device including the same may be a flexible touch device. Therefore, a user may bend or fold it by hand. Such a flexible touch window may be applied to a wearable touch or the like.

[0166] Referring to FIG. **15**, the COF module may be included in various wearable touch devices including a curved display. Therefore, an electronic device including the COF module may be reduced in thickness or weight.

[0167] Referring to FIG. **16**, the COF module may be used for various electronic devices having a display portion such as a TV, a monitor, and a laptop computer. In this case, the COF module may be used for an electronic device having a curved-shaped display portion

[0168] However, the embodiment is not limited thereto, and of course, such a COF flexible printed circuit board and a COF module obtained by processing the same may be used for various electronic devices.

[0169] The characteristics, structures and effects described in the embodiments above are included in at least one embodiment but are not limited to one embodiment. Furthermore, the characteristic, structure, and effect illustrated in each embodiment may be combined or modified for other embodiments by a person skilled in the art. Thus, it should be construed that contents related to such a combination and such a modification are included in the scope of the present disclosure.

[0170] In addition, embodiments are mostly described above, but the embodiments are merely examples and do not limit the present disclosure, and a person skilled in the art may appreciate that several variations and applications not presented above may be made without departing from the essential characteristic of embodiments. For example, each component specifically represented in the embodiments may be varied. In addition, it should be construed that differences related to such a variation and such an application are included in the scope of the present disclosure defined in the following claims.

Claims

1. A flexible printed circuit board comprising: a substrate; a circuit pattern disposed on the substrate; and a protective layer disposed on the substrate and the circuit pattern, wherein the

- protective layer includes an open region passing through upper and lower surfaces of the protective layer and spaced from outer surfaces of the protective layer, wherein the circuit pattern includes a routing circuit pattern including a plurality of routing pad portions disposed in the open region and a routing wiring portion in direct connected between the plurality of routing pad portions, and wherein the routing wiring portion includes a plurality of bent portions.
2. The flexible printed circuit board of claim 1, wherein the routing wiring portion includes 10 or more bent portions.
 3. The flexible printed circuit board of claim 1, wherein the routing circuit pattern is provided in plural, wherein a plurality of routing circuit pattern are spaced apart along a first horizontal direction and extended along a second horizontal direction perpendicular to the first horizontal direction, and wherein a bent portion of a routing wiring portion of one routing pattern among the plurality of routing circuit patterns overlaps with a bent portion of a routing wiring portion of at least one other routing circuit pattern among the plurality of routing circuit patterns along the first horizontal direction.
 4. The flexible printed circuit board of claim 1, wherein the plurality of bent portions of the routing wiring portion are disposed in the open region.
 5. The flexible printed circuit board of claim 1, wherein the routing circuit pattern includes a first routing circuit pattern disposed entirely in the open region.
 6. The flexible printed circuit board of claim 5, wherein a plurality of routing pad portions and a routing wiring portion of the first routing pattern are not connected to an outer circuit patterns arranged outside the open region.
 7. The flexible printed circuit board of claim 5, wherein the routing circuit pattern includes a second routing circuit pattern including a first part disposed in the open region and a second part disposed outside the open region and covered with the protective layer, and wherein a routing wiring portion of the second part of the second routing circuit pattern is connected a routing wiring portion of the first part of the second routing circuit pattern.
 8. The flexible printed circuit board of claim 1, wherein the protective layer includes a first end and a second end facing each other along a first horizontal direction, wherein the circuit pattern further includes: a first circuit pattern including a first-first pad portion disposed inside the open region, a first-second pad portion disposed outside the open region and adjacent to the first end, and a first wiring portion connecting the first-first pad portion and the first-second pad portion and extending from the open region toward the first end; and a second circuit pattern including a second-first pad portion disposed inside the open region, a second-second pad portion disposed outside the open region and adjacent to the second end, and a second wiring portion connecting the second-first pad portion and the second-second pad portion and extending from the open region toward the second end, wherein the routing circuit pattern extends along a second horizontal direction between the first circuit pattern and the second circuit pattern.
 9. The flexible printed circuit board of claim 8, wherein the routing wiring portion includes a concave part pattern recessed in the first horizontal direction by the bent part.
 10. The flexible printed circuit board of claim 8, wherein the routing wiring portion includes a first routing wiring portion and a second routing wiring portion intersecting with the first routing wiring portion, and wherein the first routing wiring portion and the second routing wiring include an intersection region intersecting with each other, and a non-intersection region other than the intersection region.
 11. The flexible printed circuit board of claim 10, wherein a width of the intersection region is greater than a width of the non-intersection region.
 12. The flexible printed circuit board of claim 8, wherein the routing wiring portion includes a plurality of non-bent portions, and wherein at least one of the plurality of routing pad portions is disposed at the non-bent portion.
 13. The flexible printed circuit board of claim 8, wherein a number of routing pad portions is

smaller than a number of the first-first pad portion and a number of the second-first pad portion.

14. The flexible printed circuit board of claim 8, wherein a number of the routing wiring portion is smaller than a number of the first wiring portion and a number of the second wiring portion.

15. The flexible printed circuit board of claim 1, wherein the routing wiring portion includes a region where a width varies.

16. The flexible printed circuit board of claim 1, wherein the routing wiring portion include a region in which a spacing varies.

17. The flexible printed circuit board of claim 8, wherein the substrate includes a first surface and a second surface opposite to the first surface, and wherein the routing circuit pattern, the first circuit pattern and the second circuit pattern are disposed on the first surface.

18. A chip on film (COF) module comprising: a flexible printed circuit board according to claim 1; and a chip disposed in the open region.

19. The chip on film module according to claim 18, wherein the routing circuit pattern is connected to the chip.

20. An electronic devise comprising: a COF module according to claim 18; a display panel connected to one end of the flexible printed circuit board, and a printed circuit board connected to another end of the flexible printed circuit board.
