United States Patent	12395173
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Oh; Kyung Suk et al.

Integrated circuit that applies different data interface terminations during and after write data reception

Abstract

In an integrated circuit component having a command interface to receive commands, a data interface to receive write data during a write-data reception interval, and first and second registers, control circuitry within the integrated circuit component responds to one or more of the commands by storing within the first register and the second register, respectively, a first control value that specifies a first termination to be applied to the data interface during the write-data reception interval, and a second control value that specifies a second termination to be applied to the data interface after the write-data reception interval transpires.

Inventors:	**Oh; Kyung Suk (Cupertino, CA), Shaeffer; Ian P. (Los Gatos, CA)**
Applicant:	**Rambus Inc.** (San Jose, CA)
Family ID:	**1000008764431**
Assignee:	**Rambus Inc. (San Jose, CA)**
Appl. No.:	**17/745435**
Filed:	**May 16, 2022**

Prior Publication Data

Document Identifier	Publication Date
US 20220345131 A1	Oct. 27, 2022

Related U.S. Application Data

continuation parent-doc US 16940349 20200727 US 11349478 child-doc US 17745435
continuation parent-doc US 16853658 20200420 US 10944400 20210309 child-doc US 16940349
continuation parent-doc US 16356243 20190318 US 10651849 20200512 child-doc US 16853658
continuation parent-doc US 16051291 20180731 US 10270442 20190423 child-doc US 16356243

continuation parent-doc US 15581480 20170428 US 10056902 20180821 child-doc US 16051291
continuation parent-doc US 15132532 20160419 US 9660648 20170523 child-doc US 15581480
continuation parent-doc US 14857794 20150917 US 9337835 20160510 child-doc US 15132532
continuation parent-doc US 14523923 20141026 US 9166583 20151020 child-doc US 14857794
continuation parent-doc US 13952393 20130726 US 8981811 20150317 child-doc US 14523923
continuation parent-doc US 13480298 20120524 US 8610459 20131217 child-doc US 13952393
continuation parent-doc US 13180550 20110712 US 8188762 20120529 child-doc US 13480298
continuation parent-doc US 13043946 20110309 US 8089298 20120103 child-doc US 13180550
continuation parent-doc US 12861771 20100823 US 7924048 20110412 child-doc US 13043946
continuation parent-doc US 12507794 20090722 US 7782082 20100824 child-doc US 12861771
continuation parent-doc US 12199726 20080827 US 7602209 20091013 child-doc US 12507794
continuation parent-doc US 11422022 20060602 US 7486104 20090203 child-doc US 12199726

Publication Classification

Int. Cl.: **H03K19/00** (20060101); **G06F3/06** (20060101); **G06F13/40** (20060101); **G11C11/401** (20060101); **G11C11/4063** (20060101); **G11C11/4093** (20060101); **G11C11/41** (20060101); **G11C11/413** (20060101); **G11C11/417** (20060101); **G11C11/419** (20060101); **G11C16/06** (20060101); **G11C16/26** (20060101); **G11C16/32** (20060101); **H03K19/0175** (20060101)

U.S. Cl.:

CPC   **H03K19/0005** (20130101); **G06F3/0605** (20130101); **G06F3/0659** (20130101); **G06F3/0685** (20130101); **G06F13/4086** (20130101); **G11C11/401** (20130101); **G11C11/4063** (20130101); **G11C11/4093** (20130101); **G11C11/41** (20130101); **G11C11/413** (20130101); **G11C11/417** (20130101); **G11C11/419** (20130101); **G11C16/06** (20130101); **G11C16/26** (20130101); **G11C16/32** (20130101); **H03K19/017545** (20130101);

Field of Classification Search

CPC: H03K (19/0005); H03K (19/10745); G06F (3/0605); G06F (3/0659); G06F (3/0685); G06F (13/4086); G11C (11/401); G11C (11/4063); G11C (11/4093); G11C (11/41); G11C (11/413); G11C (11/417); G11C (11/419); G11C (16/06); G11C (16/26); G11C (16/32)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4131942	12/1977	Gillett et al.	N/A	N/A
5467455	12/1994	Gay et al.	N/A	N/A
5553250	12/1995	Miyagawa et al.	N/A	N/A
5663661	12/1996	Dillon et al.	N/A	N/A
5663663	12/1996	Cao et al.	N/A	N/A
5666078	12/1996	Lamphier et al.	N/A	N/A
5982191	12/1998	Starr	N/A	N/A
5995894	12/1998	Wendte	N/A	N/A

6060907	12/1999	Vishwanthaiah et al.	N/A	N/A
6069539	12/1999	Sanders et al.	N/A	N/A
6157206	12/1999	Taylor et al.	N/A	N/A
6198307	12/2000	Garlepp et al.	N/A	N/A
6232792	12/2000	Starr	N/A	N/A
6308232	12/2000	Gasbarro	N/A	N/A
6356105	12/2001	Volk	N/A	N/A
6356106	12/2001	Greeff	333/32	G06F 13/4086
6424200	12/2001	McNitt et al.	N/A	N/A
6560666	12/2002	Harriman et al.	N/A	N/A
6639423	12/2002	Martin et al.	N/A	N/A
6675272	12/2003	Ware et al.	N/A	N/A
6762620	12/2003	Jang et al.	N/A	N/A
6781405	12/2003	Rajan et al.	N/A	N/A
6856169	12/2004	Frans et al.	N/A	N/A
6894691	12/2004	Juenger	N/A	N/A
6924660	12/2004	Nguyen et al.	N/A	N/A
6965529	12/2004	Zumkehr et al.	N/A	N/A
6980020	12/2004	Best et al.	N/A	N/A
6981089	12/2004	Dodd et al.	N/A	N/A
7034565	12/2005	Lee	N/A	N/A
7092299	12/2005	Kwak et al.	N/A	N/A
7102200	12/2005	Fan et al.	N/A	N/A
7103792	12/2005	Moon	N/A	N/A
7123047	12/2005	Lim	N/A	N/A
7138823	12/2005	Janzen et al.	N/A	N/A
7148721	12/2005	Park	N/A	N/A
7205787	12/2006	Massoumi	326/27	H04L 25/0298
7342411	12/2007	Vergis et al.	N/A	N/A
7372293	12/2007	Cox et al.	N/A	N/A
7414426	12/2007	Cox et al.	N/A	N/A
7432731	12/2007	Bains et al.	N/A	N/A
7516281	12/2008	LaBerge	N/A	N/A
2002/0178318	12/2001	Muff	N/A	N/A
2003/0012046	12/2002	Lee et al.	N/A	N/A
2003/0016550	12/2002	Yoo	365/51	G11C 11/4093
2003/0039151	12/2002	Matsui	365/195	G11C 7/1063
2003/0126338	12/2002	Dodd et al.	N/A	N/A
2003/0234664	12/2002	Yamagata	N/A	N/A
2003/0235084	12/2002	Zumkehr et al.	N/A	N/A
2004/0098528	12/2003	Janzen	N/A	N/A
2004/0201402	12/2003	Rajan et al.	N/A	N/A
2004/0228196	12/2003	Kwak	365/230.03	G11C 5/063
2005/0007835	12/2004	Lee et al.	N/A	N/A

2005/0040845	12/2004	Park	N/A	N/A
2005/0048973	12/2004	Hou et al.	N/A	N/A
2005/0185480	12/2004	Mukker	365/198	G11C 7/1048
2005/0212551	12/2004	So et al.	N/A	N/A
2005/0226080	12/2004	Lee	N/A	N/A
2005/0228912	12/2004	Walker et al.	N/A	N/A
2005/0264316	12/2004	Atkinson	N/A	N/A
2006/0007761	12/2005	Ware et al.	N/A	N/A
2006/0034134	12/2005	Choi et al.	N/A	N/A
2006/0071683	12/2005	Best et al.	N/A	N/A
2006/0077731	12/2005	Ware et al.	N/A	N/A
2006/0106951	12/2005	Bains	N/A	N/A
2006/0277355	12/2005	Ellsberry et al.	N/A	N/A
2007/0007992	12/2006	Bains et al.	N/A	N/A
2007/0070717	12/2006	Kim	N/A	N/A
2007/0126463	12/2006	Cox	326/30	G11C 5/066
2007/0126465	12/2006	Cox et al.	N/A	N/A
2007/0247185	12/2006	Oie	326/30	H04L 25/0298
2008/0144382	12/2007	Asauchi et al.	N/A	N/A
2009/0201711	12/2008	Solomon et al.	N/A	N/A
2009/0230989	12/2008	Murayama et al.	N/A	N/A
2009/0303802	12/2008	Lee	N/A	N/A
2009/0313410	12/2008	Jeong et al.	N/A	N/A
2010/0027356	12/2009	Shaeffer et al.	N/A	N/A
2010/0226185	12/2009	Lee	N/A	N/A
2011/0057720	12/2010	Komyo et al.	N/A	N/A
2011/0110168	12/2010	Sung et al.	N/A	N/A
2011/0242916	12/2010	Seol et al.	N/A	N/A
2011/0314200	12/2010	Wilson et al.	N/A	N/A
2013/0162287	12/2012	Ko	N/A	N/A
2014/0002131	12/2013	Shaeffer	N/A	N/A
2014/0192583	12/2013	Rajan	365/63	G11C 7/10
2015/0023112	12/2014	Eom et al.	N/A	N/A
2016/0028395	12/2015	Bains et al.	N/A	N/A
2018/0166112	12/2017	Kwon et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102005036528	12/2006	DE	N/A
0531630	12/1992	EP	N/A
0693730	12/1995	EP	N/A
07-084863	12/1994	JP	N/A
10-198473	12/1997	JP	N/A
2003-283322	12/2002	JP	N/A
WO-1997-002658	12/1996	WO	N/A
WO-1998-004041	12/1997	WO	N/A

WO-2000-041300	12/1999	WO	N/A	
WO-2000-070474	12/1999	WO	N/A	
WO-2004-061690	12/2003	WO	N/A	
WO-2005-119471	12/2004	WO	N/A	
WO-2007-078496	12/2006	WO	N/A	

OTHER PUBLICATIONS

EP Extended European Search Report with Mail Date Sep. 25, 2023 re: EP Appln. No. 23175747.7. 9 pages. cited by applicant

"JEDEC Standard DDR2 Specification JESD79-2B", JEDEC Solid State Technology Association, Jan. 2005, pp. 1-113. 113 Pages. cited by applicant

CN First Office Action dated Aug. 4, 2010 in CN Application No. 200780020133.3, Includes English Translation. 11 pages. cited by applicant

CN Office Action dated Feb. 21, 2011 re CN Application No. 200780020133.3, Includes English Translation. 6 pages. cited by applicant

CN Response dated Dec. 20, 2010 re CN Application No. 200780020133.3. 7 pages. cited by applicant

CN Response dated Mar. 29, 2011 to the Second Office Action dated Feb. 21, 2011 re CN Application No. 200780020133.3, Includes English Translation. 12 pages. cited by applicant

Elpida Memory, Inc., "512M bits DDR3 SDRAM," Preliminary Data Sheet, Document No. E0785E11, Ver. 1.1, Feb. 2006, www.elpida.com. 4 pages. cited by applicant

EP—Communication Pursuant to Article 94(3) EPC with mail date Jul. 28, 2016 re EP Appln. No. 14195760.5. 6 Pages. cited by applicant

EP Communication—Extended European Search Report with Mail Date Dec. 4, 2020 re: EP Appln. No. 20186614.2. 7 pages. cited by applicant

EP Examination Report dated May 31, 2013 in EP Application No. 11193683.7. 5 pages. cited by applicant

EP Extended European Search Report dated Dec. 12, 2012 re EP Application No. 11193654.8. 11 pages. cited by applicant

EP Extended Search Report dated Jan. 29, 2010 re EP Application No. 09163220.8. 9 pages. cited by applicant

EP Extended Search Report dated Mar. 18, 2015 re EP Application No. 14195760.5. 6 pages. cited by applicant

EP Extended Search Report dated May 3, 2012 re EP Application No. 11193683.7. 6 pages. cited by applicant

EP Office Communication dated Aug. 12, 2009 for EP Application No. 07853485.6. 3 pages. cited by applicant

EP Office Communication dated Aug. 8, 2013 in EP Application No. 11193683.7. 3 pages. cited by applicant

EP Office Communication dated Sep. 28, 2010 in EP Application No. 09163220.8. 1 page. cited by applicant

EP Partial European Search Report dated Mar. 7, 2012 re EP Application No. 1193654.8. 6 pages. cited by applicant

EP Partial European Search Report dated Nov. 11, 2009 in EP Application No. 09163220.8. 4 pages. cited by applicant

EP Response dated Apr. 7, 2010 re EP Application No. 07853485.6, Includes New Claims 1-13 (Clear and Highlighted Amendments) and New Description pp. 2 and 2a. 14 pages. cited by applicant

EP Response dated Jul. 15, 2013 in EP Application No. 11193654.8. 21 pages. cited by applicant

EP Response dated Jun. 18, 2015 in EP Application No. 14195760.5, Includes New Claims

(Highlighted and Clear copies) and Claim Chart. 22 pages. cited by applicant

EP Response dated Mar. 31, 2011 in EP Application No. 09163220.8. 29 pages. cited by applicant

EP Response dated Oct. 10, 2012 re EP Application No. 11193683.7. 16 pages. cited by applicant

EP Response dated Oct. 2, 2013 in EP Application No. 11193683.7, Includes New Claims (Clear and Highlighted Copies) and New Description pp. 2, 8, and 14. 15 pages. cited by applicant

EP Response filed on Jul. 2, 2021 in Response to the Extended European Search Report Dated Dec. 4, 2020 and the Communication Pursuant to Rules 69 EPC and 70a (1) EPC Dated Jan. 15, 2021 re: EP Appln. No. 20186614.2. 11 pages. cited by applicant

EP Response With Mail Date of Nov. 3, 2016 for EP Application No. 14195760.5 in Response to EP Communication Dated Jul. 28, 2016. 17 Pages. cited by applicant

Exhibit 10—U.S. Appl. No. 60/061,770, filed Oct. 10, 1997 to Barth et al., related to U.S. Pat. No. 7,330,953. 76 pages. cited by applicant

Farrell, Todd, "Core Architecture Doubles MEM Data Rate," in Electronic Engineering Times Asia, Dec. 16, 2005. 4 pages. cited by applicant

Gervasi, Bill, "DRAM Module Market Overview," SimpleTech, JEDEX Shanghai, Oct. 25-26, 2005. 50 pages. cited by applicant

Hynix Semiconductor, "JEDEX Shanghai 2005," Oct. 2005. 24 pages. cited by applicant

Invitation to Pay Additional Fees and Communication Relating to the Results of the Partial International Search dated Jan. 16, 2008 in International Application No. PCT/US2007/069471. 8 pages. cited by applicant

Janzen, Jeff, "DDR2 Offers New Features and Functionality," Designline, vol. 12, Issue 2, Micron, Jul. 31, 2003, EN.L. 16 pages. cited by applicant

JEDEC Standard, "DDR2 SDRAM Specification," JESD-2B, Revision of JESD79-2A, JEDEC Solid State Technology Association, Jan. 2005. 112 pages. cited by applicant

Johnson, Chris, "Graphics DDR3 On-Die Termination and Thermal Considerations," Micron Designline, vol. 12, Issue 1, Rev. Apr. 1, 2003, 1Q03/2Q03. 8 pages. cited by applicant

Johnson, Chris, "The Future of Memory: Graphics DDR3 SDRAM Functionality," Micron Designline, vol. 11, Issue 4, 4Q02, Oct. 2002. 8 pages. cited by applicant

JP Office Action dated Jan. 18, 2012 in JP Application No. 2009-513379, Includes English Translation. 9 pages. cited by applicant

JP Office Action dated May 17, 2012 re JP Application No. 2009-513379, Includes English Translation. 5 pages. cited by applicant

JP Request dated Apr. 9, 2009 for Examination and a Voluntary Amendment re JP Application No. 2009-513379. 17 pages. cited by applicant

JP Response Argument and Amendment dated Apr. 16, 2012 in JP Application No. 2009-513379, Includes English Translation. 46 pages. cited by applicant

JP Response dated Aug. 15, 2012 re JP Application No. 2009-513379. 19 pages. cited by applicant

Kyungki-Do et al., "GDDR2 ODT On/Off Control Method (Single Rank/Dual Rank)," Samsung Electronics Co., Ltd., Application Note, Product Planning & Application Engineering Team, Jul. 2003. 12 pages. cited by applicant

Lee, K.H., "MultiMediaCard Solutions of Digital Storage Applications," Samsung Electronics, JEDEX Shanghai, Oct. 26, 2005. 28 pages. cited by applicant

Micron Technical Note, "DDR2-533 Memory Design Guide for Two-DIMM Unbuffered Systems," TN-47-01, 2003. 19 pages. cited by applicant

Micron Technical Note, "TN-47-07: DDR2 Simulation Support," Rev. A 7/05, 2003. 4 pages. cited by applicant

Nanya Technology Corporation, "512Mb DDR2 SDRAM," Preliminary Specification, Dec. 18, 2003, Rev. 0.2. 80 pages. cited by applicant

PCT International Preliminary Report on Patentability dated Jul. 23, 2008 in International Application No. PCT/US2007/069471. 9 pages. cited by applicant

PCT International Search Report and Written Opinion dated Apr. 7, 2008 in International Application No. PCT/US2007/069471. 18 pages. cited by applicant

Response dated Nov. 17, 2010 to Notice of Non-Compliant Information Disclosure Statement re U.S. Appl. No. 12/861,771. 1 Page. cited by applicant

Rhoden et al., "DDR/DDR2/DDR3 SDRAM Tutorial," Oct. 25-26, 2005, Slide Presentation. 118 pages. cited by applicant

Rhoden, Desi, "VTF 2005: The Evolution of DDR," Via Technology Forum 2005, Inphi Corporation, JEDEC 42 Memory Committee. 23 pages. cited by applicant

Samsung Electronics, "512Mb E-die DDR3 SDRAM Specification," Preliminary 512Mb DDR3 SDRAM, Rev. 0.5, Dec. 2006, K4B510846E. 55 pages. cited by applicant

Samsung Electronics, "DDR2 ODT Control," Product Planning & Application Engineering Team, Dec. 2004. 8 pages. cited by applicant

Shen, Dr. William Wu, "DDR3 Functional Outlook," Infineon, JEDEX Shanghai, Oct. 25-26, 2005, JEDEC 42.3B Letter Committee, Functional and Features. 30 pages. cited by applicant

Shen, Dr. William Wu, "DDR3 Functional Outlook," JEDEX San Jose, Apr. 2006, JEDEC 42.3B Letter Committee, Functional and Features. 31 pages. cited by applicant

Shen, Dr. William Wu, "System Challenges on DDR3 High Speed Clock/Address/Command Fly-by Bus Topology," JEDEX San Jose, Apr. 18, 2006. 47 pages. cited by applicant

Trost, Dr. Hans-Peter, "Press Presentation DDR3 Introduction," Memory Products Group, Infineon Technologies, AG, Jun. 2005. 11 pages. cited by applicant

Weidlich, Rainer, "What Comes Next in Commodity DRAMS—DDR3," Infineon Technologies, Jun. 2005. 4 pages. cited by applicant

EP Response as Filed Sep. 23, 2024 in Response to the Official Communication Pursuant to Article 94(3) EPC dated Jul. 5, 2024 re: EP Appln. No. 23175747.7. 19 pages. cited by applicant

Primary Examiner: Kim; Seokjin

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/940,349, filed Jul. 27, 2020 (now U.S. Pat. No. 11,349,478), which is a continuation of U.S. patent application Ser. No. 16/853,658, filed Apr. 20, 2020 (now U.S. Pat. No. 10,944,400), which is a continuation of U.S. patent application Ser. No. 16/356,243, filed Mar. 18, 2019 (now U.S. Pat. No. 10,651,849), which is a continuation of U.S. patent application Ser. No. 16/051,291, filed Jul. 31, 2018 (issued as U.S. Pat. No. 10,270,442), which is a continuation of U.S. patent application Ser. No. 15/581,480, filed Apr. 28, 2017 (issued as U.S. Pat. No. 10,056,902), which is a continuation of U.S. patent application Ser. No. 15/132,532, filed Apr. 19, 2016 (issued as U.S. Pat. No. 9,660,648), which is a continuation of U.S. patent application Ser. No. 14/857,794, filed Sep. 17, 2015 (issued as U.S. Pat. No. 9,337,835), which is a continuation of U.S. patent application Ser. No. 14/523,923, filed Oct. 26, 2014 (issued as U.S. Pat. No. 9,166,583), which is a continuation of U.S. patent application Ser. No. 13/952,393, filed Jul. 26, 2013 (issued as U.S. Pat. No. 8,981,811), which is a continuation of U.S. patent application Ser. No. 13/480,298, filed May 24, 2012 (issued as U.S. Pat. No. 8,610,459), which is a continuation of U.S. patent application Ser. No. 13/180,550, filed Jul. 12, 2011 (issued as U.S. Pat. No. 8,188,762), which is a continuation of U.S. patent application Ser. No. 13/043,946, filed Mar. 9, 2011 (issued as U.S. Pat. No. 8,089,298), which is a continuation of U.S. patent application Ser. No. 12/861,771, filed Aug. 23, 2010 (issued as U.S. Pat. No. 7,924,048), which is a continuation of U.S. patent application Ser. No. 12/507,794, filed Jul. 22, 2009 (issued as U.S. Pat. No. 7,782,082), which is a

continuation of U.S. patent application Ser. No. 12/199,726, filed Aug. 27, 2008 (issued as U.S. Pat. No. 7,602,209), which is a continuation of U.S. patent application Ser. No. 11/422,022, filed Jun. 2, 2006 (issued as U.S. Pat. No. 7,486,104). Each of the foregoing applications is hereby incorporated by reference.

TECHNICAL FIELD

(1) The present invention relates to high-speed signaling systems and components.

BACKGROUND

(2) High-speed signal lines are commonly terminated by resistive loads selected to match the characteristic impedance of the signal lines and thereby cancel undesired reflections. Historically, the terminating elements have been implemented by discrete resistors connected to metal traces on a mother board or other printed circuit board. More recently, particularly in the domain of high-bandwidth memory systems, on-die termination structures have been provided, for example, on the integrated circuit die of a memory device or memory controller.

(3) FIG. **1** illustrates a prior-art memory system **100** that employs an on-die termination scheme. The memory system **100** includes a memory controller **101** and pair of memory modules **103**A and **103**B, with each memory module coupled in parallel to a shared data path **102** (DATA), and each memory module (**103**A, **103**B) coupled to a termination control line (TC**1**, TC**2**, respectively) to enable receipt of respective termination control signal from the memory controller. As shown in detail view **106**, each of the memory devices **105** within a given memory module **103** includes a set of data input/output (I/O) circuits **107**.sub.1-**107**.sub.N having a data signal transceiver **109** (i.e., output driver and signal receiver coupled to provide inbound data to and receive outbound data from I/O logic/memory core circuitry **115**) and a switched termination structure **111** coupled in parallel to a respective data line **117**.sub.1-**117**.sub.N of data path **112** (Data[N:1]), where data lines **117**.sub.1-**117**.sub.N of data path **112** constitutes a subset of the data lines within data path **102**. The switched termination structures **111** themselves each include a respective load element (R) coupled to the corresponding data line via a switch element (X), with each of the switch elements within the memory devices of a given memory module **103** coupled to a common termination control input, TC, to receive an incoming termination control signal. By this arrangement, the memory controller **101** may assert the termination control signal supplied to either of the memory modules **103** (i.e., via termination control lines TC**1** and TC**2**) to switchably connect the load elements within the constituent memory devices of the memory module to respective lines of the data path **102**. During write operations in which data is output onto the data path **102** to be received within a selected one of the memory modules (**103**A or **103**B), the memory controller **101** asserts a termination control signal on the termination control line coupled to the non-selected memory module, thereby terminating the data path stub coupled to that memory module and suppressing undesired reflections. At the same time, the memory controller **101** deasserts the termination control signal supplied to the selected memory module thereby isolating the data path **102** from the on-die terminations within the memory devices **105** of that memory module to avoid undue signal attenuation. This operation of the memory controller is shown at **120** of FIG. **1**.

(4) Analysis shows that, unfortunately, the single-termination scheme of FIG. **1** may yield sub-optimal signaling performance due, at least in part, to impedance discontinuity that tends to result at the selected memory module when the on-die terminations within that module are decoupled from the data path **102**. On the other hand, asserting the termination control signal at the selected memory module tends to unduly attenuate the incoming data signals, reducing signaling margin and increasing the likelihood of signaling errors.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present invention is illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings and in which like reference numerals refer to similar elements and in which:

(2) FIG. **1** illustrates a prior-art memory system that employs an on-die termination scheme;

(3) FIG. **2** illustrates an embodiment of a memory system having multiple, graduated on-die terminations per high-speed signaling line;

(4) FIG. **3** illustrates an exemplary approach for achieving graduated termination within a memory system without adding additional termination structures within the constituent memory devices;

(5) FIG. **4** illustrates an alternative embodiment of a memory system having graduated on-die terminations;

(6) FIG. **5** illustrates another embodiment of a memory system having graduated on-die terminations; and

(7) FIG. **6** illustrates an exemplary state diagram of a finite state machine that may be applied within a memory device in combination with explicit or implicit termination control detection circuitry to effect a desired one of multiple, graduated terminations.

DETAILED DESCRIPTION

(8) Signaling systems having improved signaling characteristics that result from multiple, graduated on-die terminations are disclosed in various embodiments. In one embodiment, each memory device within a multiple-module memory system includes multiple on-die termination structures per incoming high-speed signal line to enable any of multiple different termination loads to be switchably coupled to the signal line according to whether the memory module is a destination for incoming signals. For example, in a particular embodiment, each memory device within a two-module memory system includes two termination structures per incoming data line, with the load elements within the two termination structures being implemented by or programmed to have different impedance values, thereby enabling selection between a relatively high-load termination and a relatively low-load termination within a given memory module according to whether the memory module is the destination for high-speed signals. Thus, during a write operation, the high-load terminations, referred to herein as hard terminations, may be switchably connected to the high-speed signaling lines within the memory devices of the non-selected (e.g., non-addressed) memory module to provide transmission line load-matching, while the low-load termination, referred to herein as a soft termination, may be switchably connected to the high-speed signaling lines within the memory devices of the selected memory module to provide a desired level of energy absorption (e.g. to cancel reflections) without unduly attenuating the incoming signals. In a subsequent write operation directed to the alternate memory module, the termination selections may be quickly reversed to establish soft termination at the alternately selected memory module and hard termination at the non-selected memory module.

(9) In one embodiment, multiple termination control lines are provided for each rank of memory devices on a memory module (a rank of memory devices being a set of one or more memory devices that are selected to receive or output data as a parallel group) to enable independent selection between soft and hard terminations therein. In an alternative embodiment, a snoop logic circuit is provided within each of the memory devices to determine whether the memory device is the target of a particular signaling transaction and to switchably couple either the soft terminations or the hard terminations to the data lines and/or other high-speed signal lines accordingly. In another embodiment, a buffer integrated circuit (IC) is provided to receive incoming signals within a memory module and to distribute the signals to one of multiple ranks of memory devices on the memory module. In such an embodiment, multiple, graduated on-die termination structures per high-speed signaling line may be provided on the buffer IC instead of, or in addition to, the memory devices. The high-speed signal lines coupled to the multiple, graduated on-die termination

structures may include data signal lines, address signal lines, command signal lines (any or all of which may be time multiplexed and thus constitute a single set of signal lines) or any combination thereof. Further, a non-volatile memory such as a serial presence detect (SPD) memory may be programmed with information indicating whether the memory devices within a given memory module include support for graduated terminations. By this arrangement, a memory controller may read the SPD memory (or other characterizing circuit or storage) to determine whether graduated terminations are supported and, if so, issue termination control signals accordingly, thus enabling the memory controller to operate in either a legacy termination mode or graduated termination mode. Also, in a system having dual-rank memory modules, the termination values for each of the two ranks on a given memory module may be programmed to have low-load and high-load values, thus enabling selection between hard and soft terminations according to whether the module is the destination for high-speed signals. These and other embodiments are described in further detail below.

(10) FIG. **2** illustrates an embodiment of a memory system **150** having multiple, graduated on-die terminations per high-speed signaling line. The memory system **150** includes a memory controller **151** coupled to two memory modules, **153**A and **153**B via a multi-drop data path **152** (i.e., the memory modules **153**A and **153**B are coupled in parallel to the data path **152**), though additional memory modules may be coupled to the multi-drop data path **152** in alternative embodiments. Also, one or more additional signal paths (not shown) for conveying command, address and timing signals may be coupled between the memory controller **151** and memory modules **153**.

(11) Each of the memory modules **153** includes multiple integrated-circuit memory devices **155** coupled to respective subsets of signal lines of the data path (i.e., coupled to respective slices of the data path **152**), thereby forming a memory rank. In general, the memory devices within the memory rank are accessed as a group, thus enabling transfer of N×M-bit wide read and write data words, where N is the number of data bits conveyed to or from a given memory device in a given transaction (i.e., the slice width), and M is the number of memory devices within the memory rank (i.e., the number of data path slices).

(12) In contrast to the memory devices of FIG. **1**, described above, each of the memory devices **155** within memory modules **153** includes two termination control inputs to enable reception of two independent termination control signals and thus provide for switched connection of one of two graduated termination loads (i.e., termination loads having different impedance values) to each data line of the incoming data slice. In the particular embodiment shown, termination control signals are output from the memory controller **151** on termination control lines, TC**1** and TC**2**, that are coupled respectively to termination control inputs, TCa and TCb, of memory module **153**A and, in reverse order, to termination control inputs TCb and TCa of memory module **153**B. Within each of the memory modules **153**, the TCa and TCb termination control inputs are coupled to corresponding TCa and TCb inputs of the individual memory devices **155**. Referring to detail view **156**, each of the memory devices **155** within a given module **153** includes a set of data I/O circuits **157**.sub.1-**157**.sub.N having a data transceiver structure **159** (e.g., output driver **160***a* and signal receiver **160***b* coupled to provide inbound data to and receive outbound data from I/O logic and memory core **165**) and a pair of switched termination structures **161***a* and **161***b* all coupled in parallel to a respective data line **167**.sub.1-**167**.sub.N of data path **162**, where data lines **167**.sub.1-**167**.sub.N of data path **162** constitute a subset of the data lines within overall data path **152**. Each of the switched termination structures **161***a*, **161***b* includes a respective load element R**1**, R**2** coupled to the corresponding data line via a corresponding switch element X**1**, X**2**. As shown, the switch elements X**1** within each of the data I/O circuits **157**.sub.1-**157**.sub.N is coupled in common to termination control input TCa and the switch elements X**2** are coupled in common to termination control input TCb. By this arrangement, when a termination control signal is asserted on signal line TC**1**, load elements R**1** are switchably coupled to respective lines of the data path **152** within module **153**A, and load elements R**2** are switchably coupled to the respective lines of the data path within module

153B (i.e., by virtue of the swapped coupling of lines TC**1**/TC**2** to the TCa and TCb inputs of the two memory modules **153**A and **153**B). Thus, by programming (or implementing) load elements R**1** to have a relatively high load (i.e., a relatively low impedance) and load elements R**2** to have a relatively low load (i.e., a relatively high impedance) within each of the memory devices **155**, load elements R**1** may be switchably coupled to the data path to effect a hard termination and load elements R**2** may be switchably coupled to the data path to effect a soft termination. Accordingly, as shown by the controller operation at **170**, during a write operation directed to memory module **153**A, the memory controller **151** may assert a termination control signal on line TC**2** (and deassert the termination control signal on line TC**1**) to switchably couple load elements R**1** to the data path **152** within memory module **153**B and to switchably couple load elements R**2** to the data path **152** within memory module **153**A, thus effecting a graduated termination within the selected and non-selected memory modules; that is, a soft termination in the selected memory module and a hard termination in the non-selected memory module (note that a third control state may be established by deasserting both termination control signals, thus decoupling termination loads from the data path **102** within both memory modules). When compared with the conventional on/off termination scheme described above in reference to FIG. **1**, the multiple, graduated terminations generally yield larger signaling margins (i.e., more open data eyes), thus providing reduced bit error rate and additional headroom for increased signaling rates.

(13) Still referring to FIG. **2**, it should be noted that the termination structures **161**a and **161**b may alternatively be included within output driver **160**a, in which case the output driver **160**a may turn on a subset of the elements used to drive the signal line (e.g., a weaker subset of drive elements than the full set used when actually driving a signal) and concurrently couple pull-up and/or pull-down termination elements to the signal line at the same time to establish the termination. Also, while a single pair of termination control lines are shown in FIG. **2** and described above (i.e., coupled to the termination control inputs TCa and TCb of memory module **153**A and in reverse order to the termination control inputs of memory module **153**B), a separate pair of termination control lines may be provided to each memory module in an alternative embodiment.

(14) FIG. **3** illustrates an exemplary approach for achieving graduated termination within a memory system **200** without adding additional termination structures within the constituent memory devices. As shown, the memory system **200** includes a memory controller **201** coupled to two dual-rank memory modules, **203**A and **203**B, via a multi-drop data path **152** (though additional dual-rank memory modules **203** may be coupled to the multi-drop data path **152** in alternative embodiments and additional ranks may be provided per memory module), but with only one termination control line provided per memory rank, instead of multiple termination control lines per memory rank as in the embodiment of FIG. **2**. Because the two ranks (**207**.sub.1 and **207**.sub.2) of memory devices **205** within a given memory module **203** are coupled in parallel to the data path **152**, and the impedance of the relatively short path between them (**208**) is relatively small as compared to the off-module portion of the data path **152**, the termination structures (or load elements thereof) within corresponding memory devices **205** within the two different ranks **207**.sub.1 and **207**.sub.2 may be programmed to have (or implemented with) different impedance values, and thus provide for selection between graduated termination loads. More specifically, as shown at detail views **216**a and **216**b, in each of the memory devices **205**A within memory rank **207**.sub.1 of module **203**A may be programmed to have a relatively high termination load, R**1** (i.e., low impedance) and each of the memory devices **205**B within memory rank **2** of memory module **203**A may be programmed to a relatively low termination load, R**2**, thus establishing a soft-terminated memory rank **207**.sub.1 and a hard-terminated memory rank **207**.sub.2 within the same memory module. Note that this arrangement is possible even within memory devices **205** that have a single termination structure (i.e., with switch X and termination load coupled in parallel with signal transceiver **159** within an I/O circuit **211**) per incoming data line **214**, and that the programming of soft and hard termination loads (R**1** and R**2**) within the devices of the different

memory ranks may be achieved through register programming (e.g., storing a value within register **221** within the I/O logic and memory core **219**), production-time configuration (e.g., fuse, anti-fuse, non-volatile storage element, etc.) or external contact strapping. The memory devices **205** within the two memory ranks **207**.sub.1 and **207**.sub.2 of memory module **203**B may be programmed in the same manner as shown in detail views **216***c* and **216***d*. By this arrangement, instead of deasserting termination the control signals supplied to a memory module selected to receive write data, the termination control signal that controls switched coupling of the soft-terminated memory rank **207**.sub.2 of the selected memory module **203** may be asserted, and the termination control signal that controls switched coupling of the hard-terminated memory rank **207**.sub.1 deasserted to establish a soft termination at the selected memory module **203**, while the termination control signals supplied to the non-selected memory module are oppositely asserted and deasserted (i.e., asserting the termination control signal to engage the hard termination at memory rank **207**.sub.1 and deasserting the termination control signal to disengage (decouple) the soft termination at memory rank **207**.sub.2) to establish a hard termination at the non-selected memory module. Accordingly, as shown by the controller operation at **230**, in a write operation directed to memory module **203**A (memory module A), termination control signals are deasserted on termination control lines TC**1** and TC**4** (i.e., set to logic '0') and asserted on termination control lines TC**2** and TC**3** (set to logic '1') to switchably couple the R**2** termination loads within memory rank **207**.sub.2 of memory module **203**A to the data path **152** (and switchably decouple the R**1** termination loads within memory rank **207**.sub.1) to effect soft-termination for the selected memory module, and switchably coupling the R**1** termination loads within memory rank **207**.sub.1 of memory module **203**B to the data path **152** to effect hard termination for the non-selected memory module. In a write operation directed to memory module **203**B, the signal levels on the termination control lines are inverted to establish soft termination (TC**3**=0, TC**4**=1) in the selected memory module **203**B, and hard termination (TC**1**=1, TC**2**=0) in the non-selected memory module **203**A.

(15) In an alternative approach to that shown in FIG. **3**, hard termination may be achieved by asserting both the termination control signals provided to a given memory module, in effect switchably coupling the load elements within commonly coupled termination structures of the two memory ranks **207**.sub.1 and **207**.sub.2 in parallel to establish an impedance R**1***R**2**/(R**1**+R**2**) which, when R**1** and R**2** are programmed to (or implemented with) the same value, becomes R**1**/2. Thus, in such an approach, both termination control signals may be asserted simultaneously to effect hard termination within a non-selected module, while a single termination control signal is asserted to effect soft termination (R**1** or R**2** or, if programmed with the same value, then either of them) within the selected memory module.

(16) FIG. **4** illustrates an alternative embodiment of a memory system **250** having graduated on-die terminations. The memory system **250** includes a memory controller **251** coupled to memory modules **253**A and **253**B via a multi-drop data path **152** and termination control lines TC**1** and TC**2** generally as described in reference to FIG. **2**. In contrast to FIG. **2**, however, each of the memory modules **253** includes a buffer IC **261** that operates as an intermediary between the memory controller **251** and one or more ranks of memory devices **263**.sub.1-**263**.sub.R. More specifically, the buffer IC **261** includes controller interface to receive signals from and output signals to the memory controller **251** (i.e., coupled to the data path, termination control lines as well as other signal lines (not shown) for conveying command, address and timing signals to/from the memory controller **251**), and multiple memory interfaces to transfer signals to and from respective memory ranks **263** (note that, in this regard, the buffer IC **261** may be implemented by multiple separate ICs, each interfacing with a respective one of the memory ranks **263** or a respective subset of the memory ranks). Each of the data paths (and/or other signal paths for conveying command, address and timing signals) coupled between a memory rank **263** and a given memory interface of the buffer IC **261** may be a point-to-point link or and may be singly or doubly terminated (i.e.,

termination structures coupled to one or both ends) either on die or on the memory module **253**. In one embodiment, the controller interface within the buffer IC **261** is implemented in generally the manner described for the individual memory devices within the embodiment of FIG. **2**. That is, each buffer IC **261** includes two termination control inputs, TCa and TCb, to enable reception of two independent termination control signals and thus provide for switched connection of one of two graduated termination loads to each high-speed signal line of the data path **152**. As in the embodiment of FIG. **2**, the termination control line connections between TC**1**/TC**2** and TCa/TCb are reversed in memory module **253**A relative to memory module **253**B so that, when a termination control signal is asserted on line TC**1**, it is received via termination control input TCa in memory module **253**A and via termination control input TCb in memory module **253**B (as discussed above, a separate pair of termination control lines may be provided for memory module instead of a shared pair of polarity-reversed control lines). Similarly, when a termination control signal is asserted on line TC**2**, it is received via termination control input TCb in memory module **253**A and via termination control input TCa in memory module **253**B. As mentioned, multiple buffer ICs may be provided to interface with respective ranks or other groupings of memory ICs within a memory module.

(17) Referring to detail view **256**, the controller interface within each buffer IC **261** may be implemented by a set of data I/O circuits **157** that are constructed generally as described above in reference to detail view **156** of FIG. **2**. That is, each I/O circuit **157** includes a data transceiver structure **159** (e.g., output driver and signal receiver) and a pair of switched termination structures **161***a* and **161***b* all coupled in parallel to a respective data line of data path **152**. Each of the switched termination structures **161***a* and **161***b* includes a respective load element (R**1**, R**2**) coupled to the data line via a corresponding switch element (X**1**, X**2**). The data transceivers **159** are coupled to a buffer logic circuit **265** which operates to multiplex (e.g., switchably couple) inbound signals received from the memory controller **251** via transceivers **159** to a selected one of the memory ranks **263**.sub.1-**263**.sub.R via a corresponding one of memory interfaces **266**.sub.1-**266**.sub.R, and to multiplex outbound signals received from one of the memory ranks **263**.sub.1-**263**.sub.R to the data transceivers **159** and thus to the memory controller **251**.

(18) As in the embodiment of FIG. **2**, the switch elements X**1** within each of the I/O circuits **157** is coupled in common to termination control input TCa and the switch elements X**2** are coupled in common to termination control input TCb. By this arrangement, and by virtue of the reversed connection of the TCa/TCb termination control inputs of memory modules **253**A and **253**B to termination control lines TC**1** and TC**2**, when a termination control signal is asserted on termination control line TC**1**, load elements R**1** are switchably coupled to respective lines of the data path **152** within memory module **253**A, and load elements R**2** are switchably coupled to respective lines of the data path **152** within memory module **253**B. Similarly, when a termination control signal is asserted on termination control line TC**2**, load elements R**2** are switchably coupled to the data path **152** within memory module **253**A and load elements R**1** are switchably coupled to the data path **152** within memory module **253**B. Accordingly, by programming (or implementing) load elements R**1** to have a relatively low impedance (i.e., relatively high load) and load elements R**2** to have a relatively high impedance (i.e., relatively low load), load elements R**1** may be switchably coupled to the data path **152** to effect hard termination and load elements R2 may be switchably coupled to the data path to effect soft termination. Thus, as shown by the controller operation at **272**, during a write operation directed to memory module **253**A (memory module A), a termination control signal may be asserted on line TC**2** to switchably couple load elements R**1** to the data path within memory module **253**B, and to switchably couple load elements R**1** to the data path within memory module **253**A, thus effecting a graduated termination within the selected and non-selected memory modules; a soft termination within the selected memory module and a hard termination within the non-selected memory module.

(19) FIG. **5** illustrates another embodiment of a memory system **300** having graduated on-die

terminations. The memory system **300** includes a memory controller **301** coupled to memory modules **303**A and **303**B via a multi-drop data path **152**, as in the embodiments described above, and also via a multi-drop command/address path **302** (CA) which may also be referred to herein as a request path (note that the command/address path may also be provided in the embodiments of FIGS. **2**, **3** and **4**, but is omitted to avoid obscuring other features of those embodiments). In contrast to the embodiments of FIGS. **2**, **3** and **4**, however, termination control lines TC**1**/TC**2** are omitted (or at least unused) in favor of snoop logic circuitry within the memory devices **305** of memory modules **303**A and **303**B. In one embodiment, shown in detail view **306** of a memory device **305**, the snoop logic **315** is included with in the I/O logic and memory core circuitry **310** and is coupled via signal receiver **311** to receive all or a subset of the signals conveyed on command/address path **302**. The snoop logic **315** includes circuitry to determine the nature of a requested transaction (e.g., read or write) and to compare a module selector (or module address) conveyed on the command/address path **302** with a module identifier value established for the memory module to determine whether a given memory access transaction is directed to the host memory device **305** (i.e., the memory device in which the snoop logic **315** resides) or to another memory device **305** coupled to the same data slice, and to generate control signals C**1** and C**2**, accordingly (which control signals are supplied to respective switch elements within data I/O circuits **157** implemented as described above in reference to FIG. **2**). As shown by the memory operation at **320**, if the snoop logic **315** within the memory devices of memory module **303**A detects a memory write transaction directed to memory module **303**A (i.e., write-enable signal asserted (WE=1) and module selector=module identifier for module **303**A), the snoop logic will deassert control signal C**1** and assert on control signal C**2** to switchably couple load elements R**2** (i.e., programmed or implemented by a relatively low-load value to establish a soft termination within the selected module) to the respective lines of data path **152** and switchably decouple load elements R**1** from the data path **152**. During the same transaction, the snoop logic **315** within the memory devices of memory module **303**B will determine that the memory write transaction is directed to another memory module (i.e., memory module A) and, in response, assert terminal control line C**2** and deassert control signal C**1** to switchably couple load elements R**1** to the data path **152** and switchably coupled load elements R**2** from the data path **152**, thereby establishing a hard termination in the non-selected memory module **303**B. When the memory controller issues a memory write command directed to memory module **303**B, the snoop logic circuits **315** within memory modules **303**A and **303**B will detect the reversed roles of the memory modules, with the snoop logic **315** within the memory devices **305** of the non-selected memory module **303**A switchably coupling load elements R**1** to the data path **152** to effect hard terminations and the snoop logic **315** within the memory devices **305** of the selected memory module **303**B switchably coupling load elements R**2** to the data path **152** to effect soft terminations.

(20) Note that a module address may be established for the memory module through configuration register programming, production-time programming or configuration (e.g., established by a fuse, anti-fuse or other non-volatile circuit element), pin strapping, etc. Also, with respect to the signals actually snooped by snoop logic **315** to determine whether the host memory device is intended to participate in a given transaction, the snoop logic may evaluate one or all bits of an incoming address field, chip-select signals and/or any other signals that bear on whether the memory device is to respond to the incoming command.

(21) Still referring to FIG. **5**, it should be noted that snoop logic circuit **315** may be combined with explicit termination control in alternative embodiments. For example, in one such embodiment, a single termination control line is provided per memory module. A termination control signal is asserted on the termination control line to indicate that a termination should be enabled, while the snoop logic indicates the gradation of the termination to be applied (e.g., soft termination or hard termination). In another alternative embodiment, a finite state machine (FSM) may be provided in place of or in combination with snoop logic circuit **315** to determine the termination value. For

example, if a given memory device (or group of memory devices) or buffer IC is expecting to receive data at the time that a termination control signal is asserted (e.g., based on a command, address value or other information received within the memory device or buffer IC a predetermined amount of time prior to transmission of the data or assertion of the control signal), the FSM may signal such expectation and thus elect to apply an appropriate one of multiple termination values. If a single termination control line is provided per module, and the termination control line to a given module is activated but no data is expected, the FSM may elect to apply a different (e.g., higher-load) termination value. A memory device or buffer IC may include an internal state machine for request/command handling purposes (and other control functions), in which case only a relatively small amount of additional logic should be needed within the state machine to select between multiple graduated terminations. Note that a state machine implementation may also be combined with snoop logic instead of or in addition to providing a dedicated termination control line. For example, a FSM within each memory module may determine the termination timing and termination value to be applied within the module according to whether the snoop logic circuit indicates the memory module to be a selected or non-selected memory module for a given transaction. In all such cases, the combination of state machine, dedicated control line input and/or snoop logic circuitry may be provided within a buffer IC as generally described in reference to FIG. **4** instead of within memory ICs.

(22) In an embodiment in which a finite state machine or other control circuit is used instead of or in combination with snoop logic circuit **315** to determine the termination value to be applied during a given transaction, each individual memory devices within each memory rank may include a finite state machine that indicates the operating state of the memory device at any given time, including whether a write or read operation is currently being performed within the memory device. Accordingly, each memory device may respond to assertion of a termination control signal on a shared or dedicated termination control line (i.e., termination control line coupled in common to multiple memory ranks or a dedicated termination control line per memory rank) by effecting hard termination, soft termination or no-termination according to the present device operating state. Alternatively, each memory device may include snoop logic circuitry (e.g., generally as described in reference to FIG. **5**) in addition to the finite state machine and may respond to detection of a transaction indicating need for termination control (i.e., the snoop logic, in effect, substituting for dedicated termination control lines) by effecting hard termination, soft termination or no-termination according to the present operating state. FIG. **6** illustrates an exemplary state diagram **350** of a finite state machine that may be applied within a memory device in combination with explicit or implicit termination control detection circuitry (i.e., circuitry coupled to a shared or dedicated termination control line, or snoop logic circuitry) to effect a desired one of multiple, graduated terminations. As shown, the memory devices of a given rank (the state machines of which may generally be operated in lock step) may initially be in an idle operating state **351** in which no rows of the constituent memory banks are activated. Although not specifically shown, the memory devices may transition between the idle state (or any of the other states shown in FIG. **6**) and various low power states, initialization states, calibration states, configuration states (i.e., for device configuration operations, including setting of programmable registers), refresh states, etc. that are not specifically shown in FIG. **6**. Because no read or write operation is occurring within the memory devices while in the idle state, detection of a termination demand (e.g., detection assertion of a dedicated or shared termination control signal or detection of information on a control and/or address path that indicates a memory read or write transaction) may be inferred to be directed to another memory rank, so that the idle-state memory devices will effect a hard termination ("Hard T"). When an activate command is received within the idle memory rank (i.e., memory rank in which the constituent memory devices are in idle state **351**), the constituent memory devices perform respective row activations at the specified row and bank address (and may assume one or more intermediate operating states) and thus transition to active state **353**. During the transition to

the active state and while in the active state, termination demands may still be inferred to be directed to other memory ranks (i.e., because no read or write operations are occurring within the subject memory rank) so that hard termination is applied as shown. When a write command is received within an activated rank, the constituent memory devices transition to a write state **355** in which write data is delivered to the write-state memory rank and a soft termination ("Soft T") is applied to improve the signaling characteristics over the data path as described above. Note that other memory ranks may apply hard termination during transfer of the write data in accordance with their operating states. After the write operation is completed (or multiple successive write operations completed), the memory devices of the memory rank may transition to a precharge state ("Prchg") **359** (e.g., in an auto-precharge mode) or back to the active state **353**. In the precharge state **359**, the memory devices of the memory rank perform operations to close the open bank and precharge internal signal lines in preparation for a subsequent activation operation. Accordingly, termination demands detected while in the precharge state **359** may be inferred to be directed to other memory ranks so that hard termination is applied as shown. Referring again to active state **353**, if a memory read command is received, the memory devices of the memory rank will transition to a read state **357** in which read data is output from the memory devices to a memory controller or other device. Accordingly, during the read state, the memory devices may decouple all termination elements from the data lines on which read data is being driven to avoid undue signal attenuation. As in the write state **355**, other memory ranks may apply hard termination during transfer of the read data in accordance with their operating states.

(23) It should be noted that while embodiments and approaches that include or support graduated signal terminations have been described primarily in the context of memory systems, such embodiments and approaches may readily be applied in any signaling system or components thereof in which dynamically-selected, graduated terminations may be beneficial. Also, with respect to memory systems, the nature of the core memory storage elements may vary according to application needs and may include, for example and without limitation, dynamic random access memory (dynamic RAM or DRAM) storage elements, static random access memory (SRAM) storage elements, non-volatile storage elements such as floating-gate transistors within an electrically erasable programmable read only memory (EEPROM or Flash EEPROM) or the like. With regard to implementation of on-die terminations themselves, the load elements may be implemented by virtually any type of passive components (e.g., resistors), active components (e.g., transistors or diodes) or any combination thereof, and the switch elements likewise may be implemented by transistor switches or any other on-die structures that may be used to connect or disconnect a load element from a given node. Also, while the multiple on-die termination elements or circuits have generally been depicted herein as distinct termination circuits, in all such cases two or more termination circuits may be implemented by respective load elements that include shared components. For example, a first load element within a first termination circuit may be implemented by a first set of transistors that are enabled or disabled as a group to effect a first termination impedance, while a second load element within a second termination circuit may include a subset of the first set of transistors that are enabled or disabled as a group to effect a different termination impedance.

(24) Various aspects of embodiments disclosed herein are set forth, for example and without limitation, in the following numbered clauses: 1. A memory module comprising: a plurality of data inputs to couple to signal lines of an external data path; first and second termination control inputs to receive first and second termination control signals, respectively; a buffer integrated circuit (IC) having a first interface coupled to the plurality of data inputs and to the first and second control inputs and having a first memory interface that includes a plurality input/output (I/O) nodes; and a first plurality of memory ICs, each memory IC coupled to a respective subset of the plurality of I/O nodes. 2. The memory module of clause 1 wherein the buffer IC comprises a plurality of termination circuits coupled respectively to the subset of the plurality of data inputs, each

termination circuit including a first load element switchably coupled to a corresponding one of the data inputs and a second load element switchably coupled to the corresponding one of the data inputs. 3. The memory module of clause 2 wherein each of the plurality of termination circuits includes a first switch element to switchably couple the first load element to or switchably decouple the first load element from the corresponding one of the data inputs according to the state of a signal received via the first termination control input, and a second switch element to switchably couple the second load element to or switchably decouple the second load from the corresponding one of the data inputs according to the state of a signal received via the second termination control input. 4. The memory module of clause 1 wherein each memory IC of the first plurality of memory ICs comprises an array of dynamic random access memory (DRAM) storage elements. 5. The memory module of clause 1 wherein the buffer IC comprises a second memory interface, and wherein the memory module comprises a second plurality of memory ICs coupled to the second memory interface.

(25) It should also be noted that the various circuits disclosed herein may be described using computer aided design tools and expressed (or represented), as data and/or instructions embodied in various computer-readable media, in terms of their behavioral, register transfer, logic component, transistor, layout geometries, and/or other characteristics. Formats of files and other objects in which such circuit expressions may be implemented include, but are not limited to, formats supporting behavioral languages such as C, Verilog, and VHDL, formats supporting register level description languages like RTL, and formats supporting geometry description languages such as GDSII, GDSIII, GDSIV, CIF, MEBES and any other suitable formats and languages. Computer-readable media in which such formatted data and/or instructions may be embodied include, but are not limited to, non-volatile storage media in various forms (e.g., optical, magnetic or semiconductor storage media) and carrier waves that may be used to transfer such formatted data and/or instructions through wireless, optical, or wired signaling media or any combination thereof. Examples of transfers of such formatted data and/or instructions by carrier waves include, but are not limited to, transfers (uploads, downloads, e-mail, etc.) over the Internet and/or other computer networks via one or more data transfer protocols (e.g., HTTP, FTP, SMTP, etc.).

(26) When received within a computer system via one or more computer-readable media, such data and/or instruction-based expressions of the above described circuits may be processed by a processing entity (e.g., one or more processors) within the computer system in conjunction with execution of one or more other computer programs including, without limitation, net-list generation programs, place and route programs and the like, to generate a representation or image of a physical manifestation of such circuits. Such representation or image may thereafter be used in device fabrication, for example, by enabling generation of one or more masks that are used to form various components of the circuits in a device fabrication process.

(27) In the foregoing description and in the accompanying drawings, specific terminology and drawing symbols have been set forth to provide a thorough understanding of the present invention. In some instances, the terminology and symbols may imply specific details that are not required to practice the invention. For example, the interconnection between circuit elements or circuit blocks may be shown or described as multi-conductor or single conductor signal lines. Each of the multi-conductor signal lines may alternatively be single-conductor signal lines, and each of the single-conductor signal lines may alternatively be multi-conductor signal lines. Signals and signaling paths shown or described as being single-ended may also be differential, and vice-versa. Similarly, signals described or depicted as having active-high or active-low logic levels may have opposite logic levels in alternative embodiments. As another example, circuits described or depicted as including metal oxide semiconductor (MOS) transistors may alternatively be implemented using bipolar technology or any other technology in which logical elements may be implemented. With respect to terminology, a signal is said to be "asserted" when the signal is driven to a low or high logic state (or charged to a high logic state or discharged to a low logic state) to indicate a

particular condition. Conversely, a signal is said to be "deasserted" to indicate that the signal is driven (or charged or discharged) to a state other than the asserted state (including a high or low logic state, or the floating state that may occur when the signal driving circuit is transitioned to a high impedance condition, such as an open drain or open collector condition). A signal driving circuit is said to "output" a signal to a signal receiving circuit when the signal driving circuit asserts (or deasserts, if explicitly stated or indicated by context) the signal on a signal line coupled between the signal driving and signal receiving circuits. A signal line is said to be "activated" when a signal is asserted on the signal line, and "deactivated" when the signal is deasserted. Additionally, the prefix symbol "/" attached to signal names indicates that the signal is an active low signal (i.e., the asserted state is a logic low state). A line over a signal name (e.g., '<signal name>') is also used to indicate an active low signal. The term "coupled" is used herein to express a direct connection as well as a connection through one or more intervening circuits or structures. Integrated circuit device "programming" may include, for example and without limitation, loading a control value into a register or other storage circuit within the device in response to a host instruction and thus controlling an operational aspect of the device, establishing a device configuration or controlling an operational aspect of the device through a one-time programming operation (e.g., blowing fuses within a configuration circuit during device production), and/or connecting one or more selected pins or other contact structures of the device to reference voltage lines (also referred to as strapping) to establish a particular device configuration or operation aspect of the device. The term "exemplary" is used to express an example, not a preference or requirement.

(28) While the invention has been described with reference to specific embodiments thereof, it will be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention. For example, features or aspects of any of the embodiments may be applied, at least where practicable, in combination with any other of the embodiments or in place of counterpart features or aspects thereof. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

Claims

1. An integrated circuit component comprising: a data interface; a command interface; a chip-select input; one or more programmable registers to store first and second termination control values; and control circuitry to: enable the command interface to receive a memory access command if a chip-select signal is asserted at the chip-select input during a first interval and, if the memory access command indicates a memory write operation, to: transition a termination coupled to the data interface from a first impedance specified by the first control value to a second impedance specified by the second control value; enable the data interface to receive write data during a write-data reception interval that transpires after the termination coupled to the data interface has transitioned to the second impedance; and transition the termination coupled to the data interface from the second impedance to the first impedance after the write-data reception interval transpires; and maintain the termination coupled to the data interface at the first impedance throughout a time period that would otherwise constitute the write-data reception interval if the chip-select signal is not asserted at the chip-select input during the first interval.

2. The integrated circuit component of claim 1 wherein the control circuitry to transition the termination coupled to the data interface from the first impedance to the second impedance comprises circuitry to transition the termination from the first impedance to the second impedance a predetermined time prior to reception of the write data via the data interface.

3. The integrated circuit component of claim 1 wherein the control circuitry to transition the termination coupled to the data interface from the first impedance to the second impedance comprises circuitry to transition the termination from the first impedance to the second impedance a predetermined time after reception of the command indicating the memory write operation.

4. The integrated circuit component of claim 1 wherein the control circuitry to transition the termination coupled to the data interface from the second impedance to the first impedance after the write-data reception interval transpires comprises circuitry to transition the termination from the second impedance to the first impedance a predetermined time after conclusion of the write-data reception interval.

5. The integrated circuit component of claim 1 wherein the data interface comprises a plurality of data input/output (I/O) nodes to be coupled to respective external data-signaling lines, and wherein the control circuitry to transition the termination to the second impedance comprises circuitry to switchably couple, to each of the plurality of data I/O nodes, a respective first plurality of termination load elements.

6. The integrated circuit component of claim 5 wherein the control circuitry to transition the termination to the first impedance comprises circuitry to switchably couple, to each of the plurality of data I/O nodes, a respective second plurality of termination load elements, the second plurality of termination load elements including at least one termination load element not included in the first plurality of termination load elements.

7. The integrated circuit component of claim 5 wherein the data interface comprises output drivers coupled respectively to the data I/O nodes, and wherein the circuitry to switchably couple the respective first plurality of termination load elements to each of the plurality of I/O nodes comprises circuitry to couple, to each of the plurality of I/O nodes, a plurality of pull-up elements and a plurality of pull-down elements within a respective one of the output drivers.

8. The integrated circuit component of claim 1 further comprising circuitry to write the first and second termination control values, after reception thereof via the command interface, into the one or more programmable registers for storage therein.

9. The integrated circuit component of claim 8 wherein the circuitry to write the first and second termination control values into the one or more programmable registers comprises circuitry to write the first and second termination control values into the one or more programmable registers in response to a register-write command received via the command interface, wherein at least one of the first and second termination control values is received via the command interface as part of the register-write command.

10. The integrated circuit component of claim 8 wherein the circuitry to write the first and second termination control values into the one or more programmable registers comprises circuitry to write, into the one or more programmable registers, first and second digital bit patterns indicative of the first and second impedances, respectively.

11. A method of operation within an integrated circuit component having a data interface, a command interface, a chip-select input, and one or more programmable registers, the method comprising: storing first and second termination control values within the one or more programmable registers; if a chip-select signal is asserted at the chip-select input during the first interval, receiving a command via the command interface; if the command indicates a memory write operation: transitioning a termination coupled to the data interface from a first impedance specified by the first control value to a second impedance specified by the second control value; receiving write data via the data interface during a write-data reception interval that transpires after the termination coupled to the data interface has transitioned to the second impedance; and after receiving the write data via the data interface, transitioning the termination coupled to the data interface from the second impedance to the first impedance; and if the chip-select signal is not asserted at the chip-select input during the first interval, maintaining the termination coupled to the data interface at the first impedance throughout a time period that would otherwise constitute the write-data reception interval.

12. The method of claim 11 wherein transitioning the termination coupled to the data interface from the first impedance to the second impedance comprises transitioning the termination from the first impedance to the second impedance a predetermined time prior to reception of the write data via

the data interface.

13. The method of claim 11 wherein transitioning the termination coupled to the data interface from the first impedance to the second impedance comprises transitioning the termination from the first impedance to the second impedance a predetermined time after reception of the command indicating the memory write operation.

14. The method of claim 11 wherein transitioning the termination coupled to the data interface from the second impedance to the first impedance comprises transitioning the termination from the second impedance to the first impedance a predetermined time after conclusion of the write-data reception interval.

15. The method of claim 11 wherein the data interface comprises a plurality of data input/output (I/O) nodes to be coupled to respective external data-signaling lines, and wherein transitioning the termination to the second impedance comprises coupling, to each of the plurality of data I/O nodes, a respective first plurality of termination load elements.

16. The method of claim 15 wherein transitioning the termination to the first impedance comprises coupling, to each of the plurality of data I/O nodes, a respective second plurality of termination load elements, the second plurality of termination load elements including at least one termination load element not included in the first plurality of termination load elements.

17. The method of claim 15 wherein the data interface comprises output drivers coupled respectively to the data I/O nodes, and wherein coupling the respective first plurality of termination load elements to each of the plurality of I/O nodes comprises coupling, to each of the plurality of I/O nodes, a plurality of pull-up elements and a plurality of pull-down elements within a respective one of the output drivers.

18. The method of claim 11 further comprising receiving the first and second termination control values via the command interface.

19. The method of claim 11 wherein storing first and second termination control values within the one or more programmable registers comprises storing first and second digital bit patterns indicative of the first and second impedances, respectively.

20. An integrated circuit component comprising: a data interface; a command interface; a chip-select input; means for storing first and second termination control values; and means for: enabling the command interface to receive a memory access command if a chip-select signal is asserted at the chip-select input during a first interval and, if the memory access command indicates a memory write operation, for: transitioning a termination coupled to the data interface from a first impedance specified by the first control value to a second impedance specified by the second control value; enabling the data interface to receive write data during a write-data reception interval that transpires after the termination coupled to the data interface has transitioned to the second impedance; and transitioning the termination coupled to the data interface from the second impedance to the first impedance after the write-data reception interval transpires; and maintaining the termination coupled to the data interface at the first impedance throughout a time period that would otherwise constitute the write-data reception interval if the chip-select signal is not asserted at the chip-select input during the first interval.