



US 20250256174A1

(19) **United States**

(12) **Patent Application Publication**
Higdon et al.

(10) **Pub. No.: US 2025/0256174 A1**

(43) **Pub. Date: Aug. 14, 2025**

(54) **MULTI-COMPONENT PUTTER**

(71) Applicant: **KARSTEN MANUFACTURING CORPORATION**, Phoenix, AZ (US)

(72) Inventors: **David A. Higdon**, Cave Creek, AZ (US); **Jacob T. Clarke**, Apex, NC (US)

(73) Assignee: **KARSTEN MANUFACTURING CORPORATION**, Phoenix, AZ (US)

(21) Appl. No.: **19/192,123**

(22) Filed: **Apr. 28, 2025**

Related U.S. Application Data

(63) Continuation of application No. 17/444,468, filed on Aug. 4, 2021, now Pat. No. 12,285,662, which is a continuation-in-part of application No. 29/720,679, filed on Jan. 15, 2020, now Pat. No. Des. 930,097, which is a continuation of application No. 17/243,338, filed on Apr. 28, 2021, now Pat. No. 11,458,375,

which is a continuation-in-part of application No. 29/720,679, filed on Jan. 15, 2020, now Pat. No. Des. 930,097, which is a continuation of application No. 16/590,270, filed on Oct. 1, 2019, now Pat. No. 11,020,640.

(60) Provisional application No. 62/739,747, filed on Oct. 1, 2018.


Publication Classification

(51) **Int. Cl.**
A63B 53/04 (2015.01)

(52) **U.S. Cl.**
CPC **A63B 53/0487** (2013.01); **A63B 53/0412** (2020.08); **A63B 53/0416** (2020.08); **A63B 53/0441** (2020.08)

(57) **ABSTRACT**

An embodiment of a putter type golf club head with an upper and lower portion, made from two different materials, is enclosed herein. Other embodiments are described herein.






FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2B




FIG. 2A






FIG. 2C








FIG. 3C






FIG. 4C




FIG. 5B





FIG. 5C






FIG. 6C




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8B

FIG. 8A




FIG. 8C




FIG. 9B




FIG. 9A




FIG. 9C




FIG. 10B

FIG. 10A




FIG. 10C




FIG. 11B

FIG. 11A

MULTI-COMPONENT PUTTER

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This is a continuation of U.S. patent application Ser. No. 17/444,468, filed on Aug. 4, 2021, which is a continuation-in-part of U.S. patent application Ser. No. 29/720,679, filed on Jan. 15, 2020, now U.S. Pat. No. D930,097, issued on Sep. 7, 2021. U.S. patent application Ser. No. 17/444,468 is also a continuation of U.S. patent application Ser. No. 17/243,338, filed on Apr. 28, 2021, now U.S. Pat. No. 11,458,375, issued on Oct. 4, 2022, which is a continuation-in-part of U.S. patent application Ser. No. 29/720,679, filed on Jan. 15, 2020, now U.S. Pat. No. D930,097, issued on Sep. 7, 2021. U.S. patent application Ser. No. 17/243,338 is also a continuation of U.S. patent application Ser. No. 16/590,270, filed on Oct. 1, 2019, which claims the benefit of U.S. Provisional Patent Appl. No. 62/739,747, filed on Oct. 1, 2018, the contents all of which are incorporated fully herein by reference.

TECHNICAL FIELD

[0002] This disclosure relates generally to golf clubs and relates more particularly to a multi-component putter type golf club head.

BACKGROUND

[0003] In many putter-type golf club heads, there is a use of a weight distribution device, in order to vary the center of gravity or increase the moment of inertia (MOI) of the golf club head. Common weight distribution devices include removable weight ports in the heel and toe regions of the sole, weighted faceplate inserts, inserts for the back of portion of the face, and attachments for the outer perimeter of the toe and heel regions. In particular putter-type golf club heads, often use weight ports in the heel and toe regions that can be removable attached by a fastener, or permanently attached through a variety of epoxies, glues, or machining methods. The use of weight ports in the heel and toe regions, the increases the MOI in the putter head, thereby producing a straighter ball path after impact.

[0004] Although these weight ports in the heel and toe regions increase MOI, they increase the weight of the golf club head and can make the golf club head heavier than an ideal weight for a putter. In addition, installing weight ports into a golf club putter head requires a cavity or recess to place these weight ports into the putter head during manufacturing, thereby increasing the cost of that putter head. Additionally, the weight ports can cause vibrations within the cavity or recess during impact, when the golf club head contacts a golf ball. These cavities and recesses can cause the sound of the club head to change as well, creating a hollow sound within the club head. There is a need in the art to develop a putter having perimeter weighting and having an ideal weight for balanced putting without adding complicated structures such as weight ports.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] FIG. 1A illustrates an exploded view of a blade putter type golf club head.

[0006] FIG. 1B illustrates an isometric view of the blade putter type golf club head of FIG. 1A.

[0007] FIG. 1C illustrates a side view of the blade putter type golf club head of FIG. 1A.

[0008] FIG. 2A illustrates an exploded view of a blade putter type golf club head.

[0009] FIG. 2B illustrates an isometric view of the blade putter type golf club head of FIG. 2A.

[0010] FIG. 2C illustrates a side view of the blade putter type golf club head of FIG. 2A.

[0011] FIG. 3A illustrates an exploded view of a crescent putter type golf club head.

[0012] FIG. 3B illustrates an isometric view of the crescent putter type golf club head of FIG. 3A.

[0013] FIG. 3C illustrates a side view of the crescent putter type golf club head of FIG. 3A.

[0014] FIG. 4A illustrates an exploded view of a semi-circular putter type golf club head.

[0015] FIG. 4B illustrates an isometric view of the semi-circular putter type golf club head of FIG. 4A.

[0016] FIG. 4C illustrates a side view of the semi-circular putter type golf club head of FIG. 4A.

[0017] FIG. 5A illustrates an exploded view of another semi-circular putter type golf club head.

[0018] FIG. 5B illustrates an isometric view of the semi-circular putter type golf club head of FIG. 5A.

[0019] FIG. 5C illustrates a side view of the semi-circular putter type golf club head of FIG. 5A.

[0020] FIG. 6A illustrates an exploded view of a winged putter type golf club head.

[0021] FIG. 6B illustrates an isometric view of the winged putter type golf club head of FIG. 6A.

[0022] FIG. 6C illustrates a side view of the winged putter type golf club head of FIG. 6A.

[0023] FIG. 7A illustrates an exploded view of a spade putter type golf club head.

[0024] FIG. 7B illustrates an isometric view of the spade putter type golf club head of FIG. 7A.

[0025] FIG. 7C illustrates a side view of the spade putter type golf club head of FIG. 7A.

[0026] FIG. 8A illustrates an exploded view of a T-shaped putter type golf club head with periphery spans.

[0027] FIG. 8B illustrates an isometric view of the T-shaped putter type golf club head with periphery spans of FIG. 8A.

[0028] FIG. 8C illustrates a side view of the T-shaped putter type golf club head with periphery spans of FIG. 8A.

[0029] FIG. 9A illustrates an exploded view of a dual rail putter type golf club head.

[0030] FIG. 9B illustrates an isometric view of the dual rail putter type golf club head of FIG. 9A.

[0031] FIG. 9C illustrates a side view of the dual rail putter type golf club head of FIG. 9A.

[0032] FIG. 10A illustrates an exploded view of a circular putter type golf club head.

[0033] FIG. 10B illustrates an isometric view of the circular putter type golf club head of FIG. 10A.

[0034] FIG. 10C illustrates a side view of the circular putter type golf club head of FIG. 10A.

[0035] FIG. 11A illustrates an exploded view of a putter type golf club head with at least one strike face insert.

[0036] FIG. 11B illustrates an exploded view of another putter type golf club head with at least one strike face insert.

[0037] Other aspects of the disclosure will become apparent by consideration of the detailed description and accompanying drawings.

DESCRIPTION

I. Putter Golf Club Head

[0038] Described herein is a two part putter having an upper portion made of a first material such as low density metal (i.e., aluminum, but not limited to) and a lower portion made of a second material, such as a high density metal (i.e., steel, but not limited to). The upper portion has crown that spans from a strike face to a back edge. This upper portion is affixed to the lower portion and is farther from a ground plane than the lower portion. The lower portion, in most embodiments, has less than 35% of the total solid volume of the putter head, but greater than 45% of the mass. The lower portion provides a peripheral construction and a sole. This combination of peripheral construction and high density lower portion, results in an increase in MOI of at least 30%, over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single material such as a steel putter or a putter investment cast of a single material).

[0039] The terms “first,” “second,” “third,” “fourth,” and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms “include,” and “have,” and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, system, article, device, or apparatus that comprises a list of elements is not necessarily limited to those elements but may include other elements not expressly listed or inherent to such process, method, system, article, device, or apparatus.

[0040] The terms “left,” “right,” “front,” “back,” “upper,” “lower,” “over,” “under,” “top,” “bottom,” and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the apparatus, methods, and/or articles of manufacture described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein.

[0041] Before any embodiments of the disclosure are explained in detail, it is to be understood that the disclosure is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The disclosure is capable of other embodiments and of being practiced or of being carried out in various ways.

[0042] In many embodiments, the golf club head can comprise a putter-type golf club head (the putter type golf club head **100**, **200**, **300** **400** . . . , etc.). FIGS. **1-12B** illustrate multiple embodiments of a putter-type golf club head having an upper portion and lower portion that are separately made of different materials and coupled together. The putter-type golf club head can be a mallet-type putter head, mid-mallet type putter head, a blade type putter head, a high MOI putter head, or any other type of putter-type golf club head.

[0043] In many embodiments, the putter-type golf club head can have a loft angle less than 10 degrees. In many embodiments, the loft angle of the club head can be between 0 and 5 degrees, between 0 and 6 degrees, between 0 and 7 degrees, or between 0 and 8 degrees. For example, the loft angle of the club head can be less than 10 degrees, less than 9 degrees, less than 8 degrees, less than 7 degrees, less than 6 degrees, or less than 5 degrees. For further example, the loft angle of the club head can be 0 degrees, 1 degree, 2 degrees, 3 degrees, 4 degrees, 5 degrees, 6 degrees, 7 degrees, 8 degrees, 9 degrees, or 10 degrees.

[0044] The putter-type golf club head comprises an upper portion and a lower portion. The golf club head can comprise a toe end and a heel end opposite the toe end. The putter-type golf club head can comprise a strike face. The putter-type golf club head can comprise a rear wall opposite the strike face. Further, the putter-type golf club head can comprise an alignment feature. Furthermore, the putter-type golf club head can comprise a hosel attached to the heel end of the golf club head. The hosel may be attached to the center of the putter-type golf club head. The hosel may be attached to the heel end of the putter-type golf club head. The hosel may be integrally formed with the upper portion of the putter-type golf club head. The hosel may be integrally formed with the lower portion of the putter-type golf club head.

[0045] The upper portion is made of a first material. The lower portion is made of a second material. The first material is different than the second material. The first material has a first density. The second material has a second density. The first density is not the same as the second density.

[0046] In many embodiments, the putter-type golf club head can have a mass that ranges between 340 and 385 grams. In other embodiments, the mass of the putter-type golf club head can range between 340 grams-345 grams, 345 grams-350 grams, 350 grams-355 grams, 355 grams-360 grams, 360 grams-365 grams, 365 grams-370 grams, 370 grams-375 grams, 375 grams-380 grams, or 380 grams-385 grams. In some embodiments, the mass of the putter-type golf club head can be 340 grams, 341 grams, 342 grams, 343 grams, 344 grams, 345 grams, 346 grams, 347 grams, 348 grams, 349 grams, 350 grams, 351 grams, 352 grams, 353 grams, 354 grams, 355 grams, 356 grams, 357 grams, 358 grams, 359 grams, 360 grams, 361 grams, 362 grams, 363 grams, 364 grams, 365 grams, 366 grams, 367 grams, 368 grams, 369 grams, 370 grams, 371 grams, 372 grams, 373 grams, 374 grams, 375 grams, 376 grams, 377 grams, 378 grams, 379 grams, 380 grams, 381 grams, 382 grams, 383 grams, 384 grams, or 385 grams.

[0047] In many embodiments, the putter type golf club head can comprise a club head volume ranging between 25 cc and 125 cc. In some embodiments, the club head volume can range between 25 cc-30 cc, 30 cc-35 cc, 35 cc-40 cc, 40 cc-45 cc, 45 cc-50 cc, 50 cc-55 cc, 55 cc-60 cc, 60 cc-65 cc, 65 cc-70 cc, 70 cc-75 cc, 75 cc-80 cc, 80 cc-85 cc, 85 cc-90 cc, 90 cc-95 cc, 95 cc-100 cc, 100 cc-105 cc, 105 cc-110 cc, 110 cc-115 cc, 115 cc-120 cc, or 120 cc-125 cc. In one embodiment, the club head volume can range between 40 cc-110 cc. In some embodiments, the club head volume can be greater than 25 cc, greater than 50 cc, greater than 75 cc, or greater than 100 cc.

[0048] In some embodiments, the putter type golf club head can comprise a strike face made of the first material. In other embodiments, the strike face can be made of the second material. In these embodiments, the material of the

strike face can be any one or combination of the following: 8620 alloy steel (7.83 g/cc), S25C steel (7.85 g/cc), carbon steel (7.85 g/cc), maraging steel (8.00 g/cc), 17-4 stainless steel (7.81 g/cc), 303 stainless steel (8.03 g/cc), 304 stainless steel (8.00 g/cc), stainless steel alloy (7.75 g/cc-8.05 g/cc), tungsten (19.25 g/cc), aluminum (2.70 g/cc), aluminum alloy (2.64 g/cc-2.81 g/cc), ADC-12 (2.75 g/cc), or any metal suitable for creating a golf club head. In some embodiments, the strike face can be integrally formed to the upper portion. In other embodiments the strike face can be integrally formed to the lower portion. The strike face can be integrally formed to the club head by co-molding, injection molding, casting, additive manufacturing or other forming process.

[0049] Referring to FIGS. 11A and 11B, in some embodiments, the putter type golf club head can comprise a strike face insert. In these embodiments, the strike face is independently formed prior to being coupled to the club head. The side of the strike face insert that will contact the club head can comprise geometry complementary to the geometry of the corresponding portion of the club head that will contact the strike face. In some embodiments, the strike face insert can be made of the first material or the second material. In other embodiments, the strike face insert can be made of a third material. In some embodiments, the strike face insert can be integrally formed with the upper portion or the lower portion. In other embodiments, the strike face insert can be separately formed from both the upper portion and the lower portion.

[0050] The strike face can be secured to the club head by being integrally formed to a portion of the club head or by a fastening means. In some embodiments, the strike face is secured to the upper portion. In these embodiments, the upper portion can comprise an insert cavity. The upper portion insert cavity functions to receive the strike face insert. Further, in these embodiments, when the insert is affixed to the upper portion, the upper portion encompasses and mates with the insert cavity. In other embodiments, the strike face is secured to the lower portion. In these embodiments, the lower portion can comprise an insert cavity. The lower portion insert cavity functions to receive the strike face insert. Further, in these embodiments, when the insert is affixed to the lower portion, the lower portion encompasses and mates with the insert cavity. The strike face can be secured by an adhesive such as glue, very high bond (VHB™) tape, epoxy or another adhesive. Alternately or additionally, the strike face can be secured by welding, soldering, screws, rivets, pins, mechanical interlock structure, or another fastening method.

[0051] The strike face insert of these embodiments can comprise any one or layered combination of the following: aluminum, stainless steel, copper, thermoplastic co-polyester elastomer (TPC), thermoplastic elastomer (TPE), thermoplastic urethane (TPU), steel, nickel, TPU/aluminum, TPE/aluminum, plastic/metal screen insert, polyethylene, polypropylene, polytetrafluoroethylene, polyisobutylene, polyvinyl chloride, PEBAX®, or any other desired material. PEBAX® is a polyether block amide that is a thermoplastic elastomer made of a flexible polyether and rigid polyamide. The rigid polyamide can comprise Nylon. The PEBAX® can comprise different compounds that correspond to different Shore D hardness values, polyether percentages, and/or polyamide percentages. In many embodiments, the PEBAX® can comprise a PEBAX® 4033 (Arkema, Paris

France) or a PEBAX® 6333 (Arkema, Paris France). The PEBAX® 4033 (Arkema, Paris France) comprises a tetramethylene oxide (53% wt) and a Nylon 12. The PEBAX® 6333 (Arkema, Paris France) comprises a Nylon 11. In some embodiments, the face insert can comprise a material such as steel, steel alloys, tungsten, tungsten alloys, aluminum, aluminum alloys, titanium, titanium alloys, vanadium, vanadium alloys, chromium, chromium alloys, cobalt, cobalt alloys, nickel, nickel alloys, other metals, other metal alloys, composite polymer materials or any combination thereof.

[0052] The PEBAX® can comprise a percentage of polyether by volume. In some embodiments, the PEBAX® can comprise 0% to 10%, 10% to 20%, 15% to 30%, 20% to 30%, 30% to 40%, 30% to 50%, 30% to 60%, 40% to 50%, 40% to 60%, 50% to 60%, or 60% to 70% polyether by volume. For example, the PEBAX® can comprise 0%, 5%, 10%, 15%, 20%, 25%, 30%, 35%, 40%, 45%, 50%, 55%, 60%, 65%, or 70% of polyether by volume. In some embodiments, the PEBAX® can comprise 0% to 10%, 10% to 20%, 15% to 30%, 20% to 30%, 30% to 40%, 40% to 50%, 40% to 60%, 50% to 60%, or 60% to 70% of polyamide by volume. For example, the PEBAX® can comprise 0%, 5%, 10%, 15%, 20%, 25%, 30%, 35%, 40%, 45%, 50%, 55%, 60%, 65%, or 70% of polyamide by volume. As the percentage of polyether percentage increases, the hardness of the PEBAX® decreases. As the percentage of polyamide percentage increases, the hardness of the PEBAX® increases. For example, the PEBAX® 4033 (Arkema, Paris France) can comprise 40% to 60% polyether by volume and 15% to 30% polyamide by volume. For example, the PEBAX® 6333 (Arkema, Paris France) can comprise 15% to 30% polyether by volume and 40% to 60% polyamide by volume.

[0053] In many embodiments, the PEBAX® can comprise a hardness ranging from Shore 25D to Shore 75D. In some embodiments, the hardness of the PEBAX can range from Shore 25D to Shore 35D, Shore 35D to Shore 45D, Shore 36D to Shore 44D, Shore 38D to Shore 42D, Shore 45D to Shore 55D, Shore 55D to Shore 65D, Shore 56D to Shore 64D, Shore 60D to Shore 65D, or Shore 65D to Shore 75D. For example, the hardness of the PEBAX can be Shore D 25, 30, 35, 40, 45, 50, 55, 60, 65, or 70.

[0054] In many embodiments, the PEBAX® 4033 (Arkema, Paris France) can comprise a lower hardness than the PEBAX® 6333 (Arkema, Paris France). In many embodiments, the PEBAX® 4033 (Arkema, Paris France) can comprise a hardness range of Shore 35D to Shore 55D. In some embodiments, the PEBAX® 4033 (Arkema, Paris France) can comprise a hardness range of Shore 38D to Shore 42D, or Shore 39D to Shore 41D. For example, the PEBAX® 4033 (Arkema, Paris France) can be comprise a Shore D hardness of 40. In many embodiments, the PEBAX® 6333 (Arkema, Paris France) can comprise a hardness range of Shore 50D to Shore 75D. In some embodiments, the PEBAX® 6333 (Arkema, Paris France) can comprise a hardness range of Shore 55D to Shore 70D, or Shore 60D to Shore 65D. For example, the PEBAX® 6333 (Arkema, Paris France) can comprise a Shore D hardness of 63.

[0055] In some embodiments, the face insert can comprise a two-component system. The two-component system can comprise a ball striking face plate and a face insert base. The ball striking face plate of the face insert can comprise a first insert material. The face insert base of the face insert can

comprise a second insert material. In many embodiments, the first insert material of the ball striking face plate and the second material of the face insert base can be different. In some embodiments, the first insert material of the ball striking face plate and the second insert material of the face insert base can be similar. In many embodiments, the first insert material of the ball striking face plate can comprise a polymer type material. In some embodiments, the first insert material of the ball striking face plate can comprise a metallic material. In many embodiments, the second insert material of the face insert base can comprise a polymer type material.

[0056] The first insert material can comprise a metal such as steel, steel alloys, tungsten, tungsten alloys, aluminum, aluminum alloys, titanium, titanium alloys, vanadium, vanadium alloys, chromium, chromium alloys, cobalt, cobalt alloys, nickel, nickel alloys, other metals, other metal alloys, composite polymer materials or any combination thereof.

[0057] The first insert material or the second insert material can comprise a polymer type material. The polymer type material can comprise polyethylene, polypropylene, polytetrafluoroethylene, polyisobutylene, polyvinyl chloride, or any other polymer type material. In many embodiments, the face insert can comprise a PEBAX®. More specifically, the PEBAX® is a polyether block amide that is a thermoplastic elastomer made of a flexible polyether and rigid polyamide. The rigid polyamide can comprise Nylon. The PEBAX® can comprise different compounds that correspond to different Shore D hardness values, polyether percentages, and/or polyamide percentages. In many embodiments, the PEBAX® can comprise a PEBAX® 4033 (Arkema, Paris France) or a PEBAX® 6333 (Arkema, Paris France). The PEBAX® 4033 (Arkema, Paris France) comprises a tetramethylene oxide (53% wt) and a Nylon 12. The PEBAX® 6333 (Arkema, Paris France) comprises a Nylon 11. The first insert material and the second insert material can comprise similar polyether percentages, polyamide percentages, or Shore D hardness values as described above.

[0058] The ball striking face plate of the face insert can comprise a thickness. In many embodiments, the thickness of the ball striking face plate can range from 0.015 to 0.115 inch. In some embodiments, the thickness of the ball striking face plate can range from 0.015 to 0.045 inch, 0.020 to 0.050 inch, 0.025 to 0.055 inch, 0.050 to 0.100 inch, 0.055 to 0.105 inch, 0.060 to 0.110, or 0.065 to 0.115 inch. In some embodiments, the thickness of the ball striking face plate can be at least 0.015, 0.020, 0.025, 0.030, 0.035, 0.040, 0.045, 0.050, 0.055, 0.060, 0.065, 0.070, 0.075, 0.080, 0.085, 0.090, 0.095, 0.10, 0.105, 0.110, or 0.115 inch. In some embodiments, the thickness of the ball striking face plate can be greater than or equal to 0.015, 0.020, 0.025, 0.030, 0.035, 0.040, 0.045, 0.050, 0.055, 0.060, 0.065, 0.070, 0.075, 0.080, 0.085, 0.090, 0.095, 0.10, 0.105, 0.110, or 0.115 inch. In some embodiments, the thickness of the ball striking face plate can be less than or equal to 0.015, 0.020, 0.025, 0.030, 0.035, 0.040, 0.045, 0.050, 0.055, 0.060, 0.065, 0.070, 0.075, 0.080, 0.085, 0.090, 0.095, 0.10, 0.105, 0.110, or 0.115 inch. For example, the thickness of the ball striking face plate can be 0.015, 0.020, 0.025, 0.030, 0.035, 0.040, 0.045, 0.050, 0.055, 0.060, 0.065, 0.070, 0.075, 0.080, 0.085, 0.090, 0.095, 0.10, 0.105, 0.110, or 0.115 inch.

[0059] In other embodiments, the thickness of the ball striking face plate can range from 0.115 to 0.40 inch. In some embodiments, the thickness of the ball striking face

plate can range from 0.115 to 0.20 inch, 0.15 to 0.30 inch, 0.20 to 0.30 inch, 0.25 to 0.35 inch, or 0.30 to 0.40 inch. In some embodiments, the thickness of the ball striking face plate can be at least 0.15, 0.20, 0.25, 0.30, 0.35, or 0.40 inch. In some embodiments, the thickness of the ball striking face plate can be greater than or equal to 0.15, 0.20, 0.25, 0.30, 0.35, or 0.40. In some embodiments, the thickness of the ball striking face plate can be less than or equal to 0.15, 0.20, 0.25, 0.30, 0.35, or 0.40 inch. For example, the thickness of the ball striking face plate can be 0.15, 0.20, 0.25, 0.30, 0.35, or 0.40 inch.

[0060] The face insert base of the face insert can comprise a thickness. In many embodiments, the thickness of the face insert base can range from 0.05 to 0.20 inch. In some embodiments, the thickness of the face insert base can range from 0.05 to 0.10 inch, or 0.10 to 0.20 inch. In some embodiments, the thickness of the face insert base can be at least 0.05, 0.10, 0.15, or 0.20 inch. In some embodiments, the thickness of the face insert base can be greater than or equal to 0.05, 0.10, 0.15, or 0.20 inch. In some embodiments, the thickness of the face insert base can be less than or equal to 0.05, 0.10, 0.15, or 0.20 inch. For example, the thickness of the face insert base can be 0.05, 0.10, 0.15, or 0.20 inch.

[0061] In other embodiments, the thickness of the face insert base can range from 0.20 to 0.80 inch. In some embodiments, the thickness of the face insert base can range from 0.20 to 0.50 inch, 0.30 to 0.60 inch, 0.40 to 0.70 inch, or 0.50 to 0.80 inch. In some embodiments, the thickness of the face insert base can range from 0.20 to 0.40 inch, 0.30 to 0.50 inch, 0.40 to 0.60 inch, 0.50 to 0.70 inch, or 0.60 to 0.80 inch. In some embodiments, the face insert base of the face insert can be at least 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, or 0.80 inch. In some embodiments, the face insert base of the face insert can be greater than or equal to 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, or 0.80 inch. In some embodiments, the face insert base of the face insert can be less than or equal to 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, or 0.80 inch. For example, the thickness of the face insert base can be 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, or 0.80 inch.

[0062] The face insert can be formed by a number of different processes. The different forming processes include the following: injection molding, casting, blow molding, compression molding, co-molding, laser forming, film insert molding, gas assist molding, rotational molding, thermoforming, laser cutting, 3-D printing, forging, stamping, electroforming, machining, molding, or any combination thereof. Further, the face insert can have any combination of hardness, volume, thickness, and forming processes described above.

[0063] In many embodiments, the upper portion of the putter-type golf club head having the first material comprises a first density ranging between 1.0 g/cc and 6.0 g/cc. The first density can range between 2.0 g/cc to 5.0 g/cc. In some embodiments, the first density can range between 1.0-1.25 g/cc, 1.25-1.5 g/cc, 1.5-1.75 g/cc, 1.75-2.0 g/cc, 2.0-2.25 g/cc, 2.25-2.5 g/cc, 2.5-2.75 g/cc, 2.75-3.0 g/cc, 3.25-3.5 g/cc, 3.5-3.75 g/cc, 3.75-4.0 g/cc, 4.0-4.25 g/cc, 4.25-4.5 g/cc, 4.5-4.75 g/cc, 4.75-5.0 g/cc, 5.0-5.25 g/cc, 5.0-5.25 g/cc, 5.25-5.5 g/cc, 5.5-5.75 g/cc, or 5.75-6.0 g/cc. In one embodiment, the first density of the lower portion can range between 2.0-3.0 g/cc. In some embodiments, the first

density can be less 6.0 g/cc, less than 5.0 g/cc, less than 4.0 g/cc, less than 3.0 g/cc, or less than 2.0 g/cc. In some embodiments, the first density can be 1.25 g/cc, 1.50 g/cc, 1.75 g/cc, 2.0 g/cc, 2.25 g/cc, 2.50 g/cc, 2.75 g/cc, 3.0 g/cc, 3.25 g/cc, 3.50 g/cc, 3.75 g/cc, 4.0 g/cc, 4.25 g/cc, 4.50 g/cc, 4.75 g/cc, 5.0 g/cc, 5.25 g/cc, 5.50 g/cc, 5.75 g/cc, or 6.0 g/cc.

[0064] In many embodiments, the lower portion of the putter-type golf club head having the second material. The second material can comprise a density. The density is a second density to the first density of the first material in the upper portion. The second density of the second material of the lower portion can range between 7.0 g/cc and 20.0 g/cc. In some embodiments, the second density can range between 7.0-7.5 g/cc, 7.5-8.0 g/cc, 8.0-8.5 g/cc, 8.5-9.0 g/cc, 9.0-9.5 g/cc, 9.5-10.0 g/cc, 10.0-10.5 g/cc, 10.5-11.0 g/cc, 11.0-11.5 g/cc, 11.5-12.0 g/cc, 12.0-12.5 g/cc, 12.5-13.0 g/cc, 13.0-13.5 g/cc, 13.5-14.0 g/cc, 14.0-14.5 g/cc, 14.5-15.0 g/cc, 15.0-15.5 g/cc, 15.5-16.0 g/cc, 16.0-16.5 g/cc, 16.5-17.0 g/cc, 17.0-17.5 g/cc, 17.5-18.0 g/cc, 18.0-18.5 g/cc, 18.5-19.0 g/cc, or 19.0-19.5 g/cc, or 19.5-20.0 g/cc. In one embodiment, the second density of the second material in the lower portion can range between 8.0-9.0 g/cc. In some embodiments, the second density can be 7.0 g/cc, 7.5 g/cc, 8.0 g/cc, 8.5 g/cc, 9.0 g/cc, 9.5 g/cc, 10.0 g/cc, 10.5 g/cc, 11.0 g/cc, 11.5 g/cc, 12.0 g/cc, 12.5 g/cc, 13.0 g/cc, 13.5 g/cc, 14.0 g/cc, 14.5 g/cc, 15.0 g/cc, 15.5 g/cc, 16.0 g/cc, 16.5 g/cc, 17.0 g/cc, 17.5 g/cc, 18.0 g/cc, 18.5 g/cc, 19.0 g/cc, 19.5 g/cc, or 20.0 g/cc. In some embodiments, the second density of the lower portion can be at least 2 times greater than the first density, at least 3 times greater than the first density, at least 4 times greater than the first density, or at least 5 times greater than the first density. In some embodiments, the second density can be greater than 7.0 g/cc, greater than 9.0 g/cc, greater than 10.0 g/cc, greater than 11.0 g/cc, or greater than 12.0 g/cc.

[0065] The upper portion of the putter-type golf club having the first material can be made from any one or combination of the following: 8620 alloy steel (7.83 g/cc), S25C steel (7.85 g/cc), carbon steel (7.85 g/cc), maraging steel (8.00 g/cc), 17-4 stainless steel (7.81 g/cc), 303 stainless steel (8.03 g/cc), 304 stainless steel (8.00 g/cc), stainless steel alloy (7.75 g/cc-8.05 g/cc), tungsten (19.25 g/cc), aluminum (2.70 g/cc), aluminum alloy (2.64 g/cc-2.81 g/cc), ADC-12 (2.75 g/cc), or any metal suitable for creating a golf club head. In many embodiments, the upper portion is made of aluminum alloy or ADC-12.

[0066] The lower portion of the putter-type golf club having the second material can be made from any one or combination of the following: 8620 alloy steel (7.83 g/cc), S25C steel (7.85 g/cc), carbon steel (7.85 g/cc), maraging steel (8.00 g/cc), 17-4 stainless steel (7.81 g/cc), 303 stainless steel (8.03 g/cc), 304 stainless steel (8.00 g/cc), stainless steel alloy (7.75 g/cc-8.05 g/cc), tungsten (19.25 g/cc), aluminum (2.70 g/cc), aluminum alloy (2.64 g/cc-2.81 g/cc), ADC-12 (2.75 g/cc), or any metal suitable for creating a golf club head. In many embodiments, the lower portion is made of 304 stainless steel, 8620 alloy steel, 17-4 stainless steel, or 1380 stainless steel. However, the lower and upper portion are not made from the same one material or the same combination of materials.

[0067] Furthermore, the upper and lower portion of the putter-type golf club head can be joined in any one or combination of the following methods: welding, soldering,

brazing, swedging, adhesion, epoxy, or mechanical fastening. In some embodiments, the upper and lower portion can be joined by adhesion with epoxy, polyurethanes, resins, hot melts, or any other adhesive.

A. Benefits

[0068] The putter-type golf club head provides MOI, CG, feel, and weighting benefits, in a putter-type golf club head with an upper and lower portion having different densities and/or without using mechanically fastened weights or weight ports. By creating an upper portion and lower portion of a putter-type golf club head from two different material, the weighting of the club head shifts towards the peripheries of the putter-type golf club head, without any weight ports or attachments to the heel end and toe end of the putter-type golf club head. This shift in weight, towards the peripheries of the putter-type golf club head, raises the MOI of the club head about the y-axis (I_{yy}), therefore preventing the rotation about the y-axis and assuring the strike face is square to a golf ball during impact. The increase in MOI about the y-axis helps achieve a straighter ball path and improve the outcome of off-centered hits (impact at the heel end or toe end).

[0069] By creating the putter-type golf club head from two portions of two different materials, the putter-type golf club head can be optimized to improve the MOI, while keeping the golf club head at a desirable overall weight. In some embodiments, the moment of inertia of the golf club head about the y-axis center of gravity is between 3500 g·cm²-6500 g·in². In other embodiments the moment of inertia of the golf club head about the y-axis center of gravity can be between 3500 g·cm²-4000 g·cm², 4000 g·cm²-4500 g·cm², 4500 g·cm²-5000 g·cm², 5000 g·cm²-5500 g·cm², 5500 g·cm²-6000 g·cm², or 6000 g·cm²-6500 g·cm².

[0070] The putter-type golf club head with upper and lower portions of two different materials, increases the MOI about the y-axis center of gravity by at least 30% over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single material such as a steel putter or a putter investment cast of a single material). In some embodiments, the putter-type golf club head with upper and lower portions of two different materials, increases the MOI about the y-axis center of gravity by at least 35%, by at least 40%, by at least 45%, by at least 50%, by at least 55%, by at least 60%, by at least 65%, by at least 70%, by at least 75%, by at least 80%, by at least 85%, by at least 90%, by at least 95%, by at least 95%, by at least 100%, or by at least 105%, over a putter with the same volume, mass, and single material construction.

II. EMBODIMENTS

a. Blade Embodiment

[0071] In one embodiment, the putter-type golf club head can be a blade type putter head **100**. Referring to FIGS. 1A and 1B, the blade type putter head **100** has an upper portion **104** and a lower portion **108**. The upper portion **104** is made from a first material having a first density and the lower portion **108** is made from a second material having a second density. The first density is less than the second density. The upper portion **104** and lower portion **108** combine to create a balanced putter head **100**, while maintaining a desirable volume and mass.

[0072] The lower portion 108 comprises a toe end 124, a heel end 128 opposite the toe end 124, a rear wall 132 opposite a front surface 112, a rear portion 156, and an under surface (not shown). The under surface and the upper portion 104 form a sole 168. The rear wall 132 is opposite and approximately parallel to the front surface 112. The toe end 124 is opposite the heel end 128, while adjacent to the strike face 112 and the rear portion 156. The rear portion 156 spans from the heel end 128 to the toe end 124, while also extending away from the rear wall 132 and the front surface face 112. The rear portion 156 is adjacent the sole. The under surface spans from the heel end 128 to the toe end 124 and is adjacent the rear portion 156 and the front surface 112.

[0073] Further, the toe end 124, heel end 128, and front surface 112 of the lower portion 108 forms a recess 140, wherein the recess extends inwards from the front surface 112, towards the rear wall 132. The recess functions to receive the upper portion 104. In most embodiments, the recess 140 comprises a corresponding geometry similar or identical to that of the upper portion 104. When the upper portion 104 is affixed to the lower portion 108, the upper portion 104 encompasses and mates with the lower portion 108 to fit within the recess 140.

[0074] The lower portion 108 of the blade type putter head 100 can further comprise an alignment feature 136. The alignment feature 136 can be any one or combination of the following: a line, a circle, a dashed line, a triangle, a channel, or any other desired alignment feature 136. Referring to FIGS. 2A-2C, in some embodiments, the blade type putter head 200 can comprise an alignment feature 236 on the upper portion 204, rather than the lower portion 208.

[0075] The upper portion 104 of the blade type putter 100 head comprises a hitting surface 113 and an adhesion surface 115. The hitting surface 113 comprises an upper edge 116 and a lower edge 121, wherein the upper edge 116 is further from a ground plane 172 than the lower edge 116. The ground plane 172 is tangent to the lower portion 108, when the putter head is at an address position to strike a golf ball. The upper edge 116 is adjacent the hitting surface 113 and the adhesion surface 115, while opposite the lower edge 121. In most embodiments, the hitting surface 113 and adhesion surface 115 are parallel, however in other embodiments, the hitting surface 113 and adhesion surface 115 are not parallel.

[0076] When the upper portion 104 and lower portion 108 are joined, the adhesion surface 115 is affixed to the recess 140 of the lower portion 108. The hitting surface 113 of the upper portion 104, and the front surface 112 of the lower surface, align to form a strike face 120, that will function to hit strike golf ball.

[0077] The lower edge 121 of the upper portion 104, and under surface of the lower portion 108 combine to create the sole 168. The sole 168 is perpendicular to the ground plane 172, wherein the ground plane 172 is tangent to the sole 168, when the putter 100 is at an address position to strike a golf ball. The sole 168 of the putter 100 extends from the toe end 124 of the putter head 100 to the heel end 128 of the putter head 100.

[0078] Referring to FIG. 1C, in most embodiments, the sole 168 of the putter head 100 can be perfectly flat. In some embodiments, the sole 168 of the putter head 100 can have a slight arch in a heel 128 to toe 124 direction, wherein the slight arch can be linear, or a function of a polynomial. In some embodiments, the sole 168 of the putter head 100 can have a strong arch in the heel 128 to toe 124 direction,

wherein the strong arch can be linear, or a function of a polynomial. The sole 168 functions to provide a surface to rest the putter head 100 on the ground plane 172.

[0079] The strike face 120 of the blade type putter head 100 comprises a strike face center point 176 and a loft plane 180. The strike face center point 176 is equidistant from the lower edge 120 and upper edge 116 of the strike face 120, as well as equidistant from the heel end 128 and toe end 124 of the blade type putter head 100. The loft plane 180 is tangent to the strike face 112 of the blade type putter head 100. Further, a midplane 184 intersects the strike face center point 176 and is perpendicular to the loft plane 180. Furthermore, a y-axis 188 intersects the strike face center point 176 and is perpendicular to the ground plane 172.

[0080] In some embodiments, when the lower portion 108 and the upper portion 104 are joined, the upper edge 116 of the upper portion 104 can protrude in a direction away from the strike face 120, overlaying at least a portion of the rear wall 132 of the lower portion 108. Further, the lower edge 121 of the upper portion 104 can protrude in a direction away from the strike face 120, towards at least a portion of the under surface of the lower portion 108, thereby making up a portion of the sole 168. In these embodiments, the rear wall 132 of the lower portion 108 does not make up a portion of the sole 168.

[0081] The combination of the low density first material upper portion 104 with the high density second material lower portion 108, increases the MOI of the putter 100, over a putter of unitary, solid block construction. The two part construction (upper portion 104 and lower portion 108) of the putter 100, moves denser material towards the heel 128 and toe 124, while placing lighter material (the upper portion 104) near the center, thereby increasing the MOI of the putter 100, since more mass is further from the center of gravity. The denser material of the lower portion helps increase the MOI of the putter-type golf club head by shifting the weight of the putter head 100 towards the outer portions of the putter-type golf club head. A single material putter fails to allocate high density material to the periphery. In some embodiments, the putter-type golf club head 100 with upper 104 and lower portions 108 of two different materials, increases the MOI about the y-axis center of gravity by at least 15% over a putter with the same volume, mass, and single material construction.

b. Crescent Embodiment

[0082] In one embodiment, the putter-type golf club head can be a crescent-shaped putter head 300. Referring to FIG. 3A-3C, the crescent-shaped putter head 300 has an upper portion 304 and a lower portion 308. The upper portion 304 is made from a first material have a first density and the lower portion 308 is made from a second material having a second density. The first density is less than the second density. The upper portion 304 and lower portion 308 combine to create a balanced putter head 300, while maintaining a desirable volume and mass. The high density lower portion 308 and low density upper portion 304, place more mass near the peripheries of the putter head 300, thus increasing the MOI and stability over a putter with the same volume, mass, and single material construction.

[0083] As discussed above, the lower portion 308 is comprised of a high-density material (i.e., the second material). The lower portion 308 comprises a rear periphery 352, a toe end 312, a heel end 316, a strike face 320, a rear wall 332.

The upper portion **304** comprises a back edge **334**, a crown **342**, a front edge **370**, and an under surface (not shown). The under surface and the upper portion **304** form a sole **368**. The toe end **312** is opposite the heel end **316**. The toe end **312** and the heel end **316** of the lower portion **308** respectively comprise a toe side periphery **356** and a heel side periphery **360**. The strike face **320** spans from the toe end **312** to the heel end **316** and is opposite the rear wall **332**. The rear wall **332** is opposite, and approximately parallel to, the strike face **320**. The lower portion further comprises a heel side periphery **360**, a toe side periphery **356**, a front edge **348**, and an upper edge.

[0084] The front edge **348** is adjacent to the toe side periphery **356** and the heel side periphery **360**, and opposite to the rear periphery **352**. The toe side periphery **356** is adjacent to the front edge **348** and the rear periphery **352**, and opposite and to the heel side periphery **360**. The heel side periphery **360** is also adjacent to the front edge **348** and the rear periphery **352**, but opposite to the toe side periphery **356**.

[0085] In most embodiments, the toe side periphery **356** extends perpendicularly from the front edge **348**, towards the rear periphery **352**, such that a right angle (90° angle) is formed at the junction of the toe side periphery **356** and the front edge **348**. However, in other embodiments, the toe side periphery **356** can extend from the front edge **348** in any direction, such that any angle (0°-180°) can be formed at the junction of the toe side periphery **356** and the front edge **348**. Further, in most embodiments, the heel side periphery **360** extends perpendicularly from the front edge **348**, such that a right angle (90° angle) is formed at the junction of the heel side periphery **360** and the front edge **348**. However, in other embodiments, the heel side periphery **360** can extend from the front edge **348** in any direction, such that any angle (0°-180°) can be formed at the junction of the heel side periphery **360** and the front edge **348**.

[0086] The front edge **348**, rear periphery **352**, toe side periphery **356**, and heel side periphery **360** form an aperture **364**. The aperture **364** is bounded by the front edge **348**, rear periphery **352**, the toe side periphery **356**, and the heel side periphery **360**. The aperture **364** shifts a majority of the volume and mass of the putter to the extremities of the lower portion **308**. The aperture **364** can comprise any shape, however in one embodiment the aperture **364** is approximately rectangular. In other embodiments, the aperture **364** can be circular, curvilinear, triangular, trapezoidal, parabolic, golf ball shaped, square, or any other desired geometric shape.

[0087] The upper portion **304** of the putter head **300** comprises a crown **342**, a front edge **370**, and a back edge **334**. The crown **342** extends away from the front edge **370** to the back edge **334** of the upper portion **304**. The under surface is opposite the crown **342**, spanning from the front edge **348** to the back edge **334**.

[0088] In some embodiments, the heel side periphery **360** and toe side periphery **356** can be parallel, while in some embodiments, the heel side periphery **360** and toe side periphery **356** are not parallel. In some embodiments, the rear periphery **352** and front edge **348** can be parallel, while in some embodiments, the rear periphery **352** and front edge **348** are not parallel. The rear periphery **352** of the crescent-shaped putter head **300** is approximately crescent-shaped, and therefore, the rear periphery **352** and front edge **348** are not parallel. The rear periphery **352** can be curvilinear

spanning from the heel side periphery **360** to the toe side periphery **356**. The rear periphery **352** comprises a curve length measured along the rear periphery **352** from the junction between the heel side periphery **360** and the rear periphery **352** to the junction between the toe side periphery **356** and the rear periphery **352**. In some embodiments, the rear periphery **352** curve length can be between 4.5 inches and 6.5 inches. In some embodiments, the rear periphery curve length can be 4.5 inches-4.75 inches, 4.75 inches-5.0 inches, 5.0 inches-5.25 inches, 5.25 inches-5.5 inches, 5.5 inches-5.75 inches, 5.75 inches-6.0 inches, 6.0 inches-6.25 inches, or 6.25 inches-6.5 inches.

[0089] When the upper portion **304** and the lower portion **308** are joined, the crown **342** extends between the strike face **320** to the rear periphery **352**. The crown **342**, in most embodiments, spans approximately inward 25% of the total club head **300** width from the toe side periphery **356** and spans approximately inward 25% of the total club head **300** width from the heel side periphery **360**. In other embodiments, the crown **342** can, continuously or discontinuously, span the entire width of the total club head **300**, in a heel **316** to toe **312** direction. In some embodiments, the crown **342**, can span less than 90% of the total width of the club head **300**, less than 80% of the total width of the club head **300**, less than 70% of the total width of the club head **300**, less than 60% of the total width of the club head **300**, less than 50% of the total width of the club head **300**, less than 40% of the total width of the club head **300**, or less than 30% of the total width of the club head **300**. Further, in some embodiments, the crown **342** can be substantially flat from the strike face **320** to the back edge **334** or ascend from the strike face **320** to the back edge **334**. In most embodiments, the ascent or descent of the crown **342** can be linear, curvilinear, parabolic, sinusoidal, or a function of polynomial.

[0090] The crown **342** further comprises an alignment trough **355**, wherein the alignment trough **355** is equidistant from the heel end **316** and the toe end **312**. The alignment trough **355** is adjacent the rear wall **328** and approximately perpendicular to the strike face. The alignment trough **355** is bounded by the back edge **334**, the rear wall **332**, and the crown **342** on the heel end **316** and the toe end **312**. In most embodiments, the alignment trough is approximately the width of a golf ball (approximately 4.27 cm) to provide the viewer a visual alignment field that extends the width of the golf ball.

[0091] Furthermore, the upper portion **304** of the putter head **300** can comprise one or more alignment features **344** on the crown **342**. The alignment feature **344** can be any one or combination of the following: a line, a series of lines, milling troughs, a circle, a dashed line, a triangle, a channel, or any other desired alignment feature **344**. The alignment features **344** can be equally spaced on the entire crown **342**, a portion of the crown **342**, or the alignment trough **355**. The alignment features **344**, extending along the alignment trough **355**, function to provide the viewer a visual alignment field that extends the width of the golf ball, from the rear wall **332** to the back edge **334** of the putter **300**. The goal is to align the entire putter **300** with the golf ball using these alignment features **344** along the crown **342** and/or the alignment trough **355**.

[0092] Referring to FIG. 3C, the upper portion **304** can be affixed to the lower portion **308** such that the upper portion **304** is further from a ground plane than the lower portion

308, wherein the ground plane **372** is tangent to the lower portion **308**, when the putter head **300** is at an address position to strike a golf ball. As such, the upper portion **304** is spaced rearward from a loft plane **380**, described below. Particularly, putter head **300** can be configured such that the lower portion **308** does not reside along the loft plane, as illustrated in FIG. 3C.

[0093] Referring to FIG. 3C, the strike face **320** of the putter head **300** comprises a strike face center point **376** and a loft plane **380**. The strike face center point **376** is equidistant from the crown **342** and the under surface of the upper portion **304**, as well as equidistant from the heel end **316** and toe end **312** of the putter head **300**. The loft plane **380** is tangent to the strike face **320** of the putter head **300**. Further, a midplane **384** intersects the strike face center point **376** and is perpendicular to the loft plane **380**. Furthermore, referring to FIG. 3B, a y-axis **388** intersects the midplane **384**, and is perpendicular to the ground plane **372**.

[0094] When the upper portion **304** and lower portion **308** are joined such that the heel end **316** overlays at least a portion of the toe side periphery **356**. Further, when the upper portion **304** and lower portion **308** are joined such that the toe end **312** overlays at least a portion of the heel side periphery **360**. Further still, when the upper portion **304** and lower portion **308** are joined such that the strike face **320** overlays at least a portion of the front edge **316**. Finally, the upper portion **304** and lower portion **308** are joined such that the back edge **364** overlays at least a portion of the rear periphery **352**.

[0095] The front edge **348**, rear periphery **352**, toe side periphery **356**, and heel side periphery **360** of the lower portion **308**, combined with the upper portion **304**, create the sole **368**. The sole **368** is perpendicular to the ground plane **372**, wherein the ground plane **372** is tangent to the sole **368**, when the putter head **300** is at an address position to strike a golf ball. The sole **368** of the putter head **300** extends from the toe end **312** of the putter head **300** to the heel end **316** of the putter head **300**.

[0096] In most embodiments, the sole **368** of the putter head **300** can be perfectly flat. In some embodiments, the sole **368** of the putter head **300** can have a slight arch in a heel **324** to toe **320** direction, wherein the slight arch can be linear, or a function of a polynomial. In some embodiments, the sole **368** of the putter head **300** can have a strong arch in the heel **324** to toe **320** direction, wherein the strong arch can be linear, or a function of a polynomial. The sole **368** functions to provide a surface to rest the putter head **300** on the ground plane **372**.

[0097] Referring to FIG. 3A, in one embodiment, the lower portion **308** can further comprise a toe mass **341** and a heel mass **343**. The toe mass **341** and heel mass **343** are integral to the lower portion **308** and are in contact with the toe side periphery **356** and heel side periphery **360**, respectively. The toe mass **341** and heel mass **343** extend from the lower portion **308**, in a direction away from the ground plane **372**, and toward the upper portion **304**. The toe mass **341** and heel mass **343** provide a means to position and align the upper portion **304** with the lower portion **308** of the putter head **300**.

[0098] Furthermore, the toe mass **341** and heel mass **343** provide an additional means of adding weight to the perimeters for increasing the MOI of the crescent-shaped putter head **300** when compared with putters without these mass features. These mass features can have weights that range

from 2-5 grams, 3-7 grams or 1-6 grams. The mass features can have all the same weight or be different weight within the ranges provided above. The weight of the mass features can be 1 gram, 2 grams, 3 grams, 4 grams, 5 grams, 6 grams, or 7 grams. The toe mass **341** and a heel mass **343** can respectively be any one or combination of the following shapes: rectangular, triangular, pyramidal, spherical, crescent-shaped, square, cylindrical, ovalar, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0099] Referring to FIG. 3A, the toe mass **341** and heel mass **343** can be positioned away from the rear periphery **352**, wherein the toe mass **341** and heel mass **343** do not touch or intersect with the rear periphery **352**. However, in other embodiments, the toe mass **341** and heel mass **343**, can be positioned on the rear periphery **352**, wherein the toe mass **341** and heel mass **343** are integral to and intersect the rear periphery **352**.

[0100] In one embodiment, the toe mass **341** is positioned on the front edge **348**, at the junction of the toe side periphery **356** and the front edge **348**, however in other embodiments the toe mass **341** can be positioned anywhere along the toe side periphery **356**. In one embodiment, the heel mass **343**, is positioned on the front edge **348**, at the junction of the heel side periphery **360** and the front edge **348**, however in other embodiments the heel mass **343** can be positioned anywhere along the heel side periphery **360**.

[0101] The toe mass **341** and heel mass **343** provide areas of concentrated mass, such that the toe mass **341** and heel mass **343** function to increase the moment of inertia of the putter head **300**. The placement of the toe mass **341** and the heel mass **343** on or near the front edge **316** and on or near the toe side periphery **356** and heel side periphery **360**, respectively, increases the MOI since the toe mass **341** and the heel mass **343** are farther from a center of gravity of the putter **300**. The toe mass **341** and the heel mass **343** can be integrally formed from the second material, wherein the second material is denser than the first material.

[0102] The toe mass **341** and heel mass **343** offer dual functionalities, such that the toe mass **341** and heel mass **343** function not only to increase the MOI of the putter **300** but provide additional surfaces for the upper portion **304** to join to the lower portion **308**. Therefore, the toe mass **341** can also be referred to as a front toe adhesion portion **341** and the heel mass **343** can also be referred to as a front heel adhesion portion **343**.

[0103] In some embodiments, the under surface, crown **342**, front edge **370**, and back edge **334** of the upper portion **304**, can form a first cavity (not shown). The first cavity extends inwards from the under surface, on the toe end **312**, towards the crown **342** but does not reach the crown **342**. The first cavity is bounded by the back edge **334**, the crown **342**, and the front edge **370**. The first cavity functions to receive the toe mass **341** of the lower portion **308**.

[0104] In some embodiments, the under surface, crown **342**, front edge **370**, and back edge **334** of the upper portion **304**, can form a second cavity (not shown). The second cavity extends inwards from the under surface, on the heel end **316**, towards the crown **342** but does not reach the crown **342**. The second cavity is bounded by the back edge **334**, the crown **342**, and the front edge **370**. The second cavity functions to receive the heel mass **343** of the lower portion **308**.

[0105] The first and second cavities can comprise any desired geometry. However, in most embodiments, the first and second cavity comprise a geometry similar or identical to that of the corresponding toe mass 341 or the heel mass 343. Further, when the upper portion 304 is affixed to the lower portion 308, the first cavity is positioned such that the first cavity encompasses the toe mass 341, and the second cavity is positioned such that the second cavity encompasses the heel mass 343.

[0106] The combination of the low density first material upper portion 304 with the high density second material lower portion 308, creates a high MOI putter 300, without creating an extremely heavy putter. The large aperture 364 formed by the rear wall 332, the rear periphery 352, the toe side periphery 356, and the heel side periphery 360 of the lower portion 308 forms a dense, yet low volume portion that increases the MOI of the putter, in comparison to a putter milled from a single material. A single material putter fails to allocate high density material to the periphery, while maintaining a desirable volume (50 cc-75 cc) and mass (340 grams-385 grams).

[0107] The lower portion 308, in most embodiments, comprises less than 38% of a volume of the putter 300. In some embodiments, the lower portion 308 comprises less than 37% of the total volume of the putter 300, less than 36% of the total volume of the putter 300, less than 35% of the total volume of the putter 300, less than 34% of the total volume of the putter 300, less than 33% of the total volume of the putter 300, less than 32% of the total volume of the putter 300, less than 31% of the total volume of the putter 300, less than 30% of the total volume of the putter 300, less than 29% of the total volume of the putter 300, less than 28% of the total volume of the putter 300, or less than 27% of the total volume of the putter 300.

[0108] Although the lower portion 308 comprises less than half of the volume of the putter 300, the lower portion 308 comprises at least 45% of an overall mass of the putter 300. In some embodiments, the lower portion 308 comprises at least 46% of the mass of the putter 300, at least 46% of the mass of the putter 300, at least 47% of the mass of the putter 300, at least 48% of the mass of the putter 300, at least 49% of the mass of the putter 300, at least 50% of the mass of the putter 300, at least 51% of the mass of the putter 300, at least 52% of the mass of the putter 300, at least 53% of the mass of the putter 300, at least 54% of the mass of the putter 300, or at least 55% of the overall mass of the putter 300.

[0109] The beneficial shift of mass to the periphery of the putter head 300 increases the MOI of the putter 300, over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single stainless steel block, or a putter investment cast of a single material).

c. Semi-Circular Embodiment

[0110] In one embodiment, the putter-type golf club head can be a semi-circular shaped putter head 400. Referring to FIG. 4A-4C, the semi-circular putter head 400 has an upper portion 404 and a lower portion 408. The upper portion 404 is made from a first material have a first density and the lower portion 408 is made from a second material having a second density. The first density is less than the second density. The upper portion 404 and lower portion 408 combine to create a high-MOI putter head 400 (5000 g-cm²-6500 g-cm²), while maintaining a desirable volume and mass.

[0111] As discussed above, the lower portion 408 is comprised of a high-density material (i.e., the second material). The lower portion 408 comprises a front edge 448, a rear periphery 452, a toe side span 456, and a heel side span 460. The lower portion 408 and an under surface of the top portion 404 combine to create a sole 468. The front edge 448 is adjacent to the toe side span 456 and the heel side span 460, and opposite to the rear periphery 452. The toe side span 456 is adjacent to the front edge 448 and the rear periphery 452, and opposite and to the heel side span 460. The heel side span 460 is also adjacent to the front edge 448 and the rear periphery 452, but opposite to the toe side span 456. The toe side span 456 and heel side span 460, extend beyond the rear periphery 448 of the upper portion 404. In some embodiments, the heel side span 460 and toe side span 456 can be parallel, while in some embodiments, the heel side span 460 and toe side span 456 are not parallel. In some embodiments, the rear periphery 452 and front edge 448 can be parallel, while in some embodiments, the rear periphery 452 and front edge 448 are not parallel. In this embodiment, the rear periphery 452 is approximately semi-circular, thus the rear periphery 452 and front edge 448 are not parallel.

[0112] In most embodiments, the toe side span 456 extends perpendicularly from the front edge 448, such that a right angle (90° angle) is formed at the junction of the toe side span 456 and the front edge 448. However, in other embodiments, the toe side span 456 can extend from the front edge 448 in any direction, such that any angle (0°-180°) can be formed at the junction of the toe side span 456 and the front edge 448. Further, in most embodiments, the heel side span 460 extends perpendicularly from the front edge 448, such that a right angle (90° angle) is formed at the junction of the heel side span 460 and the front edge 448. However, in other embodiments, the heel side span 460 can extend from the front edge 448 in any direction, such that any angle (0°-180°) can be formed at the junction of the heel side span 460 and the front edge 448.

[0113] The front edge 448, toe side span 456, and heel side span 460 form a gap 464. The gap 464 is bounded by the front edge 448, the toe side span 456, and the heel side span 460. The gap 464 formed by the front edge 448, the toe side span 456, and the heel side span 460 shifts a majority of the volume and mass of the putter to the extremities of the lower portion 408. The gap 464 can comprise any shape, however in one embodiment the gap is approximately rectangular. In other embodiments, the gap 464 can be circular, curvilinear, triangular, trapezoidal, parabolic, golf ball shaped, square, or any other desired geometric shape.

[0114] The upper portion 404 of the putter head 400 comprises a toe end 412, a heel end 416, a strike face 420, a rear wall 432, a back edge 434, a crown 442, and an under surface (not pictured). The toe end 412 is opposite the heel end 416. The strike face 420 spans from the toe end 412 to the heel end 416 and is opposite the rear wall 432. The rear wall 432 is opposite, and approximately parallel to the strike face 420. The crown 442 extends away from the strike face 420 to the back edge 434 of the upper portion 404. Furthermore, the under surface is opposite the crown 442, spanning from the strike face 420 to the back edge 434.

[0115] The crown 442 further descends from the strike face 420 to the back edge 434. Additionally, the crown 442 extends away from the strike face 420, over the front edge 448 of lower portion 408, and to the back edge 434 of the upper portion 404. The crown 442, in most embodiments,

spans approximately inward 25% of the total club head 400 width from the toe side span 456 and spans approximately inward 25% of the total club head 400 width from the heel side span 460. In other embodiments, the crown 442 can, continuously or discontinuously, span the entire width of the total club head 400, in a heel to toe direction. In some embodiments, the crown 442, can span less than 90% of the total width of the club head 400, less than 90% of the total width of the club head 400, less than 80% of the total width of the club head 400, less than 70% of the total width of the club head 400, less than 60% of the total width of the club head 400, less than 50% of the total width of the club head 400, less than 40% of the total width of the club head 400, or less than 30% of the total width of the club head 400. Further, in some embodiments, the crown 442 can be substantially flat from the strike face 420 to the back edge 434 or ascend from the strike face 420 to the back edge 434. In most embodiments, the ascent or descent of the crown 442 can be linear, curvilinear, parabolic, sinusoidal, or a function of polynomial.

[0116] The crown 442 further comprises an alignment trough 455, wherein the alignment trough 455 is equidistant from the heel end 416 and the toe end 412. The alignment trough 455 is adjacent the rear wall 432 and approximately perpendicular to the strike face 420. The alignment trough 455 is bounded by the back edge 434, the rear wall 432, and the crown 442 on the heel end 416 and the toe end 412. In most embodiments, the alignment trough 455 is approximately the width of a golf ball (approximately 4.27 cm) to provide the viewer a visual alignment field that extends the width of the golf ball.

[0117] Furthermore, the upper portion 404 of the putter head 400 can comprise one or more alignment features 444 on the crown 442. The alignment feature 444 can be any one or combination of the following: a line, a series of lines, milling troughs, a circle, a dashed line, a triangle, a channel, or any other desired alignment feature 444. The alignment features 444 can be equally spaced on the entire crown 442, a portion of the crown 442, or the alignment trough 455. The alignment features 444, extending along the alignment trough 455, function to provide the viewer a visual alignment field that extends the width of the golf ball, from the rear wall 432 to the back edge 434 of the putter 400. The goal is to align the entire putter 400 with the golf ball using these alignment features 444 along the crown 442 and/or the alignment trough 455.

[0118] Referring to FIG. 4C, the upper portion 404 is affixed to the lower portion 408 such that the upper portion 404 is further from a ground plane 472 than the lower portion 408, wherein the ground plane 472 is tangent to the lower portion 404, when the putter head 400 is at an address position to strike a golf ball.

[0119] Further, the strike face 420 of the putter head 400 comprises a strike face center point 476 and a loft plane 480. The strike face center point 476 is equidistant from the crown 442 and the undersurface of the upper portion 404, as well as equidistant from the heel end 416 and toe end 412 of the putter head 400. The loft plane 480 is tangent to the strike face 420 of the putter head 400. Further, a midplane 484 intersects the strike face center point 476 and is perpendicular to the loft plane 480. Furthermore, a y-axis 488 intersects the midplane 484, and is perpendicular to the ground plane 472.

[0120] When the upper portion 404 and lower portion 408 are joined such that the heel end 416 overlays at least a portion of the toe side span 456. Further, when the upper portion 404 and lower portion 408 are joined such that the toe end 412 overlays at least a portion of the heel side span 460. Further still, when the upper portion 404 and lower portion 408 are joined such that the strike face 420 overlays at least a portion of the front edge 448. Finally, the upper portion 404 and lower portion 408 are joined such that the back edge 434 overlays at least a portion of the rear periphery 452.

[0121] The rear periphery 452 can be curvilinear spanning from the heel side 416 to the toe side 416. The rear periphery 452 comprises a curve length measured along the rear periphery 452 from the junction between the heel side 416 and the rear periphery 452 to the junction between the toe side 416 and the rear periphery 452. In some embodiments, the rear periphery 452 curve length can be between 4.5 inches and 8.0 inches. In some embodiments, the rear periphery 452 curve length can be 4.5 inches-4.75 inches, 4.75 inches-5.0 inches, 5.0 inches-5.25 inches, 5.25 inches-5.5 inches, 5.5 inches-5.75 inches, 5.75 inches-6.0 inches, 6.0 inches-6.25 inches, 6.25 inches-6.5 inches, 6.5 inches-6.75 inches, 6.75 inches-7.0 inches, 7.25 inches-7.50 inches, 7.50 inches-7.75 inches, or 7.75 inches-8.0 inches.

[0122] The front edge 448, rear periphery 452, toe side span 456, and heel side span 460 of the lower portion 408, combined with the upper portion 404, create the sole 468. The sole 468 is perpendicular to the ground plane 472, wherein the ground plane 472 is tangent to the sole 468, when the putter head 400 is at an address position to strike a golf ball. The sole 468 of the putter head 400 extends from the toe end 412 of the putter head 400 to the heel end 416 of the putter head 400.

[0123] In most embodiments, the sole 468 of the putter head 400 can be perfectly flat. In some embodiments, the sole 468 of the putter head 400 can have a slight arch in a heel 416 to toe 412 direction, wherein the slight arch can be linear, or a function of a polynomial. In some embodiments, the sole 468 of the putter head 400 can have a strong arch in the heel 416 to toe 412 direction, wherein the strong arch can be linear, or a function of a polynomial. The sole 468 functions to provide a surface to rest the putter head 400 on the ground plane 472.

[0124] Referring to FIG. 4A, in one embodiment, the lower portion 408 can further comprise a front toe mass 441 and a front heel mass 443. The front toe mass 441, front heel mass 443 are integral to the lower portion 408. The front toe mass 441 and front heel mass 443 extend from the lower portion 408, in a direction away from the ground plane 472, and toward the upper portion 404. These mass portions provide a means to position and align the upper portion 404 with the lower portion 408 of the putter head 400. Furthermore, these mass portions (i.e., the front toe mass 441 and front heel mass 443) provide an additional means of adding weight to the perimeters for increasing the MOI of the putter 400 over putters without these mass features. These mass features can have weight that range from 2-5 grams, 3-7 grams or 1-6 grams. The mass features can have all the same weight or be different weight within the ranges provided above. The mass features can be 1 gram, 2 grams, 3 grams, 4 grams, 5 grams, 6 grams, or 7 grams. The front toe mass 441 and a front heel mass 443 can respectively be any one or combination of the following shapes: rectangular, trian-

gular, pyramidal, spherical, semi-circular, square, cylindrical, ovalar, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0125] In FIG. 4A, the front toe mass 441 and front heel mass 443 are positioned away from the rear periphery 452, wherein the front toe mass 441 and front heel mass 443 do not touch or intersect with the rear periphery 452. However, referring to FIG. 5A-5C, an alternate semi-circular shaped putter 500 is illustrated below. Putter 500 comprises the same features as putter 400, however the front toe mass 541 and front heel mass 543 of putter 500, are positioned on the rear periphery 552, wherein the front toe mass 541 and front heel mass 53 are integral to and intersect the rear periphery 452.

[0126] In one embodiment, the front toe mass 441 is positioned on the front edge 448, at the junction of the toe side span 456 and the front edge 448, however in other embodiments the front toe mass 441 can be positioned anywhere along the toe side span 456. In one embodiment, the front heel mass 443, is positioned on the front edge 448, at the junction of the heel side span 460 and the front edge 448, however in other embodiments the front heel mass 443 can be positioned anywhere along the heel side span 460.

[0127] The front toe mass 441 and front heel mass 443 provide areas of concentrated mass, such that each mass 441, 443 function to increase the moment of inertia of the putter head 400. The placement of each mass 441, 443 on the front edge 448 and spans 456, 460 increases the MOI since each mass 441, 443 since each mass is farther from a center of gravity of the putter 400. Each mass 441, 443 on the periphery 448 and spans 456, 460 is integrally formed from the second material, wherein the second material is denser than the first material.

[0128] The front toe mass 441 and front heel mass 443 offer dual functionalities, such that the front toe mass 441 and front heel mass 443 function not only to increase the MOI of the putter 400 but provide additional surfaces for the upper portion 404 to join to the lower portion 408. Therefore, the front toe mass 441 can also be referred to as a front toe adhesion portion 441 and the front heel mass 443 can also be referred to as a front heel adhesion portion 443.

[0129] In some embodiments, the under surface, strike face 420, and rear wall 432 of the upper portion 408, can form a first cavity (not shown). The first cavity extends inwards from the under surface, on the toe end 412, towards the crown 442 but does not reach the crown 442. The first cavity is bounded by the rear wall 432, the strike face 420, and the toe 412. The first cavity functions to receive the front toe mass 441 of the lower portion 408.

[0130] In some embodiments, the under surface, strike face 420, and rear wall 432 of the upper portion 408, can form a second cavity (not shown). The second cavity extends inwards from the under surface, on the heel end 416, towards the crown 442 but does not reach the crown 442. The second cavity is bounded by the rear wall 432, the strike face 420, and the heel 416. The second cavity functions to receive the front heel mass 443 of the lower portion 408.

[0131] The first and second cavity can comprise any desired geometry, however in most embodiments, the first and second cavity comprise a geometry similar or identical to that of the front toe mass 441 and the front heel mass 443. Further, when the upper portion 704 is affixed to the lower portion 408, the first cavity is positioned such that the first

cavity encompasses the front toe mass 441, and the second cavity is positioned such that the second cavity encompasses the front heel mass 443.

[0132] The combination of the low density first material upper portion 404 with the high density second material lower portion 408, creates a high MOI putter 400, without creating an extremely heavy putter. The large gap 464 formed by the rear periphery 452 and the spans 456, 460 of the lower portion 408 forms a dense, yet low volume portion that increases the MOI of the putter, in comparison to a putter milled from a single material. A single material putter fails to allocate high density material to the periphery, while maintaining a desirable volume (75 cc-100 cc) and mass (340 grams-385 grams).

[0133] The lower portion 408, in most embodiments, comprises less than 38% of a volume of the putter 400. In some embodiments, the lower portion 408 comprises less than 37% of the total volume of the putter 400, less than 36% of the total volume of the putter 400, less than 35% of the total volume of the putter 400, less than 34% of the total volume of the putter 400, less than 33% of the total volume of the putter 400, less than 32% of the total volume of the putter 400, less than 31% of the total volume of the putter 400, less than 30% of the total volume of the putter 400, less than 29% of the total volume of the putter 400, less than 28% of the total volume of the putter 400, or less than 27% of the total volume of the putter 400.

[0134] Although the lower portion 408 comprises less than half of the volume of the putter 400, the lower portion 408 comprises at least 45% of an overall mass of the putter 400. In some embodiments, the lower portion 408 comprises at least 46% of the mass of the putter 400, at least 46% of the mass of the putter 400, at least 47% of the mass of the putter 400, at least 48% of the mass of the putter 400, at least 49% of the mass of the putter 400, at least 50% of the mass of the putter 400, at least 51% of the mass of the putter 400, at least 52% of the mass of the putter 400, at least 53% of the mass of the putter 400, at least 54% of the mass of the putter 400, or at least 55% of the mass of the putter 400.

[0135] The beneficial shift of mass to the periphery of the putter head 400, through the use of a high density, low volume lower portion 408, increases the MOI of the putter 400, over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single stainless steel block, or a putter investment cast of a single material).

d. Winged Embodiment

[0136] In one embodiment, the putter-type golf club head can be a winged shaped putter head with periphery spans 600. Referring to FIGS. 6A and 6B, the winged shaped putter head 600 has an upper portion 604 and a lower portion 608. The upper portion 604 is made from a first material having a first density and the lower portion 608 is made from a second material having a second density. The first density is less than the second density. The upper portion 604 and lower portion 608 combine to create a high-MOI putter head 600 ($5000 \text{ g}\cdot\text{cm}^2$ - $6500 \text{ g}\cdot\text{cm}^2$), while maintaining a desirable volume and mass.

[0137] As discussed above, the lower portion 608 is comprised of a high-density material (i.e., the second material). The lower portion 608 comprises a front periphery 648, a sole 668, a rear periphery 652, a toe side wing 656, and a heel side wing 660. As discussed below, FIG. 6C, the front

periphery 648, rear periphery 652, toe side wing 656, and heel side wing 660 of the lower portion 608, combined with the upper portion 604, create a sole 668. The front periphery 648 is adjacent to the toe side periphery 656 and the heel side periphery 660, and opposite to the rear periphery 652. The toe side wing 656 is adjacent to the front periphery 648 and the rear periphery 652, and opposite to the heel side wing 660. The heel side wing 660 is also adjacent to the front periphery 648 and the rear periphery 652, but opposite to the toe side wing 656. The toe side wing 656 and heel side wing 660, extend beyond the rear periphery 648 of the upper portion 604. In some embodiments, the heel side wing 660 and toe side wing 656 can be parallel, while in some embodiments, the heel side wing 660 and toe side wing 656 are not parallel. In some embodiments, the rear periphery 652 and front periphery 648 can be parallel, while in some embodiments, the rear periphery 652 and front periphery 648 are not parallel.

[0138] In most embodiments, the toe side wing 656 extends perpendicularly from the rear periphery 652, such that a right angle (90° angle) is formed at the junction of the toe side wing 656 and the rear periphery 652. However, in other embodiments, the toe side wing 656 can extend from the rear periphery 652 in any direction, such that any angle (0°-180°) can be formed at the junction of the toe side wing 656 and the rear periphery 652. Further, in most embodiments, the heel side wing 660 extends perpendicularly from the rear periphery 652, such that a right angle (90° angle) is formed at the junction of the heel side wing 660 and the rear periphery 652. However, in other embodiments, the heel side wing 660 can extend from the rear periphery 652 in any direction, such that any angle (0°-180°) can be formed at the junction of the heel side wing 660 and the rear periphery 652.

[0139] The front periphery 648, of the lower portion 608, comprises a front width. The front width is measured from the junction of the toe side wing 656 and the front periphery 648, to the junction of the heel side wing 660 and the front periphery 648. Further, the lower portion 608, comprises a rear width. The rear width is measured from a tip 657 of the toe side wing 656 and a tip 661 of a toe side wing 660, wherein the tip 657 is the point of the toe side wing 656 furthest from the front periphery 648 and the tip 661 is the point of the heel side wing 660 furthest from the front periphery 648. In most embodiments, the front width is greater than the rear width, however in some embodiments, the front width can be equal to or less than the rear width.

[0140] The rear periphery 652, toe side wing 656, and heel side wing 660 form a gap 664. The gap 664 is bounded by the rear periphery 652, the toe side wing 656, and the heel side wing 660. The gap 664 formed by the rear periphery 652, the toe side wing 656, and the heel side wing 660 shifts a majority of the volume and mass of the putter to the extremities of the lower portion 608. The gap 664 can comprise any shape, however in one embodiment the gap is approximately rectangular. In other embodiments, the gap 664 can be circular, curvilinear, triangular, trapezoidal, parabolic, golf ball shaped, square, or any other desired geometric shape.

[0141] The upper portion 604 of the putter head 600 comprises a toe end 612, a heel end 616, a strike face 620, a rear wall 632, a back edge 634, a crown 642, and an under surface (not pictured). The toe end 612 is opposite the heel end 616. The strike face 620 spans from the toe end 612 to

the heel end 616 and is opposite the rear wall 632. The rear wall 632 is opposite, and approximately parallel to the strike face 620. The crown 642 extends away from the strike face 620 and to the back edge 634 of the upper portion 604. Furthermore, the under surface is opposite the crown 642, spanning from the strike face 620 to the back edge 634.

[0142] The crown 642 further descends from the strike face 620 to the back edge 634. Additionally, the crown 642 extends away from the strike face 620, over the front periphery 648 of lower portion 608, and to the back edge 634 of the upper portion 604. The crown 642, in most embodiments, spans approximately inward 25% of the total club head 600 width from the toe side wing 656 and spans approximately inward 25% of the total club head 600 width from the heel side wing 660. In other embodiments, the crown 642 can, continuously or discontinuously, span the entire width of the total club head 600, in a heel to toe direction. In some embodiments, the crown 642, can span less than 90% of the total width of the club head 600, less than 90% of the total width of the club head 600, less than 80% of the total width of the club head 600, less than 70% of the total width of the club head 600, less than 60% of the total width of the club head 600, less than 50% of the total width of the club head 600, less than 40% of the total width of the club head 600, or less than 30% of the total width of the club head 600. Further, in some embodiments, the crown 642 can be substantially flat from the strike face 620 to the back edge 634 or ascend from the strike face 620 to the back edge 634. In most embodiments, the ascent or descent of the crown 642 can be linear, curvilinear, parabolic, sinusoidal, or a function of polynomial.

[0143] The crown 642 further comprises an alignment trough 655, wherein the alignment trough 655 is equidistant from the heel end 616 and the toe end 612. The alignment trough 655 is adjacent the rear wall 632 and approximately perpendicular to the strike face 620. The alignment trough 655 is bounded by the back edge 634, the rear wall 632, and the crown 642 on the heel end 616 and the toe end 612. In most embodiments, the alignment trough is approximately the width of a golf ball (approximately 4.27 cm) to provide the viewer a visual alignment field that extends the width of the golf ball.

[0144] Furthermore, the upper portion 604 of the putter head 600 can comprise one or more alignment features 644 on the crown 642. The alignment feature 644 can be any one or combination of the following: a line, a series of lines, milling troughs, a circle, a dashed line, a triangle, a channel, or any other desired alignment feature 644. The alignment features 644 can be equally spaced on the entire crown 642, a portion of the crown 642, or the alignment trough 655. The alignment features 644, extending along the alignment trough 655, function to provide the viewer a visual alignment field that extends the width of the golf ball, from the rear wall 632 to the back edge 634 of the putter 600. The goal is to align the entire putter 600 with the golf ball using these alignment features 644 along the crown 642 and/or the alignment trough 655.

[0145] The upper portion 604 is affixed to the lower portion 608 such that the upper portion 604 is further from a ground plane 672 than the lower portion 608, wherein the ground plane 672 is tangent to the lower portion 604, when the putter head 600 is at an address position to strike a golf ball.

[0146] Further, the strike face 620 of the putter head 600 comprises a strike face center point 676 and a loft plane 680. The strike face center point 676 is equidistant from the crown 642 and the undersurface of the upper portion 604, as well as equidistant from the heel end 616 and toe end 612 of the putter head 600. The loft plane 680 is tangent to the strike face 620 of the putter head 600. Further, a midplane 684 intersects the strike face center point 676 and is perpendicular to the loft plane 680. Furthermore, a y-axis 688 intersects the midplane 648, and is perpendicular to the ground plane 672.

[0147] When the upper portion 604 and lower portion 608 are joined such that the heel end 616 overlays at least a portion of the toe side wing 656. Further, when the upper portion 604 and lower portion 608 are joined such that the toe end 612 overlays at least a portion of the heel side wing 660. Further still, when the upper portion 604 and lower portion 608 are joined such that the strike face 620 overlays at least a portion of the front periphery 648. Finally, the upper portion 604 and lower portion 608 are joined such that the back edge 634 overlays at least a portion of the rear periphery 652.

[0148] Referring to FIG. 6C, the front periphery 648, rear periphery 652, toe side wing 656, and heel side wing 660 of the lower portion 608, combined with the upper portion 604, create a sole 668. The sole 668 is perpendicular to the ground plane 672, wherein the ground plane 672 is tangent to the sole 668, when the putter head 600 is at an address position to strike a golf ball. The sole 668 of the putter head 600 extends from the toe end 612 of the putter head 600 to the heel end 616 of the putter head 600.

[0149] In most embodiments, the sole 668 of the putter head 600 can be perfectly flat. In some embodiments, the sole 668 of the putter head 600 can have a slight arch in a heel 616 to toe 612 direction, wherein the slight arch can be linear, or a function of a polynomial. In some embodiments, the sole 668 of the putter head 600 can have a strong arch in the heel 616 to toe 612 direction, wherein the strong arch can be linear, or a function of a polynomial. The sole 668 functions to provide a surface to rest the putter head 600 on the ground plane 672.

[0150] Referring to FIG. 6A, in one embodiment, the lower portion 608 can further comprise a front toe mass 641, a front heel mass 643, a toe wing mass 645, and a heel wing mass 647. The front toe mass 641, front heel mass 643, toe wing mass 645, and heel wing mass 647 are integral to the lower portion 608. The front toe mass 641, front heel mass 643, toe wing mass 645, and heel wing mass 647 extend from the lower portion 608, in a direction away from the ground plane 672, and toward the upper portion 604. These mass portions provide a means to position to upper portion 604 and align with the lower portion 608 of the putter head 600. Furthermore, these mass portions (i.e., the front toe mass 641, front heel mass 643, toe wing mass 645, and heel wing mass 647) provide an additional means of adding weight to the perimeters for increasing the MOI of the putter 600 over putters without these mass features. These mass features can have weight that range from 2-5 grams, 3-7 grams or 1-6 grams. The mass features can have all the same weight or be different weight within the ranges provided above. The mass features can be 1 gram, 2 grams, 3 grams, 4 grams, 5 grams, 6 grams, or 7 grams. The front toe mass 641, a front heel mass 643, a toe wing mass 645, and a heel wing mass 647 can respectively be any one or combination

of the following shapes: rectangular, triangular, pyramidal, spherical, semi-circular, square, cylindrical, ovalar, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0151] In one embodiment, the front toe mass 641 is positioned on the front periphery 648, at the junction of the toe wing 656 and the front periphery 648, however in other embodiments the front toe mass 641 can be positioned anywhere along the front periphery 648. In one embodiment, the front heel mass 643, is positioned on the front periphery 648, at the junction of the heel wing 660 and the front periphery 648, however in other embodiments the front heel mass 643 can be positioned anywhere along the front periphery 648. In one embodiment, the toe wing mass 645 can be positioned over a portion of toe side wing 656, however in other embodiments the toe wing mass 645 can be positioned anywhere along a portion of, or the entire, toe side wing 656. In one embodiment, the heel wing mass 647 can be positioned over a portion of the heel side wing 660, however in other embodiments the heel wing mass 647 can be positioned along a portion of, or the entire, heel side wing 660.

[0152] The front toe mass 641, front heel mass 643, toe wing mass 645, and heel wing mass 647, provide areas of concentrated mass, such that each mass 641, 643, 645, and 647 function to increase the moment of inertia of the putter head 600. The placement of each mass 641, 643, 645, and 647 on the periphery 648 and wings 656, 660, increases the MOI since each mass 641, 643, 645, and 647 since each mass is farther from a center of gravity of the putter 600. Each mass 641, 643, 645, 647 on the periphery 648 and wings 656, 660 is integrally formed from the second material, wherein the second material is denser than the first material.

[0153] The front toe mass 641 and front heel mass 643 offer dual functionalities, such that the front toe mass 641 and front heel mass 643 function not only to increase the MOI of the putter 600 but provide additional surfaces for the upper portion 604 to join to the lower portion 608. Therefore, the front toe mass 641 can also be referred to as a front toe adhesion portion 641 and the front heel mass 643 can also be referred to as a front heel adhesion portion 643.

[0154] In some embodiments, the under surface, strike face 620, and rear wall 632 of the upper portion 608, can form a first cavity (not shown). The first cavity extends inwards from the under surface, on the toe end 612, towards the crown 642 but does not reach the crown 642. The first cavity is bounded by the rear wall 632, the strike face 620, and the toe 612. The first cavity functions to receive the front toe mass 641 of the lower portion 608.

[0155] In some embodiments, the under surface, strike face 620, and rear wall 632 of the upper portion 608, can form a second cavity (not shown). The second cavity extends inwards from the under surface, on the heel end 616, towards the crown 642 but does not reach the crown 642. The second cavity is bounded by the rear wall 632, the strike face 620, and the heel 616. The second cavity functions to receive the front heel mass 643 of the lower portion 608.

[0156] The first and second cavity can comprise any desired geometry, however in most embodiments, the first and second cavity comprise a geometry similar or identical to that of the front toe mass 641 and the front heel mass 643. Further, when the upper portion 604 is affixed to the lower portion 608, the first cavity is positioned such that the first

cavity encompasses the front toe mass **641**, and the second cavity is positioned such that the second cavity encompasses the front heel mass **643**.

[0157] The combination of the low density first material upper portion **604** with the high density second material lower portion **608**, creates a high MOI putter **600**, without creating an extremely heavy putter. The large gap **664** formed by the rear periphery **652** and the wings **656**, **660** of the lower portion **608** forms a dense, yet low volume portion that increases the MOI of the putter, in comparison to a putter milled from a single material. A single material putter fails to allocate high density material to the periphery, while maintaining a desirable volume (75 cc-100 cc) and mass (340 grams-385 grams).

[0158] The lower portion **608**, in most embodiments, comprises less than 38% of a total volume of the putter **600**. In some embodiments, the lower portion **608** comprises less than 37% of the total volume of the putter **600**, less than 36% of the total volume of the putter **600**, less than 35% of the total volume of the putter **600**, less than 34% of the total volume of the putter **600**, less than 33% of the total volume of the putter **600**, less than 32% of the total volume of the putter **600**, less than 31% of the total volume of the putter **600**, less than 30% of the total volume of the putter **600**, less than 29% of the total volume of the putter **600**, less than 28% of the total volume of the putter **600**, or less than 27% of the total volume of the putter **600**.

[0159] Although the lower portion **608** comprises less than half of the volume of the putter **600**, the lower portion **608** comprises at least 45% of an overall mass of the putter **600**. In some embodiments, the lower portion **608** comprises at least 46% of the overall mass of the putter **600**, at least 46% of the overall mass of the putter **600**, at least 47% of the overall mass of the putter **600**, at least 48% of the overall mass of the putter **600**, at least 49% of the overall mass of the putter **600**, at least 50% of the overall mass of the putter **600**, at least 51% of the overall mass of the putter **600**, at least 52% of the overall mass of the putter **600**, at least 53% of the overall mass of the putter **600**, at least 54% of the overall mass of the putter **600**, or at least 55% of the overall mass of the putter **600**.

[0160] The beneficial shift of mass to the periphery of the putter head **600**, through the use of a high density, low volume lower portion **608**, increases the MOI of the putter **600**, over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single stainless steel block, or a putter investment cast of a single material).

e. Spade Embodiment

[0161] In one embodiment, the putter-type golf club head can be a spade shaped putter head with periphery spans **700**. Referring to FIGS. 7A and 7B, the spade shaped putter head **700** has an upper portion **704** and a lower portion **708**. The upper portion **704** is made from a first material having a first density and the lower portion **708** is made from a second material having a second density. The first density is less than the second density. The upper portion **704** and lower portion **708** combine to create a high-MOI putter head **700** (5000 g-cm²-6500 g-cm²), while maintaining a desirable volume and mass.

[0162] As discussed above, the lower portion **708** is comprised of a high-density material (i.e., the first material), thereby lowering the mass below a midline **784**. The lower

portion **708** comprises a front periphery **748**, a rear periphery **752**, a toe side periphery **756**, and a heel side periphery **760**. The front periphery **748** is adjacent to the toe side periphery **756** and the heel side periphery **760**, and opposite to the rear periphery **752**. The toe side periphery **756** is adjacent to the front periphery **748** and the rear periphery **752**, and opposite and to the heel side periphery **760**. The heel side periphery **760** is also adjacent to the front periphery **748** and the rear periphery **752**, but opposite to the toe side periphery **756**. In some embodiments, the heel side periphery **760** and toe side periphery **756** can be parallel, while in some embodiments the heel side periphery **760** and toe side periphery **756** are not parallel. In some embodiments, the rear periphery **752** and front periphery **748** can be parallel, while in some embodiments the rear periphery **752** and front periphery **748** are not parallel.

[0163] The front periphery **748**, of the lower portion **708**, comprises a front width. The front width is measured from the junction of the toe side periphery **756** and the front periphery **748**, to the junction of the heel side periphery **760** and the front periphery **748**. Further, the rear periphery **752**, of the lower portion **708**, comprises a rear width. The rear width is measured from the junction of the toe side periphery **756** and the rear periphery **752**, to the junction of the heel side periphery **760** and the rear periphery **752**. In most embodiments, the front width is greater than the rear width, however in some embodiments, the front width can be equal to or less than the rear width.

[0164] The front periphery **748**, rear periphery **752**, toe side periphery **756**, and heel side periphery **760**, join to form an aperture **764**, wherein the aperture **764** is bounded by the four peripheries (front **756**, rear **752**, toe side **756**, and heel side **760**). The four peripheries **756**, **752**, **756**, **760**, form a perimeter around the aperture **764**. The central aperture **764**, formed by the peripheries **756**, **752**, **756**, **760** of the lower portion **708**, shifts a majority of the volume and mass of the putter to the extremities of the lower portion **708**.

[0165] The upper portion **704** of the putter head **700** comprises a toe end **712**, a heel end **716**, a strike face **720**, a rear wall **732**, a back edge **734**, a crown **742**, and an under surface (not pictured). The toe end **712** is opposite the heel end **716**. The strike face **720** spans from the toe end **712** to the heel end **716** and is opposite the rear wall **732**. The rear wall **732** is opposite, and approximately parallel to the strike face **720**. The crown **742** extends away from the strike face **720**, over at least a portion of the rear wall **732**, and to the back edge **734** of the upper portion **704**. Furthermore, the under surface is opposite the crown **742**, spanning from the strike face **720** to the back edge **734**.

[0166] The crown **742** further descends from the strike face **720** to the back edge **734**. Additionally, the crown **742** extends away from the strike face **720**, over at least a portion of the rear wall **732**, the aperture **764** of the lower portion **708**, and to the back edge **734** of the upper portion **704**. The crown **742**, in most embodiments, is inward 25% of the total club head **700** width from the toe side periphery **756** and the heel side periphery **760**. In this embodiment, the crown **742** spans approximately 50% of the width of the club head **700**. In other embodiments, the crown **742**, can span the entire width of the total club head **700**, in a heel to toe direction. In some embodiments, the crown **742**, can span less than 90% of the total width of the club head **700**, less than 90% of the total width of the club head **700**, less than 80% of the total width of the club head **700**, less than 70% of the total

width of the club head **700**, less than 60% of the total width of the club head **700**, less than 50% of the total width of the club head **700**, less than 40% of the total width of the club head **700**, or less than 30% of the total width of the club head **700**. Further, in some embodiments, the crown **742** can be substantially flat from the strike face **720** to the back edge **734** or ascend from the strike face **720** to the back edge **734**. In most embodiments, the ascent or descent of the crown **742** can be linear, curvilinear, parabolic, sinusoidal, or a function of polynomial.

[0167] Furthermore, the upper portion **704** of the putter head **700** can comprise one or more alignment features **744** on the crown **742**. The alignment feature **744** can be any one or combination of the following: a line, a series of lines, milling troughs, a circle, a dashed line, a triangle, a channel, or any other desired alignment feature **744**. The alignment features **744** are equally spaced on the entire crown **742**, wherein the crown is configured to be the width of a golf ball (approximately 4.27 cm). The alignment features **744**, extending along the crown **742**, function to provide the viewer a visual alignment field that extends the width of the golf ball, from the strike face **720** to the back edge **734** of the putter **700**. The goal is to align the entire putter **700** with the golf ball using these alignment features **744** along the crown **742**.

[0168] Referring to FIG. 7C, the upper portion **704** is affixed to the lower portion **708** such that the upper portion **704** is further from a ground plane **772** than the lower portion **708**, wherein the ground plane **772** is tangent to the lower portion **704**, when the putter head **700** is at an address position to strike a golf ball.

[0169] Further, the strike face **720** of the putter head **700** comprises a strike face center point **776** and a loft plane **780**. The strike face center point **776** is equidistant from the crown **742** and the undersurface of the upper portion **704**, as well as equidistant from the heel end **716** and toe end **712** of the putter head **700**. The loft plane **780** is tangent to the strike face **720** of the putter head **700**. Further, a midplane **748** intersects the strike face center point **776** and is perpendicular to the loft plane **780**. Furthermore, a y-axis **788** intersects the midplane **784**, and is perpendicular to the ground plane **772**.

[0170] When the upper portion **704** and lower portion **708** are joined such that the heel end **716** overlays at least a portion of the toe side periphery **756**. Further, when the upper portion **704** and lower portion **708** are joined such that the toe end **712** overlays at least a portion of the heel side periphery **760**. Further still, when the upper portion **704** and lower portion **708** are joined such that the strike face **720** overlays at least a portion of the front periphery **748**. Finally, the upper portion **704** and lower portion **708** are joined such that the back edge **734** overlays at least a portion of the rear periphery **752**.

[0171] The four peripheries (front **748**, rear **752**, toe side **756**, and heel side **760**) of the lower portion **708**, combined with the upper portion **704**, create a sole **768**. The sole **768** is perpendicular to the ground plane **772**, wherein the ground plane **772** is tangent to the sole **768**, when the putter head **700** is at an address position to strike a golf ball. The sole **768** of the putter head **700** extends from the toe end **712** of the putter head **700** to the heel end **716** of the putter head **700**.

[0172] In most embodiments, the sole **768** of the putter head **700** can be perfectly flat. In some embodiments, the

sole **768** of the putter head **700** can have a slight arch in a heel **716** to toe **712** direction, wherein the slight arch can be linear, or a function of a polynomial. In some embodiments, the sole **768** of the putter head **700** can have a strong arch in the heel **716** to toe **712** direction, wherein the strong arch can be linear, or a function of a polynomial. The sole **768** functions to provide a surface to rest the putter head **700** on the ground plane **772**.

[0173] Referring to FIG. 7A, in one embodiment, the lower portion **708** can further comprise a front mass **741**, a rear mass **743**, a toe mass **745**, and a heel mass **747**. The front mass **741**, rear mass **743**, toe mass **745**, and heel mass **747** are integral to the lower portion **708**. The front mass **741**, rear mass **743**, toe mass **745**, and heel mass **747** extend from the lower portion **708**, in a direction away from the ground plane **772**, and toward the upper portion **704**. These mass portions provide a means to position to upper portion **704** and align with the lower portion **708** of the putter head **700**. Furthermore, these mass portions (i.e., the front mass **741**, rear mass **743**, toe mass **745**, and heel mass **747**) provide an additional means of adding weight to the perimeters for increasing the MOI of the putter **700** over putters without these mass features. These mass features can have weight that range from 2-5 grams, 3-7 grams or 1-6 grams. The mass features can have all the same weight or be different weight within the ranges provided above. The mass features can be 1 gram, 2 grams, 3 grams, 4 grams, 5 grams, 6 grams, or 7 grams. The front mass **741**, a rear mass **743**, a toe mass **745**, and a heel mass **747** can respectively be any one or combination of the following shapes: rectangular, triangular, pyramidal, spherical, semi-circular, square, cylindrical, ovalar, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0174] In one embodiment, the front mass **741** is positioned on the front periphery **748**, is equidistance from the toe side periphery **756** and the heel side periphery **760**, however in other embodiments the front mass **741** can be positioned anywhere along the front periphery **748**. In one embodiment, the rear mass **743**, is positioned on the rear periphery **752**, equidistance from the toe side periphery **756** and the heel side periphery **760**, however in other embodiments the rear mass **743** can be positioned anywhere along the rear periphery **752**. In one embodiment, the toe mass **745** can be positioned at the junction of the toe side periphery **756** and the rear periphery **752**, however in other embodiments the toe mass **745** can be positioned anywhere along the toe side periphery **756**. In one embodiment, the heel mass **747** can be positioned at the junction of the heel side periphery **760** and the rear periphery **752**, however in other embodiments the heel mass **747** can be positioned anywhere along the heel side periphery **760**.

[0175] The front mass **741**, a rear mass **743**, a toe mass **745**, and a heel mass **747**, provide areas of concentrated mass, such that each mass **741**, **743**, **745**, and **747** function to increase the moment of inertia of the putter head **700**. The placement of each mass **741**, **743**, **745**, and **747** on the peripheries **748**, **752**, **756**, **760**, increases the MOI since each mass **741**, **743**, **745**, and **747** since each mass is farther from a center of gravity of the putter **700**. Each mass **741**, **743**, **745**, **747** on the peripheries **748**, **752**, **756**, **760** is integrally formed from the second material, wherein the second material is denser than the first material.

[0176] The front mass 741 and the rear mass 743 offer dual functionalities, such that the front mass 741 and rear mass 743 function not only to increase the MOI of the putter 700 but provide additional surfaces for the upper portion 704 to join to the lower portion 708. Therefore, the front mass 741 can also be referred to as a front adhesion portion 741 and the rear mass 743.

[0177] In some embodiments, the under surface, strike face 720, and rear wall 732 of the upper portion 708, can form a first cavity (not shown). The first cavity extends inwards from the under surface towards the crown 742 but does not reach the crown 742. The first cavity is bounded by the rear wall 732 and the strike face 720. The first cavity functions to receive the front mass 741 of the lower portion 708.

[0178] In some embodiments, the under surface, the back edge 734, and the crown 742 forms a second cavity (not shown). The second cavity extends inwards from the under surface, towards the crown 742, but does not reach the crown 742. The second cavity is bounded by the back edge 734, and the crown 732. In most embodiments, the second cavity is positioned equidistance between the toe side periphery 756 and the heel side periphery 760, when the lower portion 708 is joined to the upper portion 704. The second cavity functions to receive the rear mass 743 of the lower portion 708.

[0179] The first and second cavity can comprise any desired geometry, however in most embodiments, the first and second cavity comprise a geometry similar or identical to that of the front mass 741 and the rear mass 743. Further, when the upper portion 704 is affixed to the lower portion 708, the first cavity is positioned such that the first cavity encompasses the front mass 741, and the second cavity is positioned such that the second cavity encompasses the rear mass 743.

[0180] The combination of the low density first material upper portion 704 with the high density second material lower portion 708, creates a high MOI putter 700, without creating an extremely heavy putter. The large aperture 764 formed by the peripheries 748, 752, 756, 760 of the lower portion 708 forms a dense, yet low volume portion that increases the MOI of the putter, in comparison to a putter milled from a single material. A single material putter fails to allocate high density material to the periphery, while maintaining a desirable volume (75 cc-100 cc) and mass (340 grams-385 grams).

[0181] The lower portion 708, in most embodiments, comprises less than 35% of a total volume of the putter 700. In some embodiments, the lower portion 708 comprises less than 34% of the total volume of the putter 700, less than 33% of the total volume of the putter 700, less than 32% of the total volume of the putter 700, less than 31% of the total volume of the putter 700, less than 30% of the total volume of the putter 700, less than 29% of the total volume of the putter 700, less than 28% of the total volume of the putter 700, or less than 27% of the total volume of the putter 700.

[0182] Although the lower portion 708 comprises less than half of the volume of the putter 700, the lower portion 708 comprises at least 45% of an overall mass of the putter 700. In some embodiments, the lower portion 708 comprises at least 46% of the mass of the putter 700, at least 47% of the mass of the putter 700, at least 48% of the mass of the putter 700, at least 49% of the mass of the putter 700, at least 50% of the mass of the putter 700, at least 51% of the mass of the

putter 700, at least 52% of the mass of the putter 700, at least 53% of the mass of the putter 700, at least 54% of the mass of the putter 700, or at least 55% of the mass of the putter 700.

[0183] The beneficial shift of mass to the periphery of the putter head 700, through the use of a high density, low volume lower portion 708, increases the MOI of the putter 700, over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single stainless steel block, or a putter investment cast of a single material).

f. T-Shaped Embodiment with Periphery Spans

[0184] In one embodiment, the putter-type golf club head can be a T-shaped putter head with periphery spans 800. Referring to FIGS. 8A and 8B, the T-shaped putter head with periphery spans 800 has an upper portion 804 and a lower portion 808. The upper portion 804 is made from a first material having a first density and the lower portion 808 is made from a second material having a second density. The first density is less than the second density. The upper portion 804 and lower portion 808 combine to create a high-MOI putter head 800 ($5000 \text{ g}\cdot\text{cm}^2$ - $6500 \text{ g}\cdot\text{cm}^2$), while maintaining a desirable volume and mass.

[0185] As discussed above, the lower portion 808 is comprised of a high-density material (i.e., the second material), thereby lowering the mass below a midline 884. The lower portion 808 comprises a front periphery 848, a rear periphery 852, a toe side periphery 856, and a heel side periphery 860. The front periphery 848 is adjacent to the toe side periphery 856 and the heel side periphery 860, and opposite to the rear periphery 852. The toe side periphery 856 is adjacent to the front periphery 848 and the rear periphery 852, and opposite to the heel side periphery 860. The heel side periphery 860 is also adjacent to the front periphery 848 and the rear periphery 852, but opposite to the toe side periphery 856. In some embodiments, the heel side periphery 860 and toe side periphery 856 can be parallel, while in some embodiments the heel side periphery 860 and toe side periphery 856 are not parallel. In some embodiments, the rear periphery 852 and front periphery 848 can be parallel, while in some embodiments the rear periphery 852 and front periphery 848 are not parallel.

[0186] The front periphery 848, of the lower portion 808, comprises a front width. The front width is measured from the junction of the toe side periphery 856 and the front periphery 848, to the junction of the heel side periphery 860 and the front periphery 848. Further, the rear periphery 852, of the lower portion 808, comprises a rear width. The rear width is measured from the junction of the toe side periphery 856 and the rear periphery 852, to the junction of the heel side periphery 860 and the rear periphery 852. In most embodiments, the front width is greater than the rear width, however in some embodiments, the front width can be equal to or less than the rear width.

[0187] The front periphery 848, rear periphery 852, toe side periphery 856, and heel side periphery 860, join to form an aperture 864, wherein the aperture 864 is bounded by the four peripheries (front 856, rear 852, toe side 856, and heel side 860). The four peripheries 856, 852, 856, 860, form a perimeter around the aperture 864. The central aperture 864, formed by the peripheries 856, 852, 856, 860 of the lower portion 808, shifts a majority of the volume and mass of the putter to the extremities of the lower portion 808.

[0188] In some embodiments, the aperture **864**, formed by the front periphery **848**, rear periphery **852**, toe side periphery **856**, and heel side periphery **860** can be any one of the following shapes: rectangular, triangular, semi-circular, circular (golf ball sized), circular (larger than a golf ball), circular (smaller than a golf ball), square, ovular, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0189] The upper portion **804** of the putter head **800** comprises a toe end **812**, a heel end **816**, a strike face **820**, a rear wall **832**, a back edge **834**, a crown **842**, and an under surface (not pictured). The toe end **812** is opposite the heel end **816**. The strike face **820** spans from the toe end **812** to the heel end **816** and is opposite the rear wall **832**. The rear wall **832** is opposite, and approximately parallel to the strike face **820**. The crown **842** extends away from the strike face **820**, over at least a portion of the rear wall **832**, and to the back edge **834** of the upper portion **804**. Furthermore, the under surface is opposite the crown **842**, spanning from the strike face **820** to the back edge **834**.

[0190] The crown **842** further descends from the strike face **820** to the back edge **834**. Additionally, the crown **842** extends away from the strike face **820**, over at least a portion of the rear wall **832**, the aperture **864** of the lower portion **808**, and to the back edge **834** of the upper portion **804**. The crown **842**, in most embodiments, is inward 25% of the total club head **800** width from the toe side periphery **856** and the heel side periphery **860**. In this embodiment, the crown **842** spans approximately 50% of the width of the club head **800**, thus forming a “T-Shape” with the strike face. In other embodiments, the crown **842**, can span the entire width of the total club head **800**, in a heel to toe direction. In some embodiments, the crown **842**, can span less than 90% of the total width of the club head **800**, less than 90% of the total width of the club head **800**, less than 80% of the total width of the club head **800**, less than 70% of the total width of the club head **800**, less than 60% of the total width of the club head **800**, less than 50% of the total width of the club head **800**, less than 40% of the total width of the club head **800**, or less than 30% of the total width of the club head **800**. Further, in some embodiments, the crown **842** can be substantially flat from the strike face **820** to the back edge **834** or ascend from the strike face **820** to the back edge **834**. In most embodiments, the ascent or descent of the crown **842** can be linear, curvilinear, parabolic, sinusoidal, or a function of polynomial.

[0191] Furthermore, the upper portion **804** of the putter head **800** can comprise one or more alignment features **844** on the crown **842**. The alignment feature **844** can be any one or combination of the following: a line, a series of lines, milling troughs, a circle, a dashed line, a triangle, a channel, or any other desired alignment feature **844**. The alignment features **844** are equally spaced on the entire crown **842**, wherein the crown is configured to be the width of a golf ball (approximately 4.27 cm). The alignment features **844**, extending along the crown **842**, function to provide the viewer a visual alignment field that extends the width of the golf ball, from the strike face **820** to the back edge **834** of the putter **800**. The goal is to align the entire putter **800** with the golf ball using these alignment features **844** along the crown **842**.

[0192] Referring to FIG. 8C, the upper portion **804** is affixed to the lower portion **808** such that the upper portion **804** is further from a ground plane **872** than the lower

portion **808**, wherein the ground plane **872** is tangent to the lower portion **804**, when the putter head **800** is at an address position to strike a golf ball.

[0193] Further, the strike face **820** of the putter head **800** comprises a strike face center point **876** and a loft plane **880**. The strike face center point **876** is equidistant from the crown **842** and the undersurface of the upper portion **804**, as well as equidistant from the heel end **816** and toe end **812** of the putter head **800**. The loft plane **880** is tangent to the strike face **820** of the putter head **800**. Further, a midplane **884** intersects the strike face center point **876** and is perpendicular to the loft plane **880**. Furthermore, a y-axis **888** intersects the midplane **884**, and is perpendicular to the ground plane **872**.

[0194] When the upper portion **804** and lower portion **808** are joined such that the heel end **816** overlays at least a portion of the toe side periphery **856**. Further, when the upper portion **804** and lower portion **808** are joined such that the toe end **812** overlays at least a portion of the heel side periphery **860**. Further still, when the upper portion **804** and lower portion **808** are joined such that the strike face **820** overlays at least a portion of the front periphery **848**. Finally, the upper portion **804** and lower portion **808** are joined such that the back edge **834** overlays at least a portion of the rear periphery **852**.

[0195] The four peripheries (front **848**, rear **852**, toe side **856**, and heel side **860**) of the lower portion **808**, combined with the upper portion **804**, create a sole **868**. The sole **868** is perpendicular to the ground plane **872**, wherein the ground plane **872** is tangent to the sole **868**, when the putter head **800** is at an address position to strike a golf ball. The sole **868** of the putter head **800** extends from the toe end **812** of the putter head **800** to the heel end **816** of the putter head **800**.

[0196] In most embodiments, the sole **868** of the putter head **800** can be perfectly flat. In some embodiments, the sole **868** of the putter head **800** can have a slight arch in a heel **816** to toe **812** direction, wherein the slight arch can be linear, or a function of a polynomial. In some embodiments, the sole **868** of the putter head **800** can have a strong arch in the heel **816** to toe **812** direction, wherein the strong arch can be linear, or a function of a polynomial. The sole **868** functions to provide a surface to rest the putter head **800** on the ground plane **872**.

[0197] Referring to FIG. 8A, in one embodiment, the lower portion **808** can further comprise a front mass **841**, a rear mass **843**, a toe mass **845**, and a heel mass **847**. The front mass **841**, rear mass **843**, toe mass **845**, and heel mass **847** are integral to the lower portion **808**. The front mass **841**, rear mass **843**, toe mass **845**, and heel mass **847** extend from the lower portion **808**, in a direction away from the ground plane **872**, and toward the upper portion **804**. These mass portions provide a means to position to upper portion **804** and align with the lower portion **808** of the putter head **800**. Furthermore, these mass portions (i.e., the front mass **841**, rear mass **843**, toe mass **845**, and heel mass **847**) provide an additional means of adding weight to the perimeters for increasing the MOI of the putter **800** over putters without these mass features. These mass features can have weight that range from 2-5 grams, 3-7 grams or 1-6 grams. The mass features can have all the same weight or be different weight within the ranges provided above. The mass features can be 1 gram, 2 grams, 3 grams, 4 grams, 5 grams, 6 grams, or 7 grams. The front mass **841**, a rear mass **843**,

a toe mass **845**, and a heel mass **847** can respectively be any one or combination of the following shapes: rectangular, triangular, pyramidal, spherical, semi-circular, square, cylindrical, ovalar, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0198] In one embodiment, the front mass **841** is positioned on the front periphery **848**, is equidistance from the toe side periphery **856** and the heel side periphery **860**, however in other embodiments the front mass **841** can be positioned anywhere along the front periphery **848**. In one embodiment, the rear mass **843**, is positioned on the rear periphery **852**, equidistance from the toe side periphery **856** and the heel side periphery **860**, however in other embodiments the rear mass **843** can be positioned anywhere along the rear periphery **852**. In one embodiment, the toe mass **845** can be positioned at the junction of the toe side periphery **856** and the rear periphery **852**, however in other embodiments the toe mass **845** can be positioned anywhere along the toe side periphery **856**. In one embodiment, the heel mass **847** can be positioned at the junction of the heel side periphery **860** and the rear periphery **852**, however in other embodiments the heel mass **847** can be positioned anywhere along the heel side periphery **860**.

[0199] The front mass **841**, a rear mass **843**, a toe mass **845**, and a heel mass **847**, provide areas of concentrated mass, such that each mass **841**, **843**, **845**, and **847** function to increase the moment of inertia of the putter head **800**. The placement of each mass **841**, **843**, **845**, and **847** on the peripheries **848**, **852**, **856**, **860**, increases the MOI since each mass **841**, **843**, **845**, and **847** since each mass is farther from a center of gravity of the putter **800**. Each mass **841**, **843**, **845**, **847** on the peripheries **848**, **852**, **856**, **860** is integrally formed from the second material, wherein the second material is denser than the first material.

[0200] The front mass **841** and the rear mass **843** offer dual functionalities, such that the front mass **841** and rear mass **843** function not only to increase the MOI of the putter **800** but provide additional surfaces for the upper portion **804** to join to the lower portion **808**. Therefore, the front mass **841** can also be referred to as a front adhesion portion **841** and the rear mass **843**.

[0201] In some embodiments, the under surface, strike face **820**, and rear wall **832** of the upper portion **808**, can form a first cavity (not shown). The first cavity extends inwards from the under surface towards the crown **842** but does not reach the crown **842**. The first cavity is bounded by the rear wall **832** and the strike face **820**. The first cavity functions to receive the front mass **841** of the lower portion **808**.

[0202] In some embodiments, the under surface, the back edge **834**, and the crown **842** forms a second cavity (not shown). The second cavity extends inwards from the under surface, towards the crown **842**, but does not reach the crown **842**. The second cavity is bounded by the back edge **834**, and the crown **832**. In most embodiments, the second cavity is positioned equidistance between the toe side periphery **856** and the heel side periphery **860**, when the lower portion **808** is joined to the upper portion **804**. The second cavity functions to receive the rear mass **843** of the lower portion **808**.

[0203] The first and second cavity can comprise any desired geometry, however in most embodiments, the first and second cavity comprise a geometry similar or identical

to that of the front mass **841** and the rear mass **843**. Further, when the upper portion **804** is affixed to the lower portion **808**, the first cavity is positioned such that the first cavity encompasses the front mass **841**, and the second cavity is positioned such that the second cavity encompasses the rear mass **843**.

[0204] The combination of the low density first material upper portion **804** with the high density second material lower portion **808**, creates a high MOI putter **800**, without creating an extremely heavy putter. The large aperture **864** formed by the peripheries **848**, **852**, **856**, **860** of the lower portion **808** forms a dense, yet low volume portion that increases the MOI of the putter, in comparison to a putter milled from a single material. A single material putter fails to allocate high density material to the periphery, while maintaining a desirable volume (75 cc-100 cc) and mass (340 grams-385 grams).

[0205] The lower portion **808**, in most embodiments, comprises less than 35% of a total volume of the putter **800**. In some embodiments, the lower portion **908** comprises less than 34% of the total volume of the putter **800**, less than 33% of the total volume of the putter **800**, less than 32% of the total volume of the putter **800**, less than 31% of the total volume of the putter **800**, less than 30% of the total volume of the putter **800**, less than 29% of the total volume of the putter **800**, less than 28% of the total volume of the putter **800**, or less than 27% of the total volume of the putter **800**.

[0206] Although the lower portion **808** comprises less than half of the volume of the putter **800**, the lower portion **808** comprises at least 45% of an overall mass of the putter **800**. In some embodiments, the lower portion **808** comprises at least 46% of the mass of the putter **800**, at least 46% of the mass of the putter **800**, at least 46% of the mass of the putter **800**, at least 47% of the mass of the putter **800**, at least 48% of the mass of the putter **800**, at least 49% of the mass of the putter **800**, at least 50% of the mass of the putter **800**, at least 51% of the mass of the putter **800**, at least 52% of the mass of the putter **800**, at least 53% of the mass of the putter **800**, at least 54% of the mass of the putter **800**, or at least 55% of the mass of the putter **800**.

[0207] The beneficial shift of mass to the periphery of the putter head **800**, through the use of a high density, low volume lower portion **808**, increases the MOI of the putter **800**, over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single stainless steel block, or a putter investment cast of a single material).

g. Dual-Rail Embodiment

[0208] In another embodiment, the putter-type golf club head can be a dual-rail putter head **900**. Referring to FIGS. 9A and 9B, the dual-rail putter head **900** has an upper portion **904** and a lower portion **908**. The upper portion **904** is made from a first material having a first density and the lower portion **908** is made from a second material having a second density. The first density is less than the second density. The upper portion **904** and lower portion **908** combine to create a high-MOI putter head **900** (5000 g·cm²-6500 g·cm²), while maintaining a desirable volume and mass.

[0209] As discussed above, the lower portion **908** is comprised of a high-density material (i.e., the second material), thereby lowering the mass below a midline **984**. The lower portion **908** comprises a front periphery **948**, a rear periphery **952**, a toe side periphery **956**, and a heel side periphery

960. The front periphery **948** is adjacent to the toe side periphery **956** and the heel side periphery **960**, and opposite to the rear periphery **952**. The toe side periphery **956** is adjacent to the front periphery **948** and the rear periphery **952**, and opposite and to the heel side periphery **960**. The heel side periphery **956** is also adjacent to the front periphery **948** and the rear periphery **952**, but opposite to the toe side periphery **956**. In some embodiments, the heel side periphery **960** and toe side periphery **956** can be parallel, while in some embodiments the heel side periphery **960** and toe side periphery **956** are not parallel. In some embodiments, the rear periphery **952** and front periphery **948** can be parallel, while in some embodiments the rear periphery **952** and front periphery **948** are not parallel.

[0210] The front periphery **948**, of the lower portion **908**, comprises a front width. The front width is measured from the junction of the toe side periphery **956** and the front periphery **948**, to the junction of the heel side periphery **960** and the front periphery **948**. Further, the rear periphery **952**, of the lower portion **908**, comprises a rear width. The rear width is measured from the junction of the toe side periphery **956** and the rear periphery **952**, to the junction of the heel side periphery **960** and the rear periphery **952**. In most embodiments, the front width is greater than the rear width, however in some embodiments, the front width can be equal to or less than the rear width.

[0211] The front periphery **948**, rear periphery **952**, toe side periphery **956**, and heel side periphery **960**, join to form an aperture **964**, wherein the aperture **964** is bounded by the four peripheries (front **948**, rear **952**, toe side **956**, and heel side **960**). The four peripheries **948**, **952**, **956**, **960**, form a perimeter around the aperture **964**. The central aperture **964**, formed by the peripheries **948**, **952**, **956**, **960** of the lower portion **908**, shifts a majority of the volume and mass of the putter to the extremities of the lower portion **908**.

[0212] In some embodiments, the aperture **964**, formed by the front periphery **948**, rear periphery **952**, toe side periphery **956**, and heel side periphery **960** can be any one of the following shapes: rectangular, triangular, semi-circular, circular (golf ball sized), circular (larger than a golf ball), circular (smaller than a golf ball), square, oval, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0213] The upper portion **904** of the dual-rail putter head **900** comprises a toe end **912**, a heel end **916**, a strike face **920**, a rear wall **932**, a back edge **934**, a crown **942**, and an under surface (not pictured). The toe end **912** is opposite the heel end **916**. The strike face **920** spans from the toe end **912** to the heel end **916** and is opposite the rear wall **932**. The rear wall **932** is opposite, and approximately parallel to the strike face **920**. The crown **942** extends away from the strike face **920**, over at least a portion of the rear wall **932**, and to the back edge **934** of the upper portion **904**. Furthermore, the under surface is opposite the crown **942**, spanning from the strike face **920** to the back edge **934**.

[0214] The crown **942** of the upper portion **904** further comprises a toe end mid-rail **936** and a heel end mid-rail **940**. In most embodiments, the toe end mid-rail **936** and heel end mid-rail **940** are approximately parallel, while perpendicular to the strike face **920**. Further, the toe end mid-rail **936** and heel end mid-rail **940** do not contact the toe side periphery **956** or the heel side periphery **960**. The toe end mid-rail **936** and the heel end mid-rail **940** are approximately $\frac{1}{3}$ inward of the total club head width from the outer

periphery of the toe side periphery **956** and heel side periphery **960** respectively. However, in other embodiments, the toe end mid-rail **936** and the heel end mid-rail **940** can be more or less than $\frac{1}{3}$ inward of the total club head width from the outer periphery of the toe-side periphery and heel-side periphery respectively. The toe end mid-rail **936** and heel end mid-rail **940** descend from the strike face **920** to the back edge **934**. In some embodiments, the toe end mid-rail **936** and heel end mid-rail **940** are not parallel and not perpendicular to the strike face **920**. In some embodiments, the toe end mid-rail **936** and heel end mid-rail **940** can be substantially flat from the strike face **920** to the back edge **934** or ascend from the strike face **920** to the back edge **934**. In most embodiments, the ascent or descent of the mid-rails **936**, **940** can be linear, curvilinear, parabolic, sinusoidal, or a function of polynomial.

[0215] Furthermore, the upper portion **904** of the dual-rail putter head **900** can comprise one or more alignment features **944** on toe end mid-rail **936** and heel end mid-rail **940**. The alignment feature **944** can be any one or combination of the following: a line, a circle, a dashed line, a triangle, a channel, or any other desired alignment feature **944**. The alignment features **944** are spaced such on the rails **936**, **940** to be the width of a golf ball (approximately 4.27 cm). The alignment features **944** extend along the rails to provide the viewer a visual alignment field that extends from the golf ball, strike face **920** to the entire putter **900**. The goal is to align the entire putter **900** with the golf ball using these alignment features **944** along the toe end mid-rail **936** and heel end mid-rail **940**.

[0216] The upper portion **904** is affixed to the lower portion **908** such that the upper portion **904** is further from a ground plane **972** than the lower portion **908**, wherein the ground plane **972** is tangent to the lower portion **904**, when the dual-rail putter head **900** is at an address position to strike a golf ball.

[0217] Further, the strike face **920** of the dual-rail putter head **900** comprises a strike face center point **976** and a loft plane **980**. The strike face center point **976** is equidistant from the crown **942** and the undersurface of the upper portion **904**, as well as equidistant from the heel end **916** and toe end **912** of the dual-rail putter head **900**. The loft plane **980** is tangent to the strike face **920** of the dual-rail putter head **900**. Further, a midplane **984** intersects the strike face center point **976** and is perpendicular to the loft plane **980**. Furthermore, a y-axis **988** intersects the midplane **984**, and is perpendicular to the ground plane **972**.

[0218] When the upper portion **904** and lower portion **908** are joined such that the heel end **916** overlays at least a portion of the toe side periphery **956**. Further, when the upper portion **904** and lower portion **908** are joined such that the toe end **912** overlays at least a portion of the heel side periphery **960**. Further still, when the upper portion **904** and lower portion **908** are joined such that the strike face **920** overlays at least a portion of the front periphery **948**. Finally, when the upper portion **904** and lower portion **908** are joined such that the back edge **934** overlays at least a portion of the rear periphery **952**.

[0219] Referring to FIG. 9C, the four peripheries (front **948**, rear **952**, toe side **956**, and heel side **960**) of the lower portion **908**, combined with the upper portion **904**, create a sole **968**. The sole **968** is perpendicular to the ground plane **972**, wherein the ground plane **972** is tangent to the sole **968**, when the dual-rail putter head **900** is at an address position

to strike a golf ball. The sole 968 of the dual-rail putter head 900 extends from the toe end 912 of the dual-rail putter head 900 to the heel end 916 of the dual-rail putter head 900.

[0220] In most embodiments, the sole 968 of the dual-rail putter head 900 can be perfectly flat. In some embodiments, the sole 968 of the putter head 900 can have a slight arch in a heel to toe direction, wherein the slight arch can be linear, or a function of a polynomial. In some embodiments, the sole 968 of the putter head 900 can have a strong arch in the heel to toe direction, wherein the strong arch can be linear, or a function of a polynomial. The sole 968 functions to provide a surface to rest the dual-rail putter head 900 on the ground plane 972.

[0221] Referring to FIG. 10A, in one embodiment, the lower portion 908 can further comprise a front mass 941, a rear mass 943, a toe mass 945, and a heel mass 947. The front mass 941, rear mass 943, toe mass 945, and heel mass 947 are integral to the lower portion 908. The front mass 941, rear mass 943, toe mass 945, and heel mass 947 extend from the lower portion 908, in a direction away from the ground plane 972, and toward the upper portion 904. These mass portions provide a means to position to upper portion and align with the lower portion of the dual-rail putter head 900. Furthermore, these mass portions (i.e., the front mass 941, rear mass 943, toe mass 945, and heel mass 947) provide an additional means of adding weight to the perimeters for increasing the MOI of the putter over putters without these mass features. These mass features can have weight that range from 2-5 grams, 3-7 grams or 1-6 grams. The mass features can have all the same weight or be different weight within the ranges provided above. The mass features can be 1 gram, 2 grams, 3 grams, 4 grams, 5 grams, 6 grams, or 7 grams. The front mass 941, a rear mass 943, a toe mass 945, and a heel mass 947 can respectively be any one or combination of the following shapes: rectangular, triangular, pyramidal, spherical, semi-circular, square, cylindrical, ovular, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0222] In one embodiment, the front mass 941 is positioned on the front periphery 948, is equidistance from the toe side periphery 956 and the heel side periphery 960, however in other embodiments the front mass 941 can be positioned anywhere along the front periphery 948. In one embodiment, the rear mass 943, is positioned on the rear periphery 952, equidistance from the toe side periphery 956 and the heel side periphery 960, however in other embodiments the rear mass 943 can be positioned anywhere along the rear periphery 952. In one embodiment, the toe mass 945 can be positioned at the junction of the toe side periphery 956 and the rear periphery 952, however in other embodiments the toe mass 945 can be positioned anywhere along the toe side periphery 956. In one embodiment, the heel mass 947 can be positioned at the junction of the heel side periphery 960 and the rear periphery 952, however in other embodiments the heel mass 947 can be positioned anywhere along the heel side periphery 960.

[0223] The front mass 941, a rear mass 943, a toe mass 945, and a heel mass 947, provide areas of concentrated mass, such that each mass 941, 943, 945, and 947 function to increase the moment of inertia of the putter head 900. The placement of each mass 941, 943, 945, and 947 on the peripheries 948, 952, 956, 960, increases the MOI since each mass 941, 943, 945, and 947 since each mass is farther from

a center of gravity of the putter 900. Each mass 941, 943, 945, 947 on the peripheries 948, 952, 956, 960 is integrally formed from the second material, wherein the second material is denser than the first material.

[0224] The front mass 941, a rear mass 943, a toe mass 945, and a heel mass 947 offer dual functionalities, such that each mass 941, 943, 945, and 947 functions not only to increase the MOI of the putter 900, but provide additional surface for the upper portion 904 to join to the lower portion 908. Therefore, the front mass 941 can also be referred to as a front adhesion portion 941, the rear mass 943 can also be referred to as rear adhesion portion 943, the toe mass 945 can also be referred to as a toe adhesion portion 945, and the heel mass 947 can also be referred to as a heel adhesion portion 947.

[0225] Further, the crown 942 of the upper portion 942 comprises a toe end cap 949, and a heel end cap 951, such that the toe end cap 949 and heel end cap 951 function to mate to the toe mass 945 and the heel mass 947, respectively. The toe end cap 949 is adjacent the toe end mid-rail 936 and the back edge 934. The heel end cap 951 is adjacent the heel end mid-rail 940 and the back edge 934. In most embodiments, the toe end cap 949 and heel end cap 951 comprise identical geometries, however in some embodiments, the toe end cap 949 and heel end cap 951 can comprise different geometries.

[0226] In most embodiments, the toe end cap 949 and heel end cap 951, of the crown 942, are larger than the toe mass 945 and heel mass 947, respectively, so that the toe end cap 949 and heel end cap 951 encompass the toe mass 945 and heel mass 947, when the upper portion 904 is affixed to the lower portion 908. Further, when the upper portion 904 is affixed to the lower portion 908, the toe end cap 949 is positioned such that the toe end cap 949 overlays at least a portion of the toe side periphery 956 and the toe mass 945. Further still, when the upper portion 904 is affixed to the lower portion 908, the heel end cap 951 is positioned such that the heel end cap 951 overlays at least a portion of the heel side periphery 960 and the heel mass 960.

[0227] In some embodiments, the under surface, strike face 920, and rear wall 932 of the upper portion 908, can form a first cavity (not shown). The first cavity extends inwards from the under surface towards the crown 942 but does not reach the crown 942. The first cavity is bounded by the rear wall 932 and the strike face 920. The first cavity functions to receive the front mass 941 of the lower portion 908.

[0228] In some embodiments, the under surface, the back edge 934, and the crown 942 forms a second cavity (not shown). The second cavity extends inwards from the under surface, towards the crown 942, but does not reach the crown 942. The second cavity is bounded by the back edge 934, the toe cap 949, and the heel end cap 951. In most embodiments, the second cavity is positioned equidistance between the toe end cap 949 and the heel end cap 951. The second cavity functions to receive the rear mass 943 of the lower portion 908.

[0229] The first and second cavity can comprise any desired geometry, however in most embodiments, the first and second cavity comprise a geometry similar or identical to that of the front mass 941 and the rear mass 943. Further, when the upper portion 904 is affixed to the lower portion 908, the first cavity is positioned such that the first cavity

encompasses the front mass **941**, and the second cavity is positioned such that the second cavity encompasses the rear mass **943**.

[0230] The combination of the low density first material upper portion **904** with the high density second material lower portion **908**, creates a high MOI putter **900**, without creating an extremely heavy putter. The large aperture **964** formed by the peripheries **948**, **952**, **956**, **960** of the lower portion **908** forms a dense, yet low volume portion that increases the MOI of the putter, in comparison to a putter milled from a single material. A single material putter fails to allocate high density material to the periphery, while maintaining a desirable volume (75 cc-100 cc) and mass (340 grams-385 grams).

[0231] The lower portion **908**, in most embodiments, comprises less than 35% of a total volume of the putter **900**. In some embodiments, the lower portion **908** comprises less than 34% of the total volume of the putter **900**, less than 33% of the total volume of the putter **900**, less than 32% of the total volume of the putter **900**, less than 31% of the total volume of the putter **900**, less than 30% of the total volume of the putter **900**, less than 29% of the total volume of the putter **900**, less than 28% of the total volume of the putter **900**, or less than 27% of the total volume of the putter **900**.

[0232] Although the lower portion **908** comprises less than half of the volume of the putter **900**, the lower portion **908** comprises at least 45% of an overall mass of the putter **900**. In some embodiments, the lower portion **908** comprises at least 46% of the mass of the putter **900**, at least 46% of the mass of the putter **900**, at least 47% of the mass of the putter **900**, at least 48% of the mass of the putter **900**, at least 49% of the mass of the putter **900**, at least 50% of the mass of the putter **900**, at least 51% of the mass of the putter **900**, at least 52% of the mass of the putter **900**, at least 53% of the mass of the putter **900**, at least 54% of the mass of the putter **900**, or at least 55% of the mass of the putter **900**.

[0233] The beneficial shift of mass to the periphery of the putter head **900**, through the use of a high density, low volume lower portion **908**, increases the MOI of the putter **900**, over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single stainless steel block, or a putter investment cast of a single material).

h. Circular Embodiment

[0234] In another embodiment, the putter-type golf club head **1000** can be a circular shaped putter head **1000**. Referring to FIG. 10A-10C, the circular putter head **1000** has an upper portion **1004** and a lower portion **1008**. The lower portion **1008** is made from a first material have a first density and the upper portion **1004** is made from a second material having a second density. The first density is less than the second density. The upper portion **1004** and lower portion **1008** combine to create a high-MOI putter head **1000** (5000 g·cm²-6500 g·cm²), while maintaining a desirable volume and mass.

[0235] As discussed above, the upper portion **1004** is comprised of a high-density material (i.e., the second material). The upper portion **1004** comprises a toe end **1012**, a heel end **1016**, a strike face **1020**, a rear wall **1032**, and an under surface (not pictured). The toe end **1012** is opposite the heel end **1016**. The strike face **1020** spans from the toe end **1012** to the heel end **1016** and is opposite the rear wall

1032. The rear wall **1032** is opposite, and approximately parallel to the strike face **1020**.

[0236] The upper portion **1004** further comprises a toe side span **1056**, and a heel side span **1060**. The toe side span **1056** is adjacent to the toe end **1012** and opposite and to the heel side span **1060**. The heel side span **1060** is also adjacent to the heel end **1016** and opposite to the toe side span **1056**. In some embodiments, the heel side span **1060** and toe side span **1056** can be parallel, while in some embodiments, the heel side span **1060** and toe side span **1056** are not parallel. The toe side span **1056** and heel side span **1060**, extend perpendicularly away from the rear wall **1032**, in a direction away from the rear wall **1032**, and strike face **1020**.

[0237] In most embodiments, the toe side span **1056** extends perpendicularly from rear wall **1032** such that a right angle (90° angle) is formed at the junction of the toe side span **1056** and the rear wall **1032**. However, in other embodiments, the toe side span **1056** can extend from the rear wall **1032** in any direction, such that any angle (0°-180°) can be formed at the junction of the toe side span **1056** and the rear wall **1032**. Further, in most embodiments, the heel side span **1060** extends perpendicularly from the rear wall **1032**, such that a right angle (90° angle) is formed at the junction of the heel side span **1060** and the rear wall **1032**. However, in other embodiments, the heel side span **1060** can extend from the rear wall **1032** in any direction, such that any angle (0°-180°) can be formed at the junction of the heel side span **1060** and the rear wall **1032**.

[0238] The rear wall **1032**, toe side span **1056**, and heel side span **1060** form a gap **1064**. The gap **1064** is bounded by the rear wall **1032**, the toe side span **1056**, and the heel side span **1060**. The gap **1064** formed by the rear wall **1032**, the toe side span **1056**, and the heel side span **1060** shifts a majority of the volume and mass of the putter to the extremities of the upper portion **1008**. The gap **1064** can comprise any shape, however in one embodiment the gap is approximately rectangular. In other embodiments, the gap **1064** can be circular, curvilinear, triangular, trapezoidal, parabolic, golf ball shaped, square, or any other desired geometric shape.

[0239] The lower portion **1008** of the putter head **1000** comprises a front edge **1041**, a rear edge **1034**, a toe edge **1043**, and a heel edge **1045**. The front edge **1041** is adjacent to the toe edge **1043** and the heel edge **1045**, and opposite to the rear edge **1034**. The toe edge **1034** is adjacent to the front edge **1041** and rear edge **1034**, and opposite to the heel edge **1045**. The heel edge **1045** is also adjacent to the front edge **1041** and the rear edge **1034**, and opposite to the toe edge **1043**. In some embodiments, the toe edge **1043** and heel edge **1045** can be parallel, while in some embodiments, the toe edge **1043** and heel edge **1045** are not parallel. In some embodiments, the front edge **1041** and rear edge **1034** can be parallel, while in some embodiments, the front edge **1041** and rear edge **1034** are not parallel.

[0240] The front edge **1041**, rear edge **1034**, toe edge **1043**, and heel edge **1045** join to form an aperture **1065**, wherein the aperture **1065** is bounded by the four edges (front **1041**, rear **1034**, toe **1043**, heel **1045**). The four edges **1041**, **1034**, **1043**, **1045**, form a perimeter around the aperture **1065**.

[0241] In some embodiments, the aperture **1065**, formed by the front edge **1041**, rear edge **1034**, toe edge **1043**, and heel edge **1045** can be any one of the following shapes: rectangular, triangular, semi-circular, circular (golf ball

sized), circular (larger than a golf ball), circular (smaller than a golf ball), square, ovular, elliptical, trapezoidal, pentagonal, hexagonal, octagonal, or any other desired geometric or non-geometric shape.

[0242] Referring to FIG. 10C, the lower portion **1008** is affixed to the upper portion **1004** such that a portion of the upper portion **1004** and the lower portion **1008** intersect a ground plane **1072**. The ground plane **1072** is tangent to the lower portion **1004**, when the putter head **1000** is at an address position to strike a golf ball.

[0243] Further, the strike face **1020** of the putter head **1000** comprises a strike face center point **1076** and a loft plane **1080**. The strike face center point **1076** is equidistant from a top rail **1050** and the ground plane **1072** of the upper portion **1004**, wherein the top rail **1050** is adjacent the strike face **1020** and the rear wall **1032**, while opposite the ground plane **1072**. The strike face center point **1076** is also equidistant from the heel end **1016** and toe end **1012** of the putter head **1000**. The loft plane **1080** is tangent to the strike face **1020** of the putter head **1000**. Further, a midplane **1084** intersects the strike face center point **1076** and is perpendicular to the loft plane **1080**. Furthermore, a y-axis **1088** intersects the midplane **1084**, and is perpendicular to the ground plane **1072**.

[0244] When the upper portion **1004** and lower portion **1008** are joined such that the toe side span **1056** overlays at least a portion of the toe edge **1043**. Further, when the upper portion **1004** and lower portion **1008** are joined such that the heel side span **1060** overlays at least a portion of the heel edge **1045**. Further still, when the upper portion **1004** and lower portion **1008** are joined such that the strike face **1020** overlays at least a portion of the front edge **1048**. Finally, when the upper portion **1004** and lower portion **1008** are joined such that the lower portion **1008** is affixed to a portion of the strike face **1020**, toe side span **1056**, and heel side span **1060**, thereby filling at least a portion of the gap **1064** formed by the rear wall **1032**, toe side span **1056**, and heel side span **1060**.

[0245] The lower portion **1008**, and the toe side span **1056** and heel side span **1060** of the upper portion **1004**, when combined create a sole **1068**. The sole **1068** is perpendicular to the ground plane **1072**, wherein the ground plane **1072** is tangent to the sole **1068**, when the putter head **1000** is at an address position to strike a golf ball. The sole **1068** of the putter head **1000** extends from the toe end **1012** of the putter head **1000** to the heel end **1016** of the putter head **1000**.

[0246] In most embodiments, the sole **1068** of the putter head **1000** can be perfectly flat. In some embodiments, the sole **1068** of the putter head **1000** can have a slight arch in a heel **1016** to toe **1012** direction, wherein the slight arch can be linear, or a function of a polynomial. In some embodiments, the sole **1068** of the putter head **1000** can have a strong arch in the heel **1016** to toe **1012** direction, wherein the strong arch can be linear, or a function of a polynomial. The sole **1068** functions to provide a surface to rest the putter head **1000** on the ground plane **1072**.

[0247] In some embodiments, the upper portion **1004** can further comprise a crown (not shown). The crown extends away from the strike face **1020** to the back edge **1034** of the lower portion **1008**. Furthermore, the crown, spans from the strike face **1020** to the back edge **1034**, at least over a portion of the aperture **1065** of the lower portion and at least over a portion of the rear wall **1032**.

[0248] The crown can further descend from the strike face **1020** to the back edge **1034**. The crown, in most embodiments, spans approximately inward 25% of the total club head **1000** width from the toe side span **1056** and spans approximately inward 25% of the total club head **1000** width from the heel side span **1060**. In other embodiments, the crown can, continuously or discontinuously, span the entire width of the total club head **1000**, in a heel to toe direction. In some embodiments, the crown, can span less than 90% of the total width of the club head **1000**, less than 90% of the total width of the club head **1000**, less than 80% of the total width of the club head **1000**, less than 70% of the total width of the club head **1000**, less than 60% of the total width of the club head **1000**, less than 50% of the total width of the club head **1000**, less than 40% of the total width of the club head **1000**, or less than 30% of the total width of the club head **1000**. Further, in some embodiments, the crown can be substantially flat from the strike face **1020** to the back edge **1034** or ascend from the strike face **1020** to the back edge **1034**. In most embodiments, the ascent or descent of the crown can be linear, curvilinear, parabolic, sinusoidal, or a function of polynomial.

[0249] Furthermore, the upper portion **1004** of the putter head **1000** can comprise one or more alignment features **1044** on the toe side span **1065** and the heel side span **1060**. The alignment feature **1044** can be any one or combination of the following: a line, a series of lines, milling troughs, a circle, a dashed line, a triangle, a channel, or any other desired alignment feature **1044**. The alignment features **1044** can be equally spaced on the entire toe side span **1065** and the heel side span **1060**, a portion of the crown, or the entire crown. The alignment features **1044**, extending along the toe side span **1056** and the heel side span **1060**, function to provide the viewer a visual alignment field that extends the width of the golf ball, from the rear wall **1032** to the back edge **1034** of the putter **1000**. The goal is to align the entire putter **1000** with the golf ball using these alignment features **1044** along the toe side span **1056** and the heel side span **1060** and/or the crown.

[0250] The combination of the high density first material upper portion **1004** with the low density second material lower portion **1008**, creates a high MOI putter **1000**, without creating an extremely heavy putter. The large gap **1064** formed by the rear wall **1032** and the spans **1056**, **1060** of the upper portion **1004** forms a dense, yet low wide periphery that increases the MOI of the putter, in comparison to a putter milled from a single material. A single material putter fails to allocate high density material to the periphery, while maintaining a desirable volume (75 cc-100 cc) and mass (340 grams-385 grams).

[0251] The beneficial shift of mass to the periphery of the putter head **1000**, through the use of a high density, upper portion **1008**, and low volume low mass lower portion **100**, increases the MOI of the putter **1000**, over a putter with the same volume, mass, and single material construction (i.e., a putter milled of a single stainless steel block, or a putter investment cast of a single material).

[0252] Replacement of one or more claimed elements constitutes reconstruction and not repair. Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more pronounced, however, are not to be

construed as critical, required, or essential features or elements of any or all of the claims.

[0253] As the rules to golf may change from time to time (e.g., new regulations may be adopted or old rules may be eliminated or modified by golf standard organizations and/or governing bodies such as the United States Golf Association (USGA), the Royal and Ancient Golf Club of St. Andrews (R&A), etc.), golf equipment related to the apparatus, methods, and articles of manufacture described herein may be conforming or non-conforming to the rules of golf at any particular time. Accordingly, golf equipment related to the apparatus, methods, and articles of manufacture described herein may be advertised, offered for sale, and/or sold as conforming or non-conforming golf equipment. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

[0254] The above examples may be described in connection with a putter-type golf club, the apparatus, methods, and articles of manufacture described herein. Alternatively, the apparatus, methods, and articles of manufacture described herein may be applicable other type of sports equipment such as a hockey stick, a tennis racket, a fishing pole, a ski pole, etc.

[0255] Moreover, embodiments and limitations disclosed herein are not dedicated to the public under the doctrine of dedication if the embodiments and/or limitations: (1) are not expressly claimed in the claims; and (2) are or are potentially equivalents of express elements and/or limitations in the claims under the doctrine of equivalents.

[0256] Clause 1: A putter type golf club head comprising: an upper portion and a lower portion; wherein the upper portion is made from a first material having a first density and the lower portion is made from a second material having a second density; wherein the first density is less than the second density; the lower portion comprises a front periphery, a toe side periphery, a heel side periphery, and a rear periphery; wherein the lower portion further comprises an aperture bounded by the front periphery, toe side periphery, heel side periphery, and rear periphery; the upper portion comprises a heel end, a toe end, a strike face, a rear wall, a back edge, a crown, and an under surface; wherein the toe end is opposite the heel end, the back edge is opposite the strike face; the crown extends away from the strike face, over at least a portion of the rear wall, and to the back edge; the under surface is opposite the crown spanning from the strike face to the back edge; the upper portion is affixed to the lower portion, and is farther from a ground plane than the lower portion, wherein the heel end overlays at least a portion of the heel side periphery, the toe end overlays at least a portion of the toe side periphery, the strike face overlays at least a portion of the front periphery, and the crown spans from the strike face to the rear periphery; the lower portion and upper portion combine to create a sole; wherein the sole is tangent to the ground plane, when the golf club head is at an address position; the strike face is tangent to a loft plane, wherein a loft angle formed between the loft plane and the ground plane; a volume and a mass; wherein the lower portion comprises less than 30% of the volume of the golf club head; and wherein the lower portion comprises greater than 50% of the mass of the golf club head.

[0257] Clause 2: The putter type golf club head of clause 1, wherein the lower portion further comprises: a toe mass at the junction of the toe side periphery and the rear

periphery; a heel mass at the junction of the heel side periphery and the rear periphery; a rear mass positioned on the rear periphery, equidistance from the toe side periphery and the heel side periphery; and a front mass positioned on the front periphery, equidistance from the toe side periphery and the heel side periphery.

[0258] Clause 3: The putter type golf club head of clause 2, wherein the toe mass, heel mass, rear mass, and front mass are integral and extend away from the lower portion, in a direction away from the ground plane and toward the upper portion.

[0259] Clause 4: The putter type golf club head of clause 1, wherein the crown, of the upper portion, further comprises a toe end mid-rail, a heel end mid-rail, a toe end cap, and a heel end cap.

[0260] Clause 5: The putter type golf club head of clause 4, wherein the toe end cap is configured to mate with the toe mass and the heel end cap is configured to mate with the heel mass.

[0261] Clause 6: The putter type golf club head of clause 5, wherein the upper portion further comprises a first cavity, wherein the first cavity is formed in the under surface, between the strike face and the rear wall, and extends in a direction towards the crown; and a second cavity, wherein the rear aperture is formed in the under surface, adjacent the back edge, and equidistant between the toe end cap and the heel end cap.

[0262] Clause 7: The putter type golf club head of clause 6, wherein the first cavity is configured to mate with the front mass, and the second cavity is configured to mate with the rear mass.

[0263] Clause 8: The putter type golf club head of clause 4, wherein the toe end mid-rail and heel end mid-rail descend from the strike face to the rear periphery.

[0264] Clause 9: The putter type golf club head of clause 4, wherein the heel end mid-rail and the toe end mid-rail comprise one or more alignment features on the heel end mid-rail and the toe end mid-rail.

[0265] Clause 10: The putter type golf club head of clause 9, wherein the one or more alignment features can be unequally or equally spaced apart from the strike face to the rear periphery.

[0266] Clause 11: The putter type golf club head of clause 1, wherein the front periphery, of the lower portion, comprises a front width measured from the junction of the toe side periphery and the front periphery, to the junction of the heel side periphery and the front periphery;

[0267] Clause 12: The putter type golf club head of clause 11, wherein the rear periphery, of the lower portion, comprises a rear width measured from the junction of the toe side periphery and the rear periphery, to the junction of the heel side periphery and the rear periphery.

[0268] Clause 13: The putter type golf club head of clause 12, wherein the front width is greater than the rear width.

[0269] Clause 14: The putter type golf club head of clause 1, wherein one or more alignment feature is positioned on the crown.

[0270] Clause 15: The putter type golf club head of clause 1, wherein the first density of the first material is less than 6.0 g/cc.

[0271] Clause 16: The putter type golf club head of clause 1, wherein the second density of the second material is greater than 7.0 g/cc.

[0272] Clause 17: The putter type golf club head of clause 1, wherein the second density of the second material is at least 2 times greater than the first density of the first material.

[0273] Clause 18: The putter type golf club head of clause 1, wherein the first material can comprise any one or combination of the following: 8620 alloy steel, S25C steel, carbon steel, maraging steel, 17-4 stainless steel, 303 stainless steel, 304 stainless steel, stainless steel alloy, tungsten, aluminum, aluminum alloy, ADC-12, or any metal suitable for creating a golf club head.

[0274] Clause 19: The putter type golf club head of clause 1, wherein the second material can comprise any one or combination of the following: 8620 alloy steel, S25C steel, carbon steel, maraging steel, 17-4 stainless steel, 303 stainless steel, 304 stainless steel, stainless steel alloy, tungsten, aluminum, aluminum alloy, ADC-12, or any metal suitable for creating a golf club head.

[0275] Clause 20: The putter type golf club head of clause 1, wherein the first material is ADC-12 and the second material is 304 stainless steel.

What is claimed is:

1. A putter type golf club head comprising:
 - an upper portion and a lower portion;
 - wherein the upper portion is made from a first material having a first density and the lower portion is made from a second material having a second density;
 - wherein the first density is less than the second density;
 - the lower portion comprises a toe mass and a heel mass, and defines a loft plane;
 - wherein the toe mass and the heel mass are integral to the lower portion; and
 - the toe mass and heel mass extend from the lower portion, in a direction away from a ground plane, and toward the upper portion; and
 - the upper portion is affixed to the lower portion, is farther from a ground plane than the lower portion, and is spaced rearward from the loft plane, such that the lower portion does not reside along the loft plane;
 - a volume and a mass;
 - wherein the lower portion comprises less than 30% of the volume of the putter type golf club head; and
 - wherein the lower portion comprises greater than 50% of the mass of the putter type golf club head.
 - 2. The putter type golf club head of claim 1, wherein the first density of the first material is less than 6.0 g/cc.
 - 3. The putter type golf club head of claim 1, wherein the second density of the second material is greater than 7.0 g/cc.
 - 4. The putter type golf club head of claim 1, wherein the second density of the second material is at least 2 times greater than the first density of the first material.
 - 5. The putter type golf club head of claim 1, wherein the first material comprises any one or a combination of the following: 8620 alloy steel, S25C steel, carbon steel, maraging steel, 17-4 stainless steel, 303 stainless steel, 304 stainless steel, stainless steel alloy, tungsten, aluminum, aluminum alloy, ADC-12, or any metal suitable for creating a golf club head.
 - 6. The putter type golf club head of claim 1, wherein the second material comprises any one or a combination of the following: 8620 alloy steel, S25C steel, carbon steel, maraging steel, 17-4 stainless steel, 303 stainless steel, 304 stain-

less steel, stainless steel alloy, tungsten, aluminum, aluminum alloy, ADC-12, or any metal suitable for creating a golf club head.

7. The putter type golf club head of claim 1, wherein the first material is ADC-12 and the second material is 304 stainless steel.

8. A putter type golf club head comprising:

an upper portion and a lower portion;

wherein the upper portion is made from a first material having a first density and the lower portion is made from a second material having a second density;

wherein the first density is less than the second density; the lower portion comprises a toe end, a heel end opposite the toe end, a front surface, a rear wall opposite the front surface, a rear portion, and an under surface;

wherein a recess extends inward from the front surface towards the rear wall;

the upper portion comprises a hitting surface, an adhesion surface opposite the hitting surface, and a lower edge; wherein the lower edge protrudes in a direction away from the hitting surface;

wherein the adhesion surface is affixed within the recess of the lower portion;

wherein the front surface and the hitting surface align to form a strike face;

wherein the putter type golf club head comprises a sole formed by the lower edge of the upper portion and the under surface of the lower portion; and

wherein the first material and the second material are both metallic materials.

9. The putter type golf club head of claim 8, further comprising a center of gravity and a y-axis extending vertically through the center of gravity;

wherein a moment of inertia measured about the y-axis is at least 15% greater than a similar putter constructed of a single material and comprising identical mass and volume.

10. The putter type golf club head of claim 8, wherein the first material comprises any one or a combination of the following: 8620 alloy steel, S25C steel, carbon steel, maraging steel, 17-4 stainless steel, 303 stainless steel, 304 stainless steel, stainless steel alloy, tungsten, aluminum, aluminum alloy, or ADC-12.

11. The putter type golf club head of claim 8, wherein the second material comprises any one or a combination of the following: 8620 alloy steel, S25C steel, carbon steel, maraging steel, 17-4 stainless steel, 303 stainless steel, 304 stainless steel, stainless steel alloy, tungsten, aluminum, aluminum alloy, and ADC-12.

12. The putter type golf club head of claim 8, wherein the first density of the first material is less than 6.0 g/cc.

13. The putter type golf club head of claim 8, wherein the second density of the second material is greater than 7.0 g/cc.

14. The putter type golf club head of claim 8, wherein the upper portion comprises an alignment feature selected from the group consisting of: a line, a circle, a dashed line, a triangle, and a channel.

15. The putter type golf club head of claim 8, wherein the lower portion comprises an alignment feature selected from the group consisting of: a line, a circle, a dashed line, a triangle, and a channel.

16. The putter type golf club head of claim 8, wherein the club head comprises a heel-to-toe moment of inertia between $5000 \text{ g}\cdot\text{cm}^2$ - $6500 \text{ g}\cdot\text{cm}^2$.

17. The putter type golf club head of claim 8, wherein the adhesion surface and the hitting surface are parallel.

18. The putter type golf club head of claim 8, wherein the rear wall does not make up a portion of the sole.

19. The putter type golf club head of claim 8, wherein the upper portion and lower portion are joined in any one or combination of the following methods: welding, soldering, brazing, swedging, adhesion, epoxy, or mechanical fastening.

* * * * *