

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250263287

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Melkonian; Arman et al.

---

### **VARIABLE TEMPERATURE CONTROL ASSEMBLY FOR A WATER DISPENSER**

---

#### **Abstract**

A variable temperature control assembly for a water dispenser, using a variable water temperature selector, that delivers water to the consumer at the temperature requested on the variable temperature selector by calculating the required ratio of hot water, cold water and ambient water needed to deliver water at the temperature requested.

---

**Inventors:** Melkonian; Arman (La Cañada Flintridge, CA), Melkonian; Mark (Northridge, CA), Sawhney; Ravi (Malibu, CA), Steele; Craig (Manhattan Beach, CA), Patel; Samaykumar (Santa Clarita, CA), Kulick; Michael (Simi Valley, CA)

**Applicant:** Brio Water Technology, Inc. (City of Industry, CA)

**Family ID:** 1000008770540

**Assignee:** Brio Water Technology, Inc. (City of Industry, CA)

**Appl. No.:** 18/883804

**Filed:** September 12, 2024

#### **Related U.S. Application Data**

parent US continuation 18581130 20240219 parent-grant-document US 12168600 child US 18883804

---

#### **Publication Classification**

**Int. Cl.:** B67D1/12 (20060101); B67D1/00 (20060101)

**U.S. Cl.:**

## Background/Summary

REFERENCE TO RELATED APPLICATION [0001] This application is a continuation of, and claims priority from, application U.S. Ser. No. 18/581,130 filed on Feb. 19, 2024.

### BACKGROUND

[0002] Currently, when a user requests a specific water temperature for his dispensed water, it is often frustrating because the water dispensed is not the temperature requested. To attempt to achieve a requested water temperature, most current water dispensers mix fixed ratios of hot, cold or ambient temperature water from tanks, but the fixed ratios may not create the exact temperature requested because the water temperature in one or all of the tanks may have varied for a number of reasons. This method essentially amounts to guessing and hoping the water dispensed is not too far off from what the dispenser user is expecting and is “good enough”.

[0003] Some systems have tried to address this issue by variably mixing hot and cold water on-the-fly at the time of the user's requests. These systems mix the hot and cold water at the time of dispensing and have a sensor to measure the temperature of the mixed water at the dispensing point. By doing this, these systems create a feedback loop and adjust the temperature of the dispensed water by adjusting the hot and cold mixing ratio to try to get the water to the temperature requested. These systems also, usually, come up short. The time between mixing and dispensing is so short that the feedback loop usually has a lag, and the on-the-fly variable mixing can have a wide temperature range between selectable temperatures. As a result, the user typically selects between a set of limited buttons that provide for approximate pre-programmed temperatures when depressed. These systems are not capable of providing the precise water temperature that the user desires. These trial-and-error type approaches also have the potential of wasting water.

[0004] Accordingly, there is a need for a water dispenser that allows a user to select almost any dispensing water temperature, and the dispenser is capable of providing water, in real-time, at the temperature, or very near the temperature, requested.

### SUMMARY

[0005] According to one aspect of the present invention, a variable temperature control assembly for use in a water dispenser includes a variable temperature selector; a hot water system, which includes a hot water tank and a hot water solenoid, where the hot water solenoid is in communication with the hot water tank; a cold water system, which includes a cold water tank and a cold water solenoid, where the cold water solenoid is in communication with the hot water tank; and a processor, in communication with the variable temperature selector, the hot water solenoid and the cold water solenoid, capable of determining the ratio of hot water and cold water required to deliver water at a temperature selected on the variable temperature selector. When a user selects a temperature to dispense water at on the variable temperature selector and based on the input received from the variable temperature selector, the processor determines the temperature of water in the hot water tank and the temperature of the water in the cold water tank and using the determined temperatures of the water in the hot water tank and the water in the cold water tank, calculates the ratio of hot water and cold water required to deliver water at the temperature selected on the variable temperature selector and sends a signal to each of the hot water solenoid and the cold water solenoid to dispense water at the determined ratio.

[0006] According to another aspect of the present invention, a variable temperature control assembly for use in a water dispenser, includes a variable temperature selector; a hot water system, which includes a hot water tank and a hot water solenoid, where the hot water solenoid is in

communication with the hot water tank; a cold water system, which includes a cold water tank and a cold water solenoid, where the cold water solenoid is in communication with the hot water tank; an ambient water system, which includes an ambient water tank and an ambient water solenoid, where the ambient water solenoid is in communication with the ambient water tank; a processor, in communication with the variable temperature selector, the hot water solenoid, the cold water solenoid and the ambient water solenoid, capable of determining the ratio of hot water, cold water and ambient water required to deliver water at a temperature selected on the variable temperature selector; and a mixing chamber in fluid communication with the hot water solenoid, the cold water solenoid and the ambient water solenoid. When a user selects a temperature to dispense water at on the variable temperature selector and based on the input received from the variable temperature selector, the processor determines the temperature of water in the hot water tank, the temperature of the water in the cold water tank and the temperature of the water in the ambient water tank and using the determined temperatures of the water in the hot water tank, the water in the cold water tank and the water in the ambient water tank, calculates the ratio of hot water, cold water and ambient water required to deliver water at the temperature selected on the variable temperature selector and sends a simultaneous one-time signal to each of the hot water solenoid, the cold water solenoid and the ambient water solenoid to release water into the mixing chamber at the determined ratio in order to dispense water at the selected temperature.

[0007] According to yet another aspect of the present invention, a method for delivering water at a specific requested temperature in a water dispenser includes the steps of providing a variable temperature control assembly, having a variable temperature selector; a hot water system, having a hot water tank and a hot water solenoid, where the hot water solenoid is in communication with the hot water tank; a cold water system, having a cold water tank and a cold water solenoid, where the cold water solenoid is in communication with the cold water tank; a processor, in communication with the variable temperature selector, the hot water solenoid and the cold water solenoid capable of determining the ratio of hot water and cold water required to deliver water at a temperature selected on the variable temperature selector; selecting a temperature to dispense water at on the variable temperature selector; sending a signal to the processor based on the requested water temperature input received from the variable temperature selector; determining the temperature of water in the hot water tank and the temperature of the water in the cold water tank; calculating the ratio of hot water and cold water required to deliver water at the requested water temperature using the determined temperatures of the water in the hot water tank and the water in the cold water tank; simultaneously sending a one-time signal to each of the hot water solenoid and the cold water solenoid to dispense water at the determined ratio; and dispensing water at the requested water temperature.

---

## **Description**

### **DRAWINGS**

[0008] Objects, features, and advantages of the present invention will become apparent upon reading the following description in conjunction with the drawing figures, in which:

[0009] FIG. 1 is a front perspective view of a water dispenser utilizing an embodiment of a variable temperature control assembly of the present invention;

[0010] FIG. 2 illustrates a functional block diagram an embodiment of a variable temperature control assembly of the present invention disposed in a water dispenser;

[0011] FIG. 3 is a partial front view of a water dispenser utilizing an embodiment of a variable temperature control assembly of the present invention showing the interior components of the water dispenser;

[0012] FIG. 4 is a partial right side view of a water dispenser utilizing an embodiment of a variable

temperature control assembly of the present invention showing some of the interior components of the water dispenser;

[0013] FIG. 5 is a left side view of a water dispenser utilizing an embodiment of a variable temperature control assembly of the present invention showing the interior components of the water dispenser;

[0014] FIG. 6 is a flowchart illustrating an embodiment of a process of the present invention to maintain water in a state ready to dispense water;

[0015] FIG. 7 depicts a capacitive touch temperature slider used in an embodiment of a variable temperature control assembly of the present invention; and

[0016] FIG. 8 is a flowchart illustrating an embodiment of a process of the present invention to mix water to a certain selected temperature.

#### DESCRIPTION

[0017] Referring to FIGS. 1-2, an exemplary water dispenser **20** utilizing an embodiment of a variable temperature control assembly **30** of the present invention is depicted. In this exemplary water dispenser **20**, the water dispenser **20** has, among other things, a user interface **22**, for the user to select what temperature is desired and to dispense water, and a water dispensing nozzle **24**.

Referring now to FIG. 2, a functional block diagram of an embodiment of the variable temperature control assembly **30** of the present invention, housed in the water dispenser **20**, is depicted. The variable temperature control assembly **30** in this embodiment includes three water tanks: a hot water tank **40**, an ambient water tank **42** and a cold water tank **44**. The variable temperature control assembly **30** includes three tanks in this embodiment, but it should be understood that the variable temperature control assembly **30** of the present invention could include any number of water tanks, and the tanks could be any combination of temperatures of tanks (e.g. two hot and two cold or one hot and one cold with no ambient, etc.). Each water tank **40**, **42**, **44** connects to a water supply **46** for the water dispenser **20**, such as a tap water source, that supplies water **48** to the water tanks **40**, **42**, **44**. Also, in this embodiment, the water **48** from the water supply **46** goes through a filtration system **50** before a water pump **52** pumps the water **48** to the water tanks **40**, **42**, **44**.

[0018] The variable temperature control assembly **30**, in this embodiment, includes a hot water system **60**, an ambient water system **62** and a cold water system **64**. The hot water system **60** includes the hot water tank **40**, a hot water pump **70**, a hot water variable solenoid **72** and piping **74** that connects the hot water tank **40**, the hot water pump **70** and the hot water variable solenoid **72** and carries hot water **78** between these components. Disposed within the hot water tank **40**, in this embodiment, are a hot water temperature sensor **80**, a high water level sensor **82**, a low water level sensor **84** and a heating coil **86**. The ambient water system **62** includes the ambient water tank **42**, an ambient water pump **90**, an ambient water variable solenoid **92** and piping **94** that connects the ambient water tank **42**, the ambient water pump **90** and the ambient water variable solenoid **92** and carries ambient water **98** between these components. Disposed within the ambient water tank **42**, in this embodiment, are an ambient water temperature sensor **100**, a high water level sensor **102**, a low water level sensor **104**. Further, the cold water system **64** includes the cold water tank **44**, a cold water pump **110**, a cold water variable solenoid **112** and piping **114** that connects the cold water tank **44**, the cold water pump **110** and the cold water variable solenoid **112** and carries cold water **118** between these components. Disposed within the cold water tank **44**, in this embodiment, are a cold water temperature sensor **120**, a high water level sensor **122**, a low water level sensor **124**. The cold water system **64** further includes a chiller system **126** that connects with chiller coils **128** that are disposed outside of the cold water tank **44**. The chiller system **126** chills a refrigerant that circulates through the chiller coils **128** to chill the water **48** in the cold water tank **44**. It should be understood that any method or system to chill water **48** in the cold water tank **44** may be employed.

[0019] The variable temperature control assembly **30** of this embodiment of the present invention further includes a processor **130** which receives input signals from and sends output signals to the

components of the water dispenser **20** (e.g. user interface **22**; water pump **52**; filtration system **50**; chiller system **126**; chiller coils **128**; heating coil **86**; hot water temperature sensor **80**; ambient water temperature sensor **100**; cold water temperature sensor **120**; high water level sensors **82**, **102**, **122**; low water level sensors **84**, **104**, **124**; cold water pump **110**; hot water pump **70**; ambient water pump **90**; cold water variable solenoid **112**, hot water variable solenoid **72** and ambient water variable solenoid **92**). The processor **130** further has other functions, including storing data; making computations and issuing component commands to allow the variable temperature control assembly **30** to function and, generally, to keep the water dispenser **20** operating.

[0020] FIGS. 3-5 illustrate an embodiment of a water dispenser **20** utilizing a variable temperature control assembly **30** of the present invention. Referring now to FIGS. 6-9, the process of how the variable temperature control assembly **30** of the present invention functions is illustrated and described. In FIG. 7, at step **200**, the processor **130** of the water dispenser **20** continuously monitors the water level and temperature of the water **48** in the hot water tank **40**, the ambient water tank **42** and the cold water tank **44**. The processor **130** continuously monitors this information so the processor **130** knows at any given moment the temperatures in each water tank **40**, **42**, **44**. The processor **130** uses that information, as explained below, to mix and deliver water **48** to the user at the precise temperature requested.

[0021] For the hot water tank **40**, at step **202**, the processor **130**, using the water level sensors **82**, **84**, continuously checks to see if the water level of the water **78** in the hot water tank **40** is within pre-set high and low limits. If the water level of the water **78** is outside the pre-set limits, at step **206**, the processor **130** adjusts the water level in the hot water tank **40** to bring it within pre-set high and low limits. At step **202**, if the water level in the hot water tank **40** is within the pre-set limits, the processor **130** does nothing and does not adjust the water level. At step **204**, the processor **130**, using the water temperature sensor **80**, continuously checks to see if the water temperature of the water **78** in the hot water tank **40** is below a pre-set lower limit. If it is below this pre-set lower limit, that means the water **78** is not hot enough and needs to be heated. The water **78** may get cool for a number of reasons, including the water **78** has been sitting for a while or users of the water dispenser **20** have dispensed water; lowering the water level in the hot water tank **40** and causing it to be filled with ambient water **48**. At step **204**, if the water temperature in the hot water tank **40** is above the pre-set lower limit, that means the water **78** is appropriately heated and does not need to be adjusted.

[0022] For the ambient water tank **42**, at step **210**, the processor **130**, using the water level sensors **102**, **104**, continuously checks to see if the water level of the water **98** in the ambient water tank **42** is within pre-set high and low limits. If the water level of the water **98** is outside the pre-set limits, at step **210**, the processor **130** adjusts the water level in the ambient water tank **42** to bring it within pre-set high and low limits. At step **210**, if the water level in the ambient water tank **42** is within the pre-set limits, the processor **130** does nothing and does not adjust the water level. Further, for the cold water tank **44**, at step **214**, the processor **130**, using the water level sensors **122**, **124**, continuously checks to see if the water level of the water **118** in the cold water tank **44** is within pre-set high and low limits. If the water level of the water **118** is outside the pre-set limits, at step **210**, the processor **130** adjusts the water level in the cold water tank **44** to bring it within pre-set high and low limits. At step **214**, if the water level in the cold water tank **44** is within the pre-set limits, the processor **130** does nothing and does not adjust the water level. At step **216**, the processor **130**, using the water temperature sensor **120**, continuously checks to see if the water temperature of the water **118** in the cold water tank **44** is above a pre-set higher limit. If it is above this pre-set higher limit, that means the water **118** is not cool enough and needs to be cooled. The water **118** may get warm for a number of reasons, including the water **118** has been sitting for a while or users of the water dispenser **20** have dispensed water; lowering the water level in the cold water tank **44** and causing it to be filled with ambient water **48**. At step **216**, if the water temperature in the cold water tank **40** is below the pre-set higher limit, that means the water **118** is

appropriately cooled and does not need to be adjusted.

[0023] Referring now to FIG. 7, in this embodiment, the user interface **22** includes a capacitive touch temperature slider **230** having a selector **232**. The capacitive touch temperature slider **230** allows a user to choose from any mix of cold and hot water. If the user slides the selector **232** one end of the capacitive touch temperature slider **230**, the water dispensed will be at the coldest temperature the water dispenser **20** can generate. If the user slides the selector **230** to the other end of the capacitive touch temperature slider **230**, the water dispensed will be at the hottest temperature the water dispenser **20** can generate. If the user selects anywhere in the between the two ends of the of the capacitive touch temperature slider **230**, the variable temperature control assembly **30** of the present invention will mix and dispense the water the temperature selected, as described in FIG. 8. Once the user selects a temperature that he wants the water to dispensed at using the selector **232** (Step **300**), at step **302**, the processor **130**, which has been continually monitoring the water temperatures of the water tanks **40**, **42**, **44** using the water temperature sensors **80**, **100**, **120** determines the present temperature of each of the water tanks **40**, **42**, **44**. At step **304**, using the present temperature of the water in each water tank **40**, **42**, **44**, the processor **130** calculates the ratio of water needed from each water tank **40**, **42**, **44** to deliver the water at the precise temperature the user selected with the selector **232**. With the ratio calculated for each water tank **40**, **42**, **44**, the processor **130** sends a signal simultaneously to the variable solenoid **72**, **92**, **112** associated with each water tank **40**, **42**, **44** (Steps **306**, **310**, **314**). At steps **308**, **312**, **316**, the variable solenoids **72**, **92**, **112** dispense the exact amount of water, signaled by the processor **130**, from their respective water tanks **40**, **42**, **44** into the mixing chamber **24** (i.e. the hot water variable solenoid **72** dispenses the water **78** it was signaled to release from the hot water tank **40**; the ambient water variable solenoid **92** dispenses the water **98** it was signaled to release from the ambient water tank **42**; and the cold water variable solenoid **112** dispenses the water **118** it was signaled to release from the cold water tank **44**.) At step **318**, the mixing chamber **132** receives the water **78**, **98**, **118** from the variable solenoids **72**, **92**, **112** and the water **78**, **98**, **118** mixes water together to get the water to the temperature requested by the user. After mixing in the mixing chamber **132**, at step **320**, the mixed water is dispensed to the user through the water dispensing nozzle **24**. By preparing, mixing and dispensing the water in this manner, no feedback sensor or feedback loop is needed to get the user water at the precise temperature requested.

[0024] Although certain embodiments and features of a variable temperature control assembly have been described herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all embodiments of the teachings of the disclosure that fairly fall within the scope of permissible equivalents.

## Claims

1. A variable temperature control assembly, for use in a water dispenser having a water dispensing nozzle through which an amount of water at a user-specified temperature is dispensed, comprising: a variable temperature selector having a range of available temperatures for a user to select a specific temperature for the amount of water at a user-specified temperature to be dispensed through the water dispensing nozzle; a hot water system in communication with the water dispensing nozzle, comprising a hot water tank, at least one hot water temperature sensor and a hot water solenoid, wherein the hot water solenoid is in communication with the hot water tank and, in use, the hot water tank holds a supply of hot water having a present temperature measured by the at least one hot water temperature sensor; a cold water system in communication with the water dispensing nozzle, comprising a cold water tank, at least one cold water temperature sensor and a cold water solenoid, wherein the cold water solenoid is in communication with the cold water tank and, in use, the cold water tank holds a supply of cold water having a present temperature measured by the at least one cold water temperature sensor; a processor, in communication with the variable

temperature selector, the at least one hot water temperature sensor, the hot water solenoid, the at least one cold water temperature sensor and the cold water solenoid; capable of retrieving the present temperature of the hot water in the hot water tank from the at least one hot water temperature sensor, capable of retrieving the present temperature of the cold water in the cold water tank from the at least one cold water temperature sensor, capable of calculating a ratio of an amount of hot water from the hot water tank needed to be mixed with an amount of cold water from the cold water tank to produce the amount of water at a user-specified temperature at the specific temperature selected by the user and capable of simultaneously sending signals to the hot water solenoid to dispense the amount of hot water from the hot water tank and to the cold water solenoid to dispense the amount of cold water from the cold water tank at the calculated ratio of the amount of hot water to the amount of cold water needed to be mixed together to produce the amount of water at a user-specified temperature at the specific temperature selected by the user; and wherein, in use: the user selects from the range of available temperatures on the variable temperature selector a temperature at which the amount of water at a user-specified temperature is to be dispensed through the water dispensing nozzle the user selected temperature is communicated to the processor; the processor retrieves the present temperature of the hot water in the hot water tank from the at least one hot water temperature sensor, and retrieves the present temperature of the cold water in the cold water tank from the at least one cold water temperature sensor; using the retrieved present temperatures of the hot water in the hot water tank and the cold water in the cold water tank, along with the user selected temperature, the processor calculates a ratio of an amount of hot water from the hot water tank needed to be mixed with an amount of cold water from the cold water tank to produce the amount of water at a user-specified temperature at the specific temperature selected by the user; the processor simultaneously sends signals to the hot water solenoid to dispense the amount of hot water from the hot water tank and to the cold water solenoid to dispense the amount of cold water from the cold water tank at the calculated ratio of the amount of hot water to the amount of cold water needed to mix together to produce the amount of water at a user-specified temperature at the specific temperature selected by the user.

2. The variable temperature control assembly of claim 1, further comprising a mixing chamber in communication with the hot water solenoid and the cold water solenoid.

3. The variable temperature control assembly of claim 1, wherein the hot water system further comprises a pump and the cold water system further comprises a pump.

4. The variable temperature control assembly of claim 1, further comprising at least one low water level sensor disposed in the hot water tank and at least one low water level sensor disposed in the cold water tank.

5. The variable temperature control assembly of claim 1, further comprising at least one high water level sensor disposed in the hot water tank and at least one high water level sensor disposed in the cold water tank.

6. A water dispenser, comprising: a water dispensing nozzle; a variable temperature selector having a range of available temperatures for a user to select a specific temperature for the amount of water at a user-specified temperature to be dispensed through the water dispensing nozzle; a hot water system in communication with the water dispensing nozzle, comprising a hot water tank, at least one hot water temperature sensor and a hot water solenoid, wherein the hot water solenoid is in communication with the hot water tank and, in use, the hot water tank holds a supply of hot water having a present temperature measured by the at least one hot water temperature sensor; a cold water system in communication with the water dispensing nozzle, comprising a cold water tank, at least one cold water temperature sensor and a cold water solenoid, wherein the cold water solenoid is in communication with the cold water tank and, in use, the cold water tank holds a supply of cold water having a present temperature measured by the at least one cold water temperature sensor; a processor, in communication with the variable temperature selector, the at least one hot water temperature sensor, the hot water solenoid, the at least one cold water temperature sensor and the

cold water solenoid; capable of retrieving the present temperature of the hot water in the hot water tank from the at least one hot water temperature sensor, capable of retrieving the present temperature of the cold water in the cold water tank from the at least one cold water temperature sensor, capable of calculating a ratio of an amount of hot water from the hot water tank needed to be mixed with an amount of cold water from the cold water tank to produce the amount of water at a user-specified temperature at the specific temperature selected by the user and capable of simultaneously sending signals to the hot water solenoid to dispense the amount of hot water from the hot water tank and to the cold water solenoid to dispense the amount of cold water from the cold water tank at the calculated ratio of the amount of hot water to the amount of cold water needed to be mixed together to produce the amount of water at a user-specified temperature at the specific temperature selected by the user; and wherein, in use: the user selects from the range of available temperatures on the variable temperature selector a temperature at which the amount of water at a user-specified temperature is to be dispensed through the water dispensing nozzle; the user selected temperature is communicated to the processor; the processor retrieves the present temperature of the hot water in the hot water tank from the at least one hot water temperature sensor, and retrieves the present temperature of the cold water in the cold water tank from the at least one cold water temperature sensor; using the retrieved present temperatures of the hot water in the hot water tank and the cold water in the cold water tank, along with the user selected temperature, the processor calculates a ratio of an amount of hot water from the hot water tank needed to be mixed with an amount of cold water from the cold water tank to produce the amount of water at a user-specified temperature at the specific temperature selected by the user; the processor simultaneously sends signals to the hot water solenoid to dispense the amount of hot water from the hot water tank and to the cold water solenoid to dispense the amount of cold water from the cold water tank at the calculated ratio of the amount of hot water to the amount of cold water needed to mix together to produce the amount of water at a user-specified temperature at the specific temperature selected by the user; the dispensed amount of hot water from the hot water tank and the dispensed amount of cold water from the cold water tank are mixed together to produce the amount of water at a user-specified temperature at the specific temperature selected by the user; the produced amount of water at a user-specified temperature at the specific temperature selected by the user is dispensed through the water dispensing nozzle.

**7.** The water dispenser of claim 6, further comprising a mixing chamber in communication with the hot water solenoid and the cold water solenoid.

**8.** The water dispenser of claim 6, wherein the hot water system further comprises a pump and the cold water system further comprises a pump.

**9.** The water dispenser of claim 6, further comprising at least one low water level sensor disposed in the hot water tank and at least one low water level sensor disposed in the cold water tank.

**10.** The water dispenser of claim 6, further comprising at least one high water level sensor disposed in the hot water tank and at least one high water level sensor disposed in the cold water tank.

**11.** A method for delivering water at a specific requested temperature in a water dispenser, comprising the steps of: providing a water dispenser, having: a water dispensing nozzle; a variable temperature selector having a range of available temperatures for a user to select a specific temperature for the amount of water at a user-specified temperature to be dispensed through the water dispensing nozzle; a hot water system in communication with the water dispensing nozzle, comprising a hot water tank, at least one hot water temperature sensor and a hot water solenoid, wherein the hot water solenoid is in communication with the hot water tank and, in use, the hot water tank holds a supply of hot water having a present temperature measured by the at least one hot water temperature sensor; a cold water system in communication with the water dispensing nozzle, comprising a cold water tank, at least one cold water temperature sensor and a cold water solenoid, wherein the cold water solenoid is in communication with the cold water tank and, in use, the cold water tank holds a supply of cold water having a present temperature measured by the at



least one cold water temperature sensor; a processor, in communication with the variable temperature selector, the at least one hot water temperature sensor, the hot water solenoid, the at least one cold water temperature sensor and the cold water solenoid; capable of retrieving the present temperature of the hot water in the hot water tank from the at least one hot water temperature sensor, capable of retrieving the present temperature of the cold water in the cold water tank from the at least one cold water temperature sensor, capable of calculating a ratio of an amount of hot water from the hot water tank needed to be mixed with an amount of cold water from the cold water tank to produce the amount of water at a user-specified temperature at the specific temperature selected by the user and capable of simultaneously sending signals to the hot water solenoid to dispense the amount of hot water from the hot water tank and to the cold water solenoid to dispense the amount of cold water from the cold water tank at the calculated ratio of the amount of hot water to the amount of cold water needed to be mixed together to produce the amount of water at a user-specified temperature at the specific temperature selected by the user; selecting from the range of available temperatures on the variable temperature selector a temperature at which the amount of water at a user-specified temperature is to be dispensed through the water dispensing nozzle; retrieving the present temperature of the hot water in the hot water tank from the at least one hot water temperature sensor, and retrieving the present temperature of the cold water in the cold water tank from the at least one cold water temperature sensor; using the retrieved present temperatures of the hot water in the hot water tank and the cold water in the cold water tank, along with the user selected temperature, calculating a ratio of an amount of hot water from the hot water tank needed to be mixed with an amount of cold water from the cold water tank to produce the amount of water at a user-specified temperature at the specific temperature selected by the user; simultaneously sending signals to the hot water solenoid to dispense the amount of hot water from the hot water tank and to the cold water solenoid to dispense the amount of cold water from the cold water tank at the calculated ratio of the amount of hot water to the amount of cold water needed to mix together to produce the amount of water at a user-specified temperature at the specific temperature selected; mixing together the dispensed amount of hot water from the hot water tank and the dispensed amount of cold water from the cold water tank to produce the amount of water at a user-specified temperature at the specific temperature selected; and dispensing the produced amount of water at a user-specified temperature at the specific temperature selected through the water dispensing nozzle.

**12.** The method for delivering water at a specific requested temperature in a water dispenser of claim 11, further comprising the step of providing a mixing chamber in communication with the hot water solenoid and the cold water solenoid; wherein, at the step of mixing, the dispensed amount of hot water from the hot water tank and the dispensed amount of cold water from the cold water tank are mixed together in the mixing chamber to produce the amount of water at a user-specified temperature at the specific temperature selected.

**13.** The method for delivering water at a specific requested temperature in a water dispenser of claim 11, wherein the provided hot water system further comprises a pump and the provided cold water system further comprises a pump.

**14.** The method for delivering water at a specific requested temperature in a water dispenser of claim 11, further comprising the steps of: providing a pre-set temperature lower limit for the supply of hot water in the hot water tank; continuously monitoring the temperature of the supply of hot water in the hot water tank; if the temperature of the supply of hot water in the hot water tank is below the pre-set temperature lower limit for the supply of hot water in the hot water tank, heating the supply of hot water in the water tank until the temperature of the supply of hot water in the hot water tank is above the pre-set temperature lower limit; providing a pre-set temperature upper limit for the supply of cold water in the cold water tank; continuously monitoring the temperature of the supply of cold water in the cold water tank; and if the temperature of the supply of cold water in the cold water tank is above the pre-set temperature upper limit for the supply of cold water in the cold

water tank, chilling the supply of cold water in the cold water tank until the temperature of the supply of cold water in the cold water tank is below the pre-set temperature upper limit.

**15.** The method for delivering water at a specific requested temperature in a water dispenser of claim 11, further comprising the step of providing at least one low water level sensor disposed in the hot water tank and at least one low water level sensor disposed in the cold water tank.

**16.** The method for delivering water at a specific requested temperature in a water dispenser of claim 11, further comprising the step of providing at least one high water level sensor disposed in the hot water tank and at least one high water level sensor disposed in the cold water tank.

---