United States Patent Application Publication 20250283974
Kind Code A1
Publication Date September 11, 2025
Inventor(s) DUAN; Weimin et al.

HYBRID CONTINUOUS-WAVE RADAR TECHNIQUES FOR RADIO FREQUENCY SENSING

Abstract

Disclosed are techniques for wireless communication. In an aspect, a sensing node may receive an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components. The sensing node may transmit a hybrid continuous-wave radar signal. In some case, the hybrid continuous-wave radar signal may comprise at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.

Inventors: **DUAN; Weimin (San Diego, CA), LIU; Kangqi (San Diego, CA)**

Applicant: **QUALCOMM Incorporated** (San Diego, CA)

Family ID: **95248960**

Appl. No.: **18/600463**

Filed: **March 08, 2024**

Publication Classification

Int. Cl.: **G01S7/35** (20060101); **G01S7/00** (20060101); **G01S7/02** (20060101); **G01S13/58** (20060101)

U.S. Cl.:

CPC **G01S7/35** (20130101); **G01S7/006** (20130101); **G01S7/023** (20130101); **G01S13/584** (20130101);

Background/Summary

BACKGROUND OF THE DISCLOSURE

1. Field of the Disclosure

[0001] Aspects of the disclosure relate generally to wireless technologies.

2. Description of the Related Art

[0002] Wireless communication systems have developed through various generations, including a first-generation analog wireless phone service (1G), a second-generation (2G) digital wireless phone service (including interim 2.5G and 2.75G networks), a third-generation (3G) high speed data, Internet-capable wireless service and a fourth-generation (4G) service (e.g., Long Term Evolution (LTE) or WiMax). There are presently many different types of wireless communication systems in use, including cellular and personal communications service (PCS) systems. Examples of known cellular systems include the cellular analog advanced mobile phone system (AMPS), and digital cellular systems based on code division multiple access (CDMA), frequency division multiple access (FDMA), time division multiple access (TDMA), the Global System for Mobile communications (GSM), etc.

[0003] A fifth generation (5G) wireless standard, referred to as New Radio (NR), enables higher data transfer speeds, greater numbers of connections, and better coverage, among other improvements. The 5G standard, according to the Next Generation Mobile Networks Alliance, is designed to provide higher data rates as compared to previous standards, more accurate positioning (e.g., based on reference signals for positioning (RS-P), such as downlink, uplink, or sidelink positioning reference signals (PRS)), and other technical enhancements. These enhancements, as well as the use of higher frequency bands, advances in PRS processes and technology, and high-density deployments for 5G, enable highly accurate 5G-based positioning.

SUMMARY

[0004] The following presents a simplified summary relating to one or more aspects disclosed herein. Thus, the following summary should not be considered an extensive overview relating to all contemplated aspects, nor should the following summary be considered to identify key or critical elements relating to all contemplated aspects or to delineate the scope associated with any particular aspect. Accordingly, the following summary has the sole purpose to present certain concepts relating to one or more aspects relating to the mechanisms disclosed herein in a simplified form to precede the detailed description presented below.

[0005] In an aspect, a method of wireless communication performed by a sensing node includes receiving an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and transmitting a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.

[0006] In some aspects, the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first time duration, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second time duration different from the first time duration.

[0007] In some aspects, the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second symbol in the time domain different from the first symbol.

[0008] In some aspects, each of the first symbol and the second symbol is compatible with a cyclic prefix (CP) orthogonal frequency division multiplexing (CP-OFDM) symbol.

[0009] In some aspects, the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first portion of a symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second portion of the symbol in the time

domain different from the first portion.

[0010] In some aspects, the hybrid continuous-wave radar signal comprises a chirp sequence, the first portion of the symbol is a first chirp of the chirp sequence, and the second portion of the symbol is a second chirp of the of the chirp sequence immediately following the first chirp.

[0011] In some aspects, the method includes receiving signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission, or selecting, absent signaling, the predefined format of the hybrid continuous-wave radar signal to use for the transmission.

[0012] In some aspects, the method includes receiving signaling corresponding to an RS configuration that indicates a format of the hybrid continuous-wave radar signal to use for transmission on at least one RS resource.

[0013] In some aspects, the at least one scrambled continuous-wave waveform component comprises a number of scrambled continuous-wave waveform components based on an estimation of interference associated with the at least one RS resource.

[0014] In some aspects, the format of the hybrid continuous-wave radar signal indicates at least one tuning gap between the at least one unscrambled continuous-wave waveform component and the at least one scrambled continuous-wave waveform component.

[0015] In some aspects, the at least one scrambled continuous-wave waveform component comprises a phase-coded (PC) frequency-modulated continuous wave (PC-FMCW) waveform component or a frequency domain-scrambled digital FMCW waveform component, and the at least one unscrambled continuous-wave waveform component comprises an FMCW waveform component.

[0016] In an aspect, a method of wireless communication performed by a sensing node includes transmitting an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and receiving a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.

[0017] In some aspects, the method includes transmitting an indication for one or more tuning gaps between unscrambled continuous-wave waveform components and scrambled continuous-wave waveform components.

[0018] In some aspects, the method includes transmitting an indication of a minimum tuning gap between an unscrambled continuous-wave waveform component and a scrambled continuous-wave waveform component.

[0019] In some aspects, the method includes receiving signaling corresponding to an RS configuration that indicates one or more of: a format of the hybrid continuous-wave radar signal for transmission on at least one RS resource, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, information corresponding to scrambling associated with the at least one scrambled continuous-wave waveform component, or any combination thereof.

[0020] In some aspects, the method includes detecting a target based on a first range-Doppler profile using the at least one scrambled continuous-wave waveform component; and estimating one or more parameters associated with the target based on a second range-Doppler profile using the at least one unscrambled continuous-wave waveform component.

[0021] In an aspect, a sensing node includes one or more memories; one or more transceivers; and one or more processors communicatively coupled to the one or more memories and the one or more transceivers, the one or more processors, either alone or in combination, configured to: receive, via the one or more transceivers, an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and transmit, via the one or more

transceivers, a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0022] In an aspect, a sensing node includes one or more memories; one or more transceivers; and one or more processors communicatively coupled to the one or more memories and the one or more transceivers, the one or more processors, either alone or in combination, configured to: transmit, via the one or more transceivers, an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and receive, via the one or more transceivers, a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0023] In an aspect, a sensing node includes means for receiving an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and means for transmitting a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0024] In an aspect, a sensing node includes means for transmitting an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and means for receiving a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0025] In an aspect, a non-transitory computer-readable medium stores computer-executable instructions that, when executed by a sensing node, cause the sensing node to: receive an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and transmit a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0026] In an aspect, a non-transitory computer-readable medium stores computer-executable instructions that, when executed by a sensing node, cause the sensing node to: transmit an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and receive a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0027] Other objects and advantages associated with the aspects disclosed herein will be apparent to those skilled in the art based on the accompanying drawings and detailed description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS
[0028] The accompanying drawings are presented to aid in the description of various aspects of the disclosure and are provided solely for illustration of the aspects and not limitation thereof.
[0029] FIG. **1** illustrates an example wireless communications system, according to aspects of the disclosure.
[0030] FIGS. **2**A, **2**B, and **2**C illustrate example wireless network structures, according to aspects of the disclosure.
[0031] FIGS. **3**A, **3**B, and **3**C are simplified block diagrams of several sample aspects of components that may be employed in a user equipment (UE), a base station, and a network entity, respectively, and configured to support communications as taught herein.
[0032] FIGS. **4**A and **4**B illustrate different types of wireless sensing, according to aspects of the

disclosure.
[0033] FIG. **5** illustrates an example call flow for a New Radio (NR)-based sensing procedure in which the network configures the sensing parameters, according to aspects of the disclosure.
[0034] FIG. **6** illustrates an example of a sensing network with multiple sensing nodes, according to aspects of the disclosure.
[0035] FIG. **7** illustrates an example of an interference simulation graph for received sensing signals, according to aspects of the disclosure.
[0036] FIG. **8** illustrates an example of a circuit block diagram of one or more devices that perform RF sensing, according to aspects of the disclosure.
[0037] FIGS. **9**A to **9**C illustrate examples of time and frequency graphs for signals corresponding to the circuit block diagram of FIG. **8**, according to aspects of the disclosure.
[0038] FIG. **10** illustrates examples of range estimation graphs for unscrambled and scrambled sensing signals, according to aspects of the disclosure.
[0039] FIGS. **11**A to **11**C illustrate examples of range mapping diagrams and detection graphs for unscrambled and scrambled sensing signals, according to aspects of the disclosure.
[0040] FIG. **12** illustrates an example of a sensing network with multiple sensing nodes according to aspects of the disclosure.
[0041] FIG. **13** illustrates examples of hybrid continuous-wave waveforms, according to aspects of the disclosure.
[0042] FIG. **14** illustrates examples of range mapping diagrams for unscrambled and scrambled sensing signals, according to aspects of the disclosure.
[0043] FIGS. **15** and **16** illustrate example processes of wireless communication, according to aspects of the disclosure.

DETAILED DESCRIPTION

[0044] Aspects of the disclosure are provided in the following description and related drawings directed to various examples provided for illustration purposes. Alternate aspects may be devised without departing from the scope of the disclosure. Additionally, well-known elements of the disclosure will not be described in detail or will be omitted so as not to obscure the relevant details of the disclosure.
[0045] Various aspects relate generally to hybrid continuous-wave radar techniques for radio frequency (RF) sensing. Some aspects more specifically relate to hybrid frequency modulation continuous wave (FMCW) radar techniques for secure and interference robust RF sensing. That is, for example, a sensing reference signal using hybrid FMCW radar techniques may be configured to include at least one unscrambled FMCW waveform component and at least one scrambled FMCW waveform component. In some examples, the sensing RS may be transmitted on one or more symbols. For example, the sensing RS may be transmitted in multiple symbols such that one or more symbols include one or more unscrambled FMCW waveform components and one or more other symbols include one or more scrambled FMCW waveform components. In some examples, the sensing reference signal may be transmitted on a symbol such that one or more unscrambled FMCW waveform components are included in a first portion of the symbol and one or more scrambled FMCW waveform components are included in a second portion of the same symbol.
[0046] Particular aspects of the subject matter described in this disclosure can be implemented to realize one or more of the following potential advantages. In some examples, by including unscrambled and scrambled FMCW waveform components in one or more symbols of a sensing reference signal, the hybrid-FMCW radar transmission may mitigate cross-node interference while achieving sufficient dynamic range for target detection. In some examples, by including unscrambled and scrambled FMCW waveform components in one or more symbols of a sensing reference signal, the hybrid-FMCW radar transmission may enable secure sensing operation. That is, for example, a signal attack from an aggressor sensing node may be filtered out through the scrambled FMCW waveform component while the performance of the sensing operation can still

be maintained through the unscrambled FMCW waveform component.

[0047] The words “exemplary” and/or “example” are used herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” and/or “example” is not necessarily to be construed as preferred or advantageous over other aspects. Likewise, the term “aspects of the disclosure” does not require that all aspects of the disclosure include the discussed feature, advantage or mode of operation.

[0048] Those of skill in the art will appreciate that the information and signals described below may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the description below may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof, depending in part on the particular application, in part on the desired design, in part on the corresponding technology, etc.

[0049] Further, many aspects are described in terms of sequences of actions to be performed by, for example, elements of a computing device. It will be recognized that various actions described herein can be performed by specific circuits (e.g., application specific integrated circuits (ASICs)), by program instructions being executed by one or more processors, or by a combination of both. Additionally, the sequence(s) of actions described herein can be considered to be embodied entirely within any form of non-transitory computer-readable storage medium having stored therein a corresponding set of computer instructions that, upon execution, would cause or instruct an associated processor of a device to perform the functionality described herein. Thus, the various aspects of the disclosure may be embodied in a number of different forms, all of which have been contemplated to be within the scope of the claimed subject matter. In addition, for each of the aspects described herein, the corresponding form of any such aspects may be described herein as, for example, “logic configured to” perform the described action.

[0050] As used herein, the terms “user equipment” (UE) and “base station” are not intended to be specific or otherwise limited to any particular radio access technology (RAT), unless otherwise noted. In general, a UE may be any wireless communication device (e.g., a mobile phone, router, tablet computer, laptop computer, consumer asset locating device, wearable (e.g., smartwatch, glasses, augmented reality (AR)/virtual reality (VR) headset, etc.), vehicle (e.g., automobile, motorcycle, bicycle, etc.), Internet of Things (IoT) device, etc.) used by a user to communicate over a wireless communications network. A UE may be mobile or may (e.g., at certain times) be stationary, and may communicate with a radio access network (RAN). As used herein, the term “UE” may be referred to interchangeably as an “access terminal” or “AT,” a “client device,” a “wireless device,” a “subscriber device,” a “subscriber terminal,” a “subscriber station,” a “user terminal” or “UT,” a “mobile device,” a “mobile terminal,” a “mobile station,” or variations thereof. Generally, UEs can communicate with a core network via a RAN, and through the core network the UEs can be connected with external networks such as the Internet and with other UEs. Of course, other mechanisms of connecting to the core network and/or the Internet are also possible for the UEs, such as over wired access networks, wireless local area network (WLAN) networks (e.g., based on the Institute of Electrical and Electronics Engineers (IEEE) 802.11 specification, etc.) and so on.

[0051] A base station may operate according to one of several RATs in communication with UEs depending on the network in which it is deployed, and may be alternatively referred to as an access point (AP), a network node, a NodeB, an evolved NodeB (eNB), a next generation eNB (ng-eNB), a New Radio (NR) Node B (also referred to as a gNB or gNodeB), etc. A base station may be used primarily to support wireless access by UEs, including supporting data, voice, and/or signaling connections for the supported UEs. In some systems a base station may provide purely edge node signaling functions while in other systems it may provide additional control and/or network management functions. A communication link through which UEs can send signals to a base station is called an uplink (UL) channel (e.g., a reverse traffic channel, a reverse control channel, an access channel, etc.). A communication link through which the base station can send signals to UEs is called a downlink (DL) or forward link channel (e.g., a paging channel, a control channel, a broadcast channel, a forward traffic channel, etc.). As used herein the term traffic channel (TCH) can refer to either an uplink/reverse or downlink/forward traffic channel.

[0052] The term "base station" may refer to a single physical transmission-reception point (TRP) or to multiple physical TRPs that may or may not be co-located. For example, where the term "base station" refers to a single physical TRP, the physical TRP may be an antenna of the base station corresponding to a cell (or several cell sectors) of the base station. Where the term "base station" refers to multiple co-located physical TRPs, the physical TRPs may be an array of antennas (e.g., as in a multiple-input multiple-output (MIMO) system or where the base station employs beamforming) of the base station. Where the term "base station" refers to multiple non-co-located physical TRPs, the physical TRPs may be a distributed antenna system (DAS) (a network of spatially separated antennas connected to a common source via a transport medium) or a remote radio head (RRH) (a remote base station connected to a serving base station). Alternatively, the non-co-located physical TRPs may be the serving base station receiving the measurement report from the UE and a neighbor base station whose reference RF signals the UE is measuring. Because a TRP is the point from which a base station transmits and receives wireless signals, as used herein, references to transmission from or reception at a base station are to be understood as referring to a particular TRP of the base station.

[0053] In some implementations that support positioning of UEs, a base station may not support wireless access by UEs (e.g., may not support data, voice, and/or signaling connections for UEs), but may instead transmit reference signals to UEs to be measured by the UEs, and/or may receive and measure signals transmitted by the UEs. Such a base station may be referred to as a positioning beacon (e.g., when transmitting signals to UEs) and/or as a location measurement unit (e.g., when receiving and measuring signals from UEs).

[0054] An "RF signal" comprises an electromagnetic wave of a given frequency that transports information through the space between a transmitter and a receiver. As used herein, a transmitter may transmit a single "RF signal" or multiple "RF signals" to a receiver. However, the receiver may receive multiple "RF signals" corresponding to each transmitted RF signal due to the propagation characteristics of RF signals through multipath channels. The same transmitted RF signal on different paths between the transmitter and receiver may be referred to as a "multipath" RF signal. As used herein, an RF signal may also be referred to as a "wireless signal" or simply a "signal" where it is clear from the context that the term "signal" refers to a wireless signal or an RF signal.

[0055] FIG. **1** illustrates an example wireless communications system **100**, according to aspects of the disclosure. The wireless communications system **100** (which may also be referred to as a wireless wide area network (WWAN)) may include various base stations **102** (labeled "BS") and various UEs **104**. The base stations **102** may include macro cell base stations (high power cellular base stations) and/or small cell base stations (low power cellular base stations). In an aspect, the macro cell base stations may include eNBs and/or ng-eNBs where the wireless communications system **100** corresponds to an LTE network, or gNBs where the wireless communications system **100** corresponds to a NR network, or a combination of both, and the small cell base stations may include femtocells, picocells, microcells, etc.

[0056] The base stations **102** may collectively form a RAN and interface with a core network **170** (e.g., an evolved packet core (EPC) or a 5G core (5GC)) through backhaul links **122**, and through the core network **170** to one or more location servers **172** (e.g., a location management function (LMF) or a secure user plane location (SUPL) location platform (SLP)). The location server(s) **172** may be part of core network **170** or may be external to core network **170**. A location server **172** may be integrated with a base station **102**. A UE **104** may communicate with a location server **172** directly or indirectly. For example, a UE **104** may communicate with a location server **172** via the base station **102** that is currently serving that UE **104**. A UE **104** may also communicate with a location server **172** through another path, such as via an application server (not shown), via another network, such as via a wireless local area network (WLAN) access point (AP) (e.g., AP **150** described below), and so on. For signaling purposes, communication between a UE **104** and a location server **172** may be represented as an indirect connection (e.g., through the core network **170**, etc.) or a direct connection (e.g., as shown via direct connection **128**), with the intervening nodes (if any) omitted from a signaling diagram for clarity.

[0057] In addition to other functions, the base stations **102** may perform functions that relate to one or more of transferring user data, radio channel ciphering and deciphering, integrity protection, header compression, mobility control functions (e.g., handover, dual connectivity), inter-cell interference coordination, connection setup and release, load balancing, distribution for non-access stratum (NAS) messages, NAS node selection, synchronization, RAN sharing, multimedia broadcast multicast service (MBMS), subscriber and equipment trace, RAN information management (RIM), paging, positioning, and delivery of warning messages. The base stations **102** may communicate with each other directly or indirectly (e.g., through the EPC/5GC) over backhaul links **134**, which may be wired or wireless.

[0058] The base stations **102** may wirelessly communicate with the UEs **104**. Each of the base stations **102** may provide communication coverage for a respective geographic coverage area **110**. In an aspect, one or more cells may be supported by a base station **102** in each geographic coverage area **110**. A “cell” is a logical communication entity used for communication with a base station (e.g., over some frequency resource, referred to as a carrier frequency, component carrier, carrier, band, or the like), and may be associated with an identifier (e.g., a physical cell identifier (PCI), an enhanced cell identifier (ECI), a virtual cell identifier (VCI), a cell global identifier (CGI), etc.) for distinguishing cells operating via the same or a different carrier frequency. In some cases, different cells may be configured according to different protocol types (e.g., machine-type communication (MTC), narrowband IoT (NB-IoT), enhanced mobile broadband (eMBB), or others) that may provide access for different types of UEs. Because a cell is supported by a specific base station, the term “cell” may refer to either or both of the logical communication entity and the base station that supports it, depending on the context. In addition, because a TRP is typically the physical transmission point of a cell, the terms “cell” and “TRP” may be used interchangeably. In some cases, the term “cell” may also refer to a geographic coverage area of a base station (e.g., a sector), insofar as a carrier frequency can be detected and used for communication within some portion of geographic coverage areas **110**.

[0059] While neighboring macro cell base station **102** geographic coverage areas **110** may partially overlap (e.g., in a handover region), some of the geographic coverage areas **110** may be substantially overlapped by a larger geographic coverage area **110**. For example, a small cell base station **102′** (labeled “SC” for “small cell”) may have a geographic coverage area **110′** that substantially overlaps with the geographic coverage area **110** of one or more macro cell base stations **102**. A network that includes both small cell and macro cell base stations may be known as a heterogeneous network. A heterogeneous network may also include home eNBs (HeNBs), which may provide service to a restricted group known as a closed subscriber group (CSG).

[0060] The communication links **120** between the base stations **102** and the UEs **104** may include uplink (also referred to as reverse link) transmissions from a UE **104** to a base station **102** and/or downlink (DL) (also referred to as forward link) transmissions from a base station **102** to a UE **104**. The communication links **120** may use MIMO antenna technology, including spatial multiplexing, beamforming, and/or transmit diversity. The communication links **120** may be through one or more carrier frequencies. Allocation of carriers may be asymmetric with respect to downlink and uplink (e.g., more or less carriers may be allocated for downlink than for uplink).

[0061] The wireless communications system **100** may further include a wireless local area network

(WLAN) access point (AP) **150** in communication with WLAN stations (STAs) **152** via communication links **154** in an unlicensed frequency spectrum (e.g., 5 GHz). When communicating in an unlicensed frequency spectrum, the WLAN STAs **152** and/or the WLAN AP **150** may perform a clear channel assessment (CCA) or listen before talk (LBT) procedure prior to communicating in order to determine whether the channel is available.
[0062] The small cell base station **102**′ may operate in a licensed and/or an unlicensed frequency spectrum. When operating in an unlicensed frequency spectrum, the small cell base station **102**′ may employ LTE or NR technology and use the same 5 GHz unlicensed frequency spectrum as used by the WLAN AP **150**. The small cell base station **102**′, employing LTE/5G in an unlicensed frequency spectrum, may boost coverage to and/or increase capacity of the access network. NR in unlicensed spectrum may be referred to as NR-U. LTE in an unlicensed spectrum may be referred to as LTE-U, licensed assisted access (LAA), or MULTEFIRE®.
[0063] The wireless communications system **100** may further include a millimeter wave (mmW) base station **180** that may operate in mmW frequencies and/or near mmW frequencies in communication with a UE **182**. Extremely high frequency (EHF) is part of the RF in the electromagnetic spectrum. EHF has a range of 30 GHz to 300 GHz and a wavelength between 1 millimeter and 10 millimeters. Radio waves in this band may be referred to as a millimeter wave. Near mmW may extend down to a frequency of 3 GHZ with a wavelength of 100 millimeters. The super high frequency (SHF) band extends between 3 GHz and 30 GHz, also referred to as centimeter wave. Communications using the mmW/near mmW radio frequency band have high path loss and a relatively short range. The mmW base station **180** and the UE **182** may utilize beamforming (transmit and/or receive) over a mmW communication link **184** to compensate for the extremely high path loss and short range. Further, it will be appreciated that in alternative configurations, one or more base stations **102** may also transmit using mmW or near mmW and beamforming. Accordingly, it will be appreciated that the foregoing illustrations are merely examples and should not be construed to limit the various aspects disclosed herein.
[0064] Transmit beamforming is a technique for focusing an RF signal in a specific direction. Traditionally, when a network node (e.g., a base station) broadcasts an RF signal, it broadcasts the signal in all directions (omni-directionally). With transmit beamforming, the network node determines where a given target device (e.g., a UE) is located (relative to the transmitting network node) and projects a stronger downlink RF signal in that specific direction, thereby providing a faster (in terms of data rate) and stronger RF signal for the receiving device(s). To change the directionality of the RF signal when transmitting, a network node can control the phase and relative amplitude of the RF signal at each of the one or more transmitters that are broadcasting the RF signal. For example, a network node may use an array of antennas (referred to as a “phased array” or an “antenna array”) that creates a beam of RF waves that can be “steered” to point in different directions, without actually moving the antennas. Specifically, the RF current from the transmitter is fed to the individual antennas with the correct phase relationship so that the radio waves from the separate antennas add together to increase the radiation in a desired direction, while cancelling to suppress radiation in undesired directions.
[0065] Transmit beams may be quasi-co-located, meaning that they appear to the receiver (e.g., a UE) as having the same parameters, regardless of whether or not the transmitting antennas of the network node themselves are physically co-located. In NR, there are four types of quasi-co-location (QCL) relations. Specifically, a QCL relation of a given type means that certain parameters about a second reference RF signal on a second beam can be derived from information about a source reference RF signal on a source beam. Thus, if the source reference RF signal is QCL Type A, the receiver can use the source reference RF signal to estimate the Doppler shift, Doppler spread, average delay, and delay spread of a second reference RF signal transmitted on the same channel. If the source reference RF signal is QCL Type B, the receiver can use the source reference RF signal to estimate the Doppler shift and Doppler spread of a second reference RF signal transmitted on the

same channel. If the source reference RF signal is QCL Type C, the receiver can use the source reference RF signal to estimate the Doppler shift and average delay of a second reference RF signal transmitted on the same channel. If the source reference RF signal is QCL Type D, the receiver can use the source reference RF signal to estimate the spatial receive parameter of a second reference RF signal transmitted on the same channel.

[0066] In receive beamforming, the receiver uses a receive beam to amplify RF signals detected on a given channel. For example, the receiver can increase the gain setting and/or adjust the phase setting of an array of antennas in a particular direction to amplify (e.g., to increase the gain level of) the RF signals received from that direction. Thus, when a receiver is said to beamform in a certain direction, it means the beam gain in that direction is high relative to the beam gain along other directions, or the beam gain in that direction is the highest compared to the beam gain in that direction of all other receive beams available to the receiver. This results in a stronger received signal strength (e.g., reference signal received power (RSRP), reference signal received quality (RSRQ), signal-to-interference-plus-noise ratio (SINR), etc.) of the RF signals received from that direction.

[0067] Transmit and receive beams may be spatially related. A spatial relation means that parameters for a second beam (e.g., a transmit or receive beam) for a second reference signal can be derived from information about a first beam (e.g., a receive beam or a transmit beam) for a first reference signal. For example, a UE may use a particular receive beam to receive a reference downlink reference signal (e.g., synchronization signal block (SSB)) from a base station. The UE can then form a transmit beam for sending an uplink reference signal (e.g., sounding reference signal (SRS)) to that base station based on the parameters of the receive beam.

[0068] Note that a “downlink” beam may be either a transmit beam or a receive beam, depending on the entity forming it. For example, if a base station is forming the downlink beam to transmit a reference signal to a UE, the downlink beam is a transmit beam. If the UE is forming the downlink beam, however, it is a receive beam to receive the downlink reference signal. Similarly, an “uplink” beam may be either a transmit beam or a receive beam, depending on the entity forming it. For example, if a base station is forming the uplink beam, it is an uplink receive beam, and if a UE is forming the uplink beam, it is an uplink transmit beam.

[0069] The electromagnetic spectrum is often subdivided, based on frequency/wavelength, into various classes, bands, channels, etc. In 5G NR two initial operating bands have been identified as frequency range designations FR1 (410 MHz-7.125 GHZ) and FR2 (24.25 GHz-52.6 GHZ). It should be understood that although a portion of FR1 is greater than 6 GHZ, FR1 is often referred to (interchangeably) as a “Sub-6 GHz” band in various documents and articles. A similar nomenclature issue sometimes occurs with regard to FR2, which is often referred to (interchangeably) as a “millimeter wave” band in documents and articles, despite being different from the extremely high frequency (EHF) band (30 GHZ-300 GHZ) which is identified by the INTERNATIONAL TELECOMMUNICATION UNION® as a “millimeter wave” band.

[0070] The frequencies between FR1 and FR2 are often referred to as mid-band frequencies. Recent 5G NR studies have identified an operating band for these mid-band frequencies as frequency range designation FR3 (7.125 GHZ-24.25 GHZ). Frequency bands falling within FR3 may inherit FR1 characteristics and/or FR2 characteristics, and thus may effectively extend features of FR1 and/or FR2 into mid-band frequencies. In addition, higher frequency bands are currently being explored to extend 5G NR operation beyond 52.6 GHz. For example, three higher operating bands have been identified as frequency range designations FR4a or FR4-1 (52.6 GHz-71 GHZ), FR4 (52.6 GHz-114.25 GHZ), and FR5 (114.25 GHZ-300 GHz). Each of these higher frequency bands falls within the EHF band.

[0071] With the above aspects in mind, unless specifically stated otherwise, it should be understood that the term “sub-6 GHz” or the like if used herein may broadly represent frequencies that may be less than 6 GHZ, may be within FR1, or may include mid-band frequencies. Further, unless specifically stated otherwise, it should be understood that the term “millimeter wave” or the like if used herein may broadly represent frequencies that may include mid-band frequencies, may be within FR2, FR4, FR4-a or FR4-1, and/or FR5, or may be within the EHF band.

[0072] In a multi-carrier system, such as 5G, one of the carrier frequencies is referred to as the “primary carrier” or “anchor carrier” or “primary serving cell” or “PCell,” and the remaining carrier frequencies are referred to as “secondary carriers” or “secondary serving cells” or “SCells.” In carrier aggregation, the anchor carrier is the carrier operating on the primary frequency (e.g., FR1) utilized by a UE **104**/**182** and the cell in which the UE **104**/**182** either performs the initial radio resource control (RRC) connection establishment procedure or initiates the RRC connection re-establishment procedure. The primary carrier carries all common and UE-specific control channels, and may be a carrier in a licensed frequency (however, this is not always the case). A secondary carrier is a carrier operating on a second frequency (e.g., FR2) that may be configured once the RRC connection is established between the UE **104** and the anchor carrier and that may be used to provide additional radio resources. In some cases, the secondary carrier may be a carrier in an unlicensed frequency. The secondary carrier may contain only necessary signaling information and signals, for example, those that are UE-specific may not be present in the secondary carrier, since both primary uplink and downlink carriers are typically UE-specific. This means that different UEs **104**/**182** in a cell may have different downlink primary carriers. The same is true for the uplink primary carriers. The network is able to change the primary carrier of any UE **104**/**182** at any time. This is done, for example, to balance the load on different carriers. Because a “serving cell” (whether a PCell or an SCell) corresponds to a carrier frequency/component carrier over which some base station is communicating, the term “cell,” “serving cell,” “component carrier,” “carrier frequency,” and the like can be used interchangeably.

[0073] For example, still referring to FIG. **1**, one of the frequencies utilized by the macro cell base stations **102** may be an anchor carrier (or “PCell”) and other frequencies utilized by the macro cell base stations **102** and/or the mmW base station **180** may be secondary carriers (“SCells”). The simultaneous transmission and/or reception of multiple carriers enables the UE **104**/**182** to significantly increase its data transmission and/or reception rates. For example, two 20 MHz aggregated carriers in a multi-carrier system would theoretically lead to a two-fold increase in data rate (i.e., 40 MHZ), compared to that attained by a single 20 MHz carrier.

[0074] The wireless communications system **100** may further include a UE **164** that may communicate with a macro cell base station **102** over a communication link **120** and/or the mmW base station **180** over a mmW communication link **184**. For example, the macro cell base station **102** may support a PCell and one or more SCells for the UE **164** and the mmW base station **180** may support one or more SCells for the UE **164**.

[0075] In some cases, the UE **164** and the UE **182** may be capable of sidelink communication. Sidelink-capable UEs (SL-UEs) may communicate with base stations **102** over communication links **120** using the Uu interface (i.e., the air interface between a UE and a base station). SL-UEs (e.g., UE **164**, UE **182**) may also communicate directly with each other over a wireless sidelink **160** using the PC5 interface (i.e., the air interface between sidelink-capable UEs). A wireless sidelink (or just “sidelink”) is an adaptation of the core cellular (e.g., LTE, NR) standard that allows direct communication between two or more UEs without the communication needing to go through a base station. Sidelink communication may be unicast or multicast, and may be used for device-to-device (D2D) media-sharing, vehicle-to-vehicle (V2V) communication, vehicle-to-everything (V2X) communication (e.g., cellular V2X (cV2X) communication, enhanced V2X (cV2X) communication, etc.), emergency rescue applications, etc. One or more of a group of SL-UEs utilizing sidelink communications may be within the geographic coverage area **110** of a base station **102**. Other SL-UEs in such a group may be outside the geographic coverage area **110** of a base station **102** or be otherwise unable to receive transmissions from a base station **102**. In some cases, groups of SL-UEs communicating via sidelink communications may utilize a one-to-many (1:M) system in which each SL-UE transmits to every other SL-UE in the group. In some cases, a base station **102** facilitates the scheduling of resources for sidelink communications. In other cases, sidelink communications are carried out between SL-UEs without the involvement of a base station **102**.

[0076] In an aspect, the sidelink **160** may operate over a wireless communication medium of interest, which may be shared with other wireless communications between other vehicles and/or infrastructure access points, as well as other RATs. A "medium" may be composed of one or more time, frequency, and/or space communication resources (e.g., encompassing one or more channels across one or more carriers) associated with wireless communication between one or more transmitter/receiver pairs. In an aspect, the medium of interest may correspond to at least a portion of an unlicensed frequency band shared among various RATs. Although different licensed frequency bands have been reserved for certain communication systems (e.g., by a government entity such as the Federal Communications Commission (FCC) in the United States), these systems, in particular those employing small cell access points, have recently extended operation into unlicensed frequency bands such as the Unlicensed National Information Infrastructure (U-NII) band used by wireless local area network (WLAN) technologies, most notably IEEE 802.11x WLAN technologies generally referred to as "Wi-Fi." Example systems of this type include different variants of CDMA systems, TDMA systems, FDMA systems, orthogonal FDMA (OFDMA) systems, single-carrier FDMA (SC-FDMA) systems, and so on.

[0077] Note that although FIG. **1** only illustrates two of the UEs as SL-UEs (i.e., UEs **164** and **182**), any of the illustrated UEs may be SL-UEs. Further, although only UE **182** was described as being capable of beamforming, any of the illustrated UEs, including UE **164**, may be capable of beamforming. Where SL-UEs are capable of beamforming, they may beamform towards each other (i.e., towards other SL-UEs), towards other UEs (e.g., UEs **104**), towards base stations (e.g., base stations **102**, **180**, small cell **102′**, access point **150**), etc. Thus, in some cases, UEs **164** and **182** may utilize beamforming over sidelink **160**.

[0078] In the example of FIG. **1**, any of the illustrated UEs (shown in FIG. **1** as a single UE **104** for simplicity) may receive signals **124** from one or more Earth orbiting space vehicles (SVs) **112** (e.g., satellites). In an aspect, the SVs **112** may be part of a satellite positioning system that a UE **104** can use as an independent source of location information. A satellite positioning system typically includes a system of transmitters (e.g., SVs **112**) positioned to enable receivers (e.g., UEs **104**) to determine their location on or above the Earth based, at least in part, on positioning signals (e.g., signals **124**) received from the transmitters. Such a transmitter typically transmits a signal marked with a repeating pseudo-random noise (PN) code of a set number of chips. While typically located in SVs **112**, transmitters may sometimes be located on ground-based control stations, base stations **102**, and/or other UEs **104**. A UE **104** may include one or more dedicated receivers specifically designed to receive signals **124** for deriving geo location information from the SVs **112**.

[0079] In a satellite positioning system, the use of signals **124** can be augmented by various satellite-based augmentation systems (SBAS) that may be associated with or otherwise enabled for use with one or more global and/or regional navigation satellite systems. For example an SBAS may include an augmentation system(s) that provides integrity information, differential corrections, etc., such as the Wide Area Augmentation System (WAAS), the European Geostationary Navigation Overlay Service (EGNOS), the Multi-functional Satellite Augmentation System (MSAS), the Global Positioning System (GPS) Aided Geo Augmented Navigation or GPS and Geo Augmented Navigation system (GAGAN), and/or the like. Thus, as used herein, a satellite positioning system may include any combination of one or more global and/or regional navigation satellites associated with such one or more satellite positioning systems.

[0080] In an aspect, SVs **112** may additionally or alternatively be part of one or more non-terrestrial networks (NTNs). In an NTN, an SV **112** is connected to an earth station (also referred to as a ground station, NTN gateway, or gateway), which in turn is connected to an element in a 5G network, such as a modified base station **102** (without a terrestrial antenna) or a network node in a 5GC. This element would in turn provide access to other elements in the 5G network and ultimately to entities external to the 5G network, such as Internet web servers and other user devices. In that way, a UE **104** may receive communication signals (e.g., signals **124**) from an SV **112** instead of, or in addition to, communication signals from a terrestrial base station **102**.

[0081] The wireless communications system **100** may further include one or more UEs, such as UE **190**, that connects indirectly to one or more communication networks via one or more device-to-device (D2D) peer-to-peer (P2P) links (referred to as "sidelinks"). In the example of FIG. **1**, UE **190** has a D2D P2P link **192** with one of the UEs **104** connected to one of the base stations **102** (e.g., through which UE **190** may indirectly obtain cellular connectivity) and a D2D P2P link **194** with WLAN STA **152** connected to the WLAN AP **150** (through which UE **190** may indirectly obtain WLAN-based Internet connectivity). In an example, the D2D P2P links **192** and **194** may be supported with any well-known D2D RAT, such as LTE Direct (LTE-D), WI-FI DIRECT®, BLUETOOTH®, and so on.

[0082] FIG. **2**A illustrates an example wireless network structure **200**. For example, a 5GC **210** (also referred to as a Next Generation Core (NGC)) can be viewed functionally as control plane (C-plane) functions **214** (e.g., UE registration, authentication, network access, gateway selection, etc.) and user plane (U-plane) functions **212**, (e.g., UE gateway function, access to data networks, IP routing, etc.) which operate cooperatively to form the core network. User plane interface (NG-U) **213** and control plane interface (NG-C) **215** connect the gNB **222** to the 5GC **210** and specifically to the user plane functions **212** and control plane functions **214**, respectively. In an additional configuration, an ng-eNB **224** may also be connected to the 5GC **210** via NG-C **215** to the control plane functions **214** and NG-U **213** to user plane functions **212**. Further, ng-eNB **224** may directly communicate with gNB **222** via a backhaul connection **223**. In some configurations, a Next Generation RAN (NG-RAN) **220** may have one or more gNBs **222**, while other configurations include one or more of both ng-eNBs **224** and gNBs **222**. Either (or both) gNB **222** or ng-eNB **224** may communicate with one or more UEs **204** (e.g., any of the UEs described herein).

[0083] Another optional aspect may include a location server **230**, which may be in communication with the 5GC **210** to provide location assistance for UE(s) **204**. The location server **230** can be implemented as a plurality of separate servers (e.g., physically separate servers, different software modules on a single server, different software modules spread across multiple physical servers, etc.), or alternately may each correspond to a single server. The location server **230** can be configured to support one or more location services for UEs **204** that can connect to the location server **230** via the core network, 5GC **210**, and/or via the Internet (not illustrated). Further, the location server **230** may be integrated into a component of the core network, or alternatively may be external to the core network (e.g., a third party server, such as an original equipment manufacturer (OEM) server or service server).

[0084] FIG. **2**B illustrates another example wireless network structure **240**. A 5GC **260** (which may correspond to 5GC **210** in FIG. **2**A) can be viewed functionally as control plane functions, provided by an access and mobility management function (AMF) **264**, and user plane functions, provided by a user plane function (UPF) **262**, which operate cooperatively to form the core network (i.e., 5GC **260**). The functions of the AMF **264** include registration management, connection management, reachability management, mobility management, lawful interception, transport for session management (SM) messages between one or more UEs **204** (e.g., any of the UEs described herein) and a session management function (SMF) **266**, transparent proxy services for routing SM messages, access authentication and access authorization, transport for short message service (SMS) messages between the UE **204** and the short message service function (SMSF) (not shown), and security anchor functionality (SEAF). The AMF **264** also interacts with an authentication server function (AUSF) (not shown) and the UE **204**, and receives the intermediate key that was established as a result of the UE **204** authentication process. In the case of authentication based on a UMTS (universal mobile telecommunications system) subscriber identity module (USIM), the AMF **264** retrieves the security material from the AUSF. The functions of the AMF **264** also include security context management (SCM). The SCM receives a key from the SEAF that it uses to derive access-network specific keys. The functionality of the AMF **264** also includes location services management for regulatory services, transport for location services messages between the UE **204** and a location management function (LMF) **270** (which acts as a location server **230**), transport for location services messages between the NG-RAN **220** and the LMF **270**, evolved packet system (EPS) bearer identifier allocation for interworking with the EPS, and UE **204** mobility event notification. In addition, the AMF **264** also supports functionalities for non-3GPP® (Third Generation Partnership Project) access networks.

[0085] Functions of the UPF **262** include acting as an anchor point for intra/inter-RAT mobility (when applicable), acting as an external protocol data unit (PDU) session point of interconnect to a data network (not shown), providing packet routing and forwarding, packet inspection, user plane policy rule enforcement (e.g., gating, redirection, traffic steering), lawful interception (user plane collection), traffic usage reporting, quality of service (QOS) handling for the user plane (e.g., uplink/downlink rate enforcement, reflective QoS marking in the downlink), uplink traffic verification (service data flow (SDF) to QoS flow mapping), transport level packet marking in the uplink and downlink, downlink packet buffering and downlink data notification triggering, and sending and forwarding of one or more "end markers" to the source RAN node. The UPF **262** may also support transfer of location services messages over a user plane between the UE **204** and a location server, such as an SLP **272**.

[0086] The functions of the SMF **266** include session management, UE Internet protocol (IP) address allocation and management, selection and control of user plane functions, configuration of traffic steering at the UPF **262** to route traffic to the proper destination, control of part of policy enforcement and QoS, and downlink data notification. The interface over which the SMF **266** communicates with the AMF **264** is referred to as the N11 interface.

[0087] Another optional aspect may include an LMF **270**, which may be in communication with the 5GC **260** to provide location assistance for UEs **204**. The LMF **270** can be implemented as a plurality of separate servers (e.g., physically separate servers, different software modules on a single server, different software modules spread across multiple physical servers, etc.), or alternately may each correspond to a single server. The LMF **270** can be configured to support one or more location services for UEs **204** that can connect to the LMF **270** via the core network, 5GC **260**, and/or via the Internet (not illustrated). The SLP **272** may support similar functions to the LMF **270**, but whereas the LMF **270** may communicate with the AMF **264**, NG-RAN **220**, and UEs **204** over a control plane (e.g., using interfaces and protocols intended to convey signaling messages and not voice or data), the SLP **272** may communicate with UEs **204** and external clients (e.g., third-party server **274**) over a user plane (e.g., using protocols intended to carry voice and/or data like the transmission control protocol (TCP) and/or IP).

[0088] Yet another optional aspect may include a third-party server **274**, which may be in communication with the LMF **270**, the SLP **272**, the 5GC **260** (e.g., via the AMF **264** and/or the UPF **262**), the NG-RAN **220**, and/or the UE **204** to obtain location information (e.g., a location estimate) for the UE **204**. As such, in some cases, the third-party server **274** may be referred to as a location services (LCS) client or an external client. The third-party server **274** can be implemented as a plurality of separate servers (e.g., physically separate servers, different software modules on a single server, different software modules spread across multiple physical servers, etc.), or alternately may each correspond to a single server.

[0089] User plane interface **263** and control plane interface **265** connect the 5GC **260**, and specifically the UPF **262** and AMF **264**, respectively, to one or more gNBs **222** and/or ng-eNBs **224** in the NG-RAN **220**. The interface between gNB(s) **222** and/or ng-eNB(s) **224** and the AMF **264** is referred to as the "N2" interface, and the interface between gNB(s) **222** and/or ng-eNB(s)

224 and the UPF **262** is referred to as the “N3” interface. The gNB(s) **222** and/or ng-eNB(s) **224** of the NG-RAN **220** may communicate directly with each other via backhaul connections **223**, referred to as the “Xn-C” interface. One or more of gNBs **222** and/or ng-eNBs **224** may communicate with one or more UEs **204** over a wireless interface, referred to as the “Uu” interface.
[0090] The functionality of a gNB **222** may be divided between a gNB central unit (gNB-CU) **226**, one or more gNB distributed units (gNB-DUs) **228**, and one or more gNB radio units (gNB-RUs) **229**. A gNB-CU **226** is a logical node that includes the base station functions of transferring user data, mobility control, radio access network sharing, positioning, session management, and the like, except for those functions allocated exclusively to the gNB-DU(s) **228**. More specifically, the gNB-CU **226** generally host the radio resource control (RRC), service data adaptation protocol (SDAP), and packet data convergence protocol (PDCP) protocols of the gNB **222**. A gNB-DU **228** is a logical node that generally hosts the radio link control (RLC) and medium access control (MAC) layer of the gNB **222**. Its operation is controlled by the gNB-CU **226**. One gNB-DU **228** can support one or more cells, and one cell is supported by only one gNB-DU **228**. The interface **232** between the gNB-CU **226** and the one or more gNB-DUs **228** is referred to as the “F1” interface. The physical (PHY) layer functionality of a gNB **222** is generally hosted by one or more standalone gNB-RUs **229** that perform functions such as power amplification and signal transmission/reception. The interface between a gNB-DU **228** and a gNB-RU **229** is referred to as the “Fx” interface. Thus, a UE **204** communicates with the gNB-CU **226** via the RRC, SDAP, and PDCP layers, with a gNB-DU **228** via the RLC and MAC layers, and with a gNB-RU **229** via the PHY layer.
[0091] Deployment of communication systems, such as 5G NR systems, may be arranged in multiple manners with various components or constituent parts. In a 5G NR system, or network, a network node, a network entity, a mobility element of a network, a RAN node, a core network node, a network element, or a network equipment, such as a base station, or one or more units (or one or more components) performing base station functionality, may be implemented in an aggregated or disaggregated architecture. For example, a base station (such as a Node B (NB), evolved NB (eNB), NR base station, 5G NB, AP, TRP, cell, etc.) may be implemented as an aggregated base station (also known as a standalone base station or a monolithic base station) or a disaggregated base station.
[0092] An aggregated base station may be configured to utilize a radio protocol stack that is physically or logically integrated within a single RAN node. A disaggregated base station may be configured to utilize a protocol stack that is physically or logically distributed among two or more units (such as one or more central or centralized units (CUs), one or more distributed units (DUs), or one or more radio units (RUs)). In some aspects, a CU may be implemented within a RAN node, and one or more DUs may be co-located with the CU, or alternatively, may be geographically or virtually distributed throughout one or multiple other RAN nodes. The DUs may be implemented to communicate with one or more RUs. Each of the CU, DU and RU also can be implemented as virtual units, i.e., a virtual central unit (VCU), a virtual distributed unit (VDU), or a virtual radio unit (VRU).
[0093] Base station-type operation or network design may consider aggregation characteristics of base station functionality. For example, disaggregated base stations may be utilized in an integrated access backhaul (IAB) network, an open radio access network (O-RAN (such as the network configuration sponsored by the O-RAN ALLIANCE®)), or a virtualized radio access network (vRAN, also known as a cloud radio access network (C-RAN)). Disaggregation may include distributing functionality across two or more units at various physical locations, as well as distributing functionality for at least one unit virtually, which can enable flexibility in network design. The various units of the disaggregated base station, or disaggregated RAN architecture, can be configured for wired or wireless communication with at least one other unit.
[0094] FIG. **2**C illustrates an example disaggregated base station architecture **250**, according to

aspects of the disclosure. The disaggregated base station architecture **250** may include one or more central units (CUs) **280** (e.g., gNB-CU **226**) that can communicate directly with a core network **267** (e.g., 5GC **210**, 5GC **260**) via a backhaul link, or indirectly with the core network **267** through one or more disaggregated base station units (such as a Near-Real Time (Near-RT) RAN Intelligent Controller (RIC) **259** via an E2 link, or a Non-Real Time (Non-RT) RIC **257** associated with a Service Management and Orchestration (SMO) Framework **255**, or both). A CU **280** may communicate with one or more DUs **285** (e.g., gNB-DUs **228**) via respective midhaul links, such as an F1 interface. The DUs **285** may communicate with one or more radio units (RUS) **287** (e.g., gNB-RUs **229**) via respective fronthaul links. The RUs **287** may communicate with respective UEs **204** via one or more RF access links. In some implementations, the UE **204** may be simultaneously served by multiple RUs **287**.

[0095] Each of the units, i.e., the CUS **280**, the DUs **285**, the RUs **287**, as well as the Near-RT RICs **259**, the Non-RT RICs **257** and the SMO Framework **255**, may include one or more interfaces or be coupled to one or more interfaces configured to receive or transmit signals, data, or information (collectively, signals) via a wired or wireless transmission medium. Each of the units, or an associated processor or controller providing instructions to the communication interfaces of the units, can be configured to communicate with one or more of the other units via the transmission medium. For example, the units can include a wired interface configured to receive or transmit signals over a wired transmission medium to one or more of the other units. Additionally, the units can include a wireless interface, which may include a receiver, a transmitter or transceiver (such as a RF transceiver), configured to receive or transmit signals, or both, over a wireless transmission medium to one or more of the other units.

[0096] In some aspects, the CU **280** may host one or more higher layer control functions. Such control functions can include RRC, PDCP, service data adaptation protocol (SDAP), or the like. Each control function can be implemented with an interface configured to communicate signals with other control functions hosted by the CU **280**. The CU **280** may be configured to handle user plane functionality (i.e., Central Unit-User Plane (CU-UP)), control plane functionality (i.e., Central Unit-Control Plane (CU-CP)), or a combination thereof. In some implementations, the CU **280** can be logically split into one or more CU-UP units and one or more CU-CP units. The CU-UP unit can communicate bidirectionally with the CU-CP unit via an interface, such as the E1 interface when implemented in an O-RAN configuration. The CU **280** can be implemented to communicate with the DU **285**, as necessary, for network control and signaling.

[0097] The DU **285** may correspond to a logical unit that includes one or more base station functions to control the operation of one or more RUs **287**. In some aspects, the DU **285** may host one or more of a RLC layer, a MAC layer, and one or more high PHY layers (such as modules for forward error correction (FEC) encoding and decoding, scrambling, modulation and demodulation, or the like) depending, at least in part, on a functional split, such as those defined by the 3rd Generation Partnership Project (3GPP®). In some aspects, the DU **285** may further host one or more low PHY layers. Each layer (or module) can be implemented with an interface configured to communicate signals with other layers (and modules) hosted by the DU **285**, or with the control functions hosted by the CU **280**.

[0098] Lower-layer functionality can be implemented by one or more RUs **287**. In some deployments, an RU **287**, controlled by a DU **285**, may correspond to a logical node that hosts RF processing functions, or low-PHY layer functions (such as performing fast Fourier transform (FFT), inverse FFT (IFFT), digital beamforming, physical random access channel (PRACH) extraction and filtering, or the like), or both, based at least in part on the functional split, such as a lower layer functional split. In such an architecture, the RU(s) **287** can be implemented to handle over the air (OTA) communication with one or more UEs **204**. In some implementations, real-time and non-real-time aspects of control and user plane communication with the RU(s) **287** can be controlled by the corresponding DU **285**. In some scenarios, this configuration can enable the

DU(s) **285** and the CU **280** to be implemented in a cloud-based RAN architecture, such as a vRAN architecture.

[0099] The SMO Framework **255** may be configured to support RAN deployment and provisioning of non-virtualized and virtualized network elements. For non-virtualized network elements, the SMO Framework **255** may be configured to support the deployment of dedicated physical resources for RAN coverage requirements which may be managed via an operations and maintenance interface (such as an O1 interface). For virtualized network elements, the SMO Framework **255** may be configured to interact with a cloud computing platform (such as an open cloud (O-Cloud) **269**) to perform network element life cycle management (such as to instantiate virtualized network elements) via a cloud computing platform interface (such as an O2 interface). Such virtualized network elements can include, but are not limited to, CUs **280**, DUs **285**, RUs **287** and Near-RT RICs **259**. In some implementations, the SMO Framework **255** can communicate with a hardware aspect of a 4G RAN, such as an open eNB (O-eNB) **261**, via an O1 interface. Additionally, in some implementations, the SMO Framework **255** can communicate directly with one or more RUs **287** via an O1 interface. The SMO Framework **255** also may include a Non-RT RIC **257** configured to support functionality of the SMO Framework **255**.

[0100] The Non-RT RIC **257** may be configured to include a logical function that enables non-real-time control and optimization of RAN elements and resources, artificial intelligence/machine learning (AI/ML) workflows including model training and updates, or policy-based guidance of applications/features in the Near-RT RIC **259**. The Non-RT RIC **257** may be coupled to or communicate with (such as via an A1 interface) the Near-RT RIC **259**. The Near-RT RIC **259** may be configured to include a logical function that enables near-real-time control and optimization of RAN elements and resources via data collection and actions over an interface (such as via an E2 interface) connecting one or more CUs **280**, one or more DUs **285**, or both, as well as an O-eNB, with the Near-RT RIC **259**.

[0101] In some implementations, to generate AI/ML models to be deployed in the Near-RT RIC **259**, the Non-RT RIC **257** may receive parameters or external enrichment information from external servers. Such information may be utilized by the Near-RT RIC **259** and may be received at the SMO Framework **255** or the Non-RT RIC **257** from non-network data sources or from network functions. In some examples, the Non-RT RIC **257** or the Near-RT RIC **259** may be configured to tune RAN behavior or performance. For example, the Non-RT RIC **257** may monitor long-term trends and patterns for performance and employ AI/ML models to perform corrective actions through the SMO Framework **255** (such as reconfiguration via O1) or via creation of RAN management policies (such as A1 policies).

[0102] FIGS. **3**A, **3**B, and **3**C illustrate several example components (represented by corresponding blocks) that may be incorporated into a UE **304** (which may correspond to any of the UEs described herein), a base station **302** (which may correspond to any of the base stations described herein), and a network entity **306** (which may correspond to or embody any of the network functions described herein, including the location server **230** and the LMF **270**, or alternatively may be independent from the NG-RAN **220** and/or 5GC **210**/**260** infrastructure depicted in FIGS. **2**A and **2**B, such as a private network) to support the operations described herein. It will be appreciated that these components may be implemented in different types of apparatuses in different implementations (e.g., in an ASIC, in a system-on-chip (SoC), etc.). The illustrated components may also be incorporated into other apparatuses in a communication system. For example, other apparatuses in a system may include components similar to those described to provide similar functionality. Also, a given apparatus may contain one or more of the components. For example, an apparatus may include multiple transceiver components that enable the apparatus to operate on multiple carriers and/or communicate via different technologies.

[0103] The UE **304** and the base station **302** each include one or more wireless wide area network (WWAN) transceivers **310** and **350**, respectively, providing means for communicating (e.g., means for transmitting, means for receiving, means for measuring, means for tuning, means for refraining from transmitting, etc.) via one or more wireless communication networks (not shown), such as an NR network, an LTE network, a GSM network, and/or the like. The WWAN transceivers **310** and **350** may each be connected to one or more antennas **316** and **356**, respectively, for communicating with other network nodes, such as other UEs, access points, base stations (e.g., eNBs, gNBs), etc., via at least one designated RAT (e.g., NR, LTE, GSM, etc.) over a wireless communication medium of interest (e.g., some set of time/frequency resources in a particular frequency spectrum). The WWAN transceivers **310** and **350** may be variously configured for transmitting and encoding signals **318** and **358** (e.g., messages, indications, information, and so on), respectively, and, conversely, for receiving and decoding signals **318** and **358** (e.g., messages, indications, information, pilots, and so on), respectively, in accordance with the designated RAT. Specifically, the WWAN transceivers **310** and **350** include one or more transmitters **314** and **354**, respectively, for transmitting and encoding signals **318** and **358**, respectively, and one or more receivers **312** and **352**, respectively, for receiving and decoding signals **318** and **358**, respectively.

[0104] The UE **304** and the base station **302** each also include, at least in some cases, one or more short-range wireless transceivers **320** and **360**, respectively. The short-range wireless transceivers **320** and **360** may be connected to one or more antennas **326** and **366**, respectively, and provide means for communicating (e.g., means for transmitting, means for receiving, means for measuring, means for tuning, means for refraining from transmitting, etc.) with other network nodes, such as other UEs, access points, base stations, etc., via at least one designated RAT (e.g., Wi-Fi, LTE Direct, BLUETOOTH®, ZIGBEE®, Z-WAVE®, PC5, dedicated short-range communications (DSRC), wireless access for vehicular environments (WAVE), near-field communication (NFC), ultra-wideband (UWB), etc.) over a wireless communication medium of interest. The short-range wireless transceivers **320** and **360** may be variously configured for transmitting and encoding signals **328** and **368** (e.g., messages, indications, information, and so on), respectively, and, conversely, for receiving and decoding signals **328** and **368** (e.g., messages, indications, information, pilots, and so on), respectively, in accordance with the designated RAT. Specifically, the short-range wireless transceivers **320** and **360** include one or more transmitters **324** and **364**, respectively, for transmitting and encoding signals **328** and **368**, respectively, and one or more receivers **322** and **362**, respectively, for receiving and decoding signals **328** and **368**, respectively. As specific examples, the short-range wireless transceivers **320** and **360** may be Wi-Fi transceivers, BLUETOOTH® transceivers, ZIGBEE® and/or Z-WAVE® transceivers, NFC transceivers, UWB transceivers, or vehicle-to-vehicle (V2V) and/or vehicle-to-everything (V2X) transceivers.

[0105] The UE **304** and the base station **302** also include, at least in some cases, satellite signal interfaces **330** and **370**, which each include one or more satellite signal receivers **332** and **372**, respectively, and may optionally include one or more satellite signal transmitters **334** and **374**, respectively. In some cases, the base station **302** may be a terrestrial base station that may communicate with space vehicles (e.g., space vehicles **112**) via the satellite signal interface **370**. In other cases, the base station **302** may be a space vehicle (or other non-terrestrial entity) that uses the satellite signal interface **370** to communicate with terrestrial networks and/or other space vehicles.

[0106] The satellite signal receivers **332** and **372** may be connected to one or more antennas **336** and **376**, respectively, and may provide means for receiving and/or measuring satellite positioning/communication signals **338** and **378**, respectively. Where the satellite signal receiver(s) **332** and **372** are satellite positioning system receivers, the satellite positioning/communication signals **338** and **378** may be global positioning system (GPS) signals, global navigation satellite system (GLONASS) signals, Galileo signals, Beidou signals, Indian Regional Navigation Satellite System (NAVIC), Quasi-Zenith Satellite System (QZSS) signals, etc. Where the satellite signal receiver(s) **332** and **372** are non-terrestrial network (NTN) receivers, the satellite positioning/communication signals **338** and **378** may be communication signals (e.g., carrying control and/or user data) originating from a 5G network. The satellite signal receiver(s) **332** and **372** may comprise any suitable hardware and/or software for receiving and processing satellite positioning/communication signals **338** and **378**, respectively. The satellite signal receiver(s) **332** and **372** may request information and operations as appropriate from the other systems, and, at least in some cases, perform calculations to determine locations of the UE **304** and the base station **302**, respectively, using measurements obtained by any suitable satellite positioning system algorithm.

[0107] The optional satellite signal transmitter(s) **334** and **374**, when present, may be connected to the one or more antennas **336** and **376**, respectively, and may provide means for transmitting satellite positioning/communication signals **338** and **378**, respectively. Where the satellite signal transmitter(s) **374** are satellite positioning system transmitters, the satellite positioning/communication signals **378** may be GPS signals, GLONASS® signals, Galileo signals, Beidou signals, NAVIC, QZSS signals, etc. Where the satellite signal transmitter(s) **334** and **374** are NTN transmitters, the satellite positioning/communication signals **338** and **378** may be communication signals (e.g., carrying control and/or user data) originating from a 5G network. The satellite signal transmitter(s) **334** and **374** may comprise any suitable hardware and/or software for transmitting satellite positioning/communication signals **338** and **378**, respectively. The satellite signal transmitter(s) **334** and **374** may request information and operations as appropriate from the other systems.

[0108] The base station **302** and the network entity **306** each include one or more network transceivers **380** and **390**, respectively, providing means for communicating (e.g., means for transmitting, means for receiving, etc.) with other network entities (e.g., other base stations **302**, other network entities **306**). For example, the base station **302** may employ the one or more network transceivers **380** to communicate with other base stations **302** or network entities **306** over one or more wired or wireless backhaul links. As another example, the network entity **306** may employ the one or more network transceivers **390** to communicate with one or more base station **302** over one or more wired or wireless backhaul links, or with other network entities **306** over one or more wired or wireless core network interfaces.

[0109] A transceiver may be configured to communicate over a wired or wireless link. A transceiver (whether a wired transceiver or a wireless transceiver) includes transmitter circuitry (e.g., transmitters **314**, **324**, **354**, **364**) and receiver circuitry (e.g., receivers **312**, **322**, **352**, **362**). A transceiver may be an integrated device (e.g., embodying transmitter circuitry and receiver circuitry in a single device) in some implementations, may comprise separate transmitter circuitry and separate receiver circuitry in some implementations, or may be embodied in other ways in other implementations. The transmitter circuitry and receiver circuitry of a wired transceiver (e.g., network transceivers **380** and **390** in some implementations) may be coupled to one or more wired network interface ports. Wireless transmitter circuitry (e.g., transmitters **314**, **324**, **354**, **364**) may include or be coupled to a plurality of antennas (e.g., antennas **316**, **326**, **356**, **366**), such as an antenna array, that permits the respective apparatus (e.g., UE **304**, base station **302**) to perform transmit “beamforming,” as described herein. Similarly, wireless receiver circuitry (e.g., receivers **312**, **322**, **352**, **362**) may include or be coupled to a plurality of antennas (e.g., antennas **316**, **326**, **356**, **366**), such as an antenna array, that permits the respective apparatus (e.g., UE **304**, base station **302**) to perform receive beamforming, as described herein. In an aspect, the transmitter circuitry and receiver circuitry may share the same plurality of antennas (e.g., antennas **316**, **326**, **356**, **366**), such that the respective apparatus can only receive or transmit at a given time, not both at the same time. A wireless transceiver (e.g., WWAN transceivers **310** and **350**, short-range wireless transceivers **320** and **360**) may also include a network listen module (NLM) or the like for performing various measurements.

[0110] As used herein, the various wireless transceivers (e.g., transceivers **310**, **320**, **350**, and **360**, and network transceivers **380** and **390** in some implementations) and wired transceivers (e.g., network transceivers **380** and **390** in some implementations) may generally be characterized as “a transceiver," "at least one transceiver," or "one or more transceivers." As such, whether a particular transceiver is a wired or wireless transceiver may be inferred from the type of communication performed. For example, backhaul communication between network devices or servers will generally relate to signaling via a wired transceiver, whereas wireless communication between a UE (e.g., UE **304**) and a base station (e.g., base station **302**) will generally relate to signaling via a wireless transceiver.

[0111] The UE **304**, the base station **302**, and the network entity **306** also include other components that may be used in conjunction with the operations as disclosed herein. The UE **304**, the base station **302**, and the network entity **306** include one or more processors **342**, **384**, and **394**, respectively, for providing functionality relating to, for example, wireless communication, and for providing other processing functionality. The processors **342**, **384**, and **394** may therefore provide means for processing, such as means for determining, means for calculating, means for receiving, means for transmitting, means for indicating, etc. In an aspect, the processors **342**, **384**, and **394** may include, for example, one or more general purpose processors, multi-core processors, central processing units (CPUs), ASICs, digital signal processors (DSPs), field programmable gate arrays (FPGAs), other programmable logic devices or processing circuitry, or various combinations thereof.

[0112] The UE **304**, the base station **302**, and the network entity **306** include memory circuitry implementing memories **340**, **386**, and **396** (e.g., each including a memory device), respectively, for maintaining information (e.g., information indicative of reserved resources, thresholds, parameters, and so on). The memories **340**, **386**, and **396** may therefore provide means for storing, means for retrieving, means for maintaining, etc. In some cases, the UE **304**, the base station **302**, and the network entity **306** may include waveform component **348**, **388**, and **398**, respectively. The waveform component **348**, **388**, and **398** may be hardware circuits that are part of or coupled to the processors **342**, **384**, and **394**, respectively, that, when executed, cause the UE **304**, the base station **302**, and the network entity **306** to perform the functionality described herein. In other aspects, the waveform component **348**, **388**, and **398** may be external to the processors **342**, **384**, and **394** (e.g., part of a modem processing system, integrated with another processing system, etc.). Alternatively, the waveform component **348**, **388**, and **398** may be memory modules stored in the memories **340**, **386**, and **396**, respectively, that, when executed by the processors **342**, **384**, and **394** (or a modem processing system, another processing system, etc.), cause the UE **304**, the base station **302**, and the network entity **306** to perform the functionality described herein. FIG. **3**A illustrates possible locations of the waveform component **348**, which may be, for example, part of the one or more WWAN transceivers **310**, the memory **340**, the one or more processors **342**, or any combination thereof, or may be a standalone component. FIG. **3**B illustrates possible locations of the waveform component **388**, which may be, for example, part of the one or more WWAN transceivers **350**, the memory **386**, the one or more processors **384**, or any combination thereof, or may be a standalone component. FIG. **3**C illustrates possible locations of the waveform component **398**, which may be, for example, part of the one or more network transceivers **390**, the memory **396**, the one or more processors **394**, or any combination thereof, or may be a standalone component.

[0113] The UE **304** may include one or more sensors **344** coupled to the one or more processors **342** to provide means for sensing or detecting movement and/or orientation information that is independent of motion data derived from signals received by the one or more WWAN transceivers **310**, the one or more short-range wireless transceivers **320**, and/or the satellite signal interface **330**. By way of example, the sensor(s) **344** may include an accelerometer (e.g., a micro-electrical mechanical systems (MEMS) device), a gyroscope, a geomagnetic sensor (e.g., a compass), an altimeter (e.g., a barometric pressure altimeter), and/or any other type of movement detection sensor. Moreover, the sensor(s) **344** may include a plurality of different types of devices and combine their outputs in order to provide motion information. For example, the sensor(s) **344** may use a combination of a multi-axis accelerometer and orientation sensors to provide the ability to

compute positions in two-dimensional (2D) and/or three-dimensional (3D) coordinate systems.
[0114] In addition, the UE **304** includes a user interface **346** providing means for providing indications (e.g., audible and/or visual indications) to a user and/or for receiving user input (e.g., upon user actuation of a sensing device such a keypad, a touch screen, a microphone, and so on). Although not shown, the base station **302** and the network entity **306** may also include user interfaces.
[0115] Referring to the one or more processors **384** in more detail, in the downlink, IP packets from the network entity **306** may be provided to the processor **384**. The one or more processors **384** may implement functionality for an RRC layer, a packet data convergence protocol (PDCP) layer, a radio link control (RLC) layer, and a medium access control (MAC) layer. The one or more processors **384** may provide RRC layer functionality associated with broadcasting of system information (e.g., master information block (MIB), system information blocks (SIBs)), RRC connection control (e.g., RRC connection paging, RRC connection establishment, RRC connection modification, and RRC connection release), inter-RAT mobility, and measurement configuration for UE measurement reporting; PDCP layer functionality associated with header compression/decompression, security (ciphering, deciphering, integrity protection, integrity verification), and handover support functions; RLC layer functionality associated with the transfer of upper layer PDUs, error correction through automatic repeat request (ARQ), concatenation, segmentation, and reassembly of RLC service data units (SDUs), re-segmentation of RLC data PDUs, and reordering of RLC data PDUs; and MAC layer functionality associated with mapping between logical channels and transport channels, scheduling information reporting, error correction, priority handling, and logical channel prioritization.
[0116] The transmitter **354** and the receiver **352** may implement Layer-1 (L1) functionality associated with various signal processing functions. Layer-1, which includes a physical (PHY) layer, may include error detection on the transport channels, forward error correction (FEC) coding/decoding of the transport channels, interleaving, rate matching, mapping onto physical channels, modulation/demodulation of physical channels, and MIMO antenna processing. The transmitter **354** handles mapping to signal constellations based on various modulation schemes (e.g., binary phase-shift keying (BPSK), quadrature phase-shift keying (QPSK), M-phase-shift keying (M-PSK), M-quadrature amplitude modulation (M-QAM)). The coded and modulated symbols may then be split into parallel streams. Each stream may then be mapped to an orthogonal frequency division multiplexing (OFDM) subcarrier, multiplexed with a reference signal (e.g., pilot) in the time and/or frequency domain, and then combined together using an inverse fast Fourier transform (IFFT) to produce a physical channel carrying a time domain OFDM symbol stream. The OFDM symbol stream is spatially precoded to produce multiple spatial streams. Channel estimates from a channel estimator may be used to determine the coding and modulation scheme, as well as for spatial processing. The channel estimate may be derived from a reference signal and/or channel condition feedback transmitted by the UE **304**. Each spatial stream may then be provided to one or more different antennas **356**. The transmitter **354** may modulate an RF carrier with a respective spatial stream for transmission.
[0117] At the UE **304**, the receiver **312** receives a signal through its respective antenna(s) **316**. The receiver **312** recovers information modulated onto an RF carrier and provides the information to the one or more processors **342**. The transmitter **314** and the receiver **312** implement Layer-1 functionality associated with various signal processing functions. The receiver **312** may perform spatial processing on the information to recover any spatial streams destined for the UE **304**. If multiple spatial streams are destined for the UE **304**, they may be combined by the receiver **312** into a single OFDM symbol stream. The receiver **312** then converts the OFDM symbol stream from the time-domain to the frequency domain using a fast Fourier transform (FFT). The frequency domain signal comprises a separate OFDM symbol stream for each subcarrier of the OFDM signal. The symbols on each subcarrier, and the reference signal, are recovered and demodulated by

determining the most likely signal constellation points transmitted by the base station **302**. These soft decisions may be based on channel estimates computed by a channel estimator. The soft decisions are then decoded and de-interleaved to recover the data and control signals that were originally transmitted by the base station **302** on the physical channel. The data and control signals are then provided to the one or more processors **342**, which implements Layer-3 (L3) and Layer-2 (L2) functionality.

[0118] In the downlink, the one or more processors **342** provides demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, and control signal processing to recover IP packets from the core network. The one or more processors **342** are also responsible for error detection.

[0119] Similar to the functionality described in connection with the downlink transmission by the base station **302**, the one or more processors **342** provides RRC layer functionality associated with system information (e.g., MIB, SIBs) acquisition, RRC connections, and measurement reporting; PDCP layer functionality associated with header compression/decompression, and security (ciphering, deciphering, integrity protection, integrity verification); RLC layer functionality associated with the transfer of upper layer PDUs, error correction through ARQ, concatenation, segmentation, and reassembly of RLC SDUs, re-segmentation of RLC data PDUs, and reordering of RLC data PDUs; and MAC layer functionality associated with mapping between logical channels and transport channels, multiplexing of MAC SDUs onto transport blocks (TBs), demultiplexing of MAC SDUs from TBs, scheduling information reporting, error correction through hybrid automatic repeat request (HARQ), priority handling, and logical channel prioritization.

[0120] Channel estimates derived by the channel estimator from a reference signal or feedback transmitted by the base station **302** may be used by the transmitter **314** to select the appropriate coding and modulation schemes, and to facilitate spatial processing. The spatial streams generated by the transmitter **314** may be provided to different antenna(s) **316**. The transmitter **314** may modulate an RF carrier with a respective spatial stream for transmission.

[0121] The uplink transmission is processed at the base station **302** in a manner similar to that described in connection with the receiver function at the UE **304**. The receiver **352** receives a signal through its respective antenna(s) **356**. The receiver **352** recovers information modulated onto an RF carrier and provides the information to the one or more processors **384**.

[0122] In the uplink, the one or more processors **384** provides demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, control signal processing to recover IP packets from the UE **304**. IP packets from the one or more processors **384** may be provided to the core network. The one or more processors **384** are also responsible for error detection.

[0123] For convenience, the UE **304**, the base station **302**, and/or the network entity **306** are shown in FIGS. **3**A, **3**B, and **3**C as including various components that may be configured according to the various examples described herein. It will be appreciated, however, that the illustrated components may have different functionality in different designs. In particular, various components in FIGS. **3**A to **3**C are optional in alternative configurations and the various aspects include configurations that may vary due to design choice, costs, use of the device, or other considerations. For example, in case of FIG. **3**A, a particular implementation of UE **304** may omit the WWAN transceiver(s) **310** (e.g., a wearable device or tablet computer or personal computer (PC) or laptop may have Wi-Fi and/or BLUETOOTH® capability without cellular capability), or may omit the short-range wireless transceiver(s) **320** (e.g., cellular-only, etc.), or may omit the satellite signal interface **330**, or may omit the sensor(s) **344**, and so on. In another example, in case of FIG. **3**B, a particular implementation of the base station **302** may omit the WWAN transceiver(s) **350** (e.g., a Wi-Fi "hotspot" access point without cellular capability), or may omit the short-range wireless transceiver(s) **360** (e.g., cellular-only, etc.), or may omit the satellite signal interface **370**, and so on.

For brevity, illustration of the various alternative configurations is not provided herein, but would be readily understandable to one skilled in the art.

[0124] The various components of the UE **304**, the base station **302**, and the network entity **306** may be communicatively coupled to each other over data buses **308**, **382**, and **392**, respectively. In an aspect, the data buses **308**, **382**, and **392** may form, or be part of, a communication interface of the UE **304**, the base station **302**, and the network entity **306**, respectively. For example, where different logical entities are embodied in the same device (e.g., gNB and location server functionality incorporated into the same base station **302**), the data buses **308**, **382**, and **392** may provide communication between them.

[0125] The components of FIGS. **3**A, **3**B, and **3**C may be implemented in various ways. In some implementations, the components of FIGS. **3**A, **3**B, and **3**C may be implemented in one or more circuits such as, for example, one or more processors and/or one or more ASICs (which may include one or more processors). Here, each circuit may use and/or incorporate at least one memory component for storing information or executable code used by the circuit to provide this functionality. For example, some or all of the functionality represented by blocks **310** to **346** may be implemented by processor and memory component(s) of the UE **304** (e.g., by execution of appropriate code and/or by appropriate configuration of processor components). Similarly, some or all of the functionality represented by blocks **350** to **388** may be implemented by processor and memory component(s) of the base station **302** (e.g., by execution of appropriate code and/or by appropriate configuration of processor components). Also, some or all of the functionality represented by blocks **390** to **398** may be implemented by processor and memory component(s) of the network entity **306** (e.g., by execution of appropriate code and/or by appropriate configuration of processor components). For simplicity, various operations, acts, and/or functions are described herein as being performed "by a UE," "by a base station," "by a network entity," etc. However, as will be appreciated, such operations, acts, and/or functions may actually be performed by specific components or combinations of components of the UE **304**, base station **302**, network entity **306**, etc., such as the processors **342**, **384**, **394**, the transceivers **310**, **320**, **350**, and **360**, the memories **340**, **386**, and **396**, the waveform component **348**, **388**, and **398**, etc.

[0126] In some designs, the network entity **306** may be implemented as a core network component. In other designs, the network entity **306** may be distinct from a network operator or operation of the cellular network infrastructure (e.g., NG RAN **220** and/or 5GC **210**/**260**). For example, the network entity **306** may be a component of a private network that may be configured to communicate with the UE **304** via the base station **302** or independently from the base station **302** (e.g., over a non-cellular communication link, such as Wi-Fi).

[0127] Wireless communication signals (e.g., RF signals configured to carry OFDM symbols in accordance with a wireless communications standard, such as LTE, NR, etc.) transmitted between a UE and a base station can be used for environment sensing (also referred to as "RF sensing" or "radar"). Using wireless communication signals for environment sensing can be regarded as consumer-level radar with advanced detection capabilities that enable, among other things, touchless/device-free interaction with a device/system. The wireless communication signals may be cellular communication signals, such as LTE or NR signals, WLAN signals, such as Wi-Fi signals, etc. As a particular example, the wireless communication signals may be an OFDM waveform as utilized in LTE and NR. High-frequency communication signals, such as millimeter wave (mmW) RF signals, are especially beneficial to use as sensing signals because the higher frequency provides, at least, more accurate range (distance) detection.

[0128] Possible use cases of RF sensing include health monitoring use cases, such as heartbeat detection, respiration rate monitoring, and the like, gesture recognition use cases, such as human activity recognition, keystroke detection, sign language recognition, and the like, contextual information acquisition use cases, such as location detection/tracking, direction finding, range estimation, and the like, and automotive sensing use cases, such as smart cruise control, collision avoidance, and the like.

[0129] There are different types of sensing, including monostatic sensing (also referred to as "active sensing") and bistatic sensing (also referred to as "passive sensing"). FIGS. **4**A and **4**B illustrate these different types of sensing. Specifically, FIG. **4**A is a diagram **400** illustrating a monostatic sensing scenario and FIG. **4**B is a diagram **430** illustrating a bistatic sensing scenario. In FIG. **4**A, the transmitter (Tx) and receiver (Rx) are co-located in the same sensing device **404** (e.g., a UE). The sensing device **404** transmits one or more RF sensing signals **434** (e.g., uplink or sidelink positioning reference signals (PRS) where the sensing device **404** is a UE), and some of the RF sensing signals **434** reflect off a target object **406**. The sensing device **404** can measure various properties (e.g., times of arrival (ToAs), angles of arrival (AoAs), phase shift, etc.) of the reflections **436** of the RF sensing signals **434** to determine characteristics of the target object **406** (e.g., size, shape, speed, motion state, etc.).

[0130] In FIG. **4**B, the transmitter (Tx) and receiver (Rx) are not co-located, that is, they are separate devices (e.g., a UE and a base station). Note that while FIG. **4**B illustrates using a downlink RF signal as the RF sensing signal **432**, uplink RF signals or sidelink RF signals can also be used as RF sensing signals **432**. In a downlink scenario, as shown, the transmitter is a base station and the receiver is a UE, whereas in an uplink scenario, the transmitter is a UE and the receiver is a base station.

[0131] Referring to FIG. **4**B in greater detail, the transmitter device **402** transmits RF sensing signals **432** and **434** (e.g., positioning reference signals (PRS)) to the sensing device **404**, but some of the RF sensing signals **434** reflect off a target object **406**. The sensing device **404** (also referred to as the "sensing device") can measure the times of arrival (ToAs) of the RF sensing signals **432** received directly from the transmitter device and the ToAs of the reflections **436** of the RF sensing signals **434** reflected from the target object **406**.

[0132] More specifically, as described above, a transmitter device (e.g., a base station) may transmit a single RF signal or multiple RF signals to a sensing device (e.g., a UE). However, the receiver may receive multiple RF signals corresponding to each transmitted RF signal due to the propagation characteristics of RF signals through multipath channels. Each path may be associated with a cluster of one or more channel taps. Generally, the time at which the receiver detects the first cluster of channel taps is considered the ToA of the RF signal on the line-of-site (LOS) path (i.e., the shortest path between the transmitter and the receiver). Later clusters of channel taps are considered to have reflected off objects between the transmitter and the receiver and therefore to have followed non-LOS (NLOS) paths between the transmitter and the receiver.

[0133] Thus, referring back to FIG. **4**B, the RF sensing signals **432** followed the LOS path between the transmitter device **402** and the sensing device **404**, and the RF sensing signals **434** followed an NLOS path between the transmitter device **402** and the sensing device **404** due to reflecting off the target object **406**. The transmitter device **402** may have transmitted multiple RF sensing signals **432**, **434**, some of which followed the LOS path and others of which followed the NLOS path. Alternatively, the transmitter device **402** may have transmitted a single RF sensing signal in a broad enough beam that a portion of the RF sensing signal followed the LOS path (RF sensing signal **432**) and a portion of the RF sensing signal followed the NLOS path (RF sensing signal **434**).

[0134] Based on the ToA of the LOS path, the ToA of the NLOS path, and the speed of light, the sensing device **404** can determine the distance to the target object(s). For example, the sensing device **404** can calculate the distance to the target object as the difference between the ToA of the LOS path and the ToA of the NLOS path multiplied by the speed of light. In addition, if the sensing device **404** is capable of receive beamforming, the sensing device **404** may be able to determine the general direction to a target object as the direction (angle) of the receive beam on which the RF sensing signal following the NLOS path was received. That is, the sensing device **404** may determine the direction to the target object as the angle of arrival (AoA) of the RF sensing signal, which is the angle of the receive beam used to receive the RF sensing signal. The sensing device

404 may then optionally report this information to the transmitter device **402**, its serving base station, an application server associated with the core network, an external client, a third-party application, or some other sensing entity. Alternatively, the sensing device **404** may report the ToA measurements to the transmitter device **402**, or other sensing entity (e.g., if the sensing device **404** does not have the processing capability to perform the calculations itself), and the transmitter device **402** may determine the distance and, optionally, the direction to the target object **406**.
[0135] Note that if the RF sensing signals are uplink RF signals transmitted by a UE to a base station, the base station would perform object detection based on the uplink RF signals just like the UE does based on the downlink RF signals.
[0136] Like conventional radar, wireless communication-based sensing signals can be used to estimate the range (distance), velocity (Doppler), and angle (AoA) of a target object. However, the performance (e.g., resolution and maximum values of range, velocity, and angle) may depend on the design of the reference signal.
[0137] FIG. **5** illustrates an example call flow **500** for an NR-based sensing procedure (e.g., a bistatic sensing procedure) in which the network configures the sensing parameters, according to aspects of the disclosure. Although FIG. **5** illustrates a network-coordinated sensing procedure, the sensing procedure could be coordinated over sidelink channels.
[0138] At stage **505**, a sensing server **570** (e.g., inside or outside the core network) sends a request for network (NW) information to a gNB **522** (e.g., the serving gNB of a UE **504**). The request may be for a list of the UE's **504** serving cell and any neighboring cells. At stage **510**, the gNB **522** sends the requested information to the sensing server **570**. At stage **515**, the sensing server **570** sends a request for sensing capabilities to the UE **504**. At stage **520**, the UE **504** provides its sensing capabilities to the sensing server **570**.
[0139] At stage **525**, the sensing server **570** sends a configuration to the UE **504** indicating one or more reference signal (RS) resources that will be transmitted for sensing. The reference signal resources may be transmitted by the serving and/or neighboring cells identified at stage **510**. In some cases, the NR-based sensing procedure illustrated in FIG. **5** may be a sensing-only procedure or a joint communication and sensing (JCS) procedure. In the case of a sensing-only procedure, the reference signal resources may be reference signal resources specifically configured for sensing purposes. In the case of a JCS procedure, the reference signal resources may be reference signal resources for communication that can also be used for sensing purposes. Alternatively, the reference signal resources for sensing may be multiplexed (e.g., time-division multiplexed) with reference signal resources for communication. For example, the reference signal resources for communication may be an OFDM waveform, while the reference signal resources for sensing may be a FMCW waveform.
[0140] At stage **530**, the sensing server **570** sends a request for sensing information to the UE **504**. The UE **504** then measures the transmitted reference signals and, at stage **535**, sends the measurements, or any sensing results determined from the measurements, to the sensing server **570**.
[0141] In an aspect, the communication between the UE **504** and the sensing server **570** may be via the LTE positioning protocol (LPP). The communication between the sensing server **570** and the gNB may be via NR positioning protocol type A (NRPPa).
[0142] Aspects of the disclosure relate to hybrid continuous-wave radar techniques for secure and interference robust RF sensing. In some examples, the hybrid continuous-wave radar techniques overcome various challenges associated with FMCW radar transmissions necessary for robust and scalable RF sensing operations in networks, such as 3GPP NR 5G Advanced networks. In some examples, the hybrid continuous-wave radar techniques may also enable secure sensing operations. That is, for example, an attacking transmission may be filtered out through use of scrambled FMCW waveform components in the reference signal transmissions, while certain performance aspects are maintained through use of unscrambled FMCW waveform components in the reference

signal transmissions.

[0143] As described herein, these hybrid continuous-wave radar techniques and corresponding waveform transmissions are used in examples of RF sensing operations. In some cases, however, these hybrid continuous-wave radar techniques may also be used for positioning operations. That is, for example, 3GPP 6G networks and other advanced networks may use these hybrid continuous-wave radar techniques for secure and interference robust positioning operations (e.g., PRS waveform transmissions having unscrambled and scrambled FMCW waveform components).

[0144] FIG. **6** illustrates an example of a sensing network **600** with multiple sensing nodes according to aspects of the disclosure. The sensing network **600** may correspond to, or include aspects of, the wireless communications system **100**. Each of the first sensing node **604***a*, second sensing node **604***b*, and third sensing node **604***c* may correspond to, or include aspects of, the UE **104**, UE **204**, UE **304**, or any other UE or sensing node described herein.

[0145] In the example of FIG. **6**, the first sensing node **604***a* may be a victim sensing node. The first sensing node **604***a* may transmit a first FMCW sensing signal that may reflect off of target **606**. The first sensing node **604***a* may receive the first reflection of the first FMCW sensing signal transmission and may measure the first reflection for sensing purposes. The second sensing node **604***b* may be a first aggressor sensing node that transmits a second FMCW sensing signal that may reflect off of the target **606**. A second reflection of the second FMCW sensing signal transmission may be received by the first sensing node **604***a*, which may measure the second reflection for sensing purposes. The third sensing node **604***c* may be a second aggressor sensing node that transmits a third FMCW sensing signal that may reflect off of the target **606**. A third reflection of the second FMCW sensing signal transmission may also be received by the first sensing node **604***a*, which may also measure the third reflection for sensing purposes.

[0146] This example scenario shows the cross-node interference that may occur when FMCW sensing signals are used by multiple sensing nodes for sensing operations. That is, for example, the first sensing node **604***a* may not be able to discern which of the first reflection, the second reflection, or the third reflection corresponds to the first FMCW sensing signal transmission. Thus, the second reflection and the third reflection may cause interference resulting in inaccurate sensing measurements. The cross-node interference may become exacerbated in larger networks with substantial sensing operations being performed because a limited number of parameters (e.g., a slope of the waveform) can be configured for FMCW sensing signals by each sensing node.

[0147] FIG. **7** illustrates an example of an interference simulation graph **700** for received sensing signals, according to aspects of the disclosure. The interference simulation graph **700** illustrates the cross-node interference in terms of a range Doppler map (RDM) of the FMCW sensing signals from the sensing network **600**. The interference simulation graph **700** showing the RDM of the FMCW sensing signals is plotted using a velocity axis and a range axis.

[0148] That is, for example, each of the first sensing node **604***a*, second sensing node **604***b*, and third sensing node **604***c* may transmit FMCW sensing signals having one or more of the same parameters (e.g., a same slope of the waveform). Thus, the first sensing node **604***a* may observe the FMCW sensing signals of the other sensing nodes. That is, the interference simulation graph **700** shows the target reflection corresponding to the first reflection of the first FMCW sensing signal, as well as the first interference signal corresponding to the second reflection of the second FMCW sensing signal transmission from the first aggressor sensing node, and the second interference signal corresponding to the third reflection of the third FMCW sensing signal transmission from the second aggressor sensing node.

[0149] FIG. **8** illustrates an example of a circuit block diagram **800** of one or more devices that perform RF sensing, according to aspects of the disclosure. Aspects of the circuit block diagram **800** may be included in any UE, or other sensing node described herein to support hybrid continuous-wave radar techniques for secure and interference robust RF sensing. Additionally, or alternatively, one or more aspects of the circuit block diagram **800** may be separately incorporated in the various sensing nodes that transmit and/or receive FMCW sensing signals as described herein.

[0150] In some examples, a sensing node may transmit and receive scrambled sensing signal transmissions. For example, the circuit block diagram **800** may be used as a phase-coded FMCW (PC-FMCW) transceiver in a sensing node. With reference to the example of FIG. **8**, a narrowband phase coder block may operate to apply a narrowband phase code in the transmitter side. That is, for example, a modulator block may receive the narrowband phase code information and modulate a wideband FMCW signal received from a wideband FMCW signal generator block with the phase code information. The resulting signal may constitute a wideband PC-FMCW signal, which the modulator block may pass to a power amplifier prior to transmitting the wideband PC-FMCW signal for use as a sensing signal via one or more antennas.

[0151] A sensing node may receive a wideband PC-FMCW signal transmission via one or more antennas. This wideband PC-FMCW signal may constitute a scrambled signal received by the circuit block diagram **800**. For example, the circuit block diagram **800** may be designed to pass the receiving scrambled signal to a low noise amplifier (LNA). The LNA may pass the received scrambled signal into a mixer. The mixer may combine the received scrambled signal from the LNA with a wideband FMCW signal from the wideband FMCW signal generator block. The combined signal may be passed to a low pass filter (LPF) block, then to a low rate analog to digital converter (ADC), and then to a baseband processing block.

[0152] In some examples, the baseband processing block may receive and apply descrambling information associated with the narrowband PC information to descramble the wideband PC-FMCW signal. Accordingly, the circuit block diagram **800** may enable the sensing node to achieve at least some level of interference mitigation in accordance with some aspects.

[0153] FIGS. **9**A to **9**C illustrate examples of time and frequency graphs for signals corresponding to the circuit block diagram **800** of FIG. **8**, according to aspects of the disclosure. In the example of FIG. **9**A, a first time graph **910** and first frequency graph **920** may represent the wideband FMCW signal from the wideband FMCW signal generator block. In the first time graph **910**, time is represented horizontally (on the X axis) with time increasing from left to right, and amplitude is represented vertically (on the Y axis) with the amplitude of the wideband FMCW signal increasing (or decreasing) from bottom to top. In the first frequency graph **920**, frequency is represented horizontally (on the X axis) with frequency increasing from left to right, and magnitude is represented vertically (on the Y axis) with the magnitude of the wideband FMCW signal increasing (or decreasing) from bottom to top.

[0154] In the example of FIG. **9**B, a second time graph **930** and second frequency graph **940** may represent the narrowband PC signal from the narrowband phase coder block. In the second time graph **930**, time is represented horizontally (on the X axis) with time increasing from left to right, and amplitude is represented vertically (on the Y axis) with the amplitude of the narrowband PC signal increasing (or decreasing) from bottom to top. In the second frequency graph **940**, frequency is represented horizontally (on the X axis) with frequency increasing from left to right, and magnitude is represented vertically (on the Y axis) with the magnitude of the narrowband PC signal increasing (or decreasing) from bottom to top.

[0155] In the example of FIG. **9**C, a third time graph **950** and third frequency graph **960** may represent the wideband PC-FMCW signal that may be transmitted by the PC-FMCW transceiver in the circuit block diagram **800**. In the third time graph **950**, time is represented horizontally (on the X axis) with time increasing from left to right, and amplitude is represented vertically (on the Y axis) with the amplitude of the wideband PC-FMCW signal increasing (or decreasing) from bottom to top. In the third frequency graph **960**, frequency is represented horizontally (on the X axis) with frequency increasing from left to right, and magnitude is represented vertically (on the Y axis) with the magnitude of the wideband PC-FMCW signal increasing (or decreasing) from bottom to top.

[0156] It is to be noted that the wideband PC-FMCW signal may inherit certain properties of both

PC signal transmissions and FMCW signal transmissions. That is, for example, the wideband PC-FMCW signal may include frequency ramping structures or noise-like characteristics in the frequency spectrum in accordance with some aspects.

[0157] FIG. **10** illustrates examples of range estimation graphs for unscrambled and scrambled sensing signals, according to aspects of the disclosure. In some examples, the first range estimation graph **1010** and second range estimation graph **1020** may correspond to simulation results achieved from a PC-FMCW transceiver in accordance with the circuit block diagram **800** and an FMCW transceiver.

[0158] A comparison of the sensing performance between PC-FMCW signals (e.g., scrambled signals) and FMCW signals (e.g., unscrambled signals) in range estimation with different code lengths is illustrated in FIG. **10**. For example, the first range estimation graph **1010** includes an FMCW signal plot **1012** and first PC-FMCW signal plot **1014**. The first PC-FMCW signal plot **1014** corresponds to 64 code lengths used for the first PC-FMCW signal.

[0159] For example, the second range estimation graph **1020** includes the FMCW signal plot **1012** and a second PC-FMCW signal plot **1016**. The second PC-FMCW signal plot **1016** corresponds to 512 code lengths used for the second PC-FMCW signal. It is to be noted that each signal of the FMCW signal plot **1012**, first PC-FMCW signal plot **1014**, the second PC-FMCW signal plot **1016** may have approximately the same peak **1018** or main lobe. In some cases, the range resolution of a PC-FMCW signal may be approximately the same as the range resolution of a FMCW signal. As can be seen in the second range estimation graph **1020** and second PC-FMCW signal plot **1016**, increasing the code length per chirp may raise the side lobes (e.g., peaks other than the peak of the main lobe) of PC-FMCW signal.

[0160] FIGS. **11**A to **11**C illustrate examples of range mapping diagrams and detection graphs for unscrambled and scrambled sensing signals, according to aspects of the disclosure. The examples of FIGS. **11**A to **11**C illustrate the trade-off between (1) sensing transmissions having unscrambled signals or scrambled signals with a low number of code lengths, which may be effective for accurate range detection, and (2) sensing transmissions having a higher number of code lengths in the scrambled signal, which may be effective for greater interference mitigation. In the examples of FIGS. **11**A to **11**C, the range mapping diagrams are range Doppler mapping (RDM) diagrams, and the detection graphs are constant false alarm rate (CFAR) detection graphs.

[0161] In some examples, the range mapping diagrams and detection graphs for unscrambled and scrambled sensing signals may correspond to simulation results in a sensing network, such as the sensing network **600** with multiple sensing nodes. In some examples, range mapping diagrams and detection graphs for unscrambled and scrambled sensing signals may correspond to simulation results when multiple sensing nodes use a PC-FMCW transceiver in accordance with the circuit block diagram **800** configured to transmit FMCW and PC-FMCW waveforms.

[0162] In FIG. **11**A, a first RDM diagram **1110** and first CFAR detection graph **1120** are shown for a victim sensing node. In the first RDM diagram **1110**, range is represented horizontally (on the X axis) with range in meters increasing from left to right, and velocity is represented vertically (on the Y axis) in meters/second. In the first CFAR detection graph **1120**, range is represented on the X axis with range in meters, velocity is represented on the Y axis in meters/second, and CFAR detection results are represented on the Z axis.

[0163] The first RDM diagram **1110** and first CFAR detection graph **1120** illustrate simulation results for the victim sensing node that receives a target signal reflected from an FMCW sensing signal transmission by the victim sensing node. The victim sensing node may also receive a first interference signal corresponding to an FMCW sensing signal transmission from a first aggressor sensing node. The victim sensing node may also receive a second interference signal corresponding to an FMCW sensing signal transmission from a second aggressor sensing node. As shown in the first CFAR detection graph **1120**, three peaks are detected corresponding to each of the target signal, first interference signal, and the second interference signal.

[0164] In FIG. **11**B, a second RDM diagram **1130** and second CFAR detection graph **1140** are shown for the victim sensing node. In the second RDM diagram **1130**, range is represented horizontally (on the X axis) with range in meters increasing from left to right, and velocity is represented vertically (on the Y axis) in meters/second. In the second CFAR detection graph **1140**, range is represented on the X axis with range in meters, velocity is represented on the Y axis in meters/second, and CFAR detection results are represented on the Z axis.

[0165] The second RDM diagram **1130** and second CFAR detection graph **1140** illustrate simulation results for the victim sensing node that receives a target signal reflected from a PC-FMCW sensing signal transmission by the victim sensing node. The victim sensing node may also receive a first interference signal corresponding to a PC-FMCW sensing signal transmission from a first aggressor sensing node. The victim sensing node may also receive a second interference signal corresponding to a PC-FMCW sensing signal transmission from a second aggressor sensing node. The number of phase codes in the various PC-FMCW transmissions is 64 resulting in an increase in the side lobe levels with respect to the second and third interference signals, as shown in the second RDM diagram **1130**. As shown in the second CFAR detection graph **1140**, only a single peak is detected corresponding to the target signal.

[0166] In FIG. **11**C, a third RDM diagram **1150** and third CFAR detection graph **1160** are shown for the victim sensing node. In the third RDM diagram **1150**, range is represented horizontally (on the X axis) with range in meters increasing from left to right, and velocity is represented vertically (on the Y axis) in meters/second. In the third CFAR detection graph **1160**, range is represented on the X axis with range in meters, velocity is represented on the Y axis in meters/second, and CFAR detection results are represented on the Z axis.

[0167] The third RDM diagram **1150** and third CFAR detection graph **1160** illustrate simulation results for the victim sensing node that receives a target signal reflected from a PC-FMCW sensing signal transmission by the victim sensing node. The victim sensing node may also receive a first interference signal corresponding to a PC-FMCW sensing signal transmission from a first aggressor sensing node. The victim sensing node may also receive a second interference signal corresponding to a PC-FMCW sensing signal transmission from a second aggressor sensing node. The number of phase codes in the various PC-FMCW transmissions is 512 resulting in an increase in the side lobe level with respect to the target signal, as shown in the third RDM diagram **1150**. As shown in the third CFAR detection graph **1160**, only a single peak is detected corresponding to the target signal.

[0168] By using scrambled signal transmissions, interference may be spread as illustrated in the second RDM diagram **1130** and third RDM diagram **1150**, thereby facilitating the use of advanced algorithms for target detection as illustrated in the second CFAR detection graph **1140** and third CFAR detection graph **1160**.

[0169] FIG. **12** illustrates an example of a sensing network **1200** with multiple sensing nodes according to aspects of the disclosure. The sensing network **1200** may correspond to, or include aspects of, the wireless communications system **100** or sensing network **600**. Each sensing node **1204** may correspond to, or include aspects of, the UE **104**, UE **204**, UE **304**, **604** or any other UE or sensing node described herein. Additionally, or alternatively, base station **1202** may be a sensing node and may correspond to, or include aspects of, the base station **102**, base station **202**, base station **302**, or any other base station/network device or sensing node described herein.

[0170] The sensing network **1200** with multiple sensing nodes may support the various hybrid continuous-wave radar techniques described herein. That is, for example, scrambled continuous-wave radar (e.g., FMCW) waveforms may be used for cross-node interference mitigation. In some cases, the scrambling added to the continuous-wave radar waveforms may be in the time domain. That is, for example, the scrambled continuous-wave radar waveforms may be PC-FMCW waveforms. In some cases, the scrambling added to the continuous-wave radar waveforms may be in the frequency domain. That is, for example, the scrambled continuous-wave radar waveforms may be frequency domain-scrambled digital FMCW waveforms.

[0171] It is to be noted that increasing the interference mitigation may result in smaller dynamic range (e.g., peak to side lobe level), which is also a key metric for some sensing waveform designs. That is, for example, the peak to side lobe level may be critical to achieve enough dynamic range for some use cases. In some cases, a large target object radar cross-section (RCS) may cause a small target object to be missed if the small target object is close to the large target object. That is, for example, when detecting a large target object (e.g., a bus), a small target object (e.g., a person near the bus) may go undetected if the dynamic range associated with the sensing reference signal is insufficient.

[0172] Accordingly, the hybrid continuous-wave radar techniques may include reference signal designs that combine advantages of a scrambled continuous-wave waveform (e.g., PC-FMCW waveform or a frequency domain-scrambled digital FMCW waveform) and an unscrambled continuous-wave waveform (e.g., an FMCW waveform) to achieve a tradeoff between cross-node interference mitigation and sensing dynamic range.

[0173] In some examples, the sensing node **1204** may receive an indication **1212** to transmit a sensing reference signal having one or more scrambled continuous-wave waveform components. That is, for example, when the sensing node **1204** is a UE, the base station may transmit the indication **1212** to the sensing node **1204**. The indication **1212** and/or signaling corresponding to the transmission of the sensing reference signal may be in the form of a reference signal configuration (e.g., via RRC) or other signaling (e.g., via DCI, MAC-CE, etc.) to the sensing node **1204**. When the sensing node is the base station **1202**, the indication and/or signaling may be received from another base station or a network element. In some examples, the sensing node **1204** may transmit a hybrid continuous-wave radar signal towards a target **1206** based on the indication **1212**.

[0174] The indication **1212** and/or signaling may indicate various information related to the sensing operation. For example, the sensing node **1204** may receive signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission. In some cases, the reference signal configuration received by the sensing node **1204** may indicate a format of the hybrid continuous-wave radar signal to use for transmission on a reference signal resource. For example, the reference signal configuration may indicate a number of scrambled continuous-wave waveform components in the format of the hybrid continuous-wave radar signal.

[0175] That is, for example, the number of scrambled continuous-wave waveform components may be based on an estimation of interference associated with the reference signal resource. For example, if there is no interference or a small amount of interference determined in the sensing channel, the ratio between unscrambled FMCW waveform components and scrambled FMCW waveform components may be high to favor the sensing dynamic range aspects. If, however, there is some amount of interference determined in the sensing channel (e.g., above an SINR threshold), the ratio between unscrambled FMCW waveform components and scrambled FMCW waveform components may be low to favor the interference mitigation aspects.

[0176] In some examples, the format of the hybrid continuous-wave radar signal may indicate at least one tuning gap between the at least one unscrambled continuous-wave waveform component and the at least one scrambled continuous-wave waveform component. That is, for example, the sending node **1204** may benefit from a time period between transmitting and/or receiving the two different waveforms to assist the transceiver tuning associated with processing the hybrid FMCW signal. For some sensing nodes and/or sensing operation scenarios or formats of the hybrid FMCW signal, a tuning gap may not be necessary, but for other sensing nodes and/or sensing operation scenarios or formats of the hybrid FMCW signal, the tuning gap may be needed.

[0177] It is to be noted that the format of the hybrid FMCW may include a bundling of the scrambled and unscrambled FMCW waveforms within a short interval (e.g., an OFDM symbol, intra-OFDM symbol, intra-FMCW waveform, etc.). Thus, in some cases, the sensing node **1204** may optimize processing gain because the sensing channel may be similar. In some cases, the sensing node **1204** may select, absent signaling, a predefined format of the hybrid continuous-wave radar signal to use for the transmission. In some case, the selection may be based on a table (or like design) know a priori to the sensing node **1204**.

[0178] The at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal may be arranged in various configurations and/or patterns. Some non-limiting examples of the hybrid continuous-wave radar signal are described herein with respect to FIG. **13**.

[0179] FIG. **13** illustrates examples of hybrid continuous-wave waveforms, according to aspects of the disclosure. In some examples, a sensing reference signal resource may be based on or configured to include a hybrid continuous-wave waveform. These hybrid continuous-wave waveforms may be transmitted and/or received by a sensing node, such as sensing node **1204** or other sensing nodes as described herein. In some examples, these hybrid continuous-wave waveforms are compatible with a cyclic prefix (CP)-OFDM structure and numerology.

[0180] In some examples, a first hybrid FMCW format **1310** may be transmitted or received by a sensing node. The first hybrid FMCW format **1310** may be considered a symbol-level hybrid FMCW format in accordance with some aspects. For example, a first symbol may include an unscrambled FMCW waveform component and a second symbol may include a scrambled FMCW waveform component. In some cases, each sensing reference signal resource configured may include multiple symbols (e.g., a symbol configured to align with the format and numerology associated with CP-OFDM symbols). That is, for example, at least one symbol includes an unscrambled FMCW waveform component and at least one symbol includes a scrambled FMCW waveform component. In some examples, each symbol of a multiple symbol sensing reference signal transmission is: (1) a symbol that only includes one or more unscrambled waveforms, or (2) a symbol that only includes one or more scrambled waveforms, in accordance with some implementations.

[0181] In some examples, a second hybrid FMCW format **1320** may be transmitted or received by a sensing node. The second hybrid FMCW format **1320** may be considered an intra-symbol-level hybrid FMCW format in accordance with some aspects. For example, a single symbol may include an unscrambled FMCW waveform component and a scrambled FMCW waveform component. For example, each sensing reference signal symbol (e.g., a symbol configured to align with the format and numerology associated with CP-OFDM symbols) may have a first portion that includes an unscrambled FMCW waveform component and a second portion that includes a scrambled FMCW waveform component. That is, for example, each symbol configured for the sensing reference signal resource includes an unscrambled FMCW waveform component and a scrambled FMCW waveform component within that symbol.

[0182] In some examples, a third hybrid FMCW format **1330** may be transmitted or received by a sensing node. The third hybrid FMCW format **1330** may be considered an intra-FMCW waveform-level hybrid FMCW format in accordance with some aspects. For example, each sensing reference signal symbol may include one or multiple FMCW waveform components. These multiple FMCW waveform components may be arranged in various patterns (e.g., alternating or interleaving patterns) within the sensing reference signal symbol. For example, each sensing reference signal symbol (e.g., a symbol configured to align with the format and numerology associated with CP-OFDM symbols) may have multiple first portions that include unscrambled FMCW waveform components and multiple second portions that include scrambled FMCW waveform components. In some cases, each FMCW waveform within a symbol may include multiple FMCW waveform components. For example, when a triangular FMCW waveform is used, the triangular FMCW waveform may include one up-ramp chirp and one down-ramp chirp. Within each FMCW waveform, at least one FMCW waveform component of the FMCW waveform is unscrambled and at least one FMCW waveform component of the FMCW waveform is scrambled.

[0183] That is, for example, the third hybrid FMCW format **1330** may have a chirp sequence, in which a first chirp (e.g., an up-ramp chirp) of the chirp sequence correspond to an unscrambled FMCW waveform component and a second chirp (e.g., a down-ramp chirp) of the of the chirp sequence immediately following the first chirp includes a scrambled FMCW waveform component. It is to be noted that an unscrambled FMCW waveform component may be first in the time domain, and a scrambled FMCW waveform component may be second in the time domain, in accordance with some aspects. Additionally, or alternatively, the scrambled FMCW waveform component may be first in the time domain, and the unscrambled FMCW waveform component may be second in the time domain, in accordance with some aspects. It is also to be noted that other chirp sequences are contemplated as would be understood given the benefit of the disclosure.
[0184] Referring back to FIG. **12**, sensing operations within the sensing network **1200** may benefit from the sensing node **1204** reporting one or more capabilities associated with support of hybrid continuous-wave waveforms. For example, in addition to whether the sensing node **1204** can support transmission or reception of hybrid continuous-wave waveforms, other capabilities that may impact the hybrid FMCW transmissions in the sensing network **1200** may be reported. For example, whether the sensing node **1204** as a receiver of the hybrid FMCW transmissions requires a tuning gap to tune the transceiver or receiver components between a scrambled FMCW waveform component and unscrambled FMCW waveform component. In some cases, the sensing node **1204** may report a minimum tuning gap value needed for the transceiver or receiver tuning procedure.
[0185] In some examples, the sensing node **1204** may receive a reference signal configuration or other indication associated with a hybrid FMCW transmission. That is, for example, the sensing node **1204** may receive an indication **1212** of certain FMCW parameters and/or the scrambling information associated with the hybrid FMCW transmission in the reference signal configuration. In some cases, a format of the hybrid FMCW waveform to be transmitted is indicated in the reference signal configuration.
[0186] In some examples, the sensing node **1204** while receiving one or more hybrid FMCW transmissions may first determine the range-Doppler profile associated with the scrambled FMCW waveform components to detect the target **1206** and filter out any interference associated with the sensing reference signal transmissions. The sensing node **1204** may then determine the range-Doppler profile associated with the unscrambled FMCW to estimate one or more parameters corresponding to the detected target **1206**. A non-limiting example of this sensing operation is described with respect to FIG. **14**.
[0187] FIG. **14** illustrates examples of range mapping diagrams for unscrambled and scrambled sensing signals, according to aspects of the disclosure. The examples of FIG. **14** illustrate how unscrambled and scrambled FMCW waveform components of a hybrid continuous-wave radar reference signal may be used by a sensing node in a sensing operation. In the examples of FIG. **14**, the range mapping diagrams are RDM diagrams.
[0188] In FIG. **14**, a first detection-based RDM diagram **1410** is shown for a sensing node. In the first detection-based RDM diagram **1410**, range is represented horizontally (on the X axis) with range in meters increasing from left to right, and velocity is represented vertically (on the Y axis) in meters/second. The scrambled signal and waveform components shown in the first detection-based RDM diagram **1410** corresponds to a PC-FMCW signal that uses 512 code lengths.
[0189] The first detection-based RDM diagram **1410** represents a first range-Doppler profile determined by the sensing node. That is, for example, the sensing node may use interference mitigation aspects of a hybrid FMCW transmission to filter out interference and detect a target signal corresponding to the target object.
[0190] A second parameter-based RDM diagram **1420** is shown in FIG. **14**. That is, for example, the sensing node may perform further sensing processing **1415** upon detecting the location of the target object. In the second parameter-based RDM diagram **1420**, range is represented horizontally (on the X axis) with range in meters increasing from left to right, and velocity is represented

vertically (on the Y axis) in meters/second. The unscrambled signal and waveform components shown in the second parameter-based RDM diagram **1420** corresponds to an FMCW signal.

[0191] The second parameter-based RDM diagram **1420** represents a second range-Doppler profile determined by the sensing node. That is, for example, the sensing node may use sensing dynamic range aspects of the hybrid FMCW transmission to obtain more accurate parameters associated with the target signal using the second range-Doppler profile and can ignore the false positives associated with a first interference signal and second interference signal based on the results of the first range-Doppler profile illustrated in the first detection-based RDM diagram **1410**.

[0192] FIG. **15** is a flowchart of an example process **1500** associated with hybrid continuous-wave radar techniques, according to aspects of the disclosure. In some implementations, one or more process blocks of FIG. **15** may be performed by a sensing node (e.g., base station **302** or UE **304**). In some implementations, one or more process blocks of FIG. **15** may be performed by another device or a group of devices separate from or including the sensing node. Additionally, or alternatively, one or more process blocks of FIG. **15** may be performed by one or more components of an apparatus, such as a processor(s), memory, or transceiver(s), any or all of which may be means for performing the operations of process **1500**.

[0193] As shown in FIG. **15**, process **1500** may include, at block **1510**, receiving an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components. Means for performing the operation of block **1510** may include the processor(s), memory, or transceiver(s) of any of the apparatuses described herein. For example, the sensing node may receive an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components, using WWAN transceivers **310**, **350**.

[0194] As further shown in FIG. **15**, process **1500** may include, at block **1520**, transmitting a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component. Means for performing the operation of block **1520** may include the processor(s), memory, or transceiver(s) of any of the apparatuses described herein. For example, the sensing node may transmit a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, using WWAN transceivers **310**, **350**.

[0195] Process **1500** may include additional implementations, such as any single implementation or any combination of implementations described below and/or in connection with one or more other processes described elsewhere herein.

[0196] In some aspects, process **1500** includes the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first time duration, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second time duration different from the first time duration.

[0197] In some aspects, process **1500** includes the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second symbol in the time domain different from the first symbol.

[0198] In some aspects, each of the first symbol and the second symbol is compatible with a cyclic prefix (CP) orthogonal frequency division multiplexing (CP-OFDM) symbol.

[0199] In some aspects, process **1500** includes the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first portion of a symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second portion of the

symbol in the time domain different from the first portion.
[0200] In some aspects, process **1500** includes the hybrid continuous-wave radar signal comprises a chirp sequence, the first portion of the symbol is a first chirp of the chirp sequence, and the second portion of the symbol is a second chirp of the of the chirp sequence immediately following the first chirp.
[0201] In some aspects, process **1500** includes receiving signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission, or selecting, absent signaling, the predefined format of the hybrid continuous-wave radar signal to use for the transmission.
[0202] In some aspects, process **1500** includes receiving signaling corresponding to an RS configuration that indicates a format of the hybrid continuous-wave radar signal to use for transmission on at least one RS resource.
[0203] In some aspects, the at least one scrambled continuous-wave waveform component comprises a number of scrambled continuous-wave waveform components based on an estimation of interference associated with the at least one RS resource.
[0204] In some aspects, the format of the hybrid continuous-wave radar signal indicates at least one tuning gap between the at least one unscrambled continuous-wave waveform component and the at least one scrambled continuous-wave waveform component.
[0205] In some aspects, the at least one scrambled continuous-wave waveform component comprises a phase-coded (PC) frequency-modulated continuous wave (PC-FMCW) waveform component or a frequency domain-scrambled digital FMCW waveform component, and the at least one unscrambled continuous-wave waveform component comprises an FMCW waveform component.
[0206] Although FIG. **15** shows example blocks of process **1500**, in some implementations, process **1500** may include additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in FIG. **15**. Additionally, or alternatively, two or more of the blocks of process **1500** may be performed in parallel.
[0207] FIG. **16** is a flowchart of an example process **1600** associated with hybrid continuous-wave radar techniques, according to aspects of the disclosure. In some implementations, one or more process blocks of FIG. **16** may be performed by a sensing node (e.g., base station **302** or UE **304**). In some implementations, one or more process blocks of FIG. **16** may be performed by another device or a group of devices separate from or including the sensing node. Additionally, or alternatively, one or more process blocks of FIG. **16** may be performed by one or more components of an apparatus, such as a processor(s), memory, or transceiver(s), any or all of which may be means for performing the operations of process **1600**.
[0208] As shown in FIG. **16**, process **1600** may include, at block **1610**, transmitting an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components. Means for performing the operation of block **1610** may include the processor(s), memory, or transceiver(s) of any of the apparatuses described herein. For example, the sensing node may transmit an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components, using WWAN transceivers **310**, **350**.
[0209] As further shown in FIG. **16**, process **1600** may include, at block **1620**, receiving a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component. Means for performing the operation of block **1620** may include the processor(s), memory, or transceiver(s) of any of the apparatuses described herein. For example, the sensing node may receive a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, using WWAN

transceivers **310**, **350**.

[0210] Process **1600** may include additional implementations, such as any single implementation or any combination of implementations described below and/or in connection with one or more other processes described elsewhere herein.

[0211] In some aspects, process **1600** includes transmitting an indication for one or more tuning gaps between unscrambled continuous-wave waveform components and scrambled continuous-wave waveform components.

[0212] In some aspects, process **1600** includes transmitting an indication of a minimum tuning gap between an unscrambled continuous-wave waveform component and a scrambled continuous-wave waveform component.

[0213] In some aspects, process **1600** includes receiving signaling corresponding to an RS configuration that indicates one or more of a format of the hybrid continuous-wave radar signal for transmission on at least one RS resource, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, information corresponding to scrambling associated with the at least one scrambled continuous-wave waveform component, or any combination thereof.

[0214] In some aspects, process **1600** includes detecting a target based on a first range-Doppler profile using the at least one scrambled continuous-wave waveform component, and estimating one or more parameters associated with the target based on a second range-Doppler profile using the at least one unscrambled continuous-wave waveform component.

[0215] Although FIG. **16** shows example blocks of process **1600**, in some implementations, process **1600** may include additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in FIG. **16**. Additionally, or alternatively, two or more of the blocks of process **1600** may be performed in parallel.

[0216] As will be appreciated, a technical advantage of the process **1400** and **1500** may include mitigating cross-node interference while achieving sufficient dynamic range for target detection by including unscrambled and scrambled waveform components in a hybrid continuous-wave radar transmission associated with a sensing reference signal. Another technical advantage of the process **1400** and **1500** may include enabling secure sensing operation through hybrid-FMCW radar transmission by including unscrambled and scrambled FMCW waveform components in one or more symbols of a sensing reference signal. That is, for example, a signal attack from an aggressor sensing node may be filtered out through the scrambled FMCW waveform component while the performance of the sensing operation can still be maintained through the unscrambled FMCW waveform component.

[0217] In the detailed description above it can be seen that different features are grouped together in examples. This manner of disclosure should not be understood as an intention that the example clauses have more features than are explicitly mentioned in each clause. Rather, the various aspects of the disclosure may include fewer than all features of an individual example clause disclosed. Therefore, the following clauses should hereby be deemed to be incorporated in the description, wherein each clause by itself can stand as a separate example. Although each dependent clause can refer in the clauses to a specific combination with one of the other clauses, the aspect(s) of that dependent clause are not limited to the specific combination. It will be appreciated that other example clauses can also include a combination of the dependent clause aspect(s) with the subject matter of any other dependent clause or independent clause or a combination of any feature with other dependent and independent clauses. The various aspects disclosed herein expressly include these combinations, unless it is explicitly expressed or can be readily inferred that a specific combination is not intended (e.g., contradictory aspects, such as defining an element as both an electrical insulator and an electrical conductor). Furthermore, it is also intended that aspects of a

clause can be included in any other independent clause, even if the clause is not directly dependent on the independent clause.
[0218] Implementation examples are described in the following numbered clauses:
[0219] Clause 1. A method of wireless communication performed by a sensing node, comprising: receiving an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and transmitting a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0220] Clause 2. The method of clause 1, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first time duration, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second time duration different from the first time duration.
[0221] Clause 3. The method of any of clauses 1 to 2, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second symbol in the time domain different from the first symbol.
[0222] Clause 4. The method of clause 3, wherein each of the first symbol and the second symbol is compatible with a cyclic prefix (CP) orthogonal frequency division multiplexing (CP-OFDM) symbol.
[0223] Clause 5. The method of any of clauses 1 to 4, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first portion of a symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second portion of the symbol in the time domain different from the first portion.
[0224] Clause 6. The method of clause 5, wherein: the hybrid continuous-wave radar signal comprises a chirp sequence, the first portion of the symbol is a first chirp of the chirp sequence, and the second portion of the symbol is a second chirp of the of the chirp sequence immediately following the first chirp.
[0225] Clause 7. The method of any of clauses 1 to 6, further comprising: receiving signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission, or selecting, absent signaling, the predefined format of the hybrid continuous-wave radar signal to use for the transmission.
[0226] Clause 8. The method of any of clauses 1 to 7, further comprising: receiving signaling corresponding to an RS configuration that indicates a format of the hybrid continuous-wave radar signal to use for transmission on at least one RS resource.
[0227] Clause 9. The method of clause 8, wherein the at least one scrambled continuous-wave waveform component comprises a number of scrambled continuous-wave waveform components based on an estimation of interference associated with the at least one RS resource.
[0228] Clause 10. The method of any of clauses 8 to 9, wherein the format of the hybrid continuous-wave radar signal indicates at least one tuning gap between the at least one unscrambled continuous-wave waveform component and the at least one scrambled continuous-wave waveform component.
[0229] Clause 11. The method of any of clauses 1 to 10, wherein: the at least one scrambled continuous-wave waveform component comprises a phase-coded (PC) frequency-modulated continuous wave (PC-FMCW) waveform component or a frequency domain-scrambled digital FMCW waveform component, and the at least one unscrambled continuous-wave waveform component comprises an FMCW waveform component.
[0230] Clause 12. A method of wireless communication performed by a sensing node, comprising:

transmitting an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and receiving a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.

[0231] Clause 13. The method of clause 12, further comprising: transmitting an indication for one or more tuning gaps between unscrambled continuous-wave waveform components and scrambled continuous-wave waveform components.

[0232] Clause 14. The method of any of clauses 12 to 13, further comprising: transmitting an indication of a minimum tuning gap between an unscrambled continuous-wave waveform component and a scrambled continuous-wave waveform component.

[0233] Clause 15. The method of any of clauses 12 to 14, further comprising: receiving signaling corresponding to an RS configuration that indicates one or more of: a format of the hybrid continuous-wave radar signal for transmission on at least one RS resource, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, information corresponding to scrambling associated with the at least one scrambled continuous-wave waveform component, or any combination thereof.

[0234] Clause 16. The method of any of clauses 12 to 15, further comprising: detecting a target based on a first range-Doppler profile using the at least one scrambled continuous-wave waveform component; and estimating one or more parameters associated with the target based on a second range-Doppler profile using the at least one unscrambled continuous-wave waveform component.

[0235] Clause 17. A sensing node, comprising: one or more memories; one or more transceivers; and one or more processors communicatively coupled to the one or more memories and the one or more transceivers, the one or more processors, either alone or in combination, configured to: receive, via the one or more transceivers, an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and transmit, via the one or more transceivers, a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.

[0236] Clause 18. The sensing node of clause 17, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first time duration, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second time duration different from the first time duration.

[0237] Clause 19. The sensing node of any of clauses 17 to 18, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second symbol in the time domain different from the first symbol.

[0238] Clause 20. The sensing node of clause 19, wherein each of the first symbol and the second symbol is compatible with a cyclic prefix (CP) orthogonal frequency division multiplexing (CP-OFDM) symbol.

[0239] Clause 21. The sensing node of any of clauses 17 to 20, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first portion of a symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second portion of the symbol in the time domain different from the first portion.

[0240] Clause 22. The sensing node of clause 21, wherein: the hybrid continuous-wave radar signal comprises a chirp sequence, the first portion of the symbol is a first chirp of the chirp sequence, and the second portion of the symbol is a second chirp of the of the chirp sequence immediately following the first chirp.

[0241] Clause 23. The sensing node of any of clauses 17 to 22, wherein the one or more processors, either alone or in combination, are further configured to: receive, via the one or more transceivers, signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission, or select, absent signaling, the predefined format of the hybrid continuous-wave radar signal to use for the transmission.

[0242] Clause 24. The sensing node of any of clauses 17 to 23, wherein the one or more processors, either alone or in combination, are further configured to: receive, via the one or more transceivers, signaling corresponding to an RS configuration that indicates a format of the hybrid continuous-wave radar signal to use for transmission on at least one RS resource.

[0243] Clause 25. The sensing node of clause 24, wherein the at least one scrambled continuous-wave waveform component comprises a number of scrambled continuous-wave waveform components based on an estimation of interference associated with the at least one RS resource.

[0244] Clause 26. The sensing node of any of clauses 24 to 25, wherein the format of the hybrid continuous-wave radar signal indicates at least one tuning gap between the at least one unscrambled continuous-wave waveform component and the at least one scrambled continuous-wave waveform component.

[0245] Clause 27. The sensing node of any of clauses 17 to 26, wherein: the at least one scrambled continuous-wave waveform component comprises a phase-coded (PC) frequency-modulated continuous wave (PC-FMCW) waveform component or a frequency domain-scrambled digital FMCW waveform component, and the at least one unscrambled continuous-wave waveform component comprises an FMCW waveform component.

[0246] Clause 28. A sensing node, comprising: one or more memories; one or more transceivers; and one or more processors communicatively coupled to the one or more memories and the one or more transceivers, the one or more processors, either alone or in combination, configured to: transmit, via the one or more transceivers, an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and receive, via the one or more transceivers, a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.

[0247] Clause 29. The sensing node of clause 28, wherein the one or more processors, either alone or in combination, are further configured to: transmit, via the one or more transceivers, an indication for one or more tuning gaps between unscrambled continuous-wave waveform components and scrambled continuous-wave waveform components.

[0248] Clause 30. The sensing node of any of clauses 28 to 29, wherein the one or more processors, either alone or in combination, are further configured to: transmit, via the one or more transceivers, an indication of a minimum tuning gap between an unscrambled continuous-wave waveform component and a scrambled continuous-wave waveform component.

[0249] Clause 31. The sensing node of any of clauses 28 to 30, wherein the one or more processors, either alone or in combination, are further configured to: receive, via the one or more transceivers, signaling corresponding to an RS configuration that indicates one or more of: a format of the hybrid continuous-wave radar signal for transmission on at least one RS resource, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, information corresponding to scrambling associated with the at least one scrambled continuous-wave waveform component, or any combination thereof.

[0250] Clause 32. The sensing node of any of clauses 28 to 31, wherein the one or more processors, either alone or in combination, are further configured to: detect a target based on a first range-Doppler profile using the at least one scrambled continuous-wave waveform component; and estimate one or more parameters associated with the target based on a second range-Doppler profile using the at least one unscrambled continuous-wave waveform component.
[0251] Clause 33. A sensing node, comprising: means for receiving an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and means for transmitting a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0252] Clause 34. The sensing node of clause 33, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first time duration, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second time duration different from the first time duration.
[0253] Clause 35. The sensing node of any of clauses 33 to 34, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second symbol in the time domain different from the first symbol.
[0254] Clause 36. The sensing node of clause 35, wherein each of the first symbol and the second symbol is compatible with a cyclic prefix (CP) orthogonal frequency division multiplexing (CP-OFDM) symbol.
[0255] Clause 37. The sensing node of any of clauses 33 to 36, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first portion of a symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second portion of the symbol in the time domain different from the first portion.
[0256] Clause 38. The sensing node of clause 37, wherein: the hybrid continuous-wave radar signal comprises a chirp sequence, the first portion of the symbol is a first chirp of the chirp sequence, and the second portion of the symbol is a second chirp of the of the chirp sequence immediately following the first chirp.
[0257] Clause 39. The sensing node of any of clauses 33 to 38, further comprising: means for receiving signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission, or means for selecting, absent signaling, the predefined format of the hybrid continuous-wave radar signal to use for the transmission.
[0258] Clause 40. The sensing node of any of clauses 33 to 39, further comprising: means for receiving signaling corresponding to an RS configuration that indicates a format of the hybrid continuous-wave radar signal to use for transmission on at least one RS resource.
[0259] Clause 41. The sensing node of clause 40, wherein the at least one scrambled continuous-wave waveform component comprises a number of scrambled continuous-wave waveform components based on an estimation of interference associated with the at least one RS resource.
[0260] Clause 42. The sensing node of any of clauses 40 to 41, wherein the format of the hybrid continuous-wave radar signal indicates at least one tuning gap between the at least one unscrambled continuous-wave waveform component and the at least one scrambled continuous-wave waveform component.
[0261] Clause 43. The sensing node of any of clauses 33 to 42, wherein: the at least one scrambled continuous-wave waveform component comprises a phase-coded (PC) frequency-modulated continuous wave (PC-FMCW) waveform component or a frequency domain-scrambled digital FMCW waveform component, and the at least one unscrambled continuous-wave waveform

component comprises an FMCW waveform component.
[0262] Clause 44. A sensing node, comprising: means for transmitting an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and means for receiving a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0263] Clause 45. The sensing node of clause 44, further comprising: means for transmitting an indication for one or more tuning gaps between unscrambled continuous-wave waveform components and scrambled continuous-wave waveform components.
[0264] Clause 46. The sensing node of any of clauses 44 to 45, further comprising: means for transmitting an indication of a minimum tuning gap between an unscrambled continuous-wave waveform component and a scrambled continuous-wave waveform component.
[0265] Clause 47. The sensing node of any of clauses 44 to 46, further comprising: means for receiving signaling corresponding to an RS configuration that indicates one or more of: a format of the hybrid continuous-wave radar signal for transmission on at least one RS resource, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, information corresponding to scrambling associated with the at least one scrambled continuous-wave waveform component, or any combination thereof.
[0266] Clause 48. The sensing node of any of clauses 44 to 47, further comprising: means for detecting a target based on a first range-Doppler profile using the at least one scrambled continuous-wave waveform component; and means for estimating one or more parameters associated with the target based on a second range-Doppler profile using the at least one unscrambled continuous-wave waveform component.
[0267] Clause 49. A non-transitory computer-readable medium storing computer-executable instructions that, when executed by a sensing node, cause the sensing node to: receive an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and transmit a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0268] Clause 50. The non-transitory computer-readable medium of clause 49, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first time duration, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second time duration different from the first time duration.
[0269] Clause 51. The non-transitory computer-readable medium of any of clauses 49 to 50, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second symbol in the time domain different from the first symbol.
[0270] Clause 52. The non-transitory computer-readable medium of clause 51, wherein each of the first symbol and the second symbol is compatible with a cyclic prefix (CP) orthogonal frequency division multiplexing (CP-OFDM) symbol.
[0271] Clause 53. The non-transitory computer-readable medium of any of clauses 49 to 52, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first portion of a symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second portion of the symbol in the time domain different from

the first portion.
[0272] Clause 54. The non-transitory computer-readable medium of clause 53, wherein: the hybrid continuous-wave radar signal comprises a chirp sequence, the first portion of the symbol is a first chirp of the chirp sequence, and the second portion of the symbol is a second chirp of the of the chirp sequence immediately following the first chirp.
[0273] Clause 55. The non-transitory computer-readable medium of any of clauses 49 to 54, further comprising computer-executable instructions that, when executed by the sensing node, cause the sensing node to: receive signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission, or select, absent signaling, the predefined format of the hybrid continuous-wave radar signal to use for the transmission.
[0274] Clause 56. The non-transitory computer-readable medium of any of clauses 49 to 55, further comprising computer-executable instructions that, when executed by the sensing node, cause the sensing node to: receive signaling corresponding to an RS configuration that indicates a format of the hybrid continuous-wave radar signal to use for transmission on at least one RS resource.
[0275] Clause 57. The non-transitory computer-readable medium of clause 56, wherein the at least one scrambled continuous-wave waveform component comprises a number of scrambled continuous-wave waveform components based on an estimation of interference associated with the at least one RS resource.
[0276] Clause 58. The non-transitory computer-readable medium of any of clauses 56 to 57, wherein the format of the hybrid continuous-wave radar signal indicates at least one tuning gap between the at least one unscrambled continuous-wave waveform component and the at least one scrambled continuous-wave waveform component.
[0277] Clause 59. The non-transitory computer-readable medium of any of clauses 49 to 58, wherein: the at least one scrambled continuous-wave waveform component comprises a phase-coded (PC) frequency-modulated continuous wave (PC-FMCW) waveform component or a frequency domain-scrambled digital FMCW waveform component, and the at least one unscrambled continuous-wave waveform component comprises an FMCW waveform component.
[0278] Clause 60. A non-transitory computer-readable medium storing computer-executable instructions that, when executed by a sensing node, cause the sensing node to: transmit an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and receive a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
[0279] Clause 61. The non-transitory computer-readable medium of clause 60, further comprising computer-executable instructions that, when executed by the sensing node, cause the sensing node to: transmit an indication for one or more tuning gaps between unscrambled continuous-wave waveform components and scrambled continuous-wave waveform components.
[0280] Clause 62. The non-transitory computer-readable medium of any of clauses 60 to 61, further comprising computer-executable instructions that, when executed by the sensing node, cause the sensing node to: transmit an indication of a minimum tuning gap between an unscrambled continuous-wave waveform component and a scrambled continuous-wave waveform component.
[0281] Clause 63. The non-transitory computer-readable medium of any of clauses 60 to 62, further comprising computer-executable instructions that, when executed by the sensing node, cause the sensing node to: receive signaling corresponding to an RS configuration that indicates one or more of: a format of the hybrid continuous-wave radar signal for transmission on at least one RS resource, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, information corresponding to scrambling associated with the at least one scrambled continuous-wave waveform

component, or any combination thereof.
[0282] Clause 64. The non-transitory computer-readable medium of any of clauses 60 to 63, further comprising computer-executable instructions that, when executed by the sensing node, cause the sensing node to: detect a target based on a first range-Doppler profile using the at least one scrambled continuous-wave waveform component; and estimate one or more parameters associated with the target based on a second range-Doppler profile using the at least one unscrambled continuous-wave waveform component.
[0283] Those of skill in the art will appreciate that information and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.
[0284] Further, those of skill in the art will appreciate that the various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the aspects disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present disclosure.
[0285] The various illustrative logical blocks, modules, and circuits described in connection with the aspects disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an ASIC, a field-programmable gate array (FPGA), or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, for example, a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.
[0286] The methods, sequences and/or algorithms described in connection with the aspects disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module may reside in random access memory (RAM), flash memory, read-only memory (ROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), registers, hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An example storage medium is coupled to the processor such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an ASIC. The ASIC may reside in a user terminal (e.g., UE). In the alternative, the processor and the storage medium may reside as discrete components in a user terminal.
[0287] In one or more example aspects, the functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Computer-readable media includes both computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A storage media may be any available media that can be accessed by a computer. By way of example, and not limitation, such computer-readable media can comprise RAM, ROM, EEPROM, CD-ROM

or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store desired program code in the form of instructions or data structures and that can be accessed by a computer. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, includes compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above should also be included within the scope of computer-readable media.

[0288] While the foregoing disclosure shows illustrative aspects of the disclosure, it should be noted that various changes and modifications could be made herein without departing from the scope of the disclosure as defined by the appended claims. For example, the functions, steps and/or actions of the method claims in accordance with the aspects of the disclosure described herein need not be performed in any particular order. Further, no component, function, action, or instruction described or claimed herein should be construed as critical or essential unless explicitly described as such. Furthermore, as used herein, the terms “set,” “group,” and the like are intended to include one or more of the stated elements. Also, as used herein, the terms “has,” “have,” “having,” “comprises,” “comprising,” “includes,” “including,” and the like does not preclude the presence of one or more additional elements (e.g., an element “having” A may also have B). Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise. Also, as used herein, the term “or” is intended to be inclusive when used in a series and may be used interchangeably with “and/or,” unless explicitly stated otherwise (e.g., if used in combination with “either” or “only one of”) or the alternatives are mutually exclusive (e.g., “one or more” should not be interpreted as “one and more”). Furthermore, although components, functions, actions, and instructions may be described or claimed in the singular, the plural is contemplated unless limitation to the singular is explicitly stated. Accordingly, as used herein, the articles “a,” “an,” “the,” and “said” are intended to include one or more of the stated elements. Additionally, as used herein, the terms “at least one” and “one or more” encompass “one” component, function, action, or instruction performing or capable of performing a described or claimed functionality and also “two or more” components, functions, actions, or instructions performing or capable of performing a described or claimed functionality in combination.

Claims

1. A method of wireless communication performed by a sensing node, comprising: receiving an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and transmitting a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.

2. The method of claim 1, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first time duration, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second time duration different from the first time duration.

3. The method of claim 1, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid

continuous-wave radar signal is transmitted during a second symbol in the time domain different from the first symbol.
4. The method of claim 3, wherein each of the first symbol and the second symbol is compatible with a cyclic prefix (CP) orthogonal frequency division multiplexing (CP-OFDM) symbol.
5. The method of claim 1, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first portion of a symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second portion of the symbol in the time domain different from the first portion.
6. The method of claim 5, wherein: the hybrid continuous-wave radar signal comprises a chirp sequence, the first portion of the symbol is a first chirp of the chirp sequence, and the second portion of the symbol is a second chirp of the of the chirp sequence immediately following the first chirp.
7. The method of claim 1, further comprising: receiving signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission, or selecting, absent signaling, the predefined format of the hybrid continuous-wave radar signal to use for the transmission.
8. The method of claim 1, further comprising: receiving signaling corresponding to an RS configuration that indicates a format of the hybrid continuous-wave radar signal to use for transmission on at least one RS resource.
9. The method of claim 1, wherein: the at least one scrambled continuous-wave waveform component comprises a phase-coded (PC) frequency-modulated continuous wave (PC-FMCW) waveform component or a frequency domain-scrambled digital FMCW waveform component, and the at least one unscrambled continuous-wave waveform component comprises an FMCW waveform component.
10. A method of wireless communication performed by a sensing node, comprising: transmitting an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and receiving a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
11. The method of claim 10, further comprising: transmitting an indication for one or more tuning gaps between unscrambled continuous-wave waveform components and scrambled continuous-wave waveform components.
12. The method of claim 10, further comprising: transmitting an indication of a minimum tuning gap between an unscrambled continuous-wave waveform component and a scrambled continuous-wave waveform component.
13. The method of claim 10, further comprising: receiving signaling corresponding to an RS configuration that indicates one or more of: a format of the hybrid continuous-wave radar signal for transmission on at least one RS resource, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, information corresponding to scrambling associated with the at least one scrambled continuous-wave waveform component, or any combination thereof.
14. The method of claim 10, further comprising: detecting a target based on a first range-Doppler profile using the at least one scrambled continuous-wave waveform component; and estimating one or more parameters associated with the target based on a second range-Doppler profile using the at least one unscrambled continuous-wave waveform component.
15. A sensing node, comprising: one or more memories; one or more transceivers; and one or more processors communicatively coupled to the one or more memories and the one or more transceivers, the one or more processors, either alone or in combination, configured to: receive, via

the one or more transceivers, an indication to transmit a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and transmit, via the one or more transceivers, a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.
16. The sensing node of claim 15, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first time duration, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second time duration different from the first time duration.
17. The sensing node of claim 15, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second symbol in the time domain different from the first symbol.
18. The sensing node of claim 17, wherein each of the first symbol and the second symbol is compatible with a cyclic prefix (CP) orthogonal frequency division multiplexing (CP-OFDM) symbol.
19. The sensing node of claim 15, wherein: the at least one unscrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a first portion of a symbol in a time domain, and the at least one scrambled continuous-wave waveform component of the hybrid continuous-wave radar signal is transmitted during a second portion of the symbol in the time domain different from the first portion.
20. The sensing node of claim 19, wherein: the hybrid continuous-wave radar signal comprises a chirp sequence, the first portion of the symbol is a first chirp of the chirp sequence, and the second portion of the symbol is a second chirp of the of the chirp sequence immediately following the first chirp.
21. The sensing node of claim 15, wherein the one or more processors, either alone or in combination, are further configured to: receive, via the one or more transceivers, signaling that indicates a predefined format of the hybrid continuous-wave radar signal to use for transmission, or select, absent signaling, the predefined format of the hybrid continuous-wave radar signal to use for the transmission.
22. The sensing node of claim 15, wherein the one or more processors, either alone or in combination, are further configured to: receive, via the one or more transceivers, signaling corresponding to an RS configuration that indicates a format of the hybrid continuous-wave radar signal to use for transmission on at least one RS resource.
23. The sensing node of claim 22, wherein the at least one scrambled continuous-wave waveform component comprises a number of scrambled continuous-wave waveform components based on an estimation of interference associated with the at least one RS resource.
24. The sensing node of claim 22, wherein the format of the hybrid continuous-wave radar signal indicates at least one tuning gap between the at least one unscrambled continuous-wave waveform component and the at least one scrambled continuous-wave waveform component.
25. The sensing node of claim 15, wherein: the at least one scrambled continuous-wave waveform component comprises a phase-coded (PC) frequency-modulated continuous wave (PC-FMCW) waveform component or a frequency domain-scrambled digital FMCW waveform component, and the at least one unscrambled continuous-wave waveform component comprises an FMCW waveform component.
26. A sensing node, comprising: one or more memories; one or more transceivers; and one or more processors communicatively coupled to the one or more memories and the one or more transceivers, the one or more processors, either alone or in combination, configured to: transmit,

via the one or more transceivers, an indication of support to receive a sensing reference signal (RS) having one or more scrambled continuous-wave waveform components; and receive, via the one or more transceivers, a hybrid continuous-wave radar signal, wherein the hybrid continuous-wave radar signal comprises at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component.

27. The sensing node of claim 26, wherein the one or more processors, either alone or in combination, are further configured to: transmit, via the one or more transceivers, an indication for one or more tuning gaps between unscrambled continuous-wave waveform components and scrambled continuous-wave waveform components.

28. The sensing node of claim 26, wherein the one or more processors, either alone or in combination, are further configured to: transmit, via the one or more transceivers, an indication of a minimum tuning gap between an unscrambled continuous-wave waveform component and a scrambled continuous-wave waveform component.

29. The sensing node of claim 26, wherein the one or more processors, either alone or in combination, are further configured to: receive, via the one or more transceivers, signaling corresponding to an RS configuration that indicates one or more of: a format of the hybrid continuous-wave radar signal for transmission on at least one RS resource, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, one or more parameters associated with the at least one unscrambled continuous-wave waveform component and at least one scrambled continuous-wave waveform component, information corresponding to scrambling associated with the at least one scrambled continuous-wave waveform component, or any combination thereof.

30. The sensing node of claim 26, wherein the one or more processors, either alone or in combination, are further configured to: detect a target based on a first range-Doppler profile using the at least one scrambled continuous-wave waveform component; and estimate one or more parameters associated with the target based on a second range-Doppler profile using the at least one unscrambled continuous-wave waveform component.