

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392074
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Chun; Kwang Min et al.

Washing machine

Abstract

Disclosed is a washing machine having an improved wire connection structure for electrically connecting electrical components. The washing machine includes a cabinet which has a first electrical component, forms an exterior, and has an opening through which laundry is inserted; a door provided with a second electrical component, and configured to open and close the opening; a wire which electrically connects the first electrical component and the second electrical component; and a hinge which has a wire guide portion for coupling the door to the cabinet so as to be rotatable about a rotating axis and for guiding the wire.

Inventors: Chun; Kwang Min (Suwon-si, KR), Kim; Hwa Shik (Suwon-si, KR), Choi; Min Jea (Suwon-si, KR), Park; Nae Young (Seoul, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008765389

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 18/481967

Filed: October 05, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240035220 A1	Feb. 01, 2024

Foreign Application Priority Data

KR	10-2015-0107288	Jul. 29, 2015
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **D06F37/10** (20060101); **D06F34/10** (20200101); **D06F37/28** (20060101); **D06F39/14** (20060101); **E05D11/00** (20060101); D06F34/04 (20200101)

U.S. Cl.:

CPC **D06F37/10** (20130101); **D06F34/10** (20200201); **D06F37/28** (20130101); **D06F39/14** (20130101); **E05D11/0081** (20130101); D06F34/04 (20200201)

Field of Classification Search

CPC: D06F (37/10); D06F (37/28); D06F (39/14); E05D (11/0081)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3883201	12/1974	Busoni	N/A	N/A
9708749	12/2016	Woo et al.	N/A	N/A
11834767	12/2022	Chun et al.	N/A	N/A
2004/0144138	12/2003	Takeuchi et al.	N/A	N/A
2006/0064846	12/2005	Espindola et al.	N/A	N/A
2012/0096734	12/2011	Moon et al.	N/A	N/A
2013/0127911	12/2012	Brown	N/A	N/A
2015/0123523	12/2014	Woo et al.	N/A	N/A
2017/0121898	12/2016	Kwon et al.	N/A	N/A
2018/0038040	12/2017	Kim et al.	N/A	N/A
2018/0127911	12/2017	Chen et al.	N/A	N/A
2018/0216381	12/2017	Lee	N/A	E05D 7/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
715484	12/2019	CH	N/A
2013-1505	12/2017	CL	N/A
2495765	12/2001	CN	N/A
1517477	12/2003	CN	N/A
101086194	12/2006	CN	N/A
104674521	12/2014	CN	N/A
105420996	12/2015	CN	N/A
107532365	12/2017	CN	N/A
10259980	12/2003	DE	N/A
1389643	12/2003	EP	N/A
2415920	12/2011	EP	N/A
2868795	12/2014	EP	N/A

3263757	12/2017	EP	N/A
3330424	12/2020	EP	N/A
2005-000583	12/2004	JP	N/A
2012-075689	12/2011	JP	N/A
10-2004-0015480	12/2003	KR	N/A
10-2007-0002336	12/2006	KR	N/A
10-2007-0027106	12/2006	KR	N/A
10-2009-0096948	12/2008	KR	N/A
10-2010-0027019	12/2009	KR	N/A
10-1145598	12/2011	KR	N/A
10-2013-0123544	12/2012	KR	N/A
10-2013-0133135	12/2012	KR	N/A
10-2015-0006264	12/2014	KR	N/A
2015006264	12/2014	KR	N/A
10-2015-0051466	12/2014	KR	N/A
10-2015-0073517	12/2014	KR	N/A
2005108725	12/2004	WO	N/A
2011063486	12/2010	WO	N/A
2016173552	12/2015	WO	N/A
2017014492	12/2016	WO	N/A

OTHER PUBLICATIONS

Machine translation of KR 20150006264 A, dated Jan. 2015. (Year: 2015). cited by applicant
Written Report and Search Report in connection with Brazilian Application No. 112018000008-6 dated Jan. 6, 2020, 8 pages. cited by applicant
European Search Report in connection with European Application No. 19000498.6 dated Feb. 21, 2020, 10 pages. cited by applicant
Communication pursuant to Article 94(3) EPC in connection with European Application No. 16830743.7 dated Mar. 27, 2020, 50 pages. cited by applicant
Examination report in connection with Indian Application No. 201717046876 dated Jan. 21, 2020, 6 pages. cited by applicant
Office Action in connection with Indian Patent Application No. 201717046876 dated Jan. 21, 2020, 6 pages. cited by applicant
Office Action in connection with Chinese Patent Application No. 201680044434.9 dated Oct. 30, 2019, 25 pages. cited by applicant
Supplementary European Search Report in connection with European Application No. EP16830743.7 dated Jun. 14, 2019, 9 pages. cited by applicant
Examination report in connection with Chilean Application No. CL 201703149 dated May 31, 2019, 13 pages. cited by applicant
Office Action in connection with Chilean Application No. CL201703149 dated Dec. 12, 2018, 13 pages. cited by applicant
Notice of Patent Allowance in connection with Korean Application No. KR10-2018-0033818 dated Dec. 24, 2018, 3 pages. cited by applicant
Office Action in connection with Iran Patent Application No. 1396501140003009101 dated Sep. 8, 2018, 2 pages. cited by applicant
Notice of Acceptance for patent application in connection with Australian Patent Application No. 2016300022 dated Sep. 24, 2018, 3 pages. cited by applicant
Examination report No. 1 for standard patent application in connection with Australian Application No. AU2016300022 dated May 22, 2018, 6 pages. cited by applicant
Communication pursuant to Rules 161(2) and 162 EPC in connection with European Application

No. 16830743.7 dated Apr. 13, 2018, 3 pages. cited by applicant
Detailed Ground(s) for Rejection in connection with Korean Application No. KR10-2018-0033818 dated Jun. 20, 2018, 6 pages. cited by applicant
Notice of Allowance in connection with Korean Patent Application No. 10-2015-0107288 dated Apr. 13, 2018, 7 pages. cited by applicant
Notice of Final Rejection in connection with Korean Patent Application No. 10-2015-0006264 dated Feb. 23, 2018, 5 pages. cited by applicant
Office Action in connection with Korean Application No. 10-2015-0107288 dated Aug. 21, 2017, 12 pages. cited by applicant
International Search Report in connection with International Application No. PCT/KR2016/007849 dated Oct. 27, 2016, 5 pages. cited by applicant
Written Opinion of the International Searching Authority in connection with International Application No. PCT/KR2016/007849 dated Oct. 27, 2016, 6 pages. cited by applicant
The Second Office Action in connection with Chinese Application No. 201680044434.9 dated Jun. 16, 2020, 9 pages. cited by applicant
Communication pursuant to Article 94(3) EPC in connection with European Application No. 19000498.6 dated Sep. 7, 2020, 4 pages. cited by applicant
Office Action dated Nov. 16, 2020 in connection with Chinese Patent Application No. 202010406271.2, 15 pages. cited by applicant
Office Action dated Oct. 13, 2020 in connection with Korean Patent Application No. 10-2019-0032834, 7 pages. cited by applicant
Written Opinion dated Dec. 2, 2020 in connection with Singapore Patent Application No. 10202000818U, 6 pages. cited by applicant
Office Action dated Dec. 1, 2020 in connection with Vietnamese Patent Application No. 1-2017-05291, 4 pages. cited by applicant
European Patent Office, "Communication pursuant to Article 94(3) EPC" issued Mar. 16, 2021, in connection with European Patent Application No. 19000498.6, 8 pages. cited by applicant
Korean Intellectual Property Office, "Results of Examination" issued Apr. 27, 2021, in connection with Korean Patent Application No. 10-2019-0032834, 4 pages. cited by applicant
Notice of Patent Allowance dated Jul. 26, 2021, in connection with Korean Application No. 10-2019-0032834, 5 pages. cited by applicant
Notice of Preliminary Rejection dated Feb. 13, 2022, in connection with Korean Application No. 10-2021-0143518, 8 pages. cited by applicant
Hearing Notice in Reference to Indian Application No. 201717046876 dated Jun. 28, 2022, 2 pages. cited by applicant
Office Action dated Apr. 25, 2022, in connection with Brazilian Application No. 112018000008-6, 5 pages. cited by applicant
Office Action dated Apr. 26, 2022, in connection with Mexican Application No. MX/a/2018/000383, 5 pages. cited by applicant
Notice of Final Rejection dated Aug. 29, 2022, in connection with Korean Application No. 10-2021-0143518, 5 pages. cited by applicant
Non-final Office Action dated Oct. 6, 2022, in connection with U.S. Appl. No. 17/582,000, 9 pages. cited by applicant
Final Office Action dated Apr. 12, 2023, in connection with U.S. Appl. No. 17/582,000, 10 pages. cited by applicant
Notice of Preliminary Rejection dated Aug. 7, 2023, in connection with Korean Application No. 10-2023-0036884, 6 pages. cited by applicant
Result of substantive examination dated Apr. 26, 2024, in connection with Vietnam Application No. 1-2021-04175, 4 pages. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of application Ser. No. 16/947,237, filed Jul. 24, 2020, which is a continuation of application Ser. No. 15/576,227, filed Nov. 21, 2017, now U.S. Pat. No. 10,767,300, which is the 371 National Stage of International Application No. PCT/KR2016/007849, filed Jul. 19, 2016, which claims priority to Korean Application No. 10-2015-0107288, filed on Jul. 29, 2015, the disclosures of which are fully incorporated herein by reference into the present disclosure as if fully set forth herein.

BACKGROUND

1. Field

(1) Embodiments of the present disclosure relate to a washing machine, and more particularly, to a washing machine provided with an improved wire connection structure capable of electrically connecting electrical components.

2. Description of Related Art

(2) Generally, a washing machine is a device configured to wash laundry by rotating a rotating tub of a cylindrical shape, which accommodates the laundry and washing water. The washing machine includes a drum washing machine in which a rotating tub is horizontally disposed and configured to raise upward laundry along an inner circumferential surface thereof and drop the laundry downward when the rotating tub is rotated in forward and reverse directions about a horizontal axis, thereby washing the laundry; and a vertical washing machine in which a rotating tub provided with a pulsator therein is vertically arranged and configured to wash laundry using a water stream generated by the pulsator when the rotating tub is rotated in forward and reverse directions about a vertical axis.

(3) The drum washing machine may include a cabinet configured to form an exterior, a cylindrical tub installed inside the cabinet and configured to accommodate washing water, a drum rotatably installed inside the tub and configured to wash laundry, a drive motor disposed in rear of the tub and configured to rotate the drum, and a door installed at a front surface of the cabinet. An opening communicating with the drum is provided at the cabinet, and the door is able to open and close the opening.

(4) Generally, electrical components are disposed inside the cabinet. However, while washing machines having various designs are realized, there is a case in which electrical components disposed inside the cabinet and electrical components disposed at an outside of the cabinet are electrically connected using a wire.

SUMMARY

(5) According to one aspect of the present disclosure, there is provided a washing machine with an improved structure capable of electrically connecting electrical components inside a door and electrical components inside a cabinet.

(6) According to another aspect of the present disclosure, there is provided a washing machine with an improved structure capable of connecting electrical components inside a door and electrical components inside a cabinet using a wire without hindering an aesthetic exterior of the washing machine.

(7) According to still another aspect of the present disclosure, there is provided a washing machine with an improved structure capable of allowing a wire to pass through a hinge assembly to electrically connect electrical components inside a door and electric components inside a cabinet.

(8) A washing machine according to the spirit of the present disclosure may include a first electrical component; a cabinet configured to form an exterior and having an opening through which laundry is introduced; a door provided with a second electrical component and configured to open and close the opening; a wire configured to electrically connect the first electrical component and the second electrical component; and a hinge configured to couple the door to the cabinet to allow the door to be pivotable about a rotating axis, and having a wire guide portion configured to guide the wire.

(9) The second electrical component may be provided inside the door.

(10) The door may be pivotable about a single rotation axis.

(11) The wire guide portion may be formed and recessed into the hinge to allow the wire to be insertable into the wire guide portion.

(12) The wire guide portion may be formed to pass through the hinge.

(13) The hinge may include a hinge body coupled to the cabinet; and at least one hinge arm extending from the hinge body and at which the wire guide portion is formed.

(14) The at least one hinge arm may include a first surface facing the cabinet, and the wire guide portion may be formed and recessed along at least a portion of the first surface.

(15) The at least one hinge arm may include a second surface that is directed downward in a rotating axis direction, and the wire guide portion may be formed and recessed along at least a portion of the second surface.

(16) The hinge may further include at least one protrusion that is formed to protrude from the at least one hinge arm in a rotating axis direction to form the rotating axis.

(17) The at least one protrusion may include a first protrusion formed to protrude upward from the at least one hinge arm in the rotating axis direction; and a second protrusion formed to protrude downward from the at least one hinge arm in the rotating axis direction, wherein a wire inlet may be formed on at least one of the first protrusion and the second protrusion to allow the wire to enter the wire guide portion.

(18) A wire outlet may be formed at one surface of the hinge body, which faces the cabinet, to allow the wire to exit from the wire guide portion.

(19) A through-hole may be formed at one surface of the cabinet to which the hinge body is coupled, and the wire exiting from the wire outlet may pass through the through-hole to enter the cabinet.

(20) The hinge may include a hinge cover detachably coupled to the wire guide portion to prevent the wire, which is inserted into the wire guide portion, from being exposed to the outside.

(21) The hinge may include a hinge body coupled to the cabinet; and at least one hinge arm extending from the hinge body toward a front side of the washing machine, wherein the wire guide portion may be formed to pass through the hinge body.

(22) A washing machine according to the spirit of the present disclosure may include a cabinet configured to form an exterior and having an opening through which laundry is introduced; a door provided to open and close the opening; a hinge configured to pivotably couple the door to the cabinet; and a wire passing through the hinge, wherein one end portion of the wire may be positioned inside the door, and the other end portion thereof may include a wire that is positioned inside the cabinet.

(23) A first electrical component may be provided inside the cabinet, a second electrical component may be provided inside the door, and the wire may electrically connect the first electrical component and the second electrical component.

(24) A wire guide portion, through which the wire passes, may be formed and recessed into the hinge.

(25) A wire guide portion, through which the wire passes, may be formed at the hinge and may pass therethrough.

(26) The hinge may include a hinge body coupled to the cabinet; and at least one hinge arm extending from the hinge body and at which a wire guide portion through which the wire passes is

formed.

(27) The at least one hinge arm may include a first arm extending from the hinge body toward a front side of the washing machine; and a second arm extending from the first arm and bent toward an outside of the washing machine, wherein the wire guide portion may be formed and recessed along at least one of one surface of the first arm and one surface of the second arm.

(28) The wire guide portion may be consecutively formed and recessed along at least one of the one surface of the first arm and the one surface of the second arm.

(29) The door may be pivotable about a single rotating axis, and the hinge may further include at least one protrusion that is formed to protrude from the at least one hinge arm in a rotating axis direction to form the rotating axis.

(30) The at least one hinge arm may include a first arm extending from the hinge body toward a front side of the washing machine; and a second arm extending from the first arm and bent toward outside the washing machine, wherein the at least one protrusion may be formed to protrude from the second arm in the rotating axis direction.

(31) A wire inlet may be formed on at least one of the protrusions to allow the wire to enter the wire guide portion.

(32) A wire outlet may be formed at one surface of the hinge body, which faces the cabinet, to allow the wire to exit from the wire guide portion.

(33) The hinge may include a hinge cover detachably coupled to the wire guide portion to prevent the wire, which is inserted into the wire guide portion, from being exposed to the outside.

(34) A washing machine according to the spirit of the present disclosure may include a cabinet having an opening through which laundry is introduced; a door provided with an electrical component and provided to open and close the opening; a wire electrically connected to the electrical component; and a hinge configured to couple the door to the cabinet and having a wire guide portion through which the wire passes.

(35) The door may be pivotable about a single rotation axis.

(36) While the electric components provided inside the door and the electric components provided inside the cabinet are connected by the wire, the wire is allowed to pass through the hinge such that the wire can be prevented from being significantly exposed to the outside.

(37) The wire is inserted into the wire guide portion formed at the hinge such that the wire can pass through the hinge in a simple and easy manner.

(38) The wire cover is coupled to the wire guide portion such that foreign materials can be prevented from flowing into the wire guide portion.

(39) The wire cover detachably coupled to the wire guide portion is used and thus, while the wire is inserted into the wire guide portion, a work may be performed in a state in which the wire cover is removed such that work efficiency can be improved, and, when the wire is inserted into the wire guide portion, the wire cover is coupled to the wire guide portion such that the wire can be stably accommodated in a wire accommodating space.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is one exemplified diagram illustrating a state in which a display is applied to a washing machine according to one embodiment of the present disclosure.

(2) FIG. 2 is another exemplified diagram illustrating a state in which a light emitting portion is applied to the washing machine according to one embodiment of the present disclosure.

(3) FIG. 3 is a perspective view illustrating a state in which a door of the washing machine according to one embodiment of the present disclosure is open.

(4) FIG. 4 is an exploded perspective view illustrating a coupling relationship between the door and

a hinge of the washing machine according to one embodiment of the present disclosure.

(5) FIG. 5 is an enlarged diagram of a part of FIG. 4.

(6) FIG. 6 is a diagram illustrating FIG. 5 when viewed at a different angle.

(7) FIG. 7 is an exploded perspective view illustrating a hinge according to a first example in the washing machine according to one embodiment of the present disclosure.

(8) FIG. 8 is an exploded perspective view illustrating the hinge according to the first example shown in FIG. 7 when viewed at a different angle in the washing machine according to one embodiment of the present disclosure.

(9) FIG. 9 is a diagram illustrating a coupling structure of the hinge according to the first example in the washing machine according to one embodiment of the present disclosure.

(10) FIG. 10 is a diagram schematically illustrating a connection state of a wire in the washing machine according to one embodiment of the present disclosure.

(11) FIG. 11 is a diagram schematically illustrating the connection state of the wire when viewed from a front side of a glass holder in the washing machine according to one embodiment of the present disclosure.

(12) FIG. 12 is a diagram schematically illustrating the connection state of the wire when viewed from a rear side of the glass holder in the washing machine according to one embodiment of the present disclosure.

(13) FIG. 13 is a diagram illustrating a coupling structure of a hinge according to a second example in the washing machine according to one embodiment of the present disclosure.

(14) FIG. 14 is a diagram illustrating a coupling structure of a hinge according to a third example in the washing machine according to one embodiment of the present disclosure.

(15) FIG. 15 is a diagram illustrating a coupling structure of a hinge according to a fourth example in the washing machine according to one embodiment of the present disclosure.

(16) FIG. 16 is an exploded perspective view illustrating a hinge according to a fifth example in the washing machine according to one embodiment of the present disclosure.

(17) FIG. 17 is a diagram illustrating a coupling structure of the hinge according to the fifth example in the washing machine according to one embodiment of the present disclosure.

(18) FIG. 18 is a diagram illustrating a coupling structure of a hinge according to a sixth example in the washing machine according to one embodiment of the present disclosure.

DETAILED DESCRIPTION

(19) Hereinafter, preferred embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. Meanwhile, the terms used in the following description of a “front end,” a “rear end,” an “upper portion,” a “lower portion,” an “upper end,” a “lower end,” and the like are defined based on the drawing, and a shape and a position of each component are not limited by these terms.

(20) An electrical component refers to an electrical and electronic component that receives power to operate. Also, the electrical component may also be used to include a power supply. The electrical component may include a first electrical component and a second electrical component, and detailed descriptions of the first electrical component and the second electrical component will be described below.

(21) FIG. 1 is one exemplified diagram illustrating a state in which a display is applied to a washing machine according to one embodiment of the present disclosure.

(22) As shown in FIG. 1, a display 2 may be applied to a washing machine 1. Specifically, the display 2 may be provided at a door 20 of the washing machine 1. The display 2 may display an operating state of the washing machine 1. Also, the display 2 may be implemented by a touch screen method so as to enable a user to easily select functions of the washing machine 1. Also, for convenience of the user, the display 2 may display a time, a temperature, and the like. In addition, the display 2 may display a picture, a photo, an image, and the like in consideration of design factors. At least one of the display 2 and a control panel 70 may be provided at the washing

machine **1**.

(23) As shown in FIG. **1**, when the display **2** is provided at the door **20** of the washing machine **1**, at least some of various electrical components required for operating the display **2** may be provided inside the door **20**. A circuit board configured to control an operating state of the display **2** may be one example of the electrical component.

(24) FIG. **2** is another exemplified diagram illustrating a state in which a light emitting portion is applied to the washing machine according to one embodiment of the present disclosure.

(25) As shown in FIG. **2**, a light emitting portion **3** may be applied to the washing machine **1**. Specifically, the light emitting portion **3** may be provided at the door **20** of the washing machine **1**. As one example, the light emitting portion **3** may be provided along an edge of the door **20**. The light emitting portion **3** is provided at the door **20** of the washing machine **1** so that the washing machine **1** may be implemented to have a dynamic design.

(26) As shown in FIG. **2**, when the light emitting portion **3** is provided at the door **20** of the washing machine **1**, at least some of various electrical components required to implement or operate the light emitting portion **3** may be provided inside the door **20**. A light emitting element, such as a light emitting diode (LED), or a circuit board configured to control an operating state of the light emitting portion **3** may be one example of the electrical component.

(27) As described above, various functions may be added to the door **20** of the washing machine **1** in consideration of user's convenience or a design aspect, and at least one of electrical components configured to implement the various functions may be provided inside the door **20**.

(28) FIG. **3** is a perspective view illustrating a state in which a door of the washing machine according to one embodiment of the present disclosure is open. FIG. **3** illustrates the washing machine **1** to which a hinge **100** according to a first example is applied.

(29) As shown in FIG. **3**, the washing machine **1** may include a cabinet **10** configured to form an exterior of the washing machine **1**. The cabinet **10** may include a front surface frame **11** configured to form a front exterior of the washing machine **1**, an upper surface frame **12** configured to form an upper exterior of the washing machine **1**, a side frame **13** configured to form a side exterior of the washing machine **1**, a lower surface frame (not shown) configured to form a lower exterior of the washing machine **1**, and a rear frame (not shown) configured to form a rear exterior of the washing machine **1**.

(30) The washing machine **1** may further include a tub (not shown). The tub may be installed inside the cabinet **10** and may accommodate washing water.

(31) The washing machine **1** may further include a drum **15**. The drum **15** may be rotatably installed inside the tub. A plurality of spin-drying holes **15a** may be formed at a wall surface of the drum **15**. The drum **15** may be cylindrical in shape. An opening may be provided at a front surface portion of the drum **15** to allow laundry to enter and exit from the drum **15**.

(32) The washing machine **1** may further include the door **20**. An opening **16** may be provided at the front surface frame **11** to allow laundry to enter and exit therefrom. The door **20** may be provided to open and close the opening **16**. Specifically, the door **20** may be pivotably installed at the front surface frame **11** of the cabinet **10** to open and close the opening **16**. The door **20** may be installed to be pivotable about a single rotating axis **195**. The door **20** will be described in detail below.

(33) A door contact portion **17** may be provided at the front surface frame **11** of the cabinet **10** to be in contact with the door **20** when the door **20** closes the opening **16**. The door contact portion **17** may be formed and recessed inside the washing machine **1** and may be formed along an edge of the opening **16**.

(34) Also, the door contact portion **17** may be formed to correspond to a shape of the door **20**. Accordingly, when the door **20** closes, a part protruding from a surface of the cabinet **10** may be minimized to improve the aesthetic exterior.

(35) The washing machine **1** may further include a water supply pipe (not shown) and a detergent

container **18**. The water supply pipe may be installed over the tub to supply the washing water inside the tub. One side of the water supply pipe may be connected to a water supply valve (not shown), and the other side thereof may be connected to the detergent container **18**.

(36) The detergent container **18** is connected to the drum **15** through a connection pipe (not shown), and water supplied through the water supply pipe is supplied inside the drum **15** in association with a detergent via the detergent container **18**.

(37) The washing machine **1** may further include a drive motor (not shown). The drive motor may be provided in rear of the drum **15** to drive the drum **15**.

(38) The washing machine **1** may further include a drainage unit (not shown). The drainage unit may be provided below the cabinet **10** to discharge the washing water inside the tub to an outside of the washing machine **1**. The drainage unit may include a drainage pump (not shown), a connection hose (not shown) configured to connect the tub and the drainage pump and allow the water inside the tub to flow into the drainage pump, and a drain hose (not shown) configured to guide the water pumped by the drainage pump to the outside of the washing machine **1**.

(39) The washing machine **1** may further include the control panel **70**. The control panel **70** may be provided at an upper portion of the front surface frame **11** of the cabinet **10**. The control panel **70** may include a display window **71** configured to display the operating state of the washing machine **1**, and a manipulation portion **72** provided to allow a user to manipulate the operating state of the washing machine **1**.

(40) The washing machine **1** may further include the hinge **100**. The hinge **100** may couple the door **20** to the cabinet **10**. In other words, the hinge **100** may pivotably couple the door **20** to the cabinet **10**. The hinge **100** will be described in detail below.

(41) The washing machine **1** may further include a first electrical component **200** (See, FIG. **10**). The first electrical component **200** may be provided at the cabinet **10**. Preferably, the first electrical component **200** may be provided inside the cabinet **10**.

(42) The first electrical component **200** may include, for example, a main printed circuit board (PCB), a sub PCB, a water supply valve, a drive motor, a power supply device, and the like. The main PCB may be disposed inside the cabinet **10**. Specifically, the main PCB may be disposed at a bottom surface of a rear side of the cabinet **10**. In other words, the main PCB may be disposed in rear of the drum **15**. The main PCB may control operating states of a microcomputer, the water supply valve, the drive motor, and the like. Also, the main PCB may control an operating state of a second electrical component **300**. The sub PCB may be disposed inside the control panel **70**. The sub PCB may control operating states of the display window **71**, the manipulation portion **72**, and the like, which are provided at the control panel **70**. Positions of the main PCB and the sub PCB are not limited to the above-described examples and may be variously changed. Hereinafter, as an example of the first electrical component **200**, the main PCB will be mainly described.

(43) The washing machine **1** may further include the second electrical component **300** (See, FIG. **10**). The second electrical component **300** may be provided outside the cabinet **10**. As one example of a position at which the second electrical component **300** is provided, the second electrical component **300** may be provided at the door **20**. Preferably, the second electrical component **300** may be provided inside the door **20**. As described in FIGS. **1** and **2**, the second electrical component **300** may include, for example, a circuit board configured to control an operating state of the display **2** (See, FIG. **1**), a light emitting element such as an LED, a circuit board configured to control an operating state of the light emitting portion **3** (See, FIG. **2**), and the like.

(44) The washing machine **1** may further include a wire **400** (See, FIG. **10**). The wire **400** may connect the first electrical component **200** and the second electrical component **300**. Specifically, the wire **400** may electrically connect the first electrical component **200** and the second electrical component **300**. The wire **400** will be described in detail below.

(45) FIG. **4** is an exploded perspective view illustrating a coupling relationship between the door and a hinge of the washing machine according to one embodiment of the present disclosure, and

FIG. 5 is an enlarged diagram of a part of FIG. 4. FIG. 6 is a diagram illustrating FIG. 5 when viewed at a different angle, and FIG. 7 is an exploded perspective view illustrating a hinge according to a first example in the washing machine according to one embodiment of the present disclosure. FIG. 8 is an exploded perspective view illustrating the hinge according to the first example shown in FIG. 7 when viewed at a different angle in the washing machine according to one embodiment of the present disclosure, and FIG. 9 is a diagram illustrating a coupling structure of the hinge according to the first example in the washing machine according to one embodiment of the present disclosure. FIGS. 4 to 6 illustrate the washing machine 1 to which the hinge 100 according to the first example is applied.

(46) As shown in FIGS. 4 to 9, the door 20 may include a door glass 30 provided to allow the user to verify an inside of the drum 15; a glass holder 40 to which the door glass 30 is coupled, and at which an accommodating recess 44 is formed, the accommodating recess 44 having one side in which or to which at least a portion of the hinge 100 is accommodated or coupled; a door cover 50 configured to cover a front surface of the glass holder 40; and a cover plate 60 positioned between the glass holder 40 and the door cover 50, and configured to form a receiving portion (not shown) covering the accommodating recess 44 to accommodate the accommodating recess 44 and the at least a portion of the hinge 100.

(47) The door glass 30 may be formed of a transparent plastic material to allow the user to visually verify a washing process.

(48) The door glass 30 may include a cylindrical glass body 31 having an open front side, a flange 32 formed along an outer circumferential surface of the glass body 31 to be coupled to the glass holder 40, and a guide portion 33 inclinedly formed behind the glass body 31 and configured to guide washing water, which is used in the washing process, to the drum 15.

(49) The glass holder 40 may include a holder body 41 with a circular-shaped plate in a central portion of which is hollow, a handgrip 42 formed at a front surface of the holder body 41 along a circumferential direction of the holder body 41, and a hinge coupling portion 43 formed at the front surface of the holder body 41 along the circumferential direction of the holder body 41 at a position facing the handgrip 42.

(50) The hinge coupling portion 43 may include at least one accommodating recess 44 in which or to which the at least a portion of the hinge 100 is accommodated or coupled, and a coupling rib 45 protruding from the front surface of the holder body 41 by a predetermined length to allow the cover plate 60 to be coupled to the coupling rib 45.

(51) The accommodating recess 44 may include a first accommodating recess 44a configured to accommodate a second arm 122 of the hinge 100 in a state in which the door 20 closes the opening 16, and a second accommodating recess 44b configured to accommodate a protrusion 130 of the hinge 100. The first accommodating recess 44a may be formed such that a portion of the holder body 41 is incised from an outside of the holder body 41 to an inside thereof by a predetermined length, and the second accommodating recess 44b may intersect and communicate with the first accommodating recess 44a. The first accommodating recess 44a may be provided in a direction approximately parallel to the ground and the second accommodating recess 44b may be provided in a direction approximately perpendicular to the first accommodating recess 44a.

(52) The coupling rib 45 is formed to be long along the circumferential direction of the holder body 41 and protrudes from the front surface of the holder body 41 by a predetermined length to allow the cover plate 60 to be coupled to the coupling rib 45. Also, since the coupling rib 45 protrudes from the front surface of the holder body 41 by a predetermined length, rigidity of the hinge coupling portion 43, on which a load of the door 20 is concentrated while the door 20 is pivoted, is reinforced so the door 20 may be stably pivoted without drooping or damage.

(53) The door cover 50 may form an exterior of the door 20 and may be coupled to the glass holder 40 to cover the front surface of the glass holder 40.

(54) The door glass 30, the glass holder 40, and the door cover 50 may be injection-molded with a

plastic material having a lightened weight and certain strength.

(55) The cover plate **60** is provided in a shape corresponding to the coupling rib **45** and is coupled to the hinge coupling portion **43** in a direction parallel to an axial direction of the drum **15**. The cover plate **60** may include a plurality of bent portions **61** formed such that an outer end of each of the plurality of bent portions **61** is bent to cover the hinge coupling portion **43**, and a third accommodating recess **62** configured to accommodate a portion of each of the second arm **122** and the protrusion **130** at a position corresponding to each of the first accommodating recess **44a** and the second accommodating recess **44b** so as for the door **20** not to interfere with the second arm **122** and the protrusion **130** of the hinge **100** in a state in which the door **20** closes the opening **16**.

(56) The third accommodating recess **62** may form an accommodating portion (not shown) configured to accommodate at least a portion of the hinge **100** in association with the first accommodating recess **44a** and the second accommodating recess **44b**. Specifically, the third accommodating recess **62** may accommodate the second arm **122** in association with the first accommodating recess **44a** so as to prevent the cover plate **60** from interfering with the second arm **122**, and may accommodate or support the protrusion **130** in association with the second accommodating recess **44b** so as to allow the door **20** to be pivoted about the rotating axis **195**.

(57) The hinge **100** may couple the door **20** to the cabinet **10** to allow the door **20** to be pivotable about the rotating axis **195**.

(58) The hinge **100** may include a hinge body **110**. The hinge body **110** may be coupled to the cabinet **10**. Specifically, the hinge body **110** may be coupled to a front surface of the cabinet **10** at an outside of the opening **16**. That is, the hinge body **110** may be coupled to the front surface frame **11** at the outside of the opening **16**.

(59) The hinge body **110** may be provided as a plate formed to be long approximately along a circumferential direction of the door **20**. Also, the hinge body **110** may include a plurality of fixing holes **111** to be fixed to the front surface of the cabinet **10**, that is, the front surface frame **11**.

(60) The hinge **100** may further include at least one hinge arm **120**. The at least one hinge arm **120** may extend from the hinge body **110**.

(61) The at least one hinge arm **120** may include a first arm **121** extending from the hinge body **110** toward a front side of the washing machine **1**. That is, the first arm **121** may be formed to extend from a front surface of the hinge body **110** by a predetermined length.

(62) The at least one hinge arm **120** may further include the second arm **122** extending from the first arm **121** and bent toward an outside of the washing machine **1**.

(63) According to another aspect, the at least one hinge arm **120** may include a first surface **123**. The first surface **123** may face the cabinet **10**. Specifically, the first surface **123** may face the front surface of the cabinet **10**.

(64) The at least one hinge arm **120** may further include a second surface **124**. The second surface **124** may be directed downward in a rotating axis direction X.

(65) The at least one hinge arm **120** may further include a third surface **125**. The third surface **125** may be directed upward in the rotating axis direction X.

(66) The at least one hinge arm **120** may further include a fourth surface **126**. The fourth surface **126** may face the door **20**.

(67) The second surface **124** and the third surface **125** may respectively connect the first surface **123** and the fourth surface **126**. Specifically, the second surface **124** may connect a lower end portion of the first surface **123** and a lower end portion of the fourth surface **126**. The third surface **125** may connect an upper end portion of the first surface **123** and an upper end portion of the fourth surface **126**.

(68) The hinge **100** may further include at least one protrusion **130**. The at least one protrusion **130** may be formed to protrude from the at least one hinge arm **120** in the rotating axis direction X. The at least one protrusion **130** may form the rotating axis **195**.

(69) The at least one protrusion **130** may include a first protrusion **131** and a second protrusion **132**.

The first protrusion **131** may be formed to protrude upward from the at least one hinge arm **120** in the rotating axis direction X. The second protrusion **132** may be formed to protrude downward from the at least one hinge arm **120** in the rotating axis direction X. Specifically, the first protrusion **131** may be formed to protrude upward from one end of the second arm **122** in the rotating axis direction X, and the second protrusion **132** may be formed to protrude downward from one end of the second arm **122** in the rotating axis direction X. That is, the first protrusion **131** and the second protrusion **132** may respectively extend upward and downward from the second arm **122** in the rotating axis direction X.

(70) The hinge **100** may further include a wire guide portion **140** configured to guide the wire **400**.

(71) The wire guide portion **140** may be formed at the hinge **100**. The wire guide portion **140** may be formed and recessed into the hinge **100** to allow the wire **400** to pass through the wire guide portion **140**. In other words, the wire guide portion **140** may be formed and recessed into the hinge **100** to allow the wire **400** to be inserted into the wire guide portion **140**.

(72) The wire guide portion **140** may be formed at the at least one hinge arm **120**. The wire guide portion **140** may be formed and recessed along at least one of one surface of the first arm **121** and one surface of the second arm **122**. The wire guide portion **140** may be consecutively formed and recessed along the at least one of one surface of the first arm **121** and one surface of the second arm **122**.

(73) The wire guide portion **140** may be formed and recessed along at least a portion of the first surface **123**.

(74) The hinge **100** may further include a wire inlet **150**. The wire inlet **150** may be formed to communicate with the wire guide portion **140** to allow the wire **400** to enter the wire guide portion **140**. The wire inlet **150** may be formed on at least one of the at least one protrusion **130**. That is, the wire inlet **150** may be formed on at least one of the first protrusion **131** and the second protrusion **132**. Preferably, the wire inlet **150** may be formed at the second protrusion **132**.

(75) The hinge **100** may further include a wire outlet **160**. The wire outlet **160** may be formed at one surface **112** of the hinge body **110**, which faces the cabinet **10**, to allow the wire **400** to exit from the wire guide portion **140**. The wire outlet **160** may be formed to communicate with the wire guide portion **140** to allow the wire **400** to exit from the wire guide portion **140**.

(76) The hinge **100** may further include a hinge cover **170**. The hinge cover **170** may be detachably coupled to the wire guide portion **140**. The hinge cover **170** may serve to prevent foreign materials from flowing into the wire guide portion **140**. Also, the hinge cover **170** may serve to prevent the wire **400** inserted into the wire guide portion **140** from being exposed to the outside. The hinge cover **170** may be detachably coupled to the wire guide portion **140** and form a portion of an exterior of the hinge **100**. Thus, the hinge cover **170** detachably coupled to the wire guide portion **140** is used, and thus, while the wire **400** is inserted into the wire guide portion **140**, a work may be performed in a state in which the hinge cover **170** is removed such that work performance may be improved, and, when the wire **400** has been inserted into the wire guide portion **140**, the hinge cover **170** is coupled to the wire guide portion **140** such that the wire **400** may be stably accommodated in the wire guide portion **140**.

(77) The hinge cover **170** may include a cover body **171**.

(78) The hinge cover **170** may further include at least one coupling rib **172**. The at least one coupling rib **172** may extend from the cover body **171**. Preferably, the at least one coupling rib **172** may include a first coupling rib **172a** extending upward from the cover body **171** in the rotating axis direction and a second coupling rib **172b** extending downward from the cover body **171** in the rotating axis direction X.

(79) The at least one coupling rib **172** may be coupled to at least one coupling recess **127** formed at the at least one hinge arm **120**. The at least one coupling rib **172** may be fitted into and coupled to the at least one coupling recess **127**. The at least one coupling recess **127** may be formed on a plane the same as one surface of the at least one hinge arm **120**, at which the wire guide portion **140** is

formed. As one example, when the wire guide portion **140** is formed at the first surface **123** of the at least one hinge arm **120**, the at least one coupling recess **127** may also be formed at the first surface **123** of the at least one hinge arm **120**.

(80) The hinge cover **170** may further include at least one support rib **173**. The at least one support rib **173** may extend from the cover body **171**. The at least one support rib **173** may be hooked and coupled to one surface of the at least one hinge arm **120**. The at least one support rib **173** may include a bent portion **174** with a bent shape to allow the hinge cover **170** to be coupled to the wire guide portion **140**. As one example, when the wire guide portion **140** is formed at the first surface **123** of the at least one hinge arm **120**, the at least one support rib **173** may extend downward from the cover body **171** in the rotating axis direction X, and, at this point, the bent portion **174** may be hooked and coupled to the second surface **124** of the at least one hinge arm **120**. As another example, when the wire guide portion **140** is formed at the first surface **123** of the at least one hinge arm **120**, the at least one support rib **173** may extend upward from the cover body **171** in the rotating axis direction X, and, at this point, the bent portion **174** may be hooked and coupled to the third surface **125** of the at least one hinge arm **120**.

(81) The hinge cover **170** may be stably coupled to the wire guide portion **140** by the at least one coupling rib **172** and the at least one support rib **173**.

(82) One end portion of the hinge cover **170** may form the wire inlet **150** in association with the at least one protrusion **130**. Specifically, the at least one protrusion **130** may include an incised portion **175**, and one end portion of the hinge cover **170** may be coupled to the incised portion **175** to form the wire inlet **150** in association with the at least one protrusion **130**.

(83) The other end portion of the hinge cover **170** may form a part of the wire outlet **160**. In other words, the other end portion of the hinge cover **170** may form the wire outlet **160** in association with the hinge body **110**.

(84) The hinge **100** may further include at least one protrusion cover **180**. The at least one protrusion cover **180** may be coupled to enclose the at least one protrusion **130**. The at least one protrusion cover **180** may be detachably coupled to the at least one protrusion **130** to prevent abrasion or damage of the at least one protrusion **130** serving as the rotating axis **195**.

(85) The washing machine **1** may further include a fixing ring **190** coupled to the at least one protrusion **130**. The fixing ring **190** may be coupled to enclose the at least one protrusion **130** from the outside. The fixing ring **190** may be coupled to the at least one protrusion **130** at which the wire inlet **150** is formed. The fixing ring **190** may have a cylindrical shape with an open bottom. However, the shape of the fixing ring **190** is not limited to the describe above, and may be variously modified. The fixing ring **190** may simultaneously enclose at least one protrusion forming the wire inlet **150** and one end portion of the hinge cover **170**. The at least one protrusion **130** and the one end portion of the hinge cover **170** may be firmly coupled by the fixing ring **190**.

(86) The at least one hinge arm **120** may include a first hinge arm **128** positioned downward in the rotating axis direction X, and a second hinge arm **129** positioned upward in the rotating axis direction X. As shown in FIGS. 7 to 9, the wire guide portion **140** of the hinge **100** according to the first example may be formed at the first hinge arm **128**. Specifically, the wire guide portion **140** of the hinge **100** according to the first example may be formed and recessed into the first surface **123** of the first hinge arm **128**.

(87) FIG. 10 is a diagram schematically illustrating a connection state of a wire in the washing machine according to one embodiment of the present disclosure, and FIG. 11 is a diagram schematically illustrating the connection state of the wire when viewed from a front side of a glass holder in the washing machine according to one embodiment of the present disclosure. FIG. 12 is a diagram schematically illustrating the connection state of the wire when viewed from a rear side of the glass holder in the washing machine according to one embodiment of the present disclosure. In FIG. 10, the wire **400** disposed inside the washing machine **1** is illustrated by a solid line to help understanding of the present disclosure.

(88) As shown in FIGS. **10** to **12**, the wire **400** may pass through the hinge **100**. Specifically, one end portion of the wire **400**, which passes through the hinge **100**, may be positioned inside the door **20**, and the other end portion of the wire **400**, which passes through the hinge **100**, may be positioned inside the cabinet **10**.

(89) The wire **400** may be electrically connected to an electrical component. In other words, the wire **400** may electrically connect the first electrical component **200** and the second electrical component **300**.

(90) The wire **400** may include a first wire **410** and a second wire **420** connected to the first wire **410**. The first wire **410** may pass through the hinge **100** to be connected to the second wire **420**. One end portion of the first wire **410** may be connected to the second electrical component **300** provided inside the door **20**, and the other end portion of the first wire **410** may be connected to the second wire **420**. In other words, the first wire **410** and the second wire **420** may be connected to each other through coupling between a connector **411** provided at the other end portion of the first wire **410** and a connector **421** provided at a one end portion of the second wire **420**. The coupling between the first wire **410** and the second wire **420** may be made inside the cabinet **10**. The second wire **420** may include a main wire harness.

(91) While the first electrical component **200** and the second electrical component **300** are connected, at least a portion of the wire **400** may be disposed along the circumferential direction of the door **20**. As one example, at least a portion of the wire **400** positioned inside the door **20** may be disposed along the circumferential direction of the door **20**.

(92) A through-hole **10a** (See, FIG. **4**) may be formed at the cabinet **10**. Specifically, the through-hole **10a** may be formed at one surface of the cabinet **10** to which the hinge body **110** is coupled, that is, at the front surface of the cabinet **10**. The wire **400** passing through the hinge **100** may pass through the through-hole **10a** to enter the cabinet **10**.

(93) The wire **400** connected to the second electrical component **300** reaches the hinge **100**, and the wire **400** reaching the hinge **100** passes through the hinge **100** to be connected to the first electrical component **200** provided inside the cabinet **10**. In other words, the one end portion of the wire **400** may be connected to the second electrical component **300**, and the other end portion thereof may pass through the hinge **100** to be connected to the first electrical component **200**. As described above, since the first electrical component **200** and the second electrical component **300** may be electrically connected by the wire **400** passing through the hinge **100**, it may be prevented that most of the wire **400** is exposed to the outside to hinder an aesthetic beauty of the washing machine **1**.

(94) The wire **400** connected to the second electrical component **300** provided at the door **20** reaches the hinge **100** along the circumferential direction of the door **20**. The wire **400** reaching the hinge **100** is inserted into the wire guide portion **140** through the wire inlet **150**. The wire **400** inserted into the wire guide portion **140** passes through the wire outlet **160** and the through-hole **10a**, which is provided at the one surface of the cabinet **10** to correspond to the wire outlet **160**, to exit inside the cabinet **10**. The wire **400** exiting from the cabinet **10** is connected to the first electrical component **200** provided inside the cabinet **10**.

(95) FIG. **13** is a diagram illustrating a coupling structure of a hinge according to a second example in the washing machine according to one embodiment of the present disclosure. Hereinafter, a description overlapping with that of the hinge **100** according to the first example will be omitted.

(96) As shown in FIG. **13**, a wire guide portion **540** of a hinge **500** according to a second example may be formed at the second hinge arm **129** positioned upward in the rotating axis direction X. Specifically, the wire guide portion **540** of the hinge **500** according to the second example may be formed and recessed into the first surface **123** of the second hinge arm **129**.

(97) FIG. **14** is a diagram illustrating a coupling structure of a hinge according to a third example in the washing machine according to one embodiment of the present disclosure. Hereinafter, a description overlapping with that of the hinge **100** according to the first example will be omitted.

(98) As shown in FIG. **14**, a wire guide portion **640** may be formed to pass through a hinge **600**. In

other words, the wire guide portion **640** may be formed at the hinge **600** in a form of a hole to allow the wire **400** to pass through the wire guide portion **640**.

(99) Specifically, the wire guide portion **640** may be formed to pass through the at least one hinge arm **120**. The wire guide portion **640** may be formed to pass through the at least one hinge arm **120** in a direction approximately perpendicular to the rotating axis **195**. The wire inlet **150** may be formed at the fourth surface **126** of the at least one hinge arm **120**. The wire outlet **160** may be formed at the one surface **112** of the hinge body **110**, which faces the cabinet **10**. The wire inlet **150** and the wire outlet **160** may be formed to communicate with the wire guide portion **640**.

(100) FIG. **14** illustrates a case in which the wire guide portion **640** is formed at the first hinge arm **128**, but the wire guide portion **640** may be formed on at least one of the first hinge arm **128** and the second hinge arm **129**.

(101) FIG. **15** is a diagram illustrating a coupling structure of a hinge according to a fourth example in the washing machine according to one embodiment of the present disclosure. Hereinafter, a description overlapping with that of the hinge **100** according to the first example will be omitted.

(102) As shown in FIG. **15**, a wire guide portion **740** may be formed to pass through a hinge **700**. In other words, the wire guide portion **740** may be formed at the hinge **700** in a form of a hole to allow the wire **400** to pass through the wire guide portion **740**.

(103) Specifically, the wire guide portion **740** may be formed to pass through the hinge body **110**. The wire guide portion **740** may be formed to pass through the hinge body **110** in a direction approximately perpendicular to the rotating axis **195**. The wire inlet **150** may be formed at one surface **113** of the hinge body **110**, which faces the door **20**. The wire outlet **160** may be formed at the one surface **112** of the hinge body **110**, which faces the cabinet **10**. The wire inlet **150** and the wire outlet **160** may be formed to communicate with the wire guide portion **740**.

(104) FIG. **15** illustrates a case in which the wire guide portion **740** is formed below the first hinge arm **128**, but the wire guide portion **740** may be formed between the first hinge arm **128** and the second hinge arm **129**, or over the second hinge arm **129**.

(105) FIG. **16** is an exploded perspective view illustrating a hinge according to a fifth example in the washing machine according to one embodiment of the present disclosure, and FIG. **17** is a diagram illustrating a coupling structure of the hinge according to the fifth example in the washing machine according to one embodiment of the present disclosure. Hereinafter, a description overlapping with that of the hinge **100** according to the first example will be omitted.

(106) As shown in FIGS. **16** and **17**, a wire guide portion **840** may be formed and recessed into a hinge **800** to allow the wire **400** to be inserted into the wire guide portion **840**. Specifically, the wire guide portion **840** may be formed and recessed into the at least one hinge arm **120**.

(107) The wire guide portion **840** may be formed and recessed along at least a portion of the second surface **124** of the at least one hinge arm **120**, wherein the at least a portion is directed downward in the rotating axis direction X.

(108) The wire inlet **150** may be formed at the at least one protrusion **130**. Specifically, the at least one protrusion **130** may include the incised portion **175**, and the one end portion of the hinge cover **170** may be coupled to the incised portion **175** to form the wire inlet **150** in association with the at least one protrusion **130**.

(109) The wire outlet **160** may be formed at the one surface **112** of the hinge body **110**, which faces the cabinet **10**, to allow the wire **400** to exit from the wire guide portion **840**.

(110) The wire inlet **150** and the wire outlet **160** may be formed to communicate with the wire guide portion **840**.

(111) The hinge **800** may further include an additional wire outlet **841**. The additional wire outlet **841** may be formed at a side surface of the hinge body **110**. Specifically, the additional wire outlet **841** may be formed at one side surface of the hinge body **110**, which is directed to the rotating axis **195**. The additional wire outlet **841** may also be formed to communicate with the wire guide portion **840**.

(112) The wire **400** is inserted into the wire inlet **150** to be directed upward in the rotating axis direction X. The wire **400** inserted into the wire inlet **150** is moved toward an inside of the cabinet **10** in a direction approximately perpendicular to the rotating axis direction X. In other words, the wire **400** inserted into the wire inlet **150** is moved toward the inside of the cabinet **10** along one surface of the second arm **122**. Thereafter, the wire **400** is moved toward the rear side of the washing machine **1**. In other words, the wire **400** is moved toward the rear side of the washing machine **1** along one side of the first arm **121**. The wire **400**, which is moved toward the rear side of the washing machine **1** along the one side of the first arm **121**, may pass through the wire outlet **160** or the additional wire outlet **841** to enter the cabinet **10**. After the wire **400** is inserted into the wire guide portion **840**, the hinge cover **170** may be detachably coupled to the wire guide portion **840**.

(113) As shown in FIGS. **16** and **17**, the wire guide portion **840** may be formed and recessed into the first hinge arm **128**. Specifically, the wire guide portion **840** may be formed and recessed along at least a portion of the second surface **124** of the first hinge arm **128**.

(114) FIG. **18** is a diagram illustrating a coupling structure of a hinge according to a sixth example in the washing machine according to one embodiment of the present disclosure. Hereinafter, descriptions overlapping with those of the hinge **100** according to the first example and the hinge **800** according to the fifth example will be omitted.

(115) As shown in FIG. **18**, a wire guide portion **940** of a hinge **900** may be formed and recessed into the second hinge arm **129**. Specifically, the wire guide portion **940** may be formed and recessed along at least a portion of the second surface **124** of the second hinge arm **129**.

(116) Hereinbefore, specific embodiments are shown and described. However, the present disclosure is not limited to these specific embodiments, and various modified embodiments can be devised from those skilled in the art without departing from the gist of a technical spirit that is defined by the appended claims.

Claims

1. A washing machine comprising: a cabinet having an opening at a front side; a drum rotatably disposed inside the cabinet; a door configured to open or close the opening; a hinge configured to pivotably couple the door to the cabinet; and a wire extending from an inside of the cabinet to the door, wherein the hinge comprises: a hinge body coupled to the cabinet, a first hinge arm, a second hinge arm that is spaced apart from the first hinge arm along a direction of a rotating axis, and a wire guide portion formed at the first hinge arm to accommodate the wire, wherein the first hinge arm includes a first surface facing the second hinge arm and a second surface opposite the first surface, and wherein the wire guide portion is formed to be recessed at the second surface.
2. The washing machine of claim 1, wherein the hinge further comprises a protrusion protruding from the first hinge arm to form the rotating axis of the door.
3. The washing machine of claim 2, wherein the hinge further comprises a hinge cover coupled to the first hinge arm and the protrusion to cover the wire guide portion.
4. The washing machine of claim 3, wherein the hinge further comprises a fixing ring configured to enclose the protrusion and an end portion of the hinge cover to couple the end portion of the hinge cover to the protrusion.
5. The washing machine of claim 4, wherein the wire passes through the fixing ring.
6. The washing machine of claim 4, wherein the protrusion includes an incised portion extending from the first hinge arm along an exterior surface of the protrusion.
7. The washing machine of claim 6, wherein the door includes an accommodating recess configured to accommodate the fixing ring enclosing the protrusion and the end portion of the hinge cover.
8. The washing machine of claim 7, wherein the accommodating recess allows the fixing ring to

rotate about the rotation axis of the protrusion.

9. The washing machine of claim 7, wherein the wire passes through the accommodating recess when the fixing ring is inserted to provide power to an electrical component in the door.

10. The washing machine of claim 6, wherein the end portion of the hinge cover completes an outer circumference of the protrusion at the incised portion.

11. The washing machine of claim 2, wherein the protrusion includes an incised portion extending from the first hinge arm along an exterior surface of the protrusion.

12. The washing machine of claim 11, wherein the incised portion forms a wire inlet together with an end portion of the hinge cover.

13. The washing machine of claim 2, wherein the protrusion includes: a first protrusion formed to protrude in a first direction from the first hinge arm, and a second protrusion formed to protrude in a second direction opposite to the first direction.

14. The washing machine of claim 13, wherein the hinge further includes a protrusion cover configured to be coupled to the second protrusion to protect the second protrusion.

15. The washing machine of claim 1, wherein the first hinge arm extends from the hinge body toward the front side of the cabinet.

16. The washing machine of claim 1, wherein the wire is disposed in the recessed wire guide portion.

17. The washing machine of claim 1, further comprising: a first electrical component provided at the cabinet; and a second electrical component provided at the door, wherein the wire connects the first electrical component and the second electrical component.

18. The washing machine of claim 1, wherein a wire outlet is formed at one surface of the hinge body to allow the wire to exit from the wire guide portion.

19. The washing machine of claim 18, wherein: the cabinet includes a through-hole, and the wire exiting from the wire outlet passes through the through-hole to enter the cabinet.

20. The washing machine of claim 18, wherein the wire outlet is spaced apart from at least one of the first hinge arm or the second hinge arm.
