

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12393906
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Kirmani; Shahzad Farooq et al.

System and method of object tracking using weight confirmation

Abstract

Methods and systems for tracking an object comprise a horizontal surface upon which objects are to be placed, a weight sensor disposed on one side of the horizontal surface, and a processor in communication with the weight sensor. The processor is adapted to detect a change in weight measured by the weight sensor, to associate the detected weight change with an identified object and with a location on the horizontal surface, and to confirm whether a cause of the weight change at the location on the horizontal surface corresponds to a proper handling of the identified object.

Inventors: Kirmani; Shahzad Farooq (Scarborough, ME), Seiger; Alex (Concord, NH)

Applicant: Position Imaging, Inc. (Portsmouth, NH)

Family ID: 1000008766938

Assignee: Position Imaging, Inc. (Portsmouth, NH)

Appl. No.: 18/737468

Filed: June 07, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240330843 A1	Oct. 03, 2024

Related U.S. Application Data

continuation parent-doc US 17894472 20220824 US 12008513 child-doc US 18737468
continuation parent-doc US 15259474 20160908 US 11436553 20220906 child-doc US 17894472

Publication Classification

Int. Cl.: G06Q10/0833 (20230101); G01G19/00 (20060101); G06K7/10 (20060101)

U.S. Cl.:

CPC **G06Q10/0833** (20130101); **G01G19/005** (20130101); **G06K7/10861** (20130101);

Field of Classification Search

CPC: G06Q (10/08); G06K (7/00); G01G (19/00); G01G (19/002-007)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2408122	12/1945	Wirkler	N/A	N/A
3824596	12/1973	Guion et al.	N/A	N/A
3940700	12/1975	Fischer	N/A	N/A
4018029	12/1976	Safranski et al.	N/A	N/A
4328499	12/1981	Anderson et al.	N/A	N/A
4570416	12/1985	Shoenfeld	N/A	N/A
5010343	12/1990	Andersson	N/A	N/A
5343212	12/1993	Rose et al.	N/A	N/A
5426438	12/1994	Peavey et al.	N/A	N/A
5510800	12/1995	McEwan	N/A	N/A
5545880	12/1995	Bu et al.	N/A	N/A
5574468	12/1995	Rose	N/A	N/A
5592180	12/1996	Yokev et al.	N/A	N/A
5600330	12/1996	Blood	N/A	N/A
5657026	12/1996	Culpepper et al.	N/A	N/A
5671362	12/1996	Cowe et al.	N/A	N/A
5923286	12/1998	Divakaruni	N/A	N/A
5953683	12/1998	Hansen et al.	N/A	N/A
6088653	12/1999	Sheikh et al.	N/A	N/A
6101178	12/1999	Beal	N/A	N/A
6167347	12/1999	Lin	N/A	N/A
6255991	12/2000	Hedin	N/A	N/A
6285916	12/2000	Kadaba et al.	N/A	N/A
6292750	12/2000	Lin	N/A	N/A
6409687	12/2001	Foxlin	N/A	N/A
6417802	12/2001	Diesel	N/A	N/A
6492905	12/2001	Mathias et al.	N/A	N/A
6496778	12/2001	Lin	N/A	N/A
6512748	12/2002	Mizuki et al.	N/A	N/A
6593885	12/2002	Wisherd et al.	N/A	N/A
6619550	12/2002	Good et al.	N/A	N/A
6630904	12/2002	Gustafson et al.	N/A	N/A
6634804	12/2002	Toste et al.	N/A	N/A
6683568	12/2003	James et al.	N/A	N/A
6697736	12/2003	Lin	N/A	N/A
6720920	12/2003	Breed et al.	N/A	N/A
6721657	12/2003	Ford et al.	N/A	N/A

6744436	12/2003	Chirieleison, Jr. et al.	N/A	N/A
6750816	12/2003	Kunysz	N/A	N/A
6861982	12/2004	Forstrom et al.	N/A	N/A
6867774	12/2004	Halmshaw et al.	N/A	N/A
6988079	12/2005	Or-Bach et al.	N/A	N/A
6989789	12/2005	Ferreol et al.	N/A	N/A
7009561	12/2005	Menache et al.	N/A	N/A
7104453	12/2005	Zhu et al.	N/A	N/A
7143004	12/2005	Townsend et al.	N/A	N/A
7168618	12/2006	Schwartz	N/A	N/A
7190309	12/2006	Hill	N/A	N/A
7193559	12/2006	Ford et al.	N/A	N/A
7236091	12/2006	Kiang et al.	N/A	N/A
7292189	12/2006	Orr et al.	N/A	N/A
7295925	12/2006	Breed et al.	N/A	N/A
7315281	12/2007	Dejanovic et al.	N/A	N/A
7336078	12/2007	Merewether et al.	N/A	N/A
7353994	12/2007	Farrall et al.	N/A	N/A
7407100	12/2007	Guyett et al.	N/A	N/A
7409290	12/2007	Lin	N/A	N/A
7443342	12/2007	Shirai et al.	N/A	N/A
7499711	12/2008	Hector et al.	N/A	N/A
7533569	12/2008	Sheynblat	N/A	N/A
7612715	12/2008	Macleod	N/A	N/A
7646330	12/2009	Karr	N/A	N/A
7689465	12/2009	Shakes et al.	N/A	N/A
7844507	12/2009	Levy	N/A	N/A
7868760	12/2010	Smith et al.	N/A	N/A
7876268	12/2010	Jacobs	N/A	N/A
7933730	12/2010	Li et al.	N/A	N/A
7995109	12/2010	Kamada et al.	N/A	N/A
8009918	12/2010	Van Droogenbroeck et al.	N/A	N/A
8189855	12/2011	Opalach et al.	N/A	N/A
8201737	12/2011	Palacios Durazo	235/383	G06Q 10/087
8219438	12/2011	Moon et al.	N/A	N/A
8269624	12/2011	Chen et al.	N/A	N/A
8295542	12/2011	Albertson et al.	N/A	N/A
8334513	12/2011	Garvey, III et al.	N/A	N/A
8406470	12/2012	Jones et al.	N/A	N/A
8457655	12/2012	Zhang et al.	N/A	N/A
8619144	12/2012	Chang et al.	N/A	N/A
8749433	12/2013	Hill	N/A	N/A
8843231	12/2013	Ragusa et al.	N/A	N/A
8860611	12/2013	Anderson et al.	N/A	N/A
8957812	12/2014	Hill et al.	N/A	N/A
9063215	12/2014	Perthold et al.	N/A	N/A
9092898	12/2014	Fraccaroli et al.	N/A	N/A
9120621	12/2014	Curlander et al.	N/A	N/A

9141194	12/2014	Keyes et al.	N/A	N/A
9171278	12/2014	Kong et al.	N/A	N/A
9174746	12/2014	Bell et al.	N/A	N/A
9269022	12/2015	Rhoads et al.	N/A	N/A
9349076	12/2015	Liu et al.	N/A	N/A
9424493	12/2015	He et al.	N/A	N/A
9482741	12/2015	Min et al.	N/A	N/A
9497728	12/2015	Hill	N/A	N/A
9500396	12/2015	Yoon et al.	N/A	N/A
9514389	12/2015	Erhan et al.	N/A	N/A
9519344	12/2015	Hill	N/A	N/A
9544552	12/2016	Takahashi	N/A	N/A
9594983	12/2016	Alattar et al.	N/A	N/A
9656749	12/2016	Hanlon	N/A	N/A
9740937	12/2016	Zhang et al.	N/A	N/A
9782669	12/2016	Hill	N/A	N/A
9872151	12/2017	Puzanov et al.	N/A	N/A
9904867	12/2017	Fathi et al.	N/A	N/A
9933509	12/2017	Hill et al.	N/A	N/A
9961503	12/2017	Hill	N/A	N/A
9996818	12/2017	Ren et al.	N/A	N/A
10001833	12/2017	Hill	N/A	N/A
10148918	12/2017	Seiger et al.	N/A	N/A
10163149	12/2017	Famularo et al.	N/A	N/A
10180490	12/2018	Schneider et al.	N/A	N/A
10257654	12/2018	Hill	N/A	N/A
10324474	12/2018	Hill et al.	N/A	N/A
10332066	12/2018	Palaniappan	N/A	G01G 19/42
10339493	12/2018	Famularo et al.	N/A	N/A
10373322	12/2018	Buibas et al.	N/A	N/A
10399778	12/2018	Shekhawat et al.	N/A	N/A
10416276	12/2018	Hill et al.	N/A	N/A
10444323	12/2018	Min et al.	N/A	N/A
10455364	12/2018	Hill	N/A	N/A
10605904	12/2019	Min et al.	N/A	N/A
10664795	12/2019	Worley et al.	N/A	N/A
10853757	12/2019	Hill et al.	N/A	N/A
11361536	12/2021	Chakravarty et al.	N/A	N/A
11416805	12/2021	Piotrowski et al.	N/A	N/A
11562318	12/2022	Robinson et al.	N/A	N/A
11983663	12/2023	Hill et al.	N/A	N/A
2001/0027995	12/2000	Patel et al.	N/A	N/A
2002/0021277	12/2001	Kramer et al.	N/A	N/A
2002/0095353	12/2001	Razumov	N/A	N/A
2002/0140745	12/2001	Ellenby et al.	N/A	N/A
2002/0177476	12/2001	Chou	N/A	N/A
2003/0024987	12/2002	Zhu	N/A	N/A
2003/0053492	12/2002	Matsunaga	N/A	N/A
2003/0110152	12/2002	Hara	N/A	N/A
2003/0115162	12/2002	Konick	N/A	N/A

2003/0120425	12/2002	Stanley et al.	N/A	N/A
2003/0132279	12/2002	Stemmle	N/A	N/A
2003/0176196	12/2002	Hall et al.	N/A	N/A
2003/0184649	12/2002	Mann	N/A	N/A
2003/0195017	12/2002	Chen et al.	N/A	N/A
2004/0002642	12/2003	Dekel et al.	N/A	N/A
2004/0095907	12/2003	Agee et al.	N/A	N/A
2004/0107072	12/2003	Dietrich et al.	N/A	N/A
2004/0176102	12/2003	Lawrence et al.	N/A	N/A
2004/0203846	12/2003	Caronni et al.	N/A	N/A
2004/0267640	12/2003	Bong et al.	N/A	N/A
2005/0001712	12/2004	Yarbrough	N/A	N/A
2005/0025353	12/2004	Kaneko et al.	N/A	N/A
2005/0057647	12/2004	Nowak	N/A	N/A
2005/0062849	12/2004	Foth et al.	N/A	N/A
2005/0074162	12/2004	Tu et al.	N/A	N/A
2005/0143916	12/2004	Kim et al.	N/A	N/A
2005/0154685	12/2004	Mundy et al.	N/A	N/A
2005/0184907	12/2004	Hall et al.	N/A	N/A
2005/0275626	12/2004	Mueller et al.	N/A	N/A
2006/0013070	12/2005	Holm et al.	N/A	N/A
2006/0022800	12/2005	Krishna et al.	N/A	N/A
2006/0061469	12/2005	Jaeger et al.	N/A	N/A
2006/0066485	12/2005	Min	N/A	N/A
2006/0101497	12/2005	Hirt et al.	N/A	N/A
2006/0192709	12/2005	Schantz et al.	N/A	N/A
2006/0208893	12/2005	Anson et al.	N/A	N/A
2006/0279459	12/2005	Akiyama et al.	N/A	N/A
2006/0290508	12/2005	Moutchkaev et al.	N/A	N/A
2007/0060384	12/2006	Dohta	N/A	N/A
2007/0073552	12/2006	Hileman	N/A	N/A
2007/0138270	12/2006	Reblin	N/A	N/A
2007/0205867	12/2006	Kennedy et al.	N/A	N/A
2007/0210920	12/2006	Panotopoulos	N/A	N/A
2007/0222560	12/2006	Posamentier	N/A	N/A
2007/0237356	12/2006	Dwinell et al.	N/A	N/A
2008/0007398	12/2007	DeRose et al.	N/A	N/A
2008/0035390	12/2007	Wurz	N/A	N/A
2008/0048913	12/2007	Macias et al.	N/A	N/A
2008/0143482	12/2007	Shoarinejad et al.	N/A	N/A
2008/0150678	12/2007	Giobbi et al.	N/A	N/A
2008/0154691	12/2007	Wellman et al.	N/A	N/A
2008/0156619	12/2007	Patel et al.	N/A	N/A
2008/0174485	12/2007	Carani et al.	N/A	N/A
2008/0183328	12/2007	Danelski	N/A	N/A
2008/0204322	12/2007	Oswald et al.	N/A	N/A
2008/0204589	12/2007	Chang	N/A	N/A
2008/0266253	12/2007	Seeman et al.	N/A	N/A
2008/0281618	12/2007	Mermet et al.	N/A	N/A
2008/0316324	12/2007	Rofougaran et al.	N/A	N/A

2009/0043504	12/2008	Bandyopadhyay et al.	N/A	N/A
2009/0073428	12/2008	Magnus et al.	N/A	N/A
2009/0114575	12/2008	Carpenter et al.	N/A	N/A
2009/0121017	12/2008	Cato et al.	N/A	N/A
2009/0149202	12/2008	Hill et al.	N/A	N/A
2009/0164277	12/2008	Bhattacharya	N/A	N/A
2009/0216394	12/2008	Heppe et al.	N/A	N/A
2009/0224040	12/2008	Kushida et al.	N/A	N/A
2009/0243932	12/2008	Moshfeghi	N/A	N/A
2009/0245573	12/2008	Saptharishi et al.	N/A	N/A
2009/0323586	12/2008	Hohl et al.	N/A	N/A
2010/0019905	12/2009	Boddie et al.	N/A	N/A
2010/0076594	12/2009	Salour et al.	N/A	N/A
2010/0090852	12/2009	Eitan et al.	N/A	N/A
2010/0097208	12/2009	Rosing et al.	N/A	N/A
2010/0103173	12/2009	Lee et al.	N/A	N/A
2010/0103989	12/2009	Smith et al.	N/A	N/A
2010/0123664	12/2009	Shin et al.	N/A	N/A
2010/0131340	12/2009	Brown et al.	N/A	N/A
2010/0159958	12/2009	Naguib et al.	N/A	N/A
2010/0213256	12/2009	Fjellstad et al.	N/A	N/A
2011/0002509	12/2010	Nobori et al.	N/A	N/A
2011/0006774	12/2010	Baiden	N/A	N/A
2011/0037573	12/2010	Choi	N/A	N/A
2011/0066086	12/2010	Aarestad et al.	N/A	N/A
2011/0143779	12/2010	Rowe et al.	N/A	N/A
2011/0166694	12/2010	Griffits et al.	N/A	N/A
2011/0187600	12/2010	Landt	N/A	N/A
2011/0208481	12/2010	Slastion	N/A	N/A
2011/0210843	12/2010	Kummetz	N/A	N/A
2011/0241942	12/2010	Hill	N/A	N/A
2011/0256882	12/2010	Markhovsky et al.	N/A	N/A
2011/0264520	12/2010	Puhakka	N/A	N/A
2011/0279828	12/2010	Matsumoto et al.	N/A	N/A
2011/0286633	12/2010	Wang et al.	N/A	N/A
2011/0313893	12/2010	Weik, III	N/A	N/A
2011/0315770	12/2010	Patel et al.	N/A	N/A
2012/0013509	12/2011	Wisherd et al.	N/A	N/A
2012/0020518	12/2011	Taguchi	N/A	N/A
2012/0030133	12/2011	Rademaker	N/A	N/A
2012/0081544	12/2011	Wee	N/A	N/A
2012/0087572	12/2011	Dedeoglu et al.	N/A	N/A
2012/0127088	12/2011	Pance et al.	N/A	N/A
2012/0176227	12/2011	Nikitin	N/A	N/A
2012/0184285	12/2011	Sampath et al.	N/A	N/A
2012/0257061	12/2011	Edwards et al.	N/A	N/A
2012/0257064	12/2011	Kim et al.	N/A	N/A
2012/0286933	12/2011	Hsiao	N/A	N/A
2012/0319822	12/2011	Hansen	N/A	N/A
2013/0010144	12/2012	Park	N/A	N/A

2013/0017812	12/2012	Foster	N/A	N/A
2013/0018582	12/2012	Miller et al.	N/A	N/A
2013/0021417	12/2012	Ota et al.	N/A	N/A
2013/0029685	12/2012	Moshfeghi	N/A	N/A
2013/0036043	12/2012	Faith	N/A	N/A
2013/0051624	12/2012	Iwasaki et al.	N/A	N/A
2013/0063567	12/2012	Burns et al.	N/A	N/A
2013/0073093	12/2012	Songkakul	N/A	N/A
2013/0094693	12/2012	Bolton	N/A	N/A
2013/0113993	12/2012	Dagit, III	N/A	N/A
2013/0117377	12/2012	Miller	N/A	N/A
2013/0166067	12/2012	Irwin et al.	N/A	N/A
2013/0182114	12/2012	Zhang et al.	N/A	N/A
2013/0191193	12/2012	Calman et al.	N/A	N/A
2013/0226655	12/2012	Shaw	N/A	N/A
2013/0281084	12/2012	Batada et al.	N/A	N/A
2013/0293684	12/2012	Becker et al.	N/A	N/A
2013/0293722	12/2012	Chen	N/A	N/A
2013/0314210	12/2012	Schoner et al.	N/A	N/A
2013/0335318	12/2012	Nagel et al.	N/A	N/A
2013/0335415	12/2012	Chang	N/A	N/A
2014/0022058	12/2013	Striemer et al.	N/A	N/A
2014/0036069	12/2013	Gehring et al.	N/A	N/A
2014/0108136	12/2013	Zhao et al.	N/A	N/A
2014/0139426	12/2013	Kryze et al.	N/A	N/A
2014/0253368	12/2013	Holder	N/A	N/A
2014/0270356	12/2013	Dearing et al.	N/A	N/A
2014/0300516	12/2013	Min et al.	N/A	N/A
2014/0317005	12/2013	Balwani	N/A	N/A
2014/0330603	12/2013	Corder et al.	N/A	N/A
2014/0357295	12/2013	Skomra et al.	N/A	N/A
2014/0361078	12/2013	Davidson	N/A	N/A
2015/0009949	12/2014	Khoryaev et al.	N/A	N/A
2015/0012396	12/2014	Puerini et al.	N/A	N/A
2015/0019391	12/2014	Kumar et al.	N/A	N/A
2015/0029339	12/2014	Kobres et al.	N/A	N/A
2015/0039458	12/2014	Reid	N/A	N/A
2015/0055821	12/2014	Fotland	N/A	N/A
2015/0059374	12/2014	Hebel	N/A	N/A
2015/0085096	12/2014	Smits	N/A	N/A
2015/0091757	12/2014	Shaw et al.	N/A	N/A
2015/0130664	12/2014	Hill et al.	N/A	N/A
2015/0133162	12/2014	Meredith et al.	N/A	N/A
2015/0134418	12/2014	Leow et al.	N/A	N/A
2015/0169916	12/2014	Hill et al.	N/A	N/A
2015/0170002	12/2014	Szegedy et al.	N/A	N/A
2015/0202770	12/2014	Patron et al.	N/A	N/A
2015/0210199	12/2014	Payne	N/A	N/A
2015/0221135	12/2014	Hill et al.	N/A	N/A
2015/0227890	12/2014	Bednarek et al.	N/A	N/A

2015/0248765	12/2014	Criminisi et al.	N/A	N/A
2015/0254906	12/2014	Berger et al.	N/A	N/A
2015/0278759	12/2014	Harris et al.	N/A	N/A
2015/0310539	12/2014	McCoy et al.	N/A	N/A
2015/0323643	12/2014	Hill et al.	N/A	N/A
2015/0341551	12/2014	Perrin et al.	N/A	N/A
2015/0362581	12/2014	Friedman et al.	N/A	N/A
2015/0371178	12/2014	Abhyanker et al.	N/A	N/A
2015/0371319	12/2014	Argue et al.	N/A	N/A
2015/0379366	12/2014	Nomura et al.	N/A	N/A
2016/0035078	12/2015	Lin et al.	N/A	N/A
2016/0063610	12/2015	Argue et al.	N/A	N/A
2016/0093184	12/2015	Locke et al.	N/A	N/A
2016/0098679	12/2015	Levy	N/A	N/A
2016/0140436	12/2015	Yin et al.	N/A	N/A
2016/0142868	12/2015	Kulkarni et al.	N/A	N/A
2016/0150196	12/2015	Horvath	N/A	N/A
2016/0156409	12/2015	Chang	N/A	N/A
2016/0178727	12/2015	Bottazzi	N/A	N/A
2016/0180283	12/2015	Ghosh et al.	N/A	N/A
2016/0180667	12/2015	Bunker et al.	N/A	N/A
2016/0189277	12/2015	Davis	N/A	N/A
2016/0195602	12/2015	Meadow	N/A	N/A
2016/0232857	12/2015	Tamaru	N/A	N/A
2016/0238692	12/2015	Hill et al.	N/A	N/A
2016/0248969	12/2015	Hurd	N/A	N/A
2016/0256100	12/2015	Jacofsky et al.	N/A	N/A
2016/0260161	12/2015	Atchley et al.	N/A	N/A
2016/0286508	12/2015	Khoryaev et al.	N/A	N/A
2016/0300187	12/2015	Kashi et al.	N/A	N/A
2016/0335593	12/2015	Clarke et al.	N/A	N/A
2016/0366561	12/2015	Min et al.	N/A	N/A
2016/0370453	12/2015	Boker et al.	N/A	N/A
2016/0371574	12/2015	Nguyen et al.	N/A	N/A
2017/0030997	12/2016	Hill et al.	N/A	N/A
2017/0031432	12/2016	Hill	N/A	N/A
2017/0066597	12/2016	Hiroi	N/A	N/A
2017/0094251	12/2016	Wolke et al.	N/A	N/A
2017/0117233	12/2016	Anayama et al.	N/A	N/A
2017/0123426	12/2016	Hill et al.	N/A	N/A
2017/0140329	12/2016	Bernhardt	N/A	B65G 1/1371
2017/0234979	12/2016	Mathews et al.	N/A	N/A
2017/0261592	12/2016	Min et al.	N/A	N/A
2017/0280281	12/2016	Pandey et al.	N/A	N/A
2017/0293885	12/2016	Grady et al.	N/A	N/A
2017/0313514	12/2016	Lert, Jr. et al.	N/A	N/A
2017/0323174	12/2016	Joshi et al.	N/A	N/A
2017/0323376	12/2016	Glaser et al.	N/A	N/A
2017/0350961	12/2016	Hill et al.	N/A	N/A

2017/0351255	12/2016	Anderson et al.	N/A	N/A
2017/0359573	12/2016	Kim et al.	N/A	N/A
2017/0372524	12/2016	Hill	N/A	N/A
2017/0374261	12/2016	Teich et al.	N/A	N/A
2018/0003962	12/2017	Urey et al.	N/A	N/A
2018/0025417	12/2017	Brathwaite et al.	N/A	N/A
2018/0033151	12/2017	Matsumoto et al.	N/A	N/A
2018/0068100	12/2017	Seo	N/A	N/A
2018/0068266	12/2017	Kirmani et al.	N/A	N/A
2018/0094936	12/2017	Jones et al.	N/A	N/A
2018/0108134	12/2017	Venable et al.	N/A	N/A
2018/0139431	12/2017	Simek et al.	N/A	N/A
2018/0157328	12/2017	Brunner	N/A	N/A
2018/0164103	12/2017	Hill	N/A	N/A
2018/0197139	12/2017	Hill	N/A	N/A
2018/0197218	12/2017	Mallesan et al.	N/A	N/A
2018/0205899	12/2017	Lieberman et al.	N/A	N/A
2018/0231649	12/2017	Min et al.	N/A	N/A
2018/0242111	12/2017	Hill	N/A	N/A
2018/0339720	12/2017	Singh	N/A	N/A
2019/0029277	12/2018	Dderdal et al.	N/A	N/A
2019/0053012	12/2018	Hill	N/A	N/A
2019/0073785	12/2018	Hafner et al.	N/A	N/A
2019/0090744	12/2018	Mahfouz	N/A	N/A
2019/0098263	12/2018	Seiger et al.	N/A	N/A
2019/0138849	12/2018	Zhang	N/A	N/A
2019/0204588	12/2018	Zhang et al.	N/A	N/A
2019/0295290	12/2018	Schena et al.	N/A	N/A
2019/0298600	12/2018	Shen et al.	N/A	N/A
2019/0394448	12/2018	Ziegler et al.	N/A	N/A
2020/0005116	12/2019	Kuo	N/A	N/A
2020/0011961	12/2019	Hill et al.	N/A	N/A
2020/0012894	12/2019	Lee	N/A	N/A
2020/0097724	12/2019	Chakravarty et al.	N/A	N/A
2022/0405704	12/2021	Kirmani et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102017205958	12/2017	DE	N/A
2001006401	12/2000	WO	N/A
2005010550	12/2004	WO	N/A
2007130529	12/2006	WO	N/A
2009007198	12/2008	WO	N/A
2018067127	12/2017	WO	N/A
2020061276	12/2019	WO	N/A

OTHER PUBLICATIONS

R. Vargheese and H. Dahir, “An IoT/IoE enabled architecture framework for precision on shelf availability: Enhancing proactive shopper experience,” 2014 IEEE International Conference on Big

Data (Big Data), Washington, DC, USA, 2014, pp. 21-26, doi: 10.1109/BigData.2014.7004418. (Year: 2014). cited by examiner

Final Office Action in U.S. Appl. No. 17/894,472 mailed on Oct. 19, 2023. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/894,472 mailed on Jan. 31, 2024. cited by applicant

Farmer, Michael E and Anil K. Jain, "Smart Automotive Airbags: Occupant Classification and Tracking" IEEE Transactions on Vehicular Technology, vol. 56, No. 1, Jan. 2007, pp. 60-80. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/894,472 mailed on Apr. 26, 2023. cited by applicant

Final Office Action in U.S. Appl. No. 15/259,474, mailed Mar. 9, 2021; 23 pages. cited by applicant

Final Office Action in U.S. Appl. No. 15/259,474 mailed on Jan. 10, 2020; 19 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/259,474, mailed on Sep. 1, 2020; 17 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/259,474 mailed on May 29, 2019; 19 pages. cited by applicant

Final Office Action in U.S. Appl. No. 15/861,414 mailed on Feb. 8, 2021. cited by applicant

Final Office Action in U.S. Appl. No. 15/861,414 mailed on Nov. 17, 2020. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/861,414 mailed on Apr. 6, 2020; 14 pages. cited by applicant

Final Office Action in U.S. Appl. No. 16/437,767 mailed on Feb. 5, 2021. cited by applicant

Non-Final Office Action in U.S. Appl. No. 16/437,767, mailed on Jul. 15, 2020; 19 pages. cited by applicant

Notice of Allowance and Fees Due in U.S. Appl. No. 16/437,767, mailed on May 14, 2021; 8 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 16/575,837, mailed on Apr. 21, 2021; 18 pages. cited by applicant

International Preliminary Report on Patentability in PCT/US2019/051874 mailed on Apr. 1, 2021. cited by applicant

International Search Report and Written Opinion in PCT/US2019/051874 mailed on Dec. 13, 2020; 9 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 16/740,679, mailed on Jan. 6, 2021; 15 pages. cited by applicant

Notice of Allowance and Fees Due in U.S. Appl. No. 16/740,679, mailed on Apr. 20, 2021; 15 pages. cited by applicant

International Search Report and Written Opinion in PCT/US2020/013280 mailed on Mar. 10, 2020; 9 pages. cited by applicant

Pourhomayoun, Mohammad and Mark Fowler, "Improving WLAN-based Indoor Mobile Positioning Using Sparsity," Conference Record of the Forty Sixth Asilomar Conference on Signals, Systems and Computers, Nov. 4-7, 2012, pp. 1393-1396, Pacific Grove, California. cited by applicant

Proakis, John G. and Masoud Salehi, "Communication Systems Engineering", Second Edition, Prentice-Hall, Inc., Upper Saddle River, New Jersey, 2002. cited by applicant

Raza, Rana Hammad "Three Dimensional Localization and Tracking for Site Safety Using Fusion of Computer Vision and RFID," 2013, Dissertation, Michigan State University. cited by applicant

Santiago Alban, "Design and Performance of a Robust GPS/INS Attitude System for Automobile Applications", Dissertation, Stanford University, Jun. 2004. cited by applicant

Schmidt & Phillips, "INS/GPS Integration Architectures", NATO RTO Lecture Series, First Presented Oct. 20-21, 2003. cited by applicant

Sun, et al., "Analysis of the Kalman Filter With Different INS Error Models for GPS/INS

Integration in Aerial Remote Sensing Applications”, Beijing, 2008, The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences vol. XXXVII, Part B5. cited by applicant

Szeliski, Richard “Image Alignment and Stitching: A Tutorial,,” Technical Report, MST-TR-2004-92, Dec. 10, 2006. cited by applicant

Vikas Numar N., “Integration of Inertial Navigation System and Global Positioning System Using Kalman Filtering”, M.Tech Dissertation, Indian Institute of Technology, Bombay, Mumbai, Jul. 2004. cited by applicant

Welch, Greg and Gary Bishop, “An Introduction to the Kalman Filter,,” Department of Computer Science, University of North Carolina at Chapel Hill, Chapel Hill, NC 27599-3175, Updated: Monday, Jul. 24, 2006. cited by applicant

Wilde, Andreas, “Extended Tracking Range Delay-Locked Loop,,” Proceedings IEEE International Conference on Communications, Jun. 1995, pp. 1051-1054. cited by applicant

Xu, Wei and Jane Mulligan “Performance Evaluation of Color Correction Approaches for Automatic Multi-view Image and Video Stitching,,” International Conference on Computer Vision and Pattern Recognition (CVPR10), San Francisco, CA, 2010. cited by applicant

Yong Yang, “Tightly Coupled MEMS INS/GPS Integration with INS Aided Receiver Tracking Loops”, Jun. 2008, UCGE Reports No. 20270. cited by applicant

Final Office Action in U.S. Appl. No. 15/259,474 mailed on Feb. 8, 2022. cited by applicant

Notice of Allowance in U.S. Appl. No. 15/259,474 mailed on Jul. 11, 2022. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/259,474 mailed on Aug. 26, 2021. cited by applicant

Final Office Action in U.S. Appl. No. 15/861,414 mailed on Mar. 16, 2022. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/861,414 mailed on Aug. 26, 2021. cited by applicant

Final Office Action in U.S. Appl. No. 16/575,837 mailed on Sep. 3, 2021. cited by applicant

International Preliminary Report on Patentability in PCT/US2020/013280 mailed on Jul. 22, 2021. cited by applicant

Shakeri, Moein and Hong Zhang, “Cooperative Targeting: Detection and Tracking of Small Objects with a Dual Camera System” Field and Service Robotics, Springer, Cham, 2015. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/371,479 mailed on Aug. 18, 2022. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/861,414 mailed on Dec. 16, 2022. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/371,479 mailed on Dec. 20, 2022. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/877,269, mailed on Oct. 6, 2023. cited by applicant

Non-Final Office Action in U.S. Appl. No. 18/184,486, mailed on Sep. 28, 2023. cited by applicant

Restriction Requirement in U.S. Appl. No. 17/472,978, mailed on Nov. 6, 2023. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/877,269 mailed on Mar. 13, 2024. cited by applicant

Final Office Action in U.S. Appl. No. 18/184,486 mailed on Mar. 22, 2024. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/472,978 mailed on Mar. 6, 2024. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/472,978 mailed on Aug. 29, 2024. cited by applicant

Non-Final Office Action in U.S. Appl. No. 18/303,809 mailed on Oct. 1, 2024. cited by applicant

Notice of Allowance in U.S. Appl. No. 15/091,180 mailed on Sep. 21, 2022. cited by applicant

Final Office Action in U.S. Appl. No. 17/962,632, mailed on Sep. 25, 2023. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/962,632 mailed on Mar. 31, 2023. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/962,632 mailed on Jan. 30, 2024. cited by applicant

Final Office Action in U.S. Appl. No. 17/104,158, mailed on Sep. 21, 2023. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/104,157 mailed on Mar. 29, 2023. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/104,158 mailed on Dec. 28, 2023. cited by applicant

Non-Final Office Action in U.S. Appl. No. 18/184,486 mailed on Nov. 1, 2024. cited by applicant

Final Office Action in U.S. Appl. No. 17/472,978 mailed on Jun. 14, 2024. cited by applicant

“ADXL202/ADXL210 Product Sheet,” Analog. com, 1999. cited by applicant

Adrian Schumacher, “Integration of a GPS aided Strapdown Inertial Navigation System for Land

Vehicles”, Master of Science Thesis, KTH Electrical Engineering, 2006. cited by applicant

Brown, Matthew and David G. Lowe “Automatic Panoramic Image Stitching using Invariant Features,” International Journal of Computer Vision, vol. 74, No. 1, pp. 59-73, 2007. cited by applicant

Debo Sun, “Ultra-Tight GPS/Reduced IMU for Land Vehicle Navigation”, Mar. 2010, UCGE Reports No. 20305. cited by applicant

Dictionary Definition for Peripheral Equipment. (2001). Hargrave's Communications Dictionary, Wiley. Hoboken, NJ: Wiley. Retrieved from https://search.credoreference.com/content/entry/hargravecomms/peripheral_equipment/0 (Year:2001). cited by applicant

Farrell & Barth, “The Global Positioning System & Inertial Navigation”, 1999, McGraw-Hill; pp. 245-252. cited by applicant

Farrell, et al., “Real-Time Differential Carrier Phase GPS-Aided INS”, Jul. 2000, IEEE Transactions on Control Systems Technology, vol. 8, No. 4. cited by applicant

Filho, et al., “Integrated GPS/INS Navigation System Based on a Gyroscope-Free IMU”, DINCON Brazilian Conference on Dynamics, Control, and Their Applications, May 22-26, 2006. cited by applicant

Goodall, Christopher L., “Improving Usability of Low-Cost INS/GPS Navigation Systems using Intelligent Techniques”, Jan. 2009, UCGE Reports No. 20276. cited by applicant

Grewal & Andrews, “Global Positioning Systems, Inertial Navigation, and Integration”, 2001, John Wiley and Sons, pp. 252-256. cited by applicant

Jennifer Denise Gautier, “GPS/INS Generalized Evaluation Tool (GIGET) for the Design and Testing of Integrated Navigation Systems”, Dissertation, Stanford University, Jun. 2003. cited by applicant

Jianchen Gao, “Development of a Precise GPS/INS/On-Board Vehicle Sensors Integrated Vehicular Positioning System”, Jun. 2007, UCGE Reports No. 20555. cited by applicant

Li, et al. “Multifrequency-Based Range Estimation of RFID Tags,” IEEE International Conference on RFID, 2009. cited by applicant

Morbella N50: 5-inch GPS Navigator User's Manual, Maka Technologies Group, May 2012. cited by applicant

International Search Report & Written Opinion in international patent application PCT/US12/64860, mailed on Feb. 28, 2013; 8 pages. cited by applicant

Hill, et al. “Package Tracking Systems and Methods” U.S. Appl. No. 15/091,180, filed Apr. 5, 2016. cited by applicant

Final Office Action in U.S. Appl. No. 15/091,180 mailed Jan. 23, 2020; 17 pages. cited by applicant

Final Office Action in U.S. Appl. No. 15/091,180, mailed Mar. 10, 2021; 24 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/091,180, mailed Jun. 27, 2019; 11 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/091,180 mailed on Oct. 1, 2020. cited by applicant

Restriction Requirement in U.S. Appl. No. 15/091,180 mailed on Mar. 19, 2019; 8 pages. cited by applicant

Corrected Notice of Allowability in U.S. Appl. No. 15/270,749 mailed on Oct. 30, 2018; 5 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 15/270,749 mailed on Apr. 4, 2018; 8 pages. cited by applicant

Notice of Allowance in U.S. Appl. No. 15/270,749 mailed on Oct. 4, 2018; 5 pages. cited by applicant

Final Office Action in U.S. Appl. No. 16/206,745 mailed on Feb. 5, 2020; 15 pages. cited by

applicant
Final Office Action in U.S. Appl. No. 16/206,745 mailed on May 22, 2019; 9 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 16/206,745 mailed on Jan. 7, 2019; 10 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 16/206,745 mailed on Oct. 18, 2019; 8 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 16/206,745 mailed on Sep. 23, 2020. cited by applicant
Notice of Allowance and Fees Due in U.S. Appl. No. 16/206,745, mailed Mar. 12, 2021; 9 pages. cited by applicant
Final Office Action in U.S. Appl. No. 15/416,366 mailed on Oct. 7, 2019; 14 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 15/416,366 mailed Apr. 6, 2020; 13 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 15/416,366 mailed on Jun. 13, 2019; 11 pages. cited by applicant
Notice of Allowance in U.S. Appl. No. 15/416,366 mailed on Aug. 19, 2020; 13 pages. cited by applicant
Piotrowski, et al. "Light-Based Guidance for Package Tracking Systems" U.S. Appl. No. 15/416,379, filed Jan. 26, 2017. cited by applicant
Final Office Action in U.S. Appl. No. 15/416,379 mailed on Jan. 27, 2020; 15 pages. cited by applicant
Final Office Action in U.S. Appl. No. 15/416,379, mailed on May 13, 2021; 18 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 15/416,379, mailed Jun. 27, 2019; 12 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 15/416,379 mailed on Oct. 2, 2020. cited by applicant
Final Office Action in U.S. Appl. No. 15/091,180 mailed on May 12, 2022. cited by applicant
Non-Final Office Action in U.S. Appl. No. 15/091,180 mailed on Sep. 1, 2021. cited by applicant
Ex Parte Quayle Action in U.S. Appl. No. 15/416,379 mailed on Oct. 5, 2021. cited by applicant
Notice of Allowance in U.S. Appl. No. 15/416,379 mailed on Mar. 30, 2022. cited by applicant
Piotrowski, et al. "Light-Based Guidance for Package Tracking Systems" U.S. Appl. No. 17/877,269, filed Jul. 29, 2022. cited by applicant
Non-Final Office Action in U.S. Appl. No. 18/662,471 mailed on Apr. 24, 2025. cited by applicant
Non-Final Office Action in U.S. Appl. No. 18/778,516 mailed on Apr. 24, 2025. cited by applicant
Final Office Action in U.S. Appl. No. 18/184,486 mailed on Apr. 21, 2025. cited by applicant
Final Office Action in U.S. Appl. No. 18/303,809 mailed on Apr. 24, 2025. cited by applicant

Primary Examiner: Tungate; Scott M

Attorney, Agent or Firm: Schmeiser, Olsen & Watts LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/894,472 filed Aug. 24, 2022, titled "System and Method of Object Tracking Using Weight Confirmation" which is a continuation of U.S. patent application Ser. No. 15/259,474, filed Sep. 8,

FIELD OF THE INVENTION

(1) The invention relates generally to systems and methods of tracking packages and other assets.

BACKGROUND

(2) The shipping of packages, including, but not limited to, letters, parcels, containers, and boxes of any shape and size, is big business, one that grows annually because of online shopping. Every day, people and businesses from diverse locations throughout the world ship millions of packages.

Efficient and precise delivery of such packages to their correct destinations entails complex logistics.

(3) Most package shippers currently use barcodes on packages to track movement of the packages through their delivery system. Each barcode stores information about its package; such information may include the dimensions of the package, its weight and destination. When shipping personnel pick up a package, he or she scans the barcode to sort the package appropriately. The delivery system uses this scanned information to track movement of the package.

(4) For example, upon arriving at the city of final destination, a package rolls off a truck or plane on a roller belt. Personnel scan the package, and the system recognizes that the package is at the city of final destination. The system assigns the package to an appropriate delivery truck with an objective of having delivery drivers operating at maximum efficiency. An employee loads the delivery truck, scanning the package while loading it onto the truck. The scanning operates to identify the package as "out for delivery". The driver of the delivery truck also scans the package upon delivery to notify the package-delivery system that the package has reached its final destination.

(5) Such a package-delivery system provides discrete data points for tracking packages, but it has its weaknesses: there can be instances where the position or even the existence of the package is unknown. For example, a package loader may scan a package for loading on delivery truck A, but the package loader may place the package erroneously on delivery truck B. In the previously described package-delivery system, there is no way to prevent or quickly discover this error.

(6) Further, package-delivery systems can be inefficient. Instructions often direct the person who is loading a delivery truck to load it for optimized delivery. This person is usually not the delivery person. Thus, his or her perception of an efficient loading strategy may differ greatly from that of the person unloading the vehicle. Further, different loaders may pack a vehicle differently.

Additionally, the loader may toss packages into the truck or misplace them. Packages may also shift during transit. Time expended by drivers searching for packages in a truck is expended cost and an inefficiency that financially impacts the shippers.

(7) Industry has made attempts to track packages efficiently. One such attempt places RFID (Radio Frequency Identification) chips on the packages. Such a solution requires additional systems and hardware. For instance, this solution requires the placement of an RFID tag on every package and the use of readers by package loaders or the placement of readers throughout the facility to track packages.

SUMMARY

(8) All examples and features mentioned below can be combined in any technically possible way.

(9) In one aspect, an object tracking system comprises a horizontal surface upon which objects are to be placed, a weight sensor disposed on one side of the horizontal surface, and a processor in communication with the weight sensor. The processor is adapted to detect a change in weight measured by the weight sensor, to associate the detected weight change with an identified object and with a location on the horizontal surface, and to confirm whether a cause of the weight change at the location on the horizontal surface corresponds to a proper handling of the identified object.

(10) In another aspect, a method of tracking an object comprises identifying an object by obtaining

identification information from a scannable medium associated with the object, detecting a change in weight measured by a weight sensor disposed on one side of a horizontal surface, associating the measured weight change with the identified object and with a location on the horizontal surface, and confirming whether a cause of the weight change at the location on the horizontal surface corresponds to a proper handling of the identified object.

(11) In still another aspect, a package tracking system comprises a plurality of shelves upon which packages are to be placed, a plurality of weight sensors coupled to the plurality of shelves to measure weight of packages placed on the plurality of shelves, and at least one processor in communication with the plurality of weight sensors. The at least one processor is adapted to detect a change in weight measured by a given weight sensor of the plurality of weight sensors, to associate the detected weight change with an identified package and with a location on a given shelf of the plurality of shelves, and to confirm whether a cause of the weight change at the location on the given shelf of the plurality of shelves corresponds to a proper handling of the identified package.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and further advantages of this invention may be better understood by referring to the following description in conjunction with the accompanying drawings, in which like numerals indicate like structural elements and features in various figures. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention.

(2) FIG. 1 is a view of an embodiment of a package tracking system.

(3) FIG. 2 is a diagram of an example implementation of the package tracking system within a delivery system.

(4) FIG. 3 is a flow diagram of an embodiment of a process for general package tracking.

(5) FIG. 4A is a diagram illustrating an example of a match between a detected package and a scanned package.

(6) FIG. 4B is a diagram illustrating an example of a mismatch between a detected package and a scanned package.

(7) FIG. 5 is a flow diagram of an embodiment of an image-processing process for identifying and matching a package.

(8) FIGS. 6A, 6B, and 6C together are a flow diagram of an embodiment of an image-processing process that uses depth information to track a package.

(9) FIG. 7 is a diagram of embodiments of a package tracking system that uses radio frequency position determinations in conjunction with optical tracking.

(10) FIG. 8 is a schematic for an embodiment of a package tracking system.

DETAILED DESCRIPTION

(11) Package tracking systems described herein actively track packages continuously.

Advantageously such systems may not require major alterations in personnel behavior and can be implemented with low hardware cost. In general, these systems employ cameras, depth sensors, or other optical sensors (herein referred to generally as cameras), and physical sensors, such as weight sensors, to track packages, objects, assets, or items (herein referred to generally as packages). The cameras are placed in or adjacent to the holding area for the packages, for example, the cargo bay of a delivery vehicle or a package room. One or more cameras can also be situated near a package conveyor or roller belt, to track the movement of packages optically before the packages are placed into a holding area. Weight sensors are disposed on surfaces (atop, below, or between) where packages are expected to be placed. A package barcode is scanned in conjunction with the package being moved into the holding area. As used herein, a barcode is any readable or scannable medium,

examples of which include, but are not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor media, or any suitable combination thereof. Package identification information about the package is determined from scanning the package barcode. Such package identification information typically includes dimensions, weight, contents, or other information that may be utilized to detect and track the package.

(12) An image processor analyzes the video stream from the cameras associated with the holding area to detect the presence of the package(s) contained within. When a package is identified, the image processor determines if the package corresponds to the package data derived from the package barcode. If the package barcode data and package image data match with a high degree of confidence, the system marks the package as existing within the camera area of coverage (e.g., within the delivery vehicle). Any user that thereafter views a stream of the camera view or a static image of the packages inside the holding area may receive an overlay that identifies the packages contained therein and their precise location.

(13) Weight sensors disposed on either or both sides of the shelves can further increase the degree of confidence that the package identified by the camera (and matched to the package barcode data) corresponds to that package just placed on the shelf. Multiple weight sensors can be organized into arrays used to determine not only the overall weight on a given shelf or section of a shelf, but also the distribution of weight on the shelf or section of the shelf. Additionally, a measured increase in weight signifies placement of the package on the shelf; the shelf location of the particular weight sensor that detects the weight increase identifies the location of the placed package. When this shelf location corresponds to the location obtained from the camera images, then the degree of confidence is increased that the identified package has been properly placed.

(14) Similarly, a weight sensor can measure a decrease in weight, signifying removal of a package from the location of this particular weight sensor on a shelf. When images obtained from the camera detect the absence of the package, the degree of confidence increases that the package previously disposed at that location is no longer present because the weight sensor confirms the camera images. If the package was supposed to be removed, then this confirmation signifies proper package handling. But if the package was not supposed to be removed, then the processor can raise an alarm that there has been improper package handling.

(15) Use of weight sensors to confirm the presence or absence of a package on a shelf can be particularly advantageous when the field of view of a camera is obstructed (e.g., by delivery personnel). Further, some embodiments of package tracking systems may not employ optical sensors to confirm the placement and removal of packages from the shelves, instead relying on the operation of the weight sensors to identify the locations at which packages are placed or from which packages are removed.

(16) A package tracking system can also employ one or more guidance mechanisms (e.g., audible, visual) to guide placement of a package into a holding area or to bring attention to the present location of a package (e.g., for purposes of removal).

(17) FIG. 1 shows a view of one embodiment of a package tracking system **100** deployed in a tracking area **112**. Example embodiments of the tracking area **112** include, but are not limited to, the cargo bay of a delivery truck or water-going vessel, a storage room, a package room, a closet, an open-area used for placing or safekeeping objects, and a warehouse. For illustrative purposes, the tracking area **112** includes a plurality of shelves **114-1, 114-n** (generally, shelf or shelves **114**), and on the shelves **114** are packages and/or assets **116-1, 116-n** (generally, package **116**). Disposed on one or both sides of the shelves **114** are weight sensors **126-1, 126-2, 126-3, 126-4, 126-n** (generally, weight sensor **126**). Such weight sensors **126** can be commercial off-the-shelf components. In general, the number of weight sensors **126** used and the spacing among them serve to accommodate the size of the shelves **114** and the average or anticipated sizes of the packages. The placement pattern of the weight sensors **126** on the shelves **114** depends on the resolution, range, and sensitivity of the weight sensors **126**. As few as one weight sensor **126** per shelf **114**

may suffice. As another example, multiple weight sensors **126** can be arranged on a shelf **114** in an array. One embodiment of the weight sensors **126** can measure weight change within plus or minus 50 grams (2 oz.). Each weight sensor **126** is in communication with an analog-to-digital (ADC) circuit (not shown), which is in communication with a processor (e.g., CPU **122**) by way of a wired or wireless path, or a combination thereof.

(18) Shipper systems typically identify and track packages **116** using barcodes. A barcode is placed on a package **116** when the shipper takes possession of the package. The barcode includes package identification information about the package, including the package dimensions, identification number, delivery address, shipping route and other data. The term barcode is to be broadly understood herein to include images or markings on a package that contain information or data (coded or otherwise) pertaining to the package. The barcode on the package is initially scanned into the system **100** with a scanner **124**.

(19) In general, the scanner **124** may be optical, magnetic, or electromagnetic means, depending on the type of barcode on the package. The scanner **124** may be a conventional barcode scanner or a smart phone or tablet-like device. The form factor of the scanner **124** is not limiting. Example embodiments of the scanner **124** and techniques for wirelessly tracking the scanner **124** are described in U.S. patent application Ser. No. 14/568,468, filed Dec. 12, 2014, titled "Tracking System with Mobile Reader," the entirety of which is incorporated by reference herein.

(20) The system **100** includes an optical system. In this embodiment, the optical system includes four optical sensors represented by cameras **118-1**, **118-2**, **118-3**, and **118-14** (generally, camera **118**). Each camera **118** has a field of view **120** covering a portion of the area within which the packages **116** lie (to simplify the illustration, only one field of view is shown). An appropriate number of cameras **118** can be mounted inside the tracking area **112** in such a way to provide a complete field of view, or at least a functionally sufficient field of view, of the area **112**, and, in some cases, of an area outside the area **112** (e.g., a conveyor belt moving the packages prior to loading). Before the system **100** begins to operate, each camera position is fixed to ensure the camera(s) cover the tracking area **112**. The exact position and number of cameras **118** is within the discretion of the system designer.

(21) The camera **118** may be a simple image or video capture camera in the visual range, an infrared light detection sensor, depth sensor, or other optical sensing approach. In general, this camera enables real-time package tracking when the package is within the camera's area of coverage. The area of coverage is preferably the shelves **114** and tracking area **112**. In some instances, the field of view can extend beyond the tracking area **112**, to ensure that the packages scanned outside the tracking area **112** correspond to those packages placed inside the tracking area **112**.

(22) In addition, each camera **118** is in communication with a processor **122** (CPU **122**), for example, a DSP (digital signal processor) or a general processor of greater or lesser capability than a DSP. In one embodiment, the CPU **122** is a Raspberry Pi. Although shown as a single CPU within the tracking area **112**, the processor **122** can be a processing system comprised of one or more processors inside the tracking area, outside of the tracking area, or a combination thereof. Communication between the cameras **118** and the CPU **122** is by way of a wired or wireless path or a combination thereof. The protocol for communicating images, the compression of image data (if desired), and the image quality required are within the scope of the designer.

(23) In one embodiment, the cameras **118** are video cameras running in parallel, and the cameras simultaneously provide images to the CPU **122**, which performs an image processing solution. For this approach, the images are merged into a pre-determined map or layout of the tracking area **112** and used like a panorama. (Alternatively, or additionally, the CPU **122** can merge the images into a mosaic, as described in more detail below). The camera images are synchronized to fit the map and operate as one camera with a panorama view. In this embodiment, two (or more) cameras capture two different perspectives and the CPU **122** flattens the images by removing perspective distortion

in each of them and merges the resulting image into the pre-determined map.

(24) An image stitching process usually first performs image alignment using algorithms that can discover the relationships among images with varying degrees of overlap. These algorithms are suited for applications such as video stabilization, summarization, and the creation of panoramic mosaics, which can be used in the images taken from the cameras **118** (i.e., optical sensors) in the described system.

(25) After alignment is complete, image-stitching algorithms take the estimates produced by such algorithms and blend the images in a seamless manner, while taking care of potential problems, such as blurring or ghosting caused by parallax and scene movement as well as varying image exposures inside the environment at which the cameras are placed in. Example image stitching processes are described in “Image Alignment and Stitching: A Tutorial”, by Richard Szeliski, Dec. 10, 2006, Technical Report, MSR-TR-2004-92, Microsoft Research; “Automatic Panoramic Image Stitching using Invariant Features,” by Brown and D. Lowe, International Journal of Computer Vision, 74 (1), pages 59-73, 2007; and “Performance Evaluation of Color Correction Approaches for Automatic Multiview Image and Video Stitching,” by Wei Xu and Jane Mulligan, In Intl. Conf on Computer Vision and Pattern Recognition (CVPR10), San Francisco, CA, 2010, the teachings of which are incorporated by reference herein in their entireties.

(26) In an alternative embodiment, a mosaic approach may be utilized to integrate camera images. In this embodiment, one camera **118** is used for a certain area, a second (or third or fourth) camera **118** is used for another area, and a handoff is used during the tracking, with the images from cameras **118** being run in parallel on the CPU **122**. In a mosaic, like a panorama approach, image data from the multiple cameras (or from other sensors) are merged into the map of the tracking area **112** (e.g., truck, container, plane, etc.) with each viewpoint designated for the area that is seen by the camera **118**. It will be recognized that in both embodiments, a handoff is made when objects move from one viewpoint to another or are seen by one camera and not the others. These handoffs may be made using the images running in parallel on the cameras **118**, with the package placement and movement determined by the CPU **122** using whichever camera has the best view of the package **116**.

(27) In an alternative embodiment, if the system **100** is using depth sensors, the image stitching operation can be omitted and each camera stream data is processed independently for change, object detection and recognition. Then, the result “areas of interest” are converted to individual point clouds (described further in connection with FIG. 6C) and transformed in to a single common coordinate system. The translation and rotation transformations used for this process are based on the camera sensors position and orientation in relations with each other. One camera is picked as the main sensor and all other camera data is transformed into the main coordinate system, achieving the same end result as the image stitching procedure, namely, unification of package coordinates between sensors.

(28) In one embodiment, the image processing is performed by the CPU **122**. Alternatively, if bandwidth is not a significant concern, the image data can be transferred to a central server (FIG. 2) and image processing may be performed by the central server. Those of ordinary skill in the art will recognize that any controller, CPU, graphics processor or other computing device capable of processing image data to perform the image analysis described herein may be utilized.

(29) The image processing CPU **122** creates the aforementioned map of the tracking area **112** under surveillance. Locating the shelves **114** assists the image processor **112** identification edge locations of packages **116**. Further, a priori calculation of the distance of each camera **18** from shelves **114** assists in properly calculating package dimensions. In one embodiment, a single reference dimension is needed and dimensions of a tracked asset **116** can be determined at any position in space relative to the known dimension. In case of image or video cameras only, a dimension reference has to be related to position in the tracking area **112** (i.e., the length and depth of the shelves are known, thus the dimensions of a package placed on these shelves can be determined in

relation with these shelves). In this embodiment, pixel count or vector distances of contours of these pixels can represent the package **116** and be used to help determine relevant package dimension data.

(30) It is to be understood that in some embodiments the CPU **122** does not need to have image-processing capabilities to confirm the placement of packages on a shelf. The CPU **122** can use weight measurements from one or more of the weight sensors **126** to detect a weight change and to determine whether placement or removal of a package from the shelf has caused the weight change. When a weight change is measured, the CPU **122** determines whether the weight change corresponds to a proper or improper placement or removal of a package onto or from the shelves. For example, after a package is scanned, the CPU **122** expects the next package to be placed to be the scanned package. When one of the weight sensors **126** measures an increase in weight, the CPU **122** registers the scanned package at the location of that weight sensor **126**. As another example, when the CPU **122** expects a package disposed at a particular location to be the next package removed from a shelf, the CPU **122** expects a particular weight sensor **126** disposed at that location to measure a weight decrease. If the particular weight sensor measures a weight decrease, the CPU **122** confirms that the correct package has been removed. But if, instead, a different weight sensor **126** measures a weight decrease, one not at the registered location of the package, the CPU **122** can alert a system user of the improper package handling.

(31) In addition, the CPU **122** can aggregate the weight measured by multiple weight sensors **126** arranged in an array on a given shelf **114**, to calculate an overall weight placed on that shelf. Further, the CPU **122** can determine the weight distribution on a given shelf **114** based on the individual weights measured by each weight sensor **126** in an array and on the known location of that weight sensor **126** on the shelf **114**.

(32) Empirical data have shown that environmental temperature may affect the weight measured by the weight sensors **126**. Accordingly, the CPU **122** can apply a temperature compensation factor to individual or aggregate weights measured by individual or arrays of weight sensors, to account for the temperature in the region where the shelves **114** are located. In such embodiments, temperature sensors (not shown) may be situated at various locations on or near the shelves **114**, and may provide temperature readings to the CPU **122**, automatically at regular intervals or manually on request. A simple example of a compensation factor (TC) derives from measuring the weight of an object over time, measuring the range of temperature over that period, and dividing the range in measured weight (ΔW) by the range in temperature (ΔT): $TC = \Delta W / \Delta T$. Temperature compensated weight (TCW) is a factor of the measured weight (MW) subtracted by the product of the compensation factor (TC) and the difference between the measured temperature (MT) and average temperature (ΔT): $TCW = MW - TC * (MT - AT)$. The compensation factor, TC, stabilizes weight measurements across temperature, thereby ensuring that the cause of any measured weight change is the result of the placement or removal of an object from a shelf, and not the result of a temperature change.

(33) FIG. 2 shows an example of an implementation of the package tracking system **100** (FIG. 1) within a delivery system **200**. For illustration purposes, the delivery system **200** includes multiple delivery vehicles **202-1**, **202-n** (generally, **202**) and scanners **124-1**, **124-n** (generally, **124**) used by personnel to obtain package identification information from packages. Although shown in FIG. 2 as trucks, a delivery vehicle **202** may be any form of transport, including, but not limited to, an airplane, automobile, van, sea-going vessel, train, airplane baggage cart. The delivery vehicles **202** and scanners **124** are in communication with a central server (or servers) **204** over communication connections **206**. The server **204** (or servers) can be cloud based, meaning that a provider of the server **204** makes applications, services, and resources available on demand to users over a network (e.g., the Internet). The communication connections **206** may be established using any type of communication system including, but not limited to, a cellular network, private network, local network, wired network, wireless network, or any combination thereof.

(34) The scanners **124** are in communication with the central server **204**, either continuously or through data dumps, to transfer package identification information when a barcode on a package is scanned and the location. Typically, the location of the scanner **124** is generic (e.g., “Atlanta”).

(35) Each delivery vehicle **202** includes a tracking area **112**, containing packages **116**, and a processor **122**. Each delivery vehicle **202** may have a GPS system (FIG. 7) for use in directing and tracking the vehicle **202**. The cloud-based server **204** (or a central controller, not shown) identifies the appropriate shipping route, and the next appropriate delivery vehicle, if any. The delivery vehicles **202** may also communicate data (e.g., package identification information) to the central server **204**. The transfer of data between the vehicles **202** and the central server **204**, like the scanners, can be continuous or intermittent (e.g., data dumps). Based on such communications, the central server **204** not only can track the delivery vehicles **202**, but also the progress of the packages **116** they carry through the shipping route. The central server **204** can use the package identification information to notify the driver of the next appropriate delivery vehicle, through the scanner of the driver, to expect the package.

(36) FIG. 3 shows an embodiment of a process **300** for general package tracking. For purposes of illustrating the process **300** by example, reference is made to the delivery vehicle **202-1** and other elements of FIG. 2. It is to be understood that the area in which packages are stored, and later removed, can be non-vehicular in nature, for example, a room, closet, or open area within a building. Before loading a package **116-1** onto the delivery vehicle **202-1**, a loader uses a scanner **124-1** to scan (step **302**) a barcode associated with the package **116-1**. The scanner **124** transmits (step **304**) the barcode (i.e., package identification) information to the image processing CPU **122** of the delivery vehicle **202-1** or to the central server **204**, which can then transmit the data to the CPU **122**. Transmission of this information may be by Bluetooth, WIFI or other communication protocols, wired or wireless. By receiving the barcode information (e.g., identification number, size, color) describing the package **116-1**, the image processing CPU **122** becomes notified (step **306**) of the package **116-1** and expects this package **116-1** to be subsequently loaded onto the delivery vehicle **202-1** (or placed on a shelf). A loader places (step **308**) the package **116-1** on a shelf of the vehicle **202-1**. Light-based guidance may be used to direct the loader to the particular vehicle **202-1** upon which to load the package, the particular location on the shelf where to place the package **116-1**, or both.

(37) The image processing CPU **122** detects (step **310**) the presence of the package **116-1**, as described in more detail in connection with FIG. 5. The image-processing CPU **122** then attempts to identify (step **312**) the detected package as that package expected to be loaded (i.e., from step **306**). Identifying the package **116-1** generally entails comparing certain visible characteristics of the package **116-1** to certain barcode information obtained during the scanning operation. In one embodiment, the size of the package measured using the camera(s) **118** of the delivery vehicle **202-1** is compared to the expected package dimensions as read from the barcode. In another embodiment, the image-processing CPU **122** registers the package **116-1** by virtue of the package **116-1** being the first package detected after notification (at step **306**) of the package **116-1** being scanned. In such an instance, the image-processing CPU **122** can register the package **116-1** by associating image data captured by the camera(s) with the identification number read from the barcode of the detected package **116-1**.

(38) To increase the confidence level that the package **116-1** detected by the camera(s) **118** corresponds to the package most recently scanned, the CPU **122** uses (step **312**) weight measurements from the weight sensors **126**. If a weight sensor that is disposed at the shelf location where the camera(s) **118** detected the package **116-1** measures an increase in weight, the CPU **122** has additional data confirming this shelf location as the location of the scanned and camera-detected package **116-1**, first, because the CPU **122** interprets a measured increase in weight as the placement of a package, second, the CPU **122** expects the next package placement to correspond to the last package scanned, and, third, the CPU **122** location of the weight sensor **126** increase

substantially matches the location of the package **116-1** detected by the camera(s). If a different weight sensor **126** measures a weight increase, at a location other than the location at which the camera(s) detected the package **116-1**, the CPU **122** can flag the placement of the package **116-1** as improper and alert the user as to the ambiguity between the camera detection and the weight sensor results.

(39) Others embodiments of the process **300** may not use cameras **118** to detect and confirm the placement of packages. Such embodiments can employ weight sensors **126** to detect the placement or removal of a package from a shelf. An increase in measured weight at a specific weight sensor location, accompanied by an expectation of the scanned package being the next package placed on the shelf, can be sufficient to confirm proper or improper placement of the package on a shelf. Similarly, a decrease in measured weight at a specific weight sensor location, accompanied by an expectation of the package at that location being the target for removal, can be sufficient to confirm proper or improper removal of the package from a shelf. In such embodiments, the CPU **122** does need to be, although it may be, an image-processing processor.

(40) FIG. **4A** shows an example of when such a comparison produces a match, thereby signifying a high level of confidence that the appropriate package was loaded on the delivery vehicle **202-1**. In this example, the scanned barcode data identify the package **116-1** to be loaded as having package dimensions of 10" by 20". The images captured by the camera(s) **118** on the delivery vehicle **202-1** indicate that a package with dimensions of 9.8" by 19.7" was loaded on the delivery vehicle **202-1**. The image-processing CPU **122** is configured to consider the differences between the dimensions of the captured images and the dimensions according to the barcode data to fall within acceptable criteria for declaring a match.

(41) FIG. **4B** shows an example of when a comparison does not produce a match. In this example, a 10" by 20" package is scanned, but subsequent image capture data shows that a 7.4" by 12.3" package was loaded onto the delivery vehicle **202-1**. The image processing CPU **122** can be configured to consider the differences between the dimensions to be too great to consider the detected package as a match to the scanned package.

(42) Referring back to FIG. **3**, if the data captured by the barcode scanner matches (within a predetermined threshold) the package image data captured by the camera **118**, a match occurs. The matched package is not only marked or identified in real time as being within the delivery vehicle **202-1**, but also the exact location of the package **116-1** in the vehicle may be made continuously available to the central server **204**, loader, driver or anyone else with access to the system **200**. This information, which may be referred to hereafter as package location data, can be stored on memory associated with the image processing CPU **122**. Package location data includes the dimension information detected for the matched package associated with the location of the package within the delivery vehicle **202-1**. More specifically, the image processing CPU **122** may overlay the initially created vehicle map with the package identification information in the corresponding location. If communications allow, marked package location data may be stored in memory at other locations, including (or additionally) in the central server **204**.

(43) As stated previously, the image-processing CPU **122** includes wireless communication (commonly Bluetooth, Wi-Fi, or other communication methods and protocols suitable for the size of the area of coverage of the camera). The image processing CPU **122** continuously receives (step **314**) real-time views captured by the cameras **118** in the delivery vehicle **202-1** and measurements from the weight sensors **126**. Because the location of the matched package is stored in memory of the image processing CPU, the real-time image data from the camera **118** is streamed to a handheld or fixed or mounted view screen to show the live view of the package overlaid with augmented reality markings identifying the package. The image-processing CPU **122** continuously monitors and tracks (step **314**) within the vehicle **202-1** until motion of an object is detected (step **316**). Such motion may be detected by the camera(s) **118** or by a measured decrease in weight by one or more of the weight sensors **126**. In response to the detection of motion, the process **300** returns to

detecting packages at step **310**.

(44) Implications of such real-time tracking can be appreciated by the following illustration. A driver entering the delivery vehicle **202-1** may not and need not have any personal knowledge of what packages were loaded where in the vehicle. Instead, the driver carries a view screen (often in the form of a handheld tablet, smartphone, or scanner) that displays a stream of one of the cameras **118** in the cargo bay of the vehicle **202-1**. The image appearing on the view screen includes marks identifying various packages. A mark may be a box around the live view of the package with text stating the package name, identifier, intended addressee or most efficient package identifier. Upon arriving at a stop for an intended package addressee, for example Mr. Jones, the driver can walk to the back of the delivery vehicle. The system **200** may automatically display the package(s) intended for delivery to Mr. Jones using highlighting or demarcating for easy location.

Alternatively, the driver can search the image data on the view screen for markings labeled “Jones” and such packages are demarcated on the view screen for easy location. In addition, the system **200** may employ light-based guidance to show the driver the location of the package.

(45) In some embodiments, multiple live streams of the cargo in a vehicle are available, with one camera (e.g., **118-1** of FIG. **1**) covering one area of the cargo bay and another camera (e.g., **118-2** of FIG. **2**) covering another area of the cargo bay. The system **200** can thus quickly and effectively permit a loader or delivery person who enters the cargo area to locate a package using the camera stream overlaid with package marking (location). For a person using a tablet viewing the cargo area, the “video stream” in one embodiment can be a static image of the delivery vehicle sent from the image-processing CPU **122**. Since the central map of the delivery vehicle can be used for positioning the packages, that central map, with the location of each package of interest, is what is used for viewing on a device.

(46) FIG. **5** shows an embodiment of an image-processing process **500** for identifying and matching a package. In a description of the process **500**, reference is made to elements of FIG. **1**. At step **502**, color data (e.g., RGB) for at least two image frames (N and $N-1$) are acquired from a camera **118**. The color data is converted (step **504**) to grey scale data for the at least two image frames. Those of ordinary skill in the art are familiar with producing grey scale data from color image sensors.

(47) At step **506**, an absolute difference is determined across the two images to detect the presence of new objects. To quicken the processing, threshold detection (step **508**) may be utilized to detect regions of interest. In addition, in those regions of interest data may be filtered (step **510**) to limit the amount of data processed. After filtering, threshold detection (step **512**) may be utilized on the filtered data.

(48) At step **514**, if no changes between the grayscale images are found, this indicates a high probability of no new package being located; the system **100** does not identify or mark a package. For instance, the loader may not have moved or loaded a package, or a new package cannot be located. The system **100** then acquires (step **502**) the next temporal two frames (N and $N+1$). Sampling frequency may be continuous or at regular intervals according to designer preference, available processing power, and bandwidth.

(49) If a change in the images (N and $N-1$) is detected at step **514**, further analysis occurs. For example, the change detected by the system **100** may be the detection of the presence of the loader in the image. Alternatively, if changes in the images are indicative of a package moving, the image-processing CPU **122** also continues to work on the current image data (frame N and $N-1$).

(50) Those of ordinary skill in the art will recognize that a variety of images may be compared to determine loading or movement of a package. For example, an N ‘current frame’ and $N-X$ ‘previous frame’ may be tested for motion, where X is greater than 1, and if motion occurs then the $N-X$ frame (before motion occurred) may be saved as a background frame for later processing in comparison to a more recent image frame (i.e., a new N ‘current frame’). After motion is stopped, the background frame and a new N current frame are used for package location and identification.

(51) Whenever a new package is located, the package is to be identified. In one embodiment, the image-processing CPU **122** uses edge detection to determine (step **516**) the dimensions of the package. Objects that are not compatible with being a package are filtered at this point. For example, if an object size is less than the smallest possible package, the object is ignored. The system **100** can also filter other objects of a size, dimension, or location that do not correspond to a package (e.g., the loader or a clipboard or tablet carried by the loader).

(52) Various metrics may be utilized in addition to or conjunction with those described above to aid in identifying a package. For example, any object placed on a shelf (mapped as described above) may be weighted logically so as to be presumed to be the last scanned package. The package size, color (if cameras are color), contours or other distinguishing characteristics may be compared to any data captured by the barcode scanner. As previously described, when a package barcode is scanned, the system **100** expects that the next package detected will match the scanned package. Reliance on this assumption is accurate provided loaders handle packages sequentially, that is, a barcode of a package is scanned and then that package is sorted and moved appropriately. This a priori knowledge facilitates package identification.

(53) At step **518**, the package dimensions are used to match the package to the scanned barcode data, as described previously in connection with FIG. **3**. The size of a package as determined from image data is compared to the predicted package size based on barcode-scanned data to determine a package match. As previously described, weight sensors **126** can provide additional confirmation regarding the match. If the match occurs, the system **100** marks (step **520**) the loaded package as identified as described in more detail below. The system **100** provides a cue to anyone entering the cargo area of a delivery vehicle as to the location and identification of packages kept within.

(54) In addition to view screens, other package location identification methods can be used to improve the locating process. For example, as a vehicle arrives at the destination address for the delivery of a certain package, a light projector (LED, laser or other) can be used to shine focused light, or a particular color light, on the location of the package within the cargo area to show the delivery person exactly where the “matched” package is in the vehicle. The focused light can be altered to change colors, blink, flash, or shine a pattern to signal additional information to the delivery person, for example, priorities of delivery and warnings of weight, or to signify that the package of interest is behind or under another package. Information is directly overlaid on the package that to be picked up, without needing any other screen or sound interface that might consume time to read or hear and consequently prolong the delivery process.

(55) The above discussion assumes that a package that is scanned is relatively quickly matched to a package placed in the delivery vehicle. However, there may be instances where no match occurs or where a delay in matching occurs. This may occur if the package is loaded on the wrong truck, the driver scans one package but loads a different package, the driver tosses a package into the truck but not within video coverage (e.g., the package is occluded from view) or the driver's body occludes video coverage of a package.

(56) In such situations, an embodiment of the system **100** requires a deliverable (i.e., a particular outcome) after a package is scanned. For example, if no package is detected by a camera or weight sensor that matches the scanned package, the system **100** may disallow further packages from being scanned, the system **100** may mark the package as scanned but unidentified, issue a warning to the loader, notify a central server of an unidentified package, or any combination thereof. The system designer may choose how rigidly to require package identification and processing (i.e., no further scanning until the package is appropriately tracked or just marking the package as scanned but with an unconfirmed loading status).

(57) In some situations, a package may be loaded without having been scanned. This may be a loader error, where the loader places the package on the wrong truck, or may be intentional as in the case of theft. In these situations, the image processing CPU **122** still recognizes the existence of a loaded package, but there will be no “match” of the loaded package to a scanned package. Such a

package may be “marked” in image streams as “unidentified”, instead of with data identifying the package, and the system may issue a “warning” to the loader (visual/auditory or other) that an unidentified package is in the vehicle. The warnings may allow the loader (or driver) to correct the issue by scanning the package, placing the package in the camera view and producing an appropriately matched package. Alternatively, the system **100** may be constructed to disallow further scanning of packages if such errors occur, may issue warnings, may send the errors to the central server, or any combination thereof. In one example of an unidentified package being loaded into a delivery vehicle, the driver upon first entering the delivery vehicle may receive a notice that **300** packages have been loaded in the vehicle, but that one of the packages is “unidentified”. The driver's tablet can show the location of the unidentified package, and remedial action may be suggested to, or required from, the driver. Alternatively, a distinct light (i.e., red light) may be directed onto the location where the unidentified package rests.

(58) Visual detection of a package may be delayed or inhibited by occlusion of the field of view (such as the loader's body or another package). Through prediction from threshold detection from the loader position inside the vehicle cargo area and the vehicle cargo area map already stored by CPU **122**, the system **100** can compare the known map of the vehicle cargo space before the loader enters with a package with the new map of the vehicle cargo space after the loader places a package in the cargo area to determine the location of the package. Thus, even if the loader's body temporarily occludes optical tracking as the package is placed inside the cargo area, the package can be located, identified, and matched by using image frames after the loader leaves the cargo area to frames before the loader entered the cargo area. Further, the weight sensors **126** can provide alternative physical evidence confirming the placement of a package.

(59) In one embodiment, the system **100** performs the process **500** to track packages continuously after they have been scanned, loaded, and “matched”. The process **500** enables tracking of matched packages within an area of coverage after a package has been identified (“marked”). Specifically, after a package is loaded and marked in one place, the image processing CPU **122** can regularly (or continuously) perform the same (or similar) threshold detection to search for a “change” at the location of interest. This accounts for object movement during transport.

(60) In this scenario, the system **100** has identified packages within the area of coverage and no new packages have been scanned. This may represent when the driver is driving the vehicle to a destination. If the image-processing CPU **122** detects a weight change or image change at or near a package location, a tracking subroutine is invoked. The detection of a change may comprise an image absolute difference comparison between frames as previously described with respect to detailed image processing. The processor **122** analyzes the location of the package within the image at which the change occurred and determines if the package at that location still matches the data for the package captured off the barcode. If the match is identical, the system **100** may continue to label the package as corresponding to the package scanned and placed at that location.

(61) If, however, no package is detected at the location or if the package dimensions do not match the expected package dimensions with a high level of confidence, the image processor **122** searches for an “unidentified” package that matches the moved package dimensions. This search can entail detecting the package optically or by measuring a weight increase at another weight sensor. When the matching package is located, its overlay marking on the cargo system is updated to display the new package location.

(62) The above ability to identify movement of previously located packages is particularly valuable in delivery vehicles. Drivers often shift packages forward in the vehicle during the delivery day to make packages accessible. By monitoring known package locations and tracking the movement of a package to a new location, the system **100** maintains a real time map of package locations.

(63) In another embodiment, the system **100** can be configured to reduce potential human loading errors that occur from a breakdown of a sequential loading pattern of scanning a package then loading that package immediately into truck. This reduction may be achieved by, for example,

providing additional scanners over the delivery vehicle loading doors to scan bar codes automatically as packages are placed into the vehicle. Such a system can guarantee that the packages scanned are the packages loaded into the truck. After a package is scanned, it is also viewed by the optical sensors in the vehicle, weighed by a weight sensor, or both; that direct and almost simultaneous registration improves package identification.

(64) In another embodiment, the system **100** can alternatively provide continuous, real time tracking, albeit with more complicated image processing. In such a system, for example, a person (loader, driver, etc.) may be identified and the system may detect objects located in the vicinity of the hands of the person to determine if the object matches the package expected to be loaded. Further, an algorithm for identifying a package or its unique identifier (size, color, etc.) may be tailored to specific environments or hardware. The tradeoff of such a full real-time tracking system is increased system complexity.

(65) In another embodiment of the system **100**, an augmented reality (“AR”) real time video view may be presented to the loader/driver. For AR video in real time, a single perspective is shown of the vehicle cargo map with those designated packages needing to be taken being highlighted or lit. The user may view one perspective of the vehicle from the front (or back, depending on how the user is removing the packages, that is, from either the front or from the back), one perspective of the left side of the vehicle and one perspective of the right side of the vehicle associated with each camera. The image-processing CPU **122** may determine where the driver/delivery person is and provide a perspective on the tablet based on the driver position in relation to the package being delivered. As previously described, identifying the user position within the area of coverage is analogous to identifying a package.

(66) Additional package delivery data may be gathered using the present system. For example, the system **100** may track package movement in real time. Therefore, tracking package movement, especially velocity, can help prevent mistreatment of packages through packages being thrown, dropped, or placed in positions that are not secure and risk having the packages fall. By tracking packages movement in real time and determining movement velocity, impact through rough handling can be monitored and reported to improve the quality of the loading and unloading procedures and to prevent damage to the packages. In this embodiment, velocity may be determined by dividing the distance a package moves by the frame rate in which such movement occurs.

(67) FIGS. **6A**, **6B**, and **6C** together show an embodiment of an image-processing process **600** that uses optical information supplemented with depth information to track a package, product, or item. Specifically, as is familiar to one of ordinary skill in the art, a two-dimensional (2D) optical image capture device (i.e., a camera) with a single aperture is capable of capturing 2D image information on a plane (film, CCD, etc). To acquire three-dimensional (3D) information typically requires acquisition of additional data. Three-dimensional data can be acquired using multiple cameras or by combining one or more cameras with one or more depth sensors. Cameras can utilize visible light, infrared light, or other optical wavelength ranges. Depth sensors can be based on infrared, laser or other wavelength emitters that transmit light to an object, or to a portion of the object. Depth sensors typically determine the distance to the object, or to portion of the object, from the light that is reflected or backscattered from the object. Alternatively, depth sensors can utilize acoustic signals to determine distance. In one embodiment, depth sensing is integrated into the optical camera, for example, the KINECT™ K000949, although other devices can be used.

(68) Referring to FIG. **6A**, at step **602**, frames are acquired from the camera system. A camera system with depth sensing capability typically outputs video (e.g., RGB, CYMG) and depth field information. Video may optionally be encoded to a well known format, such as MPEG. At step **604**, the optical and depth information are stitched together. Open libraries such as OpenCV or OpenNI (used to capture depth images) enable the optical and depth information to be stitched together. Alternatively, a user may develop customized software for generating 3D information for

object data generated by optical images and depth sensors.

(69) At step **606**, an initial calibration is performed if a calibration has not been previously performed. A function of this initial calibration, which is performed over multiple image frames, is to determine background information both for 2D optical images and depth sensing. Any motion (e.g., people) is extracted or ignored (step **608**) during background extraction until stable background optical (RGB) and depth information can be stored (step **610**). Calibration may optionally include creation of a foreground or front-ground region. This front region limits the data set for analysis to a region near shelves where objects of interest (e.g., packages) are to be located. Calibration may be performed on start-up, at intervals, be initiated by the user, or by the system, for example, if errors are detected.

(70) After calibration is complete, the resulting spatial filter masks are used to extract the “area of interest.” In one embodiment, this area of interest corresponds to the area between the background and the foreground, so everything that is not the wall and the shelves (for background) and not the person in front of the shelves, is ignored. This ignoring of the background and foreground focuses on data within the depth threshold of the area of interest being monitored. Alternatively, the “area of interest” can include a different part of the scene, for example, the foreground in order to see where the person is in later recognition steps and can be expanded or contracted as system requirements dictate. In general, the area of interest applies to any cut-out of a scene that is to be the focus within which to perform object tracking.

(71) Multiple image frames (e.g., $N-1$ and N) are obtained (step **612**) and compared (step **614**), similarly to that performed in process **500** (FIG. 5), although the image frames in the process **600** include depth information in addition to RGB data. Image and depth information can be filtered for noise and then processed to determine if a difference between two frames exists. This can be done with edge detection, threshold and difference algorithms, or other image processing techniques. In the process **600**, information from the depth sensor is also processed to compare image frames.

(72) Referring to FIG. 6B, when no image change is found (step **618**), that is, when depth and optical data remain substantially unchanged, the process **600** continues with the next temporal images received (e.g., N and $N+1$). When a change is detected, the process **600** determines (step **620**) whether a “background” object has moved. If a background object has not moved, the process **600** continues with the next temporal images received (e.g., N and $N+1$). If a background object is determined to have moved, the system **100** does not have to consider a package for tracking, and further general tracking continues. In this instance, the system **100** may go back to the calibration step to establish a new stable background data set having 2D optical image and depth information.

(73) In one embodiment, the process **600** compares two frames of image information for change, ignoring the background/foreground masks; any actual change in the image triggers further analysis. However, it is less processing and power intensive to detect only changes in the “area of interest” between the background and foreground (if foreground masking is utilized). When the background is stable, at step **622** absolute background subtraction is performed (likewise for foreground). This step allows the resulting 3D information to be processed faster for determining areas of interest in which one or more new packages may be present. Absolute image subtraction may be formed using OpenCV library modules in one embodiment, though other alternative techniques may also be used.

(74) With the background information (and foreground if applicable) subtracted, the process **600** checks (step **624**) for changes in depth of any objects in the field of view of the camera(s) and the measurement field of the depth sensor(s). If no changes are found and no package has been scanned (step **626**), this indicates that no package has been detected and the next images are processed (step **602**). However, if a package was scanned (step **626**), but no package was detected, the process **600** can use (step **628**) historical optical and depth information (or information from an adjacent wireless tracking system) to register that the last scanned package has not been located, indicate the last known location of the package, and inform the user of the ambiguity.

(75) Referring now to FIG. 6C, if at step 624 a change in the depth of one or more objects has been detected, an area of interest around that region of change is generated (step 630). In one embodiment, an area of interest is generated using a software module from the OpenCV library, though other techniques may be employed. Typically, though not necessarily, the area of interest also includes movement information or vector information that indicates object motion.

(76) When the area of interest is determined, a “point cloud” is generated (step 632) using the optic sensor(s) extrinsic and intrinsic parameters through algorithms for “2D to 3D” data representation conversion performed on the RGB and/or depth images obtained and processed through OpenNI and OpenCV. In one embodiment, the Point Cloud Library may be used. The object shape and location information generated from the Point Cloud Library are used to identify and track a package in three dimensions using edge detection, color detection, object recognition and/or other algorithms for determining an object within the scene. If object information is in the shape of a human, for example, then the process 600 continues processing further image data and does not track the human (unless the system 100 tracks user motion). However, if the size, shape or other appearance information indicates that the object is a package, the object is recorded as such. The process 600 resolves (step 634) the identity of a plurality of scanned packages based on this information by comparing expected package size, shape and/or appearance attributes (as established by information associated with scanning a package) with measured information. The use of both optical and depth sensing information allows the system to calculate package size based on the 3D data generated from the camera images and depth sensor data. The identity, location and other information (e.g., time of placement and motion) may be stored at a central server (e.g., 204 of FIG. 2) for later analysis.

(77) When an object is detected and matches a scanned package in size and appearance, the object is registered. A variety of reasons exist for a detected object not to match a scanned package. For example, the object may be partially occluded or a different object may have been substituted. In some instances, further analysis on subsequent image frames is performed to resolve the object size and appearance. In such instances, further image processing occurs until the object is identified or marked unidentified (step 636).

(78) The aforementioned description of the process 600 is with respect to a positive change in an image scene: specifically, a new object is located. A “negative change” can also be detected in a similar fashion and occurs when a package is removed from an area of interest. In such a situation, a difference is not mistaking package occlusion as object removal. Specifically, if a person steps in front of a package, then the system detects the motion and shape of the person. After the person moves away from the front of the package, the image processor 122 detects if the identified package was removed. Note that the user typically scans a package when moving it, so taking a package from a location without scanning it may trigger a flag to the user to scan or identify the package.

(79) In many situations, a second package may be placed so as to partially occlude a first registered package. In those instances, the system 100 looks for evidence based on depth and size information that the first package is still in its original location. Such evidence can be a corner of the package remaining visible behind the second package. If the first package is fully occluded, but not scanned to indicate its removal, then the system 100 may be designed to assume the first package is sitting behind the larger second package.

(80) As previously described, the system 100 detects changes in a field of view to build a database of known packages. The database is used to locate and disregard these registered packages while looking for identifying new objects being placed into the field of view. While the registered packages are “disregarded” when looking for new packages that are being loaded, they are continually monitored to see if they have moved or been removed.

(81) The process 600 may run continuously or be triggered upon user startup, detection of motion, or other triggers. Allowing the system 100 to drop to a lower state of analysis may be desirable in

some instances to reduce bandwidth and power consumption. For example, if a delivery vehicle is being loaded, then the system **100** can run at full speed with processing of images at the maximum rate described by the camera. However, after loading is complete, the system **100** can operate at intervals (for example, by processing images once every 3 seconds) to conserve power, data storage and bandwidth while meeting the requirements of the specific application. The image-processing process **600** may be augmented with weight sensors, as previously described.

(82) Augmented Package Loading Techniques

(83) Package tracking systems described herein can track packages within conventional delivery systems wherein loaders place packages on vehicles according to their perception of proper loading protocols. This perception may vary by loader, region, delivery vehicle, or other factors. Such package tracking systems can also be configured to optimize package loading in addition to delivery. In one example, the central server **204** (FIG. 2) or image processor CPU **122** (FIG. 1) may keep a list of all packages intended for placement on a particular delivery vehicle. In this example, the package identification information for each package includes the intended addressee and package size information. The intended addressees are used to generate an order of delivery that may be used to place packages in a specific order in the delivery vehicle (e.g., packages to be delivered first are put in a position of easiest access). Package size may also be a factor affecting package loading. Heavy or large packages can be located on the floor or an appropriate (i.e., low) shelf, irrespective of the delivery order.

(84) In one embodiment, when the loader scans a package and enters the delivery vehicle with the package, the CPU **122** activates a light that shines on the location for that package. The location and matching of the package may be confirmed as previously described. A focused light may be used to identify the proper loading place for the package. The source of the light can be the same light as that used to identify a package for a driver.

(85) In the various embodiments detailed herein, the location of a package may be “marked” or indicated in a variety of manners: by projecting light on the package of interest (unidentified package, package to be delivered, etc.), by projecting light where the package is to be loaded, by marking the position of the package on a live camera feed of the cargo bay, in a representational view of the cargo bay with the package location identified, or in a projection of the marking in augmented reality glasses.

(86) As an example of light-based guidance for package loading, consider a system that employs conveyor belts to move packages inside a facility. As the packages are transported on the conveyor belt they are scanned for identification, either by optical, magnetic, or electromagnetic means. After each package is identified, the system continually monitors the position of the package as it moves from one area of the facility to the end destination for transportation vehicle loading. As packages reach areas for vehicle loading, the system uses a form of light guidance to help loaders identify proper vehicle package assignment. For example, if a package is assigned to particular truck, that truck could be assigned a particular color, say blue. The package designated for the blue truck is then illuminated with a blue light, through LED, laser, or related light guidance means, thus making package vehicle identification easy for loaders. After the loader places the package in the identified delivery truck, the package tracking system can detect its presence and register its location as previously described.

(87) One of ordinary skill in the art will recognize that other cues (visual, auditory or the like) using various technologies may be used to mark package location for easy loading, delivery or tracking of packages.

(88) Augmented Tracking

(89) Various embodiments of the package tracking systems described herein may benefit from additional tracking technology. For example, in the bigger areas (e.g., freight, air cargo, large shipping containers), one may incorporate other techniques to make tracking more interactive, such as Ultra-wideband (UWB) or Wireless Lan (including, but not limited to, 802.11 protocol

communications or the like). Example implementations of techniques for tracking can be found in U.S. patent application Ser. No. 14/614,734, filed Feb. 5, 2015, titled “Virtual Reality and Augmented Reality Functionality for Mobile Devices,” the entirety of which is hereby incorporated by reference.

(90) In a package tracking system that augments optical tracking with UWB tracking, the driver, the driver's tablet, the packages, or all of the above, are actively tracked as described in U.S. patent application Ser. No. 15/041,405, filed Feb. 11, 2016, titled “Accurate Geographic Tracking of Mobile Devices,” the entirety of which is incorporated by reference herein. In one embodiment, the position of the driver's tablet is tracked so that the viewpoint from the tablet's camera associated with the tablet location and orientation is streamed to the tablet, with digital images overlaid onto the tablet's camera view, and is used for navigation or package identification. In this example, as the tablet camera views a stack of packages, the accurate tracking of the physical position and orientation of the tablet allows the system to overlay a digital image, for example, a flashing red light, on top of the package that is seen by the tablet camera. In this case, digital images are shown on the tablet camera view, not projected onto the actual package by an external light source.

(91) Small delivery (and other delivery modes, like airfreight, cargo containers) may use of UWB or RF (radio frequency) to improve positional accuracy tracking for when and where packages are scanned. The packages may be tracked using UWB with tags on the packages until a handoff to the camera for optically tracking inside the delivery vehicle becomes possible. This is a benefit as it reduces or eliminates the need to do optical image processing in the delivery vehicle, but still provides package ID confirmation and tracking (which may then also be re-registered via dimension data inside the delivery vehicle by the cameras).

(92) In addition, cumulative tracking methods (i.e., optics and UWB) help track the driver and packages. For example, in dark environments, large environments or in situations involving other issues with optical coverage, it may be preferable to use UWB or related RF-based tracking to identify initial package location, and to switch to optical scanning after package location is generally identified. In such situations, UWB tracking may augment or supplant optical tracking.

(93) Also, in some situations, one may want to track the loader using a tag physically associated with that person. In such an environment, one may scan a package and then track the loader using UWB to make sure the package goes to the correct delivery vehicle (for instance, they may be loading multiple trucks) or, in other use cases, track the driver as the driver leaves the delivery vehicle to insure proper delivery drop off location. In the scenario where a driver is being tracked, the driver is tracked as he leaves the delivery vehicle with the GPS position known either on the delivery vehicle or on the driver. As the driver leaves the delivery vehicle, the driver is tracked and when the package is dropped off, the package is scanned and the position in relation to the delivery vehicle is recorded to show proof of delivery. As described in the aforementioned U.S. patent application Ser. No. 15/041,405, augmented reality (AR) glasses can be used to track a driver. In this scenario, the AR glasses are being tracked by a form of RF tracking, and the orientation and position of the driver may be determined by the glasses.

(94) Example implementations of UWB or other wireless tracking systems are described disclosed in U.S. patent application Ser. No. 13/975,724, filed Aug. 26, 2013, titled “Radio Frequency Communication System”, the entirety of which is incorporated by reference herein. Tracking may be implemented outside the delivery to confirm that a package that was scanned by glasses or a finger scanner is the same package that gets loaded into the delivery vehicle. In such scenarios, a loader scans the package off a conveyor belt, and the loader is tracked by the UWB system to ensure that the package scanned is the package placed in the truck or is at the proper loading area of the delivery vehicle. Thereafter, the optical tracking system tracks packages within the area of coverage.

(95) FIG. 7 shows a diagram of an embodiment of a package tracking system **700** including a tracking hub **702** augmented with a radio frequency (RF) positioning system **704**. The package

tracking system **700** includes a user device **706** and a cloud-based central server system **708**. The hub **702** is deployed in an area **710** used to hold packages, assets, objects, items, or the like, and is in communication with the cloud-based central server system **708** over a wireless communications channel (e.g., cellular) **716**. Depending on the service provider for cellular PHY communications, if the holding area (e.g., delivery truck) is outside of the service area, the hub **702** buffers the data, package identification information, transactions, etc., until the holding area comes into range of a facility with secure Wi-Fi (i.e., provided, for example, by the package delivery company). For purposes of enabling customers to push or pull data from the cloud-based central server system **708**, the hub provides a “Cloud” API (application program interface).

(96) The RF positioning system **704** includes four RF nodes **712-1**, **712-2**, **712-3**, and **712-4** (generally, **712**) and an RF tag **714**. The RF positioning system **704** operates to track the position of the RF tag **714**, which can be affixed to the package or worn by personnel, such as a driver or package loader. In general, the RF nodes **712** provide an interface over Wi-Fi to the user device **706**. The RF nodes **712** are in communication with the user device **706** via Wi-Fi, and the user device **706** is in communication with the hub **702** via Wi-Fi; in effect, the hub **702** provides an ad hoc Wi-Fi hotspot to the user device **706** and RF nodes **712**.

(97) The user device **706** is any computing device capable of running applications and wireless communications. Examples of the user device **706** include, but are not limited to, tablets and smart phones. The user device **706** can be in communication with the hub **702** over a wireless communications link **718**, with the server system **708** over a wireless communications link **720**, or both. An example implementation of the communication links **718**, **720** is Wi-Fi.

(98) The area **710** for holding assets can be stationary or mobile. A stationary holding area can be disposed anywhere along the delivery chain, from a warehouse to a package delivery center. Examples of stationary holding areas include, but are not limited to, package rooms, closets, warehouses, inventory rooms, storage rooms, and trailers. Examples of mobile holding areas include, but are not limited to, delivery trucks, tractor trailers, railway cars, shipping containers, and airplane cargo bays. Each holding area (i.e., each facility, truck, etc.) is equipped with a tracking hub **702**. An example of a delivery truck that can be equipped with a tracking hub **702** is the standard Ford® P1000.

(99) The RF tag **714** is in communication with the user device **706** over a wireless communication link **722**, for example, Bluetooth, and with the RF nodes **712** by way of RF signals **724**.

(100) During operation, in general the hub **702** provides interior tracking (e.g., inside a delivery vehicle) of a package using optical techniques and the RF positioning system **704** provides exterior tracking (e.g., outside of the delivery vehicle) of the RF tag **714** using RF signals. In one embodiment, the user device **706** directly communicates with the server system **708** (e.g., in the cloud). In another embodiment, the user device **706** provides data to the hub **702**, and the hub **702** communicates with the server system **708**. In this embodiment, any feedback information from the server system **708** goes through the hub **702**, which communicates such information to the user device **706** by Wi-Fi.

(101) FIG. **8** is a schematic for an embodiment of a package tracking system **800** including a holding area **802**, configured for optical tracking and augmented with RF tracking, in communication with a hub and power subsystem **804**. The holding area **802** includes four RF nodes **806-1**, **806-2**, **806-3**, **806-4** (generally, **806**) with antennae, three cameras (with depth sensors) **808-1**, **808-2**, **808-3** (generally, **808**), weight sensors **838-1** . . . **838-n** (generally, **838**) and an optional monitor or display device **810** (e.g., an HDMI video display, with or without a speaker) to provide a visual status of the system **800**. In one embodiment, the three cameras **808** are USB3-based. Each RF node **806**, camera **808**, weight sensor **838**, and display device **810** is connected to a power bus **812** (e.g., a 12 VDC). The holding area **802** can also include a light projector (not shown) to shine focused light, or a particular color light, on the location within the area, to show personnel where a particular package can be currently found or where a particular package being loaded should be

placed.

(102) The hub and power subsystem **804** includes an image processor **814**, a power subsystem **816** connected to a power source **818**, and an optional charger **820**. The power subsystem **816** provides power to the image processor **814** and charger **820** by the power bus **814**. In one embodiment, the power source **818** is a battery (e.g., 12 VDC, 55 aH). An accessory power source **842** is connected to the power subsystem **816**. In communication with the image processor **814** is a cellular antenna **822**, a GPS antenna **824** and a Wi-Fi antenna **826**. The image processor **814** is also in communication with the cameras **808** by communication links **828**, with the weight sensors **838** by communication links **840** (an ADC that receives the sensed weight not being shown to simplify the drawing), and with the optional display device **810** by communication link **830**. Also shown are the user device **832**, RF tag **834**, and scanner **836**. An optional light projector external to the holding area **802** (not shown) can be used to shine light on a package before the package is loaded, for purposes of guiding a loader to the location where the package is to be loaded (e.g., a particular delivery truck).

(103) In one embodiment, the image processor **814** is implemented with a bCOM6-L1400 Express Module produced by General Electric of Fairfield, CT. The interfaces of the image processor **814** include: at least three USB3 ports for connecting to the cameras **808** and a USB2 port for connecting to an optional light-projector gimbal; an HDMI port for connecting to the display device **810**; an integral GPS unit with the external GPS antenna; a cellular PHY card/interface (e.g., LTE, GSM, UMTS, CDMA or WCDMA, or WiMAX) with a cellular antenna jack (for an appropriate multiband cellular antenna operating at 800-950 MHz, 1800-1900, 1900-2000, 2100-2200 MHz bands, and can be a different physical antenna depending on the cellular PHY provider chosen for the given area) to enable a wireless connection to a cellular data service provider; and a Wi-Fi module with a Wi-Fi antenna jack (the antenna is omni-directional, providing 500 m of range, and operating over the 2400-2480 MHz range).

(104) The holding area **802** can be stationary or mobile. For a mobile holding area **802**, such as a delivery truck, the RF nodes **806** can be mounted externally on the roof of the cargo area at the four corners, with the cameras **808** and display device **810** mounted internally within the holding area **802**. All of the cameras **808** are mounted near the ceiling of the truck box, facing towards the back of the truck, one camera at each front corner of the truck box, with the third camera at the front of the truck box disposed between the other two cameras. The cellular antenna **822** and Wi-Fi antenna **826** are mounted inside the truck and the GPS antenna **824** is mounted on the roof. In addition, a standard small form factor 2-axis gimbal can be mounted to the ceiling or rafter of the truck box. The gimbal provides azimuth (180 degree) and elevation angle (90 degree) positioning of the optional interior light projector (e.g., a laser pointer), which can be turned on and off. A USB2 interface of the image processor to a light projector sets the azimuth, elevation, and on/off state of the light.

(105) The hub and power subsystem **804** can be placed within the cab of the truck, for example, behind the driver's seat. The system **800** is not attached directly to the vehicle DC power terminals, or directly to the battery of the vehicle, to avoid draining the battery of the delivery vehicle. Power subsystem **818** can connect to the accessory power **842** of the vehicle on a fuse. When the delivery vehicle is parked and off, the accessory power **842** is turned off, and the system **800** runs on the internal battery **818**. The battery **818** thus ensures that when the delivery vehicle is off (such as during package loading) the various components of the system **800** remain powered. When the vehicle is idling or in motion, the system **800** charges the battery **818**. The power subsystem **818** also provides 12 VDC and 5 VDC dedicated for the RF Nodes **806** and the cameras **808**.

(106) For a stationary holding area **802**, the RF nodes **806** can be mounted externally near an entrance to the area **802**, with the cameras **808** and display device **810** installed inside. The hub and power subsystem **804** can also be installed inside or outside of the holding area **802**. For a stationary holding area **802**, the cellular antenna **822** and GPS antenna **824** are optional.

(107) A schematic diagram, as shown in FIG. 8, without the RF nodes 806 and RF tag 834, can illustrate an embodiment of a package tracking system that is not augmented with RF tracking.

(108) As will be appreciated by one skilled in the art, aspects of the systems described herein may be embodied as a system, method, and computer program product. Thus, aspects of the systems described herein may be embodied in entirely hardware, in entirely software (including, but not limited to, firmware, program code, resident software, microcode), or in a combination of hardware and software. All such embodiments may generally be referred to herein as a circuit, a module, or a system. In addition, aspects of the systems described herein may be in the form of a computer program product embodied in one or more computer readable media having computer readable program code embodied thereon.

(109) Any combination of one or more computer readable medium(s) may be utilized. The computer readable medium may be a computer readable signal medium or a computer readable storage medium. The computer readable medium may be a non-transitory computer readable storage medium, examples of which include, but are not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device, or any suitable combination thereof.

(110) As used herein, a computer readable storage medium may be any tangible medium that can contain or store a program for use by or in connection with an instruction execution system, apparatus, device, computer, computing system, computer system, or any programmable machine or device that inputs, processes, and outputs instructions, commands, or data. A non-exhaustive list of specific examples of a computer readable storage medium include an electrical connection having one or more wires, a portable computer diskette, a floppy disk, a hard disk, a random access memory (RAM), a read-only memory (ROM), a USB flash drive, an non-volatile RAM (NVRAM or NOVRAM), an erasable programmable read-only memory (EPROM or Flash memory), a flash memory card, an electrically erasable programmable read-only memory (EEPROM), an optical fiber, a portable compact disc read-only memory (CD-ROM), a DVD-ROM, an optical storage device, a magnetic storage device, or any suitable combination thereof.

(111) A computer readable signal medium may include a propagated data signal with computer readable program code embodied therein, for example, in baseband or as part of a carrier wave. Such a propagated signal may take any of a variety of forms, including, but not limited to, electromagnetic, optical, or any suitable combination thereof. A computer readable signal medium may be any computer readable medium that is not a computer readable storage medium and that can communicate, propagate, or transport a program for use by or in connection with an instruction execution system, apparatus, or device. As used herein, a computer readable storage medium is not a computer readable propagating signal medium or a propagated signal.

(112) Program P code may be embodied as computer-readable instructions stored on or in a computer readable storage medium as, for example, source code, object code, interpretive code, executable code, or combinations thereof. Any standard or proprietary, programming or interpretive language can be used to produce the computer-executable instructions. Examples of such languages include C, C++, Pascal, JAVA, BASIC, Smalltalk, Visual Basic, and Visual C++.

(113) Transmission of program code embodied on a computer readable medium can occur using any appropriate medium including, but not limited to, wireless, wired, optical fiber cable, radio frequency (RF), or any suitable combination thereof.

(114) The program code may execute entirely on a user's device, partly on the user's device, as a stand-alone software package, partly on the user's device and partly on a remote computer or entirely on a remote computer or server. Any such remote computer may be connected to the user's device through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider).

(115) Additionally, the methods described herein can be implemented on a special purpose

computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, a hard-wired electronic or logic circuit such as discrete element circuit, a programmable logic device such as PLD, PLA, FPGA, PAL, or the like. In general, any device capable of implementing a state machine that is in turn capable of implementing the proposed methods herein can be used to implement the principles described herein.

(116) Furthermore, the disclosed methods may be readily implemented in software using object or object-oriented software development environments that provide portable source code that can be used on a variety of computer or workstation platforms. Alternatively, the disclosed system may be implemented partially or fully in hardware using standard logic circuits or a VLSI design. Whether software or hardware is used to implement the systems in accordance with the principles described herein is dependent on the speed and/or efficiency requirements of the system, the particular function, and the particular software or hardware systems or microprocessor or microcomputer systems being utilized. The methods illustrated herein however can be readily implemented in hardware and/or software using any known or later developed systems or structures, devices and/or software by those of ordinary skill in the applicable art from the functional description provided herein and with a general basic knowledge of the computer and image processing arts.

(117) Moreover, the disclosed methods may be readily implemented in software executed on programmed general-purpose computer, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of the principles described herein may be implemented as program embedded on personal computer such as JAVA® or CGI script, as a resource residing on a server or graphics workstation, as a plug-in, or the like. The system may also be implemented by physically incorporating the system and method into a software and/or hardware system.

(118) While the aforementioned principles have been described in conjunction with a number of embodiments, it is evident that many alternatives, modifications, and variations would be or are apparent to those of ordinary skill in the applicable arts. References to “one embodiment” or “an embodiment” or “another embodiment” means that a particular, feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment described herein. A reference to a particular embodiment within the specification do not necessarily all refer to the same embodiment. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Accordingly, it is intended to embrace all such alternatives, modifications, equivalents, and variations that are within the spirit and scope of the principles described herein.

Claims

1. A tracking system comprising: an electromagnetic means configured to acquire identification information associated with an object of interest; a weight sensor at a location configured to measure a weight of the object at the location; a camera that captures images of the location; and at least one processor in communication with the electromagnetic means and the weight sensor, the at least one processor configured to: receive from the electromagnetic means the identification information associated with the object; determine, based on the weight measured by the weight sensor after the electromagnetic means acquires the identification information associated with the given object, an occurrence of a weight change at the location; expect a next object to be placed at the location where the weight sensor can measure the weight of the next object or removed from the location to be the object to which the identification information is associated; register the object as being at the location if the next object expected to be placed at the location is the object and if the weight sensor determines an increase in weight at the location in response to the electromagnetic means acquiring the identification information associated with the object; and compare a change in the captured images with the increase or decrease in weight at the location;

confirm, in response to the comparison, that an activity involving a placement of the object on or removal of the object from the location has appeared next in the captured images, and has occurred at the location where the increase or decrease in weight occurs; and confirming a proper removal of the object from the location if, in response to receiving the identification information associated with the object, the next object expected to be removed from the location is the object by detecting by the weight sensor a change at the location that is a decrease in weight and the object was previously registered as being at the location.

2. The tracking system of claim 1, wherein the tracking system identifies the location as an initial location of the object, then switches to an optical scanning mode using the camera after the location is identified where the object is located.

3. The tracking system of claim 1, wherein the identification information received by the electromagnetic means includes a radio frequency (RF) tag identification corresponding to an electronic tag at the object.

4. The tracking system of claim 3, wherein the electromagnetic means includes an RFID sensor.

5. The tracking system of claim 1, wherein the electromagnetic means includes a barcode scanner.

6. The tracking system of claim 1, wherein the electromagnetic means is located inside a vehicle.

7. A tracking system comprising: an electromagnetic means configured to acquire identification information associated with an object of interest; a weight sensor at a location configured to measure a weight of the object at the location; a camera that captures images of the location; and at least one processor in communication with the electromagnetic means and the weight sensor, the at least one processor configured to: receive from the electromagnetic means the identification information associated with the object; determine, based on the weight measured by the weight sensor after the electromagnetic means acquires the identification information associated with the given object, an occurrence of a weight change at the location; expect a next object to be placed at the location where the weight sensor can measure the weight of the next object or removed from the location to appear next in the captured images and be the given object to which the identification information is associated; register the object as being at the location if the weight sensor determines an increase in weight at the location in response to the electromagnetic means acquiring the identification information associated with the object; and compare a change in the captured images with the increase or decrease in weight at the location in response to expecting the next object to be placed at the location with the weight sensor and associating the change in the captured images with the placement of the next object at the location; and confirm, in response to the comparison, that an activity involving a placement of the object on or removal of the object from the location has appeared next in the captured images, and has occurred at the location where the increase or decrease in weight occurs; and confirming a proper removal of the object from the location if the weight sensor determines a decrease in weight and the object was previously registered as being at the location.

8. The tracking system of claim 7, wherein the tracking system identifies the location as an initial location of the object, then switches to an optical scanning mode using the camera after the location is identified where the object is located.

9. The tracking system of claim 7, wherein the identification information received by the electromagnetic means includes a radio frequency (RF) tag identification corresponding to an electronic tag at the object.

10. The tracking system of claim 9, wherein the electromagnetic means includes an RFID sensor.

11. The tracking system of claim 7, wherein the electromagnetic means includes a barcode scanner.

12. The tracking system of claim 7, wherein the electromagnetic means is located inside a vehicle.
