

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392330
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Irvin, Sr.; Whitaker B.

Waveform disks and a system using the waveform disks

Abstract

A disk-pack turbine for use, for example, in systems and methods in at least one embodiment for separating fluids including liquids and gases into subcomponents by passing the fluid through a vortex chamber into an expansion chamber and then through at least a portion of a waveform pattern present between at least two rotors and/or disks. The rotors and/or disks having waveform patterns on at least one side. In at least one embodiment, the waveform patterns include a plurality of hyperbolic waveforms travelling around an axial center of the disk with each hyperbolic waveform having a varying diameter along the waveform.

Inventors:	Irvin, Sr.; Whitaker B. (Kamas, UT)
Applicant:	QWTIP, LLC (Park City, UT)
Family ID:	1000008767902
Assignee:	QWTIP LLC (Park City, UT)
Appl. No.:	17/750578
Filed:	May 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220275791 A1	Sep. 01, 2022

Related U.S. Application Data

continuation parent-doc US 13213452 20110819 US 9605663 20170328 child-doc US 15469547
division parent-doc US 15469547 20170326 US 11339767 20170524 child-doc US 17750578
us-provisional-application US 61376438 20100824

Publication Classification

Int. Cl.: **B01F27/1152** (20220101); **B01D35/06** (20060101); **B01D45/12** (20060101); **B01D45/14** (20060101); **B01D47/16** (20060101); **B01D53/24** (20060101); **B01F27/93** (20220101); **B03C3/00** (20060101); **B04B1/04** (20060101); **B04B5/08** (20060101); **B04B5/12** (20060101); **F03G7/10** (20060101); **F04D5/00** (20060101); B03C3/017 (20060101); B04B9/06 (20060101); F04D17/16 (20060101)

U.S. Cl.:

CPC **F03G7/119** (20210801); **B01D35/06** (20130101); **B01D45/12** (20130101); **B01D45/14** (20130101); **B01D47/16** (20130101); **B01D53/24** (20130101); **B01F27/1152** (20220101); **B01F27/93** (20220101); **B03C3/00** (20130101); **B04B1/04** (20130101); **B04B5/08** (20130101); **B04B5/12** (20130101); **F04D5/00** (20130101); **F04D5/001** (20130101); B01D2259/814 (20130101); B03C3/017 (20130101); B03C2201/00 (20130101); B03C2201/16 (20130101); B03C2201/22 (20130101); B04B2005/125 (20130101); B04B9/06 (20130101); F04D17/161 (20130101)

Field of Classification Search

CPC: B01F (7/0075); B01F (7/008); B01F (7/00808); B01F (7/00816); B01F (7/00833); B01F (7/00358); B01F (2215/0431); B01F (7/00775); B01F (7/00791); B01F (7/00758); B01F (7/00766); B01F (7/0085); B01F (7/00858); B01F (7/00866); B01F (7/00875); B01F (7/00633); B01F (2215/0036); B01F (2215/0427); B01F (2215/0459); B01F (2215/0481); B01F (25/4331); B01F (25/64); B01F (27/93); B01F (27/115); B01F (27/1155); C02F (1/34); C02F (2201/003); C02F (1/04); C02F (2103/08); A23C (3/00); A23L (3/0155); B01D (11/0226); B01D (11/0257); B01D (2011/002); B01D (3/08); B01D (35/06); B01D (45/12); B01D (45/14); B01D (47/16); B01D (53/24); B01D (2259/814); B01D (53/02); B01D (17/02); B01D (53/96); B01J (19/0066); B01J (19/008); B01J (19/1806); B01J (2219/00765); B01J (2219/00779); B01J (8/0045); B01J (8/10); B01J (19/1818); A23V (2002/00); Y02A (20/144); F03G (7/119); F03G (7/135); B03C (3/00); B03C (3/017); B03C (2201/00); B03C (2201/16); B03C (2201/22); B04B (1/04); B04B (5/08); B04B (5/12); B04B (9/06); B04B (2005/125); F04D (5/00); F04D (5/001); F04D (17/161)

USPC: 366/286; 366/302; 366/304; 366/305; 366/306; 366/315-317

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
146324	12/1873	Denmead	N/A	N/A
699636	12/1901	Thrupp	N/A	N/A
1061142	12/1912	Tesla	N/A	N/A
1061206	12/1912	Tesla	N/A	N/A
1374446	12/1920	Greenawalt	N/A	N/A
1383937	12/1920	Guthrie	415/76	F01D 1/36
1489786	12/1923	Povey	366/296	B01F 27/40
1820977	12/1930	Imhoff	N/A	N/A
2087834	12/1936	Brown et al.	N/A	N/A

2173580	12/1938	Fawcett	N/A	N/A
2321599	12/1942	Hofmann	241/257.1	B01F 27/271
2514039	12/1949	Downward	N/A	N/A
2569567	12/1950	Korn	N/A	N/A
2601519	12/1951	Hardy et al.	N/A	N/A
2657802	12/1952	Reed	N/A	N/A
2752090	12/1955	Kyselka	N/A	N/A
3009685	12/1960	Rettig	165/92	B29C 48/76
3253300	12/1965	Gove	366/144	B29C 48/47
3487784	12/1969	Rafferty et al.	N/A	N/A
3498454	12/1969	Timson	N/A	N/A
3514074	12/1969	Self	N/A	N/A
3623977	12/1970	Reid	N/A	N/A
3632221	12/1971	Uehling	N/A	N/A
3664268	12/1971	Lucas et al.	N/A	N/A
3731800	12/1972	Timson	N/A	N/A
4042351	12/1976	Anderson	N/A	N/A
4118207	12/1977	Wilhelm	N/A	N/A
4172034	12/1978	Carlsson	N/A	N/A
4186554	12/1979	Possell	N/A	N/A
4201512	12/1979	Marynowski et al.	N/A	N/A
4350236	12/1981	Stahluth	N/A	N/A
4361490	12/1981	Saget	N/A	N/A
4371382	12/1982	Ross	N/A	N/A
4936990	12/1989	Brunsell et al.	N/A	N/A
5146853	12/1991	Suppes	N/A	N/A
5215501	12/1992	Ushikoski	N/A	N/A
5248238	12/1992	Ishida et al.	N/A	N/A
5254250	12/1992	Rolchigo et al.	N/A	N/A
5447630	12/1994	Rummler	N/A	N/A
5464536	12/1994	Rogers	N/A	N/A
5498329	12/1995	Lamminen et al.	N/A	N/A
5501803	12/1995	Walin	N/A	N/A
5534118	12/1995	McCutchen	N/A	N/A
5744004	12/1997	Ekholm et al.	N/A	N/A
5778695	12/1997	Conner	N/A	N/A
6116420	12/1999	Horton	N/A	N/A
6227795	12/2000	Schmoll, III	N/A	N/A
6328527	12/2000	Conrad et al.	N/A	N/A
6517309	12/2002	Zaher	N/A	N/A
6682077	12/2003	Letourneau	N/A	N/A
6692232	12/2003	Letourneau	N/A	N/A
6719817	12/2003	Marin	N/A	N/A
6873235	12/2004	Fiske et al.	N/A	N/A
6890443	12/2004	Adams	N/A	N/A
7074008	12/2005	Motonaka	N/A	N/A
7341424	12/2007	Dial	N/A	N/A
7462945	12/2007	Baarman	N/A	N/A
7489060	12/2008	Qu et al.	N/A	N/A

8623212	12/2013	Irvin, Sr. et al.	N/A	N/A
8636910	12/2013	Irvin, Sr. et al.	N/A	N/A
8851741	12/2013	Ganmor	366/172.1	B01F 23/41
9605563	12/2016	Chardonnet et al.	N/A	N/A
9605663	12/2016	Irvin, Sr.	N/A	B03C 3/00
9878636	12/2017	Irvin, Sr.	N/A	B60L 13/04
10463993	12/2018	Irvin	N/A	N/A
10464824	12/2018	Irvin	N/A	N/A
10576398	12/2019	Irvin, Sr.	N/A	N/A
10682653	12/2019	Irvin, Sr.	N/A	B04C 5/04
10790723	12/2019	Irvin, Sr.	N/A	B04B 1/04
10807478	12/2019	Irvin, Sr.	N/A	B60L 13/04
11045750	12/2020	Irvin, Sr.	N/A	N/A
11339767	12/2021	Irvin, Sr.	N/A	B01D 45/14
12145449	12/2023	Irvin, Sr.	N/A	B60L 13/04
12234812	12/2024	Irvin, Sr.	N/A	B01D 35/06
12234813	12/2024	Irvin, Sr.	N/A	B01D 47/16
12270387	12/2024	Irvin, Sr.	N/A	B04B 5/12
2002/0155203	12/2001	Jensen	N/A	N/A
2002/0195862	12/2001	Kelly et al.	N/A	N/A
2003/0106858	12/2002	Sharpe	N/A	N/A
2003/0233939	12/2002	Szepessy et al.	N/A	N/A
2004/0009063	12/2003	Polacsek	N/A	N/A
2004/0107681	12/2003	Carlsson et al.	N/A	N/A
2004/0159085	12/2003	Carlsson et al.	N/A	N/A
2005/0019154	12/2004	Dial	N/A	N/A
2005/0169743	12/2004	Hicks	N/A	N/A
2005/0180845	12/2004	Vreeke et al.	N/A	N/A
2006/0000383	12/2005	Nast	N/A	N/A
2006/0054549	12/2005	Schoendorfer	N/A	N/A
2006/0233647	12/2005	Saunders	N/A	N/A
2006/0272624	12/2005	Pettersson	N/A	N/A
2007/0089636	12/2006	Guardo, Jr.	N/A	N/A
2007/0144956	12/2006	Park et al.	N/A	N/A
2007/0249479	12/2006	Eliasson et al.	N/A	N/A
2008/0009402	12/2007	Kane	N/A	N/A
2008/0168899	12/2007	Decker	N/A	N/A
2008/0308480	12/2007	Lagerstedt et al.	N/A	N/A
2009/0078150	12/2008	Hasegawa et al.	N/A	N/A
2009/0200129	12/2008	Houle et al.	N/A	N/A
2009/0283007	12/2008	Taylor	N/A	N/A
2009/0314161	12/2008	Al-Alusi et al.	N/A	N/A
2010/0107647	12/2009	Bergen	N/A	N/A
2010/0180854	12/2009	Baumann et al.	N/A	N/A
2011/0038707	12/2010	Blackstone	N/A	N/A
2011/0266811	12/2010	Smadja	N/A	N/A
2011/0285234	12/2010	Jang	N/A	N/A

2012/0051908	12/2011	Irvin, Sr.	416/1	B01D 47/16
2012/0093906	12/2011	Ganmor	424/725	A01N 65/00
2014/0070541	12/2013	Irvin, Sr.	290/52	F04D 5/00
2014/0128240	12/2013	Eigemeir	N/A	N/A
2014/0158514	12/2013	Wang	N/A	N/A
2015/0144478	12/2014	Irvin, Sr.	N/A	N/A
2015/0151649	12/2014	Leung	N/A	N/A
2016/0185624	12/2015	Miller	210/663	C02F 1/34
2016/0257220	12/2015	Irvin, Sr.	N/A	B01D 45/14
2018/0003163	12/2017	Irvin, Sr.	N/A	F04D 5/00
2019/0039478	12/2018	Irvin, Sr.	N/A	F03G 7/00
2020/0246726	12/2019	Irvin, Sr.	N/A	N/A
2021/0001355	12/2020	Irvin, Sr.	N/A	N/A
2021/0067000	12/2020	Irvin, Sr.	N/A	F03G 7/00
2021/0101487	12/2020	Irvin, Sr.	N/A	F03G 7/00
2022/0275791	12/2021	Irvin, Sr.	N/A	B04B 5/12
2022/0282713	12/2021	Irvin, Sr.	N/A	F04D 5/00
2022/0282714	12/2021	Irvin, Sr.	N/A	B01D 45/12
2022/0282715	12/2021	Irvin, Sr.	N/A	B01D 53/24
2023/0065304	12/2022	Irvin, Sr.	N/A	B04B 1/04
2025/0065726	12/2024	Irvin, Sr.	N/A	F04D 5/001
2025/0074202	12/2024	Irvin, Sr.	N/A	F03G 7/00
2025/0074203	12/2024	Irvin, Sr.	N/A	F04D 5/001
2025/0108697	12/2024	Irvin, Sr.	N/A	F03G 7/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
196680	12/1957	AT	N/A
1453730	12/1969	DE	N/A
0101770	12/1983	EP	N/A
1896100	12/2005	EP	N/A
1770717	12/2006	EP	N/A
1063096	12/1966	GB	N/A
1187632	12/1969	GB	N/A
1262961	12/1971	GB	N/A
11028375	12/1998	JP	N/A
2009293984	12/2008	JP	N/A
96/41082	12/1995	WO	N/A
2004112938	12/2003	WO	N/A
2008054131	12/2007	WO	N/A
2009010248	12/2008	WO	N/A
2009024154	12/2008	WO	N/A
2009109020	12/2008	WO	N/A
2010/085044	12/2009	WO	N/A

OTHER PUBLICATIONS

Coats, Callum, "Living Energies," 2001, pp. 107-117, 156-192, 197-200, and 275-293. cited by applicant

Schauberger, Viktor, translated and edited by Callum Coats, "The Energy Evolution: Harnessing Free Energy from Nature," vol. 4 of the Eco-Technology Series, Mar. 2001, pp. 9-28, 62-63, 104-113, 130-142, 164-195, and 200-203. cited by applicant

Schauberger, Viktor, translated and edited by Callum Coats, "The Fertile Earth: Nature's Energies in Agriculture, Soil Fertilisation and Forestry," vol. Three of Eco-Technology Series, Mar. 2001, pp. 26-29, 39-43, 48-50, 57-68, and 72-74. cited by applicant

GuardianTrader, Genesis Vortex, http://guardiantrader.com/Genesis_Vortex.html, printed Jul. 12, 2011. cited by applicant

Natural Energy Works, "Wasserwirbler (Water Vortex Shower)", <http://www.orgonclab.org/cart/yvortex.htm>, printed Jul. 12, 2011. cited by applicant

Wikipedia, "Tesla Turbine," http://en.wikipedia.org/wiki/Tesla_turbine, printed Mar. 23, 2010. cited by applicant

Jens Fischer, "Original Martin-Wirbelwasser", <http://fischer-wirbelwasser.de/Schauberger/schauberger.html>, printed Jul. 12, 2011. cited by applicant

Wirbelwasser, "Was ist Wirbelwasser?", http://fischer-wirbelwasser.de/Wasserwirbler/Was_ist_Wirbelwasser/body_was_ist_wirbelwasser.html, printed Jul. 12, 2011. cited by applicant

Espacenet, English Abstract for JP2009293984 (A), printed Mar. 14, 2013. cited by applicant

Fractal Water, LLC, "Structured water is Fractal Water's Implosion nozzle Vortex", copyrighted 2012, printed on Dec. 28, 2012 from <http://www.fractalwater.com/vortex/>. cited by applicant

Fractal Water, LLC, "Magnetic Water Treatment with the Fractal Water Super Imploder Magnetics", copyrighted 2012, printed on Dec. 28, 2012 from <http://www.fractalwater.com/magnetics/>. cited by applicant

Fractal Water, LLC, "Fractal Water: Vortex Magnetic Systems: Physics of the Imploder Vortex Nozzle", copyrighted 2012, printed on Dec. 28, 2012 from <http://www.fractalwater.com/science/physics-of-the-imploder-vortex-nozzle/>. cited by applicant

Fractal Water, LLC, "Buy the Super Imploder from Fractal Water, Vortex Magnetic System", copyrighted 2012, printed on Dec. 28, 2012 from <http://www.fractalwater.com/products/imploder-magnetic-water/>. cited by applicant

Fractal Water, LLC, "Implosion water structured vortex", copyrighted 2012, printed on Dec. 28, 2012 from <http://www.fractalwater.com/products/tri-ploder-vortex/>. cited by applicant

Fractal Water, LLC, "Fractal Water: Vortex Magnetic Systems :: Imploder Vortex Shower Head", copyrighted 2012, printed on Dec. 28, 2012 from <http://www.fractalwater.com/products/imploder-vortex-shower-head/>. cited by applicant

WIPO PCT International Preliminary Report on Patentability, PCT/US2011/048901, issued Feb. 26, 2013. cited by applicant

United States Patent and Trademark Office, U.S. Appl. No. 13/213,452 Office Action, dated Jan. 23, 2015. cited by applicant

United States Patent and Trademark Office, U.S. Appl. No. 13/213,452 Final Office Action, dated Sep. 18, 2015. cited by applicant

United States Patent and Trademark Office, U.S. Appl. No. 13/213,452 Office Action, dated Aug. 19, 2016. cited by applicant

United States Patent and Trademark Office, U.S. Appl. No. 13/783,037 Office Action, dated Feb. 22, 2017. cited by applicant

United States Patent and Trademark Office, U.S. Appl. No. 13/783,037 Final Office Action, dated

Oct. 30, 2017. cited by applicant

United States Patent and Trademark Office, U.S. Appl. No. 13/783,037 Office Action, dated Jul. 24, 2018. cited by applicant

QWTIP LLC, U.S. Appl. No. 13/783,037 (U.S. Patent Application Publication No. 2014/0070541 A1, published Mar. 13, 2014), Amendment filed Mar. 30, 2018. cited by applicant

QWTIP LLC, U.S. Appl. No. 15/651,050 (U.S. Patent Application Publication No. 2018/0126300 A1, published May 10, 2018), Preliminary Amendment filed Nov. 9, 2018. cited by applicant

QWTIP LLC, U.S. Appl. No. 15/295,732 (U.S. Patent Application Publication No. 2017/0232454 A1, published Aug. 17, 2017), Preliminary Amendment filed Oct. 31, 2018. cited by applicant

QWTIP LLC, U.S. Appl. No. 15/331,892 (U.S. Patent Application Publication No. 2017/0291124 A1, published Oct. 12, 2017), Preliminary Amendment filed Oct. 31, 2018. cited by applicant

United States Patent and Trademark Office, U.S. Appl. No. 15/295,732 Office Action, dated Mar. 19, 2019. cited by applicant

European Patent Office, English abstract for JP2009293984 (A), printed on Mar. 14, 2013. cited by applicant

U.S. Patent and Trademark Office, Final Office Action in U.S. Pat. U.S. Appl. No. 15/295,732, filed Oct. 29, 2019, pp. 3-10. cited by applicant

U.S. Patent and Trademark Office, Amendment after Final in U.S. Appl. No. 15/295,732, filed Jan. 29, 2020, pp. 1-12. cited by applicant

U.S. Patent and Trademark Office, Notice of Allowance in U.S. Appl. No. 15/295,732, filed Feb. 10, 2020, p. 3 and Notice of References Cited (document pp. 7 and 9). cited by applicant

U.S. Patent and Trademark Office, Office Action in U.S. Appl. No. 16/672,477, filed Jan. 29, 2021, p. 7. cited by applicant

Primary Examiner: Cooley; Charles

Attorney, Agent or Firm: Cahn & Samuels, LLP

Background/Summary

(1) This application is a divisional application of U.S. patent application Ser. No. 15/469,547, filed on Mar. 26, 2017 and issued as U.S. Pat. No. 11,339,767, which is a continuation application of U.S. patent application Ser. No. 13/213,452, filed Aug. 19, 2011 and issued as U.S. Pat. No. 9,605,663, which claims the benefit of U.S. provisional Application Ser. No. 61/376,438, filed Aug. 24, 2010, which are hereby incorporated by reference.

I. FIELD OF THE INVENTION

(1) The present invention relates to a system and method for processing a fluid to dissociate fluid in one or more embodiments and for dissociating components of the fluid in one or more embodiments. More particularly, the system and method of at least one embodiment of the present invention provides rotating hyperbolic waveform structures and dynamics that may be used to controllably affect the fundamental properties of fluids and/or fields for separation of gases and/or power generation.

II. SUMMARY OF THE INVENTION

(2) In at least one embodiment, this invention provides a system including a housing having at least one feed inlet, a vortex chamber in fluid communication with the at least one feed inlet; a plurality of waveform disks in fluid communication with the vortex chamber, the plurality of waveform disks forming an axially centered expansion and distribution chamber; at least one coil array in magnetic communication with the plurality of waveform disks; at least one rotating disk rotatable

about the housing, wherein the plate includes an array of magnets; and a drive system engaging the plurality of waveform disks.

(3) In at least one embodiment, this invention provides a system including a vortex induction chamber; a housing in communication with the vortex induction chamber, wherein the housing includes an upper case having a paraboloid shape formed on at least one face, a lower case having a parabolic shape formed on at least one face, and a peripheral side wall connecting the upper case and the lower case such that a paraboloid chamber is formed; an arrangement of disks disposed within the casing, wherein at least one of the disks includes an opening in the center in fluid communication with the vortex induction chamber; and a drive system connected to the arrangement of disks.

(4) In at least one embodiment, this invention provides a system including a vortex induction chamber, a case connected to the vortex induction chamber, the case including a chamber having multiple discharge ports, a pair of rotors in rotational connection to the case, the rotors forming at least a portion of an expansion and distribution chamber, at least one waveform channel exists between the rotors, and a motor connected to the rotors; and a fluid pathway exists from the vortex induction chamber into the expansion and distribution chamber through the at least one waveform channel to the case chamber and the multiple discharge ports.

(5) In at least one embodiment, this invention provides a system including at least one feed inlet; a plurality of waveform disks in fluid communication with the at least one feed inlet, the plurality of waveform disks each having an opening passing therethrough forming an axially centered expansion chamber; at least one coil array in magnetic communication with the plurality of waveform disks; at least one magnet plate rotatable about the feed inlet, wherein the plate includes an array of magnets where one of the at least one coil array is between one of the at least one magnet plate and the plurality of waveform disks; and a drive system engaging the plurality of waveform disks.

(6) In at least one embodiment, this invention provides a system including an intake chamber; a housing connected to the intake chamber, wherein the housing includes an upper case having a paraboloid shape formed on at least one face, a lower case having a paraboloid shape formed on at least one face, and a peripheral side wall connecting the upper case and the lower case such that a chamber that is at least one of a paraboloid and toroid is formed; a disk-pack turbine disposed within the housing, the disk-pack turbine includes at least one disk having an opening in the center in fluid communication with the intake chamber; and a drive system connected to the disk-pack turbine.

(7) In at least one embodiment, this invention provides a system including a vortex induction chamber, a housing connected to the vortex induction chamber, the housing including a chamber having multiple discharge ports, a pair of rotors in rotational connection to the housing, the rotors forming at least a portion of an expansion chamber, disk mounted on each of the rotors, at least one disk chamber exists between the disks, and a motor connected to the rotors; and a fluid pathway exists from the vortex induction chamber into the expansion chamber through the at least one waveform channel to the housing chamber and the multiple discharge ports.

(8) In at least one embodiment, this invention provides a system including a housing having at least one feed inlet, a vortex chamber in fluid communication with the at least one feed inlet; a disk-pack turbine having an expansion chamber axially centered and in fluid communication with the vortex chamber, wherein the disk-pack turbine includes members having waveforms formed on at least one surface; a first coil array placed on a first side of the disk-pack turbine; a second coil array placed on a second side of the disk-pack turbine; an array of magnets in magnetic communication with the disk-pack turbine; and a drive system engaging the disk-pack turbine.

(9) In at least one embodiment, this invention provides a disk array for use in a system manipulating at least one fluid, the disk array including at least one pair of mated disks, the mated disks are substantially parallel to each other, each disk having a top surface, a bottom surface, a

waveform pattern on at least one surface of the disk facing at least one neighboring disk such that the neighboring waveform patterns substantially form between the neighboring disks in the pair of mated disks a passageway, at least one mated disk in each pair of mated disks includes at least one opening passing through its height, and a fluid pathway exists for directing fluid from the at least one opening in the disks through the at least one passageway towards the periphery of the disks; and each of the waveform patterns includes a plurality of at least one of protrusions and depressions.

(10) In at least one embodiment, this invention provides a method for generating power including driving a plurality of disks having mating waveforms, feeding a fluid into a central chamber defined by openings passing through a majority of the plurality of disks with the fluid flowing into spaces formed between the disks to cause the fluid to dissociate into separate components, and inducing current flow through a plurality of coils residing in a magnetic field created between the waveform disks and at least one magnet platform rotating through magnetic coupling with the waveform disks.

Description

III. BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present invention is described with reference to the accompanying drawings. In the drawings, like reference numbers indicate identical or functionally similar elements. The use of cross-hatching and shading within the drawings is not intended as limiting the type of materials that may be used to manufacture the invention.

(2) FIG. 1 illustrates a block diagram in accordance with present invention.

(3) FIG. 2 illustrates a top view of an embodiment according to the invention.

(4) FIG. 3 illustrates a cross-sectional view of the system illustrated in FIG. 2 taken at 3-3.

(5) FIG. 4 illustrates an exploded and partial cross-sectional view of the system illustrated in FIG. 2.

(6) FIG. 5 illustrates a partial cross-sectional view of the system illustrated in FIG. 2.

(7) FIGS. 6A and 6B illustrate side and perspective views of another embodiment according to the invention.

(8) FIGS. 7A and 7B illustrate an example disk-pack turbine according to the invention.

(9) FIGS. 8A-8C illustrate another example disk-pack turbine according to the invention.

(10) FIG. 9A illustrates a side view of another embodiment according to the invention. FIG. 9B illustrates a top view of the system illustrated in FIG. 9A. FIG. 9C illustrates a partial cross-section of an embodiment according to the invention take at 9C-9C in FIG. 9B.

(11) FIG. 10 illustrates a cross-sectional view of the embodiment taken at 10-10 in FIG. 9B.

(12) FIG. 11 illustrates a cross-sectional view of the embodiment taken at 11-11 in FIG. 9B.

(13) FIG. 12 illustrates a top view of another embodiment according to the invention.

(14) FIG. 13 illustrates a side view of the system illustrated in FIG. 12.

(15) FIG. 14 illustrates a cross-sectional view of the system illustrated in FIG. 12 taken at 14-14 in FIG. 12.

(16) FIGS. 15A-15D illustrate another example disk-pack turbine according to the invention.

(17) FIG. 16 illustrates a side view of another embodiment according to the invention.

(18) FIG. 17 illustrates a side view of another embodiment according to the invention.

(19) FIG. 18 illustrates a side view of another embodiment according to the invention.

(20) FIGS. 19A-19E illustrate another example disk-pack turbine according to the invention.

(21) FIG. 20 illustrates a perspective view of another example disk according to the invention.

(22) FIG. 21A-21D illustrate another example disk-pack turbine according to the invention.

(23) FIG. 22 illustrates another example disk-pack turbine according to the invention.

(24) Given the following enabling description of the drawings, the invention should become evident to a person of ordinary skill in the art.

IV. DETAILED DESCRIPTION OF THE DRAWINGS

(25) The present invention, in at least one embodiment, provides a highly efficient system and method for processing fluid to harness the energy contained in the fluid and the environment and/or to dissociate elements of the fluid. In order to accomplish the results provided herein, in at least one embodiment the present invention utilizes elegant, highly-specialized rotating hyperbolic waveform structures and dynamics. It is believed these rotating hyperbolic waveform structures and dynamics, in at least one embodiment, are capable of efficiently propagating at ambient temperature desired effects up to the fifth state of matter, i.e., the etheric/particle state, and help accomplish many of the functional principles of at least one embodiment of the present invention. More particularly, in at least one embodiment, the system of the present invention is capable of producing very strong field energy at ambient temperatures while using relatively minimal input energy to provide rotational movement to the waveform disks. As will be more fully developed in this disclosure, the waveform patterns on facing disk surfaces form chambers (or passageways) for fluid to travel through including towards the periphery and/or center while being exposed to a variety of pressure zones that, for example, compress, expand and/or change direction and/or rotation of the fluid particles.

(26) In this disclosure, waveforms include, but are not limited to, circular, sinusoidal, multiple axial sinusoidal, biaxial, biaxial sinucircular, a series of interconnected scallop shapes, a series of interconnected arcuate forms, hyperbolic, and/or multi-axial including combinations of these that when rotated provide progressive, disk channels with the waveforms being substantially centered about an expansion chamber. Examples of waveform patterns include at least one hyperbolic waveform, at least one biaxial waveform, at least one multiple axial sinusoidal waveform. In at least one embodiment, a substantial portion of the surface of a disk is covered by the waveform pattern. The waveforms are formed by a plurality of ridges (or protrusions or rising waveforms), grooves, and depressions (or descending waveforms) in the waveform surface including the features having different heights and/or depths compared to other features and/or along the individual features. In some embodiments, the height in the vertical axis and/or the depth measured along a radius of the disk chambers vary along a radius as illustrated, for example, in FIG. 15D. In the illustrated embodiments, each of the plurality of at least one of protrusions and depressions intersect twice with a diameter taken along the surface of the disk on which the waveform pattern is present. When a line is taken in a radial direction along a second surface of a disk having waveforms, the line intersects each ridge and each depression. In some embodiments, the waveforms are implemented as ridges that have different waveforms for each side (or face) of the ridge. In this disclosure, waveform patterns (or geometries) are a set of waveforms on one disk surface. Neighboring rotor and/or disk surfaces have matching waveform patterns that form a channel running from the expansion chamber to the periphery of the disks. In this disclosure, matching waveforms include complimentary waveforms, mirroring geometries that include cavities and other beneficial geometric features. FIGS. 3-5, 8b, 8C, 9C-11, 14, 15B-15D, and 19A-22 illustrate a variety of examples of these waveforms.

(27) In this disclosure, a bearing may take a variety of forms while minimizing the friction between components with examples of material for a bearing include, but are not limited to, ceramics, nylon, phenolics, bronze, and the like. Examples of bearings include, but are not limited to, bushings and ball bearings.

(28) In this disclosure, examples of non-conducting material for electrical isolation include, but are not limited to, non-conducting ceramics, plastics, Plexiglass, phenolics, nylon or similarly electrically inert material. In some embodiments, the non-conducting material is a coating over a component to provide the electrical isolation.

(29) In this disclosure, examples of non-magnetic (or very low magnetic) materials for use in

housings, plates, disks, rotors, and frames include, but are not limited to, aluminum, aluminum alloys, brass, brass alloys, stainless steel such as austenitic grade stainless steel, copper, beryllium-copper alloys, bismuth, bismuth alloys, magnesium alloys, silver, silver alloys, and inert plastics. Examples of non-magnetic materials for use in bearings, spacers, tubing include, but are not limited to, inert plastics, non-conductive ceramics, nylon, and phenolics.

(30) In this disclosure, examples of diamagnetic material includes, but are not limited to, aluminum, brass, stainless steel, carbon fibers, copper, magnesium, other non-ferrous material alloys some of which containing high amounts of bismuth relative to other metals.

(31) The present invention in at least one embodiment provides a novel approach to the manipulation and harnessing of energy and matter, resulting in, for example: (a) systems and methods for economical, efficient, environmentally positive separation, expansion, dissociation, combination, transformation, and/or conditioning of liquids and gases for applications such as dissociation of water for energy, elemental restructuring and rendering of pure and complex gases, and the production of highly energetic gases for direct, dynamic application; and (b) systems and methods for the production, transformation, and/or conversion of mass/matter to highly energetic electrical, magnetic, diamagnetic, paramagnetic, kinetic, polar and non-polar fluxes and fields. The present invention provides, in one or more embodiments, systems and methods that are beneficial for electrical power generation.

(32) The systems and methods of the present invention in at least one embodiment, in their most fundamental form, include an intake chamber and a disk-pack turbine having an expansion and distribution chamber (or expansion chamber) in fluid communication with the intake chamber, and disk chambers formed between the rotors and/or disks that form the expansion chamber as illustrated, for example, in FIG. 1. The intake chamber serves to draw charging media, i.e., liquids and/or gases (hereinafter “fluid” or “media” or “material”) into the system before passing the charging media into the expansion chamber. The expansion chamber is formed by two or more stacked rotatable rotors and/or disks having an opening in their center. The stacked rotatable rotors and/or disk(s) are centered axially such that one or more openings are aligned whereby the aligned openings form the expansion chamber. The expansion chamber may include a variety of shapes, ranging from a horizontal substantially cylindrical shape to varying degrees of converging and diverging structures. However, in at least one embodiment, the expansion chamber includes both a convergent structure and a divergent structure designed to first compress, and then expand the media. The disks in at least one embodiment also include one or more patterns of waveform structure which may be highly application specific. In an alternative embodiment, the system draws in fluid from the periphery in addition or in place of the intake chamber.

(33) In some embodiments, the intake chamber may be formed as a vortex induction chamber that creates a vertical vortex in the charging media, which in most embodiments is a fluid including liquid and/or gas, in order to impart desired physical characteristics on the fluid. Examples of how the charging media is provided include ambient air, pressurized supply, and metered flow. The vertical vortex acts to shape, concentrate, and accelerate the charging media into a through-flowing vortex, thereby causing a decrease in temperature of the charging media and conversion of heat into kinetic energy. These effects are realized as the charging media is first compressed, then rapidly expanded as it is drawn into the expansion chamber by the centrifugal suction/vacuum created by the dynamic rotation and progressive geometry of the disks. The vortex also assists the fluid in progressing through the system, i.e., from the vortex induction chamber, into the expansion chamber, through the disk chambers formed by the patterns and channels created by the waveforms such as hyperbolic waveforms on the disks, and out of the system. In some embodiments, there may also be a reverse flow of fluid within the system where fluid components that are dissociated flow from the disk chambers to the expansion chamber back up (i.e., flow simultaneously axially and peripherally) the vortex chamber and, in some embodiments, out the fluid intakes. Media (or material) tends toward being divided relative to mass/specific gravity, with the lighter materials

discharging up through the eye of the vortex while simultaneously discharging gases/fluids of greater mass at the periphery. While progressing through the waveform geometries, the charging media is exposed to a multiplicity of dynamic action and reactionary forces and influences such as alternating pressure zones and changing circular, vortex and multi-axial flows of fluid as the fluid progresses over the valleys and peaks and highly variable hyperbolic and/or non-hyperbolic geometries in the infinitely variable waveforms.

(34) The number and arrangement of disks can vary depending upon the particular embodiment. Systemic effects may be selectively amplified by the incorporation of geometries as well as complimentary components and features that serve to supplement and intensify desired energetic influences such as sympathetic vibratory physics (harmonic, sympathetic and/or dissonant, electrical charging, polar differentiation, specific component isolation, i.e., electrical continuity, and magnetism-generated fixed/static permanent magnetic fields, permanent dynamic magnetic fields, induced magnetic fields, etc.). Examples of the various disk arrangements include paired disks, multiple paired disks, stacked disks, pluralities of stacked disks, multi-staged disk arrays, and various combinations of these disk arrangements as illustrated, for example, in FIGS. 3, 7A, 8A-8C, 10, 11, and 19E. Further examples add one or more rotors to the disks. A disk-pack turbine is a complete assembly with rotors and/or disks being elements within the disk-pack turbine. In at least one embodiment, the bottom rotor (or disk) includes a parabolic/concave rigid feature that forms the bottom of the expansion chamber.

(35) As the highly energized charging media passes from the vortex induction chamber into the expansion chamber, the charging media is divided and drawn into channels created by the waveforms on the stacked disks. Once within the rotating waveform patterns, the media is subjected to numerous energetic influences, including sinusoidal, tortile, and reciprocating motions in conjunction with simultaneous centrifugal and centripetal dynamics. See, e.g., FIG. 5. These dynamics in at least one embodiment include a multiplicity of multi-axial high pressure centrifugal flow zones and low pressure centripetal flow zones, the majority of which are vortexual in nature.

a. Overview

(36) FIG. 1 provides a broad overview of an example of a system according to the present invention. This overview is intended to provide a basis for understanding the principles and components of the various embodiments of the present invention that will be discussed in more detail below. The system as illustrated in FIG. 1 includes an intake module 100 with an intake chamber 130 and a disk-pack module 200 having an expansion and distribution chamber (or expansion chamber) 252 and a disk-pack turbine 250. To simplify the discussion, the optional housing around the disk-pack turbine 250 is not included in FIG. 1. The expansion chamber 252 is formed by openings and the recess present in the rotors and/or disk(s) that form the disk-pack turbine 250. See, e.g., FIGS. 3 and 4. The rotatable rotors and/or disks are stacked or placed adjacent to each other such that a small space of separation remains between the adjacent members to form disk chambers. The intake chamber 130 is in fluid communication with the expansion chamber 252. A drive system 300 is connected to the disk-pack turbine 250 to provide rotational movement to the disk-pack turbine 250.

(37) The drive system 300 in at least one embodiment is connected to the disk-pack turbine 250 through a drive shaft 314 or other mechanical linkage 316 (see, e.g., FIGS. 4 and 6A) such as a belt, and in a further embodiment the drive system 300 is connected directly to the disk-pack turbine 250. In use, the drive system 300 rotates the plurality of rotors and/or disks in the disk-pack turbine 250. In at least one embodiment, the rotation of which creates a centrifugal suction or vacuum within the system that causes a charging media to be drawn into the intake chamber 130 via inlets 132 and in further embodiments the fluid is drawn in from a periphery of the disk-pack turbine 250.

(38) The intake chamber 130 concentrates (compresses) and passes the charging media into the expansion chamber 252. The expansion chamber 252 causes the compressed charging media to

quickly expand and distribute through the disk chambers **262** and over the surfaces of the disk-pack turbine members towards a periphery via the disk chambers **262** and in some embodiments back towards the expansion chamber **252**. In at least one embodiment, components of the fluid reverse course through the system, for example, lighter elements present in the fluid that are dissociated from heavier elements present in the fluid. In at least one embodiment, the system includes a capture system for one or more of the dissociated fluid elements. See, e.g., FIGS. **6A** and **6B**. The media is conditioned as it passes between the rotating disks from the center towards the periphery of the disks. In at least one embodiment, the intake chamber **130** is omitted.

b. Fluid Conditioning

(39) FIGS. **2-4** provide various views of an example embodiment of the present invention that is useful in the conditioning, separating, dissociating, and/or transforming liquids, gases and/or other matter. FIGS. **2** and **3** illustrate an embodiment of the fluid conditioning system according to the present invention. In accordance with this embodiment, the system includes a fluid intake module **100** with a vortex induction chamber (or vortex chamber) **130** and a disk-pack module **200** with a housing **220**, and a disk-pack turbine **250** with an expansion and distribution chamber (or expansion chamber) **252**. The fluid intake module **100** acts as a source of the charging medium provided to the disk-pack module **200**.

(40) Charging media enters the vortex chamber **130** via fluid inlets **132**. The fluid inlets **132** may also be sized and angled to assist in creating a vortex in the charging media within the vortex chamber **130** as illustrated, for example, in FIG. **2**. The vortex chamber **130** provides the initial stage of fluid processing. The housing **220** illustrated in FIGS. **3** and **4** is around the disk-pack turbine **250** and is an example of how to collect fluid components that exit from the periphery of the disk chambers **262**.

(41) FIGS. **3** and **4** illustrate, respectively, a cross-section view and an exploded view of the fluid conditioning system in accordance with an embodiment illustrated in FIG. **2**. The housing **220** around the disk-pack turbine **250** provides an enclosure in which the disk(s) **260** and rotors **264**, **266** are able to rotate. The following disclosure provides an example of how these modules may be constructed and assembled.

(42) The fluid intake module **100** includes a vortex chamber (or intake chamber) **130** within a housing **120** having fluid inlets **132** in fluid inlets in at least one embodiment are sized and angled to assist in creating a vortex in the charging medium within the vortex chamber **130**. The vortex chamber **130** is illustrated as including an annular mounting collar **125** having an opening **138**. The collar **125** allows the intake chamber **130** to be connected in fluid communication with the expansion chamber **252**. The fluid intake module **100** sits above the disk-pack module **200** and provides the initial stage of fluid processing. In at least one embodiment, the vortex chamber **130** is stationary in the system with flow of the charging media through it driven, at least in part, by rotation of the disk-pack turbine **250** present in the housing **220**. In another embodiment, a vortex is not created in the charging media but, instead, the vortex chamber **130** acts as a conduit for moving the charging media from its source to the expansion chamber **252**.

(43) The disk-pack module **200** includes at least one disk-pack turbine **250** that defines at least one expansion chamber **252** in fluid communication with the vortex chamber **130**. The fluid exits from the vortex chamber **130** into the expansion chamber **252**. The expansion chamber **252** as illustrated is formed by a rigid feature **2522** incorporated into a lower rotor (or lower disk) **266** in the disk-pack turbine **250** with the volumetric area defined by the center holes in the stacked disks **260** and an upper rotor **264**. In at least one embodiment, there are multiple expansion chambers within the disk-pack turbine each having a lower disk **266** with the rigid feature **2522**. See, e.g., FIGS. **9** and **10** and the next section of this disclosure.

(44) As illustrated, the disk-pack turbine **250** includes an upper rotor **264**, a middle disk **260**, and a lower rotor **266** with each member having at least one surface having a waveform pattern **261** present on it. The illustrated at least one rotatable disk(s) **260** and rotors **264**, **266** are stacked or

placed adjacent to each other such that a small space of separation remains between the adjacent disk/rotor to form disk chambers **262** through which the charging media will enter from the expansion chamber **252**. The disk chambers **262** are lined with waveforms **261** that are complementary between adjacent rotor/disk(s) as illustrated, for example, in FIGS. **8A-8C**, **15A**, and **15B**. In at least one embodiment, the waveforms include no angles along any radius extending from a start of the waveform pattern to the end of the waveform pattern. In FIG. **4**, the illustrated waveform patterns **261** are a series of concentric circles, but based on this disclosure it should be understood that the concentric circles can be replaced by other patterns discussed in this disclosure and depicted in the figures. The illustrated rotors **264**, **266** and disk(s) **260** are spaced from each other to form disk chambers **262** between them that are in fluid communication with the expansion chamber **252**. One way to space them apart is illustrated in FIGS. **3** and **4**, where impellers **270** such as ceramic spacers are used to separate them and also to interconnect them together so that they rotate together. Alternative materials besides ceramics that would work include materials that do not conduct electrical current to electrically isolate the illustrated rotors and disk from each other and the system. In further embodiments one or more of the upper rotor **264**, the middle disk **260**, and the lower rotor **266** are electrically connected. Another way they may be separated is using support pieces fixedly attached to support bolts running between the top and lower rotors **264**, **266**. The illustrated lower rotor **266** includes a parabolic/concave rigid feature **2522** that forms the bottom of the expansion chamber **252**. In an alternative embodiment, the rotors **264**, **266** and the disk(s) **260** are attached on their peripheries.

(45) The upper rotor **264** and the lower rotor **266** include shoulders **2642**, **2662** extending from their respective non-waveform surface. The upper rotor **264** includes a raised shoulder **2642** that passes through an opening **2222** in the upper case **222** of the disk-pack module **200** to establish a fluid pathway connection with the intake chamber **130**. In the illustrated embodiment, the upper rotor shoulder **2642** is ringed by a bearing **280** around it that rests on a flange **2224** of the upper case **222** and against the inside of the collar **125** of the intake chamber housing **120**. The lower rotor shoulder **2662** passes through an opening **2262** in a lower case **226** to engage the drive shaft **314**. The lower rotor shoulder **2662** is surrounded by a bearing **280** that rests against the flange **2264** of the lower case **226**. In an alternative embodiment, the upper rotor **264** and the lower rotor **266** include a nesting hole for receiving a waveform disk where the nesting hole is defined by a periphery wall with gaps for receiving a connection member of the waveform disk. See, e.g., FIG. **15D**.

(46) In at least one embodiment, the center disk **260** will begin to resonate during use as it spins around the central vertical axis of the system and fluid is passing over its surface. As the center disk **260** resonates between the upper and lower rotors **264**, **266**, the disk chambers **262** will be in constant flux, creating additional and variable zones of expansion and compression in the disk chambers **262** as the middle disk resonates between the upper and lower rotors **264**, **266**, which in at least one embodiment results in varied exotic motion. The resulting motion in at least one embodiment is a predetermined resonance, sympathy, and/or dissonance at varying stages of progression with the frequency targeted to the frequency of the molecules/atoms of the material being processed to manipulate through harmonics/dissonance of the material.

(47) In at least one embodiment, one or more of the disk-pack turbine components may be prepared/equipped with a capacity for the induction of specifically selected and/or differentiated electrical charges which may be static or pulsed at desirable frequencies from sources **320**. Examples of how electrical charges may be delivered to specific components include electrical brushes or electromechanical isolated devices, induction, etc., capable of delivering an isolated charge to specific components such as alternately charging disks within a rotor with opposite/opposing polarities. In addition to inducing electrical charges to rotating disk-pack turbine components, electrical charging can also be a useful means of affecting a polar fluid, i.e., when it is desirable to expose a subject charging medium to opposing attractive influences or, in some cases,

pre-ionization of a fluid. For example, passing in-flowing media through a charged ion chamber for pre-excitation of molecular structures prior to entry into the vortex chamber, followed by progression into the expansion and distribution chamber may enhance dissociative efficiencies.

(48) The housing **220** includes a chamber **230** in which the disk-pack turbine **250** rotates. As illustrated in FIGS. **3** and **4**, the housing chamber **230** and the outside surface of the disk-pack turbine **250** in at least one embodiment have complementary surfaces. The illustrated housing **220** includes the upper case **222**, the bottom case **226**, and a peripheral case **224**. The illustrated housing **222** also includes a pair of flow inhibitors **223**, **225** attached respectively to the upper case **222** and the bottom case **226**. Based on this disclosure, it should be appreciated that some components of the housing **220** may be integrally formed together as one piece. FIG. **3** also illustrates how the housing **220** may include a paraboloid feature **234** for the chamber **230** in which the disk-pack turbine **250** rotates. The paraboloid shape of the outside surface of the disk-pack turbine **250**, in at least one embodiment, assists with obtaining the harmonic frequency of the rotors **264**, **266** and disk(s) **260** themselves as they spin in the chamber **230**, thus increasing the dissociation process for the fluid passing through the system. In at least one embodiment, the rotors **264**, **266** have complementary outer faces to the shape of the chamber **230**.

(49) The upper case **222** includes an opening **2222** passing through its top that is aligned with the opening in the bearing **280**. As illustrated in FIGS. **3** and **4**, a bearing **280** is present to minimize any friction that might exist between the shoulder **2642** of the top rotor **264** and the housing collar **125** and the upper case **222**. The bearing **280**, in at least one embodiment, also helps to align the top **2524** of the expansion chamber **252** with the outlet **138** of the vortex chamber **130**. Likewise, the lower case **226** includes an opening **2262** passing through its bottom that is lined with a bearing **280** that surrounds the shoulder (or motor hub) **2662** of the lower disk **266**.

(50) The peripheral case **224** includes a plurality of discharge ports **232** spaced about its perimeter. The discharge ports **232** are in fluid communication with the disk chambers **262**. The flow inhibitors **223**, **225** in the illustrated system, in at least one embodiment, assist with routing the flow of fluid exiting from the periphery of the disk-pack turbine **250** towards the discharge ports (or collection points) **132** in the housing **220**. In at least one embodiment, there is a containment vessel **900** (see, e.g., FIGS. **6** and **7**) around the housing **220** to collect the discharged gas from the system.

(51) Additional examples of electrical isolation components include the following approaches. The drive system/spindle/shaft is electrically isolated via the use of a large isolation ring made of non-conductive material, which creates discontinuity between the drive shaft and ground. In at least one embodiment, all disk-pack turbine components are electrically isolated from one another utilizing, for example, non-conducting tubes, shims, bushings, isolation rings, and washers. The main feed tube (or intake chamber) is also electrically isolated from the top rotor via the use of an additional isolation ring. The feed tube and support structure around the system are electrically isolated via the use of additional isolation elements such as nylon bolts. In most cases, there is no electrical continuity between any components, from drive shaft progressing upward through all rotating components to the top of the vortex chamber and support structures. There are, however, occasions when electrical continuity is desirable as described previously.

(52) In at least one embodiment, the vortex chamber **130** shapes the inflowing charging media into a through-flowing vortex that serves to accumulate, accelerate, stimulate, and concentrate the charging media as it is drawn into the expansion chamber **252** by centrifugal suction. As the rotating compressed charging media passes through the base opening **138** of the vortex chamber **130**, it rapidly expands as it enters into the revolving expansion chamber **252**. Once within the expansion chamber **252**, the charging media is further accelerated and expanded while being divided and drawn by means of a rotary vacuum into the waveform disk channels **262** of the rotors **264**, **266** and disk(s) **260** around the expansion chamber **252**. While progressing through the waveform geometries of the rotors and disks around the expansion chamber **252**, the charging

media is exposed to a multiplicity of dynamic action and reactionary forces and influences which work in concert to achieve desired outcomes relative to conditioning, separation, and/or transformation of liquids and gases and/or other matter.

(53) FIG. 5 illustrates a partial cutaway view of the embodiment illustrated in FIGS. 2-4. FIG. 5 provides an example of the fluid flow dynamics within the disks in accordance with the present invention. Waveforms channels are formed in the disk chambers **262** by the geometric patterns **261** on the rotors **264**, **266** and disk(s) **260**. FIG. 5 illustrates how stepped waveform harmonics cause high and low pressure zones to form in the channels with the circulation of the flow illustrated from the top to the bottom of the zones by the C's (clockwise) and backward C's (counterclockwise) that reflect the circulation. These pressure zones and tortile reciprocating motion allow the charging media and material to flow within the channels and to break the bonds between atoms in at least one embodiment. As the disk-pack turbine **250** rotates the charging media within the expansion chamber **252**, the charging media flows from the center of the disk-pack turbine **250** through the disk chambers **262** towards the periphery of the disk-pack turbine **250**. As the charging media passes through the disk chambers **262** the media is conditioned, separated, dissociated, and/or transformed based on controllable variables such as construction materials, waveform geometry, tolerances, numbers of progressions, waveform diameters, disk stack densities, internal and external influences and charging media composition.

(54) FIGS. 6A and 6B illustrate an embodiment having a plurality of gas collection conduits **902**, **904**, **906**, **908** for further separating gases based on weight. The illustrated system includes a containment vessel **900** that encloses the disk-pack module **200A**. Also illustrated is an example of motor **310A** driving the driveshaft **312A** with a belt **316A** and a work surface (or bench/platform) **910**. The illustrated embodiment shares some similarities with the previous embodiment including the presence of an intake module **100A** with an intake **132A** and a disk-pack module **200A**.

(55) The illustrated system includes at least five points for removal of gas and other material from the system. Extending out from the containment vessel **900** is a separation conduit **902** that branches twice into a first branch conduit **904** and a second branch conduit **906**. The first branch conduit **904** provides three points at which fluid may be withdrawn from the system through valves **930**, **931**, **932**. The second branch conduit **906** leads to valve **933**. Extending from the intake module **100A** is a third branch conduit **908** that leads to valve **934**. Based on this disclosure, it should be appreciated that the separation conduits can take a variety of forms other than those that are illustrated in FIGS. 6A and 6B. The gases (or fluids) are separated in at least one embodiment using at least one of the following: specific gravity, exit velocity, opposite-attractors installed along the conduit or proximate to a valve, electric and/or magnetic for matter with positive/negative or North/South polar predominance. In at least one embodiment the waveform disks illustrated in FIGS. 7A and 7B were used to in a gas separation designed system. In at least one embodiment, it was found that when the waveform disks illustrated in FIGS. 7A and 7B were rotated between 3,680 and 11,000 RPM that hydrogen was separated out from environmental air.

(56) FIG. 7A illustrates a pair of disks **260Z** installed in a top rotor **264Z** and a bottom rotor **266Z**, respectively, that have been found to be beneficial for a gas separation embodiment. The illustrated disks **260Z** include matched waveform patterns with two sets of hyperbolic waveforms **2642Z** and three sets of substantially circular waveforms **2646Z**. FIGS. 7A and 7B illustrate an alternative embodiment that includes exit ports including multiple convergent exit ports **2649Z** and multiple divergent exit ports **2648Z** that pair together to form convergent/divergent ports. FIG. 7B illustrates an example of a waveform changing height as it travels around the disk (**2611Z** represents the low level and **2612Z** represents the high level). FIG. 7B illustrates an example of how the waveforms may vary in width (**2613Z** represents a wide segment and **2614Z** represents a thinner segment). FIGS. 7A and 7B illustrate an example of how waveforms **2642Z** and **2646Z** travel substantially around and substantially axially centered about the opening **252Z** in top rotor **264Z**.

(57) For various applications, it may be desirable to have an internal geometry conducive to hyper-

expansion of the charging media followed by reduction/diminishing flow tolerances for the purpose of compression or reconstitution of the charging media. This secondary compression cycle is useful for producing concentrated, highly energetic, molecularly reorganized charging media for applications such as fuel formulation.

(58) One cool, moist morning prior to starting a testing session with a system built according to the invention similar to the fluid intake module **100A** and the disk-pack module **200A** illustrated in FIG. **6A**, a system valve **132A** in fluid communication with the containment vessel (or housing) **900** was pulled open. This resulted in a relatively loud thump/energetic reaction/phoom. On the next day, another individual was asked to pull the valve **132A** open for verification. The reactionary phoom occurred again. It was understood that the moisture content in the air, itself, was being dissociated, with the lighter material being contained in the upper, domed part of the sealed vessel and trapped therein by a cushion of air. For verification, all valves were closed and the system was allowed to run at 2700 RPM in this closed condition for 5 minutes. A valve **132A** was slowly pulled open and a flame applied to the discharging material, which resulted in the valve erupting in a momentary pale blue flame. Further testing and refinement of the process included the introduction of higher moisture/water concentrations in the form of atomized mist and water injection. Simple vessel valve and tubing arrangements were set up for rudimentary gas product division and capture as illustrated in FIGS. **6A** and **6B**. Utilizing a small biaxial configuration for the disk-pack turbine, which included just an upper rotor **264A** and a lower rotor **266A**, was sufficient to establish repeatable, verifiable dissociation achieved through hyperbolic rotary motion alone. An example of the rotors **264A**, **266A** of the disk-pack turbine **250A** is illustrated in FIGS. **8A-8C**. FIG. **8A** illustrates the top of the disk-pack turbine **250A**, FIG. **8B** illustrates the bottom face of the upper rotor **264A**, and FIG. **8C** illustrates the top face of the lower rotor **266A**. The illustrated waveform pattern includes a sinusoidal ridge **2642A** and a circular ridge **2646A**. The lower rotor **266A** includes a circular outer face ridge **2646A**. Also, illustrated is an example of mounting holes **2502A** for assembling the disk-pack turbine **250A**. In an alternative embodiment, the wave patterns are switched between the upper rotor **264A** and the bottom rotor **266A**. Stoichiometric gas concentrations capable of sustaining flame were achieved through broad variations in systemic configuration and operating conditions.

c. Multi-Stage Systems

(59) FIGS. **9A-11** illustrate different embodiments of a multiple stage system that includes disk-pack turbines **250B-250D** for each stage of the system. The illustrated disk-pack turbines are different, because the waveform disks are conical shape with circular waveform patterns. FIGS. **9A** and **9B** illustrate a common housing **220B**, intake module **130B**, and discharge port **232B**. Each disk-pack turbine includes at least one expansion chamber **252B-252D** that routes fluid into the at least one disk chamber **260** of the disk-pack turbine **250B-250D**. In the illustrated examples, each disk-pack turbine **250B-250D** includes a top rotor **264B-264D** that substantially provides a barrier to fluid exiting the periphery from flowing upwards above the disk-pack turbine to assist in routing the exiting fluid to the next stage or the at least one discharge port. In a further embodiment, the at least one discharge port is located along the periphery of the last disk-pack turbine instead of or in addition to the illustrated bottom discharge port **232B** in FIGS. **10** and **11**. These figures illustrate the disk-pack module housing **220B** with only a representative input illustrated to represent the vortex chamber (or alternatively an intake chamber that is substantially cylindrical) that feeds these illustrated systems.

(60) When the discharge port is at the bottom of the housing, the driveshaft (not illustrated) passes up through the discharge port to engage the lowest rotor. Between the individual disk-pack turbines there are driveshafts such as those illustrated in FIG. **9C** that extend through the top rotating rotor/disk of the lower disk-pack turbine to the bottom rotor of the higher disk-pack turbine or alternatively there are a plurality of impellers between each pair of disks that are not mounted to the housing. The driveshafts **312B** will connect to the rotating disk via support members to allow

for the flow of fluid through the expansion chamber. FIG. 9C illustrates a partial cross-section of a multi-stage system with a disk-pack turbine **250D'** and a second disk-pack turbine **250B'** that are similar to the disk-pack turbines discussed in connection with FIGS. **10** and **11** except there is no flange depicted on the top rotor and the bottom of the expansion chambers is provided by a concave feature **3122B** and **3124B** incorporated into the driveshaft **312B**. Below each disk-pack turbine is a discharge module that includes discharge ports **232'** in a top surface to funnel the captured gas through discharge outlet **2322'** into the next stage or the discharge port of the system.

(61) FIG. **10** illustrates a cross-sectional and conceptual view of an example of a multi-stage stacked waveform disk system in accordance with an embodiment of the present invention. The illustrated multi-stage system includes a plurality of stacked disk-pack turbines **250B-250D** that are designed to first expand/dissociate and then compress/concentrate the charging media through the expansion chamber and the disk chambers in each disk-pack turbine. In an alternative embodiment, additional ports are added around the periphery at one or more of the stages to allow material (or fluid) to be added or material to be recovered/removed from the system.

(62) Disk-pack turbine **250B** is an expansive waveform disk-pack turbine and includes multiple waveform channels. Disk-pack turbine **250C** is a second stage concentrating/compressive waveform disk-pack turbine. Disk-pack turbine **250B** is a third stage concentrating/compressive waveform disk-pack turbine that provides an example of just a pair of rotors. The illustrated system includes an intake chamber **130B** in fluid communication with the expansion chamber **252B**. The expansion chamber **252B** is formed by openings in the center of the plurality of rotors **264B**, **266B** and disks **260B** that form disk-pack turbine **250B**. The bottom rotors **266B-266D** in disk-pack turbines **250B-250D**, respectively, are solid and do not have an opening in the center, but instead include a bottom concave feature **2522B**, **2522C**, **2522D** that forms the bottom of the expansion chamber **252B**. The solid bottom rotors **266B-266D** prevent fluid from flowing completely through the center of the disk-pack turbine **250B-250D** and encourage the fluid to be distributed into the various disk chambers **262** within the disk-pack turbines **250B-250D** such that the fluid flows from the center to the periphery. Each of the top rotors **264B-264D** in disk-pack turbines **250B-250D** includes lips **2646** that substantially seal the perimeter of the top disk with a housing **220**. The lips **2646** thereby encourage fluid to flow within discharge channels **253B-253D**. Discharge channel **253B** connects disk-pack turbine **250B** and the expansion chamber of disk-pack turbine **250C** in fluid communication. Discharge channel **253C** connects disk-pack turbine **250C** and the expansion chamber **252B** of disk-pack turbine **250B** in fluid communication. Discharge channel **253D** connects disk-pack turbine **250D** in fluid communication with fluid outlet **232B**. In an alternative embodiment, the top rotors do not rotate and are attached to the housing to form the seals.

(63) FIG. **11** illustrates a cross-sectional view of another example of a multi-stage stacked waveform disk system in accordance with an embodiment of the present invention. The multi-stage system of this embodiment includes a plurality of disk-pack turbines. The illustrated disk-pack turbines **250D**, **250C**, **250B** are taken from the previous embodiment illustrated in FIG. **10** and have been reordered to provide a further example of the flexibility provided by at least one embodiment of the invention.

(64) The charging media may also be externally pre-conditioned or “pre-sweetened” prior to entering the system. The pre-conditioning of the charging media may be accomplished by including or mixing into the charging media desirable material that can be molecularly blended or compounded with the predominant charging media. This material may be introduced as the media enters into and progresses through the system, or at any stage within the process. Polar electrical charging or excitation of the media may also be desirable. Electrical charging of the media may be accomplished by pre-ionizing the media prior to entering the system, or by exposing the media to induced frequency specific pulsed polar electrical charges as the media flows through the system via passage over the surface of the disks.

d. Power Generation

(65) These objectives are accomplished, for example, via the harnessing and utilization of transformational dynamics and forces propagated as the result of liquids, gases, and/or other forms of matter and energy progressing through and/or interacting with rotating hyperbolic waveform structure.

(66) In at least one embodiment the present invention provides a system and method for producing and harnessing energy from ambient sources at rates that are over unity, i.e., the electrical energy produced is higher than the electrical energy consumed (or electrical energy out is greater than electrical energy in). The system and method in at least one embodiment of the present invention utilize rotating waveforms to manipulate, condition, and transform mass and matter into highly energetic fields, e.g., polar flux, electrical, and electro-magnetic fields. The present invention, in at least one embodiment, is also capable of generating diamagnetic fields as strong forces at ambient operational temperatures.

(67) FIGS. **12-15D** illustrate an example embodiment of the present invention that is useful in generating electrical energy. The illustrated system uses as inputs environmental energies, air and electrical energy to drive a motor to rotate the disk-pack turbine and, in a further embodiment, it harnesses the environment around the system to form magnetic fields. The present invention in at least one embodiment is capable of producing very strong field energy at ambient temperatures while using relatively minimal input electrical energy compared to the electrical energy production. FIGS. **15A-15D** illustrate a pair of waveform disks that can be mated together with a pair of rotors. The illustrated waveform disks are depicted in FIG. **14**. FIG. **15A** illustrates the top of a disk-pack turbine **250E** with a top rotor **264E** with an opening into the expansion chamber **2522E**. FIGS. **15B** and **15C** illustrate a pair of mated disks for use in power generation according to the invention. The disks are considered to be mated because they fit together as depicted in FIG. **15D**, because a disk channel **262E** is formed between them while allowing fluid to pass between the disks **260E**. FIG. **15D** illustrates an example of the mated disks **260E** placed between a top rotor **264E** and a bottom rotor **266E** with bolts attaching the components together around the periphery. As mentioned earlier, the bolts in at least one embodiment pass through a nylon (or similar material) tube and the spacers are nylon rings.

(68) The creation of a magnetic field to generate electrical current results from the rotation of a disk-pack turbine **250E** and at least one magnet disk **502** that is on an opposite side of the coil disk from the disk-pack turbine. In at least one embodiment, the coil disk **510** includes a plurality of coils **512** that are connected into multiple-phase sets. The disclosure that follows provides additional discussion of the embodiment illustrated in FIGS. **12-15D**; as an example, starting with the chamber **130E** and proceeding down through the system. As with the previous embodiments, the chamber **130E** feeds the charging media to the disk-pack turbine **250E** during operation of the system and in at least one further embodiment the chamber **130E** is omitted as depicted in FIGS. **16** and **17**. In the embodiments depicted in FIGS. **16** and **17**, the intake occurs through the feed housing **126E** and/or the periphery of the disk-pack turbine **250E**.

(69) In at least one embodiment, the intake chamber **100E** includes a cap **122E**, a housing **120E** connected to an intake port **132E**, a lower housing **124E** around a bearing **280E** as illustrated, for example, in FIG. **14**. In an alternative embodiment, one or more of the intake chamber components are integrally formed together. The housing **120E** includes a vortex chamber **130E** that includes a funnel section that tapers the wall inward from the intake ports **132E** to an opening that is axially aligned with the feed chamber **136E**. The funnel section in at least one embodiment is formed by a wall that has sides that follow a long radial path in the vertical descending direction from a top to the feed chamber **136E** (or other receiving section or expansion chamber). The funnel section assists in the formation of a vortex flow of charging medium downward into the system.

(70) Below the main part of the chamber **130E** is a tri-arm centering member **602** that holds in place the system in axial alignment with the drive shaft **314E**. The vortex chamber **130E** is in fluid communication with feed chamber **136E** present in feed housing **126E**. The feed housing **126E**

passes through a collar housing **125E** and a magnet plate **502**, which is positioned and in rotational engagement with the collar housing **125E**. The feed housing **126E** is in rotational engagement through bearings **282E** with the collar housing **125E**. The collar housing **125E** is supported by bearing **282E** that rides on the top of the lower feed housing **127E** that is connected to the disk-pack turbine **250E**. The feed chamber **136E** opens up into a bell-shaped section **138E** starting the expansion back out of the flow of the charging medium for receipt by the expansion chamber **252E**. The intake housing components **120E**, **122E**, **124E** together with the feed housing **138E** in at least one embodiment together are the intake module **100E**.

(71) The magnet plate **502** includes a first array of six magnets (not shown) attached to or embedded in it that in the illustrated embodiment are held in place by bolts **5022** as illustrated, for example, in FIG. **14**. In another embodiment, the number of magnets is determined based on the number of phases and the number of coils such that the magnets of the same polarity pass over each of coils in each phase-set geometrically at the exact moment of passage. The magnet plate **502** in at least one embodiment is electrically isolated from the feed housing **126E** and the rest of system via, for example, electrically insulated/non-conducting bearings (not shown). The upper plate **502** is able to freely rotate about the center axis of the disk-pack turbine **250E** by way of the collar housing **125E** made from, for example, aluminum which is bolted to the top of the upper round plate **502** and has two centrally located ball bearing assemblies, an upper bearing **282E** and a lower bearing **283E**, that slide over the central feed housing **126E**, which serves as a support shaft. The distance of separation between the magnet plate **502** and the top of the disk-pack turbine **250E** is maintained, for example, by a mechanical set collar, shims, or spacers.

(72) During operation, the first array of magnets is in magnetic and/or flux communication with a plurality of coils **512** present on or in a stationary non-conductive disk (or platform) **510**. The coil platform **510** is supported by support members **604** attached to the frame **600** in a position between the array of magnets and the disk-pack turbine **250E**. The platform **510** in the illustrated embodiment is electrically isolated from the rest of the system. In at least one embodiment, the platform **510** is manufactured from Plexiglas, plastic, phenolic or a similarly electrically inert material or carbon fiber.

(73) A disk-pack turbine **250E** is in rotational engagement with the feed chamber **138E**. As with the other embodiments, the disk-pack turbine **250E** includes an expansion chamber **252E** that is in fluid communication with the intake chamber **130E** to establish a fluid pathway from the inlets to the at least one disk chamber **262E** (two are illustrated in FIGS. **14**) in the disk-pack turbine **250E**. The illustrated embodiment includes two pairs of mated disks **260E** sandwiched by a pair of rotors **264E**, **266E** where the disks **260E** and the top rotor **264E** each includes an opening passing therethrough and the bottom rotor **266E** includes a rigid feature **2522E** that together define the expansion chamber **252E**. The disk chambers **262** in the illustrated embodiment are present between the two disks in each mated pair with slightly paraboloid shaped surfaces (although they could be tapered or flat) being present between the neighboring disks, where the bottom disk of the top mated disk pair and the top disk of the bottom mated disk pair are the neighboring disks. Each disk **260E** of the mated pairs of disks is formed of complimentary non-magnetic materials by classification, such that the mated pair incorporating internal hyperbolic relational waveform geometries creates a disk that causes lines of magnetic flux to be looped into a field of powerful diamagnetic tori and repelled by the disk. An example of material to place between the mated disk pairs is phenolic cut into a ring shape to match the shape of the disks.

(74) In the illustrated embodiment, the bottom rotor **266E** provides the interface **2662E** with the drive system **314E**. In at least one embodiment, the rotors will be directly connected to the respective disks without electrically isolating the rotor from the nested disk. In another embodiment, the disks are electrically isolated from the rotor nesting the disk. The illustrated configuration provides for flexibility in changing disks **260E** into and out of the disk-pack turbine **250E** and/or rearranging the disks **260E**.

(75) A lower coil platform **510'** may also be attached to the frame **600** with a plurality of support members **604**. The lower platform **510'** includes a second array of coils **512'** adjacent and below the disk-pack turbine **250E**. An optional second array of six magnets (not shown) present in magnet plate **504** are illustrated as being in rotational engagement of a drive shaft **314E** that drives the rotation of the disk-pack turbine **250E**, but the bottom magnet plate **504** in at least one embodiment is in free rotation about the drive shaft **314E** using, for example, a bearing. The drive shaft **314E** is driven by a motor, for example, either directly or via a mechanical or magnetic coupling.

(76) Each of the first array of coils **512** and the second array of coils **512'** are interconnected to form a phased array such as a three or four phase arrangement with 9 and 12 coils, respectively. Each coil set includes a junction box **5122** (illustrated in FIG. 12) that provides a neutral/common to all of the coils present on the coil disk **510** and provision for Earth/ground. Although not illustrated, it should be understood based on this disclosure that there are a variety of ways to interconnect the coils to form multiple phases in wye or delta or even a single phase by connecting coils in series or parallel. As illustrated, for each coil, there are a pair of junction points that are used to connect to common and positive and as illustrated the left box **5124** attaches to electrical power out while the right box **5126** connects to neutral/common.

(77) In at least one embodiment with a three phase arrangement, the coils for each phase are separated by **120** degrees with the magnets in the magnet plate spaced every **60** degrees around the magnet plate. The first array of magnets, the first array of coils **512**, the second array of coils **512'**, and second array of magnets should each be arranged in a pattern substantially within the vertical circumference of the disk-pack turbine **250E**, e.g., in circular patterns or staggered circular patterns of a substantially similar diameter as the disks **160E**. In another embodiment, there are multiple coil platforms and/or coil arrays between the disk-pack turbine and the magnet plate.

(78) The lower magnet plate **504** has a central hub **5042** bolted to it which also houses two ball bearing assemblies **282E**, which are slid over the main spindle drive shaft **314E** before the disk-pack turbine **250E** is attached. This allows the lower magnet plate **504** to freely rotate about the center axis of the system and the distance of separation between the lower plate **504E** and disk-pack turbine **250E** is maintained, for example, by a mechanical set collar, spacers, and/or shims or the height of the driveshaft **314E**.

(79) Suitable magnets for use in at least one embodiment of the invention are rare earth and/or electromagnets. An example is using three inch disk type rare earth magnets rated at **140** pounds. Depending on the construction used, all may be North magnets, South magnets, or a combination such as alternating magnets. In at least one embodiment, all metallic system components, e.g., frame **600**, chamber housing **120E**, magnet plates **502**, **504**, are formed of non-magnetic or very low magnetic material with other system components, e.g., bearings, spacers, tubing, etc., are preferably formed of non-magnetic materials. The system, including frame **600** and lower platform **504**, in at least one embodiment are electrically grounded (Earth). In a further embodiment, all movable components, particularly including chamber housing **120E** and individual components of the disk-pack turbine **250E**, are all electrically isolated by insulators such as non-conductive ceramic or phenolic bearings, and/or spacers.

(80) In a further embodiment, the magnet plate(s) is mechanically coupled to the waveform disks. In a still further embodiment, the magnet plate(s) is mechanically locked to rotate in a fixed relationship with the disk-pack turbine through for example the collar housing **125E** illustrated in FIG. 13. This results in lower, but very stable and safe output values. In a further embodiment, one set of coil platform and magnet plate are omitted from the illustrated embodiments of FIG. 12-17.

(81) In use of the illustrated embodiment of FIGS. 12-14, the rotatable disk-pack turbine is driven by an external power source. As the disk-pack turbine rotates a vacuum or suction is created in the system according to at least one embodiment. This vacuum draws a charging media into the intake chamber **130E** via fluid inlets **132E**. The intake chamber **130E** transforms the drawn charging media into a vortex that further facilitates passing the charging media into the expansion chamber.

As the charging media passes through the system, at least a portion of the through-flowing charging media is transformed into polar fluxes which are discharged or emanated from specific exit points within the system. This magnetic polar energy discharges at the center axis and periphery of the rotatable disk-pack turbine. For example, when the magnetic polar energy discharged at the periphery is a North polar flow, the magnetic energy discharged at the axis is a South polar flow. In this example, by introducing north-facing permanent magnets on magnet plates **502**, **504** into the north-flowing flux, repulsive forces are realized. By placing the North-facing polar arrays at specific oblique angles, the rotatable disk-pack turbine is driven by the repelling polar flux. Utilizing only the polar drive force and ambient environmental energies and air as the charging media, the system is capable of being driven at a maximum allowed speed. Simultaneously, while generating polar flux discharges at the axis and periphery of the disk-pack turbine **250E**, powerful, high torque, levitative diamagnetic fields manifest through the top and bottom surfaces of the disk-pack turbine. The field strength of the diamagnetic fields is directly proportionate to the speed of rotation of the magnet arrays and magnet strength in relation to the rotating disk-pack turbine. Each of the mated pairs of rotatable waveform disks **160E** is capable of producing very strong field energy at ambient temperatures while utilizing an extraordinarily small amount of input energy. As an example, each of the mated pairs of rotatable waveform disks **160E** is capable of producing well over one thousand (1,000) pounds of resistive, repulsive, levitative field energy. That is, the system is capable of repeatedly, sustainably and controllably producing a profoundly powerful diamagnetic field at ambient temperatures while utilizing relatively minimal input energy.

(82) In a further embodiment illustrated, for example, in FIG. **16**, the chamber **120E** above the tri-arm support member **602** is omitted and the expansion chamber pulls charging material from the atmosphere as opposed to through the intake chamber **120**. In at least one embodiment, material is pulled from and discharged at the periphery of the disk-pack turbine **250E** simultaneously.

(83) FIG. **17** illustrates an alternative embodiment to that illustrated in FIG. **16**. The illustrated embodiment includes a flux return **700** to restrain the magnetic fields and concentrate the magnetic flux created by the disk-pack turbine **250E** and increase the flux density on the magnet plate **502** and coils **512**. An example of material that can be used for the flux shield **600** is steel. In at least one embodiment, the flux return **700** is sized to match the outer diameter of the outer edge of the magnets on the magnet plate **502**.

(84) Another example embodiment of the present invention is illustrated in FIG. **18** and includes two disk-pack turbines **250F** having a pair of rotors **264F**, **266F** sandwiching a pair of disks **260F**, two sets of coil electrical coil arrays configured for the production of three-phase electrical power, and two bearing-mounted, free-floating, all North-facing magnetic arrays, along with various additional circuits, controls and devices. One difference with the previous embodiments is that the disk-pack turbines **250F** are spaced apart leaving an open area between them.

(85) Another difference for the power-generation embodiments from the other described embodiments is the omission of a housing around all of the rotating components. One reason for this difference is that the illustrated embodiment is directed at power generation, but based on this disclosure it should be understood that an alternative embodiment adds a collection/containment dome (or wall) to this illustrated system to provide a means of collecting and harnessing for application/utilization the profound additional environmental electrical fields/DC voltages and dramatic currents/field amperage as well as the collection of any fluid components that manifest as a result of the power generation processes.

(86) The nature of electricity generated by this embodiment is substantially different as compared to conventional power generation. The waveform disks are manufactured as nesting pairs. Each waveform disk pair may be of like or dissimilar materials, depending on design criteria, i.e., aluminum and aluminum, or, as example, aluminum, brass or copper. When a waveform disk pair is separated by a specific small distance/gap and are electrically isolated from one another by means of no mechanical contact and non-conducting isolation and assembly methods and elements like

those described earlier, chambers are formed between each disk pair that provide for highly exotic flow paths, motion, screening currents, frequencies, pressure differentials, and many other actionary and reactionary fluid and energetic dynamics and novel electrical and polar phenomena. Immediately upon energizing the drive motor to set the disk-pack turbine rotor in motion, the inner disk hyperbolic geometries begin to interact with the magnetic fields provided by the rotatable Rare Earth magnet arrays, even though there are no magnetic materials incorporated into the manufacture of the disk-pack turbine. By the time the disk-pack turbine reaches the speed of approximately 60 RPM, diamagnetic field effects between the disk-pack turbine faces and magnet arrays are sufficient to establish a driving/impelling link between the disk-pack turbine and magnet array faces.

(87) A variety of magnetic polar fluxes and electrical currents begin to manifest and dramatically increase in proportion to speed of rotation. Diamagnetism manifests as a profoundly strong force at the upper and lower rotor faces as primarily vertical influences which, through repellent diamagnetic fields, act to drive the magnet arrays while simultaneously generating a significant rotational torque component. It has been determined that these strong force diamagnetic fields can be transmitted through/passed through insulators to other metallic materials such as aluminum and brass. These diamagnetic fields, generated at ambient temperatures, are always repellant irrespective of magnet polarity. Although mechanically generated, these diamagnetic fields are, believed to be in fact, screening and/or eddy currents previously only recognized as a strong force associated with magnetic fields as they relate to superconductors operating at cryogenic temperatures. The system is configured to rotate on the horizontal plane, resulting in the most profound magnetic field effects manifesting and emanating at an oblique, though near right angle relative to the upper and lower rotor faces. The most profound electrical outputs in the system emanate from the periphery of the disk-pack turbine and are measurable as very high field amperages and atmospheric voltages. As an example, when attaching a hand held amp meter to any of the three structural aluminum risers of the built system illustrated, for example, in FIG. 12, it is common to observe amperages of over 150 amps per electrically isolated riser. Polar/magnetic fluxes are the primary fluid acting in this system configured for electrical power generation. An additional component acting within the system is atmospheric air. In certain implementations, allowing the intake, dissociation, and discharge of the elements within atmospheric air as well as exposure to ambient atmospheric energies increases the magnetic field effects and electrical power output potential by plus/minus 40%.

(88) The diamagnetic fields utilized for electrical power generation make it possible to orient all magnets within the magnet arrays to North, South, or in a customary North/South alternating configuration. When all North or South facing magnets are configured in relation to the diamagnetic rotor fields, voltages and frequencies realized are extremely high. With all North or South magnet orientation the diamagnetism, which is both North and South magnetic loops, provides the opposite polarity for the generation of AC electricity. By configuring the system with alternating magnetic polarities and minor power output conditioning, it has been possible to practically divide the output values and bring the voltages and frequencies into useful ranges. As an example, measuring combined upper coil array only, output values of 900 volts at 60 HZ with a rotor speed of 1200 RPM are typical. Based on research, it is believed the magnetic fluxes behave like gasses/fluids and can act as such. The addition/intake/dissociation of air and other ambient influences adds significantly to the process; however, with the presence of magnetic fields interacting with the hyperbolic waveform structures alone, it is believed that both exotic, magnetic phenomena as well as electricity are generated. It is believed it would be impossible to be generating these profound diamagnetic fields without also simultaneously generating corresponding electrical currents. As soon as a magnet, even handheld, is introduced above the disk surface and the diamagnetic repellent effect is felt, electrical current is being produced, thereby creating the diamagnetic phenomena.

e. Testing of Prototype

(89) At least one prototype has been built according to the invention to test the operation of the system and to gather data regarding its operation. The prototype shown in FIGS. **12-18** include a three phase arrangement of nine coils, three coils per phase using 16 gauge copper magnet wire with 140 turns and six magnets (three North and three South magnets alternating with each other) above the disk-pack turbine and coils. On the bottom side of the disk-pack turbine there is a four phase arrangement of 12 coils, three coils per phase using 20 gauge copper magnet wire with 260 turns and six magnets. Based on this disclosure, it should be appreciated that the gauge and material of the wire and the number of turns and of coils can be modified and that the above descriptions are examples. The disk-pack turbine was assembled with two pairs of mated disks between the top rotor and the bottom rotor as illustrated, for example, in FIG. **16**. In this particular configuration the two top waveform disks were made of aluminum and the bottom two waveform disks were made of brass. It has been found that alternating brass and aluminum disks, as opposed to nesting like disks results in significantly higher magnetic and electrical values being produced. In further testing when copper is used in place of brass, the voltages have stayed substantially equal, but a much higher current has been produced. After one testing session, it was discovered that the brass disks were not electrically isolated from each other and there was still excess electrical power generated compared to the power required to run the motor. The feed tube (or intake chamber) is made of brass and electrically isolated from the aluminum rotor face through use of a non-conductive isolation ring, which also is present between the two mated disk pairs. The system was connected to a motor via a belt.

(90) An interesting phenomenon has been noticed during operation of the prototype that indicates that ambient atmospheric energies from the surrounding environment is being transformed and harnessed by the system to create supplemental electrical current. There is a certain amount of background ionizing radiation present all around us. The level of detected ionizing radiation decreases from background levels when the system is in operation by an amount greater than the margin of error for the detector.

(91) When the motor was not running, and the disk-pack turbine was slowly rotated by hand, even at this very low speed, a diamagnetic field arose sufficient to engage the upper magnet plate (the magnet plate was not mechanically coupled), resulting in the production of enough electricity to cause a connected three-phase motor (2 HP, 230 V) to rotate as the disk-pack turbine was being turned by hand from the current produced in the coil arrays.

(92) The lower magnet disk rotated with the disk-pack turbine while the upper magnet disk was magnetically coupled to the waveform disks. One way to illustrate the results will be to use classic power generation formulas. One of the greatest points of interest is that, even though there is, mathematically speaking, production of very high power readings as relates to watts, there is very little discernable heat generated through the process, and this phenomenon extends to devices connected and driven by this electricity, such as multiple three-phase high voltage electric motors. An example is prior to starting the system, ambient temperatures for the induction coils and other associated devices were about 82° Fahrenheit. After running the system for in excess of one hour, the temperature rise was as little as two or three degrees and, at times, the temperature has been found to actually fall slightly. The temperature measured at the core of the waveform rotor when measured always has dropped a few degrees over time. The temperature of an unloaded three phase electric motor connected to the output will generally remain within one or two degrees of coil temperature. The three phases of the upper generating assembly were measured with each phase was producing plus/minus 200 volts at 875 RPM. Based on measurements, each of the three coil sets in the three-phase system measure out at 1.8 ohms. Divide 200 volts peak-to-peak by ohms equals about 111.11 Amps, times 200 volts equals about 22,222 Watts, times three phases equals about 66,666 total Watts. The motor powering the system was drawing 10.5 Amps with a line voltage of 230 volts, which yields us 2,415 Watts being consumed by the motor to produce this

output of about 66,666 Watts.

(93) When the top magnet disk was locked with the waveform disks, the process was repeated. The upper coil array produced about 540 Volts peak-to-peak between the three phases and about 60 Amps for a power generation of about 32,400 Watts. With regard to the lower generator, the math is actually quite different because there is a higher coil set resistance of approximately 3.7 Ohms per coil set of three (four phases). So, with an output of 120 Volts peak-to-peak per phase divided by 3.7 Ohms equals 32.43 Amps times 120 Volts equals 3,891.6 Watts per phase times four equals 15,566.40 Watts. These readings are from running the system at a virtual idle of about 875. Testing has found that diamagnetic energy will really start to rise at 1700 RPM and up as do the corresponding electrical outputs.

(94) Changing the material used for the intake chamber in the built system from D2 steel to brass improved the strength of the diamagnetic field and resulting power generation by approximately 30%.

f. Discussion Regarding Diamagnetism

(95) Diamagnetism has generally only been known to exist as a strong force from the screening currents that occur in opposition to load/current within superconductors operating at super low cryogenic temperatures, i.e., 0 degrees Kelvin (0 K) or -273 degrees Celsius (-273 C). When a superconductor-generated diamagnetic field is approached by a magnetic field (irrespective of polar orientation) a resistive/repulsive force resists the magnetic field with ever-increasing repulsive/resistive force as distance of separation decreases. The superconductor's resistive force is known to rise, in general, in a direct one-to-one ratio relative to the magnetic force applied. A 100 pound magnet can expect 100 pounds of diamagnetic resistance. A logical assumption would lead one to believe that this diamagnetic force, acting upon a superconductor in this way, would result in increases in systemic resistance and net losses in efficiency. The counter-intuitive reality is that this interaction results in a zero net loss to the system.

(96) As described above, diamagnetism manifests as a strong force in superconductors due to the screening currents that occur at cryogenic temperatures. As with superconductors, the system of the present invention in at least one embodiment, utilizes screening currents working in concert with internal oppositional currents, flows, counter-flows, reciprocating flows and pressures generated by hyperbolic waveforms present on the rotatable waveform disks. These forces in combination with specific metallic materials, material relationships, component isolation technologies, and charging media as discussed in the example embodiments above manifest as profoundly powerful diamagnetic fields at the bottom and top surfaces of the rotatable disk-pack turbine at ambient temperatures. The diamagnetic waveform disks are fabricated from non-magnetic materials that are incapable of maintaining/retaining a residual electric field in the absence of an applied charge. The diamagnetic fields created by the rotatable waveform disks are a direct product of the specialized waveform motions, interaction with environmental matter and energies, and a modest amount of through-flowing and centripitated ambient air.

(97) The diamagnetic fields generated by the waveform disks can be utilized as a substitute for the North or South magnetic poles of permanent magnets for the purpose of generating electricity. However, unlike the North/South lines of force exhibited by common magnetic fields, diamagnetic fields manifest as North/South loops or tori that spin around their own central axis. This distinction results in the diamagnetic field not being a respecter of magnetic polarity and always repellent. The magnetic repellency allows one pole of the north/south alternating magnetic fields to be substituted with the diamagnetic field generated by the waveform disks. In use, the upper array of magnets and the lower array of magnets float freely and are driven by the diamagnetic levitative rotational torque. As the all north-facing rare earth magnets cut a circular right-angle path over the upper array of coils, and lower array of coils, electrical power is generated.

(98) Systems utilizing this arrangement for electrical power generation, in at least one embodiment of the present invention, have realized a multiplication in the production of voltage and current as

compared to an electrical power generation arrangement utilizing traditional North to South pole fluxuations. Further, power input required to run the systems are extremely low while power production is accomplished with minimal rise in heat or resistance, e.g., systems temperatures of less than five degrees over ambient temperatures. Also, when a coil or circuit is placed into the diamagnetic field, the resistance drops to near 0 Ohms with actual repeatable readings being about 0.01.

(99) Further, in at least one embodiment, the system of the present invention is capable of producing at very low operational speeds powerful diamagnetic fields that are capable of functioning as an invisible coupling between a rotating waveform disk and a rotatable magnetic array. The system drive side may be either the magnetic array side of the system or the diamagnetic disk side of the system. The magnets may move over the internal waveform geometries, thereby causing the fields to arise, or vise-versa. Actual power/drive ratios are established via progressive waveform amplitude and waveform iterations. The magnetic drive array will allow for the magnets to be dynamically/mechanically progressed toward periphery as systemic momentum increases and power requirements decrease. Conversely, when loads increase, the systemic driving magnets will migrate toward higher torque/lower speed producing geometries.

g. Waveform Disks

(100) The previously described waveforms and the one illustrated in FIGS. **8B** and **8C** are examples of the possibilities for their structure. The waveform patterns increase the surface area in which the charging media and fields pass over and through during operation of the system. It is believed the increased surface area as alluded to earlier in this disclosure provides an area in which the environmental fields in the atmosphere are screened in such a way as to provide a magnetic field in the presence of a magnet. This is even true when the waveform disk is stationary and a magnet is passed over its surface (either the waveform side or back side of the waveform disk), and the ebbs and flow of the magnetic field track the waveform patterns on the disk, manifesting in at least one embodiment as strong, geometric eddy currents/geometric molasses.

(101) As discussed above, the waveform disks include a plurality of radii, grooves and ridges that in most embodiments are complimentary to each other when present on opposing surfaces. In at least one embodiment, the height in the vertical axis and/or the depth measured along a radius of the disk chambers vary along a radius as illustrated, for example, in FIG. **15D**. In at least one embodiment, when a disk surface with the waveforms on it is viewed looking towards the waveforms, the waveforms take a variety of shapes that radiate from the opening that passes through (or the ridge feature on) the disk. In at least one embodiment, the number of peaks for each level of waveforms progressing out from the center increases, which in a further embodiment includes a multiplier selected from a range of 2 to 8 and more particularly in at least one embodiment is 2.

(102) In at least one embodiment, the disk surfaces having waveforms present on it eliminates almost all right angles and flat surfaces from the surface such that the surface includes a continuously curved face.

(103) In at least one embodiment, at least one ridge includes a back channel formed into the outer side of the ridge that together with the complementary groove on the adjoining disk form an area having a vertical oval cross-section.

(104) FIGS. **19A-19E** illustrate a variety of additional waveform examples. The illustrated plates include two different waveforms. The first waveform is a circular waveform **2646G** in the center and around the periphery. The second waveform **2642G** is a biaxial, sinocircular, progressive waveform located between the two sets of circular waveforms. The illustrated disks mate together to form the disk channels discussed previously. Each of the disks includes a plurality of assembly flanges **2629G** for mounting impellers between the disks.

(105) FIG. **19A** illustrates an example combination of biaxial, sinuocircular, progressive, and concentric sinusoidal progressive waveform geometry on a disk **260G** according to the invention.

FIG. 19B and 19C illustrate respectively the opposing sides of the middle disk 260G. FIG. 19D illustrates the top surface of the bottom disk 260G. FIG. 19E illustrates how the three disks fit together to form the disk chambers 262G and the expansion chamber 252G of a disk-pack turbine. In an alternative embodiment, one or more of the circular waveforms is modified to include a plurality of biaxial segments.

(106) FIG. 20 illustrates an example of a center disk incorporating varied biaxial geometries between two sets of circular waveforms according to the invention.

(107) FIGS. 21A-21D illustrate a two disk disk-pack turbine 250H. FIG. 21A illustrates the top of the disk-pack turbine 250H with an expansion chamber 252H. FIG. 21B illustrates the bottom surface of the top disk 264H. FIG. 21C illustrates the top surface of the bottom disk 266H including the concave feature 2522H that provides the bottom of the expansion chamber 252H in the disk-pack turbine 250H. FIG. 21D illustrates the bottom of the disk-pack turbine 250H including an example of a motor mount 2662H. The illustrated waveforms are circular, but as discussed previously a variety of waveforms including hyperbolic waveforms can be substituted for the illustrated circular waveforms.

(108) FIG. 22 illustrates another example of a disk-pack turbine 250I with a top rotor 264I, a disk 260I, and a bottom rotor 266I. The top rotor 264I and the disk 260I are shown in cross-section with the plane taken through the middle of the components. FIG. 22 also illustrates an embodiment where the components are attached around the periphery of the opening that defines the expansion chamber 250I through mounting holes 2502I. Each of the waveform patterns on the top rotor 264I, the disk 260I, and the bottom rotor 266I includes two sets of circular waveforms 2646I and one set of hyperbolic waveforms 2642I.

h. Conclusion

(109) While the invention has been described with reference to certain preferred embodiments, numerous changes, alterations and modifications to the described embodiments are possible without departing from the spirit and scope of the invention, as defined in the appended claims and equivalents thereof. The number, location, and configuration of disks and/or rotors described above and illustrated are examples and for illustration only. Further, the terms disks and rotors are used interchangeably throughout the detailed description without departing from the invention.

(110) The example and alternative embodiments described above may be combined in a variety of ways with each other without departing from the invention.

(111) As used above “substantially,” “generally,” and other words of degree are relative modifiers intended to indicate permissible variation from the characteristic so modified. It is not intended to be limited to the absolute value or characteristic which it modifies but rather possessing more of the physical or functional characteristic than its opposite, and preferably, approaching or approximating such a physical or functional characteristic.

(112) The foregoing description describes different components of embodiments being “connected” to other components. These connections include physical connections, fluid connections, magnetic connections, flux connections, and other types of connections capable of transmitting and sensing physical phenomena between the components.

(113) The foregoing description describes different components of embodiments being “in fluid communication” to other components. “In fluid communication” includes the ability for fluid to travel from one component/chamber to another component/chamber.

(114) Although the present invention has been described in terms of particular embodiments, it is not limited to those embodiments. Alternative embodiments, examples, and modifications which would still be encompassed by the invention may be made by those skilled in the art, particularly in light of the foregoing teachings.

(115) Those skilled in the art will appreciate that various adaptations and modifications of the embodiments described above can be configured without departing from the scope and spirit of the

invention. Therefore, it is to be understood that, within the scope of the appended claims, the invention may be practiced other than as specifically described herein.

Claims

1. A waveform disk set comprising: a first waveform disk having divergent exit ports spaced around a periphery of the first waveform disk, a second waveform disk having convergent exit ports spaced around a periphery of the second waveform disk; the first and second waveform disks each having matched waveform patterns located on a surface of the disks that include hyperbolic waveforms travelling substantially around an axial center of the disk with each hyperbolic waveform having a varying diameter along the waveform.
 2. The waveform disk set according to claim 1, wherein the first and second waveform disks includes two levels of hyperbolic waveforms and three levels of substantially circular waveforms.
 3. The waveform disk set according to claim 2, wherein the hyperbolic waveforms change height as the waveform travels around the waveform disk as measured in a radial direction.
 4. The waveform disk set according to claim 1, wherein when the first and second waveform disks are assembled, each convergent exit port aligns with one respective divergent exit port to form a convergent/divergent port pair.
 5. The waveform disk set according to claim 4, wherein the hyperbolic waveforms change height as the waveform travels around the waveform disk as measured in a radial direction.
 6. The waveform disk set according to claim 5, wherein each waveform pattern having waveforms each being intersected twice by a diameter taken along said surface with the waveform pattern.
 7. The waveform disk set according to claim 5, wherein the first waveform disk having an opening passing through its height and located at an axial center of the first waveform disk; and a fluid pathway exists for directing fluid through the axial center opening and through a passageway between the waveform disks towards the peripheries of the waveform disks.
 8. The waveform disk set according to claim 1, wherein each waveform disk including a plurality of flanges horizontally extending from the periphery of said disk, each flange having a plurality of openings passing therethrough.
 9. The waveform disk set according to claim 1, wherein each waveform pattern having waveforms each being intersected twice by a diameter taken along said surface with the waveform pattern.
 10. The waveform disk set according to claim 1, wherein the second waveform disk having an opening passing through its height and located at an axial center of the second waveform disk; and a fluid pathway exists for directing fluid through the axial center opening and through a passageway between the waveform disks towards the peripheries of the waveform disks.
-